

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12390214
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Wilson; Andrew D. et al.

---

### Automated rotation of a needle in a computer-assisted system

---

#### Abstract

Techniques for automated rotation of a needle in a computer-assisted system include an end effector having a drive mechanism configured to be coupled to a curved needle and configured to rotationally actuate the curved needle along an arcuate path and a control unit coupled to the drive mechanism. The control unit is configured to, in response to receiving a first input, cause the drive mechanism to rotationally actuate the curved needle by a first preset rotation amount along the arcuate path, and, in response to receiving a second input, cause the drive mechanism to rotationally actuate the curved needle by a second preset rotation amount along the arcuate path.

---

**Inventors:** Wilson; Andrew D. (Hamden, CT), Brisson; Gabriel F. (Livermore, CA), Reid; Robert C. (Fairfield, CA)

**Applicant:** INTUITIVE SURGICAL OPERATIONS, INC. (Sunnyvale, CA)

**Family ID:** 1000008764668

**Assignee:** INTUITIVE SURGICAL OPERATIONS, INC. (Sunnyvale, CA)

**Appl. No.:** 18/194283

**Filed:** March 31, 2023

#### Prior Publication Data

Document Identifier	Publication Date
US 20230233202 A1	Jul. 27, 2023

#### Related U.S. Application Data

continuation parent-doc US 17918865 PENDING WO PCT/US2021/027134 20210413 child-doc US 18194283  
us-provisional-application US 63009961 20200414

---

## Publication Classification

**Int. Cl.:** **A61B17/04** (20060101); **A61B17/00** (20060101); **A61B17/06** (20060101); **A61B34/00** (20160101)

**U.S. Cl.:**

**CPC** **A61B17/0482** (20130101); **A61B34/71** (20160201); A61B2017/00137 (20130101); A61B2017/00973 (20130101); A61B2017/0608 (20130101)

## Field of Classification Search

**CPC:** A61B (17/0482); A61B (34/71); A61B (2017/00137); A61B (2017/00973); A61B (2017/0608)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8123764	12/2011	Meade et al.	N/A	N/A
9724087	12/2016	Berry	N/A	N/A
10470758	12/2018	Mumaw et al.	N/A	N/A
2006/0292917	12/2005	Miyamoto et al.	N/A	N/A
2013/0282029	12/2012	Skinlo et al.	N/A	N/A
2016/0367243	12/2015	Martin	N/A	A61B 17/06133
2017/0150961	12/2016	Marczyk et al.	N/A	N/A
2019/0206565	12/2018	Shelton, IV	N/A	N/A

### FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
108498126	12/2017	CN	N/A

### OTHER PUBLICATIONS

International Search Report and Written Opinion for Application No. PCT/US2021/027134, mailed Jul. 29, 2021, 10 pages. cited by applicant

Vertut, J, and Coiffet, P., "Robot Technology: Teleoperation and Robotics Evolution and Development," English translation, Prentice-Hall, Inc., Englewood Cliffs, NJ, USA 1986, vol. 3A, 332 pages. cited by applicant

---

*Primary Examiner:* Ho; Tan-Uyen T

*Assistant Examiner:* Le; Khoa Tan

*Attorney, Agent or Firm:* Artega Law Group, LLC

---

## Background/Summary

CROSS-REFERENCES TO RELATED APPLICATIONS (1) The present application is a Continuation of U.S. patent application Ser. No. 17/918,865, filed Oct. 13, 2022, which is a U.S. National Stage patent application of International Patent Application No. PCT/US2021/027134, filed Apr. 13, 2021, the benefit of which is claimed, and claims priority to U.S. Provisional Patent Application No. 63/009,961 filed Apr. 14, 2020, each of which is hereby incorporated herein by reference in its entirety.

## TECHNICAL FIELD

(1) The present disclosure relates generally to operation of devices with actuatable instruments and more particularly to automated rotation of a needle in a computer-assisted system.

## BACKGROUND

(2) Compared to conventional open site procedures, minimally invasive procedures may be performed with suitably configured devices that may be introduced into a workspace through a small opening, such as a port, an orifice, and/or an incision site. In some medical examples, minimally-invasive procedures help reduce trauma and disability, help reduce a chance of infection, and/or improve recovery time. Because minimally invasive procedures involve the insertion and manipulation of instruments through ports, small incisions, and/or natural orifices, the work site within the workspace is not as accessible as in open site procedures. As a result, manipulating such instruments may be awkward, particularly when the operator performs complicated tasks like stitching a material or stitching a suture. In addition, human hands typically have some minimal amount of tremor, which may further increase the difficulty of certain minimally invasive tasks.

(3) To address the limitations of minimally invasive procedures, computer-assisted devices have been developed. During procedures with a computer-assisted device, the dexterity of the operator when utilizing the instruments inserted into the workspace is enhanced. Instruments with end effectors for performing various tasks include forceps, needle drivers, clip applicators, retractors, cautery instruments, suturing devices, and/or the like, which can be actuated to grasp, sever, cauterize, suture, and/or otherwise precisely manipulate material, such as tissue and/or other objects. However, even with the improved dexterity afforded by such computer-assisted devices, the stitching of material (e.g., tissue) and setting of the knots is generally a difficult and time-consuming process, due to the complicated motions involved and the lack of space that is available for movement of the end effectors in the workspace.

(4) Accordingly, improved methods and systems for stitching a material during minimally invasive procedures are desirable.

## SUMMARY

(5) Consistent with some embodiments, a computer-assisted device includes an end effector having a drive mechanism configured to be coupled to a curved needle and configured to rotationally actuate the curved needle along an arcuate path and a control unit coupled to the drive mechanism. The control unit is configured to, in response to receiving a first input, cause the drive mechanism to rotationally actuate the curved needle by a first preset rotation amount along the arcuate path, and, in response to receiving a second input, cause the drive mechanism to rotationally actuate the curved needle by a second preset rotation amount along the arcuate path.

(6) Consistent with some embodiments, a computer-assisted device includes an end effector having a drive mechanism configured to be coupled to a curved needle and configured to rotationally actuate the curved needle along an arcuate path and a control unit coupled to the drive mechanism. The control unit is configured to receive an operator input signal, based on a mapping of the operator input signal to a rotational arc amount of the curved needle, determine an arc of rotation for the curved needle along an arcuate path corresponding to the operator input signal, and cause the drive mechanism to rotationally actuate the curved needle through the arc of rotation along the arcuate path.

(7) Consistent with some embodiments, in a computer-assisted device that includes an end effector,

a method includes, in response to receiving a first input, causing a drive mechanism of the end effector to rotationally actuate a curved needle coupled to the drive mechanism by a first preset rotation amount along an arcuate path, and, in response to receiving a second input, causing the drive mechanism to rotationally actuate the curved needle by a second preset rotation amount along the arcuate path.

(8) Consistent with some embodiments, in a computer-assisted device that includes an end effector having a drive mechanism configured to be coupled to a curved needle and configured to rotationally actuate the curved needle along an arcuate path, a method includes receiving an operator input signal, based on a mapping of the operator input signal to a rotational arc amount of the curved needle, determining an arc of rotation for the curved needle along the arcuate path corresponding to the operator input signal, and causing the drive mechanism to rotationally actuate the curved needle through the arc of rotation along the arcuate path.

(9) Consistent with some embodiments, a non-transitory machine-readable medium including a plurality of machine-readable instructions which when executed by one or more processors are adapted to cause the one or more processors to perform any of the methods described herein.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a simplified diagram of a computer-assisted system according to some embodiments.

(2) FIG. 2 is a schematic diagram of an end effector according to some embodiments.

(3) FIG. 3 shows elements of a drive mechanism of an end effector according to some embodiments.

(4) FIGS. 4 and 5 show further elements of the drive mechanism of FIG. 3 according to some embodiments.

(5) FIG. 6 shows elements of a drive mechanism of an end effector according to some embodiments.

(6) FIG. 7 is a simplified diagram of a method of automated rotation of a needle in a computer-assisted system according to some embodiments.

(7) FIG. 8 is a simplified diagram of a method of automated rotation of a needle in a computer-assisted system, according to some embodiments.

(8) FIG. 9 is a schematic illustration of a graphical user interface for interaction with a computer-assisted device, according to various embodiments.

(9) FIG. 10 is a simplified diagram of a method of automated rotation of a needle in a computer-assisted system, according to some embodiments.

(10) FIG. 11 is a simplified diagram of a method of automated rotation of a needle in a computer-assisted system, according to some embodiments.

(11) FIG. 12 is a simplified diagram of a method of automated rotation of a needle in a computer-assisted system, according to some embodiments.

(12) In the figures, elements having the same designations have the same or similar functions.

### DETAILED DESCRIPTION

(13) In this description, specific details are set forth describing some embodiments consistent with the present disclosure. Numerous specific details are set forth in order to provide a thorough understanding of the embodiments. It will be apparent, however, to one skilled in the art that some embodiments may be practiced without some or all of these specific details. The specific embodiments disclosed herein are meant to be illustrative but not limiting. One skilled in the art may realize other elements that, although not specifically described here, are within the scope and the spirit of this disclosure. In addition, to avoid unnecessary repetition, one or more features shown and described in association with one embodiment may be incorporated into other

embodiments unless specifically described otherwise or if the one or more features would make an embodiment non-functional.

(14) Further, this description's terminology is not intended to limit the invention. For example, spatially relative terms—such as “beneath”, “below”, “lower”, “above”, “upper”, “proximal”, “distal”, and the like—may be used to describe one element's or feature's relationship to another element or feature as illustrated in the figures. These spatially relative terms are intended to encompass different positions (i.e., locations) and orientations (i.e., rotational placements) of the elements or their operation in addition to the position and orientation shown in the figures. For example, if the content of one of the figures is turned over, elements described as “below” or “beneath” other elements or features would then be “above” or “over” the other elements or features. Thus, the term “below,” for example, can encompass both positions and orientations of above and below. A device may be otherwise oriented (e.g., rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein interpreted accordingly. Likewise, descriptions of movement along and around various axes include various special element positions and orientations. In addition, the singular forms “a”, “an”, and “the” are intended to include the plural forms as well, unless the context indicates otherwise. And, the terms “comprises”, “comprising”, “includes”, and the like specify the presence of stated features, steps, operations, elements, and/or components but do not preclude the presence or addition of one or more other features, steps, operations, elements, components, and/or groups. Components described as coupled may be electrically or mechanically directly coupled, or they may be indirectly coupled via one or more intermediate components.

(15) Elements described in detail with reference to one embodiment, implementation, or module may, whenever practical, be included in other embodiments, implementations, or modules in which they are not specifically shown or described. For example, if an element is described in detail with reference to one embodiment and is not described with reference to a second embodiment, the element may nevertheless be claimed as included in the second embodiment. Thus, to avoid unnecessary repetition in the following description, one or more elements shown and described in association with one embodiment, implementation, or application may be incorporated into other embodiments, implementations, or aspects unless specifically described otherwise, unless the one or more elements would make an embodiment or implementation non-functional, or unless two or more of the elements provide conflicting functions.

(16) In some instances, well known methods, procedures, components, and circuits have not been described in detail so as not to unnecessarily obscure aspects of the embodiments.

(17) This disclosure describes various devices, elements, and portions of computer-assisted devices and elements in terms of their state in three-dimensional space. As used herein, the term “position” refers to the location of an element or a portion of an element in a three-dimensional space (e.g., three degrees of translational freedom along Cartesian x-, y-, and z-coordinates). As used herein, the term “orientation” refers to the rotational placement of an element or a portion of an element (three degrees of rotational freedom—e.g., roll, pitch, and yaw, angle-axis, rotation matrix, quaternion representation, and/or the like). As used herein, the term “pose” refers to the six degree of freedom (DOF) spatial position and orientation of an element or a portion of an element. As used herein, the term “shape” refers to a set of positions and/or orientations measured along an element. As used herein, and for a computer-assisted device with repositionable arms, the term “proximal” refers to a direction toward the base of the computer-assisted device along its kinematic chain and the term “distal” refers to a direction away from the base along the kinematic chain.

(18) Aspects of this disclosure are described in reference to computer-assisted systems and devices, which may include systems and devices that are teleoperated, remote-controlled, autonomous, semiautonomous, robotic, and/or the like. Further, aspects of this disclosure are described in terms of an implementation using a surgical system, such as the da Vinci® Surgical System commercialized by Intuitive Surgical, Inc. of Sunnyvale, California Knowledgeable persons will

understand, however, that inventive aspects disclosed herein may be embodied and implemented in various ways, including robotic and, if applicable, non-robotic embodiments and implementations. Implementations on da Vinci® Surgical Systems are merely examples and are not to be considered as limiting the scope of the inventive aspects disclosed herein. In some embodiments, the instruments, systems, and methods described herein may be suitable for use in, for example, surgical, teleoperated surgical, diagnostic, therapeutic, or biopsy procedures. While some embodiments are provided herein with respect to such procedures, any reference to medical or surgical instruments and medical or surgical methods is intended as non-limiting. Thus, the instruments, systems, and methods described herein may be used for humans, animals, portions of human or animal anatomy, non-surgical diagnosis, as well as for industrial systems, general robotic, or teleoperational systems. As further examples, the instruments, systems, and methods described herein may be used for non-medical purposes including industrial uses, general robotic uses, sensing or manipulating non-tissue work pieces, cosmetic improvements, imaging of human or animal anatomy, gathering data from human or animal anatomy, setting up or taking down systems, training medical or non-medical personnel, and/or the like. Additional example applications include use for procedures on tissue removed from human or animal anatomies (without return to a human or animal anatomy) and for procedures on human or animal cadavers. Further, these techniques can also be used for medical treatment or diagnosis procedures that include, or do not include, surgical aspects.

(19) FIG. 1 is a simplified diagram of a computer-assisted system **100** according to some embodiments. As shown in FIG. 1, computer-assisted system **100** includes a device **110** with one or more movable or repositionable arms **120**. Each of the one or more repositionable arms **120** may support and drive one or more end effectors **121**. In some examples, device **110** may be a computer-assisted surgical device. The one or more repositionable arms **120** each provide support for and drive surgical instruments, imaging devices, and/or the like. The end effectors **121** may be located at a distal end portion of the surgical instruments. In some embodiments, computer-assisted surgical devices with other configurations, fewer or more articulated arms, and/or the like may be used with computer-assisted system **100**.

(20) In some embodiments, the device **110** may be mounted near or adjacent an operating or surgical table, or the device **110** may be mounted directly to the table, or to a rail coupled to the table, or integrally part of the table structure. In some embodiments, the device **110** may be a movable cart (e.g., a patient-side cart). The movable cart may be separate from and spaced from the table in the operating room and may be independently movable relative to the table. In some embodiments, the movable cart may be docked or attached to the table. In some embodiments, the device **110** may be mounted to a ceiling, floor, and/or wall of the operating room. In some embodiments having a plurality of devices **110**, each device may be mounted to any structure or in any manner as described above. For example, one device **110** may be mounted to a surgical table and another device **110** may be mounted to a ceiling.

(21) Device **110** may further be coupled to an operator workstation (not shown), which may include one or more master controls **180** for selectively operating device **110**, the one or more repositionable arms **120**, and/or the end effectors. Master controls **180** are input devices that enable an operator to manipulate end effectors **121** and, in some embodiments, repositionable arms **120**. Specifically, as the operator performs a procedure by manipulating one or more master controls **180**, control unit **130** causes one or more slave manipulators to manipulate a respective repositionable arm **120** and/or end effector **121**. In some embodiments, the movements of master controls **180** the associated devices are scaled, which can facilitate performance of intricate procedures with greater ease than conventional open-site procedures. Master controls **180** may include one or more continuous motion input devices **181** and/or one or more digital input devices **182**. In some embodiments, device **110**, the operator workstation, and the control unit **130** may correspond to a da Vinci® Surgical System commercialized by Intuitive Surgical, Inc. of

Sunnyvale, California.

(22) The one or more continuous motion input devices **181** are configured to enable an operator to generate an input that varies along a continuum of values, for example, from 0% to 100% of a particular input range. As such, each of the one or more continuous motion input devices **181** can include any one or more of a variety of input devices, such as joysticks, gloves, trigger-guns, hand-operated controllers (grippers, sliders, knobs, rotary inputs, etc.) and/or the like. Alternatively or additionally, in some embodiments, one or more of the continuous motion input devices **181** may be configured to enable an operator to generate multiple inputs that each vary along a respective continuum of values. For example, in an embodiment, a particular continuous motion input device **181** includes a different continuous input generator for each degree of freedom of an end effector **121** that is currently associated with that particular continuous motion input device **181**.

(23) The one or more digital input devices **182** are configured to enable an operator to generate a digital or binary input. Thus, each of the one or more digital input devices **182** enables an operator to toggle between a first mode and a second mode, select and deselect a specific control option of device **110**, etc. For example, in an embodiment, a first actuation of a particular digital input device **182** by an operator causes an energy delivery instrument included in an end effector **121** to be energized and a second actuation of the particular digital input device **182** by the operator causes the energy delivery instrument to be de-energized. Suitable examples of digital input devices **182** include a foot pedal, a hand- or foot-operated button, a switch, a lever, and/or the like.

(24) Device **110** is coupled to a control unit **130** via an interface. The interface may include one or more cables, connectors, and/or buses, and may further include one or more networks (e.g., wired and/or wireless networks) with one or more network switching and/or routing devices. Control unit **130** includes a processor **140** coupled to memory **150**. Operation of control unit **130** is controlled by processor **140**. And although control unit **130** is shown with only one processor **140**, it is understood that processor **140** may be representative of one or more central processing units, multi-core processors, microprocessors, microcontrollers, digital signal processors, field programmable gate arrays (FPGAs), application specific integrated circuits (ASICs), tensor processing units (TPUs), and/or the like in control unit **130**. Control unit **130** may be implemented as a stand-alone subsystem and/or board added to a computing device or as a virtual machine. In some embodiments, control unit may be included as part of the operator workstation and/or operated separately from, but in coordination with the operator workstation.

(25) Memory **150** may be used to store software executed by control unit **130** and/or one or more data structures used during operation of control unit **130**. Memory **150** may include one or more types of machine readable media. Some common forms of machine readable media may include floppy disk, flexible disk, hard disk, magnetic tape, any other magnetic medium, CD-ROM, any other optical medium, punch cards, paper tape, any other physical medium with patterns of holes, RAM, PROM, EPROM, FLASH-EPROM, any other memory chip or cartridge, and/or any other medium from which a processor or computer is adapted to read.

(26) As shown, memory **150** includes a motion control application **160** that may be used to support autonomous and/or semiautonomous control of device **110**. Motion control application **160** may include one or more application programming interfaces (APIs) for receiving position, orientation, motion, and/or other sensor information from device **110**, exchanging position, orientation, motion, and/or collision avoidance information with other control units regarding other devices, such as a surgical table and/or imaging device, and/or planning and/or assisting in the planning of motion for device **110**, repositionable arms **120**, and/or end effectors **121** of device **110**. And although motion control application **160** is depicted as a software application, motion control application **160** may be implemented using hardware, firmware, software, and/or a combination thereof, any of which interact with or are otherwise executed by processor **140**.

(27) In some embodiments, memory **150** further includes a mapping **170** that maps values of a proportional input signal from a continuous motion input device **181** to a particular rotational arc

amount (e.g., of a rotational drive mechanism in an end effector). Mapping **170** can include any technically feasible mapping of proportional input signals to rotational arc amounts.

(28) For example, in an embodiment in which a continuous motion input device **181** includes a gripping controller, mapping **170** maps values of the proportional input signal from the gripping controller to corresponding values of rotational arc of a drive mechanism included in an end effector **121**. In one such embodiment, a proportional input signal value corresponding to 0% gripping motion is mapped to 0 degrees of rotational arc, a proportional input signal value corresponding to 100% gripping motion is mapped to 180 degrees of rotational arc, and proportional input signal values corresponding to gripping motion between 0% and 100% gripping motion are distributively mapped to respective rotational arcs between 0 degrees and 180 degrees of rotational arc. In another embodiment, a proportional input signal value corresponding to 0% gripping motion is mapped to 0 degrees of rotational arc, a proportional input signal value corresponding to 100% gripping motion is mapped to 360 degrees of rotational arc, and proportional input signal values corresponding to gripping motion between 0% and 100% gripping motion are distributively mapped to respective rotational arcs between 0 degrees and 360 degrees of rotational arc. In some embodiments, the gripping motion of the gripping controller may be continuously movably between a fully open state (e.g., corresponding to 0% gripping motion) and a fully closed state (e.g., corresponding to 100% gripping motion), or vice versa. In some embodiments gripping motion may be distributively mapped from 0 degrees of rotational arc to less than 180 degrees of rotation arc at 100% gripping motion. In some embodiments the mapping of the fully opened and fully closed states may be reversed, for example, with the fully open state corresponding to 100% gripping motion and the fully closed state corresponding to 0% gripping motion. In some embodiments, the gripping motion may be constrained to be movable to an extent less than fully open and fully closed states.

(29) Alternatively, in an embodiment in which a continuous motion input device **181** includes a rotary input device, such as a rotating knob, mapping **170** maps values of the proportional input signal from the rotary input device to corresponding values of rotational arc of a drive mechanism included in an end effector **121**. In one such embodiment, a proportional input signal value has a 1:1 mapping between rotation of the rotary input device and rotational arc of the drive mechanism. Thus, in such an embodiment, 0% rotation of the rotary input device is mapped to a signal resulting in 0 degrees of rotational arc of the drive mechanism, while 100% (e.g., 360 degrees) rotation of the rotary input device is mapped to a signal resulting in a complete 360-degree rotation of the drive mechanism. In some embodiments, the rotary input device is configured to be continuously movable in one rotational direction only (e.g., clockwise), and in some embodiments the rotary input device is configured to be continuously movable in both the clockwise and the counterclockwise directions. In some embodiments, the rotary input device is configured with a hard stop limiting motion in one direction, such as the direction of rotation of the reciprocating drive mechanism. In some embodiments, the rotary input device is configured to provide feedback to the operator (e.g., haptic feedback), for example to indicate when a curved needle being driven by the drive mechanism is being commanded to certain positions, such as when the curved needle extends out of a housing of the end effector **121**, or when the needle is fully retracted in such a housing, based on the rotational position of the drive mechanism.

(30) In yet another embodiment, mapping **170** includes a first mapping of proportional input signal values of a first proportional input signal from a continuous motion input device **181** and a second mapping of proportional input signal values of a second proportional input signal from the same continuous motion input device **181**, with the first mapping and the second mapping being mapped to corresponding values of rotational arc of a drive mechanism included in an end effector **121**. In such an embodiment, the first proportional input signal from the continuous motion input device **181** may be generated by motion or actuation of the continuous input device **181** in a first direction and the second proportional input signal from the continuous motion input device **181** may be



generated by motion or actuation of the continuous input device **181** in a second direction different from the first direction. Positions of the gripping controller while being closed (e.g., while gripping motion of the gripping controller is moved from an open state to a closed state) may correspond to proportional input signals distributed through a first preset rotational amount. In addition, positions of the gripping controller while being opened (e.g., while gripping motion of the gripping controller is moved from a closed state to an open state) may correspond to proportional input signals distributed through a second preset rotational amount. For example, in some embodiments in which the continuous input device **181** is a gripping controller, the first mapping may map proportional input signal values generated by the gripping controller while being closed. The first mapping may be mapped to respective rotational arcs between 0 degrees and 180 degrees of rotational arc of a drive mechanism included in an end effector **121**. Similarly, the second mapping may map proportional input signal values generated by the gripping controller while being opened. In some embodiments, the drive mechanism may be configured to continuously reciprocate around 360 degrees of rotational arc. In such embodiments, the second mapping may be mapped to respective rotational arcs between 180 degrees and 360 degrees of rotational arc of the drive mechanism. Alternatively, the drive mechanism may be configured to reciprocate around less than 360 degrees of rotational arc. For example, the drive mechanism may be configured with 180 degrees of rotational arc, wherein the first mapping may be mapped to rotational arcs between 0 and 180 degrees of the drive mechanism and the second mapping may be mapped to respective rotational arcs between 180 degrees and 0 degrees of the drive mechanism (i.e., opposite to the mapping of the first mapping). In some embodiments, the drive mechanism may be configured with 180 degrees of rotational actuation. In such embodiments, the second mapping may be mapped to a reverse stroke of the drive mechanism, in which the drive mechanism returns from 180 degrees of rotation back to 0 degrees of rotation.

(31) In some embodiments, memory **150** further includes a graphical user interface (GUI) **190** that facilitates operation of device **110**, including repositionable arms **120** and/or end effectors **121**. In some embodiments, GUI **190** presents one or more visual elements to an operator for interacting with device **110**, such as icons, menus, graphical panels, graphical buttons, and/or the like. One embodiment of GUI **190** is described further below in conjunction with FIG. 8.

(32) In some embodiments, computer-assisted system **100** may be found in an operating room and/or an interventional suite. And although FIG. 1 depicts computer-assisted system **100** with one device **110** having two repositionable arms **120**, one of ordinary skill would understand that computer-assisted system **100** may include any number of devices with repositionable arms and/or end effectors **121** of similar and/or different design from device **110**. In some examples, each of the devices may include fewer or more repositionable arms and/or end effectors **121**.

(33) According to various embodiments, one or more of end effectors **121** are configured to rotatably actuate a needle (such as a suturing needle) of a stitching or suturing device. An operator may control the rotational actuation of the needle by using a continuous motion of a continuous motion input device (such as continuous motion input device **181**), by using a digital input (such as digital motion input device **182**, for example, by depressing a button, a foot pedal, a lever, and/or the like), and/or any combination thereof. In one example, the continuous motion of the continuous motion input device is mapped to rotational motion of the needle relative to an axis of a needle track on the device (e.g., a curved needle track), so that a continuous change in the motion of the input device (e.g., a continuous change in a position of the input device) results in a corresponding rotational motion of the needle. In another example, actuation of the digital input results in autonomous rotational actuation of the needle. For example, depression of a foot pedal or a push of a button may cause the needle to autonomously rotate through a 180° or 360° arc. Thus, execution of a complete stitch can be commanded by an operator by appropriately positioning the needle near a target material to be stitched (such as tissue in a medical example) and then actuating the digital input (e.g., by depressing the foot pedal, pushing a button, etc.). This process allows for multiple

complete stitches to be created quickly and accurately. Consequently, the large sequence of individual needle manipulations normally employed in creating a stitch may be simplified. Various embodiments of end effectors **121** are described below in conjunction with FIGS. **2-6**.

(34) In some embodiments, a curved needle may be coupled to a drive mechanism included in the end effector **121**. The drive mechanism is configured to rotate the curved needle around a rotational arc, such as around a curved needle track. The drive mechanism may be controlled by an operator via manipulation of the continuous motion input device, the digital input, and/or any combination thereof.

(35) FIG. **2** is a schematic diagram of an end effector **200** of an instrument configured according to some embodiments. End effector **200** is a portion of a stitching device configured for performing minimally invasive stitching and can be employed as an end effector **121** of FIG. **1**. End effector **200** is disposed near a distal end of an instrument shaft and includes a stitching aperture **201**, a curved needle **202** (which is hidden in FIG. **2** and shown in dashed lines), and a drive mechanism (not shown). As described in further detail below, the curved needle **202** may move along an arcuate needle path. In some embodiments, the curved needle **202** moves along an arcuate needle track within end effector **200** about an axis **203**. The arcuate needle track defines an arcuate needle path along which curved needle **202** moves. The drive mechanism is configured to be coupled to curved needle **202** and to rotationally actuate curved needle **202** around the arcuate needle track along an arcuate path. In some embodiments, curved needle **202** is formed as a portion of a circle, however, the curved needle **202** may have other shapes. In some embodiments, axis **203** includes or passes through a center point of a circle defined by the arcuate needle track and, in some embodiments, axis **203** may be located within stitching aperture **201**. Axis **203** is oriented to be substantially perpendicular to a longitudinal axis **211** of end effector **200**, and therefore is shown as a point in FIG. **2**.

(36) In operation, stitching material or thread (not shown) is connected to curved needle **202**, for example via an attachment opening or other feature, and the drive mechanism of end effector **200** drives curved needle **202** in a curved path about axis **203**. In some embodiments, the drive mechanism drives curved needle **202** around the arcuate needle track via two drive notches **205** and **206** that are each formed on an outer face of curved needle **202**, for example at about 180 degrees apart. Drive notch **205** may be located near a trailing end of curved needle **202** and drive notch **206** may be located near a leading end of curved needle **202**. The leading end of the curved needle **202** may have a sharpened tip. Embodiments of drive mechanisms are described in greater detail below in conjunction with FIGS. **3-6**.

(37) FIG. **3** shows elements of a drive mechanism **300** of end effector **200**, configured according to some embodiments. A housing of drive mechanism **300** is omitted in FIG. **3** for clarity. In the embodiment illustrated in FIG. **3**, drive mechanism **300** includes a follower pulley **302**, a drive pulley **304**, and a drive pulley **303**, which is hidden by drive pulley **304** in FIG. **3**. As shown, follower pulley **302** and drive pulley **304** are rotationally coupled to each other via connectors **305**, which partially wrap around follower pulley **302** and drive pulley **304**. The connectors **305** may be belts, cables, and the like. Drive pulley **303** is coupled to and rotates about the same axis **307** as drive pulley **304**. In alternate embodiments, follower pulley **302** may be coupled to drive pulley **304** via connectors **305**. In operation, follower pulley **302**, drive pulley **304**, and drive pulley **303** are configured to rotate in sync together, for example over a rotational arc of about 190 degrees. The synchronized rotation of follower pulley **302** and drive pulleys **303** and **304** causes an actuator arm **311** to rotationally drive curved needle **202**. As described in further detail below, actuator arm **311** includes a pawl **312** that is configured to releasably engage drive notches **205** and **206** on curved needle **202** to drive curved needle **202** through a 360 arc of rotation. Pawl **312** engages drive notch **205** to drive the needle **202** through an approximate 180 degree arc, releases from drive notch **205**, and then engages drive notch **206** to drive needle **202** through another approximate 180 degree arc.

(38) FIGS. 4 and 5 show further elements of drive mechanism **300** of end effector **200**, configured according to some embodiments. Drive mechanism **300** further includes cables **484** and **486**, which may be made from stainless steel or any other suitable material. Cable **484** (shown in FIG. 5) is connected to drive pulley **304**, and cable **486** (shown in FIG. 4) is connected to drive pulley **303**. Connected at a proximal end **405** of drive mechanism **300** is a portion **408** that contains part of drive mechanism **300** that includes two idler pulleys **480** and cables **484** and **486**. FIG. 4 shows drive mechanism **300** with drive pulley **303** in place (and drive pulley **304** hidden from view) and cable **486** running through idler pulleys **480** and wrapped around drive pulley **303**. FIG. 5 shows drive mechanism **300** with drive pulley **303** removed and cable **484** running through idler pulleys **480** and wrapped around drive pulley **304**. Cable **484** runs from drive pulley **303** through an instrument shaft connected to the proximal end of the end effector **200** to a suitable drive mechanism disposed in a proximal portion of instrument shaft.

(39) The curved needle **202** is configured to be moved between a home position in which the needle **202** is retracted within a housing of the drive mechanism **300** and an engaged position in which the needle **202** extends from the housing and across aperture **201** to engage in tissue. In some embodiments, the engaged position may correspond to the curved needle rotating approximately 180 degrees relative to the home position. To drive curved needle **202**, actuator arm **311** is configured to be moved along an arcuate path within the housing. In various examples, actuator arm **311** may be configured to move along an approximate 180 degree arc, an approximate 190 degree arc, etc. In some embodiments, actuator arm may move along an arcuate path between a needle-driving position corresponding to an approximate 6 o'clock rotational position (as shown in FIGS. 4-5) and a needle-ending position corresponding to an approximate 12 o'clock rotational position. The rotational positions are provided by way of example and various other rotational positions are possible for the needle-driving position and the needle-ending position.

(40) In an example embodiment, the force to rotationally actuate curved needle **202** from the home position to the engaged position is provided by a cable-tensioning device (not shown) that is connected to cable **484**. Thus, to rotationally actuate curved needle **202** from the home position (as shown in FIGS. 4 and 5) to the engaged position in which the needle **202** extends from the housing, an operator performs a suitable input action with an input device as described herein, and the cable-tensioning device that is connected to cable **484** causes drive pulley **304** to turn counterclockwise (relative to the orientations shown in FIGS. 4 and 5). The counterclockwise rotation of drive pulley **304** drives actuator arm **311** from the needle-driving position to the needle-ending position. The curved needle **202** is correspondingly moved through approximately 180 degrees of rotational arc via engagement of actuator arm **311** with drive notch **205** such that the curved needle **202** moves across aperture **201**. Following the counterclockwise rotation of the actuator arm **311** from the needle-driving position to the needle-ending position to drive the curved needle **202**, the actuator arm **311** is disengaged from the curved needle **202**. The actuator arm **311** may then be returned to the needle-driving position without driving the curved needle **202**. To rotationally actuate curved needle **202** from the engaged position to the home position, an operator performs a suitable input action with an input device as described herein, and the cable-tensioning device that is connected to cable **484** causes drive pulley **304** to again turn counterclockwise. In this instance, the counterclockwise rotation of drive pulley **304** drives actuator arm **311** from the needle-driving position to the needle-ending position to move curved needle **202** through approximately 180 degrees of rotational arc via engagement of actuator arm **311** with drive notch **206**. The orientation of the curved needle **202** relative to the housing and the counterclockwise motion of the actuator arm **311** from the needle-driving position to the needle-ending position are by way of example only. In alternate embodiments, the orientation of the needle may be reversed, such that the needle and actuator arm **311** may move in a clockwise motion from the needle-driving position to the needle-ending position.

(41) In an example embodiment, the force to move actuator arm **311** from the needle-ending

position to the needle-driving position is provided by a cable-tensioning device (not shown) that is connected to cable **486**. Thus, to rotationally return actuator arm **311** from the needle-ending position to the needle-driving position, an operator performs a suitable input action with an input device as described herein. In response, the cable-tensioning device that is connected to cable **486** causes drive pulley **303** to turn clockwise, through approximately 180 degrees. In this way, actuator arm **311** is returned to the needle-driving position, as shown in FIGS. **4** and **5**.

(42) In operation, a stitching cycle is completed in four steps. First, with the actuator arm **311** in the needle-driving position and pawl **312** engaged with drive notch **205** of curved needle **202**, tension in cable **484** causes follower pulley **302**, drive pulley **304**, and drive pulley **303** to rotate counterclockwise for approximately 180 degrees to drive actuator arm **311** to the needle-ending position and drive curved needle **202** from the home position into the engaged position. Second, tension in cable **486** causes follower pulley **302** and drive pulley **304** and drive pulley **303** to rotate clockwise for approximately 180 degrees, which disengages pawl **312** from drive notch **205** of curved needle **202** and repositions actuator arm **311** to the needle-driving position so that pawl **312** engages drive notch **206** of the curved needle **202**. Third, tension in cable **484** causes follower pulley **302**, drive pulley **304**, and drive pulley **303** to rotate counterclockwise for approximately 180 degrees to again move actuator arm **311** to the needle-ending position and drive curved needle **202** via drive notch **206** from the engaged position back into the home position. Fourth, tension in cable **486** causes follower pulley **302**, drive pulley **304**, and drive pulley **303** to rotate clockwise for approximately 180 degrees, which disengages pawl **312** from drive notch **206** and repositions actuator arm **311** to the needle-driving position so that pawl **312** again engages drive notch **205**.

(43) In the embodiments described above, cables are employed to cause drive mechanism **300** to rotationally actuate curved needle **202**. In other embodiments, any other technically feasible actuation apparatus can be employed to cause drive mechanism **300** to rotationally actuate curved needle **202**. For example, in one such embodiment, one or both of follower pulley **302** and drive pulley **304** and/or additional drive pulley **303** is motorized. Additionally or alternatively, in one such embodiment, belt drives and/or gears are employed in drive mechanism **300** to rotationally actuate curved needle **202** in addition to or in lieu of cables **484** and **486**. A more detailed description of the configuration and operation of an end effector that includes a curved needle and drive mechanism for minimally invasive stitching can be found in U.S. Pat. No. 8,123,764, which is incorporated in its entirety herein.

(44) FIG. **6** shows elements of a drive mechanism **600** of end effector **200**, configured according to some embodiments. A housing of drive mechanism **600** is omitted in FIG. **6** for clarity. In the embodiment illustrated in FIG. **6**, drive mechanism **600** includes a follower pulley **602**, a drive pulley **604**, and link arm **605** that connects follower pulley **602** and drive pulley **604**. In FIG. **6**, drive pulley **602** is configured as a pulley element with connector arms in lieu of a disk-shaped body. In other embodiments, drive pulley **602** may be configured with a disk-shaped body. Drive pulley **604** may be connected to a single cable **684**, for example via a crimp connector **609**.

Alternatively, drive pulley **604** may be connected to two cables (e.g., tensed in opposite directions). Alternatively, cable **684** can be implemented as one or more belts. Similar to drive mechanism **300** of FIG. **3**, follower pulley **602** and drive pulley **604** are rotationally coupled and therefore rotate in sync together, causing an actuator arm **611** to alternately engage drive notch **205** or **206** on curved needle **202** with pawl **312**. Specifically, counterclockwise rotation of follower pulley **602** and drive pulley **604** for 180 degrees drives curved needle **202** through an arc of 180 degrees of rotation drive notch **205** or **206**. Conversely, clockwise rotation of follower pulley **602** and drive pulley **604** for 180 degrees disengages pawl **312** from drive notch **205** or **206** and returns actuator arm **611** to the needle-driving position, which is shown in FIG. **6**.

(45) In operation of drive mechanism **600**, a stitching cycle is completed via drive mechanism **600** in four steps by reciprocally actuating actuator arm **611** around the needle track while keeping actuator arm **611** clear of stitching aperture **201**. First, with actuator arm **611** in the needle-driving

position and pawl **312** engaged with drive notch **205** of curved needle **202**, tension **621** in cable **684** causes follower pulley **602** and drive pulley **604** to rotate counterclockwise for approximately 180 degrees. Actuator arm **611** is thereby moved to the needle-ending position and curved needle **202** is driven from the home position into the engaged position. Second, tension **622** in cable **684** causes follower pulley **602** and drive pulley **604** to rotate clockwise for approximately 180 degrees, which disengages pawl **312** from drive notch **205** of curved needle **202** and repositions actuator arm **611** from the needle-ending position to the needle-driving position, so that pawl **312** engages drive notch **206** of curved needle **202**. Third, tension **621** in cable **684** causes follower pulley **602** and drive pulley **604** to rotate counterclockwise for approximately 180 degrees, thereby causing actuator arm **611** to move to the needle-ending position and causing curved needle **202** via drive notch **206** to move from the engaged position back into the home position. Fourth, tension **622** in cable **684** causes follower pulley **602** and drive pulley **604** to rotate clockwise for approximately 180 degrees, which disengages pawl **312** from drive notch **206** and repositions actuator arm **611** back to the needle-driving position, so that pawl **312** again engages drive notch **205**.

(46) Optionally, in some embodiments, drive mechanisms **300**, **600** may include one or more gears coupling the drive pulleys **303**, **304**, **604** with the respective follower pulleys **302**, **602**. Referring by way of example to drive mechanism **600**, drive pulley **604** and follower pulley **602** may be coupled to each other by one or more gears instead of link arm **605**. For example, drive pulley **604** may be coupled to a first gear having an axis of rotation that coincides with an axis of rotation of drive pulley **604**, and follower pulley **602** may be coupled to a second gear having an axis of rotation that coincides with an axis of rotation of the follower pulley **602**. The first gear and the second gear may be intermeshed or may be coupled via one or more intermediate gears. In operation, the drive pulley **604** may be driven by cable **684**, with rotation of drive pulley **604** causing rotation of the first gear, which thereby causes rotation of the second gear and follower pulley **602** (which may be through one or more intermediate gears).

(47) FIG. 7 is a simplified diagram of a method **700** of automated rotation of a needle in a computer-assisted system, according to some embodiments. One or more of the processes **710-770** of method **700** may be implemented, at least in part, in the form of executable code stored on non-transient, tangible, machine readable media that when run by one or more processors (e.g., the processor **140** in control unit **130**) may cause the one or more processors to perform one or more of the processes **710-770**. In some embodiments, the method **700** may be performed by control unit **130** and an application, such as motion control application **160**.

(48) At a process **710**, an input signal (e.g., an input) is received from an input device, such as a continuous motion input device **181** or a digital input device **182**.

(49) At a process **720**, the determination is made whether the input received at process **710** is a proportional input signal or a digital input signal. In an instance in which the input signal received is generated by a continuous motion input device **181**, such as a gripping controller or a rotary controller, the input signal is determined to be a proportional input signal and method **700** proceeds to process **730**. In an instance in which the input signal received is generated by a digital input device **182**, such as a foot pedal or button, the input signal is determined to be a digital input signal and method **700** proceeds to process **750**. In an instance in which both a digital input signal and a continuous input signal are received concurrently, an input priority may indicate which of the two signals to respond to. For example, in some embodiments, a digital input signal is given priority over a concurrent continuous input signal, so that the digital input signal is acted upon and the continuous input signal is not acted upon.

(50) At a process **730**, an arc of rotation of curved needle **202** is determined based on mapping **170** and the proportional input signal. For example, in an embodiment in which the continuous motion input device **181** is a gripping controller, the input signal received is proportional in value to how much an operator has closed the gripping controller. Thus, in such an embodiment, when an operator closes the gripping controller 25%, the proportional input signal has a value representing

25% of a maximum available value. In some embodiments, the maximum available value is 180 degrees of rotational actuation of curved needle **202**. In such an embodiment, when the proportional input signal has a value corresponding to 25% of the gripping motion being performed by the operator, the arc of rotation determined in process **730** is 45 degrees and when the proportional input signal has a value corresponding to 100% of the gripping motion being performed by the operator, the arc of rotation determined in process **730** is 180 degrees. In other embodiments, the maximum available value is 360 degrees of rotational actuation of curved needle **202**. Consequently, in such an embodiment, when the proportional input signal has a value corresponding to 25% of the gripping motion being performed by the operator, the arc of rotation determined in process **730** is 90 degrees and when the proportional input signal has a value corresponding to 100% of the gripping motion being performed by the operator, the arc of rotation determined in process **730** is 360 degrees.

(51) At process **740**, drive mechanism **300** is caused to rotationally actuate curved needle **202** through the arc of rotation determined in process **730**. Method **700** then proceeds back to process **710**.

(52) At process **750**, the determination is made whether the current position of actuator arm **311** is at the needle-driving position. If yes, method **700** proceeds to process **760**; if no, method **700** proceeds to process **770**.

(53) At process **760**, drive mechanism **300** is caused to rotationally actuate curved needle **202** through a preset arc of rotation, for example 180 degrees or 360 degrees. In some embodiments, the preset arc of rotation is selected based on which digital input device **182** generates the input signal received in process **710**. For example, in an embodiment, operator depression of a first pedal generates a digital input signal associated with causing a rotational actuation of curved needle **202** of 180 degrees, while operator depression of a second pedal generates a digital input signal associated with causing a rotational actuation of curved needle **202** of 360 degrees. Upon completion of process **760**, method **700** returns back to the start of method **700**.

(54) In one example, to cause rotational actuation of 180 degrees, follower pulley **302**, drive pulley **304**, and drive pulley **303** of drive mechanism **300** are rotated counterclockwise for approximately 180 degrees, for example via tension in cable **484**. The resultant motion of actuator arm **311** (i.e., from the needle-driving position to the needle-ending position) drives curved needle **202** from the home position into the engaged position. Follower pulley **302** and drive pulleys **303** and **304** of drive mechanism **300** are then rotated clockwise for approximately 180 degrees, for example via tension in cable **486**. The resultant motion of actuator arm **311** (i.e., from the needle-ending position to the needle-driving position) disengages pawl **312** from drive notch **205** of the curved needle **202**, repositions actuator arm **311** to the needle-driving position without repositioning the curved needle **202**, and engages pawl **312** with drive notch **206** of the curved needle **202**.

(55) In another example, to cause rotational actuation of 360 degrees, follower pulley **302**, drive pulley **304**, and drive pulley **303** are rotated counterclockwise for approximately 180 degrees and then clockwise for approximately 180 as described above. Then the process is repeated, so that curved needle **202** is driven via drive notch **206** from the engaged position back into the home position, and actuator arm **311** is repositioned back to the needle-driving position.

(56) At process **770**, drive mechanism **300** is caused to complete a remainder portion of rotational actuation of curved needle **202** through a preset rotation amount about axis **203**, such as for instances where actuator arm **311** is not in the needle-driving position. For example, in one instance, the preset rotation amount about axis **203** is 180 degrees. Further, in response to a proportional input signal being received, certain rotational actuation of drive mechanism **300** occurs (e.g., 45 degrees), and curved needle **202** is driven through a portion of the preset rotation amount about axis **203**. In such an instance, when a digital input signal is subsequently received at process **710**, process **770** then occurs, in which drive mechanism **300** is caused to complete the remainder portion of rotational actuation of curved needle **202** associated with that digital input

signal (i.e., 135 degrees in this example).

(57) Thus, at process **770**, when actuator arm **311** is not disposed in the needle-driving position (e.g., due a previously received proportional input signal) and a digital input signal is received that is associated with rotation of curved needle **202** through a preset rotation amount, drive mechanism **300** rotationally actuates curved needle **202** through the remainder portion of the preset rotation amount in response to the digital input signal. In this way, upon completion of process **770**, curved needle **202** is driven to either the home position or the engaged position and does not remain in an intermediate position therebetween. Upon completion of process **770**, method **700** returns back to the start of method **700**.

(58) FIG. **8** is a simplified diagram of a method **800** of automated rotation of a needle in a computer-assisted surgical system, according to some embodiments. One or more of the processes **810-840** of method **800** may be implemented, at least in part, in the form of executable code stored on non-transient, tangible, machine readable media that when run by one or more processors (e.g., the processor **140** in control unit **130**) may cause the one or more processors to perform one or more of the processes **810-840**. In some embodiments, the method **800** may be performed by an application, such as motion control application **160**.

(59) At a process **810**, an input signal is received from an input device, such as a digital input device **182**.

(60) At a process **820**, the determination is made whether the input received at process **810** is a digital input signal from a first digital input device **182** or a second digital input device **182**. In some embodiments, first digital input device **182** is a first foot-operated pedal or floor button and second digital input device **182** is a second foot-operated pedal or floor button. When the input received is from the first digital input device **182**, method **800** proceeds to process **830**; when the input received is from the second digital input device **182**, method **800** proceeds to process **840**.

(61) At a process **830**, drive mechanism **300** is caused to rotationally actuate curved needle **202** through a first preset arc of rotation, for example 180 degrees. In some embodiments, process **840** is substantially similar to the process of causing rotational actuation of 180 degrees of curved needle **202** described in process **760** of FIG. **7**. At process **830**, the preset arc of rotation is selected based on which digital input device **182** generates the input signal received in process **810**. Upon completion of process **830**, method **800** returns back to the start of method **800**.

(62) At a process **840**, drive mechanism **300** is caused to rotationally actuate curved needle **202** through a second preset arc of rotation, for example 360 degrees. In some embodiments, process **840** is substantially similar to the process of causing rotational actuation of 360 degrees of curved needle **202** described in process **760** of FIG. **7**. At process **840**, the preset arc of rotation is selected based on which digital input device **182** generates the input signal received in process **810**. Upon completion of process **840**, method **800** returns back to the start of method **800**.

(63) In some embodiments, GUI **190** includes one or more visual elements that facilitate operator interaction with a computer-assisted device. One such embodiment is described below in conjunction with FIG. **9**. FIG. **9** is a schematic illustration of a GUI **900** for interaction with a computer-assisted device, according to various embodiments. In some embodiments, the computer assisted device may correspond to computer-assisted device **110** of FIG. **1**. In some embodiments, some or all features of GUI **900** are implemented as a separate screen or window from other screens employed by an operator during use of the computer-assisted device. Alternatively or additionally, in some embodiments some or all features of GUI **900** are implemented as visual elements that are incorporated into or superimposed on information normally displayed to an operator. In FIG. **9**, GUI **900** is depicted as a separate window.

(64) As shown, GUI **900** includes one or more icons **920** that indicate what needle actuation controls are available to the operator. For example, in some embodiments, a half-rotation icon **921** indicates whether a digital input device **182** is available for causing a 180-degree rotation of curved needle **202** to occur; a full-rotation icon **922** indicates whether a digital input device **182** is

available for causing a 360-degree rotation of curved needle **202** to occur; and/or a proportional motion icon **923** indicates whether a proportional input signal from a continuous motion input device **181** can be employed by the operator.

(65) In some embodiments, GUI **900** includes one or more icons **930** that indicate current status information associated with stitching operations being performed by the operator, such as a rotational indicator icon **931**, a needle engagement icon **932**, and/or a needle location image **933**. In some embodiments, rotational indicator icon **931** or other indicator displays information indicating the current rotational progress or arc of rotation completed. In such embodiments, the information displayed may be based on the current rotational displacement of a drive mechanism, such as one of follower pulley **302** or drive pulley **304** of FIG. **3**. In some embodiments, needle engagement icon **932** or other indicator displays information indicating curved needle **202** is currently at least partially engaged with a material, such as tissue in a medical example. In such embodiments, the information displayed may be based on electrical and/or mechanical feedback that occurs when curved needle **202** has engaged with the material. In some embodiments, a needle location image **933** or other indicator is superimposed in images of the current worksite, for example to indicate a current location of curved needle **202** when engaged in material and is not visible to the operator. In such embodiments, the needle location information displayed may be based on the current rotational displacement of a drive mechanism, such as one of follower pulley **302** or drive pulley **304** of FIG. **3**.

(66) In some embodiments, a drive mechanism of an end effector in a device, such as device **110** of FIG. **1**, is configured to provide retraction (e.g., backward) rotary motion of a curved needle in addition to forward rotary motion of the curved needle. Thus, in such embodiments, mechanical coupling between the rotary actuation elements of the drive mechanism and the curved needle can both push and pull the curved needle, for example via a pawl or other feature coupled to the curved needle. Further, in such embodiments, a continuous motion input device (e.g., continuous motion input device **181** of FIG. **1**) is configured to be continuously movable in two opposing directions and to generate a corresponding proportional input signal. By way of a non-limiting example, the curved needle may have a home position in which the curved needle is completely within the housing of the drive mechanism and an engaged position in which the curved needle extends from the housing and across aperture **201** (as shown in FIG. **2**) to engage in tissue. In some embodiments, the engaged position may correspond to the curved needle rotating approximately 180 degrees relative to the home position. The embodiments described herein enable an operator to “peek” the curved needle out of the home position and into a tissue gap area of the end effector (such as stitching aperture **201** shown in FIG. **2**) via actuation of the continuous motion input device in one direction. A peek of the needle may correspond to a needle leading edge position that is between the home position and the engaged position. As a result, operator visualization of the curved needle before instituting a loop with a digital input is enabled. In such embodiments, the operator can then retract the curved needle back to the home position via actuation of the continuous motion input device in an opposite direction prior to causing autonomous rotation of the curved needle via a digital input.

(67) In embodiments in which continuous motion device **181** is implemented as a rotary input device, continuous motion device **181** is configured to be continuously movable in both the clockwise and the counterclockwise directions. In such embodiments, a proportional input signal from the continuous motion device **181** being actuated in the clockwise direction indicates one of forward rotary motion or retraction rotary motion of the curved needle, and a proportional input signal from the continuous motion device **181** being actuated in the counterclockwise direction indicates the opposing rotary motion of the curved needle. In some embodiments, retraction rotary motion of the curved needle beyond a home position can be indicated by rotation of the rotary input device beyond a corresponding “0” position. In such embodiments, the proportional input signal from the continuous motion device **181** may indicate a negative value (e.g., -25%) that causes the curved



needle to retract further backwards beyond the home position. In such embodiments, mapping **170** of the proportional input signal from the rotary input device to rotational arc amounts of the curved needle may include such negative values.

(68) In embodiments in which continuous motion device **181** is implemented as a gripping controller, continuous motion device **181** is configured to be continuously movable from a 0% open gripping position to a 100% closed gripping position. In such embodiments, a proportional input signal from the continuous motion device **181** being actuated in the gripping direction indicates forward rotary motion of the curved needle, and a proportional input signal from the continuous motion device **181** being actuated in the opening direction indicates retraction rotary motion of the curved needle. Thus, in such embodiments, the gripping controller may be mapped between fully open (0% of travel) and fully closed (100% of travel). An operator can partially close or actuate the gripping controller (e.g., 25% closed) from a home position to cause the curved needle to rotate to a corresponding partially rotated position (e.g., rotated 25% of a 180-degree rotation or a 360-degree rotation), for example, to “peek” the needle outward a desired amount from the housing but less than the engaged position. The operator may then return the curved needle back to the home position by opening the gripping controller back to 0% closed. In such embodiments, mapping **170** of the proportional input signal from the gripping controller to rotational arc amounts of the curved needle can be implemented independently from the direction of rotary motion of the curved needle.

(69) In embodiments in which a drive mechanism of an end effector is configured to provide forward and retraction rotary motion of a curved needle, automated rotation of a needle can be conducted after an operator has caused the curved needle to peek into a tissue gap area of the end effector, for example to perform a 180-degree rotation or a 360-degree rotation of the curved needle.

(70) In some embodiments where a peek is performed, before the automated rotation of the curved needle is performed, the curved needle may either be returned by the operator to the home position or continued to the engaged position via the continuous motion device **181**. Optionally, in some embodiments, automated rotation may be disabled while the needle is peeked into the tissue gap area. For example, an operator may actuate a continuous motion device **181** to a needle peek position (e.g., by actuating a gripping controller to 10% of the gripping controller travel). While in the needle peek position, optionally, automated rotation of the curved needle may be disabled. However, upon return of the needle to the home position of the continuous motion device **181** (e.g., 0% of gripping controller travel, or fully open), automated rotation may be re-enabled. The user may alternatively re-enable automated rotation by instead using the continuous motion device **181** to move the needle to the engaged position (100% of gripping controller travel, or fully closed). In such embodiments, the automated rotation of the curved needle is not conducted unless the gripping controller (or other continuous motion device **181**) is returned to a position at or near the non-actuation position, or moved to a position at or near the engaged position. One such embodiment is described below in conjunction with FIG. **10**.

(71) FIG. **10** is a simplified diagram of a method of automated rotation of a needle in a computer-assisted system, according to some embodiments. One or more of the processes **1010-1070** of method **1000** may be implemented, at least in part, in the form of executable code stored on non-transient, tangible, machine readable media that when run by one or more processors (e.g., the processor **140** in control unit **130**) may cause the one or more processors to perform one or more of the processes **1010-1070**. In some embodiments, the method **1000** may be performed by control unit **130** and an application, such as motion control application **160**.

(72) At a process **1010**, an input signal (e.g., an input) is received from an input device, such as a continuous motion input device **181**, a digital input device **182**, or a combination of both. It is noted that when a combination of both a digital input signal and a proportional input signal is received at process **1010**, generally, the digital input signal is received as an additional input signal while the proportional input signal is already being received. For example, when an operator

actuates a continuous motion input device **181** to a certain position (e.g., closing a gripping controller 25%), then actuates a digital input device **182** while actuating the continuous motion device (and thus maintaining the proportional input signal), a combination of both a digital input signal and a proportional input signal is received at process **1110**.

(73) At a process **1020**, the determination is made whether the input received at process **1010** is a proportional input signal, a digital input signal, or a combination of both. In an instance in which the input signal received is generated by a continuous motion input device **181**, such as a gripping controller or a rotary controller, the input signal is determined to be a proportional input signal and method **1000** proceeds to process **1030**. In an instance in which the input signal received is generated by a digital input device **182**, such as a foot pedal or button, the input signal is determined to be a digital input signal and method **1000** proceeds to process **1050**. In an instance in which both a digital input signal and a continuous input signal are received concurrently, method **1000** proceeds to process **1050**.

(74) At a process **1030**, an arc of rotation of curved needle **202** is determined based on mapping **170** and the proportional input signal. In some embodiments, process **1030** is substantially similar to process **730** in method **700** of FIG. 7.

(75) At process **1040**, drive mechanism **300** is caused to rotationally actuate curved needle **202** through the arc of rotation determined in process **1030**. In some embodiments, process **1040** is substantially similar to process **740** in method **700** of FIG. 7. Method **1000** then returns to process **1010**.

(76) At process **1050**, the determination is made whether the current position of actuator arm **311** is at (or within a predetermined tolerance from) a needle-driving position. If yes, method **1000** proceeds to process **1060**; if no, method **1000** proceeds to process **1070**.

(77) At process **1060**, drive mechanism **300** is caused to rotationally actuate curved needle **202** through a preset arc of rotation, for example 180 degrees or 360 degrees. In some embodiments, process **1060** is substantially similar to process **760** in method **700** of FIG. 7. Upon completion of process **1060**, method **1000** returns back to the start of method **1000**.

(78) At process **1070**, the operator is alerted. For example, in some embodiments, the alert can be provided to the operator via one or more of a visual display (via icons and/or text), a playing of an audio message, and/or a haptic feedback. In some embodiments, the alert indicates that rotational actuation of curved needle **202** through a preset arc of rotation cannot occur until the current position of actuator arm **311** is at (or within a predetermined tolerance from) a needle-driving position (e.g., the home position). Alternatively or additionally, in some embodiments, the alert prompts the operator to actuate continuous motion input device **181** to a 0% position of the input range of the continuous motion input device **181**. In some embodiments, the alert may alternatively or additionally inform the user that actuation of continuous motion input device **181** to a 100% position of its input range is permitted (e.g., corresponding to the engaged position). Method **1000** then returns back to process **1010**.

(79) As noted above, in some embodiments, a drive mechanism of an end effector is configured to provide forward and retraction rotary motion of a curved needle, and automated rotation of a needle can be conducted after an operator has caused the curved needle to peek into a tissue gap area of the end effector, for example to perform a 180-degree rotation or a 360-degree rotation of the curved needle. In some embodiments, the automated rotation of the curved needle is initiated while the curved needle is still disposed in the tissue gap of the end effector. Thus, in such embodiments, the automated rotation of the curved needle is performed even though the gripping controller (or other continuous motion device **181**) has not been returned to a position at or near the non-actuation position or to the engaged position. One such embodiment is described below in conjunction with FIG. **11**.

(80) FIG. **11** is a simplified diagram of a method of automated rotation of a needle in a computer-assisted system, according to some embodiments. One or more of the processes **1110-1170** of

method **1100** may be implemented, at least in part, in the form of executable code stored on non-transient, tangible, machine readable media that when run by one or more processors (e.g., the processor **140** in control unit **130**) may cause the one or more processors to perform one or more of the processes **1110-1170**. In some embodiments, the method **1100** may be performed by control unit **130** and an application, such as motion control application **160**.

(81) At a process **1110**, an input signal (e.g., an input) is received from an input device, such as a continuous motion input device **181**, a digital input device **182**, or a combination of both. It is noted that when a combination of both a digital input signal and a proportional input signal is received at process **1110**, generally, the digital input signal is received as an additional input signal while the proportional input signal is already being received. For example, when an operator actuates a continuous motion input device **181** to a certain position (e.g., closing a gripping controller 25%), then actuates a digital input device **182** while actuating the continuous motion device (and thus maintaining the proportional input signal), a combination of both a digital input signal and a proportional input signal is received at process **1110**.

(82) At a process **1120**, the determination is made whether the input received at process **1110** is a proportional input signal, a digital input signal, or a combination of both. In an instance in which the input signal received is generated by a continuous motion input device **181**, such as a gripping controller or a rotary controller, the input signal is determined to be a proportional input signal and method **1100** proceeds to process **1130**. In an instance in which the input signal received is generated by a digital input device **182**, such as a foot pedal or button, the input signal is determined to be a digital input signal and method **1100** proceeds to process **1170**. In an instance in which both a digital input signal and a continuous input signal are received concurrently, method **1100** proceeds to process **1170**.

(83) At a process **1130**, an arc of rotation of curved needle **202** is determined based on mapping **170** and the proportional input signal. In some embodiments, process **1130** is substantially similar to process **730** in method **700** of FIG. 7.

(84) At process **1140**, drive mechanism **300** is caused to rotationally actuate curved needle **202** through the arc of rotation determined in process **1130**. In some embodiments, process **1140** is substantially similar to process **740** in method **700** of FIG. 7. Method **1100** then returns to process **1110**.

(85) At process **1170**, drive mechanism **300** is caused to complete rotational actuation of curved needle **202** through a preset arc of rotation, for example 180 degrees or 360 degrees. In some embodiments, process **1170** is substantially similar to processes **760** and/or **770** in method **700** of FIG. 7. In some embodiments, at process **1170**, drive mechanism **300** is caused to complete a remainder portion of rotational actuation of curved needle **202**. In such embodiments, completion of the rotational actuation of curved needle **202** entails rotational actuation through a remainder portion of a preset rotation amount about axis **203**, such as for instances where actuator arm **311** is not in the home position. Thus, in such embodiments, the digital input received in process **1110** results in rotation of less than a preset rotation amount about axis **203**, such as the preset rotation amount about axis **203** minus the amount of rotational actuation performed of the curved need after completing process **1140**. Method **1100** then returns to process **1110**.

(86) In some embodiments, use of autonomous rotational actuation of curved needle **202** in conjunction with an operator peeking curved needle **202** out of a home position (via actuation of continuous motion input device **181**) is facilitated by a remapping of values of a proportional input signal from continuous motion input device **181**. In such embodiments, an operator can peek curved needle **202** into a tissue gap area of the end effector via continuous motion input device **181**, then cause a digital input signal to be generated via digital input device **182** while continuing to hold the same position for continuous motion input device **181**. In such embodiments, the digital input motion causes autonomous rotational actuation of curved needle **202**, so that curved needle **202** is rotated about axis **203** until a preset rotation amount is completed, such as a 180-degree or

360-degree rotation amount. In such embodiments, a remapping of the proportional input signal from continuous motion input device **181** is performed, in which the remaining continuous motion travel available for continuous motion input device **181** is mapped to 0% to 100% of the travel of curved needle **202**. Thus, in such embodiments, after the autonomous rotational actuation of curved needle **202** occurs and curved needle **202** is rotated until the preset rotation amount is completed, an operator can peek curved needle **202** into the tissue gap area of the end effector via continuous motion input device **181** again, without first resetting continuous motion input device **181** back to a 0% closed (e.g., home) position. For example, in an embodiment in which continuous motion input device **181** is implemented as a gripping controller, an operator can close the gripping controller to a 10% closed position to peek curved needle **202** into the tissue gap and cause autonomous rotational actuation of curved needle **202** with digital input device **182** while continuing to hold the gripping controller at the 10% closed position. In response to the gripping controller being maintained at the 10% closed position while a digital input signal is received from digital input device **182**, a modified mapping of values included in mapping **170** is generated. In some embodiments, mapping **170** is modified to include a modified mapping of values of the proportional input signal from continuous motion input device **181** to values of a rotational arc amount of curved needle **202** that is based on the proportional input signal received while the digital input signal is received from digital input device **182**. Thus, in an example, in mapping **170**, values of the proportional input signal corresponding to 10% to 100% of gripping controller closure are mapped to values corresponding to 0% to 100% of the preset rotation amount of curved needle **202**. Therefore, in such an example, 10% closure of the gripping controller is mapped to curved needle **202** being positioned at a 0% (home) position. Based on the modified mapping, the operator can then close the gripping controller from the 10% closed position to a 20% closed position to again peek curved needle **202** into the tissue gap (e.g., to 11% of the preset rotation amount) and again cause autonomous rotational actuation of curved needle **202** with digital input device **182** while continuing to hold the gripping controller at the 20% closed position. In response to the gripping controller being maintained at the 20% closed position while a digital input signal is received from digital input device **182**, another modified mapping of values included in mapping **170** is generated. Such a process can continue until an operator resets the mapping of the proportional input signal from continuous motion input device **181** by opening the gripping controller to the 0% closed position, at which point values included in mapping **170** are reset to an original mapping. One such embodiment is described below in conjunction with FIG. **12**.

(87) FIG. **12** is a simplified diagram of a method of automated rotation of a needle in a computer-assisted system, according to some embodiments. One or more of the processes **1210-1290** of method **1200** may be implemented, at least in part, in the form of executable code stored on non-transient, tangible, machine readable media that when run by one or more processors (e.g., the processor **140** in control unit **130**) may cause the one or more processors to perform one or more of the processes **1210-1290**. In some embodiments, the method **1200** may be performed by control unit **130** and an application, such as motion control application **160**.

(88) At a process **1210**, an input signal (e.g., an input) is received from an input device, such as a continuous motion input device **181**, a digital input device **182**, or a combination of both. In some embodiments, process **1210** is substantially similar to process **1110** in method **1100** of FIG. **11**.

(89) At a process **1220**, the determination is made whether the input received at process **1210** is a proportional input signal, a digital input signal, or a combination of both. In an instance in which the input signal received is generated by a continuous motion input device **181**, such as a gripping controller or a rotary controller, the input signal is determined to be a proportional input signal and method **1200** proceeds to process **1230**. In an instance in which the input signal received is generated by a digital input device **182**, such as a foot pedal or button, the input signal is determined to be a digital input signal and method **1200** proceeds to process **1250**. In an instance in which both a digital input signal and a continuous input signal are received concurrently, method

**1200** proceeds to process **1280**.

(90) At a process **1230**, the determination is made whether a temporary remapping of mapping **170** has been enabled. If yes, method **1200** proceeds to process **1240**; if no, method **1200** proceeds to process **1250**.

(91) At a process **1240**, the determination is made whether the proportional input signal received in process **1210** indicates a return to a zero or home position. If yes, method **1200** proceeds to process **1270**; if no, method **1200** proceeds to process **1250**.

(92) At a process **1270**, mapping **170** is returned to an original mapping of values of a proportional input signal received from continuous motion input device **181** to a particular rotational arc amount. In some embodiments, the original mapping maps values of the full input range of proportional input signal (e.g., 0% to 100%) to values of a preset rotational arc amount of the curved needle, e.g., a 180-degree or 360-degree rotation amount. Thus, in such embodiments, a value corresponding to a 0% proportional input signal (e.g., a gripping controller 0% closed) is mapped to 0% of the preset rotational arc amount (e.g. 0 degrees rotation of curved needle **202**), and a value corresponding to a 100% proportional input signal (e.g., a gripping controller 100% closed) is mapped to 100% of the preset rotational arc amount (e.g. 180 degrees or 350 degrees of rotation of curved needle **202**). Method **1200** then returns back to process **1210**.

(93) At a process **1250**, an arc of rotation of curved needle **202** is determined based on mapping **170** and the proportional input signal. In some embodiments, process **1250** is substantially similar to process **1130** in method **1100** of FIG. **11**, except that a modified mapping **170** may be employed instead of the original mapping **170**.

(94) At process **1260**, drive mechanism **300** is caused to rotationally actuate curved needle **202** through the arc of rotation determined in process **1250**. In some embodiments, process **1260** is substantially similar to process **1140** in method **1100** of FIG. **11**. Method **1200** then returns to process **1210**.

(95) At process **1280**, in response to the proportional input signal being received in combination with the digital input signal, mapping **170** is temporarily modified. Specifically, the values of the proportional input signal from continuous motion input device **181** are remapped to different rotational arc amounts. In some embodiments, the value of the proportional input signal received in combination with the digital input signal is remapped to 0 rotational arc and the maximum available value of the proportional input signal (e.g., 100% gripping motion) received in combination with the digital input signal is mapped to a preset rotation amount about axis **203**, such as a 180-degree or 360-degree rotation amount. Method **1200** then returns to process **1210**.

(96) At process **1290**, drive mechanism **300** is caused to rotationally actuate curved needle **202** through a preset arc of rotation, for example 180 degrees or 360 degrees. In some embodiments, process **1290** is substantially similar to process **1170** in method **1100** of FIG. **11**. In some embodiments, at process **1290**, drive mechanism **300** is caused to complete a remainder portion of rotational actuation of curved needle **202**. In such embodiments, completion of the rotational actuation of curved needle **202** entails rotational actuation through a remainder portion of a preset rotation amount about axis **203**, such as for instances where actuator arm **311** is not in the home position when the digital signal is received. Method **1200** then returns to process **1210**.

(97) Some examples of control units, such as control unit **130** may include non-transient, tangible, machine readable media that include executable code that when run by one or more processors (e.g., processor **140**) may cause the one or more processors to perform the processes of methods **700** and/or **800**. Some common forms of machine readable media that may include the processes of methods **700** and/or **800** are, for example, floppy disk, flexible disk, hard disk, magnetic tape, any other magnetic medium, CD-ROM, any other optical medium, punch cards, paper tape, any other physical medium with patterns of holes, RAM, PROM, EPROM, FLASH-EPROM, any other memory chip or cartridge, and/or any other medium from which a processor or computer is adapted to read.

(98) 1. In some embodiments, a method in a computer-assisted device that includes an end effector includes: in response to receiving a first input, causing a drive mechanism of the end effector to rotationally actuate a curved needle coupled to the drive mechanism by a first preset rotation amount along an arcuate path; and in response to receiving a second input, causing the drive mechanism to rotationally actuate the curved needle by a second preset rotation amount along the arcuate path.

(99) 2. The method of clause 1, wherein the arcuate path comprises a circular path and the drive mechanism is configured to rotationally actuate the curved needle about an axis that includes a center point of the circular path.

(100) 3. The method of clause 2, wherein the first preset rotation amount is a 180 degree rotation of the curved needle about the axis.

(101) 4. The method of clause 2, wherein the second preset rotation amount is a 360 degree rotation of the curved needle about the axis.

(102) 5. The method of clause 1, wherein the first input is received from a first input device and the second input is received from a second input device different from the first input device.

(103) 6. The method of clause 1, wherein the first input and the second input are each received from a same input device.

(104) 7. The method of clause 5, wherein the first input device comprises a first foot pedal and the second input device comprises a second foot pedal.

(105) 8. The method of clause 5, wherein the first input device comprises a first digital button and the second input device comprises a second digital button.

(106) 9. The method of clause 1, wherein the computer-assisted device is a surgical device and the curved needle is a curved suturing needle.

(107) 10. The method of clause 1, wherein the end effector is configured to be mounted near a distal end of a repositionable arm.

(108) 11. The method of any of clauses 1 to 10, wherein the control unit is further configured to, in response to receiving a digital input signal from a second input device, cause the drive mechanism to complete a rotational actuation of the curved needle through a preset rotation amount about an axis.

(109) 12. The method of clause 11, wherein the operator input signal and the digital input signal are received concurrently.

(110) 13. The method of clause 11, further comprising, to cause the drive mechanism to complete the rotational actuation of the curved needle through the preset rotation amount, causing the drive mechanism to actuate the curved needle through a first rotation amount that is less than the preset rotation amount or more than the preset rotation amount.

(111) 14. The method of clause 13, wherein the first rotation amount is based on a rotation amount that corresponds to the operator input signal that is received concurrently with the digital input signal.

(112) 15. The method of clause 13, wherein the first rotation amount is based on a difference between the preset rotation amount and a rotation amount that corresponds to the operator input signal that is received concurrently with the digital input signal.

(113) 16. The method of clause 13, further comprising, generating a modified mapping of the operator input signal, wherein the modified mapping maps values of the operator input signal to values of a rotational arc amount of the curved needle that is smaller than the preset rotation amount.

(114) 17. The method of clause 16, wherein the values of the rotational arc amount of the curved needle that is smaller than the preset rotation amount is based on the operator input signal received concurrently with the digital input signal.

(115) 18. The method of clause 16, further comprising, in response to receiving an operator input signal corresponding to a fully open position of a grip controller of the computer-assisted device

after the generation of the modified mapping, resetting the mapping of the operator input signal to an original mapping of the values of the operator input signal to the values of the rotational arc amount of the curved needle.

(116) 19. The method of clause 16, further comprising, in response to receiving a second operator input signal after receiving the digital input signal: based on the modified mapping, determining an arc of rotation for the curved needle along an arcuate path corresponding to the second operator input signal; and causing the drive mechanism to rotationally actuate the curved needle through the arc of rotation along the arcuate path corresponding to the second operator input signal.

(117) 20. The computer-assisted device of any one of clauses 1 to 10, further comprising, in response to receiving a digital input signal from a second input device: determining that the drive mechanism is not disposed within a certain distance of a home position; and preventing the drive mechanism from completing the rotational actuation of the curved needle through a preset rotation amount about the axis.

(118) 21. In some embodiments, a method in a computer-assisted device that includes an end effector having a drive mechanism configured to be coupled to a curved needle and configured to rotationally actuate the curved needle along an arcuate path includes: receiving an operator input signal; based on a mapping of the operator input signal to a rotational arc amount of the curved needle, determining an arc of rotation for the curved needle along the arcuate path corresponding to the operator input signal; and causing the drive mechanism to rotationally actuate the curved needle through the arc of rotation along the arcuate path.

(119) 22. The method of clause 21, wherein the operator input signal is received from a continuous motion input device.

(120) 23. The method of clause 22, wherein the continuous motion input device comprises a rotary input device of a computer-assisted system.

(121) 24. The method of clause 23, wherein the mapping maps one revolution of the rotary input device to 360 degrees of rotation for the curved needle.

(122) 25. The method of clause 22, wherein the operator input signal is received from a gripping controller of a computer-assisted system.

(123) 26. The method of clause 25, wherein the mapping maps movement of the gripping controller from open to closed to 180 degrees or 360 degrees of rotation for the curved needle.

(124) 27. The method of clause 21, wherein the arcuate path comprises a circular path and the drive mechanism is configured to rotationally actuate the curved needle about an axis that includes a center point of the circular path.

(125) 28. The method of clause 27, wherein the axis is located at a center of a circle defined by a curve of the curved needle.

(126) 29. The method of clause 21, wherein the computer-assisted device is a surgical device and the curved needle is a curved suturing needle.

(127) 30. The method of clause 21, wherein the end effector is configured to be mounted near a distal end of a repositionable arm.

(128) 31. The method of clause 21, wherein the mapping includes a first mapping of a first proportional input signal that is generated by actuation of a continuous motion input device in a first direction and a second mapping of a second proportional input signal that is generated by actuation of the continuous motion input device in a second direction.

(129) 32. The method of clause 31, wherein the first mapping maps values of the first proportional input signal to values of a first rotational arc of the drive mechanism and the second mapping maps values of the second proportional input signal to values of a second rotational arc of the drive mechanism.

(130) 33. The method of clause 11, further comprising, in response to receiving a digital input signal from a second input device, causing the drive mechanism to complete a rotational actuation of the curved needle through a preset rotation amount about an axis.

- (131) 34. The method of clause 33, wherein the second input device comprises a digital input device.
- (132) 35. The method of clause 33, wherein the second input device comprises a foot pedal.
- (133) 36. The method of clause 33, wherein the preset rotation amount is a 180 degree or a 360 degree rotation of the curved needle about an axis.
- (134) 37. A non-transitory machine-readable medium comprising a plurality of machine-readable instructions which when executed by one or more processors are adapted to cause the one or more processors to perform the method of any one of clauses 1 to 36.
- (135) Although illustrative embodiments have been shown and described, it is to be understood that such embodiments are merely illustrative of and not restrictive on the broad inventive concept. A wide range of modification, change and substitution is contemplated in the foregoing disclosure and in some instances, some features of the embodiments may be employed without a corresponding use of other features. One of ordinary skill in the art would recognize many variations, alternatives, and modifications. Thus, the scope of the invention should be limited only by the following claims and equivalents thereof.

## Claims

1. A computer-assisted device comprising: an end effector having a drive mechanism configured to be coupled to a curved needle and configured to rotationally actuate the curved needle along an arcuate path; and a control unit coupled to the drive mechanism; wherein the control unit is configured to: receive an operator input signal; based on a mapping of values of the operator input signal to values of a rotational arc amount of the curved needle, determine an arc of rotation for the curved needle along the arcuate path corresponding to the operator input signal; cause the drive mechanism to rotationally actuate the curved needle through the arc of rotation along the arcuate path; and in response to receiving a digital input signal from a second input device, cause the drive mechanism to complete a rotational actuation of the curved needle through a preset rotation amount about an axis.
2. The computer-assisted device of claim 1, wherein the operator input signal is received from a continuous motion input device.
3. The computer-assisted device of claim 2, wherein the continuous motion input device comprises a rotary input device of a computer-assisted system.
4. The computer-assisted device of claim 3, wherein the mapping maps values corresponding to one revolution of the rotary input device to values corresponding to 360 degrees of rotation for the curved needle.
5. The computer-assisted device of claim 2, wherein the operator input signal is received from a gripping controller of a computer-assisted system.
6. The computer-assisted device of claim 5, wherein the mapping maps values corresponding to movement of the gripping controller from open to closed to values corresponding to 180 degrees or 360 degrees of rotation for the curved needle.
7. The computer-assisted device of claim 1, wherein the arcuate path comprises a circular path and the drive mechanism is configured to rotationally actuate the curved needle about an axis that includes a center point of the circular path.
8. The computer-assisted device of claim 2, wherein the mapping includes a first mapping of values of a first proportional input signal that is generated by actuation of the continuous motion input device in a first direction and a second mapping of values of a second proportional input signal that is generated by actuation of the continuous motion input device in a second direction.
9. The computer-assisted device of claim 8, wherein the first mapping maps the values of the first proportional input signal to values of a first rotational arc of the drive mechanism and the second mapping maps the values of the second proportional input signal to values of a second rotational



arc of the drive mechanism.

10. The computer-assisted device of claim 1, wherein the operator input signal is received from a continuous motion input device and the digital input signal is received from a digital motion input device.

11. The computer-assisted device of claim 1, wherein the preset rotation amount is a 180 degree or a 360 degree rotation of the curved needle about the axis.

12. The computer-assisted device of claim 1, wherein the operator input signal and the digital input signal are received concurrently.

13. The computer-assisted device of claim 1, wherein to cause the drive mechanism to complete the rotational actuation of the curved needle through the preset rotation amount, the control unit is further configured to cause the drive mechanism to actuate the curved needle through a first rotation amount that is less than the preset rotation amount or more than the preset rotation amount.

14. The computer-assisted device of claim 13, wherein the first rotation amount is based on a rotation amount that corresponds to the operator input signal that is received concurrently with the digital input signal.

15. The computer-assisted device of claim 13, wherein the first rotation amount is based on a difference between the preset rotation amount and a rotation amount that corresponds to the operator input signal that is received concurrently with the digital input signal.

16. The computer-assisted device of claim 13, wherein the control unit is further configured to generate a modified mapping of the operator input signal, wherein the modified mapping maps values of the operator input signal to values of a rotational arc amount of the curved needle that is smaller than the preset rotation amount.

17. The computer-assisted device of claim 16, wherein the values of the rotational arc amount of the curved needle that is smaller than the preset rotation amount are based on the operator input signal received concurrently with the digital input signal.

18. The computer-assisted device of claim 16, wherein the control unit is further configured to, in response to receiving an operator input signal corresponding to a fully open position of a grip controller of the computer-assisted device after the generation of the modified mapping, reset the mapping of the operator input signal to an original mapping of the values of the operator input signal to the values of the rotational arc amount of the curved needle.

19. The computer-assisted device of claim 16, wherein the control unit is further configured to, in response to receiving a second operator input signal after receiving the digital input signal: based on the modified mapping, determine an arc of rotation for the curved needle along an arcuate path corresponding to the second operator input signal; and cause the drive mechanism to rotationally actuate the curved needle through the arc of rotation along the arcuate path corresponding to the second operator input signal.

20. The computer-assisted device of claim 1, wherein the control unit is further configured to, in response to receiving the digital input signal from the second input device: determine that the drive mechanism is not disposed within a certain distance of a home position; and prevent the drive mechanism from completing the rotational actuation of the curved needle through the preset rotation amount about the axis.

---