



US012384337B1

(12) **United States Patent**  
**Verhoff et al.**

(10) **Patent No.:** **US 12,384,337 B1**

(45) **Date of Patent:** **Aug. 12, 2025**

(54) **MILITARY VEHICLE**

(71) Applicant: **Oshkosh Defense, LLC**, Oshkosh, WI (US)

(72) Inventors: **Don Verhoff**, Oshkosh, WI (US); **Gary Schmiedel**, Oshkosh, WI (US); **Chris Yakes**, Oshkosh, WI (US); **Rob Messina**, Oshkosh, WI (US); **Brian Wilkins**, Oshkosh, WI (US); **Kent Schulte**, Oshkosh, WI (US); **Daniel R. Seffernick**, Oshkosh, WI (US); **Joseph Holda**, Oshkosh, WI (US); **Michael Peotter**, Oshkosh, WI (US); **David McGraw**, Oshkosh, WI (US); **Anthony Seefeldt**, Oshkosh, WI (US); **Dave Pelko**, Oshkosh, WI (US); **Jesse Gander**, Oshkosh, WI (US); **Jerry Reineking**, Oshkosh, WI (US); **Jesse Steinke**, Oshkosh, WI (US)

(73) Assignee: **Oshkosh Defense, LLC**, Oshkosh, WI (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **18/732,064**

(22) Filed: **Jun. 3, 2024**

**Related U.S. Application Data**

(63) Continuation of application No. 17/718,535, filed on Apr. 12, 2022, now Pat. No. 12,036,966, which is a (Continued)

(51) **Int. Cl.**  
**F41H 5/16** (2006.01)  
**B60G 17/04** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **B60T 7/20** (2013.01); **B60G 17/04** (2013.01); **B60T 13/14** (2013.01); **B60T 13/16** (2013.01);  
(Continued)

(58) **Field of Classification Search**

CPC . B60T 7/20; B60T 13/14; B60T 13/16; B60T 13/249; B60T 13/581;

(Continued)

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

815,574 A 3/1906 Russell  
1,001,863 A 8/1911 Kirkwood

(Continued)

**FOREIGN PATENT DOCUMENTS**

CA 2478228 A1 2/2006  
CA 2581525 4/2006

(Continued)

**OTHER PUBLICATIONS**

How the U.S. military plans to replace the iconic Humvee. Aug. 13, 2021. CNBC. <https://www.cnbc.com/2021/08/13/how-the-US-military-plans-to-replace-the-iconic-humvee.html>.

(Continued)


*Primary Examiner* — Karen Beck

(74) *Attorney, Agent, or Firm* — Foley & Lardner LLP

(57) **ABSTRACT**

A military vehicle assembly includes a rear module. The rear module includes a rear frame assembly, a bed supported by the rear frame assembly, a rear tractive assembly, a transaxle supported by the rear frame assembly and coupled to the rear tractive assembly, and a rear suspension system including at least one component extending between a housing of the transaxle and the rear tractive assembly. The rear frame assembly has one or more upper interfaces and one or more lower interfaces. The one or more upper interfaces are configured to detachably couple to a rear end of a passenger capsule of a military vehicle. The one or more lower interfaces are configured to detachably couple to a bottom

(Continued)



of the passenger capsule. The transaxle is configured to couple to a prime mover and a front differential of the military vehicle.

## 20 Claims, 9 Drawing Sheets

### Related U.S. Application Data

continuation of application No. 17/398,581, filed on Aug. 10, 2021, now Pat. No. 11,332,104, which is a continuation of application No. 16/529,508, filed on Aug. 1, 2019, now Pat. No. 11,541,851, which is a continuation of application No. 15/599,174, filed on May 18, 2017, now Pat. No. 10,434,995, which is a continuation of application No. 14/724,279, filed on May 28, 2015, now Pat. No. 9,656,640, which is a continuation of application No. 13/841,686, filed on Mar. 15, 2013, now Pat. No. 9,045,014.

- (60) Provisional application No. 61/615,812, filed on Mar. 26, 2012.

### (51) Int. Cl.

**B60K 17/10** (2006.01)  
**B60T 7/20** (2006.01)  
**B60T 13/14** (2006.01)  
**B60T 13/16** (2006.01)  
**B60T 13/24** (2006.01)  
**B60T 13/58** (2006.01)  
**B62D 21/15** (2006.01)  
**B62D 21/18** (2006.01)  
**B62D 24/00** (2006.01)  
**B62D 33/06** (2006.01)  
**B62D 63/02** (2006.01)  
**F41H 7/04** (2006.01)  
**B60T 13/66** (2006.01)

### (52) U.S. Cl.

CPC ..... **B60T 13/249** (2013.01); **B60T 13/581** (2013.01); **B60T 13/583** (2013.01); **B62D 21/152** (2013.01); **B62D 21/18** (2013.01); **B62D 24/00** (2013.01); **B62D 33/0617** (2013.01); **B62D 63/025** (2013.01); **F41H 5/16** (2013.01); **F41H 7/044** (2013.01); **B60G 2300/07** (2013.01); **B60K 17/105** (2013.01); **B60T 13/66** (2013.01); **F41H 7/048** (2013.01)

### (58) Field of Classification Search

CPC ..... B60T 13/583; B60T 13/66; B60G 17/04; B60G 2300/07; B62D 21/152; B62D 21/18; B62D 24/00; B62D 33/0617; B62D 63/025; F41H 5/16; F41H 7/044; F41H 7/048; B60K 17/105

See application file for complete search history.

### (56) References Cited

#### U.S. PATENT DOCUMENTS

1,278,460 A 9/1918 Hanger  
 1,376,467 A 5/1921 Simmon  
 1,463,569 A 7/1923 Bathrick  
 1,835,132 A 12/1931 Anania  
 1,941,582 A 1/1934 Schroeder  
 2,261,693 A 11/1941 Mathauer  
 2,628,127 A 2/1953 Palsgrove  
 2,632,577 A 3/1953 Sacco  
 2,907,575 A 10/1959 Locker

2,915,334 A 12/1959 Barenyi  
 2,916,997 A 12/1959 Terrie  
 2,997,242 A 8/1961 Grosholz  
 3,010,533 A 11/1961 Ross  
 3,021,166 A 2/1962 Kempel et al.  
 3,039,788 A 6/1962 Farago  
 3,046,045 A 7/1962 Campbell  
 3,083,790 A 4/1963 McAfee et al.  
 3,131,963 A 5/1964 Schilberg  
 3,146,839 A 9/1964 Carlson  
 3,188,966 A 6/1965 Tetlow  
 3,306,390 A 2/1967 Jamme  
 3,395,672 A 8/1968 Ruf  
 3,500,961 A 3/1970 Eberhardt et al.  
 3,590,948 A 7/1971 Milner, Jr.  
 3,726,308 A 4/1973 Eberhardt  
 3,778,115 A 12/1973 Ryburn  
 3,881,767 A 5/1975 Klees  
 4,037,664 A 7/1977 Gibson  
 4,059,170 A 11/1977 Young  
 4,072,362 A 2/1978 Van Anrooy  
 4,084,522 A 4/1978 Younger  
 4,103,757 A 8/1978 McVaugh  
 4,153,262 A 5/1979 Diamond et al.  
 4,157,733 A 6/1979 Ewers et al.  
 4,160,492 A 7/1979 Johnston  
 4,185,924 A 1/1980 Graham  
 4,241,803 A 12/1980 Lauber  
 4,270,771 A 6/1981 Fujii  
 4,280,393 A 7/1981 Giraud et al.  
 4,326,445 A 4/1982 Bemiss  
 4,329,109 A 5/1982 Den Bleyker  
 4,337,830 A 7/1982 Eberhardt  
 4,369,010 A 1/1983 Ichinose et al.  
 4,373,600 A 2/1983 Buschbom et al.  
 4,395,191 A 7/1983 Kaiser  
 4,422,685 A 12/1983 Bonfilio et al.  
 4,456,093 A 6/1984 Finley et al.  
 4,492,282 A 1/1985 Appelblatt et al.  
 4,558,758 A 12/1985 Littman et al.  
 4,563,124 A 1/1986 Eskew  
 4,586,743 A 5/1986 Edwards et al.  
 4,587,862 A 5/1986 Hoffman  
 4,655,307 A 4/1987 Lamoureux  
 4,659,104 A 4/1987 Tanaka et al.  
 4,669,744 A 6/1987 Sano et al.  
 4,696,489 A 9/1987 Fujishiro et al.  
 4,709,358 A 11/1987 Appling et al.  
 4,733,876 A 3/1988 Heider et al.  
 4,811,804 A 3/1989 Ewers et al.  
 4,826,141 A 5/1989 Buma et al.  
 4,834,418 A 5/1989 Buma et al.  
 4,848,835 A 7/1989 Derees  
 4,889,395 A 12/1989 Fujita et al.  
 4,926,954 A 5/1990 Ataka et al.  
 4,945,780 A 8/1990 Bosma  
 5,004,156 A 4/1991 Montanier  
 5,010,971 A 4/1991 Hamada et al.  
 5,021,917 A 6/1991 Pike et al.  
 5,028,088 A 7/1991 Del Monico et al.  
 5,040,823 A 8/1991 Lund  
 5,054,806 A 10/1991 Chester  
 5,076,597 A 12/1991 Korekane et al.  
 5,080,392 A 1/1992 Bazergui  
 5,111,901 A 5/1992 Bachhuber et al.  
 5,113,946 A 5/1992 Cooper  
 5,137,101 A 8/1992 Schaeff  
 5,137,292 A 8/1992 Eisen  
 5,139,104 A 8/1992 Moscicki  
 5,143,326 A 9/1992 Parks  
 5,158,614 A 10/1992 Takeuchi  
 5,169,197 A 12/1992 Underbakke et al.  
 5,209,003 A 5/1993 Maxfield et al.  
 5,211,245 A 5/1993 Relyea et al.  
 5,217,083 A 6/1993 Bachhuber et al.  
 5,301,756 A 4/1994 Relyea et al.  
 5,314,230 A 5/1994 Hutchison et al.  
 5,319,436 A 6/1994 Manns et al.  
 5,322,321 A 6/1994 Yopp

(56)

**References Cited**

## U.S. PATENT DOCUMENTS

5,327,989	A	7/1994	Furuhashi et al.	6,561,718	B1	5/2003	Archer et al.
5,346,334	A	9/1994	Einaru et al.	6,619,673	B2	9/2003	Eckelberry et al.
5,368,317	A	11/1994	McCombs et al.	6,623,020	B1	9/2003	Satou
5,390,945	A	2/1995	Orr	6,658,984	B2	12/2003	Zonak
5,438,908	A	8/1995	Madden, Jr.	6,692,366	B1	2/2004	Savant
5,467,827	A	11/1995	McLoughlin	6,695,328	B2	2/2004	Cope
5,476,202	A	12/1995	Lipp	6,695,566	B2	2/2004	Rodriguez Navio
5,487,323	A	1/1996	Madden, Jr.	6,702,058	B2	3/2004	Ishii et al.
5,501,288	A	3/1996	Ducote	6,736,232	B1	5/2004	Bergstrom et al.
5,533,781	A	7/1996	Williams	6,757,597	B2	6/2004	Yakes et al.
5,538,185	A	7/1996	Rabitsch et al.	6,764,085	B1	7/2004	Anderson
5,538,274	A	7/1996	Schmitz et al.	6,769,733	B2	8/2004	Seksaria et al.
5,549,230	A	8/1996	Palmen	6,779,806	B1	8/2004	Breitbach et al.
5,553,673	A	9/1996	Hackman	D497,849	S	11/2004	Yanase
5,617,696	A	4/1997	Young	6,820,908	B1	11/2004	Tousi et al.
5,663,520	A	9/1997	Ladika et al.	6,848,693	B2	2/2005	Schneider
5,670,734	A	9/1997	Middione et al.	6,860,332	B1	3/2005	Archer et al.
5,679,918	A	10/1997	Korpi et al.	6,878,481	B2	4/2005	Bushong et al.
5,687,669	A	11/1997	Engler	6,882,917	B2	4/2005	Pillar et al.
5,716,066	A	2/1998	Chou et al.	6,883,815	B2	4/2005	Archer
5,746,396	A	5/1998	Thorton-Trump	6,885,920	B2	4/2005	Yakes et al.
5,752,862	A	5/1998	Mohler et al.	6,899,191	B1	5/2005	Lykken
5,785,372	A	7/1998	Glatzmeier et al.	6,909,944	B2	6/2005	Pillar et al.
5,788,158	A	8/1998	Relyea	6,922,615	B2	7/2005	Pillar et al.
5,794,966	A	8/1998	Macleod	6,923,453	B2	8/2005	Pivac
5,807,056	A	9/1998	Osborn et al.	6,925,735	B2	8/2005	Hamm et al.
5,820,150	A	10/1998	Archer et al.	6,959,466	B2	11/2005	Alowonle et al.
D400,835	S	11/1998	Le Quemant et al.	6,976,688	B2	12/2005	Archer et al.
5,836,657	A	11/1998	Tilley et al.	6,993,421	B2	1/2006	Pillar et al.
5,839,664	A	11/1998	Relyea	7,006,902	B2	2/2006	Archer et al.
RE36,196	E	4/1999	Eberhardt	7,024,296	B2	4/2006	Squires et al.
5,897,123	A	4/1999	Cherney et al.	D523,381	S	6/2006	Taguchi et al.
5,899,276	A	5/1999	Relyea et al.	7,072,745	B2	7/2006	Pillar et al.
5,900,199	A	5/1999	Dickson et al.	7,073,620	B2	7/2006	Braun et al.
5,905,225	A	5/1999	Joynt	D528,482	S	9/2006	Hamburger
5,909,780	A	6/1999	De Andrade	7,107,129	B2	9/2006	Rowe et al.
5,915,728	A	6/1999	Blackburn	7,114,764	B1	10/2006	Barsoum et al.
5,915,775	A	6/1999	Martin et al.	7,127,331	B2	10/2006	Pillar et al.
5,919,240	A	7/1999	Ney et al.	D533,485	S	12/2006	Schiavone et al.
5,954,364	A	9/1999	Nechushtan	7,144,039	B2	12/2006	Kawasaki et al.
6,009,953	A	1/2000	Laskaris et al.	D535,589	S	1/2007	Lau et al.
6,015,155	A	1/2000	Brookes et al.	7,162,332	B2	1/2007	Pillar et al.
6,036,201	A	3/2000	Pond et al.	7,164,977	B2	1/2007	Yakes et al.
6,101,794	A	8/2000	Christopherson et al.	7,184,662	B2	2/2007	Arbel et al.
6,105,984	A	8/2000	Schmitz et al.	7,184,862	B2	2/2007	Pillar et al.
6,109,684	A	8/2000	Reitnouer	7,184,866	B2	2/2007	Squires et al.
6,131,685	A	10/2000	Sakamoto et al.	7,188,893	B2	3/2007	Akasaka
6,149,226	A	11/2000	Hoelzel et al.	7,195,306	B2	3/2007	Egawa et al.
6,155,351	A	12/2000	Breedlove et al.	7,198,130	B2	4/2007	Schimke
6,178,746	B1	1/2001	Thoma et al.	7,198,278	B2	4/2007	Donaldson
6,220,532	B1	4/2001	Manon et al.	7,207,582	B2	4/2007	Siebers et al.
6,231,466	B1	5/2001	Thoma et al.	7,213,872	B2	5/2007	Ronacher et al.
6,270,098	B1	8/2001	Heyring et al.	7,234,534	B2	6/2007	Froland et al.
6,270,153	B1	8/2001	Toyao et al.	7,240,906	B2	7/2007	Klees
6,289,995	B1	9/2001	Fuller	7,246,835	B1	7/2007	Colburn et al.
6,311,795	B1	11/2001	Skotnikov et al.	7,254,468	B2	8/2007	Pillar et al.
6,318,742	B2	11/2001	Franzini	7,258,194	B2	8/2007	Braun et al.
6,357,769	B1	3/2002	Omundson et al.	7,267,394	B1	9/2007	Mouch et al.
6,364,597	B2	4/2002	Klinkenberg	7,270,346	B2	9/2007	Rowe et al.
6,394,007	B2	5/2002	Lewis et al.	7,274,976	B2	9/2007	Rowe et al.
6,394,534	B1	5/2002	Dean	D552,522	S	10/2007	Sandy et al.
6,398,236	B1	6/2002	Richardson	7,277,782	B2	10/2007	Yakes et al.
6,398,478	B2	6/2002	Smith et al.	7,281,600	B2	10/2007	Chernoff et al.
6,421,593	B1	7/2002	Kempen et al.	7,288,920	B2	10/2007	Bushong et al.
6,435,071	B1	8/2002	Campbell	7,302,320	B2	11/2007	Nasr et al.
6,435,298	B1	8/2002	Mizuno et al.	7,306,069	B2	12/2007	Takeshima et al.
6,443,687	B1	9/2002	Kaiser	D561,665	S	2/2008	Thomas et al.
6,460,907	B2	10/2002	Usui	7,329,161	B2	2/2008	Roering
6,503,035	B1	1/2003	Perrott	D563,289	S	3/2008	Pfeiffer
6,516,914	B1	2/2003	Andersen et al.	7,357,203	B2	4/2008	Morrow et al.
6,520,494	B1	2/2003	Andersen et al.	D568,217	S	5/2008	Tomatsu et al.
6,527,494	B2	3/2003	Hurlburt	7,377,549	B2	5/2008	Hasegawa et al.
D473,829	S	4/2003	Hoyle, Jr.	7,379,797	B2	5/2008	Nasr et al.
6,553,290	B1	4/2003	Pillar	7,380,800	B2	6/2008	Klees
D474,430	S	5/2003	Hill et al.	7,392,122	B2	6/2008	Pillar et al.
				7,393,016	B2	7/2008	Mitsui et al.
				7,406,909	B2	8/2008	Shah et al.
				7,412,307	B2	8/2008	Pillar et al.
				7,419,021	B2	9/2008	Morrow et al.

(56)

**References Cited**

## U.S. PATENT DOCUMENTS

7,425,891	B2	9/2008	Colburn et al.	8,424,443	B2	4/2013	Gonzalez
7,439,711	B2	10/2008	Bolton	8,430,196	B2	4/2013	Halliday
7,441,615	B2	10/2008	Borroni-Bird et al.	D683,675	S	6/2013	Munson et al.
7,441,809	B1	10/2008	Coombs et al.	8,459,619	B2	6/2013	Trinh et al.
7,448,460	B2	11/2008	Morrow et al.	8,465,025	B2	6/2013	Venton-Walters et al.
7,451,028	B2	11/2008	Pillar et al.	D686,121	S	7/2013	McCabe et al.
7,472,914	B2	1/2009	Anderson et al.	8,561,735	B2	10/2013	Morrow et al.
7,472,919	B2	1/2009	Pratt et al.	8,578,834	B2	11/2013	Tunis et al.
7,510,235	B2	3/2009	Kobayashi et al.	8,596,183	B2	12/2013	Coltrane
7,520,354	B2	4/2009	Morrow et al.	8,596,648	B2	12/2013	Venton-Walters et al.
7,522,979	B2	4/2009	Pillar	8,601,931	B2	12/2013	Naroditsky et al.
7,555,369	B2	6/2009	Pillar et al.	8,616,617	B2	12/2013	Sherbeck et al.
D597,002	S	7/2009	Jamieson et al.	D698,281	S	1/2014	Badstuebner et al.
7,594,561	B2	9/2009	Hass et al.	8,635,776	B2	1/2014	Newberry et al.
7,611,153	B2	11/2009	Kim et al.	8,667,880	B1	3/2014	Berman
7,611,154	B2	11/2009	Delaney	D702,615	S	4/2014	Conway et al.
7,618,063	B2	11/2009	Takeshima et al.	D703,119	S	4/2014	Platto et al.
7,624,835	B2	12/2009	Bowers	8,714,592	B1	5/2014	Thoreson et al.
7,624,995	B2	12/2009	Barbison	8,746,741	B2	6/2014	Gonzalez
7,641,268	B2	1/2010	Goffart et al.	8,764,029	B2	7/2014	Venton-Walters et al.
7,681,892	B1	3/2010	Crews et al.	8,770,086	B2	7/2014	Enck
7,689,332	B2	3/2010	Yakes et al.	8,801,017	B2	8/2014	Ellifson et al.
7,695,053	B1	4/2010	Boczek et al.	D714,476	S	9/2014	Lai
7,699,385	B2	4/2010	Kurata	8,863,884	B2	10/2014	Jacob-Lloyd
7,711,460	B2	5/2010	Yakes et al.	8,876,133	B2	11/2014	Ellifson
7,715,962	B2	5/2010	Rowe et al.	D718,683	S	12/2014	Thole et al.
7,725,225	B2	5/2010	Pillar et al.	8,905,164	B1	12/2014	Capouellez et al.
D617,255	S	6/2010	Tezak et al.	8,921,130	B2	12/2014	Kundaliya et al.
7,726,429	B2	6/2010	Suzuki	8,943,946	B1	2/2015	Richmond et al.
7,729,831	B2	6/2010	Pillar et al.	8,944,497	B2	2/2015	Dryselius et al.
D619,062	S	7/2010	Improta	8,947,531	B2	2/2015	Fischer et al.
7,756,621	B2	7/2010	Pillar et al.	8,955,859	B1	2/2015	Richmond et al.
7,757,805	B2	7/2010	Wakuta et al.	8,960,068	B2	2/2015	Jacquemont et al.
7,770,506	B2	8/2010	Johnson et al.	D725,555	S	3/2015	Wolff et al.
D623,100	S	9/2010	Bimbi	8,967,699	B1	3/2015	Richmond et al.
D623,565	S	9/2010	Cogswell	8,991,834	B2	3/2015	Venton-Walters et al.
7,789,010	B2	9/2010	Allor et al.	8,991,840	B2	3/2015	Zuleger et al.
7,792,618	B2	9/2010	Quigley et al.	9,016,703	B2	4/2015	Rowe et al.
7,802,816	B2	9/2010	McGuire	D728,435	S	5/2015	Hanson et al.
D627,686	S	11/2010	Thompson et al.	9,045,014	B1	6/2015	Verhoff et al.
7,824,293	B2	11/2010	Schimke	D735,625	S	8/2015	Mays et al.
7,835,838	B2	11/2010	Pillar et al.	D739,317	S	9/2015	McMahan et al.
7,848,857	B2	12/2010	Nasr et al.	D740,187	S	10/2015	Jamieson
7,905,534	B2	3/2011	Boczek et al.	9,156,507	B1	10/2015	Reed
7,905,540	B2	3/2011	Kiley et al.	D742,287	S	11/2015	Hanson et al.
7,908,959	B2	3/2011	Pavon	D743,308	S	11/2015	Hanson et al.
D636,305	S	4/2011	Alvarez et al.	D743,856	S	11/2015	Ma
7,931,103	B2	4/2011	Morrow et al.	9,174,686	B1	11/2015	Oshkosh
7,934,766	B2	5/2011	Boczek et al.	D745,986	S	12/2015	Gorsten Schuenemann et al.
7,938,478	B2	5/2011	Kamimae	9,221,496	B2	12/2015	Barr et al.
D642,099	S	7/2011	Nagao et al.	D749,464	S	2/2016	Giolito
7,997,182	B1	8/2011	Cox	9,291,230	B2	3/2016	Ellifson et al.
8,000,850	B2	8/2011	Nasr et al.	D754,039	S	4/2016	Behmer et al.
D646,203	S	10/2011	Thompson et al.	9,303,715	B2	4/2016	Oshkosh
D646,607	S	10/2011	Verhee et al.	9,327,576	B2	5/2016	Ellifson
8,029,021	B2	10/2011	Leonard et al.	9,328,986	B1	5/2016	Pennau et al.
8,033,208	B2	10/2011	Joynt et al.	9,329,000	B1	5/2016	Richmond et al.
D649,908	S	12/2011	Mullen	9,358,879	B1	6/2016	Bennett
D649,909	S	12/2011	Mullen	9,366,507	B1	6/2016	Richmond et al.
8,095,247	B2	1/2012	Pillar et al.	D762,148	S	7/2016	Platto et al.
8,096,225	B1	1/2012	Johnson et al.	9,409,471	B2	8/2016	Hoppe et al.
8,123,645	B2	2/2012	Schimke	9,420,203	B2	8/2016	Broggi et al.
D655,226	S	3/2012	Hanson et al.	D765,566	S	9/2016	Vena et al.
8,139,109	B2	3/2012	Schmiedel et al.	D768,320	S	10/2016	Lai
8,146,477	B2	4/2012	Joynt	D769,160	S	10/2016	Platto et al.
8,146,478	B2	4/2012	Joynt et al.	D772,768	S	11/2016	Chiang
D661,231	S	6/2012	Galante et al.	9,492,695	B2	11/2016	Betz et al.
8,205,703	B2	6/2012	Halliday	D774,994	S	12/2016	Aleman et al.
D662,865	S	7/2012	Van Braeckel	D775,021	S	12/2016	Harriton et al.
8,333,390	B2	12/2012	Linsmeier et al.	D776,003	S	1/2017	Lee et al.
8,347,775	B2	1/2013	Altenhof et al.	D777,220	S	1/2017	Powell
8,376,077	B2	2/2013	Venton-Walters	D777,615	S	1/2017	Hanson et al.
8,402,878	B2	3/2013	Schreiner et al.	D778,217	S	2/2017	Ito et al.
8,413,567	B2	4/2013	Luther et al.	D782,711	S	3/2017	Dunshee et al.
8,413,568	B2	4/2013	Kosheleff	D784,219	S	4/2017	Jung
				D787,993	S	5/2017	McCabe et al.
				9,650,005	B2	5/2017	Patelczyk et al.
				9,656,640	B1	5/2017	Verhoff et al.
				D789,840	S	6/2017	Curic et al.

(56)

**References Cited**

## U.S. PATENT DOCUMENTS

D790,409 S	6/2017	Baste	10,759,251 B1	9/2020	Zuleger
9,688,112 B2	6/2017	Venton-Walters et al.	D898,244 S	10/2020	Badstuebner et al.
D791,987 S	7/2017	Lin	D898,632 S	10/2020	Gander
9,707,869 B1	7/2017	Messina et al.	D899,979 S	10/2020	Hamilton et al.
D794,853 S	8/2017	Lai	D900,690 S	11/2020	Lovati
9,738,186 B2	8/2017	Krueger et al.	D902,096 S	11/2020	Gander et al.
D796,715 S	9/2017	Lin	D902,807 S	11/2020	Ruiz
D797,332 S	9/2017	Lin	D902,809 S	11/2020	Hunwick
D797,603 S	9/2017	Noone et al.	D904,227 S	12/2020	Bracy
D802,491 S	11/2017	Mainville	D904,240 S	12/2020	Heilaneh et al.
D804,065 S	11/2017	Lai	D906,902 S	1/2021	Duncan et al.
9,809,080 B2	11/2017	Ellifson et al.	D908,935 S	1/2021	Lin
9,829,282 B1	11/2017	Richmond et al.	D909,639 S	2/2021	Chen
D804,372 S	12/2017	Kozub	D909,641 S	2/2021	Chen
D805,965 S	12/2017	Davis	D909,644 S	2/2021	Chen
D805,968 S	12/2017	Piscitelli et al.	D909,934 S	2/2021	Gander et al.
D813,757 S	3/2018	Kozub	D910,502 S	2/2021	Duncan et al.
D813,758 S	3/2018	Gonzales	10,906,396 B1	2/2021	Schimke et al.
D815,574 S	4/2018	Mainville	D911,883 S	3/2021	Bae
D818,885 S	5/2018	Seo	D914,562 S	3/2021	Kirkman et al.
D820,179 S	6/2018	Kladde	D915,252 S	4/2021	Duncan et al.
D823,182 S	7/2018	Yates	10,978,039 B2	4/2021	Seffernick et al.
D823,183 S	7/2018	Yates	10,981,538 B2	4/2021	Archer et al.
D824,294 S	7/2018	Ge et al.	10,987,829 B2	4/2021	Datema et al.
10,023,243 B2	7/2018	Hines et al.	D919,527 S	5/2021	Bender et al.
10,030,737 B2	7/2018	Dillman et al.	D922,916 S	6/2021	Koo
D824,806 S	8/2018	Knox	D924,740 S	7/2021	Zhao et al.
D824,811 S	8/2018	Mainville	D925,416 S	7/2021	Duncan et al.
D824,814 S	8/2018	Heyde	D925,421 S	7/2021	Mallicote et al.
D827,410 S	9/2018	Earley	D926,093 S	7/2021	McMath
D828,258 S	9/2018	Zipfel	D926,642 S	8/2021	Duncan et al.
D830,242 S	10/2018	Zipfel	D928,672 S	8/2021	Gander et al.
D837,106 S	1/2019	Yang	D929,913 S	9/2021	Gander
D837,702 S	1/2019	Gander et al.	D930,862 S	9/2021	Gander et al.
D839,164 S	1/2019	Zipfel	D932,397 S	10/2021	Kaneko et al.
10,184,553 B2	1/2019	Kwiatkowski et al.	D933,545 S	10/2021	Piaskowski et al.
D842,183 S	3/2019	Jackson et al.	D933,547 S	10/2021	Hamilton et al.
D843,281 S	3/2019	Gander et al.	D934,306 S	10/2021	Boone et al.
D849,283 S	5/2019	Lin	D934,745 S	11/2021	Kentley-Klay et al.
D850,676 S	6/2019	Lin	D934,766 S	11/2021	Duncan et al.
D853,285 S	7/2019	Yang	D935,962 S	11/2021	Grand
D853,293 S	7/2019	Heroux et al.	D935,965 S	11/2021	Yang
D856,860 S	8/2019	Gander	D935,966 S	11/2021	Bibb
10,369,860 B2	8/2019	Ellifson et al.	D936,529 S	11/2021	Tang et al.
10,392,056 B2	8/2019	Perron et al.	11,173,959 B2	11/2021	Chalifour
D859,226 S	9/2019	Grooms	11,181,345 B2	11/2021	Krueger et al.
D860,887 S	9/2019	Gander et al.	D939,393 S	12/2021	Jevremovic
10,421,332 B2	9/2019	Venton-Walters et al.	D940,605 S	1/2022	Sheffield et al.
D862,752 S	10/2019	Lai	D940,607 S	1/2022	Park et al.
D863,144 S	10/2019	Gander	D941,195 S	1/2022	Koo et al.
D864,031 S	10/2019	Gander et al.	D942,340 S	2/2022	Hallgren
D864,802 S	10/2019	Davis et al.	D944,136 S	2/2022	De Leon
10,434,995 B2	10/2019	Verhoff et al.	D945,335 S	3/2022	Duncan et al.
10,435,026 B2	10/2019	Shively et al.	11,260,835 B2	3/2022	Verhoff et al.
D865,601 S	11/2019	Goodrich et al.	11,273,804 B2	3/2022	Verhoff et al.
D867,951 S	11/2019	Izard	11,273,805 B2	3/2022	Verhoff et al.
D869,332 S	12/2019	Gander et al.	D952,536 S	5/2022	Finney et al.
D871,283 S	12/2019	Gander et al.	11,332,104 B2	5/2022	Verhoff et al.
10,495,419 B1	12/2019	Krueger et al.	D955,946 S	6/2022	Kirkman et al.
10,609,874 B1	4/2020	Shumaker	11,364,882 B2	6/2022	Verhoff et al.
10,611,203 B1	4/2020	Rositch et al.	D960,059 S	8/2022	Mallicote et al.
10,611,204 B1	4/2020	Zhang et al.	D961,478 S	8/2022	Hoste et al.
10,619,696 B2	4/2020	Dillman et al.	D966,161 S	10/2022	Ruiz et al.
10,632,805 B1	4/2020	Rositch et al.	D980,145 S	3/2023	Schwartz et al.
D883,876 S	5/2020	Beasley et al.	D1,000,652 S	10/2023	Wu
D885,281 S	5/2020	Duncan et al.	D1,004,510 S	11/2023	Bryant et al.
D887,050 S	6/2020	Lin	D1,010,520 S	1/2024	Bjerke
D888,629 S	6/2020	Gander et al.	D1,016,683 S	3/2024	Heilaneh et al.
D891,331 S	7/2020	Dickman et al.	D1,020,557 S	4/2024	Lin
D892,002 S	8/2020	Gander	D1,020,560 S	4/2024	Lin
D893,066 S	8/2020	Lin	D1,022,063 S	4/2024	Ye
D894,063 S	8/2020	Dionisopoulos et al.	D1,025,848 S	5/2024	Piaskowski et al.
D894,442 S	8/2020	Lin	D1,027,731 S	5/2024	Lee
10,752,075 B1	8/2020	Shukla et al.	D1,029,703 S	6/2024	Powell et al.
D897,010 S	9/2020	Momokawa	D1,029,705 S	6/2024	Gound
			D1,030,557 S	6/2024	Willing et al.
			D1,031,105 S	6/2024	Wu
			D1,032,414 S	6/2024	Ecuyer et al.
			D1,033,282 S	7/2024	Kim et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

D1,034,320 S	7/2024	Tsuchida et al.	2006/0201727 A1	9/2006	Chan
D1,034,325 S	7/2024	Kaban et al.	2006/0244225 A1	11/2006	Power et al.
D1,034,347 S	7/2024	Moffett	2006/0249325 A1	11/2006	Braun et al.
D1,034,839 S	7/2024	Ye	2006/0273566 A1	12/2006	Hepner et al.
D1,036,321 S	7/2024	Duncan et al.	2007/0088469 A1	4/2007	Schmiedel et al.
D1,037,088 S	7/2024	Demkiw et al.	2007/0102963 A1	5/2007	Frederick et al.
D1,037,960 S	8/2024	Sicot	2007/0120334 A1	5/2007	Holbrook
D1,039,432 S	8/2024	Badstuebner et al.	2007/0145816 A1	6/2007	Gile
D1,039,433 S	8/2024	Badstuebner et al.	2007/0158920 A1	7/2007	Delaney
D1,040,056 S	8/2024	George	2007/0186762 A1	8/2007	Dehart et al.
D1,040,057 S	8/2024	George	2007/0234896 A1	10/2007	Joynt
D1,040,691 S	9/2024	Armigliato et al.	2007/0246902 A1	10/2007	Trudeau et al.
D1,040,870 S	9/2024	Armigliato et al.	2007/0288131 A1	12/2007	Yakes et al.
D1,042,226 S	9/2024	Lee	2007/0291130 A1	12/2007	Broggi et al.
D1,042,229 S	9/2024	Kuhlmann	2008/0017426 A1	1/2008	Walters et al.
D1,042,249 S	9/2024	Wu	2008/0017434 A1	1/2008	Harper et al.
D1,042,251 S	9/2024	Willing et al.	2008/0034953 A1	2/2008	Barbe et al.
D1,043,472 S	9/2024	Wu	2008/0041048 A1	2/2008	Kanenobu et al.
D1,044,612 S	10/2024	Wu	2008/0053739 A1	3/2008	Chernoff et al.
D1,049,949 S	11/2024	Montoya Bueloni et al.	2008/0059014 A1	3/2008	Nasr et al.
D1,049,958 S	11/2024	Oh	2008/0065285 A1	3/2008	Yakes et al.
D1,055,788 S	12/2024	Young et al.	2008/0066613 A1	3/2008	Mills et al.
D1,059,229 S	1/2025	Kobayashi	2008/0071438 A1	3/2008	Nasr et al.
D1,061,966 S	2/2025	Wu	2008/0099213 A1	5/2008	Morrow et al.
D1,063,727 S	2/2025	Wu	2008/0150350 A1	6/2008	Morrow et al.
D1,063,728 S	2/2025	Wu	2008/0252025 A1	10/2008	Plath
D1,063,733 S	2/2025	Willing et al.	2008/0284118 A1	11/2008	Venton-Walters et al.
2001/0015559 A1	8/2001	Storer	2008/0315629 A1	12/2008	Abe et al.
2002/0103580 A1	8/2002	Yakes et al.	2009/0001761 A1	1/2009	Yasuhsara et al.
2002/0119364 A1	8/2002	Bushong et al.	2009/0033044 A1	2/2009	Linsmeier
2002/0129696 A1	9/2002	Pek et al.	2009/0061702 A1	3/2009	March
2002/0130771 A1	9/2002	Osborne et al.	2009/0079839 A1	3/2009	Fischer et al.
2002/0153183 A1	10/2002	Puterbaugh et al.	2009/0088283 A1	4/2009	Schimke
2002/0190516 A1	12/2002	Henksmeier et al.	2009/0127010 A1	5/2009	Morrow et al.
2003/0001346 A1	1/2003	Hamilton et al.	2009/0174158 A1	7/2009	Anderson et al.
2003/0155164 A1	8/2003	Mantini et al.	2009/0194347 A1	8/2009	Morrow et al.
2003/0158638 A1	8/2003	Yakes et al.	2009/0227410 A1	9/2009	Zhao et al.
2003/0205422 A1	11/2003	Morrow et al.	2009/0322123 A1	12/2009	Tanaka et al.
2003/0230863 A1	12/2003	Archer	2010/0019538 A1	1/2010	Kiley et al.
2004/0069553 A1	4/2004	Ohashi et al.	2010/0026046 A1	2/2010	Mendoza et al.
2004/0074686 A1	4/2004	Abend et al.	2010/0032932 A1	2/2010	Hastings
2004/0113377 A1	6/2004	Klees	2010/0116569 A1	5/2010	Morrow et al.
2004/0130168 A1	7/2004	O'Connell	2010/0123324 A1	5/2010	Shoup et al.
2004/0133332 A1	7/2004	Yakes et al.	2010/0163330 A1	7/2010	Halliday
2004/0145344 A1	7/2004	Bushong et al.	2010/0187864 A1	7/2010	Tsuchida
2004/0149500 A1	8/2004	Chernoff et al.	2010/0218667 A1	9/2010	Naroditsky et al.
2004/0245039 A1	12/2004	Braun et al.	2010/0264636 A1	10/2010	Fausch et al.
2004/0256024 A1	12/2004	Schlachter	2010/0301668 A1	12/2010	Yakes et al.
2005/0001400 A1	1/2005	Archer et al.	2010/0307328 A1	12/2010	Hoadley et al.
2005/0034911 A1	2/2005	Darby	2010/0307329 A1	12/2010	Kaswen et al.
2005/0062239 A1	3/2005	Shore	2010/0319525 A1	12/2010	Pavon
2005/0093265 A1	5/2005	Niaura et al.	2011/0045930 A1	2/2011	Schimke
2005/0099885 A1	5/2005	Tamminga	2011/0068606 A1	3/2011	Klimek et al.
2005/0109553 A1	5/2005	Ishii et al.	2011/0079134 A1	4/2011	Jacquemont et al.
2005/0110229 A1	5/2005	Kimura et al.	2011/0079978 A1	4/2011	Schreiner et al.
2005/0113988 A1	5/2005	Nasr et al.	2011/0114409 A1	5/2011	Venton-Walters
2005/0119806 A1	6/2005	Nasr et al.	2011/0120791 A1	5/2011	Greenwood et al.
2005/0132873 A1	6/2005	Diaz Supisiche et al.	2011/0169240 A1	7/2011	Schreiner et al.
2005/0161891 A1	7/2005	Trudeau et al.	2011/0266838 A1	11/2011	Leopold
2005/0191542 A1	9/2005	Bushong et al.	2011/0291444 A1	12/2011	Ische
2005/0196269 A1	9/2005	Racer et al.	2011/0314999 A1	12/2011	Luther et al.
2005/0209747 A1	9/2005	Yakes et al.	2012/0049470 A1	3/2012	Rositch et al.
2005/0284682 A1	12/2005	Hass et al.	2012/0049570 A1	3/2012	Aizik
2006/0021541 A1	2/2006	Siebers et al.	2012/0083380 A1	4/2012	Reed et al.
2006/0021764 A1	2/2006	Archer et al.	2012/0097019 A1	4/2012	Sherbeck et al.
2006/0048986 A1	3/2006	Bracciano	2012/0098172 A1	4/2012	Trinh et al.
2006/0065451 A1	3/2006	Morrow et al.	2012/0098215 A1	4/2012	Rositch et al.
2006/0065453 A1	3/2006	Morrow et al.	2012/0111180 A1	5/2012	Johnson et al.
2006/0070776 A1	4/2006	Morrow et al.	2012/0143430 A1	6/2012	Broggi et al.
2006/0070788 A1	4/2006	Schimke	2012/0174767 A1	7/2012	Naroditsky et al.
2006/0071466 A1	4/2006	Rowe et al.	2012/0181100 A1	7/2012	Halliday
2006/0082079 A1	4/2006	Eichhorn et al.	2012/0186428 A1	7/2012	Peer et al.
2006/0116032 A1	6/2006	Roering	2012/0192706 A1	8/2012	Gonzalez
2006/0192354 A1	8/2006	Van Cayzele	2012/0193940 A1	8/2012	Tunis et al.
2006/0192361 A1	8/2006	Anderson et al.	2013/0009423 A1	1/2013	Yamamoto et al.
			2013/0014635 A1	1/2013	Kosheleff
			2013/0093154 A1	4/2013	Cordier et al.
			2013/0153314 A1	6/2013	Niedzwiecki
			2013/0205984 A1	8/2013	Henker et al.

(56)

**References Cited****U.S. PATENT DOCUMENTS**

2013/0241237 A1 9/2013 Dziuba et al.  
 2013/0249175 A1 9/2013 Ellifson  
 2013/0249183 A1 9/2013 Ellifson et al.  
 2013/0263729 A1 10/2013 Johnson et al.  
 2013/0264784 A1 10/2013 Venton-Walters et al.  
 2013/0312595 A1 11/2013 Lee  
 2014/0035325 A1 2/2014 Naito et al.  
 2014/0060304 A1 3/2014 Harmon et al.  
 2014/0131969 A1 5/2014 Rowe et al.  
 2014/0151142 A1 6/2014 Hoppe et al.  
 2014/0232082 A1 8/2014 Oshita et al.  
 2014/0251742 A1 9/2014 Dillman et al.  
 2014/0255136 A1 9/2014 Malcolm et al.  
 2014/0262591 A1 9/2014 Turner et al.  
 2014/0265203 A1 9/2014 Zuleger et al.  
 2014/0291945 A1 10/2014 Venton-Walters et al.  
 2014/0326555 A1 11/2014 Ellifson et al.  
 2015/0028529 A1 1/2015 Ellifson  
 2015/0191069 A1 7/2015 Zuleger et al.  
 2015/0197129 A1 7/2015 Venton-Walters et al.  
 2015/0224847 A1 8/2015 Rowe et al.  
 2015/0283889 A1 10/2015 Agnew  
 2015/0306954 A1 10/2015 Matsuura et al.  
 2016/0009231 A1 1/2016 Perron et al.  
 2016/0047631 A1 2/2016 Berman  
 2016/0144211 A1 5/2016 Betz et al.  
 2016/0167475 A1 6/2016 Ellifson et al.  
 2016/0208883 A1 7/2016 Dillman et al.  
 2016/0257360 A1 9/2016 Mackenzie et al.  
 2016/0304051 A1 10/2016 Archer et al.  
 2016/0347137 A1 12/2016 Despres-Nadeau et al.  
 2016/0368432 A1 12/2016 Perron et al.  
 2016/0375805 A1 12/2016 Krueger et al.  
 2017/0028844 A1 2/2017 Melone et al.  
 2017/0137076 A1 5/2017 Perron et al.  
 2017/0253221 A1 9/2017 Verhoff et al.  
 2017/0259666 A1 9/2017 Weber et al.  
 2017/0267052 A1 9/2017 Zuleger et al.  
 2017/0282670 A1 10/2017 Venton-Walters et al.  
 2017/0291802 A1 10/2017 Hao et al.  
 2017/0291805 A1 10/2017 Hao et al.  
 2017/0297425 A1 10/2017 Wildgrube et al.  
 2017/0328054 A1 11/2017 Bakken  
 2017/0355400 A1 12/2017 Weston  
 2017/0361491 A1 12/2017 Datema et al.  
 2017/0361492 A1 12/2017 Datema et al.  
 2018/0001839 A1 1/2018 Perron et al.  
 2018/0056746 A1 3/2018 Ellifson et al.  
 2018/0162704 A1 6/2018 Hao et al.  
 2018/0222481 A1 8/2018 Okada et al.  
 2018/0222484 A1 8/2018 Shively et al.  
 2018/0326843 A1 11/2018 Danielson et al.  
 2018/0335104 A1 11/2018 Dillman et al.  
 2019/0039407 A1 2/2019 Smith  
 2019/0106083 A1 4/2019 Archer et al.  
 2019/0118875 A1 4/2019 Perron et al.  
 2019/0145465 A1 5/2019 Olason  
 2019/0185077 A1 6/2019 Smith et al.  
 2019/0185301 A1 6/2019 Hao et al.  
 2019/0276102 A1 9/2019 Zuleger et al.  
 2019/0316650 A1 10/2019 Dillman et al.  
 2019/0322321 A1 10/2019 Schwartz et al.  
 2019/0337348 A1 11/2019 Oshkosh  
 2019/0337350 A1 11/2019 Ellifson et al.  
 2019/0344475 A1 11/2019 Datema et al.  
 2019/0344838 A1 11/2019 Perron et al.  
 2019/0351883 A1 11/2019 Verhoff et al.  
 2019/0352157 A1 11/2019 Hao et al.  
 2019/0355339 A1 11/2019 Seffernick et al.  
 2020/0062071 A1 2/2020 Zuleger et al.  
 2020/0094671 A1 3/2020 Wildgrube et al.  
 2020/0223276 A1 7/2020 Rositch et al.  
 2020/0223277 A1 7/2020 Zhang et al.  
 2020/0232533 A1 7/2020 Dillman et al.  
 2020/0254840 A1 8/2020 Rositch et al.

2020/0290237 A1 9/2020 Steffens et al.  
 2020/0291846 A1 9/2020 Steffens et al.  
 2020/0316816 A1 10/2020 Messina et al.  
 2020/0317083 A1 10/2020 Messina et al.  
 2020/0346547 A1 11/2020 Rocholl et al.  
 2020/0346855 A1 11/2020 Rocholl et al.  
 2020/0346857 A1 11/2020 Rocholl et al.  
 2020/0346861 A1 11/2020 Rocholl et al.  
 2020/0346862 A1 11/2020 Rocholl et al.  
 2020/0347659 A1 11/2020 Rocholl et al.  
 2020/0391569 A1 12/2020 Zuleger  
 2020/0399107 A1 12/2020 Buege et al.  
 2021/0031611 A1 2/2021 Yakes et al.  
 2021/0031612 A1 2/2021 Yakes et al.  
 2021/0031649 A1 2/2021 Messina et al.  
 2021/0107361 A1 4/2021 Linsmeier et al.  
 2021/0213642 A1 7/2021 Datema et al.  
 2021/0221190 A1 7/2021 Rowe  
 2021/0221216 A1 7/2021 Yakes et al.  
 2021/0225349 A1 7/2021 Seffernick et al.  
 2021/0229755 A1 7/2021 Schwartz et al.  
 2021/0380085 A1 12/2021 Verhoff et al.  
 2022/0176921 A1 6/2022 Verhoff et al.  
 2022/0194333 A1 6/2022 Verhoff et al.  
 2022/0194334 A1 6/2022 Verhoff et al.

**FOREIGN PATENT DOCUMENTS**

CA 2724324 11/2009  
 CA 2809527 A1 9/2013  
 CA 2852786 A1 11/2013  
 CN 201371806 Y 12/2009  
 CN 201463718 U 5/2010  
 DE 11 86 334 1/1965  
 DE 36 20 603 A1 1/1987  
 DE 10 2008 062 340 A1 6/2010  
 DE 10 2008 052 072 B4 4/2011  
 EP 0 685 382 A1 12/1995  
 EP 1 229 636 A2 8/2002  
 EP 1 633 619 B1 6/2004  
 EP 1 371 391 B1 12/2009  
 EP 2 413 089 A2 2/2012  
 FR 1471914 A 3/1967  
 FR 2380176 A1 9/1978  
 GB 2 168 015 A0 6/1986  
 GB 2 365 829 9/2004  
 GB 2 400 588 A 1/2005  
 GB 2 400 589 A 2/2005  
 GB 2 400 590 A 3/2005  
 GB 2 545 187 A 6/2017  
 HK 1088583 10/2007  
 JP 4230421 B2 8/1992  
 JP 06-037090 5/1994  
 JP 2906249 B2 6/1999  
 JP 2005-007995 A 1/2005  
 JP 2005-212698 A 8/2005  
 JP 2006-056463 A 3/2006  
 JP 2012-096557 A 5/2012  
 WO WO-91/08939 A1 6/1991  
 WO WO-01/76912 A1 10/2001  
 WO WO-03/049987 A2 6/2003  
 WO WO-2007/140179 A2 12/2007  
 WO WO-2015/061840 A1 5/2015

**OTHER PUBLICATIONS**

Oshkosh Defense Highlights Advanced Technology Capabilities At Modern Day Marine 2022. May 10, 2022. Oshkosh Defense. <https://oshkoshdefense.com/oshkosh-defense-highlights-advanced-technology-capabilities-at-modern-day-marine-2022/>.  
 US Army Contradictions Muddy Humvee-Replacement Plan. Mar. 21, 2019. Defense One. <https://www.defenseone.com/business/2019/03/US-armys-contradictory-statements-leave-jltv-plan-unclear/155707/>.  
 U.S. Appl. No. 10/171,075, filed Jun. 13, 2002, Archer et al.  
 U.S. Appl. No. 14/532,679, filed Nov. 4, 2014, Oshkosh Corporation.

(56)

**References Cited****OTHER PUBLICATIONS**

U.S. Appl. No. 29/680,745, filed Feb. 19, 2019, Oshkosh Corporation.

U.S. Appl. No. 29/683,330, filed Mar. 12, 2019, Oshkosh Corporation.

U.S. Appl. No. 29/683,333, filed Mar. 12, 2019, Oshkosh Corporation.

U.S. Appl. No. 29/700,665, filed Aug. 5, 2019, Oshkosh Corporation.

U.S. Appl. No. 29/706,533, filed Sep. 20, 2019, Oshkosh Corporation.

U.S. Appl. No. 29/706,547, filed Sep. 20, 2019, Oshkosh Corporation.

"Military Troop Transport Truck." Sep. 14, 2012. Deviant Art. <https://www.deviantart.com/shitalloverhumanity/art/Military-Troop-Transport-Truck-327166456>.

"New Oshkosh JL TV Next to an Old Humvee." May 2, 2017. ReddIt. [https://www.reddil.com/r/MilitaryPorn/comments/8jflee/new\\_oshkoshjltv\\_next\\_to\\_an\\_old\\_humvee\\_hmmwv\\_may/](https://www.reddil.com/r/MilitaryPorn/comments/8jflee/new_oshkoshjltv_next_to_an_old_humvee_hmmwv_may/).

"Troop Transport Truck Tutorial." Jun. 13, 2009. Dave Taylor Miniatures. <http://davetaylorminiatures.blogspot.com/2009/06/troop-transport-truck-tutorial-part-one.html>.

1953-56 Ford F100 Pickup 3 Inch Wider Right Rear Fenders. 1956. eBay. <https://www.ebay.com/p/710218145>.

2019 Nissan NV1500 Cargo Consumer Reviews, Kelley Blue Book, Apr. 14, 2021, 12 pages, <https://www.kbb.com/nissan/nv1500-cargo/2019/consumer-reviews/>.

Feeburg, Elisabet. "Mine-Resistant, Ambush-Protected All-Terrain Vehicle", 2009. Britannica, <https://www.britannica.com/technology/armoured-vehicle/Wheeled-armoured-vehicles>.

Grille Designs, Questel, orbit.com, Retrieved Apr. 14, 2021, 26 pages. <https://www.army-technology.com/news/newslenco-bear-troop-transport-armoured-vehicle/>"Lenco Completes Blast Test for BEAR Troop Transport Armoured Vehicle." Aug. 16, 2013. Army Technology.

Huddleston, Scott. "Fortified Tactical Vehicle Offered to Replace Military Humvee." Jan. 4, 2014. My San Antonio. <https://www.mysanantonio.com/news/local/military/article/Fortified-tactical-vehicle-offered-to-replace-5109387.php#photo-5673528>.

Iriarte, Mariana. "Power Distribution from the Ground Up." Nov. 9, 2016. Military Embedded Systems. <https://militaryembedded.com/comms/communications/power-distribution-the-ground-up>.

MD Juan CFA005 Front Fender for 52-75 Jeep. 1975. Quadratec. <https://quadratec.com/p/md-juan/front-fender-cj5-cj6-m38a1>.

Miller, Stephen W., "The MRAP Story: Learning from History", Asian Military Review, Oct. 30, 2018, 9 pages.

Rear Fender Fiberglass Pick Up Truck 1947-1963. 1963. Walck's 4 Wheel Drive. [https://walcks4wd.com/Rear-Fender-Fiberglass-Pick-Up-Truck-1947-1963\\_p\\_1780.html](https://walcks4wd.com/Rear-Fender-Fiberglass-Pick-Up-Truck-1947-1963_p_1780.html).

Vehicle fenders. (Design—Questel) orbit.com. [Online PDF compilation of references selected by examiner] 34 pgs. Print Dates Range Apr. 14, 2022—Nov. 8, 2019 [Retrieved Nov. 18, 2022].

Vehicle Headlights. (Design—Questel) orbit.com. [online PDF] 38 pgs. Print Dates Range Mar. 19, 2021—May 23, 2019 [Retrieved Apr. 23, 2021].

Vehicle Hood (Design -Questel) orbit.com. [Online PDF compilation of references selected by examiner] 42 pgs. Print Dates Range Mar. 24, 2021—Jul. 22, 2020 [Retrieved Dec. 13, 2021].

Jen Judson, "Oshkosh unveils hybrid electric Joint Light Tactical Vehicle". Jan. 25, 2022. Defense News. <https://www.defensenews.com/land/2022/01/25/oshkosh-unveils-hybrid-electric-joint-light-tactical-vehicle/>.

Staff Sgt. Tawny Kruse, "A vehicle of the future Iowa training center receives new tactical vehicles". May 7, 2023. DVIDS. <https://www.dvidshub.net/news/448328/vehicle-future-iowa-training-center-receives-new-tactical-vehicles>.

Todd South, "The newly fielded Joint Light Tactical Vehicle was briefly deemed 'not operationally suitable'". Feb. 22, 2019. Army Times. <https://www.armytimes.com/news/your-army/2019/02/22/the-newly-fielded-joint-light-tactical-vehicle-is-not-operationally-suitable/>.






FIG. 1




FIG. 2





FIG. 3



**FIG. 4**




FIG. 5




FIG. 6






FIG. 7






FIG. 10A





FIG. 10B



**FIG. 11**






FIG. 12

# 1

## MILITARY VEHICLE

### CROSS-REFERENCE TO RELATED PATENT APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 17/718,535, filed Apr. 12, 2022, which is a continuation of U.S. patent application Ser. No. 17/398,581, filed Aug. 10, 2021, which is a continuation of U.S. patent application Ser. No. 16/529,508, filed Aug. 1, 2019, which is a continuation of U.S. patent application Ser. No. 15/599,174, filed May 18, 2017, which is a continuation of U.S. patent application Ser. No. 14/724,279, filed May 28, 2015, which is a continuation of U.S. patent application Ser. No. 13/841,686, filed Mar. 15, 2013, which claims the benefit of U.S. Provisional Patent Application No. 61/615,812, filed Mar. 26, 2012, all of which are incorporated herein by reference in their entireties.

### BACKGROUND

The present application relates to vehicles. In particular, the present application relates to the structural frame assembly of a military vehicle.

A military vehicle may be used in a variety of applications and conditions. These vehicles generally include a number of vehicle systems or components (e.g., a cab or body, a drive train, etc.). The military vehicle may also include various features and systems as needed for the specific application of the vehicle (e.g., a hatch, a gun ring, an antenna, etc.). Proper functioning and arrangement of the vehicle systems or components is important for the proper functioning of the vehicle.

Traditional military vehicles include a cab assembly coupled to a pair of frame rails that extend along the length of the vehicle. The drive train, engine, and other components of the vehicle are coupled to the frame rails. Such vehicles may be transported by securing lifting slings to the frame rails and applying a lifting force (e.g., with a crane, with a helicopter, etc.). As the frame rails are the primary structure of the vehicle, a lifting force applied to a rear portion and a front portion elevate the vehicle from a ground surface. In such a configuration, the components of the vehicle must be coupled to the structural frame rails thereby requiring sequential assembly.

### SUMMARY

One embodiment relates to a military vehicle assembly. The military vehicle assembly includes a rear module. The rear module includes a rear frame assembly, a bed supported by the rear frame assembly, a rear tractive assembly, a transaxle supported by the rear frame assembly and coupled to the rear tractive assembly, and a rear suspension system including at least one component extending between a housing of the transaxle and the rear tractive assembly. The rear frame assembly has one or more upper interfaces and one or more lower interfaces. The one or more upper interfaces are configured to detachably couple to a rear end of a passenger capsule of a military vehicle. The one or more lower interfaces are configured to detachably couple to a bottom of the passenger capsule. The transaxle is configured to couple to a prime mover and a front differential of the military vehicle.

Another embodiment relates to a military vehicle assembly. The military vehicle assembly includes a rear module. The rear module includes a rear frame assembly, a rear

2

tractive assembly, a transaxle supported by the rear frame assembly and coupled to the rear tractive assembly, and a rear suspension system including at least one component extending between a housing of the transaxle and the rear tractive assembly. The rear frame assembly has one or more upper interfaces and one or more lower interfaces. The one or more upper interfaces are configured to detachably couple to a rear end of a passenger capsule of a military vehicle. The one or more lower interfaces are configured to detachably couple to a bottom of the passenger capsule. The transaxle is configured to couple to a prime mover and a front differential of the military vehicle.

Still another embodiment relates to a military vehicle assembly. The military vehicle assembly includes a rear module and a suspension control system. The rear module includes a rear frame assembly, a rear tractive assembly, a transaxle supported by the rear frame assembly, and a rear suspension system. The rear frame assembly has one or more upper interfaces and one or more lower interfaces. The one or more upper interfaces are configured to detachably couple to a rear end of a passenger capsule of a military vehicle. The one or more lower interfaces are configured to detachably couple to a bottom of the passenger capsule. The transaxle is coupled to the rear tractive assembly. The transaxle is configured to couple to a prime mover and a front differential of the military vehicle. The rear suspension system includes a pair of gas springs and a pair of hydraulic dampers. The pair of hydraulic dampers are cross-plumbed to provide a hydraulic body roll control function. The suspension control system is configured to monitor a ride height of the military vehicle and control the pair of gas springs to adjust the ride height as load is added to or removed from the military vehicle.

The invention is capable of other embodiments and of being carried out in various ways. Alternative exemplary embodiments relate to other features and combinations of features as may be recited in the claims.

### BRIEF DESCRIPTION OF THE DRAWINGS

The disclosure will become more fully understood from the following detailed description, taken in conjunction with the accompanying figures, wherein like reference numerals refer to like elements, in which:

FIGS. 1-2 are a perspective views of a vehicle, according to an exemplary embodiment.

FIG. 3 is a schematic side view of the vehicle of FIG. 1, according to an exemplary embodiment.

FIGS. 4-6 are perspective views of a vehicle having a passenger capsule, a front module, and a rear module, according to an exemplary embodiment.

FIGS. 7-9 are perspective views of a vehicle having a passenger capsule, a front module, and a rear module, according to an alternative embodiment.

FIG. 10A is a schematic sectional view of a vehicle having at least a portion of a suspension system coupled to a transaxle, according to an exemplary embodiment, and FIG. 10B is schematic sectional view of a vehicle having a passenger capsule, according to an exemplary embodiment.

FIG. 11 is schematic view of a braking system for a vehicle, according to an exemplary embodiment.

FIG. 12 is schematic view of a vehicle control system, according to an exemplary embodiment.

### DETAILED DESCRIPTION

Before turning to the figures, which illustrate the exemplary embodiments in detail, it should be understood that the

present application is not limited to the details or methodology set forth in the description or illustrated in the figures. It should also be understood that the terminology is for the purpose of description only and should not be regarded as limiting.

Referring to FIGS. 1-3, a military vehicle **1000** includes a hull and frame assembly **100**, an armor assembly **200**, an engine **300**, a transmission **400**, a transaxle **450**, wheel and tire assemblies **600**, a braking system **700**, a fuel system **800**, and a suspension system **460** coupling the hull and frame assembly **100** to the wheel and tire assemblies **600**. According to an exemplary embodiment, the military vehicle **1000** includes a power generation system **900**. As shown in FIG. 1, the military vehicle **1000** also includes a trailer **1100**.

#### Hull and Frame Assembly

Referring to FIG. 2, the hull and frame assembly **100** includes a passenger capsule, shown as passenger capsule **110**, a front module, shown as front module **120**, and a rear module, shown as rear module **130**. According to an exemplary embodiment, the front module **120** and the rear module **130** are coupled to the passenger capsule **110** with a plurality of interfaces. As shown in FIG. 2, the front module **120** includes a front axle having wheel and tire assemblies **600**.

According to an exemplary embodiment, the rear module **130** includes a body assembly, shown as bed **132**. As shown in FIG. 2, front module **120** also includes a body panel, shown as hood **122**. In some embodiments, the hood **122** partially surrounds the engine of military vehicle **1000**. The hood **122** is constructed of a composite material (e.g., carbon fiber, fiberglass, a combination of fiberglass and carbon fiber, etc.) and sculpted to maximize vision and clear under-hood components. According to an alternative embodiment, the hood **122** is manufactured from another material (e.g., steel, aluminum, etc.). The front portion of hood **122** mounts to a lower cooling package frame, and the upper mount rests on the windshield wiper cowl. This mounting configuration reduces the number and weight of components needed to mount the hood **122**. The Oshkosh Corporation® logo is mounted to a frame structure, which is itself mounted directly to the cooling package. The hood **122** includes bumperettes **123** that provide mounting locations for antennas (e.g., a forward-facing IED jammer, a communications whip antenna, etc.). In one embodiment, the bumperettes **123** and front of the hood **122** may be reinforced (e.g., with structural fibers, structural frame members, etc.) to become structural members intended to prevent damage to the tire assemblies **600**. In an alternative embodiment, the bumperettes **123** may be crushable members or “break away” members that disengage upon impact to prevent interference between the bumperettes **123** and tire assemblies **600** in the event of a front impact.

Referring next to the exemplary embodiment shown in FIGS. 4-9, the military vehicle **1000** includes passenger capsule **110**, front module **120**, and rear module **130**. As shown in FIGS. 4 and 7, passenger capsule **110** includes a structural shell **112** that forms a monocoque hull structure. Monocoque refers to a form of vehicle construction in which the vehicle body and chassis form a single unit. The structural shell **112** is configured to provide a structural load path between front module **120** and rear module **130** of military vehicle **1000** (e.g., during driving, a lifting operation, during a blast event, etc.). According to an exemplary embodiment, the structural shell **112** includes a plurality of integrated armor mounting points configured to engage a supplemental armor kit (e.g., a “B-Kit,” etc.). The structural shell **112** is rigidly connected to the rest of the powertrain, drivetrain, suspension, and major systems such that they all absorb blast

energy during a blast event, according to an exemplary embodiment. According to an exemplary embodiment, the structural shell **112** is large enough to contain four-passengers in a standard two-by-two seating arrangement and four doors **104** are rotatably mounted to the structural shell **112**. According to the alternative embodiment shown in FIGS. 7-9, two doors **104** are coupled to structural shell **112**. Front module **120** and rear module **130** are configured to engage a passenger capsule having either two doors or four doors, according to an exemplary embodiment. As shown in FIGS. 6 and 9, the structural shell **112** includes a first end **114** and a second end **116**.

According to an exemplary embodiment, front module **120** includes a subframe having a first longitudinal frame member **124** and a second longitudinal frame member **126**. As shown in FIGS. 4-9, an underbody support structure **128** is coupled to the first longitudinal frame member **124** and the second longitudinal frame member **126**. According to an exemplary embodiment, the first longitudinal frame member **124** and the second longitudinal frame member **126** extend within a common plane (e.g., a plane parallel to a ground surface). The underbody support structure **128** is coupled to the first end **114** of structural shell **112** and includes a plurality of apertures **129** that form tie down points. In some embodiments, an engine for the military vehicle **1000** is coupled to the first longitudinal frame member **124** and the second longitudinal frame member **126**. In other embodiments, the front module **120** includes a front axle assembly coupled to the first longitudinal frame member **124** and the second longitudinal frame member **126**.

As shown in FIGS. 4 and 6, rear module **130** includes a subframe having a first longitudinal frame member **134** and a second longitudinal frame member **136**. As shown in FIGS. 4-9, an underbody support structure **138** is coupled to the first longitudinal frame member **134** and the second longitudinal frame member **136**. According to an exemplary embodiment, the first longitudinal frame member **134** and the second longitudinal frame member **136** extend within a common plane (e.g., a plane parallel to a ground surface). The underbody support structure **138** is coupled to the second end **116** of structural shell **112**, the first longitudinal frame member **134**, and the second longitudinal frame member **136**. According to an exemplary embodiment, the first longitudinal frame member **134** and the second longitudinal frame member **136** include a plurality of apertures **139** that form tie down points. In some embodiments, a transaxle **450** or a differential for the military vehicle **1000** is coupled to at least one of the first longitudinal frame member **134** and the second longitudinal frame member **136**. In other embodiments, the rear module **130** includes a rear axle assembly coupled to the first longitudinal frame member **134** and the second longitudinal frame member **136**.

The subframes of the front module **120** and the rear module **130** may be manufactured from High Strength Steels (HSS), high strength aluminum, or another suitable material. According to an exemplary embodiment, the subframes feature a tabbed, laser cut, bent and welded design. In other embodiments, the subframes may be manufactured from tubular members to form a space frame. The subframe may also include forged, rather than fabricated or cast frame sections to mitigate the stress, strains, and impact loading imparted during operation of military vehicle **1000**. Aluminum castings may be used for various cross member components where the loading is compatible with material properties. Low cost aluminum extrusions may be used to tie and box structures together.

The structural shell **112** and the subframes of the front module **120** and the rear module **130** are integrated into the hull and frame assembly **100** to efficiently carry chassis loading imparted during operation of the military vehicle **1000**, during a lift event, during a blast event, or under still other conditions. During a blast event, conventional frame rails can capture the blast force transferring it into the vehicle. Military vehicle **1000** replaces conventional frame rails and instead includes passenger capsule **110**, front module **120**, and rear module **130**. The passenger capsule **110**, front module **120**, and rear module **130** provides a vent for the blast gases (e.g., traveling upward after the tire triggers an IED) thereby reducing the blast force on the structural shell **112** and the occupants within passenger capsule **110**. Traditional frame rails may also directly impact (i.e. contact, engage, hit, etc.) the floor of traditional military vehicles. Military vehicle **1000** that includes passenger capsule **110**, front module **120**, and rear module **130** does not include traditional frame rails extending along the vehicle's length thereby eliminating the ability for such frame rails to impact the floor of the passenger compartment. Military vehicle **1000** that includes a passenger capsule **110**, front module **120**, and rear module **130** also has an improved strength-to-weight performance, abuse tolerance, and life-cycle durability.

According to an exemplary embodiment, the doors **104** incorporate a combat lock mechanism. In some embodiments, the combat lock mechanism is controlled through the same handle that operates the automotive door latch system, allowing a passenger to release the combat locks and automotive latches in a single motion for quick egress. The doors **104** also interface with an interlocking door frame **109** defined within structural shell **112** adjacent to the latch, which helps to keep the doors **104** closed and in place during a blast event. Such an arrangement also distributes blast forces between a front and a rear door mounting and latching mechanism thereby improving door functionality after a blast event.

#### Lift Structure

According to an exemplary embodiment, the military vehicle **1000** may be transported from one location to another in an elevated position with respect to a ground surface (e.g., during a helicopter lift operation, for loading onto or off a ship, etc.). As shown in FIGS. 4-9, military vehicle **1000** includes a lift structure **140** coupled to the front module **120**. According to an exemplary embodiment, the lift structure includes a first protrusion **144** extending from the first longitudinal frame member **124**, a second protrusion **146** coupled to the second longitudinal frame member **126**, and a lateral frame member **148** extending between the first protrusion **144** and the second protrusion **146**. As shown in FIGS. 4-9, the first protrusion **144** and the second protrusion **146** extend along an axis that is generally orthogonal (e.g., within 20 degrees of an orthogonal line) to a common plane within which the first longitudinal frame member **134** and the second longitudinal frame member **126** extend. As shown in FIGS. 5-6 and 8-9, the first protrusion **144** defines a first aperture **145**, and the second protrusion **146** defines a second aperture **147**. The first aperture **145** and the second aperture **147** define a pair of front lift points. An operator may engage the front lift points with a sling, cable, or other device to elevate military vehicle **1000** from a ground surface (e.g., for transport).

According to an exemplary embodiment, the hood **122** defines an outer surface (e.g., the surface exposed to a surrounding environment) and an inner surface (e.g., the surface facing the first longitudinal frame member **124** and

the second longitudinal frame member **126**). It should be understood that the outer surface is separated from the inner surface by a thickness of the hood **122**. As shown schematically in FIGS. 4, 6-7, and 9, first protrusion **144** and second protrusion **146** extend through a first opening and a second opening defined within the hood **122**. According to an exemplary embodiment, the pair of front lift points is positioned along the outer surface of the hood **122** (e.g., to provide preferred sling angles, to facilitate operator access, etc.).

According to an exemplary embodiment, the first longitudinal frame member **124** and the second longitudinal frame member **126** are coupled to the first end **114** of the structural shell **112** with a plurality of interfaces. Such interfaces may include, by way of example, a plurality of fasteners (e.g., bolts, rivets, etc.) extending through corresponding pads coupled to the front module **120** and the structural shell **112**. According to an exemplary embodiment, a lifting force applied to the pair of front lift points is transmitted into the structural shell of the passenger capsule to lift the vehicle.

In some embodiments, the military vehicle **1000** includes breakaway sections designed to absorb blast energy and separate from the remaining components of military vehicle **1000**. The blast energy is partially converted into kinetic energy as the breakaway sections travel from the remainder of military vehicle **1000** thereby reducing the total energy transferred to the passengers of military vehicle **1000**. According to an exemplary embodiment, at least one of the front module **120** and the rear module **130** are breakaway sections. Such a military vehicle **1000** includes a plurality of interfaces coupling the front module **120** and the rear module **130** to passenger capsule **110** that are designed to strategically fail during a blast event. By way of example, at least one of the plurality of interfaces may include a bolted connection having a specified number of bolts that are sized and positioned (e.g., five 0.5 inch bolts arranged in a pentagon, etc.) to fail as an impulse force is imparted on front module **120** or rear module **130** during a blast event. In other embodiments, other components of the military vehicle **1000** (e.g., wheel, tire, engine, etc.) are breakaway sections.

Referring again to the exemplary embodiment shown in FIGS. 4-6, the military vehicle **1000** may be lifted by a pair of apertures defined within a pair of protrusions **115**. The apertures define a pair of rear lift points for military vehicle **1000**. As shown in FIG. 5, the pair of protrusions **115** extend from opposing lateral sides of the structural shell **112**. It should be understood that a lifting force applied directly to the pair of protrusions **115** may, along with the lifting force applied to lift structure **140**, elevate the military vehicle **1000** from a ground surface. The structural shell **112** carries the loading imparted by the lifting forces applied to the lift structure **140** (e.g., through the plurality of interfaces) and the pair of protrusions **115** to elevate the military vehicle **1000** from the ground surface without damaging the passenger capsule **110**, the front module **120**, or the rear module **130**.

#### Armor Assembly

Referring next to the exemplary embodiment shown in FIG. 10B, the armor assembly **200** includes fabricated subassemblies (roof, floor, sidewalls, etc.) that are bolted together. The armor assembly **200** may be manufactured from steel or another material. The armor assembly **200** provides a robust and consistent level of protection by using overlaps to provide further protection at the door interfaces, component integration seams, and panel joints.

In another embodiment, the armor assembly **200** further includes a 360-degree modular protection system that uses high hard steel, commercially available aluminum alloys, ceramic-based SMART armor, and two levels of underbody mine/improved explosive device (“IED”) protection. The modular protection system provides protection against kinetic energy projectiles and fragmentation produced by IEDs and overhead artillery fire. The modular protection system includes two levels of underbody protection. The two levels of underbody protection may be made of an aluminum alloy configured to provide an optimum combination of yield strength and material elongation. Each protection level uses an optimized thickness of this aluminum alloy to defeat underbody mine and IED threats.

Referring now to FIG. **10B**, the armor assembly **200** also includes a passenger capsule assembly **202**. The passenger capsule assembly **202** includes a V-shaped belly deflector **203**, a wheel deflector, a floating floor, footpads **206** and energy absorbing seats **207**. The V-shaped belly deflector **203** is integrated into the sidewall. The V-shaped belly deflector **203** is configured to mitigate and spread blast forces along a belly. In addition, the wheel deflector mitigates and spreads blast forces. The “floating” floor utilizes isolators and standoffs to decouple forces experienced in a blast event from traveling on a direct load path to the passenger’s lower limbs. The floating floor mounts to passenger capsule assembly **202** isolating the passenger’s feet from direct contact with the blast forces on the belly. Moreover, footpads protect the passenger’s feet. The energy absorbing seats **207** reduce shock forces to the occupants’ hips and spine through a shock/spring attenuating system. The modular approach of the passenger capsule assembly **202** provides increased protection with the application of perimeter, roof and underbody add on panels. The components of the passenger capsule assembly **202** mitigate and attenuate blast effects, allow for upgrades, and facilitate maintenance and replacements.

The passenger capsule assembly **202** further includes a structural tunnel **210**. For load purposes, the structural tunnel **210** replaces a frame or rail. The structural tunnel **210** has an arcuately shaped cross section and is positioned between the energy absorbing seats **207**. The configuration of the structural tunnel **210** increases the distance between the ground and the passenger compartment of passenger capsule assembly **202**. Therefore, the structural tunnel **210** provides greater blast protection from IEDs located on the ground because the IED has to travel a greater distance in order to penetrate the structural tunnel **210**.

Engine

The engine **300** is a commercially available internal combustion engine modified for use on military vehicle **1000**. The engine **300** includes a Variable Geometry Turbocharger (VGT) configured to reduce turbo lag and improve efficiency throughout the engine **300**’s operating range by varying compressor housing geometry to match airflow. The VGT also acts as an integrated exhaust brake system to increase engine braking capability. The VGT improves fuel efficiency at low and high speeds and reduces turbo lag for a quicker powertrain response.

The engine **300** includes a glow plug module configured to improve the engine **300** cold start performance. In some embodiments, no ether starting aid or arctic heater is required. The glow plug module creates a significant system cost and weight reduction.

In addition, engine **300** includes a custom oil sump pickup and windage tray, which ensures constant oil supply to engine components. The integration of a front engine mount

into a front differential gear box eliminates extra brackets, reduces weight, and improves packaging. Engine **300** may drive an alternator/generator, a hydraulic pump, a fan, an air compressor and/or an air conditioning pump. Engine **300** includes a top-mounted alternator/generator mount in an upper section of the engine compartment that allows for easy access to maintain the alternator/generator and forward compatibility to upgrade to a higher-power export power system. A cooling package assembly is provided to counteract extreme environmental conditions and load cases.

According to an exemplary embodiment, the military vehicle **1000** also includes a front engine accessory drive (FEAD) that mounts engine accessories and transfers power from a front crankshaft dampener/pulley to the accessory components through a multiple belt drive system. According to an exemplary embodiment, the FEAD drives a fan, an alternator, an air conditioning pump, an air compressor, and a hydraulic pump. There are three individual belt groups driving these accessories to balance the operational loads on the belt as well as driving them at the required speeds. A top-mounted alternator provides increased access for service and upgradeability when switching to the export power kit (e.g., an alternator, a generator, etc.). The alternator is mounted to the front sub frame via tuned isolators, and driven through a constant velocity (CV) shaft coupled to a primary plate of the FEAD. This is driven on a primary belt loop, which is the most inboard belt to the crank dampener. No other components are driven on this loop. A secondary belt loop drives the hydraulic pump and drive through pulley. This loop has one dynamic tensioner and is the furthest outboard belt on the crankshaft dampener pulley. This belt loop drives power to a tertiary belt loop through the drive through pulley. The tertiary belt loop drives the air conditioning pump, air compressor, and fan clutch. There is a single dynamic tensioner on this loop, which is the furthest outboard loop of the system.

Transmission, Transfer Case, Differentials

Military vehicle **1000** includes a commercially available transmission **400**. Transmission **400** also includes a torque converter configured to improve efficiency and decrease heat loads. Lower transmission gear ratios combined with a low range of an integrated rear differential/transfer case provide optimal speed for slower speeds, while higher transmission gear ratios deliver convoy-speed fuel economy and speed on grade. In addition, a partial throttle shift performance may be refined and optimized in order to match the power outputs of the engine **300** and to ensure the availability of full power with minimal delay from operator input. This feature makes the military vehicle **1000** respond more like a high performance pickup truck than a heavy-duty armored military vehicle.

The transmission **400** includes a driver selectable range selection. The transaxle **450** contains a differential lock that is air actuated and controlled by switches on driver’s control panel. Indicator switches provide shift position feedback and add to the diagnostic capabilities of the vehicle. Internal mechanical disconnects within the transaxle **450** allow the vehicle to be either flat towed or front/rear lift and towed without removing the drive shafts. Mechanical air solenoid over-rides are easily accessible at the rear of the vehicle. Once actuated, no further vehicle preparation is needed. After the recovery operation is complete, the drive train is re-engaged by returning the air solenoid mechanical over-rides to the original positions.

The transaxle **450** is designed to reduce the weight of the military vehicle **1000**. The weight of the transaxle **450** was minimized by integrating the transfer case and rear differen-

tial into a single unit, selecting an optimized gear configuration, and utilizing high strength structural aluminum housings. By integrating the transcase and rear differential into transaxle **450** thereby forming a singular unit, the connecting drive shaft and end yokes traditionally utilized between to connect them has been eliminated. Further, since the transcase and rear carrier have a common oil sump and lubrication system, the oil volume is minimized and a single service point is used. The gear configuration selected minimizes overall dimensions and mass providing a power dense design. The housings are cast from high strength structural aluminum alloys and are designed to support both the internal drive train loads as well as structural loads from the suspension system **460** and frame, eliminating the traditional cross member for added weight savings. According to the exemplary embodiment shown in FIG. **10A**, at least a portion of the suspension system **460** (e.g., the upper control arm **462**, the lower control arm **464**, both the upper and lower control arms **462**, **464**, a portion of the spring **466**, damper **468**, etc.) is coupled to the transaxle **450**. Such coupling facilitates assembly of military vehicle **1000** (e.g., allowing for independent assembly of the rear axle) and reduces the weight of military vehicle **1000**. The front axle gearbox also utilizes weight optimized gearing, aluminum housings, and acts as a structural component supporting internal drive train, structural, and engine loads as well. The integrated transcase allows for a modular axle design, which provides axles that may be assembled and then mounted to the military vehicle **1000** as a single unit. An integral neutral and front axle disconnect allows the military vehicle **1000** to be flat towed or front/rear lift and towed with minimal preparation. Further, the integrated design of the transaxle **450** reduces the overall weight of the military vehicle **1000**. The transaxle **450** further includes a disconnect capability that allows the front tire assemblies **600** to turn without rotating the entire transaxle **450**. Housings of the front and rear gearbox assembly are integrated structural components machined, for example, from high strength aluminum castings. Both front and rear gearbox housings provide stiffness and support for rear module **130** and the components of the suspension system **460**.

#### Suspension

The military vehicle **1000** includes a suspension system **460**. The suspension system **460** includes high-pressure nitrogen gas springs **466** calibrated to operate in tandem with standard low-risk hydraulic shock absorbers **468**, according to an exemplary embodiment. In one embodiment, the gas springs **466** include a rugged steel housing with aluminum end mounts and a steel rod. The gas springs **466** incorporate internal sensors to monitor a ride height of the military vehicle **1000** and provide feedback for a High Pressure Gas (HPG) suspension control system. The gas springs **466** and HPG suspension control system are completely sealed and require no nitrogen replenishment for general operation.

The HPG suspension control system adjusts the suspension ride height when load is added to or removed from the military vehicle **1000**. The control system includes a high pressure, hydraulically-actuated gas diaphragm pump, a series of solenoid operated nitrogen gas distribution valves, a central nitrogen reservoir, a check valve arrangement and a multiplexed, integrated control and diagnostics system.

The HPG suspension control system shuttles nitrogen between each individual gas spring and the central reservoir when the operator alters ride height. The HPG suspension control system targets both the proper suspension height, as well as the proper gas spring pressure to prevent “cross-

jacking” of the suspension and ensure a nearly equal distribution of the load from side to side. The gas diaphragm pump compresses nitrogen gas. The gas diaphragm pump uses a lightweight aluminum housing and standard hydraulic spool valve, unlike more common larger iron cast industrial stationary systems not suitable for mobile applications.

The suspension system **460** includes shock absorbers **468**. In addition to their typical damping function, the shock absorbers **468** have a unique cross-plumbed feature configured to provide auxiliary body roll control without the weight impact of a traditional anti-sway bar arrangement. The shock absorbers **468** may include an equal area damper, a position dependent damper, and/or a load dependent damper.

#### Brakes

The braking system **700** includes a brake rotor and a brake caliper. There is a rotor and caliper on each wheel end of the military vehicle **1000**, according to an exemplary embodiment. According to an exemplary embodiment, the brake system includes an air over hydraulic arrangement. As the operator presses the brake pedal, and thereby operates a treadle valve, the air system portion of the brakes is activated and applies air pressure to the hydraulic intensifiers. According to an exemplary embodiment, military vehicle **1000** includes four hydraulic intensifiers, one on each brake caliper. The intensifier is actuated by the air system of military vehicle **1000** and converts air pressure from onboard military vehicle **1000** into hydraulic pressure for the caliper of each wheel. The brake calipers are fully-integrated units configured to provide both service brake functionality and parking brake functionality.

To reduce overall system cost and weight while increasing stopping capability and parking abilities, the brake calipers may incorporate a Spring Applied, Hydraulic Released (SAHR) parking function. The parking brake functionality of the caliper is created using the same frictional surface as the service brake, however the mechanism that creates the force is different. The calipers include springs that apply clamping force to the brake rotor to hold the military vehicle **1000** stationary (e.g. parking). In order to release the parking brakes, the braking system **700** applies a hydraulic force to compress the springs, which releases the clamping force. The hydraulic force to release the parking brakes comes through a secondary hydraulic circuit from the service brake hydraulic supply, and a switch on the dash actuates that force, similar to airbrake systems.

Referring specifically to the exemplary embodiment shown in FIG. **11**, braking system **700** is shown schematically to include a motor **710** having a motor inlet **712**. The motor **710** is an air motor configured to be driven by an air system of military vehicle **1000**, according to an exemplary embodiment. The motor **710** may be coupled to the air system of military vehicle **1000** with a line **714**. As shown in FIG. **11**, braking system **700** includes a pump **720** that includes a pump inlet **722**, a pump outlet **724**, and a pump input shaft **726**. The pump input shaft **726** is rotatably coupled to the motor **710** (e.g., an output shaft of the motor **710**).

As shown in FIG. **11**, braking system **700** includes a plurality of actuators **730** coupled to the pump outlet **724**. According to an exemplary embodiment, the actuators **730** includes a housing **732** that defines an inner volume and a piston **734** slidably coupled to the housing **732** and separating the inner volume into a first chamber and a second chamber. The plurality of actuators **730** each include a resilient member (e.g., spring, air chamber, etc.), shown as resilient member **736** coupled to the housing and configured

## 11

to generate a biasing force (e.g., due to compression of the resilient member 736, etc.). According to an exemplary embodiment, the plurality of actuators 730 each also include a rod 738 extending through an end of the housing 732. The rod 738 is coupled at a first end to piston 734 and coupled at a second end to a brake that engages a braking member (e.g., disk, drum, etc.), shown as braking member 740. As shown in FIG. 11, the rod is configured to apply the biasing force to the braking member 740 that is coupled to wheel and tire assemblies 600 thereby inhibiting movement of the military vehicle 1000.

According to an exemplary embodiment, a control is actuated by the operator, which opens a valve to provide air along the line 714. Pressurized air (e.g., from the air system of military vehicle 1000, etc.) drives motor 710, which engages pump 720 to flow a working fluid (e.g., hydraulic fluid) a through line 750 that couples the pump outlet 724 to the plurality of actuators 730. According to an exemplary embodiment, the pump 720 is a hydraulic pump and the actuator 730 is a hydraulic cylinder. Engagement of the pump 720 provides fluid flow through line 750 and into at least one of the first chamber and the second chamber of the plurality of actuators 730 to overcome the biasing force of resilient member 736 with a release force. The release force is related to the pressure of the fluid provided by pump 720 and the area of the piston 734. Overcoming the biasing force releases the brake thereby allowing movement of military vehicle 1000.

As shown in FIG. 11, braking system 700 includes a valve, shown as directional control valve 760, positioned along the line 750. According to an exemplary embodiment, directional control valve 760 includes a valve body 770. The valve body 770 defines a first port 772, a second port 774, and a reservoir port 776, according to an exemplary embodiment. When valve gate 762 is in the first position (e.g., pressurized air is not applied to air pilot 766) valve gate 762 places first port 772 in fluid communication with reservoir port 776. A reservoir 780 is coupled to the reservoir port 776 with a line 752. The reservoir 780 is also coupled to the pump inlet 722 with a line 754. It should be understood that the fluid may be forced into reservoir 780 from any number of a plurality of actuators 730 by resilient member 736 (e.g., when pump 720 is no longer engaged).

According to an exemplary embodiment, the directional control valve 760 selectively couples the plurality of actuators 730 to the pump outlet 724 or reservoir 780. The directional control valve 760 includes a valve gate 762 that is moveable between a first position and a second position. According to an exemplary embodiment, the valve gate 762 is at least one of a spool and a poppet. The valve gate 762 is biased into a first position by a valve resilient member 764. According to an exemplary embodiment, the directional control valve 760 also includes an air pilot 766 positioned at a pilot end of the valve gate 762. The air pilot 766 is coupled to line 714 with a pilot line 756. Pressurized air is applied to line 714 drives motor 710 and is transmitted to air pilot 766 to overcome the biasing force of valve resilient member 764 and slide valve gate 762 into a second position. In the second position, valve gate 762 places first port 772 in fluid communication with 774 thereby allowing pressurized fluid from pump 720 to flow into actuators 730 to overcome the biasing force of resilient member 736 and allow uninhibited movement of military vehicle 1000.

## Control System

Referring to FIG. 12, the systems of the military vehicle 1000 are controlled and monitored by a control system 1200. The control system 1200 integrates and consolidates infor-

## 12

mation from various vehicle subsystems and displays this information through a user interface 1201 so the operator/crew can monitor component effectiveness and control the overall system. For example, the subsystems of the military vehicle 1000 that can be controlled or monitored by the control system 1200 are the engine 300, the transmission 400, the transaxle 450, the suspension system 460, the wheels and tire assemblies 600, the braking system 700, the fuel system 800, the power generation system 900, and a trailer 1100. However, the control system 1200 is not limited to controlling or monitoring the subsystems mentioned above. A distributed control architecture of the military vehicle 1000 enables the control system 1200 process.

In one embodiment, the control system 1200 provides control for terrain and load settings. For example, the control system 1200 can automatically set driveline locks based on the terrain setting, and can adjust tire pressures to optimal pressures based on speed and load. The control system 1200 can also provide the status for the subsystems of the military vehicle 1000 through the user interface 1201. In another example, the control system 1200 can also control the suspension system 460 to allow the operator to select appropriate ride height.

The control system 1200 may also provide in-depth monitoring and status. For example, the control system 1200 may indicate on-board power, output power details, energy status, generator status, battery health, and circuit protection. This allows the crew to conduct automated checks on the subsystems without manually taking levels or leaving the safety of the military vehicle 1000.

The control system 1200 may also diagnose problems with the subsystems and provide a first level of troubleshooting. Thus, troubleshooting can be initiated without the crew having to connect external tools or leave the safety of the military vehicle 1000.

The construction and arrangements of the vehicle, as shown in the various exemplary embodiments, are illustrative only. Although only a few embodiments have been described in detail in this disclosure, many modifications are possible (e.g., variations in sizes, dimensions, structures, shapes and proportions of the various elements, values of parameters, mounting arrangements, use of materials, colors, orientations, etc.) without materially departing from the novel teachings and advantages of the subject matter described herein. Some elements shown as integrally formed may be constructed of multiple parts or elements, the position of elements may be reversed or otherwise varied, and the nature or number of discrete elements or positions may be altered or varied. The order or sequence of any process, logical algorithm, or method steps may be varied or re-sequenced according to alternative embodiments. Other substitutions, modifications, changes, and omissions may also be made in the design, operating conditions and arrangement of the various exemplary embodiments without departing from the scope of the present invention.

The invention claimed is:

1. A military vehicle assembly comprising:

a rear module including:

- a rear frame assembly having one or more upper interfaces and one or more lower interfaces, the one or more upper interfaces configured to detachably couple to a rear end of a passenger capsule of a military vehicle, the one or more lower interfaces configured to detachably coupled to a bottom of the passenger capsule;
- a bed supported by the rear frame assembly;
- a rear tractive assembly;

## 13

- a transaxle supported by the rear frame assembly, the transaxle coupled to the rear tractive assembly, the transaxle configured to couple to a prime mover and a front differential of the military vehicle; and a rear suspension system including at least one component extending between a housing of the transaxle and the rear tractive assembly.
2. The military vehicle assembly of claim 1, wherein the rear suspension system includes a first spring, a second spring, a first damper, and a second damper, and wherein the at least one component includes at least one of (a) the first spring and the second spring or (b) the first damper and the second damper.
3. The military vehicle assembly of claim 2, wherein the at least one component includes the first spring and the second spring.
4. The military vehicle assembly of claim 2, wherein the at least one component includes the first damper and the second damper.
5. The military vehicle assembly of claim 2, wherein the at least one component includes the first spring, the second spring, the first damper, and the second damper.
6. The military vehicle assembly of claim 2, wherein the first spring and the second spring are high-pressure nitrogen springs, and wherein the first damper and the second damper are hydraulic dampers.
7. The military vehicle assembly of claim 1, wherein the rear suspension system includes a pair of gas springs, further comprising a suspension control system configured to: monitor a ride height of the military vehicle; and control the pair of gas springs to adjust the ride height as load is added to or removed from the military vehicle.
8. The military vehicle assembly of claim 7, wherein the pair of gas springs are high-pressure nitrogen springs.
9. The military vehicle assembly of claim 1, wherein the rear suspension system includes a pair of hydraulic dampers, wherein the pair of hydraulic dampers are cross-plumbed to provide a hydraulic body roll control function.
10. The military vehicle assembly of claim 1, wherein the transaxle includes an internal mechanical disconnect that facilitates decoupling the transaxle from the front differential.
11. The military vehicle assembly of claim 10, further comprising an actuator configured to facilitate manually engaging the internal mechanical disconnect.
12. The military vehicle assembly of claim 1, wherein the transaxle includes a transference component and a rear differential component at least partially contained within the housing.
13. The military vehicle assembly of claim 1, further comprising a front module including:  
a front frame assembly having one or more upper interfaces and one or more lower interfaces, the one or more upper interfaces configured to detachably couple to a front end of the passenger capsule, the one or more lower interfaces configured to detachably couple to the bottom of the passenger capsule;  
a front tractive assembly;  
the prime mover; and

## 14

- the front differential coupled to the front tractive assembly.
14. The military vehicle assembly of claim 13, wherein the front module and the rear module are coupleable to different variants of the passenger capsule to provide different variants of the military vehicle.
15. The military vehicle assembly of claim 14, wherein the different variants of the passenger capsule include a first variant defining four door openings and a second variant defining two door openings.
16. The military vehicle assembly of claim 13, wherein the prime mover includes an engine.
17. A military vehicle assembly comprising:  
a rear module including:  
a rear frame assembly having one or more upper interfaces and one or more lower interfaces, the one or more upper interfaces configured to detachably couple to a rear end of a passenger capsule of a military vehicle, the one or more lower interfaces configured to detachably couple to a bottom of the passenger capsule;  
a rear tractive assembly;  
a transaxle supported by the rear frame assembly, the transaxle coupled to the rear tractive assembly, the transaxle configured to couple to a prime mover and a front differential of the military vehicle; and  
a rear suspension system including at least one component extending between a housing of the transaxle and the rear tractive assembly.
18. The military vehicle assembly of claim 17, wherein the rear suspension system includes a pair of gas springs and a pair of hydraulic dampers.
19. A military vehicle assembly comprising:  
a rear module including:  
a rear frame assembly having one or more upper interfaces and one or more lower interfaces, the one or more upper interfaces configured to detachably couple to a rear end of a passenger capsule of a military vehicle, the one or more lower interfaces configured to detachably couple to a bottom of the passenger capsule;  
a rear tractive assembly;  
a transaxle supported by the rear frame assembly, the transaxle coupled to the rear tractive assembly, the transaxle configured to couple to a prime mover and a front differential of the military vehicle; and  
a rear suspension system including a pair of gas springs and a pair of hydraulic dampers, wherein the pair of hydraulic dampers are cross-plumbed to provide a hydraulic body roll control function; and  
a suspension control system configured to:  
monitor a ride height of the military vehicle; and  
control the pair of gas springs to adjust the ride height as load is added to or removed from the military vehicle.
20. The military vehicle assembly of claim 19, wherein at least one of (a) the pair of gas springs or (b) the pair of hydraulic dampers extend between a housing of the transaxle and the rear tractive assembly.

\* \* \* \* \*