

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250257826

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Short; Daniel T.

---

### FLANGED CLAMP UNION AND METHOD OF ASSEMBLY

---

#### Abstract

A flange clamp is provided for coupling a fluid connector to a bulkhead plate of a bulkhead assembly. The flange clamp includes a clamp body having an inner surface configured to engage with the fluid connector, and a plurality of openings formed in the clamp body. The plurality of openings includes at least a first opening, a second opening, and a third opening. At least one extended body portion is integrally formed at an outer periphery of the clamp body. A retaining portion is formed with the at least one extended body portion and projects away therefrom. The retaining portion is configured to be disposed within an opening formed in the bulkhead plate, where the retaining portion is configured to selectively maintain an orientation of the clamp body on the bulkhead plate.

---

**Inventors:** Short; Daniel T. (Ankeny, IA)

**Applicant:** Deere & Company (Moline, IL)

**Family ID:** 94633481

**Appl. No.:** 18/976687

**Filed:** December 11, 2024

#### Related U.S. Application Data

us-provisional-application US 63553203 20240214

---

#### Publication Classification

**Int. Cl.:** F16L23/028 (20060101); F16L23/032 (20060101); F16L39/00 (20060101); F16L41/00 (20060101)

**U.S. Cl.:**

## Background/Summary

RELATED APPLICATIONS [0001] This application claims the benefit of U.S. Provisional Patent Application Ser. No. 63/553,203, filed Feb. 14, 2024, the disclosure of which is hereby incorporated by reference in its entirety.

### FIELD OF THE DISCLOSURE

[0002] The present disclosure relates to a bulkhead application on a work machine, and in particular, to a flanged clamp union assembly for a bulkhead on a work machine.

### BACKGROUND

[0003] Work machines, such as those in the agricultural, construction, and forestry industries, may include one or more hydraulic connections for fluidly coupling a pair of fluid lines or hoses to one another. These hydraulic connections may be flanged connections as found in bulkhead applications for larger work machines.

### SUMMARY

[0004] In one implementation of the present disclosure, a flange clamp is provided for coupling a fluid connector to a bulkhead plate of a bulkhead assembly, the flange clamp including a clamp body having a curved inner surface configured to engage with the fluid connector; a plurality of openings formed in the clamp body, the plurality of openings including at least a first opening, a second opening, and a third opening; an extended body portion integrally formed at an outer periphery of the clamp body; a retaining portion formed on a first surface of the extended body portion, the retaining portion projecting away from the first surface; wherein the retaining portion is configured to be disposed within a keyhole or other opening formed in the bulkhead plate, where the retaining portion is configured to selectively maintain an orientation of the clamp body on the bulkhead plate.

[0005] In one example of this implementation, the plurality of openings formed in the clamp body are axially aligned with one another. In a second example, the third opening is formed in the extended body portion, the third opening defined through the projecting portion. In a third example, the clamp body includes a first end and a second end, the second end spaced from the first end, where the extended body portion extends from the second end of the clamp body. In a fourth example, the clamp body includes a first end and a second end, the second end spaced from the first end, where the extended body portion extends from the clamp body at a location between the first end and the second end.

[0006] In a fifth example, the first opening is formed in the clamp body adjacent the first end, the second opening is formed in the clamp body adjacent the second end, and the third opening is formed in the extended body portion at a location between the first and second openings. In a sixth example, the retaining portion includes a shaped profile having at least three sides. In a seventh example, the retaining portion includes a triangular-shaped profile, square-shaped profile, rectangular-shaped profile, pentagonal-shaped profile, hexagonal-shaped profile, or octagonal-shaped profile.

[0007] In another example, the clamp body includes a first body portion and a second body portion, the first body portion being offset from the second body portion. In yet another example, a post portion is located between the first body portion and the second body portion. In a further example, the retaining portion is arranged parallel to and offset from the post portion. In yet a further example, at least one of the plurality of openings is a threaded opening.

[0008] In another implementation of the present disclosure, a bulkhead assembly is provided for

fluidly coupling a first fluid connector to a second fluid connector. The bulkhead assembly includes a union plate that includes a plate body forming a plurality of coupler openings, the plurality of coupler openings including at least a connector opening, a first coupler opening, a second coupler opening, and a third coupler opening; a flange clamp configured to fluidly couple the first fluid connector to the union plate, the flange clamp including a clamp body having an inner surface configured to engage with the first fluid connector, the inner surface disposed along at least a portion of the connector opening; a plurality of openings formed in the clamp body, the plurality of openings including at least a first opening, a second opening, and a third opening; an extended body portion integrally formed at an outer periphery of the clamp body; a retaining portion formed in the extended body portion, the retaining portion projecting in a direction away from the extended body portion; wherein, in first configuration, the flange clamp is arranged relative to the union plate such that the retaining portion is disposed within the third coupler opening formed in the union plate, where in the first configuration the retaining portion is configured to selectively maintain an orientation of the clamp body with respect to the union plate.

[0009] In one example of this implementation, in the first configuration, the clamp body and extended body portion are located on a first side of the union plate, and the retaining portion is located at least partially on the second side of the union plate. In a second example, a fastener is inserted into the third opening formed in the retaining portion to maintain the orientation of the clamp body with respect to the union plate. In a third example, the retaining portion includes a shape having a first profile; the third coupler opening is shaped having a second profile, the first profile having a shape similar to the second profile. In a fourth example, the first profile and second profile include a triangular-shaped profile, square-shaped profile, rectangular-shaped profile, pentagonal-shaped profile, hexagonal-shaped profile, or octagonal-shaped profile. In a fifth example, the first profile and second profile include a curved profile.

[0010] In a sixth example, a second flange clamp includes a second clamp body, the second clamp body forming at least a fourth opening and a fifth opening; wherein, the flange clamp is coupled to a first side of the union plate, and the second flange clamp is coupled to a second side of the union plate; wherein, in a second configuration, the retaining portion is disposed within the third coupler opening, the first opening and fourth opening are aligned with the first coupler opening, and the second opening and the fifth opening are aligned with the second coupler opening.

[0011] In a seventh example, the first opening or the fourth opening is threaded, and the second opening or the fifth opening is threaded. In an eighth example, the first opening, the second opening, the fourth opening and the fifth opening are formed as non-threaded, clearance openings. In a ninth example, the second clamp body includes a second extended body portion, the second extended body portion including a second retaining portion; wherein, the second retaining portion is disposed within a fourth coupler opening formed in the union plate, the fourth coupler opening being spaced from the third coupler opening.

[0012] In a tenth example, the clamp body includes a first body portion and a second body portion, the first body portion being offset from the second body portion. In an eleventh example, a post portion is located between the first body portion and the second body portion. In a twelfth example, the retaining portion is arranged parallel to and offset from the post portion. In another example, the union plate includes an elongate slotted opening formed between the first coupler opening and the third coupler opening. In yet another example, in a second configuration, the retaining portion is disposed within the third coupler opening and the post portion is disposed within the elongate slotted opening. In still another example, the first opening and the second opening are formed in the first body portion, and the third opening is formed in the second body portion and the retaining portion. In a further example, in the second configuration, the first body portion is located on a first side of the union plate and the second body portion is located on a second side of the union plate, the first side and second side being opposite from one another.

[0013] In a further implementation of the present disclosure, a method of assembling a bulkhead

assembly for fluidly coupling a first fluid connector to a second fluid connector includes positioning the first fluid connector on a first side of a union plate such that the first fluid connector is aligned with a connector opening formed in the union plate; aligning a first flange clamp adjacent to the first connector on the first side of the union plate; locating a retaining portion of the first flange clamp to project through a keyhole or other opening formed in the union plate; coupling a first fastener to a retaining opening formed in the retaining portion of the first flange clamp; and selectively maintaining an orientation of the first flange clamp with respect to the union plate via the coupling of the first fastener to the retaining portion.

[0014] In a first example of the present disclosure, the method includes aligning a second flange clamp on the first side of the union plate adjacent to the first flange clamp. In a second example, the coupling the first fastener includes coupling the first fastener to the retaining portion on a second side of the union plate. In a third example, the aligning the first flange clamp includes aligning at least a first opening formed in the first flange clamp with a first coupler opening formed in the union plate. In a fourth example, the method includes positioning a second flange clamp on a second side of the union plate, the second clamp flange including a second opening; aligning the second opening in the second flange clamp with a first coupler opening formed in the union plate and a first opening formed in the first flange clamp; and coupling the first flange clamp to the union plate and the second flange clamp.

[0015] In a fifth example, the coupling the first flange clamp includes inserting a fastener through the second opening and the first coupler opening and into the first opening; and threadably coupling the fastener to the first opening formed in the first flange clamp. In another example, the coupling the first flange clamp includes inserting a fastener through the first opening and the first coupler opening and into the second opening; and threadably coupling the fastener to the second opening formed in the second flange clamp. In yet another example, the coupling the first flange clamp includes inserting a fastener through the first opening, the first coupler opening and the second opening; and threadably coupling a second fastener to a threaded portion of the fastener.

[0016] In a further example, the method includes clamping the first flange clamp and the first fluid connector to the union plate; and forming a fluidly sealed connection between the first fluid connector and the union plate. In yet a further example, the method includes forming an anti-rotational connection between the first flange clamp and the union plate. In still a further example, the forming the anti-rotational connection includes disposing the retaining portion having a first shaped profile into the keyhole or other opening having a second shaped profile, the first shaped profile and the second shaped profile being the same.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0017] The above-mentioned aspects of the present disclosure and the manner of obtaining them will become more apparent and the disclosure itself will be better understood by reference to the following description of the implementations of the disclosure, taken in conjunction with the accompanying drawings, wherein:

[0018] FIG. 1 is a perspective view of one example implementation of a chassis of a work machine;

[0019] FIG. 2 is a partial perspective view of the example implementation of the chassis of FIG. 1 including a bulkhead assembly with a plurality of fluid lines and connections;

[0020] FIG. 3 is a perspective view of an example implementation of a bulkhead assembly with a plurality of fluid connections;

[0021] FIG. 4 is a perspective view of a portion of the bulkhead assembly of FIG. 3;

[0022] FIG. 5A is a perspective view of an example implementation of a first side of a first flange

clamp and a second flange clamp;

[0023] FIG. 5B is a perspective view of an example implementation of a second side of the first flange clamp and the second flange clamp of FIG. 5A;

[0024] FIG. 6 is a perspective view of an example implementation of a plate assembly for a bulkhead assembly;

[0025] FIG. 7 is a perspective view of an example implementation of a first flange clamp and first connector for coupling to the plate assembly of FIG. 6;

[0026] FIG. 8 is a perspective view of an example implementation of a second flange clamp for coupling to the plate assembly of FIG. 6;

[0027] FIG. 9 is a partial cross-sectional view of the second flange clamp of FIG. 8, first connector of FIG. 7, and plate assembly of FIG. 6;

[0028] FIG. 10 is a perspective view of another side of the plate assembly of FIG. 6;

[0029] FIG. 11 is another partial cross-sectional view of the second flange clamp of FIG. 8, first connector of FIG. 7, and plate assembly of FIG. 6;

[0030] FIG. 12 is a perspective cross-sectional view of the second flange clamp of FIG. 8, first connector of FIG. 7, and plate assembly of FIG. 6;

[0031] FIG. 13 is a perspective view of the plate assembly of FIG. 6 and a second connector for coupling to a bulkhead assembly;

[0032] FIG. 14 is a perspective view of an example implementation of another flange clamp assembly, the plate assembly of FIG. 6 and the second connector of FIG. 13;

[0033] FIG. 15 is a side cross-sectional view of the bulkhead assembly of FIG. 14;

[0034] FIG. 16 is a perspective view of another example implementation of a bulkhead assembly;

[0035] FIG. 17 is a perspective view of another example implementation of a bulkhead assembly;

[0036] FIG. 18 is a perspective view of another example implementation of a bulkhead assembly;

[0037] FIG. 19 is a partial perspective view of an example implementation of a plate assembly of the bulkhead assembly of FIG. 18;

[0038] FIG. 20 is a side view of an example implementation of a flange clamp of the bulkhead assembly of FIG. 18;

[0039] FIG. 21 is a perspective view of the bulkhead assembly of FIG. 18;

[0040] FIG. 22 is a flow diagram of an example implementation of assembling a bulkhead assembly;

[0041] FIG. 23 is a perspective view of another example implementation of a bulkhead assembly; and

[0042] FIG. 24 is a perspective view of an implementation of a flange clamp.

[0043] Corresponding reference numerals are used to indicate corresponding parts throughout the several views.

#### DETAILED DESCRIPTION

[0044] For the purposes of promoting an understanding of the principles of the present disclosure, reference will now be made to the implementations described herein and illustrated in the drawings and specific language will be used to describe the same. It will nevertheless be understood that no limitation of the scope of the present disclosure is thereby intended, such alterations and further modifications in the illustrated devices and methods, and such further applications of the principles of the present disclosure as illustrated therein being contemplated as would normally occur to one skilled in the art to which the present disclosure relates. Terms of degree, such as “substantially,” “about,” “approximately,” etc. are understood by those of ordinary skill to refer to reasonable ranges outside of the given value, for example, general tolerances associated with manufacturing, assembly, and use of the described implementations.

[0045] A bulkhead assembly may be found on different types of vehicles, machines, and other equipment. In some instances, the bulkhead assembly may be used for coupling a fluid connection to a structure such as a chassis or frame. For example, a first fluid line or hose may be coupled to a

bulkhead assembly on a first side, while a second fluid line or hose may be coupled to an opposite side thereof.

[0046] In some implementations, a flanged clamp union is used for assembly to enable the connection between two flanged connectors. This is typically required in bulkhead applications that are necessary for modularized assembly of large work machines. The work machines may be any agricultural machine, construction machine, forestry machine, or other known work machines. In a conventional flanged clamp union, there is often a large manifold block with independent fastening hardware for connecting two connectors on both sides. During service, some of these flanged clamp unions may be disassembled from either or both sides. In other instances, a thinner mating plate may be used in place of the large manifold block. In these instances, many of the flanged clamp unions may require disassembly from both sides of the plate, rather than on only a single side of the plate.

[0047] Moreover, since both sides of the manifold block are disassembled, there is a need for space to perform the disassembly. The manifold block is often large and has a heavy mass associated therewith. In this application, there are requirements for a minimum thread length for each fastener when engaging the manifold. For this reason, the manifold is designed to be large so that the fasteners can connect on both sides thereof to satisfy standards for minimum thread engagement. In some work machines, there are one or more of these manifolds which adds weight to the work machine and thus requires more power to move the machine. This additional weight and power can increase the cost of the work machine.

[0048] One type of a flanged clamp union is with a four-bolt flange hydraulic connection. The four-bolt flange hydraulic connection is a known sealing technology with several benefits over other hydraulic sealing technologies. For example, the four-bolt flange hydraulic connection may include a lower assembly torque and higher pressure rating as compared to other technologies (e.g., O-ring face seal, 37-degree flare, etc.) when used in similar applications.

[0049] One example implementation of a four-bolt flange hydraulic connection is shown in FIGS. 1-4. Referring to FIGS. 1-2 of the present disclosure, for example, a chassis **100** of a work machine is shown. The work machine may be an agricultural machine, a construction machine, a forestry machine, and the like. The chassis **100** may form a frame body **102** to which a first flanged clamp union assembly **104** and a second flanged clamp union assembly **106** are mounted. As shown, a first plurality of fluid lines or hoses **108** are coupled to one side of the first flanged clamp union assembly **104**, and a second plurality of fluid lines or hoses **110** are coupled to an opposite side thereof. A third plurality of fluid lines or hoses **112** are coupled to one side of the second flanged clamp union assembly **106**, and a fourth plurality of fluid lines or hoses **114** are coupled to an opposite side thereof.

[0050] Conventional four bolt flange connections can have some drawbacks, and particularly when it comes to union mating connections in a bulkhead. Conventional four bolt flange connections require four independent bolts per connector to clamp the connection in a sealing manner. At a bulkhead union, i.e., where two fluid or plumbing connections meet, there is generally a need for at least eight fasteners (e.g., bolts, screws, etc.) and a large manifold to close the connection. An example of this is shown in FIG. 3. As shown, a four-bolt flange connection for connecting a pair of plumbing connections to a bulkhead assembly **300** is shown. Here, a large manifold **302** is formed as a casting and has a first side and a second side. A manifold plate **304** having a plurality of openings is coupled to the manifold **302**. A first fluid input line **308**, a second fluid input line **312**, and a third fluid input line **316** are coupled to the first side of the manifold **302**. A first fluid output line **310** is coupled to the opposite side of the manifold **302** such that the first fluid input line **308** is fluidly coupled to the first fluid output line **310**. Similarly, a second fluid output line **314** and a third fluid output line **318** are coupled to the second side of the manifold **302**. In this way, the second fluid input line **312** is fluidly coupled to the second fluid output line **314** via the manifold **302**, and the third fluid input line **316** is fluidly coupled to the third fluid output line **318**. A fastener

**306** is shown in FIG. 3. It is to be understood there are at least four fasteners **306** for coupling the input fluid lines to the first side of the manifold **302**, and there are at least four fasteners **306** for coupling the output fluid lines to the second side of the manifold **302**.

[0051] With many conventional four bolt flange connections, it is necessary to disassemble both sides of the manifold during service and/or repair operations. In the four-bolt flange connection of FIG. 4, which is an example implementation found in some work machines, it is desirable to have the ability to independently assemble and disassemble both sides of the bulkhead connection. The independent assembly may be required for both service applications as well as during production assembly when it can be difficult to make the final assembly on both sides of the bulkhead at the same time.

[0052] In the example implementation of FIG. 4, for example, a bulkhead assembly **400** may include a manifold **402** and a manifold plate coupled thereto. In many conventional four bolt flange connections, the manifold forms the sealing face for the different fluid connectors. On the side of the manifold shown in FIG. 4, a first flange clamp **404** and a second flange clamp **406** are shown coupled to the manifold via a plurality of fasteners **408**. In this implementation, there are four fasteners **408** shown, where two fasteners **408** couple the first flange clamp **404** to the manifold **402** and the other two fasteners **408** couple the second flange clamp **406** to the manifold **402**. An opening **410** is formed between the first and second flange clamps in which a fluid connector (not shown) may be coupled.

[0053] In FIG. 4, the first flange clamp **404** and the second flange clamp **406** include at least one opening for a fastener **408** to couple the flange clamp to the manifold **402**. As shown, in this example implementation, each flange clamp includes at least two openings for a pair of fasteners **408** to couple the corresponding flange clamp to the manifold. In this example, each flange clamp is independently coupled to the manifold via the fasteners **408**. Moreover, each flange clamp forms part of the opening **410** to which the fluid connector is coupled.

[0054] The present disclosure provides one or more additional example implementations of flanged hydraulic bulkhead plumbing connections required for modular assembly to work machines. In these example implementations, the large manifold is removed to help reduce cost. Moreover, independent flange mounting hardware and multiple final assembly torque application operations can be eliminated. To do so, the present disclosure discloses one or more example implementations of a flanged clamp union for sequenced assembly to a work machine (e.g., to the chassis of the work machine). The one or more example implementations of flange clamp unions can maintain the ability to secure the hydraulic or fluid connectors to either side of the bulkhead assembly at different times, i.e., independent coupling, as may be required by a production line assembly or service operation. In other words, the one or more example implementations may allow coupling of the flange clamp union connections on one side independent of the flange clamp union connections on the opposite side.

[0055] Further, in the one or more example implementations of flange clamp unions, a bulkhead union plate (e.g., manifold plate or plate assembly) may include one or more additional openings which may be used for an in-process retention function to loosely secure the flange clamp and retained fluid connector in place on one side of the plate assembly until final assembly. The additional one or more openings in the plate assembly may be shaped and sized to receive a keying projection portion on a flange clamp. This is shown best and will be described in further detail with regards to FIG. 6. Thus, in the one or more example implementations of new flange clamp unions described herein, each bulkhead assembly may include a bulkhead union plate or plate assembly that forms the sealing surface on both sides thereof as well as one or more flange clamps that may be directly coupled to the plate assembly during assembly.

[0056] Referring to FIGS. 5A and 5B, a pair of flange clamps are illustrated. On the left side of FIGS. 5A and 5B, a first flange clamp **500** is shown. In FIG. 5A, a first side of the first flange clamp **500** is shown, and in FIG. 5B a second and opposite side thereof is shown. The first flange

clamp **500** may be a standard or conventional flange clamp similar to the first flange clamp **404** and second flange clamp **406** of FIG. **4**. Here, the first flange clamp **500** includes a clamp body **502** having a generally arced, curved, or semi-circular shape. The clamp body **502** may include a first opening **506** located near a first end and a second opening **508** located near an opposite end thereof. The first opening **506** and second opening **508** may be clearance or through openings. The clamp body **502** may include a raised portion **504** located between the first opening **506** and the second opening **508**. The overall shape of the first flange clamp **500** forms a portion of a connector opening **510**. When assembled to a bulkhead assembly, the first flange clamp **500** may be paired with another flange clamp similar to the first flange clamp **500** to form the connector opening **510**. [0057] In FIG. **5B**, the first flange clamp **500** includes a second side **526** of the clamp body **502**. On the second side **526** thereof, the clamp body **502** includes a recessed portion **528**. The recessed portion **528** is arcuate or rounded in shape. In some examples, the recessed portion **528** may be semicircular. In other implements, the recessed portion **528** may be curved less than 180°. In any event, a flange portion of a fluid connector may be disposed in the recessed portion **528** when mounted to a plate assembly, as will be described in further detail below. When the first flange clamp **500** is securely tightened to the plate assembly, the fluid connector may be fluidly and sealingly coupled to the plate assembly.

[0058] As noted above, the first flange clamp **500** in FIGS. **5A** and **5B** is similar to a conventional or standard flange clamp shown in FIG. **4**. As also shown, however, is one example implementation of a second flange clamp **512**. In FIG. **5A**, the second flange clamp **512** may include a first side of a clamp body **514**, and an opposite side **530** thereof is shown in FIG. **5B**. The clamp body **514** of the second flange clamp **512** may include a first opening **518** and a second opening **520**. A raised portion **516** of the clamp body **514** may be provided at a location between the first opening **518** and the second opening **520**. In addition, the shape of the second flange clamp **512** may partially form a connector opening **524**. In other words, a connector may be disposed in a connector opening **524** that is at least partially formed by the second flange clamp **512**.

[0059] The second flange clamp **512** may include a recessed portion **532** on the second side **530** of the clamp body **514**. As shown in FIG. **5B**, the recessed portion **532** may be semicircular. In other implements, the recessed portion **532** may have a curvature less than 180°. In other implementations, the recessed portion **532** may have a curvature of 180° or greater. In any event, a flange portion of a fluid connector may be disposed in the recessed portion **532** when mounted to a plate assembly, as will be described in further detail below. When the second flange clamp **512** is securely tightened to the plate assembly, the fluid connector may be fluidly and sealingly coupled to the plate assembly.

[0060] As further shown in FIGS. **5A** and **5B**, the second flange clamp **512** may include an extended body portion **536**. The extended body portion **536** extends past the second opening **520** and forms a third opening **522** therein. As also shown, the extended body portion **536** may form a projecting portion **534**. The second flange clamp **512** may be disposed in a plane, and the projecting portion **534** projects from the extended body portion **536** in a direction that is substantially perpendicular to the plane. In FIG. **5A**, the projecting portion **534** may project into the page. The projecting portion **534** may be better seen in FIG. **5B**. In any event, in one implementation, the first opening **518**, the second opening **520**, and the third opening **522** may be substantially parallel to one another. In other implementations, at least two of the three openings may be parallel to one another.

[0061] As best shown in FIG. **5B**, the projecting portion **534** of the second flange clamp **512** may have a square-like shape. In another implementation, the projecting portion **534** may form a hexagonal shape. In yet another implementation, the projecting portion **534** may include an oval-like shape or any shape with three or more sides. In one implementation, the projecting portion **534** forms an anti-rotational feature. In this implementation, the projecting portion **534** may include at least one substantially flat side. In other implementations, the projecting portion **534** may include at



least two substantially flat sides. In some implementations, the projecting portion **534** may include three or more substantially flat sides. In several implementations, the projecting portion **534** may form an elongated oval-like design. The number of flat sides and overall shape of the projecting portion **534** is not intended to be limited to that shown in FIGS. **5A-17**.

[0062] In another implementation, the second flange clamp **512** may include a second projecting portion **534** (not shown). In this implementation, the second flange clamp **512** may include a pair of projecting portions. The location of each projecting portion relative to the other projecting portion may not be limited. In other words, in FIG. **5A**, a first extended body portion **536** may be located adjacent the second opening **520** and a second extended body portion **536** may be located adjacent the first opening **518**, where each of the first and second extended body portions **536** include a projecting portion **534**. When a flange clamp includes two or more extended body portions that have a corresponding projecting portion, each of the corresponding projecting portions may be circular, triangular, square, rectangular, oval, pentagonal, hexagonal, octagonal, etc. With two or more projecting portions, the flange clamp may be held relatively stationary without rotating.

[0063] Besides providing an anti-rotational feature, the projecting portion **534** may also be aligned with a corresponding sized hole or opening in the plate assembly to assist with aligning the flange clamp to the plate assembly. When a fastener is coupled to the third opening **522** in the extended body portion **536**, the flange clamp **512** may be coupled and aligned with the plate assembly as will be described in further detail below. However, the flange clamp **512** may not fluidly seal the flange portion of the fluid connector to the plate assembly by only coupling the fastener to the projecting portion **534**.

[0064] Further, the extended body portion **536** is shown in FIGS. **5A** and **5B** to be offset vertically from the remainder of the clamp body **514** of the first flange clamp **512**. This is only one implementation. In other implementations, the extended body portion **536** may be disposed offset horizontally (e.g., FIG. **17**) or at an angle relative to the rest of the clamp body **514**. Thus, the orientation or position of the extended body portion **536** may vary in different implementations.

[0065] As noted above, the projecting portion **534** of the second flange clamp **512** assists with alignment and anti-rotation. With respect to alignment, the projecting portion **534** may be disposed within a corresponding opening in the plate assembly in a similar fashion as a key fits into a key slot. Referring, for example, to FIG. **6** of the present disclosure, a union plate **600** is shown. The union plate **600** may be formed as a plate body **602** with a plurality of defined openings therein. In the implementation of FIG. **6**, the union plate **600** is arranged such that a first connector opening **608** is defined at a first connector location **604** and a second connector opening **610** is defined at a second connector location **606**. Each of the first and second connector openings are defined in the union plate **600**. In other implementations, the union plate **600** may include only a single connector opening. In other implementations, the union plate **600** may include a plurality of connector openings.

[0066] In the implementation of FIG. **6**, for each connector opening, the plate **600** may include corresponding openings for a pair of flange clamps on each side thereof. For instance, the union plate **600** may include a first plurality of openings **612** for a first flange clamp (not shown) and a second plurality of openings **614** for a second flange clamp (not shown). In this example, the first flange clamp and second flange clamp may couple a first connector to the first connector location **604** on one side of the union plate **600**. Similarly, the union plate **600** may include a third plurality of openings **616** for a third flange clamp (not shown) and a fourth plurality of openings **618** for a fourth flange clamp (not shown). In this example, the third flange clamp and fourth flange clamp may couple a second connector to the second connector location **606** on one side of the union plate **600**. As also shown in the implementation of FIG. **6**, the union plate **600** may include one or more key openings **620** for receiving the projecting portion **534** of a corresponding flange clamp **512**. As shown, the key opening **620** may be sized and shaped based on the corresponding size and shape of

the projecting portion **534**. While each key opening **620** in FIG. **6** has a square shape, it is to be understood the key opening **620** may include any known shape including circular, oval, triangular, square, rectangular, pentagonal, hexagonal, octagonal, etc. In some implementations, the key opening **620** may be sized just large enough for a press-fit type connection with the projecting portion **534**. In other implementations, the key opening **620** may be over-sized compared to the projecting portion **534**.

[0067] In several implementations, the placement of fasteners through the third opening **522** in the extended body portion **536** of the flange clamp **512** and the key opening **620** of the union plate may not seal the fluid connector to the face of the plate body **602**. In other implementations, the placement of fasteners through the third opening **522** in the extended body portion **536** of the flange clamp **512** and the key opening **620** of the union plate may seal the fluid connector to the face of the plate body **602**. In some implementations, the fluid connector (not shown) may be fluidly sealed to the face of the plate body **602** when fasteners are securely fastened when inserted through the first opening **518** and second opening **520**. In yet other implementations, the fluid connector (not shown) may be fluidly sealed to the face of the plate body **602** when at least one fastener is securely fastened when inserted through either the first opening **518** or the second opening **520**.

[0068] In FIG. **22**, an example implementation of assembling a bulkhead assembly is illustrated. To facilitate the assembly process, FIGS. **7-15** of the present disclosure provide an example implementation that illustrates one or more steps in the assembly process. Before describing the process, it is to be understood that the different blocks shown in FIG. **22** are not intended to represent a sequential order of the assembly process. It is to be understood that the present disclosure is not limited to the order in which the blocks in FIG. **22** are arranged, but rather in some implementations one or more of the blocks in FIG. **22** may be omitted. In other implementations, there may be one or more additional blocks for executing the assembly process. In yet another implementation, the blocks in FIG. **22** may be arranged in a different order. Thus, the arrangement of blocks in FIG. **22** is intended to represent only one example implementation of the process for assembling a bulkhead assembly on a work machine, and there may be a plurality of ways the blocks in FIG. **22** may be executed including with fewer blocks being executed, additional blocks being executed, or the blocks being executed in different orders.

[0069] In any event, referring to FIG. **22**, the example implementation of the assembly process **2200** may be executed at block **2202** in which a first fluid connector **700** is positioned on a first side of a union plate **600**. As shown in FIG. **7**, the union plate **600** of FIG. **6** is provide as an example implementation of a union plate to be used in a bulkhead assembly. The union plate **600** may include the plurality of openings and keyhole openings as shown in FIG. **6**. For purposes of this disclosure, a keyhole opening may be an opening have a size and shape configured to receive a correspondingly sized and shaped body or structure. As described as one example in this disclosure, a keyhole opening includes a size and shape configured to receive a projecting portion of a flange clamp. In other examples, a keyhole opening may receive other bodies or structures disclosed herein. The first fluid connector **700** in FIG. **7** may be any standard connector capable of being coupled to a fluid line, hose, or cable. The first fluid connector **700** may be positioned in contact with the face of the plate body **602** as shown in FIG. **7**. Moreover, the first fluid connector **700** may include a defined passageway through which fluid flows therethrough. Thus, when positioning the first fluid connector **700** in contact with the face of the plate body **602**, the passageway of the first fluid connector **700** may be aligned with first connector opening **610**. In this manner, fluid may flow through the first fluid connector **700** and the first connector opening **610** to the other side of the union plate **600**.

[0070] Once the fluid connector **700** is arranged on the union plate **600**, the process **2200** may advance to block **2204** in which a first flange clamp **702** may be aligned on the union plate **600** adjacent to the fluid connector **700**. The first flange clamp **702** may be structurally similar to the

second flange clamp **512** of FIGS. 5A-5B. As shown in FIG. 7, the first flange clamp **702** may include a clamp body **704** having a raised portion **706** located between a first opening **708** and a second opening **710**. In some implementations, the first opening **708** and second opening **710** may be threaded openings. In other implementations, the first opening **708** and second opening **710** may be clearance or through-hole openings. In yet other implementations, one of the two openings may be a threaded opening and the other a non-threaded opening.

[0071] The first flange clamp **702** may include an extended body portion **714** as shown. The extended body portion **714** may include a projecting portion (not shown as it is disposed within a keyhole opening in the union plate **600**). The extended body portion **714** may define a third opening **712** as shown. A fastener (not shown) may be inserted into the third opening **712** to secure the first flange clamp **702** to the union plate **600**. To do so, the projecting portion (not shown) may be inserted through the keyhole opening **620** in the union plate **600** and a fastener may be secured on the opposite side of the union plate to retain the first flange clamp **702** to the union plate **600**. As described above, the projecting portion may be shaped and sized to fit in the keyhole opening **620**. Depending on the shape and size of both the projecting portion and the keyhole opening, the projecting portion may function as an anti-rotational feature or portion of the first flange clamp **702**.

[0072] As the first flange clamp **702** is positioned on the union plate **600**, the clamp body **704** may include a recessed portion on an opposite side thereof similar to the recessed portion **532** in FIG. 5B. A flange portion of the fluid connector **700** may be disposed within the recessed portion of the clamp body **704** to partially hold the fluid connector **700** in place and in contact or proximate contact with the union plate **600**.

[0073] Moreover, as the first flange clamp **702** is positioned on the union plate **600**, the first opening **708** and second opening **710** may be aligned with the fourth plurality of openings **618** formed in the union plate **600**. As will be described, fasteners may be connected through the fourth plurality of openings **618** to couple the first flange clamp **702** to the union plate **600**.

[0074] Once the first flange clamp **702** is aligned on the union plate **600**, the process **2200** of FIG. 22 may advance to block **2206** whereby a second flange clamp **802** may be coupled to a first side **800** of the union plate **600**. The second flange clamp **802** may be structurally similar to the second flange clamp **512** of FIGS. 5A-B and the first flange clamp **702** of FIG. 7. As shown in FIG. 8, the second flange clamp **802** may include a clamp body **804** having a raised portion **806** located between a first opening **808** and a second opening **810**. In some implementations, the first opening **808** and second opening **810** may be threaded openings. In other implementations, the first opening **808** and second opening **810** may be clearance or through-hole openings. In yet other implementations, one of the two openings may be a threaded opening and the other a non-threaded opening.

[0075] The second flange clamp **802** may include an extended body portion **814** as shown. The extended body portion **814** may include a projecting portion (not shown as it is disposed within a keyhole opening in the union plate **600**). The extended body portion **814** may define a third opening **812** as shown. A fastener (not shown) may be inserted into the third opening **812** to secure the second flange clamp **802** to the union plate **600**. To do so, the projecting portion (not shown) may be inserted through the keyhole opening **620** in the union plate **600** and a fastener may be secured on the opposite side of the union plate to retain the second flange clamp **802** to the union plate **600**. As described above, the projecting portion may be shaped and sized to fit in the keyhole opening **620**. Depending on the shape and size of both the projecting portion and the keyhole opening, the projecting portion may function as an anti-rotational feature or portion of the second flange clamp **802**.

[0076] As the second flange clamp **802** is positioned on the union plate **600**, the clamp body **804** may include a recessed portion on an opposite side thereof similar to the recessed portion **532** in FIG. 5B. A flange portion of the fluid connector **700** may be disposed within the recessed portion

of the clamp body **804** to partially hold the fluid connector **700** in place and in contact or proximate contact with the union plate **600**.

[0077] Moreover, as the second flange clamp **802** is positioned on the union plate **600**, the first opening **808** and second opening **810** may be aligned with the third plurality of openings **616** formed in the union plate **600**. As will be described, fasteners may be connected through the third plurality of openings **616** to couple the second flange clamp **802** to the union plate **600**.

[0078] Referring to FIG. **9** of the present disclosure, a portion of the second flange clamp **802** is shown coupled to the union plate **600**. As shown, the passageway defined in the fluid connector **700** is axially aligned with the connector opening **610**, and the first opening **808** and second opening **810** are aligned with the third plurality of openings **616** formed in the union plate **600**. In the example implementation of FIG. **9**, the union plate **600** is shown in a forwardmost position relative to the second flange clamp **802** in the sense that the face of the plate body **602** is in close proximity with a face of the second flange clamp **802**. In this implementation, and as shown in FIGS. **9** and **11** of the present disclosure, an inner face or surface **902** of the second flange clamp **802** is shown in contact with a surface of the flange portion of the connector **700**. When fasteners are used to securely tighten the second flange clamp **802** to the flange portion of the connector **700**, the position of the second flange clamp **802** relative to the union plate **600** is shown in FIGS. **9** and **11**. In this position, the second flange clamp **802** forms a recessed portion **900** in which the flange portion of the fluid connector **700** is disposed, and the flange portion of the fluid connector **700** is sealingly coupled to the union plate **600**.

[0079] In FIG. **9**, the second flange clamp **802** is shown having a projecting portion **1200** formed at the extended body portion **814**. The projecting portion **1200** may project through the keyhole opening **620** formed in the union plate **600**. As shown, the projecting portion **1200** projects a distance “*t*” from the inner face **902** of the second flange clamp **802**. As also shown, the union plate **600** may have a thickness “*d*”. In one example implementation, the distance “*t*” is greater than the thickness “*d*.” In one example implementation, the distance “*t*” is twice the thickness “*d*.” In a second example implementation, the distance “*t*” is at least twice the thickness “*d*.” In another example implementation, the distance “*t*” is at least three times the thickness “*d*.” In yet another example implementation, the distance “*t*” is approximately the same as the thickness “*d*.” In a further example implementation, the distance “*t*” is less than the thickness “*d*.” In the illustrated implementation of FIG. **9**, the projecting portion **1200** has a distance “*t*” that is greater than the plate thickness “*d*” and therefore extends through the keyhole opening **620** and past a first plate surface **1102** of the union plate **600**. Here, the projecting portion **1200** protrudes just far enough past the first plate surface **1102** to enable the second flange clamp **802** and fluid connector **700** to be retained in place with the union plate **600** without sealing the fluid connector **700** to the union plate **600**. In this arrangement, block **2208** of the assembly process **2200** is complete.

[0080] Once block **2208** is complete, the process **2200** may advance to block **2210** where one or more fasteners may be coupled to the projecting portions of the first flange clamp **702** and the second flange clamp **802**. In FIG. **10** of the present disclosure, one or more fasteners **1000** may be coupled to the projecting portions **1200** on a second side of the union plate **600**.

[0081] As shown in FIGS. **11** and **12**, a fastener **1000** may be coupled to the projecting portion **1200** of the second flange clamp **802** and the union plate **600** at a connection location **1204**. In FIG. **11**, due to the distance “*t*” of the projecting portion **1200** being greater than the plate thickness “*d*” (as shown in FIG. **9**), a gap **1100** may be defined between a surface **1104** of a flange portion of the fastener **1000** and the first plate surface **1102**. Due to the gap **1100**, secure tightening of the fastener **1000** to the projecting portion **1200** may not bias the clamping of the remaining fasteners (not shown) to the second flange clamp **802**. In other words, when the fastener **1000** is coupled to the projecting portion **1200**, the second flange clamp **802** does not seal against the union plate **600**. As shown in FIG. **11**, a second plate surface **1108** of the union plate **600** is just offset or displaced (i.e., not in contact with) from the inner face **902** of the second flange clamp **802** and a surface **1106** of

the fluid connector **700**. In one implementation, the surface **1106** of the fluid connector **700** (and, in some implementations, the inner face **902** of the second flange clamp **802**) may be in contact with the second plate surface **1108**, but it is not sealed in this implementation.

[0082] In FIG. **11** of the present disclosure, the second flange clamp **802** is shown in a configuration in which the flange portion of the connector **700** is disposed in a fluidly sealing connection with the union plate **600**. As will be described below, for this position to be achieved, fasteners will be secured through the first and second openings **808**, **810**, respectively, of the second flange clamp **802**. In a sealed position, an o-ring or seal **1202** may be disposed within the passageway of the fluid connector **700**. The o-ring or seal **1202** may be compressed between the flange portion of the fluid connector **700** and the second plate surface **1108** of the union plate **600**. In this implementation, the second flange clamp **802** may be spaced from the second plate surface **1108** of the union plate **600** such that in the sealed configuration, the flange portion of the connector **700** is sealed against the union plate **600**.

[0083] In FIG. **12** of the present disclosure, the flange portion of the connector **700** is not fluidly sealed against the second surface **1108** of the union plate **600**. Instead, the surface **1104** of the flange portion of the fastener **1000** is shown in contact with the first plate surface **1102** of the union plate **600**. In this implementation, the first plate surface **1102** of the union plate **600** is spaced from the second flange clamp **802** by a second gap,  $x$ . In other words, a second gap,  $x$ , is defined between the union plate **600** and the second flange clamp **802** in FIG. **12**. The height of the o-ring or seal **1202**, however, may be greater than the second gap,  $x$ . This greater height of the seal **1202** allows the seal **1202** to maintain its position as shown in FIG. **12** without moving therefrom. In some implementations, the height of the seal **1202** may be greater than a difference between the distance,  $t$ , and the thickness of the union plate **600**.

[0084] In block **2212** of the assembly process **2200** of FIG. **22**, a second fluid connector may be positioned on the second side of the union plate **600** opposite the first fluid connector. As shown in FIG. **13**, the first fluid connector **700** is disposed on a first side **1302** of the union plate **600** and a second fluid connector **1300** is positioned on a second side **1304** thereof. The second fluid connector **1300** in FIG. **13** may be any standard connector capable of being coupled to a fluid line, hose, or cable. The second fluid connector **1300** may be positioned in contact with the face of the plate body **602** as shown in FIG. **13**. Moreover, the second fluid connector **1300** may include a defined passageway through which fluid flows therethrough. Thus, when positioning the second fluid connector **1300** in contact with the face of the plate body **602**, the passageway of the second fluid connector **1300** may be aligned with first connector opening **610**. In this manner, fluid may flow through the first fluid connector **700**, the first connector opening **610** and to the other side of the union plate **600** where it flows through the second fluid connector **1300**.

[0085] Once the second fluid connector **1300** is arranged on the union plate **600**, the process **2200** may advance to blocks **2214** and **2216** in which a third flange clamp and a fourth flange clamp may be installed and aligned on the union plate **600** adjacent to the second fluid connector **1300**.

Referring to the example implementation of FIG. **14**, for example, a third flange clamp **1400** and a fourth flange clamp **1402** are shown. In this implementation, the third flange clamp **1400** and the fourth flange clamp **1402** may be structurally similar to one another. In other implementations, the third flange clamp **1400** and the fourth flange clamp **1402** may be structurally dissimilar to one another. In yet another implementation, the third flange clamp **1400** and the fourth flange clamp **1402** may be structurally similar to the first flange clamp **500** of FIGS. **5A-5B**. In a further implementation, the third flange clamp **1400** and the fourth flange clamp **1402** may be structurally similar to the first flange clamp **702** and second flange clamp **802** shown in FIGS. **7** and **8**, respectively. In several implementations, the third flange clamp **1400** and the fourth flange clamp **1402** may be conventional, “off-the-shelf” flange clamps. In other implementations, the third flange clamp **1400** and the fourth flange clamp **1402** may be structurally designed for connecting with the first flange clamp **702** and second flange clamp **802**.

[0086] In the illustrated implementation of FIG. 14 the third flange clamp **1400** and the fourth flange clamp **1402** may be structurally similar to the first flange clamp **500** of FIGS. 5A-5B. In the third flange clamp **1400** and the fourth flange clamp **1402**, each flange clamp may include a first opening and a second opening similar to the first opening **506** and second opening **508** of FIG. 5A. In one implementation, the pair of openings in the third flange clamp **1400** and the fourth flange clamp **1402** may be clearance openings, i.e., threadless openings. In another implementation, the pair of openings in the third flange clamp **1400** and the fourth flange clamp **1402** may be threaded openings.

[0087] The third flange clamp **1400** and the fourth flange clamp **1400** may be arranged adjacent to the second fluid connector **1300**. In one implementation, the third and fourth flange clamps may include a clamp body (e.g., the clamp body **502**) having a recessed portion (e.g., the recessed portion **528**). In this implementation, the recessed portion may be arranged such that a flange portion of the second fluid connector **1300** may be disposed therein when mounted to the union plate **600**.

[0088] Once the third and fourth flange clamps are positioned on the union plate **600** and their corresponding first and second openings are aligned with the third plurality of openings **616** and fourth plurality of openings **618** in the union plate **600**, the assembly process **2200** of FIG. 22 can advance to block **2218**. In block **2218**, fasteners may be used to couple the first flange clamp to the third flange clamp and the second flange clamp to the fourth flange clamp. Referring to FIG. 14, for example, a plurality of fasteners (e.g., bolts, screws, etc.) **1404** may be used for coupling the first flange clamp **702** to the third flange clamp **1400** and the second flange clamp **802** to the fourth flange clamp **1402**. In assembly process **2200** of FIG., 22 the fasteners **1404** may be tightened in block **2220** to seal the flange clamps to the union plate **600**, compress the seal **1202**, and fluidly coupling the first fluid connector **700** and the second fluid connector **1300** in a sealing manner to the union plate and with one another. As the fasteners **1404** are tightened in block **2220**, the flange clamps may be disposed in a secured position **1406** with the union plate **600** as best shown in FIG. 15.

[0089] As shown in FIG. 15, when the fasteners **1404** are tightened and the flange clamps move to the secured position **1406**, the union plate **600** may be moved away from the surface **1104** of the fastener **1000**. As this happens, the gap **1100** is present between the union plate **600** and the surface **1104** of the fastener **1000**.

[0090] In one implementation of block **2220**, the tightening of the fasteners **1404** may be done in a known sequential manner such as in a star pattern. Other patterns of tightening the fasteners **1404** may be performed during block **2220**. In some applications, the fasteners can be sensitive to being over-torqued and tightened. In block **2220**, the fasteners **1404** may be tightened in a sequential pattern to avoid over-torquing the fasteners and ensuring equal pressure is applied via each of the fasteners **1404**.

[0091] In one implementation, the fasteners **1404** may include threads at one end thereof for being threadedly coupled to the first and second flange clamps. For example, in this implementation, the first and second openings (e.g., openings **508**, **510**) in the third flange clamp **1400** and fourth flange clamp **1402** may be clearance or through-hole openings without any threads. As such, the fasteners **1404** may be inserted first through the first and second openings (e.g., openings **508**, **510**) in the third and fourth flange clamps and the third plurality of openings **616** and the fourth plurality of openings **618** in the union plate **600**. In this implementation, the first opening **708** and the second opening **710** in the first flange clamp **702** may be threaded. In the same manner, the first opening **808** and the second opening **810** in the second flange clamp **802** may be threaded. Thus, the threaded portion of the fasteners **1404** may be threadedly coupled to the threads in the first and second openings in the first and second flange clamps. As the fasteners **1404** are tightened in block **2220**, the first flange clamp **702** and the third flange clamp **1402** move towards one another to clamp against their respective side of the union plate **600**. Similarly, the second flange clamp **802**

and the fourth flange clamp **1404** are moved towards one another to clamp against their respective side of the union plate **600**. In this implementation, the fasteners **1404** may be inserted on the second side **1304** of the union plate **600**. Once the flange clamps are clamped to the union plate **600**, the fasteners **1000** coupled to the projection portions **1200** may be removed.

[0092] In another implementation, the first and second openings (e.g., openings **508**, **510**) in the third flange clamp **1400** and fourth flange clamp **1402** may be threaded openings, and the first opening **708** and the second opening **710** in the first flange clamp **702** as well as the first opening **808** and the second opening **810** in the second flange clamp **802** may be clearance or through-hole openings without threads. In this implementation, the fasteners **1404** may be longer such that the threaded portion of each fastener **1404** extends past the openings in the first and second flange clamps so that a washer and nut, for example, may be coupled to the threaded portion. Further, in this implementation, it may also be possible to insert the longer fasteners **1404** through the fasteners on the first side **1302** of the union plate **600** or the second side **1304** of the union plate **600**.

[0093] In yet another implementation, the first and second openings (e.g., openings **508**, **510**) in the third flange clamp **1400** and fourth flange clamp **1402** may be threaded, whereas the first opening **708** and the second opening **710** in the first flange plate **702** as well as the first opening **808** and the second opening **810** in the second flange clamp **802** may be clearance or through-hole openings. As such, the fasteners **1404** may be inserted first through the first and second openings in the first and second flange clamps and the third plurality of openings **616** and the fourth plurality of openings **618** in the union plate **600**. Thus, the threaded portion of the fasteners **1404** may be threadably coupled to the threads in the first and second openings in the third and fourth flange clamps.

[0094] Referring to illustrated implementations of FIGS. **16** and **17** of the present disclosure, it is noted that each flange clamp can be shaped and structured differently than the first flange clamp **702** and second flange clamp **802**. For example, the position of the extended body portion and flange portion may be arranged differently than that in the first flange clamp **702** and second flange clamp **802**. In other words, the extended body portion **714** of the first flange clamp **702** and the extended body portion **814** of the second flange clamp **802** is shown in FIGS. **7-15** to be offset vertically when coupled to the union plate **600**. This too is shown in FIG. **16**. In FIG. **17**, however, the extended body portions and thus projected portions of each flange clamp is offset to the side horizontally. In other non-illustrated example implementations, the extended body portion of a respective flange clamp may be located at an outer edge or periphery of the clamp body. In one example implementation, the extended body portion may be disposed angularly with respect to a horizontal or vertical axis passing through the flange clamp. In another example implementation, the extended body portion may be arranged at a 10°, 20°, 30°, 40°, 45°, 50°, 60°, 70°, or 80° relative to a vertical axis passing through the centers of both the first and second openings of the flange clamp. In other words, the location of the third opening and projecting portion of the flange clamp may differ from that shown in FIGS. **7-15**.

[0095] In FIG. **16** of the present disclosure, an example implementation of a bulkhead assembly **1600** is illustrated. In this assembly **1600**, a first fluid connector **1602** and a second fluid connector **1604** are coupled to the same side of the union plate **600**. Here, the first fluid connector **1602** may be fluidly coupled to the union plate **600** via a first flange clamp assembly **1606**. The first flange clamp assembly **1606** may include a first flange clamp **1610** and a second flange clamp **1612**. The second fluid connector **1604** may be fluidly coupled to the union plate **600** via a second flange clamp assembly **1608**. The second flange clamp assembly **1608** may also include a first flange clamp **1610** and a second flange clamp **1612**. Each of the first and second flange clamps may include a plurality of openings **1614** in substantially similar locations as the first openings **708**, **808** and second openings **710**, **712** shown and described previously. The plurality of openings **1614** may be threaded or clearance openings (i.e., without threads).

[0096] The first flange clamp **1610** and the second flange clamp **1612** may include extended body

portions that are offset vertically as shown in FIG. 16. Each extended body portion may form a projecting portion **1618** with a defined opening **1616** similar to the third openings **714, 814** described above. The opening **1616** is offset vertically in the illustrated implementation of FIG. 16 similar to that of the first and second flange clamps **702, 802** of FIGS. 7 and 8.

[0097] In the implementation of FIG. 16, a pair of fluid connectors **1602, 1604** are shown. In other implementations, only the first fluid connector **1602** or the second fluid connector **1604** may be coupled to the union plate **600**. In yet other implementations, there may be more two or more fluid connectors coupled to one side of the union plate.

[0098] In yet a different implementation of the present disclosure, an example implementation of a bulkhead assembly **1700** is illustrated in FIG. 17. In this assembly **1700**, a first fluid connector **1702** and a second fluid connector **1704** are coupled to the same side of the union plate **600**. Here, the first fluid connector **1702** may be fluidly coupled to the union plate **600** via a first flange clamp assembly **1706**. The first flange clamp assembly **1706** may include a first flange clamp **1710** and a second flange clamp **1712**. The second fluid connector **1704** may be fluidly coupled to the union plate **600** via a second flange clamp assembly **1708**. The second flange clamp assembly **1708** may also include a first flange clamp **1710** and a second flange clamp **1712**. Each of the first and second flange clamps may include a plurality of openings **1714** in substantially similar locations as the first openings **708, 808** and second openings **710, 712** shown and described previously. The plurality of openings **1714** may be threaded or clearance openings (i.e., without threads).

[0099] The first flange clamp **1710** and the second flange clamp **1712** may include extended body portions that are offset horizontally as shown in FIG. 17. Each extended body portion may form a projecting portion **1718** with a defined opening **1716** similar to the third openings **714, 814** described above. The opening **1716** is offset horizontally in the illustrated implementation of FIG. 17 unlike that of the first and second flange clamps **702, 802** of FIGS. 7 and 8 and the flange clamps of FIG. 16. In each flange clamp of FIGS. 7, 8, 16, and 17, the extended body portion and corresponding projecting portion is located at an outer edge or periphery of the respective flange clamp. This allows a fastener to be coupled to the projecting portion to help with retention and assembly/disassembly.

[0100] In the aforementioned illustrated implementations of FIGS. 16 and 17, the flange clamp assemblies **1606, 1608, 1706, 1708** are each illustrated as including a combination of flange clamps. For example, the first flange clamp assembly **1606** is shown in FIG. 16 as including a combination of a first flange clamp **1610** and a second flange clamp **1612**. The first and second flange clamps **1610, 1612** are each shown as including two of the four mounting openings **1614** and one of the two retention openings **1616**. In this implementation, the first and second flange clamps may be referred to as a half flange clamp given each has half of the mounting openings and half of the retention openings.

[0101] In alternative implementations, however, each flange clamp may be designed differently. In one implementation, a flange clamp may be a full flange clamp having all of the mounting openings necessary for coupling to the union plate **600** and a corresponding one or more flange clamps on the opposite side of the union plate **600**. The full flange clamp, for example, may include four mounting openings **1614**. In one implementation, the full flange clamp may include a pair of extended body portions with each including a retention opening **1616**. In yet another implementation, the full flange clamp may include all of the mounting openings **1614** and only a single retention opening **1616**. In a further implementation, the full flange clamp may include two or more retention openings **1616** and a plurality of mountings openings (i.e., two or more). With a full flange clamp, the location of the projecting portion and retention opening may be at a periphery or outer edge of the full flange clamp similar to the illustrated implementations of FIGS. 16 and 17.

[0102] In another implementation, a flange clamp may be a quarter flange clamp including at least one mounting opening and a retention opening. In an example implementation, a flange clamp assembly having four mounting openings may be formed by four quarter flange clamps. In this



implementation, each quarter flange clamp may include a single mounting opening and a single retention opening. Moreover, in this implementation, each quarter flange clamp may include an extended body portion including a projecting portion and the retention opening. Each quarter flange clamp may couple a fluid connector to the union plate similar to the previously described implementations.

[0103] In FIGS. **16** and **17**, the first flange clamp assembly **1606**, **1706** and the second flange clamp assembly **1608**, **1708** are shown on only one side of the union plate **600**. However, in some implementations, the flange clamp assemblies may be coupled to the opposite side of the union plate **600** as well. In other words, in some implementations, the flange clamp assemblies may be coupled to both sides of the union plate. In other implementations, the flange clamp assemblies may be coupled to either or both sides of the union plate **600**. For example, in one implementation, the flange clamp assemblies of either FIG. **16** or **17** may be installed on a first side of the union plate. In a second implementation, the flange clamp assemblies of either FIG. **16** or **17** may be installed on a second side of the union plate. In a third implementation, the flange clamp assemblies of either FIG. **16** or **17** may be installed on the first and second sides of the union plate.

[0104] In one example implementation, the flange clamp assemblies of either FIG. **16** or **17** (or a different flange clamp assembly that is not illustrated such as, e.g., an assembly having a full flange clamp or several quarter flange clamps) may be installed on the first and second sides of the union plate. In this implementation, each flange clamp assembly may include the retention opening and an anti-rotational feature as described above. In this implementation, the method of assembly or disassembly may benefit from being able to remove the flange clamp assembly on either the first side or the second side of the union plate without having to remove the other flange clamp assembly. The retention opening formed in the projecting portion of each flange clamp may allow each flange clamp assembly to remain coupled to the union plate while a different flange clamp assembly is disassembled therefrom. Another benefit is the ability to assemble the flange clamp assemblies to the union plate in any order. Thus, the order of assembly is not dependent on which side of the union plate one of the flange clamp assemblies with a retention feature is provided. For sake of this disclosure, the retention feature refers to the projecting portion and retention opening (e.g., key opening **1616**, **1716** or third opening **712**, **812**) as previously described.

[0105] In an implementation with the flange clamp assemblies of either FIG. **16** or **17** (or a different flange clamp assembly that is not illustrated such as, e.g., an assembly having a full flange clamp or several quarter flange clamps) installed on the first and second sides of the union plate, the flange clamp assembly on one side of the union plate may include threaded openings and the flange clamp assembly on the opposite side thereof may include non-threaded, clearance openings. In this manner, a fastener may be first inserted through the flange clamps having the non-threaded clearance openings and then coupled to the opposite flange clamps having the threaded openings.

[0106] In another implementation with the flange clamp assemblies of either FIG. **16** or **17** (or a different flange clamp assembly that is not illustrated such as, e.g., an assembly having a full flange clamp or several quarter flange clamps) installed on the first and second sides of the union plate, the flange clamp assembly on one side of the union plate may include non-threaded, clearance openings and the flange clamp assembly on the opposite side thereof may include non-threaded, clearance openings. In this implementation, the fasteners may be first installed on either side of the union plate **600** and passed through the flange clamps on both sides of the union plate **600** before a nut or similar fastener is coupled to the threaded portion of the fastener for coupling the flange clamp assemblies to the union plate.

[0107] In several implementations, the union plate described herein may be formed of sheet metal. Other materials may be used in other implementations including steel, aluminum, titanium, plastic, etc. In yet other implementations, the union plate may be formed as a casting and/or machined.

[0108] In one implementation of the present disclosure, a flange clamp may be formed by investment casting. The flange clamp may be formed of a ductile iron and plated for corrosion

resistance. In other implementations, the flange clamp may be formed by a machining process of billet material or an additive manufacturing process. In some implementations, the flange clamp may be formed from steel, aluminum, titanium, or a plastic material. The material selection of the flange clamp may be at least partially based on a minimum strength requirement. The minimum strength requirement may be a function of a type of pressure application the flange clamp will be used in. In one non-limiting example, the minimum stress requirement may be approximately 330 MPa with a minimum elongation of fracture of 3% in a high pressure application. In another non-limiting example, the minimum stress requirement may be approximately 215 MPa with a minimum elongation of fracture of 10% in a low or standard pressure application.

[0109] In some implementations, the thickness of each flange clamp may be designed to have a minimum thickness to accommodate a required minimum thread length. For example, a fastener may have a threaded length,  $l$ , and a flange clamp has a thickness,  $t$ , and a minimum tapped length,  $m$ , in a mating opening. In one implementation, the thickness,  $t$ , of the flange clamp is at least as thick as the minimum tapped length,  $m$ . In another implementation, the thickness,  $t$ , of the flange clamp may be at least 1.5 times the minimum tapped length,  $m$ . In yet another implementation, the thickness,  $t$ , of the flange clamp may be at least twice the minimum tapped length,  $m$ . In a further implementation, the thickness,  $t$ , of the flange clamp may be at least 1-3 times the minimum tapped length,  $m$ . For purposes of this disclosure, the thickness,  $t$ , of the flange clamp is at least the same if not greater than the minimum tapped length,  $m$ .

[0110] In another example implementation of the present disclosure, a different bulkhead assembly **1800** is shown in FIGS. **18-21**. In this implementation, it may be possible to independently assemble and disassemble the mating fluid connector from either side of the union plate. This may be achieved with a different structural design for the retention feature (i.e., the projecting portion and retention opening) from the previously described implementations. In FIG. **18**, for example, the bulkhead assembly **1800** may include a first fluid connector **1802** and a second fluid connector **1804**. In this illustrated implementation, the first fluid connector **1802** and the second fluid connector **1804** are shown coupled to the same side of a union plate **1900** having a plate body **1902**. Although not shown, a third fluid connector may be fluidly coupled to the first fluid connector **1802**, and a fourth fluid connector may be fluidly coupled to the second fluid connector **1804**. The third and fourth fluid connectors may be located and coupled to the opposite side of the union plate **1900**.

[0111] In FIG. **18**, a first flange clamp assembly **1806** may couple the first fluid connector **1802** to the union plate **1900**, and a second flange clamp assembly **1808** may couple the second fluid connector **1804** to the union plate **1900**. The first flange clamp assembly **1806** and the second flange clamp assembly **1808** may include a plurality of first openings **1810** for coupling each assembly to the union plate **1900**. In particular, the first flange clamp assembly **1806** may be coupled to another flange clamp assembly located on the opposite side of the union plate **1900** via a plurality of fasteners coupled thereto via the plurality of first openings **1810**. In FIG. **18**, a first fastener **1812** and a second fastener **1814** are shown for coupling the flange clamp assemblies to the union plate **1900**.

[0112] Referring to FIG. **19**, a portion of the union plate **1900** is shown. Here, the union plate **1900** is formed by a plate body **1902** having a plurality of openings formed therein. For example, the union plate **1900** may include a connector opening **1904** formed therein. The fluid connectors may be arranged relative to the union plate **1900** such that fluid may be transferred therebetween through the connector opening **1904**. The union plate **1900** may also include one or more first coupler openings **1906** that each may be aligned with a corresponding one of the plurality of first openings **1810** in the respective flange clamp assembly.

[0113] In the implementation of FIG. **19**, the union plate **1900** may also include one or more elongate slot openings **1908**. The one or more elongate slot openings **1908** may be oval or egg-like in shape in some implementations. In other implementations, including the one depicted in FIG. **19**,

the one or more elongate slot openings **1908** may be shaped to include a rounded or curved portion **1910** and one or more substantially straight or linear portions **1914**. In other implementations, the one or more elongate slot openings **1908** may be substantially rectangular or shaped in another manner.

[0114] The union plate **1900** of FIG. **19** may also include one or more second coupler openings **1912**, as shown. In one implementation, each of the one or more second coupler openings **1912** may be larger than the one or more first coupler openings **1906**. In another implementation, each of the one or more second coupler openings **1912** may be smaller than the one or more first coupler openings **1906**. In a further implementation, each of the one or more second coupler openings **1912** may be approximately the same size as the one or more first coupler openings **1906**.

[0115] In at least one implementation, the one or more elongate slot openings **1908** may be larger than the one or more first coupler openings **1906** and the one or more second coupler openings **1912**. In another implementation, the one or more elongate slot openings **1908** may be smaller than the one or more first coupler openings **1906** and the one or more second coupler openings **1912**. In yet another implementation, the one or more elongate slot openings **1908** may be larger than either the one or more first coupler openings **1906** or the one or more second coupler openings **1912** but not both. In a further implementation, the one or more elongate slot openings **1908** may be approximately the same size as one or both of the one or more first coupler openings **1906** and the one or more second coupler openings **1912**.

[0116] In FIG. **20** of the present disclosure, an example implementation of a flange clamp **2000** of the first flange clamp assembly **1806** or second flange clamp assembly **1808** is shown. The flange clamp **2000** may include a clamp body having a first body portion **2002** and a second body portion **2006**. The second body portion **2006** may be offset from the first body portion **2002** as shown in FIG. **20**. In particular, the first body portion **2002** may be arranged along a first axis, A, and the second body portion **2006** may be arranged along a second axis, B. In the implementation of FIG. **20**, the first axis, A, and the second axis, B, may be parallel to one another. In other implementations, the first and second axes may be angled relative to one another but not parallel.

[0117] The flange clamp **2000** may further include a raised portion **2004** formed on one side of the first body portion **2002**. Similar to the other raised portions described herein, the raised portion **2004** may form a stiffening rib or structure for supporting the flange clamp **2000**. The raised portion **2004** may be an optional feature in this implementation as well as the other implementations described herein. In the implementation of FIG. **20**, the second body portion **2006** is offset from one side of the first body portion **2002** that is opposite from the side of the first body portion **2002** in which the raised portion **2004** is located. In other words, the second body portion **2006** is offset from a first surface **2012** or side of the first body portion **2002**, whereas the raised portion **2004** is formed on a second surface **2014** or side of the first body portion **2002**.

[0118] The flange clamp **2000** may include a first post portion **2008** and a second post portion **2010**. The first post portion **2008** may be aligned along a third axis, C, in FIG. **20** whereas the second post portion **2010** may be aligned along a fourth axis, D. In one implementation, the third axis, C, may be parallel to the fourth axis, D. In another implementation, the third axis and fourth axis may be angled relative to one another but not parallel to one another. In any event, the third post portion **2008** and the fourth post portion **2010** may be offset from one another as shown in FIG. **20**. The second body portion **2006** may be coupled to the first body portion **2002** via the first post portion **2008**. In FIG. **20**, the first post portion **2008** is shown as being substantially perpendicular relative to the first surface **2012** of the first body portion **2002**. In other implementations, the first post portion **2008** may be angled relative to the first surface **2012** at an angle greater than 90°. In some implementations, the first post portion **2008** may be angled relative to the first surface **2012** at an angle between 90°-180°. In a further implementation, the first post portion **2008** may be angled relative to the first surface **2012** at an angle between 90°-150°. In yet a further implementation, the first post portion **2008** may be angled relative to the first surface **2012**

at an angle between 90°-135°.

[0119] In one implementation, the first post portion **2008** may be located generally at one end of the second body portion **2006** and the second post portion **2010** may be located generally at an opposite end thereof. In another implementation, the second body portion **2006** may have a first end and a second end, and the first post portion **2008** may be located generally towards the first end and the second post portion **2010** may be located generally towards the second end. In a further implementation, the second body portion **2006** may have a first end and a second end, and the first post portion **2008** may be located closer towards the first end compared to the second post portion **2010**, and the second post portion **2010** may be located closer towards the second end compared to the first post portion **2008**.

[0120] The second post portion **2010** in FIG. **20** is shown being disposed in a generally vertical or downward orientation relative to the second body portion **2006**. In one implementation, the second post portion **2010** may extend from the second body portion **2006** generally perpendicularly relative to the second axis, B. In another implementation, the second post portion **2010** may extend from the second body portion **2006** at an angle between 10°-170° relative to the second axis, B. In yet another implementation, the second post portion **2010** may extend from the second body portion **2006** at an angle between 20°-160° relative to the second axis, B. In a further implementation, the second post portion **2010** may extend from the second body portion **2006** at an angle between 30°-150° relative to the second axis, B. In yet a further implementation, the second post portion **2010** may extend from the second body portion **2006** at an angle between 45°-135° relative to the second axis, B. In still a further implementation, the second post portion **2010** may extend from the second body portion **2006** at an angle between 60°-120° relative to the second axis, B. In yet another implementation, the second post portion **2010** may extend from the second body portion **2006** at approximately 90° relative to the second axis, B.

[0121] The flange clamp **2000** of FIG. **20** may form part of the first flange clamp assembly **1806** and the second flange clamp assembly **1808** of FIG. **18**. For example, in one implementation, the flange clamp **2000** may be located on both sides of each fluid connector. Moreover, in the illustrated implementation of FIGS. **18-21**, the flange clamp **2000** may be located on both sides of the first fluid connector **1802** as well as the second fluid connector **1804**. In the implementation of FIG. **18**, for example, there may be a pair of flange clamps **2000** that form the first flange clamp assembly **1806** and a pair of flange clamps **2000** that form the second flange clamp assembly **1808**. Moreover, in the implementation of FIG. **18**, a third flange clamp assembly (not shown) may be coupled to the union plate **1900** on the opposite side thereof with the first flange clamp assembly, and a fourth flange clamp assembly (not shown) may be coupled to the union plate **1900** on the opposite side thereof with the second flange clamp assembly. In each instance, there may be a pair of flange clamps **2000** that form the third flange clamp assembly (not shown) and a pair of flange clamps **2000** that form the fourth flange clamp assembly (not shown).

[0122] In the implementation of FIG. **20**, the flange clamp **2000** is shown without the first openings **1810** depicted. The first openings **1810**, however, may be formed in the first body portion **2002**. In one implementation, the first openings **1810** may be formed in the first body portion **2002** on each side of the raised portion **2004**. For example, a first of the first openings **1810** may be formed therein on one side of the raised portion **2004** closest to the first post portion **2008**, and a second of the first openings **1810** may be formed therein on an opposite side of the raised portion **2004** furthest from the first post portion **2008**. In one implementation, each of the first openings **1810** may be threaded openings. In another implementation, each of the first openings **1810** may be non-threaded, clearance openings. In yet another implementation, at least one of the first openings **1810** may be a threaded opening. In still another implementation, at least one of the first openings **1810** may be a non-threaded opening.

[0123] As shown in FIG. **21**, a retention opening **2102** may be formed in the second post portion **2010** of the flange clamp **2000**. The retention opening **2102** may be a threaded opening in one

implementation. In another implementation, the retention opening **2102** may be a non-threaded, clearance opening. In some implementations, the first openings **1810** in the flange clamp **2000** may be non-threaded, clearance openings whereas the retention opening **2102** is a threaded opening. In other implementations, the first openings **1810** in the flange clamp **2000** may be threaded openings whereas the retention opening **2102** is a non-threaded, clearance opening. In another implementation, the first openings **1810** and the retention opening **2102** in the flange clamp **2000** may be non-threaded, clearance openings. In yet a further implementation, the first openings **1810** and the retention opening **2102** in the flange clamp **2000** may be threaded openings.

[0124] In one implementation, the flange clamps **2000** of the first clamp assembly **1806** on the first side of the union plate **1900** has threaded first openings **1810**, whereas the flange clamp used for the third flange clamp assembly located on a second, opposite side of the union plate **1900** has non-threaded, clearance first openings. In this implementation, fasteners may be first inserted through the non-threaded, clearance first openings in the flange clamps on the second side of the union plate **1900** and then threaded to the threaded first openings **1810** of the first flange clamp assembly **1806** during the assembly process. In other implementations, the opposite may be true where the first openings in the first flange clamp assembly **1806** are non-threaded clearance openings **1810**, and the third flange assembly includes flange clamps with threaded first openings. In still other implementations, the flange clamps on both sides of the union plate **1900** may include non-threaded, clearance openings such that fasteners may pass through each of the first openings in the first and third flange clamp assemblies and a nut or similar fastener may be used to couple the flange clamp assemblies to one another and the union plate **1900**.

[0125] Referring to the illustrated implementation of FIG. **21**, the first flange clamp assembly **1806** is shown being coupled to the union plate **1900**. In this implementation, the first flange clamp assembly **1806** includes a pair of flange clamps **2000**. During the assembly process, each flange clamp **2000** may be aligned with the different openings in the union plate **1900** including the coupler opening **1904**, the one or more first coupler openings **1906**, the one or more elongate slot openings **1908**, and the one or more second openings **1912**.

[0126] The second body portion **2006** and second post portion **2010** may be integrally formed with one another to form a J-like structure. In other implementations, the second body portion **2006** may be coupled to the second post portion **2010** via a fastener, a slide-connection, latch, adhesive, welding, etc. To assemble the flange clamp **2000** to a first side of the union plate **1900**, the second post portion **2010** may be first inserted through one of the one or more elongate slots **1908** formed in the union plate **1900**. As such, the second post portion **2010** is located on the second side of the union plate **1900** opposite the first side. The flange clamp **2000** may then be rotated or maneuvered to enable the second body portion **2006** to pass through the same elongate slot **1908** to the second side of the union plate **1900**. Next, the flange clamp **2000** may be rotated or moved again to align the second post portion **2010** with one of the one or more second coupler openings **1912** formed in the union plate **1900**. Here, the second coupler opening **1912** that is aligned with the corresponding elongate slot and first coupler openings **1906** is the one in which the second post portion **2010** is aligned with. Once the second post portion **2010** is aligned with the second coupler opening **1912**, the flange clamp **2000** may be maneuvered such that the second post portion **2010** passes through the second coupler opening **1912** and returns to the first side of the union plate **1900**.

[0127] In this position, the first body portion **2002** of the flange clamp **2000** is located on the first side of the union plate **1900**, and the second body portion **2006** of the flange clamp **2000** is located on the second side of the union plate **1900**. This assembly process is partially shown in FIG. **21** where the second post portion **2010** and second body portion **2006** are located on the second side of the union plate **1900**, and the flange clamp **2000** is rotated in a counterclockwise direction indicated by arrow **2100** to align the second post portion **2010** with the second coupler opening **1912**. In doing so, the first openings **1810** in the flange clamp **2000** may also be aligned with the one or more first coupler openings **1906** in the union plate **1900**. Moreover, a curved portion of the first

body portion **2002** of the flange clamp is aligned with the connector opening **1904** formed in the union plate **1900** such that the flange clamp **2000** may be used for clamping and fluidly sealing the first fluid connector **1802** to the union plate **1900**.

[0128] In the aforementioned assembly process, as the second post portion **2010** and second body portion **2006** are maneuvered relative to the union plate **1900** to align the second post portion **2010** with the second coupler opening **1912**, the flange clamp **2000** may be tilted or rotated in such a way that the flange clamp **2000** is arranged at an angle relative to the union plate **1900**. The rounded or curved portion **1910** of the elongate slot **1908** may help to allow for this maneuverability of the flange clamp **2000** relative to the union plate **1900**. Moreover, the second post portion **2010** may include a rounded or curved profile to also assist with the maneuverability of the flange clamp **2000** relative to the union plate **1900**.

[0129] A pair of flange clamps **2104** forming the third flange clamp assembly are partially shown in FIG. **21** such that each flange clamp **2104** may be coupled to the flange clamps **2000** that form the first flange clamp assembly **1806**. Each flange clamp **2104** may be structured similarly to the flange clamp **2000** such that each flange clamp **2104** includes a first body portion, a second body portion, a first post portion, and a second post portion. When assembling and coupling the first flange clamp assembly **1806** to the third flange clamp assembly, each of the flange clamps may be at least partially located on both the first and second sides of the union plate. In the implementation shown in FIG. **21**, the first body portion **2002** of each flange clamp **2000** of the first flange clamp assembly **1806** is located on the first side of the union plate **1900** while the second body portion **2006** thereof is located on the second side of the union plate **1900**. In the same way, a first body portion of each flange clamp **2104** is located on the second side of the union plate **1900** whereas a second body portion is located on the first side of the union plate **1900**.

[0130] In the example implementations of FIGS. **18** and **21**, the first fastener **1812** may be used for passing through and/or coupling to the first openings **1810** in the flange clamps **2000**. The first fastener **1812** may therefore be used for coupling the flange clamps **2000** to the union plate **1900** for fluidly sealing and clamping the fluid connector **1802** to the union plate **1900**. The second fastener **1814** may be used for coupling to the retention feature, i.e., the second post portion **2010**, via the retention opening **2102**. In some implementations, when the second fastener **1814** couples the second post portion **1810** to the union plate **1900**, the coupling thereof helps retain the flange clamp **2000** to the union plate **1900** to allow the flange clamps on the opposite side thereof to be assembled or disassembled. Here, the flange clamp **2000** may not be disassembled and removed from the union plate **1900** during this process. In other implementations, when the second fastener **1814** couples the second post portion **1810** to the union plate **1900**, the coupling thereof may form an anti-rotational feature that inhibits or prevents the flange clamp **2000** from rotating relative to the union plate **1900**.

[0131] In the example implementation of FIGS. **18-21**, the second post portion **2010** is shown having a rounded or curved profile. In other implementations, the second post portion **2010** may have a square, rectangular, triangular, pentagonal, hexagonal, octagonal, oval-like shape, or any other known type of shaped profile. Likewise, the second coupler openings may also be shaped in accordance with the shaped profile of the second post portion **2010**. In this way, the second post portion **2010** may fit within the second coupler opening **1912** like a key being inserted into a key opening.

[0132] In FIG. **23** of the present disclosure, another example implementation of a bulkhead assembly **2300** is illustrated. In this assembly **2300**, a first fluid connector **2302** and a second fluid connector **2304** are shown being coupled to one side of a union plate **2324**. In several implementations, the union plate **2324** may be similar to the union plate **600** of FIG. **6**. In FIG. **23**, the first fluid connector **2302** may be fluidly coupled to the union plate **2324** via a first flange clamp assembly **2306**. The first flange clamp assembly **2306** may include a first flange clamp **2310** and a second flange clamp **2312**. The second fluid connector **2304** may be fluidly coupled to the

union plate **2324** via a second flange clamp assembly **2308**. The second flange clamp assembly **2308** may also include a first flange clamp **2310** and a second flange clamp **2312**. In at least one implementation, only a single fluid connector with a single flange clamp assembly having one first flange clamp **2310** and one second flange clamp **2312** may be coupled to the union plate **2324**. In another implementation, there may be additional fluid connectors as well as additional flange clamp assemblies coupled to the union plate **2324**.

[0133] As shown in the implementation of FIG. **23**, each of the first and second flange clamps may include a plurality of openings **2314** in substantially similar locations as the first openings **708**, **808** and second openings **710**, **712** shown and described previously. The plurality of openings **2314** may be threaded or clearance openings (i.e., without threads). As previously described, fasteners (not shown) may be coupled to or through the plurality of openings **2314** for coupling each flange clamp to the union plate **2324**. Flange clamps (not shown) such as those shown in FIGS. **4** and **14** of the present disclosure may be coupled to the opposite side of the union plate **2324** for coupling to the first and second flange clamp assemblies of FIG. **23**. Alternatively, flange clamp assemblies such as those shown in FIG. **17** may be coupled to the opposite side of the union plate **2324** shown in FIG. **23**.

[0134] The first flange clamp **2310** and the second flange clamp **2312** may include extended body portions that are offset as shown in FIGS. **23** and **24**. In particular, each flange clamp may include at least two extended body portions, as shown. In FIG. **23**, for example, the first flange clamp **2310** and second flange clamp **2312** may include a first extended body portion **2320** and a second extended body portion **2322**. A first keyhole or retention opening **2316** may be formed in the first extended body portion **2320**, and a second keyhole or retention opening **2318** may be formed in the second extended body portion **2322**.

[0135] As best shown in FIG. **24**, each flange clamp may include the first extended body portion **2320** formed at a first end **2408** of the flange clamp and the second extended body portion **2322** formed at a second end **2410** thereof. Each of the first and second extended body portions may form a projecting portion. For example, the first extended body portion **2320** may form a first projecting portion **2404**, and the second extended body portion **2322** may form a second projecting portion **2406**. The first projecting portion **2404** may project through a corresponding opening in the union plate **2324** and the second projecting portion **2406** may project through another corresponding opening in the union plate **2324**. In this manner, fasteners may initially couple to the first and second projecting portions on the opposite side of the union plate **2324** shown in FIG. **23** to retain the flange clamp **2312** to the plate **2324**.

[0136] In the implementation of FIG. **24**, the flange clamp **2312** may include a raised portion **2400** on one side thereof and a recessed portion **2402** on the opposite side thereof. In the illustrated implementation, the first projecting portion **2404** and the second projecting portion **2406** are arranged to project substantially perpendicularly to a plane along which an inner surface **2412** of the flange clamp **2312** lies. Moreover, the first extended body portion **2320** and the second body portion **2322** are shown being offset from one another by approximately 180°. In other implementations, the first and second body portions may be offset from one another by less than 180°. For example, in one implementation, the first and second body portions may be offset from one another by 150°. In another implementation, the first and second body portions may be offset from one another by 120°. In a further implementation, the first and second body portions may be offset from one another by 90°. In yet a further implementation, the first and second body portions may be offset from one another by less than 90°.

[0137] In the present disclosure, the implementations described herein may be used on any agricultural, construction, or forestry equipment. For example, the implementations described herein may be used on sprayers, harvesters, tractors, and any other type of heavy equipment. The implementations described herein may be used on any four bolt flange assemblies. The implementations described herein may be located on a chassis, body frame, main frame, wing

frame, auxiliary frame, bulkhead module, and the like. The implementations described herein may be provided at locations of pump assemblies that provide pressure and flow to motors (e.g., wheel motors). Any frame of a work machine or vehicle (e.g., agricultural, construction, forestry, cement truck, dump truck, refuse truck, fuel truck, work vehicle, passenger vehicle, etc.) that includes a frame with a bulkhead may include any one of the implementations described herein. Any type of rail car, bus, motorhome, plane, boat, etc. that includes a frame with a bulkhead may include any one of the implementations described herein.

[0138] While exemplary implementations incorporating the principles of the present disclosure have been described herein, the present disclosure is not limited to such implementations. Instead, this application is intended to cover any variations, uses, or adaptations of the disclosure using its general principles. Further, this application is intended to cover such departures from the present disclosure as come within known or customary practice in the art to which this disclosure pertains.

## Claims

1. A flange clamp for coupling a fluid connector to a bulkhead plate of a bulkhead assembly, the flange clamp comprising: a clamp body having a curved inner surface configured to engage with the fluid connector; a plurality of openings formed in the clamp body, the plurality of openings including at least a first opening, a second opening, and a third opening; at least one extended body portion integrally formed at an outer periphery of the clamp body; a retaining portion integrally formed with the at least one extended body portion, the retaining portion projecting away from the at least one extended body portion; wherein the retaining portion is configured to be disposed within an opening formed in the bulkhead plate, where the retaining portion is configured to selectively maintain an orientation of the clamp body on the bulkhead plate.
2. The flange clamp of claim 1, wherein the plurality of openings formed in the clamp body are axially aligned with one another.
3. The flange clamp of claim 1, wherein the third opening is formed in the at least one extended body portion, the third opening defined through the retaining portion.
4. The flange clamp of claim 1, wherein the clamp body comprises a first end and a second end, the second end spaced from the first end, where the at least one extended body portion extends from the second end of the clamp body.
5. The flange clamp of claim 1, wherein the clamp body comprises a first end and a second end, the second end spaced from the first end, where the at least one extended body portion extends from the clamp body at a location between the first end and the second end.
6. The flange clamp of claim 5, wherein the first opening is formed in the clamp body adjacent the first end, the second opening is formed in the clamp body adjacent the second end, and the third opening is formed in the at least one extended body portion at a location between the first and second openings.
7. The flange clamp of claim 1, wherein the retaining portion comprises a shaped profile having at least three sides.
8. The flange clamp of claim 7, wherein the retaining portion comprises a triangular-shaped profile, square-shaped profile, rectangular-shaped profile, pentagonal-shaped profile, hexagonal-shaped profile, or octagonal-shaped profile.
9. The flange clamp of claim 1, wherein the clamp body comprises a first body portion and a second body portion, the first body portion being offset from the second body portion.
10. The flange clamp of claim 9, further comprising a post portion located between the first body portion and the second body portion.
11. The flange clamp of claim 10, wherein the retaining portion is arranged parallel to and offset from the post portion.
12. The flange clamp of claim 1, wherein at least one of the plurality of openings is a threaded



opening.

**13.** The flange clamp of claim 1, wherein the at least one extended body portion comprises a first extended body portion and a second extended body portion.

**14.** The flange clamp of claim 13, wherein the clamp body comprises a first end and a second end, the second end spaced from the first end; wherein the first extended body portion extends from the first end of the clamp body, and the second extended body portion extends from the second end of the clamp body.

**15.** A bulkhead assembly for fluidly coupling a first fluid connector to a second fluid connector, comprising: a union plate comprising a plate body forming a plurality of coupler openings, the plurality of coupler openings including at least a connector opening, a first coupler opening, a second coupler opening, and a third coupler opening; a flange clamp configured to fluidly couple the first fluid connector to the union plate, the flange clamp comprising: a clamp body having an inner surface configured to engage with the first fluid connector, the inner surface disposed along at least a portion of the connector opening; a plurality of openings formed in the clamp body, the plurality of openings including at least a first opening, a second opening, and a third opening; at least one extended body portion integrally formed at an outer periphery of the clamp body; a retaining portion formed in the at least one extended body portion, the retaining portion projecting in a direction away from the at least one extended body portion; wherein, in a first configuration, the flange clamp is arranged relative to the union plate such that the retaining portion is disposed within the third coupler opening formed in the union plate, where in the first configuration the retaining portion is configured to selectively maintain an orientation of the clamp body with respect to the union plate.

**16.** The bulkhead assembly of claim 15, wherein, in the first configuration, the clamp body and the at least one extended body portion are located on a first side of the union plate, and the retaining portion is located at least partially on the second side of the union plate.

**17.** The bulkhead assembly of claim 15, wherein: the retaining portion comprises a shape having a first profile; the third coupler opening is shaped having a second profile, the first profile having a shape similar to the second profile.

**18.** The bulkhead assembly of claim 15, further comprising a second flange clamp having a second clamp body, the second clamp body forming at least a fourth opening and a fifth opening; wherein, the flange clamp is coupled to a first side of the union plate, and the second flange clamp is coupled to a second side of the union plate; wherein, in a second configuration, the retaining portion is disposed within the third coupler opening, the first opening and fourth opening are aligned with the first coupler opening, and the second opening and the fifth opening are aligned with the second coupler opening.

**19.** The bulkhead assembly of claim 18, wherein the second clamp body comprises a second extended body portion of the at least one extended body portion, the second extended body portion including a second retaining portion; wherein, the second retaining portion is disposed within a fourth coupler opening formed in the union plate, the fourth coupler opening being spaced from the third coupler opening.

**20.** A method of assembling a bulkhead assembly for fluidly coupling a first fluid connector to a second fluid connector, the method of assembly comprising: positioning the first fluid connector on a first side of a union plate such that the first fluid connector is aligned with a connector opening formed in the union plate; aligning a first flange clamp adjacent to the first connector on the first side of the union plate; locating a retaining portion of the first flange clamp to project through an opening formed in the union plate; coupling a first fastener to a retaining opening formed in the retaining portion of the first flange clamp; and selectively maintaining an orientation of the first flange clamp with respect to the union plate via the coupling of the first fastener to the retaining portion.

---

