United States Patent	12396070
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Chow; Nicholas

Methods and systems for TRIAC set point based control of power delivery

Abstract

In an aspect, data representative of an electrical value is received and a target value for an inductive load based on the electrical value is accessed from memory of the controller. A target value for an inductive load can be accessed based on the electrical value. A transfer function based algorithm can be implemented for determining a set point value using the electrical value the set point value can be applied on a triode for alternating current (TRIAC). Operation of the inductive load to the target power responsive to the applying of the set point value on the TRIAC can be adjusted. The operation of the inductive load at the target power causes operation of the inductive load at the target value.

Inventors:	**Chow; Nicholas (Boston, MA)**
Applicant:	**SharkNinja Operating LLC** (Needham, MA)
Family ID:	**1000008765411**
Assignee:	**SharkNinja Operating LLC (Needham, MA)**
Appl. No.:	**18/501450**
Filed:	**November 03, 2023**

Prior Publication Data

Document Identifier	Publication Date
US 20240407058 A1	Dec. 05, 2024

Related U.S. Application Data

continuation parent-doc WO PCT/US2023/077571 20231024 PENDING child-doc US 18501450
continuation parent-doc US 18204687 20230601 US 11792895 20231017 child-doc US PCT/US2023/077571

Publication Classification

Int. Cl.: H05B6/08 (20060101); **A47J37/07** (20060101); **H05B1/02** (20060101)

U.S. Cl.:

CPC   **H05B6/08** (20130101); **A47J37/0709** (20130101); **A47J37/0763** (20130101); **A47J37/0786** (20130101); **H05B1/0261** (20130101);

Field of Classification Search

CPC: A47J (37/0641); A47J (37/0664); A47J (37/0709); A47J (37/0763); A47J (37/0786); A47J (37/079); H02P (25/04); H02P (7/295); H05B (1/0261); H05B (3/64); H05B (6/08)

USPC: 219/665

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5470142	12/1994	Sargeant	312/265.5	A47L 15/23
6868777	12/2004	Higgins et al.	N/A	N/A
7426885	12/2007	McLemore et al.	N/A	N/A
7703389	12/2009	McLemore et al.	N/A	N/A
8109263	12/2011	Pliml	N/A	N/A
9441838	12/2015	Baker	N/A	N/A
9883770	12/2017	Hunt et al.	N/A	N/A
9930897	12/2017	Blue et al.	N/A	N/A
10021887	12/2017	McLemore et al.	N/A	N/A
10045546	12/2017	Giebel et al.	N/A	N/A
10292531	12/2018	Hancock et al.	N/A	N/A
10327584	12/2018	Shingler et al.	N/A	N/A
10327588	12/2018	Dahle et al.	N/A	N/A
10327589	12/2018	Dahle et al.	N/A	N/A
10455979	12/2018	Colston et al.	N/A	N/A
10478016	12/2018	McLemore et al.	N/A	N/A
10588461	12/2019	Dahle	N/A	N/A
10660473	12/2019	Dahle et al.	N/A	N/A
10674866	12/2019	Colston	N/A	N/A
10694892	12/2019	Colston	N/A	N/A
10772467	12/2019	Dahle	N/A	N/A
10888193	12/2020	Dahle et al.	N/A	N/A
10952564	12/2020	Dahle et al.	N/A	N/A
10959572	12/2020	Dahle et al.	N/A	N/A
10986960	12/2020	Colston	N/A	N/A
10995964	12/2020	Dahle	N/A	N/A
11162684	12/2020	Colston et al.	N/A	N/A
11172688	12/2020	Powell et al.	N/A	N/A
11181276	12/2020	Colston et al.	N/A	N/A

Patent No.	Date	Name	Class	CPC
11181277	12/2020	Donnelly et al.	N/A	N/A
11206948	12/2020	Measom et al.	N/A	N/A
11684212	12/2022	Dahle et al.	N/A	N/A
11732895	12/2022	Chow et al.	N/A	N/A
2010/0092275	12/2009	Savitz	N/A	N/A
2013/0201316	12/2012	Binder	701/2	G07C 3/02
2018/0139973	12/2017	Flood et al.	N/A	N/A
2018/0168397	12/2017	Colston	N/A	N/A
2019/0290064	12/2018	Colston et al.	N/A	N/A
2019/0290069	12/2018	Colston et al.	N/A	N/A
2019/0320669	12/2018	Powell et al.	N/A	N/A
2020/0093145	12/2019	Powell et al.	N/A	N/A
2020/0116349	12/2019	Rahmani et al.	N/A	N/A
2020/0202027	12/2019	Chan et al.	N/A	N/A
2020/0214501	12/2019	Gafford et al.	N/A	N/A
2020/0214503	12/2019	Altenritter	N/A	N/A
2020/0237139	12/2019	Colston	N/A	N/A
2020/0275804	12/2019	Dahle	N/A	N/A
2021/0007550	12/2020	Puertas et al.	N/A	N/A
2021/0052108	12/2020	Dahle	N/A	N/A
2021/0169269	12/2020	Meadows et al.	N/A	N/A
2021/0196078	12/2020	Colston et al.	N/A	N/A
2021/0196079	12/2020	Dahle et al.	N/A	N/A
2021/0228020	12/2020	Hanks et al.	N/A	N/A
2021/0235927	12/2020	Colston	N/A	N/A
2021/0244233	12/2020	Bush et al.	N/A	N/A
2021/0251423	12/2020	Dahle et al.	N/A	N/A
2021/0282590	12/2020	Dahle et al.	N/A	N/A
2021/0302027	12/2020	Dahle	N/A	N/A
2021/0315416	12/2020	Fullmer et al.	N/A	N/A
2021/0352923	12/2020	Li et al.	N/A	N/A
2021/0369052	12/2020	Fullmer et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2016297715	12/2016	AU	N/A
2016216635	12/2016	AU	N/A
2018251790	12/2018	AU	N/A
2019202070	12/2018	AU	N/A
2019202071	12/2018	AU	N/A
2019202074	12/2018	AU	N/A
2019202075	12/2018	AU	N/A
2019342959	12/2020	AU	N/A
2941277	12/2016	CA	N/A
3037207	12/2018	CA	N/A
3037934	12/2018	CA	N/A
3037936	12/2018	CA	N/A
3038088	12/2018	CA	N/A
3066299	12/2019	CA	N/A
203852233	12/2013	CN	N/A

205391021	12/2015	CN	N/A
107529920	12/2017	CN	N/A
110353518	12/2018	CN	N/A
110353519	12/2018	CN	N/A
110353520	12/2018	CN	N/A
110353525	12/2018	CN	N/A
111493681	12/2019	CN	N/A
106998964	12/2020	CN	N/A
212016000022	12/2016	DE	N/A
212016000157	12/2017	DE	N/A
102019107552	12/2019	DE	N/A
1517093	12/2005	EP	N/A
1514502	12/2005	EP	N/A
2605690	12/2013	EP	N/A
2433530	12/2013	EP	N/A
3364838	12/2018	EP	N/A
3243269	12/2019	EP	N/A
3677157	12/2019	EP	N/A
3375335	12/2019	EP	N/A
3865031	12/2020	EP	N/A
2555054	12/2017	GB	N/A
2558532	12/2017	GB	N/A
2572489	12/2018	GB	N/A
2572491	12/2018	GB	N/A
2572492	12/2018	GB	N/A
2001193939	12/2000	JP	N/A
2018526036	12/2017	JP	N/A
20180039541	12/2017	KR	N/A
20180067383	12/2017	KR	N/A
2017044598	12/2016	WO	N/A
2021138455	12/2020	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion received for PCT/US2023/077571, mailed on Mar. 7, 2024, 10 pages. cited by applicant

Primary Examiner: Abraham; Ibrahime A

Assistant Examiner: Iskra; Joseph W

Attorney, Agent or Firm: Mintz, Levin, Cohn, Ferris, Glovsky and Popeo, P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a bypass continuation of PCT Application No. PCT/US23/77571, filed on Oct. 24, 2023 and entitled "METHODS AND SYSTEMS FOR TRIAC SET POINT BASED CONTROL OF POWER DELIVERY," which claims priority to U.S. application Ser. No. 18/204,687 filed on Jun. 1, 2023

entitled "Methods and Systems for Triac Set Point Based Control of Power Delivery," the entire contents of which are hereby incorporated by reference in their entireties.

FIELD

(1) A grill system including a smoke unit, and methods for initiating the combustion of fuel contained therein and controlling the delivery of power to inductive loads are provided.

BACKGROUND

(2) Smoke can be used in a variety of cooking devices and with a variety of cooking operations to impart flavor. As an example, grills and grilling devices can come equipped with smoking capabilities, or the means with which to impart smoke flavor into food cooked with these grills and grilling devices. However, electric cooking appliances may only be able to impart limited smoke flavor or no smoke flavor into food cooked therewith. Further, in grilling systems which impart smoke flavor into food, control of the smoke output can be challenging.

(3) Additionally, the quality of the smoke output can depend on how the fuel source used to generate the smoke is ignited. For example, if the fuel source is over-ignited by an igniter, the ignitor can provide an excessive amount of energy to the fuel source, such that there is too much combustion for the amount of airflow within the system and not enough oxygen supply to sustain a clean and efficient burn. For example, if the fuel source is under-ignited by the igniter, the igniter can provide too little energy to the fuel source, such that there is not a large enough ember generated to ensure a self-sustained combustion reaction that will spread throughout the rest of the fuel source in a consistent manner. In order to generate optimal smoke production for cooking, there is an ideal range of energy that must be provided to the fuel source from the ignitor such that there is just the right amount of heat to create a sustained combustion reaction, but not so much that combustion region starves itself of oxygen or burns through a fuel source more vigorously than intended.

(4) However, reliably monitoring the performance of the fuel source ignition process, such that it results in optimized smoke production for cooking, can be difficult due to the nature of the perceivable outputs from combustion. For example, the physical outputs resulting from combustion of the fuel source are heat and combustion products such as smoke compounds or CO_2— therefore, in order to achieve closed loop control for combustion, a given control system must be able to detect those outputs from combustion in a statistically significant way. However, designing a system that would be cost effective and reliable enough to detect either of these outputs can be impractical. Additionally, closed loop control from the perspective of detecting combustion products as an input can also be challenging because it can be infeasible or impossible to implement a sensor that is safe, cost effective, and able to withstand the operating environment of a smoke unit.

(5) Inductive loads such as shaded-pole motors are used to operate various types of devices such as exhaust fans, cooling fans, table fans, hairdryers, relays, and air conditioners. Shaded-pole motors are often coupled with Triodes for Alternating Currents (TRIACs) to modulate the operating speed of fans primarily because these motors are robust, cost effective, and reliable. However, the performance of these motors is adversely affected by several factors such as, e.g., variations in supply voltages, a low power factor, low initial torque when devices are turned on, inefficiency due to the presence of a shading coil, and so forth.

(6) Accordingly, there remains a need for improved systems and methods for ignition of a smoke unit fuel source and improving the accuracy with which the operating speeds of various devices are modulated based on power delivered to the motors of these devices.

SUMMARY

(7) A cooking device, a smoke unit, and methods of cooking food using a cooking device with a smoke unit are provided. Related apparatuses and techniques are also described.

(8) In one aspect, a cooking device is provided and can include a housing having a base defining a

hollow cooking chamber and a movable cover coupled to the base. The movable cover can be configured to cover an opening in the housing to the hollow cooking chamber. In some embodiments, the movable cover can be in the form of a lid or door. The cooking device can also include a smoke unit coupled to the housing, and the smoke unit can include a fuel box defining an interior chamber in fluid communication with the hollow cooking chamber. The smoke unit can also include an igniter proximate the fuel box and configured to ignite fuel contained in the fuel box. The cooking device can also include an electronic controller in operable communication with the igniter. The electronic controller can be configured to determine an average rate of energy supplied to the igniter during a predetermined period of time of activation of the igniter and during an initial ignition operating mode of the igniter, determine an average temperature of a region proximate the igniter during the predetermined period of time, and adjust a maximum time of activation of the igniter when the igniter is operating in the initial ignition operating mode during a subsequent period of time following the predetermined period of time based on the determined average rate of energy and the determined average temperature. In some embodiments, the electronic controller can be configured to adjust the maximum time of activation of the igniter based on an operating mode of the smoke unit.

(9) While the cooking device can have a variety of configurations, in some embodiments, the cooking device can include a fan coupled to the housing, in fluid communication with the fuel box, and in operable communication with the electronic controller, and the electronic controller can be configured to adjust an amount of power delivered to the fan during the initial ignition operating mode. In some embodiments, the electronic controller can be configured to adjust the amount of power delivered to the fan when a difference between a temperature of the region proximate the igniter and a temperature of air within the hollow cooking chamber is less than or equal to a predetermined temperature difference threshold. In some embodiments, the electronic controller can be configured to adjust the amount of power delivered to the fan when the temperature of the air within the hollow cooking chamber is less than a predetermined temperature threshold. In some embodiments, the electronic controller is configured to adjust the amount of power delivered to the fan when the rate of energy supplied to the igniter is less than a predetermined threshold. In some embodiments, the movable cover can be in the form of a lid or door.

(10) In another aspect, a system is provided and can include at least one data processor and memory storing instructions, which when executed by the at least one data processor, cause the at least one data processor to perform operations including receiving data characterizing a plurality of measurements of a rate of energy supplied to an igniter of a smoke unit and of a temperature of a region proximate the igniter, each of the plurality of measurements acquired during a predetermined period of time during which the igniter is activated and during an initial ignition operating mode of the igniter; determining, based on the received data, an average rate of energy supplied to the igniter during the predetermined period of time and an average temperature of the region proximate the igniter during the predetermined period of time; determining, based on the determined average rate of energy supplied to the igniter and the determined average temperature of the region proximate the igniter, a maximum time of activation of the igniter when the igniter is operating in the initial ignition operating mode; determining whether a total length of time during which the igniter is activated exceeds the maximum time of activation; and causing the igniter to deactivate in response to determining that the total length of the time exceeds the determined maximum time of activation.

(11) One or more of the following features can be included in any feasible combination. For example, the operations can further include receiving second data characterizing an operating mode of the smoke unit, and the maximum time of activation can be determined based on the received second data. For example, the operations can further include receiving third data characterizing a temperature of the air within a hollow cooking chamber in fluid communication with the smoke unit, and determining, based on the received third data, whether the hollow cooking chamber is in a

cold temperature state. For example, the operations can further include receiving fourth data characterizing a temperature of the region proximate the igniter; and the determining of whether the smoke unit is in a cold temperature state can include determining whether a difference between the temperature of the region proximate the igniter and the temperature of the air within the hollow cooking chamber is less than or equal to a predetermined temperature difference threshold. For example, the determining of whether the smoke unit is in a cold temperature state can include determining whether the temperature of the region proximate the igniter is less than a predetermined temperature threshold. For example, the determining of whether the smoke unit is in a cold temperature state can include determining whether the temperature of the air within the hollow cooking chamber is less than the predetermined temperature threshold. For example, the operations can further include in response to determining that the smoke unit is in a cold temperature state, determining instructions for operating a fan in fluid communication with the smoke unit in a fan compensation mode; and providing the instructions to a controller of the fan to cause the fan to operate in the fan compensation mode.

(12) In another aspect, data characterizing a plurality of measurements of a rate of energy supplied to an igniter of a smoke unit and of a temperature of a region proximate the igniter can be received. Each of the plurality of measurements can be acquired during a predetermined period of time during which the igniter is activated and during an initial ignition operating mode of the igniter. An average rate of energy supplied to the igniter during the predetermined period of time and an average temperature of the region proximate the igniter during the predetermined period of time can be determined based on the received data. A maximum time of activation of the igniter when the igniter is operating in the initial ignition operating mode can be determined based on the determined average rate of energy supplied to the igniter and the determined average temperature of the region proximate the igniter. Whether a total length of time during which the igniter is activated exceeds the maximum time of activation can be determined. The igniter can be deactivated in response to determining that the total length of the time exceeds the determined maximum time of activation.

(13) One or more features can be included in any feasible combination. For example, second data characterizing an operating mode of the smoke unit can be received, and the maximum time of activation can be determined based on the second received data. For example, third data characterizing a temperature of the air within a hollow cooking chamber in fluid communication with the smoke unit can be received, and whether the smoke unit is in a cold temperature state can be determined based on the received third data. For example, fourth data characterizing a temperature of the region proximate the igniter can be received, and the determining of whether the smoke unit is in a cold temperature state can include determining whether a difference between the temperature of the region proximate the igniter and the temperature of the air within the hollow cooking chamber is less than or equal to a predetermined temperature difference threshold. For example, the determining of whether the smoke unit is in a cold temperature state can include determining whether the temperature of the region proximate the igniter is less than a predetermined temperature threshold. For example, the determining of whether the smoke unit is in a cold temperature state can include determining whether the temperature of the air within the hollow cooking chamber is less than the predetermined temperature threshold.

(14) In one aspect, a device is provided and can include a power sensor, a temperature sensor, a triode for alternative current (TRIAC), an inductive load, and an electronic controller that includes memory. The TRIAC can be in operable communication with the electronic controller and the inductive load. The power sensor is in operable communication with the electronic controller and is configured to detect data representative of an electrical value. The electronic controller is configured to access, from the memory, a target value for the inductive load based on the electrical value, implement a transfer function based algorithm for determining a set point value using the electric value, apply the set point value on the TRIAC, and adjust operation of the inductive load to

the target power responsive to the application of the set point value on the TRIAC, the operation of the inductive load at the target power causes the operation of the inductive load at the target value.

(15) In some embodiments, the device may further comprise a fan including at least one fan blade that is operably coupled to the inductive load. In some embodiments, the inductive load can be a shaded-pole motor that controls rotational speed of the at least one fan blade disposed on the fan. Further, the implementing of the transfer function based algorithm can be based on at least one transfer function. The at least one transfer function can be based on a linear relationship between a plurality of power values of the inductive load at the electrical value and a plurality of speeds of the inductive load the electrical value. It is noted that the target value is a target speed.

(16) The at least one transfer function enables mapping a plurality of speeds of the inductive load relative to the electrical value with the plurality of power values at the electrical value. The target speed is included in the plurality of speeds and the target power is included in the plurality of power values. The electrical value is a supply voltage, a current, or a power. In some embodiments, the adjusting of the operation of the inductive load can include increasing an amount of power delivered to the inductive load from a current power to the target power. In other embodiments, the adjusting of the operation of the inductive load can include decreasing an amount of power delivered to the inductive load from a current power to the target power.

(17) In some embodiments, the electronic controller is further configured to determine, using the temperature sensor, a current temperature of the inductive load, compare the current temperature to a threshold temperature range, wherein the threshold temperature range is from 15° C. to 50° C., and initiate a starting condition compensation algorithm responsive to the current temperature being within the threshold temperature range or below the temperature threshold range. The initiation of the starting condition compensation algorithm can include applying a decaying value to a starting power, and driving the inductive load with the starting power, upon which the decaying value is applied, for a predetermined time frame.

(18) In another aspect, a method implemented by a controller is provided and can include receiving an electrical value. Further, a target value for an inductive load that is based on the electrical value may be accessed by the controller via the memory of the controller, a transfer function based algorithm the set point value can be applied on a triode for alternating current (TRIAC). Additionally, operation of the inductive load may be adjusted responsive to the applying of the set point value on the TRIAC. The operation of the inductive load at the target power causes operation of the inductive load at the target value. In some embodiments, the inductive load can be a shaded-pole motor that is coupled to a fan.

(19) In yet another aspect, a system is provided and can include a power source, a temperature sensor, a triode for alternative current (TRIAC), an inductive load, and at least one data processor that is communicatively coupled to the TRIAC. The at least one data processor can store instructions, which when executed by the at least one data processor, causes the at least one data processor to perform various operations. One or more of the following features can be included in any feasible combination. For example, the operations can include determining an electrical value, accessing a target value for the inductive load that is specific to the electrical value, implementing a transfer function based algorithm for determining a set point value using the electric value, applying the set point value on the TRIAC, and adjusting operation of the inductive load to the target power responsive to the applying of the set point value on the TRIAC, the operation of the inductive load at the target power causes operation of the inductive load at the target value.

(20) In some aspects, the operations further comprise determining, using the temperature sensor, a current temperature of the inductive load, and comparing the current temperature to a threshold temperature range, wherein the threshold temperature range is from 15° C. to 50° C., and initiating a starting condition compensation algorithm responsive to the current temperature being within the threshold temperature range or below the temperature threshold range.

(21) The details of one or more variations of the subject matter described herein are set forth in the

accompanying drawings and the description below. Other features and advantages of the subject matter described herein will be apparent from the description and drawings, and from the claims.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) These and other features will be more readily understood from the following detailed description taken in conjunction with the accompanying drawings, in which:

(2) FIG. **1** is a front perspective view of a cooking device according to an embodiment;

(3) FIG. **2** is a rear perspective view of the cooking device of FIG. **1**;

(4) FIG. **3**A is a perspective view of another embodiment of a cooking device;

(5) FIG. **3**B is a cross-sectional view of the cooking device of FIG. **3**A;

(6) FIG. **4**A is a side perspective view of the exemplary smoke unit for use with embodiments of the cooking devices described herein;

(7) FIG. **4**B is a rear perspective view of the smoke unit of FIG. **4**A;

(8) FIG. **4**C is a side cross-sectional view of the smoke unit of FIG. **4**A;

(9) FIG. **4**D is a partial cross-sectional view of the smoke unit of FIG. **4**A;

(10) FIG. **4**E is a side perspective view of a lid of the smoke unit of FIG. **4**A;

(11) FIG. **4**F is an exploded view of the smoke unit of FIG. **4**A;

(12) FIG. **5** is a schematic diagram illustrating components of the cooking device of FIG. **1**A;

(13) FIG. **6** illustrates a flow chart for controlling the speed of the fan when the cooking device **10** is operating in fan compensation mode, according to one or more embodiments described and illustrated herein;

(14) FIG. **7** illustrates a graphical representation of values that can be calculated by the controller using a first transfer function, according to some embodiments described and illustrated herein;

(15) FIG. **8** illustrates a three dimensional graphical representation of values that can be calculated by the controller using a second transfer function, according to some embodiments described and illustrated herein;

(16) FIG. **9** depicts a two-dimensional graphical representation including only the TRIAC set point values and electric power values;

(17) FIG. **10** depicts a set point included as part of an alternating current (AC) waveform;

(18) FIG. **11** depicts a non-linear relationship between operating speeds of the fan blades based on variations in the set point of the TRIAC;

(19) FIG. **12** depicts a substantially linear relationship between electric power values and operating speeds;

(20) FIG. **13**A depicts a graphical representation that shows a relationship between supply voltages and electric power values at various set points, according to some embodiments described and illustrated herein;

(21) FIG. **13**B depicts fitting lines that indicate relationships between electric power values and supply voltages at various set point values;

(22) FIG. **13**C illustrates a graphical representation includes an intersection point of various fitting lines and a plurality of additional supply voltage values and a plurality of additional electric power values;

(23) FIG. **14** depicts a graphical representation that shows a relationship between set points of the TRIAC and the electric power values at these set points;

(24) FIG. **15** depicts a graphical representation of a sigmoid function;

(25) FIG. **16** depicts a graphical representation that includes a line that fits the data used to generate the graphical representation of FIG. **15**, according to some embodiments described and illustrated herein;

(26) FIG. **17** depicts a graphical representation of an electric power delivered to an inductive load upon which the decaying value is applied over a particular time frame, according to some embodiments described and illustrated herein;

(27) FIG. **18** depicts a graphical representation of the operating speed of the inductive load based on the gradual reduction of the electric power delivered to the inductive load, as illustrated in FIG. **17**;

(28) FIG. **19** is a block diagram of an exemplary computing system in accordance with an illustrative implementation of the current subject matter.

(29) It is noted that the drawings are not necessarily to scale. The drawings are intended to depict only typical aspects of the subject matter disclosed herein, and therefore should not be considered as limiting the scope of the disclosure.

DETAILED DESCRIPTION

(30) Certain exemplary embodiments will now be described to provide an overall understanding of the principles of the structure, function, manufacture, and use of the devices and methods disclosed herein. One or more examples of these embodiments are illustrated in the accompanying drawings, and additional examples of specific system structures, functions, manufactures, uses, and related methods can be found in U.S. application Ser. Nos. 17/733,237, 17/663,582, 18/307,595, 18/307,583, and 18/079,781, each of which is incorporated by reference herein in its entirety Those skilled in the art will understand that the devices and methods specifically described herein and illustrated in the accompanying drawings are non-limiting exemplary embodiments and that the scope of the present invention is defined solely by the claims. The features illustrated or described in connection with one exemplary embodiment may be combined with the features of other embodiments. Such modifications and variations are intended to be included within the scope of the present invention.

(31) Further, in the present disclosure, like-named components of the embodiments generally have similar features, and thus within a particular embodiment each feature of each like-named component is not necessarily fully elaborated upon. Additionally, to the extent that linear or circular dimensions are used in the description of the disclosed systems, devices, and methods, such dimensions are not intended to limit the types of shapes that can be used in conjunction with such systems, devices, and methods. A person skilled in the art will recognize that an equivalent to such linear and circular dimensions can easily be determined for any geometric shape.

(32) In general, methods and systems for open-loop ignition of a smoke unit fuel source are provided. The open-loop ignition process can determine an average rate of energy supplied to the igniter during a predetermined period of time of activation of the igniter and during an initial ignition operating mode of the igniter. The open-loop ignition process can then determine an average temperature of a region proximate the igniter during the predetermined period of time adjust a maximum time of activation of the igniter when the igniter is operating in the initial ignition operating mode during a subsequent period of time following the predetermined period of time based on the determined average rate of energy and the determined average temperature. After the maximum time of activation has elapsed, the igniter can be deactivated.

(33) In addition to describing methods and systems for open-loop ignition of a smoke unit fuel source, the present disclosure also describes methods and systems for controlling the delivery of power to inductive loads. As stated above, devices that utilize inductive loads, e.g., shaded-pole motors, to control the operating speeds of fans disposed in these devices suffer from numerous drawbacks. The performance of shaded-pole motors are negatively impacted by supply voltage variations, a low power factor, and low initial torque during device activation.

(34) The transfer function based power delivery system described herein addresses and overcomes these drawbacks. In particular, the system is implemented by a controller of a cooking device and operates to receive data representative of a supply voltage from a power source that is external to the controller. A power sensor that is communicatively coupled to the controller can operate to

detect the supply voltage and route data representative of the supply voltage to the controller. The controller then accesses a target operating speed for the inductive load that is specific to the supply and implements a transfer function based algorithm to determine a set point value using the electric value. In particular, the controller then determines a set point value specific to a target power and the supply voltage that is delivered to the device in which the controller is disposed. The controller applies the set point value to a TRIAC of the device and adjusts the operation of the inductive load to the target power based on the application of the set point value. The operation of the inductive load at the target power ensures that the inductive load operates at the target operating speed.

(35) The use of the transfer function based algorithm, which includes one or more transfer functions to control the operating speeds of motors, provides various benefits. Specifically, the use of transfer functions improves the amount of mechanical rotational energy (output consistency) generated by the shaded-pole motors and the accuracy with which the operating speeds of these motors are modulated. The system described herein also provide these devices with power compensation and regulation under various conditions, e.g., during initiation (e.g., starting) of a device from an inactive or "cold" state. Additionally, the use of transfer functions enables efficient use of memory because these transfer functions can be approximated and solved using a set of polynomial expressions.

(36) FIGS. **1-2** illustrate a cooking device **10** according to an embodiment and for use in some implementations of the current subject matter. The cooking device **10** can be used to cook food in a variety of cooking modes, including conductive and convective modes (e.g., sauté, grill, bake, air fry, dehydrate, roast, broil, etc.). The cooking device **10** includes a base **12** and a movable cover, such as a lid **14**, movably coupled to the base **12**, such as via a hinge **16**. Together, the base **12** and the lid **14** can be referred to generally as a housing and can define an interior cooking chamber **20** that is sized to receive a variety of food products and/or food containers (e.g., a baking tray, a rack, etc.). A seal **15** can be located at a perimeter of the base **12** and/or the lid **14** to assist in sealing the interior cooking chamber **20** at the point of connection between the base **12** and the lid **14** when the lid **14** is in a closed position. The seal **15** can generally operate like a gasket and can be any material capable of operating as a seal, as would be known by a person skilled in the art. For example, the seal **15** can be rubber, plastic, fiberglass, metal, or any other material.

(37) The base **12** can include a cooking surface **18** upon which a food product can be placed during an operating procedure of the cooking device **10**, such as a grill or griddle surface, cooking stone (e.g., pizza stone, and the like), a wire rack, or another type of platform. The cooking device **10** can include at least one heating element disposed in the lid **14**, the base **12**, and/or the interior cooking chamber **20** that is configured to heat the cooking surface **18**, the interior cooking chamber **20** and/or the food product through conduction, convection, radiation, or a combination thereof. In some variations, the cooking device **10** can include a first heating element **22**A disposed beneath the cooking surface **18** and a second heating element **22**B disposed in the lid **14**. The cooking device **10** can also include at least one vent **24** located within the lid **14** and/or the base **12** to allow airflow to exit the interior cooking chamber **20**. The vent **24** can be seen at least in FIG. **2** located on a rear of the cooking device **10**. As a result of the seal **15** located around a perimeter of the base **12** and/or the lid **14**, the vent **24** can be the primary (or the only) airflow exit for the interior cooking chamber **20**. Accordingly, the size of the vent **24** can proportionally drive airflow through the cooking device **10**.

(38) The cooking device **10** can also include a fan **30**, which can be operated to circulate air within the interior cooking chamber **20** during a variety of cooking modes. The fan **30** can be located within the interior cooking chamber **20**, and can be coupled to the lid **14**, the base **12**, or any other portion of the cooking device **10**. For example, in some embodiments, the fan **30** is located on an upper region of the interior cooking chamber **20** and can be configured to rotate about a vertical axis. A motor **32** capable of driving the fan **30** can be located within a motor housing **34** externally of the interior cooking chamber **20**. In some variations, the fan **30** can be located external to the

interior cooking chamber **20** and can be in fluid communication with the interior cooking chamber **20** through an air pathway, such as a ventilation system or the like.

(39) The cooking device can include a user interface **40** located on an external portion of the cooking device **10**, such as on a front face of the base **12**, as seen, for example, in FIG. **1**. The user interface **40** can include a screen **42** and a variety of inputs **44** with which a user can select various parameters for a cooking and/or a smoke process for a food product. The user interface **40** can include a variety of pre-programmed operating modes. These cooking modes can include conductive, convective, and radiative heating modes, such as grilling, baking, air frying, dehydrating, broiling, and other known cooking modes. Further, these cooking modes can combined with smoke generated by a smoke unit **50** as explained in further detail below. Smoke can be introduced from the smoke unit, and can include low-and-slow modes to impart smoke over a longer period of time and perfume smoke to impart smoke flavor over a short period of time. Further, smoke can be imparted onto a food product independent of a cooking mode, such that the food product may be imparted with smoke flavor without being cooked. Any of the listed operations can be used in combination with one another, both in succession or at the same time.

(40) The cooking device **10** can also employ a smoke unit **50** coupled to the cooking device **10** to impart smoke flavor onto a food product in any mode. The smoke unit **50** is described in further detail below and with respect to FIGS. **4**A-**4**F. The smoke unit **50** can be coupled internally or externally to the cooking device **10**, such as to the base **12**, the lid **14**, or anywhere else on the cooking device. The smoke unit **50** can receive a fuel source, such as wood pellets, and can ignite the pellets using a heating element to generate smoke to impart flavor onto a food product contained within the interior cooking chamber. The generation of smoke can occur during a cooking mode to impart smoke flavors. Further, the cooking device **10** can employ the smoke unit **50** independent of a cooking mode in order to impart smoke flavor to a food product without cooking the food product. The smoke unit **50** can also include an intake located on an exterior thereof, which can provide the cooking device **10** with a source of new air to feed a smoke generation process and allow for air to circulate within the interior cooking chamber **20**. The intake can be intentionally and deliberately sized to correspond to a size of the vent **24** located on the lid **14** and/or the base **12** of the cooking device such that the amount of airflow exiting the interior hollow chamber is approximately equal to the amount of airflow entering the intake.

(41) The cooking device **10** can also employ a smoke channel to introduce smoke generated by the smoke unit into the interior cooking chamber. The smoke channel can provide a pathway through which generated smoke can be drawn, by operation of the fan, into the interior cooking chamber in order to impart smoke flavor onto a food product. Further, the smoke channel can also form part of an airflow pathway that begins with the intake of the smoke unit **50** and ends with the vent **24**. The smoke channel can come in a variety of forms, as will be discussed below.

(42) FIGS. **3**A and **3**B depict another embodiment of a cooking device **10′**. The illustrated cooking device **10′** can be generally similar to cooking device **10**, and for brevity, similar components will not be described again. For example, the cooking device **10′** can generally include a housing **12′**, a smoke unit **50′**, a fan **30′**, and a user interface **40′**. However, in this embodiment the cooking device **10′** includes a movable cover that is in the form of a door **14′** that can be pivoted open on the front of the cooking device. Further, an exemplary difference between the cooking device **10′** and the cooking device **10** is the location of the fan **30′** on the cooking device **10′**. As shown in FIG. **3**B, the fan **30′** is located on a rear wall **12**A′ of the interior cooking chamber **20′**, rather than on a ceiling or upper region of the interior cooking chamber **20′**. Generally, the fan **30′** can be located on a wall of the interior cooking chamber **20′** opposite the front and the movable door **14′**. In this arrangement, the fan **30′** can rotate about a horizontal axis, but the fan **30′** generally operates in a similar manner as the fan **30**. The smoke channel **100** can be seen in the right side of the housing **12′**, and the smoke channel **100** can be at least partially defined by the housing **12′**, similar to the form of the smoke channel **100**. The smoke channel **100** can lead from the smoke unit **50′** at a first

end **102** thereof to the fan **30′** at a second end **104** thereof. Despite the difference in arrangement between the cooking device **10** and the cooking device **10′**, the principle of operation of the smoke channel **100** is generally the same in each device. Accordingly, although reference is made herein to the cooking device **10**, descriptions are equally applicable to the cooking device **10′**.

(43) As referenced above, FIGS. **4**A-**4**F illustrate an exemplary embodiment of a smoke unit, such as the smoke unit **50** described above, that can be used in some implementations of the current subject matter. Generally, the smoke unit **50** is configured to generate smoke for use in a cooking operation. The smoke unit **50** can be mounted to an exterior surface of the movable cover, such as lid **14**, and is configured to be in fluid communication with the interior cooking chamber **20** via a lid aperture **18***d*. While the smoke unit **50** is described herein as being mounted to components of the cooking device **10** and the cooking device **10′**, in some embodiments, the smoke unit **50** can be coupled to additional types of cooking devices, such as a propane grill configured to cook food with a propane-fueled heat source. For example, in some embodiments, the smoke unit **50** can be similarly mounted to an exterior surface of such a propane grill and configured to be in fluid communication with an interior cooking chamber of the propane grill, in which food is placed for cooking, via an aperture formed in the exterior surface.

(44) The smoke unit **50** can include a smoke unit housing **52** having a generally rectangular configuration with top and bottom surfaces **52***a*, **52***b*, and four sides—narrower left and right sides **52***c*, **52***d*, and wider front and rear sides **52***e*, **52***f*—that together form an interior cavity **54**. As shown in FIGS. **4**A-**4**F, the front side **52***e*, proximate the base **12**, is formed to fit a contour of the outer surface of the lid **14**, and therefore may be shorter than the rear side **52***f*. The rear side **52***f*, opposite the front side **52***e*, may include a first air intake **56***a* disposed at a lower region to allow air into the interior cavity **54**. The top surface **52***a* includes a lid **58** hinged to the smoke housing **52** that leads to the interior cavity **54**. In some embodiments, the lid **58** is biased to a closed position via a spring **58***a* with enough force to prevent accidental opening, or to prevent excess air from seeping into the interior cavity **54**. The interior cavity **54** is sized to receive an insertable removable fuel box assembly **60** therein. In some embodiments, the force exerted by spring **58***a* is large enough to prevent the fuel box assembly **60** from sliding out of the smoke unit housing **52** when the lid **14** is in an open position.

(45) The fuel box assembly **60** can be configured to receive and retain fuel for use during a cooking operation, and the fuel box assembly **60** can also catch and hold ash generated by combustion of the fuel. The fuel box assembly **60**, seen within the smoke unit housing **52** in FIG. **4**C and removed from the smoke unit housing **52** in FIG. **4**F, includes left and right sidewalls **60***a*, **60***b*, and front and rear sidewalls **60***c*, **60***d*, which are wider than the left and right sidewalls **60***a*, **60***b* similar to the smoke unit housing **52**. The fuel box assembly **60** also includes a top surface **60***e* and a bottom surface **60***f* which extend between the sidewalls **60***a-d* at respective top and bottom ends. The particular shape and arrangement of the fuel box assembly **60** can vary in dimension, and certain features can be rounded or generally altered from what is depicted. The front sidewall **60***c*, disposed proximate the housing **52**, is shown covered by a mesh **64** with a plurality of small apertures **62***a* disposed thereon. At an upper region of the front sidewall, beyond the mesh, the smoke unit further includes a large aperture **62***b*. The particular amount and arrangement of apertures **62***a*, **62***b* can vary in number, arrangement, and/or dimension. The rear sidewall of the fuel box assembly **60** is substantially solid, except for at a lower region, which can contain a second air intake **56***b* that aligns with the first air intake **56***a* located on the rear sidewall of the smoke unit housing **52**. The first and second air intakes **56***a*, **56***b* define a portion of an airflow path through the cooking device **10**.

(46) The fuel box assembly **60** is further configured to be placed within the smoke unit housing **52** to substantially conform with the left, right, and rear sides. A region near the front side of the smoke unit housing **52** proximate the upper lid portion can be larger than a region occupied by the fuel box assembly **60**, and is thus not filled by the fuel box assembly **60** when the fuel box

assembly **60** is inserted into the smoke unit housing **52**. As shown in FIGS. **4A-4F**, this region can contain an igniter **66**, such as a wire heating element, that is configured to heat fuel contained in the fuel box assembly **60** through the smaller apertures **62***a* of the mesh **64** on the front fuel box assembly sidewall **60***e*. In various embodiments, the igniter **66** can take on various forms, such as, for example, an electrical tubular heating element having a first terminal end at one end of the heating element and a second terminal end at an opposite end of the heating element, or a sparking device. When smoke generation is required for a cooking operation, the igniter **66** can be powered on to ignite fuel contained in the fuel box assembly **60**.

(47) As further shown in FIGS. **4A-4F**, the fuel box assembly **60** has an interior space. This interior space is divided into two regions, an upper region in the form of a pellet box **68** that is configured to receive and hold fuel for use during a smoke generation process, and a lower region in the form of an ash catcher **70** that is configured to receive and store ash created during a smoke generation process. The pellet box **68** and the ash catcher **70** are shown in the illustrated embodiment as being separated by a mesh divider **72**. The mesh divider **72** includes apertures which are sized to be large enough to allow for ash to fall from the pellet box **68** to the ash catcher **70** during a smoke generation process, while also being small enough to prevent fuel from passing through the mesh divider **72**. The ash catcher **70** is further configured to retain ash generated by the fuel box assembly **60**, such that removal of the fuel box assembly **60** from the smoke unit housing **52** will also remove ash from the smoke unit housing **52** to facilitate disposal and prevent ash spillage. A person skilled in the art will appreciate that other techniques can be used to separate ash from the fuel.

(48) In some embodiments, and as depicted in the FIGS. **4A-4F**, the smoke unit **50** can include a temperature sensor **74** disposed proximate to the igniter **66**. The temperature sensor **74** can take on any suitable form, and, for example, may be one of a thermocouple, a resistance temperature detector (RTD), a thermistor, and a semiconductor based integrated circuit. However, any form of sensor capable of measuring temperature can be used. The temperature sensor **74** is configured to measure a temperature of the interior of the fuel box assembly **60** during smoke processes and non-smoke processes.

(49) The smoke unit interior **54**, including the interior of both the smoke unit housing **52** and the fuel box assembly **60**, are in fluid communication with the interior cooking chamber **20**. As mentioned previously, and as shown especially in FIG. **4C**, the front sidewall of the smoke unit **50**, above the region containing the igniter **66**, contains a large aperture **62***b*. The large aperture **62***b* defines part of the airflow pathway, joining the smoke unit **50** interior with the interior cooking chamber **20**. Covering the large aperture **62***b*, as depicted in FIGS. **4A-4C**, is a baffle **80** disposed in the airflow path. When the smoke unit **50** is coupled to the cooking device **10** at the lid aperture **18***d*, the baffle **80** passes through the lid aperture **18***d* and is thereby positioned within the interior cooking chamber **20**.

(50) In the embodiment shown in FIGS. **4A-4F**, the baffle **80** is a tunnel baffle **82**. The tunnel baffle **82** can include a cover **82***c* spanning the large aperture **62***b* that is oriented horizontally to align with a direction of airflow in the interior cooking chamber **20**. The cover **82***c* can include openings at each end thereof such that, in relation to airflow through the interior cooking chamber **20**, one opening is an upstream opening **82***a* and the other opening is a downstream opening **82***b*.

(51) As schematically illustrated in FIG. **5** and as referenced above, the cooking device **10** can include a controller **100** that is in operable communication with one or more of the components described above (e.g., the user interface **40**, the fan **30**, the temperature sensor **74**, etc.). As shown, the controller **100** can include at least one processor **101** and a memory **102** storing instructions which, when executed by the processor **101**, can cause the at least one data processor to perform one or more of the operations described elsewhere herein. The controller **100** can also include an input/output (I/O) interface **103** that enables the processor **101** to receive commands and/or data from other components of the cooking device **10** for use in performing the operations.

(52) As shown in FIG. **5**, the cooking device **10** can also include a power supply **110** that is configured to supply power to the igniter **66** (in addition to other components of the cooking device **10** requiring power to operate). The power supply **110** can be in operable communication with the controller **100** and the igniter **66**. As such, the power supply **110** can be configured to receive commands from the controller **110** (provided via the I/O interface **103**) that cause the power supply **110** to provide electrical power to the igniter **66** to thereby cause the igniter **66** to activate. In some embodiments, the power delivered to the igniter **66** can vary based on the commands received from the controller **65**. For example, the level and/or duration of power supplied to the igniter **66** can vary over a given period of time based on power delivery instructions characterized by the commands received from the controller **100**. As a result, the level and/or duration of heat being supplied to the fuel contained within the smoke unit **50** can vary over the given period of time based on the commands received from the controller **100**.

(53) In some embodiments, the activation of the igniter **66** can occur when an ignition mode is selected via the user interface **40**. When this occurs, the controller **100** can cause the power supply **110** to supply full power to the igniter **66**.

(54) In some embodiments, the controller **100** can be configured to receive data characterizing a plurality of measurements of a rate of energy (e.g., power, etc.) that is supplied to the igniter **66** of the smoke unit **50** by the power supply **110** and a plurality of measurements of a temperature of a region proximate the igniter **66** as acquired by the temperature sensor **74**.

(55) Each of the plurality of measurements can be acquired at regular intervals during a predetermined period of time (e.g., every second over a 30 second period of time). In some embodiments, the predetermined period of time can be a period of time during which the igniter **66** is activated and/or during an initial operating mode of the igniter **66** (e.g., an operating mode during which the igniter **66** is used for the first time since the cooking device has been powered on). In some embodiments, each of the plurality of measurements of the rate of energy can be acquired with a power sensor (not shown) that is configured to measure the rate of energy supplied to the igniter **66** by the power supply **110**.

(56) In some embodiments, each of the plurality of measurements of the rate of energy supplied to the igniter **66** can be derived from a measurement of voltage applied to the igniter **66** and a measurement of a resistance of the igniter **66**. For example, in some embodiments, measurements of the voltage applied to the igniter **66** can be acquired with a voltage sensor (not shown) that is configured to acquire a value of the voltage, and measurements of the resistance of the igniter **66** can be acquired with a resistance sensor (not shown) that is configured to acquire an amount of resistance of the igniter **66**. Each of the plurality of measurements of the rate of energy supplied to the igniter **66** can be derived using the equation $P = V^2/R$, where P is the measurement of the rate of energy supplied to the igniter **66**, V is the measured voltage, and R is the measured resistance. In some embodiments, each of the plurality of measurements of the rate of energy supplied to the igniter **66** can be derived using an assumed value of resistance of the igniter **66** in lieu of or in addition to using a measured value of resistance.

(57) In some embodiments, each of the plurality of measurements of the rate of energy supplied to the igniter **66** can be derived from a measurement of current passing through the igniter **66**. For example, in some embodiments, measurements of the current passing through the igniter **66** can be acquired with a current sensor (not pictured) that is configured to acquire a value of the current. Each of the plurality of measurements of the rate of energy supplied to the igniter **66** can be derived using the equation $P = I^2 * R$, where P is the measurement of the rate of energy supplied to the igniter **66**, I is the measured current, and R is the measured resistance. In some embodiments, each of the plurality of measurements of the rate of energy supplied to the igniter **66** can be derived using an assumed value of resistance of the igniter **66** in lieu of or in addition to using a measured value of resistance.

(58) In some embodiments, each of the plurality of measurements of the rate of energy supplied to

the igniter **66** can be derived from the measurement of current passing through the igniter **66** and the measurement of voltage applied to the igniter **66**. For example, current and voltage measurements can be acquired using the current and voltage sensors described above, respectively, and each of the plurality of measurements of the rate of energy supplied to the igniter **66** can be derived using the equation $P=I*V$, where P is the measurement of the rate of energy supplied to the igniter **66**, I is the measured current, and V is the measured voltage.

(59) In some embodiments, at the conclusion of the predetermined period of time, the controller **100** can be configured to determine an average rate of energy supplied to the igniter **66** during the predetermined period of time. For example, the controller **100** can calculate an average of each of the received plurality of measurements of the rate of energy supplied to the igniter **66** during the predetermined period of time to determine an average rate of energy supplied to the igniter **66** during the predetermined period of time. Similarly, in some embodiments, the controller **100** can be configured to determine an average temperature of the region proximate the igniter **66** during the predetermined period of time. For example, the controller **100** can calculate, using each of the received plurality of measurements of the temperature of the region proximate the igniter **66**, an average value of the temperature of the region proximate the igniter **66**.

(60) In some embodiments, the controller **100** can monitor the length of time during which the igniter **66** is activated. As such, the controller **100** can be configured to determine, based on the determined average rate of energy supplied to the igniter **66** and the determined average temperature of the region proximate the igniter **66**, a maximum time of activation of the igniter when the igniter is operating in the initial ignition operating mode and during a subsequent period of time that follows the predetermined period of time. The controller **100** can be configured to adjust the maximum time of activation of the igniter **66** when the igniter **66** is operating in the initial ignition operating mode and during the subsequent period of time based on a variety of factors. For example, the controller **100** can adjust the maximum time of activation based on the determined average rate of energy and/or the determined average temperature. For example, the maximum time of activation can be determined using a weighted average algorithm in which the determined average temperature of the region proximate the igniter **66** and/or the determined average rate of energy supplied to the igniter **66** are provided as variables that are multiplied by negative value weight factors. As such, the determined maximum time of activation can vary inversely with the average temperature of the region proximate the igniter **66** and/or the determined average rate of energy supplied to the igniter **66**.

(61) In some embodiments, the maximum time of activation can be determined based on an average amount of voltage applied to the igniter **66** during the predetermined period of time. For example, the controller **100** can calculate an average of each of the received plurality of measurements of the voltage applied to the igniter **66** during the predetermined period of time to determine the average amount of voltage supplied to the igniter **66** during the predetermined period of time. The determined average amount of voltage applied to the igniter **66** can be used in lieu of or in addition to the determined average rate of energy supplied to the igniter **66** in determining the maximum time of activation in the manner described above. In some embodiments, the average amount of voltage applied to the igniter **66** can be used in lieu of the determined average amount of voltage supplied to the igniter **66** when the resistance of one or more heating elements in the cooking device **10** (e.g., igniter **66**) is assumed to be the same value.

(62) In some embodiments, the controller **100** can be configured to adjust the maximum time of activation of the igniter **66** based on an operating mode of the smoke unit **50**. For example, the controller **100** can use a first algorithm for determining the maximum time of activation of the igniter **66** when the smoke unit **50** is being used in a smoker operating mode) (in which the smoke generator outputs smoke for an extended duration of time (e.g., a relatively long portion of, or all of, the time during which the food is cooked using the cooking device **10**)) and/or a second algorithm for determining the maximum time of activation of the igniter **66** when the smoke unit

50 is being used in an infusion operating mode (in which the smoke generator outputs a limited-duration burst of smoke on an on-demand basis (e.g., a relatively short portion of the time during which the food is cooked with the cooking device **10**)). The first algorithm and/or the second algorithm can be substantially similar to the weighted average algorithm described above (e.g., the determined average temperature of the region proximate the igniter **66** and/or the determined average rate of energy supplied to the igniter **66** are provided as variables to the first and second algorithms that are multiplied by negative value weight factors). However, the magnitudes of the negative value weight factors for each of the first algorithm and the second algorithm can differ based on the operating mode of the smoke unit **50**.

(63) In some embodiments, the controller **100** can be configured to adjust (e.g., increase or decrease) an amount of power delivered to the fan **30** during the initial ignition operating mode. In some embodiments, the controller **100** can receive, from a temperature sensor (not shown) located in the cooking chamber **20**, data characterizing the temperature of the cooking chamber **20**. The controller **100** can determine a difference between the temperature of the cooking chamber **20** and the temperature of the region proximate the igniter **66** characterized by one or more of the above-described plurality of measurements, and the controller **100** can determine whether the determined difference is less than or equal to a predetermined temperature difference threshold value (e.g., 6 degrees Celsius). Additionally, the controller **100** can be configured to determine whether the temperature of the region proximate the igniter **66** and the temperature of the cooking chamber **20** are each less than a predetermined temperature threshold. When the difference between the temperature of the cooking chamber **20** and the temperature of the region proximate the igniter **66** is less than or equal to the predetermined temperature difference threshold value, and when the temperature of the region proximate the igniter **66** and the temperature of the cooking chamber **20** are both less than a predetermined temperature threshold, the cooking device **10** is determined to be in a "cold state" at the beginning of the ignition process (e.g., a state in which the cooking device **10** has not been recently used and, as such, is not at a temperature that is close to the normal operating temperature of the cooking device **10**).

(64) As such, when the controller **100** determines that the cooking device **10** is in a "cold state," the controller **100** can operate the cooking device **10** in a fan compensation mode in which the amount of power delivered to the fan **30** is adjusted. The fan compensation mode can allow for optimized ignition of the fuel located in the smoke unit **50** when the cooking device **10** is in the "cold state." For example, in some embodiments, the controller **100** can cause an adjusted (e.g., increased or decreased) amount of power to be delivered to the fan **30** in order to compensate for internal friction that is present within the motor of the fan **30** when the cooking device is determined to be in the cold state (by, for example, determining that the temperature of the cooking chamber **20** is less than a predetermined threshold) and thereby maintain the operating speed of the fan at a rotational speed that allows for the optimized ignition of the fuel located in the smoke unit **50**. As the temperature of the cooking chamber **20** increases, the internal friction abates and as such the controller **100** can deactivate the fan compensation mode in response to determining that the temperature of the cooking chamber **20** exceeds a predetermined threshold. For example, once the temperature of the cooking chamber **20** has increased such that the cooking device **10** is no longer in the cold state, the controller **100** can deactivate the fan compensation mode and adjust (e.g., increase or decrease) the amount of power delivered to the fan and thereby maintain the operating speed of the fan at the rotational speed that allows for the optimized ignition of the fuel located in the smoke unit **50**. Additionally, in some embodiments, when the controller **100** is operating the cooking device **10** in the fan compensation mode, the controller **100** can monitor a level of voltage generated by the power supply **110** and determine whether the level of voltage is less than a predetermined threshold. In response to determining that the level of voltage generated by the power supply **110** is less than the predetermined threshold, the controller **100** can cause an increased amount of power to be delivered to the fan **30** to compensate for the level of voltage

generated by the power supply **110** being less than the threshold and thereby maintain the operating speed of the fan at the rotational speed that allows for the optimized ignition of the fuel located in the smoke unit **50**. After each of the operations of the fan compensation mode have concluded, the controller **100** can adjust (e.g., increase or decrease) the amount of power delivered to the fan **30** such that the operating speed of the fan **30** is adjusted to a preset value for ignition of the fuel within the smoke unit **50**. After the operating speed of the fan **30** has been adjusted to the preset value, the controller **110** can continue to operate in the ignition mode until the maximum time of activation has elapsed.

(65) In some embodiments, such as those where the fan compensation mode is not active or enabled, after the controller has determined the maximum time of activation and during the above-described subsequent period of time, the controller **100** can cause a maximum amount of power to be supplied to the fan **30**, such that the fan **30** operates at full power, until a predetermined portion of the subsequent period of time has elapsed (e.g., 120 seconds). Once the predetermined portion has elapsed, the controller **100** can adjust the amount of power delivered to the fan such that the operating speed of the fan **30** is adjusted to the preset value described above. And, similar to the above-described functionality, after the operating speed of the fan **30** has been adjusted to the preset value, the controller **110** can continue to operate in the ignition mode until the maximum time of activation has elapsed.

(66) The cooking device **100** also includes a power sensor **76** that is communicatively and operably coupled to the controller **100** and the power supply **110**. In operation, the power supply **110** can receive a steady stream of voltage ("supply voltage") from an external power source such as an electrical outlet. For example, one end of a three pronged cord can be connected to the external power source and the other end may be directly connected to the power supply **110**. Thereafter, when the cooking device **10** is activated (e.g., turned on), voltage in a range of 110 V to 120 V can be consistently delivered to the power supply **110** by the external power source. The power supply **110** uses the received voltage to drive current to several components of the cooking device **10**, namely the controller **100**. The driving or movement of the current by the received voltage results in the generation of electrical power, which operates various components of the cooking device **10**.

(67) In some embodiments, the power sensor **76** detects, substantially in real time, a supply voltage that is received by the power supply **110** and communicates data representative of the supply voltage to the controller **100**. The controller **100** stores this data in memory **102**. In some embodiments, the power sensor **76** can be configured to detect the supply voltage at fixed time intervals, at a predefined time, and so forth. The controller **100** utilizes the data representative of the supply voltage to perform calculations using, e.g., a transfer function based algorithm that utilizes one or more transfer functions. Details regarding the implementation of the transfer functions will be described later on in this disclosure. Broadly speaking, the controller **100** receives electric power from the power supply **110** and implements one or more transfer functions to deliver a precise amount of electric power to the fan **30**. Controlling the amount of electrical power delivered to the fan **30** enables control over the operating speed of the fan, namely the rate of rotation of the blades of the fan **30**.

(68) FIG. **5** also schematically illustrates various components of the fan **30**, namely a TRIAC **78**, an inductive load **80**, and fan blades **82**. The TRIAC **78**, a component that is in operable communication with the controller **100** and the inductive load **80**, is a three-pinned electronic circuit used to control an amount of current that flows to a component, and by extension, the amount of power delivered to the component. TRIACs are used as dimmer switches for lighting components, output controllers for electric heaters, and as components that control the operating speed of motors. One such motor is a shaded-pole motor, which utilizes a magnetic field to convert electrical current into mechanical rotational energy. The shaded-pole motor, one example of the inductive load **80**, is in operable communication with the TRIAC **78** and the fan blades **82**. When the cooking device operates in fan compensation mode, the controller **100** can adjust the operating

speed of the fan blades **82** by controlling the amount of electric power delivered to the shaded-pole motor.

(69) For example, to increase the operating speed of the fan blades **82** relative to a current operating speed, the controller **100** can increase an amount of electric power delivered to the inductive load **80**. Delivery of a higher electric power causes the inductive load **80** (e.g., the shaded-pole motor) to generate a higher amount of mechanical rotational energy which, when delivered by the inductive load **80** to the fan blades **82**, increases the operating speed (i.e. rotational speed) of the fan blades **82**. Conversely, to decrease the operating speed of the fan blades **82**, the controller **100** can decrease an amount of power delivered to inductive load **80**. A lower electric power causes the inductive load **80** (e.g., the shaded-pole motor) to generate a lower amount of mechanical rotational energy which, when delivered by the inductive load **80** to the fan blades **82**, decreases the operating speed (i.e. rotational speed) of the fan blades **82** relative to the current operating speed.

(70) FIG. **6** illustrates a flow chart **600** for controlling the speed of the fan **30** when the cooking device **10** is operating in fan compensation mode, according to one or more embodiments described and illustrated herein. It is noted that FIGS. **7-10** will be discussed interchangeably with the discussion of FIG. **6**.

(71) At block **602**, the controller **100** can receive data representative of an electrical value. The electrical value can be a supply voltage, a current, or a power. In aspects, a supply voltage from a power source that is external to the controller **100** may be received. For example, as described above with respect to FIG. **5**, the power sensor **76** can detect the voltage supplied to the power supply **110** by an external power source (e.g., an electrical outlet) and communicate data representative of the detected voltage to the controller **100**. The controller **100** then stores the data in the memory **102** of the controller **100**. While the external power source is capable of supplying 120 V, the supply voltage typically received from the external power source can be in a range from 104 V to 120 V because there is a drop in the supply voltage from 120 V to 110 V (or 104 V) when the cooking device **10** is activated (e.g., turned on). In aspects, the voltage supplied by the external power source to the power supply **110** can be in the range of 110 V to 120 V and the drop in voltage (i.e. voltage sagging) can be in a range from 2 V to 6 V. Such a voltage drop or voltage sag occurs because the external power source can be connected to a high power load such as, e.g., the inductive load **80**.

(72) At block **604**, the controller **100** can access, from the memory **102**, a target value (e.g., a target speed) for the inductive load **80** at the supply voltage (electrical value) that is delivered to the cooking device **10**. For example, during the design and manufacture of the cooking device **10**, a particular operating speed of the fan blades **82** can be preprogrammed in the memory **102**. As such, the controller **100** operates to facilitate deliver of a requisite amount of electric power to the inductive load **80** to ensure that the fan blades **82** consistently operate at this preprogrammed operating speed. In fact, one of the purposes of the fan compensation mode is to ensure that the fan blades **82** consistently operate at the preprogrammed operating speed. The preprogrammed operating speed can be 1000 RPM. In other embodiments, the preprogrammed operating speed can be an operating speed range, e.g., 800 revolutions per minute (RPM), 900 RPM, 1000 RPM, or an operating speed range of 500-700 RPM.

(73) In some embodiments, the controller **100** initiates operation of the cooking device **10** in the fan compensation mode, automatically and without user intervention, upon determining that the fan blades **82** fail to operate at the preprogrammed operating speed, e.g., 1000 RPM. One way that the controller **100** can determine the operating speed of the fan blades **82** is by receiving data from a sensor that is disposed in close proximity with or directly on the fan blades **82**. In operation, the sensor can detect, substantially in real time, the rotational speed of the fan blades **82** and communicate data representative of the rotational speed to the controller **100**. The controller **100** can then compare the rotational speed with the operating speed of the fan blades **82** that was

preprogrammed in the memory **102** to determine whether the fan blades **82** are operating at the preprogrammed operating speed. Such sensors, however, are inaccurate, cost prohibitive, and difficult to install.

(74) Additionally, conventional technologies suffer from excess costs because the controllers used in conventional technologies typically need an additional pin in order to communicate directly with these expensive and inaccurate sensors. The need for such separate hardware interrupts the operation of the timers on these controllers, which are configured to measure the operating speeds of motors connected to these timers. Due to these interruptions, the controllers used in conventional technologies may be unable to measure the operating speeds of various components (e.g., motors) without reducing various time critical processes of these controllers.

(75) The methods and techniques described herein, namely the transfer function based power delivery system of the present disclosure, address and overcome the above described deficiencies. In particular, the transfer function based power delivery system utilizes one or more transfer functions in conjunction with temperature data and electric power data to control operating speed of the fan blades **82**, thereby bypassing the need for the installation of sensors directly on or in close proximity of the fan blades **82**. For example, the controller **100** can receive temperature data from the temperature sensor **74**, electric power data from the power sensor **76**, and implement one or more transfer functions using the electric power data to determine whether the fan blades **82** are rotating at a speed that matches the preprogrammed operating speed.

(76) If the rotating speed of the fan blades **82** is less than the preprogrammed operating speed, the controller **100** can implement one or more transfer functions to enable the supply of a particular amount of electric power to the inductive load **80**, which in turn will generate and supply a particular amount of mechanical power to the fan blades **82** to ensure that the fan blade rotational speed matches the preprogrammed operating speed. Similarly, if the rotating speed of the fan blades **82** is more than the preprogrammed operating speed, the controller **100** will use one or more transfer functions to supply another amount of electric power to the inductive load **80**, which in turn will generate and supply another amount of mechanical power to the fan blades to ensure that the fan blade rotational speed matches the preprogrammed speed.

(77) At block **606**, the controller **100** can implement a transfer function based algorithm for determining a set point value using the electrical value of block **602**. The implementation of the transfer function based algorithm can involve the processing of one or more transfer functions. In particular, the processing can involve determining, using a first transfer function, a target power for operating the inductive load **80** at the target value (e.g., target speed). The target speed corresponds the preprogrammed operating speed of the fan blades **82** described above with respect to block **604**. In some embodiments, the controller **100** can access the preprogrammed operating speed stored in the memory **102** and implement a transfer function (e.g., the first transfer function) to determine an amount of electric power that has to be delivered to the inductive load **80**. As stated above, the delivery of this electric power to the inductive load **80** causes the fan blades **82** to operate at the preprogrammed operating speed. It is noted that the target speed is only one example of the target value. In embodiments, the target value can correspond to aspects other than speed.

(78) FIG. **7** illustrates a graphical representation **700** of values that can be calculated by the controller **100** using the first transfer function, according to some embodiments described and illustrated herein. The graphical representation **700** includes an x-axis **702** and a y-axis **704**. The values on the x-axis **702** correspond to electric power delivered to the inductive load **80** at various time periods during the operation of the cooking device **10**, and the values on the y-axis **704** correspond to various operating speeds of the fan blades **82** at various time periods during the operation of the cooking device **10**. As illustrated, the electric power values on the x-axis **702** range from 0 to 60 W and the operating speeds on the y-axis **704** range from 0 to 4000 RPM.

(79) The controller **100**, upon accessing the target speed for the inductive load at the supply voltage received from the external power source (e.g., 104 V to 120 V), accesses and implements a first

transfer function stored in the memory **102**. In particular, the controller **100** inputs the target speed that is preprogrammed into the memory **102** during the design and manufacture of the cooking device **102**, e.g., an operating speed of 1000 RPM, into the first transfer function, and determines a corresponding electric power value as an output of the first transfer function. The determined electric power value can then be delivered to the inductive load **80** to control operation of the fan blades **82** to ensure that the fan blades **82** operate at the target speed (i.e. preprogrammed operating speed).

(80) For example, the controller **100** can access the target speed of 1000 RPM from the memory **102** and determine, using the first transfer function, that the corresponding electric power needed to generate this target speed is in the range of 19 Watts to 20 Watts. The controller **100** then operates to deliver the electric power of 19-20 Watts to the inductive load **80** via the TRIAC **78**. The controller **100** enables the delivery of 19-20 Watts of electric power by selecting a particular setting on the TRIAC. Determining this setting requires the use of a second transfer function, as described in greater detail below.

(81) The graphical representation **700** depicts a line **706** that accurately approximates a plurality of operating speeds of the inductive load **80** (ranging from 0 to 4000 RPM) for a plurality of electric power values (ranging from 0 to 60 Watts) given a particular supply voltage, e.g., the supply voltage in the range of approximately 104 V to 120 V. As illustrated, the relationship between a particular electric power value and a corresponding operating speed is substantially linear, as indicated by points **708**, **710**, **712**, **714**, and **716**.

(82) Further, the implementing of the transfer function based algorithm can involve the processing of a second transfer function. In particular, the processing of the second transfer function enables the determination of a set point value (e.g., a setting) specific to the target power and the supply voltage (e.g., 104 V to 110 V). After determining the target power for operating the fan blades **82** at a target speed, as described above with respect to blocks **604** and **606** above, the controller **100** can input the values of the target power at the given target speed and the supply voltage received from the external power supply into the second transfer function and determine a set point value for the TRIAC. The set point value corresponds to a setting in the TRIAC that enables the delivery of the target power to the inductive load **80**, which then generates mechanical rotational energy that is delivered to the fan blades **82** to rotate at the preprogrammed operating speed.

(83) FIG. **8** illustrates a three dimensional graphical representation **800** of values that can be calculated by the controller **100** using the second transfer function, according to some embodiments described and illustrated herein. In particular, the three-dimensional graphical representation **800** includes an x-axis **802** corresponding to TRIAC set point values (also referred to as Phase Angle Target (or PAT) values), a y-axis **804** corresponding to supply voltages, and a z-axis **806** that corresponds to electric power values. The graphical representation also depicts a curve **808** that captures the relationship between supply voltages, electric power values, and set point values.

(84) As described above, the controller **100**, having determined a target power value and the supply voltage, implements the second transfer function and determines a set point for the TRIAC that is specific to the target power and the supply voltage. The values that can be determined using the second transfer function are shown in the curve **808** of the three dimensional graphical representation **800**. For example, for a supply voltage of 220 V and a target power of approximately 24 Watts, the TRIAC set point can have a value of approximately 28.

(85) FIG. **9** depicts a two-dimensional graphical representation **900** including only the TRIAC set point values and electric power values. As illustrated, an x-axis **902** lists a plurality of set point values and a y-axis **904** lists a plurality of electric power values. The two-dimensional graphical representation **900** is a version of the three-dimensional graphical representation **800**, but is based on a constant supply voltage, e.g., 110 V, 250 V, etc. As shown in the two-dimensional graphical representation **900**, the curve **906** closely matches the points **908**, **910**, and **912**, which are examples of electric power values at which the cooking device **10** can be operated. As such, the

curve **808** and the curve **906**, which represents various values that can be calculated using the second transfer function, show that at a particular supply voltage and an electric power value, a controller **100** can accurately determine a set point value for the TRIAC **78**.

(86) At block **608**, the controller **100** applies the set point value on the TRIAC. The manner in which the set point is selected and utilized to control the operating speed of the fan blades **82** is described in greater detail below.

(87) FIG. **10** depicts a set point included as part of an alternating current (AC) waveform **1000**. Broadly speaking, an AC waveform represents the behavior of voltage and current in an alternating current (AC) based electrical system. In this system, which is implemented on the cooking device **10**, supply voltage fluctuates at various time intervals from a positive voltage to a negative voltage, which in turn results in a change in the direction of the current (flow of electrons). The fluctuation in voltage (i.e. electric potential) from the positive voltage to the negative voltage and the resulting change in the direction of the current due to this fluctuation generates the electric power that is fundamental to operating various components of the cooking device **10**, namely the controller **100** and the inductive load **80**.

(88) In the AC waveform **1000** of FIG. **10**, an x-axis **1002** corresponds to a plurality of time values (measured in seconds or milliseconds) and a y-axis **1004** corresponds to positive and negative voltage values. In some embodiments, as the supply voltage received by the power supply **110**, as described in block **602** above, is in the range of 104 V to 110 V, the peak value **1006** of the AC waveform **1000** can be a value of, e.g., approximately 120 V. The positive voltage value **1008** at this peak value can be approximately 120 V, depending on the precise value of the supply voltage received by the power supply **110**. Similarly, the trough value **1010** of the AC waveform **1000** can be a value of, e.g., (approximately −120 V). As such, the negative voltage value **1012** at this trough value can be either approximately −120 V. When the cooking device **10** is turned on or is in operation, the controller **100** receives, the supply voltage from the power supply **110**, which drivers or moves a particular amount of current in a sinusoidal direction. As stated above, the driving of the current by the supply voltage in the sinusoidal orientation results in the generation of electric power that operates various components of the cooking device.

(89) Thereafter, as stated above, the controller **100** utilizes the second transform function to determine a set point of the TRIAC **78** and applies this set point to the TRIAC **78**. The controller **100** can control the amount of electric power delivered to the inductive load **80** based on the value of the set point. Each set point value represents a portion or a percentage of the wave that is filtered or blocked by the TRIAC **78**. If the controller **100** applies a set point value of 0 for the TRIAC **78**, the TRIAC **78** will transmit the entirety of the AC waveform **1000** that it received from the controller **100**, to the inductive load **80**. As a result, a maximum amount of electric power will be delivered to the inductive load **80**, which in turn will result in the generation of a large amount of mechanical rotational energy that is delivered to the fan blades **82**. In contrast, if a higher set point value is determined and applied to the TRIAC **78**, a larger percentage of the AC waveform will be filtered or block, and as a result, a smaller amount of mechanical rotational energy will be generated and delivered to the fan blades **82**.

(90) Returning to FIG. **10**, based on the selection and application of a set point (e.g., set point having a value of 30) by the controller **100**, the TRIAC **78** filters or blocks a particular portion or percentage of the current shown in AC waveform **1000** from being transmitted to the inductive load **80**. The portion **1014** of the AC waveform **1000** that is blocked, based on the set point, is indicated by the dotted line in FIG. **10**. In operation, the TRIAC **78** blocks the portion **1014** by abruptly reducing the voltage from, e.g., the positive voltage value **1008** at the peak value **1006** of the AC waveform **1000** to a voltage of 0. The TRIAC **78** then maintains the 0 voltage value for a time frame **1016**. When the voltage of 0 is maintained, the current corresponding to the portion **1014** is not transmitted to the inductive load **80**, as there is no voltage available to drive the current. After a particular time frame, the TRIAC **78** increases the voltage from 0 to a voltage value **1018**, which

reinitiates the transfer of current to the inductive load **80**. As such, the set point value of 30 represents the time frame **1016** during which the voltage is maintained at 0 V.

(91) A large set point value, e.g., **70**, results in a TRIAC **78** abruptly reducing the voltage from a particular value to 0 V and maintaining the voltage value at 0 V for a prolonged period of time, which results in a significant portion of the current of the AC waveform **1000** from being transmitted to downstream components, e.g., the inductive load **80**. As such, the controller **100** can operate to significantly reduce the operating speed of the inductive load **80** by selecting and applying a set point of 70, and by extension, the operating speed of the fan blades **82**. In contrast, the controller **100** can operate to increase the operating speed of the inductive load **80** by selecting and applying a set point of, e.g., **10**, because such a set point results in the TRIAC **78** blocking a relatively small portion of the current of the AC waveform **1000** from being transmitted to the inductive load.

(92) At block **610**, the controller **100** adjusts operation of the inductive load to the target power responsive to the application of the set point value on the TRIAC **78**. In embodiments, the operation of the inductive load **80** at the target power causes the operation of the inductive load **80** at the target speed. For example, after the controller **100** applies the set point value on the TRIAC **78** as described above with respect to block **610**, the TRIAC **78** blocks a precise amount of current from the AC waveform **1000**. In other words, based on the set point value applied in block **610**, the TRIAC **78** enables a precise amount of current of the AC wave form **1000**, and by extension, electric power, to flow to the inductive load **80**, which results in the inductive load **80** generating a particular amount of mechanical rotational energy that causes the fan blades **82** to rotate at the preprogrammed operating speed of, e.g., 1000 RPM.

(93) As explained above, the set point value that is applied to the TRIAC controls the amount of current of the AC waveform **1000** that is supplied to the inductive load **80**, and by consequence, the operating speed of the fan blades **82**. A large set point value (e.g., 70) that is selected and applied on the TRIAC **78** results in a reduction in the operating speed of the fan blades **82** and a smaller set point value results in an increase in the operating seed of the fan blades **82**.

(94) Having described the manner in which the controller **100** utilizes transfer functions to determine a target power for operating the inductive load to control the operating speed of the fan **30**, a description of the transfer functions is instructive. Versions of the transfer function that are utilized to determine the set point of the TRIAC **78** (e.g., the second transfer function) can be expressed as follows:

(95) $$P_{@\_V}(PAT) = \frac{A}{E + e^{(\frac{PAT + C}{B})}} + D \quad (1)$$

$$AFP(PAT, SPV) = (\frac{P_{@\_V}(PAT) - y_o}{-x_o})(SPV - x_0) + y_o \quad (2)$$

$$PAT(SPV, AFP) = \ln(\frac{A}{(\frac{AFP - y_o) * (-x_o)}{(SPV - x_o)}) + y_o - D} - E) * B - C \quad (3)$$

(96) As shown in expressions (1), (2), and (3), each expression includes a plurality of polynomials. It is noted that each of the above expressions represent different versions of the second transfer function that is utilized to determine a set point of the TRIAC **78**. As stated above, the set point of the TRIAC **78** is also referred to as a phase angle target or the variable (PAT). The variables of A, B, C, D, E, x.sub.0, y.sub.0, and a are constant values that are derived from data that is gathered from monitoring the operation various components of the cooking device **100** for a particular time frame. The expression (1) and (2) are utilized by the controller **100** to determine an electric power that is delivered to the inductive load **80** based on a known phase angle target (set point) and a constant supply voltage. Additionally, expression (3) is utilized by the controller **100** to determine a phase angle target value (PAT) given an input power and a supply voltage value. The input power value (e.g., Apparent Power Value) can be defined as a target power value that is necessary to ensure that the fan blades **82** operate at an operating speed that is preprogrammed or hardwired into the memory **102** of the controller **100**, as described in blocks **604** and **606** above. However, it is

noted that characters or expressions other than polynomials can also be utilized in each of the first and the second transfer functions in order to implement the transfer function based electrical power delivery system described herein.

(97) In addition, the expression (3) can be defined as a set two separate expressions:

(98) $PAT(\ ) = \ln(\frac{A}{+y_o -D} - E) * B - C$ (4) $(AFP, SPV) = (\frac{(AFP - y_o)*(\ -x_o)}{(SPV - x_o)})$ (5)

(99) Partitioning of the expression (3) into expressions (4) and (5) enables defining the function of PAT(AFT, SPV)—which is used to determine a phase angle target given the values of an electric power and a supply voltage—using a polynomial expression, which significantly reduces the space allocation requirement in the memory **102** needed to implement or process expression (3). In some embodiments, a manner in which PAT (β) is implemented and approximated is expressed by the following expression:

(100) $PAT(\ ) \approx PAT_{\text{polyApprx}}(\ ) = k_3 * {}^3 + k_2 * {}^2 + k_1 * + k_0$ (6)

(101) The above expression also includes various polynomials that, when processed by the controller **100**, significantly reduce the space allocation requirement in the memory **102** needed to process expression (3). These polynomials are k.sub.0, k.sub.1, k.sub.2, k.sub.3, β, β.sup.2, and β.sup.3. To generate expressions (1)-(5), it is assumed that the relationship between the supply voltage and the electric power that is utilized to control the operating speed of the fan blades **82** share a linear relationship. Further, as described above, a reduction in the set point of the TRIAC **78** results in a reduction of the electric power that is delivered to the inductive load **80**, and by extension, the power (i.e. mechanical rotational energy) that is delivered to the fan blades **82**.

(102) In some embodiments, the controller **100** implements a set of equations or expressions that enable compensation for and reduction of losses in electric power that may occur due to various environmental factors. In other words, these expressions, shown below, enable power factor compensation:

(103) $E(PAT) = \frac{(c_1 + c_2 * e^{c_3 * x})}{c_1}$ (7) $PFP = AFP * E(PAT)$ (8)

(104) In the above expressions, the variable AFP represents the electric power that is delivered to the inductive load **80**, which in turn results in the generation of the mechanical rotational energy that causes the fan blades **82** to run at a particular operating speed. The variable PFP correspond to practical fan power, which is a portion of the apparent power that corresponds to power losses that occur due to the operation of the inductive load **80**. The expressions (7) and (8) are only implemented under particular conditions, which is illustrated in FIG. **11**.

(105) FIG. **11** depicts a non-linear relationship **1100** between operating speeds of the fan blades **82** based on variations in the set point of the TRIAC **78**. As illustrated in FIG. **11**A, the x-axis **1102** lists a plurality of electric power values ranging from 0 to 45 Watts and the y-axis **1104** lists a plurality of operating speeds of the fan blades **82** ranging from 0 to 3000 RPM. As shown, when the electric power values are in a range from 15 to 20 Watts, the operating speeds of the fan blades **82** range from 1000 to 1500 RPM. However, when the electric power value is approximately 24 Watts, the operating speeds of the fan blades **82** vary significantly from 1000-2500 RPM. As such, the relationship between the set points and the operating speeds are not linear.

(106) In contrast with FIG. **11**, FIG. **12** depicts a substantially linear relationship **1200** between electric power values and operating speeds. FIG. **12** includes an x-axis **1202** that lists a plurality of electrical power values ranging from 0 to 20 Watts and a y-axis **1204** that lists a plurality of operating speeds ranging from 0 to 2500 RPM. As shown in FIG. **12**, a number of points are positioned in close proximity to or directly on the fitting line **1206**, indicating a clear linear relationship between the electric power values and the operating speeds.

(107) In order to accurately implement the transfer functions as shown in expressions (1), (2), and (3), the parameters represented by variables of A, B, C, D, E, x.sub.0, y.sub.0, and a are obtained by the controller **100** by analyzing trends associated with the supply voltage and electric power

delivered to the inductive load **80**. One trend that is analyzed is the relationship between electric power delivered to the inductive load **80** (apparent power) and the supply voltage.

(108) FIG. **13**A depicts a graphical representation **1300** that shows a relationship between supply voltages and electric power values at various set points. The x-axis **1302** lists supply voltages ranging from 0 to 130 Volts and the y-axis **1304** lists electric power values ranging from 4 Watts to 20 Watts. Further, various subsets of points are indicated with a different color and each color corresponds to a specific phase angle target value or set point value of the TRIAC **78** (e.g., as shown in box **1306** and the graphical representation **1300**). In order to determine two of the parameters—x.sub.0 and y.sub.0—a plurality of diagonal fitting lines may be to determine the relationship between electric power values and supply voltages at each set point, as shown in FIG. **13**B. In FIG. **13**B, a graphical representation **1307** depicts fitting lines **1308**, **1310**, **1312**, **1314**, **1316**, and **1318** that are generated in order to determine the relationship between electric power values and supply voltages at set point values (phase angle target values) of 0, 12, 18, 21, 24, and 27. As indicated by these fitting lines, the relationship between the supply voltages and the electric power values is substantially linear. Thereafter, to determine the value of the parameters of x.sub.0 and y.sub.0, a point where the fitting lines **1308**, **1310**, **1312**, **1314**, **1316**, and **1318** intersect is determined by the controller **100**. Such an intersection point is depicted in FIG. **13**C.

(109) FIG. **13**C illustrates a graphical representation **1320** in which a plurality of additional supply voltage values are added to the x-axis **1302** and a plurality of additional electric power values are added to the y-axis **1304**. The graphical representation **1320** also includes and an intersection point **1322** of various fitting lines. Specifically, the x-axis **1302** in FIG. **13**C includes values ranging from 20 V to 130 V and the y-axis **1304** includes values ranging from −10 to 20 Watts. Further, the intersection point **1322** of the fitting lines **1308**, **1310**, **1312**, **1314**, **1316**, and **1318** is indicated in FIG. **13**C. This intersection point **1322** corresponds to the values of x.sub.0 and y.sub.0. In aspects, the value of x.sub.0 and y.sub.0 can be 28.29 and −8.46, respectively. However, it is noted the values of x.sub.0 and y.sub.0 can vary significantly based on differing characteristics across various systems.

(110) Additionally, other trends can be analyzed by the controller **100** to determine the value of the parameters A, B, C, D, E, and a.

(111) FIG. **14** depicts a graphical representation **1400** that shows a relationship between set points of the TRIAC **78** and the electric power values at these set points. The x-axis **1402** lists a plurality of set point values ranging from 0 to 35 and the y-axis **1404** lists a plurality of electric power values, namely the electric power values delivered to the inductive load **80**. These values range from 5 to 20 Watts. Further, a constant supply voltage that is delivered to controller **100** while the controller **100** applies a subset of the range of set points listed on the x-axis **1402** corresponds to the a value. In some embodiment, the a value can be approximately 112 V.

(112) Thereafter, the controller **100** can apply a sigmoid function **1500** to the data depicted in the graphical representation **1400**, as illustrated in FIG. **15**. The sigmoid function **1500** can be represented by the following expression:

(113) $\quad (z) = \frac{1}{1 + e^{-x}}$ (9)

(114) Part of the application of the sigmoid function **1500** to the data includes replacing various values in expression (9) with parameters or coefficients of A, B, C, D, E such that the expression (9) can be replaced by the following expression:

(115) $P_{@\,V}(PAT) = \frac{A}{E + e^{\left(\frac{PAT + C}{B}\right)}} + D$ (10)

(116) Thereafter, an optimization problem can be designed and solved by the controller **100** to generate a line that fits the data that is used to generate the graphical representation **1400**. The optimization problem is solved by the controller **100** in order to minimize an amount of variance in the data. With respect to the optimization problem, it is noted that in order to determine the values of parameters or coefficients A, B, C, D, and E, a least squares error analysis can be performed.

The implementation of the least squares error analysis enables for the determination of specific values for the parameters or coefficients A, B, C, D, and E that ensure that a specific set of data points closely fit the expression 10 (i.e. equation 10).

(117) FIG. **16** depicts a graphical representation **1600** that includes a line **1602** that fits the data used to generate the graphical representation **1400**. The values of each of the coefficients A, B, C, D, E can be derived from the line **1902**.

(118) In some embodiments, the temperature sensor **74**, as stated above, is configured to measure a temperature of the interior of the fuel box assembly **60** and route the temperature data to the memory **102** of the controller **100**. This temperature data can be analyzed by the controller **100** to determine the overall temperature of the cooking device **10** and the components disposed therein including, e.g., the inductive load **80**. In some embodiments, if the temperature data measured by the controller **100** is below a threshold value such as, e.g., ambient temperature or room temperature in the range of 59 degrees to 77 degrees (15, the controller **100** can determine that the cooking device **10** is in a cold state. As defined above, a cold state is when the cooking device **10** has not been recently used, e.g., has been off for a long period of time such as several hours.

(119) When the cooking device **10** is initiated (e.g., turned on) from such a state, the controller **100**, automatically and without user intervention, can initiate a starting condition compensation algorithm. Upon initiation of this algorithm, the controller **100** enables the application of a substantial amount electric power (e.g., high starting electric power) to the inductive load **80**. The controller **100** then applies a linear decaying value to this starting electric power, over a particular time frame, to modify the electric power delivered to the inductive load **82**. As a result, the electric power gradually regulates to the electric power that enables the fan blades **82** to operate at an operating speed that is preprogrammed into the memory **102**, e.g., 1000 RPM. An expression that represents the linearly decaying value is as follows:

(120) $P_{cold\_motor}(t) = P_{hot\_motor} * (1 + R_{comp} \frac{(t_{comp} - t)}{t_{comp}})$ (11)

(121) In the above expression, the variable P.sub.cold_motor represents an amount of electric power that is delivered to the inductive load **80** upon completion of the application of the linear decaying value over a particular time frame. The variable P.sub.hot_motor represents a power value that is required to generate the electric power that enables the inductive load **80** to operate at a particular target operating speed under, e.g., the condition that the inductive load **80** of the cooking device is operating at or satisfies a temperature threshold, e.g. the inductive load **80** operates at a temperature that can be classified as warm. The variable of R.sub.comp represents maximum multiplier ratio and t.sub.comp represents the time period over which the linearly decaying value is applied. It is noted that, while a linearly decaying value is described in expression 11, a non-linear decaying value such as an exponential value can also be utilized. In other words, the controller **110** can apply an exponential decaying value to a starting electric power, over a particular time frame, in order to modify the electrical power delivered to the inductive load **82**.

(122) FIG. **17** depicts a graphical representation **1700** of an electric power delivered to an inductive load **80** upon which the linearly decaying value is applied over a particular time frame, according to some embodiments described and illustrated herein. When the cooking device **10** is turned on from a cold state, a large amount of electric power is initially delivered to the inductive load **80**. When the cooking device **10** is activated from the cold state, the amount of the electric power that is delivered is gradually reduced and maintained at a particular level, as shown in FIG. **17**. In FIG. **17**, the x-axis **1702** corresponds to time periods and the y-axis **1704** corresponds to electric power values. In some embodiments, the cooking device **10** is determined to be in the cold state if the temperature sensor **74** detects the temperature of the cooking device **10** to be in a threshold temperature range of 15° C. to 50° C. In some embodiments, a single threshold temperature value (e.g., 21° C.) can be utilized by the controller **100**.

(123) FIG. **18** depicts a graphical representation **1800** of the operating speed of the inductive load

80 based on the gradual reduction of the electric power delivered to the inductive, as illustrated in FIG. **17** and described above. It is noted that FIG. **18** should be interpreted in combination with FIG. **17**. As shown in FIG. **18**, when the cooking device **10** is turn on from a cold state and a large amount of electric power is initially delivered to the inductive load **80**, there is a sudden and exponential increase in the operating speed of the inductive load, causing a similar increase in the operating speed of the fan blades **82**. Thereafter, as shown in FIG. **18**, the operating speed of the inductive load plateaus and is maintained at a particular level based on a steady amount of electric power being delivered to the inductive load **80** as illustrated in FIG. **17**. In FIG. **18**, the x-axis **1802** corresponds to time periods and the y-axis **1804** corresponds to operating speeds of the inductive load **80**.

(124) As explained above, in some embodiments, the controller **100** can monitor the length of time during which the igniter **66** is activated. As such, the controller **100** can be configured to determine whether a total length of time during which the igniter is activated exceeds the determined maximum time of activation. In response to determining that the total length of time exceeds the determined maximum time of activation, the controller **100** can cause the igniter **66** to deactivate and the cooking device **10** to exit the ignition mode.

(125) Additionally, in some embodiments, the controller **100** can cause the igniter **66** to deactivate and the cooking device **10** to exit the ignition mode in response to various events during the operation of the cooking device **10**. For example, the controller **100** can deactivate igniter **66** can deactivated and cause the cooking device **10** to exit the ignition mode in response to a user of the cooking device **10** pressing a start/stop button on the user interface **40** and/or in response to a user of the device changing the operating mode of the cooking device **10**, via interaction with the user interface **40**, from a smoker operating mode to an infusion operating mode.

(126) FIG. **19** is a block diagram **1900** of a computing system **1910** suitable for use in implementing the computerized components described herein. In broad overview, the computing system **1910** includes at least one processor **1950** for performing actions in accordance with instructions, and one or more memory devices (e.g., cache **1960** and/or memory **1970**) for storing instructions and data. The illustrated example computing system **1910** includes one or more processors **1950** in communication, via a bus **1915**, with memory **1970** and with at least one network interface controller **1920** with a network interface **1925** for connecting to external devices **1930**, e.g., a computing device. The one or more processors **1950** are also in communication, via the bus **1915**, with each other and with any I/O devices at one or more I/O interfaces **1940**, and any other devices **1980**. The processor **1950** illustrated incorporates, or is directly connected to, cache **1960**. Generally, a processor will execute instructions received from memory. In some embodiments, the computing system **1910** can be configured within a cloud computing environment, a virtual or containerized computing environment, and/or a web-based microservices environment.

(127) In more detail, the processor **1950** can be any logic circuitry that processes instructions, e.g., instructions fetched from the memory **1970** or cache **1960**. In many embodiments, the processor **1950** is an embedded processor, a microprocessor unit or special purpose processor. The computing system **1910** can be based on any processor, e.g., suitable digital signal processor (DSP), or set of processors, capable of operating as described herein. In some embodiments, the processor **1950** can be a single core or multi-core processor. In some embodiments, the processor **1950** can be composed of multiple processors.

(128) The memory **1970** can be any device suitable for storing computer readable data. The memory **1970** can be a device with fixed storage or a device for reading removable storage media. Examples include all forms of non-volatile memory, media and memory devices, semiconductor memory devices (e.g., EPROM, EEPROM, SDRAM, flash memory devices, and all types of solid state memory), magnetic disks, and magneto optical disks. A computing system **1910** can have any number of memory **1970**.

(129) The cache **1960** is generally a form of high-speed computer memory placed in close proximity to the processor **1950** for fast read/write times. In some implementations, the cache **1960** is part of, or on the same chip as, the processor **1950**.

(130) The network interface controller **1920** manages data exchanges via the network interface **1925**. The network interface controller **1920** handles the physical, media access control, and data link layers of the Open Systems Interconnect (OSI) model for network communication. In some implementations, some of the network interface controller's tasks are handled by the processor **1950**. In some implementations, the network interface controller **1920** is part of the processor **1950**. In some implementations, the computing system **1910** has multiple network interface controllers **1920**. In some implementations, the network interface **1925** is a connection point for a physical network link, e.g., an RJ 45 connector. In some implementations, the network interface controller **1920** supports wireless network connections and an interface port **1925** is a wireless Bluetooth transceiver. Generally, a computing system **1910** exchanges data with other external devices (the external devices **1930**) via physical or wireless links to a network interface **1925**. In some implementations, the network interface controller **1920** implements a network protocol such as LTE, TCP/IP Ethernet, IEEE 802.11, IEEE 802.16, Bluetooth, or the like.

(131) The other computing device **1930** is connected to the computing system **1910** via a network interface port **1925**. The other computing device **1930** can be a peer computing device, a network device, a server, or any other computing device with network functionality. In some embodiments, the computing device **1930** can be a network device such as a hub, a bridge, a switch, or a router, connecting the computing system **1910** to a data network such as the Internet.

(132) In some uses, the I/O interface **1940** supports an input device and/or an output device (not shown). In some uses, the input device and the output device are integrated into the same hardware, e.g., as in a touch screen. In some uses, such as in a server context, there is no I/O interface **1940** or the I/O interface **1940** is not used. In some uses, other devices **1980** are in communication with the computing system **1910**, e.g., external devices connected via a universal serial bus (USB).

(133) The other devices **1980** can include an I/O interface **1940**, external serial device ports, and any additional co-processors. For example, a computing system **1910** can include an interface (e.g., a universal serial bus (USB) interface, or the like) for connecting input devices (e.g., a keyboard, microphone, mouse, or other pointing device), output devices (e.g., video display, speaker, refreshable Braille terminal, or printer), or additional memory devices (e.g., portable flash drive or external media drive). In some implementations, an I/O device is incorporated into the computing system **1910**, e.g., a touch screen on a tablet device. In some implementations, a computing system **1910** includes an additional device **880** such as a co-processor, e.g., a math co-processor that can assist the processor **1950** with high precision or complex calculations.

(134) One or more aspects or features of the subject matter described herein can be realized in digital electronic circuitry, integrated circuitry, specially designed application specific integrated circuits (ASICs), field programmable gate arrays (FPGAs) computer hardware, firmware, software, and/or combinations thereof. These various aspects or features can include implementation in one or more computer programs that are executable and/or interpretable on a programmable system including at least one programmable processor, which can be special or general purpose, coupled to receive data and instructions from, and to transmit data and instructions to, a storage system, at least one input device, and at least one output device. The programmable system or computing system may include clients and servers. A client and server are generally remote from each other and typically interact through a communication network. The relationship of client and server arises by virtue of computer programs running on the respective computers and having a client-server relationship to each other.

(135) These computer programs, which can also be referred to as programs, software, software applications, applications, components, or code, include machine instructions for a programmable processor, and can be implemented in a high-level procedural language, an object-oriented

programming language, a functional programming language, a logical programming language, and/or in assembly/machine language. As used herein, the term "machine-readable medium" refers to any computer program product, apparatus and/or device, such as for example magnetic discs, optical disks, memory, and Programmable Logic Devices (PLDs), used to provide machine instructions and/or data to a programmable processor, including a machine-readable medium that receives machine instructions as a machine-readable signal. The term "machine-readable signal" refers to any signal used to provide machine instructions and/or data to a programmable processor. The machine-readable medium can store such machine instructions non-transitorily, such as for example as would a non-transient solid-state memory or a magnetic hard drive or any equivalent storage medium. The machine-readable medium can alternatively or additionally store such machine instructions in a transient manner, such as for example as would a processor cache or other random access memory associated with one or more physical processor cores.

(136) To provide for interaction with a user, one or more aspects or features of the subject matter described herein can be implemented on a computer having a display device, such as for example a cathode ray tube (CRT) or a liquid crystal display (LCD) or a light emitting diode (LED) monitor for displaying information to the user and a keyboard and a pointing device, such as for example a mouse or a trackball, by which the user may provide input to the computer. Other kinds of devices can be used to provide for interaction with a user as well. For example, feedback provided to the user can be any form of sensory feedback, such as for example visual feedback, auditory feedback, or tactile feedback; and input from the user may be received in any form, including, but not limited to, acoustic, speech, or tactile input. Other possible input devices include, but are not limited to, touch screens or other touch-sensitive devices such as single or multi-point resistive or capacitive trackpads, voice recognition hardware and software, optical scanners, optical pointers, digital image capture devices and associated interpretation software, and the like.

(137) Certain exemplary implementations have been described to provide an overall understanding of the principles of the structure, function, manufacture, and use of the systems, devices, and methods disclosed herein. One or more examples of these implementations have been illustrated in the accompanying drawings. Those skilled in the art will understand that the systems, devices, and methods specifically described herein and illustrated in the accompanying drawings are non-limiting exemplary implementations and that the scope of the present invention is defined solely by the claims. The features illustrated or described in connection with one exemplary implementation may be combined with the features of other implementations. Such modifications and variations are intended to be included within the scope of the present invention. Further, in the present disclosure, like-named components of the implementations generally have similar features, and thus within a particular implementation each feature of each like-named component is not necessarily fully elaborated upon.

(138) Approximating language, as used herein throughout the specification and claims, may be applied to modify any quantitative representation that could permissibly vary without resulting in a change in the basic function to which it is related. Accordingly, a value modified by a term or terms, such as "about," "approximately," and "substantially," are not to be limited to the precise value specified. In at least some instances, the approximating language may correspond to the precision of an instrument for measuring the value. Here and throughout the specification and claims, range limitations may be combined and/or interchanged, such ranges are identified and include all the sub-ranges contained therein unless context or language indicates otherwise.

(139) One skilled in the art will appreciate further features and advantages of the invention based on the above-described implementations. Accordingly, the present application is not to be limited by what has been particularly shown and described, except as indicated by the appended claims. All publications and references cited herein are expressly incorporated by reference in their entirety.

Claims

1. A device comprising: an electronic controller including memory, a power supply, a power sensor, a triode for alternative current (TRIAC), and an inductive load; the TRIAC in operable communication with the electronic controller and the inductive load; the power sensor in operable communication with the electronic controller and the power supply and configured to detect an electrical value; the electronic controller configured to: implement an algorithm for determining a set point value using the electrical value; apply the set point value on the TRIAC; and adjust operation of the inductive load to a target power responsive to the application of the set point value on the TRIAC.

2. The device of claim 1, further comprising a fan including at least one fan blade that is operably coupled to the inductive load, wherein the inductive load is a shaded-pole motor that controls rotational speed of the at least one fan blade.

3. The device of claim 1, wherein: the operation of the inductive load at the target power causes the operation of the inductive load at a target value, wherein the target value is a target speed; the implementing of the algorithm is based on at least one transfer function, the at least one transfer function is based on a linear relationship between a plurality of power values of the inductive load at the electrical value and a plurality of speeds of the inductive load at the electrical value; the adjusting of the operation of the inductive load comprises increasing an amount of power delivered to the inductive load from a current power to the target power; and the power sensor further configured to communicate data representative of the electrical value to the electronic controller.

4. The device of claim 3, wherein: the at least one transfer function enables mapping the plurality of speeds of the inductive load relative to a supply voltage with the plurality of power values at the supply voltage; and the target speed is included in the plurality of speeds and the target power is included in the plurality of power values.

5. The device of claim 1, wherein the electronic controller further configured to access from the memory, prior to the implementation of the algorithm, a target value for the inductive load based on the electrical value.

6. The device of claim 1, wherein the adjusting of the operation of the inductive load comprises decreasing an amount of power delivered to the inductive load from a current power to the target power.

7. The device of claim 1, wherein the electrical value is a supply voltage, a current, or a power.

8. The device of claim 1, further comprising a temperature sensor.

9. The device of claim 8, wherein the electronic controller is further configured to: determine, using the temperature sensor, a current temperature of the inductive load; compare the current temperature to a threshold temperature range, wherein the threshold temperature range is from 15° C. to 50° C.; and initiate a starting condition compensation algorithm responsive to the current temperature being within the threshold temperature range or below the threshold temperature range.

10. The device of claim 9, wherein the initiation of the starting condition compensation algorithm by the electronic controller comprises: applying a decaying value to a starting power; and driving the inductive load with the starting power, upon which the decaying value is applied, for a predetermined time frame.

11. A method implemented by a controller, the method comprising: receiving data representative of an electrical value; implementing an algorithm for determining a set point value using the electrical value; applying the set point value on a triode for alternative current (TRIAC); and adjusting operation of an inductive load to a target power responsive to the applying of the set point value on the TRIAC.

12. The method of claim 11, further comprising accessing from memory of the controller, prior to

the implementation of the algorithm, a target value for the inductive load based on the electrical value.

13. The method of claim 12, wherein: the implementing of the algorithm is based on at least one transfer function, the at least one transfer function is based on a linear relationship between a plurality of power values of the inductive load at the electrical value and a plurality of speeds of the inductive load at the electrical value; and wherein the target value is a target speed.

14. The method of claim 11, wherein: the adjusting of the operation of the inductive load comprises increasing an amount of power delivered to the inductive load from a current power to the target power; the operation of the inductive load at the target power causes operation of the inductive load at a target value; and the inductive load is a shaded-pole motor that is coupled to a fan blade.

15. The method of claim 11, wherein: the adjusting of the operation of the inductive load comprises decreasing an amount of power delivered to the inductive load from a current power to the target power.

16. The method of claim 11, wherein the electrical value is a supply voltage, a current, or a power.

17. A system comprising: a power source; a device including a power supply, a triode for alternative current (TRIAC), an inductive load, and at least one data processor that is communicatively coupled to the TRIAC; and memory storing instructions, which when executed by the at least one data processor, causes the at least one data processor to perform operations comprising: determining an electrical value; implementing an algorithm for determining a set point value using the electrical value; applying the set point value on the TRIAC; and adjusting operation of the inductive load to a target power responsive to the applying of the set point value on the TRIAC, the operation of the inductive load at the target power causes operation of the inductive load at a target value.

18. The system of claim 17, further comprising a temperature sensor and wherein the target value is a target speed and the electrical value is at least one of a supply voltage, a current, or a power.

19. The system of claim 18, wherein the operations further comprise: accessing the target value for the inductive load that is specific to the electrical value before the implementing of the algorithm; determining, using the temperature sensor, a current temperature of the inductive load; comparing the current temperature to a threshold temperature range, wherein the threshold temperature range is from 15° C. to 50° C.; and initiating a starting condition compensation algorithm responsive to the current temperature being within the threshold temperature range or below the threshold temperature range.

20. The system of claim 19, wherein one of the operations of the initiation of the starting condition compensation algorithm by the at least one data processor comprises: applying a decaying value to a starting power; and driving the inductive load with the starting power upon which the decaying value is applied for a predetermined time frame.