

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12395143
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Mizoguchi; Naoki

---

### Low pass filter, multilayer-type low pass filter, and method of adjusting filter characteristic

---

#### Abstract

A low pass filter includes a first input/output terminal, a second input/output terminal, a signal line, inductors connected in the signal line, and capacitors connected between the signal line and ground. In the signal line, a capacitor is connected in parallel to the inductor that is connected closest to the first input/output terminal, and the inductor and the capacitor define a first parallel resonator.

---

<b>Inventors:</b>	<b>Mizoguchi; Naoki (Nagaokakyo, JP)</b>
<b>Applicant:</b>	<b>Murata Manufacturing Co., Ltd. (Nagaokakyo, JP)</b>
<b>Family ID:</b>	<b>1000008763830</b>
<b>Assignee:</b>	<b>MURATA MANUFACTURING CO., LTD. (Kyoto, JP)</b>
<b>Appl. No.:</b>	<b>18/126747</b>
<b>Filed:</b>	<b>March 27, 2023</b>

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20230238934 A1	Jul. 27, 2023

#### Foreign Application Priority Data

JP	2020-195572	Nov. 25, 2020
JP	2021-083609	May. 18, 2021

#### Related U.S. Application Data

continuation parent-doc WO PCT/JP2021/040477 20211103 PENDING child-doc US 18126747

---

## Publication Classification

**Int. Cl.:** **H03H7/01** (20060101); **H01F27/28** (20060101); **H01F27/40** (20060101); **H01G4/30** (20060101); **H01G4/40** (20060101)

**U.S. Cl.:**

**CPC** **H03H7/0115** (20130101); **H01F27/2804** (20130101); **H01F27/40** (20130101); **H01G4/30** (20130101); **H01G4/40** (20130101); H01F2027/2809 (20130101)

## Field of Classification Search

**CPC:** H03H (7/0115); H03H (7/00); H03H (7/01); H03H (7/09); H03H (7/0138); H03H (7/0153); H03H (7/1742); H03H (7/1791); H03H (7/46); H03H (3/00)

**USPC:** 333/167; 327/551; 327/552; 327/558

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11528047	12/2021	Tsukamoto	N/A	H04B 1/40
2003/0092397	12/2002	Uriu et al.	N/A	N/A
2016/0233845	12/2015	Masuda et al.	N/A	N/A
2017/0170798	12/2016	Masuda	N/A	N/A

### FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
5924534	12/1983	JP	N/A
6115721	12/1985	JP	N/A
06290992	12/1993	JP	N/A
07192927	12/1994	JP	N/A
H11111541	12/1998	JP	N/A
2003209454	12/2002	JP	N/A
2006269653	12/2005	JP	N/A
2008271187	12/2007	JP	N/A
2015064133	12/2014	WO	N/A
2016152205	12/2015	WO	N/A
2017199749	12/2016	WO	N/A

### OTHER PUBLICATIONS

International Search Report in PCT/JP2021/040477, mailed Feb. 1, 2022, 4 pages. cited by applicant

Written Opinion in PCT/JP2021/040477, mailed Feb. 1, 2022, 6 pages. cited by applicant

---

*Primary Examiner:* Nguyen; Hai L

*Attorney, Agent or Firm:* Keating & Bennett, LLP

---

## Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application claims the benefit of priority to Japanese Patent Application No. 2021-083609 filed on May 18, 2021 and Japanese Patent Application No. 2020-195572 filed on Nov. 25, 2020, and is a Continuation Application of PCT Application No. PCT/JP2021/040477 filed on Nov. 3, 2021. The entire contents of each application are hereby incorporated herein by reference.

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

(1) The present invention relates to a low pass filter, a multilayer-type low pass filter, and a method of adjusting a filter characteristic.

#### 2. Description of the Related Art

(2) Japanese Unexamined Utility Model Registration Application Publication No. 61-15721 discloses a low pass filter. FIG. 22A illustrates the low pass filter **1000** disclosed in Japanese Unexamined Utility Model Registration Application Publication No. 61-15721.

(3) The low pass filter **1000** includes a first input/output terminal **101** and a second input/output terminal **102**. A signal line **103** is formed in between the first input/output terminal **101** and the second input/output terminal **102**.

(4) In the signal line **103**, a first inductor **104**, a second inductor **105**, and a third inductor **106** are connected in sequence. A first capacitor **107** is connected between ground and a connecting point of the first inductor **104** and the second inductor **105**. A second capacitor **108** is connected between the ground and a connecting point of the second inductor **105** and the third inductor **106**.

(5) As illustrated in FIG. 22B, in the case where the low pass filter **1000** is formed on a substrate **109**, each of the first inductor **104**, the second inductor **105**, and the third inductor **106** includes a line conductor **110** having plural turns.

(6) In the low pass filter **1000**, a desired pass band is produced in the frequency characteristic thereof, and further, a stop band is produced in a higher frequency range above the pass band.

### SUMMARY OF THE INVENTION

(7) In low pass filters, it is required that in the frequency characteristic, favorable attenuation is produced outside the pass band and a spurious noise that would become an obstacle does not occur in the stop band. However, it is difficult to design a low pass filter that sufficiently meets these two requirements at the same time.

(8) Preferred embodiments of the present invention provide low pass filters that each can produce favorable attenuation outside a high frequency side of a pass band and facilitate control of a spurious noise that occurs in a stop band.

(9) A low pass filter according to a preferred embodiment of the present invention includes a first input/output terminal, a second input/output terminal, a signal line connected between the first input/output terminal and the second input/output terminal, a first inductor connected closest to the first input/output terminal in the signal line, at least one second inductor connected closer to the second input/output terminal than the first inductor in the signal line, and a first capacitor connected between ground and a connecting point of the first inductor and the second inductor, or connected between the ground and the connecting point of the first inductor and the second inductor and between the ground and a connecting point of the second inductors adjacent to one another in a case where two of the at least one second inductor are adjacent to one another. A second capacitor is connected in parallel to the first inductor, the first inductor and the second capacitor define a first LC parallel resonator, and no capacitor is connected in parallel to the second inductor.

(10) A low pass filter according to a preferred embodiment of the present invention produces

favorable attenuation outside the high frequency side of a pass band.

(11) Further, a low pass filter according to a preferred embodiment of the present invention can perform the control in such a way that the spurious noise would not become an obstacle, for example, by dividing the at least one second inductor into a plurality of segmented inductors, causing the segmented inductors having been divided to couple with each other, adjusting an apparent inductance value of the second inductor using a degree of the coupling, and adjusting a frequency of a spurious noise that occurs in a stop band and an amount of attenuation thereof.

(12) The above and other elements, features, steps, characteristics and advantages of the present invention will become more apparent from the following detailed description of the preferred embodiments with reference to the attached drawings.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is an equivalent circuit diagram of a low pass filter **100** according to a first preferred embodiment of the present invention.

(2) FIG. 2 is an exploded perspective view of the low pass filter **100**.

(3) FIG. 3 is a graph illustrating a frequency characteristic of the low pass filter **100**.

(4) FIG. 4A is an equivalent circuit diagram of a low pass filter **1100** of a comparative example.

FIG. 4B is a graph illustrating a frequency characteristic of the low pass filter **1100**.

(5) FIG. 5 illustrates equivalent circuit diagrams illustrating circuits A to E of an experiment 1.

(6) FIG. 6 is a graph illustrating frequency characteristics of the circuits A to E.

(7) FIG. 7 illustrates exploded perspective views of relevant parts of low pass filters **200A**, **200B**, and **200C** according to a second preferred embodiment of the present invention.

(8) FIG. 8 is a graph illustrating frequency characteristics of the low pass filters **200A**, **200B**, and **200C**.

(9) FIG. 9 is an equivalent circuit diagram of a low pass filter **300** according to a third preferred embodiment of the present invention.

(10) FIG. 10 is an exploded perspective view of the low pass filter **300**.

(11) FIG. 11 is an equivalent circuit diagram of a low pass filter **400** according to a fourth preferred embodiment of the present invention.

(12) FIG. 12 is an equivalent circuit diagram of a low pass filter **500** according to a fifth preferred embodiment of the present invention.

(13) FIG. 13 is an equivalent circuit diagram of a low pass filter **600** according to a sixth preferred embodiment of the present invention.

(14) FIG. 14 is an equivalent circuit diagram of a low pass filter **700** according to a seventh preferred embodiment of the present invention.

(15) FIG. 15 is an exploded perspective view of the low pass filter **700**.

(16) FIG. 16 illustrates a graph illustrating a frequency characteristic of the low pass filter **700**.

(17) FIG. 17A is an equivalent circuit diagram illustrating a circuit F of an experiment 2. FIG. 17B is a graph illustrating frequency characteristics of the circuit F.

(18) FIG. 18 illustrates equivalent circuit diagrams illustrating circuits G to J of an experiment 3.

(19) FIG. 19 illustrates graphs illustrating frequency characteristics of the circuits G to J.

(20) FIG. 20 is an exploded perspective view of a low pass filter **800** according to an eighth preferred embodiment of the present invention.

(21) FIG. 21 is a graph illustrating frequency characteristics of the low pass filter **800**.

(22) FIG. 22A is an equivalent circuit diagram of a low pass filter **1000** disclosed in Japanese Unexamined Utility Model Registration Application Publication No. 61-15721. FIG. 22B is a plan view of the low pass filter **1000**.

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

(23) Hereinafter, preferred embodiments of the present invention are described with reference to the drawings.

(24) Note that each preferred embodiment is provided as an example of preferred embodiments of the present invention, and the present invention is not limited by contents of the preferred embodiments. Further, contents described in different preferred embodiments can be combined for implementation, and implemented contents in such case are also included within the scope of the present invention. Further, the drawings are provided to assist an understanding of the specification and are drawn schematically in some cases. Thus, ratios of dimensions of elements that are drawn or ratios of dimensions between the elements do not agree with those described in the specification in some cases. Further, there may be a case where an element described in the specification is omitted in the drawing, a case where a smaller number of elements are drawn, or the like.

### First Preferred Embodiment

(25) FIG. 1 and FIG. 2 illustrate a low pass filter **100** according to the first preferred embodiment. Note that FIG. 1 is an equivalent circuit diagram of the low pass filter **100**. FIG. 2 is an exploded perspective view of the low pass filter **100**. Note that the low pass filter **100** of FIG. 2 is such that the low pass filter **100** is configured as an electronic component including a multilayer body in which a plurality of insulating layers are stacked on top of each other.

(26) The low pass filter **100** has the equivalent circuit illustrated in FIG. 1.

(27) The low pass filter **100** includes a first input/output terminal **T1** and a second input/output terminal **T2**. A signal line **SL** is between the first input/output terminal **T1** and the second input/output terminal **T2**.

(28) In the signal line **SL**, a first stage inductor **L1**, a third stage inductor **L3**, and a fifth stage inductor **L5** are connected in sequence.

(29) The third stage inductor **L3** is divided into three segmented inductors, which are a first segmented inductor **L3a**, a second segmented inductor **L3b**, and a third segmented inductor **L3c**.

(30) A second stage capacitor **C2** is connected between ground and a connecting point of the first stage inductor **L1** and the third stage inductor **L3**. A fourth stage capacitor **C4** is connected between the ground and a connecting point of the third stage inductor **L3** and the fifth stage inductor **L5**.

(31) Moreover, a capacitor **Ca1** is connected in parallel to the first stage inductor **L1**. Moreover, the inductor **L1** and the capacitor **Ca1** define a first LC parallel resonator. As will be described later, this LC parallel resonator contributes to the production of favorable attenuation outside the high frequency side of a pass band.

(32) The low pass filter **100** preferably is a five stage low pass filter in which the first stage the first stage inductor **L1**, the second stage capacitor **C2**, the third stage inductor **L3**, the fourth stage capacitor **C4**, and the fifth stage inductor **L5** are connected in sequence in between the first input/output terminal **T1** and the second input/output terminal **T2**.

(33) Note that in the low pass filter **100**, in some cases, the inductor **L1** is referred to as the first inductor, the inductors **L3** and **L5** are referred to as the second inductors, the capacitors **C2** and **C4** are referred to as the first capacitors, and the capacitor **Ca1** is referred to as the second capacitor.

(34) In the low pass filter **100**, the circuit element closest to the first input/output terminal **T1** is a circuit element (inductor **L1**) connected in the signal line **SL**, the circuit element closest to the second input/output terminal **T2** is also a circuit element (inductor **L5**) connected in the signal line **SL**, and neither circuit element is a circuit element connected between the signal line **SL** and the ground. Thus, the low pass filter **100** is configured as a so-called T-type low pass filter.

(35) As described above, the low pass filter **100** of FIG. 2 is such that the low pass filter **100** is configured as an electronic component including a multilayer body **1** in which a plurality of insulating layers **1a** to **1i** are stacked on top of each other.

(36) As the material of the multilayer body **1** (insulating layers **1a** to **1i**), an arbitrary material may be used, and for example, a ceramic can be used. Note that in some cases, each of the insulating

layers **1a** to **1i** includes a plurality of layers. That is to say, for example, in some cases, the insulating layer **1a** includes a plurality of ceramic layers.

(37) Next, the configurations of the respective insulating layers **1a** to **1i** are described.

(38) The first input/output terminal **T1**, the second input/output terminal **T2**, and a ground terminal **TG** are provided on a lower side principal surface of the insulating layer **1a**.

(39) Eight via conductors **2a** to **2h** penetrate through both upper and lower side principal surfaces of the insulating layer **1a**.

(40) A ground electrode **3** is provided on the upper side principal surface of the insulating layer **1a**.

(41) The via conductors **2a** and **2b** penetrate through both upper and lower side principal surfaces of the insulating layer **1b**.

(42) Capacitor electrodes **4a** and **4b** are provided on the upper side principal surface of the insulating layer **1b**.

(43) The via conductors **2a** and **2b** described above and new via conductors **2i** and **2j** penetrate through both upper and lower side principal surfaces of the insulating layer **1c**.

(44) A capacitor electrode **4c** is provided on the upper side principal surface of the insulating layer **1c**.

(45) The via conductors **2a**, **2b**, **2i**, and **2j** penetrate through both upper and lower side principal surfaces of the insulating layer **1d**.

(46) A capacitor electrode **4d** is provided on the upper side principal surface of the insulating layer **1d**.

(47) The via conductors **2a**, **2b**, **2i**, and **2j** penetrate through both upper and lower side principal surfaces of the insulating layer **1e**.

(48) A capacitor electrode **4e** is provided on the upper side principal surface of the insulating layer **1e**.

(49) The via conductors **2a**, **2b**, **2i**, and **2j** penetrate through both upper and lower side principal surfaces of the insulating layer **1f**.

(50) Line conductors **5a** and **5b** are provided on the upper side principal surface of the insulating layer **1f**.

(51) The via conductors **2i** and **2j** penetrate through both upper and lower side principal surfaces of the insulating layer **1g**.

(52) A line conductor **5c** is provided on the upper side principal surface of the insulating layer **1g**.

(53) The via conductors **2i** and **2j** described above and new via conductors **2k** and **2l** penetrate through both upper and lower side principal surfaces of the insulating layer **1h**.

(54) Line conductors **5d** and **5e** are provided on the upper side principal surface of the insulating layer **1h**.

(55) The insulating layer **1i** is a protective layer, and none of the electrode, the via conductor, and the line conductor is provided on or in the insulating layer **1i**.

(56) Next, the connection relationship among the first input/output terminal **T1**, the second input/output terminal **T2**, the ground terminal **TG**, the via conductors **2a** to **2l**, the ground electrode **3**, the capacitor electrodes **4a** to **4e**, and the line conductors **5a** to **5e** in the low pass filter **100** illustrated in FIG. 2 is described.

(57) The first input/output terminal **T1** is connected to the capacitor electrode **4d** and one end portion of the line conductor **5a** by the via conductor **2a**.

(58) The second input/output terminal **T2** is connected to one end portion of the line conductor **5b** by the via conductor **2b**.

(59) The ground terminal **TG** is connected to the ground electrode **3** by the via conductors **2c** to **2h**.

(60) The other end portion of the line conductor **5a** is connected to the capacitor electrodes **4a**, **4c**, and **4e** and the other end portion of the line conductor **5d** by the via conductor **2i**.

(61) The other end portion of the line conductor **5b** is connected to the capacitor electrode **4b** and the other end portion of the line conductor **5e** by the via conductor **2j**.

(62) The other end portion of the line conductor **5d** is connected to one end portion of the line conductor **5c** by the via conductor **2k**.

(63) The other end portion of the line conductor **5e** is connected to the other end portion of the line conductor **5c** by the via conductor **2l**.

(64) An arbitrary metal can be used as the material of the first input/output terminal **T1**, the second input/output terminal **T2**, the ground terminal **TG**, the via conductors **2a** to **2l**, the ground electrode **3**, the capacitor electrodes **4a** to **4e**, and the line conductors **5a** to **5e**. Surfaces of the first input/output terminal **T1**, the second input/output terminal **T2**, and the ground terminal **TG** may be subjected to plating processing.

(65) Next, the relationship between the equivalent circuit of the low pass filter **100** illustrated in FIG. **1** and the structure of the low pass filter **100** illustrated in FIG. **2** is described.

(66) In FIG. **2**, the signal line **SL** in FIG. **1** includes a conductor line that starts from the first input/output terminal **T1** and ends at the second input/output terminal **T2** via the via conductor **2a**, the line conductor **5a**, the via conductor **2i**, the line conductor **5d**, the via conductor **2k**, the line conductor **5c**, the via conductor **2j**, the line conductor **5e**, the via conductor **2l**, the line conductor **5b**, and the via conductor **2b**.

(67) The first stage inductor **L1** mostly includes the line conductor **5a**.

(68) As described above, the third stage inductor **L3** is divided into three segmented inductors, which are the first segmented inductor **L3a**, the second segmented inductor **L3b**, and the third segmented inductor **L3c**. The first segmented inductor **L3a** mostly includes the line conductor **5d**. The second segmented inductor **L3b** mostly includes the line conductor **5c**. The third segmented inductor **L3c** mostly includes the line conductor **5e**.

(69) Note that as described above, the line conductor **5d** included in the first segmented inductor **L3a** and the line conductor **5e** included in the third segmented inductor **L3c** are both provided on the upper side principal surface of the insulating layer **1h** and are coupled with each other. The mode of the coupling is, for example, magnetic coupling. For example, it is preferable that the line conductor **5d** and the line conductor **5e** are coupled with each other in a forward direction.

(70) The fifth stage inductor **L5** mostly includes the line conductor **5b**.

(71) Note that in the present preferred embodiment, the total inductor length of the third stage inductor **L3**, which is divided into the first segmented inductor **L3a**, the second segmented inductor **L3b**, and the third segmented inductor **L3c**, is longer than the inductor length of the first stage inductor **L1** and also longer than the inductor length of the fifth stage inductor **L5**.

(72) The second stage capacitor **C2** includes the capacitance between the capacitor electrode **4a** and the ground electrode **3**.

(73) The fourth stage capacitor **C4** includes the capacitance between the capacitor electrode **4b** and the ground electrode **3**.

(74) The capacitor **Ca1** includes the capacitance between the capacitor electrode **4d** and the capacitor electrodes **4c** and **4e**.

(75) As described above, the equivalent circuit of the low pass filter **100** illustrated in FIG. **1** is configured by using the structure of the low pass filter **100** illustrated in FIG. **2**.

(76) FIG. **3** illustrates the frequency characteristic of the low pass filter **100**.

(77) For the purpose of comparison, a low pass filter **1100** according to a comparative example illustrated in FIG. **4A** is fabricated. The low pass filter **1100** is such that the capacitor **Ca1** is removed from the low pass filter **100** and the inductor **L3**, which is divided into three segmented inductors **L3a**, **L3b**, and **L3c** in the low pass filter **100**, is made up of a single inductor.

(78) FIG. **4B** illustrates the frequency characteristic of the low pass filter **1100** according to the comparative example.

(79) As can be seen from FIG. **3**, in the frequency characteristic of the low pass filter **100**, a pole **P** having favorable attenuation (steep attenuation) occurs outside the high frequency side of the pass band. It is considered that this pole **P** occurs because the first stage inductor **L1** is connected in

parallel to the capacitor Ca1, and the inductor L1 and the capacitor Ca1 define the first LC parallel resonator.

(80) Further, in the frequency characteristic of the low pass filter **100**, spurious noises SP1 to SP3 occur in a stop band. However, all the spurious noises SP1 to SP3 are outside the frequency or frequencies at which a spurious noise becomes a problem if the spurious noise occurs, and to a certain extent, a large amount of attenuation is obtained at all of the spurious noises. Thus, the spurious noises SP1 to SP3 do not become an obstacle. It is considered that this is an effect obtained by dividing the third stage inductor L3 into three segmented inductors, which are the first segmented inductor L3a, the second segmented inductor L3b, and the third segmented inductor L3c, causing the first segmented inductor L3a and the third segmented inductor L3c to couple with each other, and adjusting an apparent inductance value of the third stage inductor L3 using a degree of that coupling, thereby adjusting the frequency at which each spurious noise occurs and the amount of attenuation thereof.

(81) Note that the frequency at which a spurious noise becomes an obstacle if the spurious noise occurs and the amount of attenuation thereof vary from one electronic device (communication device or the like), in which the low pass filter **100** is used, to another.

(82) On the other hand, as illustrated in FIG. 4B, in the frequency characteristic of the low pass filter **1100** of the comparative example, the amount of attenuation outside the high frequency side of the pass band gradually increases as the frequency increases, and favorable pole does not occur. It is considered that this is because the first stage inductor L1 is not connected in parallel to the capacitor Ca1 and the first LC parallel resonator is not provided.

(83) Further, in the frequency characteristic of the low pass filter **1100**, spurious noises SP4 and SP5 occur in the stop band. The amounts of attenuations of the spurious noises SP4 and SP5 are small, and it is possible that the spurious noises SP4 and SP5 become an obstacle. It is considered that the amounts of attenuations of the spurious noises SP4 and SP5 become larger because the third stage inductor L3 is not divided into the segmented inductors, these segmented inductors are not coupled with each other, and the frequency characteristic is not adjusted.

(84) In the present preferred embodiment, the total inductor length of the third stage inductor L3 is longer than the inductor length of the first stage inductor L1 and also longer than the inductor length of the fifth stage inductor L5. Thus, each of the inductor length of the first segmented inductor L3a and the inductor length of the third segmented inductor L3c is also longer. This facilitates the adjustment of the degree of the coupling between the first segmented inductor L3a and the third segmented inductor L3c. That is to say, when the distance between the line conductor included in the first segmented inductor L3a and the line conductor included in the third segmented inductor L3c is shorter, the coupling becomes stronger, and when the distance between the line conductor included in the first segmented inductor L3a and the line conductor included in the third segmented inductor L3c is longer, the coupling becomes weaker.

(85) In a low pass filter according to a preferred embodiment of the present invention, an additional capacitor is connected in parallel to the inductor closest to the first input/output terminal T1, which is one of the inductors connected in the signal line, and the additional capacitor and the inductor closest to the first input/output terminal T1 make up the first LC parallel resonator. Further, in a low pass filter according to another preferred embodiment of the present invention, in addition to the first LC parallel resonator, an additional capacitor is connected in parallel to the inductor closest to the second input/output terminal T2, and this additional capacitor and the inductor closest to the second input/output terminal T2 define a second LC parallel resonator. Note that the “additional” means “to add in addition to the capacitors C2 and C4”.

(86) The low pass filter according to a preferred embodiment and the low pass filter according to another preferred embodiment are the configurations each derived from an experiment 1, which will be described below. Next, the reason why these configurations are used is described.

(87) Experiment 1



(88) First, as is the case with low pass filter **100**, five stage low pass filters are fabricated as basic low pass filters, in each of which the first stage inductor **L1**, the second stage capacitor **C2**, the third stage inductor **L3**, the fourth stage capacitor **C4**, and the fifth stage inductor **L5** are connected in sequence in between the first input/output terminal and the second input/output terminal. Then, five circuits, which are a circuit A to a circuit E illustrated in FIG. 5, are fabricated by varying the position to which the additional capacitor **Ca** is connected and the number of the additional capacitors **Ca**.

(89) In the circuit A, an additional capacitor **Ca1** is connected in parallel to the first stage inductor **L1**, an additional capacitor **Ca3** is connected in parallel to the third stage inductor **L3**, and an additional capacitor **Ca5** is connected in parallel to the fifth stage inductor **L5**. In the circuit B, the additional capacitor **Ca1** is connected in parallel to the first stage inductor **L1**, and the additional capacitor **Ca5** is connected in parallel to the fifth stage inductor **L5**. In the circuit C, the additional capacitor **Ca1** is connected in parallel to the first stage inductor **L1**. Note that the circuit C is equivalent to the case where the additional capacitor **Ca5** is connected in parallel to the fifth stage inductor **L5** when the signal line is seen from the opposite direction. In the circuit D, the additional capacitor **Ca3** is connected in parallel to the third stage inductor **L3**. In the circuit E, the additional capacitor **Ca** is not connected.

(90) FIG. 6 illustrates the frequency characteristics ( $S(2,1)$  characteristic) of the respective circuit A to the circuit E.

(91) In each of the circuit A and the circuit D, favorable attenuation (pole) occurs outside the high frequency side of the pass band, but the amount of attenuation is not sufficient in the stop band. In each of the circuit B and the circuit C, favorable attenuation (pole) occurs outside the high frequency side of the pass band, and the amount of attenuation in the stop band is sufficient. In the circuit E, the amount of attenuation is sufficient in the stop band, but favorable attenuation (pole) does not occur outside the high frequency side of the pass band.

(92) From the foregoing result, in a low pass filter according to a preferred embodiment of the present invention, a capacitor is additionally connected in parallel to the inductor closest to the first input/output terminal **T1**, which is one of inductors connected in the signal line. Further, in a low pass filter according to another preferred embodiment of the present invention, capacitors are respectively additionally connected in parallel to the inductor closest to the first input/output terminal **T1** and the inductor closest to the second input/output terminal **T2**, which are two of inductors connected in the signal line. Note that in the low pass filter **100** according to the first preferred embodiment, the capacitor **Ca1** is additionally connected in parallel to the first stage inductor **L1**.

#### Second Preferred Embodiment

(93) FIG. 7 illustrates three low pass filters **200A**, **200B**, and **200C** according to the second preferred embodiment. Note that FIG. 7 illustrates exploded perspective views of relevant portions and illustrates the insulating layer **1g** and the insulating layer **1h** of each low pass filter.

(94) A basic equivalent circuit for the low pass filters **200A**, **200B**, and **200C** is the same as the equivalent circuit of the low pass filter **100** according to the first preferred embodiment illustrated in FIG. 1, and a basic structure for the low pass filters **200A**, **200B**, and **200C** is the same as the structure of the low pass filter **100** illustrated in FIG. 2.

(95) The low pass filters **200A**, **200B**, and **200C** are configured in such a way that the degree of coupling between the first segmented inductor **L3a** and the third segmented inductor **L3c** in the low pass filter **100** is adjusted in three ways, which are a large degree of coupling, a medium degree of coupling, and a small degree of coupling, respectively.

(96) That is to say, in the low pass filter **200A**, the degree of coupling between the first segmented inductor **L3a** and the third segmented inductor **L3c** is large. In the low pass filter **200B**, the degree of coupling between the first segmented inductor **L3a** and the third segmented inductor **L3c** is medium. In the low pass filter **200C**, the degree of coupling between the first segmented inductor

**L3a** and the third segmented inductor **L3c** is small. The degree of coupling is adjusted using the distance between the line conductor **5d** included in the first segmented inductor **L3a** and the line conductor **5e** included in the third segmented inductor **L3c**. Specifically, when the distance between the line conductor **5d** included in the first segmented inductor **L3a** and the line conductor **5e** included in the third segmented inductor **L3c** is short, the coupling is strong, and when the distance between the line conductor **5d** included in the first segmented inductor **L3a** and the line conductor **5e** included in the third segmented inductor **L3c** is long, the coupling is weak.

(97) FIG. **8** illustrates the frequency characteristics (S(2,1) characteristic) of the respective low pass filters **200A**, **200B**, and **200C**. As can be seen from FIG. **8**, by adjusting the degree of coupling between the first segmented inductor **L3a** and the third segmented inductor **L3c**, the frequency of a spurious noise that occurs in the pass band and the amount of attenuation thereof are adjusted without changing basic filter characteristics such as the pass band.

(98) According to a preferred embodiment of the present invention, it becomes possible to facilitate the control that prevents the spurious noise from becoming an obstacle by adjusting the frequency of a spurious noise that occurs in the stop band and the amount of attenuation thereof.

#### Third Preferred Embodiment

(99) FIG. **9** and FIG. **10** illustrate a low pass filter **300** according to the third preferred embodiment. Note that FIG. **9** is an equivalent circuit diagram of the low pass filter **300**. FIG. **10** is an exploded perspective view of the low pass filter **300**.

(100) In the low pass filter **300**, a new element is added to the low pass filter **100** according to the first preferred embodiment. Specifically, in the low pass filter **100**, the additional capacitor **Ca1** is connected in parallel to the first stage inductor **L1**. In the low pass filter **300**, in addition to the capacitor **Ca1**, an additional capacitor **Ca2** is connected in parallel to the fifth stage inductor **L5**.

(101) Note that in the low pass filter **300**, in some cases, the inductor **L1** is referred to as the first inductor, the inductor **L3** is referred to as the second inductor, the inductor **L5** is referred to as the third inductor, the capacitor **C2** is referred to as the first capacitor, the capacitor **Ca1** is referred to as the second capacitor, the capacitor **C4** is referred to as the third capacitor, and the capacitor **Ca2** is referred to as the fourth capacitor.

(102) More specifically, as illustrated in FIG. **10**, a capacitor electrode **34f** connected to the via conductor **2j** is provided on the upper side principal surface of the insulating layer **1c**, a capacitor electrode **34g** connected to the via conductor **2b** is provided on the upper side principal surface of the insulating layer **1d**, and a capacitor electrode **34h** connected to the via conductor **2j** is provided on the upper side principal surface of the insulating layer **1e**. Moreover, the additional capacitor **Ca2** connected in parallel to the fifth stage inductor **L5** includes the capacitance between the capacitor electrode **34g** and the capacitor electrodes **34f** and **34h**.

(103) In the low pass filter **300**, favorable attenuation also occurs outside of the high frequency side of the pass band, and a spurious noise that would become an obstacle is less likely to occur in the stop band.

#### Fourth Preferred Embodiment

(104) FIG. **11** illustrates a low pass filter **400** according to the fourth preferred embodiment. Note that FIG. **11** is an equivalent circuit diagram of the low pass filter **400**.

(105) In the low pass filter **400**, a portion of the configuration of the low pass filter **100** according to the first preferred embodiment is also modified. Specifically, while the low pass filter **100** is the five stage low pass filter, the low pass filter **400** is a three stage low pass filter. Specifically, the configuration of the low pass filter **400** is such that the fourth stage capacitor **C4** and the fifth stage inductor **L5** are removed from the low pass filter **100**.

(106) Note that in the low pass filter **400**, in some cases, the inductor **L1** is referred to as the first inductor, the inductor **L3** is referred to as the second inductor, the capacitor **C2** is referred to as the first capacitor, and the capacitor **Ca1** is referred to as the second capacitor.

(107) In the low pass filter **400**, favorable attenuation also occurs outside of the high frequency side

of the pass band, and a spurious noise that would become an obstacle is less likely to occur in the stop band.

#### Fifth Preferred Embodiment

(108) FIG. 12 illustrates a low pass filter 500 according to the fifth preferred embodiment. Note that FIG. 12 is an equivalent circuit diagram of the low pass filter 500.

(109) In the low pass filter 500, a portion of the configuration of the low pass filter 100 according to the first preferred embodiment is also modified. Specifically, while the low pass filter 100 is the five stage low pass filter, the low pass filter 500 is a seven stage low pass filter. Specifically, the configuration of the low pass filter 500 is such that a sixth stage capacitor C6 and the seventh stage inductor L7 are added in between the fifth stage inductor L5 and the second input/output terminal T2 of the low pass filter 100.

(110) Note that in the low pass filter 500, in some cases, the inductor L1 is referred to as the first inductor, the inductors L3, L5, and L7 are referred to as the second inductors, the capacitors C2, C3, and C4 are referred to as the first capacitors, and the capacitor Ca1 is referred to as the second capacitor.

(111) Note that in the low pass filter 500, the third stage inductor L3 is divided into the segmented inductors L3a to L3c. Instead of this, the fifth stage inductor L5 or the seventh stage inductor L7 may be divided into segmented inductors.

(112) In the low pass filter 500, favorable attenuation also occurs outside of the high frequency side of the pass band, and a spurious noise that would become an obstacle is less likely to occur in the stop band.

#### Sixth Preferred Embodiment

(113) FIG. 13 illustrates a low pass filter 600 according to the sixth preferred embodiment. Note that FIG. 13 is an equivalent circuit diagram of the low pass filter 600.

(114) In the low pass filter 600, part of the configuration of the low pass filter 100 according to the first preferred embodiment is also modified. Specifically, while the low pass filter 100 is the five stage T-type low pass filter, the low pass filter 600 is a seven stage n-type low pass filter. Specifically, in the low pass filter 600, the first stage circuit element closest to the first input/output terminal T1 is a capacitor C1 connected between the signal line SL and the ground, and the seventh stage circuit element (final stage) closest to the second input/output terminal T2 is a capacitor C7 connected between the signal line SL and the ground. Moreover, the capacitor Ca1 is additionally connected in parallel to a second stage inductor L2.

(115) Note that in the low pass filter 600, in some cases, the inductor L2 is referred to as the first inductor, the inductors L4 and L6 are referred to as the second inductors, the capacitors C3 and C5 are referred to as the first capacitors, and the capacitor Ca1 is referred to as the second capacitor.

(116) In the low pass filter 600, favorable attenuation also occurs outside of the high frequency side of the pass band, and a spurious noise that would become an obstacle is less likely to occur in the stop band.

#### Seventh Preferred Embodiment

(117) FIG. 14 and FIG. 15 illustrate a low pass filter 700 according to the seventh preferred embodiment. Note that FIG. 14 is an equivalent circuit diagram of the low pass filter 700. FIG. 15 is an exploded perspective view of the low pass filter 700.

(118) In the low pass filter 700, a new element is added to the low pass filter 100 according to the first preferred embodiment. Specifically, as illustrated in FIG. 14, an additional inductor La1 is connected between the second stage capacitor C2 and the ground. Moreover, the capacitor C2 and the inductor La1 define a series resonator circuit.

(119) In the low pass filter 700, as illustrated in FIG. 15, the insulating layer 1a in the lowest side of the multilayer body 1 of the low pass filter 100 according to the first preferred embodiment is replaced by an insulating layer 71a whose configuration is different from the insulating layer 1a. Note that in the low pass filter 700, the configurations of the other insulating layers 1b to 1i that are

arranged on the insulating layer **71a** are not modified.

(120) The configuration of the insulating layer **71a** is described.

(121) The first input/output terminal **T1**, the second input/output terminal **T2**, and the ground terminal **TG** are provided on the lower side principal surface of the insulating layer **71a**.

(122) The via conductors **2a** and **2b** and via conductors **72m**, **72n**, and **72o** penetrate through both upper and lower side principal surfaces of the insulating layer **71a**.

(123) A ground electrode **73** is provided on the upper side principal surface of the insulating layer **71a**. The ground electrode **73** is connected to the ground terminal **TG** by the via conductors **72m**, **72n**, and **72o**.

(124) A capacitor electrode **74f** is provided on the upper side principal surface of the insulating layer **71a**.

(125) A line conductor **75f** is provided on the upper side principal surface of the insulating layer **71a**. The line conductor **75f** connects the capacitor electrode **74f** and the ground electrode **73**.

(126) As described above, the rest of the configuration of the low pass filter **700** is the same as that of the low pass filter **100** according to the first preferred embodiment.

(127) In the low pass filter **700**, the second stage capacitor **C2** includes the capacitance between the capacitor electrode **4a** and the capacitor electrode **74f**. The additional inductor **La1** includes the line conductor **75f**. The third stage capacitor **C3** includes the capacitance between the capacitor electrode **4b** and the ground electrode **73**.

(128) As described above, the equivalent circuit of the low pass filter **700** illustrated in FIG. **14** is configured by using the structure of the low pass filter **700** illustrated in FIG. **15**.

(129) Note that in the low pass filter **700**, in some cases, the inductor **L1** is referred to as the first inductor, the inductors **L3** and **L5** are referred to as the second inductors, the capacitors **C2** and **C4** are referred to as the first capacitors, the capacitor **Ca1** is referred to as the second capacitor, and the inductor **La1** is referred to as the fourth inductor.

(130) FIG. **16** illustrates the  $S(1,1)$  characteristic and the  $S(2,1)$  characteristic of the low pass filter **700**. Further, for the purpose of comparison, FIG. **16** illustrates the  $S(1,1)$  characteristic and the  $S(2,1)$  characteristic of the low pass filter **100**.

(131) As can be seen from the  $S(2,1)$  characteristic, in the low pass filter **700**, two poles **P1** and **P2** occur outside the high frequency side of the pass band. Because of the poles **P1** and **P2**, the low pass filter **700** obtains favorable attenuation outside the high frequency side of the pass band, and the frequency characteristic of the low pass filter **700** is improved. On the other hand, in the low pass filter **100**, only one pole **P1** occurs outside the high frequency side of the pass band. It is considered that in the low pass filter **700**, the pole **P2** occurs because the additional inductor **La1** is connected between the second stage capacitor **C2** and the ground, and that the capacitor **C2** and the inductor **La1** define the series resonator circuit.

(132) Further, in the low pass filter **700**, no new spurious noise occurs in the stop band, and favorable attenuation characteristic is maintained.

(133) Experiment 2

(134) In the low pass filter **700**, the number of poles and the position at which each pole occurs are adjusted by adjusting the inductance value of the additional inductor **La1**. In order to clarify this, the following experiment 2 is performed.

(135) A circuit **F** illustrated in FIG. **17A** is fabricated in three ways by varying the inductance value of the additional inductor **La1**. Specifically, the inductance value of the inductor **La1** is set in three ways, which are a small value, a medium value, and a large value.

(136) FIG. **17B** illustrates the  $S(2,1)$  characteristics of the respective inductors **La1**. As can be seen from FIG. **17B**, the number of poles and the position at which each pole occurs vary according to the magnitude of the inductance value of the inductor **La1** of the circuit **F**. In the low pass filter **700**, the number of poles and the position at which each pole occurs are also adjusted by adjusting the inductance value of the additional inductor **La1**.

(137) Experiment 3

(138) In the low pass filter **700**, the additional inductor **La1** is connected between the second stage capacitor **C2** and the ground. Instead of this, even in the case where the additional inductor **La1** is connected between the fourth stage capacitor **C4** and the ground, a new pole similarly occurs outside the high frequency side of the pass band. In order to clarify this, the following experiment 3 is performed.

(139) Four circuits G to J illustrated in FIG. **18** are fabricated. In the circuit G, no additional inductor **La** is connected. In the circuit H, the additional inductor **La1** is connected between the fourth stage capacitor **C4** and the ground. In the circuit I, the additional inductor **La1** is connected between the second stage capacitor **C2** and the ground. In the circuit J, the additional inductor **La1** is connected between the second stage capacitor **C2** and the ground, and an additional inductor **La2** is connected between the fourth stage capacitor **C4** and the ground.

(140) FIG. **19** illustrates the S(1,1) characteristics and the S(2,1) characteristics of the respective circuits G to J. In the circuit G, one pole occurs outside the high frequency side of the pass band. In the circuits H and I, two poles occur outside the high frequency side of the pass band. In the circuit J, two poles occur outside the high frequency side of the pass band, but the amount of attenuation in the stop band becomes smaller as a whole.

(141) As described above, it is confirmed that in the low pass filter **700**, a plurality of poles occurs outside the high frequency side of the pass band and the frequency characteristic is improved, even in the case where the additional inductor **La1** is connected between the fourth stage capacitor **C4** and the ground, instead of connecting the additional inductor **La1** between the second stage capacitor **C2** and the ground.

(142) In the low pass filter **700** according to the seventh preferred embodiment, a plurality of poles occurs outside the high frequency side of the pass band, a favorable amount of attenuation is obtained, and the frequency characteristic is improved.

#### Eighth Preferred Embodiment

(143) FIG. **20** illustrates a low pass filter **800** according to the eighth preferred embodiment. Note that FIG. **20** is an exploded perspective view of the low pass filter **800**.

(144) The low pass filter **800** has the same equivalent circuit as the low pass filter **300** according to the third preferred embodiment illustrated in FIG. **3**.

(145) In the low pass filter **800**, when a multilayer-type low pass filter is being configured, a portion of the configuration of the low pass filter **300** according to the third preferred embodiment illustrated in FIG. **10** is modified.

(146) Specifically, in the low pass filter **300** illustrated in FIG. **10**, the multilayer body **1** is formed by stacking the insulating layers **1a** to **1i** in this order. In the low pass filter **800**, the insulating layer **1g** is removed from the insulating layers **1a** to **1i** of the low pass filter **300**, and an insulating layer **81g** is added in between the insulating layer **1b** and the insulating layer **1c** instead.

(147) The via conductors **2a**, **2b**, **2i**, and **2j** penetrate through both upper and lower side principal surfaces of the insulating layer **81g**.

(148) A line conductor **85c** is provided on the upper side principal surface of the insulating layer **81g**.

(149) Further, in the low pass filter **300** illustrated in FIG. **10**, the via conductors **2k** and **2l** penetrate through both the upper and lower side principal surfaces of the insulating layer **1h**. In contrast, in the low pass filter **800**, the via conductors **2k** and **2l** of the low pass filter **300** are removed, and the via conductors **82k** and **82l** penetrate through both the upper and lower side principal surfaces of the insulating layers **1c** to **1h** instead.

(150) In the low pass filter **800**, one end portion of the line conductor **85c** is connected to the line conductor **5d** by the via conductor **82k**. The other end portion of the line conductor **85c** is connected to the line conductor **5e** by the via conductor **82l**.

(151) The rest of the configuration of the low pass filter **800** is the same as that of the low pass

filter **300**.

(152) As described above, the low pass filter **800** has the same equivalent circuit as the low pass filter **300** illustrated in FIG. 3. In the low pass filter **800**, the first segmented inductor **L3a** mostly includes the line conductor **5d**. The second segmented inductor **L3b** mostly includes the line conductor **85c**. The third segmented inductor **L3c** mostly includes the line conductor **5e**.

(153) One of the unique features of the low pass filter **800** is that the distance between the line conductor **85c** included in the second segmented inductor **L3b** and the line conductor **5d** included in the first segmented inductor **L3a** and the distance between the line conductor **85c** included in the second segmented inductor **L3b** and the line conductor **5e** included in the third segmented inductor **L3c** are long. In the low pass filter **800**, five insulating layers **1c**, **1d**, **1e**, **1f**, and **1h** are provided between the line conductors **5d** and **5e** and the line conductor **85c**.

(154) In the low pass filter **800**, the distance between the line conductor **85c** included in the second segmented inductor **L3b** and the line conductor **5d** included in the first segmented inductor **L3a** and the distance between the line conductor **85c** included in the second segmented inductor **L3b** and the line conductor **5e** included in the third segmented inductor **L3c** are long. As a result, the inductance value of the second segmented inductor **L3b** becomes larger, and the coupling between the first segmented inductor **L3a** and the third segmented inductor **L3c** becomes stronger. That is to say, in the low pass filter **800**, because of the long distances between the line conductors **5d** and **5e** and the line conductor **85c**, the via conductor **82k** and the via conductor **82l** become longer, and the inductance values become larger. Moreover, the weakening of the coupling between the line conductor **5d** and the line conductor **5e** caused by the magnetic flux generated by the line conductor **85c** is reduced or prevented, and the coupling between the first segmented inductor **L3a** and the third segmented inductor **L3c** becomes stronger.

(155) FIG. 21 illustrates the S(1,1) characteristic and the S(2,1) characteristic of the low pass filter **800**. In the low pass filter **800**, a plurality of poles occurs outside the high frequency side of the pass band, and a large amount of attenuation is obtained outside the high frequency side of the pass band. It is considered that this improvement of the characteristics is an effect obtained by having a long distance between the line conductor **85c** included in the second segmented inductor **L3b** and the line conductor **5d** included in the first segmented inductor **L3a** and a long distance between the line conductor **85c** included in the second segmented inductor **L3b** and the line conductor **5e** included in the third segmented inductor **L3c**, having a large inductance value of the second segmented inductor **L3b**, and having strong coupling between the first segmented inductor **L3a** and the third segmented inductor **L3c**.

(156) Thus far the low pass filters **100**, **200A**, **200B**, **200C**, **300**, **400**, **500**, **600**, **700**, and **800** according to the first preferred embodiment to the eighth preferred embodiment have been described. However, the present invention is not limited to the contents described above, and that various modifications may be made within the scope of the present invention.

(157) For example, in the low pass filter **100** and the like, the inductor **L3** is divided into three, which are the segmented inductors **L3a** to **L3c**. However, the number of segmented inductors having been divided is an arbitrary number. For example, the inductor **L3** may be divided into five segmented inductors. Moreover, of the segmented inductors having been divided, any segmented inductors may be coupled with each other.

(158) A low pass filter according to a preferred embodiment of the present invention application is as described in the section of "Solution to Problem".

(159) In this low pass filter, it is preferable that a third inductor is connected between the second input/output terminal and one of the second inductors that is connected closest to the second input/output terminal, a third capacitor is connected between the ground and a connecting point of the third inductor and the second inductor connected closest to the second input/output terminal, a fourth capacitor is connected in parallel to the third inductor, and the third inductor and the fourth capacitor define a second LC parallel resonator. In this case, favorable attenuation also occurs

outside the high frequency side of the pass band.

(160) It is also preferable that a fourth inductor is connected between at least one of the second capacitors and the ground and the second capacitor and the fourth inductor define a LC series resonator. In this case, a plurality of poles occurs outside the high frequency side of the pass band, a favorable amount of attenuation is obtained, and the frequency characteristic is improved.

(161) It is also preferable that the low pass filter is a T-type low pass filter.

(162) It is also preferable that a total number of the first inductor, the second inductor, the third inductor, the first capacitor, and the third capacitor is five or more. In this case, basic frequency characteristics of the low pass filter can be made favorable.

(163) It is preferable that at least one of the second inductors is divided into a plurality of segmented inductors. In this case, at least two of the segmented inductors are coupled with each other, and by using the degree of this coupling, the frequency of a spurious noise that occurs in the stop band and the amount of attenuation thereof can be easily controlled (adjusted).

(164) It is also preferable that an inductor length of the second inductor that is divided into the plurality of segmented inductors is longer than an inductor length of another inductor connected in the signal line. In this case, it becomes possible to extend the inductor length of the segmented inductor, and this makes the segmentation easier.

(165) It is also preferable that, of the plurality of the segmented inductors, at least two segmented inductors are coupled with one another. In this case, according to the degree of this coupling, the frequency of a spurious noise that occurs in the stop band and the amount of attenuation thereof can be easily controlled (adjusted).

(166) It is also preferable that the plurality of the segmented inductors includes three segmented inductors, which are a first segmented inductor, a second segmented inductor, and a third segmented inductor connected in sequence, and the first segmented inductor and the third segmented inductor are coupled with one another. In this case, the adjustment of the degree of coupling between the first segmented inductor and the third segmented inductor becomes easier.

(167) It is also preferable that the low pass filter described above is configured as a multilayer-type low pass filter including a multilayer body in which a plurality of insulating layers are stacked on top of one another, a ground electrode provided between layers of the plurality of insulating layers, line conductors each provided between layers of the plurality of insulating layers, and capacitor electrodes provided between layers of the plurality of insulating layers. The capacitor includes a capacitance between a pair of the capacitor electrodes or including a capacitance between the capacitor electrode and the ground electrode, each of the inductor and the segmented inductor mostly includes the line conductor, and at least two of the segmented inductors, which are coupled with one another, include the respective corresponding line conductors that are provided between a same pair of layers of the plurality of insulating layers.

(168) In this case, it is also preferable that the line conductors included in the at least two of the segmented inductors, which are coupled with one another, are each provided at a position farther away from the ground electrode than the line conductor included in another segmented inductor in a stacking direction of the insulating layers. In this case, the adjustment of the degree of coupling between the segmented inductors having been divided becomes easier.

(169) It is also preferable that at least two insulating layers are provided in between the line conductors included in the at least two of the segmented inductors, which are coupled with one another, and the line conductor included in another segmented inductor. In this case, the coupling between these segmented inductors becomes stronger, and the amount of attenuation outside the high frequency side of the pass band can be improved. Further, between the foregoing at least two insulating layers, the line conductor included in the inductor that is not the segmented inductor or the capacitor electrode is provided.

(170) It is also preferable to adjust a filter characteristic of the multilayer-type low pass filter described above by adjusting a strength of a coupling between at least two of the segmented

inductors, which are coupled with one another, using a magnitude of distance between at least two of the line conductors that are provided between a same pair of layers of the plurality of insulating layers and define the at least two of the segmented inductors. In this case, the occurrence of a spurious noise that would become an obstacle in the stop band can be easily reduced or prevented. (171) While preferred embodiments of the present invention have been described above, it is to be understood that variations and modifications will be apparent to those skilled in the art without departing from the scope and spirit of the present invention. The scope of the present invention, therefore, is to be determined solely by the following claims.

## Claims

1. A low pass filter comprising: a first input/output terminal; a second input/output terminal; a signal line connected between the first input/output terminal and the second input/output terminal; a first inductor connected closest to the first input/output terminal in the signal line; at least one second inductor connected closer to the second input/output terminal than the first inductor in the signal line; and a first capacitor connected between ground and a connecting point of the first inductor and the at least one second inductor, or connected between the ground and the connecting point of the first inductor and the at least one second inductor and between the ground and, when the at least one second inductor includes at least two second inductors adjacent to one another, a connecting point of the at least two second inductor; wherein a second capacitor is connected in parallel to the first inductor, and the first inductor and the second capacitor define a first LC parallel resonator; and no capacitor is connected in parallel to the at least one second inductor.
2. The low pass filter according to claim 1, wherein a third inductor is connected between the second input/output terminal and one of the at least one second inductors that is connected closest to the second input/output terminal; a third capacitor is connected between the ground and a connecting point of the third inductor and the at least one second inductor connected closest to the second input/output terminal; and a fourth capacitor is connected in parallel to the third inductor, and the third inductor and the fourth capacitor define a second LC parallel resonator.
3. The low pass filter according to claim 1, wherein a fourth inductor is connected between the first capacitors and the ground; and the first capacitor and the fourth inductor define an LC series resonator.
4. The low pass filter according to claim 1, wherein the low pass filter is a T-type low pass filter.
5. The low pass filter according to claim 1, wherein a total number of the first inductor, the at least one second inductor, the third inductor, the first capacitor, and the third capacitor is five or more.
6. The low pass filter according to claim 1, wherein at least one of the at least one second inductors is divided into a plurality of segmented inductors.
7. The low pass filter according to claim 6, wherein an inductor length of the at least one of the at least one second inductor that is divided into the plurality of the segmented inductors is longer than an inductor length of another inductor connected in the signal line.
8. The low pass filter according to claim 6, wherein of the plurality of the segmented inductors, at least two segmented inductors are coupled with one another.
9. The low pass filter according to claim 8, wherein the plurality of the segmented inductors include a first segmented inductor, a second segmented inductor, and a third segmented inductor connected in sequence; and the first segmented inductor and the third segmented inductor are coupled with one another.
10. A multilayer-type low pass filter included in the low pass filter according to claim 8, the multilayer-type low pass filter comprising: a multilayer body in which a plurality of insulating layers are stacked on top of one another; a ground electrode between layers of the plurality of insulating layers; line conductors each between layers of the plurality of insulating layers; and capacitor electrodes each between layers of the plurality of insulating layers; wherein each of the



first capacitor and the second capacitor includes a capacitance between a pair of the capacitor electrodes or a capacitance between the capacitor electrode and the ground electrode; each of the first inductor, the at least one second inductor, and the plurality of segmented inductors is mostly defined by a line conductor; and at least two of the plurality of segmented inductors, which are coupled with one another, include the respective corresponding line conductors between a same pair of layers of the plurality of insulating layers.

11. The multilayer-type low pass filter according to claim 10, wherein the line conductors included in the at least two of the plurality of segmented inductors, which are coupled with one another, are each farther away from the ground electrode than the line conductor included in another segmented inductor of the plurality of segmented inductors in a stacking direction of the insulating layers.

12. The multilayer-type low pass filter according to claim 10, wherein at least two insulating layers are in between the line conductors included in the at least two of the plurality of segmented inductors, which are coupled with one another, and the line conductor included in another segmented inductor of the plurality of segmented inductors.

13. The multilayer-type low pass filter according to claim 12, wherein at least one of the capacitor electrodes and the line conductor included in the at least one second inductor that is not the plurality of segmented inductors is provided between the layers of the plurality of insulating layers, which are between the line conductors included in the at least two of the plurality of segmented inductors, which are coupled with one another, and the line conductor included in another segmented inductor of the plurality of segmented inductors.

14. A method of adjusting a filter characteristic comprising: adjusting a filter characteristic of a multilayer-type low pass filter; wherein the multilayer-type low pass filter is included in a low pass filter; the low pass filter includes: a first input/output terminal; a second input/output terminal; a signal line connected between the first input/output terminal and the second input/output terminal; a first inductor connected closest to the first input/output terminal in the signal line; at least one second inductor connected closer to the second input/output terminal than the first inductor in the signal line; and a first capacitor connected between ground and a connecting point of the first inductor and the at least one second inductor, or connected between the ground and the connecting point of the first inductor and the at least one second inductor and between the ground and, when the at least one second inductor includes at least two second inductors adjacent to one another, a connecting point of the at least two second inductors; wherein a second capacitor is connected in parallel to the first inductor, and the first inductor and the second capacitor define a first LC parallel resonator; no capacitor is connected in parallel to the at least one second inductor; at least one of the at least one second inductor is divided into a plurality of segmented inductors; and of the plurality of the segmented inductors, at least two segmented inductors are coupled with one another; the multilayer-type low pass filter includes: a multilayer body in which a plurality of insulating layers are stacked on top of one another; a ground electrode between layers of the plurality of insulating layers; line conductors each between layers of the plurality of insulating layers; and capacitor electrodes each between layers of the plurality of insulating layers; wherein each of the first capacitor and the second capacitor includes a capacitance between a pair of the capacitor electrodes or a capacitance between the capacitor electrode and the ground electrode; each of the first inductor, the at least one second inductor, and the plurality of segmented inductors is mostly defined by a line conductor; and at least two of the plurality of segmented inductors, which are coupled with one another, include the respective corresponding line conductors between a same pair of layers of the plurality of insulating layers; and the filter characteristic of the multilayer-type low pass filter is adjusted by adjusting a strength of coupling between the at least two of the segmented inductors, which are coupled with one another, using a magnitude of a distance between at least two of the respective corresponding line conductors that are provided between the same pair of layers of the plurality of insulating layers and are included in the at least two of the segmented inductors.

15. The method according to claim 14, wherein the line conductors included in the at least two of the segmented inductors, which are coupled with one another, are each farther away from the ground electrode than the line conductor included in another segmented inductor of the plurality of segmented inductors in a stacking direction of the insulating layers.
16. The method according to claim 14, wherein at least two of the plurality of insulating layers are in between the line conductors included in the at least two of the segmented inductors, which are coupled with one another, and the line conductor included in another segmented inductor of the plurality of segmented inductors.
17. The method according to claim 16, wherein at least one of the capacitor electrodes and the line conductor included in the at least one second inductor that is not the plurality of segmented inductors is provided between the layers of the plurality of insulating layers, which are between the line conductors included in the at least two of the plurality of segmented inductors, which are coupled with one another, and the line conductor included in another segmented inductor of the plurality of segmented inductors.
-