

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250264194

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Shiner; Zachary C. et al.

LIGHTING FIXTURE SYSTEMS

Abstract

A lighting apparatus that includes a housing having first and second sidewalls, a top housing wall disposed between the first and second sidewalls, and an open end disposed between the sidewalls and opposite the top housing wall. The housing includes a housing interior enclosed by the sidewalls and the top housing wall. The apparatus includes a lighting lens housing having a first and second lens sidewalls and a lens panel disposed between the lens sidewalls, where the lighting lens housing has a lens interior. The lens sidewalls block transmission of light. The lighting lens housing is removably secured within the housing interior, wherein, upon removably securing the lighting lens housing within the housing interior, at least one of the first and second lens sidewalls is positioned at an offset and adjacent the open end of the housing.

Inventors: Shiner; Zachary C. (Madison, WI), Bilton; Timne (Arcadia, CA), Nankil; Robert (Fullerton, CA), Liu; Yang (Irvine, CA), Zepeda; Adam (Anaheim, CA)

Applicant: Leviton Manufacturing Co., Inc. (Melville, NY)

Family ID: 1000008576905

Assignee: Leviton Manufacturing Co., Inc. (Melville, NY)

Appl. No.: 19/198561

Filed: May 05, 2025

Related U.S. Application Data

parent US continuation 18527840 20231204 parent-grant-document US 12320492 child US 19198561

Publication Classification

Int. Cl.: F21S8/02 (20060101); **F21S2/00** (20160101); **F21V17/06** (20060101); **F21Y115/10** (20160101)

U.S. Cl.:

CPC F21S8/026 (20130101); **F21S2/005** (20130101); **F21V17/06** (20130101); **F21Y2115/10** (20160801)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of pending U.S. patent application Ser. No. 18/527,840, filed Dec. 4, 2023, entitled “Lighting Fixture Systems”, which is hereby incorporated by reference into the present application in its entirety.

TECHNICAL FIELD

[0002] The present disclosure is generally directed to electrical systems, and in particular to linear lighting fixture systems.

BACKGROUND

[0003] Lighting fixtures provide illumination to various spaces, e.g., rooms in houses, office spaces in buildings, large commercial warehouses, and other spaces. Typically, such lighting fixtures are suspended from a ceiling or attached to a wall and are connected to sources of electricity. Such connections may be direct and/or through one or more switches allowing users to control when lighting fixtures are on or off. Some existing lighting fixtures, especially, those for use in large spaces (e.g., offices, warehouses, etc.) are typically assembled in a pattern, e.g., linearly. Such assembly may require forming connections between different lighting fixtures. The connections are typically not optically tight, allowing unwanted light to escape from joints formed between lighting fixtures. Moreover, existing lighting fixture systems are difficult to service, oftentimes requiring access to electrical components that are far away from the actual lighting fixtures, creating difficulties in locating and resolving issues.

SUMMARY

[0004] This summary is provided to introduce a selection of concepts in a simplified form that are further described below in the detailed description. This summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended as an aid in determining the scope of the claimed subject matter.

[0005] In some implementations, the current subject matter relates to a lighting apparatus. The apparatus may include a housing having a first housing sidewall and a second housing sidewall. Each of the first and second housing sidewalls may have a first end and a second end. The apparatus may also include a lighting lens housing having a first lens sidewall, a second lens sidewall, and a lens panel having a first end and a second end, wherein the lens panel is disposed between the first and second lens sidewalls. At least one of the first and second lens sidewalls may be configured to block transmission of light. The lighting lens housing may be configured to be attached to the housing. Upon attaching the lighting lens housing to the housing, the first end of the lens panel may be offset from the first end of the first housing sidewall and the first end of the second housing sidewall.

[0006] In some implementations, the current subject matter may include one or more of the following optional features. At least one of the first and second lens sidewalls may be offset from the first end of the first housing sidewall and the first end of the second housing sidewall.

[0007] In some implementations, the second end of the lens panel may be offset from the second

end of the first housing sidewall and the second end of the second housing sidewall. The first end of the lens panel may be configured to extend beyond the first ends of the first and second housing sidewalls. The second ends of the first and second housing sidewalls may be configured to extend beyond the second end of the lens panel. Alternatively, or in addition, the first end of the lens panel may be configured to extend beyond the first ends of the first and second housing sidewalls. The second end of the lens panel may be configured to extend beyond the second ends of the first and second housing sidewalls. In some implementations, the first ends of the first and second housing sidewalls may be configured to extend beyond the first end of the lens panel. The second ends of the first and second housing sidewalls are configured to extend beyond the second end of the lens panel.

[0008] In some implementations, the current subject matter relates to a lighting system. The lighting system may include a first lighting apparatus and a second lighting apparatus. Each of the first and second lighting fixtures may have a housing having a first housing sidewall and a second housing sidewall. Each of the first and second housing sidewalls may have a first end and a second end, and a lighting lens housing having a first lens sidewall, a second lens sidewall, and a lens panel having a first end and a second end, where the lens panel may be disposed between the first and second lens sidewalls, and where at least one of the first and second lens sidewalls may be configured to block transmission of light. The lighting lens housing may be configured to be attached to the housing. Upon attaching the lighting lens housing to the housing, the first end of the lens panel may be offset from the first end of the first housing sidewall and the first end of the second housing sidewall. Upon connection of the first lighting apparatus and the second lighting apparatus, the first ends of the first and second housing sidewalls of the housing of the first lighting apparatus may form a first joint with the second ends of the first and second housing sidewalls of the housing of the second lighting apparatus. The first end of the lens panel of the lighting lens of the first lighting apparatus may form a second joint with the second end of the lens panel of the lighting lens of the second lighting apparatus. The first joint may be offset from the second joint.

[0009] In some implementations, the current subject matter relates to a lighting apparatus. The lighting apparatus may include a housing having a first housing sidewall, a second housing sidewall, a top housing wall disposed between the first and second housing sidewalls, and an open end disposed between the first and second housing sidewalls and opposite the top housing wall. The housing may have a housing interior enclosed by the first and second housing sidewalls and the top housing wall. The apparatus may include a lighting lens housing having a first lens sidewall, a second lens sidewall, a lens panel disposed between the first and second lens sidewalls. The lighting lens housing may have a lens interior. The first and second lens sidewalls may block transmission of light. The lighting lens housing may be configured to be removably secured to the housing interior, where, upon removably securing the lighting lens housing to the housing interior, at least one of the first and second lens sidewalls may be configured to be positioned at an offset with respect to the open end of the housing.

[0010] In some implementations, the current subject matter may include one or more of the following optional features. In some implementations, a first end of the first lens sidewall may extend beyond a first end of the first housing sidewall, and a first end of the second lens sidewall may extend beyond a first end of the second housing sidewall. A second end of the first housing sidewall may extend beyond a second end of the first lens sidewall, and a second end of the second housing sidewall may extend beyond a second end of the second lens sidewall.

[0011] In some implementations, at least a portion of the first lens sidewall and at least a portion of the second lens sidewall may be non-transparent to light.

[0012] In some implementations, the apparatus may include a locking mechanism disposed in the top housing wall for securing the housing to another housing. The locking mechanism may include a protruding locking tab configured to interlock with a locking recess of another locking mechanism of the other housing upon the housing being coupled to the other housing.

[0013] In some implementations, the locking mechanism may include a locking screw configured to secure the protruding locking tab to the top housing wall.

[0014] In some implementations, the lighting lens housing may be configured to snap fit into the housing.

[0015] In some implementations, the lens panel may be at least partially transparent to light.

[0016] In some implementations, the apparatus may include a liner configured to be positioned within the lighting lens housing, and one or more lighting electrical components detachably secured to the liner. One or more lighting electrical components may generate light for transmission through the lighting lens at a predetermined angle. The predetermined angle may be determined based on an angular position of the liner within the lighting lens housing. The housing may be coupled to one or more connectors configured to suspend the housing from a ceiling. One or more lighting electrical components may be electrically coupled to a source of electrical power via the one or more connectors. The source of electrical power may be positioned at the ceiling. One or more connectors may be configured to protrude through an opening in the ceiling. The opening may be configured to be covered using a removable canopy. One or more connectors may protrude into the opening in the ceiling through the removable canopy at an offset with respect to at least one of: a center of the removable canopy and a center of the opening in the ceiling.

[0017] In some implementations, at least a portion of the first lens sidewall may be inclined at a first angle with respect to the lighting lens panel and at least a portion of the second lens sidewall may be inclined at a second angle with respect to the lighting lens panel. The first and second angles may be substantially equal.

[0018] In some implementations, the liner may be removably secured to the first lens sidewall and to the second lens sidewall.

[0019] In some implementations, the liner may be snap-fit removably secured to the first lens sidewall and to the second lens sidewall.

[0020] Further features and advantages of at least some of the exemplary embodiments of the current subject matter, as well as the structure and operation of various exemplary embodiments of the current subject matter, are described in detail below with reference to the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0021] The accompanying drawings, which are incorporated in and constitute a part of this specification, show certain aspects of the subject matter disclosed herein and, together with the description, help explain some of the principles associated with the disclosed implementations. In the drawings,

[0022] FIG. 1 illustrates an example lighting fixture system, according to some implementations of the current subject matter;

[0023] FIG. 2 illustrates an example lighting fixture system, according to some implementations of the current subject matter;

[0024] FIGS. 3*a-g* illustrate further details of the locking mechanism shown in FIG. 2, according to some implementations of the current subject matter;

[0025] FIGS. 4*a-b* are cross-sectional views of the lighting fixture housing, according to some implementations of the current subject matter;

[0026] FIGS. 5*a-f* illustrate an example assembly and/or installation process for positioning of a lighting lens housing within the lighting fixture housing, according to some implementations of the current subject matter;

[0027] FIG. 6 illustrates an example connection of housings with the use of interior and exterior

offsets, according to some implementations of the current subject matter;

[0028] FIGS. 7*a-e* illustrate various example implementations of the structural support elements for a liner and resulting corresponding light disseminations, according to some implementations of the current subject matter;

[0029] FIGS. 8*a-b* illustrate portions of an example lighting lens housing that may include such refractive features, according to some implementations of the current subject matter; and

[0030] FIGS. 9*a-9b* illustrates a lighting fixture system, according to some implementations of the current subject matter.

[0031] It should be understood that the drawings are not necessarily to scale and that the disclosed examples are sometimes illustrated diagrammatically and/or in partial views. In certain instances, details that are not necessary for an understanding of the disclosed methods and devices or which render other details difficult to perceive may have been omitted. It should be further understood that this disclosure is not limited to the particular examples illustrated herein. In the drawings, like numbers refer to like elements throughout unless otherwise noted.

DETAILED DESCRIPTION

[0032] To address these and potentially other deficiencies of currently available solutions, one or more implementations of the current subject matter relate to methods, systems, articles of manufacture, and the like that can, among other possible advantages, provide linear lighting fixtures.

[0033] In some implementations, the current subject matter relates to a lighting fixture or apparatus, which may be suspended from a ceiling, attached to a wall, and/or secured to any other desired surface for the purposes of providing illumination to a space (e.g., room, office, etc.). The lighting fixture may include a housing that may have first and second housing sidewalls that may be joined at the top using a top housing wall positioned between and secured to the sidewalls, thereby forming a unitary structure. The housing may also include an open end that may be disposed between the sidewalls and opposite the top housing wall. The sidewalls and the top housing wall may enclose an interior, which may accommodate positioning of lighting lens, lighting electrical components, and/or various other components.

[0034] The housing may also include a locking mechanism, which may be disposed in the top housing wall. The locking mechanism may be used to secure the housing to another housing, which may include a counterpart locking mechanism. The locking mechanism may include a protruding locking tab that may be configured to interlock with a locking recess of another locking mechanism in a housing of another lighting fixture upon the housings of the lighting fixtures being coupled. Moreover, the locking mechanism may include a locking screw that may be configured to secure the protruding locking tab to the top housing wall. Additionally, a depth stop may be included in locking mechanism for the purposes of mating with a recess in a top housing wall of another lighting fixture upon coupling of two lighting fixtures together. Thus, to connect two lighting fixtures together, one lighting fixture's top wall may include a locking tab protruding away from one end of the top wall and another lighting fixture's top wall may include a locking recess configured to receive and interlock with the protruding locking tab. The depth stop may be configured to prevent movement of housings during coupling beyond certain points to thereby prevent any damage that may occur to the housings, the locking mechanism, and/or any other components.

[0035] The lighting fixture may also include a lighting lens housing having first and second lens sidewalls, a lens panel coupled to and positioned between the first and second lens sidewalls. The lighting lens housing may also have a lens interior. The lighting lens housing may be configured to snap fit within the housing. In some implementations, the lens panel may at least be partially transparent to light.

[0036] To providing lighting, one or more lighting electrical components may be detachably secured to a liner within the lighting lens housing. For example, the lighting electrical components

may include one or more light emitting diodes (LEDs). The lighting electrical components may generate light for transmission through the lighting lens at a predetermined angle. The angle may be determined based on an angular position of the liner within the lighting lens housing. For example, the light may be transmitted perpendicularly to the lighting lens and/or at an angle to the lighting lens. In some implementations, the liner may be removably secured to the first and second lens sidewalls. For example, the liner may be snap-fit removably secured to the first and second lens sidewalls.

[0037] In some implementations, the first and second lens sidewalls may be configured to block transmission of light. For example, the lens sidewalls may be manufactured from an opaque materials that blocks light.

[0038] Moreover, the lighting lens housing may be configured to be removably secured within the housing interior. In particular, upon removably securing the lighting lens housing within the housing interior, the lens panel along with the lens sidewalls may be configured to be positioned at an offset and adjacent the open end of the housing. The offset may be defined by respective portions of the lens sidewalls (along with the lens panel) extending beyond ends of the housing sidewalls. Alternatively, or in addition, the offset may be defined by respective portions of housing sidewalls extending beyond ends of the lens sidewalls (and the lens panel). Moreover, the portions of the lens sidewalls may be non-transparent to light.

[0039] In some implementations, at least a portion of the first lens sidewall may be inclined at a first angle with respect to the lighting lens panel. Also, at least a portion of the second lens sidewall may be inclined at a second angle with respect to the lighting lens panel. The first and second angles may be substantially equal. This may form a trapezoidal shape of the lighting lens housing that may provide a secure fit when positioning the lighting lens housing within the interior of the housing. To ensure that the lighting lens housing retains within the interior of the housing, the first lens sidewall may include a first locking feature and the second lens sidewall may include a second locking feature. The first and second locking features may be configured to removably secure the lighting lens housing within the housing upon insertion of the lighting lens housing into the interior of the housing.

[0040] In some implementations, the housing may be coupled to one or more connectors configured to suspend the housing from a ceiling (and/or any other structure). Further, the lighting electrical components may electrically be coupled to a source of electrical power via such connectors. For example, electrical wiring may be configured to extend either alongside the connectors and/or through an interior of the connectors, and/or in any other way. Moreover, the source of electrical power may be positioned at the ceiling. For example, the source of electrical power may include an LED driver, which may be electrically coupled to the LEDs.

[0041] FIG. 1 illustrates an example lighting fixture system **100**, according to some implementations of the current subject matter. While the system **100** is shown as a linear system, as can be understood, the system may be any other type of system and/or may have any desired shape (e.g., circular, square, rectangular, triangular, multi-dimensional, etc.). The system **100** may be positioned in any desired location for illumination of space (interior and/or exterior) at that location, such as, for example, but not limited to, a room, a warehouse, an office, and/or any other location. The system **100** may be configured for mounting to any horizontal surface (e.g., a ceiling), a vertical surface (e.g., a wall), a diagonal surface (e.g., a wall and/or a ceiling), and/or any other type of surface. The system **100** may include any desired types of light sources (e.g., halogen, incandescent, fluorescent, and/or any other type of light bulbs or elements, LED light bulbs or elements, CFL bulbs or elements, and/or any other types of light sources) for providing illumination to a space where the system **100** is mounted.

[0042] The system **100** may provide ease of installation, alignment, and connection with other lighting systems (e.g., other systems **100**). In particular, the system **100** may greatly reduce the level of skill and/or precision that may be required to connect lighting systems, simplify the

manner in which joining of such systems may be tightened, reduce an amount of undesired light emissions between joined systems **100**, enable custom-sizing of the system **100** during manufacture and/or installation (e.g., through custom-cutting of elements of system **100**), and provide an ease of access to its various electrical components for installation and servicing (e.g., through use of local power sources/LED drivers rather than remote ones).

[0043] Referring to back to FIG. **1**, the system **100** may include a lighting fixture housing **102** that may be configured to house a lighting lens housing **118**. The housing **102** may have a first sidewall **104a**, a second sidewall **104b**, a top wall **106**, and an open end **108**. The top wall **106** may be coupled to the first and second sidewalls **104** and being disposed opposite to the open end **108**. The sidewalls **104** and top wall **106** may enclose an interior **120** of the housing **102**.

[0044] The top wall **106** may be coupled to one or more brackets **114a** and **114b**. The brackets **114a** and **114b** may be coupled to one or more suspension cables, wires, or connectors (terms used interchangeably herewith) **112a** and **112b**, respectively. The connectors **112a** and **112b** may suspend the housing **102** from a horizontal or a diagonal surface, such as, for example, a ceiling. One or both of the connectors **112** may be configured for accommodating protrusion of electrical wiring extending from one or more power sources (e.g., an LED driver) that may be disposed in the ceiling (not shown in FIG. **1**). As shown in FIG. **1**, the connector **112b** may be coupled to an electrical wire housing **116**. The wire housing **116** may have a larger diameter than the diameter of the connector **112b**, so that the wire housing **116** may allow protrusion of electrical wiring into the lighting lens housing **118** as well as coupling to the bracket **114b**.

[0045] Alternatively, or in addition, the brackets **114a** and **114b** may be used for mounting the housing to a vertical and/or a diagonal surface, such as, for example, a wall. In this case, the electrical wiring may be protruded via a cable and/or directly from one or more power sources (e.g., an LED driver) that may be hidden behind the wall (not shown in FIG. **1**).

[0046] The interior **120** may accommodate insertion and/or positioning of the lighting lens housing **118**. Upon positioning of the lighting lens housing **118** in the interior **120**, the lighting lens or light engine (terms used interchangeably herein) **122** may be positioned adjacent the open end **108** of the housing **102**. In some example implementations, the lighting lens **122** may be flush with the edge **124a** of the sidewall **104a** and edge **124b** of the sidewall **104b**.

[0047] In some implementations, the lighting lens housing **118** may be removably secured within the interior **120** of the housing **102**. This may allow easy removal of the lighting lens housing **118** from the interior **120**, such as, for example, for servicing, repairs and/or replacement of parts, e.g., electrical parts of the lighting lens housing **118** (e.g., LEDs of the lighting component, electrical wires, etc.), mechanical parts (e.g., structural parts of the lighting lens housing **118**), optical (e.g., lens **122** of the lighting lens housing **118**), and/or any other parts. In some example, non-limiting implementations, the lighting lens housing **118** may be snap-fit within the interior **120** of the housing **102**. As can be understood, any other ways of removably securing the lighting lens housing **118** are possible. Alternatively, or in addition, the lighting lens housing **118** may be secured using one or more screws, bolts, rivets, and/or any other ways.

[0048] FIG. **2** illustrates an example lighting fixture system **200**, according to some implementations of the current subject matter. As shown in FIG. **2**, the lighting fixture system **200** may include two lighting fixture housings, i.e., lighting fixture housing **102** and a lighting fixture housing **202**. As can be understood, the lighting fixture system **200** may include any number of lighting fixture housings. For example, in an office building setting, several of the lighting fixture housings may be joined together to provide illumination to a large space (e.g., a conference room, an office space with multiple cubicles, etc.). The lighting fixture housings may be coupled together mechanically and/or electrically. For instance, the lighting fixture housing **102** may be electrically coupled to a source of electrical power and the lighting fixture housing **202** may be connect to one or more electrical contacts within the lighting fixture housing **102** for providing electrical power to its electrical components. As such, the lighting fixture housings **102** and **202** may be connected in

series to the source of electrical power.

[0049] As shown in FIG. 2, the lighting fixture housing **202** may be similar to the lighting fixture housing **102**. In particular, it may house a lighting lens housing **218**. The housing **202** may have a first sidewall **204a**, a second sidewall **204b**, a top wall **206**, and an open end **208**. The top wall **206** may be coupled to the sidewalls **204** and may be disposed opposite to the open end **208**. The sidewalls **204** and top wall **206** may enclose an interior of the housing **202**.

[0050] Further, the top wall **206** may be coupled to a bracket **214**. The bracket **214** may be coupled to a suspension cable, wire, or connector (terms used interchangeably herewith) **212**. Once the lighting fixture housing **202** is coupled to the lighting fixture housing **102**, the connectors **112a**, **112b**, and **212** may suspend the combined lighting fixture housing (formed from housings **102** and **202**) from a horizontal or a diagonal surface, such as, for example, a ceiling. The connector **112b** may be configured to accommodate protrusion of electrical wiring one or more power sources (e.g., an LED driver) that may be disposed in the ceiling (not shown in FIG. 2) so as to provide power to both lighting fixture housings **102** and **202**.

[0051] The lighting fixture housing **102** may include a first portion **220** of a locking mechanism **221** and the lighting fixture housing **202** may include a second portion **222** of the locking mechanism **221**. The locking mechanism **221** may be configured interlock the lighting fixture housings **102** and **202** together by interlocking the first and second portions **220** and **222**. In particular, the first portion **220** may be disposed on the top wall **116** of the lighting fixture housing **102**. The second portion **222** may be disposed on the top wall **216** of the lighting fixture housing **202**. The first portion **220** may be configured to receive the second portion **222** upon coupling of the first and second portions **220** and **222**. As can be understood, a lighting fixture housing may include a first portion of the locking mechanism disposed at one end of the lighting fixture housing and a second portion disposed at an opposite end of the housing. Alternatively, or in addition, the lighting fixture housing may include only the first portions or only the second portions of the locking mechanism disposed at both ends of the housing. Moreover, the lighting fixture housing may only include one of the first and second portions of the locking mechanism disposed at one end and no portions of the locking mechanism disposed at its other end (e.g., where the lighting fixture housing is the last housing in a line of housings).

[0052] FIGS. 3a-g illustrate further details of the locking mechanism **221** shown in FIG. 2. The locking mechanism **221** may be configured to have an engaged state and a disengaged state. In the engaged state, the second portion **222** may fully be inserted into the first portion **220**, as shown in FIG. 3f, thereby interlocking the portions **220** and **222** and hence, coupling the housings **102** and **202** together. In a disengaged state, as shown in FIG. 3a, the portions **220** and **222** may be separated.

[0053] As shown in FIGS. 3a-d, the first portion **220** may be formed in the top wall **106** of the housing **102**. In some implementations, the first portion **220** may include a bottom plate **302** and a top plate **304**. The top plate **304** and the bottom plate **302** may be spaced apart from one another, thereby forming a cavity **305** that may be sized to receive the second portion **222**. The top plate **304** may face outwardly and away from the interior **108** of the housing **102**. The bottom plate **302** may face inwardly into the interior **108** of the housing **102**. The top plate **106** may include one or more openings **306**, **308**. The openings **306**, **308** may interact with one or more tabs of the second portion **222** in the engaged state (as shown in FIG. 3f).

[0054] The second portion **222** may be slidably disposed between the bottom plate **312** and the top plate **314** of the top wall **206** of the housing **202** and may be configured to translate within the cavity **315** formed by the bottom plate **312** and top plate **314**. The top plate **314** may include one or more openings **318a** and **318b**. The openings **318** may interact with one or more tensioned tabs of the second portion **222**.

[0055] In some implementations, the second portion **222** may include a tongue **310** having a wide portion **311** and a narrow portion **313**, where the wide portion **311** may be disposed proximate to

the plates **312**, **314** and the narrow portion **313** may be disposed distal to the plates **312**, **314**. The narrow portion **313** may be configured for insertion into the cavity **305** formed by the plates **302** and **304** of the housing **102** for interlocking of the housings **102** and **202**.

[0056] The wide portion **311** may include a tensioned stop tab **316** and one or more tensioned retention tabs **320a**, **320b**. The tensioned retention tabs **320a**, **320b** may be directional retention tabs and may be configured to interact with the openings **318a**, **318b**, respectively, to prevent removal of the second portion **222** from the cavity **315** formed by the plates **312**, **314** in the second portion **222**. In particular, the retention tabs **320a**, **320b** may have an elevated position caused by tension in the tabs **320a**, **320b**, thereby preventing substantial removal of the second portion **222** from the cavity **315**, and a stored position caused by application of pressure or force to the tabs **320a**, **320b** causing the tabs to bend, thereby allowing the second portion **222** to translate within cavity **315**.

[0057] Upon pushing the second portion **222** into the cavity **315**, the top plate **314** may be configured to cause the retention tabs **320a**, **320b** to bend in a downward direction away from the top plate **314** and toward the bottom plate **312** (as a result of pushing force being applied to the second portion **222**), thereby having the tabs **320a**, **320b** assume the stored position. Upon pulling of the second portion **222** from the cavity **315** (e.g., for coupling with housing **102**), the retention tabs **320a**, **320b** may, under tension, return to the elevated position (as shown in FIG. **3b**) upon reaching the respective openings **318a**, **318b**. The area of the openings **318a**, **318b** may be larger than the area of the tabs **320a**, **320b** allowing the tabs to pop into the openings **318a**, **318b** in the elevated position. Once the tabs **320a**, **320b** are in the elevated position, further translation of the second portion **222** away from the cavity **315** may be prevented.

[0058] Moreover, the interaction of the tabs **320** and corresponding openings **318** may also serve as one of the alignment features that may assist in guiding and properly aligning of the housings **102** and **202** during their connection. Once the tabs **320** are positioned in the corresponding openings **318**, the second portion **222** may be oriented in a particular direction for connection with the first portion **220** of the locking mechanism **221**, thereby reducing rotational or other movement of the second portion **222**, which may cause an incorrect alignment of the housings **102** and **202**. As can be understood, while two tabs **320** and two corresponding openings **318** are shown, the current subject matter may include any number of tabs and/or openings.

[0059] The tensioned stop tab **316** may be disposed in the wide portion **311** of the second portion **222** and may be configured to interact with a recess portion **309** of the top plate **304** of the top wall **106** of the housing **102** during connection of the housings **102**, **202** (as shown in FIG. **3f**). The stop tab **316** may be configured to also prevent any further translational movement of the tongue **310** into the cavity **305** formed by the plates **302**, **304** of the top wall **106** of the housing **102**. The width of the stop tab **316** may be smaller than the width of the recess **309**, thereby allowing the recess **309** to accommodate positioning of the stop **316** during connection of the housings **102**, **202**.

[0060] The narrow portion **313** may include a tensioned retention tab **312**. The tensioned retention tab **312** may also be directional retention tab (similar to tabs **318**) and may be configured to interact with the openings **308** and **306** to prevent removal of the second portion **222** from the cavity **305** formed by the plates **302**, **304** in the first portion **220**. The retention tab **312** may have an elevated position caused by tension in the tab **312**, which may prevent removal of the second portion **222** from the cavity **305** once it is positioned in the cavity **305** and the opening **306** has engaged the retention tab **312**. It may also have a bent position caused by application of pressure or force to the tab **312** causing the tab to bend, thereby allowing the second portion **222** to translate within cavity **305** (e.g., outside of openings **306**, **308**).

[0061] Upon pushing the second portion **222** into the cavity **305**, the top plate **304** may be configured to cause the retention tab **312** to transition into the bent position by bending in a downward direction away from the top plate **304** and toward the bottom plate **302** (as a result of pushing force being applied to the second portion **222**). Upon further pushing the second portion

222 into the cavity 305, the retention tab 312 may be configured to be engaged by the opening 308 and assume its elevated position, as shown in FIG. 3b. Even further pushing of the second portion 222 into the cavity 305, the top plate 304, and in particular, its portion between openings 306 and 308, may again cause the retention tab 312 to briefly transition into the bent position, which may be followed by the elevated position of the retention tab 312 once it is engaged by the opening 306, as shown in FIGS. 3e-f. The area of the openings 306, 308 may be larger than the area of the tab 312 allowing the tab to pop into the opening 306 and then into the opening 308 in its elevated position. [0062] Upon being engaged by the opening 306, the retention tab 312 may prevent second portion 222 from being pulled away from the interior cavity 305 of the housing 102. This, along with tabs 320a, 320b may retain the housings 102 and 202 in a connected state, as shown in FIG. 3e. Retention of the housings 102 and 202 in the connected state may be afforded by the tab 312 preventing translation of the second portion 222 in one direction and tabs 320a, 320b preventing translation of the second portion 222 in an opposite direction. Further, the tabs 312 and 320 (a, b) by engaging in respective openings 308 and 318 (a, b) may assist in aligning the housings 102 and 202 in the same direction.

[0063] To remove the second portion 222 from the cavity 305 of the housing 102, the tab 312 may be pushed in a downward direction (i.e., toward the interior 108 of the housing 102), so that the opening 306 no longer engages the tab 312, and the housing 202, along with second portion 222, may be pulled away from the cavity 305. While pulling the housing 202, the tab 312 may be engaged by the opening 308 (as shown in FIG. 3b). To disengage the tab 312, from the opening 308, the tab 312 may again be pushed in the downward direction, so that the opening 308 no longer engages the tab 312. At this point, the housing 202 may be completely disengaged from the housing 102.

[0064] In some implementations, once the housings 102 and 202 are connected with tabs 312 and 320 (a, b) are engaged by their respective openings 306, 318 (a, b) and stop tab 316 is positioned in the recess 309, a screw 324 may be used to further secure the tongue 310, as shown in FIGS. 3f-g. In an engaged state of the screw 324, the screw 324 may protrude through an opening 325 of the top plate 314 of the top wall 206 of the housing 202 and into an opening 327 in the tongue 310. The opening 327 may be configured to be positioned between tab 316 and tabs 320 (a, b), as shown in FIG. 3g. Upon tightening (e.g., by rotating it in a clockwise direction) of the screw 324, the screw 324 may secure the tongue 310 and prevent its movement in any direction.

[0065] To release the tongue 310, the screw 324 may be loosened (e.g., by rotating it in a counterclockwise direction) until it is no longer engaged by the opening 327. Once released, the tab 312 may be pressed to release it from openings 306, 308, as described above, and the tongue 310 may be removed from the cavity 305. Alternatively, or in addition, the screw 324 may remain engaged by the opening 327, and instead of moving the tongue 310, the tab 312 may be pressed down and the housing 102 may be removed by translating it along the tongue 310 away from the housing 202. As can be understood, the screw 324 may be an optional securing feature in addition to the tabs 312, 316, and 320 (a, b).

[0066] In some implementations, use of the above connection features (e.g., tongue 310, tabs 312, 316, 320 (a, b), openings 306, 308, 312(a, b), screw 324, etc.) may allow for an easy changing/removal/servicing/replacement of lighting fixture housings. The connection features may be easily disengaged, thereby allowing one housing to be disengaged from another housing. Once the housing has been serviced/replaced, either the same housing or a new housing may be connected to the housing that is already in place using its connection features and the connection features of the existing housing. The arrangement and operation of connection features of the current subject matter's lighting fixtures may be beneficial in a variety of ways. For example, the current subject matter's connection features may reduce labor and failure modes during installation. In contrast, existing lighting fixtures typically require more precise alignment and may need to be joined tightly. This is inferior to the current subject matter's lighting fixtures having the above

connection features that greatly reduce the level of precision that is required to form an initial connection between lighting fixture housings and simplify tightening of fixtures once the initial connections is formed.

[0067] FIGS. **4a-b** are cross-sectional views of the lighting fixture housing **102**, according to some implementations of the current subject matter. As shown in FIGS. **4a-b**, the lighting fixture housing **102** may be configured to releasably secure the lighting lens housing **118**. The lighting lens housing **118** may include a first lens sidewall **402a**, a second lens sidewall **402b**, and the lighting lens **122** disposed between the first and second lens sidewalls **402a**, **402b**. Releasable securing of the lighting lens housing **118** within housing **102** may be accomplished by snap-fitting the lighting lens housing **118** in the interior of housing **102**. In some example implementations, the first and second lens sidewalls **402a**, **402b** may have portions that may be curved and/or have a bent structure that may substantially match curvature and/or bends of interior portions of housing sidewalls **104a**, **104b**, respectively, so as to snap-fit the lighting lens housing **118** into within the housing **102**. Upon the lighting lens housing **118** being positioned in the interior of the housing **102**, the sidewalls **402** (*a*, *b*) may be configured to be adjacent and/or be positioned against respective interior surfaces of the sidewalls **104** (*a*, *b*) (i.e., sidewall **402a** is adjacent/positioned against interior surface of sidewall **104a**; sidewall **402b** is adjacent/positioned against interior surface of sidewall **104b**). As can be understood, other ways of positioning and/or securing of the lighting lens housing **118** within the interior of the housing **102** are possible.

[0068] Upon positioning of the lighting lens housing **118** within the interior of the housing **102**, the lighting lens **122** may be configured to be positioned flush within the distal ends of **401a**, **401b** of the respective sidewalls **104a**, **104b**, as shown in FIGS. **4a-b**. As will be discussed in connection with FIG. **7e**, other ways of positioning of lighting lens housings are possible.

[0069] The lens sidewalls **402a**, **402b** of the lighting lens housing **118** may include liner support projections **407a**, **407b**, respectively. The projections **407a**, **407b** may protrude from interior surfaces of the sidewalls **402a**, **402b**, respectively, into the interior space of the lighting lens housing **118**. Each projection **407a**, **407b** may include respective tensioned forks **403a**, **403b**. The tensioned forks **403a**, **403b** may support a lighting liner **408** that may hold a lighting element (e.g., LED) **406**. The lighting liner **408** may include support arms **405a**, **405b** that may be integral with and extend outwardly from a lighting element support platform **409**. Distal ends of the support arms **405a**, **405b** may be releasably secured (such as, for example, but not limited to a snap-fit) within the respective tensioned forks **403a**, **403b** to suspend the liner **408** within the interior space of the lighting lens housing **118**, as shown in FIGS. **4a-b**.

[0070] In some implementations, the projections **407a**, **407b** may be disposed throughout the entire length of the lighting lens housing **118**. For example, each projection **407** may be as long as the lighting lens housing **118**. Alternatively, or in addition, multiple projections **407** may be distributed along the length of each respective lens sidewall of the lighting lens housing **118**. Similarly, the liner **408** may likewise be disposed throughout the entire length of the lighting lens housing **118** (e.g., the liner **408** may be as long as the length of the lighting lens housing **118**). Alternatively, or in addition, multiple liners **408** may be disposed throughout the length of the lighting lens housing and at locations corresponding to the locations of corresponding projections **407**. The lighting elements **406** may also be disposed throughout the entire length of the housing **118**, either as serially connected elements (e.g., on an adhesive tape that may be attached to the liner **408**) and/or as individual elements.

[0071] By suspending the liner **408** within the interior space of the lighting lens housing **118**, the lighting element **406** may likewise be suspended above the lighting lens **122** with the lighting element **406** projecting light (as generated by it) toward the lighting lens **122**. The lighting lens **122**, by virtue of its at least partial transparency to light, may diffuse the generated light posterior to the lighting lens housing **118** and into the exterior space (e.g., exterior to the housing **102**).

[0072] In some implementations, depending on a desired use of the lighting fixture system, the

liner **408** may be suspended in various ways within the lighting lens housing **118**. This may be accomplished through altering structure of elements that support the liner **408**. FIGS. **7a-7e** illustrate various example implementations of the structural support elements for the liner **408** and resulting corresponding light disseminations.

[0073] FIG. **7a** illustrates an arrangement of the liner **408** similar to the one shown in FIGS. **4a-b**. This arrangement may be referred to, for example, as a high efficiency arrangement that may project light generated by the lighting element **406** in substantially equally-distributed light volume from the lighting fixture. This is illustrated by distribution of light **702**.

[0074] FIG. **7b** illustrates an example lighting lens housing **708**, according to some implementations of the current subject matter. The lighting lens housing **708** may include support projections **707a** and **707b** that support the liner **408**. As shown in FIG. **7b**, the support projection **707a** may be longer than projection **707b** and thus, may extend further into the interior of the lighting lens housing **708** than the projection **707b**. This allows positioning of the liner **408** at an angle with respect to the lighting lens **122**. Such positioning may allow focusing distribution of light in an angular fashion (e.g., to illuminate a wall, a painting, etc.), as shown by the distribution of light **704**. In some example, non-limiting implementations, the lighting element(s) **406** may be fitted with one or more focusing lenses **709** (*a, b, c*), which may assist in focusing how the light generated by the lighting element(s) **406** is diffused through the lighting lens **122**.

[0075] FIG. **7c** illustrates an example lighting lens housing **718**, according to some implementations of the current subject matter. The lighting lens housing **718** may include support projections **717a** and **717b** for supporting the liner **408**. As shown in FIG. **7c**, the support projection **717a** may be shorter than projection **717b** allowing support projection **717b** to extend further into the interior of the lighting lens housing **718** than the projection **717a**. This allows positioning of the liner **408** closer to one of the lens sidewalls (e.g., sidewall **714a**) and further away the other sidewall (e.g., sidewall **714b**) rather than an angle with respect to the lighting lens **122** (as shown in FIG. **7b**). Such positioning of the liner **408** may allow focusing distribution of light in at a shaper angle (e.g., to illuminate a focused portion of a wall etc.), as shown by the distribution of light **706**. Similar to FIG. **7a**, the lighting element(s) **406** may also be fitted with one or more focusing lenses **719** (*a, b, c*), which may further focus light distribution.

[0076] FIG. **7d** illustrates an example lighting lens housing **728**, according to some implementations of the current subject matter. Similar to the lighting lens housing **708** shown in FIG. **7b**, the lighting lens housing **728** may include support projections **727a** and **727b** that support the liner **408**. However, as shown in FIG. **7d**, the support projection **727b** may be longer than projection **727a**, thereby extending further into the interior of the lighting lens housing **708**. This allows positioning of the liner **408** at an angle with respect to the lighting lens **122** and allowing for an asymmetric distribution of light through the lighting lens **122**, as shown by the distribution of light **708**. Again, in some example, non-limiting implementations, the lighting element(s) **406** may be fitted with one or more focusing lenses **729** (*a, b, c*) to further focus distribution of light.

[0077] FIG. **7e** illustrates an example lighting lens housing **738**, according to some implementations of the current subject matter. While the positioning of the liner **408** in the interior of the housing **738** may be similar to the positioning of the liner **408** shown in FIG. **7a** (e.g., using substantially equally protruding arms **737a, 737b**), the housing **738** may be fitted with a drop lighting lens **722** that may extend further away from the lighting fixture housing (not shown in FIG. **7e**) and provide a substantially full (e.g., 270-360 degrees) distribution of light, as shown by the distribution of light **710**. The drop lighting lens **722** may be coupled to the liner **408** using one or more fasteners (e.g., screws, rivets, etc.) **741a, 741b**.

[0078] In some implementations, to provide a more uniform distribution of light, the lighting lens may include one or more refractive features. FIGS. **8a-b** illustrate portions of an example lighting lens housing **818** (which may be similar to the lighting lens housing **118** shown in FIGS. **1-2b**) that may include such refractive features, according to some implementations of the current subject

matter. The lighting lens housing **818** may include lens sidewalls **802** (*a, b*) (only sidewall **802b** is shown for ease of illustration) and a lighting lens **822**. The lighting lens **822** may include one or more refractive features **824** (as shown in FIG. **8b**). The refractive features **824** may aid in more uniform diffusion of light produced by a lighting element or engine (not shown in FIGS. **8a-b**). They may also reduce glare and any unwanted reflections. As can be understood, the features **824** may be any other type of elements, e.g., polarization elements, light filtering elements, light blocking elements, light grating elements, etc. and/or any combination thereof. While FIGS. **8a-b** illustrate features **824** being uniformly spaced throughout an exterior surface of the lighting lens **822** in a wave-like fashion, the features **824** may be arranged in any desired way and may depend on a specific application of the lighting fixture and desired/preferred illumination.

[0079] Moreover, lighting lens housing **818** (as well as lighting lens housing **118**) may include lens sidewalls **822** that may be light-filtering, light blocking, and/or light-opaque to prevent light generated by the light element/engine from escaping through the sidewalls. This may prevent unwanted reflections, glare and/or any other undesired effects when lighting fixture housings are coupled together and installed in a particular space.

[0080] Referring back to FIGS. **3a-f**, the lighting lens housing **118** may be positioned within the housing **102** (and/or housing **202**) at an offset. For example, as shown in FIG. **3c**, the lighting lens housing **218** may extend beyond the edges or ends **330a**, **330b** of sidewalls **204a**, **204b**, respectively, of the housing **202**, thereby creating an exterior offset **333**. Similarly, the housing **102** may extend beyond edges or ends **331a**, **331b** of sidewalls **402a**, **402b**, respectively, of the lighting lens housing **118**, also creating an interior offset **335**. The lengths of the created offsets may be equal and/or substantially equal to allow interior offset(s) **335** to match exterior offset(s) **333** of lighting fixtures upon connection two their respective housings (e.g., connection of housing **102** and housing **202**). Moreover, as shown in FIG. **3c**, the lighting lens panel **122** may include a first end **339**, which as a result of the positioning of the lighting lens housing **118**, may be positioned at an offset with respect to the ends **331a**, **331b** of the housing **102**. The lighting lens panel **122** may also include a second end (which may be similar to the end **341** of the lighting lens **322**) that may likewise be positioned at an offset and extend beyond the ends of the housing (e.g., as shown in FIG. **3c**, the end **341** of the lighting lens **322** extends beyond the housing's ends **330a**, **330b**). It should be noted that the positioning/securing of the lighting lens housing in/to the housing may cause the lighting lens (along with lens sidewalls) to extend beyond the ends of the housing at one end of the lighting lens/housing (e.g., lens **322** extending beyond the ends of the housing **202**) while the housings' ends extending beyond the end of the lighting lens (e.g., ends of housing **102** extending beyond the end of the lighting lens **122**). In some alternate, example implementations, the lighting lens housing (including the lighting lens and the lens sidewalls) may extend beyond ends of the housing at its both ends. In further alternate, example implementations, the housing may extend beyond ends of the lighting lens housing at its both ends.

[0081] Further, in some implementations, upon connection of two housings, e.g., housings **102** and **202**, as shown in FIG. **2**, with lighting lens housings positioned therein, e.g., housings **118** and **218**, respectively, as shown in FIG. **3c**, the housings and the lighting lens housings may form respective seams. For example, as shown in FIGS. **3f** and **3g**, the housings **102** and **202** may form a housing connection joint or seam (terms used interchangeably herewith) **350**. Similarly, the lighting lens housings **118** and **218** may form a lighting lens housing connection joint or seam **352**. As shown in FIG. **3g**, the housing connection joint **350** may be positioned at an offset, as discussed herein, with respect to the lighting lens housing connection joint **352** (or vice versa). Such respective joining of the housing sidewalls and the lighting lens housing sidewalls as well as opaqueness or non-transparency of the lighting lens housing sidewalls may prevent transmission (or escape) of light through the joint **350** of the housing sidewalls.

[0082] FIG. **6** illustrates an example connection of housings **102** and **202** with the use of interior and exterior offsets **335**, **333**. As shown, the exterior offset **333** of the lighting lens housing **218** that

extends beyond the edges or ends **330a**, **330b** of sidewalls **204a**, **204b**, respectively, of the housing **202** may be aligned with the interior offset **335** created by the lighting lens housing **118** when connecting the housings **102** and **202**.

[0083] In some implementations, as shown in FIGS. **8a-b**, the lighting lens housing's sidewalls may be light-filtering, light blocking, and/or light-opaque. Thus, use of the interior and/or exterior offsets **335**, **333** in addition to the light-filtering, light blocking, and/or light-opaque nature of the lighting lens housing's sidewalls may enhance an ability to block and/or prevent escape of light as well as reduce unwanted glare, reflections and/or other undesired side effects from joints formed by connection of two housings (e.g., housings **102**, **202**).

[0084] FIGS. **5a-f** illustrate an example assembly and/or installation process for positioning of a lighting lens housing (e.g., housing **118**) within the lighting fixture housing (e.g., housing **102**), according to some implementations of the current subject matter. As can be understood, the order of FIGS. **5a-f** does not imply a particular order of assembly/installation.

[0085] As shown in FIG. **5a**, a lighting element **506** (similar to lighting element **406** shown in FIGS. **4a-b**) may be coupled to a platform **509** (similar to platform **409**) of the liner **508** (similar to liner **408**) of lighting lens housing (as shown by the arrow in FIG. **5a**). By way of a non-limiting example, the lighting element **506** may include an adhesive and/or any other attachment means that may be used to attach the lighting element **506** to the platform **509**. In some implementations, the lighting element **506** may also include one or more lighting sections **516** (a, b, . . . , n), where each lighting section **516** may include individual light producing components **518** (e.g., LEDs) (as shown in FIG. **5b**). The length of the lighting element may be adjusted to fit a particular lighting lens housing. This may be accomplished by removing one or more sections **516** from the lighting element **506**. Alternatively, or in addition, sections **516** may be separately installed as individual lighting elements. Further, in some implementations, each lighting section **516** may be electrically coupled to a source of electrical power. Alternatively, or in addition, a single lighting section **516** in the lighting element **506** may be electrically coupled to the source of electrical power, and electrically connected to other lighting sections **516** in the lighting element **506** to provide electrical power to them. Such connections may be in-series and/or in-parallel.

[0086] Referring to FIGS. **5b-d**, the lighting element **506** may be electrically coupled to an electrical connector **520** that may, in turn, be electrically connected to a source of electrical power (not shown in FIGS. **5b-c**). The electrical connector **520** may include wires **522** and **524**, which may be electrically coupled to lighting element connectors **528**, **526**, respectively. The lighting element connectors **526**, **528** may be positioned on at least one section **516** and may be electrically connected to the light producing components **518**. The wires **522**, **524** may be routed through the liner's wiring harness **530**, as shown in FIG. **5c-d**.

[0087] The lighting element **506** along with wires **522**, **524** positioned in the wiring harness **530** may be releasably secured within the lighting lens housing **118**, as shown by the arrow in FIG. **5c-d**. The electrical connector **520** may be extended from the lighting lens housing **118** at any desired location. As shown, for example, in FIG. **5d**, the electrical connector **520** may be extended from the lighting lens housing **118** in the middle of the housing **118**, which may be proximate to an electrical connector **532** in the housing **102** (as shown in FIG. **5e**) that may be used to electrically connect the electrical connector **520** to the source of electrical power. A ground wire **534** may also be connected to the lighting element **506** (as shown in FIG. **5e**).

[0088] Referring to FIGS. **5e-f**, in some implementations, an optional service string **542** may be coupled to the liner **508**. The service string **542** may be used to pull the liner **508** from the lighting lens housing **118**. This may be done when repair, replacement, and/or servicing of the components of the lighting lens housing **118**, e.g., lighting element **506**, etc., may be needed.

[0089] Once electrical connections are made, the lighting lens housing **118** may be positioned into the lighting fixture housing **102**, as shown in FIG. **5f**. In some implementations, if the lighting fixture housing **102** may include end caps **544a** and **544b** that may be positioned at ends of the

lighting fixture housing **102**. The end caps **544** may be used to enclose the interior of the lighting fixture housing **102** thereby preventing escape of unwanted light, reflections, etc. as well as collection of dust, moisture, etc. in the interior of the lighting fixture housing **102**. When multiple lighting fixture housings are connected together to form a line of lighting fixture housings, the end caps **544** may be used to cap off start and end of such line. In this case, the caps **544** would typically not be positioned between lighting fixture housings.

[0090] In some implementations, the above construction of the lighting fixture system may provide a lighting fixture with length-adjustable housing and optical electrical assembly. In particular, the current subject matter's modular optical electrical assembly construction may include a common LED and a heatsink that when coupled with a primary optic and/or lens may change the light output characteristics. This design may enable interchangeability of the optic and lens by end users with keyed features in the profile to prevent possibility of incorrect assembly. This is in contrast to convention lighting fixtures that may not have the capability to interchange components in the field to change light output characteristics. The current subject matter's modular optical electrical assembly and lighting fixture housing may be length-adjusted at one end to reduce its overall length (e.g., from a starting length of up to 96" to a minimum length of 21").

[0091] FIGS. **9a-9b** illustrates a lighting fixture system **900**, according to some implementations of the current subject matter. The lighting fixture system **900** may include one or more lighting fixture housings **102** that may enclose any of the components discussed above in connection with FIGS. **1-8b** electrically and mechanically coupled to a source of electrical power **902**. The mechanical coupling of the lighting fixture housing **102** and the source of electrical power **902** may be accomplished using one or more connectors **112** that may physically suspend the lighting fixture housing **102** from the source of electrical power **902**. The electrical coupling of the lighting fixture housing **102** and the source of electrical power **902** may be via one or more electrical wires that may be protruded through an interior of the connectors **112**.

[0092] The source of electrical power **902** may include a housing **904** having an opening **906** and one or more electrical components (e.g., one or more LED drivers) that may be needed for operating the lighting fixture connected to the source of electrical power **902**. The source of electrical power **902** may also be electrically coupled to an electrical main (not shown in FIGS. **9a-b**), however, all electrical components needed for operation of the lighting fixture connected to it may be disposed within the housing **904**. Such electrical components may also be easily accessible via an opening **906**. The opening **906** may also coincide with a ceiling opening **911** that may be created at a location of mounting of the housing **904** in the space **912**. For example, the housing **904** may be mounted to a structural element of a building (e.g., a cross-beam, a support beam, etc.). The ceiling opening **911** and, thus, the opening **906**, may be covered (when not in use for serving/repair/replacement/etc. of electrical components within the housing **904**) by a cover **914**. The cover **914** may be slidably disposed along with the connector **112** and may be secured proximate to the ceiling opening **911** when there is no need to access interior of the housing **904**. When servicing/repair/replacement of one or more electrical components of the source of electrical power **902** is needed, the cover **914** may be pulled (e.g., in a downward direction) along the connector **112** and/or rotated away to expose openings **911** and **906** allowing access to the electrical components.

[0093] In some implementations, as shown in FIG. **9b**, the connector **112** may be configured to be coupled (either to the housing **904** of the source of electrical power or to the ceiling **910**) at an offset from the center of the opening **906** and/or the ceiling opening **911** (e.g., at an edge of the opening **906**/opening **911** and/or outside of the opening **906**/opening **911** (e.g., through a separate opening in the ceiling and/or the housing **906**)). Such offset-based coupling may further allow ease of unobstructed access to the interior of the housing **904** of the source of electrical power **902**. In some example implementations, the connector **112** may only be coupled to the ceiling **910** and not the housing **904**. As can be understood, any type of coupling of the connector **112** may be used.

Further, the connector **112** may also protrude through the cover **914** at a location that may be at an offset from the center of the cover **914** (e.g., at an edge of the cover **914**), as shown in FIG. **9b**. When access to the housing **904** is required, the cover **914** may be fully rotated away and/or pulled down along the connector **112** to allow unrestricted access to the housing **904** through the opening **906**. Alternatively, or in addition, the connector **112** may protrude through the center of the cover **914** and/or at any other location on the cover **914**.

[0094] The current subject matter's use sources of electrical power that may be locally positioned to lighting fixture provides numerous beneficial features. Existing LED fixture systems typically include an LED driver that may be located far away from the suspended lighting fixture's housing and may have driver enclosures above the ceiling that may require ceiling access to service the LED drivers and/or may require a remote enclosure for placement of the LED drivers. The current subject matter's system may provide an LED driver that may be placed above the ceiling directly above the canopy of a connector suspended lighting fixture without disturbing the connector mounting. The connector mounting locations at the ceiling may be offset from the center of the canopy and/or center of the ceiling opening, whereas connector mounting locations area typically concentric to the canopy, thereby providing an unobstructed access into the ceiling. The offset of the suspension connectors from the center of the ceiling opening and/or the center of the canopy may prevent obstruction of ceiling access during service of the LED driver without disturbing the connector suspension system.

[0095] In some implementations, the above arrangement of the connector **112** with respect to the source of electrical power **902** may be beneficial in providing unrestricted access to the source of electrical power. At the outset, having the source of electrical power proximate to the lighting fixture eliminates remote location/locating of such sources (as in conventional systems) when service of the sources is required (e.g., replacement of LED driver), thereby reducing service time and easing burdens associated with assessing malfunction issues. Moreover, as stated above, having connector (e.g., connector **112**) mounting locations at the ceiling that are offset from the center of the ceiling canopy (e.g., cover **914** covering opening **906**/opening **911**) and/or non-concentrically mounted to the ceiling canopy and/or with respect to the opening in the ceiling, allows for ease of access to and serving of electrical components within the locally positioned sources of electrical power. This may be accomplished through sliding the ceiling canopy (e.g., cover **914**) down along the connector **112** without disturbing the connector and/or other electrical wiring either at the ceiling and/or the lighting fixture.

[0096] The foregoing description has broad application. While the present disclosure refers to certain implementations, numerous modifications, alterations, and changes to the described implementations are possible without departing from the sphere and scope of the present disclosure, as defined in the appended claim(s). Accordingly, it is intended that the present disclosure not be limited to the described implementations. Rather these implementations should be considered as illustrative and not restrictive in character. All changes and modifications that come within the spirit of the current subject matter are to be considered within the scope of the disclosure. The present disclosure should be given the full scope defined by the language of the following claims, and equivalents thereof. The discussion of any implementation is meant only to be explanatory and is not intended to suggest that the scope of the disclosure, including the claims, is limited to these implementations. In other words, while illustrative implementations of the disclosure have been described in detail herein, it is to be understood that the inventive concepts may be otherwise variously embodied and employed, and that the appended claims are intended to be construed to include such variations, except as limited by the prior art. Unless otherwise defined, all technical terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which the disclosure belongs.

[0097] Directional terms such as top, bottom, superior, inferior, medial, lateral, anterior, posterior, proximal, distal, upper, lower, upward, downward, left, right, longitudinal, front, back, above,

below, vertical, horizontal, radial, axial, clockwise, and counter-clockwise) and the like may have been used herein. Such directional references are only used for identification purposes to aid the reader's understanding of the present disclosure. For example, the term “distal” may refer to the end farthest away from the medical professional/operator when introducing a device into a patient, while the term “proximal” may refer to the end closest to the medical professional when introducing a device into a patient. Such directional references do not necessarily create limitations, particularly as to the position, orientation, or use of this disclosure. As such, directional references should not be limited to specific coordinate orientations, distances, or sizes, but are used to describe relative positions referencing particular implementations. Such terms are not generally limiting to the scope of the claims made herein. Any implementation or feature of any section, portion, or any other component shown or particularly described in relation to various implementations of similar sections, portions, or components herein may be interchangeably applied to any other similar implementation or feature shown or described herein.

[0098] It should be understood that, as described herein, an “implementation” (such as illustrated in the accompanying Figures) may refer to an illustrative representation of an environment or article or component in which a disclosed concept or feature may be provided or embodied, or to the representation of a manner in which just the concept or feature may be provided or embodied. However, such illustrated implementations are to be understood as examples (unless otherwise stated), and other manners of embodying the described concepts or features, such as may be understood by one of ordinary skill in the art upon learning the concepts or features from the present disclosure, are within the scope of the disclosure. Furthermore, references to “one implementation” of the present disclosure are not intended to be interpreted as excluding the existence of additional implementations that also incorporate the recited features.

[0099] In addition, it will be appreciated that while the Figures may show one or more implementations of concepts or features together in a single implementation of an environment, article, or component incorporating such concepts or features, such concepts or features are to be understood (unless otherwise specified) as independent of and separate from one another and are shown together for the sake of convenience and without intent to limit to being present or used together. For instance, features illustrated or described as part of one implementation can be used separately, or with another implementation to yield a still further implementation. Thus, it is intended that the present subject matter covers such modifications and variations as come within the scope of the appended claims and their equivalents.

[0100] As used herein, an element or step recited in the singular and proceeded with the word “a” or “an” should be understood as not excluding plural elements or steps, unless such exclusion is explicitly recited. It will be further understood that the terms “includes” and/or “comprising,” or “includes” and/or “including” when used herein, specify the presence of stated features, regions, steps, elements and/or components, but do not preclude the presence or addition of one or more other features, regions, integers, steps, operations, elements, components and/or groups thereof.

[0101] The phrases “at least one”, “one or more”, and “and/or”, as used herein, are open-ended expressions that are both conjunctive and disjunctive in operation. The terms “a” (or “an”), “one or more” and “at least one” can be used interchangeably herein.

[0102] Connection references (e.g., engaged, attached, coupled, connected, and joined) are to be construed broadly and may include intermediate members between a collection of elements and relative to movement between elements unless otherwise indicated. As such, connection references do not necessarily infer that two elements are directly connected and in fixed relation to each other. Identification references (e.g., primary, secondary, first, second, third, fourth, etc.) are not intended to connote importance or priority, but are used to distinguish one feature from another. The drawings are for purposes of illustration only and the dimensions, positions, order and relative to sizes reflected in the drawings attached hereto may vary.

[0103] The foregoing discussion has been presented for purposes of illustration and description and

is not intended to limit the disclosure to the form or forms disclosed herein. For example, various features of the disclosure are grouped together in one or more implementations or configurations for the purpose of streamlining the disclosure. However, it should be understood that various features of the certain implementations or configurations of the disclosure may be combined in alternate implementations or configurations. Moreover, the following claims are hereby incorporated into this detailed description by this reference, with each claim standing on its own as a separate implementation of the present disclosure.

Claims

- 1.** A connection apparatus for electrically coupling a lighting fixture and a source of electrical power, the connection apparatus comprising: a connector configured to suspend the lighting fixture from a ceiling, wherein the lighting fixture is electrically coupled to the source of electrical power via the connector; the connector protrudes through an opening in the ceiling, the opening is configured to be covered using a canopy; wherein the connector protrudes into the opening in the ceiling through the canopy at an offset with respect to one or more of: a center of the canopy or a center of the opening in the ceiling.
- 2.** The connection apparatus of claim 1, wherein the canopy is removable.
- 3.** The connection apparatus of claim 1, wherein the source of electrical power includes a source of electrical power housing, wherein the connector is configured to be coupled to one or more of: the source of electrical power housing or the ceiling.
- 4.** The connection apparatus of claim 3, wherein the source of electrical power is disposed above the canopy.
- 5.** The connection apparatus of claim 4, wherein the source of electrical power is disposed in the ceiling above the canopy and configured to be accessible without disconnecting the connector.
- 6.** The connection apparatus of claim 5, wherein the source of electrical power includes an LED driver.
- 7.** The connection apparatus of claim 4, wherein the source of electrical power is positioned proximately with respect to the lighting fixture.
- 8.** The connection apparatus of claim 3, wherein the lighting fixture includes a lighting fixture housing, wherein the connector is configured to be coupled to the lighting fixture housing and at least one of: the source of electrical power housing and the ceiling.
- 9.** The connection apparatus of claim 1, wherein the canopy is configured to be moved away from the opening to expose the opening.
- 10.** The connection apparatus of claim 9, wherein movement of the canopy away from the opening includes one or more of: a downward movement along the connector and/or a rotational movement about the connector.
- 11.** The connection apparatus of claim 10, wherein movement of the canopy away from the opening is configured to provide access to the source of electrical power and at least one electrical component electrically coupled to at least one of: the source of electrical power or the lighting fixture.
- 12.** The connection apparatus of claim 1, wherein the lighting fixture includes: the lighting fixture housing having a first housing sidewall and a second housing sidewall, the first and second housing sidewalls each having a first end and a second end; and a lighting lens housing having a first lens sidewall, a second lens sidewall, and a lens panel having a first end and a second end, wherein the lens panel is disposed between the first and second lens sidewalls, and wherein a one or more of the first or second lens sidewalls is configured to block transmission of light; wherein the lighting lens housing is configured to be attached to the lighting fixture housing.
- 13.** A lighting system, comprising: a lighting fixture, the lighting fixture being configured to electrically couple to the source of electrical power; a connector configured to suspend the lighting

fixture from a ceiling, wherein the lighting fixture is electrically coupled to the source of electrical power via the connector; the connector protrudes through an opening in the ceiling, the opening is configured to be covered using a canopy; wherein the connector protrudes into the opening in the ceiling through the canopy at an offset with respect to one or more of: a center of the canopy or a center of the opening in the ceiling.

14. The lighting system of claim 13, wherein the canopy is removable.

15. The lighting system of claim 13, wherein the canopy is configured to be moved away from the opening to expose the opening; wherein movement of the canopy away from the opening includes one or more of: a downward movement along connector and/or a rotation movement about the connector; wherein movement of the canopy away from the opening is configured to provide access to the source of electrical power and at least one electrical component electrically coupled to at least one of: the source of electrical power or the lighting fixture.

16. The lighting system of claim 13, wherein the source of electrical power includes a source of electrical power housing, wherein the connector is configured to be coupled to one or more of: the source of electrical power housing or the ceiling; wherein the source of electrical power is disposed above the canopy; wherein the lighting fixture includes a lighting fixture housing, wherein the connector is configured to be coupled to the lighting fixture housing and at least one of: the source of electrical power housing and the ceiling.

17. The lighting system of claim 13, wherein the source of electrical power is positioned proximately with respect to the lighting fixture.

18. A lighting system, comprising: a plurality of lighting fixtures, at least one lighting fixture in the plurality of lighting fixtures being configured to electrically couple to the source of electrical power, wherein the at least one lighting fixture in the plurality of lighting fixtures is electrically coupled to at least another lighting fixture in the plurality of lighting fixtures; one or more connectors configured to suspend the at least one lighting fixture from a ceiling, wherein the source of electrical power is electrically coupled to the at least one lighting fixture via the one or more connectors thereby providing electrical power to the at least one lighting fixture and at least another lighting fixture; the one or more connectors protrude through an opening in the ceiling, the opening is configured to be covered using a canopy; wherein the one or more connectors protrude into the opening in the ceiling through the canopy at an offset with respect to one or more of: a center of the canopy or a center of the opening in the ceiling.

19. The lighting system of claim 18, wherein the one or more connectors are configured to suspend the at least another lighting fixture from the ceiling.

20. The lighting system of claim 19, wherein the at least another lighting fixture is not directly electrically coupled to the source of electrical power using the one or more connectors.
