

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12383070
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Zaiss; Vit et al.

Distribution pad for a temperature control system

Abstract

An air distribution pad comprises an upper layer, a lower layer, and a spacer material located between the upper layer and the lower layer, the spacer material configured to allow air to pass therethrough. An air distributor is configured to distribute air to the spacer material, wherein the air distributor comprises a port configured to receive an air hose, wherein the port is directed laterally sideways from the air distributor. At least one joining structure is coupled to the upper layer and the lower layer, the at least one joining structure providing one or more channels formed through the spacer material in fluid communication with the air distributor. The one or more channels are configured to direct generally laterally flowing air from the port of the air distributor to a generally longitudinal direction along the at least one channel.

Inventors:	Zaiss; Vit (Minneapolis, MN), Karschnik; Kody (Plymouth, MN)
Applicant:	Sleep Number Corporation (Minneapolis, MN)
Family ID:	49989914
Assignee:	Sleep Number Corporation (Minneapolis, MN)
Appl. No.:	17/368019
Filed:	July 06, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20210401185 A1	Dec. 30, 2021

Related U.S. Application Data

continuation parent-doc US 16240351 20190104 US 11083308 child-doc US 17368019
continuation parent-doc US 14842177 20150901 US 10194752 20190205 child-doc US 16240351
continuation parent-doc US 13728087 20121227 US 9131781 20150915 child-doc US 14842177

Publication Classification

Int. Cl.: A47C21/04 (20060101); A47C27/14 (20060101); A61G7/057 (20060101)

U.S. Cl.:

CPC A47C21/044 (20130101); A47C21/048 (20130101); A47C27/14 (20130101); A61G7/05784 (20161101); A61G7/05792 (20161101); A47C21/04 (20130101)

Field of Classification Search

CPC: A61G (7/05792); A61G (7/05784); A47C (21/04); A47C (21/042); A47C (21/044); A47C (21/048); A47C (27/14); A47C (27/144)

USPC: 5/423

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2596547	12/1951	Winifred	N/A	N/A
2601189	12/1951	Wales	N/A	N/A
3230556	12/1965	Wiusor	N/A	N/A
3230566	12/1965	Moody	N/A	N/A
3644950	12/1971	Lindsay, Jr.	5/709	A61G 7/057
3653083	12/1971	Lapidus	N/A	N/A
3778851	12/1972	Howorth	N/A	N/A
4267611	12/1980	Agulnick	5/691	A61G 7/05776
4391009	12/1982	Schlid et al.	N/A	N/A
4660388	12/1986	Greene	N/A	N/A
4766628	12/1987	Walker	N/A	N/A
4788729	12/1987	Walker	N/A	N/A
4796316	12/1988	Boselli	5/724	A47C 27/146
4829616	12/1988	Walker	N/A	N/A
4853992	12/1988	Yu	N/A	N/A
4862921	12/1988	Hess	N/A	N/A
4867230	12/1988	Voss	N/A	N/A
4890344	12/1989	Walker	N/A	N/A
4897890	12/1989	Walker	N/A	N/A
4908895	12/1989	Walker	N/A	N/A
4991244	12/1990	Walker	N/A	N/A
5144706	12/1991	Walker	N/A	N/A
5170522	12/1991	Walker	N/A	N/A
5184612	12/1992	Augustine	N/A	N/A
5265599	12/1992	Stephenson et al.	N/A	N/A
5295709	12/1993	Bell	N/A	N/A
5382075	12/1994	Shih et al.	N/A	N/A

5473783	12/1994	Allen	N/A	N/A
5493742	12/1995	Klearman	N/A	N/A
5509154	12/1995	Shafer et al.	N/A	N/A
5564140	12/1995	Shoenhair et al.	N/A	N/A
5566409	12/1995	Klearman	N/A	N/A
5596778	12/1996	Suzuki	5/482	A61F 7/0097
5597200	12/1996	Gregory et al.	N/A	N/A
5642546	12/1996	Shoenhair	N/A	N/A
5652484	12/1996	Shafer et al.	N/A	N/A
5675848	12/1996	Kappel	N/A	N/A
5749109	12/1997	Kappel	N/A	N/A
5765246	12/1997	Shoenhair	N/A	N/A
5787534	12/1997	Hargest et al.	N/A	N/A
5878807	12/1998	Takahashi	N/A	N/A
5882349	12/1998	Wilkerson et al.	N/A	N/A
5903941	12/1998	Shafer et al.	N/A	N/A
5904172	12/1998	Gifft et al.	N/A	N/A
5921858	12/1998	Kawai et al.	N/A	N/A
5989285	12/1998	DeVibiss et al.	N/A	N/A
6006524	12/1998	Park	N/A	N/A
6037723	12/1999	Shafer et al.	N/A	N/A
6085369	12/1999	Feher	N/A	N/A
6102936	12/1999	Augustine et al.	N/A	N/A
6108844	12/1999	Kraft et al.	N/A	N/A
6119463	12/1999	Bell	N/A	N/A
6161231	12/1999	Kraft et al.	N/A	N/A
6202239	12/2000	Ward et al.	N/A	N/A
6210427	12/2000	Augustine et al.	N/A	N/A
6223539	12/2000	Bell	N/A	N/A
6263530	12/2000	Feher	N/A	N/A
6336237	12/2001	Schmid	N/A	N/A
6397419	12/2001	Mechache	N/A	N/A
6421859	12/2001	Hicks	5/737	A61G 7/05715
6483264	12/2001	Shafer et al.	N/A	N/A
6493889	12/2001	Kocurek et al.	N/A	N/A
6497720	12/2001	Augustine et al.	N/A	N/A
6511501	12/2002	Augustine et al.	N/A	N/A
6546576	12/2002	Lin	N/A	N/A
RE38128	12/2002	Gallup et al.	N/A	N/A
6596018	12/2002	Endo et al.	N/A	N/A
6606866	12/2002	Bell	N/A	N/A
6686711	12/2003	Rose et al.	N/A	N/A
6700052	12/2003	Bell	N/A	N/A
6701556	12/2003	Romano et al.	N/A	N/A
6708357	12/2003	Gaboury et al.	N/A	N/A
6763541	12/2003	Mahoney et al.	N/A	N/A
6779592	12/2003	Ichigaya	N/A	N/A
6804848	12/2003	Rose	N/A	N/A
6832397	12/2003	Gaboury et al.	N/A	N/A

6883191	12/2004	Gaboury et al.	N/A	N/A
7036163	12/2005	Schmid	N/A	N/A
7114771	12/2005	Lofy et al.	N/A	N/A
7291163	12/2006	Gammons	N/A	N/A
7296315	12/2006	Totten et al.	N/A	N/A
7389554	12/2007	Rose	N/A	N/A
7469432	12/2007	Chambers	N/A	N/A
7475464	12/2008	Lofy et al.	N/A	N/A
7480950	12/2008	Feher	N/A	N/A
7480953	12/2008	Romano et al.	N/A	N/A
7587901	12/2008	Petrovski	N/A	N/A
7591507	12/2008	Giffin et al.	N/A	N/A
7617555	12/2008	Romano et al.	N/A	N/A
7640754	12/2009	Wolas	N/A	N/A
7665803	12/2009	Wolas	N/A	N/A
7708338	12/2009	Wolas	N/A	N/A
7712164	12/2009	Chambers	N/A	N/A
RE41765	12/2009	Gregory et al.	N/A	N/A
7827805	12/2009	Comiskey et al.	N/A	N/A
7865988	12/2010	Koughan et al.	N/A	N/A
7877827	12/2010	Marquette et al.	N/A	N/A
7908687	12/2010	Ward et al.	N/A	N/A
7914611	12/2010	Vrzalik	95/52	A61G 7/05715
7937789	12/2010	Feher	N/A	N/A
7963594	12/2010	Wolas	N/A	N/A
7966835	12/2010	Petrovski	N/A	N/A
7975331	12/2010	Flocard et al.	N/A	N/A
7996936	12/2010	Marquette et al.	N/A	N/A
8065763	12/2010	Brykalski et al.	N/A	N/A
8118920	12/2011	Vrazlik et al.	N/A	N/A
8143554	12/2011	Lofy	N/A	N/A
8181290	12/2011	Brykalski et al.	N/A	N/A
8191187	12/2011	Brykalski et al.	N/A	N/A
8220090	12/2011	Gowda	N/A	N/A
8222511	12/2011	Gowda	N/A	N/A
8256236	12/2011	Lofy	N/A	N/A
8282452	12/2011	Grigsby et al.	N/A	N/A
8332975	12/2011	Brykalski et al.	N/A	N/A
8336369	12/2011	Mahoney	N/A	N/A
8353069	12/2012	Miller	N/A	N/A
8402579	12/2012	Marquette et al.	N/A	N/A
8418286	12/2012	Brykalski et al.	N/A	N/A
8434314	12/2012	Comiskey et al.	N/A	N/A
8444558	12/2012	Young et al.	N/A	N/A
8516842	12/2012	Petrovski	N/A	N/A
8539624	12/2012	Terech et al.	N/A	N/A
8621687	12/2013	Brykalski et al.	N/A	N/A
8672853	12/2013	Young	N/A	N/A
8732874	12/2013	Brykalski et al.	N/A	N/A

8769747	12/2013	Mahoney et al.	N/A	N/A
8782830	12/2013	Brykalski et al.	N/A	N/A
8893329	12/2013	Petrovski et al.	N/A	N/A
8931329	12/2014	Mahoney et al.	N/A	N/A
8966689	12/2014	McGuire et al.	N/A	N/A
8973183	12/2014	Palashewski et al.	N/A	N/A
8984687	12/2014	Stusynski et al.	N/A	N/A
9055820	12/2014	Axakov et al.	N/A	N/A
9125497	12/2014	Brykalski et al.	N/A	N/A
9131781	12/2014	Zaiss	N/A	A47C 21/044
9222685	12/2014	Lachenbruch	N/A	N/A
9254231	12/2015	Vrzalik et al.	N/A	N/A
9603459	12/2016	Brykalski et al.	N/A	N/A
9622588	12/2016	Brykalski et al.	N/A	N/A
9737154	12/2016	Mahoney et al.	N/A	N/A
9814641	12/2016	Brykalski et al.	N/A	N/A
9924813	12/2017	Basten et al.	N/A	N/A
9974394	12/2017	Brykalski et al.	N/A	N/A
10143312	12/2017	Brosnan et al.	N/A	N/A
10194752	12/2018	Zaiss et al.	N/A	N/A
10226134	12/2018	Brykalski et al.	N/A	N/A
10405667	12/2018	Comiskey et al.	N/A	N/A
10675198	12/2019	Brykalski et al.	N/A	N/A
10772438	12/2019	Griffith et al.	N/A	N/A
11020298	12/2020	Brykalski et al.	N/A	N/A
11045371	12/2020	Brykalski et al.	N/A	N/A
11083308	12/2020	Zaiss	N/A	A47C 27/14
2003/0145380	12/2002	Schmid	5/423	A47C 21/048
2003/0234247	12/2002	Stem	N/A	N/A
2004/0187216	12/2003	Lin	N/A	N/A
2005/0011009	12/2004	Wu	5/423	A47C 7/748
2005/0086739	12/2004	Wu	5/423	A47C 27/007
2005/0278863	12/2004	Bahash et al.	N/A	N/A
2006/0080778	12/2005	Chambers	N/A	N/A
2006/0101577	12/2005	Lussier	N/A	N/A
2006/0137099	12/2005	Feher	N/A	N/A
2007/0033733	12/2006	Jen	N/A	N/A
2008/0077020	12/2007	Young et al.	N/A	N/A
2008/0173022	12/2007	Petrovski	N/A	N/A
2009/0218855	12/2008	Wolas	N/A	N/A
2010/0174198	12/2009	Young et al.	N/A	N/A
2011/0107514	12/2010	Brykalski	5/652.1	A61G 7/057
2011/0115635	12/2010	Petrovski et al.	N/A	N/A
2011/0144455	12/2010	Young et al.	N/A	N/A
2011/0258778	12/2010	Brykalski et al.	N/A	N/A
2011/0289684	12/2010	Parish	5/421	A47C 21/044

2011/0306844	12/2010	Young	N/A	N/A
2012/0000207	12/2011	Parish et al.	N/A	N/A
2012/0080911	12/2011	Brykalski et al.	N/A	N/A
2012/0114512	12/2011	Lofy et al.	N/A	N/A
2012/0131748	12/2011	Brykalski et al.	N/A	N/A
2012/0144584	12/2011	Vrazalik et al.	N/A	N/A
2012/0261399	12/2011	Lofy	N/A	N/A
2012/0305043	12/2011	Kossakovski et al.	N/A	N/A
2013/0037073	12/2012	LaGrandeur et al.	N/A	N/A
2013/0059190	12/2012	Kossakovski et al.	N/A	N/A
2013/0205506	12/2012	Lachenbruch et al.	N/A	N/A
2013/0212808	12/2012	Lachenbruch et al.	N/A	N/A
2013/0259965	12/2012	Cloeren et al.	N/A	N/A
2013/0269106	12/2012	Brykalski et al.	N/A	N/A
2014/0007656	12/2013	Mahoney	N/A	N/A
2014/0026320	12/2013	Comiskey et al.	N/A	N/A
2014/0182061	12/2013	Zaiss et al.	N/A	N/A
2014/0250597	12/2013	Chen et al.	N/A	N/A
2014/0257571	12/2013	Chen et al.	N/A	N/A
2014/0259417	12/2013	Nunn et al.	N/A	N/A
2014/0259418	12/2013	Nunn et al.	N/A	N/A
2014/0259431	12/2013	Fleury et al.	N/A	N/A
2014/0259433	12/2013	Nunn et al.	N/A	N/A
2014/0259434	12/2013	Nunn et al.	N/A	N/A
2014/0277611	12/2013	Nunn et al.	N/A	N/A
2014/0277778	12/2013	Nunn et al.	N/A	N/A
2014/0277822	12/2013	Nunn et al.	N/A	N/A
2014/0366277	12/2013	Niederkrom	5/652.2	A61G 7/057
2015/0007393	12/2014	Palashewski	N/A	N/A
2015/0025327	12/2014	Young et al.	N/A	N/A
2015/0026896	12/2014	Fleury et al.	N/A	N/A
2015/0157137	12/2014	Nunn et al.	N/A	N/A
2015/0157519	12/2014	Stusynski et al.	N/A	N/A
2015/0182033	12/2014	Brosnan et al.	N/A	N/A
2015/0182397	12/2014	Palashewski et al.	N/A	N/A
2015/0182399	12/2014	Palashewski et al.	N/A	N/A
2015/0182418	12/2014	Zaiss	N/A	N/A
2015/0238020	12/2014	Petrovski et al.	N/A	N/A
2016/0066701	12/2015	Diller et al.	N/A	N/A
2016/0100696	12/2015	Palashewski et al.	N/A	N/A
2016/0235210	12/2015	Lachenbruch et al.	N/A	N/A
2016/0367039	12/2015	Young et al.	N/A	N/A
2017/0071359	12/2016	Steele et al.	N/A	N/A
2017/0079444	12/2016	Blazar	N/A	N/A
2017/0273470	12/2016	Brykalski et al.	N/A	N/A
2017/0280883	12/2016	Diller	N/A	N/A
2020/0037776	12/2019	Brykalski et al.	N/A	N/A

2020/0337470	12/2019	Sayadi et al.	N/A	N/A
2021/0037987	12/2020	Griffith et al.	N/A	N/A
2021/0038453	12/2020	Brykalski et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3320771	12/1983	DE	N/A
1142515	12/2000	EP	N/A
H08-140808	12/1995	JP	N/A
WO 1997/038607	12/1996	WO	N/A
WO 2007/060371	12/2006	WO	N/A
WO 2007/093783	12/2006	WO	N/A
WO 2008/098945	12/2007	WO	N/A
WO 2005/120295	12/2007	WO	N/A
WO 2011/026040	12/2010	WO	N/A

OTHER PUBLICATIONS

U.S. Appl. No. 15/685,912, filed Aug. 24, 2017, Petrovski et al. cited by applicant
U.S. Appl. No. 15/973,279, filed May 7, 2018, Brykalski et al. cited by applicant
U.S. Appl. No. 17/139,227, filed Dec. 31, 2020, Grabinger et al. cited by applicant
U.S. Appl. No. 17/139,243, filed Dec. 31, 2020, Grabinger et al. cited by applicant
U.S. Appl. No. 17/139,259, filed Dec. 31, 2020, Grabinger et al. cited by applicant
U.S. Appl. No. 17/139,353, filed Dec. 31, 2020, Karschnik et al. cited by applicant
U.S. Appl. No. 17/139,668, filed Dec. 31, 2020, Karschnik et al. cited by applicant
U.S. Appl. No. 17/139,683, filed Dec. 31, 2020, Karschnik et al. cited by applicant
U.S. Appl. No. 17/139,785, filed Dec. 31, 2020, Karschnik et al. cited by applicant
U.S. Appl. No. 17/139,786, filed Dec. 31, 2020, Karschnik et al. cited by applicant
U.S. Appl. No. 17/139,789, filed Dec. 31, 2020, Karschnik et al. cited by applicant
U.S. Appl. No. 17/139,851, filed Dec. 31, 2020, Karschnik et al. cited by applicant
U.S. Appl. No. 17/140,702, filed Jan. 4, 2021, Karschnik et al. cited by applicant
U.S. Appl. No. 17/360,378, filed Jun. 28, 2021, Brykalski et al. cited by applicant
U.S. Appl. No. 17/360,420, filed Jun. 28, 2021, Brykalski et al. cited by applicant
PCT International Preliminary Report on Patentability in International Appln. No. PCT/US2013/078106, dated Jul. 9, 2015, 11 pages. cited by applicant
PCT International Search Report and Written Opinion in International Appln. No. PCT/US2013/078106, dated Mar. 11, 2014, 6 pages. cited by applicant
PCT International Written Opinion in International Appln. No. PCT/US2013/078106, dated Mar. 11, 2014, 9 pages. cited by applicant
PCT Invitation to Pay Additional Fees in International Appln. No. PCT/US2013/078106, dated Feb. 24, 2014, 6 pages. cited by applicant
Response filed May 9, 2014 to PCT International Search Report dated Mar. 11, 2014 in Appln. No. PCT/US2013/078106, 9 pages. cited by applicant

Primary Examiner: Hare; David R

Attorney, Agent or Firm: Fish & Richardson P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 16/240,351, filed Jan. 4, 2019, which is a continuation of U.S. application Ser. No. 14/842,177, filed Sep. 1, 2015 (now U.S. Pat. No. 10,194,752), which is a continuation and claims priority to U.S. application Ser. No. 13/728,087, filed on Dec. 27, 2012 (now U.S. Pat. No. 9,131,781). The disclosure of the prior application is considered part of the disclosure of this application, and is incorporated in its entirety into this application.

BACKGROUND

(1) Comfort while sleeping can often depend on the ambient conditions immediately proximate to a user, such as local temperatures and humidity levels within a bed. While large-scale environmental control, such as heating, ventilation, and air conditioning (HVAC) can provide comfort control to the building as a whole, large-scale environmental control generally cannot provide for personalized control or for fine-tuning of thermal comfort within the bed.

SUMMARY

(2) The present disclosure is directed to a system including a distribution pad that can be placed on a mattress to provide for personalized heating or cooling of the personal space of a user. Heated or cooled air can be fed into the distribution pad from a device, referred to herein as an engine, that can provide heated air, cooled air, or both. The distribution pad is configured to provide desired circulation of the heated or cooled air through the distribution pad and into the user's personal space.

(3) The present describes an air distribution pad that can be placed on a mattress, the distribution pad comprising an upper layer, a lower layer, and a spacer material located between the upper layer and the lower layer, the spacer material configured to allow air to pass therethrough. The air distribution pad also includes an air distributor configured to distribute air to the spacer material, wherein the air distributor comprises a port configured to receive an air hose, wherein the port is directed laterally sideways from the air distributor. At least one joining structure is coupled to the upper layer and the lower layer, the at least one joining structure providing one or more channels formed through the spacer material in fluid communication with the air distributor. The one or more channels are configured to direct generally laterally flowing air from the port of the air distributor to a generally longitudinal direction along the at least one channel.

(4) The present disclosure also describes an air distribution pad that can be placed on a mattress, the distribution pad comprising an upper layer, a lower layer, and a spacer material located between the upper layer and the lower layer, the spacer material configured to allow air to pass therethrough. The air distribution pad also includes an air distributor configured to distribute air to the spacer material, wherein the air distributor comprises a port configured to receive an air hose. Stitching couples the upper layer and the lower layer and extends through the spacer material. The stitching provides one or more channels formed through the spacer material in fluid communication with the air distributor. At least one of the top layer and the bottom layer defines openings in communication with the one or more channels. The one or more channels are configured to direct air from the air distributor along the one or more channels and out of the openings.

(5) The present disclosure also describes a system comprising an air distribution pad including an upper layer, a lower layer, and a spacer material located between the upper layer and the lower layer, the spacer material configured to allow air to pass therethrough. The air distribution pad also includes an air distributor configured to distribute air to the spacer material, wherein the air distributor comprises a port. Stitching couples the upper layer and the lower layer and extends through the spacer material. The stitching provides one or more channels formed through the spacer material in fluid communication with the air distributor. The one or more channels are configured to direct air from the air distributor along the one or more channels. The system also includes an engine configured to perform at least one of heating air or cooling air and an air deliver hose with a first end coupleable to the engine and a second end coupleable to the port of the air

distributor.

(6) These and other examples and features of the present systems and methods will be set forth in part in the following Detailed Description. This Summary is intended to provide an overview of the present subject matter, and is not intended to provide an exclusive or exhaustive explanation. The Detailed Description below is included to provide further information about the present systems and methods.

Description

BRIEF DESCRIPTION OF THE FIGURES

- (1) FIG. 1 is a perspective view of an example system for providing heated or cooled air, or both, to a personal space of a user lying on a mattress.
- (2) FIG. 2 is an exploded view the example system shown in FIG. 1.
- (3) FIG. 3 is an exploded view of an example active layer of an air distribution pad usable with the example system of FIG. 1.
- (4) FIG. 4 is a top view of the example active layer from FIG. 3 assembled.
- (5) FIG. 5 is a cross-sectional view of the example active layer taken along the line 5-5 in FIG. 4.
- (6) FIG. 6 is a perspective view of an example air distributor assembly that can be used with the example air distribution pad of FIG. 3.
- (7) FIG. 7 is an exploded view of the example air distributor assembly of FIG. 6.
- (8) FIG. 8 is an exploded view of another example active layer of an air distribution pad.
- (9) FIG. 9 is a top view of the example active layer from FIG. 8 assembled.

DETAILED DESCRIPTION

- (10) This disclosure describes an air distribution system and various components of the air distribution system that can provide heated air, cooled air, or both to a personal space of a user while the user is lying on a mattress or other cushion. The system can provide for improved comfort of the user and improved control over ambient temperature or humidity, or both, within the personal space of the user.
- (11) FIGS. 1 and 2 show an example sleep system **10** that can include an air distribution pad **12** placed on a mattress **2**. The air distribution pad **12** can distribute heated or cooled air supplied from an air source, such as from a heating or cooling engine **14** (referred to herein as an “engine **14**”) via an air delivery hose **16**. The air distribution pad **12** can distribute the air along and through the air distribution pad **12** in order to heat or cool a user lying or sitting on the sleep system **10**.
- (12) The mattress **2** can be any mattress that can be used for sleep or rest, such as a standard sized mattress for human sleep. In an example, the mattress **2** shown in FIGS. 1 and 2 can be a mattress designed for a single user, such as a standard twin-sized mattress (e.g., about 39 inches (about 100 cm) wide and about 75 inches (about 190 cm) long) or a long twin-sized mattress (e.g., about 36 inches (about 91 cm) wide and about 80 inches (about 200 cm) long). In another example, the mattress **2** can be designed for two or more users, such as a queen-sized mattress (e.g., about 60 inches (about 150 cm) wide and about 80 (about 200 cm) long) or a king-sized mattress (e.g., about 76 inches (about 195 cm) and about 80 inches (about 200 cm) long). The mattress **2** can be of any type of mattress, such as a spring mattress, an air mattress, or a waterbed mattress. In an example, the mattress **2** comprises an adjustable air bladder mattress, such as the Innovation Series I8 TXL Sleep Number mattress sold by Select Comfort Corp., Minneapolis, MN, USA.
- (13) As best shown in FIG. 1, the air distribution pad **12** can be sized to fit substantially the entire upper surface of a twin-sized mattress **2**, to correspond to the personal area occupied by a single person. The air distribution pad **12** can be sized so that two or more air distribution pads **12** can be placed on the same mattress **2**. For example, two air distribution pads **12** can be placed on top of a mattress **2** that is sized for two people, such as an Innovation Series I8 Queen or King-sized

mattress **2**, sold by Select Comfort Corp., Minneapolis, MN, USA. Each person occupying the mattress **2** can then have their own air distribution pad **12**. In such as case, each air distribution pad **12** can have its own air source, e.g., its own engine **14** and air delivery hose **16**, and its own control.

(14) The engine **14** can provide a cooling or a heating effect to air that can then be directed into the air distribution pad **12** with the hose **16**. In an example, the engine **14** can comprise a thermoelectric device, also referred to as a Peltier cooling device or a thermoelectric heat pump, which can produce a temperature difference across the device when a voltage is applied across the device. The thermoelectric device can operate due to the Peltier effect, wherein when an electrical current flows through two dissimilar conductors or semiconductors, the junction between the two conductors or semiconductors can either absorb or release heat depending on the direction of electricity flow. The thermoelectric device can be configured so that a first side of the thermoelectric device will absorb heat (e.g., will be cooled), while an opposed second side of the thermoelectric device will release heat (e.g., will be heated).

(15) Air can be drawn into the engine **14**, such as with a fan (not shown), and the air can be directed either be cooled or heated, depending on the polarity of the voltage applied to the thermoelectric device, as it passes through the thermoelectric device depending on the desired type of air to be delivered to the mattress **2**. The engine **14** can be configured to provide for a plurality of temperature settings and a plurality of air-flow settings. For example, the engine **14** can be configured with a set number of discrete “cooling” settings each corresponding to varying degrees of heat removal (e.g., cooling) by the thermoelectric device in the engine **14**. Similarly, the engine **14** can be configured with a discrete number of “heating” settings each corresponding to varying degrees of heat supply (e.g., heating) by the thermoelectric device in the engine **14**. The engine **14** can also be configured with a heating-neutral setting, e.g., with the thermoelectric device being inactive, but with the fan or other air moving device still providing air flow. In another example, the engine **14** can be configured with a continuous temperature control setting, rather than discrete temperature settings, so that a user can select varying degrees of heating or cooling along a continuous or substantially continuous spectrum between an upper heating or cooling level and a lower heating or cooling level. The control of air flow (e.g., air flow rate) can also be configured to be either discrete or continuous.

(16) Further details of an example thermoelectric device that can be used with the air distribution pad **12** of the present disclosure is described in U.S. Published Patent Application No. 2012/0000207, filed on Sep. 13, 2011, the entire disclosure of which is incorporated herein by reference.

(17) The air distribution pad **12** can be configured to provide for desired or optimized delivery of air from the engine **14** so that a person sitting or lying on the air distribution pad **12** can have improved comfort, such as via a heating or cooling effect. FIG. 2 shows an exploded view of an example air distribution pad **12** that can be used with the sleep system **10**. The air distribution pad **12** can include an active layer **20**, which can include one or more structures to receive the heated or cooled air from the engine **14** and to distribute the air along the length of the active layer **20** and to a personal space of a user lying or sitting on the air distribution pad **12**. In an example, the active layer **20** can be the only structure or layer of the air distribution pad **12**, e.g., such that the active layer **20** is the air distribution pad **12**. In other examples, such as the examples shown in FIG. 2, the active layer **20** can be used in conjunction with other components of the air distribution pad **12**.

(18) As shown in the example of FIG. 2, the air distribution pad **12** can include a cover that can at least partially enclose the active layer **20**. For example, a cover can be formed by joining of an upper cover portion **22** and a lower cover portion **24**. The cover **22**, **24** can enclose the active layer **20** and, if desired, one or more additional structures or layers that can provide for comfort of the user. In an example, the lower cover portion **24** can comprise a substantially air impermeable and moisture impermeable material so that air being distributed from the air distribution pad **12** will be

directed upward toward the user and so that moisture, such as sweat from the user, will not pass down onto or into the mattress **2**. The cover **22**, **24** can also include an opening **25** through which the air delivery hose **16** can pass.

(19) The upper cover portion **22** can comprise a frame **26** that also comprises a substantially air impermeable and substantially moisture impermeable material, with the frame **26** surrounding an inner air and moisture permeable window **28**. In an example, the lower cover portion **24** and the frame **26** of the upper cover portion **22** can comprise a poly-vinyl chloride (PVC) layer or PVC-coated or polyurethane-backed cloth material, while the air and moisture permeable window **28** can comprise a mesh or screen-like fabric of high air permeability to allow air and moisture to flow freely from the air distribution pad **12** through the window **28**. In an example, the upper cover portion **22** and the lower cover portion **24** can be removably coupled to each other, such as via a zipper around the outer edges of the portions **22**, **24**.

(20) In addition to the active layer **20**, the cover **22**, **24** can also enclose a comfort layer **30** that can provide for added comfort for the user. The comfort layer **30** can be placed on top of the active layer **20**, as shown in FIG. **2**. The comfort layer **30** can comprise a resilient foam material that is air permeable so that air released from the air distribution pad **12** can flow through the comfort layer **30** and the window **28** to the personal space of the user. The comfort layer **30** can also comprise a plurality of passages (not shown) that pass between the upper side and the lower side of the comfort layer **30** in order to allow better airflow through the comfort layer **30**. An example of a foam material that can be used for the comfort layer **30** is a visco-elastic foam, such as a visco-elastic polyurethane polyether foam. The foam of the comfort layer **30** can have a thickness from about 0.25 inches to about 2 inches, such as from about 0.5 inches to about 1.5 inches, for example about $\frac{3}{4}$ inches. The foam can have a density that is selected for a desired firmness or compressibility, such as from about 2 pounds per cubic foot to about 4 pounds per cubic foot, such as about 3 pounds per cubic foot. An example of the foam material that can be used to make the comfort layer **30** is a visco-elastic polyurethane-polyether foam manufactured by Future Foam, Inc., Council Bluffs, IA, USA.

(21) FIGS. **3-5** show additional details of an example active layer **20** that can be used with the example sleep system **10** of the present disclosure. FIG. **3** shows an exploded view of the active layer **20**, FIG. **4** shows a top view of the assembled active layer **20**, and FIG. **5** shows a cross-sectional view of the active layer **20** taken along line 5-5 in FIG. **4**. The active layer **20** can include an internal spacer layer **32** that can be at least partially surrounded or enclosed by an external casing. The external casing can comprise an upper layer **34** and a lower layer **36** that can be joined together, such as by stitching, welding, with a joining structure, and the like. The external casing **34**, **36** can substantially surround and encase the spacer layer **32**. The spacer layer **32** can comprise a structure that permits air to flow relatively freely through the spacer layer **32**, such as a foam or a reticulated engineered material (described in more detail below). The active layer **20** can also comprise an air distributor **38** to distribute incoming air from the air delivery hose **16** throughout the spacer layer **32**, as described in more detail below. The external casing **34**, **36** can substantially encase the air distributor **38** as well, and can leave an opening (not shown) for a port **40** that can receive the air delivery hose **16**.

(22) The spacer layer **32** can include one or more layers of a spacer material that are configured to provide sufficient support to a user sitting or lying on the air distribution pad **12** so that air can flow through the spacer layer **32**, but which is resilient or forgiving enough to be comfortable for the user. In an example, best seen in FIGS. **3** and **5**, the spacer layer **32** comprises two separate layers of spacer material.

(23) As shown in the cross-sectional view of FIG. **5**, each spacer layer **32** (e.g., of two spacer layers **32** shown in the example of FIG. **5**) can comprise an engineered spacer material, such as a spacer material comprising a plurality of resilient fibers **42**. The resilient fibers **42** can be positioned and oriented in the spacer material to provide for resilient support in a direction of compression

D.sub.C that is orthogonal or substantially orthogonal to a plane of the spacer layer **32**. In other words, the fibers **42** can provide resilient support in a direction extending between the upper surface and the lower surface of the active layer **20**. The fibers **42** can be compressed in the compression direction D.sub.C when a force is applied in the compression direction D.sub.C, such as a portion of the weight of a user, but return back to their original shape when the force is removed. The fibers **42** can comprise resilient polymer fibers, such as polyester fibers. An example of a spacer material that can be used in the spacer layer **32** is a 3D spacer fabric having a thickness from about 1/8 inches to about 1 inch, for example about 3/4 inches, such as the 3D spacer fabrics manufactured by Bodet & Horst GmbH & Co. KG, Eiterlein, Germany or Pressless GmbH, Falkenau, Germany, or Welcool Cushion Technology Co., Ltd., Fujian, China.

(24) In an example, the air distribution pad **12** can be configured so that it is “cushion-neutral” to the user, e.g., so that the cushioning effect that is experienced by the user feels the same or substantially the same with the presence of the air distribution pad **12** as it does without the air distribution pad **12**. For example, the active layer **20**, including the spacer layer **32**, can be relatively firm to ensure that air will be able to flow through the spacer layer **32**. The comfort layer **30** can be selected to be relatively soft so that the active layer **20** and the comfort layer **30** can combine to feel neutral. A “cushion-neutral” feel to the air distribution pad **12** can allow a user to add the sleep system **10** to their existing bed without experiencing a change in comfort compared to what the user has grown accustomed. A “cushion-neutral” feel can also allow an adjustable bed, such as the Select Comfort SLEEP NUMBER™ Bed, to have the expected response to adjustment, rather than the adjustment being masked by an overly soft or an overly stiff air distribution pad **12**.

(25) The external casing **34**, **36** can be formed from a material having a relatively low permeability to air so that at least a portion of the air flowing through the spacer layer **32** can permeate through the upper layer **34** to be directed toward a personal area of the user. In an example, the upper layer **34** facing the user can be sufficiently permeable to allow some air to permeate out of the spacer layer **32** through the upper layer **34**, but not so permeable that all of the air being delivered from the air delivery hose **16** permeates through the upper layer **34** before the air can flow through a substantial portion of the length of the active layer **20**. Additional permeability through the upper layer **34** can be achieved due to stitching that can join the upper layer **34** to the lower layer **36**, such as stitching **44** (described in more detail below). The stitching **44** can create small puncture holes in the layers **34**, **36** that can allow air to leak from the spacer layer **32** into the user's personal space. In an example, the upper layer **34** can have a permeability of from about 0.1 ft.sup.3/min/ft.sup.2 to about 10 ft.sup.3/min/ft.sup.2, such as from about 0.5 ft.sup.3/min/ft.sup.2 to about 7 ft.sup.3/min/ft.sup.2, for example about 0.7 ft.sup.3/min/ft.sup.2 (as measured by a standard test method for air permeability of textile fabrics, such as ASTM D737.) In an example, the upper layer **34** can comprise a polyester fabric, such as a 100% polyester, with a urethane laminate backing, such as fabric sold under the trade name Semi Permeable Knit Fabric by Spec-Tex Inc., Coral Springs, FL, USA.

(26) The lower layer **36** can have the same permeability as the upper layer **34**, e.g., can be made from the same material, or the lower layer **36** can have a different permeability. In an example, the lower layer **36** can be substantially air impermeable, or relatively less air permeable than the upper layer **34**, so that air flowing through the spacer layer **32** will tend to permeate through the upper layer **34** toward the user rather than through the lower layer **36** toward the mattress **2**. However, air can be directed through the upper layer **34** rather than the bottom layer **36** due to the bottom cover **24** being made from a substantially air impermeable material.

(27) The upper layer **34** and the lower layer **36** can be joined together at the periphery of the layers **34**, **36**, such as with stitching **35** or fabric tape **37** at the periphery, as shown in FIG. 5. The upper layer **34** and the lower layer **36** can also be joined together at specified locations of the active layer **20** in order to provide channels through the active layer **20** that can direct the flow of air received from the engine **14**. In an example, one or more joining structures **44A**, **44B**, **44C**, **44D**

(collectively referred to herein as “joining structure(s) **44**”), such as stitching, can join the layers **34**, **36** together to form at least one primary channel **46A**, **46B** (collectively referred to herein as “primary channel(s) **46**”) and at least one secondary channel **48**. In an example, the stitching or other joining structures **44** can pass through the spacer layer **32** to join the upper layer **34** and the lower layer **36** together so that the same spacer layer **32** extends throughout substantially the entire active layer **20** (e.g., through the one or more primary channels **46** and the one or more secondary channels **48**).

(28) In an example, the primary channels **46** direct air through the active layer **20** (e.g., through the spacer layer **32**) substantially directly from the air distributor **38**, e.g., such that the only obstacle to air flow between the air distributor **38** and the primary channels **46** are the fibers **42** within the spacer layer **32**. In contrast, the secondary channels **48** can be indirectly connected to the air distributor **38**, e.g., such that an airflow path from the air distributor **38** to a secondary channel **48** passes through a primary channel **46** and through a joining structure **44**, such as stitching.

(29) In an example, the permeability of air between a primary channel **46** and a secondary channel **48** is relatively low, particularly compared to the air permeability through the spacer layer **32** along the primary channels **46**, which can allow the air to flow relatively freely. The secondary channels **48** are not, necessarily, completely devoid of air flowing through the channels **48**. However, in an example, the secondary channels **48** have no large paths for the ingress into or exit from the secondary channels **48**, such that any air flow through a secondary channel **48** can have a substantially smaller flow rate than the air flow through a primary channel **46**. For example, as shown in the example of FIG. 4, one or more of the joining structures **44A**, **44B** can extend along substantially the entire length **L** of the active layer **20** to form a separation between a set of primary channels **46**, e.g., the laterally interior channels **46A** and **46B**, and a set of secondary channels **48**, e.g., the laterally exterior channels **48**. A small amount of air can leak through the joining structures **44A**, **44B** between the primary channels **46A**, **46B** and the secondary channels **48**, as represented by air flow lines **50** in FIGS. 4 and 5, but this air leak flow is considerably smaller and more sporadic than the steady and substantially continuous air flow through the primary channels **46A**, **46B**, as represented by the air flow lines **52** in FIG. 4.

(30) The purpose of splitting the active layer **20** into primary channels **46** and secondary channels **48** is to promote improved or optimum air flow through the active layer **20**. In some examples, the engine **14** will have a limited flow rate that it can generate to push air through the air delivery hose **16**, the air distributor **38**, and the spacer layer **32**, such that if the active layer **20** was not divided into primary channels **46** and secondary channels **48**, the engine **14** might not be able to provide a sufficient flow rate to provide any noticeable heating or cooling effect for the user. The channels **46**, **48** can also be configured so that heated air or cooled air from the engine **14** will be directed to specified locations of the active layer **20** that are expected to have ideal perceived heating or cooling effect to a user.

(31) In an example, shown in FIG. 4, the at least one primary channel **46** can comprise a primary channel **46** located generally laterally centrally in the active layer **20**, with at least one secondary channel **48** on each lateral side of the centrally located primary channel **46**. For the purpose of optimal air flow and temperature distribution across the air distribution pad **12**, the generally centrally located primary channel **46** can be split into two or more sub-channels, such as a middle primary channel **46A** with the lateral side primary channels **46B** on either side of the middle primary channel **46A**, as shown in FIG. 4. The centrally located primary channel **46** (split into sub-channels **46A** and **48B** in FIG. 4) and the secondary channels **48** can be defined by a first joining structure **44A** proximate a first lateral side of the active layer **20** where air is delivered from the hose **16** (e.g., the right side in the view shown in FIG. 4) and a second joining structure **44B** proximate a second lateral side of the active layer **20** opposite the side the air is delivered from (e.g., the left side in FIG. 4). A third joining structure **44C** and a fourth joining structure **44D** can split the centrally located primary channel **46** into a middle primary channel **46A** with two lateral

side primary channels **46B**.

(32) The joining structures **44** can comprise any structure that is capable of reliably joining the upper layer **34** to the lower layer **36**, and in particular to any structure that can join the upper layer **34** to the lower layer **36** to provide for reduced air permeability through the spacer layer **32** across the joining structure **44** so that secondary channels **48** can be formed. Examples of joining structures **44** that can be used include, but are not limited to, fasteners such as staples, brads, pins, and the like, welding (e.g., for plastic or polymer containing layers **34**, **36**), adhesives, and stitching. In an example, the upper layer **34** and the lower layer **36** can both comprise fabric material, as can the spacer layer **32** between layers **34**, **36**, such that stitching can be an inexpensive and desirable joining structure **44**. FIG. 5 shows a cross-sectional view showing a stitching joining structure **44B** between a primary channel **46B** and a secondary channel **48**, and a corresponding stitching joining structure **44D** between a first primary channel **46A** and a second primary channel **46B**. As shown in FIG. 5, the stitching **44** can compress one or more spacer layers **32** between the upper layer **34** and the lower layer **36**. The compression of the spacer layers **32** and the stitching **44** can reduce the air permeability of the spacer material of the spacer layer **32** across the stitching **44**. As discussed above, however, the stitching **44** does not necessarily eliminate the passage of air from a primary channel **46** into a secondary channel **48**, as indicated by the arrows **50**, but the stitching **44** can provide resistance to air flow into the secondary channel **48**.

(33) The channels **46**, **48** can be configured to redirect the direction of air flow of the air received from the air delivery hose **16**, e.g., via the air distributor **38**, from a generally lateral direction to a generally longitudinal direction. The term “lateral,” as used herein, can refer to a direction across the active layer **20** extending along the width W. The term “longitudinal,” as used herein, can refer to a direction along the active layer **20** extending along the length L. As best shown in FIGS. 3 and 4, the port **40** within the air distributor **38** that can receive the air delivery hose **16** can face laterally outward from a side of the active layer **20** so that the hose **16** approaches the active layer **20** from the lateral side. A lateral approach of the air delivery hose **16** can be preferred because many user's beds include a headboard on one longitudinal end of the bed or a footboard on the opposite longitudinal end, and a longitudinal approach of the hose **16** would interfere with the headboard or footboard. However, it can be preferred that the air flow through the air distribution pad **12** be generally longitudinal in direction. Therefore, as best seen in FIG. 4, the laterally-entering air flow can be redirected to a generally longitudinal direction along the primary channel(s) **46**, e.g., by the joining structures **44A**, **44B**, **44C**, and **44D**. As shown in FIG. 4, the configuration of the primary channels **46** (e.g., through the placement of the joining structures **44**) can be such that the air flow is gradually redirected in a continuous or substantially continuous arc into each primary channel **46**.

(34) At least one of the joining structures **44** on a lateral side of the active layer **20** proximate to the air distributor **38** (e.g., joining structures **44A** and **44C** on the right side of the active layer **20** in FIG. 4) can form an acute angle A relative to a longitudinal axis Y of the active layer **20**. At least one of the joining structures **44** on a lateral side opposite the air distributor **38** (e.g., joining structures **44B** and **44D** on the left side of the active layer **20** in FIG. 4) can form an obtuse angle B relative to a lateral axis X of the active layer **20**. In an example, the acute angle A of the first joining structures **44** proximate to the air distributor **38** (e.g., joining structures **44A** and **44C**) can be from about 10° to about 35°, such as from about 20° to about 30°, for example about 23°. In an example, the obtuse angle B of the second joining structures **44** opposite the air distributor **38** (e.g., joining structures **44B** and **44D**) can be from about 90° to about 150°, such as from about 100° to about 135°, for example about 122°. In the example shown in FIG. 4, only the acute angle A on a first joining structure **44A** is shown, but a similar acute angle relative to the longitudinal axis Y (e.g., in the same ranges as acute angle A) can be selected for another joining structure **44C** on the same lateral side proximate the air distributor **38**. Similarly, in the example shown in FIG. 4, only the obtuse angle B on a second joining structure **44B** is shown, but a similar obtuse angle relative

to the lateral axis X (e.g., in the same ranges as obtuse angle B) can be selected for another joining structure **44D** on the same lateral side opposite the air distributor **38**.

(35) The joining structures **44** can also have a shape or shapes, or form a pattern or patterns, that can improve or optimize air flow through the active layer **20** in order to improve or optimize the heating or cooling effect experienced by the user. In an example, at least one of the joining structures **44** on a lateral side of the active layer **20** proximate to the air distributor **38** (e.g., joining structures **44A** and **44C**) can have a generally sinusoidal or “S” shape. As shown in the example of FIG. 4, both joining structures **44A** and **44C** on the lateral side proximate the air distributor **38** have a generally sinusoidal shape. In an example, at least one of the joining structures **44** on a lateral side opposite the air distributor **38** (e.g., joining structures **44B** and **44D** on the left side of the active layer **20** in FIG. 4) can form an arc shape, such as a concave arc with respect to the air distributor **38** (e.g., where a concave side of the arc faces the air distributor **38**). As shown in the example of FIG. 4, both joining structures **44B** and **44D** on the lateral side opposite the air distributor **38** have an arc shape (e.g., concave arc with respect to the air distributor **38**). The configurations of the joining structures **44A**, **44B**, **44C**, **44D** can provide for a desired air flow profile through the primary channels **46A**, **46B**, such as a relatively high volume of air flow through the middle primary channel **46A** and a relative low volume of air flow through each of the side primary channels **46B**.

(36) As shown in FIGS. 3 and 4, the upper layer **34** can include one or more openings **54** that can provide an open path to air flow from the spacer layer **32** out of the active layer **20**, e.g., so that the air flow into the user's personal space can be optimized for cooling or heating performance. Each opening **54** can be positioned over one of the primary channels **46** so that air from the primary channel **46** can exit through the opening **54**. The openings **54** can allow a portion of the air flowing through the spacer layer **32** to more freely exit the active layer **20** at a specified point of the air distribution pad **12**. As described above, although the upper layer **34** can be air permeable, if desired, it can have a relatively low air permeability to ensure that a portion of the air delivered from the air delivery hose **16** continues to flow down a substantial portion of the length of the primary channels **46**. One reason for providing for air flow down the primary channels **46** is to provide for convective cooling of the material of the upper layer **34**, which can then provide for convective cooling, conductive cooling, or both of the user through the upper layer **34** (which may need to occur through one or more other layers, such as the comfort layer **30** and the upper cover portion **22**). The one or more openings **54** can allow for a portion of the air flowing through the active layer **20** to pass into the personal space of the user, which can provide for one or more of conductive, convective, or evaporative cooling of the user. The openings **54** can be located at a position of the active layer **20** where it can be desired to have increased convective cooling or evaporative cooling, or both, for the user.

(37) The features of the upper layer **34** of the active layer **20** have been described in some detail. However, as will be appreciated, the lower layer **36** can have similar features to those described above for the upper layer **34**. For example, the lower layer **36** can also be air permeable (as described above), and the joining structures **44** can be joined to the lower layer **36** as well as the upper layer **34**. Similarly, the lower layer **36** can also include openings **60**, which can be similar or identical to openings **54** in the upper layer **34**. In an example, the upper layer **34** and the lower layer **36** can be configured to be substantially mirror images of each other. Mirror-image upper and lower layers **36**, **38** can provide for several benefits to the active layer **20** and resulting air distribution pad **12**. First, on a single-person bed (e.g., a standard twin- or long twin-sized bed), or on the same side of a two-person bed (e.g., a queen- or king-sized), the active layer **20** can be flipped in the longitudinal direction (e.g., about the lateral axis X) so that the position of the openings **60** will be at a different point relative to the user than openings **54** were. For example, if the openings **54** are at about two-thirds and about three-quarters of the length L from the top (e.g., the first end **56**), when the active layer **20** is flipped, the openings **60** will be about one-quarter and

about one-third of the length L from the new top end, which is now the second end **58**. The air exiting the openings **60** will thus be encountered by the user near the user's upper torso, in contrast to the air from openings **54** when the active layer **20** has not been flipped which could be felt around the upper legs.

(38) In addition, if the upper layer **34** and the lower layer **36** are mirror images of each other, the active layer **20** can be flipped laterally (e.g., about the longitudinal axis Y) so that the active layer **20** can be used on the opposite side of a two-person bed. In this way, a pair of active layers **20**, and resulting air distribution pads **12**, that are each sized for a single person can be placed on a single two-person bed (e.g., a queen- or king-sized bed). Each of the pair of active layers **20** and resulting air distribution pads **12** can be individually controlled, such as with separate engines **14**, so that each individual user on the two-person bed can control their own personal comfort level independent of the other user on the bed. For example, if the two-person bed is being used by spouses, one spouse can have a relatively cool temperature setting, while the other spouse can have a relatively warm temperature setting.

(39) FIGS. **6** and **7** show an example of an air distributor **38** and the air delivery hose **16** that can be used with the active layer **20** and resulting air distribution pad **12** of the present disclosure. FIG. **6** shows a perspective view with the air distributor **38** and air delivery hose **16** assembled, while FIG. **7** shows an exploded view of the components of the air distributor **38** and the air delivery hose **16**. The air distributor **38** can include a manifold **62** that is connectable to the hose **16**. The manifold **62** can receive air from the hose **16** and can be configured to distribute the air to the spacer layer **32**. The manifold **62** can be positioned inside the active layer **20**, such as within a corresponding cavity in the spacer layer **32**.

(40) The manifold **62** can comprise a bracket **64** and a pair of wings **66**. The wings **66** can be coupled to the bracket **64** so that the wings **66** are vertically separated from one another, leaving an air gap in the active layer **20** for the air flow to encounter immediately after being delivered to the active layer **20** from the air delivery hose **46**. The air gap between the wings **66** can feed the delivered air to the spacer layer **32**, such as to the space among the fibers **42** of the spacer material of the spacer layer **32**. The wings **66** can have a generally tear-drop shape to provide for air flow into the primary channels **46**.

(41) In an example, each of the wings **66** comprise a spacer material similar or identical to the spacer material of the spacer layer **32**. The wings **66** can be coupled or otherwise connected to the spacer material **32** to maintain the vertical spacing. The manifold **62** can be enclosed by the upper layer **34** and the lower layer **36** of the active layer **20**. As described above, in an example, shown in FIG. **5**, the spacer layer **32** can have a first thickness. Each of the wings **66** can comprise a single layer of spacer material having a second thickness that is less than or equal to the first thickness of the spacer layer **32**. Air can flow from the hose **16**, through the port **40**, and into the bracket **64**. The air can then flow either between the wings **66**, through the spacer material of the wings **66**, or both, and then into the spacer layer **32** in order to pass longitudinally along the active layer **20** through the primary channels **46**.

(42) FIGS. **8** and **9** show an example of another active layer **70** that can be used in the air distribution pad **12** of the present disclosure. FIG. **8** shows an exploded view of the active layer **70**, while FIG. **9** shows a top view of the assembled active layer **70**. The active layer **70** shown in the examples of FIGS. **8** and **9** can be similar to the active layer **20** describe above with respect to FIGS. **3-5**. For example, the active layer **70** can include an internal spacer layer **72**, similar to the spacer layer **32** of the active layer **20**. The spacer layer **72** can be at least partially surrounded or enclosed by an external casing, such as an upper layer **74** and a lower layer **76** that can be joined together, such as by stitching, welding, with a joining structure, and the like. The casing layers **74**, **76** can substantially surround and encase the spacer layer **72**.

(43) Like the spacer layer **32**, the spacer layer **72** of the active layer **70** can comprise a structure that permits air to flow relatively freely through the spacer layer **72**, such as a foam or a reticulated

engineered material, as described above. The active layer **70** can also comprise an air distributor **78**, which can be similar to the air distributor **38** described above, to distribute incoming air from the air delivery hose **16** throughout the spacer layer **72**. The casing layers **74**, **76** can substantially encase the air distributor **78** as well, and can leave an opening (not shown) for a port that can receive the air delivery hose **16**.

(44) As shown in the example of FIGS. **8** and **9**, the air distributor **78** can be located generally at the longitudinal middle of the active layer **70**, rather than proximate a longitudinal end **56**, as in the example of FIGS. **3** and **4**. In an example, the air distributor **78** can be located within the active layer **70** so that the air distributor **78** can be located generally at a pivot point of an adjustable bed or at a location of the mattress that is not raised or lower when the bed is adjusted. For example, the active layer **70** can be configured so that a first portion **80A** on a first side of the air distributor **78** (e.g., above the air distributor **78** in FIG. **9**) so that the first portion **80A** can be positioned over a first articulating section of an adjustable bed, such as a torso or head section of the adjustable bed. The active layer **70** can also include a second portion **80B** on a second side of the air distributor **78** (e.g., below the air distributor **78** in FIG. **9**) that can be positioned over a second articulating section of the adjustable bed, such as a leg or foot section of the adjustable bed. The air distributor **78** can be located within a third portion **80C** of the active layer **70**, which can be positioned over a non-articulating third section of the adjustable bed, such as over a middle or seat portion of the adjustable bed. Positioning the air distributor **78** over a non-articulating portion of an adjustable bed can be desirable, because the air distributor **78** will not be raised or lowered, which could, in turn, raise and lower a heating or cooling engine connected to the air distributor **78** via the hose **16**.

(45) Like the upper layer **34** and the lower layer **36** of the active layer **20**, the upper layer **74** and the lower layer **76** of the active layer **70** can be joined together at the periphery of the layers **74**, **76**, such as with stitching or fabric tape at the periphery. The upper layer **74** and the lower layer **76** can also be joined together with one or more joining structures **82A**, **82B**, **82C**, **82D** (collectively referred to herein as “joining structures **82**”), such as stitching. The stitching or other joining structures **82** can pass through the spacer layer **72** to join the upper layer **74** and the lower layer **76** together so that the same spacer layer **72** extends throughout substantially the entire active layer **70**. The joining structures **82** can provide channels through the active layer **70** that can direct the flow of air received from the engine **14**. The one or more joining structures **82** can join the layers **74**, **76** together to form at least one primary channel **84** and at least one secondary channel **86A**, **86B** (collectively referred to herein as “secondary channel(s) **86**”).

(46) Like the primary channels **46** described above, the primary channels **84** can direct air through the active layer **70** (e.g., through the spacer layer **72**) substantially directly from the air distributor **78**, e.g., such that the only obstacle to air flow between the air distributor **78** and the primary channels **84** are the fibers or other structures that form the spacer layer **72**. In contrast, the secondary channels **86** can be indirectly connected to the air distributor **78**, e.g., such that an airflow path from the air distributor **78** to a secondary channel **86** passes through a primary channel **84** and through a joining structure **82**, such as stitching.

(47) Like the exemplary primary channels **46** and secondary channels **48** described above, the permeability of air between a primary channel **84** and a secondary channel **86** in the example of FIGS. **8** and **9** can be relatively low, particularly compared to the air permeability through the spacer layer **72** along the primary channels **84**, which can allow the air to flow relatively freely. The secondary channels **86** are not, necessarily, completely devoid of air flowing through the channels **86**. However, in an example, the secondary channels **86** have no large paths for the ingress into or exit from the secondary channels **86**, such that any air flow through a secondary channel **86** can have a substantially smaller flow rate than the air flow through a primary channel **84**. A small amount of air can leak through the joining structures **82A** and **82B** between the primary channels **84** and the secondary channels **86**, but this air leak flow can be considerably smaller and more sporadic than the steady and substantially continuous air flow through the primary channels **84**.

(48) As shown in the example shown in FIG. 9, the primary channels **84** can include a first set of primary channels **84** located in the first portion **80A** on the first side of the air distributor **78** and a second set of primary channels **84** located in the second portion **80B** on the second side of the air distributor **78**. The air distributor **78** can direct air longitudinally toward the first portion **80A** and toward the second portion **80B**. Similarly, the secondary channels **86** can include a first set of secondary channels **86** located within the first portion **80A** and a second set of secondary channels **86** located within the second portion **80B** of the active layer **70**. Similar to the primary channels **46** and second channels **48** described above, the primary channels **84** can comprise one or more generally laterally- and centrally-located primary channels **84** with at least one secondary channel **86** on each lateral side of the centrally located primary channels **84**. The generally centrally located primary channel **84** can be split into two or more sub-channels. The centrally located primary channel **84** and the secondary channels **86** can be defined by a first joining structure **82A** proximate to a side in which air enters the air distributor **78** from the air hose **16**, with one first joining structure **82A** on each longitudinal side of the air distributor **78**. The primary channels **84** and the secondary channels **86** can also be defined by a second joining structure **82B** on a lateral side oppose from the side in which air enters the air distributor **78** from the air hose **16**. A pair of third joining structures **44C** and a pair of fourth joining structures **44D**, each having one on either longitudinal side of the air distributor **78**, can further split the centrally located primary channel **84** into a middle primary channel with two lateral side primary channels.

(49) As with the joining structures **44** described above, the joining structures **82** can comprise any structure that is capable of reliably joining the upper layer **74** to the lower layer **76**, and in particular to any structure that can join the upper layer **74** to the lower layer **76** to provide for reduced air permeability through the spacer layer **72** across the joining structure **82** so that secondary channels **86** can be formed. Like joining structures **44**, the joining structures **82** can include one or more of fasteners such as staples, brads, pins, and the like, welding (e.g., for plastic or polymer containing layers **74**, **76**), adhesives, and stitching.

(50) As with the channels **46**, **48**, described above, the channels **84**, **86** can be configured to redirect the direction of air flow of the air received from the air delivery hose **16**, e.g., via the air distributor **78**, from a generally lateral direction to a generally longitudinal direction. As shown in FIG. 9, the configuration of the primary channels **84** (e.g., through the placement of the joining structures **82**) can be such that the air flow is gradually redirected in a continuous or substantially continuous arc into each primary channel **84**.

(51) As shown in FIGS. 8 and 9, the upper layer **74** can include one or more openings **88** that can provide an open path to air flow from the spacer layer **72** out of the active layer **70**, e.g., so that the air flow into the user's personal space can be optimized for cooling or heating performance. The openings **88** shown in the example of FIGS. 8 and 9 comprise a plurality of small openings **88** scattered substantially over the entire surface of the upper layer **74**, with each opening **88** having a relatively small size, such as a diameter of from about 1 mm to about 10 mm, such as from about 3 mm to about 8 mm, for example about 5 mm. In contrast, the openings **54** shown in FIGS. 3 and 4 can have a relatively large size, such as a diameter of from about 10 mm to about 60 mm, for example from about 20 mm to about 40 mm, such as about 30 mm. The relatively large-sized openings **54** can provide for more concentrated air flow, and thus more concentrated cooling, at the specific locations of the opening **54**. The relatively smaller-sized openings **88** can provide for a smaller air flow rate from each opening **88**, but can allow for more disperse distribution of air being directed out of the spacer layer **72** while still providing for adequate air flow longitudinally along the spacer layer **72**. An active layer can use any combination of relatively-large openings, such as openings **54**, and relatively-small openings, such as openings **88**, that are desired. The one or more openings **88** can allow for air flowing through the active layer **70** to be distributed over a large area of the personal space of the user, which can provide for one or more of conductive, convective, or evaporative cooling of the user. In addition to the openings **88** in the upper layer **74**, the active layer

70 can also include a plurality of openings 90 in the lower layer 76 (FIG. 8).

(52) The use of an active layer 70 with an air distributor 78 located at a middle portion 80C of the active layer 70 with a first set of one or more primary channels 84 on a first longitudinal side of the air distributor 78 and a second set of one or more primary channels 84 on a second longitudinal side of the air distributor 78 can provide for advantages over an active layer 20 with an air distributor 28 proximate a longitudinal end 56 of the active layer 20. For example, the active layer 70 can provide for better thermal performance because the air does not have to travel as far from the air distributor 78 before reaching an end of the primary channels 84. As will be appreciated, cooled air can become heated generally proportionally to the distance that the air travels from the air distributor 78 (and similarly heated air can become cooled generally proportionally to the distance that the air travels from the air distributor 78), so that reducing the distance the air must travel can improve the heating or cooling performance of the air being delivered to the active layer 70. Further, as described above, the active layer 70 can be used with an adjustable bed without the air distributor 78 (and thus the air hose 16 or engine) being raised or lowered by the articulation of sections of the bed. Finally, the use of the active layer 70 with an air distributor 78 located in a longitudinal middle portion, rather than proximate a head end 56 of the active layer 20, can result in a user subjectively feeling that the system is quieter, because the sound-generating source (e.g., the engine 14), is located more remotely from the user's head, and because the air distributor 78 will not be located directly underneath or proximate to a pillow being used by the user.

(53) To better illustrate the present air distribution pad and system of the present disclosure, a non-limiting list of Examples is provided here: Example 1 can include subject matter (such as an apparatus, a device, a method, or one or more means for performing acts), such as can include an air distribution pad. The subject matter can comprise an upper layer, a lower layer, and a spacer material located between the upper layer and the lower layer, the spacer material configured to allow air to pass therethrough. An air distributor can be configured to distribute air to the spacer material, wherein the air distributor comprises a port configured to receive an air hose, wherein the port is directed laterally sideways from the air distributor. At least one joining structure can be coupled to the upper layer and the lower layer, the at least one joining structure providing one or more channels formed through the spacer material in fluid communication with the air distributor, wherein the one or more channels are configured to direct generally laterally flowing air from the port of the air distributor to a generally longitudinal direction along the at least one channel. Example 2 can include, or can optionally be combined with the subject matter of Example 1, to optionally include at least one of the upper layer and the lower layer defining one or more openings in communication with the one or more channels. Example 3 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1 and 2, to optionally include a first joining structure being on a first lateral side of the spacer material proximate the air distributor, and a second joining structure being on a second lateral side of the spacer material opposite the air distributor. Example 4 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-4, to optionally include a portion of the first joining structure proximate a first longitudinal end of the spacer material proximate the air distributor forming an acute angle relative to a longitudinal axis of the spacer material. Example 5 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-4, to optionally include a portion of the second joining structure proximate the first longitudinal end of the spacer material forming an obtuse angle relative to a lateral axis of the spacer material. Example 6 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-5, to optionally include the first joining structure forming a sinusoidal shape along the longitudinal direction. Example 7 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-6, to optionally include the second joining structure forming an arc shape along the longitudinal direction. Example 8 can include, or can optionally be combined with the subject matter of one or any combination of

Examples 1-7, to optionally include the at least one joining structure further comprising a third joining structure spaced laterally inward from the first joining structure. Example 9 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-8, to optionally include the at least one joining structure comprising a fourth joining structure spaced laterally inward from the second joining structure. Example 10 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-9, to optionally include the first joining structure and the third joining structure each forming a sinusoidal shape along the longitudinal direction. Example 11 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-10, to optionally include the second joining structure and the fourth joining structure each forming an arc shape along the longitudinal direction. Example 12 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-11, to optionally include at least one of the upper layer and the lower layer defining one or more first openings between the first joining structure and the third joining structure. Example 13 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-12, to optionally include at least one of the upper layer and the lower layer defining one or more second openings between the second joining structure and the fourth joining structure. Example 14 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-13, to optionally include at least one of the upper layer and the lower layer defining one or more third openings between the third joining structure and the fourth joining structure. Example 15 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-14, to optionally include the at least one joining structure comprising stitching between the upper layer and the lower layer, the stitching extending through the spacer material. Example 16 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-15, to optionally include a configuration of the upper layer being substantially a mirror image of a configuration of the lower layer. Example 17 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-16, to optionally include a comfort layer, wherein the combination of the comfort layer and the spacer material provides a cushion-neutral feel for a user. Example 18 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-17, to include subject matter (such as an apparatus, a device, a method, or one or more means for performing acts), such as can include an air distribution pad. The subject matter can comprise an upper layer, a lower layer, and a spacer material located between the upper layer and the lower layer, the spacer material configured to allow air to pass therethrough. An air distributor can be configured to distribute air to the spacer material, wherein the air distributor comprises a port configured to receive an air hose. Stitching can couple the upper layer and the lower layer and can extend through the spacer material. The stitching can provide one or more channels formed through the spacer material in fluid communication with the air distributor. At least one of the top layer and the bottom layer can define one or more openings in communication with the one or more channels. The one or more channels can be configured to direct air from the air distributor along the one or more channels and out of the one or more openings. Example 19 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-18, to optionally include the port in the air distributor being directed laterally sideways, and the one or more channels are configured to direct generally laterally flowing air from the port to a generally longitudinal direction along the at least one channel. Example 20 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-19, to optionally include the stitching comprising a first line of stitching on a first lateral side of the spacer material proximate the air distributor. Example 21 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-20, to optionally include the stitching comprising a second line of stitching on a second lateral side of the spacer material opposite the air distributor. Example 22 can include, or can optionally be combined with the subject matter of one

or any combination of Examples 1-21, to optionally include a portion of the first line of stitching proximate a first longitudinal end of the spacer material proximate the air distributor forming an acute angle relative to a longitudinal axis of the spacer material. Example 23 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-22, to optionally include a portion of the second line of stitching proximate the first longitudinal end of the spacer material forming an obtuse angle relative to a lateral axis of the spacer material. Example 24 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-23, to optionally include the first line of stitching forming a sinusoidal shape along the longitudinal direction. Example 25 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-24, to optionally include the second line of stitching forming an arc shape along the longitudinal direction. Example 26 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-25, to optionally include the stitching further comprising a third line of stitching spaced laterally inward from the first joining structure. Example 27 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-26, to optionally include the stitching further comprising a fourth line of stitching spaced laterally inward from the second joining structure. Example 28 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-27, to optionally include the first line of stitching and the third line of stitching each forming a sinusoidal shape along the longitudinal direction. Example 29 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-28, to optionally include the second line of stitching and the fourth line of stitching each forming an arc shape along the longitudinal direction. Example 30 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-29, to optionally include at least one of the upper layer and the lower layer defining one or more first openings between the first line of stitching and the third line of stitching. Example 31 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-30, to optionally include at least one of the upper layer and the lower layer defining one or more second openings between the second line of stitching and the fourth line of stitching. Example 32 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-31, to optionally include at least one of the upper layer and the lower layer defining one or more third openings between the third line of stitching and the fourth line of stitching. Example 33 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-32, to optionally include a configuration of the upper layer being substantially a mirror image of a configuration of the lower layer. Example 34 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-33, to optionally include a comfort layer, wherein the combination of the comfort layer and the spacer material provides a cushion-neutral feel for a user. Example 35 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-34, to include subject matter (such as an apparatus, a device, a method, or one or more means for performing acts), such as can include an air distribution system. The subject matter can comprise an air distribution pad including an upper layer, a lower layer, and a spacer material located between the upper layer and the lower layer, the spacer material configured to allow air to pass therethrough. The air distribution pad can further include an air distributor configured to distribute air to the spacer material, wherein the air distributor comprises a port. The air distribution pad can further include stitching, coupling the upper layer and the lower layer and extending through the spacer material, the stitching providing one or more channels formed through the spacer material in fluid communication with the air distributor. The one or more channels can be configured to direct air from the air distributor along the one or more channels. The system can further include an engine configured to perform at least one of heating air or cooling air and an air deliver hose with a first end coupleable to the engine and a second end coupleable to the port of the air distributor. Example

36 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-35, to optionally include the port in the air distributor being directed laterally sideways, and the one or more channels being configured to direct generally laterally flowing air from the port to a generally longitudinal direction along the at least one channel. Example 37 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-36, to optionally include at least one of the upper layer and the lower layer defining one or more openings in communication with the one or more channels. Example 38 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-37, to optionally include the stitching comprising a first line of stitching on a first lateral side of the spacer material proximate the air distributor. Example 39 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-38, to optionally include the stitching comprising a second line of stitching on a second lateral side of the spacer material opposite the air distributor. Example 40 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-39, to optionally include a portion of the first line of stitching proximate a first longitudinal end of the spacer material proximate the air distributor forming an acute angle relative to a longitudinal axis of the spacer material. Example 41 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-40, to optionally include a portion of the second line of stitching proximate the first longitudinal end of the spacer material forming an obtuse angle relative to a lateral axis of the spacer material. Example 42 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-41, to optionally include the first line of stitching forming a sinusoidal shape along the longitudinal direction. Example 43 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-42, to optionally include the second line of stitching forming an arc shape along the longitudinal direction. Example 44 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-43, to optionally include the stitching further comprising a third line of stitching spaced laterally inward from the first joining structure. Example 45 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-44, to optionally include the stitching further comprising a fourth line of stitching spaced laterally inward from the second joining structure. Example 46 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-45, to optionally include the first line of stitching and the third line of stitching each forming a sinusoidal shape along the longitudinal direction. Example 47 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-46, to optionally include the second line of stitching and the fourth line of stitching each forming an arc shape along the longitudinal direction. Example 48 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-47, to optionally include at least one of the upper layer and the lower layer defining one or more first openings between the first line of stitching and the third line of stitching. Example 49 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-48, to optionally include at least one of the upper layer and the lower layer defining one or more second openings between the second line of stitching and the fourth line of stitching. Example 50 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-49, to optionally include at least one of the upper layer and the lower layer defining one or more third openings between the third line of stitching and the fourth line of stitching. Example 51 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-50, to optionally include the engine comprising a thermoelectric heating and cooling device. Example 52 can include, or can optionally be combined with the subject matter of one or any combination of Examples 1-51, to optionally include a configuration of the upper layer of the air distribution pad being substantially a mirror image of a configuration of the lower layer of the air distribution pad. Example 53 can include, or can optionally be

combined with the subject matter of one or any combination of Examples 1-52, to optionally include the air distribution pad further comprising a comfort layer, wherein the combination of the comfort layer and the spacer material provides a cushion-neutral feel for a user.

(54) The above Detailed Description is intended to be illustrative, and not restrictive. For example, the above-described examples (or one or more elements thereof) can be used in combination with each other. Other embodiments can be used, such as by one of ordinary skill in the art upon reviewing the above description. Also, various features or elements can be grouped together to streamline the disclosure. This should not be interpreted as intending that an unclaimed disclosed feature is essential to any claim. Rather, inventive subject matter can lie in less than all features of a particular disclosed embodiment. Thus, the following claims are hereby incorporated into the Detailed Description, with each claim standing on its own as a separate embodiment. The scope of the invention should be determined with reference to the appended claims, along with the full scope of equivalents to which such claims are entitled.

(55) In the event of inconsistent usages between this document and any documents so incorporated by reference, the usage in this document controls.

(56) In this document, the terms “a” or “an” are used, as is common in patent documents, to include one or more than one, independent of any other instances or usages of “at least one” or “one or more.” In this document, the term “or” is used to refer to a nonexclusive or, such that “A or B” includes “A but not B,” “B but not A,” and “A and B,” unless otherwise indicated. In this document, the terms “including” and “in which” are used as the plain-English equivalents of the respective terms “comprising” and “wherein.” Also, in the following claims, the terms “including” and “comprising” are open-ended, that is, a system, device, article, composition, formulation, or process that includes elements in addition to those listed after such a term in a claim are still deemed to fall within the scope of that claim. Moreover, in the following claims, the terms “first,” “second,” and “third,” etc. are used merely as labels, and are not intended to impose numerical requirements on their objects.

(57) Method examples described herein can be machine or computer-implemented, at least in part. Some examples can include a computer-readable medium or machine-readable medium encoded with instructions operable to configure an electronic device to perform methods or method steps as described in the above examples. An implementation of such methods or method steps can include code, such as microcode, assembly language code, a higher-level language code, or the like. Such code can include computer readable instructions for performing various methods. The code may form portions of computer program products. Further, in an example, the code can be tangibly stored on one or more volatile, non-transitory, or non-volatile tangible computer-readable media, such as during execution or at other times. Examples of these tangible computer-readable media can include, but are not limited to, hard disks, removable magnetic disks, removable optical disks (e.g., compact disks and digital video disks), magnetic cassettes, memory cards or sticks, random access memories (RAMs), read only memories (ROMs), and the like.

(58) The Abstract is provided to comply with 37 C.F.R. § 1.72(b), to allow the reader to quickly ascertain the nature of the technical disclosure. It is submitted with the understanding that it will not be used to interpret or limit the scope or meaning of the claims.

(59) Although the invention has been described with reference to exemplary embodiments, workers skilled in the art will recognize that changes may be made in form and detail without departing from the spirit and scope of the invention.

Claims

1. An air distribution pad, comprising: an upper layer, a lower layer, and a spacer material located between the upper layer and the lower layer, the spacer material having a plurality of resilient support fibers configured to provide support in compression and configured to allow air to pass

therethrough; an air distributor configured to distribute air to the spacer material, wherein the air distributor comprises a port configured to receive an air hose; and at least one joining structure coupled to the upper layer and the lower layer and extending through the spacer material, the at least one joining structure providing one or more channels formed through the spacer material in fluid communication with the air distributor; wherein the one or more channels are configured to direct flowing air from the port of the air distributor along at least one of the one or more channels, and wherein the at least one joining structure comprises welding that couples the upper layer and the lower layer and extends through the spacer material, the welding configured to pull the upper layer and lower layer at least partially together to at least partially compress the spacer material and providing the one or more channels formed through the spacer material in fluid communication with the air distributor.

2. The air distribution pad according to claim 1, wherein the upper layer defines one or more openings in communication with the one or more channels.

3. The air distribution pad according to claim 1, wherein a first joining structure is on a first lateral side of the spacer material proximate the air distributor, and a second joining structure is on a second lateral side of the spacer material opposite the air distributor.

4. The air distribution pad according to claim 3, wherein the first joining structure forms a sinusoidal shape along a longitudinal direction and the second joining structure forms an arc shape along the longitudinal direction.

5. The air distribution pad according to claim 1, wherein a configuration of the at least one joining structure at the upper layer is substantially a mirror image of a configuration of the at least one joining structure at the lower layer.

6. The air distribution pad according to claim 1, further comprising a comfort layer, wherein the combination of the comfort layer and the spacer material provides a cushion-neutral feel for a user.

7. The air distribution pad according to claim 1, wherein the lower layer comprises an air impermeable material.

8. The air distribution pad according to claim 3, wherein a portion of the first joining structure proximate a first longitudinal end of the spacer material proximate the air distributor forms an acute angle relative to a longitudinal axis of the spacer material and a portion of the second joining structure proximate the first longitudinal end of the spacer material forms an obtuse angle relative to a lateral axis of the spacer material.

9. The air distribution pad according to claim 1, wherein the air distribution pad has a head area near a head of the air distribution pad, a foot area near a foot of the air distribution pad, and a central area between the head area and the foot area, wherein the air distributor is positioned at the central area of the air distribution pad, wherein the welding comprises a first length of welding extending from the central area to the head area and having a first curved shape, wherein the welding comprises a second length of welding extending from the central area to the foot area and having a second curved shape that curves differently than the first curved shape of the first length of welding, and wherein at least part of the central area has no welding between ends of the first length of welding and the second length of welding.

10. An air distribution pad, comprising: an upper layer, a lower layer, and a spacer material located between the upper layer and the lower layer, the spacer material configured to allow air to pass therethrough; an air distributor configured to distribute air to the spacer material, wherein the air distributor comprises a port configured to receive an air hose; and welding coupling the upper layer with the lower layer and extending through the spacer material, the welding configured to pull the upper layer and lower layer at least partially together to at least partially compress the spacer material and providing one or more channels between the upper layer and the lower layer, wherein the upper layer defines openings in fluid communication with the one or more channels, wherein the one or more channels are configured to direct air from the air distributor along the one or more channels and out of the openings.

11. The air distribution pad according to claim 10, wherein the port in the air distributor is directed laterally sideways, and the one or more channels are configured to direct generally laterally flowing air from the port to a generally longitudinal direction along the one or more channels.
 12. The air distribution pad according to claim 10, wherein the welding comprises a first line of welding on a first lateral side of the spacer material proximate the air distributor, and a second line of welding on a second lateral side of the spacer material opposite the air distributor, wherein a portion of the first line of welding proximate a first longitudinal end of the spacer material proximate the air distributor forms an acute angle relative to a longitudinal axis of the spacer material and a portion of the second line of welding proximate the first longitudinal end of the spacer material forms an obtuse angle relative to a lateral axis of the spacer material.
 13. The air distribution pad of claim 10, further comprising means for directing air into an inlet of the air distribution pad.
 14. A fluid distribution pad comprising: an upper layer configured to be positioned nearer a user resting on the fluid distribution pad; a lower layer configured to be positioned nearer a mattress; a spacer layer located between the upper layer and the lower layer, the spacer layer configured to at least partially resist compression and to allow fluid to pass therethrough; an inlet configured to allow fluid from outside the fluid distribution pad to flow into the spacer layer; and one or more fasteners comprising welding between the upper layer and the lower layer that couple the upper layer with the lower layer extending through the spacer layer, the one or more fasteners pulling a portion of the upper layer and a portion of the lower layer, proximal to the one or more fasteners, towards one another through the spacer layer, the one or more fasteners arranged such that a plurality of fluid channels is formed, the fluid channels defined by an inner surface of the upper layer, an inner surface of the lower layer, and the portions of the upper layer and the lower layer proximal to the one or more fasteners, the fluid channels being at least partially supported by the spacer layer.
 15. The fluid distribution pad of claim 14, wherein the one or more fasteners pull the portion of the upper layer and the portion of the lower layer, proximal to the one or more fasteners, towards one another sufficiently so that the portions touch one another through the spacer layer.
 16. The fluid distribution pad of claim 14, further comprising means for directing air into the inlet of the fluid distribution pad.
 17. The fluid distribution pad of claim 14, wherein the upper layer defines one or more openings in fluid communication with the one or more channels.
 18. The fluid distribution pad of claim 14, wherein a first portion of the welding forms a sinusoidal shape along a longitudinal direction and a second portion of the welding forms an arc shape along the longitudinal direction.
 19. The fluid distribution pad of claim 14, wherein a configuration of the welding at the upper layer is substantially a mirror image of a configuration of the welding at the lower layer.
 20. The fluid distribution pad of claim 14, further comprising a comfort layer, wherein the combination of the comfort layer and the spacer provides a cushion-neutral feel for a user.
-