

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12391467
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Conlon; Richard et al.

Modular loading system for a shipping container

Abstract

A modular loading system may include structural beams and modular beams that can be located in a shipping container. The structural beams can be arranged in a first direction, and the modular beams can be arranged in a second direction that is approximately perpendicular to the first direction. The structural beams can include a fixed contact surface and an adjustable contact surface positioned opposite the fixed contact surface for stabilizing the modular loading system in approximately the first direction. The modular beams can include receiving notches sized to receive a locking bar for stabilizing the modular loading system in a third direction that is approximately perpendicular to the first direction and the second direction.

Inventors: Conlon; Richard (London, GB), McNamara; Graham (Cranford, NJ), Willson; Brent (Price, UT), Murphey; Kevin (London, GB)

Applicant: IRON MOUNTAIN INCORPORATED (Boston, MA)

Family ID: 1000008767317

Assignee: Iron Mountain Incorporated (Boston, MA)

Appl. No.: 18/342242

Filed: June 27, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250002246 A1	Jan. 02, 2025

Publication Classification

Int. Cl.: B65D90/04 (20060101); B65D90/00 (20060101)

U.S. Cl.:

CPC **B65D90/041** (20130101); **B65D90/0053** (20130101); B65D2590/0041 (20130101);
B65D2590/04 (20130101)

Field of Classification Search

CPC: B65D (90/041); B65D (90/0053); B65D (2590/0041); B65D (2590/04); B65D
(2590/0066); B65D (2590/005); B65D (88/129); B65D (90/004); B65D (90/0046); B65D
(90/006)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3114336	12/1962	Schroeder	410/149	B60P 7/15
3647080	12/1971	Denny	108/901	A47B 47/027
3963290	12/1975	Rennemann	312/351	B65D 90/0053
4030611	12/1976	Konstant	211/182	A47B 57/485
6726041	12/2003	Dunn	206/335	B65D 19/12
6776298	12/2003	Courtwright	211/183	B65G 1/026
2002/0130099	12/2001	Rene et al.	N/A	N/A
2005/0000834	12/2004	Clive-Smith	206/335	B65D 88/129
2006/0033359	12/2005	Taylor	296/182.1	B60P 3/14
2014/0190964	12/2013	Skeid	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3046250	12/1981	DE	N/A
4341230	12/1994	DE	N/A
29708856	12/1997	DE	N/A
2933207	12/2014	EP	N/A
2894901	12/2006	FR	N/A
2967982	12/2011	FR	N/A
1504983	12/1977	GB	N/A
2543044	12/2016	GB	N/A
387314	12/1975	SE	N/A
9955601	12/1998	WO	N/A

OTHER PUBLICATIONS

Application No. EP24183939.8, Extended European Search Report, Mailed on Nov. 11, 2024, 9
pages. cited by applicant

Primary Examiner: Braden; Shawn M

Attorney, Agent or Firm: Kilpatrick Townsend & Stockton LLP

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates generally to containers and, more particularly (although not necessarily exclusively), to modular loading systems for shipping containers.

BACKGROUND

(2) Items, such as artwork, consumer goods, natural resources, and the like, can be produced in various locations throughout the world. In some instances, an end user may in a first location may desire a first item that is produced or otherwise positioned in a second location that may be far away (e.g., tens of miles, hundreds of miles, thousands of miles, or the like) from the first location. Transporting the item from the second location to the first location without causing damage to the item may be technically challenging. For example, packing the item in a shipping container may cause damage, whether during a packing operation, during transport, and the like, to the item. Additionally, other techniques for transporting the item may produce excessive amounts of carbon emissions that may be harmful to the environment.

SUMMARY

(3) In some embodiments, a modular loading system can include a set of structural beams and a set of modular beams. The set of structural beams can be positioned in a shipping container and can be spaced apart and arranged in a first direction. At least one structural beam of the set of structural beams can include a fixed contact surface and an adjustable contact surface. The fixed contact surface can be located on a first end of the at least one structural beam. The adjustable contact surface can be located on a second end of the at least one structural beam that can be located opposite the first end. The fixed contact surface and the adjustable contact surface can be configured to apply pressure to an inside surface of the shipping container to stabilize the modular loading system in approximately the first direction. The set of modular beams can be spaced apart and arranged in a second direction that is nonparallel to the first direction. Each modular beam of the plurality of modular beams can be coupled with each structural beam of the plurality of structural beams at one or more connection points.

(4) In other embodiments, a system can include a shipping container and a modular loading system that can be positioned in the shipping container and can be removed from the shipping container. The modular loading system can include a set of structural beams and a set of modular beams. The set of structural beams can be positioned in the shipping container and can be spaced apart and arranged in a first direction. At least one structural beam of the set of structural beams can include a fixed contact surface and an adjustable contact surface. The fixed contact surface can be located on a first end of the at least one structural beam. The adjustable contact surface can be located on a second end of the at least one structural beam located opposite the first end. The fixed contact surface and the adjustable contact surface can be configured to apply pressure to an inside surface of the shipping container to stabilize the modular loading system in approximately the first direction. The adjustable contact surface can be used to install the modular loading system in non-uniform spacing of the shipping container to enhance one or more parameters. The set of modular beams can be spaced apart and arranged in a second direction that is nonparallel to the first direction. Each modular beam of the set of modular beams can be coupled with each structural beam of the set of structural beams at one or more connection points. Each modular beam of the plurality of modular beams can include a set of receiving notches. Each receiving notch of the set of receiving notches can be sized to receive a locking bar that can be configured to stabilize the modular loading system in a third direction that is approximately perpendicular to the first direction and the second direction. The locking bar can be repositioned within the modular loading system for enhancing the one or more parameters.

(5) In other embodiments, a system can include a first modular loading system and a second modular loading system. The first modular loading system can include a first set of structural beams and a first set of modular beams. The first set of structural beams can be positioned in a

shipping container and can be spaced apart and arranged in a first direction. At least one structural beam of the first set of structural beams can include a first fixed contact surface and a first adjustable contact surface. The first fixed contact surface can be located on a first end of the at least one structural beam of the first set of structural beams. The first adjustable contact surface can be located on a second end of the at least one structural beam located opposite the first end. The first fixed contact surface and the first adjustable contact surface can be configured to apply pressure to an inside surface of the shipping container to stabilize the first modular loading system in approximately the first direction. The first set of modular beams can be spaced apart and arranged in a second direction that is nonparallel to the first direction. Each modular beam of the first set of modular beams can be coupled with each structural beam of the first set of structural beams at one or more connection points. Each modular beam of the first set of modular beams can include a first set of receiving notches. Each receiving notch of the first set of receiving notches can be sized to receive a first locking bar that can be configured to stabilize the first modular loading system in a third direction that is approximately perpendicular to the first direction and the second direction. The second modular loading system can include a second set of structural beams and a second set of modular beams. The second set of structural beams can be positioned in the shipping container and can be spaced apart and arranged in approximately the first direction. At least one structural beam of the second set of structural beams can include a second fixed contact surface and a second adjustable contact surface. The second fixed contact surface can be located on a first end of the at least one structural beam of the second set of structural beams. The second adjustable contact surface can be located on a second end of the at least one structural beam positioned opposite the first end. The second fixed contact surface and the second adjustable contact surface can be configured to apply pressure to the inside surface of the shipping container to stabilize the second modular loading system in approximately the first direction. The second set of modular beams can be spaced apart and arranged in approximately the second direction. Each modular beam of the second set of modular beams can be coupled with each structural beam of the second set of structural beams at one or more connection points. Each modular beam of the second set of modular beams can include a second set of receiving notches. Each receiving notch of the second set of receiving notches can be sized to receive a second locking bar that can be configured to stabilize the second modular loading system in approximately the third direction.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a perspective view of an inside of a shipping container with a modular loading system according to one example of the present disclosure.
- (2) FIG. 2 is a side-view of a modular loading system for a shipping container according to one example of the present disclosure.
- (3) FIG. 3 is a side-view of a modular loading system for a shipping container according to one example of the present disclosure.
- (4) FIG. 4 is a diagram of a modular loading system installed in a shipping container according to one example of the present disclosure.
- (5) FIG. 5 is a diagram of a modular beam of a modular loading system for a shipping container according to one example of the present disclosure.
- (6) FIG. 6 is a flowchart of a process for installing and using a modular loading system for a shipping container according to one example of the present disclosure.

DETAILED DESCRIPTION

- (7) Certain aspects and examples of the present disclosure relate to a modular loading system for a shipping container. The shipping container may be any size for packing and/or transporting items

such as artwork, natural resources, consumer goods, and the like. The shipping container may be transported via water (e.g., using a ship), via air, via land (e.g., using a truck), or the like. In a particular example, the shipping container can be packed or otherwise loaded with items at a port, positioned on a ship, and transported across an ocean or other large body of water to reach a destination with one or more end users of the items. The modular loading system can be positioned in the shipping container to facilitate packing items in the shipping container. The modular loading system may include one or more types of beams or other structural features. For example, the modular loading system can include one or more structural beams, one or more modular beams, and the like. The structural beams can be arranged in a first direction, and the modular beams may be arranged in a second direction that may be nonparallel to the first direction. In some examples, at least one of the structural beams can include a first, fixed contact surface and a second, adjustable contact surface positioned opposite the first, fixed contact surface. Each of the contact surfaces may apply adjustable pressure to an inside of the shipping container to stabilize the modular loading system, or items loaded therein, in approximately the first direction. Additionally, the modular beams may include modular notches that may be sized to receive a locking bar that can stabilize the modular loading system, or items loaded therein, in a third direction that is approximately perpendicular to the first direction and the second direction.

(8) Other shipping containers and loading techniques may cause damage to a unique set of items, may generate excessive carbon emissions, and the like. A unique set of items may have an irregular packing scheme. For example, while some items may be packed and loaded into the shipping container using standard pallets, the unique set of items may be fragile, may be irregularly shaped, or may otherwise be unable to use pallets or other standard packing techniques in shipping containers. Other loading techniques to load the unique items into other shipping containers may involve using lumber or other single-use loading material to pack items in the shipping container. The other loading techniques may waste (i) a considerable amount of space in the shipping container, (ii) a considerable amount of time constructing a custom loading system from the lumber or other single-use loading material, and the like. Wasted space in the shipping container may reduce an efficiency of transporting the items. For example, wasted space in the shipping container may cause additional trips to be made to transport a similar volume of items, may cause additional carbon emissions to be generated to transport the similar volume of items, and the like.

Additionally, constructing the custom loading system with lumber or other single-use loading materials may cause excessive materials and time to be used to pack the items in the shipping container. Since the custom loading system is specific to a particular set of items, and since the materials used to construct the custom loading system are single-use, the materials may be thrown away or otherwise wasted after transporting the particular set of items. Throwing away the materials may increase carbon emissions, for example by increasing demand for the materials, which are produced using carbon emissions, and the like.

(9) A modular loading system can reduce carbon emissions and can address other technical challenges associated with transporting a custom or otherwise unique set of items. For example, the modular loading system can be reusable. The modular loading system can be made of durable materials such as plastics, metals, and the like. Additionally, the modular loading system: (i) can be constructed in a first configuration for packing a first unique set of items in a first shipping container, (ii) can be used to transport the first unique set of items from a first location to a second location, (iii) can be reconfigured into a second configuration for packing a second unique set of items in a second shipping container, and the like. Reconfiguring the modular loading system may not involve throwing any materials away and may involve repositioning components, such as one or more locking bars, and the like, within the modular loading system. Reusing the modular loading system can reduce carbon emissions generated with respect to producing materials for packing the items in the shipping container.

(10) Additionally, since the components, such as the locking bar and the like, of the modular

loading system are adjustable, a volume of items that can be packed in the shipping container can be maximized using the modular loading system. By maximizing the volume of items that can be packed in the shipping container, an efficiency of transporting the items can be maximized. For example, fewer transport trips can be made to transport a similar volume of items compared to other packing techniques that do not use the modular loading system. And, since fewer transport trips are made to transport the items, carbon emissions are reduced by using the modular loading system.

(11) The modular loading system may additionally reduce instances of damage to items transported via the shipping container. For example, the modular loading system, or any components thereof, can be adjusted to pack the items in the shipping container in a configuration that optimizes or enhances safety to the items. Additionally, hardware components, such as nails, screws, rivets, cut wood, and the like can be reduced with the modular loading system. The hardware components may damage fragile items, such as artwork, and reducing or obviating the use of the hardware components reduces a risk of damage to the items (i) while loading the items in the shipping container, (ii) while transporting the items from a first location to a second location, and the like.

(12) Illustrative examples are given to introduce the reader to the general subject matter discussed herein and are not intended to limit the scope of the disclosed concepts. The following sections describe various additional features and examples with reference to the drawings in which like numerals indicate like elements, and directional descriptions are used to describe the illustrative aspects, but, like the illustrative aspects, should not be used to limit the present disclosure.

(13) FIG. 1 is a perspective view of an inside of a shipping container **100** with a modular loading system **102** according to one example of the present disclosure. The shipping container **100** may be positioned on a land transportation vehicle (e.g., a truck), on a water transportation vehicle (e.g., a ship), or the like. An inside of the shipping container **100** may be sized to receive the modular loading system **102** and/or other components. In some examples, the modular loading system **102** may include one or more sections **104**. For example, and as illustrated, the modular loading system includes eight sections **104** such as a first section **104a**, a second section **104b**, and a third section **104c**. In some examples, each section **104** may be similar or identical, may be different from one another, etc. Additionally or alternatively, each section **104** may be a modular loading system, or the modular loading system **102** may include two or more sections **104**. Other suitable numbers (e.g., less than eight or more than eight) of sections **104** can be included in the modular loading system **102**.

(14) In some examples, the modular loading system **102** can be positioned in the shipping container **100** to facilitate loading one or more items **106** in the shipping container **100**. The one or more items **106** may include fragile items, irregularly shape items, or any other suitable items that can be transported via the shipping container **100**. The one or more items **106** may be produced or otherwise positioned in a first location, and an end user in a second location different than the first location may request the one or more items **106**. The one or more items **106** may be packed in the shipping container **100** using the modular loading system **102** to transport the one or more items **106** from the first location to the second location. A configuration of the modular loading system **102** may be optimized or otherwise enhanced or adjusted to maximize a safety of the one or more items **106**, a volume of the one or more items **106**, or the like.

(15) The modular loading system **102** can include one or more structural beams **108**, one or more modular beams **110**, and/or other suitable components for the modular loading system **102**. As illustrated in FIG. 1, each section **104** of the modular loading system **102** may include one or more structural beams **108**, one or more modular beams **110**, and the like. As an example, the first section **104a** can include structural beams **108a-e**, modular beams **110a-d**, and any other suitable components for facilitating packing items in the shipping container **100** via the modular loading system **102**. In some examples, a structural beam may include a beam, rod, or other structural device that can provide structural integrity to (e.g., to support weight on behalf of) the modular

loading system **102** or any component thereof. Additionally or alternatively, a modular beam may include a beam, rod, or other structural device that can be used to adjust a configuration of the modular loading system **102** or any component thereof. In one particular example, a set of structural beams can be positioned in the shipping container **100** to provide structural integrity for the modular loading system **102** and/or one or more items **106** to be loaded in the shipping container **100**. Additionally, a set of modular beams can be coupled to the set of structural beams to facilitate adjustment of the modular loading system **102** to optimize or enhance loading the one or more items **106** in the shipping container **100**.

(16) The one or more structural beams **108** can be spaced apart from one another, and the one or more modular beams **110** can be spaced apart from one another. For example, and as illustrated in FIG. 1, the structural beams **108a-e** are spaced laterally apart from one another. The structural beam **108a** can be positioned in a first location, the structural beam **108b** can be positioned laterally offset from the structural beam **108a**, the structural beam **108c** can be positioned laterally offset from the structural beams **108a-b**, and so on. Additionally, the modular beams **110a-d** can be positioned vertically offset from one another. As illustrated, the modular beam **110a** can be positioned in a first location (e.g., adjacent to a top, interior surface of the shipping container **100**), the modular beam **110b** can be positioned vertically offset (e.g., lower than) from the modular beam **110a**, the modular beam **110c** can be positioned vertically offset (e.g., lower than) from the modular beams **110a-b**, and so on. The structural beams **108** and the modular beams **110** can be otherwise positioned to facilitate packing the one or more items **106** in the shipping container **100**.

(17) The structural beams **108** can be arranged in a first direction, and the modular beams **110** can be arranged in a second direction. The first direction can be approximately vertical. For example, the first direction can extend in approximately a straight line from an upper, interior surface of the shipping container **100** to a lower, interior surface of the shipping container such that the first direction is approximately perpendicular to the upper, interior surface and the lower, interior surface. The second direction can be nonparallel to the first direction. In one such example, the second direction can be approximately horizontal and can extend from the structural beam **108a** to the structural beam **108e**, and the second direction can be approximately perpendicular to the structural beam **108a** and the structural beam **108e**.

(18) In some examples, the modular loading system **102** can include one or more locking bars **112** that can facilitate packing the one or more items **106** in the shipping container **100**. As illustrated in FIG. 1, locking bar **112a** can be positioned with respect to the third section **104c** of the modular loading system **102** to stabilize the modular loading system **102** and the one or more items **106**. The locking bar **112a** can be attached to one or more modular beams **110** of the third section **104c** and of other suitable sections **104** or components of the modular loading system. In some examples, the one or more items **106** may be packed in the shipping container **100** to contact the locking bar **112a** to stabilize the one or more items **106** in one or more directions such as the first direction, the second direction, a third direction approximately perpendicular to the first direction and the second direction, etc. Additionally or alternatively, the one or more items **106** may be stabilized using a strap **114** that can be positioned around the one or more items **106**. The strap **114** may be made of metallic material, polymeric material, fabric material, or any other durable material, elastic material, or the like that can be used to stabilize the one or more items **106**. In some examples, the strap **114** can be coupled to one or more modular beams **110** of one or more sections **104** of the modular loading system **102** to retain the one or more items **106** in a particular location in the shipping container **100** during loading and transport of the one or more items **106** via the shipping container **100**.

(19) A configuration of the modular loading system **102** may be optimized or otherwise adjusted to maximize a safety of the one or more items **106**, a volume of the one or more items **106**, or the like. For example, the locking bar **112a** can be repositioned, such as by attaching the ends of the locking bar **112a** to different locations along the one or more modular beams **110**, to different modular

beams, and the like, to maximize an available volume to position the one or more items **106**, to stabilize the one or more items **106** in the shipping container **100**, etc.

(20) FIG. 2 is a side-view of a modular loading system **102** for a shipping container **100** according to one example of the present disclosure. As illustrated, the modular loading system **102** includes one section **104**, but the modular loading system **102** can include more than one (e.g., two, three, four, etc.) section **104** for packing items in the shipping container **100**. Additionally, the modular loading system **102** can include the structural beams **108a-e** and the modular beams **110a-d**. The modular loading system **102** can include any other suitable component for facilitating packing one or more items **106** in the shipping container **100**.

(21) The structural beams **108a-e** can be arranged in the modular loading system **102** in the first direction, which may be approximately vertical, though in some examples, the first direction may be non-vertical. Each structural beam of the structural beams **108a-e** may extend from at least the modular beam **110a** to the modular beam **110d**. In some examples, at least one structural beam (e.g., the structural beam **108a**) of the structural beams **108a-e** can extend from a first end of an interior surface of the shipping container **100** to a second end positioned opposite the first end of the interior of the shipping container **100**.

(22) For example, the structural beam **108a** can include a first contact surface **202a** and a second contact surface **202b** that are positioned on opposite ends of the structural beam **108a**. The first contact surface **202a** can be positioned on a first end of the structural beam **108a** to contact the first end of the interior of the shipping container **100**, and the second contact surface **202b** can be positioned on a second end opposite the first end of the structural beam **108a** to contact the second end of the interior of the shipping container **100**. The first contact surface **202a** may include a fixed contact surface that may not be adjusted. For example, the fixed contact surface may have a fixed, non-adjustable length that is a predetermined distance from a closest modular beam **110**.

Additionally or alternatively, the second contact surface **202b** may include an adjustable contact surface that can be adjusted. In some examples, the adjustable contact surface can be adjusted by rotating the adjustable contact surface, by adjusting hardware components (e.g., screws, bolts, latches, etc.) of the adjustable contact surface and/or the structural beam, by a jacking mechanism that can involve a screw jack or other similar component that can adjust the adjustable contact surface, or the like. Adjusting the adjustable contact surface can cause a length of the structural beam to increase or decrease. In some examples, adjusting the adjustable contact surface can additionally or alternatively cause a pressure applied by the structural beam to the interior surface (e.g., top and/or bottom, etc.) of the shipping container **100** to increase or decrease.

(23) The structural beams **108a-e** may be spaced apart from one another in the modular loading system **102**. In some examples, the structural beams **108a-e** can be equally spaced apart from one another, can have different distances between one another, or the like. As illustrated, the structural beam **108a** is spaced laterally apart from the structural beam **108b** by a first distance **206a**, the structural beam **108c** is spaced laterally apart from the structural beam **108b** by a second distance **206b**, and so on. The first distance **206a** can be similar or identical to the second distance **206b**, the first distance **206a** can be different from the second distance **206b**, etc. The spacing between the structural beams **108a-e** may be optimized to optimize or enhance a stability of the modular loading system in a first direction following the path of one or more of the structural beams **108a-e**, a second direction following the path of one or more of the modular beams **110a-d**, and/or a third direction that can be approximately perpendicular to the first direction and/or the second direction.

(24) The modular beams **110a-d** may be spaced apart from one another and coupled to the structural beams **108a-e** in the modular loading system **102**. In some examples, the modular beams **110a-d** can be equally spaced apart from one another, can have different distances between one another, or the like. As illustrated, the modular beam **110a** is spaced vertically apart from the modular beam **110b** by a first distance **208a**, the modular beam **110c** is spaced vertically apart from the modular beam **110b** by a second distance **208b**, and so on. The first distance **208a** can be

similar or identical to the second distance **208b**, the first distance **208a** can be different from the second distance **208b**, etc. The spacing between the modular beams **110a-d** may be optimized to optimize or enhance a stability of the modular loading system **102** in the first direction, the second direction, and/or the third direction.

(25) The modular beams **110a-d** can be mechanically coupled to the structural beams **108a-e**, chemically coupled to the structural beams **108a-e**, or the like. For example, each modular beam **110a-d**, or any subset thereof, can be coupled to each structural beam of the structural beams **108a-e** via one or more welds, one or more screws, rivets, bolts, etc., one or more adhesives, and the like. In one particular example, each modular beam of the modular beams **110a-d** can be welded at multiple points to each structural beam of the structural beams **108a-e** such that the modular beams **110a-d** are vertically offset from one another and that each modular beam of the modular beams **110a-d** is approximately perpendicular to a corresponding structural beam of the structural beams **108a-e**.

(26) The structural beams **108a-e**, or any subset thereof, and/or the modular beams **110a-d**, or any subset thereof, may be formed into a shape **210**. The shape **210** can be three-dimensional and can have a cross-section of a square, a rectangle, a circle, a triangle, other regular shapes, other irregular shapes, or the like. As illustrated, the structural beams **108a-e** are rods with a quadrilateral cross-section, though other suitable shapes are possible. Additionally or alternatively, a first structural beam of the structural beams **108a-e** may have a different shape than a second structural beam of the structural beams **108a-e**. In other examples, the shape **210** of each structural beam of the structural beams **108a-e** may be similar or identical to the shape **210** of the other structural beams of the structural beams **108a-e**.

(27) The first contact surface **202a** may be positioned a first distance **212a** from the modular beam **110a** or other closest modular beam, and the second contact surface **202b** may be positioned a second distance **212b** from the modular beam **110d** or other closest modular beam. In some examples, the first distance **212a** may be a fixed distance that does not change in response to adjusting a configuration of the modular loading system **102**. Additionally or alternatively, the second distance **212b** may be an adjustable distance that can change in response to adjusting a configuration of the modular loading system **102**. For example, if a total height (e.g., from the first contact surface **202a** to the second contact surface **202b**) is less than an interior length of the shipping container **100**, the second contact surface **202b** can be adjusted to increase the total height. Accordingly, the second distance **212b** can be increased to cause the first contact surface **202a** and the second contact surface **202b** to abut and apply pressure to respective interior surfaces of the shipping container **100**.

(28) FIG. 3 is a side-view of a modular loading system **102** for a shipping container **100** according to one example of the present disclosure. As illustrated, the modular loading system **102** includes at least two sections: a first section **104a** and a second section **104b**. In some examples, the modular loading system **102** can include other suitable numbers (e.g., less than two or more than two) sections to facilitate packing the one or more items **106** in the shipping container **100**.

(29) The first section **104a** (e.g., a first modular loading system) can be positioned in the shipping container **100**, and the second section **104b** (e.g., a second modular loading system) can be positioned in the shipping container **100** adjacent to and laterally offset from the first section **104a**. The first section **104a** may be mechanically coupled to the second section **104b**, may be chemically coupled to the second section **104b**, or the like. For example, and as illustrated, a clamp **302** can mechanically couple the first section **104a** to the second section **104b**. In some examples, the clamp **302** can be or include one or more nuts and one or more bolts that extend through the structural beam of the first section **104a** and the structural beam of the second section **104b**. The clamp **302** may simultaneously apply approximately equal and approximately opposite pressure on the first section **104a** and the second section **104b** to retain the first section **104a** and the second section **104b** a predetermined distance laterally spaced apart. One, or more than one, clamp **302** can be

used to mechanically couple the first section **104a** and the second section **104b**. For example, and as illustrated in FIG. 3, two clamps **302** mechanically coupled the first section **104a** and the second section **104b**, though other suitable numbers (e.g., less than two or more than two) of clamps **302** can be used to mechanically couple the first section **104a** and the second section **104b**.

(30) The first section **104a** can include a first adjustable contact surface **304a**, and the second section **104b** can include a second adjustable contact surface **304b**. The first adjustable contact surface **304a** and the second adjustable contact surface **304b** can be positioned on a common side with respect to an interior of the shipping container **100**. For example, and as illustrated, the first adjustable contact surface **304a** can be positioned on a first end (e.g., adjacent to a bottom, interior surface of the shipping container **100**) of the first section **104a**, and the second adjustable contact surface **304b** can be positioned on a first end of the second section **104b** corresponding to the first section **104a**. The first adjustable contact surface **304a** and the second adjustable contact surface **304b** can be adjusted such that a relative height (e.g., within the shipping container **100**) of each modular beam of the first section **104a** is approximately the same as the relative height of each modular beam of the second section **104b**.

(31) FIG. 4 is a diagram of a modular loading system **102** installed in a shipping container **100** according to one example of the present disclosure. The modular loading system **102** can include structural beams, such as the structural beams **108a-b**, modular beams, such as the modular beams **110a-d**, and latching bars **410a-b**, which may facilitate coupling together of more than one modular loading system **102** or more than one section **104** of a modular loading system **102**. The modular loading system **102** can include any other suitable numbers of structural beams, modular beams, and other components for facilitating packing the one or more items **106** in the shipping container **100**. The structural beams **108a-b** can be arranged in a first direction **402**, and the modular beams **110a-d** can be arranged in a second direction **404**, which may be substantially perpendicular to the first direction **402**. Additionally, the modular beams **110a-d** may each be coupled to each of the structural beams **108a-b** at multiple points.

(32) Each modular beam of the modular beams **110a-d**, or any subset thereof, may include receiving notches that can be sized to receive a locking bar **112**. For example, and as illustrated in FIG. 4, the modular beam **110d** can include a set of receiving notches including receiving notches **406a-c**. Each receiving notch of the set of receiving notches can be laterally spaced apart, or otherwise suitably spaced apart, for allowing a position of the locking bar **112** to be adjusted to optimize or enhance a configuration of the modular loading system **102**. For example, each receiving notch may be positioned on the respective modular beam and spaced apart by 0.25 cm (0.098 in), 0.50 cm (0.197 in), 1.00 cm (0.394 in), 2.00 cm (0.787), 4.00 cm (1.575 in), 8.00 cm (3.150 in), or further.

(33) The modular loading system **102** can include one locking bar **112**, two locking bars, three locking bars, or more than three locking bars. In some examples, the modular loading system **102** can include a number of locking bars to optimize or enhance a configuration of the modular loading system **102** such that a safety of the one or more items **106** and a volume available to pack the one or more items **106** are simultaneously maximized. The locking bar **112** can be positioned in one or more receiving notches of one or more of the modular beams **110a-d** of the modular loading system **102**. For example, and as illustrated in FIG. 4, a first end of the locking bar **112** is positioned in the receiving notch **406b** of the modular beam **110d**, though the first end of the locking bar **112** can be positioned in the receiving notch **406a**, the receiving notch **406c**, or any other suitable receiving notch for optimizing or enhancing the configuration of the modular loading system **102**.

Additionally, a second end opposite the first end of the locking bar **112** can be positioned in a different receiving notch of a different modular beam (e.g., that may be positioned on an opposite side of the interior of the shipping container **100** compared to the modular beam **110d**). Thus, the locking bar **112** may extend in a third direction **408** from a first side of the interior of the shipping container **100** to a second side of the interior of the shipping container **100**. In some examples, the

third direction **408** may be substantially perpendicular to the first direction **402** and/or substantially perpendicular to the second direction **404**.

(34) FIG. 5 is a diagram of a modular beam **110** of a modular loading system **102** for a shipping container **100** according to one example of the present disclosure. The modular beam **110** can include a set of receiving notches such as the receiving notches **406a-c**. Additionally, a first end **502** of the locking bar **112** can be positioned in one or more receiving notches of the set of receiving notches of the modular beam **110**. For example, and as illustrated, the first end **502** of the locking bar **112** can be positioned in the receiving notch **406b**, though the first end **502**, or any other end, of the locking bar **112** can be positioned in any other suitable receiving notch of the set of receiving notches of the modular beam **110**.

(35) Each receiving notch of the set of receiving notches can be sized to receive the first end **502** of the locking bar **112**. For example, each receiving notch of the set of receiving notches can have a shape similar or identical to the shape of the first end **502** and may have a size that can be approximately the same as or larger than the size (e.g., a diameter, a width, etc.) of the first end **502**. Additionally or alternatively, a lower portion **502a** (e.g., a portion positioned closer to the ground than any other portion) of the receiving notch may extend away from the modular beam **110** further than an upper portion **502b** of the receiving notch. In some examples, the lower portion **502a** may extend further in the third direction **408** than the upper portion **502b** to increase an ease of installing the locking bar **112** in the receiving notch.

(36) FIG. 6 is a flowchart of a process **600** for installing and using a modular loading system **102** for a shipping container **100** according to one example of the present disclosure. The process **600** is described as a set of operations, and each operation of the set of operations can be performed synchronously, asynchronously, and/or substantially contemporaneously. For example, two or more of the operations may be performed at the same time, may be performed in response to a separate operation being performed, or otherwise may be independently performed with or without respect to order. The operations of the process **600** are described with respect to the components, such as the modular loading system **102**, described and illustrated with respect to FIGS. 1-5.

(37) At block **602**, a set of structural beams **108** are positioned in a shipping container **100**. The structural beams **108** can include one, two, three, or more structural beams and can each be arranged spaced apart from one another and in a first direction. In some examples, the first direction may approximately follow a direction of gravity. Additionally or alternatively, a first end of each of the structural beams may be positioned adjacent to a first, interior surface of the shipping container **100**, and a second end opposite the first end of each of the structural beams may be positioned adjacent to a second, interior surface opposite the first, interior surface of the shipping container **100**.

(38) At least one structural beam of the plurality of structural beams can include a fixed contact surface and an adjustable contact surface. The fixed contact surface can be positioned on a first end of the structural beam adjacent to the first, interior surface of the shipping container **100**, and the adjustable contact surface can be positioned on a second end opposite the first end of the structural beam adjacent to the second, interior surface of the shipping container **100**. Subsequent to positioning the structural beams in the shipping container **100**, the adjustable contact surface can be adjusted to increase or decrease the pressure applied from the structural beam on the interior surfaces of the shipping container **100**.

(39) At block **604**, a set of modular beams **110** are positioned in the shipping container **100**. The modular beams **110** can include one, two, three, or more modular beams and can each be arranged spaced apart from one another and in a second direction. In some examples, the first direction may be approximately perpendicular to the first direction and may be substantially perpendicular to the direction of gravity. Each modular beam of the modular beams **110** can be coupled (e.g., mechanically, chemically, etc.) to each structural beam of the structural beams **108**. Additionally, each modular beam may include a set of receiving notches. Each receiving notch of the set of

receiving notches can be sized to receive a locking bar **112** that can stabilize the modular loading system **102** in a third direction that is approximately perpendicular to the first direction and the second direction.

(40) The operations described in the block **602** and in the block **604** can be performed simultaneously or otherwise substantially contemporaneously. For example, the modular beams **110** may be coupled, whether mechanically, chemically, or the like, to the structural beams **108** prior to positioning the structural beams **108** and the modular beams **110** in the shipping container **100**. Additionally or alternatively, the adjustable contact surface may be adjusted prior to, during, or subsequent to positioning the structural beams **108** and/or the modular beams **110** in the shipping container **100**.

(41) At block **606**, one or more items **106** are positioned in the shipping container **100** using the modular loading system **102**. A configuration of the modular loading system **102** can be optimized or otherwise adjusted prior to or substantially contemporaneously with respect to positioning the one or more items **106** in the shipping container **100**. For example, one or more locking bars **112** may be positioned in the modular loading system **102** via one or more of the modular beams to optimize a safety of the one or more items **106** while being transported via the shipping container **100**, a volume available to load the one or more items **106** in the shipping container **100**, an airflow between the one or more items **106** or otherwise throughout the shipping container **100**, and the like. Upon (or while) optimizing or adjusting the configuration of the modular loading system **102**, the one or more items **106** can be packed into the shipping container **100** using the modular loading system **102** and other packing and/or shipping materials such as straps, clamps, bolts, and the like.

(42) The foregoing description of certain examples, including illustrated examples, has been presented only for the purpose of illustration and description and is not intended to be exhaustive or to limit the disclosure to the precise forms disclosed. Numerous modifications, adaptations, and uses thereof will be apparent to those skilled in the art without departing from the scope of the disclosure.

Claims

1. A modular loading system comprising: a plurality of structural beams positionable in a shipping container, the plurality of structural beams spaced apart and arranged in a first direction, wherein at least one structural beam of the plurality of structural beams comprises: a fixed contact surface located on a first end of the at least one structural beam, the fixed contact surface arranged to make contact with an inside surface of the shipping container; and an adjustable contact surface located on a second end of the at least one structural beam located opposite the first end, the fixed contact surface and the adjustable contact surface configured to apply pressure to the inside surface of the shipping container to stabilize the modular loading system in approximately the first direction, wherein the pressure is applicable to the inside surface by the fixed contact surface based on the contact between the inside surface and the fixed contact surface; and a plurality of modular beams spaced apart and arranged in a second direction that is nonparallel to the first direction, each modular beam of the plurality of modular beams coupled with each structural beam of the plurality of structural beams at one or more connection points, wherein each modular beam of the plurality of modular beams comprises a plurality of receiving notches, each receiving notch of the plurality of receiving notches is sized to receive a locking bar that is configured to stabilize the modular loading system in a third direction that is approximately perpendicular to the first direction and the second direction.

2. The modular loading system of claim 1, wherein the at least one structural beam of the plurality of structural beams extends from a first, interior end of the shipping container to a second, interior end of the shipping container, wherein the first, interior end is located opposite the second, interior end, wherein the fixed contact surface abuts the first, interior end of the shipping container, and

wherein the adjustable contact surface abuts the second, interior end of the shipping container.

3. The modular loading system of claim 2, wherein the adjustable contact surface is adjustable to control a pressure applied (i) from the fixed contact surface to the first, interior end of the shipping container, and (ii) from the adjustable contact surface to the second, interior end of the shipping container.

4. The modular loading system of claim 2, wherein the plurality of structural beams includes one or more structural beams that are different than the at least one structural beam, wherein each structural beam of the one or more structural beams extends from a first modular beam of the plurality of modular beams to a second modular beam of the plurality of modular beams, and wherein each structural beam of the one or more structural beams contacts each modular beam of the plurality of modular beams.

5. The modular loading system of claim 1, further comprising one or more latching bars located on at least one structural beam of the plurality of structural beams, wherein the plurality of structural beams is a first plurality of structural beams included in a first section of the modular loading system, wherein the plurality of modular beams is a first plurality of modular beams included in the first section, and wherein the modular loading system further comprises a second section coupled to the first section via the one or more latching bars.

6. The modular loading system of claim 5, wherein the second section comprises: a second plurality of structural beams positionable in the shipping container, the second plurality of structural beams spaced apart and arranged in approximately the first direction, wherein at least one structural beam of the second plurality of structural beams comprises: a second fixed contact surface located on a first end of the at least one structural beam of the second plurality of structural beams; and a second adjustable contact surface located on a second end of the at least one structural beam located opposite the first end, the second fixed contact surface and the second adjustable contact surface configured to apply pressure to the inside surface of the shipping container to stabilize the modular loading system in approximately the first direction; and a second plurality of modular beams spaced apart and arranged in approximately the second direction, each modular beam of the second plurality of modular beams coupled with each structural beam of the second plurality of structural beams at one or more connection points, wherein each modular beam of the second plurality of modular beams comprises: a second plurality of receiving notches, each receiving notch of the second plurality of receiving notches sized to receive a second locking bar that is configured to stabilize the modular loading system in approximately a third direction; and wherein a first height of each modular beam of the first plurality of modular beams with respect to a floor of the shipping container is approximately equal to a second height of a corresponding modular beam of the second plurality of modular beams.

7. A system comprising: a shipping container; and a modular loading system positionable in the shipping container and removable from the shipping container, the modular loading system comprising: a plurality of structural beams positionable in the shipping container, the plurality of structural beams spaced apart and arranged in a first direction, wherein at least one structural beam of the plurality of structural beams comprises: a fixed contact surface located on a first end of the at least one structural beam, the fixed contact surface arranged to make contact with an inside surface of the shipping container; and an adjustable contact surface located on a second end of the at least one structural beam located opposite the first end, the fixed contact surface and the adjustable contact surface configured to apply pressure to an inside surface of the shipping container to stabilize the modular loading system in approximately the first direction, the adjustable contact surface usable to install the modular loading system in non-uniform spacing of the shipping container to enhance one or more parameters comprising an arrangement of items in the shipping container, wherein the pressure is applicable to the inside surface by the fixed contact surface based on the contact between the inside surface and the fixed contact surface; and a plurality of modular beams spaced apart and arranged in a second direction that is nonparallel to the first direction, each

modular beam of the plurality of modular beams coupled with each structural beam of the plurality of structural beams at one or more connection points, wherein each modular beam of the plurality of modular beams comprises: a plurality of receiving notches, each receiving notch of the plurality of receiving notches sized to receive a locking bar that is configured to stabilize the modular loading system in a third direction that is approximately perpendicular to the first direction and the second direction, the locking bar repositionable within the modular loading system for enhancing the one or more parameters.

8. The system of claim 7, wherein the one or more parameters comprise (i) a volume of items in the shipping container, (ii) a mechanical security of restrained items in the shipping container, (iii) a location of items in the shipping container, and (iv) a balance of the shipping container when loaded, and wherein the at least one structural beam of the plurality of structural beams extends from a first, interior end of the shipping container to a second, interior end of the shipping container, wherein the first, interior end is located opposite the second, interior end, wherein the fixed contact surface abuts the first, interior end of the shipping container, and wherein the adjustable contact surface abuts the second, interior end of the shipping container.

9. The system of claim 8, wherein the adjustable contact surface is adjustable to control a pressure applied (i) from the fixed contact surface to the first, interior end of the shipping container, and (ii) from the adjustable contact surface to the second, interior end of the shipping container, and wherein the adjustable contact surface and the fixed contact surface are arrangeable prior to or substantially contemporaneous with installing in the shipping container to conform to an interior dimension of the shipping container.

10. The system of claim 8, wherein the plurality of structural beams includes one or more structural beams that are different than the at least one structural beam, wherein each structural beam of the one or more structural beams extends from a first modular beam of the plurality of modular beams to a second modular beam of the plurality of modular beams, and wherein each structural beam of the one or more structural beams contacts each modular beam of the plurality of modular beams.

11. The system of claim 7, wherein the modular loading system further comprises one or more latching bars located on at least one structural beam of the plurality of structural beams, wherein the plurality of structural beams is a first plurality of structural beams included in a first section of the modular loading system, wherein the plurality of modular beams is a first plurality of modular beams included in the first section, and wherein the modular loading system further comprises a second section coupled to the first section via the one or more latching bars.

12. The system of claim 11, wherein the second section comprises: a second plurality of structural beams positionable in the shipping container, the second plurality of structural beams spaced apart and arranged in approximately the first direction, wherein at least one structural beam of the second plurality of structural beams comprises: a second fixed contact surface located on a first end of the at least one structural beam of the second plurality of structural beams; and a second adjustable contact surface located on a second end of the at least one structural beam located opposite the first end, the second fixed contact surface and the second adjustable contact surface configured to apply pressure to the inside surface of the shipping container to stabilize the modular loading system in approximately the first direction; and a second plurality of modular beams spaced apart and arranged in approximately the second direction, each modular beam of the second plurality of modular beams coupled with each structural beam of the second plurality of structural beams at one or more connection points, wherein each modular beam of the second plurality of modular beams comprises: a second plurality of receiving notches, each receiving notch of the second plurality of receiving notches sized to receive a second locking bar that is configured to stabilize the modular loading system in approximately the third direction.

13. The system of claim 12, wherein a first height of each modular beam of the first plurality of modular beams with respect to a floor of the shipping container is approximately equal to a second height of a corresponding modular beam of the second plurality of modular beams.

14. A system comprising: a first modular loading system comprising: a first plurality of structural beams positionable in a shipping container, the first plurality of structural beams spaced apart and arranged in a first direction, wherein at least one structural beam of the first plurality of structural beams comprises: a first fixed contact surface located on a first end of the at least one structural beam of the first plurality of structural beams, the first fixed contact surface arranged to make contact with an inside surface of the shipping container; and a first adjustable contact surface located on a second end of the at least one structural beam located opposite the first end, the first fixed contact surface and the first adjustable contact surface configured to apply pressure to an inside surface of the shipping container to stabilize the first modular loading system in approximately the first direction, wherein the pressure is applicable to the inside surface by the first fixed contact surface based on the contact between the inside surface and the first fixed contact surface; and a first plurality of modular beams spaced apart and arranged in a second direction that is nonparallel to the first direction, each modular beam of the first plurality of modular beams coupled with each structural beam of the first plurality of structural beams at one or more connection points, wherein each modular beam of the first plurality of modular beams comprises: a first plurality of receiving notches, each receiving notch of the first plurality of receiving notches sized to receive a first locking bar that is configured to stabilize the first modular loading system in a third direction that is approximately perpendicular to the first direction and the second direction; and a second modular loading system comprising: a second plurality of structural beams positionable in the shipping container, the second plurality of structural beams spaced apart and arranged in approximately the first direction, wherein at least one structural beam of the second plurality of structural beams comprises: a second fixed contact surface located on a first end of the at least one structural beam of the second plurality of structural beams; and a second adjustable contact surface located on a second end of the at least one structural beam positioned opposite the first end, the second fixed contact surface and the second adjustable contact surface configured to apply pressure to the inside surface of the shipping container to stabilize the second modular loading system in approximately the first direction; and a second plurality of modular beams spaced apart and arranged in approximately the second direction, each modular beam of the second plurality of modular beams coupled with each structural beam of the second plurality of structural beams at one or more connection points, wherein each modular beam of the second plurality of modular beams comprises: a second plurality of receiving notches, each receiving notch of the second plurality of receiving notches sized to receive a second locking bar that is configured to stabilize the second modular loading system in approximately the third direction.

15. The system of claim 14, wherein: the at least one structural beam of the first plurality of structural beams extends from a first, interior end of the shipping container to a second, interior end of the shipping container, wherein the first, interior end is positioned opposite the second, interior end, wherein the first fixed contact surface abuts the first, interior end of the shipping container, and wherein the first adjustable contact surface abuts the second, interior end of the shipping container; and the at least one structural beam of the second plurality of structural beams extends from the first, interior end of the shipping container to the second, interior end of the shipping container, wherein the second fixed contact surface abuts the first, interior end of the shipping container, and wherein the second adjustable contact surface abuts the second, interior end of the shipping container.

16. The system of claim 15, wherein the first adjustable contact surface and the second adjustable contact surface are each adjustable to control a pressure applied (i) from the first fixed contact surface or the second fixed contact surface, respectively, to the first, interior end of the shipping container, and (ii) from the first adjustable contact surface or the second adjustable contact surface, respectively, to the second, interior end of the shipping container.

17. The system of claim 15, wherein the first plurality of structural beams includes one or more first structural beams that are different than the at least one structural beam of the first plurality of

structural beams, wherein each structural beam of the one or more first structural beams extends from a first modular beam of the first plurality of modular beams to a second modular beam of the first plurality of modular beams, and wherein each structural beam of the one or more first structural beams contacts each modular beam of the first plurality of modular beams.

18. The system of claim 15, wherein the second plurality of structural beams includes one or more second structural beams that are different than the at least one structural beam of the second plurality of structural beams, wherein each structural beam of the one or more second structural beams extends from a first modular beam of the second plurality of modular beams to a second modular beam of the second plurality of modular beams, and wherein each structural beam of the one or more second structural beams contacts each modular beam of the second plurality of modular beams.

19. The system of claim 14, wherein a first height of each modular beam of the first plurality of modular beams with respect to a floor of the shipping container is approximately equal to a second height of a corresponding modular beam of the second plurality of modular beams.
