

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12390703
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Johnson; Matthew David et al.

Golf club heads

Abstract

Disclosed golf club heads include a weight channel positioned in the sole and defining a path along the sole. A weight member positioned in the weight channel can be adjusted to any of a range of selectable positions to adjust mass properties of the golf club head. A fastener secures the weight member in any of the selectable positions, while the fastener itself, regardless of where the weight member is positioned along the path, is secured to the body at a fixed location that is independent of the position of the weight member along the path. Part of the weight channel and weight member can be covered by an overhanging portion of the sole, which can form a sit pad. The overhanging portion can be part of a composite sole insert.

Inventors: Johnson; Matthew David (San Diego, CA), Beach; Todd P. (Encinitas, CA), Harbert; Christopher John (Carlsbad, CA)

Applicant: Taylor Made Golf Company, Inc. (Carlsbad, CA)

Family ID: 1000008763102

Assignee: Taylor Made Golf Company, Inc. (Carlsbad, CA)

Appl. No.: 18/449207

Filed: August 14, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240058664 A1	Feb. 22, 2024

Related U.S. Application Data

continuation parent-doc US 17390615 20210730 US 11759685 child-doc US 18449207
continuation-in-part parent-doc US 17135666 20201228 US 11406881 20220809 child-doc US 17390615

Publication Classification

Int. Cl.: A63B53/06 (20150101); A63B53/04 (20150101); A63B102/32 (20150101)

U.S. Cl.:

CPC **A63B53/06** (20130101); **A63B53/0433** (20200801); **A63B53/0466** (20130101); A63B2053/0491
(20130101); A63B2102/32 (20151001)

Field of Classification Search

CPC: A63B (2053/0491); A63B (2053/0495)

USPC: 473/338

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
411000	12/1888	Anderson	N/A	N/A
1133129	12/1914	Govan	N/A	N/A
1135621	12/1914	Roberts et al.	N/A	N/A
1213382	12/1916	Kent	N/A	N/A
1320163	12/1918	Fitz	N/A	N/A
1349806	12/1919	Booth	N/A	N/A
1518316	12/1923	Ellingham	N/A	N/A
1526438	12/1924	Scott	N/A	N/A
1538312	12/1924	Beat	N/A	N/A
1552297	12/1924	Elzie	N/A	N/A
1555425	12/1924	McKenzie	N/A	N/A
1592463	12/1925	Marker	N/A	N/A
1658581	12/1927	Tobia	N/A	N/A
1697846	12/1928	Anderson	N/A	N/A
1704119	12/1928	Buhrke	N/A	N/A
1705997	12/1928	Quynn	N/A	N/A
1854548	12/1931	Hunt	N/A	N/A
1970409	12/1933	Wiedemann	N/A	N/A
D107007	12/1936	Cashmore	N/A	N/A
2098445	12/1936	Wettlaufer	N/A	N/A
2163091	12/1938	Held	N/A	N/A
2171383	12/1938	Wettlaufer	N/A	N/A
2214356	12/1939	Wettlaufer	N/A	N/A
2225930	12/1939	Sexton	N/A	N/A
2257575	12/1940	Reach	N/A	N/A
2328583	12/1942	Reach	N/A	N/A
2360364	12/1943	Reach	N/A	N/A
2375249	12/1944	Richer	N/A	N/A
2460435	12/1948	Schaffer	N/A	N/A
2652256	12/1952	Thomas	N/A	N/A
2681523	12/1953	Sellers	N/A	N/A
2691525	12/1953	Callaghan	N/A	N/A
3064980	12/1961	Steiner	N/A	N/A
3084940	12/1962	Cissel	N/A	N/A
3199874	12/1964	Blasing	N/A	N/A
3466047	12/1968	Rodia et al.	N/A	N/A
3486755	12/1968	Hodge	N/A	N/A
3556533	12/1970	Hollis	N/A	N/A
3589731	12/1970	Chancellor	N/A	N/A
3606327	12/1970	Gorman	N/A	N/A
3610630	12/1970	Glover	N/A	N/A
3652094	12/1971	Glover	N/A	N/A

3672419	12/1971	Fischer	N/A	N/A
3680868	12/1971	Jacob	N/A	N/A
3692306	12/1971	Glover	N/A	N/A
3743297	12/1972	Dennis	N/A	N/A
3810631	12/1973	Braly	N/A	N/A
3860244	12/1974	Cosby	N/A	N/A
3897066	12/1974	Belmont	N/A	N/A
3976299	12/1975	Lawrence et al.	N/A	N/A
3979122	12/1975	Belmont	N/A	N/A
3979123	12/1975	Belmont	N/A	N/A
3997170	12/1975	Goldberg	N/A	N/A
4008896	12/1976	Gordos	N/A	N/A
4021047	12/1976	Mader	N/A	N/A
4043563	12/1976	Churchward	N/A	N/A
4052075	12/1976	Daly	N/A	N/A
4067572	12/1977	Coleman	N/A	N/A
4076254	12/1977	Nygren	N/A	N/A
4085934	12/1977	Churchward	N/A	N/A
4121832	12/1977	Ebbing	N/A	N/A
4150702	12/1978	Holmes	N/A	N/A
4189976	12/1979	Becker	N/A	N/A
4214754	12/1979	Zebelean	N/A	N/A
4262562	12/1980	MacNeill	N/A	N/A
D259698	12/1980	MacNeill	N/A	N/A
4280700	12/1980	Plagenhoef	473/289	A63B 60/24
4322083	12/1981	Imai	N/A	N/A
4340229	12/1981	Stuff, Jr.	N/A	N/A
4398965	12/1982	Campau	N/A	N/A
4411430	12/1982	Dian	N/A	N/A
4423874	12/1983	Stuff, Jr.	N/A	N/A
4438931	12/1983	Motomiya	N/A	N/A
4471961	12/1983	Masghati et al.	N/A	N/A
4489945	12/1983	Kobayashi	N/A	N/A
4530505	12/1984	Stuff	N/A	N/A
4535990	12/1984	Yamada	N/A	N/A
4553755	12/1984	Yamada	N/A	N/A
D284346	12/1985	Masters	N/A	N/A
4602787	12/1985	Sugioka et al.	N/A	N/A
4607846	12/1985	Perkins	N/A	N/A
4712798	12/1986	Preato	N/A	N/A
4730830	12/1987	Tilley	N/A	N/A
4736093	12/1987	Braly	N/A	N/A
4736951	12/1987	Grant	N/A	N/A
4754974	12/1987	Kobayashi	N/A	N/A
4754977	12/1987	Sahm	N/A	N/A
4762322	12/1987	Molitor et al.	N/A	N/A
4795159	12/1988	Nagamoto	473/348	A63B 60/00
4803023	12/1988	Enomoto et al.	N/A	N/A
4809983	12/1988	Langert	N/A	N/A
4867457	12/1988	Lowe	N/A	N/A
4867458	12/1988	Sumikawa et al.	N/A	N/A
4869507	12/1988	Sahm	N/A	N/A
4877249	12/1988	Thompson	N/A	N/A
4878666	12/1988	Hosoda	N/A	N/A
4890840	12/1989	Kobayashi	N/A	N/A
4895371	12/1989	Bushner	N/A	N/A

4915558	12/1989	Muller	N/A	N/A
4962932	12/1989	Anderson	N/A	N/A
4994515	12/1990	Washiyama et al.	N/A	N/A
5000454	12/1990	Soda	N/A	N/A
5006023	12/1990	Kaplan	N/A	N/A
5020950	12/1990	Ladouceur	N/A	N/A
5028049	12/1990	McKeighen	N/A	N/A
5039267	12/1990	Wollar	N/A	N/A
5042806	12/1990	Helmstetter	N/A	N/A
5050879	12/1990	Sun et al.	N/A	N/A
5058895	12/1990	Igarashi	N/A	N/A
5067715	12/1990	Schmidt et al.	N/A	N/A
5076585	12/1990	Bouquet	N/A	N/A
5078400	12/1991	Desbiolles et al.	N/A	N/A
5121922	12/1991	Harsh, Sr.	N/A	N/A
5122020	12/1991	Bedi	N/A	N/A
5193810	12/1992	Antonious	N/A	N/A
5213328	12/1992	Long et al.	N/A	N/A
5219408	12/1992	Sun	N/A	N/A
5221086	12/1992	Antonious	N/A	N/A
5232224	12/1992	Zeider	N/A	N/A
5244210	12/1992	Au	N/A	N/A
5251901	12/1992	Solheim et al.	N/A	N/A
5253869	12/1992	Dingle et al.	N/A	N/A
5255913	12/1992	Tsuchida	N/A	N/A
D343558	12/1993	Latraverse et al.	N/A	N/A
5297794	12/1993	Lu	N/A	N/A
5301941	12/1993	Allen	N/A	N/A
5306008	12/1993	Kinoshita	N/A	N/A
5316305	12/1993	McCabe	N/A	N/A
5320005	12/1993	Hsiao	N/A	N/A
5328176	12/1993	Lo	N/A	N/A
5330187	12/1993	Schmidt et al.	N/A	N/A
5346216	12/1993	Aizawa	N/A	N/A
5346217	12/1993	Tsuchiya et al.	N/A	N/A
5385348	12/1994	Wargo	N/A	N/A
5395113	12/1994	Antonious	N/A	N/A
5410798	12/1994	Lo	N/A	N/A
5419556	12/1994	Take	N/A	N/A
5421577	12/1994	Kobayashi	N/A	N/A
5429365	12/1994	McKeighen	N/A	N/A
5439222	12/1994	Kranenberg	N/A	N/A
5441274	12/1994	Clay	N/A	N/A
5447309	12/1994	Vincent	N/A	N/A
5449260	12/1994	Whittle	N/A	N/A
5451056	12/1994	Manning	N/A	N/A
5464211	12/1994	Atkins	N/A	N/A
5467983	12/1994	Chen	N/A	N/A
D365615	12/1994	Shimatani	N/A	N/A
5472201	12/1994	Aizawa et al.	N/A	N/A
5472203	12/1994	Schmidt et al.	N/A	N/A
5480152	12/1995	Schmidt et al.	N/A	N/A
5511786	12/1995	Antonious	N/A	N/A
5518243	12/1995	Redman	N/A	N/A
5533730	12/1995	Ruvang	N/A	N/A
5538245	12/1995	Moore	N/A	N/A

5564705	12/1995	Kobayashi et al.	N/A	N/A
5571053	12/1995	Lane	N/A	N/A
5573467	12/1995	Chou et al.	N/A	N/A
5582553	12/1995	Ashcraft et al.	N/A	N/A
5603668	12/1996	Antonious	N/A	N/A
5613917	12/1996	Kobayashi et al.	N/A	N/A
5616088	12/1996	Aizawa et al.	N/A	N/A
5620379	12/1996	Borys	N/A	N/A
5624331	12/1996	Lo et al.	N/A	N/A
5629475	12/1996	Chastonay	N/A	N/A
5632694	12/1996	Lee	N/A	N/A
5658206	12/1996	Antonious	N/A	N/A
5669827	12/1996	Nagamoto	N/A	N/A
5681228	12/1996	Mikame et al.	N/A	N/A
5683309	12/1996	Reimers	N/A	N/A
5688189	12/1996	Bland	N/A	N/A
5709613	12/1997	Sheraw	N/A	N/A
5718641	12/1997	Lin	N/A	N/A
5720674	12/1997	Galy	N/A	N/A
D392526	12/1997	Nicely	N/A	N/A
5735754	12/1997	Antonious	N/A	N/A
5746664	12/1997	Reynolds, Jr.	N/A	N/A
5749795	12/1997	Schmidt et al.	N/A	N/A
5755627	12/1997	Yamazaki et al.	N/A	N/A
5762567	12/1997	Antonious	N/A	N/A
5766095	12/1997	Antonious	N/A	N/A
5769737	12/1997	Holladay et al.	N/A	N/A
5776010	12/1997	Helmstetter et al.	N/A	N/A
5776011	12/1997	Su et al.	N/A	N/A
5788584	12/1997	Parente et al.	N/A	N/A
5788587	12/1997	Tseng	N/A	N/A
5798587	12/1997	Lee	N/A	N/A
5803829	12/1997	Hayashi	N/A	N/A
RE35955	12/1997	Lu	N/A	N/A
5851160	12/1997	Rugge et al.	N/A	N/A
5873791	12/1998	Allen	N/A	N/A
5888148	12/1998	Allen	N/A	N/A
D409463	12/1998	McMullin	N/A	N/A
5908356	12/1998	Nagamoto	N/A	N/A
5911638	12/1998	Parente et al.	N/A	N/A
5913735	12/1998	Kenmi	N/A	N/A
5916042	12/1998	Reimers	473/345	A63B 53/04
5924938	12/1998	Hines	N/A	N/A
D412547	12/1998	Fong	N/A	N/A
5935019	12/1998	Yamamoto	N/A	N/A
5935020	12/1998	Stites et al.	N/A	N/A
5941782	12/1998	Cook	N/A	N/A
5947840	12/1998	Ryan	N/A	N/A
5967904	12/1998	Nagai et al.	N/A	N/A
5967905	12/1998	Nakahara et al.	N/A	N/A
5971867	12/1998	Galy	N/A	N/A
5976033	12/1998	Takeda	N/A	N/A
5997415	12/1998	Wood	N/A	N/A
6015354	12/1999	Ahn et al.	N/A	N/A
6017177	12/1999	Lanham	N/A	N/A
6019686	12/1999	Gray	N/A	N/A

6023891	12/1999	Robertson et al.	N/A	N/A
6032677	12/1999	Blechman et al.	N/A	N/A
6033318	12/1999	Drajan, Jr. et al.	N/A	N/A
6033321	12/1999	Yamamoto	N/A	N/A
6042486	12/1999	Gallagher	N/A	N/A
6056649	12/1999	Imai	N/A	N/A
6059669	12/1999	Pearce	N/A	N/A
6062988	12/1999	Yamamoto	N/A	N/A
6074308	12/1999	Domas	N/A	N/A
6077171	12/1999	Yoneyama	N/A	N/A
6086485	12/1999	Hamada et al.	N/A	N/A
6089994	12/1999	Sun	N/A	N/A
6120384	12/1999	Drake	N/A	N/A
6123627	12/1999	Antonious	N/A	N/A
6139445	12/1999	Werner et al.	N/A	N/A
6149533	12/1999	Finn	N/A	N/A
6162132	12/1999	Yoneyama	N/A	N/A
6162133	12/1999	Peterson	N/A	N/A
6171204	12/2000	Starry	N/A	N/A
6186905	12/2000	Kosmatka	N/A	N/A
6190267	12/2000	Marlowe et al.	N/A	N/A
6193614	12/2000	Sasamoto et al.	N/A	N/A
6203448	12/2000	Yamamoto	N/A	N/A
6206789	12/2000	Takeda	N/A	N/A
6206790	12/2000	Kubica et al.	N/A	N/A
6210290	12/2000	Erickson et al.	N/A	N/A
6217461	12/2000	Galy	N/A	N/A
6238303	12/2000	Fite	N/A	N/A
6244974	12/2000	Hanberry, Jr.	N/A	N/A
6248025	12/2000	Murphy et al.	N/A	N/A
6254494	12/2000	Hasebe et al.	N/A	N/A
6264414	12/2000	Hartmann et al.	N/A	N/A
6270422	12/2000	Fisher	N/A	N/A
6277032	12/2000	Smith	473/336	A63B 53/047
6290609	12/2000	Takeda	N/A	N/A
6296576	12/2000	Capelli	N/A	N/A
6296579	12/2000	Robinson	N/A	N/A
6299546	12/2000	Wang	N/A	N/A
6299547	12/2000	Kosmatka	N/A	N/A
6306048	12/2000	McCabe et al.	N/A	N/A
6319149	12/2000	Lee	N/A	N/A
6319150	12/2000	Werner et al.	N/A	N/A
6334817	12/2001	Ezawa et al.	N/A	N/A
6338683	12/2001	Kosmatka	N/A	N/A
6340337	12/2001	Hasebe et al.	N/A	N/A
6344000	12/2001	Hamada et al.	N/A	N/A
6344001	12/2001	Hamada et al.	N/A	N/A
6344002	12/2001	Kajita	N/A	N/A
6348012	12/2001	Erickson et al.	N/A	N/A
6348013	12/2001	Kosmatka	N/A	N/A
6348014	12/2001	Chiu	N/A	N/A
6354961	12/2001	Allen	N/A	N/A
6354963	12/2001	Kodama et al.	N/A	N/A
6364788	12/2001	Helmstetter et al.	N/A	N/A
6379264	12/2001	Forzano	N/A	N/A
6379265	12/2001	Hirakawa et al.	N/A	N/A

6383090	12/2001	O'Doherty et al.	N/A	N/A
6386987	12/2001	Lejeune, Jr.	N/A	N/A
6386990	12/2001	Reyes et al.	N/A	N/A
6390933	12/2001	Galloway	N/A	N/A
6409612	12/2001	Evans et al.	N/A	N/A
6422951	12/2001	Burrows	N/A	N/A
6425832	12/2001	Cackett et al.	N/A	N/A
6434811	12/2001	Helmstetter et al.	N/A	N/A
6436142	12/2001	Paes et al.	N/A	N/A
6440009	12/2001	Guibaud et al.	N/A	N/A
6440010	12/2001	Deshmukh	N/A	N/A
6443851	12/2001	Liberatore	N/A	N/A
6447405	12/2001	Chen	N/A	N/A
6458044	12/2001	Vincent et al.	N/A	N/A
6461249	12/2001	Liberatore	N/A	N/A
6471604	12/2001	Hocknell et al.	N/A	N/A
6475101	12/2001	Burrows	N/A	N/A
6475102	12/2001	Helmstetter et al.	N/A	N/A
6478692	12/2001	Kosmatka	N/A	N/A
6491592	12/2001	Cackett et al.	N/A	N/A
6508978	12/2002	Deshmukh	N/A	N/A
6514154	12/2002	Finn	N/A	N/A
6524197	12/2002	Boone	N/A	N/A
6524198	12/2002	Takeda	N/A	N/A
6527649	12/2002	Neher et al.	N/A	N/A
6530847	12/2002	Antonious	N/A	N/A
6530848	12/2002	Gillig	N/A	N/A
6533679	12/2002	McCabe et al.	N/A	N/A
6547676	12/2002	Cackett et al.	N/A	N/A
6558273	12/2002	Kobayashi et al.	N/A	N/A
6565448	12/2002	Cameron et al.	N/A	N/A
6565452	12/2002	Helmstetter et al.	N/A	N/A
6569029	12/2002	Hamburger	N/A	N/A
6569040	12/2002	Bradstock	N/A	N/A
6572489	12/2002	Miyamoto et al.	N/A	N/A
6575845	12/2002	Galloway et al.	N/A	N/A
6575854	12/2002	Yang et al.	N/A	N/A
6582323	12/2002	Soracco et al.	N/A	N/A
6592468	12/2002	Vincent et al.	N/A	N/A
6602149	12/2002	Jacobson	N/A	N/A
6602150	12/2002	Kosmatka	N/A	N/A
6604568	12/2002	Bliss et al.	N/A	N/A
6605007	12/2002	Bissonnette et al.	N/A	N/A
6607452	12/2002	Helmstetter et al.	N/A	N/A
6612938	12/2002	Murphy et al.	N/A	N/A
6616547	12/2002	Vincent et al.	N/A	N/A
6623378	12/2002	Beach et al.	N/A	N/A
6638180	12/2002	Tsurumaki	N/A	N/A
6638183	12/2002	Takeda	N/A	N/A
D482089	12/2002	Burrows	N/A	N/A
D482090	12/2002	Burrows	N/A	N/A
D482420	12/2002	Burrows	N/A	N/A
6641487	12/2002	Hamburger	N/A	N/A
6641490	12/2002	Ellemor	N/A	N/A
6648772	12/2002	Vincent et al.	N/A	N/A
6648773	12/2002	Evans	N/A	N/A

6652387	12/2002	Liberatore	N/A	N/A
D484208	12/2002	Burrows	N/A	N/A
6663506	12/2002	Nishimoto et al.	N/A	N/A
6669571	12/2002	Cameron et al.	N/A	N/A
6669578	12/2002	Evans	N/A	N/A
6669580	12/2002	Cackett et al.	N/A	N/A
6676536	12/2003	Jacobson	N/A	N/A
6679786	12/2003	McCabe	N/A	N/A
6695712	12/2003	Iwata et al.	N/A	N/A
6716111	12/2003	Liberatore	N/A	N/A
6716114	12/2003	Nishio	N/A	N/A
6719510	12/2003	Cobzaru	N/A	N/A
6719641	12/2003	Dabbs et al.	N/A	N/A
6739982	12/2003	Murphy et al.	N/A	N/A
6739983	12/2003	Helmstetter et al.	N/A	N/A
6743118	12/2003	Soracco	N/A	N/A
6749523	12/2003	Forzano	N/A	N/A
6757572	12/2003	Forest	N/A	N/A
6758763	12/2003	Murphy et al.	N/A	N/A
6773360	12/2003	Willett et al.	N/A	N/A
6773361	12/2003	Lee	N/A	N/A
6776726	12/2003	Sano	N/A	N/A
6800038	12/2003	Willett et al.	N/A	N/A
6805643	12/2003	Lin	N/A	N/A
6808460	12/2003	Namiki	N/A	N/A
6824475	12/2003	Burnett et al.	N/A	N/A
6835145	12/2003	Tsurumaki	N/A	N/A
D501036	12/2004	Burrows	N/A	N/A
6855068	12/2004	Antonious	N/A	N/A
6860818	12/2004	Mahaffey et al.	N/A	N/A
6860823	12/2004	Lee	N/A	N/A
6860824	12/2004	Evans	N/A	N/A
6875124	12/2004	Gilbert et al.	N/A	N/A
6875129	12/2004	Erickson et al.	N/A	N/A
6881158	12/2004	Yang et al.	N/A	N/A
6881159	12/2004	Galloway et al.	N/A	N/A
6887165	12/2004	Tsurumaki	N/A	N/A
6890267	12/2004	Mahaffey et al.	N/A	N/A
6902497	12/2004	Deshmukh et al.	N/A	N/A
6904663	12/2004	Willett et al.	N/A	N/A
6923734	12/2004	Meyer	N/A	N/A
6926619	12/2004	Helmstetter et al.	N/A	N/A
6929565	12/2004	Nakahara et al.	N/A	N/A
6939247	12/2004	Schweigert et al.	N/A	N/A
6960142	12/2004	Bissonnette et al.	N/A	N/A
6964617	12/2004	Williams	N/A	N/A
6969326	12/2004	De Shiell	N/A	N/A
6974393	12/2004	Caldwell et al.	N/A	N/A
6988960	12/2005	Mahaffey et al.	N/A	N/A
6991558	12/2005	Beach et al.	N/A	N/A
D515165	12/2005	Zimmerman et al.	N/A	N/A
6997820	12/2005	Willett et al.	N/A	N/A
7004852	12/2005	Billings	N/A	N/A
7025692	12/2005	Erickson et al.	N/A	N/A
7029403	12/2005	Rice et al.	N/A	N/A
7063629	12/2005	Nakahara et al.	N/A	N/A

7070514	12/2005	Borunda	N/A	N/A
7077762	12/2005	Kouno et al.	N/A	N/A
7086964	12/2005	Chen et al.	N/A	N/A
7108609	12/2005	Stites et al.	N/A	N/A
7108614	12/2005	Lo	N/A	N/A
7128662	12/2005	Kumamoto	N/A	N/A
7128664	12/2005	Onoda et al.	N/A	N/A
7134971	12/2005	Franklin et al.	N/A	N/A
7137905	12/2005	Kohno	N/A	N/A
7137906	12/2005	Tsunoda et al.	N/A	N/A
7140974	12/2005	Chao et al.	N/A	N/A
7147572	12/2005	Kohno	N/A	N/A
7147573	12/2005	DiMarco	N/A	N/A
7153220	12/2005	Lo	N/A	N/A
7163468	12/2006	Gibbs et al.	N/A	N/A
7166038	12/2006	Williams et al.	N/A	N/A
7166040	12/2006	Chao et al.	N/A	N/A
7166041	12/2006	Evans	N/A	N/A
7169060	12/2006	Stevens et al.	N/A	N/A
7179034	12/2006	Ladouceur	N/A	N/A
7186190	12/2006	Beach et al.	N/A	N/A
7189169	12/2006	Billings	N/A	N/A
7198575	12/2006	Beach et al.	N/A	N/A
7201669	12/2006	Stites et al.	N/A	N/A
7223180	12/2006	Willett et al.	N/A	N/A
7252600	12/2006	Murphy et al.	N/A	N/A
7255654	12/2006	Murphy et al.	N/A	N/A
7267620	12/2006	Chao et al.	N/A	N/A
7273423	12/2006	Imamoto	N/A	N/A
7278926	12/2006	Frame	N/A	N/A
7278927	12/2006	Gibbs et al.	N/A	N/A
7294064	12/2006	Tsurumaki et al.	N/A	N/A
7294065	12/2006	Liang et al.	N/A	N/A
7314418	12/2007	Galloway et al.	N/A	N/A
7351161	12/2007	Beach	N/A	N/A
7371191	12/2007	Sugimoto	N/A	N/A
7377860	12/2007	Breier et al.	N/A	N/A
7396293	12/2007	Soracco	N/A	N/A
7404772	12/2007	Koide et al.	N/A	N/A
7407447	12/2007	Beach et al.	N/A	N/A
7419441	12/2007	Hoffman et al.	N/A	N/A
7438647	12/2007	Hocknell	N/A	N/A
7445563	12/2007	Werner	N/A	N/A
7448963	12/2007	Beach et al.	N/A	N/A
7462109	12/2007	Erickson et al.	N/A	N/A
D588223	12/2008	Kuan	N/A	N/A
7500924	12/2008	Yokota	N/A	N/A
7500926	12/2008	Rae et al.	N/A	N/A
7520820	12/2008	Dimarco	N/A	N/A
7530901	12/2008	Imamoto et al.	N/A	N/A
7530903	12/2008	Imamoto et al.	N/A	N/A
7530904	12/2008	Beach et al.	N/A	N/A
7540811	12/2008	Beach et al.	N/A	N/A
7563175	12/2008	Nishitani et al.	N/A	N/A
7568985	12/2008	Beach et al.	N/A	N/A
7572193	12/2008	Yokota	N/A	N/A

7578753	12/2008	Beach et al.	N/A	N/A
7582024	12/2008	Shear	N/A	N/A
7585233	12/2008	Horacek	N/A	N/A
7588502	12/2008	Nishino	473/332	A63B 60/02
7591737	12/2008	Gibbs et al.	N/A	N/A
7591738	12/2008	Beach et al.	N/A	N/A
7611424	12/2008	Nagai	473/335	A63B 60/02
7621823	12/2008	Beach et al.	N/A	N/A
7628707	12/2008	Beach et al.	N/A	N/A
7632193	12/2008	Thielen	N/A	N/A
7632194	12/2008	Hoffman et al.	N/A	N/A
7632196	12/2008	Reed et al.	N/A	N/A
7641569	12/2009	Best et al.	N/A	N/A
D612440	12/2009	Oldknow	N/A	N/A
7670235	12/2009	Lo	N/A	N/A
7674189	12/2009	Beach et al.	N/A	N/A
7682264	12/2009	Hsu et al.	N/A	N/A
7691006	12/2009	Burke	N/A	N/A
7695378	12/2009	Nakano	N/A	N/A
7699719	12/2009	Sugimoto	N/A	N/A
7717803	12/2009	DiMarco	N/A	N/A
7744484	12/2009	Chao	N/A	N/A
7749096	12/2009	Gibbs et al.	N/A	N/A
7749101	12/2009	Imamoto et al.	N/A	N/A
7753806	12/2009	Beach et al.	N/A	N/A
7758451	12/2009	Liang et al.	N/A	N/A
7758452	12/2009	Soracco	473/335	A63B 60/02
7771291	12/2009	Willett et al.	N/A	N/A
7775905	12/2009	Beach et al.	N/A	N/A
7775907	12/2009	Hirano	N/A	N/A
7798914	12/2009	Noble et al.	N/A	N/A
7806782	12/2009	Stites	473/409	A63B 53/0466
7824277	12/2009	Bennett et al.	N/A	N/A
7824280	12/2009	Yokota	473/334	A63B 60/02
7854364	12/2009	DeShiell et al.	N/A	N/A
7857711	12/2009	Shear	N/A	N/A
7857713	12/2009	Yokota	N/A	N/A
7867105	12/2010	Moon	N/A	N/A
7871339	12/2010	Sanchez et al.	N/A	N/A
7887431	12/2010	Beach et al.	N/A	N/A
7887434	12/2010	Beach et al.	N/A	N/A
7896753	12/2010	Boyd et al.	N/A	N/A
7914393	12/2010	Hirsch et al.	N/A	N/A
7934999	12/2010	Cackett et al.	N/A	N/A
7946931	12/2010	Oyama	N/A	N/A
7988565	12/2010	Abe	N/A	N/A
7993216	12/2010	Lee	N/A	N/A
8012038	12/2010	Beach et al.	N/A	N/A
8012039	12/2010	Greaney et al.	N/A	N/A
8016694	12/2010	Llewellyn et al.	N/A	N/A
8025587	12/2010	Beach et al.	N/A	N/A
8057323	12/2010	Liang et al.	N/A	N/A
8070623	12/2010	Stites et al.	N/A	N/A
8083609	12/2010	Burnett et al.	N/A	N/A
8088021	12/2011	Albertsen et al.	N/A	N/A
8105175	12/2011	Breier et al.	N/A	N/A

8118689	12/2011	Beach et al.	N/A	N/A
8133128	12/2011	Boyd et al.	N/A	N/A
8147350	12/2011	Beach et al.	N/A	N/A
8157672	12/2011	Greaney et al.	N/A	N/A
8167737	12/2011	Oyama	N/A	N/A
8177661	12/2011	Beach et al.	N/A	N/A
8182364	12/2011	Cole et al.	N/A	N/A
8192303	12/2011	Ban	N/A	N/A
8197358	12/2011	Watson et al.	N/A	N/A
8202175	12/2011	Ban	473/345	A63B 53/0466
8206243	12/2011	Stites	N/A	N/A
8206244	12/2011	Honea et al.	N/A	N/A
8235831	12/2011	Beach et al.	N/A	N/A
8235841	12/2011	Stites et al.	N/A	N/A
8235844	12/2011	Albertsen et al.	N/A	N/A
8241143	12/2011	Albertsen et al.	N/A	N/A
8241144	12/2011	Albertsen et al.	N/A	N/A
8257195	12/2011	Erickson	N/A	N/A
8257196	12/2011	Abbott et al.	N/A	N/A
8262498	12/2011	Beach et al.	N/A	N/A
8262506	12/2011	Watson et al.	N/A	N/A
8277337	12/2011	Shimazaki	N/A	N/A
8292756	12/2011	Greaney et al.	N/A	N/A
8303431	12/2011	Beach et al.	N/A	N/A
8303433	12/2011	Roach et al.	N/A	N/A
8328659	12/2011	Shear	N/A	N/A
8337319	12/2011	Sargent et al.	N/A	N/A
8337326	12/2011	Lukasiewicz et al.	N/A	N/A
8353786	12/2012	Beach et al.	N/A	N/A
D675692	12/2012	Oldknow et al.	N/A	N/A
8376878	12/2012	Bennett et al.	N/A	N/A
8382607	12/2012	Burnett	473/288	A63B 53/06
D678964	12/2012	Oldknow et al.	N/A	N/A
D678965	12/2012	Oldknow et al.	N/A	N/A
D678968	12/2012	Oldknow et al.	N/A	N/A
D678969	12/2012	Oldknow et al.	N/A	N/A
D678970	12/2012	Oldknow et al.	N/A	N/A
D678971	12/2012	Oldknow et al.	N/A	N/A
D678972	12/2012	Oldknow et al.	N/A	N/A
D678973	12/2012	Oldknow et al.	N/A	N/A
8398503	12/2012	Beach et al.	N/A	N/A
8403771	12/2012	Rice et al.	N/A	N/A
D679354	12/2012	Oldknow et al.	N/A	N/A
8425348	12/2012	Boyd	473/335	A63B 53/0466
8430763	12/2012	Beach	473/307	A63B 53/02
8435132	12/2012	Oldknow et al.	N/A	N/A
8435134	12/2012	Tang et al.	N/A	N/A
8496541	12/2012	Beach et al.	N/A	N/A
8496544	12/2012	Curtis et al.	N/A	N/A
8517855	12/2012	Beach et al.	N/A	N/A
8517860	12/2012	Albertsen et al.	N/A	N/A
8523702	12/2012	Thomas et al.	N/A	N/A
8529368	12/2012	Rice et al.	N/A	N/A
8540588	12/2012	Rice et al.	N/A	N/A
8562453	12/2012	Sato	N/A	N/A
8579728	12/2012	Morales et al.	N/A	N/A

8591351	12/2012	Albertsen et al.	N/A	N/A
8602907	12/2012	Beach et al.	N/A	N/A
8616999	12/2012	Greaney et al.	N/A	N/A
D697152	12/2013	Harbert et al.	N/A	N/A
8622847	12/2013	Beach et al.	N/A	N/A
8628433	12/2013	Stites et al.	N/A	N/A
8632419	12/2013	Tang et al.	N/A	N/A
8641555	12/2013	Stites et al.	N/A	N/A
8663029	12/2013	Beach et al.	N/A	N/A
8678949	12/2013	Shimazaki	N/A	N/A
8684863	12/2013	Bezilla	473/335	A63B 53/06
8690704	12/2013	Thomas	N/A	N/A
8690707	12/2013	Stites	473/335	A63B 60/42
8695487	12/2013	Sakane et al.	N/A	N/A
8696487	12/2013	Beach et al.	N/A	N/A
8696491	12/2013	Myers	N/A	N/A
8702531	12/2013	Boyd et al.	N/A	N/A
8721471	12/2013	Albertsen et al.	N/A	N/A
8727900	12/2013	Beach et al.	N/A	N/A
8734271	12/2013	Beach et al.	N/A	N/A
D707768	12/2013	Oldknow et al.	N/A	N/A
D707769	12/2013	Oldknow et al.	N/A	N/A
D707773	12/2013	Oldknow et al.	N/A	N/A
8747250	12/2013	Chao et al.	N/A	N/A
8753222	12/2013	Beach et al.	N/A	N/A
8753226	12/2013	Rice et al.	N/A	N/A
8753229	12/2013	Rae et al.	N/A	N/A
8758153	12/2013	Sargent et al.	N/A	N/A
8758163	12/2013	Stites	N/A	N/A
D708281	12/2013	Oldknow et al.	N/A	N/A
8783086	12/2013	Hirano	N/A	N/A
8790195	12/2013	Myers	473/335	A63B 53/0466
8795101	12/2013	Nishio	N/A	N/A
8821312	12/2013	Burnett	473/345	A63B 60/52
8827831	12/2013	Burnett et al.	N/A	N/A
8834289	12/2013	de la Cruz et al.	N/A	N/A
8834290	12/2013	Bezilla et al.	N/A	N/A
8834293	12/2013	Thomas et al.	N/A	N/A
8834294	12/2013	Seluga	473/345	A63B 53/04
8845450	12/2013	Beach et al.	N/A	N/A
8845454	12/2013	Boyd et al.	N/A	N/A
D714893	12/2013	Atwell	N/A	N/A
8876622	12/2013	Beach et al.	N/A	N/A
8876627	12/2013	Beach et al.	N/A	N/A
8888607	12/2013	Beach et al.	N/A	N/A
8900069	12/2013	Beach et al.	N/A	N/A
D722122	12/2014	Greensmith	N/A	N/A
8944934	12/2014	Yamamoto	N/A	N/A
8956240	12/2014	Beach et al.	N/A	N/A
8956244	12/2014	Westrum et al.	N/A	N/A
8986133	12/2014	Bennett et al.	N/A	N/A
8992339	12/2014	Matsunaga	473/335	A63B 53/04
9033821	12/2014	Beach et al.	N/A	N/A
9061186	12/2014	Larson	N/A	N/A
9072949	12/2014	Stites	N/A	A63B 53/04
9095753	12/2014	Bezilla et al.	N/A	N/A

9101811	12/2014	Goudarzi et al.	N/A	N/A
9144718	12/2014	Johnson	N/A	A63B 60/00
9162120	12/2014	Jertson et al.	N/A	N/A
9168438	12/2014	Boyd	N/A	N/A
9180348	12/2014	Beach et al.	N/A	N/A
9180349	12/2014	Seluga	N/A	A63B 53/0466
9186560	12/2014	Harbert et al.	N/A	N/A
9199145	12/2014	Myers	N/A	N/A
9205312	12/2014	Zimmerman	N/A	A63B 53/0466
9211447	12/2014	Harbert et al.	N/A	N/A
9211453	12/2014	Foster	N/A	A63B 53/06
9220953	12/2014	Beach et al.	N/A	N/A
9220955	12/2014	Hayase et al.	N/A	N/A
9227115	12/2015	Cameron	N/A	N/A
9238162	12/2015	Breier	N/A	A63B 60/52
9259627	12/2015	Myers	N/A	A63B 53/04
9289660	12/2015	Myers	N/A	A63B 53/0466
9295885	12/2015	Matsunaga	N/A	A63B 60/52
9364728	12/2015	Myers	N/A	A63B 60/52
9381406	12/2015	Boggs	N/A	N/A
9381410	12/2015	Golden	N/A	A63B 53/0466
9387373	12/2015	DeMille et al.	N/A	N/A
9403069	12/2015	Boyd et al.	N/A	N/A
9421438	12/2015	Beno et al.	N/A	N/A
9433836	12/2015	Breier	N/A	A63B 53/0466
9440126	12/2015	Boyd	N/A	A63B 60/04
9468816	12/2015	Barelmann et al.	N/A	N/A
9486677	12/2015	Seluga et al.	N/A	N/A
9498688	12/2015	Galvan et al.	N/A	N/A
9561405	12/2016	Rae et al.	N/A	N/A
9597558	12/2016	Seluga et al.	N/A	N/A
9597561	12/2016	Seluga	N/A	A63B 60/52
9597563	12/2016	Voshall et al.	N/A	N/A
9623291	12/2016	Greensmith et al.	N/A	N/A
9623294	12/2016	Kingston	N/A	A63B 60/52
9623302	12/2016	Myers	N/A	A63B 53/0466
9630069	12/2016	Foster et al.	N/A	N/A
9636552	12/2016	Cleghorn et al.	N/A	N/A
9636553	12/2016	Myers	N/A	N/A
9662545	12/2016	Beach et al.	N/A	N/A
9687701	12/2016	Seluga et al.	N/A	N/A
9687702	12/2016	Seluga et al.	N/A	N/A
9694257	12/2016	Seluga et al.	N/A	N/A
9694261	12/2016	Nunez	N/A	A63B 60/52
9700763	12/2016	Harbert et al.	N/A	N/A
9700764	12/2016	Carter	N/A	A63B 53/0466
9700769	12/2016	Beach et al.	N/A	N/A
9700771	12/2016	Murphy	N/A	A63B 53/06
9707457	12/2016	Mata et al.	N/A	N/A
9707459	12/2016	Myers	N/A	A63B 60/52
9717962	12/2016	Seluga et al.	N/A	N/A
9724577	12/2016	Kingston et al.	N/A	N/A
9731175	12/2016	Myers	N/A	A63B 60/04
9764210	12/2016	Curtis	N/A	A63B 53/0466
9776058	12/2016	Seluga et al.	N/A	N/A
9795840	12/2016	Greensmith et al.	N/A	N/A

9814954	12/2016	Westrum et al.	N/A	N/A
9855474	12/2017	Beno et al.	N/A	N/A
9855476	12/2017	Seluga et al.	N/A	N/A
9861864	12/2017	Beach et al.	N/A	N/A
9861865	12/2017	Harbert et al.	N/A	N/A
9868036	12/2017	Kleinert	N/A	A63B 53/06
9901794	12/2017	Beno et al.	N/A	N/A
9908017	12/2017	Seluga et al.	N/A	N/A
9914027	12/2017	Harbert et al.	N/A	N/A
9914028	12/2017	Cleghorn	N/A	A63B 60/02
9914030	12/2017	Cleghorn et al.	N/A	N/A
9931549	12/2017	Seluga et al.	N/A	N/A
9987533	12/2017	Oldknow	N/A	A63B 60/04
9993700	12/2017	Beach et al.	N/A	N/A
10004954	12/2017	Chen et al.	N/A	N/A
10035049	12/2017	Nielson et al.	N/A	N/A
10035051	12/2017	Cleghorn et al.	N/A	N/A
10065094	12/2017	Wallin	N/A	N/A
10076688	12/2017	Harbert et al.	N/A	N/A
10086240	12/2017	Hoffman et al.	N/A	N/A
10159880	12/2017	Mine	N/A	A63B 53/0466
10173111	12/2018	Busch et al.	N/A	N/A
10183202	12/2018	Harbert et al.	N/A	N/A
10213665	12/2018	Day et al.	N/A	N/A
10398952	12/2018	Yi et al.	N/A	N/A
10398954	12/2018	Kline et al.	N/A	N/A
10463928	12/2018	Stokke et al.	N/A	N/A
10478679	12/2018	Harbert et al.	N/A	N/A
10556161	12/2019	Jertson et al.	N/A	N/A
10569144	12/2019	Nielson et al.	N/A	N/A
10576337	12/2019	Soracco et al.	N/A	N/A
10596428	12/2019	Rumble	N/A	A63B 60/02
10639524	12/2019	Penney	N/A	A63B 53/06
10653926	12/2019	Story	N/A	A63B 53/0466
10668341	12/2019	Jertson et al.	N/A	N/A
10843048	12/2019	Hoffman et al.	N/A	N/A
10898764	12/2020	Harbert et al.	N/A	N/A
10926143	12/2020	Bennett	N/A	A63B 60/02
10974109	12/2020	Stokke	N/A	A63B 53/04
11090536	12/2020	Bennett	N/A	A63B 53/08
11192005	12/2020	Bennett	N/A	A63B 60/02
11400350	12/2021	Story et al.	N/A	N/A
11406881	12/2021	Harbert	N/A	A63B 53/06
11684830	12/2022	Mizutani	473/345	A63B 53/04
11759685	12/2022	Johnson	473/282	A63B 53/06
2001/0049310	12/2000	Cheng et al.	N/A	N/A
2001/0055995	12/2000	Cackett et al.	N/A	N/A
2002/0022535	12/2001	Takeda	N/A	N/A
2002/0025861	12/2001	Ezawa	N/A	N/A
2002/0032075	12/2001	Vatsvog	N/A	N/A
2002/0055396	12/2001	Nishimoto et al.	N/A	N/A
2002/0072434	12/2001	Yabu	N/A	N/A
2002/0123394	12/2001	Tsurumaki	N/A	N/A
2002/0137576	12/2001	Dammen	N/A	N/A
2002/0142859	12/2001	Galloway et al.	N/A	N/A
2002/0160854	12/2001	Beach et al.	N/A	N/A

2002/0169036	12/2001	Boone	N/A	N/A
2002/0183134	12/2001	Allen et al.	N/A	N/A
2003/0013545	12/2002	Vincent et al.	N/A	N/A
2003/0032500	12/2002	Nakahara et al.	N/A	N/A
2003/0036442	12/2002	Chao et al.	N/A	N/A
2003/0130059	12/2002	Billings	N/A	N/A
2004/0023729	12/2003	Nagai et al.	N/A	N/A
2004/0034986	12/2003	Cheng et al.	N/A	N/A
2004/0087388	12/2003	Beach et al.	N/A	N/A
2004/0116207	12/2003	De Shiell et al.	N/A	N/A
2004/0121852	12/2003	Tsurumaki	N/A	N/A
2004/0157678	12/2003	Kohno	N/A	N/A
2004/0157680	12/2003	Chen	N/A	N/A
2004/0176180	12/2003	Yamaguchi et al.	N/A	N/A
2004/0176183	12/2003	Tsurumaki	N/A	N/A
2004/0180730	12/2003	Franklin et al.	N/A	N/A
2004/0192463	12/2003	Tsurumaki et al.	N/A	N/A
2004/0192467	12/2003	Hocknell et al.	N/A	N/A
2004/0192468	12/2003	Onoda et al.	N/A	N/A
2004/0214660	12/2003	Chen	N/A	N/A
2004/0235584	12/2003	Chao et al.	N/A	N/A
2004/0242343	12/2003	Chao et al.	N/A	N/A
2005/0003903	12/2004	Galloway	N/A	N/A
2005/0049075	12/2004	Chen et al.	N/A	N/A
2005/0070371	12/2004	Chen et al.	N/A	N/A
2005/0096151	12/2004	Hou et al.	N/A	N/A
2005/0096154	12/2004	Chen	N/A	N/A
2005/0101404	12/2004	Long et al.	N/A	N/A
2005/0124435	12/2004	Gambetta et al.	N/A	N/A
2005/0137024	12/2004	Stites et al.	N/A	N/A
2005/0176522	12/2004	Erickson et al.	N/A	N/A
2005/0181884	12/2004	Beach et al.	N/A	N/A
2005/0209024	12/2004	Oyama	N/A	N/A
2005/0215350	12/2004	Reyes et al.	N/A	N/A
2005/0227781	12/2004	Huang et al.	N/A	N/A
2005/0233830	12/2004	Williams	N/A	N/A
2005/0239575	12/2004	Chao et al.	N/A	N/A
2005/0239576	12/2004	Stites et al.	N/A	N/A
2005/0266933	12/2004	Galloway	N/A	N/A
2006/0019768	12/2005	Lo	N/A	N/A
2006/0019770	12/2005	Meyer et al.	N/A	N/A
2006/0035722	12/2005	Beach et al.	N/A	N/A
2006/0046869	12/2005	Galloway	N/A	N/A
2006/0058112	12/2005	Haralason et al.	N/A	N/A
2006/0068932	12/2005	Rice et al.	N/A	N/A
2006/0073910	12/2005	Imamoto et al.	N/A	N/A
2006/0084525	12/2005	Imamoto et al.	N/A	N/A
2006/0122004	12/2005	Chen et al.	N/A	N/A
2006/0128500	12/2005	Tavares	N/A	N/A
2006/0154747	12/2005	Beach	N/A	N/A
2006/0172816	12/2005	Johnson	N/A	N/A
2006/0172821	12/2005	Evans	N/A	N/A
2006/0189407	12/2005	Soracco	N/A	N/A
2006/0229141	12/2005	Galloway	N/A	N/A
2006/0240907	12/2005	Latiri	N/A	N/A
2006/0240908	12/2005	Adams et al.	N/A	N/A

2007/0021234	12/2006	Tsurumaki et al.	N/A	N/A
2007/0026961	12/2006	Hou	N/A	N/A
2007/0049400	12/2006	Imamoto et al.	N/A	N/A
2007/0049415	12/2006	Shear	N/A	N/A
2007/0049417	12/2006	Shear	N/A	N/A
2007/0054750	12/2006	Rice	N/A	N/A
2007/0105646	12/2006	Beach et al.	N/A	N/A
2007/0105647	12/2006	Beach et al.	N/A	N/A
2007/0105648	12/2006	Beach et al.	N/A	N/A
2007/0105649	12/2006	Beach et al.	N/A	N/A
2007/0105650	12/2006	Beach et al.	N/A	N/A
2007/0105651	12/2006	Beach et al.	N/A	N/A
2007/0105652	12/2006	Beach et al.	N/A	N/A
2007/0105653	12/2006	Beach et al.	N/A	N/A
2007/0105654	12/2006	Beach et al.	N/A	N/A
2007/0105655	12/2006	Beach et al.	N/A	N/A
2007/0117648	12/2006	Yokota	N/A	N/A
2007/0117652	12/2006	Beach et al.	N/A	N/A
2007/0149315	12/2006	Bennett et al.	N/A	N/A
2007/0178988	12/2006	Tavares et al.	N/A	N/A
2008/0020861	12/2007	Adams et al.	N/A	N/A
2008/0132353	12/2007	Hsiao	N/A	N/A
2008/0146370	12/2007	Beach et al.	N/A	N/A
2008/0161127	12/2007	Yamamoto	N/A	N/A
2008/0261715	12/2007	Carter	N/A	N/A
2008/0261717	12/2007	Hoffman et al.	N/A	N/A
2008/0280698	12/2007	Hoffman et al.	N/A	N/A
2009/0048035	12/2008	Stites et al.	N/A	N/A
2009/0062029	12/2008	Stites et al.	N/A	N/A
2009/0088269	12/2008	Beach et al.	N/A	N/A
2009/0088271	12/2008	Beach et al.	N/A	N/A
2009/0118034	12/2008	Yokota	473/345	A63B 53/0466
2009/0137338	12/2008	Kajita	N/A	N/A
2009/0170632	12/2008	Beach et al.	N/A	N/A
2009/0221383	12/2008	Ban et al.	N/A	N/A
2009/0258725	12/2008	Jones	N/A	N/A
2009/0264214	12/2008	De La Cruz et al.	N/A	N/A
2009/0286611	12/2008	Beach et al.	N/A	N/A
2009/0286618	12/2008	Beach et al.	N/A	N/A
2009/0286619	12/2008	Beach et al.	N/A	N/A
2009/0318245	12/2008	Yim et al.	N/A	N/A
2010/0000071	12/2009	Rice	N/A	N/A
2010/0016095	12/2009	Burnett et al.	N/A	N/A
2010/0029402	12/2009	Noble et al.	N/A	N/A
2010/0029404	12/2009	Shear	N/A	N/A
2010/0029408	12/2009	Abe	N/A	N/A
2010/0035701	12/2009	Kusumoto	N/A	N/A
2010/0048316	12/2009	Honea et al.	N/A	N/A
2010/0048321	12/2009	Beach et al.	N/A	N/A
2010/0075774	12/2009	Ban	N/A	N/A
2010/0113176	12/2009	Boyd et al.	N/A	N/A
2010/0139073	12/2009	Galloway	N/A	N/A
2010/0139079	12/2009	Dawson et al.	N/A	N/A
2010/0144461	12/2009	Ban	N/A	N/A
2010/0167837	12/2009	Ban	N/A	N/A
2010/0197423	12/2009	Thomas et al.	N/A	N/A

2010/0197426	12/2009	De La Cruz et al.	N/A	N/A
2010/0234126	12/2009	Cackett et al.	N/A	N/A
2010/0234127	12/2009	Snyder et al.	N/A	N/A
2010/0273565	12/2009	Stites et al.	N/A	N/A
2010/0331103	12/2009	Takahashi et al.	N/A	N/A
2011/0014995	12/2010	Wada et al.	N/A	N/A
2011/0021284	12/2010	Stites et al.	N/A	N/A
2011/0081986	12/2010	Stites	473/334	A63B 60/00
2011/0098127	12/2010	Yamamoto	N/A	N/A
2011/0151989	12/2010	Golden et al.	N/A	N/A
2011/0151997	12/2010	Shear	N/A	N/A
2011/0195798	12/2010	Sander et al.	N/A	N/A
2011/0218053	12/2010	Tang et al.	N/A	N/A
2011/0294599	12/2010	Albertsen et al.	N/A	N/A
2011/0312437	12/2010	Sargent et al.	N/A	N/A
2012/0083359	12/2011	Stites	N/A	N/A
2012/0083360	12/2011	Boyd	473/337	A63B 53/06
2012/0083362	12/2011	Albertsen et al.	N/A	N/A
2012/0083363	12/2011	Albertsen et al.	N/A	N/A
2012/0122601	12/2011	Beach et al.	N/A	N/A
2012/0142447	12/2011	Boyd et al.	N/A	N/A
2012/0142452	12/2011	Burnett et al.	N/A	N/A
2012/0149491	12/2011	Beach et al.	N/A	N/A
2012/0165110	12/2011	Cheng	N/A	N/A
2012/0165111	12/2011	Cheng	N/A	N/A
2012/0196701	12/2011	Stites et al.	N/A	N/A
2012/0202615	12/2011	Beach et al.	N/A	N/A
2012/0220387	12/2011	Beach et al.	N/A	N/A
2012/0244960	12/2011	Tang et al.	N/A	N/A
2012/0270676	12/2011	Burnett et al.	N/A	N/A
2012/0277029	12/2011	Albertsen et al.	N/A	N/A
2012/0277030	12/2011	Albertsen et al.	N/A	N/A
2012/0289360	12/2011	Breier et al.	N/A	N/A
2012/0289361	12/2011	Beach et al.	N/A	N/A
2012/0302366	12/2011	Murphy	N/A	N/A
2013/0065705	12/2012	Morales et al.	N/A	N/A
2013/0090185	12/2012	Boyd	473/337	A63B 60/02
2013/0102410	12/2012	Stites et al.	N/A	N/A
2013/0165254	12/2012	Rice et al.	N/A	N/A
2013/0210542	12/2012	Harbert et al.	N/A	N/A
2013/0324284	12/2012	Stites et al.	N/A	N/A
2014/0031141	12/2013	Myrhum	N/A	N/A
2014/0080629	12/2013	Sargent et al.	N/A	N/A
2014/0162809	12/2013	Soracco	N/A	N/A
2015/0011328	12/2014	Harbert et al.	N/A	N/A
2015/0065265	12/2014	Motokawa et al.	N/A	N/A
2015/0105177	12/2014	Beach et al.	N/A	N/A
2015/0217167	12/2014	Frame et al.	N/A	N/A
2015/0231453	12/2014	Harbert et al.	N/A	N/A
2015/0297961	12/2014	Voshall et al.	N/A	N/A
2015/0306475	12/2014	Curtis et al.	N/A	N/A
2015/0321055	12/2014	Golden	473/334	A63B 60/42
2016/0001146	12/2015	Sargent et al.	N/A	N/A
2016/0008682	12/2015	Beach et al.	N/A	N/A
2016/0023060	12/2015	Harbert et al.	N/A	N/A
2016/0236047	12/2015	Chen et al.	N/A	N/A

2016/0250525	12/2015	Motokawa et al.	N/A	N/A
2016/0271464	12/2015	Murphy et al.	N/A	N/A
2016/0279490	12/2015	Onuki	N/A	N/A
2017/0304692	12/2016	Beach et al.	N/A	N/A
2018/0147461	12/2017	Stokke	N/A	A63B 53/04
2021/0086042	12/2020	Story et al.	N/A	N/A
2021/0128994	12/2020	Yi	N/A	A63B 53/047
2022/0111263	12/2021	Yi	N/A	A63B 53/0433

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2436182	12/2000	CN	N/A
2742991	12/2004	CN	N/A
201353407	12/2008	CN	N/A
203389296	12/2013	CN	N/A
204106986	12/2014	CN	N/A
3711964	12/1987	DE	N/A
9012884	12/1989	DE	N/A
0470488	12/1994	EP	N/A
0617987	12/1996	EP	N/A
1001175	12/1999	EP	N/A
2377586	12/2010	EP	N/A
3434340	12/2018	EP	A63B 53/04
194823	12/1922	GB	N/A
2327889	12/1998	GB	N/A
S57157374	12/1981	JP	N/A
H4180778	12/1991	JP	N/A
H05317465	12/1992	JP	N/A
H06126004	12/1993	JP	N/A
H06190088	12/1993	JP	N/A
H06238022	12/1993	JP	N/A
H06304271	12/1993	JP	N/A
3035480	12/1995	JP	N/A
09-028844	12/1996	JP	N/A
H09308717	12/1996	JP	N/A
H09327534	12/1996	JP	N/A
H10234902	12/1997	JP	N/A
H10277187	12/1997	JP	N/A
H11114102	12/1998	JP	N/A
2000014841	12/1999	JP	N/A
2000197718	12/1999	JP	N/A
2001054595	12/2000	JP	N/A
2001129130	12/2000	JP	N/A
2001170225	12/2000	JP	N/A
2001204856	12/2000	JP	N/A
2001346918	12/2000	JP	N/A
2002003969	12/2001	JP	N/A
2002017910	12/2001	JP	N/A
2002052099	12/2001	JP	N/A
2002248183	12/2001	JP	N/A
2002253706	12/2001	JP	N/A
2003038691	12/2002	JP	N/A
2003093554	12/2002	JP	N/A
2003126311	12/2002	JP	N/A
2003226952	12/2002	JP	N/A
2004174224	12/2003	JP	N/A

2004183058	12/2003	JP	N/A
2004222911	12/2003	JP	N/A
2004261451	12/2003	JP	N/A
2004267438	12/2003	JP	N/A
2004313762	12/2003	JP	N/A
2004351054	12/2003	JP	N/A
2004351173	12/2003	JP	N/A
2005028170	12/2004	JP	N/A
2005296458	12/2004	JP	N/A
2005296582	12/2004	JP	N/A
2005323978	12/2004	JP	N/A
2006101918	12/2005	JP	N/A
2006198385	12/2005	JP	N/A
2006231063	12/2005	JP	N/A
2006320493	12/2005	JP	N/A
2007312846	12/2006	JP	N/A
2008515560	12/2007	JP	N/A
4128970	12/2007	JP	N/A
2008200118	12/2007	JP	N/A
2008272274	12/2007	JP	N/A
2009000281	12/2008	JP	N/A
2010252964	12/2009	JP	N/A
2010279847	12/2009	JP	N/A
2011005167	12/2010	JP	A63B 53/0466
2011024999	12/2010	JP	N/A
2011229914	12/2010	JP	N/A
2011229914	12/2010	JP	N/A
2012-115415	12/2011	JP	N/A
2012125291	12/2011	JP	N/A
2014131766	12/2013	JP	A63B 53/0466
2015019998	12/2014	JP	A63B 53/02
I389719	12/2012	TW	N/A
M465945	12/2012	TW	N/A
I526236	12/2015	TW	N/A
WO 88/02642	12/1987	WO	N/A
WO 96/22817	12/1995	WO	N/A
WO 1999/020358	12/1998	WO	N/A
WO 2001/049376	12/2000	WO	N/A
WO 01/66199	12/2000	WO	N/A
WO 02/062501	12/2001	WO	N/A
WO 03/061773	12/2002	WO	N/A
WO 2004/043549	12/2003	WO	N/A
WO 2006/044631	12/2005	WO	N/A
WO-2013028853	12/2012	WO	A63B 53/00
WO 2014/070343	12/2013	WO	N/A

OTHER PUBLICATIONS

Adams Golf Speedline F11 Ti 14.5 degree fairway wood (www.bombsquadgolf.com, posted Oct. 18, 2010).
cited by applicant

Callaway Golf, World's Straightest Driver: FT-i Driver downloaded from
www.callawaygolf.com/ft%2Di/driver.aspx?lang=en on Apr. 5, 2007. cited by applicant

Declaration of Tim Reed, VP of R&D, Adams Golf, Inc., dated Dec. 7, 2012. cited by applicant

Jackson, Jeff, The Modern Guide to Golf Clubmaking, Ohio: Dynacraft Golf Products, Inc., copyright 1994, p.
237. cited by applicant

Nike Golf, Sasquatch 460, downloaded from www.nike.com/nikegolf/index.htm on Apr. 5, 2007. cited by
applicant

Nike Golf, Sasquatch Sumo Squared Driver, downloaded from www.nike.com/nikegolf/index.htm on Apr. 5, 2007. cited by applicant
Taylor Made Golf Company, Inc. Press Release, Burner Fairway Wood, www.tmag.com/media/pressreleases/2007/011807_burner_fairway_rescue.html, Jan. 26, 2007. cited by applicant
Taylor Made Golf Company Inc., R7 460 Drivers, downloaded from www.taylormadegolf.com/product_detail.asp?pID=14section=overview on Apr. 5, 2007. cited by applicant
Titleist 907D1, downloaded from www.tees2greens.com/forum/Uploads/Images/7ade3521-192b-4611-870b-395d.jpg on Feb. 1, 2007. cited by applicant

Primary Examiner: Hunter; Alvin A

Attorney, Agent or Firm: Klarquist Sparkman, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/390,615, filed Jul. 30, 2021, which is a continuation-in-part of U.S. patent application Ser. No. 17/135,666, filed Dec. 28, 2020, now U.S. Pat. No. 11,406,881. Each of these applications is incorporated by reference herein in its entirety. (2) In addition, other patents and patent applications concerning golf clubs, including U.S. Pat. Nos. 7,753,806; 7,887,434; 8,118,689; 8,663,029; 8,888,607; 8,900,069; 9,186,560; 9,211,447; 9,220,953; 9,220,956; 9,848,405; and 9,700,763 and U.S. patent application Ser. No. 15/859,071, are incorporated by reference herein in their entirety.

FIELD

(1) This application concerns golf club heads, and more particularly, golf club heads for wood-type clubs including driver-type, fairway-type, and hybrid-type golf clubs.

BACKGROUND

(2) Much of the recent improvement activity in the field of golf has involved the use of new and increasingly more sophisticated materials in concert with advanced club-head engineering. For example, modern “wood-type” golf clubs (notably, “drivers,” “fairway woods,” and “utility or hybrid clubs”), with their sophisticated shafts and non-wooden club-heads, bear little resemblance to the “wood” drivers, low-loft long-irons, and higher numbered fairway woods used years ago. These modern wood-type clubs are generally called “metalwoods” since they tend to be made primarily of strong, lightweight metals, such as titanium.

(3) An exemplary metalwood golf club such as a driver or fairway wood typically includes a hollow shaft having a lower end to which the golf club head is attached. Most modern versions of these golf club heads are made, at least in part, of a lightweight but strong metal such as titanium alloy. In many cases, the golf club head comprises a body made primarily of such strong metals.

(4) Some current approaches to reducing structural mass of a metalwood club-head are directed to making one or more portions of the golf club head of an alternative material. Whereas the bodies and face plates of most current metalwoods are made of titanium alloys, some golf club heads are made, at least in part, of components formed from either graphite/epoxy-composite (or other suitable composite material) and a metal alloy. Graphite composites have a much lower density compared to titanium alloys, which offers an opportunity to provide more discretionary mass in the club-head.

(5) The ability to utilize such materials to increase the discretionary mass available for placement at various points in the club-head allows for optimization of a number of physical properties of the club-head which can greatly impact the performance obtained by the user. Forgiveness on a golf shot is generally maximized by configuring the golf club head such that the center of gravity (“CG”) of the golf club head is optimally located and the moment of inertia (“MOI”) of the golf club head is maximized. CG and MOI can also critically affect a golf club head's performance, such as launch angle and flight trajectory on impact with a golf ball, among other characteristics.

(6) In addition to the use of various materials to optimize the strength-to-weight properties and acoustic properties of the golf club heads, advances have been made in the mass distribution properties provided by using thicker and thinner regions of materials, raising and lowering certain portions of the sole and crown, providing adjustable weight members and adjustable head-shaft connection assemblies, and many other golf

SUMMARY

(7) This application discloses, among other innovations, wood-type golf club heads that provide, among other attributes, improved forgiveness, ball speed, adjustability and playability, while maintaining durability.

(8) The following describes wood-type golf club heads that include a body defining an interior cavity, a sole positioned at a bottom portion of the golf club head and a crown positioned at a top portion. The body also has a face defining a forward portion extending between a heel portion of the golf club head and a toe portion of the golf club head, a rearward portion opposite the face, and a hosel.

(9) Certain of the described golf club heads have a weight channel formed in the sole and defining a path along the sole. In certain instances, a weight member is positioned in or on the weight channel, and may be configured to be adjusted along the path to any of a range of selectable positions in the weight channel to adjust mass properties of the golf club head. In particular instances, a fastener is configured to secure the weight member to the golf club head body in any of the selectable positions along the path. In certain examples, there are at least five, or in some cases at least ten such selectable positions. The fastener may be secured to the golf club head body at a fixed location that is independent of the position of the weight member along the path, so that this position does not change, regardless of where the weight member is positioned along the path.

(10) In certain instances, the path may comprise a substantially linear path extending in a substantially heel-toe direction, or, alternatively, in a substantially forward-rearward direction. In other instances, the path comprises a curved path extending in a substantially heel-toe direction. In some instances, the weight channel is positioned in a forward portion of the sole, and, in particular instances, the channel comprises a toe and a heel end, and wherein the channel curves rearwardly at the toe and heel ends, away from the face. In other instances, the channel is positioned in a rearward portion of the sole, and, in particular instances, the channel comprises a toe end and a heel end, and wherein the channel curves forwardly at the toe and heel ends. In some instances, the weight channel comprises an outer arc that extends at least half of a length of the golf club head from a heel of the golf club head to a toe of the golf club head, or half of a depth of the golf club head from the face to a trailing edge of the golf club head.

(11) The weight member may comprise a forward side and a rearward side. In particular instances, the forward side of the weight member is curved parallel to a corresponding curved forward edge of the weight channel. In some cases, the rearward side is also curved parallel to a corresponding curved rearward edge of the weight channel. In particular instances, the weight member is positioned entirely external to the interior cavity. In some instances, a lower surface of the weight member is approximately parallel to the sole to serve as a ground contact point when the golf club head is soled.

(12) The golf club may comprise a front channel in the sole positioned forward of the weight channel and extending into the interior cavity of the golf club head, the front channel extending substantially in a heel-toe direction. The front channel, or a similar slot channel in addition to the weight channel may increase or enhance the perimeter flexibility of the striking face of the golf club head in order to increase the coefficient of restitution and/or characteristic time of the golf club head and frees up additional discretionary mass which can be utilized elsewhere in the golf club head. In some instances, the front channel, or similar slot or other mechanism is located in the forward portion of the sole of the golf club head, adjacent to or near to the forwardmost edge of the sole. Also, in some instances, the front channel extends into the interior cavity of the golf club head, and in particular cases extends substantially in a heel-toe direction.

(13) In particular instances, the weight member comprises an elongated weight slot that extends through an interior of the weight member, the fastener extends through the weight slot, and is configured to permit the weight member to translate along the path while the fastener is stationary. In some instances, the fastener comprises a fastener head that is recessed within the weight slot and a threaded fastener shaft that extends from the fastener head and is secured to the body at a fastener port in the body. In certain instances, the fastener port is forward of the fastener head. The fastener may be configured to, in a loosened position, allow the weight member to translate along the path as the fastener remains stationary relative to the fastener port. The fastener may further be configured to, in a secured position, retain the weight member in a selected position. In some instances, the fastener may comprise two or more fasteners each passing through the weight slot and secured to the golf club head body at different locations. In some instances, the fastener may itself comprise a removable weight, which mass can be adjusted as desired to adjust mass properties of the golf club head. In some instances, the fastener at least partially covers the weight member. In particular instances, the fastener does not extend through the weight member. In certain cases, the fastener comprises a tab that extends below at least a portion of either a forward edge or a rearward edge of the weight member, and may in particular instances further comprise a removable screw or bolt that extends through the tab and into the body of the golf club head.

(14) The weight channel may have a path dimension representing a distance of travel for the weight member, wherein the distance comprises the distance between a first path end positioned proximate to a first end of the channel and a second path end positioned proximate to a second end of the channel. In particular instances, the weight member may have a first dimension that is normal to the path dimension and a second dimension that is parallel to the path dimension, and in some cases the second dimension is at least 50 percent of the path dimension. In some cases, the second dimension may be at least 70 percent of the path dimension.

(15) In some cases, translating the weight member from a first position adjacent a first end of the channel to a second position adjacent a second end of the channel provides a golf club head center of gravity movement along an x-axis (CGx) of at least 3 mm, at least 4 mm or at least 5 mm. In certain instances, the weight member has a mass of at least 40 grams, or at least 60 grams. In particular instances, the weight member comprises at least 25 percent, or in some cases at least 30 percent, of a total mass of the golf club head. The weight member may comprise a forward side and a rearward side, and have a center of mass that is nearer the forward side than the rearward side. In particular examples, a height of the weight member at the forward side is greater than a height of the weight member at the rearward side. The weight member may in some instances be tapered down from the forward side to the rearward side. Additionally or alternatively, the weight member may comprise two or more stepped portions. In particular cases, a first stepped portion at the forward side has a first height that is greater than a second height of a second stepped portion at the rearward side. In some cases, wherein the rearward side of the weight member comprises a chamfered edge. In particular instances, the golf club head further comprises a polymeric pad positioned between the chamfered edge and the body. The rearward end of the weight member may comprise a recessed ledge portion that corresponds to a protruding ledge portion on the golf club head body, such as in the weight channel. In some cases, a polymeric pad may be positioned between the recessed ledge portion and the protruding ledge portion.

(16) In particular instances, the weight member is configured to move in an arcuate path defined by a center axis of curvature located rearward of the face, rearward of the weight channel, and/or rearward of a center of gravity of the golf club head. In some cases, the weight member is configured to move in an arc of less than 90 degrees, or less than 180 degrees around the center axis of curvature. In particular cases, the weight member may be configured to move around the center axis of curvature in an arc of between 5 degrees and 90 degrees, between 10 degrees and 30 degrees, or between 15 degrees and 45 degrees. Additionally or alternatively, the weight member may be configured to move around a center axis of curvature, wherein the center axis of curvature is not collocated with a position of the fastener.

(17) In some instances, the golf club head may have a balance point up (BP Up) value of less than 23 mm, less than 22 mm, or less than 20 mm.

(18) In some embodiments, part of the weight channel, or weight track, is covered by an overhanging portion of the body or the sole insert, and part of the weight can slide under the overhanging portion and be hidden. For example, the track can extend in a heel-toe direction across the sole and the heelward end portion of the track can be covered by an overhang portion of a composite sole insert, which overhang portion can also act as a sit point for the club head to contact the ground when the club head is in the normal address position. The overhang portion can protect the weight and track, while also improving aerodynamics of the sole. In some embodiments, the weight can be asymmetric, with a forward portion of the weight being thicker and the rearward portion of the weight being thinner.

(19) The foregoing and other objects, features, and advantages of the disclosed technology will become more apparent from the following detailed description, which proceeds with reference to the accompanying figures.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1A is a front elevational view of an exemplary golf club head disclosed herein.

(2) FIG. 1B is heel-side view of the golf club head of FIG. 1A.

(3) FIG. 2A is a bottom rear perspective view of the golf club head of FIG. 1A.

(4) FIG. 2B is a front perspective view of the golf club head of FIG. 1A.

(5) FIG. 3 is an exploded perspective view of the golf club head of FIG. 1A, with a weight member removed.

(6) FIG. 4 is a bottom perspective view of the golf club head of FIG. 1A, with a weight member removed.

(7) FIG. 5A is a bottom view of the golf club head of FIG. 1, with a weight member removed.

(8) FIG. 5B is a cross-sectional view of a weight channel in the golf club head of FIG. 5A, taken along line 5B-5B in FIG. 5A.

(9) FIG. 6 is a perspective view of a weight member that may be used with the golf club heads of this disclosure.

(10) FIG. 7 is a perspective view of another weight member that may be used with the golf club heads of this disclosure.

(11) FIG. 8 is a front cross-sectional view of the golf club head of FIG. 1A.

(12) FIG. 9A is a bottom view of the golf club head of FIG. 1A.

(13) FIG. 9B is a cross-sectional view of a weight member, weight channel, and fastener in the golf club head of FIG. 9A, taken along line 9B-9B in FIG. 9A.

(14) FIG. 10 is a top view of the golf club head of FIG. 1A, with the crown insert removed.

(15) FIG. 11 is a cross-section of the golf club head of FIG. 10, taken along line 11-11 in FIG. 10.

(16) FIG. 12 is a cross-sectional view of a hosel of the golf club head of FIG. 1A.

(17) FIG. 13 is a cross-sectional view of an adjustable hosel-shaft assembly of the golf club head of FIG. 1A.

(18) FIG. 14 is a bottom view of another exemplary golf club head disclosed herein.

(19) FIG. 15 is a toe-side cross-sectional view of the golf club head of FIG. 14.

(20) FIG. 16 is a bottom view of another exemplary golf club head disclosed herein.

(21) FIG. 17 is a bottom perspective view of another exemplary golf club head disclosed herein.

(22) FIG. 18 is a bottom perspective view of another exemplary golf club head disclosed herein.

(23) FIG. 19 is a top view of another weight member that may be used with the golf club heads of this disclosure.

(24) FIG. 20 is an elevational view of the weight member of FIG. 19.

(25) FIG. 21 is a cross-sectional view of another weight member that may be used with the golf club heads of this disclosure.

(26) FIG. 22 is a cross-sectional view of another weight member that may be used with the golf club heads of this disclosure.

(27) FIG. 23A is a bottom view of another exemplary golf club head disclosed herein.

(28) FIG. 23B is a toe-side cross-sectional view of the golf club head of FIG. 23A, taken along line 23B-23B in FIG. 23A.

(29) FIG. 24 is a bottom view of another exemplary golf club head disclosed herein, with a weight member positioned in a first, forward position.

(30) FIG. 25 is a toe-side cross-sectional view of the golf club head of FIG. 24, taken along the path 1237 in FIG. 24, with the weight member positioned in a first, forward position.

(31) FIG. 26 is a bottom view of the golf club head of FIG. 24, with the weight member positioned in a second, rearward position.

(32) FIG. 27 is a toe-side cross-sectional view of the golf club head of FIG. 26, taken along the path 1237 in FIG. 26, with the weight member positioned in a second, rearward position.

(33) FIG. 28 is a bottom view of another exemplary golf club head disclosed herein, with a weight member positioned in a first, forward position.

(34) FIG. 29 is a bottom view of the golf club head of FIG. 29, with the weight member positioned in a second, rearward position.

(35) FIG. 30 is a rear cross-sectional view of the weight channel and weight member of the golf club head of FIG. 26.

(36) FIG. 31 is a rear cross-sectional view of a weight channel and weight member applicable to the exemplary golf club heads disclosed herein.

(37) FIG. 32 is a bottom view of an exemplary golf club head having a front-rear adjustable weight that is partially covered.

(38) FIG. 33 is a bottom view of an exemplary golf club head having two heel-toe adjustable weights and a stationary rear weight.

(39) FIG. 34 is a bottom view of an exemplary golf club head having a heel-toe adjustable weight that is partially covered, and a stationary rear weight.

(40) FIG. 35 is a bottom view of another exemplary golf club head having a heel-toe adjustable weight that is partially covered, and a stationary rear weight.

(41) FIG. 36 shows a bottom view of a front body portion of the club head of FIG. 35 in isolation.

(42) FIG. 37 is a cross-section view of the club head of FIG. 35 illustrating the position of the weight and fastener within the weight track.

(43) FIGS. 38A-38C illustrate a process of inserting a weight member into a weight track.

(44) FIG. 39 shows an alternative weight member that includes a hole/recess and ridges for moving the weight

along the weight track.

DETAILED DESCRIPTION

(45) The following describes embodiments of golf club heads for metalwood type golf clubs, including drivers, fairway woods, rescue clubs, hybrid clubs, and the like. Several of the golf club heads incorporate features that provide the golf club heads and/or golf clubs with increased moments of inertia and low centers of gravity, centers of gravity located in preferable locations, improved golf club head and face geometries, increased sole and lower face flexibility, higher coefficients of restitution (“COR”) and characteristic times (“CT”), and/or decreased backspin rates relative to fairway wood and other golf club heads that have come before.

(46) This disclosure describes embodiments of golf club heads in the exemplary context of fairway wood-type golf clubs, but the principles, methods and designs described may be applicable in whole or in part to other wood-type golf clubs, such as drivers, utility clubs (also known as hybrid clubs), rescue clubs, and the like.

(47) The disclosed inventive features include all novel and non-obvious features disclosed herein, both alone and in novel and non-obvious combinations with other elements. As used herein, the phrase “and/or” means “and,” “or” and both “and” and “or.” As used herein, the singular forms “a,” “an” and “the” refer to one or more than one, unless the context clearly dictates otherwise. As used herein, the terms “including” and “having” (and their grammatical variants) mean “comprising.”

(48) This disclosure also refers to the accompanying drawings, which form a part hereof. The drawings illustrate specific embodiments, but other embodiments may be formed and structural changes may be made without departing from the intended scope of this disclosure and the technology discussed herein. Directions and references (e.g., up, down, top, bottom, left, right, rearward, forward, heelward, toward, etc.) may be used to facilitate discussion of the drawings but are not intended to be limiting. For example, certain terms may be used such as “up,” “down,” “upper,” “lower,” “horizontal,” “vertical,” “left,” “right” and the like. These terms are used where applicable, to provide some clarity of description when dealing with relative relationships, particularly with respect to the illustrated embodiments. Such terms are not, however, intended to imply absolute relationships, positions and/or orientations, unless otherwise indicated. For example, with respect to an object, an “upper” surface can become a “lower” surface simply by turning the object over. Nevertheless, it is still the same object. Accordingly, the following detailed description shall not be construed in a limiting sense and the scope of property rights sought shall be defined by the appended claims and their equivalents.

(49) Golf club head “forgiveness” generally describes the ability of a golf club head to deliver a desirable golf ball trajectory despite a miss-hit (e.g., a ball struck at a location on the face plate other than an ideal impact location, e.g., an impact location where coefficient of restitution is maximized). Large mass moments of inertia contribute to the overall forgiveness of a golf club head. In addition, a low center-of-gravity improves forgiveness for golf club heads used to strike a ball from the turf by giving a higher launch angle and a lower spin trajectory (which improves the distance of a fairway wood golf shot). Providing a rearward center-of-gravity reduces the likelihood of a slice or fade for many golfers. Accordingly, forgiveness of fairway wood golf club heads, can be improved using the techniques described above to achieve high moments of inertia and low center-of-gravity compared to conventional fairway wood golf club heads.

(50) For example, a golf club head with a crown thickness less than about 0.65 mm throughout at least about 70% of the crown can provide significant discretionary mass. A 0.60 mm thick crown formed from steel can provide as much as about 8 grams of discretionary mass compared to a 0.80 mm thick crown. Alternatively, a 0.80 mm thick crown formed from a composite material having a density of about 1.5 g/cc can provide as much as about 26 grams of discretionary mass compared to a 0.80 mm thick crown formed from steel. The large discretionary mass can be distributed to improve the mass moments of inertia and desirably locate the golf club head center-of-gravity. Generally, discretionary mass should be located sole-ward rather than crown-ward to maintain a low center-of-gravity, forward rather than rearward to maintain a forwardly positioned center of gravity, and rearward rather than forward to maintain a rearwardly positioned center-of-gravity. In addition, discretionary mass should be located far from the center-of-gravity and near the perimeter of the golf club head to maintain high mass moments of inertia.

(51) Another parameter that contributes to the forgiveness and successful playability and desirable performance of a golf club is the coefficient of restitution (COR) of the golf club head. Upon impact with a golf ball, the golf club head's face plate deflects and rebounds, thereby imparting energy to the struck golf ball. The golf club head's coefficient of restitution is the ratio of the velocity of separation to the velocity of approach. A thin face plate generally will deflect more than a thick face plate. Thus, a properly constructed club with a thin, flexible face plate can impart a higher initial velocity to a golf ball, which is generally desirable, than a club with a thick, rigid face plate. In order to maximize the moment of inertia (MOI) about the center of gravity (CG) and achieve a high COR, it typically is desirable to incorporate thin walls and a thin face plate into the design of the

golf club head. Thin walls afford the designers additional leeway in distributing golf club head mass to achieve desired mass distribution, and a thinner face plate may provide for a relatively higher COR.

(52) Thus, thin walls are important to a club's performance. However, overly thin walls can adversely affect the golf club head's durability. Problems also arise from stresses distributed across the golf club head upon impact with the golf ball, particularly at junctions of golf club head components, such as the junction of the face plate with other golf club head components (e.g., the sole, skirt, and crown). One prior solution has been to provide a reinforced periphery about the face plate, such as by welding, in order to withstand the repeated impacts. Another approach to combat stresses at impact is to use one or more ribs extending substantially from the crown to the sole vertically, and in some instances extending from the toe to the heel horizontally, across an inner surface of the face plate. These approaches tend to adversely affect club performance characteristics, e.g., diminishing the size of the sweet spot, and/or inhibiting design flexibility in both mass distribution and the face structure of the golf club head. Thus, these golf club heads fail to provide optimal MOI, CG, and/or COR parameters, and as a result, fail to provide much forgiveness for off-center hits for all but the most expert golfers.

(53) Thus, the golf club heads of this disclosure are designed to allow for introduction of a face which can be adjusted in thickness as needed or desired to interact with the other disclosed aspects, such as a channel or slot positioned behind the face, as well as increased areas of mass and/or removable weights. The golf club heads of this disclosure may utilize, for example, the variable thickness face features described in U.S. Pat. Nos. 8,353,786, 6,997,820, 6,800,038, and 6,824,475, which are incorporated herein by reference in their entirety. Additionally, the mass of the face, as well as other of the above-described properties can be adjusted by using different face materials, structures, and features, such as those described in U.S. Pat. No. RE42,544; U.S. Pat. Nos. 8,096,897; 7,985,146; 7,874,936; 7,874,937; 8,628,434; and 7,267,620; and U.S. Patent Pub. Nos. 2008/0149267 and 2009/0163289, which are herein incorporated by reference in their entirety. Additionally, the structure of the front channel, club head face, and surrounding features of any of the embodiments herein can be varied to further impact COR and related aspects of the golf club head performance, as further described in U.S. Pat. No. 9,662,545; and U.S. Patent Pub. No. 2016/0023062, which are incorporated by reference herein in their entirety.

(54) Golf club heads and many of their physical characteristics disclosed herein will be described using “normal address position” as the golf club head reference position, unless otherwise indicated. The normal address position of the club head is defined as the angular position of the head relative to a horizontal ground plane when the shaft axis lies in a vertical plane that is perpendicular to the centerface target line vector and when the shaft axis defines a lie angle relative to the ground plane such that the scorelines on the face of the club are horizontal (if the club does not have scorelines, then the normal address position lie angle shall be defined as 60-degrees). The centerface target line vector is defined as a horizontal vector that points forward (along the Y-axis) from the centerface point of the face. The centerface point (axis origin point) can be defined as the geometric center of the striking surface and/or can be defined as an ideal impact location on the striking surface.

(55) FIGS. 1A-1B illustrate one embodiment of a fairway wood type golf club head **100** at normal address position, though it is understood that similar measurements may be made for other wood-type golf clubs, such as drivers, utility clubs (also known as hybrid clubs), rescue clubs, and the like. At normal address position, the golf club head **100** rests on a ground plane **210**, a plane parallel to the ground, which is intersected by a centerline axis **205** of a club shaft of the golf club head **100**.

(56) In addition to the thickness of the face plate and the walls of the golf club head, the location of the center of gravity also has a significant effect on the COR and other properties of a golf club head. For example, as illustrated in FIG. 1B, a given golf club head having a given CG will have a projected center of gravity or “balance point” or “CG projection” on the face plate **111** that is determined by an imaginary line **240** passing through the CG **230** and oriented normal to the face plate **111**. The location **255** where the imaginary line **240** intersects the face plate **111** is the projected CG point **255**, which is typically expressed as a distance above or below the geometric center **105** of the face plate **111**.

(57) When the projected CG point **255** is well above the center **105** of the face, impact efficiency, which is measured by COR, is not maximized. It has been discovered that a fairway wood with a relatively lower CG projection or a CG projection located at or near an ideal impact location on the striking surface of the club face, as described more fully below, improves the impact efficiency of the golf club head as well as initial ball speed. One important ball launch parameter, namely ball spin, is also improved.

(58) The distance from the ground plane **210** to the Projected CG point **255** may also be an advantageous measurement of golf head playability, and may be represented by a CG plane **250** that is parallel to the ground

plane **210**. The distance **260** from the ground plane **210** to this CG plane **250** representing CG projection on the face plate **111** may be referred to as the balance point up (BP Up), as also illustrated in FIG. **1B**. In the advantageous examples disclosed herein, BP Up may be less than 23 mm, regardless of the position of a weight member along its path of travel, (e.g., path **137** in FIGS. **5A** and **9A**). In particular instances, BP Up may be lower than 22 mm for any position of the weight member along its path of travel. In still further examples, BP Up may be lower than 20 mm for any position of the weight member along its path of travel.

(59) Additionally, “Zup,” as further described herein, may also provide an advantageous measurement of golf club head playability. Zup generally refers to the height of the CG above the ground plane as measured along the z-axis. For example, as illustrated in FIG. **1B**, an imaginary line **232** representing Zup extends out from the CG **230** parallel to the ground plane **210**.

(60) Fairway wood shots typically involve impacts that occur below the center of the face, and ball speed and launch parameters are often less than ideal. This results because most fairway wood shots are from the ground and not from a tee, and most golfers have a tendency to hit their fairway wood ground shots low on the face of the golf club head. Maximum ball speed is typically achieved when the ball is struck at a location on the striking face where the COR is greatest.

(61) For traditionally designed fairway woods, the location where the COR is greatest is the same as the location of the CG projection on the striking surface. This location, however, is generally higher on the striking surface than the below center location of typical ball impacts during play. In contrast to these conventional golf clubs, it has been discovered that greater shot distance is achieved by configuring the golf club head to have a CG projection that is located near to the center of the striking surface of the golf club head.

(62) It is known that the coefficient of restitution of a golf club may be increased by increasing the height H.sub.ss of the face plate—illustrated in FIG. **1A** as the distance **204** between the ground plane **210** and a plane **202** intersecting the top of the face plate—and/or by decreasing the thickness of the face plate of a golf club head. However, in the case of a fairway wood, hybrid, or rescue golf club, increasing the face height may be considered undesirable because doing so will potentially cause an undesirable change to the mass properties of the golf club (e.g., center of gravity location) and to the golf club's appearance.

(63) The United States Golf Association (USGA) regulations constrain golf club head shapes, sizes, and moments of inertia. Due to these constraints, golf club manufacturers and designers struggle to produce golf club heads having maximum size and moment of inertia characteristics while maintaining all other golf club head characteristics. For example, one such constraint is a volume limitation of 460 cm³. In general, volume is measured using the water displacement method. However, the USGA will fill any significant cavities in the sole or series of cavities which have a collective volume of greater than 15 cm³.

(64) To produce a more forgiving golf club head, designers struggle to maximize certain parameters such as face area, moment of inertia about the z-axis and x-axis, and address area. A larger face area makes the golf club head more forgiving. Likewise, higher moment of inertia about the z-axis and x-axis makes the golf club head more forgiving. Similarly, a larger front to back dimension will generally increase moment of inertia about the z-axis and x-axis because mass is moved further from the center of gravity and the moment of inertia of a mass about a given axis is proportional to the square of the distance of the mass away from the axis. Additionally, a larger front to back dimension will generally lead to a larger address area which inspires confidence in the golfer when s/he addresses the golf ball.

(65) However, when designers seek to maximize the above parameters it becomes difficult to stay within the volume limits and golf club head mass targets. Additionally, the sole curvature begins to flatten as these parameters are maximized. A flat sole curvature provides poor acoustics. To counteract this problem, designers may add a significant amount of ribs to the internal cavity to stiffen the overall structure and/or thicken the sole material to stiffen the overall structure. See for example FIGS. **55C** and **55D** and the corresponding text of U.S. Pub. No. 2016/0001146 A1, published Jan. 7, 2016. This, however, wastes discretionary mass that could be put elsewhere to improve other properties like moment of inertia about the z-axis and x-axis, or to permit adjustment of other mass properties such as BP Up or center of gravity movement.

(66) A golf club head Characteristic Time (CT) can be described as a numerical characterization of the flexibility of a golf club head striking face. The CT may also vary at points distant from the center of the striking face, but may not vary greater than approximately 20% of the CT as measured at the center of the striking face. The CT values for the golf club heads described in the present application were calculated based on the method outlined in the USGA “Procedure for Measuring the Flexibility of a Golf Clubhead,” Revision 2.0, Mar. 25, 2005, which is incorporated by reference herein in its entirety. Specifically, the method described in the sections entitled “3. Summary of Method,” “5. Testing Apparatus Set-up and Preparation,” “6. Club Preparation and Mounting,” and “7. Club Testing” are exemplary sections that are relevant. Specifically, the

characteristic time is the time from a rise from 5% of a maximum velocity to 95% of the maximum velocity under the test set forth by the USGA as described above.

(67) FIGS. **1A-13** illustrate an exemplary golf club head **100** that embodies certain inventive technologies disclosed herein. This exemplary embodiment of a golf club head provides increased COR by increasing or enhancing the perimeter flexibility of a face plate **111** of the golf club without necessarily increasing the height or decreasing the thickness of the face plate **111**. Additionally, it improves BP Up by positioning a significant amount of discretionary mass low and forward of the club head's center of gravity. For example, FIG. **2A** is a bottom perspective view of a golf club head **100** having a high COR. The golf club head **100** comprises a body **102** having a hosel **162** (best illustrated in FIGS. **1**, **12**, and **13**), in which a golf club shaft may be inserted and secured to the golf club head **100**. A weight member **140** may be at least partially secured within a weight channel **130** and secured with a fastener **150** as further described below. The golf club head **100** defines a front end or face **104**, an opposed rear end **110**, heel side **106**, toe side **108**, lower side or sole **103**, and upper side or crown **109** (all embodiments disclosed herein share similar directional references).

(68) The front end **104** includes a face plate **111** (FIG. **1A**) for striking a golf ball, which may be an integral part of the body **102** (e.g., the body **102** and face plate **111** may be cast as a single part), or may comprise a separate insert. For embodiments where the face plate is not integral to the body **102**, the front end **104** can include a face opening (not shown) to receive a face plate **111** that is attached to the body by welding, braising, soldering, screws or other fastening means.

(69) Near the face plate **111**, a front channel **114** is formed in the sole **103**. As illustrated in FIG. **11**, the front channel **114** extends between a lip **113** formed below or behind the front ground contact surface **112** and the intermediate ground contact surface **116** into an interior cavity **122** of the golf club head **100**. In some embodiments (not shown), the front channel **114** may comprise a slot that is raised up from the sole **103**, but does not extend fully into the interior cavity **122**. In some embodiments, the slot or channel may be provided with a slot or channel insert (not shown) to prevent dirt, grass, or other elements from entering the interior cavity **122** of the body **102** or from getting lodged in the slot or channel. The front channel **114** extends in a toe-heel direction across the sole, with a heelward end near the hosel **162** and an opposite toward end. The front channel can improve coefficient of restitution across the striking face and can provide increased forgiveness on off-center ball strikes. For example, the presence of the front channel can expand zones of the highest COR across the face of the club, particularly at the bottom of the club face near the channel, so that a larger fraction of the face area has a COR above a desired value, especially at the lower regions of the face. More information regarding the construction and performance benefits of the front channel **114** and similar front channels can be found in U.S. Pat. Nos. 8,870,678; 9,707,457; and 9,700,763, and U.S. Patent Pub. No. 2016/0023063 A1, all of which are incorporated by reference herein in their entireties, and various of the other publications that are incorporated by reference herein.

(70) As best illustrated in FIG. **4**, a weight channel **130** is separated from and positioned rearward of the front channel **114** in a forward portion of the golf club head. The weight channel **130** is further described below. The body **102** can include a front ground contact surface **112** on the body forward of the front channel **114** adjacent the bottom of the face plate **111**. The body can also have an intermediate ground contact surface, or sit pad, **116** rearward of the front channel **114**. The intermediate ground contact surface **116** can have an elevation and curvature congruent with that of the front ground contact surface **112**. Some embodiments may not include a front channel or slot in which case the intermediate ground contact surface may extend to the bottom of the face plate **111**, thereby providing additional potential contact surface area. The body **102** can further comprise a downwardly extending rear sole surface **118** that extends around at least a portion of the perimeter of the rear end **110** of the body. The rear sole surface may comprise one or more visual markings **119** that may correspond to a visual weight position indicator **149** on a weight member **140** that may be positioned within weight channel **130**. In some embodiments, the rear sole surface **118** can act as a ground contact or sit pad as well, having a curvature and elevation congruent with that of the front ground contact surface **112** and the intermediate ground contact surface **116**.

(71) The body **102** can further include a raised sole portion **160** that is recessed up from the rear sole surface **118**. The raised sole portion **160** can span over any portion of the sole **103**, and in the illustrated embodiment the raised sole portion **160** spans over most of the rearward portion of the sole. The sole **103** can include a sloped transition portion where the intermediate ground contact surface **116** transitions up to the raised sole portion **160**. The sole can also include other similar sloped portions (not shown), such as around the boundary of the raised sole portion **160**. In some embodiments (not shown), one or more cantilevered ribs or struts can be included on the sole that span from the sloped transition portion to the raised sole portion **160**, to provide increased stiffness and rigidity to the sole.

(72) The raised sole portion **160** can optionally include grooves, channels, ridges, or other surface features that increase its rigidity. Similarly, the intermediate ground contact surface **116** can include stiffening surface features, such as ridges, though grooves or other stiffening features can be substituted for the ridges.

(73) A sole such as the sole **103** of the golf club head **100** may be referred to as a two-tier construction, bi-level construction, raised sole construction, or dropped sole construction, in which one portion of the sole is raised or recessed relative to the other portion of the sole. The terms raised, lowered, recessed, dropped, etc. are relative terms depending on perspective. For example, the intermediate ground contact surface **116** could be considered “raised” relative to the raised sole portion **160** and the weight channel **130** when the head is upside down with the sole facing upwardly as in FIG. 2A. On the other hand, the intermediate ground contact surface **116** portion can also be considered a “dropped sole” part of the sole, since it is located closer to the ground relative to the raised sole portion **160** and the weight channel **130** when the golf club head is in a normal address position with the sole facing the ground.

(74) Additional disclosure regarding the use of recessed or dropped soles is provided in U.S. Provisional Patent Application No. 62/515,401, filed on Jun. 5, 2017, the entire contents of which are incorporated herein by reference.

(75) The raised sole constructions described herein and in the incorporated references are counterintuitive because the raised portion of the sole tends to raise the lyy position, which is sometimes considered disadvantageous. However, the raised sole portion **160** (and other raised sole portions disclosed herein) allows for a smaller radius of curvature for that portion of the sole (compared to a conventional sole without the raised sole portion) resulting in increased rigidity and better acoustic properties due to the increased stiffness from the geometry. This stiffness increase means fewer ribs or even no ribs are needed in that portion of the sole to achieve a desired first mode frequency, such as 3000 Hz or above, 3200 Hz or above, or even 3400 Hz or above. Fewer ribs provide a mass/weight savings, which allows for more discretionary mass that can be strategically placed elsewhere in the golf club head or incorporated into user adjustable movable weights.

(76) Furthermore, sloped transition portions around the raised sole portion **160**, as well as optional grooves and ridges associated therewith can provide additional structural support and additional rigidity for the golf club head, and can also modify and even fine tune the acoustic properties of the golf club head. The sound and modal frequencies emitted by the golf club head when it strikes a golf ball are very important to the sensory experience of a golfer and provide functional feedback as to where the ball impact occurs on the face (and whether the ball is well struck).

(77) In some embodiments, the raised sole portion **160** can be made of a relatively thinner and/or less dense material compared to other portions of the sole and body that take more stress, such as the ground contact surfaces **112**, **116**, **118**, the face region, and the hosel region. By reducing the mass of the raised sole portion **160**, the higher CG effect of raising that portion of the sole is mitigated while maintaining a stronger, heavier material on other portions of the sole and body to promote a lower CG and provide added strength in the area of the sole and body where it is most needed (e.g., in a sole region proximate to the hosel and around the face and shaft connection components where stress is higher).

(78) The body **102** can also include one or more internal ribs, such as ribs **192**, as best shown in FIG. 10, that are integrally formed with or attached to the inner surfaces of the body. Such ribs can vary in size, shape, location, number and stiffness, and can be used strategically to reinforce or stiffen designated areas of the body's interior and/or fine tune acoustic properties of the golf club head.

(79) Generally, the center of gravity (CG) of a golf club head is the average location of the weight of the golf club head or the point at which the entire weight of the golf club-head may be considered as concentrated so that if supported at this point the head would remain in equilibrium in any position. A golf club head origin coordinate system can be defined such that the location of various features of the golf club head, including the CG, can be determined with respect to a golf club head origin positioned at the geometric center of the striking surface and when the club-head is at the normal address position (i.e., the club-head position wherein a vector normal to the club face substantially lies in a first vertical plane perpendicular to the ground plane, the centerline axis of the club shaft substantially lies in a second substantially vertical plane, and the first vertical plane and the second substantially vertical plane substantially perpendicularly intersect).

(80) The head origin coordinate system defined with respect to the head origin includes three axes: a head origin z-axis (or simply “z-axis”) extending through the head origin in a generally vertical direction relative to the ground; a head origin x-axis (or simply “x-axis”) extending through the head origin in a toe-to-heel direction generally parallel to the striking surface (e.g., generally tangential to the striking surface at the center) and generally perpendicular to the z-axis; and a head origin y-axis (or simply “y-axis”) extending through the head origin in a front-to-back direction and generally perpendicular to the x-axis and to the z-axis. The x-axis

and the y-axis both extend in generally horizontal directions relative to the ground when the golf club head is at the normal address position. The x-axis extends in a positive direction from the origin towards the heel of the golf club head. The y axis extends in a positive direction from the head origin towards the rear portion of the golf club head. The z-axis extends in a positive direction from the origin towards the crown. Thus for example, and using millimeters as the unit of measure, a CG that is located 3.2 mm from the head origin toward the toe of the golf club head along the x-axis, 36.7 mm from the head origin toward the rear of the clubhead along the y-axis, and 4.1 mm from the head origin toward the sole of the golf club head along the z-axis can be defined as having a CGx of -3.2 mm, a CGy of +36.7 mm, and a CGz of -4.1 mm.

(81) Further as used herein, Delta 1 is a measure of how far rearward in the golf club head body the CG is located. More specifically, Delta 1 is the distance between the CG and the hosel axis along the y axis (in the direction straight toward the back of the body of the golf club face from the geometric center of the striking face). It has been observed that smaller values of Delta 1 result in lower projected CGs on the golf club head face. Thus, for embodiments of the disclosed golf club heads in which the projected CG on the ball striking club face is lower than the geometric center, reducing Delta 1 can lower the projected CG and increase the distance between the geometric center and the projected CG. Note also that a lower projected CG can promote a higher launch and a reduction in backspin due to the z-axis gear effect. Thus, for particular embodiments of the disclosed golf club heads, in some cases the Delta 1 values are relatively low, thereby reducing the amount of backspin on the golf ball helping the golf ball obtain the desired high launch, low spin trajectory.

(82) Similarly, Delta 2 is the distance between the CG and the hosel axis along the x axis (in the direction straight toward the back of the body of the golf club face from the geometric center of the striking face).

(83) Adjusting the location of the discretionary mass in a golf club head as described herein can provide the desired Delta 1 value. For instance, Delta 1 can be manipulated by varying the mass in front of the CG (closer to the face) with respect to the mass behind the CG. That is, by increasing the mass behind the CG with respect to the mass in front of the CG, Delta 1 can be increased. In a similar manner, by increasing the mass in front of the CG with the respect to the mass behind the CG, Delta 1 can be decreased.

(84) In addition to the position of the CG of a club-head with respect to the head origin another important property of a golf club-head is the projected CG point, e.g., projected CG point **255** discussed above. This projected CG point (also referred to as “CG Proj”) can also be referred to as the “zero-torque” point because it indicates the point on the ball striking club face that is centered with the CG. Thus, if a golf ball makes contact with the club face at the projected CG point, the golf club head will not twist about any axis of rotation since no torque is produced by the impact of the golf ball. A negative number for this property indicates that the projected CG point is below the geometric center of the face. So, in the exemplary golf club head illustrated in FIG. 1B, because the projected CG point **255** is located below the geometric center **105** of the golf club head **100** on the club face **111**, this property would be expected to have a negative value. As discussed above, this point can also be measured using a value (BP Up) that measures the distance of the CG point **255** from the ground plane **210**.

(85) In terms of the MOI of the club-head (i.e., a resistance to twisting) it is typically measured about each of the three main axes of a club-head with the CG as the origin of the coordinate system. These three axes include a CG z-axis extending through the CG in a generally vertical direction relative to the ground when the golf club head is at normal address position; a CG x-axis extending through the CG origin in a toe-to-heel direction generally parallel to the striking surface (e.g., generally tangential to the striking surface at the club face center), and generally perpendicular to the CG z-axis; and a CG y-axis extending through the CG origin in a front-to-back direction and generally perpendicular to the CG x-axis and to the CG z-axis. The CG x-axis and the CG y-axis both extend in generally horizontal directions relative to the ground when the golf club head is at normal address position. The CG x-axis extends in a positive direction from the CG origin to the heel of the golf club head. The CG y-axis extends in a positive direction from the CG origin towards the rear portion of the golf club head. The CG z-axis extends in a positive direction from the CG origin towards the crown. Thus, the axes of the CG origin coordinate system are parallel to corresponding axes of the head origin coordinate system. In particular, the CG z-axis is parallel to the z-axis, the CG x-axis is parallel to the x-axis, and CG y-axis is parallel to the y-axis.

(86) Specifically, a golf club head has a moment of inertia about the vertical CG z-axis (“Izz”), a moment of inertia about the heel/toe CG x-axis (“Ixx”), and a moment of inertia about the front/back CG y-axis (“Iyy”). Typically, however, the MOI about the CG z-axis (Izz) and the CG x-axis (Ixx) is most relevant to golf club head forgiveness.

(87) A moment of inertia about the golf club head CG x-axis (Ixx) is calculated by the following Equation 1:

$$I_{xx} = \int (y_{sup.2} + z_{sup.2}) dm \quad (1)$$

where y is the distance from a golf club head CG xz-plane to an infinitesimal mass dm and z is the distance from a golf club head CG xy-plane to the infinitesimal mass dm. The golf club head CG xz-plane is a plane defined by the golf club head CG x-axis and the golf club head CG z-axis. The CG xy-plane is a plane defined by the golf club head CG x-axis and the golf club head CG y-axis.

(88) Similarly, a moment of inertia about the golf club head CG z-axis (I_{zz}) is calculated by the following Equation 2:

$$I_{zz} = \int (x^2 + y^2) dm \quad (2)$$

where x is the distance from a golf club head CG yz-plane to an infinitesimal mass dm and y is the distance from the golf club head CG xz-plane to the infinitesimal mass dm. The golf club head CG yz-plane is a plane defined by the golf club head CG y-axis and the golf club head CG z-axis.

(89) A further description of the coordinate systems for determining CG positions and MOI can be found in U.S. Pat. No. 9,358,430, the entire contents of which are incorporated by reference herein.

(90) An alternative, above ground, club head coordinate system places the head origin at the intersection of the z-axis and the ground plane, providing positive z-axis coordinates for every club head feature. As used herein, "Zup" means the CG z-axis location determined according to this above ground coordinate system. Zup generally refers to the height of the CG above the ground plane **210** as measured along the z-axis, which is illustrated, e.g., by Zup line **232** extending from the CG **230** illustrated in FIG. 1B.

(91) As described herein, desired golf club head mass moments of inertia, golf club head center-of-gravity locations, and other mass properties of a golf club head can be attained by distributing golf club head mass to particular locations. Discretionary mass generally refers to the mass of material that can be removed from various structures providing mass that can be distributed elsewhere for tuning one or more mass moments of inertia and/or locating the golf club head center-of-gravity.

(92) Golf club head walls provide one source of discretionary mass. In other words, a reduction in wall thickness reduces the wall mass and provides mass that can be distributed elsewhere. Thin walls, particularly a thin crown **109**, provide significant discretionary mass compared to conventional golf club heads. For example, a golf club head made from an alloy of steel can achieve about 4 grams of discretionary mass for each 0.1 mm reduction in average crown thickness. Similarly, a golf club head made from an alloy of titanium can achieve about 2.5 grams of discretionary mass for each 0.1 mm reduction in average crown thickness. Discretionary mass achieved using a thin crown, e.g., less than about 0.65 mm, can be used to tune one or more mass moments of inertia and/or center-of-gravity location.

(93) To achieve a thin wall on the golf club head body **102**, such as a thin crown **109**, a golf club head body **102** can be formed from an alloy of steel or an alloy of titanium. For further details concerning titanium casting, please refer to U.S. Pat. No. 7,513,296, incorporated herein by reference.

(94) Additionally, the thickness of the hosel **162** may be varied to provide for additional discretionary mass, as described in U.S. Pat. No. 9,731,176, the entire contents of which are hereby incorporated by reference.

(95) Various approaches can be used for positioning discretionary mass within a golf club head. For example, golf club heads may have one or more integral mass pads (not shown in the illustrated embodiments) cast into the head at predetermined locations that can be used to lower, to move forward, to move rearward, or otherwise to adjust the location of the golf club head's center-of-gravity, as further described herein. Also, epoxy can be added to the interior of the golf club head, such as through an epoxy port **115** (illustrated in FIGS. 1 and 8) in the golf club head to obtain a desired weight distribution. Alternatively, weights formed of high-density materials can be attached to the sole or other parts of a golf club head, as further described, for example, in co-pending U.S. patent application Ser. No. 15/859,071, the entire contents of which are hereby incorporated by reference. With such methods of distributing the discretionary mass, installation is critical because the golf club head endures significant loads during impact with a golf ball that can dislodge the weight. Accordingly, such weights are usually permanently attached to the golf club head and are limited to a fixed total mass, which of course, permanently fixes the golf club head's center-of-gravity and moments of inertia.

(96) Alternatively, weights can be attached in a manner which allows adjustment of certain mass properties of the golf club head. For example, FIG. 2A illustrates positioning a weight member **140** within a weight channel **130**, as further described below.

(97) As shown in FIG. 2B, the golf club head **100** can optionally include a separate crown insert **168** that is secured to the body **102**, such as by applying a layer of epoxy adhesive **167** or other securement means, such as bolts, rivets, snap fit, other adhesives, or other joining methods or any combination thereof, to cover a large opening **190** (illustrated in FIG. 10) at the top and rear of the body, forming part of the crown **109** of the golf club head. The crown insert **168** covers a substantial portion of the crown's surface area as, for example, at least 30%, at least 40%, at least 50%, at least 60%, at least 70% or at least 80% of the crown's surface area. The

crown's outer boundary generally terminates where the crown surface undergoes a significant change in radius of curvature, e.g., near where the crown transitions to the golf club head's sole **103**, hosel **162**, and front end **104**.

(98) As best illustrated in FIG. **10**, the crown can be formed to have a recessed peripheral ledge or seat **170** to receive the crown insert **168**, such that the crown insert is either flush with the adjacent surfaces of the body to provide a smooth seamless outer surface or, alternatively, slightly recessed below the body surfaces. The front of the crown insert **168** can join with a front portion of the crown **109** on the body to form a continuous, arched crown extend forward to the face. A forwardmost portion of the recessed ledge can extend forward of a rearward-most portion of the hosel such that a first distance to the rearward-most portion of the hosel is greater than a second distance to the forwardmost portion of the recessed ledge as measured relative to the y-axis. The crown insert **168** can comprise any suitable material (e.g., lightweight composite and/or polymeric materials including fiber reinforced polymeric materials all of which typically have a density ranging between about 1 g/cc and 2 g/cc, preferably between 1.3 g/cc and 1.7 g/cc) and can be attached to the body in any suitable manner, as described in more detail elsewhere herein.

(99) A wood-type golf club head, such as golf club head **100** and the other wood-type club heads disclosed herein have a volume, typically measured in cubic-centimeters (cm.sup.3) equal to the volumetric displacement of the club head, assuming any apertures are sealed by a substantially planar surface. (See United States Golf Association "Procedure for Measuring the Club Head Size of Wood Clubs," Revision 1.0, Nov. 21, 2003). In other words, for a golf club head with one or more weight ports within the head, it is assumed that the weight ports are either not present or are "covered" by regular, imaginary surfaces, such that the club head volume is not affected by the presence or absence of ports.

(100) In some embodiments, as in the case of a fairway wood (as illustrated), the golf club head may have a volume between about 100 cm.sup.3 and about 300 cm.sup.3, such as between about 150 cm.sup.3 and about 250 cm.sup.3, or between about 130 cm.sup.3 and about 190 cm.sup.3, or between about 125 cm.sup.3 and about 240 cm.sup.3, and a total mass between about 125 g and about 260 g, or between about 200 g and about 250 g. In the case of a utility or hybrid club (analogous to the illustrated embodiments), the golf club head may have a volume between about 60 cm.sup.3 and about 150 cm.sup.3, or between about 85 cm.sup.3 and about 120 cm.sup.3, and a total mass between about 125 g and about 280 g, or between about 200 g and about 250 g. In the case of a driver (analogous to the illustrated embodiments), any of the disclosed golf club heads can have a volume between about 300 cm.sup.3 and about 600 cm.sup.3, between about 350 cm.sup.3 and about 600 cm.sup.3, and/or between about 350 cm.sup.3 and about 500 cm.sup.3, and can have a total mass between about 145 g and about 260 g, such as between about 195 g and about 205 g.

(101) In some of the embodiments described herein, a comparatively forgiving golf club head for a fairway wood can combine an overall golf club head height (H.sub.ch)—illustrated in FIG. **1B** as the distance **280** from a ground plane **210** to a parallel height plane **270** at a crown **109** of the golf club head **100**—of less than about 46 mm and an above ground balance point (BP Up) between 10 and 25 mm, such as a BP Up of less than about 23 mm. Some examples of the golf club head provide a BP Up less than about 22 mm, less than about 21 mm, or less than about 20 mm. In some of these golf club heads, Zup may be between 10 and 20 mm, such as less than 17 mm, less than 16 mm, less than 15 mm, or less than 14 mm. Some examples of the golf club head provide a first crown height at a face-to-crown transition region where the face connects to the crown near a front end of the body, a second crown height at a crown-to-skirt transition region where the crown connects to a skirt of the golf club head near a rear end of the body, and a third crown height located rearward of the first crown height and forward of the second crown height and the third crown height is greater than both the first and second crown heights.

(102) The crown insert **168**, disclosed in various embodiments herein, can help overcome manufacturing challenges associated with conventional golf club heads having normal continuous crowns made of titanium or other metals, and can replace a relatively heavy component of the crown with a lighter material, freeing up discretionary mass which can be strategically allocated elsewhere within the golf club head. In certain embodiments, the crown may comprise a composite material, such as those described herein and in the incorporated disclosures, such as a composite material having a density of less than 2 grams per cubic centimeter. In still further embodiments, the material has a density of no more than 1.5 grams per cubic centimeter, or a density between 1 gram per cubic centimeter and 2 grams per cubic centimeter. Providing a lighter crown further provides the golf club head with additional discretionary mass, which can be used elsewhere within the golf club head to serve the purposes of the designer. For example, with the discretionary mass, additional ribs **192** can be strategically added to the hollow interior of the golf club head and thereby improve the acoustic properties of the head. Discretionary mass in the form of ribs, mass pads or other features

also can be strategically located in the interior, or even on the exterior of the golf club head to shift the effective CG fore or aft, toward or heelward or both (apart from any further CG adjustments made possible by adjustable weight features) or to improve desirable MOI characteristics, as further described herein.

(103) Methods of making any of the golf club heads disclosed herein, or associated golf clubs, may include one or more of the following steps: forming a frame having a sole opening, forming a composite laminate sole insert, injection molding a thermoplastic composite head component over the sole insert to create a sole insert unit, and joining the sole insert unit to the frame, as described in more detail in the incorporated U.S. Provisional Patent Application No. 62/440,886; providing a composite head component which is a weight track capable of supporting one or more slidable weights; forming the sole insert and/or crown insert from a thermoplastic composite material having a matrix compatible for bonding with the weight track; forming the sole insert and/or crown insert from a continuous fiber composite material having continuous fibers selected from the group consisting of glass fibers, aramide fibers, carbon fibers and any combination thereof, and having a thermoplastic matrix consisting of polyphenylene sulfide (PPS), polyamides, polypropylene, thermoplastic polyurethanes, thermoplastic polyureas, polyamide-amides (PAI), polyether amides (PEI), polyetheretherketones (PEEK), and any combinations thereof, wherein the sole insert is formed from a composite material having a density of less than 2 grams per cubic centimeter. In still further embodiments, the material has a density of less than 1.5 grams per cubic centimeter, or a density between 1 gram per cubic centimeter and 2 grams per cubic centimeter and the sole insert has a thickness of from about 0.195 mm to about 0.9 mm, preferably from about 0.25 mm to about 0.75 mm, more preferably from about 0.3 mm to about 0.65 mm, even more preferably from about 0.36 mm to about 0.56 mm; forming both the sole insert and/or crown insert and weight track from thermoplastic composite materials having a compatible matrix; forming the sole insert and/or crown insert from a thermosetting material, coating the sole insert with a heat activated adhesive, and forming the weight track from a thermoplastic material capable of being injection molded over the sole insert after the coating step; forming the frame from a material selected from the group consisting of titanium, one or more titanium alloys, aluminum, one or more aluminum alloys, steel, one or more steel alloys, and any combination thereof; forming the frame with a crown opening, forming a crown insert from a composite laminate material, and joining the crown insert to the frame such that the crown insert overlies the crown opening; selecting a composite head component from the group consisting of one or more ribs to reinforce the head, one or more ribs to tune acoustic properties of the head, one or more weight ports to receive a fixed weight in a sole portion of the club head, one or more weight tracks to receive a slidable weight, and combinations thereof; forming the sole insert and crown insert from a continuous carbon fiber composite material; forming the sole insert and crown insert by thermosetting using materials suitable for thermosetting, and coating the sole insert with a heat activated adhesive; forming the frame from titanium, titanium alloy or a combination thereof and has a crown opening, and the sole insert and weight track are each formed from a thermoplastic carbon fiber material having a matrix selected from the group consisting of polyphenylene sulfide (PPS), polyamides, polypropylene, thermoplastic polyurethanes, thermoplastic polyureas, polyamide-amides (PAI), polyether amides (PEI), polyetheretherketones (PEEK), and any combinations thereof; forming the frame with a crown opening, forming a crown insert from a thermoplastic composite material, and joining the crown insert to the frame such that it overlies the crown opening; and providing a crown to sole stiffening member, as described in more detail in U.S. Pat. No. 9,693,291, the entire contents of which is hereby incorporated by reference in its entirety.

(104) The bodies of the golf club heads disclosed herein, and optionally other components of the club heads as well, serve as frames and may be made from a variety of different types of suitable materials. In some embodiments, for example, the body and/or other head components can be made of a metal material such as steel and steel alloys, a titanium or titanium alloy (including but not limited to 6-4 titanium, 3-2.5, 6-4, SP700, 15-3-3-3, 10-2-3, or other alpha/near alpha, alpha-beta, and beta/near beta titanium alloys), or aluminum and aluminum alloys (including but not limited to 3000 series alloys, 5000 series alloys, 6000 series alloys, such as 6061-T6, and 7000 series alloys, such as 7075). The body may be formed by conventional casting, metal stamping or other known processes. The body also may be made of other metals as well as non-metals. The body can provide a framework or skeleton for the club head to strengthen the club head in areas of high stress caused by the golf ball's impact with the face, such as the transition region where the club head transitions from the face to the crown area, sole area and skirt area located between the sole and crown areas.

(105) In some embodiments, the sole insert and/or crown insert of the club head may be made from a variety of composite materials and/or polymeric materials, such as from a thermoplastic material, preferably from a thermoplastic composite laminate material, and most preferably from a thermoplastic carbon composite laminate material. For example, the composite material may comprise an injection moldable material,

thermoformable material, thermoset composite material or other composite material suitable for golf club head applications. One exemplary material is a thermoplastic continuous carbon fiber composite laminate material having long, aligned carbon fibers in a PPS (polyphenylene sulfide) matrix or base. One commercial example of this type of material, which is manufactured in sheet form, is TEPEX® DYNALITE 207 manufactured by Lanxess.

(106) TEPEX® DYNALITE 207 is a high strength, lightweight material having multiple layers of continuous carbon fiber reinforcement in a PPS thermoplastic matrix or polymer to embed the fibers. The material may have a 54% fiber volume but other volumes (such as a volume of 42% to 57%) will suffice. The material weighs about 200 g/m.^{sup.2}.

(107) Another similar exemplary material which may be used for the crown insert and/or sole insert is TEPEX® DYNALITE 208. This material also has a carbon fiber volume range of 42% to 57%, including a 45% volume in one example, and a weight of 200 g/m.^{sup.2}. DYNALITE 208 differs from DYNALITE 207 in that it has a TPU (thermoplastic polyurethane) matrix or base rather than a polyphenylene sulfide (PPS) matrix.

(108) By way of example, the TEPEX® DYNALITE 207 sheet(s) (or other selected material such as DYNALITE 208) are oriented in different directions, placed in a two-piece (male/female) matched die, heated past the melt temperature, and formed to shape when the die is closed. This process may be referred to as thermoforming and is especially well-suited for forming sole and crown inserts.

(109) Once the crown insert and/or sole insert are formed (separately) by the thermoforming process just described, each is cooled and removed from the matched die. The sole and crown inserts are shown as having a uniform thickness, which lends itself well to the thermoforming process and ease of manufacture. However, the sole and crown inserts may have a variable thickness to strengthen select local areas of the insert by, for example, adding additional plies in select areas to enhance durability, acoustic or other properties in those areas.

(110) A crown insert and/or sole insert can have a complex three-dimensional curvature corresponding generally to the crown and sole shapes of a fairway wood-type club head and specifically to the design specifications and dimensions of the particular head designed by the manufacturer. It will be appreciated that other types of club heads, such as drivers, utility clubs (also known as hybrid clubs), rescue clubs, and the like may be manufactured using one or more of the principles, methods and materials described herein.

(111) In an alternative embodiment, the sole insert and/or crown insert can be made by a process other than thermoforming, such as injection molding or thermosetting. In a thermoset process, the sole insert and/or crown insert may be made from prepreg plies of woven or unidirectional composite fiber fabric (such as carbon fiber) that is preimpregnated with resin and hardener formulations that activate when heated. The prepreg plies are placed in a mold suitable for a thermosetting process, such as a compression mold, e.g., a metal matched compression mold, or a bladder mold, and stacked/oriented with the carbon or other fibers oriented in different directions. The plies are heated to activate the chemical reaction and form the sole (or crown) insert. Each insert is cooled and removed from its respective mold. Additional disclosure regarding methods of forming sole and/or crown inserts can be found in U.S. Pat. No. 9,579,549, the entire contents of which are incorporated by reference.

(112) The carbon fiber reinforcement material for the thermoset sole/crown insert may be a carbon fiber known as “34-700” fiber, available from Grafil, Inc., of Sacramento, California, which has a tensile modulus of 234 Gpa (34 Msi) and tensile strength of 4500 Mpa (650 Ksi). Another suitable fiber, also available from Grafil, Inc., is a carbon fiber known as “TR50S” fiber which has a tensile modulus of 240 Gpa (35 Msi) and tensile strength of 4900 Mpa (710 Ksi). Exemplary epoxy resins for the prepreg plies used to form the thermoset crown and sole inserts are Newport 301 and 350 and are available from Newport Adhesives & Composites, Inc., of Irvine, California.

(113) In one example, the prepreg sheets have a quasi-isotropic fiber reinforcement of 34-700 fiber having an areal weight of about 70 g/m.^{sup.2} and impregnated with an epoxy resin (e.g., Newport 301), resulting in a resin content (R/C) of about 40%. For convenience of reference, the primary composition of a prepreg sheet can be specified in abbreviated form by identifying its fiber areal weight, type of fiber, e.g., 70 FAW 34-700. The abbreviated form can further identify the resin system and resin content, e.g., 70 FAW 34-700/301, R/C 40%.

(114) Once the sole insert and crown insert are formed, they can be joined to the body in a manner that creates a strong integrated construction adapted to withstand normal stress, loading and wear and tear expected of commercial golf clubs. For example, the sole insert and crown insert each may be bonded to the frame using epoxy adhesive, such as an adhesive applied between an interior surface of each respective insert and a corresponding exterior surface of the body, with the crown insert seated in and overlying the crown opening

and the sole insert seated in and overlying the sole opening. Alternatively, a sole insert or crown insert may be attached inside an internal cavity of the body and then subsequently attached by securing an exterior surface of the insert to an interior surface of the body. Alternative attachment methods for bonding an insert to either an internal or an external surface of the body include bolts, rivets, snap fit, adhesives, other known joining methods or any combination thereof.

(115) Exemplary polymers for the embodiments described herein may include without limitation, synthetic and natural rubbers, thermoset polymers such as thermoset polyurethanes or thermoset polyureas, as well as thermoplastic polymers including thermoplastic elastomers such as thermoplastic polyurethanes, thermoplastic polyureas, metallocene catalyzed polymer, unimodaethylene/carboxylic acid copolymers, unimodal ethylene/carboxylic acid/carboxylate terpolymers, bimodal ethylene/carboxylic acid copolymers, bimodal ethylene/carboxylic acid/carboxylate terpolymers, polyamides (PA), polyketones (PK), copolyamides, polyesters, copolyesters, polycarbonates, polyphenylene sulfide (PPS), cyclic olefin copolymers (COC), polyolefins, halogenated polyolefins [e.g. chlorinated polyethylene (CPE)], halogenated polyalkylene compounds, polyalkenamer, polyphenylene oxides, polyphenylene sulfides, diallylphthalate polymers, polyimides, polyvinyl chlorides, polyamide-ionomers, polyurethane ionomers, polyvinyl alcohols, polyarylates, polyacrylates, polyphenylene ethers, impact-modified polyphenylene ethers, polystyrenes, high impact polystyrenes, acrylonitrile-butadiene-styrene copolymers, styrene-acrylonitriles (SAN), acrylonitrile-styrene-acrylonitriles, styrene-maleic anhydride (S/MA) polymers, styrenic block copolymers including styrene-butadiene-styrene (SBS), styrene-ethylene-butylene-styrene, (SEBS) and styrene-ethylene-propylene-styrene (SEPS), styrenic terpolymers, functionalized styrenic block copolymers including hydroxylated, functionalized styrenic copolymers, and terpolymers, cellulosic polymers, liquid crystal polymers (LCP), ethylene-propylene-diene terpolymers (EPDM), ethylene-vinyl acetate copolymers (EVA), ethylene-propylene copolymers, propylene elastomers (such as those described in U.S. Pat. No. 6,525,157, to Kim et al, the entire contents of which are hereby incorporated by reference), ethylene vinyl acetates, polyureas, and polysiloxanes and any and all combinations thereof.

(116) Of these preferred are polyamides (PA), polyphthalimide (PPA), polyketones (PK), copolyamides, polyesters, copolyesters, polycarbonates, polyphenylene sulfide (PPS), cyclic olefin copolymers (COC), polyphenylene oxides, diallylphthalate polymers, polyarylates, polyacrylates, polyphenylene ethers, and impact-modified polyphenylene ethers. Especially preferred polymers for use in the golf club heads of the present invention are the family of so called high performance engineering thermoplastics which are known for their toughness and stability at high temperatures. These polymers include the polysulfones, the polyetherimides, and the polyamide-imides. Of these, the most preferred are the polysulfones.

(117) Aromatic polysulfones are a family of polymers produced from the condensation polymerization of 4,4'-dichlorodiphenylsulfone with itself or one or more dihydric phenols. The aromatic polysulfones include the thermoplastics sometimes called polyether sulfones, and the general structure of their repeating unit has a diaryl sulfone structure which may be represented as -arylene-SO₂-arylene-. These units may be linked to one another by carbon-to-carbon bonds, carbon-oxygen-carbon bonds, carbon-sulfur-carbon bonds, or via a short alkylene linkage, so as to form a thermally stable thermoplastic polymer. Polymers in this family are completely amorphous, exhibit high glass-transition temperatures, and offer high strength and stiffness properties even at high temperatures, making them useful for demanding engineering applications. The polymers also possess good ductility and toughness and are transparent in their natural state by virtue of their fully amorphous nature. Additional key attributes include resistance to hydrolysis by hot water/steam and excellent resistance to acids and bases. The polysulfones are fully thermoplastic, allowing fabrication by most standard methods such as injection molding, extrusion, and thermoforming. They also enjoy a broad range of high temperature engineering uses.

(118) Three commercially significant polysulfones are: polysulfone (PSU); Polyethersulfone (PES also referred to as PESU); and Polyphenylene sulfone (PPSU).

(119) Particularly important and preferred aromatic polysulfones are those comprised of repeating units of the structure —C₆H₄SO₂—C₆H₄—O— where C₆H₄ represents an m- or p-phenylene structure. The polymer chain can also comprise repeating units such as —C₆H₄—, C₆H₄—O—, —C₆H₄-(lower-alkylene)-C₆H₄—O—, —C₆H₄—O—C₆H₄—O—, —C₆H₄—S—C₆H₄—O— and other thermally stable substantially-aromatic difunctional groups known in the art of engineering thermoplastics. Also included are the so called modified polysulfones where the individual aromatic rings are further substituted in one or substituents including

(120) ##STR00001##

wherein R is independently at each occurrence, a hydrogen atom, a halogen atom or a hydrocarbon group or a combination thereof. The halogen atom includes fluorine, chlorine, bromine and iodine atoms. The hydrocarbon group includes, for example, a C.sub.1-C.sub.20 alkyl group, a C.sub.2-C.sub.20 alkenyl group, a C.sub.3-C.sub.20 cycloalkyl group, a C.sub.3-C.sub.20 cycloalkenyl group, and a C.sub.6-C.sub.20 aromatic hydrocarbon group. These hydrocarbon groups may be partly substituted by a halogen atom or atoms, or may be partly substituted by a polar group or groups other than the halogen atom or atoms. As specific examples of the C.sub.1-C.sub.20 alkyl group, there can be mentioned methyl, ethyl, propyl, isopropyl, amyl, hexyl, octyl, decyl and dodecyl groups. As specific examples of the C.sub.2-C.sub.20 alkenyl group, there can be mentioned propenyl, isopropenyl, butenyl, isobutenyl, pentenyl and hexenyl groups. As specific examples of the C.sub.3-C.sub.20 cycloalkyl group, there can be mentioned cyclopentyl and cyclohexyl groups. As specific examples of the C.sub.3-C.sub.20 cycloalkenyl group, there can be mentioned cyclopentenyl and cyclohexenyl groups. As specific examples of the aromatic hydrocarbon group, there can be mentioned phenyl and naphthyl groups or a combination thereof.

(121) Individual preferred polymers, include, the polysulfone made by condensation polymerization of bisphenol A and 4,4'-dichlorodiphenyl sulfone in the presence of base, and having the main repeating structure

(122) ##STR00002##

having the abbreviation PSF and sold under the tradenames Udel®, Ultrason® S, Eviva®, RTP PSU, the polysulfone made by condensation polymerization of 4,4'-dihydroxydiphenyl and 4,4'-dichlorodiphenyl sulfone in the presence of base, and having the main repeating structure

(123) ##STR00003##

having the abbreviation PPSF and sold under the tradenames RADEL® resin; and a condensation polymer made from 4,4'-dichlorodiphenyl sulfone in the presence of base and having the principle repeating structure

(124) ##STR00004##

having the abbreviation PPSF and sometimes called a "polyether sulfone" and sold under the tradenames Ultrason® E, LNP™, Veradel® PESU, Sumikaexce, and VICTREX® resin, and any and all combinations thereof.

(125) In some embodiments, a composite material, such as a carbon composite, made of a composite including multiple plies or layers of a fibrous material (e.g., graphite, or carbon fiber including turbostratic or graphitic carbon fiber or a hybrid structure with both graphitic and turbostratic parts present. Examples of some of these composite materials for use in the metalwood golf clubs and their fabrication procedures are described in U.S. Reissue Pat. No. RE41,577; U.S. Pat. Nos. 7,267,620; 7,140,974; 8,096,897; 7,628,712; 7,985,146; 7,874,936; 7,874,937; 8,628,434; and 7,874,938; and U.S. Patent Pub. Nos. 2008/0149267 and 2009/0163289, which are all incorporated herein by reference. The composite material may be manufactured according to the methods described at least in U.S. Patent Pub. No. 2008/0149267, the entire contents of which are herein incorporated by reference.

(126) Alternatively, short or long fiber-reinforced formulations of the previously referenced polymers. Exemplary formulations include a Nylon 6/6 polyamide formulation which is 30% Carbon Fiber Filled and available commercially from RTP Company under the trade name RTP 285. The material has a Tensile Strength of 35000 psi (241 MPa) as measured by ASTM D 638; a Tensile Elongation of 2.0-3.0% as measured by ASTM D 638; a Tensile Modulus of 3.30×10^{10} psi (22754 MPa) as measured by ASTM D 638; a Flexural Strength of 50000 psi (345 MPa) as measured by ASTM D 790; and a Flexural Modulus of 2.60×10^{10} psi (17927 MPa) as measured by ASTM D 790.

(127) Also included is a polyphthalamide (PPA) formulation which is 40% Carbon Fiber Filled and available commercially from RTP Company under the trade name RTP 4087 UP. This material has a Tensile Strength of 360 MPa as measured by ISO 527; a Tensile Elongation of 1.4% as measured by ISO 527; a Tensile Modulus of 41500 MPa as measured by ISO 527; a Flexural Strength of 580 MPa as measured by ISO 178; and a Flexural Modulus of 34500 MPa as measured by ISO 178.

(128) Also included is a polyphenylene sulfide (PPS) formulation which is 30% Carbon Fiber Filled and available commercially from RTP Company under the trade name RTP 1385 UP. This material has a Tensile Strength of 255 MPa as measured by ISO 527; a Tensile Elongation of 1.3% as measured by ISO 527; a Tensile Modulus of 28500 MPa as measured by ISO 527; a Flexural Strength of 385 MPa as measured by ISO 178; and a Flexural Modulus of 23,000 MPa as measured by ISO 178.

(129) An example is a polysulfone (PSU) formulation which is 20% Carbon Fiber Filled and available commercially from RTP Company under the trade name RTP 983. This material has a Tensile Strength of 124 MPa as measured by ISO 527; a Tensile Elongation of 2% as measured by ISO 527; a Tensile Modulus of 11032 MPa as measured by ISO 527; a Flexural Strength of 186 MPa as measured by ISO 178; and a Flexural

Modulus of 9653 MPa as measured by ISO 178.

(130) Another example is a polysulfone (PSU) formulation which is 30% Carbon Fiber Filled and available commercially from RTP Company under the trade name RTP 985. This material has a Tensile Strength of 138 MPa as measured by ISO 527; a Tensile Elongation of 1.2% as measured by ISO 527; a Tensile Modulus of 20685 MPa as measured by ISO 527; a Flexural Strength of 193 MPa as measured by ISO 178; and a Flexural Modulus of 12411 MPa as measured by ISO 178.

(131) Also an option is a polysulfone (PSU) formulation which is 40% Carbon Fiber Filled and available commercially from RTP Company under the trade name RTP 987. This material has a Tensile Strength of 155 MPa as measured by ISO 527; a Tensile Elongation of 1% as measured by ISO 527; a Tensile Modulus of 24132 MPa as measured by ISO 527; a Flexural Strength of 241 MPa as measured by ISO 178; and a Flexural Modulus of 19306 MPa as measured by ISO 178.

(132) The foregoing materials are well-suited for composite, polymer and insert components of the embodiments disclosed herein, as distinguished from components which preferably are made of metal or metal alloys.

(133) Additional details regarding providing composite soles and/or crowns and crown layups are provided in U.S. Patent Pub. No. 2016/0001146, the entire contents of which are hereby incorporated by reference.

(134) As described in detail in U.S. Pat. No. 6,623,378, filed Jun. 11, 2001, entitled "METHOD FOR MANUFACTURING AND GOLF CLUB HEAD" and incorporated by reference herein in its entirety, the crown or outer shell of the golf club head **100** may be made of a composite material, such as, for example, a carbon fiber reinforced epoxy, carbon fiber reinforced polymer, or a polymer. Additionally, U.S. Patent Pub. No. 2004/0116207 and U.S. Pat. No. 6,969,326, also incorporated by reference herein in their entirety, describe golf club heads with lightweight crowns. Furthermore, U.S. patent application Ser. No. 12/974,437 (now U.S. Pat. No. 8,608,591), also incorporated by reference herein in its entirety, describes golf club heads with lightweight crowns and soles.

(135) In some embodiments, composite materials used to construct the crown and/or sole insert should exhibit high strength and rigidity over a broad temperature range as well as good wear and abrasion behavior and be resistant to stress cracking. Such properties include (1) a Tensile Strength at room temperature of from about 7 ksi to about 330 ksi, preferably of from about 8 ksi to about 305 ksi, more preferably of from about 200 ksi to about 300 ksi, even more preferably of from about 250 ksi to about 300 ksi (as measured by ASTM D 638 and/or ASTM D 3039); (2) a Tensile Modulus at room temperature of from about 0.4 Msi to about 23 Msi, preferably of from about 0.46 Msi to about 21 Msi, more preferably of from about 0.46 Msi to about 19 Msi (as measured by ASTM D 638 and/or ASTM D 3039); (3) a Flexural Strength at room temperature of from about 13 ksi to about 300 ksi, from about 14 ksi to about 290 ksi, more preferably of from about 50 ksi to about 285 ksi, even more preferably of from about 100 ksi to about 280 ksi (as measured by ASTM D 790); and (4) a Flexural Modulus at room temperature of from about 0.4 Msi to about 21 Msi, from about 0.5 Msi to about 20 Msi, more preferably of from about 10 Msi to about 19 Msi (as measured by ASTM D 790).

(136) In certain embodiments, composite materials that are useful for making club-head components comprise a fiber portion and a resin portion. In general, the resin portion serves as a "matrix" in which the fibers are embedded in a defined manner. In a composite for club-heads, the fiber portion is configured as multiple fibrous layers or plies that are impregnated with the resin component. The fibers in each layer have a respective orientation, which is typically different from one layer to the next and precisely controlled. The usual number of layers for a striking face is substantial, e.g., forty or more. However, for a sole or crown, the number of layers can be substantially decreased to, e.g., three or more, four or more, five or more, six or more, examples of which will be provided below. During fabrication of the composite material, the layers (each comprising respectively oriented fibers impregnated in uncured or partially cured resin; each such layer being called a "prepreg" layer) are placed superposedly in a "lay-up" manner. After forming the prepreg lay-up, the resin is cured to a rigid condition. If interested a specific strength may be calculated by dividing the tensile strength by the density of the material. This is also known as the strength-to-weight ratio or strength/weight ratio.

(137) In tests involving certain club-head configurations, composite portions formed of prepreg plies having a relatively low fiber areal weight (FAW) have been found to provide superior attributes in several areas, such as impact resistance, durability, and overall club performance. FAW is the weight of the fiber portion of a given quantity of prepreg, in units of g/m.². Crown and/or sole panels may be formed of plies of composite material having a fiber areal weight of between 20 g/m.² and 200 g/m.² and a density between about 1 g/cc and 2 g/cc. However, FAW values below 100 g/m.², and more desirably 75 g/m.² or less, can be particularly effective. A particularly suitable fibrous material for use in making prepreg plies is carbon fiber, as noted. More than one fibrous material can be used. In other embodiments, however, prepreg plies having FAW

values below 70 g/m.^{sup.2} and above 100 g/m.^{sup.2} may be used. Generally, cost is the primary prohibitive factor in prepreg plies having FAW values below 70 g/m.^{sup.2}.

(138) In particular embodiments, multiple low-FAW prepreg plies can be stacked and still have a relatively uniform distribution of fiber across the thickness of the stacked plies. In contrast, at comparable resin-content (R/C, in units of percent) levels, stacked plies of prepreg materials having a higher FAW tend to have more significant resin-rich regions, particularly at the interfaces of adjacent plies, than stacked plies of low-FAW materials. Resin-rich regions tend to reduce the efficacy of the fiber reinforcement, particularly since the force resulting from golf-ball impact is generally transverse to the orientation of the fibers of the fiber reinforcement. The prepreg plies used to form the panels desirably comprise carbon fibers impregnated with a suitable resin, such as epoxy. An example carbon fiber is “34-700” carbon fiber (available from Grafil, Sacramento, Calif.), having a tensile modulus of 234 Gpa (34 Msi) and a tensile strength of 4500 Mpa (650 Ksi). Another Grafil fiber that can be used is “TR50S” carbon fiber, which has a tensile modulus of 240 Gpa (35 Msi) and a tensile strength of 4900 Mpa (710 ksi). Suitable epoxy resins are types “301” and “350” (available from Newport Adhesives and Composites, Irvine, Calif.). An exemplary resin content (R/C) is between 33% and 40%, preferably between 35% and 40%, more preferably between 36% and 38%.

(139) Some of the embodiments of the golf club head **100** discussed throughout this application may include a separate crown, sole, and/or face that may be a composite, such as, for example, a carbon fiber reinforced epoxy, carbon fiber reinforced polymer, or a polymer crown, sole, and/or face. Alternatively, the crown, sole, and/or face may be made from a less dense material, such as, for example, Titanium or Aluminum. A portion of the crown may be cast from either steel (~7.8-8.05 g/cm.^{sup.3}) or titanium (~4.43 g/cm.^{sup.3}) while a majority of the crown may be made from a less dense material, such as for example, a material having a density of about 1.5 g/cm.^{sup.3} or some other material having a density less than about 4.43 g/cm.^{sup.3}. In other words, the crown could be some other metal or a composite. Additionally or alternatively, the face may be welded in place rather than cast as part of the sole.

(140) By making the crown, sole, and/or face out of a less dense material, it may allow for weight to be redistributed from the crown, sole, and/or face to other areas of the club head, such as, for example, low and forward and/or low and back. Both low and forward and low and back may be possible for club heads incorporating a front to back sliding weight track.

(141) U.S. Pat. No. 8,163,119 discloses composite articles and methods for making composite articles, which disclosure is incorporated by reference herein in the entirety. U.S. Pat. Nos. 9,452,325 and 7,279,963 disclose various composite crown constructions that may be used for golf club heads, which disclosures are also incorporated by reference herein in their entireties. The techniques and layups described in U.S. Pat. Nos. 8,163,119; 9,452,325; and 7,279,963, incorporated herein by reference in their entirety, may be employed for constructing a composite crown panel, composite sole panel, composite toe panel located on the sole, and/or composite heel panel located on the sole.

(142) U.S. Pat. No. 8,163,119 discloses the usual number of layers for a striking plate is substantial, e.g., fifty or more. However, improvements have been made in the art such that the layers may be decreased to between 30 and 50 layers. Additionally, for a panel located on the sole and/or crown the layers can be substantially decreased down to three, four, five, six, seven, or more layers.

(143) Table 1 below provides examples of possible layups. These layups show possible crown and/or sole construction using unidirectional plies unless noted as woven plies. The construction shown is for a quasi-isotropic layup. A single layer ply has a thickness ranging from about 0.065 mm to about 0.080 mm for a standard FAW of 70 g/m.^{sup.2} with about 36% to about 40% resin content, however the crown and/or sole panels may be formed of plies of composite material having a fiber areal weight of between 20 g/m.^{sup.2} and 200 g/m.^{sup.2}. The thickness of each individual ply may be altered by adjusting either the FAW or the resin content, and therefore the thickness of the entire layup may be altered by adjusting these parameters.

(144) TABLE-US-00001 TABLE 1 ply ply ply ply AW 1 2 3 4 ply 5 ply 6 ply 7 ply 8 g/m.^{sup.2} 0 -60 +60 290- 360 0 -45 +45 90 390- 480 0 +60 90 -60 0 490- 600 0 +45 90 -45 0 490- 600 90 +45 0 -45 90 490- 600 +45 90 0 90 -45 490- 600 +45 0 90 0 -45 490- 600 0 90 +45 -45 0/90 490- woven 720 0 90 +45 -45 +45 0/90 490- woven 720 -60 -30 0 +30 60 90 590- 720 0 90 +45 -45 90 0 590- 720 90 0 +45 -45 0 90 590- 720 0 90 45 -45 45 0/90 590- woven 720 90 0 45 -45 45 90/0 590- woven 720 0 90 45 -45 -45 45 0/90 680- woven 840 90 0 45 -45 -45 45 90/0 680- woven 840 +45 -45 90 0 0 90 -45/45 680- woven 840 0 90 45 -45 -45 45 90 UD 680- 840 0 90 45 -45 0 -45 45 0/90 780- woven 960 90 0 45 -45 0 -45 45 90/0 780- woven 960

(145) The Area Weight (AW) is calculated by multiplying the density times the thickness. For the plies shown above made from composite material the density is about 1.5 g/cm³ and for titanium the density is about 4.5 g/cm³. Depending on the material used and the number of plies the composite crown and/or sole thickness

ranges from about 0.195 mm to about 0.9 mm, preferably from about 0.25 mm to about 0.75 mm, more preferably from about 0.3 mm to about 0.65 mm, even more preferably from about 0.36 mm to about 0.56 mm. It should be understood that although these ranges are given for both the crown and sole together it does not necessarily mean the crown and sole will have the same thickness or be made from the same materials. In certain embodiments, the sole may be made from either a titanium alloy or a steel alloy. Similarly, the main body of the golf club head **100** may be made from either a titanium alloy or a steel alloy. The titanium will typically range from 0.4 mm to about 0.9 mm, preferably from 0.4 mm to about 0.8 mm, more preferably from 0.4 mm to about 0.7 mm, even more preferably from 0.45 mm to about 0.6 mm. In some instances, the crown and/or sole may have non-uniform thickness, such as, for example varying the thickness between about 0.45 mm and about 0.55 mm.

(146) A lot of discretionary mass may be freed up by using composite material in the crown and/or sole especially when combined with thin walled titanium construction (0.4 mm to 0.9 mm) in other parts of the golf club head **10**. The thin walled titanium construction increases the manufacturing difficulty and ultimately fewer parts are cast at a time. In the past, 100+ golf club heads could be cast at a single time, however due to the thinner wall construction fewer golf club heads are cast per cluster to achieve the desired combination of high yield and low material usage.

(147) An important strategy for obtaining more discretionary mass is to reduce the wall thickness of the golf club head **10**. For a typical titanium-alloy “metal-wood” club-head having a volume of 460 cm³ (i.e., a driver) and a crown area of 100 cm², the thickness of the crown is typically about 0.8 mm, and the mass of the crown is about 36 g. Thus, reducing the wall thickness by 0.2 mm (e.g., from 1 mm to 0.8 mm) can yield a discretionary mass “savings” of 9.0 g.

(148) The following examples will help to illustrate the possible discretionary mass “savings” by making a composite crown rather than a titanium-alloy crown. For example, reducing the material thickness to about 0.73 mm yields an additional discretionary mass “savings” of about 25.0 g over a 0.8 mm titanium-alloy crown. For example, reducing the material thickness to about 0.73 mm yields an additional discretionary mass “savings” of about 25 g over a 0.8 mm titanium-alloy crown or 34 g over a 1.0 mm titanium-alloy crown. Additionally, a 0.6 mm composite crown yields an additional discretionary mass “savings” of about 27 g over a 0.8 mm titanium-alloy crown. Moreover, a 0.4 mm composite crown yields an additional discretionary mass “savings” of about 30 g over a 0.8 mm titanium-alloy crown. The crown can be made even thinner yet to achieve even greater weight savings, for example, about 0.32 mm thick, about 0.26 mm thick, about 0.195 mm thick. However, the crown thickness must be balanced with the overall durability of the crown during normal use and misuse. For example, an unprotected crown i.e. one without a head cover could potentially be damaged from colliding with other woods or irons in a golf bag.

(149) For example, any of the embodiments disclosed herein may have a crown or sole insert formed of plies of composite material having a fiber areal weight of between 20 g/m.^{sup.2} and 200 g/m.^{sup.2}, preferably between 50 g/m.^{sup.2} and 100 g/m.^{sup.2}, the weight of the composite crown being at least 20% less than the weight of a similar sized piece formed of the metal of the body. The composite crown may be formed of at least four plies of uni-tape standard modulus graphite, the plies of uni-tape oriented at any combination of 0° (forward to rearward of the club head), +45°, -45° and 90° (heelward to toward of the golf club head). Additionally or alternatively, the crown may include an outermost layer of a woven graphite cloth. Carbon crown panels or inserts or carbon sole panels as disclosed herein and in the incorporated applications may be utilized with any of the embodiments herein, and may have a thickness between 0.40 mm to 1.0 mm, preferably 0.40 mm to 0.80 mm, more preferably 0.40 mm to 0.65 mm, and a density between 1 gram per cubic centimeter and 2 grams per cubic centimeter, though other thicknesses and densities are also possible.

(150) One potential embodiment of a carbon sole panel that may be utilized with any of the embodiments herein weighs between 1.0 grams and 5.0 grams, such as between 1.25 grams and 2.75 grams, such as between 3.0 grams and 4.5 grams. In other embodiments, the carbon sole panel may weigh less than 3.0 grams, such as less than 2.5 grams, such as less than 2.0 grams, such as less than 1.75 grams. The carbon sole panel may have a surface area of at least 1250 mm.^{sup.2}, 1500 mm.^{sup.2}, 1750 mm.^{sup.2}, or 2000 mm.^{sup.2}.

(151) One potential embodiment of a carbon crown panel that may be utilized with any of the embodiments herein weighs between 3.0 grams and 8.0 grams, such as between 3.5 grams and 7.0 grams, such as between 3.5 grams and 7.0 grams. In other embodiments, the carbon crown panel may weigh less than 7.0 grams, such as less than 6.5 grams, such as less than 6.0 grams, such as less than 5.5 grams, such as less than 5.0 grams, such as less than 4.5 grams. The carbon crown panel may have a surface area of at least 3000 mm.^{sup.2}, 3500 mm.^{sup.2}, 3750 mm.^{sup.2}, 4000 mm.^{sup.2}.

(152) FIG. 2A illustrates one embodiment of a COR feature in combination with a sliding weight track. Similar

features are shown in the other embodiments. While the illustrated embodiments may only have a COR feature and a sliding weight track, other embodiments may have a COR feature, a sliding weight track, and an adjustable loft/lie feature or some other combination of features.

(153) As already discussed, and making reference to the embodiment illustrated in FIG. 2A, the COR feature may have a certain length L (which may be measured as the distance between toeward end and heelward end of the front channel **114**), width W (e.g., the measurement from a forward edge to a rearward edge of the front channel **114**), and offset distance OS from the front end, or face **104** (e.g., the distance between the face **104** and the forward edge of front channel **114**, also shown in FIG. 4 as the width of the front ground contact surface **112** between the face plate **111** and the front channel **114**). During development, it was discovered that the COR feature length L and the offset distance OS from the face play an important role in managing the stress which impacts durability, the sound or first mode frequency of the club head, and the COR value of the club head. All of these parameters play an important role in the overall club head performance and user perception.

(154) During development, it was discovered that a ratio of COR feature length to the offset distance may be preferably greater than 4, and even more preferably greater than 5, and most preferably greater than 5.5. However, the ratio of COR feature length to offset distance also has an upper limit and is preferably less than 15, and even more preferably less than 14, and most preferably less than 13.5. For example, for a COR feature length of 30 mm the offset distance from the face would preferably be less than 7.5 mm, and even more preferably 6 mm or less from the face. Additional disclosure about the relationship between COR feature length and offset, and related effects are provided in in co-pending U.S. patent application Ser. No. 15/859,071, the entire contents of which are hereby incorporated by reference.

(155) The offset distance is highly dependent on the slot length. As slot length increases so do the stresses in the club head, as a result the offset distance must be increased to manage stress. Additionally, as slot length increases the first mode frequency is negatively impacted.

(156) Exemplary embodiments of the structure of the weight channel **130** are further described herein. As best illustrated in in FIGS. 2A and 3-5B, weight channel **130** may be formed as a curved arc extending in a generally heel-toe direction, which may be bounded by a curved forward edge **132** opposing a curved rearward edge **134**. Forward edge **132** may comprise an outer arc of the weight channel **130** that extends at least or (as illustrated) greater than half the width of the golf club head, which the USGA defines in “United States Golf Association and R&A Rules Limited PROCEDURE FOR MEASURING THE CLUB HEAD SIZE OF WOOD CLUBS,” USGA-TPX3003, Revision 1.0.0, Nov. 21, 2003, as being measured from the heel of the golf club head to the toe of the golf club head. This length (heel-to-toe) is measured with the head positioned at a 60 degree lie angle. If the outermost point of the heel is not clearly defined, it is deemed to be 0.875 inches above the horizontal plane on which the club is lying. In some embodiments, the forward edge **132** may comprise an outer arc of the weight channel **130** that extends at least or (as illustrated) greater than half the depth of the golf club head, as measured from the face **104** of the golf club head to a trailing edge at the rear end **110** of the golf club head. The weight channel may curve rearwardly away from the face **104** to a heelward end **136** and a toeward end **138**, respectively. These ends **136**, **138** may be positioned rearward of the forward edge **132** of the weight channel. In certain other embodiments (not shown), the weight channel may extend in a primarily linear direction, such as in a heel-toe direction or in a forward-rearward direction. In still other embodiments, the weight channel may extend in a curved arc along either a toe side or a heel side of the golf club head. While in the examples shown in FIGS. 2-16, the weight channel is shown as being positioned in the forward portion of the golf club head, in other embodiments (as shown in FIGS. 17-18), the weight channel may be positioned in a rearward portion of the golf club head, as further described below.

(157) The rearward edge **134** of the weight channel may drop down to a lower channel surface **131** that is raised up from the sole of the golf club. Lower channel surface **131** may be substantially parallel to, or as illustrated, slightly angled away from the sole **103** of the golf club head, so that the weight channel **130** may be deeper at the forward edge **132** than it is at the rearward edge **134**. As illustrated in FIG. 10, one or more cantilevered ribs or struts **192** may be provided within the interior cavity **122** of the golf club head on the underside of the weight channel **130** to support and provide rigidity to the weight channel **130**. As illustrated in FIG. 3, projections (such as parallel ribbed projections **172** may be provided on the lower channel surface **131** of the weight channel **130**, such as at the forward edge **132**, to interact with corresponding ribbed weight projections **182** on a mating surface of the weight member **140** to better hold the weight member **140** in a desired position when a fastener **150** is tightened to secure the weight member **140**. A rear weight channel ledge **174** may protrude up and out from the lower channel surface **131** and run parallel to the rearward edge **134** of the weight channel **130**, to engage a corresponding recessed ledge portion **184** on a surface of the

weight member **140**, as further described below. Additionally, an indentation **176** may be formed within the rearward edge **134** of the weight channel **130** and configured for at least partially containing a material for damping the weight member **140**. One example of such a material would be a layer of compressible foam, such as PORON® foam, though other materials, such as or a SORBOTHANE®, or PORON®, polyurethane foam material, thermoplastic elastomer or other appropriate damping materials may be used.

(158) In certain embodiments, this compressible material may comprise an elastically compressible material that can be compressed down to, e.g., less than 90% of its original uncompressed thickness, down to less than 50% of its original uncompressed thickness, down to less than 20% of its original uncompressed thickness, or, in particular embodiments, down to less than 10% of its original uncompressed thickness, while typically being able to rebound substantially to its uncompressed thickness upon removal of a compression force. In some embodiments, the material may be compressed down to less than 50% of its original uncompressed thickness when a compression force is applied and rebound to more than 90% of its original uncompressed thickness upon removal of the compression force.

(159) The following table provides examples A-I showing an example initial uncompressed material depth, a final compressed material depth, the delta between the uncompressed and compressed material depths, and the percent the material was compressed. In this example, an uncompressed depth of 1.5 mm is used, however this is purely an example and several other depths could be used for the compressible material within indentation **176**, ranging from about 0.25 mm to about 5 mm, preferably from about 0.5 mm to about 3.5 mm, more preferably from about 0.8 mm to about 2.0 mm depending on the application.

(160) TABLE-US-00002 TABLE 2 Uncompressed Compressed Height Height Delta Percent Example (mm) (mm) (mm) Change A 1.5 0.15 1.35 -90% B 1.5 0.3 1.2 -80% C 1.5 0.45 1.05 -70% D 1.5 0.6 0.9 -60% E 1.5 0.75 0.75 -50% F 1.5 0.9 0.6 -40% G 1.5 1.05 0.45 -30% H 1.5 1.2 0.3 -20% I 1.5 1.35 0.15 -10%

(161) The percent the material is compressed is calculated by subtracting the initial uncompressed thickness from the final compressed thickness, dividing the result by the initial uncompressed shim thickness, and finally multiplying by 100 percent. See Equation 3 below for further clarification. The equation yields a negative percent change because the shim is being compressed i.e. the final thickness is less than the uncompressed shim thickness.

Percent Change=100%*(T.sub.final-T.sub.initial)/T.sub.initial (3)

(162) Additionally or alternatively, the percent change could also be expressed as an absolute percent change along with the word compression or tension to indicate the sign. In tensions the sign is positive and in compression the sign is negative. For example, a material that is compressed at least 10% is the same as a shim that has a percent change of at least -10%.

(163) Additional disclosure regarding the use of compressible material is provided in U.S. Pat. No. 9,868,036, issued on Jan. 16, 2018, the entire contents of which are incorporated herein by reference.

(164) Within lower channel surface **131** is positioned a fastener port **152**. The fastener port **152** may be configured to receive a fastener **150**. As such, fastener port **152** may be threaded so that fastener **150** can be loosened or tightened either to allow movement of, or to secure in position, weight member **140**, as further described herein. The fastener may comprise a head **151** with which a tool (not shown) may be used to tighten or loosen the fastener, and a fastener body **153** that may, e.g., be threaded to interact with corresponding threads on the fastener port **152** to facilitate tightening or loosening the fastener **150**. The fastener port **152** can have any of a number of various configurations to receive and/or retain any of a number of fasteners, which may comprise simple threaded fasteners, such as described below, or which may comprise removable weights or weight assemblies, such as described in U.S. Pat. Nos. 6,773,360, 7,166,040, 7,452,285, 7,628,707, 7,186,190, 7,591,738, 7,963,861, 7,621,823, 7,448,963, 7,568,985, 7,578,753, 7,717,804, 7,717,805, 7,530,904, 7,540,811, 7,407,447, 7,632,194, 7,846,041, 7,419,441, 7,713,142, 7,744,484, 7,223,180, 7,410,425 and 7,410,426, the entire contents of each of which are incorporated by reference in their entirety herein. As illustrated in FIG. 9B, fastener port **152** may be angled diagonally so that the fastener **150** is angled away from the front end **104** of the golf club head, and the fastener port is forward of a head **151** of the fastener, which may provide a more secure attachment by “sandwiching” the portion of the weight member **140** likely to have the greatest mass between the forward edge **132** of the weight channel **130** and the fastener **150**.

(165) As illustrated in FIGS. 5A and 9A, weight channel **130** is configured to define a path **137** for and to at least partially contain an adjustable weight member **140** (best illustrated in FIG. 9A) that is both configured to translate along the path **137** defined by the weight channel **130** and sized to be slidably retained, or at least partially retained, within the footprint of the weight channel **130** by a fastener **150**. The path **137** may comprise a path dimension representing a distance of travel for the weight member **140**, wherein the distance comprises the distance between a first end of the path proximate to a first end of the channel (e.g., heelward end **136**) and

a second path end positioned proximate to a second end of the channel (e.g., toward end **138**). Fastener **150** may be removable, and may comprise a screw, bolt, or other suitable device for fastening as described herein and in the incorporated applications. Fastener **150** may extend through an elongated weight slot **154** passing through the body of the weight member **140**. Weight slot **154** may extend through weight member **140** from a lower surface **141** of the weight member that is substantially parallel to the sole **103**—and may serve as an additional ground contact point when the golf club head is soled—through an upper surface **145** of the weight member that is positioned against the lower channel surface **131** of the weight channel and into a fastener port **152** in the weight channel **130**. The weight member **140** is positioned within the weight channel **130** and entirely external to the interior cavity **122**, and (as illustrated in FIGS. **9A** and **9B**) has a depth **143** that extends normal to the path **137** between a forward side **142** that may be curved parallel to the forward edge **132** of the weight channel **130** and a rearward side **144** that may be curved parallel to the rearward edge **134** of the weight channel. Additionally, as shown in FIGS. **6** and **7**, the weight member may have a greater height at the forward side **142** than at a rearward side **144**, and may taper down from the forward side **142** to the rearward side **144**. In particular cases, the weight member **140** may be configured so that the center of mass is positioned closer to the forward side **142** than to the rearward side **144**. Additionally, the weight member may comprise two or more stepped portions, such as a first “higher” step portion nearer the forward side of the weight member having a first height, and a second “lower” step portion adjacent the rearward side having a second height that is smaller than the first height. Additional “steps” may also be used to move from the height at the forward portion to the height at the rearward portion. In the illustrated embodiment, the second stepped portion may comprise a chamfered edge positioned in the upper surface **145** at the rearward side **144** of the weight member, which is configured to form a recessed ledge portion **184** to engage a corresponding rear weight channel ledge **174** on the weight channel **130**. As illustrated in FIG. **7**, an indentation **186** may be provided within the shelf within which a damping material, such as a polymeric pad (or other suitable material, such as the damping material described above with regard to indentation **176**) may be provided to position between the weight member **140** and the body of the golf club head **100**, such as between the recessed ledge portion **184** and the rear weight channel ledge **174**.

(166) The weight member **140**, which may comprise a steel weight member or other suitable material, has a length **147** (as illustrated in FIG. **9A**) that extends parallel to the path **137** along which the weight member translates, measured from a heelward end **146** to a toward end **148** of the weight member **140**. While in the illustrated example, length **147** is an arc, length **147** may be measured as either an arc or a straight line, as appropriate to the particular shape of the weight member **140** and the path **137**. The length of the weight member **140** in the illustrated example is at least 50 percent of the length of the path **137**, and in some instances may be at least 70 percent of the length of the path **137**. As shown in FIG. **8**, the ends of the weight member may be cantilevered, so that the heelward end **146** and toward end **148** of an upper portion of the weight member adjacent the lower channel surface **131** of the weight channel are parallel to the heelward end **136** and toward end **146**, respectively, of the weight channel, while the heelward end **146** and toward end **148** of a lower portion of the weight member that extends from the upper portion of the weight member up towards the sole **103** may be angled away from the heelward end **136** and toward end **138**, respectively, of the weight channel **130**. The weight slot **154** may comprise an elongated slot that runs a substantial portion of the length of the weight member parallel to the rearward edge **144** of the weight member **140** from a heelward end **156** to a toward end **158**. The weight slot may further comprise an interior fastener ledge **155** to support the head **151** of a fastener **150**. When tightened, the fastener **150** retains the weight member **140** in place. When fastener **150** is loosened, the fastener may be configured to remain stationary relative to the fastener port **152**, while the position of the weight member **140** may be adjusted.

(167) In the illustrated example shown in FIG. **9A**, weight member **140** may be translated laterally along the path **137** in a heelward or toward direction to adjust, for example, golf club center of gravity movement along an x-axis (CGx), such as to control left or right tendency of a golf swing. Adjusting the weight member from a first position that is closer to a heelward end **136** of the weight channel **130** to a second position that is closer to a toward end **138** of the weight channel may provide a CGx movement of at least 3 mm. In particular instances, CGx movement may exceed 4 mm, or in even more specific instances, CGx movement may exceed 5 mm. It is to be understood that in the illustrated embodiment, the weight is moving along the path **137** in an arc about a center axis of curvature **159** (illustrated in FIG. **9A**), which is situated rearward of the golf club head's face **104**. In particular cases, the center axis of curvature may be positioned rearward of the weight channel **130** itself, and in some instances, the center axis of curvature **159** may be rearward of a center of gravity of the golf club head. In the illustrated embodiment, the weight member is configured to move around the center axis of curvature **159** in an arc of less than 180 degrees, but may in particular embodiments move in

an arc of less than 90 degrees, such as in an arc of between 5 degrees and 90 degrees, or between 10 degrees and 30 degrees, or between 15 degrees and 45 degrees, or may not move in an arc at all, but simply translate linearly. It is to be understood that in the illustrated embodiment the center axis of curvature **159** is not collocated with the position of the fastener. Ribbed weight projections **182** may be provided on the lower surface **145** of the weight member **140**, such as adjacent to the forward edge **142**, to interact with corresponding parallel ribbed projections **172** on a mating surface of the weight channel **130** to better hold weight member **140** in any of a number of selectable positions which may be selected by translating weight member **140** heelward or toward (in the illustrated example) along the path of the weight channel **130** until a desired position is achieved. In some instances, five or more such positions may be provided. In other embodiments, ten or more such positions are provided. Weight member may also be configured with a visual weight position indicator **149** which may be aligned with visual markings **119** on the sole **103** of the golf club head to indicate the relative position of the weight member **140** along the path of the weight channel **130**. Once the desired position is achieved, fastener **150** may be tightened to secure the weight member **140** in place. The weight member may have a mass that is between 10 to 80 grams, or in some particular instances, a mass that is above 30 grams, above 40 grams, above 50 grams, or above 60 grams. In certain embodiments, the weight member **140** may comprise at least 25 percent of a total mass of the golf club head **100**. In particular cases, the weight member **140** may comprise at least 30 percent of the total mass of the golf club head **100**.

(168) As shown in FIG. **3**, the golf club head **100** can optionally include a separate crown insert **168** that is secured to the body **102**, such as by applying a layer of epoxy adhesive **167** or other securement means, such as bolts, rivets, snap fit, other adhesives, or other joining methods or any combination thereof, to cover a large opening **190** at the top and rear of the body, forming part of the crown **109** of the golf club head. The crown insert **168** covers a substantial portion of the crown's surface area as, for example, at least 30%, at least 40%, at least 50%, at least 60%, at least 70% or at least 80% of the crown's surface area. The crown's outer boundary generally terminates where the crown surface undergoes a significant change in radius of curvature, e.g., near where the crown transitions to the golf club head's sole **103**, hosel **162**, and front end **104**. As described above, and as partially shown in FIG. **10**, the crown opening **190** can be formed to have a recessed peripheral ledge or seat **170** to receive the crown insert **168**, such that the crown insert is either flush with the adjacent surfaces of the body to provide a smooth seamless outer surface or, alternatively, slightly recessed below the body surfaces. The front of the crown insert **168** can join with a front portion of the crown **109** on the body **102** to form a continuous, arched crown extend forward to the face. The crown insert **168** can comprise any suitable material, and can be attached to the body in any suitable manner, as described in more detail herein.

(169) As illustrated in FIG. **13**, the golf club head's hosel **162** further provides a shaft connection assembly **300** that allows the shaft to be easily disconnected from the golf club head, and that may provide the ability for the user to selectively adjust a and/or lie-angle of the golf club. The hosel **162** defines a hosel bore **163**, which in turn is adapted to receive a hosel insert **164**. The hosel bore **163** is also adapted to receive a shaft sleeve **302** mounted on the lower end portion of a shaft, as described in U.S. Pat. No. 8,303,431. A recessed port **166**, is provided on the sole **103**, and extends from the sole **103** into the interior cavity **122** of the body **102** toward the hosel **162**, and in particular the hosel bore **163**. The hosel bore **163** extends from the hosel **162** through the golf club head and opens within the recessed port **166** at the sole **103** of the golf club head **100**.

(170) The golf club head is removably attached to the shaft by shaft sleeve **302** (which is mounted to the lower end portion of a golf club shaft (not shown)) by inserting the shaft sleeve **302** into the hosel bore **163** and a hosel insert **164** (which is mounted inside the hosel bore **163**), and inserting a screw **310** (or other suitable fixation device) upwardly through a recessed port **166** in the sole **103** and, in the illustrated embodiment, tightening the screw **310** into a threaded opening of the shaft sleeve **302**, thereby securing the golf club head to the shaft sleeve **302**. A screw capturing device, such as in the form of an O-ring or washer **312**, can be placed on the shaft of the screw **310** to retain the screw in place within the golf club head when the screw is loosened to permit removal of the shaft from the golf club head.

(171) The recessed port **166** extends from the bottom portion of the golf club head into the interior of the outer shell toward the top portion of the golf club head **200** at the location of hosel **162**, as seen in FIGS. **12** and **13**. In the embodiment shown in FIG. **2A**, the mouth of the recessed port **166** in the sole **103** is generally trapezoidal-shaped, although the shape and size of the recessed port **166** may be different in alternative embodiments.

(172) The shaft sleeve **302** has a lower portion **306** including splines that mate with mating splines of the hosel insert **164**, an intermediate portion **308** and an upper head portion **314**. The intermediate portion **308** and the upper head portion **314** define an internal bore **316** for receiving the tip end portion of the shaft **300**. In the illustrated embodiment, the intermediate portion **308** of the shaft sleeve has a cylindrical external surface that is

concentric with the inner cylindrical surface of the hosel bore **163**. As described in more detail in U.S. Patent Application Pub. No. 2010/0197424, which is hereby incorporated by reference, inserting the shaft sleeve **302** at different angular positions relative to the hosel insert **164** is effective to adjust the shaft loft and/or the lie angle. For example, the loft angle may be increased or decreased by various degrees, depending on the angular position, such as ± 1.5 degrees, ± 2.0 degrees, or ± 2.5 degrees. Other loft angle adjustments are also possible. In some instances, the hosel insert may be externally attached to the hosel or integrally formed with an external portion of the hosel such that the shaft sleeve and/or an outer sleeve on the shaft sleeve may engage/interlock with the an external portion of the hosel. The external portion of the hosel that engages the shaft sleeve and/or an outer sleeve on the shaft sleeve may have castellated surfaces that correspond and are configured to mate with castellated surfaces on the shaft sleeve and/or an outer sleeve attached to the shaft sleeve. The outer sleeve attached to the shaft sleeve would be rotatable around an axis of the shaft sleeve and provide more incremental adjustment. In some instances, the outer sleeve would have castellated surfaces on an upper portion that correspond and are configured to mate with castellated surfaces on the shaft sleeve and the outer sleeve would have castellated surfaces on a lower portion that correspond and are configured to mate with castellated surfaces on the hosel. See, for example, U.S. Pat. No. 7,997,997, the entire contents of which is incorporated in its entirety by reference herein.

(173) In the embodiment shown, because the intermediate portion **308** is concentric with the hosel bore **163**, the outer surface of the intermediate portion **308** can contact the adjacent surface of the hosel bore **163**, as depicted in FIG. **13**. This allows easier alignment of the mating features of the assembly during installation of the shaft and further improves the manufacturing process and efficiency.

(174) In certain embodiments, the golf club head may be attached to the shaft via a removable head-shaft connection assembly as described in more detail in U.S. Pat. No. 8,303,431, the entire contents of which are incorporated by reference herein in their entirety. Further in certain embodiments, the golf club head may also incorporate features that provide the golf club heads and/or golf clubs with the ability not only to replaceably connect the shaft to the head but also to adjust the loft and/or the lie angle of the club by employing a removable head-shaft connection assembly. Such an adjustable lie/loft connection assembly is described in more detail in U.S. Pat. Nos. 8,025,587; 8,235,831; 8,337,319; 8,758,153; 8,398,503; 8,876,622; 8,496,541; and 9,033,821, the entire contents of which are incorporated in their entirety by reference herein.

Additional Embodiments and Features

(175) FIGS. **14-15** illustrate another exemplary golf club head **400** that embodies certain inventive technologies disclosed herein. The golf club head **400** is similar to golf club head, **100**. In golf club head **400**, weight channel **430** may contain features similar to weight channel **130**, and may be formed as a curved arc extending in a generally heel-toe direction. Weight channel **430** may comprise a lower channel surface **431** that may be substantially parallel to, or as illustrated, slightly angled away from a sole **403** of the golf club head, so that the weight channel **430** may be deeper at a forward edge **432** than it is at the rearward edge **434**. Within lower channel surface **431** are positioned several fastener ports **452**. Each of the fastener port may be configured to receive a fastener **450**. As such, fastener ports **452** may be threaded so that one or more fasteners **450** secured therein can be loosened or tightened either to allow movement of, or to secure in position a weight member **440**, as further described herein. The fastener may comprise a head **451** with which a tool (not shown) may be used to tighten or loosen the fastener **450**, and a fastener body **453** that may, e.g., be threaded to interact with corresponding threads on the fastener port **452** to facilitate tightening or loosening the fastener **450**. The fastener port **452** can have any of a number of various configurations to receive and/or retain any of a number of fasteners, which may comprise simple threaded fasteners, as described above, or any of the fastener types described in the incorporated patents and/or applications. As illustrated in FIG. **15**, fastener port **452** may be angled diagonally so that the head **451** of fastener **450** is angled away from the front end **404** of the golf club head, and the fastener port **452** is forward of the head **451** of the fastener.

(176) Similar to weight channel **130**, weight channel **430** is configured to define a path **437** for and to at least partially contain adjustable weight member **440** that is both configured to translate along the path **437** and sized to be slidably retained, or at least partially retained, within the footprint of the weight channel **430** by fastener **450**. Fastener **450** may be removable, and may comprise a screw, bolt, or other suitable device for fastening as described herein and in the incorporated applications. Fastener may be moved between or among the fastener ports **452** to further adjust mass properties of the golf club head **400**. Fastener **450** may extend through an elongated weight slot **454** passing through the body of the weight member **440**. Weight slot **454** may extend through weight member **440** from a lower surface **441** of the weight member that is substantially parallel to the sole **403**—and may serve as an additional ground contact point when the golf club head is soled—through an upper surface **445** of the weight member that is positioned against the lower channel surface **431**

the weight channel and into a fastener port **452** in the weight channel **430**. The weight member **440** is positioned within the weight channel **430** and may have a greater height at a forward side **442** than at a rearward side **444**, and may taper down from the forward side **442** to the rearward side **444**. In particular cases, the weight member **440** may be configured so that the center of mass is positioned closer to the forward side **442** than to the rearward side **444**. In the illustrated example, this is aided by the fact that the weight slot **454** and fastener **450** are positioned at the rearward side **444** of the weight member, such that the rearward side **444** of the weight member at least partially surrounds weight slot **454**. The weight slot may further comprise an interior fastener ledge **455** to support the head **451** of fastener **450**. In the illustrated example, this fastener ledge is coextensive with much of the rearward side **444** of the weight member **440**, and the rearward side of the weight member curves around to bound the fastener **450** at a forward edge **457**, at a heelward end **456**, and at a toeward end **458** of the weight slot **454**. In the illustrated example, the rearward edge **434** of weight channel **430** bounds the fastener **450** to the rear, and may comprise a ledge **474** (as shown in FIG. **15**) that protrudes up and out behind the fastener port **452** and runs parallel to the rearward edge **434** of the weight channel **430** to further support the head **451** of the fastener **450** when tightened. When tightened, the fastener **450** retains the weight member **440** in place. Once fastener **450** is loosened, the fastener is configured to remain stationary relative to the fastener port **452**, while the position of the weight member **440** may be adjusted relative to the fastener port. In the illustrated example shown in FIG. **14**, weight member **440** may be translated laterally along the path **437** in a heelward or toeward direction to adjust, for example, golf club center of gravity movement along an x-axis (CGx), such as to control left or right tendency of a golf swing.

(177) FIG. **16** illustrates another exemplary golf club head **500** that embodies certain inventive technologies disclosed herein. The golf club head **500** is similar to golf club head **100**. In golf club head **500**, weight channel **530** may contain features similar to weight channel **130**, and may be formed as a curved arc extending in a generally heel-toe direction. Within a lower channel surface **531** are positioned several fastener ports **552**. Each of the fastener port may be configured to receive a fastener **550**, or, as in the illustrated embodiment, multiple such fasteners. As such, fastener ports **552** may be threaded so that fasteners **550** can be loosened or tightened either to allow movement of, or to secure in position a weight member **540**, as further described herein. The fasteners may each comprise a head **551** with which a tool (not shown) may be used to tighten or loosen the fastener, and a fastener body (not shown) that may, e.g., be threaded to interact with corresponding threads on the fastener port **552** to facilitate tightening or loosening the fasteners **550**. The fastener port **552** can have any of a number of various configurations to receive and/or retain any of a number of fasteners, which may comprise simple threaded fasteners, as described above, or any of the fastener types described in the incorporated patents and/or applications. Similar to weight channel **130**, weight channel **530** is configured to define a path **537** for and to at least partially contain adjustable weight member **540** that is both configured to translate along the path **537** and sized to be slidably retained, or at least partially retained, within the footprint of the weight channel **530** by fastener **550**. Fasteners **550** may be removable, and may comprise screws, bolts, or other suitable devices for fastening as described herein and in the incorporated applications. Fasteners may be moved between or among the fastener ports **552** to further adjust mass properties of the golf club head **500**. Fasteners **550** may extend through an elongated weight slot **554** passing through the body of the weight member **540**. Weight slot **554** may extend through weight member **540** from a lower surface **541** of the weight member that is substantially parallel to the sole **503**—and may serve as an additional ground contact point when the golf club head is soled—through an upper surface of the weight member (not shown) that is positioned against the lower channel surface **531** of the weight channel and into a fastener port **552** in the weight channel **530**. The weight slot may further comprise an interior fastener ledge **555** to support the head **551** of fastener **550**. When tightened, fasteners **550** retain the weight member **540** in place. When fasteners **550** are loosened, the fasteners may be configured to remain stationary relative to their respective fastener ports **552**, while the position of the weight member **540** may be adjusted. In the illustrated example, weight member **540** may be translated laterally along the path **537** in a heelward or toeward direction to adjust, for example, golf club center of gravity movement along an x-axis (CGx), such as to control left or right tendency of a golf swing.

(178) FIG. **17** illustrates another exemplary golf club head **600** that embodies certain inventive technologies disclosed herein. The golf club head **600** is similar to golf club head, **100**, though one difference is that in golf club head **600**, weight channel **630** is positioned within a raised sole portion **660** at the rear end **610** of the golf club head **600**, and curves forward at the ends towards the front end **604** of the golf club head. Weight channel **630** and weight member **640** may contain features similar to weight channel **130** and weight member **140**. In the illustrated example, however, weight channel extends around the rear end **610** of the golf club head **600**, from a position around a periphery of the golf club head situated on the toe side **608** to a position on the heel

side **606**. Weight channel **630** may comprise a lower channel surface **631** that may be substantially parallel to or slightly angled away from a sole **603** of the golf club head, and may be coextensive, raised up from, or lowered from a raised sole portion **660** at the rear end **610** of the golf club head. Additionally, the weight channel **630** may extend around an entire length of the raised sole portion **660**, as illustrated, or may in some embodiments comprise only a portion of a length of the raised sole portion **660**. Within lower channel surface **631** is positioned at least one fastener port (not shown)—which may be similar to the fastener ports described herein and in the incorporated patents and/or applications—that may be configured to receive a fastener **650**. The fastener may comprise a head **651** with which a tool (not shown) may be used to tighten or loosen the fastener, and a fastener body (not shown) that may, e.g., be threaded to interact with corresponding threads on the fastener port to facilitate tightening or loosening the fastener **650**.

(179) Similar to weight channel **130**, weight channel **630** is configured to define a path **637** for and to at least partially contain adjustable weight member **640** that is both configured to translate along the path **637** and sized to be slidably retained, or at least partially retained, within the footprint of the weight channel **630** by fastener **650**. The path **637** may run the length of the weight channel **630**, or may, in some embodiments, comprise only a portion of the weight channel **630**. Fastener **650** may be removable, and may comprise a screw, bolt, or other suitable device for fastening as described herein and in the incorporated applications. Fastener **650** may extend through an elongated weight slot **654** passing through the body of the weight member **640**. Weight slot **654** may extend through weight member **640** from a lower surface **641** of the weight member that is substantially parallel to the sole **603**—and may serve as an additional ground contact point when the golf club head is soled—through an upper surface of the weight member (not shown) that is positioned against the lower channel surface **631** of the weight channel and into the fastener port in the weight channel **630**. The weight slot may further comprise an interior fastener ledge (not shown) to support the head **651** of fastener **650**. The weight member may have additional discretionary mass positioned proximate to its ends, such as within a first discretionary mass portion positioned at a heelward end **646** and a second discretionary mass portion positioned at a toward end **648**. The weight slot may further comprise an interior fastener ledge (not shown) to support the head **651** of fastener **650**. Alternatively, the lower surface **641** of the portion of weight member **640** containing the weight slot may be slightly recessed between heelward end **646** and toward end **648** so that the head **651** of the fastener **650** is lower than, or no higher than, or substantially similar in height to the remainder of the lower surface **641** of the weight member, as described further herein. When tightened, the fastener **650** retains the weight member **640** in place. When fastener **650** is loosened, the fastener may be configured to remain stationary relative to the fastener port **652**, while the position of the weight member **640** may be adjusted. In the illustrated example, weight member **640** may be translated laterally along the path **637** in a heelward or toward direction to adjust, for example, golf club center of gravity movement along an x-axis (CGx), such as to control left or right tendency of a golf swing.

(180) Weight member **640** may have a mass that is between 10 to 50 grams, or in some particular instances, a mass that is above 10 grams, or a mass that is below 40 grams, or a mass in the range of 12 to 38 grams.

(181) FIG. 18 illustrates another exemplary golf club head **700** that embodies certain inventive technologies disclosed herein. The golf club head **700** is similar to golf club head, **100**, though one difference is that in golf club head **700**, weight channel **730** is positioned within a raised sole portion **760** at the rear end **710** of the golf club head **700**, and curves forward at the ends towards the front end **704** of the golf club head. Weight channel **730** and weight member **740** may contain features similar to weight channel **130** and weight member **140**. In the illustrated example, however, weight channel extends around the rear end **710** of the golf club head **700**, from a position around a periphery of the golf club head situated on the toe side **708** to a position on the heel side **706**. Weight channel **730** may comprise a lower channel surface **731** that may be substantially parallel to or slightly angled away from a sole **703** of the golf club head, and may be coextensive, raised up from, or lowered from a raised sole portion **760** at the rear end **710** of the golf club head. Additionally, in the illustrated embodiment, the weight channel **730** comprises only a portion of a length of the raised sole portion **760**. Raised sole portion **760** further comprises external ribs **792** that may be integrally formed with the body **702** of the golf club head **700**.

(182) Within lower channel surface **731** is positioned at least one fastener port (not shown)—which may be similar to the fastener ports described herein and in the incorporated patents and/or applications—that may be configured to receive a fastener **750**. The fastener may comprise a head **751** with which a tool (not shown) may be used to tighten or loosen the fastener, and a fastener body (not shown) that may, e.g., be threaded to interact with corresponding threads on the fastener port to facilitate tightening or loosening the fastener **750**.

(183) Similar to weight channel **130**, weight channel **730** is configured to define a path **737** for and to at least partially contain adjustable weight member **740** that is both configured to translate along the path **737** and

sized to be slidably retained, or at least partially retained, within the footprint of the weight channel **730** by fastener **750**. In the illustrated embodiment, the path **737** may run the length of the weight channel **730**, or may, in some embodiments, comprise only a portion of the weight channel **730**. Fastener **750** may be removable, and may comprise a screw, bolt, or other suitable device for fastening as described herein and in the incorporated patents and applications. Fastener **750** may extend through an elongated weight slot **754** passing through the body of the weight member **740**. Weight slot **754** may extend through weight member **740** from a lower surface **741** of the weight member that is substantially parallel to the sole **703**—and may serve as an additional ground contact point when the golf club head is soled—through an upper surface of the weight member (not shown) that is positioned against the lower channel surface **731** of the weight channel and into the fastener port in the weight channel **730**. The weight member may have additional discretionary mass positioned proximate to its ends, such as within a first discretionary mass portion positioned at a heelward end **746** and a second discretionary mass portion positioned at a toeward end **748**. The weight slot may further comprise an interior fastener ledge (not shown) to support the head **751** of fastener **750**. Alternatively, the portion of the lower surface **641** of the portion of weight member **740** containing the weight slot may be slightly recessed between heelward end **746** and toeward end **748** so that the head **751** of fastener **750** is lower than, or no higher than, or substantially similar in height to the remainder of the lower surface **741** of the weight member, as described further herein. When tightened, the fastener **750** retains the weight member **740** in place. When fastener **750** is loosened, the fastener may be configured to remain stationary relative to the fastener port **752**, while the position of the weight member **740** may be adjusted. In the illustrated example, weight member **740** may be translated laterally along the path **737** in a heelward or toeward direction to adjust, for example, golf club center of gravity movement along an x-axis (CGx), such as to control left or right tendency of a golf swing.

(184) Weight member **740** may have a mass that is between 10 to 50 grams, or in some particular instances, a mass that is above 10 grams, or a mass that is below 40 grams, or a mass in the range of 12 to 38 grams. FIGS. **19-22** illustrate exemplary weight members that may be used with the golf clubs head disclosed herein.

(185) FIGS. **19** and **20** illustrate a weight member **800** having a curved shape, similar to weight member **740**, above. Weight member **800** has a middle portion **840** that contains a curved weight slot **854**. Weight slot **754** may extend through weight member **800** from a lower surface **841** of the weight member that is configured to be substantially parallel to a sole of a golf club head and to serve as an additional ground contact point when the golf club head is soled—through an upper surface **845** of the weight member **800** that is configured to be positioned against the body of the golf club head, such as a weight channel or raised sole portion, as described herein. The weight member may have additional discretionary mass positioned proximate to its ends, such as within a first discretionary mass portion positioned at a first end portion **846** (such as a heelward end portion) and a second discretionary mass portion positioned at a second end portion **848** (such as a toeward end portion). The weight slot may further comprise an interior fastener ledge (not shown) to support a fastener head. Additionally or alternatively, as illustrated in FIG. **20**, the lower surface **841** of the middle portion **840** may be slightly recessed up between the first end portion **846** and the second end portion **848** so that the head of a fastener inserted through the weight member **800** is lower than, or no higher than, or substantially similar in height to the lower surface **841** of the weight member at the first end portion **846** and the second end portion **848**.

(186) In some embodiments, the weight member **800** may be formed from a single piece of material, such as by casting, injection molding, machining, or other suitable methods, with first end portion **846** and the second end portion **848** formed to have a greater thickness than the middle portion **840**. In other embodiments, additional material, such as additional layers of material, or additional discretionary mass elements may be added to the first end portion **846** and/or the second end portion **848** to add additional mass to the ends. In particular embodiments, this may be achieved by welding an additional thickness of mass to the weight member **800** at one or both of the ends. It is to be understood, however, that additional mass could be added by other methods, such as bolting, adhering, or braising additional mass, or by introducing removable discretionary mass elements, such as described herein.

(187) In some embodiments, weight member **800** may be formed of a first material, such as titanium. In other embodiments, steel, tungsten or another suitable material or combination of materials may be used. In particular embodiments, higher density materials may be used in certain portions of the weight member **800** to add additional mass, such as, e.g., at first end portion **846** and/or second end portion **848**. For example, steel or tungsten or other suitable higher density materials could be used at first end portion **846** and the second end portion **848** to add additional discretionary mass to the ends of the weight member **800** relative to the middle portion **840**, or additional higher density elements, e.g., plates, could be added at first end portion **846** and/or second end portion **848** to add additional discretionary mass.

(188) "Split mass" configurations such as those described herein potentially allow for several high MOI positions and allow greater weight to be moved to the outside of the club head while minimizing the overall weight added to the club head. Additionally, providing the added weight along the perimeter of the golf club may have additional benefits for maximizing MOI. And, providing a curved shape weight member, combined with a split mass configuration as described herein also may provide for additional mass to be positioned more forward than in a configuration without a split mass configuration, which provides improved CG projection. Additionally, providing the slidable rear weight as illustrated in FIGS. 17-22 provides the potential for improved CGx movement (which may permit movement to affect, e.g., left/right draw/fade bias), while minimizing CGz movement, and potentially reducing CGy movement versus other traditional weight systems. This may improve overall MOI throughout the range of movement.

(189) FIG. 21 illustrates another weight member assembly **900**, which comprises a weight member **940** that may be similar to weight member **800**, or may alternatively be a linear weight member. Positioned at opposite ends of the weight member **940** are fastener ports **952**, such as those described herein and/or in the incorporated patents and applications, which may be configured to receive a fastener **950**. The fasteners may be individual movable weights ranging from 1 to 20 grams. The fasteners may have the same mass, or may be different masses. A weight kit may be provided containing weights of varying mass that a user can optionally attach or detach to **900** and **1000**. The fasteners may be used for swing weighting to achieve the targeted swing weight and offset manufacturing tolerance and custom length clubs. Or, the fasteners may help achieve a heavier e.g. D4 or lighter swing weight e.g. D1. One or both of the fasteners may be formed from a higher density material than the central region of the weight member **940**. In some instances, one or both of the fasteners may be formed of the same material as the central region of the weight member **940**. The central region may be formed from a material having a density between 9-20 g/cc (e.g. Tungsten and Tungsten alloys), 7-9 g/cc (e.g. steel and steel alloys), 4-5 g/cc (e.g. Ti and Ti alloys), 2-3 g/cc (e.g. Al and Al alloys), or 1-2 g/cc (e.g. Plastic, Carbon Fiber Reinforced Plastic, Carbon Fiber Reinforced Thermoplastic, Carbon Fiber Reinforced Thermoset), or other suitable materials.

(190) The fastener may comprise a head **951** with which a tool (not shown) may be used to tighten or loosen the fastener, and a fastener body **953** that may, e.g., be threaded to interact with corresponding threads on the fastener port **952** to facilitate tightening or loosening the fastener **950**. Further, fastener **950** is configured to retain a discretionary mass element between the lower surface **941** of the weight member **940** and the head of the fastener **950**, such as first discretionary mass element **946** positioned at a first end (such as a heelward end) of the weight member **940** and second discretionary mass element **948** positioned at a second end (such as a toeward end) of the weight member **940**. Discretionary mass elements **946** and **948** may further contain internal apertures, portions of which may be threaded to interact with threads on the fastener body **953** and other portions which may or may not be threaded and are configured to retain some or all of the fastener head **951**.

(191) In some embodiments, weight member **900** may be formed of a first material, such as titanium. In other embodiments, steel, tungsten or another suitable material or combination of materials may be used. In particular embodiments, higher density materials may be used in certain portions of the weight member **900** to add additional mass. For example, steel or tungsten or other suitable higher density materials could be used, e.g., in discretionary mass elements **946** and **948** or in fasteners **950** to add additional discretionary mass to the ends of the weight member **900**.

(192) FIG. 22 illustrates another weight member assembly **1000**, which comprises a weight member **1040** that may be similar to weight member **800**, or may alternatively be a linear weight member. Positioned at opposite ends of the weight member **1040** are fastener ports **1052**, such as those described herein and/or in the incorporated patents and applications, which may be positioned in the lower surface **1041** of the weight member **1000**, and configured to receive a fastener **1050**. The fastener may comprise a head **1051** with which a tool (not shown) may be used to tighten or loosen the fastener, and a fastener body **1053** that may, e.g., be threaded to interact with corresponding threads on the fastener ports **1052** to facilitate tightening or loosening the fastener **1050**. Fastener **1050** may itself comprise a discretionary mass, as described in the incorporated patents and/or applications, which discretionary mass may be removed and replaced with a heavier or lighter discretionary mass to adjust mass properties of a golf club head, as desired. Portions of fastener port **1052** may be threaded to interact with threads on the fastener body **1053** and other portions may not be threaded and may be configured to retain some or all of the fastener head **1051**.

(193) In some embodiments, weight member **1000** may be formed of a first material, such as titanium. In other embodiments, steel, tungsten or another suitable material or combination of materials may be used. In particular embodiments, higher density materials may be used in certain portions of the weight member **1000**

to add additional mass. For example, steel or tungsten or other suitable higher density materials could be used, e.g., in fasteners **1050** or for forming them in or adhering them to the ends of the weight member, such as in the manner further described above and in the incorporated patents and applications, to add additional discretionary mass to the ends of the weight member **1000**.

(194) FIGS. **23A** and **23B** illustrate another exemplary golf club head **1100** that embodies certain inventive technologies disclosed herein. The golf club head **1100** is similar to golf club head, **100**. In golf club head **1100**, weight channel **1130** may contain features similar to weight channel **130**, and may be formed as a curved arc extending in a generally heel-toe direction. Weight channel **1130** may comprise a lower channel surface **1131** that may be substantially parallel to, or as illustrated, slightly angled away from a sole **1103** of the golf club head, so that the weight channel **1130** may be deeper at a forward edge **1132** than it is at a rearward edge **1134**.

(195) Similar to weight channel **130**, weight channel **1130** is configured to define a path **1137** for and to at least partially contain adjustable weight member **1140** that is both configured to translate along the path **1137** and sized to be slidably retained, or at least partially retained, within the footprint of the weight channel **1130** by fastener assembly **1160**. Unlike the previous examples, which relied on fasteners passing through at least a portion of the weight member, golf club head **1100** comprises a fastener assembly **1160** comprising a fastener tab **1165** that may extend from a rear ground contact surface **1118** proximate to the rear end **1110** of the golf club head to a weight overhang or ledge **1174** that may at least partially cover the weight member **1140**, such as its rearward side **1144**, as best illustrated in FIG. **23B**. Within fastener tab **1165** is positioned one or more fastener ports **1152** (one such port is provided in the illustrated example). Fastener port **1152** may be configured to receive a removable fastener **1150**, such as a bolt or screw, or one of the other suitable fasteners described herein or in the incorporated patents and applications. As such, fastener port **1152** may be threaded so that a removable fastener **1150** secured therein can be loosened or tightened either to allow movement of, or to secure weight member **1140** in position, as further described herein. The fastener may comprise a head **1151** with which a tool (not shown) may be used to tighten or loosen the removable fastener **1150**, and a fastener body **1153** that may, e.g., be threaded to interact with corresponding threads on the fastener port **1152** to facilitate tightening or loosening the removable fastener **1150**. The fastener port **1152** can have any of a number of various configurations to receive and/or retain any of a number of fasteners, which may comprise simple threaded fasteners, as described above, or any of the fastener types described in the incorporated patents and/or applications. The fastener port may further comprise an interior fastener port ledge **1155** to support the head **1151** of fastener **1150**, which may be at least partially recessed within the fastener port **1152**, and which in the illustrated example is substantially parallel to rear ground contact surface **1118**.

(196) As illustrated in FIG. **23B**, fastener port **1152** is positioned entirely outside of the weight channel **1130** and extends from the sole **1103** into the body of the golf club head **1100**. In some embodiments, the fastener port **1152** may extend into an interior cavity **1122** of the golf club head **1100**. Additionally, the weight member may have a greater height at the forward side **1142** than at the rearward side **1144**, and may taper down from the forward side **1142** to the rearward side **1144**. In particular cases, the weight member **1140** may be configured so that the center of mass is positioned closer to the forward side **1142** than to the rearward side **1144**. Additionally, an upper surface **1145** of the weight member may extend further rearward than a lower surface **1141** of the weight member, with a rearward side **1144** of the weight member **1140** sloping up in a rearward direction from the sole **1103**, permitting at least a portion of the rearward side **1144** of the weight member to engage the ledge **1174** on the fastener tab **1165**. Ledge **1174** may itself be angled so that a lower portion nearest the sole **1103** extends further forward than an upper portion positioned nearer the lower surface **1131** of the weight channel **1130**.

(197) When tightened, the removable fastener **1150** presses down on fastener tab **1165** so that the ledge **1174** retains the weight member **1140** in place. Once removable fastener **1150** is loosened, the fastener is configured to remain stationary relative to the fastener port **1152**, while the position of the weight member **1140** may be adjusted relative to the fastener port. In the illustrated example shown in FIG. **23A**, weight member **1140** may be translated laterally along the path **1137** in a generally heelward or toward direction to adjust, for example, golf club center of gravity movement along an x-axis (CG_x), such as to control left or right tendency of a golf swing. One advantage of the golf club head **1100** shown in this example is that in moving the removable fastener **1150** outside of the weight channel **1130**, the weight member **1140** need not be specially engineered to contain a slot passing through the weight member **1140** to receive the removable fastener **1150**. This example may also provide a more consistent distribution of mass throughout the weight than some other examples.

Further Embodiments and Features

(198) FIGS. **24-27** illustrate another exemplary golf club head **1200** that embodies the inventive technologies disclosed herein. The golf club head **1200** is similar to other golf club heads discussed herein. The golf club

head **1200** includes a body **1202** defining an interior cavity **1222** (depicted in FIG. 25), a sole **1203** defining a bottom portion of the golf club head **1200**, a crown **1209** (depicted in FIG. 25) defining a top portion of the golf club head, a face **1211** (depicted in FIG. 25) defining a forward portion of the golf club head, a rearward portion of the golf club head opposite the face **1211**, and a hosel **1262**. The hosel **1262** can include a shaft connection assembly configured to selectively adjust a loft and/or a lie-angle of the of the golf club **1200**. (199) The golf club head **1200** includes a weight channel **1230** that may contain features similar to weight channel **130**, however weight channel **1230** may be formed as a path **1237** extending in a generally front-back direction. In some instances, the weight channel **1230** and therefore the path may be angled relative to a vertical x-z plane intersecting the center of the face see for example FIG. 56B of U.S. Pat. No. 10,537,773 describing an angled sliding weight track that may be angled relative to a vertical plane intersecting the center of the face and angled between about 0 degrees and about 180 degrees, such as between about 67 degrees and about 85 degrees, such as between about 20 degrees and about 160 degrees, such as between about 40 degrees and about 140 degrees, such as between about 60 degrees and about 120 degrees, such as between about 70 degrees and about 110 degrees. The entire contents of U.S. Pat. No. 10,537,773 are hereby incorporated by reference in their entirety. The weight channel **1230** is configured to define a path **1237** for and to at least partially contain adjustable weight member **1240** that is both configured to translate along the path **1237** and sized to be slidably retained, or at least partially retained, within the footprint of the weight channel **1230** by fastener **1250**.

(200) The weight member **1240** is configured to move independent of a fastener **1250** and the location of the fastener port **1252**. The fastener **1250** may be fixed at a single location or a series of locations. By fixing the fastener **1250** at a single location, the weight member **1240** is movable/adjustable independent of the fastener location. Having the fastener secured in a single or series of locations can save weight over typical infrastructure required for a sliding weight system. For example, ledges are not required for clamping or compressing against the weight member **1240**. The present embodiments of a sliding weight member **1240** also does not leave undesirable gaps between the weight member **1240** and the body **1202** because the weight member **1240** is moved to different positions. These undesirable gaps could trap air, dirt, or debris, any of which could negatively impact club head speed and ground interaction. These undesirable gaps could also create an undesirable whistling sound that a user may not want to hear during a swing, distracting the user and negatively impacting performance of the club head.

(201) The weight member **1240** can be adjusted by repositioning the weight member **1240** within the weight channel **1230**. In some embodiments, the weight member **1240** has three or more positions, such as three or more predefined or undefined positions within the weight channel **1230**. In some embodiments, the weight member **1240** can be positioned at any location along the weight channel **1230**, such as in a continuous path of positions along the weight channel **1230**. For example, in a first, forward position (depicted in FIGS. 24-25), between about 5% and about 80% of the weight member **1240** is covered by the body **1202**, preferably between 10% and 50%. In a second, rearward position (depicted in FIGS. 26-27), between 0% and 50% of the weight member **1240** is covered by the body **1202**, preferably between 0% and 25%. In a third, middle position (not depicted), between about 2.5% and about 65%, preferably between 5% and 40%. The weight member **1240** can be adjusted into additional and different positions along the path **1237** of the weight channel **1230**.

(202) In some embodiments, the weight member **1240** is configured to increase a water-displaced volume of the golf club head **1200** when the weight member **1240** is adjusted from a first, forward position in the weight channel **1230** to a second, rearward position in the weight channel **1230**. For example, when the weight member **1240** is in the first, forward position (depicted in FIGS. 24-25), at least a portion of the weight member **1240** is covered by the body **1202**, such as by the weight member **1240** occupying a weight cavity **1295** (depicted in FIG. 25) inside the body **1202**. When the weight member **1240** is in the second, rearward position (depicted in FIGS. 26-27), a smaller portion of the weight member **1240**, or no portion of the weight member **1240**, is covered by the body **1202**, such as by the weight member **1240** unoccupying at least a portion of the weight cavity **1295** (depicted in FIG. 27) inside the body **1202**. By sliding the weight member **1240** rearward and outward from the weight cavity **1295**, the water-displaced volume of the golf club head **1200** can increase, such as by the volume of the uncovered portion of the weight member **1240** extending outside of the weight cavity **1295**. In some instances, adjusting the weight member **1240** can increase the club head volume by at least 2 cc and no more than 15 cc, preferably between 2.5 cc and 12 cc, more preferably between 1.5 cc and 9 cc.

(203) The club head **1200** is provided as a wood-type club head having a volume, typically measured in cubic-centimeters (cc), equal to the volumetric displacement of the club head, assuming any concavities are sealed by a substantially planar surface. (See United States Golf Association "Procedure for Measuring the Club Head

Size of Wood Clubs,” Revision 2.1, Apr. 9, 2019) (the “USGA Procedure”). According to the USGA Procedure, prior to measuring the club head volume, significant concavities on the sole are filled with a waterproof clay or equivalent material. Multiple concavities on the sole are considered significant if the collective volume of all concavities on the sole is greater than 15 cc. Although the golf club head **1200** is depicted as a fairway wood with a volume between 120 cc and 300 cc and a mass between 115 g and 260 g, the golf club head **1200** can also be provided as any wood-type golf club head, including a driver with a volume between 300 cc and 500 cc and a mass between 145 g and 260 g, or a utility or hybrid club with a volume between 80 cc and 140 cc and a mass between 105 g and 280 g.

(204) For example, the golf club head **1200** can be a driver with a water-displaced volume between about 400 cc and about 470 cc, preferably 460 ± 10 cc. For example, when the weight member **1240** is in the first, forward position (depicted in FIGS. **24-25**), a collective concavity volume of the weight channel **1230** and all other concavities on the sole (e.g., recessed port **1266**, heelward concavity **1296**, and toeward concavity **1297**) are no more than 15 cc. By keeping sole concavities below 15 cc, an address area (e.g., surface area of the golf club head **1200** visible to the golfer at address) can be increased, giving greater confidence to the golf at address.

(205) FIGS. **24-25** illustrate the golf club head **1200** with the weight member **1240** positioned in a first, forward position along the path **1237** along the weight channel **1230**. The weight member **1240** may be translated along the path **1237** in a forward or rearward direction to adjust, for example, golf club center of gravity movement along a y-axis (CGy), such as to increase or decrease spin, dynamic loft, and moment of inertia (MOI), and to otherwise modify launch conditions of the club head **1200**. For example, the weight member **1240** can be configured to adjust CGy by between about 1 mm and about 15 mm, preferably between 3 mm and 10 mm, more preferably between 6 mm and 9 mm, even more preferably between 4 mm and 8 mm. In some embodiments, a change in CGy from a first position is at least 3 mm, more preferably at least 4 mm. The CGy movement generally corresponds to overall weight movement of no more than 31 mm from a first position to a second position, preferably no more than 26 mm, more preferably no more than 21 mm.

(206) The weight member **1240** and/or the weight channel **1230** can be curved from front to back direction along the path **1237**, such as in a convex path along the sole **1203**. The weight member **1240** and/or the weight channel **1230** can also be curved laterally, such as in a convex curve in a heel to toe direction. In some embodiments, a lower surface of the weight member **1240** is substantially shaped to match the contours of the sole **1203**, such as to provide better turf interaction and contributing to the “bounce” of sole **1203**. For example, a forward edge **1298** (depicted in FIG. **25**) of the weight channel **1230** can be closed, such as to prevent undesirable turf interaction and to reduce any dig of the sole **1203** through impact. The weight channel **1230** can be closed to the interior cavity **1222**, such as to prevent water, dirt, and other debris from entering the interior cavity **122**. The weight member **1240** can be shaped to substantially match the weight cavity **1295**, such as to reduce, minimize, or prevent water, dirt, and other debris from entering the weight cavity **1295**.

(207) One or more fasteners **1250** can be configured to pass through at least a portion of the weight member **1240**. The one or more fasteners **1250** can be threaded into a portion of the body **1202** to secure the weight member **1240**. For example, one or more fastener ports **1252** (one such port is provided in the illustrated example) are configured to receive the fastener. For example, the fastener port **1252** may be configured to receive a fastener **1250**, such as a removable bolt or screw, or one of the other suitable fasteners described herein or in the incorporated patents and applications. As such, fastener port **1252** may be threaded so that a removable fastener **1250** secured therein can be loosened or tightened either to allow movement of, or to secure weight member **1240** in position, as described herein. The fastener port **1252** can be positioned entirely outside of the weight channel **1230** and can extend from the sole **1203** into the body of the golf club head **1200**. In some embodiments, the fastener port **1252** may extend into an interior cavity **1222** of the golf club head **1200**. In some embodiments, the fastener port **1252** may extend into at least a portion of the weight channel **1230** of the golf club head **1200**. In some embodiments, at least a portion of the weight member **1240** is covered by a removable cover (not depicted) affixed to the body. In some embodiments, the removable cover is affixed over the fastener **1250**. In some embodiments, the removable cover is affixed to the body using the fastener **1250**.

(208) The fastener **1250** may extend through an elongated weight slot **1254** passing through the body of the weight member **1240**. The weight slot **1254** may extend through weight member **1240** from a lower surface **1241** of the weight member that is substantially parallel to the sole **1203**—and may serve as an additional ground contact point when the golf club head is soled—through an upper surface **1245** (depicted in FIG. **25**) of the weight member that is positioned against the lower channel surface **1231** of the weight channel and into a fastener port **1252** in the weight channel **1230**. The weight slot **1254** can be shaped to receive at least a portion of the fastener **1250**. In some embodiments, when tightened, the fastener **1250** can sit flush with the lower surface **1241** of the weight member. In some embodiments, when tightened, the fastener **1250** can be

countersunk below the lower surface **1241** of the weight member. When tightened, the fastener **1250** retains the weight member **1240** in place. Once the fastener **1250** is loosened, the fastener **1250** is configured to remain stationary relative to the fastener port **1252**, while the position of the weight member **1240** may be adjusted relative to the fastener port.

(209) The club head **1200** can include a front channel **1214** formed in the sole **1203**, as discussed herein regarding club head **100**. The front channel **1214** extends in a toe-heel direction across the sole **1203**, with a heelward end near the hosel **1262** and an opposite toward end. The front channel **1214** can extend into the interior of the club head **1200** and is positioned forward of the weight member **1240**, weight channel **1230**, weight cavity **1295**, and fastener **1250**.

(210) The weight member **1240** is formed from a higher density material than other portions of the body **1202**. In some embodiments, at least a portion of the body **1202** is formed from a first material, such as a steel or titanium alloy, and the weight member **1240** is formed from a second material, such as a tungsten alloy or steel. In some embodiments, at least a portion of the crown **1209** is formed from a first material, such as a titanium alloy, steel, or a composite material, and the weight member **1240** is formed from a second material, such as a tungsten alloy or steel. In some embodiments, at least a portion of the crown **1209** is formed from a first material, such as a composite material, and the body **1202** is formed from a second material, such as a titanium alloy or steel. For example, the composite crown can be affixed or affixed to a titanium body, frame, or shell. In an example, the body is cast without the crown, and a composite crown is affixed or bonded to the cast body. In some embodiments, at least a portion of the face **1211** is formed from a first material, such as a titanium alloy, steel or a composite material, and the weight member **1240** is formed from a second material, such as a tungsten alloy or steel.

(211) In some embodiments, the weight member **1240** is formed from a steel alloy, a tungsten alloy, or another alloy and is between about 5.5 g/cc and about 20 g/cc, preferably between about 7.5 g/cc and about 14 g/cc, the crown **1209** is between about 1 g/cc and about 5 g/cc, preferably between 1 g/cc and 2 g/cc, and the body **1202** is between about 4 g/cc and about 8 g/cc. In some embodiments, the weight member **1240** can form between about 15% and about 35% of the total mass/weight of the club head **1200**, preferably about 25% of total mass/weight. In some embodiments, the weight member **1240** can form between about 5% and about 40% of the total material volume of the body **1202**, preferably between about 7% and 36% of total material volume, even more preferably between about 10% and 29%.

(212) In some embodiments, the face **1211** is face plate is welded, bonded, or otherwise affixed to the body **1202**. For example, the face plate can be formed from steel or a titanium alloy, such as C300 alloy steel, 4140 steel, 17-4 PH SS, 431 SS, 450 SS, ZA 1300 Ti, 9-1-1 Ti, or another alloy. In some embodiments, the face plate is machined before or after the face plate is welded to the body **1202**. For example, the face plate can be machined on a lathe or milled to provide localized stiffened regions, variable thickness regions, or inverted cone technology (ICT) regions (also referred to as a “donut”) located on the face plate at a location that surrounds or that is adjacent to the ideal striking location of the striking face. In some embodiments, the face **1211** is cast with the body **1202**, such as providing for a unitary cast body **1202** with the face **1211**. For example, the face plate can be milled after casting to provide an asymmetric or non-symmetrical face thickness profile, such as opposed to a 360-degree concentric circle symmetry provided using a lathe. As such, different areas of the face can be provided with different face thicknesses, as well as milled bulge and roll, twist, score lines, and other features of the face plate. The golf club heads of this disclosure may utilize, for example, the asymmetric or non-symmetrical face thickness features described in U.S. Patent App. Pub. 2019/0046845, published Feb. 14, 2019, which is incorporated herein by reference in its entirety. In another example, a composite face plate can be bonded or otherwise affixed to the body **1202**.

(213) In addition to those noted above, some examples of metals and metal alloys that can be used to form the components of the club head **1200** described include, without limitation: titanium alloys (e.g., 3-2.5, 6-4, SP700, 15-3-3-3, 10-2-3, or other alpha/near alpha, alpha-beta, and beta/near beta titanium alloys), aluminum/aluminum alloys (e.g., 3000 series alloys, 5000 series alloys, 6000 series alloys, such as 6061-T6, and 7000 series alloys, such as 7075), magnesium alloys, copper alloys, and nickel alloys. Additional and different materials can be used to form club head components.

(214) FIGS. 26-27 illustrate the golf club head **1200** with the weight member **1240** positioned in a in a second, rearward position. As depicted, the weight member **1240** moves independently of the location of the fastener **1250**. For example, the weight member **1240** can be adjusted in conjunction with an adjustable hosel **1262** (e.g., via a shaft connection assembly configured to selectively adjust a loft and/or a lie-angle of the of the golf club **1200**).

(215) During club fitting, for example, launch conditions of the club head **1200** can be adjusted by moving the

weight member **1240** and/or by adjusting the hosel **1262**. The weight member **1240** can be moved forward to decrease spin, decrease dynamic loft, and decrease MOI. With the weight member **1240** in a forward position, distance can be increased, in some cases with a tradeoff in forgiveness. The weight member **1240** can be moved backward to increase spin, increase dynamic loft and increase MOI. With the weight member **1240** in a rearward position, forgiveness can be increased, in some cases with a tradeoff in distance. The hosel **1262** can be adjusted to add loft thereby increasing spin and dynamic loft, or to decrease loft thereby decreasing spin and dynamic loft. For example, loft can be adjusted without impacting on MOI and other properties of the club head.

(216) The weight member **1240** and the hosel **1262** can be adjusted concurrently to adjust spin, loft, dynamic loft, MOI, launch angle, and other launch conditions. For example, with the weight member **1240** in a forward position and the hosel **1262** adjusted to increase loft, distance can be increased by providing for a high launch with low spin. In another example, with the weight member **1240** in a rearward position and the hosel **1262** adjusted to decrease loft, forgiveness can be increased while by providing for a lower launch with more spin. Additional and different combinations of weight member **1240** positions and hosel **1262** adjustments can be provided.

(217) In concurrently adjusting the weight member **1240** and the hosel **1262**, the weight member movement in mm can be multiplied by the mass of the weight member and the loft change of the hosel in degrees to provide a weight member value in $\text{mm} \cdot \text{g} \cdot \text{degrees}$. The weight member **1240** can move between about 10 mm and about 40 mm, preferably between 15 mm and 30 mm. The weight member **1240** can move a total distance that is between about 10% and about 40% of a club head length, more preferably between about 17% and about 35% of a club head length, even more preferably between about 26% and about 32% of a club head length, where the club head length is measured from a leading edge to a trailing edge substantially in a front-back direction or substantially along the y-axis. The weight member **1240** can have a mass between about 35 g and about 90 g, preferably between 50 g and 80 g. The hosel **1262** can be adjusted between about 0.5 degrees and 4 degrees. Thus, the weight member value can be between about 700 $\text{mm} \cdot \text{g} \cdot \text{degrees}$ and about 10,800 $\text{mm} \cdot \text{g} \cdot \text{degrees}$, preferably between about 2,430 $\text{mm} \cdot \text{g} \cdot \text{degrees}$ and about 7,500 $\text{mm} \cdot \text{g} \cdot \text{degrees}$.

(218) As discussed herein, changing golf club head mass properties and launch conditions can impact distance and forgiveness of the golf club head **1200**. Moving the weight member **1240** forward and backward can adjust the MOI about the CG z-axis (Izz), the CG x-axis (Ixx), the CG z-axis (Zup), and the CG projection on the face **1211** referred to as the balance point up (BP up) of the golf club head **1200**. The Izz can be adjusted between about 185 $\text{kg} \cdot \text{mm} \cdot \text{sup.2}$ and about 385 $\text{kg} \cdot \text{mm} \cdot \text{sup.2}$, preferably between 200 $\text{kg} \cdot \text{mm} \cdot \text{sup.2}$ and 315 $\text{kg} \cdot \text{mm} \cdot \text{sup.2}$. The Ixx can be adjusted between about 80 $\text{kg} \cdot \text{mm} \cdot \text{sup.2}$ and about 215 $\text{kg} \cdot \text{mm} \cdot \text{sup.2}$, preferably between 100 $\text{kg} \cdot \text{mm} \cdot \text{sup.2}$ and 200 $\text{kg} \cdot \text{mm} \cdot \text{sup.2}$. A change in Izz from a forward-most position to a rearward-most position can provide a change in Izz that is no less than 30 $\text{kg} \cdot \text{mm} \cdot \text{sup.2}$. The Zup can be adjusted between about 10 mm and about 22 mm, preferably between 11 and 18, even more preferably in at least one weight position no more than 15 mm. The BP up can be adjusted between about 18.0 mm and about 29.0 mm, preferably between 18.5 mm and 25 mm. In some embodiments, the BP projection of the club head **1200** can be between 0 to 4 mm with a large repositionable weight. In some embodiments, the BP projection is between about 0 mm and 2 mm with the weight in a forward position and between about 2 mm and about 4.0 mm with the weight in the rearward position. A maximum change in Zup from a forward position to a rearward position is no more than 2 mm, preferably no more than 1.5 mm, more preferably no more than 1.0 mm. A maximum change in BPup from a forward position to a rearward position is no more than 2 mm, preferably no more than 1.5 mm, more preferably no more than 1.0 mm.

(219) For example, when the weight member **1240** is in a first, forward position, the Zup can be between 11 mm and 18 mm, and the BP up can be between 17.5 mm and 25.0 mm. When the weight member is in a second, rearward position, the Zup can be between 13 mm and 23 mm, and the BP up can be between 21 mm and 29 mm. In this example, moving the weight member **1240** from the first to the second position can shift the center of gravity (CG) by at least 3 mm, preferably between about 3 mm and about 10 mm. In this way, a relatively small movement of the weight member **1240** of between about 10 mm and about 35 mm can produce a relatively large shift in CG.

(220) Referring to FIG. 27, the weight member **1240** may have a forward height **1242** that is less than a rearward height **1244**. In some embodiments, the rearward height **1244** is configured to be greater than an internal height of the weight cavity **1295**, which can be substantially the same as forward height **1242**. The weight member **1240** is elongated in a front to back direction. The forward height **1242** can be between about 4 mm and about 20 mm, preferably between 6 mm and 12 mm. The rearward height **1244** can be between about 4 mm and about 20 mm, preferably between 7 mm and 14 mm. Preferably the rearward height is greater than

the forward height. The forward height **1242** can be between about 10% and about 40% a peak crown height of the club head measured from a ground plane to a peak crown height (crown apex) relative to a z-axis, preferably between 13% mm and 31% mm of a peak crown height. The rearward height **1244** can be between about 10% and about 40% a peak crown height, preferably between 13% and 37%. The length **1247** of the weight member **1240** can be between about 30 mm and about 55 mm, preferably between 38 mm and 55 mm. Preferably the length **1247** of the weight member **1240** can be between about 35% and about 65% of a total length of the club head as measured from a leading edge of the club head to a trailing edge of the club head as measured along the y-axis, preferably between 44% and 57%. In some embodiments, the length **1247** of the weight member **1240** is no less than 50% of a total length of the club head. The width **1243** of the weight member **1240** can be between about 10 mm and about 40 mm, preferably between 15 mm and 35 mm, more preferably between 22 mm and 28 mm. In some embodiments, the width **1243** of the weight member **1240** can be between about 15% and 35% of a club head length measured heel to toe per the USGA club head measurement rule, preferably about 20% and 30%, and even more preferably between about 22% and 28% of a club head length. The USGA rule states: "If the club does not have a defined heel, then the toe-heel dimension (length) shall be the distance between parallel planes making contact with the toe of the club (toe plane) and a point 0.875" above the sole (floor plane) of the club on the heel side (heel plane)." R&A Rules Limited and United States Golf Association, PROTOCOL FOR MEASURING THE CLUBHEAD SIZE OF WOOD CLUBS, TPX3003 Rev. 2.1 9 Apr. 2019. USGA rules can be found at the following website: <https://www.usga.org/content/dam/usga/pdf/2019/equipment-standards/TPX3003%20Protocol%20for%20Measuring%20the%20Clubhead%20Size%20of%20Wood%20Clubs.pdf> last visited Dec. 17, 2020.

(221) Referring to FIG. 27, when the weight member **1240** is in second, rearward position, at least a portion of the rear surface of the weight member **1240** is configured to engage an inner surface of the rear portion. The inner surface of the rear portion is further configured to act as a back stop for the weight member **1240** in the event that the fastener **1250** loosens or fails. The inner surface of the rear portion is slanted to allow the weight member **1240** to translate rearward as the weight member **1240** is removed and forward as the weight member **1240** is inserted. The weight member **1240** can be provided with a front chamfer on leading edge of the weight member **1240** to assist during weight member **1240** installation and to avoid the leading edge contacting the surfaces of the weight cavity **1295**.

(222) FIGS. 28-29 illustrate another exemplary golf club head **1300** that embodies the inventive technologies disclosed herein. The golf club head **1300** is similar to other golf club heads discussed herein. The golf club head **1300** includes a body **1302** with a sole **1303**, a hosel **1362**, and a front channel **1314**. The body **1302** can include a weight channel **1330** configured to receive the repositionable weight member **1340**. The weight channel **1330** includes one or more grooves **1332** for engaging the weight member **1340**. The weight member **1340** includes one or more corresponding protrusions **1334** (depicted in FIG. 30) to engage the one or more grooves **1332**. In some embodiments, the weight member is rotated as the weight member **1340** is inserted in the grooves **1332**.

(223) In some embodiments, one or more grooves **1332** (depicted in FIG. 28) are provided in a heel side and/or a toe side of the weight channel **1330**. An exemplary toe side groove **1332** is depicted in FIG. 28. Additional and different grooves **1332** can be provided in the weight channel **1330**. The one or more grooves **1332** are configured to engage the weight member **1340** to prevent the weight member **1340** from twisting and/or falling out of the weight channel **1330**. When adjusted, the weight member **1340** slides along the groove(s) **1332** in a front-to-back path along the sole **1303**. The groove(s) **1332** can also provide additional stability to the weight member **1340** when the weight member **1340** is installed, allowing a relatively larger weight member **1340** than could be safely installed with only one or more fasteners **1350**. A fastener **1350** can be installed through a weight slot **1354** of the weight member **1340** to secure the weight member **1340** within the weight channel **1330**.

(224) In some embodiments, two or more indicators **1346** (depicted in FIG. 29) are provided to indicate the position of the weight member **1340** within the weight channel **1330**. For example, each weight indicator **1346** can be provided for a different position of the weight member **1340**. Each indicator **1346** can show a set amount of adjustment for the weight member **1340**, such as providing an indicator **1346** for each of millimeter of adjustment. In some embodiments, the weight member can be between 50 g and 70 g, preferably about 60 g. In some embodiments, the indicators **1346** indicate the change in CG as a result of adjusting the weight member **1340**. In some embodiments, the weight member can move CG by between 2 mm and 6 mm, preferably between 3 mm and 5 mm.

(225) In some embodiments, at least a portion of the composite crown **1309** can wrap into at least a portion of

the heel portion (depicted in FIG. 29). In some embodiments, at least a portion of the composite crown **1309** can wrap into at least a portion of the skirt, toe portion, and/or sole portion. In some embodiments, an outermost layer of the composite crown **1309** may be a woven layer. In some embodiments, at least a portion of the composite crown **1309** is formed from carbon. In some embodiments, the weight member **1340** defines at least a portion of the rear member. For example, as depicted in FIG. 29, when the weight member **1340** is in a rearward most position, a rear surface of the weight member **1340** can be flush with the skirt and can at least partially define a rear surface of the rear portion.

(226) FIG. 30 is a section view showing one or more grooves **1332** in the weight channel **1330** and one or more weight protrusions **1334** configured to engage the one or more grooves **1332**. The section view is taken through a portion of the weight member **1340** outside of the weight slot **1354** where fastener **1350** passes through the weight member **1340**.

(227) As depicted in FIG. 30, the weight channel **1330** can include at least two grooves **1332** and at least two protrusions **1334**. The one or more weight channel grooves **1332** and corresponding protrusions **1334** on the weight member **1340** are configured to secure the weight member **1340** in the weight channel **1330** when the fastener **1350** is loosened and/or in the unlikely event of the fastener **1350** failing. When the fastener **1350** is loosened or fails, the weight member is configured to remain at least partially secured within the weight channel **1330**.

(228) In some embodiments, the one or more grooves **1332** and corresponding protrusions **1334** on the weight member **1340** are configured to provide for a clamping system like the other embodiments discussed herein where a fastener threads into a threaded port to secure the weight member in a desired position. In a clamping system, tightening the fastener **1350** can be configured to pull the weight member **1340** inward toward the interior cavity **1322** (not depicted) of the golf club body **1302** and putting the fastener **1350** in a state of tension.

(229) In some embodiments, the one or more grooves **1332** and corresponding protrusions **1334** on the weight member **1340** are configured to provide a compression system where the fastener **1350** can press against an inner wall of the weight channel **1330** (e.g., a lower channel surface **1231** as depicted in FIG. 24), which can eliminate the need for a threaded port **1352** (not depicted) to receive the fastener **1350**. In a compressive system, tightening the fastener **1350** is configured to push the weight member **1340** outward away from the interior cavity **1322** and puts the fastener **1350** in a state of compression. A compression system can place some, if not all of the load on the one or more channel grooves **1332** and the one or more protrusions **1334** extending from the weight member **1340** that engage the one or more grooves **1332**.

(230) Compression system embodiments can place more load on the bearing surfaces (i.e., the one or more grooves **1332** and the corresponding one or more weight protrusions **1334**) and there is a greater likelihood of failure of the bearing surfaces, such as catastrophic failure resulting in the weight member **1340** breaking free from the golf club head **1300**. In tension system embodiments, the one or more grooves **1332** can act as a secondary safety mechanism to trap the weight member **1340** within the weight channel **1330** in the unlikely event that the fastener **1350** fails. In some embodiments, a tension system (e.g., using fastener **1350** in tension) can secure a weight member **1340** with greater mass compared to a compression system (e.g., using fastener **1350** in compression) which can secure a weight member with a lesser mass.

(231) FIG. 31 is a section view that is showing one or more ledges **1432** in the weight channel **1430** and the one or more weight surfaces **1434** configured to engage the one or more ledges **1432**. The section view is taken through a portion of the weight member **1440** outside of the weight slot **1454** (not depicted) where fastener **1450** (not depicted) passes through the weight member **1440**. This weight channel **1430** and weight member **1440** embodiment can be used with the club heads discussed herein, including club heads **1200**, **1300**, and other exemplary club heads.

(232) As depicted in FIG. 31, the weight channel **1430** can include at least two ledges **1432** and at least two weight surfaces **1434**. The one or more weight channel ledges **1432** and corresponding weight surfaces **1434** on the weight member **1440** are configured to secure the weight member **1440** in the weight channel **1430** when the fastener **1450** is loosened and/or in the unlikely event of the fastener **1450** failing. When the fastener **1450** is loosened or fails, the weight member is configured to remain at least partially secured within the weight channel **1430**.

(233) In some embodiments, the one or more weight channel ledges **1432** and corresponding weight surfaces **1434** on the weight member **1440** can be configured in a compression system as discussed herein. For example, the one or more weight channel ledges **1432** and corresponding weight surfaces **1434** on the weight member **1440** may be superior to the one or more grooves **1332** and corresponding protrusions **1334** on the weight member **1340** depicted in FIG. 30 provided in a compression system because one or more weight channel

ledges **1432** and corresponding weight surfaces **1434** on the weight member **1440** have fewer failure points on the bearing surfaces (e.g., the groove and/or protrusions shearing or breaking off). The one or more weight channel ledges **1432** and corresponding weight surfaces **1434** on the weight member **1440** can also provide a greater surface area of contact for the compression. In other embodiments, the one or more weight channel ledges **1432** and corresponding weight surfaces **1434** on the weight member **1440** can be configured in a tension system as discussed herein.

(234) Additional club head features are disclosed in U.S. Pat. No. 10,773,135, filed Aug. 28, 2019, issued Sep. 15, 2020, which is incorporated herein by reference in its entirety.

(235) Design Parameters for Golf Club Heads with Slidably Repositionable Weight(s)

(236) Although the following discussion cites features related to golf club head **100** and its variations (e.g. **400**, **500**, **1100**, **1200**), the many design parameters discussed below substantially apply to golf club heads **600** and **700** due to the common features of the club heads. With that in mind, in some embodiments of the golf clubs described herein, the location, position or orientation of features of the golf club head, such as the golf club head **100**, **400**, **500**, **600**, **700**, **1100** and **1200**, can be referenced in relation to fixed reference points, e.g., a golf club head origin, other feature locations or feature angular orientations. The location or position of a weight or weight assembly, such as the weight member **140**, **440**, **640**, **740**, **1140** and **1240** is typically defined with respect to the location or position of the weight's or weight assembly's center of gravity. When a weight or weight assembly is used as a reference point from which a distance, i.e., a vectorial distance (defined as the length of a straight line extending from a reference or feature point to another reference or feature point) to another weight or weight assembly location is determined, the reference point is typically the center of gravity of the weight or weight assembly.

(237) The location of the weight assembly on a golf club head can be approximated by its coordinates on the head origin coordinate system. The head origin coordinate system includes an origin at the ideal impact location of the golf club head, which is disposed at the geometric center of the striking surface **105** (see FIGS. **1A** and **1B**). As described above, the head origin coordinate system includes an x-axis and a y-axis. The origin x-axis extends tangential to the face plate at the origin and generally parallel to the ground when the head is ideally positioned with the positive x-axis extending from the origin towards a heel of the golf club head and the negative x-axis extending from the origin to the toe of the golf club head. The origin y-axis extends generally perpendicular to the origin x-axis and parallel to the ground when the head is ideally positioned with the positive y-axis extending from the head origin towards the rear portion of the golf club. The head origin can also include an origin z-axis extending perpendicular to the origin x-axis and the origin y-axis and having a positive z-axis that extends from the origin towards the top portion of the golf club head and negative z-axis that extends from the origin towards the bottom portion of the golf club head.

(238) As described above, in some of the embodiments of the golf club head **100** described herein, the weight channel **130** extends generally from a heelward end **136** oriented toward the heel side **106** of the golf club head to a toeward end **138** oriented toward the toe side **108** of the golf club head, with both the heelward end **136** and toeward end **138** being at or near the same distance from the front portion of the club head. As a result, in these embodiments, the weight member **140** that is slidably retained within the weight channel **130** is capable of a relatively large amount of adjustment in the direction of the x-axis, while having a relatively small amount of adjustment in the direction of the y-axis. In some alternative embodiments, the heelward end **136** and toeward end **138** may be located at varying distances from the front portion, such as having the heelward end **136** further rearward than the toeward end **138**, or having the toeward end **138** further rearward than the heelward end **136**. In these alternative embodiments, the weight member **140** that is slidably retained within the weight channel **130** is capable of a relatively large amount of adjustment in the direction of the x-axis, while also having from a small amount to a larger amount of adjustment in the direction of the y-axis.

(239) For example, in some embodiments of a golf club head **100** having a weight member **140** that is adjustably positioned within a weight channel **130**, the weight member **140** can have an origin x-axis coordinate between about -40 mm and about 40 mm, depending upon the location of the weight assembly within the weight channel **130**. In specific embodiments, the weight member **140** can have an origin x-axis coordinate between about -35 mm and about 35 mm, or between about -30 mm and about 30 mm, or between about -25 mm and about 25 mm, or between about -20 mm and about 20 mm, or between about -15 mm and about 15 mm, or between about -13 mm and about 13 mm. Thus, in some embodiments, the weight member **140** is provided with a maximum x-axis adjustment range (Max Δx) that is less than 80 mm, such as less than 70 mm, such as less than 60 mm, such as less than 50 mm, such as less than 40 mm, such as less than 30 mm, such as less than 26 mm.

(240) On the other hand, in some embodiments of the golf club head **100** having a weight member **140** that is

adjustably positioned within a weight channel **130**, the weight member **140** can have an origin y-axis coordinate between about 5 mm and about 80 mm. More specifically, in certain embodiments, the weight member **140** can have an origin y-axis coordinate between about 5 mm and about 50 mm, between about 5 mm and about 45 mm, or between about 5 mm and about 40 mm, or between about 10 mm and about 40 mm, or between about 5 mm and about 35 mm. Additionally or alternatively, in certain embodiments, the weight member **140** can have an origin y-axis coordinate between about 35 mm and about 80 mm, between about 45 mm and about 75 mm, or between about 50 mm and about 70 mm. Thus, in some embodiments, the weight member **140** is provided with a maximum y-axis adjustment range (Max Δy) that is less than 45 mm, such as less than 30 mm, such as less than 20 mm, such as less than 10 mm, such as less than 5 mm, such as less than 3 mm. Additionally or alternatively, in some embodiments having a rearward channel, the weight member is provided with a maximum y-axis adjustment range (Max Δy) that is less than 110 mm, such as less than 80 mm, such as less than 60 mm, such as less than 40 mm, such as less than 30 mm, such as less than 15 mm.

(241) In some embodiments, a golf club head can be configured to have a constraint relating to the relative distances that the weight assembly can be adjusted in the origin x-direction and origin y-direction. Such a constraint can be defined as the maximum y-axis adjustment range (Max Δy) divided by the maximum x-axis adjustment range (Max Δx). According to some embodiments, the value of the ratio of (Max Δy)/(Max Δx) is between 0 and about 0.8. In specific embodiments, the value of the ratio of (Max Δy)/(Max Δx) is between 0 and about 0.5, or between 0 and about 0.2, or between 0 and about 0.15, or between 0 and about 0.10, or between 0 and about 0.08, or between 0 and about 0.05, or between 0 and about 0.03, or between 0 and about 0.01.

(242) As discussed above, in some driver-type golf club head embodiments, the mass of the weight member, e.g. weight member **640** and/or weight member **740**, is between about 1 g and about 50 g, such as between about 3 g and about 40 g, such as between about 5 g and about 25 g. In some alternative embodiments, the mass of the weight member **640** and/or **740** is between about 5 g and about 45 g, such as between about 9 g and about 35 g, such as between about 9 g and about 30 g, such as between about 9 g and about 25 g.

(243) As discussed above, in some fairway-type golf club head embodiments, the mass of the weight member, e.g., weight member **140**, is between about 50 g and about 90 g, such as between about 55 g and about 80 g, such as between about 60 g and about 75 g. In some alternative embodiments, the mass of the weight member **140** is between about 5 g and about 45 g, such as between about 9 g and about 35 g, such as between about 9 g and about 30 g, such as between about 9 g and about 25 g.

(244) In some embodiments, a golf club head can be configured to have constraints relating to the product of the mass of the weight assembly and the relative distances that the weight assembly can be adjusted in the origin x-direction and/or origin y-direction. One such constraint can be defined as the mass of the weight assembly (M.sub.WA) multiplied by the maximum x-axis adjustment range (Max Δx). According to some embodiments, the value of the product of M.sub.WA \times (Max Δx) is between about 250 g.Math.mm and about 4950 g.Math.mm. In specific embodiments, the value of the product of M.sub.WA \times (Max Δx) is between about 500 g.Math.mm and about 4950 g.Math.mm, or between about 1000 g.Math.mm and about 4950 g.Math.mm, or between about 1500 g.Math.mm and about 4950 g.Math.mm, or between about 2000 g.Math.mm and about 4950 g.Math.mm, or between about 2500 g.Math.mm and about 4950 g.Math.mm, or between about 3000 g.Math.mm and about 4950 g.Math.mm, or between about 3500 g.Math.mm and about 4950 g.Math.mm, or between about 4000 g.Math.mm and about 4950 g.Math.mm.

(245) According to some embodiments, the value of the product of M.sub.WA \times (Max Δx) is between about 250 g.Math.mm and about 2500 g.Math.mm. In specific embodiments, the value of the product of M.sub.WA \times (Max Δx) is between about 350 g.Math.mm and about 2400 g.Math.mm, or between about 750 g.Math.mm and about 2300 g.Math.mm, or between about 1000 g.Math.mm and about 2200 g.Math.mm, or between about 1100 g.Math.mm and about 2100 g.Math.mm, or between about 1200 g.Math.mm and about 2000 g.Math.mm, or between about 1200 g.Math.mm and about 1950 g.Math.mm, or between about 1250 g.Math.mm and about 1900 g.Math.mm, or between about 1250 g.Math.mm and about 1750 g.Math.mm.

(246) Another constraint relating to the product of the mass of the weight assembly and the relative distances that the weight assembly can be adjusted in the origin x-direction and/or origin y-direction can be defined as the mass of the weight assembly (M.sub.WA) multiplied by the maximum y-axis adjustment range (Max Δy). According to some embodiments, the value of the product of M.sub.WA \times (Max Δy) is between about 0 g.Math.mm and about 1800 g.Math.mm. In specific embodiments, the value of the product of M.sub.WA \times (Max Δy) is between about 0 g.Math.mm and about 1500 g.Math.mm, or between about 0 g.Math.mm and about 1000 g.Math.mm, or between about 0 g.Math.mm and about 500 g.Math.mm, or between about 0 g.Math.mm and about 250 g.Math.mm, or between about 0 g.Math.mm and about 150

g.Math.mm, or between about 0 g.Math.mm and about 100 g.Math.mm, or between about 0 g.Math.mm and about 50 g.Math.mm, or between about 0 g.Math.mm and about 25 g.Math.mm.

(247) As noted above, one advantage obtained with a golf club head having a repositionable weight, such as the golf club head **100** having the weight member **140**, is in providing the end user of the golf club with the capability to adjust the location of the CG of the club head over a range of locations relating to the position of the repositionable weight. In particular, the present inventors have found that there is a distance advantage to providing a center of gravity of the club head that is lower and more forward relative to comparable golf clubs that do not include a weight assembly such as the weight member **140** described herein.

(248) In some embodiments, the golf club head **100** has a CG with a head origin x-axis coordinate (CGx) between about -10 mm and about 10 mm, such as between about -4 mm and about 9 mm, such as between about -3 mm and about 8 mm, such as between about -2 mm to about 5 mm, such as between about -0.8 mm to about 8 mm, such as between about 0 mm to about 8 mm. In some embodiments, the golf club head **100** has a CG with a head origin y-axis coordinate (CGy) greater than about 15 mm and less than about 50 mm, such as between about 22 mm and about 43 mm, such as between about 24 mm and about 40 mm, such as between about 26 mm and about 35 mm. In some embodiments, the golf club head **100** has a CG with a head origin z-axis coordinate (CGz) greater than about -8 mm and less than about 3 mm, such as between about -6 mm and about 0 mm. In some embodiments, the golf club head **100** has a CG with a head origin z-axis coordinate (CGz) that is less than 0 mm, such as less than -2 mm, such as less than -4 mm, such as less than -5 mm, such as less than -6 mm.

(249) As described herein, by repositioning the weight member **140** within the weight channel **130** of the golf club head **100**, the location of the CG of the club head is adjusted. For example, in some embodiments of a golf club head **100** having a weight member **140** that is adjustably positioned within a weight channel **130**, the club head is provided with a maximum CGx adjustment range (Max Δ CGx) attributable to the repositioning of the weight member **140** that is greater than 1 mm, such as greater than 2 mm, such as greater than 3 mm, such as greater than 4 mm, such as greater than 5 mm, such as greater than 6 mm, such as greater than 8 mm, such as greater than 10 mm, such as greater than 11 mm.

(250) Moreover, in some embodiments of the golf club head **100** having a weight member **140** that is adjustably positioned within a weight channel **130**, the club head is provided with a CGy adjustment range (Max Δ CGy) that is less than 6 mm, such as less than 3 mm, such as less than 1 mm, such as less than 0.5 mm, such as less than 0.25 mm, such as less than 0.1 mm.

(251) Additionally or alternatively, in some embodiments of the golf club head **100** having a weight member **140** that is adjustably positioned within a rearward channel, the club head is provided with a CGy adjustment range (Max Δ CGy) that is less than 10 mm, such as less than 5 mm, such as less than 3 mm, such as less than 1 mm, such as less than 0.5 mm, such as less than 0.25 mm, such as less than 0.1 mm.

(252) In some embodiments, a golf club head can be configured to have a constraint relating to the relative amounts that the CG is able to be adjusted in the origin x-direction and origin y-direction. Such a constraint can be defined as the maximum CGy adjustment range (Max Δ CGy) divided by the maximum CGx adjustment range (Max Δ CGx). According to some embodiments, the value of the ratio of (Max Δ CGy)/(Max Δ CGx) is between 0 and about 0.8. In specific embodiments, the value of the ratio of (Max Δ CGy)/(Max Δ CGx) is between 0 and about 0.5, or between 0 and about 0.2, or between 0 and about 0.15, or between 0 and about 0.10, or between 0 and about 0.08, or between 0 and about 0.05, or between 0 and about 0.03, or between 0 and about 0.01.

(253) In some embodiments, a golf club head can be configured such that only one of the above constraints apply. In other embodiments, a golf club head can be configured such that more than one of the above constraints apply. In still other embodiments, a golf club head can be configured such that all of the above constraints apply.

(254) Table 3 below lists various properties of an exemplary golf club head, which may be similar to golf club head **100**, having a weight assembly retained within a front channel.

(255) TABLE-US-00003 TABLE 3 Property Value in Exemplary Golf Club Head Slidable weight 66 assembly (g) volume (cc) 150 Δ 1 (mm) 10.7-11.0 max CGx (mm) 5.3 min CGx (mm) 0.3 max CGz (mm) 13.1 Zup min CGz (mm) 13.1 Zup max CGy (mm) 11.0 Δ 1 min CGy (mm) 10.7 Δ 1 distance of weight From center face to CG assembly to striking of weight assembly: face (mm) ~31 mm. From leading edge to most forward portion of weight assembly: ~17 mm channel length (mm) ~81 mm channel width (mm) ~40 mm channel depth (mm) ~12 mm Izz (kg .Math. mm.sup.2) 209 kg .Math. mm.sup.2 Ixx (kg .Math. mm.sup.2) 93 kg .Math. mm.sup.2

(256) Table 4 below lists various properties of an exemplary golf club head, which may be similar to golf club

head 100, having a weight assembly retained within a front channel, and located at center, toe, and heel positions, respectively:

(257) TABLE-US-00004 TABLE 4 Value in Exemplary Golf Club Head Property Center Toe Heel CGx (mm) 2.8 0.3 5.3 Zup (mm) 13.1 13.1 13.1 Delta 1 (mm) 10.7 11.0 11.0 Balance Point Up (mm) 19.532 19.684 19.732 CGx Delta (mm) -2.5 2.5 BP Delta (mm) 0.152 0.200 BP Delta/CGx Delta (mm/mm) **-0.061 0.080** Absolute value BP Delta/CGx **0.061 0.080** Delta (mm/mm)

(258) In table 4 above, BP Delta or Balance Point Up Delta represents the change in the Balance Point Up relative to the Balance Point Up when the weight is in the center position. For example, when the weight is in toewardmost position the Balance Point Up is 19.684 mm compared to 19.532 mm in the center position resulting in a delta or change of 0.152 mm. Similarly, in the heel position the BP Delta is 0.200 mm (19.732 mm-19.532 mm). BP Delta/CGx Delta (mm/mm) is again calculated relative to the center position. For example, BP Delta for the heelwardmost position relative to center is 0.200 mm and the CGx delta from center to heel is 2.5 mm (5.3 mm-2.8 mm) resulting in a ratio of 0.08. It was found that this track configuration produced a very large CGx movement with very little impact to Balance Point Up, which was lacking in earlier designs.

(259) In some embodiments described herein, BP Delta in a toewardmost position is no more than 0.50 mm, and is between 0.12 mm and 0.50 mm, such as between 0.13 mm and 0.40 mm, such as between 0.14 mm and 0.30 mm. In some embodiments described herein, BP Delta in a heelwardmost position is no more than 0.30 mm, and is between 0.12 mm and 0.30 mm, such as between 0.13 mm and 0.25 mm, such as between 0.15 mm and 0.25 mm.

(260) In some embodiments described herein, a BP Delta/CGx Delta (mm/mm) when the weight is in the toewardmost position is no more than 0.170 (absolute value). More specifically, the BP Delta/CGx Delta for the toewardmost position relative the center position can be between 0.170 (absolute value) and 0.040 (absolute value). In some embodiments described herein, a BP Delta/CGx Delta (mm/mm) when the weight is in the heelwardmost position is no more than 0.120 (absolute value). More specifically, the BP Delta/CGx Delta for the heelwardmost position relative the center position can be between 0.120 (absolute value) and 0.060 (absolute value). In some embodiments described herein, the summation of the BP Delta/CGx Delta (mm/mm) in the toewardmost position (absolute value) and the BP Delta/CGx Delta (mm/mm) in the heelwardmost position (absolute value) is no more than 0.29, and is between 0.11 and 0.29, such as between 0.12 and 0.28, such as between 0.13 and 0.25. Unexpectedly, the location of the weight bearing channel in the front portion of the club head can lead to synergies in golf club performance. First, because $\Delta_{sub.1}$ (delta 1) is relatively small, dynamic lofting is reduced; thereby reducing spin that otherwise may reduce distance. Additionally, because the projection of the CG is below the center-face, the gear effect biases the golf ball to rotate toward the projection of the CG—or, in other words, with forward spin. This is countered by the loft of the golf club head imparting back spin. The overall effect is a relatively low spin profile. However, because the CG is below the center face (and, thereby, below the ideal impact location) as measured along the z-axis, the golf ball will tend to rise higher on impact. The result is a high launching but lower spinning golf shot on purely struck shots, which leads to better ball flight (higher and softer landing) with more distance due to less energy loss from spin.

(261) The distance between weight channels/weight ports and weight size can contribute to the amount of CG change made possible in a golf club head, particularly in a golf club head used in conjunction with a removable sleeve assembly, as described above.

(262) In some exemplary embodiments of a golf club head having two, three or four weights, a maximum weight mass multiplied by the distance between the maximum weight and the minimum weight is between about 100 g.Math.mm and about 3,750 g.Math.mm or about 200 g.Math.mm and 2,000 g.Math.mm. More specifically, in certain embodiments, the maximum weight mass multiplied by the weight separation distance is between about 500 g.Math.mm and about 1,500 g.Math.mm, between about 1,200 g.Math.mm and about 1,400 g.Math.mm.

(263) When a weight or weight port is used as a reference point from which a distance, i.e., a vectorial distance (defined as the length of a straight line extending from a reference or feature point to another reference or feature point) to another weight or weights port is determined, the reference point is typically the volumetric centroid of the weight port. When a movable weight club head and sleeve assembly are combined, it is possible to achieve the highest level of club trajectory modification while simultaneously achieving the desired look of the club at address. For example, if a player prefers to have an open club face look at address, the player can put the club in the “R” or open face position. If that player then hits a fade (since the face is open) shot but prefers to hit a straight shot, or slight draw, it is possible to take the same club and move the heavy weight to

the heel port to promote draw bias. Therefore, it is possible for a player to have the desired look at address (in this case open face) and the desired trajectory (in this case straight or slight draw).

(264) In yet another advantage, by combining the movable weight concept with an adjustable sleeve position (effecting loft, lie and face angle) it is possible to amplify the desired trajectory bias that a player may be trying to achieve.

(265) For example, if a player wants to achieve the most draw possible, the player can adjust the sleeve position to be in the closed face position or “L” position and also put the heavy weight in the heel port. The weight and the sleeve position work together to achieve the greater draw bias possible. On the other hand, to achieve the greatest fade bias, the sleeve position can be set for the open face or “R” position and the heavy weight is placed in the top port.

(266) As described above, the combination of a large CG change (measured by the heaviest weight multiplied by the distance between the ports) and a large loft change (measured by the largest possible change in loft between two sleeve positions, Δloft) results in the highest level of trajectory adjustability. Thus, a product of the distance between at least two weight ports, the maximum weight, and the maximum loft change is important in describing the benefits achieved by the embodiments described herein.

(267) In one embodiment, the product of the distance between at least two weight ports, the maximum weight, and the maximum loft change is between about 50 mm.Math.g.Math.deg and about 8,000 mm.Math.g.Math.deg, preferably between about 2000 mm.Math.g.Math.deg and about 6,000 mm.Math.g.Math.deg, more preferably between about 2500 mm.Math.g.Math.deg and about 4,500 mm.Math.g.Math.deg, or even more preferably between about 3000 mm.Math.g.Math.deg and about 4,100 mm.Math.g.Math.deg. In other words, in certain embodiments, the golf club head satisfies the following expressions in Equations 4-7. Notably, the maximum loft change may vary between 2-4 degrees, and the preferred embodiment having a maximum loft change of 4 degrees or ± 2 degrees.

$$50 \text{ mm.Math.g.Math.degrees} < Dwp.Math.Mhw.Math.\Delta\text{loft} < 8,000 \text{ mm.Math.g.Math.degrees} \quad (4)$$

$$2000 \text{ mm.Math.g.Math.degrees} < Dwp.Math.Mhw.Math.\Delta\text{loft} < 6,000 \text{ mm.Math.g.Math.degrees} \quad (5)$$

$$2500 \text{ mm.Math.g.Math.degrees} < Dwp.Math.Mhw.Math.\Delta\text{loft} < 4,500 \text{ mm.Math.g.Math.degrees} \quad (6)$$

$$3000 \text{ mm.Math.g.Math.degrees} < Dwp.Math.Mhw.Math.\Delta\text{loft} < 4,100 \text{ mm.Math.g.Math.degrees} \quad (7)$$

(268) In the above expressions, Dwp, is the distance between two weight port centroids (mm), Mhw, is the mass of the heaviest weight (g), and Δloft is the maximum loft change (degrees) between at least two sleeve positions. A golf club head within the ranges described above will ensure the highest level of trajectory adjustability.

(269) Additional disclosure regarding providing both a movable weight and an adjustable shaft assembly to a golf club head can be found in U.S. Pat. No. 8,622,847, the entire contents of which are incorporated by reference.

(270) According to some exemplary embodiments of a golf club head described herein, head an areal weight, i.e., material density multiplied by the material thickness, of the golf club head sole, crown and skirt, respectively, is less than about 0.45 g/cm² over at least about 50% of the surface area of the respective sole, crown and skirt. In some specific embodiments, the areal weight is between about 0.05 g/cm² and about 0.15 g/cm², between about 0.10 g/cm² and about 0.20 g/cm² between about 0.15 g/cm² and about 0.25 g/cm², between about 0.25 g/cm² and about 0.35 g/cm² between about 0.35 g/cm² and about 0.45 g/cm², or between about 0.45 g/cm² and about 0.55 g/cm².

(271) According to some exemplary embodiments of a golf club head described herein, the head comprises a skirt with a thickness less than about 0.8 mm, and the head skirt areal weight is less than about 0.41 g/cm² over at least about 50% of the surface area of the skirt. In specific embodiments, the skirt areal weight is between about 0.15 g/cm² and about 0.24 g/cm², between about 0.24 g/cm² and about 0.33 g/cm² or between about 0.33 g/cm² and about 0.41 g/cm².

(272) Some of the exemplary golf club heads described herein can be configured to have a constraint defined as the moment of inertia about the golf club head CG x-axis (I_{xx}) multiplied by the total movable weight mass. According to some embodiments, the second constraint is between about 1.4 kg.sup.2.Math.mm.sup.2 and about 40 kg.sup.2.Math.mm.sup.2. In certain embodiments, the second constraint is between about 1.4 kg.sup.2.Math.mm.sup.2 and about 2.0 kg.sup.2.Math.mm.sup.2, between about 2.0 kg.sup.2.Math.mm.sup.2 and about 10 kg.sup.2.Math.mm.sup.2 or between about 10 kg.sup.2.Math.mm.sup.2 and about 40 kg.sup.2.Math.mm.sup.2.

(273) Some of the exemplary golf club heads described herein can be configured to have another constraint defined as the moment of inertia about the golf club head CG z-axis (I_{zz}) multiplied by the total movable weight mass. According to some embodiments, the fourth constraint is between about 2.5

kg.sup.2.Math.mm.sup.2 and about 72 kg.sup.2.Math.mm.sup.2. In certain embodiments, the fourth constraint is between about 2.5 kg.sup.2.Math.mm.sup.2 and about 3.6 kg.sup.2.Math.mm.sup.2 between about 3.6 kg.sup.2.Math.mm.sup.2 and about 18 kg.sup.2.Math.mm.sup.2 or between about 18 kg.sup.2.Math.mm.sup.2 and about 72 kg.sup.2.Math.mm.sup.2.

(274) In some embodiments described herein, a moment of inertia about a golf club head CG z-axis (Izz) can be greater than about 190 kg.Math.mm.sup.2. More specifically, the moment of inertia about head CG z-axis **203** can be between about 190 kg.Math.mm.sup.2 and about 300 kg.Math.mm.sup.2, between about 300 kg.Math.mm.sup.2 and about 350 kg.Math.mm.sup.2, between about 350 kg.Math.mm.sup.2 and about 400 kg.Math.mm.sup.2, between about 400 kg.Math.mm.sup.2 and about 450 kg.Math.mm.sup.2, between about 450 kg.Math.mm.sup.2 and about 500 kg.Math.mm.sup.2 or greater than about 500 kg.Math.mm.sup.2.

(275) In some embodiments described herein, a moment of inertia about a golf club head CG x-axis (Ixx) can be greater than about 80 kg.Math.mm.sup.2. More specifically, the moment of inertia about the head CG x-axis can be between about 80 kg.Math.mm.sup.2 and about 180 kg.Math.mm.sup.2, between about 180 kg.Math.mm.sup.2 and about 250 kg.Math.mm.sup.2 between about 250 kg.Math.mm.sup.2 and about 300 kg.Math.mm.sup.2, between about 300 kg.Math.mm.sup.2 and about 350 kg.Math.mm.sup.2, between about 350 kg.Math.mm.sup.2 and about 400 kg.Math.mm.sup.2, or greater than about 400 kg.Math.mm.sup.2.

(276) Additional disclosure regarding areal weight and calculating values for moments of inertia providing both a movable weight and an adjustable shaft assembly to a golf club head can be found in U.S. Pat. No. 7,963,861, the entire contents of which are incorporated by reference.

(277) Additional Embodiments with Slidably Respositional Weights

(278) FIG. **32** shows a bottom view of an exemplary golf club head **1500** that has a forward/rearward sliding weight with a stationary weight fastener on the sole of the club head, similar to the club heads **1200** and **1300**. The club head **1500** can have any of the properties and features described herein with regard to the club heads **1200** and **1300**.

(279) The club head **1500** can comprise a body **1502** having a sole portion **1503**, a forward sole slot **1514** just behind the bottom of the face, a hosel **1562** and a hosel recess **1566** for fastening a shaft to the club head. The body **1502** can also include recessed sole portions **1596**, **1597** at the heel and toe sides of the sole.

(280) The club head **1500** can comprise a weight **1540** that has a slot **1554** and a stationary fastener **1550** that extends through the slot and fastens to the body **1502**. The weight can be relatively large like the weight **1240**, having a width **1543** similar to the width **1243**. The weight **1540** is positioned along a track **1530** having a surface **1531** that the weight moves along in a forward-rearward direction. The slot **1554** is oriented in the forward-rearward direction and defines the maximum extent the weight **1540** can move. The fastener **1550** contacts the rear end of the slot **1554** (as shown) when the weight is in its forwardmost position, and contacts the front end of the slot when the weight is in its rearwardmost position.

(281) The forward part of the weight **1540** is covered by the sole portion **1503**, while the rearward part of the weight is exposed behind the sole portion. The lateral sides of the weight **1540** can be at least partially covered by rearward portions of the body bordering the track **1530**. A cross-section view of the club head **1500** can look similar to views shown in FIGS. **25** and **27**, though the club head can have differences, such as being larger, being a driver vs a fairway for example. In addition to providing mass distribution adjustability, having the forward part of the weight covered by part of the sole portion can provide club head volume variability, as described with the club heads **1200** and **1300**, and can also provide an aerodynamic benefit over a more exposed sliding weight design.

(282) FIG. **33** shows a bottom view of an exemplary golf club head **1600** that has two laterally sliding weights and a stationary rear weight. The club head **1600** can comprise a body **1602** having a sole portion **1604**, a forward portion **1606**, a rear portion **1608**, a hosel **1610**, a hosel recess **1612**, a forward sole slot **1614**, and a sliding weight track **1620** extending in a heel-toe direction just behind the forward sole slot and hosel recess. The club head **1600** can also comprise a sole insert **1616** that forms a part of the sole between the sole portion **1604** and the rear portion **1608** of the body **1600**. The sole insert **1616** can comprise, for example, a low-density material such as a carbon-fiber composite material, and can be bonded to and enclose a lower opening in the body **1602**. The club head **1600** can also comprise a stationary rear weight **1618** that is secured to a rear end of the body via fastener **1619**.

(283) The weight track **1620** can include one or more rails, or ledges, **1621** that the weights **1622** engage with and slide along. Each weight **1622** can have its own fastener **1623** that extends through the weight and secures the weight as a desired position along the track. The fasteners **1623** move along the track **1620** with the weights **1622**. In some embodiments, the weights **1622** can comprise two or more pieces that clamp onto the rail **1621** by tightening the fastener **1623**. Each weight can be adjustably positioned independently along the track to

adjust the mass distribution properties of the club head. The track **1620** and the bottom of the weights **1623** are not covered by any part of the body and are exposed to ground contact, air flow dynamics, etc.

(284) Additional Embodiments with Slotted Sliding Weight and Stationary Fastener

(285) Some club heads can include a weight track with a sliding weight where the fastener screw is stationary relative to the body and the weight has a slot that moves relative to the stationary screw. Such a weight track and slotted weight can be oriented in a front-rear direction, a toe-heel direction, along another axis, along multiple axes, and/or along a curved path.

(286) Such embodiments can solve at least the following problems. There is significant mass allocated to the structure in sliding weight tracks where the fastener moves with the weight (such as the club head **1600**), which mass can be located very close to the front/back CG of the head. The additional mass can be partly in the form of one or more rails or ledges that the weights ride along and clamp onto. Because this additional mass is close the CG, the mass does not affect improvement of the inertial properties of the head as much as if the same mass was located farther away from the CG. Embodiments with a stationary fastening screw and a slotted weight that moves relative to the screw can also be simpler from a casting perspective and more mass efficient in that such embodiments can eliminate the rails that the weight rides along. The weight itself can also be simplified to just one piece, as opposed to two pieces that clamp together. There can also be no need to include a nut to engage the fastener shaft, which can also reduce mass and complexity. In addition, embodiments with a stationary fastening screw and a slotted weight that moves relative to the screw can also allow for more discretionary mass to be put into the weight, and as such the length of the track can be shortened while providing equivalent adjustability. For example, with a heel-toe oriented weight track, such an embodiment can maintain the same CGx adjustment range compared to a longer sliding weight track with clamping rails (like the club head **1600**) because the weight is heavier despite the shorter track length. Because the track is shorter, it can also be positioned further forward. With the mass of the track infrastructure and the mass of the weight moved forward, the CG of the weight track system can be further away from the overall CG of the club head. This can improve (increase) inertia properties of the head.

(287) FIG. **34** shows an exemplary club head **1700** that includes a heel-toe weight track with a slotted weight that moves relative to a stationary weight fastener. The club head **1700** can comprise a body **1702**, a face portion **1704**, a hosel **1706**, head-shaft coupler **1708**, rear portion **1710**, sole insert **1712** coupled to the body and having a lower density than the body, stationary rear weight **1716** with fastener **1718**, hosel recess **1720**, and front sole slot **1722**, similar to the club head **1600**. The club head also includes a crown, which can include a crown insert coupled to the body, which crown insert can comprise a composite material or other material that is less dense than the body. The club head **1700** can also include a heel-toe weight track **1724** positioned behind the slot **1722** and hosel recess **1720**, with a slotted adjustable weight **1726** secured by stationary fastener **1728**. The weights can have a greater density than the body. The weight **1726** is adjustably positionable in a heel-toe direction along the track **1724**. A slot **1730** in the weight **1726** rides along the fastener **1728** and defines a maximum extent the weight can move in the heel-toe directions.

(288) An overhang portion **1732** of the sole can cover a heel end portion of the track **1724**. A heel end portion **1734** of the weight **1726** can be covered by the overhang portion **1732**, at least when the weight is in a heelward position along the track **1724**. In some embodiments, at least a portion of the weight **1726** is always covered by the overhang portion **1732** no matter where the weight is along the track. In some embodiments, up to half of the weight can be covered by the overhang when the weight is in the heelward position. The covered part of the weight can telescope within the body, resulting in variation of the total volume of the club head, as described with reference to the club heads **1200** and **1300**. The overhang portion **1732** can also create a stable sit point for contacting the ground instead of the weight when the club head is in the normal address position. The overhang portion **1732** can also help improve aerodynamics during a swing, such as by reducing drag associated with a large open cavity and weight protuberances.

(289) FIG. **35** shows another exemplary club head **1800** that includes a heel-toe weight track with a slotted weight that moves relative to a stationary weight fastener. The club head **1800** can comprise a body **1802** having a forward portion **1804**, a hosel **1806** with head-shaft coupler **1808**, a rear portion **1810**, a hosel recess **1820**, and a front sole slot **1822**, as well as a sole insert **1812** with raised ridges **1814** coupled to the body and having a lower density than the body, and a stationary swappable rear weight **1816** with rear weight fastener **1818**, similar to the club heads **1600** and **1700**. The weights can have a greater density than the body.

(290) The rear portion **1810** of the body can, in some embodiments, comprise a separately formed rear ring portion that is attached to the front body portion **1802** at the heel and toe sides, and the rear ring can be formed of a different material (e.g., polymeric material, aluminum, or other lower density material) than the front body portion (e.g., titanium). The rear portion **1810** can include a rear recess and fastener port for receiving the

swappable rear weight **1816** via rear weight fastener **1818**. The rear weight **1816** can be swapped with alternative rear weights have different masses (and/or different materials) to adjust the mass characteristics of the club head. More information regarding the construction of club heads, in particular the front body portions and rear ring portions, as well as crown and sole inserts and weight tracks and weight members, can be found in U.S. Pub. No. 2021/0113896 published Apr. 22, 2021, which is incorporated by reference herein in its entirety.

(291) An exemplary front body portion **1802** is shown in FIG. **36**, which can be a cast component. As shown in FIG. **36**, the front body portion **1802** can include a toe connector **1870** and a heel connector **1872** that can engage with corresponding connection portion on the rear (ring) portion **1810** to secure the two parts together. The front body portion **1802** and the rear portion **1810** can each include a portion of an annular recessed ledge **1874** to which the sole insert **1812** is attached, closing a lower opening of the body. As shown in FIG. **36**, the recessed ledge **1874** can extend around the heel side and part of the front side of the weight track **1824** to accommodate a portion of the sole insert (e.g., the overhang portion **1832** discussed herein) that covers part of the weight track and weight member.

(292) The club head **1800** also includes a crown, which can include a crown insert coupled to the body. The front body portion **1802** and rear portion **1810** can each include portions of an annular crown ledge that extends around an upper opening, and the crown insert can attach to the crown ledge and close the upper opening (similar to the crown structures shown in FIGS. **1B**, **3**, **10**, **11**, **15**, **23B**, **25**, and **27**). The crown insert can comprise a composite material or other material that is less dense than the body. The sole insert **1812** can also comprise a composite material or other material that is less dense than the body. For example, in some embodiments, at least a portion of the body **1802** is formed of a titanium alloy, the adjustable weight member **1826** is formed from a material having a density no less than 7.8 g/cc, at least a portion of the crown (e.g., the crown insert) is formed of a material having a density of no more than 2 g/cc, and/or at least a portion of the sole (e.g., the sole insert) is formed of a material having a density of no more than 2 g/cc.

(293) The club head **1800** can also include a heel-toe oriented weight track **1824** positioned behind the front sole slot **1822**, with a slotted adjustable weight **1826** secured by stationary fastener **1828**. As shown in FIG. **36**, the weight track **1824** can have a generally trapezoidal shape. The weight member **1826** can also have a generally trapezoidal shape. The weight member **1826** is adjustably positionable in a heel-toe direction along the track **1824**. The weight track and weight member can also be slightly arcuate such that the weight member moves along a slightly curved path. A slot **1830** in the weight **1826** interfaces with the fastener **1828** and the heel-toe length of the slot **1830** can define a maximum extent the weight can move in the heel-toe directions. The slot **1830** in the weight can include recessed ledge around the outer perimeter of the slot the fastener head sits within. The fastener includes a threaded shaft portion that engages with a corresponding threaded port **1829** in the body, as illustrated in FIG. **37**. When the threaded shaft portion is tightened within the port, the fastener head presses against the recessed ledge to secure the weight member against the walls of the track. As shown in FIG. **36**, the track **1824** can also include ridges **1876** or other features that help the weight member engage with the weight track and prevent the weight member from unintentionally moving relative to the weight track when the fastener **1828** is tightened. Such ridges can also serve as indexing/reference features to help adjust the weight to a desired position without having to measure the exact position. Similar ridges and/or corresponding recesses can be included on other walls of the track and/or on contacting surfaces of the weight as well. In some embodiments, the weight track and weight can taper in front-rear width moving from the sole upward (as illustrated in FIG. **37**), such that the front and/or rear walls of the weight are angled and press against the front and rear walls of the track to help “wedge” the weight into the track and better secure the weight within the track when the fastener is tightened. The fastener **1828** and port **1829** can also be angled from vertical, as shown in FIG. **37**.

(294) The mass of the front adjustable weight **1826** may range between 8 grams and 30 grams, preferably 10 grams and 25 grams, and more preferably 15 grams and 23 grams. The swappable rear weight **1816** may range from 8 grams and 30 grams, preferably 10 grams and 25 grams, more preferably 15 grams and 23 grams, and even more preferably 12-18 grams. In some embodiments, the rear weight may weigh more than the front weight in order to provide greater inertia i.e. forgiveness to the golfer. A combined mass of the front weight and the rear weight may range from 30-60 grams, preferably 35-55 grams, or greater than about 35 grams.

(295) In some embodiments, a moment of inertia about the golf club head CG y-axis (I_{yy}) can be greater than about 250 kg.Math.mm.sup.2. More specifically, the moment of inertia about the head CG y-axis can be between 250 kg.Math.mm.sup.2 and 400 kg.Math.mm.sup.2, between about 250 kg.Math.mm.sup.2 and about 350 kg.Math.mm.sup.2, between about 275 kg.Math.mm.sup.2 and about 325 kg.Math.mm.sup.2, between about 300 kg.Math.mm.sup.2 and about 350 kg.Math.mm.sup.2, between about 350 kg.Math.mm.sup.2 and

about 400 kg.Math.mm.sup.2, or greater than about 400 kg.Math.mm.sup.2. In some embodiments described herein, a summation of a moment of inertia about a golf club head CG x-axis (I_{xx}) and a moment of inertia about a golf club head CG z-axis (I_{zz}) can be greater than about 700 kg.Math.mm.sup.2. More specifically, a summation of I_{xx} plus I_{zz} may be between about 700 kg.Math.mm.sup.2 and 1100 kg.Math.mm.sup.2, between about 725 kg.Math.mm.sup.2 and 875 kg.Math.mm.sup.2, between 790 kg.Math.mm.sup.2 and 950 kg.Math.mm.sup.2, between 800 kg.Math.mm.sup.2 and 850 kg.Math.mm.sup.2, or greater than about 800 kg.Math.mm.sup.2.

(296) An overhang portion **1832** of the sole insert **1812** can cover a heel end portion **1836** of the track **1824**. For example, the overhang portion **1832** of the sole insert can cover about 25-50% of the weight track, about 30-40% of the weight track, and/or about 33-37% of the weight track. A heel end portion **1834** of the weight **1826** can also be covered by the overhang portion **1832**, at least when the weight is in a heelward position along the track **1824**. In some embodiments, at least a portion of the weight **1826** is always covered by the overhang portion **1832** no matter where the weight is along the track. In some embodiments, up to half of the weight can be covered by the overhang when the weight is in the heelwardmost position. The overhang portion **1832** can allow space for the fastener **1828** to be inserted through the weigh slot into the fastener port **1829**.

(297) The weight **1826** can be inserted into, and removed from, the track **1824** from the uncovered toe side of the track, when not fastened by the fastener **1828**, by angling the weight into or out of the track and moving the weight in a heel-toe direction generally parallel with the path of the weight track. FIGS. **38A-38C** illustrate how the weight member can be inserted into the weight track, tucked under the overhang portion of the sole insert, and secured with the fastener. The overhang portion of the sole insert can be sized and positioned so that it leaves enough of the toe end of the track uncovered to provide space for the weight member to slide into or out of the track for insertion and removal. The one-piece weight member simplifies these processes compared to multi-piece weight members, such as those that clamp onto rails or ledges of the weight track for fastening. The fastener **1828** can be removed or at least uncoupled from the port **1829** before the weight member is removed from the weight track during removal, and the fastener can be inserted through the slot in the weight member after the weight member is inserted into the track during insertion. FIG. **39** shows an embodiment where the weight member includes a hole or recess on the toe end that can be used to move the weight. A tool, such as a wrench used to tighten/loosen the fastener, can be inserted into the hole/recess in the weight and used to pull or push the weight in either direction along the weight track. This can allow the weight to be moved farther under the overhang and still be retrievable with just a small part of the weight protruding out from under the overhang (the part with the hole/recess). The weight can also include ridges, bumps, or other grip features on the external surface (such as the ridges illustrated in FIG. **39**) to help a user grip and move the weight with fingers.

(298) The covered part of the weight can telescope within the club head under the overhang, resulting in variation of the total water-displaced volume of the club head, as described with reference to the club heads **1200** and **1300**. The overhang portion **1832** can also protect the weight and track from impact and debris and can create a stable sit point for contacting the ground instead of the weight/track when the club head is in the normal address position. The overhang portion **1832** can also help improve aerodynamics during a swing, such as by reducing drag associated with a large open track cavity and weight protuberances.

(299) In some embodiments, in addition to the overhang portion **1832**, the club head **1800** can include trip steps, vortex generators, or similar features forward of the weight track **1824** that help mitigate whistling sounds or other unwanted sounds that can be caused by the weight/track when the club head is traveling at high speed (e.g., during a swing). More information about trip steps, vortex generators, or similar features can be found in U.S. Pub. 2020/0139208, published May 7, 2020, which is incorporated by reference herein in its entirety. As discussed therein, in some embodiments, a surface of the sole may comprise one or more surface features, such as a plurality of vortex generators, which can for example each comprise a “wishbone” shape. These vortex generators can be raised up from the surface of the sole, such as at a height of less than 0.75 mm, such as between 0 and 0.75 mm, or between 0.2 and 0.6 mm, or between 0.3 and 0.5 mm, with a narrow end of the raised portion angled toward the rear portion of the golf club head so as to improve playability properties of the golf club head, such as to reduce “whistling” during a golf swing.

(300) While in the illustrated embodiment, these vortex generators **436** are shown as being positioned on a sole **414**, they may be placed, e.g., on a crown of a golf club head, elsewhere on the sole, or e.g., along a sole panel, along a toe surface, or at other locations on the surface of the golf club head in this or any of the golf club head embodiments illustrated herein, as desired.

(301) Additionally, in club heads like **1700** and **1800**, the weight track can be asymmetric with the track being deeper at the forward part and the weight can similarly be thick in the front and therefore more mass-biased

further forward, as illustrated in FIG. 37. FIG. 37 is a cross-sectional view of the club head **1800** taken along a front-rear vertical plane looking toward, showing the forward sole portion **1851** of the body **1802**, front sole slot **1822** with a plug inserted therein, an intermediate sole portion **1850** between the slot **1822** and the weight track **1824**, a rear sole portion **1852** of the body **1802** behind the weight track, the sole insert **1812** overlapping a rear ledge **1874** of the body **1802**, and a receptacle, or port, **1829** that receives the stationary fastener **1828**. The receptacle **1829** can be threaded and receive a threaded fastener **1828**, for example. The weight track **1824** can be reinforced by internal ribs as shown, such as rib **1884** that extends in a front/rear direction around the inner side of the track. As also shown in FIG. 37, the body **1802** can include a front opening formed in part by an annular ledge **1882** that receives a face insert **1880**, which can comprise a material (e.g., metallic or composite) different from the body and can be attached to the body via adhesive, welds, fasteners, or other methods.

(302) As shown in FIG. 37, the weight track **1824** has a deeper wall **1854** forward of the port **1829** and a shallower wall **1856** rearward of the port. A forward portion **1860** of the weight **1826** is thicker/taller and has more of the total mass of the weight while a rearward portion **1862** of the weight is thinner/shorter and has less of the total mass of the weight. Such an asymmetric weight and track configuration can allow for more extreme weight splitting, which can allow the club head to maintain balance point, maintain delta1, and increase Ixx and Izz compared to the club head **1600** of FIG. 33, as shown in Table 5.

(303) TABLE-US-00005 TABLE 5 Value in Exemplary Golf Club Head Property Club Head 1600 Club Head 1800 CGx (mm) -2.3 -2.9 CGz (mm) -5.28 -5.44 Delta 1 (mm) 22.1 23.2 Delta 2 (mm) 37.3 37.7 Head Mass (g) 201.3 201.9 Ixx (kg * mm.sup.2) 317 335 Iyy (kg * mm.sup.2) 282 286 Izz (kg * mm.sup.2) 459 481 Total Inertia (kg * mm.sup.2) 776 816 BP Projection (mm) 0.7 0.6

(304) In view of the many possible embodiments to which the principles of the disclosed technology may be applied, it should be recognized that the illustrated embodiments are only preferred examples of the technology and should not be taken as limiting the scope of the invention. Rather, the scope of the invention is at least as broad as the full scope of the following claims. We therefore claim as our invention all that comes within the scope and spirit of these claims.

Claims

1. A golf club head comprising: a body defining an interior cavity, a sole defining a bottom portion of the golf club head, a crown defining a top portion of the golf club head, a face defining a forward portion of the golf club head, a rearward portion of the golf club head opposite the face, and a hosel; a weight channel formed in the sole and defining a path along the sole, the path being oriented in a generally heel-toe direction, the weight channel defining a weight channel path axis, wherein a forward portion of the weight channel is covered by an overhang portion of the sole and at least a rearward portion of the weight channel is uncovered; a weight member positioned in the weight channel, the weight member configured to be adjusted to any of a range of selectable positions along the path to adjust mass properties of the golf club head, wherein the weight member comprises a slot that is elongated in the generally heel-toe direction; and a fastener that extends through the slot in the weight member and secures the weight member to the body in any of the selectable positions along the path, wherein when the weight member is in any of the selectable positions the fastener is secured to the body at a same fixed location on the body that is independent of the position of the weight member; wherein the weight member is asymmetric about the weight channel path axis.
2. The golf club head of claim 1, wherein the weight member comprises a first portion forward of the weight channel path axis and a second portion rearward of the weight channel path axis, and the first portion has a greater mass than the second portion.
3. The golf club head of claim 2, wherein the first portion of the weight member is thicker than the second portion of the weight member.
4. The golf club head of claim 3, wherein an upper surface of the weight member tapers from a forward side of the weight member to a rearward side of the weight member.
5. The golf club head of claim 4, wherein a center of mass of the weight member is closer to the forward side of the weight member than to the rearward side of the weight member.
6. The golf club head of claim 2, wherein a majority of the first portion of the weight member is forward of the fastener.
7. The golf club head of claim 1, wherein the golf club head defines a first axis extending in a front-rear direction and passing through the fastener, and the weight member is symmetric about the first axis.
8. The golf club head of claim 7, wherein the golf club head defines a second axis extending in a heel-toe

direction and passing through the fastener, and the weight member is asymmetric about the second axis.

9. The golf club head of claim 1, wherein the weight member is entirely external to the interior cavity of the golf club head.

10. A golf club head comprising: a body defining an interior cavity, a sole defining a bottom portion of the golf club head, a crown defining a top portion of the golf club head, a face defining a forward portion of the golf club head, a rearward portion of the golf club head opposite the face, and a hosel; a weight channel formed in the sole and defining a path along the sole; a weight member positioned in the weight channel, the weight member configured to be adjusted to any of a range of selectable positions along the path to adjust mass properties of the golf club head, wherein the weight member comprises a first end portion, a second end portion, and an elongated slot between the first end portion and the second end portion; and a fastener that extends through the slot in the weight member and secures the weight member to the body in any of the selectable positions along the path, wherein when the weight member is in any of the selectable positions the fastener is secured to the body at a same fixed location on the body that is independent of the position of the weight member; wherein a midpoint of a length of the slot of the weight member is offset from a midpoint of a length of the weight member.

11. The golf club head of claim 10, wherein: the first end portion of the weight member comprises a first end and the second end portion of the weight member comprises a second end; the slot of the weight member comprises a first end and a second end; the weight member comprises a first distance between the first end of the slot and the first end of the weight member; the weight member comprises a second distance between the second end of the slot and the second end of the weight member; and the first distance and the second distance are unequal.

12. The golf club head of claim 11, wherein the first distance between the first end of the weight member and the first end of the slot is greater than the second distance between the second end of the slot and the second end of the weight member.

13. The golf club head of claim 11, wherein the midpoint of the slot of the weight member is closer to the second end of the weight member than to the first end of the weight member.

14. The golf club head of claim 10, wherein: the path of the weight channel is oriented in a generally front-rear direction; the first end portion of the weight member is a front end portion; the second end portion of the weight member is a rear end portion; and the midpoint of the slot of the weight member is closer to the rear end portion of the weight member than to the front end portion of the weight member.

15. The golf club head of claim 14, wherein: the weight member comprises a front end and a rear end; the slot of the weight member comprises a front end and a rear end; the weight member comprises a first distance between the front end of the slot and the front end of the weight member; the weight member comprises a second distance between the rear end of the slot and the rear end of the weight member; and the first distance and the second distance are unequal.

16. The golf club head of claim 15, wherein the first distance between the front end of the weight member and the front end of the slot is greater than the second distance between the rear end of the slot and the rear end of the weight member.

17. The club head of claim 10, wherein: the club head has a center of gravity (CG) which is the origin of a coordinate system having a CG x-axis extending through the CG origin in a toe-to-heel direction, a CG y-axis extending through the CG origin in a front-to-back direction and perpendicular to the CG x-axis, and a CG z-axis extending through the CG origin in a generally vertical direction perpendicular to the CG x-axis, the CG y-axis, and to a ground plane when the club head is in a normal address position; the club head has a volume between 400 cc and 470 cc; the club head has a moment of inertia about the CG x-axis (I_{xx}), a moment of inertia about the CG y-axis (I_{yy}), and a moment of inertia about the CG z-axis (I_{zz}); and wherein a summation $I_{xx}+I_{zz}$ is between 700 kg.Math.mm.sup.2 and 1100 kg.Math.mm.sup.2, and I_{yy} is between 250 kg.Math.mm.sup.2 and 400 kg.Math.mm.sup.2.

18. The club head of claim 17, wherein at least a portion of the crown comprises a composite material, and at least a portion of the sole comprises a composite material.

19. The club head of claim 18, wherein at least a portion of the face comprises a composite material.

20. A golf club head comprising: a body defining an interior cavity, a sole defining a bottom portion of the golf club head, a crown defining a top portion of the golf club head, a face defining a forward portion of the golf club head, a rearward portion of the golf club head opposite the face, and a hosel; a weight member configured to be adjusted to any of a range of selectable positions, wherein the weight member comprises a slot that is elongated; and a fastener that extends through the slot in the weight member and secures the weight member to the body in any of the selectable positions, wherein when the weight member is in any of the selectable

positions the fastener is secured to the body at a same fixed location on the body that is independent of the position of the weight member; wherein the weight member is asymmetric; wherein when the weight member is in at least one of the selectable positions a portion of the golf club head covers at least a portion of the weight member.

21. The golf club head of claim 20, wherein the weight member comprises a first portion forward of the slot and a second portion rearward of the slot, and the first portion has a greater mass than the second portion.

22. The club head of claim 20, wherein: the club head has a center of gravity (CG) which is the origin of a coordinate system having a CG x-axis extending through the CG origin in a toe-to-heel direction, a CG y-axis extending through the CG origin in a front-to-back direction and perpendicular to the CG x-axis, and a CG z-axis extending through the CG origin in a generally vertical direction perpendicular to the CG x-axis, the CG y-axis, and to a ground plane when the club head is in a normal address position; the club head has a volume between 400 cc and 470 cc; the club head has a moment of inertia about the CG x-axis (I_{xx}), a moment of inertia about the CG y-axis (I_{yy}), and a moment of inertia about the CG z-axis (I_{zz}); and wherein a summation $I_{xx}+I_{zz}$ is between $700 \text{ kg} \cdot \text{mm}^2$ and $1100 \text{ kg} \cdot \text{mm}^2$, and I_{yy} is between $250 \text{ kg} \cdot \text{mm}^2$ and $400 \text{ kg} \cdot \text{mm}^2$.

23. The club head of claim 22, wherein at least a portion of the crown comprises a composite material, and at least a portion of the sole comprises a composite material.

24. The club head of claim 23, wherein at least a portion of the face comprises a composite material.
