

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250261382

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

DAS; INDRAJIT et al.

INDUCTOR STRUCTURE INTEGRATED IN SEMICONDUCTOR DEVICE

Abstract

The disclosed subject matter relates generally to an inductor structure integrated in a semiconductor device formed from bonded wafers, in which the semiconductor device has a three-dimensional inductor structure aligned vertically between two integrated circuit (IC) components. The inductor structure has a first metal level and a second metal level, the first metal level being in a different wafer from the second metal level.

Inventors: DAS; INDRAJIT (Bangalore, IN), VANUKURU; VENKATA NARAYANA RAO (Bangalore, IN), KAKARA; HARI KISHORE (Bangalore, IN)

Applicant: GlobalFoundries U.S. Inc. (Malta, NY)

Family ID: 96660441

Appl. No.: 18/442069

Filed: February 14, 2024

Publication Classification

Int. Cl.: H01L23/522 (20060101); H01L25/065 (20230101); H01L29/73 (20060101)

U.S. Cl.:

CPC H10D1/20 (20250101); H01L23/5226 (20130101); H01L25/0657 (20130101); H10D10/00 (20250101); H01L2225/06548 (20130101)

Background/Summary

FIELD OF THE INVENTION

[0001] The disclosed subject matter relates generally to an inductor structure integrated into a semiconductor device. More particularly, the present disclosure relates to a semiconductor device preferably formed from bonded wafers, in which the semiconductor device has a three-dimensional inductor structure aligned vertically between two integrated circuit components.

BACKGROUND

[0002] Inductors are components in an electrical circuit along with resistors, capacitors, and transistors. An inductor may typically have a structure where a conductor is wound many times in a coil, screw, or spiral form. With an increased demand for communication electronic devices, semiconductor devices or integrated circuit (IC) devices may, for example, include voltage-controlled oscillators (VCO), low noise amplifiers (LNA), tuned radio receiver circuits, or power amplifiers (PA). Each of these tuned radio receiver circuits, VCO, LNA, and PA circuits may require inductor components in their circuit designs.

[0003] Furthermore, semiconductor devices and IC devices are typically manufactured on a single semiconductor wafer. The dies of the wafer may be processed and packaged with other semiconductor devices or dies at the wafer level, and various technologies and applications have been developed for wafer level packaging. Integration of multiple semiconductor devices has become a challenge in the field with the need for chips with smaller footprints and a reduction of wasted board space on printed circuit boards.

SUMMARY

[0004] In an aspect of the present disclosure, there is provided a semiconductor device having a first semiconductor layer, a second semiconductor layer, an inductor structure vertically between the first semiconductor layer and the second semiconductor layer, the inductor structure having a first metal level and a second metal level above the first metal level, the first metal level and the second metal level each comprises at least one turn about a vertical axis, a dielectric region vertically between the first and second metal levels of the inductor structure, a first interconnect via in the dielectric region, the first interconnect via has a height, and the first interconnect via electrically contacts the first metal level of the inductor structure, and a second interconnect via in the dielectric region, the second interconnect via directly contacts the first interconnect via, the second interconnect via has a height different from the height of the first interconnect via, and the second interconnect via electrically contacts the second metal level of the inductor structure.

[0005] In another aspect of the present disclosure, there is provided a semiconductor device having a first transistor on a first semiconductor layer, the first transistor has a gate structure, a second transistor on a second semiconductor layer, the second transistor has a gate structure, an inductor structure vertically between the first transistor and the second transistor, the inductor structure having a center region, a first metal level, and a second metal level above the first metal level, the first metal level is electrically connected to the first transistor, the second metal level is electrically connected to the second transistor, the first metal level and the second metal level each comprises at least one turn that spiral about the center region of the inductor structure, in which the gate structure of the first transistor and the gate structure of the second transistor are vertically aligned with the center region of the inductor structure, a dielectric region vertically between the first and second metal levels of the inductor structure, a first interconnect via in the dielectric region, the first interconnect via electrically contacts the first metal level of the inductor structure, and a second interconnect via in the dielectric region, the second interconnect via directly contacts the first interconnect via, and the second interconnect via electrically contacts the second metal level of the inductor structure.

[0006] In yet another aspect of the present disclosure, there is provided a semiconductor device having a first semiconductor die having a first interlayer dielectric level, a first integrated circuit (IC) component in the first semiconductor die, a second semiconductor die vertically above the first

semiconductor die, the second semiconductor die having a second interlayer dielectric level, the second interlayer dielectric level directly contacts the first interlayer dielectric level, and the second interlayer dielectric level has a different thickness from the first interlayer dielectric level, a second IC component in the second semiconductor die, an inductor structure vertically between the first IC component and the second IC component, the inductor structure having a first metal level in the first semiconductor die and a second metal level in the second semiconductor die, the first metal level is electrically connected to the first IC component, and the second metal level is electrically connected to the second IC component, the first metal level and the second metal level each comprises at least one turn about a vertical axis, a first interconnect via in the first interlayer dielectric level, the first interconnect via electrically contacts the first metal level of the inductor structure, and a second interconnect via in the second interlayer dielectric level, the second interconnect via directly contacts the first interconnect via, and the second interconnect via electrically contacts the second metal level of the inductor structure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] The present disclosure may be understood by reference to the following description taken in conjunction with the accompanying drawings.

[0008] For simplicity and clarity of illustration, the drawings illustrate the general manner of construction, and certain descriptions and details of features and techniques may be omitted to avoid unnecessarily obscuring the discussion of the described embodiments of the present disclosure. Additionally, elements in the drawings are not necessarily drawn to scale. For example, the dimensions of some of the elements in the drawings may be exaggerated relative to other elements to help improve understanding of embodiments of the present disclosure. The same reference numerals in different drawings denote the same elements, while similar reference numerals may, but do not necessarily, denote similar elements.

[0009] FIG. 1 is a perspective schematic view of an example of a semiconductor device having an inductor structure vertically between a first IC component and a second IC component.

[0010] FIG. 2A is a cross-sectional view of the example semiconductor device along a vertical plane containing a line AA shown in FIG. 1.

[0011] FIG. 2B is a cross-sectional view of the example semiconductor device along a vertical plane containing a line BB shown in FIG. 1.

[0012] FIG. 3A and FIG. 3B are enlarged cross-sectional views of a first interconnect via electrically contacting a first metal level of the inductor structure and a second interconnect via electrically contacting a second metal level of the inductor structure in the example semiconductor device shown in FIG. 2B.

[0013] FIG. 4 is a top-down view of the first metal level of the inductor structure in the example semiconductor device shown in FIG. 1.

[0014] FIG. 5 is a top-down view of the second metal level of the inductor structure in the example semiconductor device shown in FIG. 1.

DETAILED DESCRIPTION

[0015] Various illustrative embodiments of the present disclosure are described below. The embodiments disclosed herein are exemplary and not intended to be exhaustive or limiting to the present disclosure.

[0016] FIG. 1 illustrates an example of a semiconductor device **100** having an inductor structure **282** vertically between a first IC component **156** and a second IC component **256**. Line AA is a section line along a vertical plane parallel to the YX plane while line BB is a section line along a vertical plane parallel to the YZ plane. Referring to FIG. 1, the semiconductor device **100** may

include a first semiconductor die **102** and a second semiconductor die **202**. The semiconductor device **100** may be formed using a wafer to wafer bonding process (e.g., hybrid bonding or direct bonding), a wafer to die bonding process, a die to wafer bonding process, or a die to die bonding process. The subsequently bonded wafers (or bonded wafer and die) may be diced to form the bonded semiconductor dies **102** and **202**. The first semiconductor die **102** may include the first IC component **156** while the second semiconductor die **202** may include the second IC component **256**. The first IC component **156** may include a first plurality of transistors **106** and the second IC component **256** may include a second plurality of transistors **206**. The pluralities of transistors **106**, **206** may be configured as common source device and common gate device. The IC components **156**, **256** may refer to components in the semiconductor device having circuitry configured for an amplifier (e.g., power amplifier, low noise amplifier, voltage amplifier, transconductance amplifier, etc.). As shown in FIG. **1**, the first plurality of transistors **106** may have at least one transistor connected to the first metal level **140** of the inductor structure **282**. The second plurality of transistors **206** may have at least one transistor connected to the second metal level **142** of the inductor structure **282**.

[0017] Although not shown in the accompanying drawings, it should be noted that the scope of this disclosure also includes examples where the inductor structure **282** includes one or more metal levels in addition to the first and second metal levels **140**, **142** illustrated in FIG. **1**. In other words, the inductor structure **282** may include three or more metal levels. The three or more metal levels may have at least one metal level in the first semiconductor die **102** and at least one metal level in the second semiconductor die **202**. For example, the inductor structure **282** may have three metal levels, the first semiconductor die **102** may include two metal levels of the inductor structure **282** while the second semiconductor die **202** may include one metal level of the inductor structure **282**. In another example, the inductor structure **282** may have four metal levels, the first semiconductor die **102** and the second semiconductor die **102** may each include two metal levels of the inductor structure. The number of metal levels of the inductor structure **282** in the first semiconductor die **102** may be either the same as or different from the number of metal levels of the inductor structure **282** in the second semiconductor die **202**.

[0018] The inductor structure **282** may include a first metal level **140** and a second metal level **142**. The first metal level **140** may be in the first semiconductor die **102** and may be electrically connected to the first IC component **156**, for example, by various interconnect features (as illustrated in subsequent drawings). The second metal level **142** may be in the second semiconductor die **202** and may be electrically connected to the second IC component **256**, for example, by various interconnect features (as illustrated in subsequent drawings). The first and second metal levels **140** and **142** may each include at least one turn about a vertical axis (e.g., Y-axis). The at least one turn in the first and second metal levels **140** and **142** may each include a metal line that extends along a horizontal plane (or a plane that the vertical axis is normal to). As used herein, the term “turn” in the metal levels **140**, **142** of the inductor structure **282** may refer to a metal line, or a part thereof, that makes at least one bend around the vertical axis. The first IC component **156**, the second IC component **256**, the first metal level **140** of the inductor structure **282**, and the second metal level **142** of the inductor structure **282** may be aligned vertically along the vertical axis. The first semiconductor die **102** may include a first interconnect via **152**. The first interconnect via **152** may electrically contact or directly contact the first metal level **140**. The second semiconductor die **202** may include a second interconnect via **252**. The second interconnect via **252** may electrically contact or directly contact the second metal level **142**. The second interconnect via **252** may have a different height from the first interconnect via **152**. The second interconnect via **252** may directly contact the first interconnect via **152**.

[0019] Referring to FIG. **2A** and FIG. **2B**, the semiconductor device **100** may include a first semiconductor layer **104**, a second semiconductor layer **204**, and an inductor structure **282** vertically between the first semiconductor layer **104** and the second semiconductor layer **204**. A first

transistor **106** may be formed in the first IC component described in FIG. 1 and a second transistor **206** may be formed in the second IC component described in FIG. 1. As described in FIG. 1, the first transistor **106** may be configured as a common source transistor while the second transistor **206** may be configured as a common gate transistor, or alternatively, the first transistor **106** may be configured as a common gate transistor while the second transistor **206** may be configured as a common source transistor. It should be noted that other device structures may be formed in the respective IC components described in FIG. 1. Examples of other device structures that can be used include, but are not limited to, memory structures (e.g., resistive random memory structures, magnetic random memory structures, etc.), capacitors, or resistors.

[0020] As shown in FIG. 2A and FIG. 2B, the first transistor **106** may be formed on the first semiconductor layer **104** in the first semiconductor die **102** and the second transistor **206** may be formed on the second semiconductor layer **204** in the second semiconductor die **202**. The inductor structure **282** may be positioned vertically between the first transistor **106** and the second transistor **206**. In some embodiments, the first semiconductor die **102** may have a first substrate **103** and the second semiconductor die **202** may have a second substrate **203**. Prior to the bonding of the first semiconductor die **102** and the second semiconductor die **202**, the second semiconductor die **202** may be in an orientation where the second substrate **203** is below the second transistor **206**. As shown in FIG. 2A and FIG. 2B, the second semiconductor die **202** may be flipped or oriented in a manner such that the second substrate **203** is above the second transistor **206**. In some embodiments, the first semiconductor layer **104** may be formed over the first substrate **103** in the first semiconductor die **102** and the second semiconductor layer **204** may be formed over the second substrate **203** in the second semiconductor die **202** (before orienting the second semiconductor die **202** in the manner illustrated in FIG. 2A and FIG. 2B). In other embodiments (not shown), the second semiconductor die **202** may not have a second substrate **203** and the second semiconductor layer **204** may be formed over an insulating layer (e.g., a buried oxide layer). Exemplary types of transistors for the first and second transistors **106**, **206** may include field effect transistors, bipolar junction transistors, heterojunction bipolar transistors, etc.

[0021] Each of the first and second transistors **106**, **206** may have input/output regions **108**, **110**, **208**, **210** (e.g., source/drain or emitter/collector) formed in the respective semiconductor layers **104**, **204** and a control structure **112**, **212** (e.g., base or gate) formed over the respective semiconductor layers **104**, **204** and being laterally between the respective input/output regions **108**, **110**, **208**, **210**. In some embodiments, the first transistor **106** may have source/drain regions **108**, **110** and a gate structure **112**. The second transistor **206** may have source/drain regions **208**, **210** and a gate structure **212**. In other embodiments (not shown), the first transistor **106** may be a field effect transistor while the second transistor **206** may be a heterojunction bipolar transistor.

[0022] The first semiconductor die **102** may have an interconnection region **144** formed above the first semiconductor layer **104**. Likewise, the second semiconductor die **202** may have an interconnection region **244** formed above the second semiconductor layer **204** (before orienting the second semiconductor die **202** in the manner illustrated in FIG. 2A and FIG. 2B). The interconnection regions **144**, **244** may each include one or more interconnection levels formed by a BEOL processing of an integrated circuit (IC) chip. For example, an “n” number of interconnection levels in either of the interconnection regions **144**, **244** may be formed in the semiconductor device. The number of interconnection levels may depend on, for example, design requirements or the process involved. As shown in FIG. 2A and FIG. 2B, the interconnection regions **144**, **244** may include various interconnect structures. In an implementation, the interconnection region **144** in the first semiconductor die **102** may include contact structures **130**, **131**, **132**, conductive lines **114**, **116**, **118**, **120**, **122**, and via structures **133**, **134**, **135**. The interconnection region **144** in the second semiconductor die **202** may include contact structures **230**, **231**, **232**, conductive lines **214**, **216**, **218**, **220**, **222**, and via structures **233**, **234**, **235**.

[0023] The contact structures **130**, **131**, **230**, **231** may contact the input/output regions **108**, **110** of

the respective first and second transistors **106**, **206** and provide electrical connection to conductive lines **114**, **116**, **214**, **216**. The contact structures **132**, **232** may contact the respective control structures **112**, **212** and provide an electrical connection to conductive lines **122**, **222**. The conductive lines **114**, **116**, **118**, **120**, **122**, **214**, **216**, **218**, **220**, **222** may provide routing or wiring of electrical signals to/from other device components in the semiconductor device **100**. Conductive lines **114**, **116** may be located in a different interconnection level from conductive lines **118**, **120**. Conductive lines **214**, **216** may be located in a different interconnection level from conductive lines **218**, **220**. The via structures **133**, **134**, **233**, **234** may provide electrical connections between the conductive lines in the different interconnection levels within the interconnection regions **144**, **244** (e.g., between conductive lines **118**, **120** and conductive lines **114**, **116**).

[0024] The inductor structure **282** may have a first metal level **140** and a second metal level **142** above the first metal level **140**. The first metal level **140** may be electrically connected to the first transistor **106**. As shown in FIG. 2A and FIG. 2B, an example of the electrical connection between the first metal level **140** and the first transistor **106** may be achieved, for example, by having the via structure **135** contact the first metal level **140** and an interconnect structure in the interconnection region **144**, for example, the conductive line **118**, which is in turn electrically connected to one of the input/output region **108** of the first transistor through the other interconnect structures in the interconnection region **144**, as described herein. Similarly, the second metal level **142** may be electrically connected to the second transistor **206**, for example, by having the via structure **235** contact the second metal level **142** and an interconnect structure in the interconnection region **244**, for example, the conductive line **220**. The conductive line **220** may be electrically connected to one of the input/output regions **210** of the second transistor **206** through the other interconnect structures in the interconnection region **244**, as described herein.

[0025] A dielectric region **280** may be formed vertically between the first metal level **140** of the inductor structure **282** and the second metal level **142** of the inductor structure **282**. The dielectric region **280** may include a first interlayer dielectric level **148** and a second interlayer dielectric level **248** directly on the first interlayer dielectric level **148**. The first interlayer dielectric level **148** may have a thickness **148t** defined as a vertical distance between its uppermost surface and its lowermost surface. The second interlayer dielectric level **248** may have a thickness **248t** defined as a vertical distance between its uppermost surface and its lowermost surface. The thickness **148t** of the first interlayer dielectric level **148** may be different from the thickness **248t** of the second interlayer dielectric level **248**. The interlayer dielectric levels **148**, **248** may include, but are not limited to, silicon dioxide, tetraethyl orthosilicate (TEOS), or a material having a chemical composition of $\text{Si.sub.xCO.sub.yH.sub.z}$, wherein x, y, and z are in stoichiometric ratio. The first interlayer dielectric level **148** may be bonded to the second interlayer dielectric level **248**. A bonding interface **150** may be formed vertically between the first interlayer dielectric level **148** and the second interlayer dielectric level **248**. The bonding interface **150** may have covalent bonds between the material in the first interlayer dielectric level **148** and the material in the second interlayer dielectric level **248**.

[0026] As shown in FIG. 2B, the first metal level **140** of the inductor structure **282** may be electrically connected to the second metal level **142** of the inductor structure **282** by a first interconnect via **152** and a second interconnect via **252**. The second interconnect via **252** may directly contact the first interconnect via **152**. The first interconnect via **152** may be bonded to the second interconnect via **252**. The contacting surfaces between the first interconnect via **152** and the second interconnect via **252** may have metallic bonding. The interconnect vias **152**, **252** may be arranged vertically between the first metal level **140** and the second metal level **142**. The first interconnect via **152** may directly contact the first metal level **140** while the second interconnect via **252** may directly contact the second metal level **142**. The interconnect vias **152**, **252** may be formed in the dielectric region **280**. For example, the first interconnect via **152** may be formed in the first interlayer dielectric level **148** while the second interconnect via **252** may be formed in the

second interlayer dielectric level **248**. The first interconnect via **152** may have a height **152t** defined as a vertical distance between its uppermost surface and its lowermost surface. The second interconnect via **252** may have a height **252t** defined as a vertical distance between its uppermost surface and its lowermost surface. The height **152t** of the first interconnect via **152** may be different from the height **252t** of the second interconnect via **252**.

[0027] Advantageously, the difference in the thicknesses **148t**, **248t** of the first and second interlayer dielectric levels **148**, **248** or the difference in the heights **152t**, **252t** of the interconnect vias **152**, **252** can enable the control of an inductance parameter between the first metal level **140** of the inductor structure **282** and the second metal level **142** of the inductor structure **282** whilst allowing flexibility in the manufacture of two semiconductor wafers or dies prior to the bonding of the two wafers or dies. For example, the first interlayer dielectric level **148** and the first interconnect via **152** can be formed in a first wafer (or die) while the second interlayer dielectric level **248** and the second interconnect via **252** can be formed in a second wafer (or die), and the respective thickness of the first and second interlayer dielectric levels can be controlled and adjusted in the two separate wafers to correspond with a desired inductance value before directly bonding the first wafer with the second wafer (or the first die with the second die).

[0028] Also advantageously, by directly contacting the first and second interconnect vias **152**, **252** with each other and directly contacting the interconnect vias **152**, **252** with the respective first and second metal levels **140**, **142** of the inductor structure **282**, the inductance between the first metal level and the second metal level can be controlled by only the heights **152t**, **252t** of the interconnect vias **152**, **252** and the thicknesses **148t**, **248t** of the interlayer dielectric levels **148**, **248**.

[0029] As shown in FIG. 2B, a first plurality of transistors **106** may be formed on the first semiconductor layer **104**. Each transistor **106** in the first plurality of transistors has a gate structure **112**. The gate structure of each transistor **106** may be connected to the same conductive line **122**. For example, a contact structure **132** may be formed on the gate structure **112** of each transistor **106** in the first plurality of transistors. The contact structure **132** may contact both the gate structure **112** and the conductive line **122**.

[0030] FIG. 3A and FIG. 3B illustrate enlarged cross-sectional views of a region **158** demarcated by broken lines shown in FIG. 2B. Referring to FIG. 3A and FIG. 3B, the first interconnect via **152** may be formed with sidewalls **152a** and the second interconnect via **252** may be formed with sidewalls **252a**. In the example shown in FIG. 3A, the sidewalls **152a** of the first interconnect via **152** may be horizontally offset relative to the sidewalls **252a** of the second interconnect via **252** by an offset displacement **1540**. Alternatively, in the example shown in FIG. 3B, the sidewalls **152a** of the first interconnect via **152** may be aligned vertically with the sidewalls **252a** of the second interconnect via **252** (i.e., there is no horizontal offset between the sidewalls **152a**, **252a**).

[0031] FIG. 4 and FIG. 5 illustrate the top down views of the first metal level **140** of the inductor structure **282** and the second metal level **142** of the inductor structure **282**, respectively. The view in FIG. 2A corresponds to a cross-section taken along the line AA in FIG. 4 and FIG. 5 and the view in FIG. 2B corresponds to a cross-section taken along the line BB in FIG. 4 and FIG. 5.

[0032] Referring to FIG. 4 and FIG. 5 together with FIG. 2A and FIG. 2B, the inductor structure **282** may have a center region **154**. As described herein, the first metal level **140** may include turns **140a**, **140b** and the second metal level **142** may include turns **142a**, **142b**. The turns **140a**, **140b** in the first metal level **140** and the turns **142a**, **142b** in the second metal level **142** may spiral about the center region **154**. The turns **140a**, **140b** in the first metal level **140** and the turns **142a**, **142b** in the second metal level **142** may be concentric to the center region **154**. The turns **140a**, **140b** in the first metal level **140** and the turns **142a**, **142b** in the second metal level **142** may provide spiral paths for which electrical current may flow.

[0033] The first metal level **140** may have an innermost end **140y** and an outermost end **140x**, in which the innermost end **140y** may be closer to the center region **154** as compared to the outermost end **140x**. The turns **140a**, **140b** in the first metal level **140** may spiral towards the center region

154 from the outermost end **140x** to the innermost end **140y**. The via structure **135** may contact the first metal level **140** at the outermost end **140x** while the first interconnect via **152** may contact the first metal level **140** at the innermost end **140y**. Similarly, the second metal level **142** may have an innermost end **142y** and an outermost end **142x**, in which the innermost end **142y** may be closer to the center region **154** as compared to the outermost end **142x**. The turns **142a**, **142b** in the second metal level **142** may spiral towards the center region **154** from the outermost end **142x** to the innermost end **142y**. The via structure **235** may contact the second metal level **142** at the outermost end **142x** while the second interconnect via **252** may contact the second metal level **142** at the innermost end **142y**.

[0034] As shown, the turns **140a**, **140b** in the first metal level **140** and the turns **142a**, **142b** in the second metal level **142** may form a rectangular shape. Apart from the shape and architecture shown in FIG. 4 and FIG. 5, other shapes and architecture of the metal levels **140**, **142** are contemplated. For example, the metal levels **140**, **142** may have a polygonal shape with “x” number of sides, in which “x” is an integer. For example, where “x” is zero, the metal levels **140**, **142** may have an elliptical, circular, or oval shape. Where “x” is eight, the metal levels **140**, **142** may have an octagonal shape. Although not shown, the number of sides of the first metal level **140**, **142** may be different from the number of sides of the second metal level **142**.

[0035] As described herein, the first transistor **106**, the second transistor **206**, the first metal level **140** of the inductor structure **282**, and the second metal level **142** of the inductor structure **282** may be arranged in a vertical stack configuration. In some embodiments, the gate structure **112** of the first transistor **106** may be vertically aligned above the gate structure **212** of the second transistor **206**. The first metal level **140** of the inductor structure **282** may be vertically aligned above the second metal level **142** of the inductor structure **282** such that there is overlap between the turns **140a**, **140b** in the first metal level **140** and the turns **142a**, **142b** in the second metal level **142**. The gate structure **112** of the first transistor **106** and the gate structure **212** of the second transistor **206** may be vertically aligned with the center region **154** of the inductor structure **282**. Advantageously, the vertical alignment of the gate structures **112**, **212** with the center region **154** of the inductor structure **282** may reduce the footprint or area occupied by the semiconductor device **100** on a printed circuit board as compared to having the inductor structure positioned laterally between two transistors.

[0036] The inductor structure **282** may be constructed using various interconnect features to form the turns **140a**, **140b**, **142a**, **142b** in the respective metal levels **140**, **142**. The term “interconnect features” may refer to wiring structures or conductors used in semiconductor devices for enabling transmission of electrical signals between circuitry components within the semiconductor devices. Examples of interconnect features may include, but are not limited to, interconnect vias, interconnect layers, conductive layers, conductive pads, and bond pads. These interconnect features may be formed in a number of ways using a number of different tools. For example, the fabrication of the interconnect features may use at least three building blocks: (i) deposition of material layers over a substrate or a semiconductor chip using deposition techniques, (ii) patterning the deposited material layers to form openings or trenches in the deposited layers using patterning techniques, and (iii) depositing conductive materials into the openings or trenches using deposition techniques.

[0037] As used herein, “deposition techniques” refer to the process of applying a material over another material (or the substrate). Exemplary techniques for deposition include, but are not limited to, spin-on coating, sputtering, chemical vapor deposition (CVD), physical vapor deposition (PVD), molecular beam deposition (MBD), pulsed laser deposition (PLD), liquid source misted chemical deposition (LSMCD), atomic layer deposition (ALD).

[0038] Additionally, “patterning techniques” include deposition of material or photoresist, patterning, exposure, development, etching, cleaning, and/or removal of the material or photoresist as required in forming a described pattern, structure, or opening. Examples of techniques for patterning include, but are not limited to, wet etch lithographic processes, dry etch lithographic

processes, or direct patterning processes. Such techniques may use mask sets and mask layers. [0039] With reference to FIG. 2A and FIG. 2B, an example of forming the semiconductor device **100** may include forming the conductive lines **114, 116, 118, 120** and the interconnection region **144** in a first wafer, and forming the conductive lines **214, 216, 218, 220** and the interconnection region **244** in a second wafer. Formation of the conductive lines **114, 116, 118, 120, 214, 216, 218, 220** and the interconnection regions **144, 244** may utilize the at least three building blocks, as described above.

[0040] A dielectric layer **146** may be formed on the interconnection region **144** in the first wafer and a dielectric layer **246** may be formed on the interconnection region **244** in the second wafer. Deposition techniques described herein may be used to form the dielectric layers **146, 246**. The dielectric layers **146, 246** may be patterned using patterning techniques to form openings or trenches in the dielectric layers **146, 246**, and metals may be deposited into the openings or trenches using deposition techniques to form the first metal level **140** and the second metal level **142**.

[0041] The first interlayer dielectric level **148** may be formed in the first wafer by depositing a material on the dielectric layer **146** and the first metal level **140**. Likewise, the second interlayer dielectric level **248** may be formed in the second wafer by depositing a material on the dielectric layer **246** and the second metal level **142**. The first and second interlayer dielectric levels **148, 248** may be patterned to form openings. The openings in the respective first and second wafers may be subsequently filled using deposition techniques to form the first interconnect via **152** and the second interconnect via **252**.

[0042] The via structures **133, 134, 135, 233, 234, 235**, the contact structures **130, 131, 132, 230, 231, 232**, the conductive lines **114, 116, 118, 120, 122, 214, 216, 218, 220, 222**, and the at least one turn in the respective first and second metal levels **140, 142** may include a metal, such as tantalum (Ta), tungsten (W), ruthenium (Ru), cobalt (Co), copper (Cu), titanium (Ti), nickel (Ni), platinum (Pt), aluminum (Al), or an alloy thereof. Other suitable types of metal, alloys, or conductive materials may also be useful. The via structures **133-135, 233-235**, the contact structures **130-132, 230-232**, the conductive lines **114, 116, 118, 120, 122, 214, 216, 218, 220, 222**, and the at least one turn in the respective first and second metal levels **140, 142** may be formed using a damascene process (e.g., a single damascene or a dual damascene). Other techniques, such as reactive ion etch (RIE) may also be used in the formation of the via structures **133-135, 233-235**, the contact structures **130-132, 230-232**, the conductive lines **114, 116, 118, 120, 122, 214, 216, 218, 220, 222**, and the at least one turn in the respective first and second metal levels **140, 142**.

[0043] The second wafer may be aligned vertically above the first wafer such that the second interconnect via **252** may be aligned vertically above the first interconnect via **152**. The first wafer may be bonded to the second wafer by directly contacting the two wafers such that the first interlayer dielectric level **148** contacts the second interlayer dielectric level **248** and the first interconnect via **152** contacts the second interconnect via **252**. An anneal process or heat treatment process may be applied to the two wafers that are in contact with each other to bond the first and second interlayer dielectric levels **148, 248** together and the first and second interconnect vias **152, 252** together. As mentioned above, the bonded wafer may be diced to form the semiconductor device **100**.

[0044] In embodiments where the inductor structure has more than one metal level in the first semiconductor die **102**, the second semiconductor die **202**, or both semiconductor dies **102, 202**, the conductive lines **114, 116, 118, 120** in the interconnection region **144** of the first semiconductor die **102** and the conductive lines **214, 216, 218, 220** in the interconnection region **244** of the second semiconductor die **202** may be used for constructing metal levels of the inductor structure **282**, as well as structural features for the transmission of electrical signals between the transistors **106, 206** and other circuitry components in the semiconductor device **100**.

[0045] Throughout this disclosure, it is to be understood that if a method is described herein as

involving a series of steps, the order of such steps as presented herein is not necessarily the only order in which such steps may be performed, and certain of the stated steps may possibly be omitted and/or certain other steps not described herein may possibly be added to the method. Furthermore, the terms “comprise”, “include”, “have”, and any variations thereof, are intended to cover a non-exclusive inclusion, such that a process, method, article, or device that comprises a list of elements is not necessarily limited to those elements, but may include other elements not expressly listed or inherent to such process, method, article, or device. Occurrences of the phrase “in an embodiment” herein do not necessarily all refer to the same embodiment.

[0046] The descriptions of the various embodiments of the present disclosure have been presented for purposes of illustration, but are not intended to be exhaustive or limited to the embodiments disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art without departing from the scope and spirit of the described embodiments. The terminology used herein was chosen to best explain the principles of the embodiments, the practical application or technical improvement over technologies found in the marketplace, or to enable others of ordinary skill in the art to understand the embodiments disclosed herein. Furthermore, there is no intention to be bound by any theory presented in the preceding background or the following detailed description. Additionally, the various tasks and processes described herein may be incorporated into a more comprehensive procedure or process having additional functionality not described in detail herein.

[0047] References herein to terms modified by language of approximation, such as “about”, “approximately”, and “substantially”, are not to be limited to the precise value specified. The language of approximation may correspond to the precision of an instrument used to measure the value and, unless otherwise dependent on the precision of the instrument, may indicate $\pm 10\%$ of the stated value(s).

[0048] As will be readily apparent to those skilled in the art upon a complete reading of the present application, the disclosed semiconductor devices and methods of forming the same may be employed in manufacturing a variety of different integrated circuit products, including, but not limited to, radio frequency (RF) modules or applications, FinFET devices, planar transistor devices, CMOS devices, wide bandgap semiconductor devices, etc.

Claims

1. A semiconductor device comprising: a first semiconductor layer; a second semiconductor layer; an inductor structure vertically between the first semiconductor layer and the second semiconductor layer, the inductor structure having a first metal level and a second metal level above the first metal level, the first metal level and the second metal level each comprises at least one turn about a vertical axis; a dielectric region vertically between the first and second metal levels of the inductor structure; a first interconnect via in the dielectric region, the first interconnect via has a height, and the first interconnect via electrically contacts the first metal level of the inductor structure; and a second interconnect via in the dielectric region, the second interconnect via directly contacts the first interconnect via, the second interconnect via has a height different from the height of the first interconnect via, and the second interconnect via electrically contacts the second metal level of the inductor structure.
2. The semiconductor device of claim 1, wherein the dielectric region includes a first interlayer dielectric level and a second interlayer dielectric level directly on the first interlayer dielectric level, the second interlayer dielectric level has a different thickness from the first interlayer dielectric level.
3. The semiconductor device of claim 2, wherein the first interconnect via is in the first interlayer dielectric level and the second interconnect via is in the second interlayer dielectric level.
4. The semiconductor device of claim 3, wherein the first interconnect via has sidewalls, the second

interconnect via has sidewalls, and the sidewalls of the first interconnect via are horizontally offset relative to the sidewalls of the second interconnect via.

5. The semiconductor device of claim 3, wherein the first interconnect via has sidewalls, the second interconnect via has sidewalls, and the sidewalls of the first interconnect via are aligned vertically with the sidewalls of the second interconnect via.

6. The semiconductor device of claim 3, further comprising: a first transistor on the first semiconductor layer, wherein the first metal level of the inductor structure is electrically connected to the first transistor; and a second transistor on the second semiconductor layer, wherein the second metal level of the inductor structure is electrically connected to the second transistor.

7. The semiconductor device of claim 6, further comprising: a first semiconductor die including the first interlayer dielectric level, the first transistor, the first semiconductor layer, the first metal level of the inductor structure, and the first interconnect via; and a second semiconductor die including the second interlayer dielectric level, the second transistor, the second semiconductor layer, the second metal level of the inductor structure, and the second interconnect via.

8. The semiconductor device of claim 7, wherein the first interlayer dielectric level is bonded to the second interlayer dielectric level and the first interconnect via is bonded to the second interconnect via.

9. The semiconductor device of claim 6, wherein the first transistor has a gate structure, the second transistor has a gate structure, and the gate structure of the first transistor is vertically aligned above the gate structure of the second transistor.

10. The semiconductor device of claim 9, wherein the inductor structure has a center region, and wherein the gate structure of the first transistor and the gate structure of the second transistor are vertically aligned with the center region of the inductor structure.

11. A semiconductor device comprising: a first transistor on a first semiconductor layer, the first transistor has a gate structure; a second transistor on a second semiconductor layer, the second transistor has a gate structure; an inductor structure vertically between the first transistor and the second transistor, the inductor structure having a center region, a first metal level, and a second metal level above the first metal level, the first metal level is electrically connected to the first transistor, the second metal level is electrically connected to the second transistor, the first metal level and the second metal level each comprises at least one turn that spiral about the center region of the inductor structure, wherein the gate structure of the first transistor and the gate structure of the second transistor are vertically aligned with the center region of the inductor structure; a dielectric region vertically between the first and second metal levels of the inductor structure; a first interconnect via in the dielectric region, the first interconnect via electrically contacts the first metal level of the inductor structure; and a second interconnect via in the dielectric region, the second interconnect via directly contacts the first interconnect via, and the second interconnect via electrically contacts the second metal level of the inductor structure.

12. A semiconductor device comprising: a first semiconductor die having a first interlayer dielectric level; a first integrated circuit (IC) component in the first semiconductor die; a second semiconductor die vertically above the first semiconductor die, the second semiconductor die having a second interlayer dielectric level, the second interlayer dielectric level directly contacts the first interlayer dielectric level, and the second interlayer dielectric level has a different thickness from the first interlayer dielectric level; a second IC component in the second semiconductor die; an inductor structure vertically between the first IC component and the second IC component, the inductor structure having a first metal level in the first semiconductor die and a second metal level in the second semiconductor die, the first metal level is electrically connected to the first IC component, and the second metal level is electrically connected to the second IC component, the first metal level and the second metal level each comprises at least one turn about a vertical axis; a first interconnect via in the first interlayer dielectric level, the first interconnect via electrically contacts the first metal level of the inductor structure; and a second interconnect via in

- the second interlayer dielectric level, the second interconnect via directly contacts the first interconnect via, and the second interconnect via electrically contacts the second metal level of the inductor structure.
- 13.** The semiconductor device of claim 12, wherein the first interconnect via, the second interconnect via, the first interlayer dielectric level, and the second interlayer dielectric level are vertically between the first metal level of the inductor structure and the second metal level of the inductor structure.
- 14.** The semiconductor device of claim 13, wherein the first interconnect via has sidewalls, the second interconnect via has sidewalls, and the sidewalls of the first interconnect via are horizontally offset relative to the sidewalls of the second interconnect via.
- 15.** The semiconductor device of claim 13, wherein the first interconnect via has sidewalls, the second interconnect via has sidewalls, and the sidewalls of the first interconnect via are aligned vertically with the sidewalls of the second interconnect via.
- 16.** The semiconductor device of claim 12, wherein the inductor structure has a center region, and wherein the at least one turn in the first metal level and the at least one turn in the second metal level spiral about the center region of the inductor structure.
- 17.** The semiconductor device of claim 12, wherein the first IC component includes a first transistor connected to the first metal level of the inductor structure, and the second IC component includes a second transistor connected to the second metal level of the inductor structure.
- 18.** The semiconductor device of claim 17, wherein the first transistor is a field effect transistor and the second transistor is a bipolar junction transistor.
- 19.** The semiconductor device of claim 12, wherein the first IC component, the second IC component, the first metal level of the inductor structure, and the second metal level of the inductor structure are aligned vertically along the vertical axis.
- 20.** The semiconductor device of claim 12, wherein the second interconnect via has a height different from the height of the first interconnect via.
-