

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12392357
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Kitagawa; Masahiro et al.

Rotating device

Abstract

A rotating device includes a shaft, an impeller fixed to the shaft, a motor causing the impeller to rotate, and a casing accommodating the impeller and the motor. The casing includes a suction port and a discharge port for a fluid. The casing and a heat sink are adjacent in a radial direction of the impeller. The heat sink includes a first part adjacent to the discharge port and a second part disposed inside the discharge port. The first part is in contact with a heat pipe. The second part is in contact with the casing in an axial direction of the impeller.

Inventors: Kitagawa; Masahiro (Kitasaku-gun, JP), Higuchi; Yukihiro (Kitasaku-gun, JP)

Applicant: MINEBEA MITSUMI Inc. (Nagano, JP)

Family ID: 1000008764628

Assignee: MINEBEA MITSUMI Inc. (Nagano, JP)

Appl. No.: 18/774006

Filed: July 16, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250027513 A1	Jan. 23, 2025

Foreign Application Priority Data

JP	2023-118364	Jul. 20, 2023
----	-------------	---------------

Publication Classification

Int. Cl.: F04D29/58 (20060101); F04D17/16 (20060101); F04D29/28 (20060101); F04D29/42 (20060101)

U.S. Cl.:

CPC **F04D29/5853** (20130101); **F04D17/16** (20130101); **F04D29/281** (20130101);
F04D29/4226 (20130101);

Field of Classification Search

CPC: F04D (17/16); F04D (25/06); F04D (29/281); F04D (29/4226); F04D (29/5806); F04D (29/5826); F04D (29/5833); F04D (29/5853)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7212404	12/2006	Wang	257/E23.099	H01L 23/427
7679907	12/2009	Kaneko	174/15.1	G06F 1/203
D694199	12/2012	Lin	D13/179	N/A
9025328	12/2014	Chiang	361/679.48	H05K 7/20154
9059146	12/2014	Inoue	N/A	G06F 1/20
9756761	12/2016	Inoue	N/A	H05K 7/20154
11512711	12/2021	Sun	N/A	F04D 17/16
2008/0105410	12/2007	Hwang	165/122	G06F 1/20
2008/0180913	12/2007	Kaneko	N/A	N/A
2011/0005728	12/2010	Hong	165/122	G06F 1/20
2012/0018132	12/2011	Chen	165/104.34	F28D 15/0233
2012/0293958	12/2011	Lee	165/104.26	H05K 7/20336
2014/0102670	12/2013	Tu	165/104.26	H01L 23/427
2014/0182818	12/2013	Wang	165/104.21	G06F 1/20

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2008-187120	12/2007	JP	N/A

Primary Examiner: Wolcott; Brian P

Attorney, Agent or Firm: Chrisman Gallo Tochtrop LLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application claims the benefit of priority to Japanese Patent Application Number 2023-118364 filed on Jul. 20, 2023. The entire contents of the above-identified application are hereby incorporated by reference.

TECHNICAL FIELD

(2) The disclosure relates to a rotating device.

BACKGROUND

(3) Computers sometimes include a housing, a heat generating element mounted in the housing, a cooling fan arranged in the housing, a heat radiating fin disposed in the housing opposed to the

cooling fan, and a heat transfer member thermally connecting the heat spreader fin to the heat generating element (e.g., see JP 2008-187120 A).

SUMMARY

(4) However, the technology described in JP 2008-187120 A has room for improvement in facilitating the manufacturing of the fan (rotating device).

(5) The disclosure has been made in view of the above, and one object of the disclosure is to provide a rotating device easy to manufacture while improving cooling performance.

(6) To solve the above problem and achieve the object, a rotating device according to the disclosure includes a shaft, an impeller fixed to the shaft, a motor causing the impeller to rotate, and a casing accommodating the impeller and the motor. The casing includes a suction port and a discharge port for a fluid. The casing and a heat sink are adjacent in a radial direction of the impeller. The heat sink includes a first part adjacent to the discharge port and a second part disposed inside the discharge port. The first part is in contact with a heat pipe. The second part is in contact with the casing in an axial direction of the impeller.

(7) One aspect of the rotating device according to the disclosure facilitates the manufacturing of the rotating device while improving the cooling performance.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a perspective view illustrating a rotating device according to an embodiment.

(2) FIG. 2 is a cross-sectional view of a part of a main body of the rotating device illustrated in FIG. 1.

(3) FIG. 3 is an exploded perspective view of the main body illustrated in FIG. 2.

(4) FIG. 4 is a perspective view of an impeller provided in the main body illustrated in FIG. 2.

(5) FIG. 5 is a cross-sectional view of the main body illustrated in FIG. 2.

(6) FIG. 6 is a perspective view of a heat sink provided in the main body illustrated in FIG. 2.

DESCRIPTION OF EMBODIMENTS

(7) Embodiments of a fan 1 as a rotating device will be described in detail below based on the drawings. It should be noted that the dimensional relationship of each element and the ratio of each element in the drawings may differ from reality. In some cases, the dimensional relationship and the ratios in the drawings may differ from each other.

Embodiments

(8) FIG. 1 is a perspective view illustrating the rotating device (fan 1) according to an embodiment. FIG. 2 is a partial sectional view of a main body M of the fan 1 illustrated in FIG. 1. FIG. 3 is an exploded perspective view of the main body M illustrated in FIG. 2. FIG. 4 is a perspective view of an impeller 4 provided in the main body M illustrated in FIG. 2. FIG. 5 is a cross-sectional view of the main body M illustrated in FIG. 2. FIG. 6 is a perspective view of a heat sink 6 provided in the main body M illustrated in FIG. 2.

(9) In the description of the fan 1 as the rotating device illustrated in FIG. 1 according to the present embodiment, a direction of a shaft 3 extending to be described below is called an axial direction A, a direction orthogonal to the axial direction A is called a lateral direction X, and a direction orthogonal to the axial direction A and the lateral direction X is called a longitudinal direction Y in order to facilitate understanding of the directions. A direction of the shaft 3 rotating is called a circumferential direction C, and a direction included in the plane orthogonal to the axial direction A and passing through an axis 30 of the shaft 3 and orthogonal to a circumferential direction C is called a radial direction R. In the fan 1 according to the present embodiment, the radial direction R is included in the longitudinal direction Y. Furthermore, in the present embodiment, the axial direction A corresponds to, for example, a vertical direction Z described

below.

(10) The fan **1** illustrated in FIG. **1** is built into a computer, for example, and is used for cooling components provided inside the computer, or the like. The fan **1** according to the present embodiment has a function of cooling a heat generating element **AT2**, such as the central processing unit of the computer. The fan **1** according to the present embodiment also includes the main body **M** and an additional device **AT**.

(11) The main body **M** includes, for example, a casing **2**, the shaft **3** (see FIG. **5**), the impeller **4**, a motor **5** (see FIGS. **4** and **5**), the heat sink **6**, and a heat pipe **7**. The main body **M** according to the present embodiment is integrally formed with the casing **2** incorporating the impeller **4**, and the heat sink **6**.

(12) The casing **2** illustrated in FIG. **2** is configured to have an interior space **2s** formed by, for example, a flat upper casing **21**, a flat lower casing **22**, and an intermediate casing **23** located between the upper casing **21** and the lower casing **22** in the axial direction **A**. The upper casing **21** is disposed at a first face **21H** facing one side in the axial direction **A** of a second part **6122**, as described below.

(13) The casing **2** has an opening **2H** communicating the interior space **2s** with the outside. The casing **2** according to the present embodiment has, for example, two openings **2H**. Among the two openings **2H**, a first opening **2H1** is formed at the upper casing **21**. Also, among the two openings **2H**, a second opening **2H2** is formed by the upper casing **21**, the lower casing **22**, and the intermediate casing **23**.

(14) The first opening **2H1** is a suction port sucking the fluid (air) from the outside into the interior space **2s** by arranging the impeller **4** at the interior space **2s** of the casing **2**. The second opening **2H2** is a discharge port discharging the fluid (air) from the interior space **2s** by arranging the impeller **4** at the interior space **2s** of the casing **2**.

(15) The impeller **4** and the motor **5** (see FIG. **5**) are arranged at the interior space **2s**. That is, the casing **2** accommodates the impeller **4** and the motor **5**.

(16) The shaft **3** illustrated in FIG. **5** is a so-called rotation axis, for example, a metallic member formed in a cylindrical shape extending along the axial direction **A**. The shaft **3** has the axis **30** and is rotatably provided around the axis **30**. In the fan **1** according to the present embodiment, the shaft **3** is rotatably attached to the lower casing **22**.

(17) The impeller **4** is fixed to the shaft **3**. The shaft **3** rotates in the circumferential direction **C** by driving the motor **5** so that a plurality of blades **44** of the impeller **4** are moved along the circumferential direction **C**, respectively, thereby discharging fluid (air) from the second opening **2H2** as a discharge port.

(18) The impeller **4** illustrated in FIG. **4** includes a top face **41**, a side face **42**, a bottom face **43**, the plurality of blades **44**, and a coupling part **45**. The top face **41** is fixed to the shaft **3** and is disposed at an uppermost side in the axial direction **A** in the impeller **4**.

(19) The side face **42** is coupled to the top face **41** and has an outer peripheral surface positioned around the axis **30** of the shaft **3**. The bottom face **43** is disposed at a lowermost side in the axial direction **A** in the impeller **4** and couples the plurality of blades **44** at the lower side.

(20) The plurality of blades **44** are evenly spaced at equal intervals around, for example, the axis **30** of the shaft **3**. That is, the plurality of blades **44** are spaced with respect to the axis **30** in the circumferential direction **C**. The coupling part **45** couples the plurality of blades **44** at the upper side. Then, the impeller **4** discharges fluid (air) from the second opening **2H2** as a discharge port to the heat sink **6** by moving the plurality of blades **44** in the circumferential direction **C**.

(21) The motor **5** illustrated in FIG. **5** is, for example, an electric motor converting electric energy from a power source into a driving force rotating in the circumferential direction **C** of the shaft **3**. The motor **5** is disposed at the interior space **2s** of the casing **2**. The motor **5** is fixed to the casing **2** via a bearing (not illustrated) or the like attached to the shaft **3**.

(22) The heat sink **6** illustrated in FIG. **3** is formed by a plurality of heat spreader plates **61** formed

of, for example, a metal such as copper having high thermal conductivity. The plurality of heat spreader plates **61** include a plurality of first heat spreader plates **611** disposed at both ends in the lateral direction X and a plurality of second heat spreader plates **612** disposed at the center in the lateral direction X. The heat sink **6** is adjacent to the casing **2** in the radial direction R of the impeller **4**.

(23) The plurality of first heat spreader plates **611** are formed having the same shape. The first heat spreader plate **611** is formed by bending both ends in the axial direction A of a punched flat plate. As illustrated in FIG. 6, the first heat spreader plate **611** includes a first heat spreader plate main body **611m** and a pair of first heat spreader plate opposing portions **611o** located at both ends in the axial direction A in the first heat spreader plate main body **611m** and opposed to each other in the axial direction A. As illustrated in FIG. 2, the first heat spreader plate **611** is disposed adjacent to the second opening **2H2** as a discharge port in the longitudinal direction Y.

(24) Additionally, a dimension **L0** in the axial direction A of the first heat spreader plate **611** is the same as a dimension **L1** in the axial direction A of a first part **6121** described below in the second heat spreader plate **612**. Furthermore, the dimension in the longitudinal direction Y of the first heat spreader plate **611** is the same as the dimension in the longitudinal direction Y of the first part **6121** of the second heat spreader plate **612**. In addition, the plurality of first heat spreader plates **611** are arranged at the same intervals in the lateral direction X.

(25) The second heat spreader plate **612** includes, in the longitudinal direction Y, the first part **6121** adjacent to the second opening **2H2** as a discharge port, and the second part **6122** disposed inside the second opening **2H2** as a discharge port. That is, the heat sink **6** according to the present embodiment includes the first part **6121** adjacent to the second opening **2H2** as a discharge port, and the second part **6122** arranged inside the second opening **2H2** as a discharge port. In other words, in the heat sink **6** of the fan **1** according to the present embodiment, the plurality of heat spreader plates **61** are constituted of the first heat spreader plates **611** and the second heat spreader plates **612**. All of the first heat spreader plates **611** are disposed outside the casing **2**, the respective first parts **6121** of all of the second heat spreader plates **612** are arranged outside the casing **2**, and the respective second parts **6122** of all of the second heat spreader plates **612** are disposed inside the casing **2**.

(26) The plurality of second heat spreader plates **612** are formed having the same shape. Each of the second heat spreader plates **612** is formed by bending both ends in the axial direction A of the punched flat plate.

(27) Each of the first parts **6121** illustrated in FIG. 6 includes a first part main body **6121m** and a pair of first part opposing portions **6121o** located at both ends in the axial direction A of the first part main body **6121m** and opposed to each other in the axial direction A.

(28) Each of the second parts **6122** includes a second part main body **6122m** and a pair of second part opposing portions **6122o** located at both ends in the axial direction A of the second part main body **6122m** and opposed to each other in the axial direction A.

(29) A dimension **L2** in the axial direction A of the second part **6122** is smaller than the dimension **L1** in the axial direction A of the first part **6121**. The dimension **L2** in the axial direction A of the second part **6122** is larger than a dimension **L3** in the axial direction A of the plurality of blades **44** (see FIG. 4). In addition, a first step **ST1** (step ST) is formed at a boundary between the first face **21H** facing one side in the axial direction A of the second part **6122** illustrated in FIG. 6 and a first face **11H** facing the one side in the axial direction A of the first part **6121**. A second step **ST2** (step ST) is formed at a boundary between a second face **22H** facing the other side in the axial direction A of the second part **6122** and a second face **12H** facing the other side in the axial direction A of the first part **6121**.

(30) Furthermore, the plurality of second heat spreader plates **612** are arranged at the same intervals in the lateral direction X. In the heat sink **6** according to the present embodiment, each interval in the lateral direction X between the plurality of first heat spreader plates **611** and each interval in the

lateral direction X between the plurality of second heat spreader plates **612** are the same. In other words, in the heat sink **6** according to the present embodiment, the plurality of heat spreader plates **61** are arranged at the same intervals in the lateral direction X. As illustrated in FIG. 3, the plurality of heat spreader plates **61** are arranged such that the plurality of first heat spreader plates **611** and the respective first parts **6121** of the plurality of second heat spreader plates **612** form a row in the lateral direction X.

(31) The heat pipe **7** is in contact with the first part **6121** illustrated in FIG. 2. In the axial direction A of the impeller **4**, the second part **6122** is in contact with the casing **2**.

(32) The first face **21H** facing the one side in the axial direction A of the second part **6122** abuts the upper casing **21**. The second face **22H** facing the other side in the axial direction A of the second part **6122** abuts the lower casing **22**.

(33) Each of the plurality of heat spreader plates **61** is fixed, for example, to a lower face **7HL** of the heat pipe **7**, then the second part **6122** of each of the second heat spreader plates **612** is inserted into the second opening **2H2** of the casing **2**, and both ends in the vertical direction Z of each of the second heat spreader plates **612** are attached to the upper casing **21** and the lower casing **22**.

(34) The heat pipe **7** is formed of, for example, a metal such as copper having high thermal conductivity, and has a function of thermally connecting the heat generating element **AT2**, such as a central processing unit, to the heat sink **6**. The heat pipe **7** is arranged at the first face **11H** facing the one side in the axial direction A of the first part **6121**. On the other hand, as described above, the upper casing **21** in the casing **2** is arranged at the first face **21H** facing the one side in the axial direction A of the second part **6122**. Thus, in the upper face view, the heat pipe **7** is arranged adjacent to the upper casing **21** with the first step **ST1** as a border. In addition, the heat pipe **7** and the upper casing **21** are not opposed in the radial direction R.

(35) An upper face **7HU** in the vertical direction Z of the heat pipe **7** is exposed outside the heat spreader plates **61**, while the lower face **7HL** in the vertical direction Z of the heat pipe **7** is attached to the plurality of heat spreader plates **61**. As illustrated in FIG. 1, the heat pipe **7** according to the present embodiment is formed to extend in the lateral direction X.

(36) The additional device **AT** includes a substrate **AT1**, the heat generating element **AT2** as a central processing unit, and a heat spreader plate **AT3**. The substrate **AT1** is a base placing the heat generating element **AT2** as a central processing unit, and abuts the lower face in the vertical direction Z of the heat generating element **AT2**. The heat spreader plate **AT3** is formed of a metal such as copper having high thermal conductivity, for example, and abuts the upper face in the vertical direction Z of the heat generating element **AT2**.

(37) As described above, the fan **1** according to the present embodiment includes the shaft **3**, the impeller **4** fixed to the shaft **3**, the motor **5** rotating the impeller **4**, and the casing **2** accommodating the impeller **4** and the motor **5**. The casing **2** has the first opening **2H1** as a suction port for a fluid, and the second opening **2H2** as a discharge port. In the radial direction R of the impeller **4**, the casing **2** and the heat sink **6** are adjacent. The heat sink **6** has the first part **6121** adjacent to the discharge port and the second part **6122** arranged inside the discharge port. The heat pipe **7** is in contact with the first part **6121**. In the axial direction A of the impeller **4**, the second part **6122** is in contact with the casing **2**. Thus, a part of the heat sink **6** according to the present embodiment enters into and abuts the casing **2**. As a result, the fan **1** according to the present embodiment can improve cooling performance.

(38) Furthermore, the plurality of first heat spreader plates **611** according to the present embodiment are formed having the same shape. In addition, the plurality of second heat spreader plates **612** according to the present embodiment are formed having the same shape. Thus, the plurality of heat spreader plates **61** according to the present embodiment can be easily manufactured so that the manufacture of the fan **1** can be facilitated.

(39) Further, the impeller **4** according to the present embodiment includes the plurality of blades **44** rotating around the axis **30**. The dimension **L2** in the axial direction A of the second part **6122** is

larger than the dimension L3 in the axial direction A of the plurality of blades 44. Thus, when a large force is applied from the axial direction A at the fan 1 according to the present embodiment, the second part 6122 receives the large force so that the large force applied to the blades 44 of the impeller 4 can be suppressed.

(40) Furthermore, at the fan 1 according to the present embodiment, the dimension L2 in the axial direction A of the second part 6122 is smaller than the dimension L1 in the axial direction A of the first part 6121. In addition, a first step ST1 (step ST) is formed at a boundary between the first face 21H facing one side in the axial direction A of the second part 6122 and a first face 11H facing the one side in the axial direction A of the first part 6121. A second step ST2 (step ST) is formed at a boundary between a second face 22H facing the other side in the axial direction A of the second part 6122 and a second face 12H facing the other side in the axial direction A of the first part 6121.

(41) At the fan 1 according to the present embodiment, the casing 2 includes the upper casing 21 and the lower casing 22. The first face 21H abuts the upper casing 21, and the second face 22H abuts the lower casing 22. Thus, the generation of noise due to the vibration of the casing 2 can be suppressed. This vibration is caused by the driving of the fan 1 and by the wind generated with the driving of the fan 1.

(42) Furthermore, the heat pipe 7 according to the present embodiment is disposed at the first face 11H facing one side in the axial direction A of the first part 6121. The upper casing 21 of the casing 2 is arranged on the first face 21H facing one side in the axial direction A of the second part 6122. Thus, the upper face 7HU of the heat pipe 7 according to the present embodiment is exposed to the outside, and the heat pipe 7 is adjacent to the casing 2 in the radial direction R. As a result, the cooling performance of the fan 1 according to the present embodiment can be improved by the heat pipe 7 and the casing 2. Moreover, vibration of the casing 2 caused by the driving of the fan 1 and by the wind generated with the driving of the fan 1 can be prevented from being transmitted to the heat pipe 7.

(43) At the fan 1 according to the above-described embodiment, the heat sink 6 is described to include the first heat spreader plates 611 and the second heat spreader plates 612. However, the heat sink 6 according to the present embodiment is not limited to the above. For example, at the heat sink 6 of the fan 1 according to the present embodiment, the plurality of heat spreader plates 61 may all be composed of the second heat spreader plates 612 having the same shape, and the respective second parts 6122 of all the second heat spreader plates 612 may be arranged inside the casing 2.

(44) Although the disclosure has been described based on the embodiment of the rotating device (fan 1) according to the disclosure, the disclosure is not limited to the embodiment, and it is needless to say that various modifications can be made without departing from the gist of the disclosure. Various modifications made without departing from the gist of the disclosure are also included in the technical scope of the disclosure, and it is clear from the description of the claims to those skilled in the art.

(45) While preferred embodiments of the disclosure have been described above, it is to be understood that variations and modifications will be apparent to those skilled in the art without departing from the scope and spirit of the disclosure. The scope of the disclosure, therefore, is to be determined solely by the following claims.

Claims

1. A rotating device, comprising: a shaft; an impeller fixed to the shaft; a motor causing the impeller to rotate; and a casing accommodating the impeller and the motor, wherein the casing includes an upper casing, a lower casing, a suction port, and a discharge port for a fluid, the casing and a heat sink are adjacent in a radial direction of the impeller, the heat sink includes a first part adjacent to the discharge port and a second part disposed inside the discharge port, the first part is

- in contact with a heat pipe, the second part is in contact with the casing in an axial direction of the impeller, a first end in the axial direction of the second part is directly attached to the upper casing, and a second end in the axial direction of the second part is directly attached to the lower casing.
2. The rotating device according to claim 1, wherein the impeller includes a plurality of blades rotating about an axis, and a dimension in the axial direction of the second part is larger than a dimension in the axial direction of the plurality of blades.
3. The rotating device according to claim 1, wherein a dimension in the axial direction of the second part is smaller than a dimension in the axial direction of the first part, a step is formed at a boundary between a first face facing one side in the axial direction of the second part and a first face facing the one side in the axial direction of the first part, and a step is formed at a boundary between a second face facing the other side in the axial direction of the second part and a second face facing the other side in the axial direction of the first part.
4. The rotating device according to claim 3, wherein the first face of the second part abuts the upper casing, and the second face of the second part abuts the lower casing.
5. The rotating device according to claim 4, wherein the heat pipe is disposed at the first face facing the one side in the axial direction of the first part, and the upper casing of the casing is disposed at the first face facing the one side in the axial direction of the second part.
-