

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250262076

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Forsell; Peter Mats

---

### APPARATUS FOR TREATING GERD

---

#### Abstract

The invention relates to an intraluminal method of treating a reflux disease in a patient by implanting a device comprising an movement restriction device that, when implanted in a patient, fills a volume in the patient's abdomen that is close to and at least partially above the patient's cardia when the patient is in a standing position. The invention further relates to a method of restoring the location of the cardia in a patient suffering from a reflux disease and to an instrument suitable to use with intraluminal method and/or restoration method. Also disclosed are instruments treating a patient suffering hiatal hernia and providing a movement restriction device to be invaginated in the stomach fundus wall.

---

**Inventors:** Forsell; Peter Mats (Sachseln, CH)

**Applicant:** Forsell; Peter Mats (Sachseln, CH)

**Family ID:** 1000008578272

**Appl. No.:** 19/200949

**Filed:** May 07, 2025

#### Foreign Application Priority Data

SE	0802138-8	Oct. 10, 2008
----	-----------	---------------

#### Related U.S. Application Data

parent US continuation 16862611 20200430 parent-grant-document US 12318278 child US 19200949

parent US continuation 15588765 20170508 parent-grant-document US 10639183 child US 16862611

parent US continuation 14672471 20150330 parent-grant-document US 9642733 child US 15588765

parent US continuation 12864843 20100727 parent-grant-document US 8992629 WO continuation

## Publication Classification

**Int. Cl.:** **A61F5/00** (20060101); **A61B1/04** (20060101); **A61B1/06** (20060101); **A61B1/273** (20060101); **A61B1/313** (20060101); **A61B17/00** (20060101); **A61B17/04** (20060101); **A61B17/064** (20060101); **A61B17/068** (20060101); **A61B17/08** (20060101); **A61B17/30** (20060101); **A61B17/32** (20060101); **A61B17/34** (20060101); **A61F2/04** (20130101); **A61N1/36** (20060101)

## U.S. Cl.:

**CPC** **A61F5/0083** (20130101); **A61B17/00234** (20130101); **A61B17/0469** (20130101); **A61F2/04** (20130101); A61B1/04 (20130101); A61B1/06 (20130101); A61B1/2736 (20130101); A61B1/3132 (20130101); A61B17/00 (20130101); A61B2017/00278 (20130101); A61B2017/00561 (20130101); A61B2017/00818 (20130101); A61B2017/00827 (20130101); A61B17/064 (20130101); A61B17/068 (20130101); A61B17/0682 (20130101); A61B17/08 (20130101); A61B2017/081 (20130101); A61B17/30 (20130101); A61B2017/306 (20130101); A61B2017/308 (20130101); A61B17/320016 (20130101); A61B17/3423 (20130101); A61B17/3474 (20130101); A61F2002/044 (20130101); A61F2002/045 (20130101); A61F5/0003 (20130101); A61F5/0013 (20130101); A61F2005/0016 (20130101); A61F2005/002 (20130101); A61F2005/0023 (20130101); A61F5/0026 (20130101); A61F5/003 (20130101); A61F5/0033 (20130101); A61F5/0036 (20130101); A61F5/004 (20130101); A61F5/0043 (20130101); A61F5/0046 (20130101); A61F5/005 (20130101); A61F5/0063 (20130101); A61F5/0069 (20130101); A61F5/0073 (20130101); A61F5/0076 (20130101); A61F5/0079 (20130101); A61F5/0086 (20130101); A61F5/0089 (20130101); A61F2250/0001 (20130101); A61F2250/0004 (20130101); A61N1/36007 (20130101)

---

## Background/Summary

[0001] This application is a continuation of U.S. patent application Ser. No. 16/862,611, filed on Apr. 30, 2020, which is a continuation of U.S. patent application Ser. No. 15/588,765, filed on May 8, 2017, and issued on May 5, 2020 as U.S. Pat. No. 10,639,183, which is a continuation of U.S. patent application Ser. No. 14/672,471, filed on Mar. 30, 2015, and issued on May 9, 2017 as U.S. Pat. No. 9,642,733, which is a continuation of U.S. application Ser. No. 12/864,843, filed on Jul. 27, 2010, and issued on Mar. 31, 2015 as U.S. Pat. No. 8,992,629, which is the U.S. national phase of International Application No. PCT/SE2009/000055, filed Jan. 29, 2009, which designated the U.S. and claims priority to U.S. Application No. 61/006,719, filed Jan. 29, 2008 and Swedish Application No. 0802138-8, filed 10 Oct. 2008, the entire contents of each of which are hereby incorporated by reference.

## TECHNICAL FIELD

[0002] The present invention relates to an apparatus for treating Gastroesophageal Reflux Disease (GERD).

## BACKGROUND

[0003] Gastroesophageal Reflux Disease (GERD), or acid reflux disease, is a chronic condition resulting in mucosal damage in the oesophagus produced by the recurring occurrence of acid reflux

in the oesophagus. This is commonly due to transient or permanent changes in the barrier between the oesophagus and the stomach. This can be due to incompetence of the lower esophageal sphincter (LES), transient LES relaxation, impaired expulsion of gastric reflux from the esophagus, or a hiatal hernia.

[0004] Gastroesophageal Reflux Disease can be treated in a number of different ways. Treatments include, but are not limited to, both medical and surgical treatments. A standard surgical treatment, which sometimes is preferred over longtime use of medication, is Nissen fundoplication surgery, in which the upper curve of the stomach (the fundus) is wrapped around the LES to strengthen the sphincter and prevent acid reflux and to repair a hiatal hernia. The procedure is often done laparoscopically.

[0005] Another surgical treatment which has been used is the Anglechik prosthesis, in which a device formed like a horseshoe is placed around the oesophagus above the cardia.

[0006] The intended effect is to prevent the cardia from slipping up into the thorax cavity.

However, this device has a number of complications, including migrating through and damaging the oesophagus.

[0007] From experience with implantation of medical devices, it is known that sutures between an implanted device and human tissue will not hold over the long term. For long term implantation of a device, there are two possibilities to keep the device in place. A first solution has been to suture human tissue to human tissue, to thereby keep the device in place. A second approach has been to provide sutures holding a device in place in the short term and to allow in-growth of human tissue into the device for holding the device in place over the long term.

[0008] A problem with providing an implantable device associated with the oesophagus is that the outer surface of the oesophagus is only comprised of oesophagus muscle tissue, which is very easy to damage or migrate through. This is probably one reason why the Anglechik prosthesis described above has resulted in many complications, such as migration.

[0009] The stomach, on the other hand, has a serosa on its outside, thereby providing a much stronger membrane for suturing. Thus, suturing a device directly to the stomach wall provides a better result than suturing an implanted device to the oesophagus.

[0010] Today, there exists a need for a long term treatment of GERD that is more effective than prior treatments and which does not result in any severe complications.

#### SUMMARY OF THE INVENTION

[0011] It is an object of the present invention to overcome, or at least reduce, some of the problems associated with existing surgical treatments of Gastroesophageal Reflux Disease (GERD).

[0012] It is another object of the present invention to provide an apparatus for treating gastroesophageal reflux disease.

[0013] These objects and others are obtained by apparatus described in the appended claims. Thus, by providing an apparatus for the treatment of acid reflux disease including an implantable movement restriction device having an outer surface that includes a biocompatible material, wherein the movement restriction device is adapted to rest with at least a part of its outer surface against the patient's stomach fundus wall, in a position between the patient's diaphragm and the fundus wall, such that movement of the cardiac notch of the patient's stomach towards the patient's diaphragm is restricted, an apparatus for treating Gastroesophageal Reflux Disease is obtained.

[0014] The movement restriction device has a size of at least 125 mm.sup.3 and a circumference of at least 15 mm and restricts movement of the cardiac notch of the patient's stomach towards the patient's diaphragm thereby preventing the cardia from sliding through the patient's diaphragm opening into the patient's thorax, maintaining the supporting pressure against the patient's cardia sphincter muscle exerted from the patient's abdomen. Fixation device are adapted to secure the movement restriction device in said position.

[0015] By adapting the outer surface of the implanted movement restriction device to rest against the wall of the fundus, there is a minimal risk of complications, such as migration of damage to

tissue, because the fundus is less fragile than the oesophagus.

[0016] In a first embodiment of the invention, the fixation device comprises sutures or staples that attach together portions of the fundus stomach wall that enclose the movement restriction device to secure the movement restriction device in said position. I.e., the movement restriction device is at least partly placed in an invaginated space. Thus, by affixing the implantable movement restriction device indirectly in this manner, no suturing between the movement restriction device and tissue is required, which, in turn, further reduces the risk for complications. Keeping the movement restriction device in place in this manner has resulted in an elastic suspension with improved long term properties.

[0017] The fixation device, such as sutures or staplers, may attach together portions of the fundus stomach wall so as to substantially or completely invaginate the movement restriction device from either inside or outside of the patient's stomach wall. Where the movement restriction device is placed on the outside of the patient's stomach wall, the movement restriction device is invaginated by the fundus stomach wall such that the stomach cavity is substantially reduced, by a volume substantially exceeding the volume of the movement restriction device.

[0018] In a second embodiment of the invention, the fixation device comprises an implantable first fixation device that attach the movement restriction device in said position to the fundus wall, a second fixation device that secures, indirectly or directly, the movement restriction device to the oesophagus close to the patient's angle of His, and a third fixation device that secures, indirectly or directly, the movement restriction device to the patient's diaphragm muscle or associated muscles. Any of the first, second and third fixation devices may be comprised of a plurality of sutures or staples. The first fixation device may comprise a tissue growth promoting structure for long term attachment of the movement restriction device to the stomach wall. The tissue growth promoting structure may be sutured to the stomach wall with a relatively large contact surface towards the stomach. The relatively large surface of the structure, such as a net, will allow for in-growth of human tissue for holding the movement restriction device in place over the long term. The tissue growth promoting structure may comprise sutures or staples that attach the net like structure to the fundus stomach wall.

[0019] In addition to invaginating the movement restriction device in accordance with the first embodiment of the invention, the second fixation device can be used to secure, indirectly or directly, the movement restriction device to the oesophagus close to the patient's angle of His, and the third fixation device may be used to secure, indirectly or directly, the movement restriction device to the patient's diaphragm muscle or associated muscles.

[0020] At least a part of the movement restriction device may be made of a material which is destructible or not destructible by stomach acid.

[0021] The movement restriction device may be inflatable and adapted to be inflated with a gel or fluid. A fluid or gel receiving member for receiving fluid to inflate the movement restriction device may be provided.

[0022] The movement restriction device may include a homogenous material and may be a solid body.

[0023] The movement restriction device may include an enclosure wall defining a chamber.

[0024] The movement restriction device may have a rigid, elastic or flexible outer wall. Where the outer wall is rigid, it is rigid enough to maintain non-deformed when subject to forces created by stomach movements. Where the movement restriction device is invaginated, in accordance with the first embodiment described above, the movement restriction device preferably comprises a body adapted to be at least partly invaginated by the patient's stomach fundus wall and having an outer surface that includes a biocompatible material. A substantial part of the outer surface of the body is adapted to rest against the stomach wall in said position between the patient's diaphragm and the portion of the lower part of the invaginated stomach fundus wall.

[0025] Suitably, the body is made of a material softer than 25 or 15 shore.

[0026] In accordance with a first general design of the body, the body has a maximum circumference as seen in a plane perpendicular to an axis through the body. The circumferences of the body as seen in other planes perpendicular to said axis are equal to the maximum circumference or decrease as seen along said axis in the direction from the maximum circumference. For example, the body may be substantially egg shaped, spherically shaped, or substantially shaped like an egg with an indented middle section or like a bent egg.

[0027] In accordance with a second general design of the body, the circumference of the body as seen in a plane perpendicular to an axis through the body increases and decreases at least two times as the plane is displaced along said axis, or decreases and increases at least one time as the plane is displaced along said axis. For example, the body may be substantially shaped like a kidney.

[0028] Preferably, the body is dimensioned with a size larger than the intestinal outlet from the stomach. The body may have a smallest outer diameter of 30 or 40 mm or larger and may have a smallest outer circumference of 150, 110, 90, 70, 50 or 30 mm.

[0029] Suitably, the body has rounded contours without too sharp edges that would be damaging to the patient's stomach wall, and has a generally smooth outer surface for resting against the fundus wall.

[0030] The body is implantable either inside or outside of the patient's stomach and is adapted to be attached to the patient's stomach wall by surgery. The body may be changeable to assume a slender form having a smaller diameter than that of a trocar for laparoscopic use, whereby the body when changed to said slender form can be pushed or pulled through the trocar. The body may include a flexible outer wall defining a chamber filled with a fluid, such as a gel, allowing the body to pass through such a trocar. Alternatively, the body may include an elastic compressible material, allowing the body to pass through a trocar.

[0031] The body may be hollow and include at least two separate pieces adapted to be inserted into the hollow body, and further adapted to be put together to one unitary piece inside the body, thereby allowing the body to pass through a trocar for laparoscopic use. Alternatively, the body may include an outer wall and a hollow compressed inner part, for being filled with a fluid or gel after insertion into the patient's body.

[0032] The body may include a chamber with an injection port, wherein the chamber of the body is filled with a fluid through the injection port.

[0033] The body may include at least one holding device adapted to be used for pushing or pulling the body through a trocar for laparoscopic use. The holding device is adapted to hold a prolongation of the body that is adapted to be held by a surgical instrument. More specifically, the holding device is adapted to hold a thread or band inserted through the holding device. Where the body comprises an outer wall the holding device is at least partly placed inside the outer wall of the body.

[0034] In an advantageous embodiment, the body is adjustable in size and invaginated in the patient's fundus stomach wall. As a result, the body stretches the patient's stomach fundus wall when the size thereof is increased, thereby creating satiety in a patient also suffering from obesity. At least two implantable adjustable stretching devices may be provided to stretch different parts of the patient's stomach wall, to thereby treat obesity by efficiently affecting the patient's appetite. The two stretching devices are suitably regulated from outside of the patient's body, whereby a first of the stretching devices is regulated at a first time to stretch a first part of the patient's stomach wall and a second of the stretching devices is regulated at a second time to stretch a second part of the patient's stomach wall.

[0035] The stretching device may be hydraulically regulated. In this case, a subcutaneously implantable hydraulic reservoir connected to the hydraulic regulated stretching device may be provided, whereby the hydraulic regulated stretching device is non-invasively regulated by manually pressing the hydraulic reservoir. Further, the movement restriction device suitably includes an inflatable body, and a pump and a chamber in fluid contact with the body are provided,

wherein the pump regulates the hydraulic reservoir by pumping fluid or air from the body to the chamber.

[0036] The apparatus may include an implantable stimulation device that sends out stimulation pulses to the cardia muscle to stimulate the cardia muscle and thereby further close the cardia to additionally prevent reflux disease. The stimulation device is comprised of at least one conductor and at least one electrode that receives the stimulation pulses and applies them to the cardia muscle to thereby stimulate the cardia muscle. The at least one electrode may also be kept in place by the stomach-oesophageal sutures or invagination in the stomach wall. The stimulation pulses may be sent as a train of pulses, wherein the pulse train is repeated with a time break in between, the break extending the break between each pulse in the pulse train. The stimulation device may include an electronic circuit and an energy source preferably adapted to incorporate the electronic circuit and energy source. In one embodiment, the stimulation of the cardia with the stimulation device is made with energy pulses to increase the sphincter tonus so that the cardia completely closes and a control device for controlling the stimulation device is operable by the patient to set the stimulation device into operation, in which operational state the stimulation device continuously alternates at a time when the patient does not swallow between an operation mode in which the cardia sphincter is stimulated with said energy pulses and a rest mode in which the cardia is not stimulated.

[0037] The stimulation device preferably comprises at least one sensor for sensing a physical parameter of the patient or a functional parameter of the movement restriction device and an internal control unit for controlling the stimulation device.

[0038] Normally, the internal control unit controls the stimulation device in response to information from the sensor.

[0039] A sensor sensing a contraction wave of the oesophagus, or any other parameter correlated to food intake, sends the information to the internal control unit and the internal control unit then ceases the stimulation in response to such information from the sensor.

[0040] The stimulation device may, at any time, be controlled by the patient.

[0041] The present invention further relates to abdominal surgical methods of treating a reflux disease.

[0042] According to a first method a reflux disease in a patient is treated by implanting a movement restriction device that, when implanted in a patient, restricts the movement of the stomach notch in relation to the diaphragm muscle preventing the cardia to slide up through the diaphragm hiatus opening. The method comprises the steps of inserting a needle or a tube like instrument into the abdomen of the patient's body; using the needle or tube like instrument to fill the patient's abdomen with gas; placing at least two laparoscopic trocars in the patient's body; inserting a camera through one of the laparoscopic trocars into the patient's abdomen, inserting at least one dissecting tool through one of said at least two laparoscopic trocars; dissecting an area of the stomach; introducing the device into the abdominal cavity; placing the device on the outside of the stomach fundus wall; and creating a pouch in the stomach fundus wall for the device; and in-vaginating the device in the pouch by providing sutures or staples to the stomach fundus wall, thereby preventing the cardia from sliding through the patient's diaphragm opening into the patient's thorax, so as to maintain the pressure support from the patient's abdomen that supports the patient's cardia sphincter muscle.

[0043] A second abdominal method of treating a reflux disease for the same purpose uses the initial steps as the first method comprises creating a hole in the stomach fundus wall; introducing a movement restriction device into the abdominal cavity; introducing the device through the hole and into the stomach; placing the device on the inside of the stomach fundus wall; creating a pouch on the outside of the stomach cavity for the device placed on the inside of the stomach fundus wall, and in-vaginating the device in the pouch by providing sutures or staples to the stomach fundus wall, preventing the cardia from sliding through the patient's diaphragm opening into the patient's thorax, so as to maintain the supporting pressure from the patient's abdomen that supports the

patient's cardia sphincter muscle.

[0044] A third abdominal method of treating a reflux disease in a patient includes implanting a movement restriction device for the same purpose as previously disclosed methods and comprises the steps of surgically incising an opening in the patient's abdominal wall; dissecting an area of the patient's stomach; introducing the movement restriction device through the abdominal incision; and attaching the device to the stomach fundus wall, thereby preventing the cardia from sliding through the patient's diaphragm opening into the patient's thorax, so as to maintain the supporting pressure from the patient's abdomen that supports the patient's cardia sphincter muscle. According to first alternative, the method includes placing the device on the outside of the stomach fundus wall; creating a pouch in the stomach fundus wall for the device; and in-vaginating the device in the pouch by providing sutures or staples to the stomach fundus wall, thereby preventing the cardia from sliding through the patient's diaphragm opening into the patient's thorax, so as to maintain the supporting pressure from the patient's abdomen that supports the patient's cardia sphincter muscle. According to a second alternative, the method includes creating a hole in the stomach fundus wall; introducing the movement restriction device through the hole and into the stomach; placing the device on the inside of the stomach fundus wall; creating a pouch on the stomach fundus wall for the device, and in-vaginating the device in the pouch by providing sutures or staples to the stomach fundus wall, preventing the cardia from sliding through the patient's diaphragm opening into the patient's thorax, so as to maintain the supporting pressure from the patient's abdomen that supports the patient's cardia sphincter muscle.

[0045] The methods further comprise affixing the device to the stomach fundus wall by providing sutures or staples and/or affixing the stomach fundus wall to the lower part of the patient's esophagus by providing sutures or staples; and/or affixing the stomach fundus wall to the patient's diaphragm muscle or associated muscles. The methods can further comprise the provision of an apparatus for regulating the reflux treatment device from the outside of the patient's body; and operating said apparatus to regulate the reflux treatment device. The regulation of the reflux treatment device can include changing the volume of the filling body when implanted. For this purpose, the methods can include the provision of an injection type syringe comprising a fluid for injection into an implanted filling body; and injecting volume of fluid into filling body. Preferably, the methods comprise enclosing the device in the pouch. In one embodiment, the method admits the pouch being at least partly open, whereby the pouch can exhibit only one opening, or the pouch can exhibit two openings and to extend non-circumferentially around the stomach. It is generally preferable that the volume of the pouch is more than 15 millilitres

[0046] A further laparoscopic abdominal method of treating a reflux disease comprises inserting a needle or a tube like instrument into the abdomen of the patient's body; using the needle or tube like instrument to fill the patient's abdomen with gas; placing at least two laparoscopic trocars in the patient's body; inserting a camera through one of the laparoscopic trocars into the patient's abdomen; inserting at least one dissecting tool through one of said at least two laparoscopic trocars; dissecting an area of the stomach; creating a pouch from the stomach fundus wall for the device; closing the pouch by providing sutures and staples; introducing a injecting member comprising an injectable filling material; and injecting the filling material into the pouch, thereby creating a filling body that, fills a volume in the patient's abdomen that is close to and above the patient's cardia when the patient is in a standing position in order to prevent the cardia from sliding through the patient's diaphragm opening into the patient's thorax, so as to maintain pressure in the patient's abdomen supporting the patient's cardia sphincter muscle.

[0047] A further surgical abdominal method of treating a reflux disease comprises cutting an opening in the skin to enter the patients abdomen dissecting an area of the stomach; creating a pouch from the stomach fundus wall for the device; closing the pouch by providing sutures and staples; introducing a injecting member comprising an injectable filling material; and injecting the filling material into the pouch, thereby creating a filling body that, fills a volume in the patient's

abdomen that is close to and above the patient's cardia when the patient is in a standing position in order to prevent the cardia from sliding through the patient's diaphragm opening into the patient's thorax, so as to maintain pressure in the patient's abdomen supporting the patient's cardia sphincter muscle.

[0048] The recited further methods can include creating the pouch on the outside of the stomach fundus wall, with the filling body placed against the inside of the stomach fundus wall, or alternatively, the methods include creating a hole in the stomach fundus wall and the pouch is created on the inside of the stomach fundus wall, with the filling body placed against the outside of the stomach fundus wall. The recited further methods preferably also include affixing the stomach fundus wall to the lower part of the patient's esophagus by providing sutures or staples and/or affixing the stomach fundus wall to the patient's diaphragm muscle or associated muscles. It is also generally preferable that the volume of the pouch is more than 15 millilitres. The filling material is preferably capable of undergoing a curing process from fluid material to a semi-solid or solid material. Such a curing process is preferably triggered by an increase in temperature from ambient temperature to body temperature. A suitable such material, well-known to persons skilled in the art, is a thermocurable polysiloxane which (in the presence of a crosslinker and a catalyst) can undergo a crosslinking reaction under the influence of heat.

[0049] A still further laparoscopic abdominal method of treating a reflux disease in a patient by implanting a movement restriction device that, when implanted in a patient, restricts the movement of the stomach notch in relation to the diaphragm muscle preventing the cardia to slide up through the diaphragm hiatus opening, comprises the steps of inserting a needle or a tube like instrument into the abdomen of the patient's body; using the needle or tube like instrument to fill the patient's abdomen with gas; placing at least two laparoscopic trocars in the patient's body; inserting a camera through one of the laparoscopic trocars into the patient's abdomen; inserting at least one dissecting tool through one of said at least two laparoscopic trocars; dissecting an area of the stomach; creating a hole in the stomach fundus wall; introducing a movement restriction device into the abdominal cavity; introducing the device through the hole and into the stomach; placing the device on the outside of the stomach fundus wall; fixating the device placed on the outside of the stomach fundus wall, and preventing the cardia from sliding through the patient's diaphragm opening into the patient's thorax, so as to maintain the supporting pressure from the patient's abdomen that supports the patient's cardia sphincter muscle. The method can further comprise the step of affixing the device to the stomach fundus wall by providing sutures or staples.

[0050] The present invention also relates to a laparoscopic instrument for providing a movement restriction device to be invaginated in the stomach fundus wall of a human patient to treat reflux disease, suitable for use with any of the mentioned laparoscopic methods. The instrument generally comprises an elongated member having a proximal end and a distal end, the elongated member having a diameter less than that of a laparoscopic trocar to be introduced into the patient's abdomen during a laparoscopic operation; a stomach pushing device for pushing the stomach fundus wall to create a tube like shaped portion of the stomach fundus wall protruding into the normal stomach cavity, said pushing device comprising the movement restriction device to be invaginated by the stomach fundus wall in the tube like shaped portion thereof. The pushing device comprises a vacuum sucking device to suck the stomach fundus to assist the instrument in forming the tube like shaped portion of the stomach fundus wall together with the pushing device. The vacuum sucking device comprises a vacuum passageway leading from the proximal to the distal end of the instrument and at the end portion of the instrument, which includes the pushing device. The vacuum passageway is divided up in multiple small openings adapted to suck the stomach wall portion to become adherent to the pushing device to further form the tube like stomach wall portion. The instrument further comprises an insertion device adapted to introduce the movement restriction device into the tube like shaped stomach portion. The instrument can further comprise at least one clamping device for holding the opening of the tube like portion substantially closed by



clamping together stomach to stomach in said opening, wherein the instrument is adapted to place the at least one clamping device at the opening in such a way that it allows later suturing of the opening. The instrument can further comprise an inflation device for inflating the movement restriction device before or after the suturing. The instrument can further comprise a suturing device adapted to suture the opening of the tube like portion with stomach to stomach sutures for creating at least partly a closed space enclosing the movement restriction device, wherein the instrument is adapted to be withdrawn leaving the movement restriction device at least partly invaginated in the stomach fundus wall. The suturing device can comprise a first and second suture positioning member provided on the elongated member to be located in the stomach at the distal end thereof. The instrument further comprises an operation device adapted to adjust the first and second suturing member in a position in which the first and second suture positioning members are in front of each other with the stomach wall on both sides of the open end of the cup like portion, and adapted to suture the open end of the cup like portion of the fundus wall with a row of stomach to stomach sutures. The suturing device preferably comprises an operable reloadable multi-suturing device, which is reloadable with sutures from outside of the patient's body and which is adapted to suture the open end of the cup like portion of the fundus wall with said row of stomach to stomach sutures, wherein the row of sutures comprises two or more sutures or staples to be sutured simultaneously. The suturing device can also comprise multiple sutures for suturing two or more sutures simultaneously.

[0051] The present invention also relate an intraluminal method of treating a reflux disease in a patient by implanting a device comprising an implantable movement restriction device that, when implanted in a patient, restricts the movement of the stomach notch in relation to the diaphragm muscle preventing the cardia to slide up through the diaphragm hiatus opening. The method comprises the steps of introducing a gastroscope in the esophagus and into the stomach of the patient; introducing an instrument in the esophagus and into the stomach of the patient, said instrument being integrated in said gastroscope or separate from the same; providing, by means of said of instrument, a pouch from the stomach fundus wall for accommodating the device and invaginating the device in the pouch with sutures or staples to the stomach fundus wall, thereby preventing the cardia from sliding through the patient's diaphragm opening into the patient's thorax, so as to maintain the supporting pressure against the patient's cardia sphincter muscle exerted from the patient's abdomen. In a first alternative, the method comprises the steps of introducing the device into the stomach by means of the instrument; placing the device on the inside of the stomach fundus wall, using said instrument; creating, by means of said instrument, a pouch in a portion of the stomach fundus wall on the outside of the stomach cavity, the device placed resting against the inside of the stomach fundus wall; and invaginating the device in the pouch by with sutures or staples to the stomach fundus wall. In a second alternative, the method comprises the steps of creating, by means of said instrument, a pouch of a portion of the stomach fundus wall; introducing the device by means of the instrument into the pouch; and invaginating the device with sutures or staples to the stomach fundus wall. According to this alternative, the method comprises inflating the device to its filling volume, preferably by injecting a filling fluid into the device so it obtains its filling volume. The filling fluid can thereby be a curable fluid of the characteristics earlier describes, such as the aforescribed thermocurable polysiloxanes. In a third alternative, the method comprises the steps of creating a hole in the stomach fundus wall; introducing the device into the stomach by means of the instrument; moving the device through the hole and placing it on the outside of the stomach fundus wall; creating, by means of said instrument, a pouch of a portion of the stomach fundus wall on the inside of the stomach cavity, with the device placed against the outside of the stomach fundus wall; invaginating the device in the pouch with sutures or staples to the stomach fundus wall; and sealing the hole with sutures or staples. In a fourth alternative, the method comprises the steps of creating a hole in the stomach fundus wall; creating, by means of said instrument, a pouch of a portion of the stomach fundus wall on the inside of the stomach

cavity; introducing the device into the stomach by means of the instrument; moving the device through the hole and placing it on the outside of the stomach fundus wall; introducing the device by means of the instrument into the pouch; invaginating the device with sutures or staples to the stomach fundus wall; and scaling the hole with sutures or staples. Also this method can comprise inflating the device to its filling volume, preferably by injecting a filling fluid into the device so it obtains its filling volume. The filling fluid can have all the previously described characteristics. The method also comprises affixing the device to the stomach fundus wall by providing sutures or staples; and/or affixing the stomach fundus wall to the lower part of the patient's oesophagus by providing sutures or staples; and/or affixing the stomach fundus wall to the patient's diaphragm muscle or associated muscles. The method can also comprise the provision of an apparatus for regulating the reflux treatment device from the outside of the patient's body; and operating said apparatus to regulate the reflux treatment device.

[0052] Regulation of the reflux treatment device preferably includes changing the volume of the filling body when implanted. For this purpose, the method can comprise the provision of an injection type syringe comprising a fluid for injection into an implanted filling body; and injecting volume of fluid into filling body. The filling fluid can be curable fluid of a nature as discussed in previous sections. The pouch created by the method can enclose the movement restriction device, or it can be at least partially open, in one example it has only one opening, and according to another example it exhibits two openings and extends non-circumferentially around the stomach. Preferably, the volume of the pouch is more than 15 millilitres. It is generally preferably in the method that the gastroscope and the instrument are integrated. The method can further include inflating the stomach with gas. In a special embodiment of the method, the instrument generates vacuum when providing the pouch from the stomach fundus wall.

[0053] The invention also relates to a method of restoring the location of the cardia and the fundus in a patient suffering from a reflux disease comprising introducing an elongated instrument having at least one flexible part into oesophagus of a patient; activating a holding device by the instrument, said activated holding device having larger cross-sectional area than said instrument; holding the distal esophagus or stomach with said holding device; moving and pushing the instrument in a distal direction so the cardia and the stomach wall, or part of fundus, incorrectly located above diaphragm, or its associated muscles, slide back in a position below the diaphragm, or its associated muscles. In a first alternative, the method comprises expanding the holding device radially above the cardia in the oesophagus and using the device to push the cardia and the stomach wall or part of fundus below the diaphragm or its associated muscles. In a second alternative, the method comprises releasing a balloon member at the proximal end of the instrument in the lower part of the stomach, and using the member to push the instrument against a lower wall part of the stomach so the cardia and the fundus or part of fundus slide below the diaphragm or its associated muscles. In a third alternative, the method comprises locating the distal end of the instrument at the level of the diaphragm or its associated muscles; expanding the member in radial direction; attaching the member to the stomach wall; and pushing the instrument in a distal direction so the cardia and the stomach wall or, part of fundus, slide below the diaphragm or its associated muscles. The method according to all recited alternatives can comprise the employment of an affixing member as part of the holding device in the distal part of the instrument capable providing sutures or staples or other invasive mechanical members for affixing the esophagus and stomach wall to the instrument, preferably, the method comprises the employment of a suturing member in the distal part of the instrument capable providing sutures or staples for suturing the stomach fundus wall to the lower part of the esophagus above said cardia,

[0054] The invention is also directed to a surgical gastroscopic instrument for treating a patient suffering from hiatal hernia, wherein a portion of the patient's stomach passes through the hiatus of the diaphragm muscle with the patient's cardia placed above the diaphragm muscle in the thorax. The instrument comprises: (i) an elongated member having a proximal end and a distal end, said

elongated member having a diameter less than that of the patient's esophagus and being flexible, thereby allowing introducing the flexible elongated member with its distal end first from the throat into the esophagus; (ii) a holding device secured to the elongated member and operable between an activated state, in which it is adapted to engage and hold the patient's esophagus or stomach, and an inactivated state, in which it is adapted to be released from the esophagus or stomach; (iii) an operation device for operating the holding device to shift between said activated and inactivated states from outside the patient's body; and (iv) a handle connected to the elongated member at the proximal end thereof to be held manually for moving the elongated member distally, wherein the holding device, when operated by the operation device in its activated state, is adapted to engage and hold the esophagus or stomach strong enough to allow the elongated member, when manually moved, to move and reintroduce the cardia back in the distal direction to a position below the diaphragm muscle. The operable holding device of the instrument is preferably adapted to radially expand relative to the elongated member from said inactivated state to said activated state, such that said holding device, when radially expanded, engages and holds the stomach or esophagus by force and friction. Alternatively, the operable holding device comprises at least one introducing member adapted to invasively introduce into the wall of the stomach or esophagus to secure the holding device on the esophagus or the stomach, when the holding device is in its activated state. In both alternatives, the operable holding device is adapted to engage and hold the esophagus proximal to the cardia or at the cardia, or to engage and hold the stomach at a position in the hiatus or distal thereto, when the cardia is above the diaphragm muscle. According to another alternative, the elongated member of the instrument comprises a first suture positioning member, which is situated in the esophagus when the holding device is in its activated state holding the esophagus or stomach, and a second suture positioning member at the distal end of the elongated member. The operation device of the instrument is adapted to bend the flexible elongated member around the stomach notch into a position in which the first suture positioning member is above the cardia and the first and second suture positioning members are in front of each other with the fundus wall and esophagus wall moved together by the first and second suture positioning members. The instrument further comprises a reloadable multi-suturing device for suturing together the patient's esophagus proximal to the cardia with the fundus stomach wall by a row of sutures, where the fundus wall and esophagus wall are moved together by the first and second suture positioning members, said row of sutures comprising two or more sutures to be sutured simultaneously by the multi-suturing device.

[0055] The invention further comprises another embodiment of a surgical gastroscopic instrument for treating a human patient suffering from hiatal hernia, This instrument comprises: (i) an elongated member having a proximal end and a distal end, said elongated member having a diameter less than that of the patient's esophagus and being flexible, thereby allowing introducing the flexible elongated member with its distal end first from the patient's throat into the esophagus;

[0056] (ii) a first suture positioning member provided on the elongated member such that it is situated in the esophagus proximal to the cardia when the elongated member has been introduced in the esophagus with the distal end of the elongated member situated in the stomach; (iii) a second suture positioning member provided on the elongated member at the distal end thereof; (iv) an operation device adapted to bend the flexible elongated member around the stomach notch into a position in which the first and second suture positioning members are in front of each other with the fundus wall and esophagus wall moved together by the first and second suture positioning members; and (v) a re-loadable multi-suturing device for suturing together the patient's esophagus proximal to the cardia with the fundus stomach wall by a row of sutures, where the fundus wall and esophagus wall are moved together by the first and second suture positioning members, the multi-suturing device being reloadable with sutures from outside the body to apply further rows of sutures in front or back of the first row of sutures, wherein said row of sutures comprises two or more sutures to be sutured simultaneously by the multi-suturing device. The instrument further comprises a holding device secured to the elongated member and operable between an activated

state, in which it is adapted to engage and hold the patient's esophagus or stomach, and an inactivated state, in which it is adapted to be released from the esophagus or stomach. The holding device is operable by the operation device to shift between said activated and inactivated states from outside the patient's body, and a handle connected to the elongated member at the proximal end thereof to be held manually for moving the elongated member distally, wherein the holding device, when operated by the operation device in said activated state, is adapted to engage and hold the esophagus or stomach strong enough to allow the elongated member, when manually moved, to move and reintroduce the cardia back in the distal direction to a position below the diaphragm muscle. In one alternative, the operable holding device is adapted to radially expand relative to the elongated member from said inactivated state to said activated state, such that the holding device, when radially expanded, engages and holds the stomach or esophagus by force and friction. In another alternative, the operable holding device comprises at least one introducing member adapted to invasively introduce into the wall of the stomach or esophagus to secure the holding device on the esophagus or the stomach, when the holding device is in its activated state. In both alternatives, the operable holding device is adapted to engage and hold the esophagus proximal to the cardia or at the cardia, or to engage and hold the stomach at a position in the hiatus or distal thereto, when the cardia is above the diaphragm muscle.

[0057] The invention further comprises still another embodiment of a surgical gastroscopic instrument for providing a movement restriction device to be invaginated in the stomach fundus wall of a human patient to treat reflux disease. The instrument comprises (i) an elongated member having a proximal end and a distal end, the elongated member having a diameter less than that of the patient's esophagus and being flexible, thereby allowing introduction of the flexible elongated member with its distal end first through the patient's throat, esophagus and into the stomach to the fundus wall; (ii) an operable stomach penetration device provided the elongated member at the distal end thereof for penetrating the stomach fundus wall to create a hole in the stomach fundus wall, to allow introduction of the elongated member through the hole; (iii) an operable special holding device provided on the elongated member proximal to the penetration device, when penetrating said stomach wall, to hold the elongated member in a position in which the elongated member extends through the stomach fundus wall and is prevented from moving through the hole in the proximal direction, wherein the special holding device includes an expandable member expandable at least radially substantially perpendicular to the elongated member to abut against the fundus wall on the outside thereof; and [0058] (iv) an insertion device for inserting the movement restriction device through the hole in the stomach fundus wall to the outside thereof to be invaginated in the fundus wall. The instrument can further comprise a forming device provided on the elongated member proximal to the special holding device to abut against the fundus wall on the inside thereof. The forming device together with the special holding device is adapted to form the stomach fundus wall in a cup like shape, whereby the special holding device is retractable relative to the forming device to pull the stomach wall against the forming device to form said cup like shaped portion of the stomach. The instrument can further comprise a suturing device adapted to suture the open end of the cup like portion of the fundus wall with stomach to stomach sutures to create a space that is at least in part enclosed by a portion of the fundus wall. The suturing device preferably comprises multiple sutures for suturing two or more sutures simultaneously. The suturing device is adapted to suture the open end of the cup like portion of the fundus wall before the movement restriction device is inserted by the insertion device through the hole of the fundus wall. The instrument can further comprise an inflation device for inflating the movement restriction device after being introduced by the insertion device through the hole of the fundus wall, or for inflating the movement restriction device after being introduced by the movement restriction device introduced through the hole of the fundus wall. The suturing device can comprise an operable reloadable multi-suturing device, which is reloadable with sutures from outside the patient's body and which is adapted to suture the open end of the cup like portion of the fundus wall with a row of

stomach to stomach sutures, wherein the row of sutures comprises two or more sutures or staples to be sutured simultaneously. In another alternative, the instrument comprises an inflatable movement restriction device, the penetration device comprises a wire adapted to be introduced through the hole in the stomach fundus wall and to be advanced at least up to the abdominal wall or be passed therethrough. The wire serves as a guide for a hydraulic tube, which is connected to the inflatable movement restriction device and which is connectable to an injection port to be placed subcutaneously for filling the inflatable movement restriction device with a fluid and adjusting the amount thereof, when the movement restriction device has been inserted by the insertion device through the hole of the fundus wall.

[0059] The invention further comprises still yet another embodiment of a surgical gastroscopic instrument for providing an inflatable movement restriction device to be invaginated in the stomach fundus wall of a human patient to treat reflux disease. The instrument comprises: (i) an elongated member having a proximal end and a distal end, the elongated member having a diameter less than that of the patient's esophagus and being flexible, thereby allowing introduction of the flexible elongated member with its distal end first through the patient's throat, esophagus and into the stomach to the fundus wall; and (ii) an operable stomach penetration device provided on the elongated member at the distal end thereof for penetrating the stomach fundus wall to create a hole in the stomach fundus wall, to allow introduction of the elongated member through the hole, wherein the penetration device includes a wire to be introduced through the hole in the stomach fundus wall and to be advanced at least up to the abdominal wall or be passed therethrough, said wire serving as a guide for a hydraulic tube, which is connected to the inflatable movement restriction device and which is connectable to an injection port to be placed subcutaneously for filling the inflatable movement restriction device with a fluid and adjusting the amount thereof, and wherein at least one of the wire and tube can be pulled to move the movement restriction device inflated with fluid towards the fundus stomach wall to be placed on the inside of the stomach fundus wall where the movement restriction device is to be invaginated in the fundus wall. Preferably, at least one of the wire and tube when pulled to move the inflated movement restriction device towards the fundus stomach wall allow a portion of the stomach fundus wall to move to form a cup like shaped portion of the stomach protruding out from the normal stomach cavity. The instrument can further comprise an operable forming device having a cup like shape for forming the cup like shaped portion of the stomach. The instrument can further comprise a suturing device adapted to suture the open end of the cup like portion of the fundus wall with stomach to stomach sutures to create a space that is at least in part enclosed by a portion of the fundus wall. The suturing device can comprises multiple sutures for suturing two or more sutures simultaneously. The suturing device can be adapted to suture the open end of the cup like portion of the fundus wall before the movement restriction device is inserted through the hole of the fundus wall. The movement restriction device, preferably is inflatable, further comprising an inflation device for inflating the movement restriction device after being introduced through the hole of the fundus wall. The instrument can further comprise a first and second suture positioning member provided on the elongated member situated in the stomach at the distal end thereof, and an operation device adapted to adjust the first and second suturing member in a position in which the first and second suture positioning members are in front of each other with the stomach wall on both sides of the open end of the cup like portion, and adapted to suture the open end of the cup like portion of the fundus wall with a row of stomach to stomach sutures. The suturing device can comprise an operable re-loadable multi-suturing device, which is reloadable with sutures from outside the patient's body and which is adapted to suture the open end of the cup like portion of the fundus wall with said row of stomach to stomach sutures, wherein the row of sutures comprises two or more sutures or staples to be sutured simultaneously.

[0060] The invention further comprises still yet another embodiment of a surgical gastroscopic instrument providing a movement restriction device to be invaginated in the stomach fundus wall

of a human patient to treat reflux disease. The instrument comprising: (i) an elongated member having a proximal end and a distal end, the elongated member having a diameter less than that of the patient's esophagus and being flexible such that introduction of the flexible elongated member with its distal end first through the patient's throat, esophagus and into the stomach to the fundus wall is allowed; (ii) an operable stomach pushing device for pushing the stomach fundus wall to create a cup like shaped portion of the stomach fundus wall protruding out from the normal stomach cavity, said pushing device including the movement restriction device to be invaginated by the stomach fundus wall in the cup like shaped portion thereof; and (iii) a suturing device adapted to suture the opening of the cup like shaped portion of the stomach fundus wall with stomach to stomach sutures to enclose at least in part the movement restriction device. The instrument further can comprise a forming device provided on the elongated member proximal to the pushing device to pull the fundus wall on the inside thereof. The forming device together with the pushing device is adapted to form the stomach fundus wall in an optimal cup like shape, wherein the pushing device is pushed to form said cup like shaped portion of the stomach. The instrument can further comprise first and second suture positioning member provided on the elongated member situated in the stomach at the distal end thereof; and an operation device adapted to adjust the first and second suturing member in a position in which said first and second suture positioning members are in front of each other with the stomach wall on both sides of the open end of the cup like portion, and adapted to suture the open end of the cup like portion of the fundus wall with a row of stomach to stomach sutures. The suturing device can comprise an operable re-loadable multi-suturing device, which is reloadable with sutures from outside the patient's body and which is adapted to suture the open end of the cup like portion of the fundus wall with said row of stomach to stomach sutures, wherein the row of sutures comprises two or more sutures or staples to be sutured simultaneously. The suturing device can also comprise multiple sutures for suturing two or more sutures simultaneously. The instrument can further comprise an inflating device for inflating the movement restriction device after the suturing. The forming device can preferably comprise a vacuum sucking device to suck the stomach fundus to help the instrument to form the cup like shaped portion of the stomach fundus wall together with the pushing device. The embodied gastroscopic instruments as described in previous section can comprise an optical device for examining the inside the esophagus or the stomach. For this purpose, the instruments can further comprise electrical wires extending along the elongated member, and the optical device comprises a camera placed distally on the elongated member and connected to the wires, which lead out from the patient's body for external exposure of images from the camera. The instruments can further comprise a light source placed distally on the elongated member for illuminating the inside of the esophagus or stomach. The optical device can suitably comprise optical fibers placed along the elongated member and leading out from the patient's body for external examination of the inside of the esophagus or stomach. The present invention further relates to an apparatus for treating a reflux disease and obesity. This apparatus comprises a movement restriction device and the fixation devices, adjustment device, wireless remote control function, wireless energy transmitter and further features as described earlier with an apparatus for treating a reflux disease. In addition the apparatus for combined treatment of a reflux disease comprises at least one operable stretching device that, when implanted in the patient, stretches a part of the patient's stomach wall, to thereby treat obesity by affecting the patient's appetite; and an operation device for operating the stretching device when implanted to stretch the stomach wall portion such that satiety is created. The stretching device may be kept in contact with the stomach wall by stomach-to-stomach sutures or staplers, in a position in which the stretching device is capable of stretching the stomach wall. Specifically, the stretching device may be invaginated by the stomach wall by means of stomach-to-stomach sutures or staplers. The stretching device may be adapted to be placed in the stomach cavity. To this end, the stretching device may be adapted to be inserted into the stomach cavity via a gastroscope or intraluminal instrument, and be adapted to be attached to the stomach wall by

surgery. Alternatively, the stretching device may be adapted to be placed on the outside of the stomach. In an embodiment, the stretching device comprises a first engaging member adapted to engage a first part of the stomach wall and a second engaging member adapted to engage a second part of the stomach wall close to but spaced from the first stomach part. The operation device is adapted to operate the first and second engaging member to move away from each other to stretch the stomach wall portion between the first and second parts of the stomach such that satiety is created. At least one of the first and second engaging members may be adapted to at least in part be invaginated by the stomach wall by stomach-to-stomach sutures or staplers holding the engaging member in place. In addition, at least one of the first and second engaging members may be adapted to be kept in place by sutures or staplers between the engaging member and the stomach wall. Suitably, at least one of the first and second engaging members comprises a tissue growth promoting structure, preferably a net like structure, adapted to be in contact with the stomach wall to secure long term attachment of the stretching device to the stomach wall. In another embodiment, the stretching device comprises at least one expandable body adapted to be invaginated by a portion of the patient's stomach wall, and the operation device comprises a fluid reservoir, which is in fluid communication with a chamber of the body. The operation device is non-invasively operable to distribute fluid from the fluid reservoir to the chamber of the body to expand the body such that the stomach wall portion is stretched, when the body is invaginated. The fluid reservoir may be operated by manually pressing it. The operation device may comprise a reverse servo, wherein a small volume of fluid in the fluid reservoir is compressed with a higher force and the chamber of the body creates a movement of a larger total volume with less force per unit of volume. The fluid reservoir may be placed subcutaneously or in the abdomen, and may be regulated by moving a wall of the reservoir, for example by a motor. Alternatively, a pump may be provided for pumping fluid or air from the reservoir to the body's chamber. The term "reversed servo means" encompasses the definition of an device that is controlled with a higher force and a small stroke i.e. for example movement of a small amount of fluid with a high force controls a larger amount of fluid moving by means of very smaller force, but may alternatively or additionally encompass the definition of a mechanism that transfers a strong force acting on a moving element having a short stroke into a small force acting on another moving element having a long stroke. The reversed servo means is preferably used when manual control of the device through intact skin is possible. In another embodiment the apparatus for treating a reflux disease and obesity comprises a large chamber in contact with one or more smaller chambers. The chambers are adapted to communicate with fluid or air being distributed between the chambers. A reversed servo for distributing fluid between the chambers may be provided, wherein a small volume of fluid in the large chamber is compressed with a higher force and the smaller chamber creates a movement of a larger total volume with less force per unit of volume. The large chamber may be adapted to be invaginated in the patient's fundus stomach wall to also treat reflux disease by restricting movement of the cardiac notch towards the diaphragm muscle of the patient, whereas the small chambers function as stretching devices to treat obesity. The large chamber may distribute fluid or air to the small chambers to cause them to expand and stretch the stomach fundus wall. In another embodiment, the stretching device comprises a mechanical stretching device, wherein a motor for mechanically regulating the stretching device may be provided. The mechanically regulated stretching device may be adapted to engage a first part of the stomach wall and a second part of the stomach, wherein the mechanically regulated stretching device comprises a joint mechanism adapted to be moved by the operation device. Alternatively, the stretching device may comprise a first engaging member adapted to engage a first part of the stomach wall and a second engaging member adapted to engage a second part of the stomach wall close to but spaced from the first stomach part, wherein the mechanical stretching device regulates the distance between the first and second parts of the stomach wall. As an alternative, the hydraulic means described above may be used for regulating such a mechanical stretching device by the hydraulic distribution of fluid or air.

The stretching device may be non-invasively adjustable postoperatively. The operation device for operating the stretching device may in its simplest form comprise a subcutaneous switch adapted to be non-invasively operated by manually pressing the switch for the operation of the stretching device. At least two operable stretching devices adapted to stretch at least two different portions of the stomach wall may be provided, wherein the apparatus is adapted to be postoperatively and non-invasively regulated. Specifically, the apparatus may be regulated from time to time such that at a first time one of the stretching devices stretches one of the portions of the stomach wall and at a second time the other of the stretching devices stretches the other portion of the stomach wall. In another embodiment, the stretching device comprises a body adapted to fill out a volume defined by wall portions of the stomach. The body suitably has rounded contours without too sharp edges that would be damaging to the patient's stomach wall. Where the body is to be invaginated it may have varying circumference to better be kept in place invaginated by stomach wall portions of the patient. The body may be shaped like an egg or like a kidney. Generally, any kind of mechanical construction may be used. Any mechanical construction driven mechanically or hydraulically or any pneumatic construction may be used. Any motor or any pump or moving material changing form when powered may be used to achieve the simple goal of stretching a part of the stomach wall by moving at least two parts of the stomach wall away from each other. Any kind of hydraulic operation may be used. It will be appreciated that instead of hydraulic operation; pneumatic operation can be used, wherein air instead of hydraulic fluid is moved between a reservoir and a chamber formed by the stretching device. Preferably the reservoir has a locking position to keep it in the desired position if it is handled by the patient. To compress the reservoir it preferably stays compressed and releases after pressing again. Any kind of hydraulic solution may be used for the stretching device. The hydraulic solution may be driven by both mechanically and powered with any motor or pump as well as manual. Of course, just expanding an in-vaginated part of the stomach also stretches away the stomach wall which also may be achieved both mechanically, hydraulically, pneumatically and both being powered with a motor or pump or by manual force.

[0061] The present invention also provides a system for a combined treatment of a reflux disease and obesity treatment system comprising an apparatus for treating obesity as described above. The system may comprise a subcutaneous electric switch adapted to manually and non-invasively control a function of the apparatus for treating obesity. The system may comprise a hydraulic device having a hydraulic reservoir, wherein the apparatus for treating obesity is adapted to non-invasively be regulated by manually pressing the hydraulic reservoir. The system may comprise a wireless remote control for controlling a function of the apparatus. The wireless remote control comprises at least one external signal transmitter and an internal signal receiver may be provided to be implanted in the patient. The wireless remote control is adapted to transmit at least one wireless control signal for controlling the apparatus. The wireless control signal may comprise a frequency, amplitude, or phase modulated signal or a combination thereof, and an analogue or a digital signal, or a combination of an analogue and digital signal. Alternatively, the wireless control signal comprises an electric or magnetic field, or a combined electric and magnetic field. The remote control may transmit a carrier signal for carrying the wireless control signal. The carrier signal may comprise digital, analogue or a combination of digital and analog signals. The remote control may transmit an electromagnetic carrier wave signal for carrying the digital or analog control signal. The system may comprise a wireless energy transmitter for non-invasively energizing the apparatus with wireless energy. The energy transmitter transmits energy by at least one wireless energy signal. The wireless energy signal may comprise a wave signal selected from the following: a sound wave signal, an ultrasound wave signal, an electromagnetic wave signal, an infrared light signal, a visible light signal, an ultra violet light signal, a laser light signal, a micro wave signal, a radio wave signal, an x-ray radiation signal and a gamma radiation signal. Alternatively, the wireless energy signal comprises an electric or magnetic field, or a combined electric and magnetic field. The wireless energy transmitter may transmit a carrier signal for carrying the wireless energy



signal. The carrier signal may comprise digital, analogue or a combination of digital and analog signals. The system may comprise an energy-transforming device for transforming the wireless energy from a first form into a second form energy. The energy-transforming device may directly during energy transfer operate the apparatus with the second form energy. The second form energy may comprise a direct current or pulsating direct current, or a combination of a direct current and pulsating direct current. The second form energy may comprise an alternating current or a combination of a direct and alternating current. An accumulator may be provided, wherein the second form energy is used at least partly to charge the accumulator. The energy of the first or second form may comprise magnetic energy, kinetic energy, sound energy, chemical energy, radiant energy, electromagnetic energy, photo energy, nuclear energy or thermal energy. One of the energy of the first form and the energy of the second form may be non-magnetic, non-kinetic, non-chemical, non-sonic, non-nuclear or non-thermal. The system may comprise an energy source adapted to power the apparatus. The energy source may comprise an internal energy source adapted to receive energy from an external energy source transmitting energy in a wireless mode. The internal energy source is charged by the energy in the wireless mode.

[0062] The system may comprise a feedback device for sending information from inside the patient's body to the outside thereof to give feedback information related to a functional parameter. The system may comprise a sensor sensing a parameter, such as a functional parameter of the system, which is correlated to the transfer of energy for charging an internal energy source. An internal control unit may be provided for controlling the operation device of the apparatus in response to the sensor sensing a functional parameter. Alternatively, sensor senses a physical parameter of the patient. The physical parameter may be one of body temperature, blood pressure, blood flow, heartbeats and breathing. The physical parameter sensor may be a pressure or motility sensor, or a sensor sensing measure, bending, stretching or food intake. The internal control unit may control the operation device in response to the sensor sensing the physical parameter. An internal control unit may be provided for receiving information from the sensor. The operation device of the apparatus may comprise a motor or a pump. Specifically, the operation device may comprise an electric motor. The operation device may be electrically powered, may be a hydraulic operation device or may be a pneumatic operation device. The transmitted energy, directly in its wireless form may affect the operation device to create kinetic energy to operate the stretching device of the apparatus during energy transfer. The system may comprise a feedback device for sending information from inside the patient's body to the outside thereof to give feedback information related to a functional parameter. The system may comprise an external data communicator and an implantable internal data communicator communicating with the external data communicator, wherein the internal communicator is adapted to feed data related to the apparatus for treating obesity or the patient back to the external data communicator or the external data communicator feeds data to the internal data communicator. The system may comprise implantable electrical components including at least one voltage level guard and/or at least one constant current guard.

[0063] The present invention also provides methods of treating a patient suffering from both a reflux disease and obesity. The methods can be performed together with or in conjunction with earlier described abdominal or intraluminal methods of treating a reflux disease. The invention provides methods listed below: [0064] a) A method for surgically treating an obese patient, the method comprising the steps of: [0065] cutting an opening in the abdominal wall of the patient, [0066] dissecting an area around the stomach, [0067] placing an apparatus for treating obesity as described above, engaging the stomach wall of the patient, and [0068] suturing the stomach wall. [0069] The method may further comprise the additional step of: [0070] postoperatively regulating the stretching device to stretch a part of the stomach wall to affect the appetite of the patient, wherein the step of regulating the stretching device is controlled from outside the patient's body. [0071] The method may further comprise the additional steps of: [0072] placing an additional

apparatus for treating obesity as described above, engaging the stomach wall of the patient, [0073] stretching a first part of the stomach wall by means of the apparatus for treating obesity, and [0074] stretching a second part of the stomach wall by means of the additional apparatus for treating obesity. [0075] b) A method for surgically placing an apparatus for treating obesity in a patient via a laparoscopic abdominal approach, the method comprising the steps of: [0076] inserting a needle or a tube like instrument into the abdomen of the patient's body, [0077] using the needle or a tube like instrument to fill the patient's abdomen with gas thereby expanding the patient's abdominal cavity, [0078] placing at least two laparoscopic trocars in the patient's body, [0079] inserting a camera through one of the laparoscopic trocars into the patient's abdomen, [0080] inserting at least one dissecting tool through one of the at least two laparoscopic trocars and dissecting an intended placement area of the patient, and [0081] placing an apparatus for treating obesity as described above, engaging the stomach wall. [0082] c) A method of using the system for treating obesity as described above, comprising the step of regulating the stretching device postoperatively to stretch a portion of the stomach wall to affect the appetite of the patient, wherein the step of regulating the stretching device is performed non-invasively. The stretching device comprises a mechanical or hydraulic stretching device. The hydraulic stretching device may comprise a reservoir, for moving gel or gas or fluid to or from the stretching device. The reservoir may be placed subcutaneously for being reached by the patients hand for moving fluid manually to or from the stretching device. The stretching device may be powered by an internal energy source for stretching or releasing the stretching device, wherein by means of a control device controlling the power from an internal control unit or from the outside the patient's body. A wireless energy transmitter for wireless transfer of energy powers the operation device to get the stretching device to directly during energy transfer cause the stretching device to stretch the stomach wall. A wireless energy transmitter for wireless transfer of energy charges the internal energy source. A reversed servo may be provided, wherein moving, in a closed hydraulic system, a small amount of fluid, a larger movement of fluid is achieved in a second larger closed hydraulic system, wherein the small amount of fluid is moved with by a higher force per area unit than the large volume. An invaginated stretching device in the fundus stomach wall of the patient is adapted to be adjustable, wherein the stretching device placed invaginated in the stomach fundus wall is adapted to be adjusted and stretching the stomach fundus wall thereby creating satiety.

[0083] The method may further comprise sending feedback information from inside the body to the outside thereof to give feedback related to the functional parameters of the device. Alternatively, the method may further comprise sending feedback information from inside the body to the outside thereof to give feedback related to the physical parameters of the patient. The functional parameter of the device may be correlated to the transfer of energy for charging the internal energy source. The device is programmable from outside the patient's body.

[0084] The method may further comprise the steps of: [0085] sensing a physical parameter of the patient or a functional parameter of the device, and [0086] sending sensing information to a control unit adapted for regulating the stretching device.

[0087] The method may further comprise the steps of: [0088] sensing a physical parameter of the patient or a functional parameter of the device, and [0089] sending sensing information to a control unit adapted for regulating the charging of the internal energy source.

[0090] The method may further comprise subcutaneously placing a reversed servo having a small control reservoir and moving a small volume from the control reservoir with a higher force per area unit, creating a larger movement of the stretching device with less force per area unit.

[0091] The method may further comprise performing the non-invasive regulation by manually pressing a subcutaneous switch.

[0092] The method may further comprise performing the non-invasive regulation by a wireless remote control.

[0093] The method may further comprise performing the non-invasive regulation by a wireless

energy transmitter.

[0094] The method may further comprise powering the apparatus for treating obesity by an internal energy source.

[0095] The method may further comprise powering the apparatus for treating obesity by an external energy source transmitting wireless energy, wherein the energy source comprises an external energy source transmitting wireless energy.

[0096] The method may further comprise transmitting wireless energy from an external energy source to charge a rechargeable internal energy source. [0097] d) A method of using an apparatus as described above, wherein the stretching device comprises a main body including a large chamber in contact with one or more smaller reservoirs/chambers adapted to stretch the stomach wall, wherein the chambers are adapted to communicate with fluid or air being moved between the chambers.

[0098] e) A method of using an apparatus as described above, wherein the large chamber are adapted to, with its main volume to be the stretching device's most important volume and wherein, the small chambers are as the stretching devices stretching the stomach wall to treat obesity, wherein the main chamber is communicating with fluid or gel to the small chambers causing the stretching effect in the stomach fundus wall thereby treating obesity. [0099] f) A method of using an apparatus as described above, comprising treating reflux disease by invaginating the large chamber with its main volume in the fundus stomach wall thereby restricting movement of the stomach notch towards the diaphragm muscle of the patient, and stretching the stomach fundus wall using the small chambers, communicating with fluid or air from the large chamber to the small chambers causing a stretching effect in the stomach fundus wall thereby treating obesity.

[0100] In another aspect, the invention relates an apparatus to treat a reflux device and/or obesity of a patient having a stomach with a food cavity. The apparatus generally comprises at least one volume filling device adapted to be at least substantially invaginated by a stomach wall portion of the patient, wherein the volume filling device is adapted to be placed on the outside of the stomach wall, so that the volume of the food cavity is reduced in size by a volume substantially exceeding the volume of the volume filling device, wherein the surface of the volume filling device comprises a biocompatible material, wherein a substantial part of the surface of the volume filling device is adapted to rest against the outside of the stomach wall, and wherein the volume filling device has a maximum circumference of at least 30 millimeters. The apparatus preferably comprises a volume filling device comprising an inflatable device expandable to an expanded state. The inflatable device, preferably has an inlet port for a fluid or a gel and is adapted to be connected to a gastroscopic instrument. The inlet port preferably comprises a fluid connection adapted to interconnect the volume filling device and the gastroscopic instrument. The volume filling device has an elongated shape. Alternatively, the volume filling device has a rounded shape, or a bent or curved shape. The volume filling device, preferably comprises an elastic material. The volume filling device, preferably comprises a bio-compatible material. Preferably, the volume filling device comprises silicone. The volume filling device can be provided with a coating of one or multiple layers, such as a Parylene coating, a polytetrafluoroethylene coating, or a polyurethane coating. The volume filling device comprises a fluid that is adapted to be transformed into solid state or fixed form. In one example the fluid is liquid polyurethane. In another example, the fluid is isotonic. In another example, the fluid comprises large molecules to prevent diffusion. In another example, the fluid comprises iodine molecules. The volume filling device comprises a homogenous material. The volume filling device can be a solid body, it can comprise an enclosure wall defining a chamber, it can comprise a rigid outer surface, it can comprise an elastic outer surface, and it can comprise a flexible outer surface. The volume filling device preferably has a maximum circumference of at least 50 millimeters, more preferably a circumference of at least 80 millimeters. The volume filling device, preferably has a volume of between  $0.00001$  and  $0.001 \text{ m}^3$ , more preferably a volume of between  $0.00001$  and  $0.0002 \text{ m}^3$ . Preferably, the volume filling device is deformable to a maximum diameter, so as to be inserted into a laparoscopic trocar. The volume

filling device is adapted to be kept in place by stomach-to-stomach sutures or staples to invaginate the device in the stomach wall. The stomach-to-stomach sutures or staples are provided with fixation portions exhibiting a structure adapted to be in contact with the stomach wall to promote growth in of human tissue to secure the long term placement of the volume filling device attached to the stomach wall. The structure preferably comprises a net like structure. The volume filling device is adapted to be non-invasively adjustable postoperatively. In one embodiment, the volume filling device has varying circumference to be better adapted to be kept in place invaginated in the stomach wall of the patient. The apparatus according to can further comprise a stretching device placed outside the stomach wall and adapted to stretch a part of the stomach wall, thereby affecting the patient's appetite, the apparatus further comprising a fluid connection interconnecting the stretching device and the volume filling device. In one embodiment, the volume filling device is adapted to be placed outside the stomach wall via a gastroscopic instrument. In one embodiment, the volume filling device comprises at least two interconnectable portions, and wherein the volume filling device is adapted to be placed outside the stomach wall as separate portions. In one embodiment, an outer surface layer of the volume filling device comprises polyurethane, Teflon®, or PTFE, or a combination thereof. In one embodiment, the volume filling device is adapted to be destroyed by acid, preferably hydrochloric acid. In one embodiment, the volume filling device comprises gel, preferably, the gel has a shore value of less than 15. In one embodiment, the volume filling device comprises an attachment device adapted to co-operate with a gripping instrument. In one embodiment, the volume filling device is adapted to be completely invaginated by the stomach wall of the patient. The apparatus can further comprise a fixating device adapted to fixate the food intake reducing device to the stomach wall to keep the volume filling device in place, when the volume filling device is implanted. The volume filling device has a volume of less than  $0.0002 \text{ m}^3$ , preferably, a volume of between  $0.0001$  and  $0.001 \text{ m}^3$ . In one embodiment, the volume filling device is adapted to be un-destroyed by acid, preferably hydrochloric acid. Preferably, the volume filling device has a circumference of at least 120 mm, more preferably, of at least 150 mm, still more preferably of at least 180 mm, and even more preferably, a circumference of at least 220 mm. The volume filling device, preferably comprises a flexible non-elastic material. The apparatus preferably comprises a volume filling device which comprises a fixation device adapted to be involved in the fixation of the device to the stomach wall. In one embodiment, the volume filling device comprises two or more fixation devices adapted to be involved in the fixation of the device to the stomach wall. In one embodiment, the volume filling device comprises a holding device adapted to be able to be held by an instrument and simplify the implantation of the device. In one embodiment, the volume filling device comprises two or more holding devices adapted to be able to be held by an instrument and simplify the implantation of the device. In one embodiment, the volume filling device comprises at least one tube connected to the device. In one embodiment, the volume filling device comprises an injection port for connecting to said tube.

[0101] The so described apparatus to treat a reflux device and/or obesity of a patient comprising at least one volume filling device can be combined with any feature disclosed in previous sections, such as, but not limited to the stretch cardia stimulation devices. It is also conceived that the so described apparatus to treat a reflux device and/or obesity of a patient comprising at least one volume filling device can be implanted by generally employing the abdominal or intraluminal methods as outlined in previous sections of this document and that suitable features of the earlier described movement restriction device can be employed with the volume filling device.

[0102] It should be noted that any embodiment or part of embodiment or feature or method or associated system or part of system described herein may be combined in any combination.

---

## Description

## BRIEF DESCRIPTION OF THE DRAWINGS

[0103] The present invention will now be described in more detail by way of non-limiting examples, and with reference to the accompanying drawings, in which:

[0104] FIGS. **1A-C** are schematic views of various embodiments of an apparatus for treating Gastroesophageal Reflux Disease implanted in a human patient.

[0105] FIGS. **2A-B** are schematic views of various embodiments of an apparatus for treating Gastroesophageal Reflux Disease implanted in a human patient.

[0106] FIGS. **3A-B** are schematic views of various embodiment of an apparatus for treating Gastroesophageal Reflux Disease implanted in a human patient.

[0107] FIGS. **4A-D** are schematic views of embodiments of an apparatus for treating Gastroesophageal Reflux Disease and obesity implanted in a human patient.

[0108] FIGS. **5a** and **b** are a schematic views of an embodiment of an apparatus for treating Gastroesophageal Reflux Disease implanted in a human patient.

[0109] FIGS. **6A-G** and **7-9** show alternative shapes of a movement restriction device for treating Gastroesophageal Reflux Disease adapted to be implanted in a human patient.

[0110] FIG. **10** is an overall view of a patient with an implanted movement restriction device for treating Gastroesophageal Reflux Disease.

[0111] FIGS. **11-27** are schematic views of various ways of powering an apparatus for treating Gastroesophageal Reflux Disease.

[0112] FIGS. **28-34** are schematic views of various ways of arranging the hydraulic or pneumatic powering of an apparatus of the invention for treating Gastroesophageal Reflux Disease.

[0113] FIG. **35** is a flowchart illustrating steps performed when implanting a movement restriction device for treating Gastroesophageal Reflux Disease.

[0114] FIGS. **36-41** shows methods for restoring the location of the cardia and the fundus in a patient suffering from reflux disease.

[0115] FIGS. **42-46** show different shapes and features of a reflux treatment device comprised in an apparatus according to the invention,

[0116] FIGS. **47a-d** show a deflated inflatable reflux treatment device comprised in an apparatus according to the invention and an instrument for placing the reflux treatment device on the outside of the stomach wall of the patient.

[0117] FIGS. **48a-i** illustrate different steps of invaginating the inflatable device of FIG. **47a** on the outside of a stomach wall of a patient,

[0118] FIG. **49** shows an embodiment wherein the reflux treatment apparatus is also adapted to treat obesity.

[0119] FIGS. **50-51** show an embodiment wherein the reflux treatment apparatus adapted also for treating obesity

[0120] FIGS. **52a-h** illustrate different steps of invaginating the inflatable device of FIG. **47a** on the inside of a stomach wall of a patient,

[0121] FIG. **53 a-c** show an instrument for creating an invagination of the wall of the stomach.

[0122] FIGS. **54-55** show an abdominal method for treating reflux disease.

## DETAILED DESCRIPTION

[0123] FIG. **1A** is a schematic view depicting an apparatus **11**, including a movement restriction device **10** of a biocompatible material, for treating reflux disease, in accordance with the invention, implanted in a human patient. In FIG. **1A**, the device is invaginated in the fundus. The device **10** comprises a body **13** having an outer surface **15** suitable for resting against a portion of the outside wall **16a** of the stomach fundus wall **16** in a position between the patient's diaphragm **18** and at least a portion of the lower part of the invaginated stomach fundus wall **16**. Thus, with the device **10** invaginated in this fashion, movement of the cardiac notch of the patient's stomach towards the patient's diaphragm is restricted, thereby the cardia is prevented from sliding through the patient's

diaphragm opening into the patient's thorax **20** and the supporting pressure against the patient's cardia sphincter muscle exerted from the patient's abdomen is maintained

[0124] The body **13** is inflatable and adapted to be inflated with a gel or fluid. A fluid or gel receiving member for receiving fluid to inflate said movement restriction device may be provided. Alternatively, the body **13** includes a homogenous material and be a solid body. Alternatively, the body **13** includes an outer wall in the form of an enclosure wall defining a chamber. The outer wall may be rigid, elastic or flexible. Where the outer wall is rigid, it is rigid enough to maintain non-deformed when subject to forces created by stomach movements.

[0125] The body **13** of the movement restriction device **10** can be affixed to the wall **16a** of the fundus **16** in a number of different ways. In the embodiment shown in FIG. **1A**, the device **10** is invaginated in the fundus stomach wall from outside the stomach. After invagination, a first fixation device consisting of a number of stomach-to-stomach sutures or staples **22a** is applied to keep the invagination in tact in the short term. This allows the growth of human tissue to keep the invagination intact over the long term.

[0126] There may optionally be a second fixation device consisting of a number of sutures or staples **22b** that are provided between the wall **16a** of the fundus **16** and the wall **24a** of the oesophagus **24** to hold the device **10** in said position between the patient's diaphragm **18** and at least a portion of the lower part of the invaginated stomach fundus wall **16a**. Thus, the device **10** is affixed in this position by this second fixation apparatus. A direct or indirect affixation of the device **10** to the diaphragm muscle **18** or associated muscles may be provided. As an alternative, a direct or indirect affixation of the device **10** to the oesophagus **24** can be provided. Alternatively, or additionally, there may be a third fixation device in the form of sutures or staples **22c** provided between the wall **16a** of the fundus **16** and the diaphragm **18** to hold the device **10** in said position.

[0127] FIG. **1B** shows an embodiment substantially similar to the one shown in FIG. **1A**.

[0128] In FIG. **1B** the body **13** and invagination are, in addition to the affixation **22**, fixed by means of sutures and/or staples **22c** between the reflux body **13** and the diaphragm **18**, to hold the device in position above the cardia **14**.

[0129] FIG. **1C** shows another embodiment substantially similar to the one shown in FIG. **1A**. In FIG. **1C** the reflux treatment device is held in place by stomach-to-stomach sutures or staplers **22a** that connects the wall **16a** of the fundus **16** to the wall **16a** of the fundus **16**. In addition the reflux treatment device **10** is held in place by sutures **22b** or staplers from the wall **16** of the fundus **16a** to the wall of the esophagus **24a**, and by sutures or staples from the wall of the fundus **16a** to the diaphragm.

[0130] An alternative embodiment of an apparatus **17** for the treatment of reflux disease in accordance with the invention is depicted in FIG. **2A**. This embodiment is, in many aspects, similar to the one described above with reference to FIG. **1A-C**. Thus, a movement restriction device **10** is shown implanted in a human patient and invaginated in the fundus. However, in the embodiment shown in FIG. **2A**, the device **10** is invaginated from the inside of the stomach, instead of from outside of the stomach, as in FIG. **1A-C**. The movement restriction device **10** comprises a body **13** adapted to rest against a portion of the inside wall of the stomach fundus wall **16** in a position between the patient's diaphragm **18** and at least a portion of the lower part of the invaginated stomach fundus wall **16**. In this embodiment, the body **13** is situated above the cardia area **14** of a standing human or animal mammal patient. The body **13** of the device **10** is shaped to rest against the wall **16a** of the fundus **16**, and further, has an outer surface **15** suitable to rest against this fundus wall. Thus, with the device **10** invaginated in this fashion as described above in connection with FIG. **1A**, movement of the cardiac notch of the patient's stomach towards the patient's diaphragm is restricted, thereby the cardia is prevented from sliding through the patient's diaphragm opening into the patient's thorax **20** and the supporting pressure against the patient's cardia sphincter muscle exerted from the patient's abdomen is maintained.

[0131] After invagination, a number of stomach-to-stomach sutures or staples **33a** comprising a

first fixation device are applied from inside the stomach **16** to keep the invagination in tact in the short term. This allows the growth of human tissue, keeping the invagination in tact over the long term. Additional sutures or staples **22b** comprising a second fixation device can be provided between a wall portion **16b** of the fundus **16** forming part of the invagination of the device **10** and the wall **24a** of the oesophagus **24** to hold the device **10** in said position. Similarly, a third fixation device in the form of sutures or staples **22c** can be provided between another wall portion **16c** of the fundus **16** forming part of the invagination of the device **10** and the diaphragm **18** to hold the device **10** in said position.

[0132] An alternative embodiment is shown in FIG. 2B. This embodiment is in many aspects similar to the one described with reference to FIG. 2A. However, here the sutures and staples **22b** and **33a** are all connected to the fixator of the reflux treatment device **10**. This embodiment lacks stomach-to-diaphragm sutures or staples.

[0133] An alternative apparatus **19** for the treatment of reflux disease is depicted in FIG. 3A. This alternative is in many aspects similar to the ones described above with reference to FIGS. 1A-C and 2 A-B. Thus, a movement restriction device **10** is shown implanted in a human patient. The device **10** comprises a body **13** adapted to rest against a portion of the stomach fundus wall **16** in a position between the patient's diaphragm **18** and stomach fundus wall **16**. However, in this alternative, the device is not invaginated in the stomach **16**. Instead, the affixation of the device **10** comprises an attachment structure **10a**, preferably a net like-structure that is adapted to be in contact with the fundus stomach wall **16a** to promote the growth of human tissue to secure long term placement of the reflux disease treatment device attached to the stomach wall. In the short term, a first fixation device in the form of sutures or staples **44a** may be provided between the attachment structure **10a** and the fundus wall **16a** to keep the attachment structure **10a** in place.

[0134] The attachment structure **10a** may be adapted for a second fixation device in the form of sutures or staples **44b** that are provided between the wall **16a** of the fundus **16** and the wall **24a** of the oesophagus **24** to hold the device **10** in said position between the patient's diaphragm **18** and stomach fundus wall **16**. Similarly, the attachment structure **10a** may also be adapted for a third fixation device in the form of sutures or staples **44c** that are provided between the wall **16a** of the fundus **16** and the diaphragm **18**, again, to hold the device **10** in said position.

[0135] An alternative embodiment is shown in FIG. 3B. This embodiment is in many aspects similar to the one described with reference to FIG. 3A. In this embodiment, the reflux treatment device **10** is, like in FIG. 2A-B invaginated from the inside of the stomach. The attachment structure **10a** is positioned on the wall **16a** of the fundus **16** above and around the invagination created by the reflux treatment device **10**.

[0136] A alternative embodiment of an apparatus **21** for treatment of reflux disease in accordance with the invention is depicted in FIG. 4A. This embodiment is in many aspects similar to the one described above with reference to FIG. 1A-C. In FIG. 4A, a view of a device **10** for treatment of reflux disease in accordance with the invention is shown implanted in a human patient. In FIG. 4A, the movement restriction device is again invaginated in the fundus **16**. The device **10** comprises a body **13** having an outer surface **15** suitable for resting against a portion of the outside wall **16a** of the stomach fundus wall **16** in a position between the patient's diaphragm **18** and at least a portion of the lower part of the invaginated stomach fundus wall **16**. The body **13** is shaped to rest against the outside wall **16a** of the fundus **16**. Thus, with the device invaginated in this fashion, movement of the cardiac notch of the patient's stomach towards the patient's diaphragm is restricted, thereby the cardia is prevented from sliding through the patient's diaphragm opening into the patient's thorax **20** and the supporting pressure against the patient's cardia sphincter muscle exerted from the patient's abdomen is maintained.

[0137] In the embodiment of FIG. 4A, as in the embodiment of FIG. 1A, after invagination of the device **10** in the fundus **16**, a first fixation device consisting of a number of stomach-to-stomach sutures or staples **22a** is applied to keep the invagination in tact in the short term. A second fixation

device consisting of a number of sutures or staples **22b** is provided to hold the device **10** in said position between the patient's diaphragm **18** and at least a portion of the lower part of the invaginated stomach fundus wall **16**. Additionally, a third fixation device in the form of sutures or staples **22c** may be provided between the wall **16a** of the fundus **16** and the diaphragm **18**, again, to hold the device **10** in said position.

[0138] In the embodiment depicted in FIG. **4A**, the size of the movement restriction device can be regulated while being implanted. The device **10** is associated with a hydraulic reservoir **52** connected to the device **10** by a lead **52b**, whereby a non-invasive regulation can be performed by manually pressing the reservoir **52**. The device **10** is, in turn, connected to one or more smaller chambers **10b**.

[0139] Furthermore, the embodiment above may alternatively be used to also treat obesity. The apparatus may, in this embodiment, be adapted to treat obesity by using the volume of the movement restriction body **13** to contain a fluid, and further using one or more smaller chambers **10b** connected to the body **13** with a pump to be filled with fluid to stretch the fundus wall to create satiety. The small chambers **10b** are also adapted to be invaginated to in the fundus stomach wall, and when filled with fluid, an expansion occurs that results in human sensor feedback creating satiety. By placing the small hydraulic reservoir/pump subcutaneously in the patient, the patient is able to pump hydraulic fluid to fill the small chambers to feel full on request.

[0140] An alternative embodiment is shown in FIG. **4B**. This embodiment is substantially similar to the one shown in FIG. **4A** but differs in how the reflux treatment device and chambers **10b** are controlled. Here, the chambers **10b** are not controlled by a subcutaneous pump but a powered internal control unit **56**. The internal control unit **56** comprises means for the patient to control the device **10** in how it shall be used regarding treatment of reflux and/or obesity. It may also comprise means of supplying power to the device.

[0141] The internal control unit **56** may comprise a battery **70**, an electric switch **72**, a motor/pump **44**, a reservoir **52**, an injection port **1001**. An energy transmission device **34** with a remote control is adapted for controlling and powering the device. The items being selected depending on the circumstances, e.g. if the device is electrically, hydraulically, pneumatically or mechanically operated.

[0142] The control unit may receive input from any sensor **76**, specially a pressure sensor. Any type of sensor may be supplied. The internal control unit **56** preferable includes intelligence in forms of a FPGA or MCU or ASIC or any other circuit, component or memory (For a more extensive description see below under "system").

[0143] FIG. **4C** shows essentially the same as FIG. **4A** with the difference that there is one small chamber **10b** instead of two small chambers as in **4A**. FIG. **4C** shows the small chamber **10b** in its empty state whereas FIG. **4D** shows the small chambers **10b** when it has been filled and enlarged to create satiety.

[0144] Yet an alternative embodiment of an apparatus **23** for the treatment of reflux disease in accordance with the invention is depicted in FIG. **5A**. This embodiment is, again, in many aspects similar to the one described above with reference to FIG. **1A-C**. Thus, as in the embodiment of FIG. **1A**, a movement restriction device **10**, which is invaginated in the fundus, is comprised of a body **13** having an outer surface **15** suitable for resting against a portion of the outside wall **16a** of the stomach fundus wall **16** in a position between the patient's diaphragm **18** and at least a portion of the lower part of the invaginated stomach fundus wall **16**. The body **13** of the device **10** is shaped to rest against the outside wall **16a** of the fundus **16** and has a generally smooth outer surface **15** suitable for resting against this fundus wall. And, again, after invagination of the device **10** in the fundus **16**, a first fixation device consisting of a number of stomach-to-stomach sutures or staples **22a** is applied to keep the invagination in tact in the short term. A second fixation device consisting of a number of sutures or staples **22b** applied between the wall **16a** of the fundus **16** and the wall **24a** of the oesophagus **24** is provided to hold the device **10** in said position.



[0145] In the alternative embodiment shown in FIG. 5A, the apparatus **23** further comprises a stimulation device **26** for sending out stimulation pulses adapted to stimulate the cardia muscle to further close the cardia to additionally prevent reflux disease. The apparatus **23** comprises at least one conductor **26a** and at least one electrode **26b** adapted to receive the stimulation pulses.

[0146] The stimulation device **26** preferably comprises an electronic circuit and an energy source, which in the preferred embodiment is provided in the device **10**.

[0147] The stimulation device **26** preferably sends stimulation pulses as a train of pulses, wherein the pulse train is adapted to be repeated with a time break in between, the break extending the break between each pulse in the pulse train.

[0148] FIG. 5B shows essentially the same embodiment as in FIG. 5A, with the addition of an internal control unit **56**, a remote control **28** and an external energy transmission device **34**. The internal control unit **56** is connected to the stimulation device with a power lead **56b**. The internal control unit **57** may comprise a battery **70** and an electric switch **72** and other components described below under “system”.

[0149] The reflux disease treatment device **10** can, in accordance with one embodiment of the present invention, be formed as a generally egg shaped body, as is shown in FIG. 6A. The reflux disease treatment device **10** can, in accordance with another embodiment of the present invention, also be formed as an egg or sphere shaped body with an indent in its middle, as is shown in FIG. 6B. The reflux disease treatment device **10** can, in accordance with yet another embodiment of the present invention, further be formed as a slightly bent egg shaped body as shown in FIG. 6C.

[0150] The reflux disease treatment device **10** can, in accordance with a further embodiment of the present invention, be formed as a generally spherically-shaped body, as shown in FIG. 6D.

[0151] As discussed above, the reflux treatment device **10** is fixed in a position which is above the esophagus in a standing patient. To enable this, one embodiment of the reflux treatment shown in FIG. 7 comprises a fixator **10d** that may, for example, serve as an attachment point for sutures or staples. The fixator may be a loop or a ridge with or without holes or have any other shape that makes it suitable for fixating the reflux treatment device **10**.

[0152] FIG. 8 show an embodiment of the reflux treatment device **10** where it is adjustable by a hydraulic means, and **10e** is an injection port where hydraulic fluid can be in order to expand the device. Alternatively, in one embodiment the reflux treatment device **10** can be inflated from a small size to a larger size during a surgical procedure where it is advantageous that the device is initially of small size, for example during a laparoscopic procedure. In such an embodiment, any filling material, solid, liquid or gas may be injected through the injection port **10e** in order for the reflux treatment device **10** to achieve its final shape.

[0153] FIG. 9 shows an embodiment where the reflux treatment device **10** has a sunken ridge **10f** adapted to being held with a surgical tool. This is to be used, for example, during a surgical procedure when the reflux treatment device is implanted.

[0154] When the reflux disease treatment device **10** is generally spherical, whereby it can be made to wholly or partly encompass the esophagus, the inner diameter D of the reflux disease treatment device **10**, is preferably such that it can encompass the esophagus and at least a part of the fundus so that the device does not rest directly against the wall of the esophagus when implanted.

[0155] The movement restriction device **10** may take any form that enables the device **10** to rest in a position in which movement of the cardiac notch of the patient's stomach towards the patient's diaphragm is restricted, thereby the cardia is prevented from sliding through the patient's diaphragm opening into the patient's thorax and the supporting pressure against the patient's cardia sphincter muscle exerted from the patient's abdomen is maintained

System

[0156] An energy and operation system, generally designated **28**, to be incorporated in the apparatus according to the invention, will now be described with reference to FIGS. 10-27.

[0157] The system **28** shown in FIG. 10 comprises an internal energy source in the form of an

implanted energy transforming device **30** adapted to supply energy consuming components of the reflux disease treatment apparatus with energy via a power supply line **32**. An external energy transmission device **34** includes a wireless remote control transmitting a wireless signal, which is received by a signal receiver which may be incorporated in the implanted energy transforming device **30**, or be separate. The implanted energy transforming device **30** transforms energy from the signal into electric energy which is supplied via the power supply line **32**.

[0158] The system **28** of FIG. **10** is shown in a more generalized block diagram form in FIG. **11**, wherein the patient's skin **36**, generally shown by a vertical line, separates the interior of the patient **29** to the right of the line from the exterior to the left of the line.

[0159] FIG. **11** shows a simplified block diagram showing the movement restriction device **10**, the energy transforming device **30** powering the device **10** via power supply line **32**, and the external energy transmission device **34**.

[0160] FIG. **12** shows an embodiment of the invention identical to that of FIG. **11**, except that a reversing device in the form of an electric switch **38** operable by polarized energy also is implanted in the patient **29** for reversing the device **10**. The wireless remote control of the external energy transmission device **34** transmits a wireless signal that carries polarized energy and the implanted energy transforming device **30** transforms the wireless polarized energy into a polarized current for operating the electric switch **38**. When the polarity of the current is shifted by the implanted energy transforming device **30** the electric switch **38** reverses the function performed by the device **10**.

[0161] FIG. **13** shows an embodiment of the invention identical to that of FIG. **11**, except that an operation device **40** implanted in the patient for regulating the reflux disease treatment device **10** is provided between the implanted energy transforming device and the device **10**. This operation device can be in the form of a motor **40**, such as an electric servomotor. The motor **40** is powered with energy from the implanted energy transforming device **30**, as the remote control of the external energy transmission device **34** transmits a wireless signal to the receiver of the implanted energy transforming device **30**.

[0162] FIG. **14** shows an embodiment of the invention identical to that of FIG. **11**, except that it also comprises an operation device in the form of an assembly **42** including a motor/pump unit **78** and a fluid reservoir **46** is implanted in the patient. In this case the device **10** is hydraulically operated, i.e. hydraulic fluid is pumped by the motor/pump unit **44** from the fluid reservoir **46** through a conduit **48** to the device **10** to operate the device, and hydraulic fluid is pumped by the motor/pump unit **44** back from the device **10** to the fluid reservoir **46** to return the device **10** to a starting position. The implanted energy transforming device **30** transforms wireless energy into a current, for example a polarized current, for powering the motor/pump unit **44** via an electric power supply line **50**.

[0163] Instead of a hydraulically operated movement restriction device **10**, it is also envisaged that the operation device comprises a pneumatic operation device. In this case, pressurized air can be used for regulation and the fluid reservoir is replaced by an air chamber and the fluid is replaced by air.

[0164] In all of these embodiments the energy transforming device **30** may include a rechargeable accumulator like a battery or a capacitor to be charged by the wireless energy and supplies energy for any energy consuming part of the apparatus.

[0165] The external energy transmission device **34** is preferably wireless and may include a remotely controlled control device for controlling the device **10** from outside the human body.

[0166] Such a control device may include a wireless remote control as well as a manual control of any implanted part to make contact with by the patient's hand most likely indirect for example a button to press placed under the skin.

[0167] FIG. **15** shows an embodiment of the invention comprising the external energy transmission device **34** with its wireless remote control, the device **10**, in this case hydraulically operated, and the implanted energy transforming device **30**, and further comprising a hydraulic fluid reservoir **52**,

a motor/pump unit **44** and an reversing device in the form of a hydraulic valve shifting device **54**, all implanted in the patient. Of course the hydraulic operation could easily be performed by just changing the pumping direction and the hydraulic valve may therefore be omitted. The remote control may be a device separated from the external energy transmission or included in the same. The motor of the motor/pump unit **44** is an electric motor. In response to a control signal from the wireless remote control of the external energy transmission device **34**, the implanted energy transforming device **30** powers the motor/pump unit **44** with energy from the energy carried by the control signal, whereby the motor/pump unit **44** distributes hydraulic fluid between the hydraulic fluid reservoir **52** and the device **10**. The remote control of the external energy transmission device **34** controls the hydraulic valve shifting device **54** to shift the hydraulic fluid flow direction between one direction in which the fluid is pumped by the motor/pump unit **44** from the hydraulic fluid reservoir **52** to the device **10** to operate the device **10**, and another opposite direction in which the fluid is pumped by the motor/pump unit **44** back from the device **10** to the hydraulic fluid reservoir **52** to return the device **10** to a starting position.

[0168] FIG. **16** shows an embodiment of the invention identical to that of FIG. **15**, except that an internal control unit **56** controlled by the wireless remote control of the external energy transmission device **34**, an accumulator **58** and a capacitor **60** also are implanted in the patient. The internal control unit **56** arranges storage of electric energy received from the implanted energy transforming device **30** in the accumulator **58**, which supplies energy to the device **10**. In response to a control signal from the wireless remote control of the external energy transmission device **34**, the internal control unit **56** either releases electric energy from the accumulator **58** and transforms the released energy via power lines **62** and **64**, or directly transforms electric energy from the implanted energy transforming device **30** via a power line **66**, the capacitor **60**, which stabilizes the electric current, a power line **68** and the power line **64**, for the operation of the device **10**.

[0169] The internal control unit is preferably programmable from outside the patient's body. In a preferred embodiment, the internal control unit is programmed to regulate the device **10** to stretch the stomach according to a pre-programmed time-schedule or to input from any sensor sensing any possible physical parameter of the patient or any functional parameter of the device.

[0170] In accordance with an alternative, the capacitor **60** in the embodiment of FIG. **16** may be omitted. In accordance with another alternative, the accumulator **58** in this embodiment may be omitted.

[0171] FIG. **17** shows an embodiment of the invention identical to that of FIG. **10**, except that a battery **70** for supplying energy for the operation of the device **10** and an electric switch **72** for switching the operation of the device **10** also are implanted in the patient. The electric switch **72** is operated by the energy supplied by the implanted energy transforming device **30** to switch from an off mode, in which the battery **70** is not in use, to an on mode, in which the battery **70** supplies energy for the operation of the device **10**.

[0172] FIG. **18** shows an embodiment of the invention identical to that of FIG. **16**, except that an internal control unit **56** controllable by the wireless remote control of the external energy transmission device **34** also is implanted in the patient. In this case, the electric switch **72** is operated by the energy supplied by the implanted energy transforming device **30** to switch from an off mode, in which the wireless remote control is prevented from controlling the internal control unit **56** and the battery is not in use, to a standby mode, in which the remote control is permitted to control the internal control unit **56** to release electric energy from the battery **70** for the operation of the device **10**.

[0173] FIG. **19** shows an embodiment of the invention identical to that of FIG. **17**, except that an accumulator **58** is substituted for the battery **70** and the implanted components are interconnected differently. In this case, the accumulator **58** stores energy from the implanted energy transforming device **30**. In response to a control signal from the wireless remote control of the external energy transmission device **34**, the internal control unit **56** controls the electric switch **72** to switch from an

off mode, in which the accumulator **58** is not in use, to an on mode, in which the accumulator **58** supplies energy for the operation of the device **10**.

[0174] FIG. **20** shows an embodiment of the invention identical to that of FIG. **18**, except that a battery **70** also is implanted in the patient and the implanted components are interconnected differently. In response to a control signal from the wireless remote control of the external energy transmission device **34**, the internal control unit **56** controls the accumulator **58** to deliver energy for operating the electric switch **72** to switch from an off mode, in which the battery **70** is not in use, to an on mode, in which the battery **70** supplies electric energy for the operation of the device **10**.

[0175] Alternatively, the electric switch **72** may be operated by energy supplied by the accumulator **58** to switch from an off mode, in which the wireless remote control is prevented from controlling the battery **70** to supply electric energy and is not in use, to a standby mode, in which the wireless remote control is permitted to control the battery **70** to supply electric energy for the operation of the device **10**.

[0176] It should be understood that the switch should be interpreted in its broadest embodiment. This means an FPGA or a DA converter or any other electronic component or circuit may switch power on and off preferably being controlled from outside the patient's body or by an internal control unit.

[0177] FIG. **21** shows an embodiment of the invention identical to that of FIG. **17**, except that a motor **40**, a mechanical reversing device in the form of a gear box **74**, and an internal control unit **56** for controlling the gear box **74** also are implanted in the patient. The internal control unit **56** controls the gear box **74** to reverse the function performed by the device **10** (mechanically operated). Even simpler is to switch the direction of the motor electronically.

[0178] FIG. **22** shows an embodiment of the invention identical to that of FIG. **20** except that the implanted components are interconnected differently. Thus, in this case, the internal control unit **56** is powered by the battery **70** when the accumulator **58**, suitably a capacitor, activates the electric switch **72** to switch to an on mode. When the electric switch **72** is in its on mode the internal control unit **56** is permitted to control the battery **70** to supply, or not supply, energy for the operation of the device **10**.

[0179] FIG. **23** schematically shows conceivable combinations of implanted components of the apparatus for achieving various communication options. Basically, there are the device **10**, the internal control unit **56**, motor or pump unit **44**, and the external energy transmission device **34** including the external wireless remote control. As already described above the wireless remote control transmits a control signal which is received by the internal control unit **56**, which in turn controls the various implanted components of the apparatus.

[0180] A feedback device, preferably in the form of a sensor **76**, may be implanted in the patient for sensing a physical parameter of the patient, such as a contraction wave in the oesophagus informing the patient is eating. The internal control unit **56**, or alternatively the external wireless remote control of the external energy transmission device **34**, may control the device **10** in response to signals from the sensor **76**. A transceiver may be combined with the sensor **76** for sending information on the sensed physical parameter to the external wireless remote control. The wireless remote control may comprise a signal transmitter or transceiver and the internal control unit **56** may comprise a signal receiver or transceiver. Alternatively, the wireless remote control may comprise a signal receiver or transceiver and the internal control unit **56** may comprise a signal transmitter or transceiver. The above transceivers, transmitters and receivers may be used for sending information or data related to the device **10** from inside the patient's body to the outside thereof.

[0181] Alternatively, the sensor **76** may be arranged to sense a functional parameter of the device **10**.

[0182] Where the motor/pump unit **44** and battery **70** for powering the motor/pump unit **44** are

implanted, the battery **70** may be equipped with a transceiver for sending information on the condition of the battery **70**. To be more precise, when charging a battery or accumulator with energy feed back information related to said charging process is sent and the energy supply is changed accordingly.

[0183] FIG. **24** shows an alternative embodiment wherein the device **10** is regulated from outside the patient's body. The system **28** comprises a movement restriction device connected to a battery **70** via a subcutaneous switch **80**. Thus, the regulation of the device **10** is performed non-invasively by manually pressing the subcutaneous switch, whereby the operation of the device **10** is switched on and off. It will be appreciated that the shown embodiment is a simplification and that additional components, such as an internal control unit or any other part disclosed in the present application can be added to the system.

[0184] FIG. **25** shows an alternative embodiment, wherein the system **28** comprises a movement restriction device **10** in fluid connection with a hydraulic fluid reservoir **52**. Non-invasive regulation is performed by manually pressing the hydraulic reservoir connected to the device **10**.

[0185] A further embodiment of a system to be incorporated in the apparatus according to the invention comprises a feedback device for sending information from inside the patient's body to the outside thereof to give feedback information related to at least one functional parameter of the movement restriction device or apparatus or a physical parameter of the patient, thereby optimizing the performance of the apparatus.

[0186] One preferred functional parameter of the device is correlated to the transfer of energy for charging the internal energy source.

[0187] In FIG. **26**, an arrangement is schematically illustrated for supplying an accurate amount of energy to a system **28** implanted in a patient, whose skin **36** is indicated by a vertical line. A movement restriction device **10** is connected to an implanted energy transforming device **30**, likewise located inside the patient, preferably just beneath the patient's skin **36**. Generally speaking, the implanted energy transforming device **30** may be placed in the abdomen, thorax, muscle fascia (e.g. in the abdominal wall), subcutaneously, or at any other suitable location. The implanted energy transforming device **30** is adapted to receive wireless energy **E** transmitted from an external energy source **34a** provided in the external energy transmission device **34** located outside the patient's skin **36** in the vicinity of the implanted energy transforming device **30**.

[0188] As is well known in the art, the wireless energy **E** may generally be transferred by means of any suitable Transcutaneous Energy Transfer (TET) device, such as a device including a primary coil arranged in the external energy source **34a** and an adjacent secondary coil arranged in the implanted energy transforming device **30**. When an electric current is fed through the primary coil, energy in the form of a voltage is induced in the secondary coil which can be used to operate a movement restriction device, e.g. after storing the incoming energy in an energy storing device or accumulator, such as a battery or a capacitor. However, the present invention is generally not limited to any particular energy transfer technique, TET devices or energy storing devices, and any kind of wireless energy may be used.

[0189] The amount of energy received inside the body to the device may be compared with the energy used by the device. The term used by the device is then understood to include also energy stored by the device. The amount of transferred energy can be regulated by means of an external control unit **34b** controlling the external energy source **34a** based on the determined energy balance, as described above. In order to transfer the correct amount of energy, the energy balance and the required amount of energy can be determined by means of an internal control unit **56** connected to the reflux disease treatment device **10**. The internal control unit **56** may thus be arranged to receive various measurements obtained by suitable sensors or the like, not shown, measuring certain characteristics of the **r10**, somehow reflecting the required amount of energy needed for proper operation of the device **10**. Moreover, the current condition of the patient may also be detected by means of suitable measuring devices or sensors, in order to provide parameters

reflecting the patient's condition. Hence, such characteristics and/or parameters may be related to the current state of the device **10**, such as power consumption, operational mode and temperature, as well as the patient's condition reflected by, e.g., body temperature, blood pressure, heartbeats and breathing.

[0190] Furthermore, an energy storing device or accumulator **58** may optionally be connected to the implanted energy transforming device **30** for accumulating received energy for later use by the device **10**. Alternatively or additionally, characteristics of such an accumulator, also reflecting the required amount of energy, may be measured as well. The accumulator may be replaced by a battery, and the measured characteristics may be related to the current state of the battery, such as voltage, temperature, etc. In order to provide sufficient voltage and current to the device **10**, and also to avoid excessive heating, it is clearly understood that the battery should be charged optimally by receiving a correct amount of energy from the implanted energy transforming device **30**, i.e., not too little or too much. The accumulator may also be a capacitor with corresponding characteristics.

[0191] For example, battery characteristics may be measured on a regular basis to determine the current state of the battery, which then may be stored as state information in a suitable storage means in the internal control unit **56**. Thus, whenever new measurements are made, the stored battery state information can be updated accordingly. In this way, the state of the battery can be “calibrated” by transferring a correct amount of energy, so as to maintain the battery in an optimal condition.

[0192] Thus, the internal control unit **56** is adapted to determine the energy balance and/or the currently required amount of energy, (either energy per time unit or accumulated energy) based on measurements made by the above-mentioned sensors or measuring devices on the reflux disease treatment device **10**, or the patient, or an energy storing device if used, or any combination thereof. The internal control unit **56** is further connected to an internal signal transmitter **82**, arranged to transmit a control signal reflecting the determined required amount of energy, to an external signal receiver **34c** connected to the external control unit **34b**. The amount of energy transmitted from the external energy source **34a** may then be regulated in response to the received control signal.

[0193] Alternatively, sensor measurements can be transmitted directly to the external control unit **34b** wherein the energy balance and/or the currently required amount of energy can be determined by the external control unit **34b**, thus integrating the above-described function of the internal control unit **56** in the external control unit **34b**. In that case, the internal control unit **56** can be omitted and the sensor measurements are supplied directly to the internal signal transmitter **82** which sends the measurements over to the external signal receiver **34c** and the external control unit **34b**. The energy balance and the currently required amount of energy can then be determined by the external control unit **34b** based on those sensor measurements.

[0194] Hence, the present solution employs the feed back of information indicating the required energy, which is more efficient than previous solutions because it is based on the actual use of energy that is compared to the received energy, e.g. with respect to the amount of energy, the energy difference, or the energy receiving rate as compared to the energy rate used by the device **10**. The device **10** may use the received energy either for consuming or for storing the energy in an energy storage device or the like. The different parameters discussed above would thus be used if relevant and needed and then as a tool for determining the actual energy balance.

[0195] However, such parameters may also be needed per se for any actions taken internally to specifically operate the device.

[0196] The internal signal transmitter **82** and the external signal receiver **34c** may be implemented as separate units using suitable signal transfer means, such as radio, IR (Infrared) or ultrasonic signals. Alternatively, the internal signal transmitter **82** and the external signal receiver **34c** may be integrated in the implanted energy transforming device **30** and the external energy source **34a**, respectively, so as to convey control signals in a reverse direction relative to the energy transfer, basically using the same transmission technique. The control signals may be modulated with

respect to frequency, phase or amplitude.

[0197] To conclude, the energy supply arrangement illustrated in FIG. **26** may operate basically in the following manner. The energy balance is first determined by the internal control unit **56**. A control signal reflecting the required amount of energy is also created by the internal control unit **56**, and the control signal is transmitted from the internal signal transmitter **82** to the external signal receiver **34c**. Alternatively, the energy balance can be determined by the external control unit **34b** instead depending on the implementation, as mentioned above. In that case, the control signal may carry measurement results from various sensors. The amount of energy emitted from the external energy source **34a** can then be regulated by the external control unit **34b**, based on the determined energy balance, e.g. in response to the received control signal. This process may be repeated intermittently at certain intervals during ongoing energy transfer, or may be executed on a more or less continuous basis during the energy transfer.

[0198] The amount of transferred energy can generally be regulated by adjusting various transmission parameters in the external energy source **34a**, such as voltage, current, amplitude, wave frequency and pulse characteristics.

[0199] A method is thus provided for controlling transmission of wireless energy supplied to an electrically operable reflux disease treatment device implanted in a patient. The wireless energy E is transmitted from an external energy source located outside the patient and is received by an internal energy receiver located inside the patient, the internal energy receiver being connected to the device **10** for directly or indirectly supplying received energy thereto. An energy balance is determined between the energy received by the internal energy receiver and the energy used for the device **10**. The transmission of wireless energy E from the external energy source is then controlled based on the determined energy balance.

[0200] A system is also provided for controlling transmission of wireless energy supplied to an electrically operable movement restriction device **10** implanted in a patient. The system is adapted to transmit the wireless energy E from an external energy source located outside the patient which is received by an implanted energy transforming device located inside the patient, the implanted energy transforming device being connected to the device **10** for directly or indirectly supplying received energy thereto. The system is further adapted to determine an energy balance between the energy received by the implanted energy transforming device and the energy used for the device **10**, and control the transmission of wireless energy E from the external energy source, based on the determined energy balance.

[0201] The functional parameter of the device is correlated to the transfer of energy for charging the internal energy source.

[0202] In yet an alternative embodiment, the external source of energy is controlled from outside the patient's body to release electromagnetic wireless energy, and released electromagnetic wireless energy is used for operating the device **10**.

[0203] In another embodiment, the external source of energy is controlling from outside the patient's body to release non-magnetic wireless energy, and released non-magnetic wireless energy is used for operating the device **10**.

[0204] Those skilled in the art will realize that the above various embodiments according to FIGS. **14-26** could be combined in many different ways. For example, the electric switch **38** operated polarized energy could be incorporated in any of the embodiments of FIGS. **12, 15-21**, the hydraulic valve shifting device **54** could be incorporated in the embodiment of FIG. **24**, and the gear box **74** could be incorporated in the embodiment of FIG. **33**. It should be noted that the switch simply could mean any electronic circuit or component.

[0205] Wireless transfer of energy for operating the movement restriction device **10** has been described to enable non-invasive operation. It will be appreciated that the device **10** can be operated with wire bound energy as well. One such example is shown in FIG. **26**, wherein an external switch **84** is interconnected between the external energy source **34a** and an operation

device, such as an electric motor regulating the device **10**, by means of power lines **86** and **88**. An external control unit **34b** controls the operation of the external switch to effect proper operation of the device **10**.

#### Hydraulic or Pneumatic Powering

[0206] FIGS. **28-31** show in more detail block diagrams of four different ways of hydraulically or pneumatically powering a movement restriction device according to the invention.

[0207] FIG. **28** shows a system for treating reflux disease as described above with. The system comprises a device **10** and further a separate regulation reservoir **46**, a one way pump **44** and an alternate valve **54**.

[0208] FIG. **29** shows the device **10** and a fluid reservoir **46**. By moving the wall of the regulation reservoir or changing the size of the same in any other different way, the adjustment of the device may be performed without any valve, just free passage of fluid any time by moving the reservoir wall.

[0209] FIG. **30** shows the device **10**, a two way pump **44** and the regulation reservoir **46**.

[0210] FIG. **31** shows a block diagram of a reversed servo system with a first closed system controlling a second closed system. The servo system comprises a regulation reservoir **46** and a servo reservoir **90**. The servo reservoir **90** mechanically controls a movement restriction device **10** via a mechanical interconnection **94**. The device **10** has an expandable/contactable cavity. This cavity is preferably expanded or contracted by supplying hydraulic fluid from the larger adjustable reservoir **92** in fluid connection with the device **10**. Alternatively, the cavity contains compressible gas, which can be compressed and expanded under the control of the servo reservoir **90**.

[0211] The servo reservoir **90** can also be part of the device itself.

[0212] In one embodiment, the regulation reservoir is placed subcutaneous under the patient's skin and is operated by pushing the outer surface thereof by means of a finger. This reflux disease treatment system is illustrated in FIGS. **32-c**. In FIG. **31**, a flexible subcutaneous regulation reservoir **46** is shown connected to a bulge shaped servo reservoir **90** by means of a conduit **48**. This bellow shaped servo reservoir **90** is comprised in a flexible movement restriction device **10**. In the state shown in FIG. **32**, the servo reservoir **90** contains a minimum of fluid and most fluid is found in the regulation reservoir **46**. Due to the mechanical interconnection between the servo reservoir **90** and the device **10**, the outer shape of the device **10** is contracted, i.e., it occupies less than its maximum volume. This maximum volume is shown with dashed lines in the figure.

[0213] FIG. **32** shows a state wherein a user, such as the patient in with the device is implanted, presses the regulation reservoir **46** so that fluid contained therein is brought to flow through the conduit **48** and into the servo reservoir **90**, which, thanks to its bellow shape, expands longitudinally. This expansion in turn expands the device **10** so that it occupies its maximum volume, thereby stretching the stomach wall (not shown), which it contacts.

[0214] The regulation reservoir **46** is preferably provided with means **46a** for keeping its shape after compression. This means, which is schematically shown in the figure, will thus keep the device **10** in a stretched position also when the user releases the regulation reservoir. In this way, the regulation reservoir essentially operates as an on/off switch for the reflux disease treatment system.

[0215] An alternative embodiment of hydraulic or pneumatic operation will now be described with reference to FIGS. **33** and **34**. The block diagram shown in FIG. **33** comprises with a first closed system controlling a second closed system. The first system comprises a regulation reservoir **46** and a servo reservoir **90**. The servo reservoir **90** mechanically controls a larger adjustable reservoir **92** via a mechanical interconnection **94**. A movement restriction device **10** having an expandable/contactable cavity is in turn controlled by the larger adjustable reservoir **92** by supply of hydraulic fluid from the larger adjustable reservoir **92** in fluid connection with the device **10**.

[0216] An example of this embodiment will now be described with reference to FIG. **34**. Like in the previous embodiment, the regulation reservoir is placed subcutaneous under the patient's skin



and is operated by pushing the outer surface thereof by means of a finger. The regulation reservoir **46** is in fluid connection with a bellow shaped servo reservoir **90** by means of a conduit **48**. In the first closed system **46, 48, 90** shown in FIG. **32a**, the servo reservoir **90** contains a minimum of fluid and most fluid is found in the regulation reservoir **46**.

[0217] The servo reservoir **90** is mechanically connected to a larger adjustable reservoir **92**, in this example also having a bellow shape but with a larger diameter than the servo reservoir **90**. The larger adjustable reservoir **92** is in fluid connection with the device **10**. This means that when a user pushes the regulation reservoir **46**, thereby displacing fluid from the regulation reservoir **46** to the servo reservoir **90**, the expansion of the servo reservoir **90** will displace a larger volume of fluid from the larger adjustable reservoir **92** to the device **10**. In other words, in this reversed servo, a small volume in the regulation reservoir is compressed with a higher force and this creates a movement of a larger total area with less force per area unit.

[0218] Like in the previous embodiment described above with reference to FIGS. **32a-c**, the regulation reservoir **46** is preferably provided with means **46a** for keeping its shape after compression. This means, which is schematically shown in the figure, will thus keep the device **10** in a stretched position also when the user releases the regulation reservoir. In this way, the regulation reservoir essentially operates as an on/off switch for the reflux disease treatment system.

[0219] In FIG. **35**, a flow chart illustrating steps performed when implanting a device in accordance with the present invention. First in a step **102**, an opening is cut in the abdominal wall. Next, in a step **104** an area around the stomach is dissected. Thereupon, in a step **106** at least one movement restriction device in accordance with the invention is placed in contact with the stomach wall, in particular the fundus wall. The stomach wall is then sutured in a step **108**.

Method for the Restoration of the Location of the Cardia and the Fundus

[0220] FIG. **36** shows how an instrument **200** having at least one flexible part **201** is introduced into the esophagus **24** of a patient that is suffering from a hiatal hernia **202** where a part of the esophagus **24** and fundus **16** that is supposed to be located below the diaphragm **18** has moved through the hiatus opening **18a** to a position above the diaphragm **18**.

[0221] In FIG. **37** it is shown how, in a subsequent step, a member **203** having a larger cross sectional area than said instrument **200** is released from the instrument **200**. The member **203** is adapted as to have a cross-sectional that is larger than the opening of the cardia **14**. This can be achieved by radial expansion of the member **203**. The instrument **200** is then pushed in a distal direction so that the cardia **14** and the fundus **16**, or part of fundus **16**, incorrectly located above diaphragm **18**, slide through the hiatus opening **18a** back to a correct position below the diaphragm **18**.

[0222] FIG. **38** shows an alternative method to the one shown in FIG. **37** which is an embodiment of the invention. In many aspects, this figure is similar to FIG. **37**. In FIG. **38**, the instrument **200** is adapted to release a balloon member **204** at the end **205** of the instrument **200** in the lower part of the stomach **206**, and using the balloon member **204** to push the instrument **200** against the lower wall part of the stomach **207** so that the cardia **14** and the fundus **16** or part of fundus **16** slide through the hiatus opening **18a** to a position below the diaphragm **18**.

[0223] FIG. **39** shows yet an alternative method which is an embodiment of the invention. Again, this figure is in many aspects similar to FIG. **37**. However, in FIG. **39** the method involves attaching the member **203** to the wall of the stomach **207** by a fixation **208**. As described above the instrument is then pushed in a distal direction so the cardia **14** and the fundus **16** or, part of fundus **16**, slides below the diaphragm **18**.

[0224] FIG. **40** shows how the fundus **16** and cardia **14** is located in a position below the diaphragm **18** after having been pushed through the hiatal opening **18a** by the instrument **200**.

[0225] FIG. **41** shows a subsequent step of the method. After the fundus **16** and cardia **14** has been pushed into its correct position below the diaphragm **18**, the wall of the fundus **16a** is affixed to the lower part of the oesophagus **24**. This is carried out by using a member **209** in the proximal part

**205** of the instrument **200** which is capable of providing sutures or staples **210**. The fixation hinders the movement of the cardia **14** and the fundus **16** to a position above the diaphragm **18**.

[0226] Other methods according to the invention are briefly described below.

[0227] A method of treating reflux disease of a patient comprises the step of implanting a reflux disease treatment system according to the invention into the patient's body.

[0228] A method of using the system for treating reflux disease according to the invention comprises the step of regulating the device postoperatively to prevent reflux.

[0229] A method for surgically placing a movement restriction device according to the invention in a patient comprises the steps of cutting an opening in the abdominal wall of the patient, dissecting the area around the stomach, placing a movement restriction device attached to the stomach wall, and suturing the stomach wall.

[0230] A method of using a reflux disease treatment system, postoperatively controlled from outside the body, regulating the device, comprises the steps of filling out a volume attached to a part of the stomach wall, and regulating the device from outside the patient's body to affect the reflux of the patient.

[0231] A method of using a movement restriction device comprises the steps of filling out a volume in a first part of the stomach wall by placing a first part of the device, filling out a volume in a second part of the stomach wall by placing a second part of the device, and regulating the devices from outside the patient's body to affect the reflux of the patient.

[0232] A method of treating reflux disease in a patient comprises the steps of inserting a needle or a tube like instrument into the abdomen of the patient's body, using the needle or tube like instrument to fill the patient's abdomen with gas thereby expanding the abdominal cavity, placing at least two laparoscopic trocars in the patient's body, inserting a camera through one of the laparoscopic trocars into the patient's abdomen, inserting at least one dissecting tool through one of said at least two laparoscopic trocars and dissecting an intended placement area of at least one portion of the stomach of the patient, placing a movement restriction device according to the invention on the stomach fundus wall, invaginating the device in the stomach fundus wall, suturing the stomach wall to itself to keep the device in place, suturing the fundus of the stomach towards the lower part of the oesophagus, and preventing the cardia to slide up through the diaphragm into the thorax. Using the method and device as described herein will provide a treatment of Gastroesophageal Reflux Disease which is very effective and which does not suffer from complications such as damaging of tissue and undesired migration of non tissue into tissue.

[0233] The filling body of the device can be adapted to be pushed or pulled through a trocar for laparoscopic use, where the trocar has a diameter that is smaller than the relaxed diameter of the body. The filling body can include an outer wall and a hollow gas filled inner part that allow the body to pass through the trocar. Alternatively, the filling body can include an outer wall and a hollow fluid filled inner part that allow the body to pass through the trocar. In this latter case, the fluid can be a gel. The filling body can further include multiple parts that can be inserted into the trocar, and that can then be put together into one unitary piece inside the patient's body, allowing the filling body to pass through the trocar. The filling body can include an outer wall and a hollow compressed inner part that is filled with a fluid or gel after insertion into the patient's body. The can further include an injection port that can be used to fill the filling body with a fluid after insertion into the patient's body through the injection port.

[0234] The filling body of the device can be an elastic compressible material, allowing the filling body to pass through the trocar. The filling body can be made from a material that is softer than 25 shure, or even 15 shure.

[0235] The filling body can also include an outer wall substantially taking the shape of a ball. The filling body can also include at least one holding device adapted to be used for pushing or pulling the filling body through a trocar for laparoscopic use. The holding device can be adapted to hold a prolongation of the device that is adapted to be held by a surgical instrument. The holding device

can also hold a tread or band inserted through the holding device. The holding device can also be at least partly placed inside the outer wall of the filling body. The filling body of the device can preferably has a size that is larger than the intestinal outlet from the stomach. to avoid ileus if the ball, as a complication, should enter into the stomach. Preferably, the body has a smallest outer diameter between 30 mm and 40 mm or larger. Preferably, the body has a smallest outer circumference between 30 mm and 150 mm.

[0236] Preferred embodiments of a device for treating reflux disease, a system comprising a device for treating reflux disease, and a method according to the invention have been described. A person skilled in the art realizes that these could be varied within the scope of the appended claims. Thus, although the different features have been described in specific embodiments, it will be appreciated that they can be combined in different configurations when applicable. For example, although hydraulic control has been described in association with the device configuration of FIG. 4A-B, it can also be applied to the device configurations of FIGS. 2A-B and 3A-B.

[0237] It is important that the implanted reflux treatment device is firmly kept in place in the stomach wall in which it is invaginated. To this end, the reflux treatment device can be provided with one or more through holes adapted for receiving sutures or staples used for fixation of the invagination. Such an embodiment is shown in FIG. 42, where the reflux treatment device 10 is provided with a row of holes 10i provided on a protruding flange-like protrusion on the reflux treatment device. In this embodiment, the row of holes extend along the longitudinal axis of the reflux treatment device.

[0238] FIG. 43 illustrates how sutures 314 are provided so that they run through the stomach wall 12a and through the holes 10i. In this way, the reflux treatment device is fixed in place in the pouch created from the stomach wall and will thus be prevented from sliding.

[0239] Although a plurality of holes is illustrated in the FIG. 42, it will be appreciated that one single hole is sufficient to obtain improved fixation of the reflux treatment device 10.

[0240] FIG. 44 illustrates a reflux treatment device provided with an inlet port 10h. The reflux treatment device is invaginated in the stomach wall and the inlet port 10h is available for connection to a tube or the like from the abdominal area of the patient.

[0241] FIG. 45 illustrates an invaginated reflux treatment device wherein, instead of an inlet port, a fixed tube 10g extends into the abdominal area of the patient.

[0242] FIG. 46 is a figure similar to FIG. 44 but also illustrating tunneling of a connection tube 10g in the stomach wall between the inlet port 10h and the reflux treatment device 10.

[0243] It has been shown that the shape of the reflux treatment device can take many different forms. It will be appreciated that also the material of the reflux treatment device can vary. It is preferred that the reflux treatment device is provided with a coating, such as a Parylene, polytetrafluoroethylene (PTFE), or polyurethane coating, or a combination of such coatings, i.e., a multi-layer coating. This coating or multi-layer coating improves the properties of the reflux treatment device, such as its resistance to wear.

[0244] In one embodiment, the reflux treatment device comprises an inflatable device expandable to an expanded state. In this case, the inflatable device is provided with an inlet port for a fluid and is adapted to be connected to a gastroscopic instrument. This embodiment will now be described in detail with reference to FIGS. 47a-47d.

[0245] An inflatable reflux treatment device in its non-expanded state is shown in FIG. 47a. It is essentially a balloon-like, deflated device 10 having an inlet port 10h. In this state, the inflatable device has a diameter of a few millimeters at the most, allowing it to be inserted into the stomach through the esophagus of the patient by means of a comprises an outer sleeve 600a and an inner sleeve 600b which can be displaced longitudinally relatively to the outer sleeve. The inner sleeve is provided with a cutter in the form of a cutting edge 615 at the distal end thereof. This cutting edge can be used for cutting a hole in the stomach wall, as will be explained in detail in the following.

[0246] When the instrument reaches a stomach wall, see FIG. 47c, the inner sleeve is brought

forward from its position in the outer sleeve and into contact with the stomach wall **12a**. The cutting edge **615** of the inner sleeve then cuts a hole in the stomach wall so as to allow subsequent insertion of the reflux treatment device **10** into and through this hole, see FIG. **47d**. In order to push the reflux treatment device through the hole, a piston **602** may be provided in the instrument. Thus, the instrument further comprises a piston **602** adapted for pushing a deflated reflux treatment device **10** out from a position in the inner sleeve, this position being shown in FIG. **47b**, to a position outside of the inner sleeve, this being shown in FIG. **47d**.

[0247] In order to protect the deflated reflux treatment device **10** from the cutting edge **615** of the inner sleeve, a further protective sleeve (not shown) can be provided around the reflux treatment device.

[0248] An intraluminal method of invaginating a reflux treatment device **10** on the outside of the stomach wall **12a** will now be described with reference to FIGS. **48a-i**. Initially, an instrument **600**, preferably a gastroscopic instrument, is inserted into the mouth of the patient, see FIG. **48a**. The instrument comprises an injection device **601**, **602** for injecting either fluid or a device into the stomach of the patient. The instrument **600** further comprises a control unit **606** adapted for controlling the operation of the instrument. To this end, the control unit **606** comprises one or more steering devices, in the embodiment shown in the figure in the form of two joysticks **603** and two control buttons **604**. A display **605** is provided for displaying the image provided by a camera (not shown) arranged at the outer end of the elongated member **607**, see FIGS. **48e-i**. The camera may be assisted by a light source (not shown).

[0249] The instrument is further inserted into the esophagus and into the stomach of the patient, see FIG. **48b**. By means of the instrument **600**, a hole **12b** is created in the wall of the stomach **12**. To this end, the instrument is provided with one or more cutters **615** at the distal end thereof, for example in the way described above with reference to FIGS. **47a-d**. These cutters can of course be designed in different ways, such as a toothed drum cutter rotating about the center axis of the tube-like instrument. The instrument **600** is hollow providing a space for the reflux treatment device **10** in its deflated state.

[0250] After cutting a hole in the stomach wall, the distal end of the instrument **600** is inserted into and through the hole **12b** so that it ends up outside the stomach wall **12a**. This is shown in FIG. **48c**, showing a side view of the stomach **12**, and FIG. **48d**, which is a sectional view through the stomach of FIG. **48c** taken along the lines Vd-Vd. The deflated reflux treatment device **10** is then inserted in the abdominal area.

[0251] The instrument **600** is adapted to create a “pocket” or “pouch” on the outside of the stomach **12** around the hole **12b** in the stomach wall. Such an instrument and the method of providing the pouch will now be described.

[0252] FIGS. **48e-i** show a gastroscopic or laparoscopic instrument for invaginating a reflux treatment device **10** in the stomach wall **12a** of the patient by creating a pouch of stomach wall **12a** material in which the reflux treatment device is placed. The instrument, generally designated **600**, and which may comprise the features described above with reference to FIGS. **47a-d**, comprises an elongated member **607** having a proximal end and a distal end, the elongated member **607** having a diameter less than that of the patient's esophagus and being flexible such as to allow introduction of the flexible elongated member **607** with its distal end first through the patient's throat, esophagus and into the stomach **12** to the stomach wall **12a**.

[0253] The stomach penetration device or cutter **615** is provided on the elongated member **607** at the distal end thereof for penetrating the stomach wall **12a** so as to create a hole in the stomach wall **12a**, to allow introduction of the elongated member **607** through the hole. The stomach penetration device **615** could be adapted to be operable for retracting said stomach penetration device **615** after the stomach fundus wall **12a** has been penetrated, for not further damaging tissue within the body. The instrument further comprises a special holding device **609** provided on the elongated member **607** on the proximal side to the penetration device **615**.

[0254] The elongated member further comprises an expandable member **611** which is adapted to be expanded after the elongated member has penetrated the stomach wall **12a** and thereby assist in the creation of a cavity or pouch adapted to hold the reflux treatment device **610**. The expandable member **611** may comprise an inflatable circular balloon provided circumferentially around the distal end portion of the flexible elongated member **607**.

[0255] The method steps when invaginating the reflux treatment device will now be described in detail. After the instrument **600** has been inserted into the stomach **12**, the stomach penetration device **615** is placed into contact with the stomach wall **12a**, see FIG. **48e**. The stomach penetration device or cutter **615** is then brought to create the hole **12b** in the stomach wall, whereafter at least the expandable member **611** is brought through the hole **12b** in the stomach wall. The special holding device **609** is in this step brought to a holding state wherein it expands radially so as to form an essentially circular abutment surface to the stomach wall **12a**, see FIG. **48f**. In this way, the insertion of the stomach penetration device **615** and the expandable member **611** through the hole **12a** in the stomach wall is limited to the position shown in FIG. **48f**.

[0256] The expandable member **611** is then expanded. In the case the expandable member comprises a balloon or the like, air or other fluid is injected into it.

[0257] The part of the elongated member **607** comprising the expandable member **611** is then retracted in the proximal direction, as indicated by the arrow in FIG. **48g**, thereby pulling the stomach wall **612** into a basket like structure created by the special holding device **609**.

[0258] A suturing or stapling device **608** is further provided, either as a device connected to the elongated member **607** or as a separate instrument. The suturing or stapling member comprises a suturing or stapling end **613** which is adapted to close the cavity or pouch by means of stomach to stomach sutures or staples **14**.

[0259] In a further step, illustrated in FIG. **48h**, an inflatable reflux treatment device **10** is placed in its deflated state in the basket like structure. The reflux treatment device **10** is then inflated to its inflated or expanded state, see FIG. **48i**. This inflation of the reflux treatment device **10** can be accomplished by injecting a fluid or a gel into the deflated reflux treatment device. It can also be accomplished by injecting a material which is allowed to cure, thereby forming a solid device **10**. Thus, the reflux treatment device **10** shown in FIGS. **48h** and **48i** can illustrate either a balloon-like device which is subsequently filled with fluid or gel or alternatively a material which is simply injected into the basket like structure formed by the stomach wall **12a**.

[0260] The fluid which is used to fill the reflux treatment device **10** could be any suitable fluid suitable to fill the inflatable device **10**, such as a salt solution. In another embodiment, when this fluid is a fluid which is adapted to be transformed into solid state, the fluid could be liquid polyurethane.

[0261] In order to minimize or entirely eliminate leakage, the fluid is iso-tonic, i.e., it has the same osmolarity as human body fluids. Another way of preventing diffusion is to provide a fluid which comprises large molecules, such as iodine molecules.

[0262] The stomach-to-stomach sutures or staples are preferably provided with fixation portions exhibiting a structure, such as a net like structure, adapted to be in contact with the stomach wall to promote growth in of human tissue to secure the long term placement of the reflux treatment device attached to the stomach wall.

[0263] After the inflatable device **10** has been inflated, partly or fully, the inlet port **10b** (not shown in FIGS. **48h** and **48i**) of the reflux treatment device **10**, is sealed and the instrument **600** is retracted from the hole **12b**, which is subsequently closed in some suitable way, such as by means of the instrument **600**. The instrument is then removed from the stomach **600** and the inflatable device **10** in its inflated or expanded state is invaginated by a stomach wall portion of the patient on the outside of the stomach wall. During one or more of the above described steps, the stomach may be inflated with gas, preferably by means of the gastroscopic instrument.

[0264] The reflux treatment device **10** described above with reference to FIGS. **48a-i** has been

described as an inflatable reflux treatment device. It will be appreciated that it also can be an elastic reflux treatment device with an elasticity allowing compression so as to be inserted into a gastroscopic instrument and which expands to an expanded state after leaving the instrument.

[0265] The apparatus for treating reflux can have the additional functionality of treating obesity. In such an embodiment, the reflux treatment device may be a volume filling device that fills a volume of the stomach and thereby creating satiety. An embodiment having this function is shown in FIG. 49, wherein a combined reflux treatment device and obesity treatment device 310 is invaginated in the stomach wall close to and at least partially above the patient's cardia 14 when the patient is in a standing position and is fixed to a position above the cardia area 14c by a fixation, such as sutures or staples 22. For example a direct or indirect fixation to the diaphragm muscle or associated muscles may be provided. As an alternative a direct or indirect fixation to the esophagus above and close to the angle of His can be provided. In this alternative embodiment, the combined device 310 rests in a position against stomach wall of the fundus when implanted and which also fills a volume above the cardia area 14c between the cardia and the diaphragm muscle so that the cardia is prevented from slipping up into the thorax cavity, whereby reflux disease is prevented.

[0266] Such a combined device 310 may be used for keeping electronics and/or an energy source and/or hydraulic fluid. Hydraulic fluid from that device may be distributed to several smaller inflatable device areas to vary the stretching area from time to time avoiding any possible more permanent stretching effect of the stomach wall. Even mechanically several stretching areas may be used.

#### Combination Reflux Treatment Device—Stretching Device

[0267] In an alternative embodiment, which is shown in FIG. 50, the volume of an inflatable reflux treatment device 310 may be in fluid connection with one or more preferably smaller inflatable devices or chambers 10b. These chambers are adapted to communicate with fluid or air being moved between the chambers.

[0268] Thus, the large chamber 310 is adapted to, with its main volume to be a reflux treatment device for reducing the size of the food cavity and for treating reflux disease and the one or several small chambers are adapted to function as the inflatable devices to treat obesity, wherein the main chamber is adapted to communicate with fluid or air to the small chambers causing a stretching effect in the stomach wall thereby further treating obesity.

[0269] FIG. 51 show an embodiment with a combination of a volume filling device invaginated in the central or lower portion of the stomach and a stretching device invaginated in the upper portion or fundus of the patient's stomach. These two devices serve to treat obesity.

[0270] The volume filling device 399 fills a volume of the stomach creating satiety. The stretching device stretches the wall of the stomach. This stretches the tissue setting off an endogenous signaling that creates satiety. This mimics the stretching effect of filling the stomach with food. Thus, in FIG. 51 there is shown an adjustable volume filling device 399, which is invaginated in the stomach wall of a patient's stomach 312. Additionally, an adjustable stretching device 350 with the previously described function is invaginated in the stomach fundus wall of the patient. It is preferred that the volume filling device 399 is substantially larger than the stretching device 350.

[0271] The volume filling device 399 and the stretching device 350 can be adapted to treat reflux. In one embodiment, the volume filling device and the stretching device are positioned to prevent the cardia 14 from slipping upwards through the opening of the hernia 18a to a position above the diaphragm 18.

[0272] The volume filling device 399 and the stretching device 350 are in fluid communication with each other via a first fluid tube 352, in which a pump 354 is provided. The pump 354 is under the control from an energy transforming device 330, which is adapted to supply the pump 350 with energy via a power supply line 356. The energy transforming device 330 is also connected to a sensor 319 provided in the esophagus of the patient so that food intake can be detected.

[0273] The reflux treatment device 10 and the stretching device 350 are also in fluid

communication with each other via a second fluid tube **358**, which preferably has a smaller cross-sectional area than the first fluid tube **352**.

[0274] The operation of this arrangement is as follows. The volume filling device **399** functions as in the above described embodiments, i.e., it reduces the size of the food cavity of the patient's stomach **12**. Additionally, when the stretching device **350** is enlarged by pumping fluid from the volume filling device **10** and to the stretching device **350** by means of the pump **354**, the stomach fundus wall is stretched, creating a feeling of satiety for the patient. Thus, for example when food intake is detected by means of the sensor **319**, fluid is automatically pumped into the stretching device **350** to increase the feeling of satiety and thereby limit the food intake.

[0275] When fluid has been injected into the stretching device **350**, the internal pressure therein is higher than the internal pressure in the reflux treatment device **399**. This difference in pressure will create a flow of fluid in the second, preferably narrower tube **358** from the stretching device **350** to the reflux treatment device **399**. The flow rate will be determined by among other things the difference in pressure and the cross-sectional area of the second tube **358**. It is preferred that the second tube is so dimensioned, that the pressures in the volume filling device **399** and the stretching device **350** will return to equilibrium after 3 hours after fluid has been injected into the stretching device **350** to create the feeling of satiety.

[0276] In this embodiment, the function of the second tube **358** is to allow fluid to return from the stretching device **350** to the volume filling device **399**. It will be appreciated that this function also can be performed by the pump **354** in the first tube **352** and that the second tube **358** then can be omitted.

Method for Placing an Reflux Treatment Device on the Inside of the Stomach Wall:

[0277] In the following a method and an instrument for placing a reflux treatment device on the inside of the stomach wall will be described.

[0278] The invagination instrument described in FIG. **52a-1** generally designated **630**, comprises an elongated tube member **632** similar to the elongated member **607** described above with reference to FIGS. **48a-i**. Thus, it can be connected to a control unit **606**, see FIG. **48a**. The invagination instrument **630** further comprises a perforated suction portion **634**, which preferably is elongated. The suction portion **634** exhibits a plurality of small holes **636**, into which air will be sucked by providing suction in the tube member **632**. This suction effect will be used to create a "pocket" or "pouch" in a part of a stomach wall, generally designated **12a**.

[0279] In other words, when the tip of the suction portion **634** is pressed against the stomach wall **12a**, see FIG. **52a**, a small recess will be formed therein. When the suction portion **634** is further pressed against the stomach wall **12a**, see FIG. **52b**, a larger recess will be formed. The part of the stomach wall **12a** that forms the recess will, due to the suction effect, adhere to the suction portion **634** of the invagination instrument **630**. As the suction portion **634** is further pressed into the stomach wall **12a**, see FIG. **52c**, a deeper recess will be formed until the entire suction portion **634** is embedded in the recess, see FIG. **18d**.

[0280] The rim of the recess will at this stage be fixated by means of fixation elements **638** and the suction portion be removed from the instrument, see FIG. **52e**. A compressed elastic reflux treatment device **10** will subsequently be inserted into the recess, see FIG. **52f**, for example in the way described above with reference to FIG. **47d**. This compressed reflux treatment device is then expanded to its final shape, see FIG. **52g**, where after the pouch is sealed by suturing or stapling by means of the fixations elements, see FIG. **52h**.

[0281] All the alternatives described above with reference to FIGS. **1-51** are also applicable to the embodiment described with reference to FIGS. **52a-1**, i.e., to the embodiment where the reflux treatment device is invaginated on the inside of the stomach wall.

[0282] FIG. **53 a-c** show an instrument for creating an invagination of the wall of the stomach that can either be placed on the outside of the wall of the stomach or on the inside of the wall of the stomach depending if the reflux treatment device is place on the inside or the outside of the wall.

The instrument uses vacuum to such a portion of the wall of the stomach into the cup of the instrument.

[0283] It has been described how the reflux treatment device **10** is invaginated in the stomach wall by means of a gastroscopic instrument. The gastroscopic instrument can be used for either placing the reflux treatment device on the outside of the wall of the stomach as shown in FIG. **1A** or on the inside of the stomach as shown in FIG. **2A**. In the latter case, the instruments will be used to make an incision in the wall of the stomach from the inside of the stomach.

[0284] It will be appreciated that abdominal operation methods can be used as well. Such methods will now be described in with reference to FIGS. **54-55**. In FIG. **54** it is shown how the stomach is accessed by creating an incision **380** in the abdomen of the patient. In FIG. **55** it is shown how an instrument **381** is inserted into the abdomen of the patient. Any of the instruments and methods described can be selected and adapted for this purpose. Thus, for example, the reflux treatment device can be placed on the outside of the stomach as shown in FIG. **1A** or on the inside as shown in FIG. **2A**. In the later case an incision is made in the wall of the stomach.

[0285] It is important that the implanted reflux treatment device is firmly kept in place in the stomach wall in which it is invaginated. To this end, the reflux treatment device can be provided with one or more through holes adapted for receiving sutures or staples used for fixation of the invagination. Such an embodiment is shown in FIG. **42**, where the reflux treatment device **10** is provided with a row of holes **10i** provided on a protruding flange-like protrusion on the reflux treatment device. In this embodiment, the row of holes extend along the longitudinal axis of the reflux treatment device.

[0286] FIG. **43** illustrates how sutures **314** are provided so that they run through the stomach wall **12a** and through the holes **10i**. In this way, the reflux treatment device is fixed in place in the pouch created from the stomach wall and will thus be prevented from sliding.

[0287] Although a plurality of holes is illustrated in the FIG. **42**, it will be appreciated that one single hole is sufficient to obtain improved fixation of the reflux treatment device **10**.

[0288] FIG. **44** illustrates a reflux treatment device provided with an inlet port **10h**. The reflux treatment device is invaginated in the stomach wall and the inlet port **10h** is available for connection to a tube or the like from the abdominal area of the patient.

[0289] FIG. **45** illustrates an invaginated reflux treatment device wherein, instead of an inlet port, a fixed tube **10g** extends into the abdominal area of the patient.

[0290] FIG. **46** is a figure similar to FIG. **44** but also illustrating tunneling of a connection tube **10g** in the stomach wall between the inlet port **10h** and the reflux treatment device **10**.

[0291] It has been shown that the shape of the reflux treatment device can take many different forms. It will be appreciated that also the material of the reflux treatment device can vary. It is preferred that the reflux treatment device is provided with a coating, such as a Parylene, polytetrafluoroethylene (PTFE), or polyurethane coating, or a combination of such coatings, i.e., a multi-layer coating. This coating or multi-layer coating improves the properties of the reflux treatment device, such as its resistance to wear.

[0292] In one embodiment, the reflux treatment device comprises an inflatable device expandable to an expanded state. In this case, the inflatable device is provided with an inlet port for a fluid and is adapted to be connected to a gastroscopic instrument. This embodiment will now be described in detail with reference to FIGS. **47a-47d**.

[0293] An inflatable reflux treatment device in its non-expanded state is shown in FIG. **47a**. It is essentially a balloon-like, deflated device **10** having an inlet port **10h**. In this state, the inflatable device has a diameter of a few millimeters at the most, allowing it to be inserted into the stomach through the esophagus of the patient by means of a comprises an outer sleeve **600a** and an inner sleeve **600b** which can be displaced longitudinally relatively to the outer sleeve. The inner sleeve is provided with a cutter in the form of a cutting edge **615** at the distal end thereof. This cutting edge can be used for cutting a hole in the stomach wall, as will be explained in detail in the following.



[0294] When the instrument reaches a stomach wall, see FIG. 47c, the inner sleeve is brought forward from its position in the outer sleeve and into contact with the stomach wall **12a**. The cutting edge **615** of the inner sleeve then cuts a hole in the stomach wall so as to allow subsequent insertion of the reflux treatment device **10** into and through this hole, see FIG. 47d. In order to push the reflux treatment device through the hole, a piston **602** may be provided in the instrument. Thus, the instrument further comprises a piston **602** adapted for pushing a deflated reflux treatment device **10** out from a position in the inner sleeve, this position being shown in FIG. 47b, to a position outside of the inner sleeve, this being shown in FIG. 47d.

[0295] In order to protect the deflated reflux treatment device **10** from the cutting edge **615** of the inner sleeve, a further protective sleeve (not shown) can be provided around the reflux treatment device.

[0296] An intraluminal method of invaginating a reflux treatment device **10** on the outside of the stomach wall **12a** will now be described with reference to FIGS. 48a-i. Initially, an instrument **600**, preferably a gastroscopic instrument, is inserted into the mouth of the patient, see FIG. 48a. The instrument comprises an injection device **601**, **602** for injecting either fluid or a device into the stomach of the patient. The instrument **600** further comprises a control unit **606** adapted for controlling the operation of the instrument. To this end, the control unit **606** comprises one or more steering devices, in the embodiment shown in the figure in the form of two joysticks **603** and two control buttons **604**. A display **605** is provided for displaying the image provided by a camera (not shown) arranged at the outer end of the elongated member **607**, see FIGS. 48e-i. The camera may be assisted by a light source (not shown).

[0297] The instrument is further inserted into the esophagus and into the stomach of the patient, see FIG. 48b. By means of the instrument **600**, a hole **12b** is created in the wall of the stomach **12**. To this end, the instrument is provided with one or more cutters **615** at the distal end thereof, for example in the way described above with reference to FIGS. 47a-d. These cutters can of course be designed in different ways, such as a toothed drum cutter rotating about the center axis of the tube-like instrument. The instrument **600** is hollow providing a space for the reflux treatment device **10** in its deflated state.

[0298] After cutting a hole in the stomach wall, the distal end of the instrument **600** is inserted into and through the hole **12b** so that it ends up outside the stomach wall **12a**. This is shown in FIG. 48c, showing a side view of the stomach **12**, and FIG. 48d, which is a sectional view through the stomach of FIG. 48c taken along the lines Vd-Vd. The deflated reflux treatment device **10** is then inserted in the abdominal area.

[0299] The instrument **600** is adapted to create a “pocket” or “pouch” on the outside of the stomach **12** around the hole **12b** in the stomach wall. Such an instrument and the method of providing the pouch will now be described.

[0300] FIGS. 48e-i show a gastroscopic or laparoscopic instrument for invaginating a reflux treatment device **10** in the stomach wall **12a** of the patient by creating a pouch of stomach wall **12a** material in which the reflux treatment device is placed. The instrument, generally designated **600**, and which may comprise the features described above with reference to FIGS. 47a-d, comprises an elongated member **607** having a proximal end and a distal end, the elongated member **607** having a diameter less than that of the patient's esophagus and being flexible such as to allow introduction of the flexible elongated member **607** with its distal end first through the patient's throat, esophagus and into the stomach **12** to the stomach wall **12a**.

[0301] The stomach penetration device or cutter **615** is provided on the elongated member **607** at the distal end thereof for penetrating the stomach wall **12a** so as to create a hole in the stomach wall **12a**, to allow introduction of the elongated member **607** through the hole. The stomach penetration device **615** could be adapted to be operable for retracting said stomach penetration device **615** after the stomach fundus wall **12a** has been penetrated, for not further damaging tissue within the body. The instrument further comprises a special holding device **609** provided on the elongated member

**607** on the proximal side to the penetration device **615**.

[0302] The elongated member further comprises an expandable member **611** which is adapted to be expanded after the elongated member has penetrated the stomach wall **12a** and thereby assist in the creation of a cavity or pouch adapted to hold the reflux treatment device **610**. The expandable member **611** may comprise an inflatable circular balloon provided circumferentially around the distal end portion of the flexible elongated member **607**.

[0303] The method steps when invaginating the reflux treatment device will now be described in detail. After the instrument **600** has been inserted into the stomach **12**, the stomach penetration device **615** is placed into contact with the stomach wall **12a**, see FIG. **48e**. The stomach penetration device or cutter **615** is then brought to create the hole **12b** in the stomach wall, whereafter at least the expandable member **611** is brought through the hole **12b** in the stomach wall. The special holding device **609** is in this step brought to a holding state wherein it expands radially so as to form an essentially circular abutment surface to the stomach wall **12a**, see FIG. **48f**. In this way, the insertion of the stomach penetration device **615** and the expandable member **611** through the hole **12a** in the stomach wall is limited to the position shown in FIG. **48f**.

[0304] The expandable member **611** is then expanded. In the case the expandable member comprises a balloon or the like, air or other fluid is injected into it.

[0305] The part of the elongated member **607** comprising the expandable member **611** is then retracted in the proximal direction, as indicated by the arrow in FIG. **48g**, thereby pulling the stomach wall **612** into a basket like structure created by the special holding device **609**.

[0306] A suturing or stapling device **608** is further provided, either as a device connected to the elongated member **607** or as a separate instrument. The suturing or stapling member comprises a suturing or stapling end **613** which is adapted to close the cavity or pouch by means of stomach to stomach sutures or staples **14**.

[0307] In a further step, illustrated in FIG. **48h**, an inflatable reflux treatment device **10** is placed in its deflated state in the basket like structure. The reflux treatment device **10** is then inflated to its inflated or expanded state, see FIG. **48i**. This inflation of the reflux treatment device **10** can be accomplished by injecting a fluid or a gel into the deflated reflux treatment device. It can also be accomplished by injecting a material which is allowed to cure, thereby forming a solid device **10**. Thus, the reflux treatment device **10** shown in FIGS. **48h** and **48i** can illustrate either a balloon-like device which is subsequently filled with fluid or gel or alternatively a material which is simply injected into the basket like structure formed by the stomach wall **12a**.

[0308] The fluid which is used to fill the reflux treatment device **10** could be any suitable fluid suitable to fill the inflatable device **10**, such as a salt solution. In another embodiment, when this fluid is a fluid which is adapted to be transformed into solid state, the fluid could be liquid polyurethane.

[0309] In order to minimize or entirely eliminate leakage, the fluid is iso-tonic, i.e., it has the same osmolarity as human body fluids. Another way of preventing diffusion is to provide a fluid which comprises large molecules, such as iodine molecules.

[0310] The stomach-to-stomach sutures or staples are preferably provided with fixation portions exhibiting a structure, such as a net like structure, adapted to be in contact with the stomach wall to promote growth in of human tissue to secure the long term placement of the reflux treatment device attached to the stomach wall.

[0311] After the inflatable device **10** has been inflated, partly or fully, the inlet port **10b** (not shown in FIGS. **48h** and **48i**) of the reflux treatment device **10**, is sealed and the instrument **600** is retracted from the hole **12b**, which is subsequently closed in some suitable way, such as by means of the instrument **600**. The instrument is then removed from the stomach **600** and the inflatable device **10** in its inflated or expanded state is invaginated by a stomach wall portion of the patient on the outside of the stomach wall. During one or more of the above described steps, the stomach may be inflated with gas, preferably by means of the gastroscopic instrument.

[0312] The reflux treatment device **10** described above with reference to FIGS. **48a-i** has been described as an inflatable reflux treatment device. It will be appreciated that it also can be an elastic reflux treatment device with an elasticity allowing compression so as to be inserted into a gastroscopic instrument and which expands to an expanded state after leaving the instrument.

[0313] The apparatus for treating reflux can have the additional functionality of treating obesity. In such an embodiment, the reflux treatment device may be a volume filling device that fills a volume of the stomach and thereby creating satiety. An embodiment having this function is shown in FIG. **49**, wherein a combined reflux treatment device and obesity treatment device **310** is invaginated in the stomach wall close to and at least partially above the patient's cardia **14** when the patient is in a standing position and is fixed to a position above the cardia area **14c** by a fixation, such as sutures or staples **22**. For example a direct or indirect fixation to the diaphragm muscle or associated muscles may be provided. As an alternative a direct or indirect fixation to the esophagus above and close to the angle of His can be provided. In this alternative embodiment, the combined device **310** rests in a position against stomach wall of the fundus when implanted and which also fills a volume above the cardia area **14c** between the cardia and the diaphragm muscle so that the cardia is prevented from slipping up into the thorax cavity, whereby reflux disease is prevented.

[0314] Such a combined device **310** may be used for keeping electronics and/or an energy source and/or hydraulic fluid. Hydraulic fluid from that device may be distributed to several smaller inflatable device areas to vary the stretching area from time to time avoiding any possible more permanent stretching effect of the stomach wall. Even mechanically several stretching areas may be used.

#### Combination Reflux Treatment Device—Stretching Device

[0315] In an alternative embodiment, which is shown in FIG. **50**, the volume of an inflatable reflux treatment device **310** may be in fluid connection with one or more preferably smaller inflatable devices or chambers **10b**. These chambers are adapted to communicate with fluid or air being moved between the chambers.

[0316] Thus, the large chamber **310** is adapted to, with its main volume to be a reflux treatment device for reducing the size of the food cavity and for treating reflux disease and the one or several small chambers are adapted to function as the inflatable devices to treat obesity, wherein the main chamber is adapted to communicate with fluid or air to the small chambers causing a stretching effect in the stomach wall thereby further treating obesity.

[0317] FIG. **51** show an embodiment with a combination of a volume filling device invaginated in the central or lower portion of the stomach and a stretching device invaginated in the upper portion or fundus of the patient's stomach. These two devices serve to treat obesity.

[0318] The volume filling device **399** fills a volume of the stomach creating satiety. The stretching device stretches the wall of the stomach. This stretches the tissue setting off an endogenous signaling that creates satiety. This mimics the stretching effect of filling the stomach with food. Thus, in FIG. **51** there is shown an adjustable volume filling device **399**, which is invaginated in the stomach wall of a patient's stomach **312**. Additionally, an adjustable stretching device **350** with the previously described function is invaginated in the stomach fundus wall of the patient. It is preferred that the volume filling device **399** is substantially larger than the stretching device **350**.

[0319] The volume filling device **399** and the stretching device **350** can be adapted to treat reflux. In one embodiment, the volume filling device and the stretching device are positioned to prevent the cardia **14** from slipping upwards through the opening of the hernia **18a** to a position above the diaphragm **18**.

[0320] The volume filling device **399** and the stretching device **350** are in fluid communication with each other via a first fluid tube **352**, in which a pump **354** is provided. The pump **354** is under the control from an energy transforming device **330**, which is adapted to supply the pump **350** with energy via a power supply line **356**. The energy transforming device **330** is also connected to a sensor **319** provided in the esophagus of the patient so that food intake can be detected.

[0321] The reflux treatment device **10** and the stretching device **350** are also in fluid communication with each other via a second fluid tube **358**, which preferably has a smaller cross-sectional area than the first fluid tube **352**.

[0322] The operation of this arrangement is as follows. The volume filling device **399** functions as in the above described embodiments, i.e., it reduces the size of the food cavity of the patient's stomach **12**. Additionally, when the stretching device **350** is enlarged by pumping fluid from the volume filling device **10** and to the stretching device **350** by means of the pump **354**, the stomach fundus wall is stretched, creating a feeling of satiety for the patient. Thus, for example when food intake is detected by means of the sensor **319**, fluid is automatically pumped into the stretching device **350** to increase the feeling of satiety and thereby limit the food intake.

[0323] When fluid has been injected into the stretching device **350**, the internal pressure therein is higher than the internal pressure in the reflux treatment device **399**. This difference in pressure will create a flow of fluid in the second, preferably narrower tube **358** from the stretching device **350** to the reflux treatment device **399**. The flow rate will be determined by among other things the difference in pressure and the cross-sectional area of the second tube **358**. It is preferred that the second tube is so dimensioned, that the pressures in the volume filling device **399** and the stretching device **350** will return to equilibrium after 3 hours after fluid has been injected into the stretching device **350** to create the feeling of satiety.

[0324] In this embodiment, the function of the second tube **358** is to allow fluid to return from the stretching device **350** to the volume filling device **399**. It will be appreciated that this function also can be performed by the pump **354** in the first tube **352** and that the second tube **358** then can be omitted.

Method for Placing an Reflux Treatment Device on the Inside of the Stomach Wall:

[0325] In the following a method and an instrument for placing a reflux treatment device on the inside of the stomach wall will be described.

[0326] The invagination instrument described in FIG. **52a-1** generally designated **630**, comprises an elongated tube member **632** similar to the elongated member **607** described above with reference to FIGS. **48a-i**. Thus, it can be connected to a control unit **606**, see FIG. **48a**. The invagination instrument **630** further comprises a perforated suction portion **634**, which preferably is elongated. The suction portion **634** exhibits a plurality of small holes **636**, into which air will be sucked by providing suction in the tube member **632**. This suction effect will be used to create a "pocket" or "pouch" in a part of a stomach wall, generally designated **12a**.

[0327] In other words, when the tip of the suction portion **634** is pressed against the stomach wall **12a**, see FIG. **52a**, a small recess will be formed therein. When the suction portion **634** is further pressed against the stomach wall **12a**, see FIG. **52b**, a larger recess will be formed. The part of the stomach wall **12a** that forms the recess will, due to the suction effect, adhere to the suction portion **634** of the invagination instrument **630**. As the suction portion **634** is further pressed into the stomach wall **12a**, see FIG. **52c**, a deeper recess will be formed until the entire suction portion **634** is embedded in the recess, see FIG. **18d**.

[0328] The rim of the recess will at this stage be fixated by means of fixation elements **638** and the suction portion be removed from the instrument, see FIG. **52e**. A compressed elastic reflux treatment device **10** will subsequently be inserted into the recess, see FIG. **52f**, for example in the way described above with reference to FIG. **47d**. This compressed reflux treatment device is then expanded to its final shape, see FIG. **52h**, where after the pouch is sealed by suturing or stapling by means of the fixations elements, see FIG. **52i**.

[0329] All the alternatives described above with reference to FIGS. **1-51** are also applicable to the embodiment described with reference to FIGS. **52a-1**, i.e., to the embodiment where the reflux treatment device is invaginated on the inside of the stomach wall.

[0330] FIG. **53 a-c** show an instrument for creating an invagination of the wall of the stomach that can either be placed on the outside of the wall of the stomach or on the inside of the wall of the

stomach depending if the reflux treatment device is place on the inside or the outside of the wall. The instrument uses vacuum to such a portion of the wall of the stomach into the cup of the instrument.

[0331] It has been described how the reflux treatment device **10** is invaginated in the stomach wall by means of a gastroscopic instrument. The gastroscopic instrument can be used for either placing the reflux treatment device on the outside of the wall of the stomach as shown in FIG. **1A** or on the inside of the stomach as shown in FIG. **2A**. In the latter case, the instruments will be used to make an incision in the wall of the stomach from the inside of the stomach.

[0332] It will be appreciated that abdominal operation methods can be used as well. Such methods will now be described in with reference to FIGS. **54-55**. In FIG. **54** it is shown how the stomach is accessed by creating an incision **380** in the abdomen of the patient. In FIG. **55** it is shown how an instrument **381** is inserted into the abdomen of the patient. Any of the instruments and methods described can be selected and adapted for this purpose. Thus, for example, the reflux treatment device can be placed on the outside of the stomach as shown in FIG. **1A** or on the inside as shown in FIG. **2A**. In the later case an incision is made in the wall of the stomach.

## Claims

**1.-84.** (canceled)

**85.** An apparatus for treating reflux disease of a human patient, the apparatus comprising an implantable movement restriction device having a size and shape adapted to be completely invaginated by the patient's stomach fundus wall without restricting a food passageway of the patient, wherein the outer surface of the movement restriction device is adapted to rest against the stomach fundus wall in a position between the patient's diaphragm and at least a portion of the invaginated stomach fundus wall, such that movement of the cardiac notch of the patient's stomach towards the patient's diaphragm is restricted, when the movement restriction device is invaginated, to thereby prevent the cardia from sliding through the patient's diaphragm opening into the patient's thorax, the movement restriction device is further adapted to contact, directly or indirectly, the diaphragm muscle to prevent sliding of the cardia through the patient's diaphragm, so as to maintain a supporting pressure against the patient's cardia sphincter muscle exerted from the patient's abdomen.

---