

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12395477
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Nomani; Muhammad Salman et al.

---

### Systems and methods for collaborative blockchain establishment for blockchain-based secure key exchange

---

#### Abstract

A system described herein provides for the secure maintaining and providing of information, such as public keys used in Public Key Infrastructure (“PKI”) techniques or other techniques, using a distributed ledger (e.g., “blockchain”) system. A first device may output a first request to a second device to establish a communication session between the first device and the second device, where the request includes a first value. The first device may receive a second request from the second device, including a second value, to establish the communication session between the first device and the second device. The first device may determine, based on a comparison of the first and second values, that the first device should initiate an establishment procedure of a blockchain associated with the communication session between the first device and the second device, and may accordingly output a blockchain establishment message to a set of devices.

---

**Inventors:** Nomani; Muhammad Salman (Hillsborough, NJ), Stokes; John M. (Yorba Linda, CA)

**Applicant:** Verizon Patent and Licensing Inc. (Basking Ridge, NJ)

**Family ID:** 1000008765984

**Assignee:** Verizon Patent and Licensing Inc. (Basking Ridge, NJ)

**Appl. No.:** 17/659152

**Filed:** April 13, 2022

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20220368683 A1	Nov. 17, 2022

#### Related U.S. Application Data

## Publication Classification

**Int. Cl.:** **H04L9/30** (20060101); **H04L9/40** (20220101)

**U.S. Cl.:**

**CPC** **H04L63/062** (20130101); **H04L9/30** (20130101);

## Field of Classification Search

**CPC:** H04L (63/062); H04L (9/30); H04L (9/0841); H04L (9/50); H04L (63/0442); H04L (63/12); H04L (63/061)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9729332	12/2016	Unagami	N/A	G06F 21/44
10999260	12/2020	Silvestri et al.	N/A	N/A
11423474	12/2021	Ribeiro	N/A	N/A
11698958	12/2022	Antar	726/2	G06Q 20/425
2007/0201472	12/2006	Bhatia	370/392	H04L 47/2416
2017/0359718	12/2016	Denny	N/A	H04L 9/0861
2019/0268312	12/2018	Ma	N/A	H04L 63/0435
2020/0313858	12/2019	Feng	N/A	G06F 21/53
2021/0004366	12/2020	Bartolucci	N/A	H04L 9/3073
2021/0049589	12/2020	Keskar	N/A	G06Q 20/3829
2021/0182423	12/2020	Padmanabhan	N/A	H04L 9/3271
2021/0357914	12/2020	Silvestri	N/A	H04L 9/0825
2022/0107994	12/2021	Bernardi	N/A	N/A
2022/0294611	12/2021	Katsumata et al.	N/A	N/A
2023/0021047	12/2022	Ammar et al.	N/A	N/A
2023/0121852	12/2022	Yan	713/153	H04L 9/3268
2023/0198747	12/2022	Sjöberg	713/168	G06Q 20/065

### OTHER PUBLICATIONS

“Key escrow”, Wikipedia, Nov. 20, 2020 (available at [https://en.wikipedia.org/w/index.php?title=Key\\_escrow&oldid=989705940](https://en.wikipedia.org/w/index.php?title=Key_escrow&oldid=989705940), visited Apr. 23, 2021). cited by applicant

Maheshwari, “Learn step-by-step how to set up a basic blockchain network”, Think 2021: The premier hybrid cloud and AI event, Jul. 10, 2020 (available at <https://developer.ibm.com/technologies/blockchain/tutorials/quick-start-guide-for-ibm-blockchain-platform/>, visited May 7, 2021). cited by applicant

Perrin, et al., “The Double Ratchet Algorithm”, Signal, Nov. 20, 2016 (available at <https://signal.org/docs/specifications/doubleratchet/>, visited Apr. 23, 2021). cited by applicant

---

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This Application is a Continuation-in-Part of U.S. patent application Ser. No. 17/321,378 filed on May 14, 2021, titled “SYSTEMS AND METHODS FOR BLOCKCHAIN-BASED SECURE KEY EXCHANGE,” the contents of which are herein incorporated by reference in their entirety.

### BACKGROUND

(1) Some encryption techniques, such as Public Key Infrastructure (“PKI”) techniques, may make use of public keys, which may be used to encrypt messages that may be decrypted using an associated private key, and/or may be used in other techniques. Public keys may be distributed or stored by key escrow systems, which may provide a single point of failure and/or an opportunity for a “man-in-the-middle” attack, via which public key may be obtained, modified, and/or otherwise compromised.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 illustrates an example overview of one or more embodiments described herein;
- (2) FIG. 2 illustrates an example of using a shared public key via a private blockchain system, in accordance with some embodiments, in a communication that utilizes double ratchet techniques to secure communications;
- (3) FIG. 3 illustrates an example of establishing a private blockchain system, in accordance with one or more embodiments;
- (4) FIG. 4 illustrates an example of using a shared public key via a private blockchain system, in accordance with some embodiments, in a communication that utilizes double ratchet techniques to secure communications;
- (5) FIGS. 5 and 6 illustrate example processes for using a shared public key via a private blockchain system, in accordance with some embodiments, in a communication that utilizes double ratchet techniques to secure communications;
- (6) FIG. 7 illustrates an example overview of one or more embodiments described herein,
- (7) FIG. 8 illustrates an example contact list along with candidate node capability indications, in accordance with some embodiments;
- (8) FIGS. 9-11 illustrate examples of collaborative blockchain establishment techniques, in accordance with some embodiments;
- (9) FIG. 12 illustrates an example process for collaborative blockchain establishment techniques, in accordance with some embodiments;
- (10) FIG. 13 illustrates an example environment in which one or more embodiments, described herein, may be implemented;
- (11) FIG. 14 illustrates an example arrangement of a radio access network (“RAN”), in accordance with some embodiments; and
- (12) FIG. 15 illustrates example components of one or more devices, in accordance with one or more embodiments described herein.

### DETAILED DESCRIPTION OF EXAMPLE EMBODIMENTS

- (13) The following detailed description refers to the accompanying drawings. The same reference numbers in different drawings may identify the same or similar elements.

(14) Embodiments described herein provide for the secure maintaining and providing of information, such as public keys used in PKI techniques or other techniques, using a secure distributed ledger (e.g., “blockchain”) system. For example, embodiments described herein may utilize a blockchain system in lieu of a key escrow system in the exchange and/or providing of public keys in a Diffie-Hellman key exchange technique, a key wrap exchange technique, or other type of technique in which public keys are provided from one entity to another. For example, as discussed herein, a first entity may generate an asymmetric key pair that includes a public key and a private key, and may provide the public key to a blockchain system for retrieval by one or more other entities. For example, the entities may be engaged in a secure messaging session, in which messages are encrypted and may be decrypted using one or more keys, including the public key. For example, the messaging session may be associated with multiple key derivation functions, in which a first key or set of keys (e.g., “root” keys) are used in the generation of one or more other keys (e.g., “send” keys and/or “receive” keys). A root key derivation function, for example, may be performed by first and second entities engaged in the communication session to generate respective send and/or receive keys for each entity. The entities may make use of different private keys in their respective root derivation functions, but may utilize one or more shared public keys for their respective root derivation functions. Examples of techniques that make use of multiple key derivation functions, including a root derivation function utilizing one or more shared public keys, include a “double ratchet” encryption technique, a “Signal Protocol,” and/or other types of techniques.

(15) In some embodiments, the contents of the secured ledger system (e.g., blockchain) may be publicly available or accessible, but the information stored therein may have no meaning or use to an attacker or other malicious user, in the context of obtaining public keys associated with PKI techniques or other techniques. In some embodiments, a private blockchain may be used, in which only authorized entities are able to access the information stored in the private blockchain. Further, as records stored in a blockchain system are immutable, an attacker may be prevented from modifying public keys and thereby potentially having access to information encrypted based on such keys. For simplicity, embodiments described herein are described in the context of the secured ledger system being a blockchain system. However, similar concepts may apply to another type of secured ledger system other than a blockchain system.

(16) As shown in FIG. 1, a first entity, such as User Equipment (“UE”) **101-1**, may generate (at **102**) a set of keys. The set of keys may be, and/or may include, asymmetric key pair **103**, which may include private key **105** and public key **107**. Private key **105** may be used to decrypt information encrypted by public key **107**, may be used in a double ratchet and/or Signal Protocol technique, and/or may be used for other suitable purposes. UE **101-1** may securely store private key **105**, such as in a local storage device associated with UE **101-1**, in a private key store, in a Universal Integrated Circuit Card (“UICC”), and/or in some other secure location.

(17) As further shown, UE **101-1** may record (at **104**) the public key to a blockchain system, such as private blockchain system **109**. As noted above, private blockchain system **109** may be “private,” in that only authorized entities (e.g., authorized UEs, authorized users, etc.) may have access to the information stored in private blockchain system **109**. The information stored in private blockchain system **109** may be organized as “blocks,” where one particular record corresponds to one particular block, and/or where one block includes multiple records. A block may also include a reference to one or more other blocks (e.g., a “previous” block and/or a “next” block), such that a group of blocks and their associated references may form a “chain” of blocks. Further, private blockchain system **109** may include a set of nodes **111** that form a consensus regarding the blocks of which the blockchain is comprised, thus preventing unauthorized changes to the information stored in the blockchain, as well as resiliency in case any particular node **111** is compromised or otherwise becomes unavailable. In some embodiments, nodes **111** may each be implemented by a respective UE **101**, such as a mobile telephone, a workstation computer, a tablet,

an Internet of Things (“IoT”) device, and/or other suitable type of device. While shown in the figure as being “external” to private blockchain system **109**, in practice, UE **101-1** may be, and/or may implement, a particular node **111** associated with private blockchain system **109**.

(18) When recording the public key to private blockchain system **109**, UE **101-1** may provide an identifier associated with UE **101-1** and/or other identifying information based on which the public key may be retrieved by an entity that may use the public key. For example, the record may include an Internet Protocol (“IP”) address associated with UE **101-1**, a device name, a user name, a Session Initiation Protocol (“SIP”) address, and/or some other suitable information associated with UE **101-1**.

(19) Additionally, or alternatively, the record may include a session identifier, which may identify a communication session between UE **101-1** and another UE, such as UE **101-2**. For example, UE **101-1** and UE **101-2** may be engaged in a secure messaging session, in which UE **101-1** and UE **101-2** exchange encrypted messages. The messaging session may be associated with a double ratchet technique, a Signal Protocol technique, and/or other type of technique in which UE **101-1** and UE **101-2** provide public keys to each other.

(20) Briefly, for example, for each message sent between UE **101-1** and UE **101-2**, a new public key may be generated (e.g., in an alternating fashion, where UE **101-1** generates a public key for a first message, UE **101-2** generates a public key for a second message, UE **101-1** generates a public key for a third message, and so on). As described below, these alternating shared public keys may serve as a first “ratchet” in a double ratchet technique to ensure security of the encrypted communications. For example, as discussed below, the public keys may be used to generate symmetric send and/or receive keys, which may be used to encrypt and/or decrypt communications between UE **101-1** and UE **101-2** without transmitting the send and/or receive keys between each other.

(21) Private blockchain system **109** is illustrated as including four nodes **111-1**, **111-2**, **111-3**, and **111-4**. In practice, private blockchain system **109** may include fewer nodes and/or additional nodes. Private blockchain system **109** may, in some embodiments, be associated with one or more suitable authentication mechanisms whereby only authorized devices or systems are able to participate as nodes **111** of private blockchain system **109**. For example, as discussed herein, particular users or UEs **101** may be specified or automatically identified (e.g., based on an address book or contact list associated with a particular UE **101** that is authorized to access private blockchain system **109** and/or some other suitable technique). As such, unauthorized devices, such as UE **101-N**, may not be able to access information stored in private blockchain system **109** and/or may not be able to participate as a node **111** of private blockchain system **109**. Further, as the nodes **111** of private blockchain system **109** may only include trusted devices, the integrity of the information stored by private blockchain system **109** may be enhanced, as the likelihood of a compromise or attack of private blockchain system **109** may be reduced or eliminated. Further, the recording and/or accessing of private blockchain system **109** may be private with respect to external devices that do not have access to private blockchain system **109**.

(22) In some embodiments, separate private blockchain systems **109** may be established for discrete groups, such as messaging or conversation groups (e.g., where a first communication session includes a first set of participants and is associated with a first private blockchain system **109**, and where a second communication session includes a second set of participants and is associated with a second private blockchain system **109**). In some embodiments, a single private blockchain system **109** may be associated with multiple communication sessions, where keys associated with a given communication session may be protected by a set of smart contracts or other security mechanisms that are accessible only to participants in the communication session.

(23) Once recorded to private blockchain system **109**, public key **107** may be obtained (at **106**) by UE **101-2** and/or another device or system to which the information stored in private blockchain system **109** is available. For example, as noted above, UE **101-2** may be a UE with which UE **101-**

1 is engaged in a communication session via which UE **101-1** and UE **101-2** exchange encrypted communications. UE **101-2** may identify a record stored in private blockchain system **109** that includes the identifier associated with UE **101-1**, a communication session associated with UE **101-1** and UE **101-2**, and/or some other suitable identifier. In some embodiments, UE **101-2** may be a node **111** of private blockchain system **109**, and may maintain a full copy of the blockchain stored by private blockchain system **109**. In some embodiments, private blockchain system **109** may implement or be communicatively coupled to a search system, which may provide records that match a query. For example, UE **101-2** may query private blockchain system **109** for the identifier associated with UE **101-1** and/or a communication session with UE **101-1**, and private blockchain system **109** may return one or more blocks that include the identifier associated with UE **101-1** and/or the communication session. In some embodiments, private blockchain system **109** may return, and/or UE **101-2** may otherwise identify, the latest (e.g., most current) block matching the query. In this manner, in situations where UE **101-1** has provided multiple public keys to private blockchain system **109** over time, UE **101-2** may be able to retrieve and/or otherwise identify the newest public key. Identifying the newest public key may be useful in a double ratchet technique, a Signal Protocol technique, and/or some other technique in which an updated public key is used for each message between UE **101-1** and UE **101-2**. In some embodiments, public keys may be provided with sequence numbers or other information, based on which public keys associated with communications received in a non-sequential manner (e.g., out of order) may be identified.

(24) In some embodiments, the public key may be provided as part of a Diffie-Hellman exchange or some other suitable technique in which public keys associated with multiple UEs **101** are exchanged amongst each other. UE **101-2** may accordingly maintain and/or use (at **108**) the received public key for a double ratchet technique, a Signal Protocol technique, and/or in some other technique that involves a Diffie-Hellman key exchange or other type of key exchange procedure.

(25) FIG. 2 illustrates an example of using a shared public key (e.g., shared via private blockchain system **109**, in accordance with some embodiments) in a communication technique that utilizes double ratchet techniques to secure communications between UE **101-1** and UE **101-2**. As shown, UE **101-1** and UE **101-2** may each include a respective messaging client **201**, which may send and/or receive encrypted communications. For example, messaging client **201-1**, associated with UE **101-1**, may encrypt communications based on techniques described herein, and may send the encrypted communications to messaging client **201-2** associated with UE **101-2**. Messaging client **201-2** may receive encrypted communications from UE **101-1** (e.g., from messaging client **201-1**), may decrypt the communications based on techniques described herein, and may present the decrypted communications (e.g., via a graphical user interface (“GUI”) or other suitable manner of presentation). Similarly, messaging client **201-2**, associated with UE **101-2**, may encrypt communications based on techniques described herein, and may send the encrypted communications to messaging client **201-1** associated with UE **101-1**. Messaging client **201-1** may receive encrypted communications from UE **101-2** (e.g., from messaging client **201-2**), may decrypt the communications based on techniques described herein, and may present the decrypted communications (e.g., via a GUI or other suitable manner of presentation).

(26) The encryption and/or decryption by messaging client **201-1** and/or messaging client **201-2** may be performed using a symmetric key that is generated based on a double ratchet technique, a Signal Protocol technique, and/or other suitable technique. For example, as discussed herein, the symmetric key may be used by a sender (e.g., UE **101-1**, in this example) to encrypt a communication, and may be used by a recipient (e.g., UE **101-2**, in this example) to decrypt the communication. The symmetric keys may be generated by respective Send Key Derivation Function (“KDF”) **205** and/or Receive KDF **207** associated with the sender and/or recipient. The symmetric keys may be generated based on one or more root keys provided by Root KDF **203** to Send KDF **205** and/or Receive KDF **207**. For example, Root KDF **203-1** may provide a root key

output based on a public key and a private key to Send KDF **205-1**, which may generate a send key (e.g., based on the root key output and one or more private keys) which may be used to encrypt communications to be sent by messaging client **201-1**. The private key based on which the root key output is generated may be privately maintained by UE **101-1** (e.g., not sent to UE **101-2**), while the public key may be shared with UE **101-2** via private blockchain system **109**, in accordance with embodiments described herein. Root KDF **203-1** may provide a different root key output for each message sent and/or received by messaging client **201-1**, based on a public key exchange (e.g., via a Diffie-Hellman key exchange or other suitable procedure) with UE **101-2**, which may be performed each time a message is sent by UE **101-1** and/or UE **101-2**.

(27) For example, when UE **101-1** sends a message, Root KDF **203-1** may generate a root key output, and may further output a public key based on which the root key output was generated, to private blockchain system **109**. As discussed above, the public key may be provided with a session identifier (e.g., to identify a communication session between messaging client **201-1** and messaging client **201-2**), an identifier associated with UE **101-1**, an identifier associated with UE **101-2**, and/or other suitable information based on which UE **101-2** may identify that the public key recorded to private blockchain system **109** is associated with the communication session between UE **101-1** and UE **101-2**.

(28) UE **101-2** (e.g., Root KDF **203-2**) may obtain the root public key from private blockchain system **109** based on the session identifier or other suitable identifier, and may generate a root key output based on the obtained public key and a private key (e.g., a different private key than the private key used by Root KDF **203-1** to encrypt the communication). As noted above, using private blockchain system **109** to exchange public keys may maintain the integrity of the keys, such as by preventing malicious actors from modifying or “spoofing” keys. Further, using private blockchain system **109** may aid in situations where a given UE **101** (e.g., UE **101-2**, in this example) is “offline” or is otherwise unavailable to receive public keys from another UE **101** (e.g., UE **101-1**, in this example) at the time that the other UE **101** outputs the public keys.

(29) Root KDF **203-2** may provide the root key output to Receive KDF **207-2**, which may generate a receive key based on the root key output and one or more private keys. In accordance with the double ratchet techniques, Signal Protocol techniques, etc., the receive key generated by Receive KDF **207-2** may be the same as the send key output generated by Send KDF **205-1**. In this manner, these respective send and receive keys may be an identical symmetric key that may be used to encrypt and decrypt communications, such as the encrypted communication sent by messaging client **201-1** to messaging client **201-2** in this example.

(30) While an example is provided here in the context of UE **101-1** encrypting a communication, sending the encrypted communication to UE **101-2**, and UE **101-2** decrypting the communication, similar techniques may be performed (e.g., iteratively) for communications encrypted and sent by UE **101-2** to UE **101-1**, as denoted by the dashed lines in FIG. 2. For example, Root KDF **203-2** may generate a root key pair, output a public key of the root key pair to private blockchain system **109** for retrieval by UE **101-1**, generate a root key output based on the root key pair, and provide the root key output to Send KDF **205-2**. Send KDF **205-2** may generate a send key based on the root key output and one or more private keys, and messaging client **201-2** may encrypt a communication based on the send key. Further, Root KDF **203-1** may retrieve the public key from private blockchain system **109**, generate a root key output based on the retrieved public key and one or more private keys, and provide the root key output to Receive KDF **207-1**. Receive KDF **207-1** may generate a receive key based on the root key output and one or more private keys, and messaging client **201-1** may decrypt a communication received from messaging client **201-2**, as encrypted based on a matching send key.

(31) As noted above, private blockchain system **109** may be a “private” blockchain, in that only approved UEs **101** (or other suitable devices or systems) may participate in private blockchain system **109** as nodes **111** of private blockchain system **109**. In some embodiments, eligible

participants may be identified based on an automated determination of contacts associated with one or more participant nodes **111** of private blockchain system **109**, and/or some other suitable technique. For example, as shown in FIG. 3, UE **101-1** may establish (at **301**) and/or join private blockchain system **109**. For example, UE **101-1** may establish a new private blockchain system **109** by generating a “genesis” block, and/or may join an existing private blockchain system **109**. In some embodiments, UE **101-1** may communicate with one or more devices or systems that facilitate the establishment of private blockchain system **109**.

(32) UE **101-1** may further automatically identify (at **303**) candidate participants (e.g., nodes **111** for private blockchain system **109**, devices or systems that are authorized to access information stored in private blockchain system **109**, or the like). For example, UE **101-1** may identify contacts in an address book, call history, and/or other type of contact list associated with UE **101-1**. Additionally, or alternatively, UE **101-1** and/or some other device or system may utilize artificial intelligence/machine learning (“AI/ML”) techniques or other suitable techniques to identify UEs **101** with which UE **101-1** has communicated.

(33) UE **101-1** may output (at **305**) an invitation to join (e.g., as a node **111** and/or as an authorized viewer of information stored in private blockchain system **109**) to identified UEs **101-2**, **101-3**, and **101-4**. In some embodiments, UE **101-1** (e.g., an application or application programming interface (“API”) associated with UE **101-1**) may communicate with contacts in a contact list associated with UE **101-1** (e.g., where the contacts include UEs **101-2**, **101-3**, and **101-4** in this example) via one or more suitable messaging or other types of communication applications, and may identify particular ones of the contacts participate in a key escrow or other type of key exchange. UE **101-1** may output an invitation to private blockchain system **109** to the identified contacts via the messaging or other communication applications and/or some other suitable communication pathway. In some embodiments, the invitation may include identifying information associated with UE **101-1**, such as an IP address associated with UE **101-1**, an MDN associated with UE **101-1**, an IMEI value associated with UE **101-1**, an IMSI value associated with UE **101-1**, and/or some other suitable identifier.

(34) UEs **101-2**, **101-3**, and **101-4** may accordingly join (at **307**, **309**, and **311**, respectively) private blockchain system **109**. For example, such UEs **101-2**, **101-3**, and **101-4** may register as nodes **111** using information provided (at **305**) by UE **101-1**, and/or may access information stored in private blockchain system **109** using such information. In this manner, private blockchain system **109** may be “private” inasmuch as UEs **101** which were not invited (at **305**) to private blockchain system **109** may not access the information stored in private blockchain system **109**.

(35) FIG. 4 illustrates an example of the use of private blockchain system **109** to exchange public keys in the encryption and/or decryption of secure communications between UEs **101** participating in a secure communication session. In this example, UEs **101-1**, **101-2**, **101-3**, and **101-4** may be nodes **111** of private blockchain system **109**. Further, UEs **101-1** and **101-3** may be participants in a communication session (e.g., via respective messaging clients **201** associated with UEs **101-1** and **101-3**). For example, UE **101-1** and UE **101-3** may establish (at **401**) a secure communication session using any suitable session establishment technique or protocol. The communication session may be associated with a session identifier or other suitable mechanism by which UEs **101-1** and/or **101-3** may identify the communication session. For example, an initiator of the communication session may generate or otherwise determine an identifier for the communication session, and/or UEs **101-1** and **101-3** may otherwise negotiate or determine an identifier for the communication session.

(36) UE **101-1** may further generate (at **403**) an asymmetric key pair, which may be used as part of a double ratchet technique, a Signal Protocol technique, and/or some other encryption technique used to secure communications between UEs **101-1** and **101-3**. For example, the asymmetric key pair generated (at **403**) by UE **101-1** may include a public key used in the generation of a send key used to encrypt communications sent to UE **101-3**. While not explicitly shown in FIG. 4, UE **101-3**



may also generate one or more keys that may be used in the encryption and/or decryption of messages between UEs **101-1** and **101-3**, in accordance with the double ratchet technique, Signal Protocol technique, and/or other suitable encryption technique.

(37) UE **101-1** may further provide (at **405**) the public key of the generated asymmetric key pair to private blockchain system **109**. As noted above, UEs **101-1**, **101-2**, **101-3**, and **101-4** may be nodes **111** of private blockchain system **109**. In other examples, UE **101-3** (e.g., a participant in the secure communication session) may not be a node **111** of private blockchain system **109**, and thus UE **101-1** may not directly provide (at **405**) the public key to UE **101-3**. When providing (at **405**) the public key to private blockchain system **109**, UE **101-1** may include the session identifier of the communication session between UEs **101-1** and **101-3**, and/or some other suitable identifier based on which UE **101-3** may identify (at **407**) the public key provided by UE **101-1**.

(38) For example, as discussed above, UE **101-3** may retrieve (at **407**) the public key from private blockchain system **109** based on identifying a record in private blockchain system **109** that includes the session identifier or other suitable identifier associated with UEs **101-1** and/or **101-3**. In situations where multiple blocks exist with the session identifier, UE **101-3** may identify a latest (e.g., newest) block. For example, in accordance with the double ratchet and/or Signal Protocol techniques, a new public key may be provided each time a message is sent and/or received by UE **101-1** and/or UE **101-3**. As such, identifying a latest public key associated with the communication session between UEs **101-1** and **101-3** may facilitate the secure communications according to the double ratchet and/or Signal Protocol techniques.

(39) UE **101-1** may further encrypt (at **409**) a message for UE **101-3** using a symmetric key (e.g., a send key, as similarly discussed above) that UE **101-1** generates based on the public key, one or more private keys, and/or one or more KDFs (e.g., Send KDF **205**). UE **101-1** may proceed to output (at **411**) the encrypted message to UE **101-3**. UE **101-3** may decrypt (at **413**) the message using a symmetric key (e.g., the same symmetric key as UE **101-1** used to encrypt (at **409**) the message), which may be generated by one or more KDFs (e.g., Receive KDF **207**) based on the retrieved (at **407**) public key.

(40) While FIG. **4** shows an example of one message being sent from UE **101-1** to UE **101-3**, similar techniques may be employed when UE **101-1** sends additional messages to UE **101-3**, and/or when UE **101-3** sends messages to UE **101-1**. For example, UE **101-3** may generate a subsequent asymmetric key pair that is derived from and/or is otherwise based on the retrieved (at **407**) public key, and may output a public key of the subsequent asymmetric key pair to private blockchain system **109**. UE **101-3** may utilize this subsequently generated public key to generate a send key, and UE **101-1** may utilize this subsequently generated public key, retrieved from private blockchain system **109**, to generate a receive key, as described above.

(41) FIGS. **5** and **6** illustrate example processes **500** and **600**, respectively, for utilizing blockchain techniques to share and/or exchange public keys. In the examples provided herein, the key exchange may be part of a Diffie-Hellman key exchange, a key exchange portion of a Signal Protocol technique, a key exchange portion of a double ratchet technique, and/or some other suitable secure exchange of public keys. In some embodiments, some or all of processes **500** and/or **600** may be performed by one or more UEs **101** (e.g., UEs **101** engaged in a communication session with each other and/or one or more other UEs **101**). In some embodiments, one or more other devices may perform some or all of processes **500** and/or **600** in concert with, and/or in lieu of, UE **101**.

(42) As shown, process **500** may include establishing (at **502**) a communication session with one or more UEs **101**. The communication session may be associated with a session identifier or other identifier based on which participant UEs **101** of the communication session may identify messages exchanged with one another and/or public keys, associated with the communication session, recorded to private blockchain system **109** in accordance with embodiments described herein.

(43) Process **500** may further include generating (at **504**) a set of root keys, which may include an

asymmetric key pair. For example, as discussed above, the root keys may include a private key which may be maintained securely by UE **101**, and a public key which may ultimately be shared with one or more other UEs **101** (e.g., another participant in the communication session).

(44) Process **500** may additionally include recording (at **506**) the public root key (e.g., the public key of the asymmetric key pair generated at **504**) to private blockchain system **109**. For example, UE **101** may output the public key to private blockchain system **109**, and private blockchain system **109** may propagate the information to one or more nodes **111** of private blockchain system **109**. Nodes **111** may form a consensus regarding the addition of the provided public key to one or more records of private blockchain system **109**, and may maintain an immutable record of the provided public key. In some embodiments, the record may include a timestamp, a block identifier, and/or other mechanism by which a recency or age of the record may be determined. As similarly described above, the record may further include a communication session identifier, an identifier of UE **101** from which the information was received, and/or other suitable information.

(45) Process **500** may also include utilizing (at **508**) the root keys to generate a send key. For example, as discussed above, Root KDF **203** may utilize the root keys (e.g., including the root public key, as well as the root private key and/or one or more other keys) to generate a root key output, and may provide the root key output to another KDF, such as Send KDF **205**. Send KDF **205** may generate a send key based on the root key output from Root KDF **203** and/or based on one or more other keys or functions. As discussed above, the generated send key may be a symmetric key that may be identical to a receive key generated by a recipient of the public key, based on a Signal Protocol technique, a double ratchet technique, etc.

(46) Process **500** may further include encrypting (at **510**) a communication using the send key. Process **500** may additionally include outputting (at **512**) the encrypted communication via the communication session, such as to a UE **101** with which the communication session was established (at **502**).

(47) As shown in FIG. **6**, process **600** may include establishing (at **602**) a communication session. For example, as similarly discussed above, UE **101** may establish a communication session with one or more other UEs **101**. The communication session may be associated with a suitable identifier, based on which the UEs **101** participating in the communication session may identify communications associated with the communication session, including encrypted messages, public keys, and/or other information.

(48) Process **600** may further include receiving (at **604**) an encrypted communication via the communication session. For example, the communication may have been encrypted using one or more KDFs, where the input to the one or more KDFs include the public root key and one or more other keys (e.g., one or more private keys, one or more KDF outputs, etc.).

(49) Process **600** may further include retrieving (at **606**) a public root key from private blockchain system **109**. In some embodiments, private blockchain system **109** and/or one or more devices or systems communicatively coupled to private blockchain system **109** may “push” the public root key to private blockchain system **109**. For example, the one or more devices or systems may identify a particular block that includes an identifier of UE **101** (e.g., where the particular block includes the identifier of UE **101** and a public root key), may identify a particular block that includes an identifier of the communication session (e.g., where the particular block includes the identifier of the communication session and a public root key), etc. Additionally, or alternatively, UE **101** may “pull” the information from private blockchain system **109** based on a suitable identifier (e.g., an identifier of UE **101**, an identifier of the communication session, etc.).

(50) Process **600** may additionally include utilizing (at **608**) the public root key to generate a receive key. For example, as discussed above, UE **101** may utilize one or more KDFs, such as Root KDF **203** and/or Receive KDF **207**, to generate a receive key. The receive key may be a symmetric key with respect to a key used to encrypt a communication received by UE **101** via the communication session. For example, as discussed above, the receive key may be identical to a

send key used by a sender of the communication, where the send key was also generated based on one or more KDFs and at least the public root key. For example, the sender and UE **101** may perform double ratchet techniques, Signal Protocol techniques, or the like, to respectively encrypt and decrypt the communication, without transmitting or sharing the symmetric key itself.

(51) Process **600** may further include decrypting (at **610**) the communication, received via the communication session, using the generated receive key. For example, UE **101** may apply one or more functions to decrypt the receive message using the receive key, which, as discussed above, may be the same as a send key used to encrypt the communication.

(52) Process **600** may additionally include generating (at **612**) a new set of root keys based on the previously retrieved public root key and one or more other root keys. For example, once UE **101** generates the receive key, the public root key (retrieved at **606**) may be discarded and/or not used for sending messages from UE **101**. In some situations, UE **101** may maintain the public root key and apply techniques described above to decrypt subsequent communications from the sender in situations where the sender sends multiple communications in a row without any intervening messages from UE **101**. The new set of root keys may be generated based on the receive key (generated at **608**), the public root key (retrieved at **606**), and/or one or more other suitable keys. UE **101** may then proceed to output the newly generated public root key to private blockchain system **109**, as similarly described above with respect to operation **506** of process **500**, may generate (e.g., similar to operation **508**) a new send key based on the newly generated public root key, etc.

(53) In some embodiments, the establishment of private blockchain system **109** (e.g., as referred to in FIG. 3) may be a collaborative procedure, in which nodes **111** of private blockchain system **109** are selected by active communication session participants. In this manner, the trust and/or security provided by private blockchain system **109** may be enhanced, as nodes **111** of private blockchain system **109** may be designated by participants in communication sessions that utilize private blockchain system **109** (e.g., for the exchange of keys, as discussed above). For example, as discussed below, private blockchain system **109** may be maintained by a first set of nodes that are trusted and/or otherwise selected by a first participant in a communication session as well as by a second set of nodes that are trusted and/or otherwise selected by a second participant in the communication session.

(54) As shown in FIG. 7, for example, one or more UEs **101** may include, maintain, implement, etc. node API **701**, messaging client **201**, and contact list **705**. Node API **701** may perform one or more operations described herein with respect to private blockchain system **109**, such as communicating with nodes of private blockchain system **109**, participating in the establishment of private blockchain system **109**, maintaining and/or validating records associated with private blockchain system **109** (e.g., where such records may include public keys generated by one or more communication session participants, as discussed above), or other suitable operations associated with private blockchain system **109**.

(55) Messaging client **201** may receive user input relating to messages to send from a given UE **101** to other communication session participants (e.g., other UEs **101**), receive messages from other UEs **101** (e.g., other instances of messaging client **201**), and encrypt or decrypt messages using techniques described above (e.g., using double ratchet techniques or other suitable key-based techniques). Contact list **705** may maintain a set of contacts associated with a given UE **101**, such as contacts that are trusted by the given UE **101** and/or other contacts that are otherwise candidates for participating as nodes **111** in private blockchain system **109** associated with a communication session in which UE **101** is a participant. In some embodiments, contact list **705** may include indications of which contacts are candidates for participating as nodes **111** in private blockchain system **109** from messaging application server **707** or some other source.

(56) For example, as shown in FIG. 7, a particular UE **101-1**, which includes, implements, etc. an instance of node API **701**, messaging client **201**, and contact list **705**, may register (at **702**) as a

candidate node **111** with messaging application server **707**. Such registration may indicate, for example, that UE **101-1** implements an instance of node API **701**, that a user associated with UE **101-1** has indicated a user preference or selection for UE **101-1** to be a candidate node **111**, and/or that UE **101-1** is otherwise available to act as a node **111** in one or more private blockchain systems **109** associated with one or more respective communication sessions. In some embodiments, node API **701** and/or messaging client **201** may communicate via a suitable API, via an operating system of UE **101-1**, and/or in some other suitable manner. In this manner, messaging application server **707** may maintain information indicating that UE **101-1** is a candidate node **111** for one or more private blockchain systems **109**. In some embodiments, UE **101-1** may indicate (at **702**) one or more particular UEs **101** or contacts for which UE **101-1** is eligible to participate as a node **111** (e.g., an “allow list”) and/or one or more particular UEs **101** or contacts for which UE **101-1** is not eligible to participate as a node **111** (e.g., a “block list”). Similarly, one or more other UEs **101** (e.g., UEs **101-2** through **101-M**) may also register (at **702**) as candidate nodes **111**, and may also provide allow lists and/or block lists, as discussed above.

(57) UE **101-1** may further receive (at **704**) indications of other UEs **101** that are candidate nodes **111** for one or more private blockchain systems **109** for communication sessions in which UE **101-1** may engage. For example, messaging application server **707** may provide indications that UEs **101-2** through **101-M** have registered as candidate nodes **111**. In situations where one or more UEs **101** (indicated at **704**) are not included in contact list **705**, UE **101-1** may augment contact list **705** to additionally include such additional UEs **101**. Additionally, or alternatively, UE **101-1** may discard indications (received at **704**) of UEs **101** that are not in contact list **705**, and may update contact list **705** to reflect which contacts, which are already included in contact list **705**, are candidate nodes **111**. Additionally, or alternatively, messaging application server **707** may receive or maintain a copy of contact list **705**, and may only provide (at **704**) indications of UEs **101** that are already in contact list **705**. Similarly, one or more other UEs **101** (e.g., UEs **101-2** through **101-M**) may also receive (at **704**) indications of one or more other UEs **101** that are candidate nodes **111**.

(58) In some embodiments, one or more UEs **101**, which may participate in communication sessions with one or more other UEs **101**, may refrain from registering as a candidate node **111**. For example, UE **101-N** may register (at **706**) with messaging application server **707**, without registering as a candidate node **111**. UE **101-N** may, for example, not implement node API **701**, a user of UE **101-N** may have disabled a setting or preference whereby node capability is enabled, and/or UE **101-N** may otherwise not be a candidate node **111**. In some embodiments, messaging application server **707** may provide (at **704**) indications to one or more other UEs **101** (e.g., UEs **101-1** through **101-M**) that UE **101-N** is not a candidate node **111** for one or more private blockchain systems **109** that may be associated with communication sessions in which UEs **101-1** through **101-M** engage.

(59) As such, a particular contact list **705** (e.g., as shown in FIG. **8** with respect to example UE **101-1**) may include indications of whether particular contacts (e.g., UEs **101** or other contacts) are candidate nodes **111**, in the event that UE **101-1** participates in a communication session associated with one or more private blockchain systems **109**, as discussed herein. For example, contact list **705** may include identifiers of one or more UEs **101** or users (e.g., IMSI values, MDNs, user identifiers, IP addresses, etc.), as well as indications of whether such UEs **101** or users are candidate nodes **111**.

(60) UEs **101** may use such information when establishing one or more private blockchain systems **109** associated with respective communication sessions between UEs **101**. As shown in FIG. **9**, for example, assume that UE **101-1** initiates a communication session with UE **101-2**. For example, a user of UE **101-1** may provide (at **902**) an instruction to initiate the communication session, such as by providing an identifier of UE **101-2**, an identifier of a user or account associated with UE **101-2**, etc. to messaging client **201**. In some embodiments, the instruction (provided at **902**) may include a

message to send to UE **101-2**, such as “hello” or some other initial message.

(61) For the purposes of this example, assume that a particular private blockchain system **109** has not been previously established for a communication session between UEs **101-1** and **101-2**, and/or that such private blockchain system **109** is not currently established. UE **101-1** may accordingly initiate (at **904**) a blockchain-based communication session with UE **101-2**. For example, messaging client **201** of UE **101-1** may output (at **904**) an initiation message to messaging client **201** of UE **101-2**. In some embodiments, such initiation message may be a peer-to-peer message sent directly from UE **101-1** to UE **101-2**. In some embodiments, such initiation message may be sent via messaging application server **707** and/or some other intermediary device or system. In some embodiments, the initiation message (sent at **904**) may include a request to provide at least a particular quantity of nodes **111** for private blockchain system **109**, such that a sufficient quorum, consensus, etc. may be provided via private blockchain system **109**.

(62) In this example, assume that UE **101-2** is included in contact list **705** of UE **101-1**, and contact list **705** indicates that UE **101-2** is a candidate node **111** and/or otherwise supports blockchain-based communication sessions as discussed herein. In other scenarios (e.g., where UE **101-2** is not in contact list **705** of UE **101-1**), UE **101-1** (e.g., messaging client **201** of UE **101**) may output a message (such as a Rich Communication Services (“RCS”) message or other type of message) to UE **101-2**, inquiring whether UE **101-2** supports blockchain-based communication sessions. For example, such message may include an inquiry of whether UE **101-2** implements node API **701** and/or is otherwise configured to provide and/or retrieve public keys for key exchange techniques described above. UE **101-2** (e.g., messaging client **201** of UE **101-2**) may reply to such message with an affirmative indication that UE **101-2** supports blockchain-based communications, which may be based on UE **101-2** implementing an instance of node API **701** and/or based on messaging client **201** of UE **101-2** otherwise being configured to or capable of accessing a particular private blockchain system **109** that may be established for the communication session between UEs **101-1** and **101-2**.

(63) Based on receiving (at **904**) the indication that a blockchain-based communication session between UEs **101-1** and **101-2** is being initiated, UE **101-2** may select (at **906**) a set of nodes **111** for a particular private blockchain system **109**, associated with the communication session. For example, UE **101-2** may select the set of nodes **111** from contact list **705** associated with UE **101-2**. The selection may be made on a random basis or on some other suitable basis, from particular UEs **101** included in contact list **705** that are indicated as candidate nodes **111** (e.g., as similarly described above with respect to FIG. 8).

(64) UE **101-2** may respond (at **908**) to UE **101-1**, including providing an indication of the selected nodes **111** from contact list **705** of UE **101-2**. In some embodiments, the indication of the selected nodes **111** from contact list **705** of UE **101-2** may include identifiers of such nodes **111**, such as MDNs, IP addresses, and/or other suitable identifiers of respective UEs **101** selected (at **906**) by UE **101-2**. UE **101-1** may also select (at **910**) a set of nodes **111** from contact list **705** of UE **101-1**. In some embodiments, although not explicitly shown here, UEs **101-1** and **101-2** may communicate with each other to confirm and/or validate the combined list of selected nodes (e.g., as selected by UEs **101-1** and **101-2**).

(65) Once the first set of nodes **111** is received (at **908**) from UE **101-2** and the second set of nodes **111** is selected (at **910**) by UE **101-1**, UE **101-1** may initiate (at **912**) the establishment of private blockchain system **109** with the selected nodes **111**. For example, as discussed above with respect to FIG. 3, UE **101-1** may output a private blockchain invitation to the other UEs **101** selected as nodes **111** for private blockchain system **109**, and the other UEs **101** may join private blockchain system **109**. In this manner, as noted above, private blockchain system **109** may include nodes **111** that are trusted or otherwise selected by both participants in the communication session, namely UEs **101-1** and **101-2** in this example.

(66) Situations may arise in which two different UEs **101** attempt to establish private blockchain

system **109** simultaneously or near-simultaneously for a communication session between the two different UEs **101**. Some embodiments may resolve such simultaneous establishment attempts by including additional information with communication session initiation messages, based on which such UEs **101** may be able to identify a particular one of the UEs **101** to initiate the blockchain establishment procedure (e.g., to invite other UEs **101** to private blockchain system **109**).

(67) As shown in FIG. **10**, for example, UE **101-1** may initiate (at **1002**) and/or receive an instruction to initiate a communication session with UE **101-2**. For example, a user of UE **101-1** may provide an instruction, outgoing message, or other indication to messaging client **201** of UE **101-1**, indicating that a communication session with UE **101-2** should be established. Similarly, at about the same time, UE **101-2** may receive (at **1004**) an instruction to initiate a communication session with UE **101-1**. In accordance with some embodiments, UEs **101-1** and **101-2** may each generate (at **1002** and **1004**, respectively) a random number using random number generation (“RNG”) techniques or other suitable techniques. For example, UE **101-1** may generate (at **1002**) a first random number RNG.sub.1, and UE **101-2** may generate (at **1004**) a second random number RNG.sub.2. In some embodiments, in situations where UE **101-2** receives (at **1004**) one or more messages to send to UE **101-1** via the communication session, UE **101-2** may forgo sending such messages until after a private blockchain system **109**, associated with the communication session, has been established. For example, once such private blockchain system **109** has been established, UE **101-2** may encrypt the one or more messages using techniques described above, and may provide one or more keys that may be used to decrypt the one or more messages to private blockchain system **109** (e.g., where UE **101-1** may retrieve such keys from private blockchain system **109**).

(68) In some embodiments, the random numbers generated by UEs **101-1** and/or **101-2** may be, include and/or, may be derived from one or more non-random or pseudorandom numbers. For example, in some embodiments, the random number for a particular UE **101** may be generated based on an identifier of the particular UE **101**, such as an MDN, an IP address, an IMSI value, and/or some other unique identifier (or some portion thereof, such as the last four digits of the MDN) of the particular UE **101**. For example, the identifier of the particular UE **101** may be, or may be included in, a “seed” based on which the random number is generated. Additionally, or alternatively, the identifier of the particular UE **101** may be appended to, prepended to, and/or otherwise incorporated in a randomly generated number. For example, in such instances, the randomly generated numbers may include a random number component and an identifier component. As one example, assume that the last four digits of the MDN of UE **101-1** are 9999 and that UE **101-1** generates a random number 12345. In some embodiments, in this example, RNG.sub.1 may be 1234599999 (e.g., the last four digits of the MDN appended to the randomly generated number), 99991234 (e.g., the last four digits of the MDN prepended to the randomly generated number), 19293949 (e.g., the last four digits of the MDN dispersed within the randomly generated number in a preset pattern), 91239949 (e.g., the last four digits of the MDN dispersed within the randomly generated number in a random order), etc. In this manner, since the randomly generated numbers include and/or otherwise based on unique identifiers of the participant UEs **101**, the randomly generated numbers may be relatively unlikely or impossible to be the same, thus eliminating potential ambiguity.

(69) Based on the initiation (at **1002**) of the communication session, at UE **101-1**, between UEs **101-1** and **101-2** (e.g., based on a user selection via messaging client **201** at UE **101-1**), UE **101-1** may output (at **1006**) a blockchain-based communication session initiation message to UE **101-2**, as similarly discussed above. For example, the initiation message may indicate that UE **101-2** should select one or more nodes **111** to maintain private blockchain system **109** associated with the communication session between UEs **101-1** and **101-2**, and/or may include a request for a particular quantity of nodes **111** (or at least the particular quantity). In some embodiments, the initiation message may also include RNG.sub.1, as generated (at **1002**) by UE **101-1**.

(70) Prior to receiving or otherwise identifying the receipt of the initiation message from UE **101-1**, UE **101-2** may output (at **1008**) a blockchain-based communication session initiation message to UE **101-1**, including RNG.sub.2 as generated (at **1004**) by UE **101-2**. For example, due to transmission and/or processing delay, UE **101-2** may not have received the initiation message from UE **101-1**. Thus, at this stage, both UEs **101-1** and **101-2** may each be attempting to establish a separate instance of private blockchain system **109** for a communication session between the same active participants (i.e., participant UEs **101-1** and **101-2**).

(71) In some embodiments, the blockchain-based communication session initiation message may be distinct from a blockchain-based communication session initiation response (e.g., at **908** in FIG. **9**). For example, the blockchain-based communication session initiation message (e.g., as provided at **1006** and **1008**) may include a first message type identifier, code, etc., while the blockchain-based communication session initiation response (e.g., at **908** in FIG. **9**) may include a second message type identifier, code, etc. In this manner, UEs **101-1** and **101-2** may be able to differentiate between the two different types of messages.

(72) UEs **101-1** and **101-2** may both identify (at **1010** and **1012**, respectively) that UE **101-1** has priority to establish private blockchain system **109** for the communication session between UEs **101-1** and **101-2**. For example, in some embodiments, UEs **101-1** and **101-2** may each compare (at **1010** and **1012**, respectively) RNG.sub.1 and RNG.sub.2, and may select the same particular UE (i.e., UE **101-1** in this example) to initiate the establishment of private blockchain system **109** (e.g., to invite other nodes **111**). For example, UEs **101-1** and **101-2** may be configured to select the lowest value between RNG.sub.1 and RNG.sub.2 or, in some embodiments, the highest value between RNG.sub.1 and RNG.sub.2. In some embodiments, UEs **101-1** and **101-2** may perform one or more functions (e.g., the same one or more functions) on RNG.sub.1 and/or RNG.sub.2, based on which UEs **101-1** and **101-2** may select the same particular UE (i.e., UE **101-1** in this example) to initiate the establishment of private blockchain system **109**.

(73) Since UE **101-1** has received (at **1008**) an initiation message from UE **101-2**, UE **101-1** may forgo outputting a request for nodes **111** from UE **101-2** and/or may forgo outputting an inquiry of whether UE **101-2** supports blockchain-based communications, as the initiation message may indicate that UE **101-2** supports blockchain-based communications. Accordingly, UE **101-1** may select (at **1010**) one or more nodes **111** to participate in private blockchain system **109** (e.g., from contact list **705** associated with UE **101-1**, as discussed above).

(74) Further, since UE **101-2** has received (at **1006**) the initiation message from UE **101-1** and has determined (at **1012**) that UE **101-1** has priority to establish private blockchain system **109** associated with the communication session (e.g., based on the comparison of the randomly generated numbers provided by UEs **101-1** and **101-2**), UE **101-2** may select one or more nodes **111** to participate in private blockchain system **109** e.g., from contact list **705** associated with UE **101-2**, as discussed above). UE **101-2** may further provide (at **1014**) an indication of the nodes **111** selected (at **1012**) by UE **101-2**, and UE **101-1** may proceed to initiate (at **1016**) the establishment of private blockchain system **109** associated with the communication session in a manner similarly discussed above.

(75) FIG. **11** illustrates an example situation in which a communication session is simultaneously (or nearly simultaneously) initiated (at **1102** and **1104**) at different UEs **101** (i.e., UEs **101-1** and **101-2**, in this example). In this example, UE **101-2** may receive (at **1106**) a blockchain-based communication session initiation message, as well as a randomly generated number (e.g., RNG.sub.1) from UE **101-1** prior to outputting a blockchain-based communication session initiation message to UE **101-1**. For example, such a circumstance may occur when UE **101-2** is processing the communication session initiation (at **1104**), when UE **101-2** is in the midst of generating a blockchain-based communication session initiation message for UE **101-1**, and/or otherwise before UE **101-2** sends a blockchain-based communication session initiation message for UE **101-1** (e.g., as performed at **1008** in FIG. **10**). For example, a user of UE **101-2** may select, via

messaging client **201** of UE **101-2**, an option to send a message to UE **101-1** (but may not yet have entered the message and/or may not yet have selected a “send” option) or may otherwise indicate that a communication session should be established with UE **101-1**.

(76) As such, even though UE **101-2** has received (at **1104**) a selection to initiate a communication with UE **101-1**, UE **101-2** may forgo outputting a blockchain-based communication session initiation message for UE **101-1** based on receiving (at **1106**) the blockchain-based communication session initiation message from UE **101-1**. UE **101-2** may identify that UE **101-1** has priority to establish private blockchain system **109** for the communication session between UEs **101-1** and **101-2**, based on the receipt (at **1106**) of the blockchain-based communication session initiation message from UE **101-1** and further based on forgoing outputting such message to UE **101-2**. That is, in this instance, there may not be the potential ambiguity introduced by the simultaneous or near-simultaneous sending of blockchain-based communication session initiation messages (e.g., as shown in FIG. **10** at **1006** and **1008**). Accordingly, even though the blockchain-based communication session initiation message from UE **101-1** included a randomly generated number (e.g., RNG.sub.1) and UE **101-2** generated (at **1104**) a randomly generated number (e.g., RNG.sub.2), UEs **101-1** and **101-2** may forgo using the randomly generated numbers to determine which UE **101** has priority to establish private blockchain system **109**.

(77) UE **101-2** may accordingly select (at **1108**) nodes **111** for private blockchain system **109**, and may output (at **1110**) an indication of the selected nodes **111** to UE **101-1**. UE **101-1** may also select (at **1112**) another set of nodes **111** for private blockchain system **109**, and may initiate (at **1114**) the establishment of private blockchain system **109** with nodes **111** selected (at **1108** and **1112**) by UEs **101-1** and **101-2**.

(78) FIG. **12** illustrates an example process **1200** for collaboratively establishing a private blockchain system **109** associated with a communication session between respective participant UEs **101**. In some embodiments, some or all of process **1200** may be performed by a particular UE **101** (e.g., a particular participant in the communication session, referred to below as a first UE **101-1**).

(79) As shown, process **1200** may include receiving (at **1202**) an indication to establish a communication session with a second UE **101-2**. For example, UE **101-1** may receive an indication from a user and/or some other indication via messaging client **201** associated with UE **101-1** that one or more messages should be sent to UE **101-2**.

(80) Process **1200** may also include generating (at **1204**) a first value based on the received indication. For example, UE **101-1** may generate a randomly generated number. As discussed above, the randomly generated number may include and/or may be based on a non-random value, such as a unique identifier of UE **101-1** (e.g., an IP address, an MDN, an IMSI value, etc.). In some embodiments, the first value may be a non-random value, such as the unique identifier of UE **101-1** and/or some other type of non-random value. In some embodiments, UE **101-1** may perform one or more other operations associated with the communication session, such as generating one or more keys which may be used to encrypt and/or decrypt messages associated with the communication session, as discussed above.

(81) Process **1200** may further include selecting (at **1206**) a set of nodes **111** to participate in private blockchain system **109** associated with the communication session. For example, as discussed above, UE **101-1** may select one or more contacts, UEs **101**, etc. from contact list **705** associated with UE **101-1**. In some embodiments, as discussed above, UE **101-1** may select from contacts for which UE **101-1** maintains or receives information that such contacts are eligible, available, opted in, etc. for participation in private blockchain system **109** (e.g., to receive, maintain, and provide records including keys associated with the communication session).

(82) Process **1200** may further include outputting (at **1208**) a request, including the first value, to the second UE **101-2**. The request may include a request to establish the communication session. In some embodiments, the request may include and/or may be based on an inquiry to the second UE



**101-2**, inquiring whether UE **101-2** supports blockchain-based communication sessions (e.g., a blockchain-based key exchange as described above). In some embodiments, the request may include an indication or instruction that a blockchain-based key exchange will be associated with the communication session. In some embodiments, the request may include a request to provide information regarding nodes **111**, selected by UE **101-2**, to participate in private blockchain system **109** associated with the communication session. In some embodiments, the request may specify a particular quantity of nodes to provide in order to establish a quorum, consensus, etc. associated with private blockchain system **109**.

(83) As discussed above, the first UE **101-1** may receive one or more different types of responses from the second UE **101-2**. For example, the varied responses may be based on whether UE **101-2** is simultaneously attempting to initiate a communication session with UE **101-1** (e.g., a separate attempt to establish the same communication session with the same active participants). In the event that UE **101-2** is not attempting to simultaneously initiate a communication session with UE **101-1**, UE **101-1** may receive (at **1210**) a response from UE **101-2**, including a list of nodes **111** to participate in private blockchain system **109** associated with the communication session. As discussed above, the list of nodes **111** received from UE **101-2** may have been selected by UE **101-2**, such as from contact list **705** associated with UE **101-2**.

(84) Process **1200** may additionally include initiating (at **1212**) a blockchain establishment procedure with nodes **111** selected by UEs **101-1** and/or UE **101-2**. For example, as discussed above, UE **101-1** may output invitation messages and/or one or more other types of messages to the selected nodes **111**. In some embodiments, UE **101-1** may perform one or more other operations relating to the establishment of private blockchain system **109**, such as generating, validating, signing, providing, etc. a genesis block of private blockchain system **109** to nodes **111**.

(85) As discussed above, in other situations, UE **101-2** may have not received the request (provided at **1208**) prior to outputting a request of its own to UE **101-1**. For example, such situations may occur when the request (at **1208**) from UE **101-1** has not been received, processed, etc. by UE **101-2** prior to UE **101-2** outputting the request to UE **101-1**. As such, UE **101-1** may receive (at **1214**) the request, including a second value (e.g., a second randomly generated value and/or some other value) from UE **101-2**, to establish the communication session.

(86) Based on determining that UE **101-2** has requested the same communication session, having the same active participant UEs **101-1** and **101-2** (e.g., in lieu of providing a response message to the request from UE **101-1**), UE **101-1** may compare (at **1216**) the first value to the second value. Similarly, UE **101-2** may also compare the first value to the second value. Based on the comparing, UE **101-1** (and/or UE **101-2**) may determine (at **1218**) whether the first UE **101-1** should establish private blockchain system **109** associated with the communication session. For example, UEs **101-1** and **101-2** may both use the same criteria, logic, functions, etc. to compare the first and second values and determine which UE **101** should establish private blockchain system **109**.

(87) If, based on the comparing, the first UE **101-1** should establish private blockchain system **109** (at **1218**—YES), UE **101-1** may receive (at **1210**) a list of nodes **111** from UE **101-2**. For example, as discussed above, UE **101-2** may select the list of nodes **111** based on determining that the first UE **101-1** should establish private blockchain system **109**. UE **101-1** may then proceed to initiate (at **1212**) the establishment of private blockchain system **109** with the nodes **111** selected by UEs **101-1** and/or **101-2**.

(88) If, on the other hand, based on the comparing, the first UE **101-1** should not establish private blockchain system **109** (at **1218**—NO), then UE **101-1** may output (at **1220**) the list of nodes (selected by UE **101-1** at **1206**) to UE **101-2**. In this situation, UE **101-2** may initiate the establishment of private blockchain system **109** with the nodes **111** selected by UEs **101-1** and/or **101-2**. Once private blockchain system **109** is established, UEs **101-1** and **101-2** may proceed to send encrypted messages to each other via the communication session, and may provide keys (e.g., public keys) to private blockchain system **109** along with communication session identifiers, such

that UEs **101-1** and **101-2** may be able to retrieve keys provided by each other and decrypt the encrypted messages (e.g., using a double ratchet technique or other suitable encryption technique). (89) FIG. **13** illustrates an example environment **1300**, in which one or more embodiments may be implemented. In some embodiments, environment **1300** may correspond to a Fifth Generation (“5G”) network, and/or may include elements of a 5G network. In some embodiments, environment **1300** may correspond to a 5G Non-Standalone (“NSA”) architecture, in which a 5G radio access technology (“RAT”) may be used in conjunction with one or more other RATs (e.g., a Long-Term Evolution (“LTE”) RAT), and/or in which elements of a 5G core network may be implemented by, may be communicatively coupled with, and/or may include elements of another type of core network (e.g., an evolved packet core (“EPC”)). As shown, environment **1300** may include UE **101**, RAN **1310** (which may include one or more Next Generation Node Bs (“gNBs”) **1311**), RAN **1312** (which may include one or more evolved Node Bs (“eNBs”) **1313**), and various network functions such as Access and Mobility Management Function (“AMF”) **1315**, Mobility Management Entity (“MME”) **1316**, Serving Gateway (“SGW”) **1317**, Session Management Function (“SMF”)/Packet Data Network (“PDN”) Gateway (“PGW”)-Control plane function (“PGW-C”) **1320**, Policy Control Function (“PCF”)/Policy Charging and Rules Function (“PCRF”) **1325**, Application Function (“AF”) **1330**, User Plane Function (“UPF”)/PGW-User plane function (“PGW-U”) **1335**, Home Subscriber Server (“HSS”)/Unified Data Management (“UDM”) **1340**, Authentication Server Function (“AUSF”) **1345**, and messaging application server **707**.

Environment **1300** may also include one or more networks, such as Data Network (“DN”) **1350**. (90) The example shown in FIG. **13** illustrates one instance of each network component or function (e.g., one instance of SMF/PGW-C **1320**, PCF/PCRF **1325**, UPF/PGW-U **1335**, HSS/UDM **1340**, and/or AUSF **1345**). In practice, environment **1300** may include multiple instances of such components or functions. For example, in some embodiments, environment **1300** may include multiple “slices” of a core network, where each slice includes a discrete set of network functions (e.g., one slice may include a first instance of SMF/PGW-C **1320**, PCF/PCRF **1325**, UPF/PGW-U **1335**, HSS/UDM **1340**, and/or AUSF **1345**, while another slice may include a second instance of SMF/PGW-C **1320**, PCF/PCRF **1325**, UPF/PGW-U **1335**, HSS/UDM **1340**, and/or AUSF **1345**). The different slices may provide differentiated levels of service, such as service in accordance with different Quality of Service (“QoS”) parameters.

(91) The quantity of devices and/or networks, illustrated in FIG. **13**, is provided for explanatory purposes only. In practice, environment **1300** may include additional devices and/or networks, fewer devices and/or networks, different devices and/or networks, or differently arranged devices and/or networks than illustrated in FIG. **13**. For example, while not shown, environment **1300** may include devices that facilitate or enable communication between various components shown in environment **1300**, such as routers, modems, gateways, switches, hubs, etc. Alternatively, or additionally, one or more of the devices of environment **1300** may perform one or more network functions described as being performed by another one or more of the devices of environment **1300**. Devices of environment **1300** may interconnect with each other and/or other devices via wired connections, wireless connections, or a combination of wired and wireless connections. In some implementations, one or more devices of environment **1300** may be physically integrated in, and/or may be physically attached to, one or more other devices of environment **1300**.

(92) UE **101** may include a computation and communication device, such as a wireless mobile communication device that is capable of communicating with RAN **1310**, RAN **1312**, and/or DN **1350**. UE **101** may be, or may include, a radiotelephone, a personal communications system (“PCS”) terminal (e.g., a device that combines a cellular radiotelephone with data processing and data communications capabilities), a personal digital assistant (“PDA”) (e.g., a device that may include a radiotelephone, a pager, Internet/intranet access, etc.), a smart phone, a laptop computer, a tablet computer, a camera, a personal gaming system, an IoT device (e.g., a sensor, a smart home appliance, or the like), a wearable device, an Internet of Things (“IoT”) device, a Machine-to-

Machine (“M2M”) device, or another type of mobile computation and communication device. UE **101** may send traffic to and/or receive traffic (e.g., user plane traffic) from DN **1350** via RAN **1310**, RAN **1312**, and/or UPF/PGW-U **1335**. In some embodiments, as discussed above, a group of UEs **101** may implement, maintain, interact with, access, etc. one or more private blockchain systems **109** (e.g., where different private blockchain systems **109** may be associated with different communication sessions between different UEs **101**).

(93) RAN **1310** may be, or may include, a 5G RAN that includes one or more base stations (e.g., one or more gNBs **1311**), via which UE **101** may communicate with one or more other elements of environment **1300**. UE **101** may communicate with RAN **1310** via an air interface (e.g., as provided by gNB **1311**). For instance, RAN **1310** may receive traffic (e.g., voice call traffic, data traffic, messaging traffic, signaling traffic, etc.) from UE **101** via the air interface, and may communicate the traffic to UPF/PGW-U **1335**, and/or one or more other devices or networks. Similarly, RAN **1310** may receive traffic intended for UE **101** (e.g., from UPF/PGW-U **1335**, AMF **1315**, and/or one or more other devices or networks) and may communicate the traffic to UE **101** via the air interface.

(94) RAN **1312** may be, or may include, a LTE RAN that includes one or more base stations (e.g., one or more eNBs **1313**), via which UE **101** may communicate with one or more other elements of environment **1300**. UE **101** may communicate with RAN **1312** via an air interface (e.g., as provided by eNB **1313**). For instance, RAN **1310** may receive traffic (e.g., voice call traffic, data traffic, messaging traffic, signaling traffic, etc.) from UE **101** via the air interface, and may communicate the traffic to UPF/PGW-U **1335**, and/or one or more other devices or networks. Similarly, RAN **1310** may receive traffic intended for UE **101** (e.g., from UPF/PGW-U **1335**, SGW **1317**, and/or one or more other devices or networks) and may communicate the traffic to UE **101** via the air interface.

(95) AMF **1315** may include one or more devices, systems, Virtualized Network Functions (“VNFs”), etc., that perform operations to register UE **101** with the 5G network, to establish bearer channels associated with a session with UE **101**, to hand off UE **101** from the 5G network to another network, to hand off UE **101** from the other network to the 5G network, manage mobility of UE **101** between RANs **1310** and/or gNBs **1311**, and/or to perform other operations. In some embodiments, the 5G network may include multiple AMFs **1315**, which communicate with each other via the N14 interface (denoted in FIG. **13** by the line marked “N14” originating and terminating at AMF **1315**).

(96) MME **1316** may include one or more devices, systems, VNFs, etc., that perform operations to register UE **101** with the EPC, to establish bearer channels associated with a session with UE **101**, to hand off UE **101** from the EPC to another network, to hand off UE **101** from another network to the EPC, manage mobility of UE **101** between RANs **1312** and/or eNBs **1313**, and/or to perform other operations.

(97) SGW **1317** may include one or more devices, systems, VNFs, etc., that aggregate traffic received from one or more eNBs **1313** and send the aggregated traffic to an external network or device via UPF/PGW-U **1335**. Additionally, SGW **1317** may aggregate traffic received from one or more UPF/PGW-Us **1335** and may send the aggregated traffic to one or more eNBs **1313**. SGW **1317** may operate as an anchor for the user plane during inter-eNB handovers and as an anchor for mobility between different telecommunication networks or RANs (e.g., RANs **1310** and **1312**).

(98) SMF/PGW-C **1320** may include one or more devices, systems, VNFs, etc., that gather, process, store, and/or provide information in a manner described herein. SMF/PGW-C **1320** may, for example, facilitate the establishment of communication sessions on behalf of UE **101**. In some embodiments, the establishment of communications sessions may be performed in accordance with one or more policies provided by PCF/PCRF **1325**.

(99) PCF/PCRF **1325** may include one or more devices, systems, VNFs, etc., that aggregate information to and from the 5G network and/or other sources. PCF/PCRF **1325** may receive

information regarding policies and/or subscriptions from one or more sources, such as subscriber databases and/or from one or more users (such as, for example, an administrator associated with PCF/PCRF **1325**).

(100) AF **1330** may include one or more devices, systems, VNFs, etc., that receive, store, and/or provide information that may be used in determining parameters (e.g., quality of service parameters, charging parameters, or the like) for certain applications.

(101) UPF/PGW-U **1335** may include one or more devices, systems, VNFs, etc., that receive, store, and/or provide data (e.g., user plane data). For example, UPF/PGW-U **1335** may receive user plane data (e.g., voice call traffic, data traffic, etc.), destined for UE **101**, from DN **1350**, and may forward the user plane data toward UE **101** (e.g., via RAN **1310**, SMF/PGW-C **1320**, and/or one or more other devices). In some embodiments, multiple UPFs **1335** may be deployed (e.g., in different geographical locations), and the delivery of content to UE **101** may be coordinated via the N9 interface (e.g., as denoted in FIG. **13** by the line marked “N9” originating and terminating at UPF/PGW-U **1335**). Similarly, UPF/PGW-U **1335** may receive traffic from UE **101** (e.g., via RAN **1310**, SMF/PGW-C **1320**, and/or one or more other devices), and may forward the traffic toward DN **1350**. In some embodiments, UPF/PGW-U **1335** may communicate (e.g., via the N4 interface) with SMF/PGW-C **1320**, regarding user plane data processed by UPF/PGW-U **1335**.

(102) HSS/UDM **1340** and AUSF **1345** may include one or more devices, systems, VNFs, etc., that manage, update, and/or store, in one or more memory devices associated with AUSF **1345** and/or HSS/UDM **1340**, profile information associated with a subscriber. AUSF **1345** and/or HSS/UDM **1340** may perform authentication, authorization, and/or accounting operations associated with the subscriber and/or a communication session with UE **101**.

(103) DN **1350** may include one or more wired and/or wireless networks. For example, DN **1350** may include an Internet Protocol IP-based PDN, a wide area network (“WAN”) such as the Internet, a private enterprise network, and/or one or more other networks. UE **101** may communicate, through DN **1350**, with data servers, other UEs **101**, and/or to other servers or applications that are coupled to DN **1350**. DN **1350** may be connected to one or more other networks, such as a public switched telephone network (“PSTN”), a public land mobile network (“PLMN”), and/or another network. DN **1350** may be connected to one or more devices, such as content providers, applications, web servers, and/or other devices, with which UE **101** may communicate.

(104) FIG. **14** illustrates an example Distributed Unit (“DU”) network **1400**, which may be included in and/or implemented by one or more RANs (e.g., RAN **1310**, RAN **1312**, or some other RAN). In some embodiments, a particular RAN may include one DU network **1400**. In some embodiments, a particular RAN may include multiple DU networks **1400**. In some embodiments, DU network **1400** may correspond to a particular gNB **1311** of a 5G RAN (e.g., RAN **1310**). In some embodiments, DU network **1400** may correspond to multiple gNBs **1311**. In some embodiments, DU network **1400** may correspond to one or more other types of base stations of one or more other types of RANs. As shown, DU network **1400** may include Centralized Unit (“CU”) **1405**, one or more Distributed Units (“DUs”) **1403-1** through **1403-N** (referred to individually as “DU **1403**,” or collectively as “DUs **1403**”), and one or more Radio Units (“RUs”) **1401-1** through **1401-M** (referred to individually as “RU **1401**,” or collectively as “RUs **1401**”).

(105) CU **1405** may communicate with a core of a wireless network (e.g., may communicate with one or more of the devices or systems described above with respect to FIG. **13**, such as AMF **1315** and/or UPF/PGW-U **1335**). In the uplink direction (e.g., for traffic from UEs **101** to a core network), CU **1405** may aggregate traffic from DUs **1403**, and forward the aggregated traffic to the core network. In some embodiments, CU **1405** may receive traffic according to a given protocol (e.g., Radio Link Control (“RLC”)) from DUs **1403**, and may perform higher-layer processing (e.g., may aggregate/process RLC packets and generate Packet Data Convergence Protocol (“PDCP”) packets based on the RLC packets) on the traffic received from DUs **1403**.

(106) In accordance with some embodiments, CU **1405** may receive downlink traffic (e.g., traffic from the core network) for a particular UE **101**, and may determine which DU(s) **1403** should receive the downlink traffic. DU **1403** may include one or more devices that transmit traffic between a core network (e.g., via CU **1405**) and UE **101** (e.g., via a respective RU **1401**). DU **1403** may, for example, receive traffic from RU **1401** at a first layer (e.g., physical (“PHY”) layer traffic, or lower PHY layer traffic), and may process/aggregate the traffic to a second layer (e.g., upper PHY and/or RLC). DU **1403** may receive traffic from CU **1405** at the second layer, may process the traffic to the first layer, and provide the processed traffic to a respective RU **1401** for transmission to UE **101**.

(107) RU **1401** may include hardware circuitry (e.g., one or more RF transceivers, antennas, radios, and/or other suitable hardware) to communicate wirelessly (e.g., via an RF interface) with one or more UEs **101**, one or more other DUs **1403** (e.g., via RUs **1401** associated with DUs **1403**), and/or any other suitable type of device. In the uplink direction, RU **1401** may receive traffic from UE **101** and/or another DU **1403** via the RF interface and may provide the traffic to DU **1403**. In the downlink direction, RU **1401** may receive traffic from DU **1403**, and may provide the traffic to UE **101** and/or another DU **1403**.

(108) RUs **1401** may, in some embodiments, be communicatively coupled to one or more Multi-Access/Mobile Edge Computing (“MEC”) devices, referred to sometimes herein simply as “MECs” **1407**. For example, RU **1401-1** may be communicatively coupled to MEC **1407-1**, RU **1401-M** may be communicatively coupled to MEC **1407-M**, DU **1403-1** may be communicatively coupled to MEC **1407-2**, DU **1403-N** may be communicatively coupled to MEC **1407-N**, CU **1405** may be communicatively coupled to MEC **1407-3**, and so on. MECs **1407** may include hardware resources (e.g., configurable or provisionable hardware resources) that may be configured to provide services and/or otherwise process traffic to and/or from UE **101**, via a respective RU **1401**.

(109) For example, RU **1401-1** may route some traffic, from UE **101**, to MEC **1407-1** instead of to a core network (e.g., via DU **1403** and CU **1405**). MEC **1407-1** may process the traffic, perform one or more computations based on the received traffic, and may provide traffic to UE **101** via RU **1401-1**. In this manner, ultra-low latency services may be provided to UE **101**, as traffic does not need to traverse DU **1403**, CU **1405**, and an intervening backhaul network between DU network **1400** and the core network. In some embodiments, MEC **1407** may include, and/or may implement, some or all of the functionality described above with respect to one or more nodes **111**.

(110) FIG. **15** illustrates example components of device **1500**. One or more of the devices described above may include one or more devices **1500**. Device **1500** may include bus **1510**, processor **1520**, memory **1530**, input component **1540**, output component **1550**, and communication interface **1560**. In another implementation, device **1500** may include additional, fewer, different, or differently arranged components.

(111) Bus **1510** may include one or more communication paths that permit communication among the components of device **1500**. Processor **1520** may include a processor, microprocessor, or processing logic that may interpret and execute instructions. In some embodiments, processor **1520** may be or may include one or more hardware processors. Memory **1530** may include any type of dynamic storage device that may store information and instructions for execution by processor **1520**, and/or any type of non-volatile storage device that may store information for use by processor **1520**.

(112) Input component **1540** may include a mechanism that permits an operator to input information to device **1500** and/or other receives or detects input from a source external to **1540**, such as a touchpad, a touchscreen, a keyboard, a keypad, a button, a switch, a microphone or other audio input component, etc. In some embodiments, input component **1540** may include, or may be communicatively coupled to, one or more sensors, such as a motion sensor (e.g., which may be or may include a gyroscope, accelerometer, or the like), a location sensor (e.g., a Global Positioning System (“GPS”)-based location sensor or some other suitable type of location sensor or location

determination component), a thermometer, a barometer, and/or some other type of sensor. Output component **1550** may include a mechanism that outputs information to the operator, such as a display, a speaker, one or more light emitting diodes (“LEDs”), etc.

(113) Communication interface **1560** may include any transceiver-like mechanism that enables device **1500** to communicate with other devices and/or systems. For example, communication interface **1560** may include an Ethernet interface, an optical interface, a coaxial interface, or the like. Communication interface **1560** may include a wireless communication device, such as an infrared (“IR”) receiver, a Bluetooth® radio, or the like. The wireless communication device may be coupled to an external device, such as a remote control, a wireless keyboard, a mobile telephone, etc. In some embodiments, device **1500** may include more than one communication interface **1560**. For instance, device **1500** may include an optical interface and an Ethernet interface.

(114) Device **1500** may perform certain operations relating to one or more processes described above. Device **1500** may perform these operations in response to processor **1520** executing software instructions stored in a computer-readable medium, such as memory **1530**. A computer-readable medium may be defined as a non-transitory memory device. A memory device may include space within a single physical memory device or spread across multiple physical memory devices. The software instructions may be read into memory **1530** from another computer-readable medium or from another device. The software instructions stored in memory **1530** may cause processor **1520** to perform processes described herein. Alternatively, hardwired circuitry may be used in place of or in combination with software instructions to implement processes described herein. Thus, implementations described herein are not limited to any specific combination of hardware circuitry and software.

(115) The foregoing description of implementations provides illustration and description, but is not intended to be exhaustive or to limit the possible implementations to the precise form disclosed. Modifications and variations are possible in light of the above disclosure or may be acquired from practice of the implementations.

(116) For example, while series of blocks and/or signals have been described above (e.g., with regard to FIGS. **1-12**), the order of the blocks and/or signals may be modified in other implementations. Further, non-dependent blocks and/or signals may be performed in parallel. Additionally, while the figures have been described in the context of particular devices performing particular acts, in practice, one or more other devices may perform some or all of these acts in lieu of, or in addition to, the above-mentioned devices.

(117) The actual software code or specialized control hardware used to implement an embodiment is not limiting of the embodiment. Thus, the operation and behavior of the embodiment has been described without reference to the specific software code, it being understood that software and control hardware may be designed based on the description herein.

(118) In the preceding specification, various example embodiments have been described with reference to the accompanying drawings. It will, however, be evident that various modifications and changes may be made thereto, and additional embodiments may be implemented, without departing from the broader scope of the invention as set forth in the claims that follow. The specification and drawings are accordingly to be regarded in an illustrative rather than restrictive sense.

(119) Even though particular combinations of features are recited in the claims and/or disclosed in the specification, these combinations are not intended to limit the disclosure of the possible implementations. In fact, many of these features may be combined in ways not specifically recited in the claims and/or disclosed in the specification. Although each dependent claim listed below may directly depend on only one other claim, the disclosure of the possible implementations includes each dependent claim in combination with every other claim in the claim set.

(120) Further, while certain connections or devices are shown, in practice, additional, fewer, or different, connections or devices may be used. Furthermore, while various devices and networks

are shown separately, in practice, the functionality of multiple devices may be performed by a single device, or the functionality of one device may be performed by multiple devices. Further, multiple ones of the illustrated networks may be included in a single network, or a particular network may include multiple networks. Further, while some devices are shown as communicating with a network, some such devices may be incorporated, in whole or in part, as a part of the network.

(121) To the extent the aforementioned implementations collect, store, or employ personal information of individuals, groups or other entities, it should be understood that such information shall be used in accordance with all applicable laws concerning protection of personal information. Additionally, the collection, storage, and use of such information can be subject to consent of the individual to such activity, for example, through well known “opt-in” or “opt-out” processes as can be appropriate for the situation and type of information. Storage and use of personal information can be in an appropriately secure manner reflective of the type of information, for example, through various access control, encryption and anonymization techniques for particularly sensitive information.

(122) No element, act, or instruction used in the present application should be construed as critical or essential unless explicitly described as such. An instance of the use of the term “and,” as used herein, does not necessarily preclude the interpretation that the phrase “and/or” was intended in that instance. Similarly, an instance of the use of the term “or,” as used herein, does not necessarily preclude the interpretation that the phrase “and/or” was intended in that instance. Also, as used herein, the article “a” is intended to include one or more items, and may be used interchangeably with the phrase “one or more.” Where only one item is intended, the terms “one,” “single,” “only,” or similar language is used. Further, the phrase “based on” is intended to mean “based, at least in part, on” unless explicitly stated otherwise.

## Claims

1. A first device, comprising: one or more hardware processors configured to: output, to a second device, a first request to establish a communication session between the first device and the second device, wherein the request includes a first value; receive, from the second device, a second request to establish the communication session between the first device and the second device, wherein the second request includes a second value; compare the first value, included in the first request outputted by the first device, with the second value included in the second request received from the second device; determine, based on comparing the first and second values, that the first device has priority, wherein the second device also determines, based on the first and second values, that the first device has priority; output, based on determining that the first device has priority, a blockchain establishment message to a set of devices that includes a third device, wherein the first device and the set of devices establish a blockchain that is accessible to the first and second devices, wherein the second device forgoes outputting a blockchain establishment message based on determining that the first device has priority; encrypt a communication associated with the communication session using a double ratchet encryption technique; record, to the blockchain associated with the communication session, one or more keys associated with the encrypting of the communication using the double ratchet encryption technique; and output the encrypted communication to the second device via the communication session, wherein the second device retrieves the one or more keys from the blockchain and uses the one or more keys to decrypt the encrypted communication.
2. The first device of claim 1, wherein the first value includes a first randomly generated number and wherein the second value includes a second randomly generated number.
3. The first device of claim 1, wherein the first value is based on a first unique identifier associated with the first device, and wherein the second value is associated with a second unique identifier

associated with the second device.

4. The first device of claim 1, wherein the one or more hardware processors are further configured to: identify a set of contacts from a contact list associated with the first device, wherein the set of devices include one or more devices associated with the set of contacts from the contact list associated with the first device.

5. The first device of claim 4, wherein the contact list is a first contact list and the set of contacts is a first set of contacts, wherein the one or more hardware processors are further configured to: receive, from the second device, information regarding one or more devices associated with a second set of contacts from a second contact list associated with the second device, wherein the set of devices further include the one or more devices associated with the second set of contacts from the second contact list associated with the second device.

6. The first device of claim 1, wherein the set of devices does not include the first device.

7. The first device of claim 1, wherein the communication session is associated with a particular communication session identifier, and wherein recording the one or more keys to the blockchain includes recording information, associating the one or more keys and the particular communication session identifier, to the blockchain.

8. A system, comprising: a first device comprising one or more hardware processors, and a second device comprising one or more hardware processors, wherein the second device is configured to: output, to the first device, a first request to establish a communication session between the first device and the second device, wherein the request includes a first value; receive, from the first device, a second request to establish the communication session between the first device and the second device, wherein the second request includes a second value; compare the first value, included in the first request outputted by the first device, with the second value included in the second request received from the second device; determine, based on comparing the first and second values, that the first device has priority, wherein the second device also determines, based on the first and second values, that the first device has priority; output, based on determining that the first device has priority, a blockchain establishment message to a set of devices that includes a third device, wherein the first device and the set of devices establish a blockchain that is accessible to the first and second devices, wherein the second device forgoes outputting a blockchain establishment message based on determining that the first device has priority; encrypt a communication associated with the communication session using a double ratchet encryption technique; record, to the blockchain associated with the communication session, one or more keys associated with the encrypting of the communication using the double ratchet encryption technique; and output the encrypted communication to the second device via the communication session, wherein the second device retrieves the one or more keys from the blockchain and uses the one or more keys to decrypt the encrypted communication.

9. The system of claim 8, wherein the first value includes a first randomly generated number and wherein the second value includes a second randomly generated number.

10. The system of claim 8, wherein the first value is based on a first unique identifier associated with the second device, and wherein the second value is associated with a second unique identifier associated with the first device.

11. The system of claim 8, wherein the second device is further configured to: identify a set of contacts from a contact list associated with the second device, wherein the set of devices include one or more devices associated with the set of contacts from the contact list associated with the second device.

12. The system of claim 11, wherein the contact list is a first contact list and the set of contacts is a first set of contacts, wherein the second device is further configured to: receive, from the first device, information regarding one or more devices associated with a second set of contacts from a second contact list associated with the first device, wherein the set of devices further include the one or more devices associated with the second set of contacts from the second contact list



associated with the first device.

13. The system of claim 8, wherein the communication session is associated with a particular communication session identifier, and wherein recording the one or more keys to the blockchain includes recording information, associating the one or more keys and the particular communication session identifier, to the blockchain.

14. A method performed by a first device, the method comprising: outputting, to a second device, a first request to establish a communication session between the first device and the second device, wherein the request includes a first value; receiving, from the second device, a second request to establish the communication session between the first device and the second device, wherein the second request includes a second value; comparing the first value, included in the first request outputted by the first device, with the second value included in the second request received from the second device; determining, based on comparing the first and second values, that the first device has priority, wherein the second device also determines, based on the first and second values, that the first device has priority; outputting, based on determining that the first device has priority, a blockchain establishment message to a set of devices that includes a third device, wherein the first device and the set of devices establish a blockchain that is accessible to the first and second devices, wherein the second device forgoes outputting a blockchain establishment message based on determining that the first device has priority; encrypting a communication associated with the communication session using a double ratchet encryption technique; recording, to the blockchain associated with the communication session, one or more keys associated with the encrypting of the communication using the double ratchet encryption technique; and outputting the encrypted communication to the second device via the communication session, wherein the second device retrieves the one or more keys from the blockchain and uses the one or more keys to decrypt the encrypted communication.

15. The method of claim 14, wherein the first value includes a first randomly generated number and wherein the second value includes a second randomly generated number.

16. The method of claim 14, wherein the first value is based on a first unique identifier associated with the first device, and wherein the second value is associated with a second unique identifier associated with the second device.

17. The method of claim 14, further comprising: identifying a set of contacts from a contact list associated with the first device, wherein the set of devices include one or more devices associated with the set of contacts from the contact list associated with the first device.

18. The method of claim 17, wherein the contact list is a first contact list and the set of contacts is a first set of contacts, the method further comprising: receiving, from the second device, information regarding one or more devices associated with a second set of contacts from a second contact list associated with the second device, wherein the set of devices further include the one or more devices associated with the second set of contacts from the second contact list associated with the second device.

19. The method of claim 14, wherein the set of devices does not include the first device.

20. The method of claim 14, wherein the communication session is associated with a particular communication session identifier, and wherein recording the one or more keys to the blockchain includes recording information, associating the one or more keys and the particular communication session identifier, to the blockchain.

---