

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12392134
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Collins; Arlan E. et al.

---

### Pre-manufactured floor-ceiling panel for a multi-story building having load bearing walls

---

#### Abstract

Floor-ceiling panels are provided for a building that includes load bearing walls that are able to withstand vertical loads and lateral loads. The building may be a low-rise building or a mid-rise building. The floor-ceiling panels, as well as the load bearing walls, corridor panels, utility walls, and other parts of the building are pre-manufactured off-site and then installed on-site at the site of the building. The floor-ceiling panels are hung from the load bearing walls and are capable to receive and transfer lateral and vertical loads, as well as providing improved sound proofing and fire rating for the building.

---

<b>Inventors:</b>	Collins; Arlan E. (Seattle, WA), Woerman; Mark L. (Seattle, WA), D'Amato; Mark (Seattle, WA), Hinckley; Eric P. (Superior, CO), Danz; Calder (Seattle, WA), Allen; Christopher J. (Aloha, OR), Paul; Dale V. (Poulsbo, WA)
<b>Applicant:</b>	Innovative Building Technologies, LLC (Seattle, WA)
<b>Family ID:</b>	1000008764736
<b>Assignee:</b>	Innovative Building Technologies, LLC (Seattle, WA)
<b>Appl. No.:</b>	18/248796
<b>Filed (or PCT Filed):</b>	October 21, 2021
<b>PCT No.:</b>	PCT/US2021/056076
<b>PCT Pub. No.:</b>	WO2022/087282
<b>PCT Pub. Date:</b>	April 28, 2022

#### Prior Publication Data

Document Identifier	Publication Date
---------------------	------------------

## Related U.S. Application Data

us-provisional-application US 63178515 20210422

us-provisional-application US 63104239 20201022

---

## Publication Classification

**Int. Cl.:** **E04B5/10** (20060101); **B66B11/00** (20060101); **E04B1/02** (20060101); **E04B1/08** (20060101); **E04B1/24** (20060101); **E04B1/348** (20060101); **E04B1/61** (20060101); **E04B2/60** (20060101); **E04B5/02** (20060101); **E04B5/04** (20060101); **E04B9/00** (20060101); **E04B9/04** (20060101)

### U.S. Cl.:

**CPC** **E04B5/04** (20130101); **B66B11/0005** (20130101); **E04B1/02** (20130101); **E04B1/08** (20130101); **E04B1/24** (20130101); **E04B1/2403** (20130101); **E04B1/3483** (20130101); **E04B1/34869** (20130101); **E04B1/612** (20130101); **E04B1/6125** (20130101); **E04B2/60** (20130101); **E04B5/10** (20130101); **E04B9/008** (20130101); **E04B9/04** (20130101); E04B2001/2415 (20130101); E04B2001/2418 (20130101); E04B2001/2451 (20130101); E04B2001/2481 (20130101); E04B2001/6191 (20130101); E04B2001/6195 (20130101); E04B5/02 (20130101); E04B2103/06 (20130101)

## Field of Classification Search

**CPC:** E04B (1/02); E04B (1/08); E04B (1/18); E04B (1/167); E04B (1/2403); E04B (1/3483); E04B (1/6125); E04B (5/02); E04B (9/04); E04B (9/10); E04B (9/22)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5644871	12/1996	Cohen	52/125.4	E04B 5/04
6073401	12/1999	Iri	52/79.9	E04B 1/3483
6460297	12/2001	Bonds et al.	N/A	N/A
8234827	12/2011	Schroeder, Sr.	52/638	E04B 1/24
8276328	12/2011	Pepin	52/657	E04C 2/386
2004/0261349	12/2003	Hashimoto	52/633	E04B 1/08
2010/0229472	12/2009	Malpas	52/173.3	E04C 2/521
2011/0277405	12/2010	Bowron	N/A	N/A
2013/0211795	12/2012	Vanker	703/1	E04B 1/08
2014/0033631	12/2013	Rokk	52/582.2	E04H 9/00
2014/0083046	12/2013	Yang	52/704	E04B 1/2403
2015/0308096	12/2014	Merhi	52/745.1	E04G 21/14
2016/0040443	12/2015	Stephenson	52/79.5	E04H 1/005

2017/0284095	12/2016	Collins	N/A	E04C 2/322
2018/0355601	12/2017	Collins	N/A	E04B 1/24
2019/0010693	12/2018	Powers	N/A	E04H 15/001
2019/0093356	12/2018	Collins et al.	N/A	N/A
2019/0169844	12/2018	Yousefi Darestani	N/A	E04B 1/167
2019/0323235	12/2018	Benson	N/A	E04C 3/34
2023/0061113	12/2022	Keller	N/A	E04B 2/56

## **FOREIGN PATENT DOCUMENTS**

<b>Patent No.</b>	<b>Application Date</b>	<b>Country</b>	<b>CPC</b>
20 2014 002 800	12/2013	DE	N/A

## **OTHER PUBLICATIONS**

USPTO, Written Opinion for International Patent Application No. PCT/US2021/056076, Jan. 28, 2022, 8 pages. cited by applicant

USPTO, International Search Report for International Patent Application No. PCT/US2021/056076, Jan. 28, 2022, 2 pages. cited by applicant

*Primary Examiner:* Agudelo; Paola

*Attorney, Agent or Firm:* IP Spring

## **Background/Summary**

CROSS-REFERENCE TO RELATED APPLICATIONS (1) The present application is the U.S. national phase filing under 35 U.S.C. § 371 of International Patent Application No. PCT/US2021/056076, filed on Oct. 21, 2021, which claims priority under 35 U.S.C. § 119 (e) and/or under PCT Article 8 to U.S. Provisional Patent Application No. 63/104,239, filed on Oct. 22, 2020, and entitled “LOAD BEARING WALLS FOR A BUILDING” and to U.S. Provisional Patent Application No. 63/178,515, filed on Apr. 22, 2021, and entitled “LOW-MID RISE BUILDING HAVING LOAD BEARING WALLS, UTILITY WALLS, AND A CORRIDOR SYSTEM, AND OTHER ACCOMPANYING STRUCTURE, AND METHOD TO CONSTRUCT THE BUILDING.” The contents of U.S. Provisional Patent Application Nos. 63/104,239 and 63/178,515 are incorporated herein by reference in their entirety. (2) The present application is related in subject matter to each of the following co-pending applications, each of which shares a common filing date of Oct. 21, 2021, entitled “MULTI-STORY BUILDING HAVING LOAD BEARING WALLS AND METHOD TO CONSTRUCT THE BUILDING”, “MULTI-STORY BUILDING HAVING PODIUM LEVEL STEEL TRANSFER STRUCTURE”, “PRE-MANUFACTURED LOAD BEARING WALLS FOR A MULTI-STORY BUILDING”, “PRE-MANUFACTURED UTILITY WALL FOR A MULTI-STORY BUILDING HAVING LOAD BEARING WALLS”, “PRE-MANUFACTURED FLOOR-CEILING CORRIDOR PANEL FOR A MULTI-STORY BUILDING HAVING LOAD BEARING WALLS”, “MULTI-STORY BUILDING HAVING PREFABRICATED STAIR AND ELEVATOR MODULES”, and “PRE-MANUFACTURED FLOOR-CEILING DRAG ANCHOR FOR A MULTI-STORY BUILDING HAVING LOAD BEARING WALLS”, all of which are hereby incorporated by reference herein, in their respective entireties.

## BACKGROUND

(1) Conventional construction is typically conducted in the field at the building job site. People in various trades (e.g., carpenters, electricians, and plumbers) measure, cut, and install material as though each unit were one-of-a-kind. Furthermore, activities performed by the trades are arranged in a linear sequence. The result is a time-consuming process that increases the risk of waste, installation imperfections, and cost overruns.

(2) Traditional building construction continues to be more and more expensive and more and more complex. Changing codes, changing environments, and new technology have all made the construction of a building more complex than it was 10 or more years ago. In addition, trade labor availability is being reduced significantly. As more and more craftsmen retire, fewer and fewer younger workers may be choosing the construction industry as a career, leaving the construction industry largely lacking in skilled and able men and women to do the growing amount of construction work.

(3) The construction industry is increasingly using modular construction techniques to improve efficiency. Modular construction techniques may include pre-manufacturing complete volumetric units (e.g., a stackable module) or one or more building components, such as wall panels, floor panels, and/or ceiling panels, offsite (e.g., in a factory or manufacturing facility), delivering the pre-manufactured modules or components to a building construction site, and assembling the pre-manufactured modules or components at the building construction site.

(4) While modular construction techniques provide certain advantages over traditional construction techniques, challenges continue to exist in being able to meet housing and other building demands in communities. For example, the construction industry, whether using modular construction techniques or traditional construction techniques, needs to be able to address issues such as reducing construction costs and construction waste, reducing time to build, providing building designs that efficiently use space, and other challenges brought on by increasing demands for affordable housing and other building needs.

## SUMMARY

(5) An embodiment provides a pre-manufactured floor-ceiling panel for a multi-story building. The pre-manufactured floor-ceiling panel includes: a plurality of parallel metal joists; an end member affixed to an end of the joists; a first angle having a horizontal section and a vertical section, wherein the horizontal section of the first angle is configured to be placed on top of a plate of a load bearing wall of the building, and wherein the vertical section of the first angle is affixed to the end member; a second angle having a horizontal section and a vertical section, wherein the horizontal section of the second angle forms a fastening location for a horizontal member of the load bearing wall, and wherein the vertical section of the second angle is affixed to the vertical section of the first angle, wherein the horizontal section of the first angle is formed with first holes for alignment with second holes formed in the plate of the load bearing wall.

(6) Another embodiment provides a multi-story building. The building includes: a stair and elevator module at a ground level of the building; brace members that are guided into position by the stair and elevator module; a steel transfer structure that is linked to the brace members, wherein the steel transfer structure includes vertical columns and horizontal beams; pre-manufactured first floor-ceiling panels that are hung from the beams; pre-manufactured first load bearing walls positioned on top of the beams; pre-manufactured utility walls that are hung from the first load bearing walls; corridor panels that are hung from the utility walls; and pre-manufactured second floor-ceiling panels that are hung from the first load bearing walls, wherein each of the pre-manufactured second floor-ceiling panels include: a plurality of parallel metal joists; an end member affixed to an end of the joists; a first angle having a horizontal section and a vertical section, wherein the horizontal section of the first angle is configured to be placed on top of a plate of a particular first load bearing wall of the building, and wherein the vertical section of the first angle is affixed to the end member;

a second angle having a horizontal section and a vertical section, wherein the horizontal section of the second angle forms a fastening location for a horizontal member of the particular first load bearing wall, and wherein the vertical section of the second angle is affixed to the vertical section of the first angle, wherein the horizontal section of the first angle is formed with first holes for alignment with second holes formed in the plate of the particular first load bearing wall.

(7) Still another embodiment provides method to manufacture a floor-ceiling panel for a multi-story building that includes load bearing walls. The method includes: arranging a plurality of metal joists in parallel; affixing an end member to ends of the joists; affixing a first angle and a second angle to each other, wherein: the first angle has a horizontal section and a vertical section, wherein the horizontal section of the first angle is configured to be placed on top of a plate of a load bearing wall of the building, the second angle has a horizontal section and a vertical section, wherein the horizontal section of the second angle forms a fastening location for a horizontal member of the load bearing wall, and the first angle and the second angle are affixed to each other by affixing the vertical section of the second angle to the vertical section of the first angle; affixing the vertical section of the first angle to the end member; forming first holes in the horizontal section of a first angle for alignment with second holes formed in the plate of the load bearing wall; and forming at least one cutout in the horizontal section of the first angle to accommodate a spigot attached to the load bearing wall.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is an illustration of an example multi-story building that can have pre-manufactured floor-ceiling panels, load bearing walls, and other building parts described herein, in accordance with some implementations.
- (2) FIG. 2 shows a partially constructed building having floor-ceiling panels at a second floor level of the building, in accordance with some implementations.
- (3) FIG. 3 shows further details of the floor-ceiling panels and load bearing walls of the partially constructed building of FIG. 2, in accordance with some implementations.
- (4) FIG. 4 shows installation of a floor-ceiling panel on a next floor level of the building, in accordance with some implementations.
- (5) FIG. 5 is a cross-sectional view showing further details of the floor-ceiling panel hung onto a load bearing wall, in accordance with some implementations.
- (6) FIGS. 6 and 7 are top views showing further details of angles for floor-ceiling panels, in accordance with some implementations.
- (7) FIG. 8 is a cross-sectional view of an assembly that includes a floor-ceiling panel and two load bearing walls, in accordance with some implementations.
- (8) FIG. 9 is a cross-sectional view showing further details of a floor-ceiling panel, in accordance with various implementations.
- (9) FIG. 10 is a cross-sectional view showing utility boxes of a floor-ceiling panel, in accordance with various implementations.
- (10) FIG. 11 is a top view showing example screw patterns for a floor-ceiling panel, in accordance with some implementations.

### DETAILED DESCRIPTION

(11) In the following detailed description, reference is made to the accompanying drawings, which form a part hereof. In the drawings, similar symbols typically identify similar components, unless context dictates otherwise. The illustrative embodiments described in the detailed description, drawings, and claims are not meant to be limiting. Other embodiments may be utilized, and other changes may be made, without departing from the spirit or scope of the subject matter presented

herein. The aspects of the present disclosure, as generally described herein, and illustrated in the Figures, can be arranged, substituted, combined, separated, and designed in a wide variety of different configurations, all of which are contemplated herein.

(12) This disclosure is drawn, inter alia, to methods, systems, products, devices, and/or apparatuses generally related to pre-manufactured floor-ceiling panels that may be used in multi-story buildings having load bearing walls and other building parts (e.g., stair and elevator modules, steel transfer structures, corridor panels, etc.), such as a low-rise or mid-rise building. The floor-ceiling panels are structural in that they are able to absorb and/or transfer lateral and/or vertical loads.

(13) Traditionally, buildings are constructed using a steel structural frame that is designed to resist vertical and lateral loads. Thus, the structural frame can be thought of as a skeletal structure of a multi-story building, wherein the structural frame provides structural support for the building by absorbing vertical loads due to the weight of multiple stories and lateral loads such as due to wind or earthquakes, as well as providing the framing for various walls, floors, ceilings, and other components that can be affixed to the structural frame during the course of constructing the building. However, manufacturing and assembling such a traditional and extensive structural frame can be time consuming and costly in terms of labor and material. For instance, an affordable housing crisis or other community needs may dictate that buildings with good structural integrity be built quickly and economically.

(14) Therefore, various embodiments disclosed herein pertain to construction of a building using load bearing walls and other building parts such that the reliance upon a traditional structural frame can be reduced or eliminated, while at the same time enabling the building to meet lateral and vertical loading requirements. The load bearing walls can be pre-manufactured demising walls, end walls, or other vertical walls (including possibly utility walls), at least some of which are constructed and arranged so as to provide the structural support for the building in a manner that is sufficient to enable the building to handle vertical and lateral loads. The other building parts, such as the pre-manufactured floor-ceiling panels and corridor panels and their accompanying components, in combination with the load bearing walls and coupling linkages between them, also enhance the structural integrity for the building (e.g., for handling or transferring loads), improve acoustical performance, and increase fire safety.

(15) The building may be a multi-story low-rise building or a multi-story mid-rise building in some embodiments. Each story of the building can include a single unit or multiple units. For instance, a particular unit may be living space, office space, retail space, storage space, or other human-occupied space or otherwise usable space in the building. In the context of living space, as an example, each story of the building may include multiple units to respectively accommodate multiple tenants.

(16) The use of the pre-manufactured load bearing walls and other pre-manufactured parts enables the building to be constructed with a shorter time to build and at a lower cost (relative to a building that is constructed using a traditional structural frame), and without sacrificing the structural integrity of the building. Moreover, the floor-ceiling panels of the building may be made thinner relative to conventional floor-ceiling panels, thereby enabling the building to have more stories per vertical foot compared to a traditional building. Thus, the building is able to provide more usable space (e.g., living space) as opposed to a traditional building that occupies the same footprint. In other cases, the thinner floor-ceiling panels provide more space between the floor and ceiling of each unit, which may be desirable for some occupants that prefer living spaces with “high ceilings.”

(17) In some embodiments, the material composition of an entire module, as well as the wall, ceiling, and floor panels, may include steel. In some embodiments, the material composition may include aluminum. In still other embodiments, the wall, ceiling, and floor panels may be made from a variety of building suitable materials ranging from metals and/or metal alloys, composites, to wood and wood polymer composites (WPC), wood based products (lignin), other organic building

materials (bamboo) to organic polymers (plastics), to hybrid materials, earthen materials such as ceramics, glass mat, gypsum, fiber cement, magnesium oxide, or any other suitable materials or combinations thereof. In some embodiments, cement, grout, or other pourable or moldable building materials may also be used. In other embodiments, any combination of suitable building material may be combined by using one building material for some elements of the entire module, as well as the wall, ceiling and floor panels, and other building materials for other elements of the entire module, as well as the wall, ceiling, and floor panels. Selection of any material may be made from a reference of material options (such as those provided for in the International Building Code), or selected based on the knowledge of those of ordinary skill in the art when determining load bearing requirements for the structures to be built. Larger and/or taller structures may have greater physical strength requirements than smaller and/or shorter buildings. Adjustments in building materials to accommodate size of structure, load, and environmental stresses can determine optimal economical choices of building materials used for components in an entire module, as well as the wall, ceiling, and floor panels described herein. Availability of various building materials in different parts of the world may also affect selection of materials for building the system described herein. Adoption of the International Building Code or similar code may also affect choice of materials.

(18) Any reference herein to “metal” includes any construction grade metals or metal alloys as may be suitable (such a steel) for fabrication and/or construction of the entire module, as well as wall, ceiling, and floor panels, and/or other components thereof described herein. Any reference to “wood” includes wood, wood laminated products, wood pressed products, wood polymer composites (WPCs), bamboo or bamboo related products, lignin products and any plant derived product, whether chemically treated, refined, processed or simply harvested from a plant. Any reference herein to “concrete” or “grout” includes any construction grade curable composite that includes cement, water, and a granular aggregate. Granular aggregates may include sand, gravel, polymers, ash and/or other minerals.

(19) FIG. 1 is an illustration of an example multi-story building **100** that can have pre-manufactured floor-ceiling panels, load bearing walls, and other building parts (e.g., pre-manufactured corridor panels, utility walls, window walls, and other type of walls, etc.), in accordance with some implementations. It is noted that the building **100** of FIG. 1 is being shown and described herein as an example for purposes of providing context for the various embodiments in this disclosure. The various embodiments may be provided for buildings that have a different number of stories, footprint, size, shape, configuration, appearance, etc. than those shown for the building **100**.

(20) The building **100** may be a multi-story building with one or more units (e.g., living, office, or other spaces) in each story. In the example of FIG. 1, the building **100** has six stories/levels/floors, labeled as levels L1-L6. Also as shown in FIG. 1, the building **100** has a generally rectangular footprint, although the various embodiments disclosed herein may be provided for buildings having footprints of some other shape/configuration. Moreover, each story may not necessarily have the same shape/configuration as the other stories. For instance in FIG. 1, level L6 of the building **100** has a smaller rectangular footprint relative to levels L1-L5.

(21) The ground floor level L1 may contain living spaces, office spaces, retail spaces, storage spaces, common areas (such as a lobby), etc. or combination thereof. Levels L2-L6 may also contain living spaces, office spaces, retail spaces, storage spaces parking, storage, common areas, etc. or combination thereof. Such spaces may be defined by discrete units, separated from each other and from corridors or common areas by interior demising walls and utility walls (not shown in FIG. 1). An individual unit in turn may be made up of multiple rooms that may be defined by load bearing or non-load bearing walls. For example, a single unit on any given level may be occupied by a tenant, and may include a kitchen, living room, bathrooms, bedrooms, etc. separated by walls, such as demising walls or utility walls. There may be multiple units (e.g., for multiple respective tenants) on each story, or only a single unit (e.g., for a single tenant) on a single story.

(22) Each end of the building **100** includes an end wall **102**. One or more panels that make up the end wall **102** may span a single story in height. Any of the sides of the building **100** may include a wall in the form of a window wall **104** that accommodates a window **106**, such as window(s) for unit(s). One or more panels that make up the window wall **104** may span a single story in height. Some parts of the building **100** may include an end wall without windows (e.g., not a window wall), such as an end wall **108**, which may be comprised of a panel that spans one story of the building **100**.

(23) The unit(s) in each story may be formed using either an entire pre-manufactured module or from one or more pre-manufactured floor-ceiling panels and wall panels (not shown in FIG. 1), and the units may also adjoin each other via hallways having pre-manufactured corridor panels as floor-ceiling panels. A floor-ceiling panel may form the floor of a first unit and a ceiling of a second unit below the first unit, and may also be used to form part of the roof of the building **100** when used as the ceiling panel for the top floor. The pre-manufactured wall panels may be used to form interior walls (e.g., demising walls, corridor walls, etc.), window walls (e.g., exterior window wall **104** that accommodate one or more windows **106**), utility walls (e.g., walls with utilities such as plumbing and electrical wiring contained therein), side/end walls, etc. According to various embodiments, at least some of these panels may be pre-manufactured off-site such as at a factory, and then installed on site by coupling them together to construct the building **100**. The various components of such panels and how such panels are attached to each other will be described later below.

(24) The sides of interior walls that face the interior space (e.g., living space) of the building **100** may be covered by a finish panel, such as wall paneling, for decorative and/or functional purposes. Analogously, the tops and bottoms of floor-ceiling panels that face the interior space (e.g., living space) of the building **100** may also be covered with laminate flooring, finish panels, tile, painted/textured sheathing, etc. for decorative and/or functional purposes. For exterior walls such as end walls, and window walls, the sides of these walls facing the outside environment may be covered with waterproofing membranes, tiles, glass, or other material for decorative and/or functional purposes.

(25) According to various implementations, the building **100** is constructed using load bearing walls (such as demising walls, end walls, etc.). In this manner, such walls are able to support vertical loads, and non-shear walls are able to transfer lateral loads and shear walls are able to transfer and resist lateral loads. Because these walls are load bearing components, the building **100** can eliminate or reduce the use of an extensive steel structural frame in at least some of the levels. For instance, a steel structural frame (e.g., made of an array of beams and columns to which each and every floor-ceiling panel and wall are directly attached) may be absent in levels L2-L6. A steel structural frame may be used in level L1 and/or further structural reinforcement may be given to load bearing walls that are used in level L1 alternatively or in addition to a structural frame, so as to provide structural integrity at ground level.

(26) The building **100**, having six levels L1-L6, is defined in some jurisdictions as a mid-rise building (e.g., buildings having six to 12 levels). Buildings having five levels and under are defined in some jurisdictions as a low-rise building. The various embodiments of the load bearing walls described herein may be used in low-rise and mid-rise buildings. Such low-rise and mid-rise buildings may have various fire ratings, with a 2-hour fire rating for mid-rise buildings of six stories or more and a 1-hour fire rating for buildings of five stories or less being examples for some of the buildings that use the load bearing walls described herein.

(27) In some embodiments, the load bearing walls and other building parts described herein (in the absence of a structural frame, or with a reduced amount thereof) may be used for buildings that have a greater number of stories than a typical low-rise or mid-rise building. In such embodiments, the load bearing walls and/or other building parts described herein may be implemented with additional and/or modified structural components, so as to account for the increased load associated with the greater number of stories.



(28) FIG. 2 shows a partially constructed building **200** having floor-ceiling panels **202** at a second floor level (L2) of the building, in accordance with some implementations. For purposes of example and illustration, the building **200** will have a generally rectangular footprint, and will be assumed to be a low-rise building having at most five stories (floor levels), and it is understood that the various implementations described herein may be used for buildings with other numbers of stories. A construction sequence described with respect to FIG. 2 and in the other figures that will be shown and described later may be adapted to construct buildings having other shapes, sizes, heights, configurations, number of stories, etc., such as the building **100** of FIG. 1 or any other building where load bearing walls, floor-ceiling panels, and the other building parts described herein are installed in the absence of extensive structural frames on at least some stories. In some embodiments, the various operations in the construction sequence may be performed in a different order, omitted, supplemented with other operations, modified, combined, performed in parallel, etc., relative to what is shown and described with respect to FIG. 2 and the other figures.

(29) To describe a construction sequence to arrive at the partially constructed building **200** in FIG. 2, a foundation **204** is first formed. The foundation **204** may be a steel reinforced concrete slab that is poured on the ground to define a footprint **206** of the building **200**, or may be some other type of shallow or deep foundation structure. Furthermore, excavation of the ground may also be performed to form a basement and/or elevator pit(s) **208** that form part of one or more elevator shafts to accommodate one or more elevators.

(30) Next in the construction sequence, pre-manufactured stair and elevator modules **210** and **212** may be built on the foundation **204**, and positioned such that the elevator portions of the modules **210** and **212** that will contain the elevator shaft are superimposed over the elevator pit(s) **208**. The modules **210** and **212** according to various embodiments may be two stories in height, and there may be one or more of these modules per building, with two modules **210** and **212** shown by way of example in FIG. 2.

(31) Each of the modules **210** and **212** may be comprised of vertical columns made of steel, and horizontal beams spanning between the columns and also made of steel. Thus, the columns and the beams form a structural frame, which according to various embodiments is a load bearing structure that is able to withstand vertical and lateral loads. In other embodiments, the columns may be replaced by load bearing wall panels and the beams may remain as load bearing rings.

(32) The modules **210** and **212** of various embodiments are positioned at specific locations of the foundation **204**. In the example of FIG. 2, the modules **210** and **212** are positioned on opposite sides of the building **200**. Other configurations may be used, such as positioning one or more modules at a central location in the building footprint **206** or at any other suitable location(s) on the building footprint **206**.

(33) Next in the construction sequence, brace members such as braced frames are installed on the foundation **204** in relation to the modules **210** and **212**. For example, braced frames **214** and **216** are arranged perpendicularly around and in close proximity to the module **210**, such that the module **210** is nested by the braced frames **214** and **216**. With respect to the module **212**, braced frames **218** and **220** are also arranged perpendicularly but spaced away from the module **212** by a greater distance.

(34) The braced frames **214-220** may be arranged on the foundation **204** in any suitable location and orientation, dependent on factors such as the footprint or configuration of the building **200**, source of lateral and/or vertical loads, location/orientation for optimal stabilization, etc. Any suitable number of braced frames may be provided at the ground level. The braced frames may further vary in configuration. The example of FIG. 2 depicts some braced frames that are generally planar in shape (made of two columns and at least one horizontal beam that joins the two columns), with cross beams (X shaped beams) at the center of the braced frames. The braced frames **214-220** may span one, two, or other stories in height or intermediate heights, and multiple braced frames may also be vertically coupled.

(35) According to various embodiments, the modules **210** and **212** are used as erection aids that guide the positioning and orientation of the braced frames **214-220**. For instance, the modules **210** and **212** are installed first, and then the braced frames **214-220** are arranged relative to the location of the modules **210** and **212**. The braced frames may be directly welded (or otherwise attached/connected) to the modules, or may be linked to the module(s) over a distance via linking beams or other structural framing. The braced frames **214-220** can operate to absorb vertical and lateral loads from the building **200**.

(36) The next phase of the construction sequence involves the erection of a steel transfer structure **222** (e.g., a podium structure) at ground level. The steel transfer structure **222** comprises a steel frame that receives and transfers load to the foundation **204**. The steel transfer structure **222** may have vertical members **224** (columns) having a height that spans one story, girders **226** that join pairs of columns **224**, and beams **228** that perpendicularly join pairs of girders **226**. The steel transfer structure **222** may further include vertically oriented “spigots” and/or other protrusions or engagement features to aid in construction, as will be described more fully below.

(37) After completion of the steel transfer structure **222**, the next phase of the construction sequence involves the placement/installation of the floor-ceiling panels **202** over consecutive beams **228**, and more specifically, hanging the floor-ceiling panels **202** onto the beams **228**. A floor deck comprised of floor-ceiling panels **202** thus results after such installation.

(38) Afterwards, load bearing walls **230** (e.g., demising and end walls) are installed by being positioned over the beams **228**, and utility walls **232** are then installed by being hung onto the load bearing walls **230**. Next, corridor panels **234** (which may be formed similarly in some respects as the floor-ceiling panels **202**) are hung from the utility walls **232**.

(39) According to the example depicted in FIG. 2, the space between consecutive beams **228** is sized to receive three adjoining floor-ceiling panels **202**, although the size of the floor-ceiling panels and the space between consecutive beams **228** and girders **226** can vary from one implementation to another. For instance, some implementations may install multiple floor-ceiling panels between consecutive beams **228** that may vary in widths from 13 feet, to 16 feet, to 20 feet, to 24 feet, etc.

(40) FIG. 3 shows further details of the floor-ceiling panels and load bearing walls of the partially constructed building **200** of FIG. 2. More particularly, FIG. 3 depicts the placement of three floor-ceiling panels **300A-300C** (collectively **300**) over and between consecutive beams **228A** and **228B** (collectively **228**). In the example shown, the floor-ceiling panel **300A** is adjacent to a window wall (not yet installed in FIG. 3) that faces an exterior of the building **200**, the floor-ceiling panel **300B** is adjacent to a utility wall (not yet installed in FIG. 3) that faces an interior corridor of the building **200**, and the floor-ceiling panel **300C** is a middle panel joined to and between the floor-ceiling panels **300A** and **300B**.

(41) An installation sequence for the floor-ceiling panels may involve installing the floor-ceiling panel **300A**, floor-ceiling panel **300C**, and floor-ceiling panel **300B** in any suitable sequence, such as floor-ceiling panels **300C-300B-300A**. After these three floor-ceiling panels are installed, then the installation sequence moves to the next adjacent space between consecutive beams **228** (e.g., to the left direction in FIG. 3) so as to install the next three floor-ceiling panels in the same manner. This installation sequence repeats until all floor-ceiling panels are installed on the steel transfer structure **224** in the manner as depicted in FIG. 2 to complete a floor deck for that story. Variations in the installation sequence are possible, such as the corridor panels and utility wall could precede the floor-ceiling panels, thereby erecting from the core outwards.

(42) FIG. 3 shows an example mounting of floor-ceiling panels, wherein if the north-south direction along the beam **228** is considered to be a transverse direction, and if the east-west direction along the girder **226** is considered to be the longitudinal direction, then the floor-ceiling panel **300** includes an angle **302** (or other piece of metal that provides ledge-like structure) that runs along its transverse direction along an upper surface (upper corner edge) of the floor-ceiling

panel **300**. It is understood that the terms transverse and longitudinal are used as relative terms herein, and may be swapped if the building **200** is being viewed or described from a different point of reference.

(43) As will be shown and described in further detail below, the angle **302** includes a horizontal section that rests on a top surface of the beam **228A**. A vertical section of the angle **302** is attached to a vertical edge of the floor-ceiling panel **300**. A similar angle **302** is attached to the other/opposite transverse edge of the floor-ceiling panel **300**, and also has a horizontal section that rests on top of a beam **228B** adjacent to that edge of the floor-ceiling panel **300**. In this manner, the floor-ceiling panel **300** is hung by its transverse edges between two consecutive beams **228**.

(44) With such an arrangement, the floor-ceiling panels provide a horizontal diaphragm that absorbs lateral and/or vertical load(s) and then transfers the load(s), via the angle **302**, to the beams **228** of the steel transfer structure **222** and/or to other supporting structure linked to the angles **302**. The steel transfer structure **222** then transfers the load(s) via a load path to the foundation **204** and/or to the braced frames (e.g., the braced frames **214-220**) via connecting links.

(45) According to some embodiments, the floor-ceiling panels **300** are supported between beams **228** along their transverse sides and are unsupported (e.g., by the girders **226**) along their longitudinal sides. In the example of FIG. 3 and as will be explained later below, the floor-ceiling panels **300** may be sized such that there may be a gap **304** between the longitudinal edge of the floor-ceiling panel **300** and the girder **226**. This gap **304** may be sized to accommodate the thickness of a utility wall **232** that will be hung from load bearing demising/end walls resting on top of the beams **228**, with the gap also providing an opening to enable utilities installed in the utility wall **232** to extend and connect to utilities at the floor level below (and similarly extend/connect to utilities installed in utility wall at a floor level above).

(46) FIG. 3 also depicts alignment/placement and securing of the walls, using spigots **306**, in more detail. More particularly, an end wall **308** and a demising wall **310** are installed by positioning these walls over the beams **228**. Both of the walls **308** and **310** are load bearing walls. The end wall **308** is also a shear wall (but may not be a shear wall in some situations), and the demising wall **310** may or may not be a shear wall. In general, various structural configurations may be used to enable a wall to be a shear wall so as to resist in-plane shear and overturning. For example, stronger stud configurations or wall material may be used, as well as more dense screw patterns for attaching metal sheets to the walls and augmentation of vertical connections between panels at end studs (tubular members).

(47) In the example of FIG. 3, the end wall **308** may include a tubular member **312**, such as a hollow structural section (HSS) tube, along both of its vertical edges. As the end wall **308** is being lowered into position, the spigots **306** (located proximate to both ends of the beam **228**), which are alignment and engagement members, are inserted into the openings of the lower ends of the tubular members **312**. The end wall **308** is then secured in place by tightening the attachment bolts on the spigot **306** and by affixing a lower edge of the end wall **308** to the upper surface of the floor-ceiling panels, which will be shown and described in further detail below with respect to FIG. 8.

(48) A similar procedure may be used to install the demising wall **310**, by fitting openings at lower ends of tubular members **314** at the vertical edges of the demising wall **310** onto the spigots **306**. A result of this installation is shown in FIG. 3, wherein two parallel walls are now standing in a self-aligned and self-supported manner, without the need for additional bracing from structural framing (e.g., an internal framing/skeleton of the building **200**).

(49) After the floor-ceiling panels, walls, and corridor panels are finished being installed on the second floor level L2, then the construction sequence described with respect to FIGS. 2 and 3 repeats for each subsequent floor level above. For example, FIG. 4 shows installation of a floor-ceiling panel **400** on a next floor level of the building **200**, which in this example is the third floor level L3.

(50) In FIG. 4, the floor-ceiling panel **400** is hung onto the previously installed end wall **308** and

demising wall **310**, via the angles **302** that run along the transverse upper edges of the floor-ceiling panel **400**. The floor-ceiling panel **400** is hung by resting the horizontal sections of the angles **302** rests on the top surfaces of the end wall **308** and demising wall **310**. The manner in which the floor-ceiling panel **400** of FIG. **4** is hung from the top surfaces of the end wall **308** and the demising wall **310**, via the angles **302**, may be generally similar to the manner that the floor-ceiling panels **300** are hung from the top surfaces of the beams **228** in FIG. **3**.

(51) Holes **402** may be formed (e.g., during manufacture at the factory) in the angles **302** of the floor-ceiling panel **400** to facilitate the alignment and positioning of the floor-ceiling panel **400** with some precision. For instance, temporary pegs or screws may be inserted into the holes **402** (which have aligned with corresponding holes of a plate **500** shown in FIG. **5**) during installation to align and hold the floor-ceiling panel **400** in place, while the angle **302** is screwed, bolted, or welded to a top plate on the top surfaces of the walls **308** and **310**. The holes **402** (with temporary pegs or other holding devices inserted therein and through the corresponding holes in the plate **500**) each provide a connection point that holds the floor-ceiling panel **400** in place for precision and safety during building erection. This fastening also creates a tight joint for weld setup, for welding the angle **302** to the plate **500**.

(52) Moreover, further spigots **306** may be installed on top of the walls **308** and **310**, for alignment and securing of the upper end wall and demising wall that will be installed next on top of the respective lower end wall **308** and demising wall **310**. The angle **302** may have cutouts **404** to accommodate fasteners (e.g., bolts) for a mounting base of spigots **306** and/or to accommodate other parts or fasteners.

(53) FIG. **4** also shows an installed utility wall **406** (e.g., the utility wall **232** shown in FIG. **2**), with the floor-ceiling panel **400** being sized and installed such that the gap **304** is provided to accommodate a next utility wall above the utility wall **406**. The gap **304** may be absent in other embodiments. FIG. **4** further shows that the gap **304** accommodates utilities **408** (e.g., plumbing, electrical, etc.) that are pre-installed in the utility wall **406**, and which may be connected to utilities that are pre-installed in the floor-ceiling panel **400**, in a manner that will be described later below with respect to FIG. **9**, and/or which may be connected to utilities contained in utility walls above/below the utility wall **406**.

(54) FIG. **5** is a cross-sectional view showing further details of the floor-ceiling panel **400** that is hung onto a load bearing wall (e.g., the end wall **308** or a demising wall). More specifically, FIG. **5** shows the angle **302** (e.g., an L-shaped member such as a hot-rolled metal angle or other type of load carrying/bearing angle) that is positioned over and rests on a plate **500** serving as a head plate at the top of the end wall **308**. The angle **302** (first angle) includes a horizontal section (flange) **502** and a vertical section (flange) **504**.

(55) The floor-ceiling panel **400** further includes a shear angle **506** (which may be a cold formed metal angle of 14 gauge, for example) that runs along each of the transverse upper edges/corners of the floor-ceiling panel **400**. The shear angle **506** (a second angle) has a horizontal section **508** and a vertical section **510**.

(56) During offsite manufacturing, the vertical section **510** of the shear angle **506** is welded to the vertical section **504** of the angle **302** (such as via a continuous weld or a stitch weld) at the upper edge (bend) of the vertical section **504**, or at upper and lower edges of the vertical section **510**. The vertical section **504** of the angle **302** is then welded (such as via a continuous weld or a stitch weld), during the off-site manufacturing, to an end member **512** (such as a track in the form of a C-channel) attached to the ends of longitudinally running parallel metal joists **514** of the floor-ceiling panel **400**. The welding may be located at a lower location **518** at the end of the angle **502** and at an upper location **520** at a corner edge of the end member **512**.

(57) Welding or otherwise attaching the vertical section **504** of the angle **302** to the floor-ceiling panel **400** enables the angle **302**, when hung to the wall **308**, to support the vertical load of the floor-ceiling panel **400**. The horizontal section **508** of the shear angle **506** in combination with the

angle **302** also provides a load path to enable lateral load to be transferred from the diaphragm, formed by the floor-ceiling panel **400**, to the plate **500** and then to load path(s) or connecting links to the braced frames, etc.

(58) The horizontal section **508** of the shear angle **506** lies on top of and may or may not be attached to an upper surface of the floor-ceiling panel **400**. If attached, screws, bolts, or other type of fastener may be used. If the upper surface of the floor-ceiling panel **400**, underneath the horizontal section **508**, is made of metal, then welding may be used for attachment, alternatively or additionally to fasteners.

(59) This arrangement of the shear angle **506** and the angle **302** thus forms a T-shaped element that each run transversely along the entire length of the upper corner edges of the floor-ceiling panel **400**. While the examples are described herein of the shear angle **506** and the angle **302** (both made of metal such as steel) being separate pieces that are attached to each other, some embodiments may use a single integrated piece of metal that is T-shaped.

(60) FIGS. **6** and **7** are top views showing further details of angles for floor-ceiling panels, in accordance with some implementations. More specifically, FIG. **6** shows the horizontal sections (flanges) **502** of angles **302A** and **302B** (collectively **302**) of respective adjacent floor-ceiling panels **400A** and **400B** (collectively **400**). A plurality of holes **402** (also shown in FIG. **4**) are formed/defined in the horizontal section **502** of the angle **302**. The holes **402** are respectively aligned (superimpose with) holes **600** formed/defined in the plate **500** (shown in FIG. **5**) at the top surface of the underlying load bearing demising wall or end wall.

(61) During installation of the floor-ceiling panel **400**, the holes **402** may be used to align the floor-ceiling panel **400** with the holes **600** of the previously erected demising/end wall. A peg, screw, or other type of holding device may be inserted through the holes **402** and **600** to keep the floor-ceiling **400** aligned/positioned, while the horizontal section **502** is welded permanently to the plate **500**. The holding device may then be removed after completing the installation of the floor-ceiling panel **400**, so as to not protrude or otherwise interfere with the next demising/end wall that will be placed on top of the horizontal section **502**.

(62) In some implementations, the holes **402** may have a larger diameter than the underlying holes **600**. Then a holding device (such as a thread forming screw or tapered pin) may be inserted in the holes **402** and **600** as a temporary clamp down mechanism, prior to welding the horizontal section **502** to the plate **500**.

(63) In other implementations, a countersunk screw or other type of fastener may be inserted in the holes **402** and **600** as a permanent holding device that will be in turn covered by the next demising/end wall.

(64) FIG. **7** is a cross-sectional view showing an example of the cutouts **404** (shown also in FIG. **4**) in the horizontal section **502** of the angles **302A** and **302B**, such as between floor levels **1** and **2**. The cutouts **404** may be sized and shaped to accommodate a mounting base **700** of the spigot **306**, and/or to accommodate bolts **702** that are used to attach the spigot **306** to an underlying structural support element (e.g., the plate **500** of the underlying demising/end wall; or an end of an HSS tube shown as a cross-section in FIG. **7** that runs vertically along the end of the underlying demising/end wall; or a beam **228** a girder **226**). For example, if spigots **306** have already been installed as vertical protrusions, by being welded or otherwise attached to the steel transfer structure for the first story, the cutouts **404** enable the subsequent floor-ceiling panels to be lowered into position without interference from the spigots **306**, since the cutouts **404** will accommodate the spigots **306** as the floor-ceiling panel is lowered. Cutouts may be provided if needed for other stories above, if there are protruding structures that need to be avoided as the floor-ceiling panel is being lowered into position.

(65) FIG. **8** shows an assembly that includes a floor-ceiling panel and two load bearing walls, in accordance with some implementations. Specifically as an example, a floor-ceiling panel **400A** and an adjacent floor-ceiling panel **400B** (collectively **400**) are depicted in FIG. **8** as being hung onto a

load bearing demising wall or end wall (e.g., the end wall **308**), via the respective horizontal sections **502A** and **502B** (collectively **502**) of the angles **302A** and **302B** (collectively **302**) of the respective floor-ceiling panels **400A** and **400B**.

(66) An upper load bearing demising wall or end wall **800** has a horizontal member **802** that is affixed (e.g., by welding, bolting, or screwing), offsite at a factory, to a track **804** joined to lower ends of studs **806** in the wall **800**. The horizontal member **802** may run along an entire length of the track **804**, or may run intermittently in sections along the track **894**, such as depicted in the example of FIG. 8.

(67) During the construction sequence, the wall **800** is lowered aligned/positioned into place (e.g., using the spigots **306** as previously explained above), and then the horizontal member **802** is affixed to the each of the horizontal sections **508** of the shear angles **506** of the floor-ceiling panels **400**, thereby permanently mounting the upper load bearing wall **800** over the lower load bearing wall **308**. The horizontal section **508** thus forms a landing/fastening location for the horizontal member **802**. The horizontal member **802** may be affixed to the shear angle **506** such as by screwing, by stitch or continuous welding the horizontal member **802** to the horizontal section **508**, or by bolting or other attachment technique.

(68) Affixing the load bearing upper wall **800** to the floor-ceiling panels **400** in this manner enables lateral load to transfer from the upper wall **800** to the horizontal member **802**, and then to the shear angle **506** and/or the angle **302**. The lateral load can then transfer across the diaphragm formed by the floor-ceiling panel **400** (e.g., via the sheets of steel in the floor-ceiling panel **400**) and then to linking connections with further load bearing walls (e.g., via other angles **502/506** and plates **500**), other floor-ceiling panels, corridor panels, and through various other linking elements and other possible load paths, and then to resisting elements such the braced frames, designated shear walls, etc. For example, in the case that the depicted walls are shear walls, lateral forces may follow the path **800** to **802** to **506/302** to **500**, and down to wall **308**, thereby transmitting collected lateral force from the diaphragm down the shear wall to the steel transfer structure at ground level and into the foundation. These lateral forces may include forces from non-shear bearing walls that are transmitted into the diaphragm by the same connection detail (as described).

(69) According to various implementations, the horizontal member **802** runs along the entire lower edge of the upper wall **800**, and may be made from 14 gauge steel, or ¼ inch steel, or some other steel gauge or thickness. The horizontal member **802** may be 12 inches wide or other dimension.

(70) The plate **500** may be steel that is about 7 inches wide and ¼ inches thick, for example. The angle **302** may be ¼ inch steel, with vertical and horizontal sections of lengths between 2-6 inches, for example. The shear angle **506** may be the same dimensions as the angle **302**, or may be made of relatively thinner (or thicker) steel with horizontal/vertical sections that are shorter (or longer) relative to the angle **302**.

(71) It is understood that the foregoing various dimensions (as well as for various other components described throughout this disclosure), such as thicknesses, gauges, lengths, widths, heights, etc. are for illustrative purposes, and that such dimensions may vary from one implementation to another depending on factors such as material availability, cost considerations, structural performance requirements (including loading and weight requirements), design variations, etc.

(72) FIG. 9 is a cross-sectional view showing further details of a floor-ceiling panel **900**, which may be similarly configured as the previously described floor-ceiling panels **202**, **300**, and **400**, etc., in accordance with various implementations. The floor-ceiling panel **900** may include a plurality of parallel joists **902**, and end members or tracks (shown in FIG. 5) attached to both ends of the joists **902**, such that the joists and end members are perpendicular to each other. An outer joist **904** is proximate to a utility wall **906**, and a similar outer joist is present on the opposite side of the floor-ceiling panel **900**.

(73) On a floor side of the floor-ceiling panel **900**, layers **908** may comprise (going from top to

bottom) a cement board layer (e.g., a ½" cement board layer, which may be a magnesium oxide layer, that is factory installed) that overlies a first sheet metal layer (e.g., a 22 gauge galvanized steel sheet metal layer that is factory installed) that is positioned against and affixed to the joists **902**. Again, it is understood that these and other dimensions identified throughout this disclosure are merely examples, and may vary from one implementation to another.

(74) Layers **910** may overlie the layers **908**. The layers **910** may comprise (going from top to bottom) a finished flooring layer (e.g., a ¾" finished floor that is field finish installed), an acoustical mat layer (e.g., a ¾" acoustical mat that is field finish installed), a cement board layer (e.g., a ½" cement board layer that is factory installed) that may be magnesium oxide, a hydronic foam layer (e.g., a 1" hydronic foam layer that is factory installed) with hydronic piping within the hydronic foam layer for radiant floor heating purposes.

(75) On a ceiling side of the floor-ceiling panel **900**, layers **912** may comprise (going from bottom to top) a ceiling panel layer (e.g., a 1" acoustical ceiling panel tile that is field finish installed), one or more gypsum board layers (e.g., two ⅝" type 'X' fiberglass mat gypsum sheathing boards that are factory installed) for sound proofing and/or fire rating purposes, and a second sheet metal layer (e.g., a 22 gauge galvanized steel sheet metal layer that is factory installed) above the gypsum board layers and positioned against and affixed to the joists **902**.

(76) The floor-ceiling panel **900** may also include pre-installed utilities. For example, pipes for plumbing, electrical/telecommunications wiring, etc. may be installed (along with sound proofing insulation) in the space(s) defined by the joists **902**. FIG. 9 shows an implementation wherein a drain pipe **914** runs (internally within the floor-ceiling panel **900**) through apertures in the joists **902**, and exits at **916** from an upper surface of the floor-ceiling panel **900** and exits at **918** from a lower surface of the floor-ceiling panel **900**. These exit points enable surface connection of the pipe **914** (or other similarly arranged utilities that are pre-installed in the floor-ceiling panel **900** at a factory) to the utilities **920** that are provided by the utility wall **906** and/or to other utilities, fixtures, devices, etc. contained in the living space, such as a drain **922**.

(77) As a further example, FIG. 10 is a cross-sectional view showing utility boxes, specifically an electrical/telecommunications box or outlet **1000**, located on an upper surface of the floor-ceiling panel **900**. Wiring for the outlet **1000** may be disposed inside of the floor-ceiling panel **900**, such as within the hydronic foam space outside of the joist cavities. Such wiring may further be connected to another outlet **1002** disposed on a wall adjacent to the floor-ceiling panel **900**.

(78) FIG. 11 shows example screw patterns for a floor-ceiling panel (such as the floor-ceiling panel **900** of FIG. 9), in accordance with some implementations. More specifically, FIG. 11 is a top view of the floor-ceiling panel **900**, and an analogous view/arrangement may be provided as a bottom view of the floor-ceiling panel **900**.

(79) Shown in FIG. 11 are the locations of the previously described joists **902**, outer joists **904**, and the tracks (end members) **512** at both ends of the joists **902/904**. Furthermore, FIG. 11 shows a screw pattern (depicted as broken lines) for both the first and second sheets of metal in the layers **908** and **912** of FIG. 9.

(80) For instance, a sheet of metal may be affixed to the end members **512** and the outer joists **904** (which define the perimeter of the diaphragm) with screws that have relatively closer spacing between them, such as 6 inches on center as opposed to 12 inches on center. Screws that affix this sheet of metal to the joists **902** may be spaced at 12 inches on center, or in some instances at a closer spacing such as 6 inches on center. The relatively closer spacing of 6 inches provides the floor-ceiling panel **900** with increased structural strength to handle and transfer loads.

(81) According to some implementations, the layer **908** (shown in FIG. 9, which is comprised of the first sheet of metal and a cement board layer) on the floor side of the floor-ceiling panel **900** may be attached (e.g., screwed) to the joists **902/904** and end members **512** in tandem, using the same sets of screws. For the layer **912** (also shown in FIG. 9) at the ceiling side of the floor-ceiling panel **900**, the second sheet of metal in the layer **912** may be screwed the joists **902/904** and end

members **512** using a first set of screws. Then, the two gypsum board layers in the layer **912** may be screwed to the second sheet of metal in the layer **912** using a second set of screws that are offset from the first set of screws and that do not contact the joists **902/904** and end members **512**. This method of attachment of the second sheet of metal only to the joists **902/904** and end members **512**, and then attachment of the gypsum board layers only to the second sheet of metal, provides improved acoustical performance (e.g., sound proofing by mitigating sound wave transfer).

(82) Thus, with the arrangement and attachment of the sheets of metal and other layers as described above, the floor-ceiling panel **900** provides various advantages. First, the sheets of metal provide additional strength while also enabling the thickness of the floor-ceiling panel to be reduced, thereby resulting in space savings that may permit increased sizes of the living spaces or more living spaces per height of the building **200**. Second, the sheets of metal provide improved acoustical performance, such as an acoustical barrier between floor levels. Third, the sheets of metal improve the fire rating between floor levels of the building **200**.

(83) The present disclosure is not to be limited in terms of the particular embodiments described in this application, which are intended as illustrations of various aspects. Many modifications and embodiments can be made without departing from its spirit and scope.

(84) Functionally equivalent methods and apparatuses within the scope of the disclosure, in addition to those enumerated herein, are possible from the foregoing descriptions. Such modifications and embodiments are intended to fall within the scope of the appended claims. The present disclosure is to be limited only by the terms of the appended claims, along with the full scope of equivalents to which such claims are entitled. This disclosure is not limited to particular methods, which can, of course, vary. The terminology used herein is for the purpose of describing particular embodiments only, and is not intended to be limiting.

(85) With respect to the use of substantially any plural and/or singular terms herein, the terms can be translated from the plural to the singular and/or from the singular to the plural as is appropriate to the context and/or application. The various singular/plural permutations may be expressly set forth herein for sake of clarity.

(86) In general, terms used herein, and especially in the appended claims (e.g., bodies of the appended claims) are generally intended as “open” terms (e.g., the term “including” should be interpreted as “including but not limited to,” the term “having” should be interpreted as “having at least,” the term “includes” should be interpreted as “includes but is not limited to,” etc.).

(87) If a specific number of an introduced claim recitation is intended, such an intent will be explicitly recited in the claim, and in the absence of such recitation, no such intent is present. For example, as an aid to understanding, the following appended claims may contain usage of the introductory phrases “at least one” and “one or more” to introduce claim recitations. However, the use of such phrases should not be construed to imply that the introduction of a claim recitation by the indefinite articles “a” or “an” limits any particular claim containing such introduced claim recitation to embodiments containing only one such recitation, even when the same claim includes the introductory phrases “one or more” or “at least one” and indefinite articles such as “a” or “an” (e.g., “a” and/or “an” should be interpreted to mean “at least one” or “one or more”); the same holds true for the use of definite articles used to introduce claim recitations. In addition, even if a specific number of an introduced claim recitation is explicitly recited, such recitation should be interpreted to mean at least the recited number (e.g., the bare recitation of “two recitations,” without other modifiers, means at least two recitations, or two or more recitations).

(88) Furthermore, in those instances where a convention analogous to “at least one of A, B, and C, etc.” is used, in general such a construction is intended in the sense one having skill in the art would understand the convention (e.g., “a system having at least one of A, B, and C” would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). In those instances where a convention analogous to “at least one of A, B, or C, etc.” is used, in general such a construction is intended in



the sense one having skill in the art would understand the convention (e.g., “a system having at least one of A, B, or C” would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). Virtually any disjunctive word and/or phrase presenting two or more alternative terms, whether in the description, claims, or drawings, should be understood to contemplate the possibilities of including one of the terms, either of the terms, or both terms. For example, the phrase “A or B” will be understood to include the possibilities of “A” or “B” or “A and B.”

(89) In addition, where features or aspects of the disclosure are described in terms of Markush groups, the disclosure is also thereby described in terms of any individual member or subgroup of members of the Markush group.

(90) For any and all purposes, such as in terms of providing a written description, all ranges disclosed herein also encompass any and all possible subranges and combinations of subranges thereof. Any listed range can be easily recognized as sufficiently describing and enabling the same range being broken down into at least equal halves, thirds, quarters, fifths, tenths, etc. As a non-limiting example, each range discussed herein can be readily broken down into a lower third, middle third and upper third, etc. All language such as “up to,” “at least,” “greater than,” “less than,” and the like include the number recited and refer to ranges which can be subsequently broken down into subranges as discussed above. Finally, a range includes each individual member. Thus, for example, a group having 1-3 items refers to groups having 1, 2, or 3 items. Similarly, a group having 1-5 items refers to groups having 1, 2, 3, 4, or 5 items, and so forth.

(91) The herein described subject matter sometimes illustrates different components contained within, or connected with, different other components. Such depicted architectures are merely embodiments, and in fact many other architectures can be implemented which achieve the same functionality. In a conceptual sense, any arrangement of components to achieve the same functionality is effectively “associated” such that the desired functionality is achieved. Hence, any two components herein combined to achieve a particular functionality can be seen as “associated with” each other such that the desired functionality is achieved, irrespective of architectures or intermedial components. Likewise, any two components so associated can also be viewed as being “operably connected”, or “operably coupled”, to each other to achieve the desired functionality, and any two components capable of being so associated can also be viewed as being “operably couplable”, to each other to achieve the desired functionality. Specific embodiments of operably couplable include but are not limited to physically mateable and/or physically interacting components.

(92) While various aspects and embodiments have been disclosed herein, other aspects and embodiments are possible. The various aspects and embodiments disclosed herein are for purposes of illustration and are not intended to be limiting.

## Claims

1. A pre-manufactured floor-ceiling panel for a multi-story building having load bearing walls, the floor-ceiling panel comprising: a plurality of parallel metal joists; an end member affixed to an end of the joists; a first angle having a horizontal section and a vertical section, wherein the horizontal section of the first angle is configured to be placed on top of a plate of a load bearing wall of the building, and wherein the vertical section of the first angle is affixed to the end member; a second angle having a horizontal section and a vertical section, wherein the horizontal section of the second angle forms a fastening location for a horizontal member of the load bearing wall, and wherein the vertical section of the second angle is affixed to the vertical section of the first angle, wherein the horizontal section of the first angle is formed with first holes for alignment with second holes formed in the plate of the load bearing wall.

2. The pre-manufactured floor-ceiling panel of claim 1, wherein: the first angle runs along an entire

length of the end member, the vertical section of the first angle is welded to the end member along the entire length of the end member, the second angle runs along the entire length of the end member, and the vertical section of the second angle is welded to the vertical section of the first angle along the entire length of the end member.

3. The pre-manufactured floor-ceiling panel of claim 1, wherein the first holes are sized and shaped to receive temporary devices inserted into the first and holes and the second holes, and wherein the temporary holding devices hold the first angle in alignment with the plate of the load bearing wall while the horizontal section of the first angle is affixed to the plate during installation and the temporary holding devices are removed thereafter.

4. The pre-manufactured floor-ceiling panel of claim 1, wherein the horizontal section of the first angle is formed with at least one cutout that is sized and shaped to accommodate a spigot attached to the load bearing wall.

5. The pre-manufactured floor-ceiling panel of claim 1, wherein the horizontal section of the second angle is affixed with screws to the horizontal member of the load bearing wall.

6. The pre-manufactured floor-ceiling panel of claim 1, further comprising: a first sheet of metal affixed, on a first side of the floor-ceiling panel, to the joists and the end member; a second sheet of metal affixed, on a second side of the floor-ceiling panel, to the joists and the end member, wherein the first and second sheets of metal provide structural strength, sound proofing, and increased fire rating for the pre-manufactured floor-ceiling panel.

7. The pre-manufactured floor-ceiling panel of claim 6, wherein: the first and second sheets of metal are affixed to the joists and the end members with closely spaced screws to increase the structural strength of the pre-manufactured floor-ceiling panel, wherein interconnection of the first and second sheets of metal, the joists, and the end members define a horizontal diaphragm configured to transmit or receive loads of the building, and the screws are spaced at about 6 inches apart.

8. The pre-manufactured floor-ceiling panel of claim 6, further comprising: a cement board layer that overlies the first sheet of metal; two gypsum board layers that underlie the second sheet of metal; a first set of screws that affix the cement board layer and the first sheet of metal to the joists and end members in tandem; a second set of screws that affix the second sheet of metal to the joists and end members in tandem; and a third set of screws, offset from the first set of screws, that affix the two gypsum board layers to the second sheet of metal.

9. The pre-manufactured floor-ceiling panel of claim 8, wherein the horizontal member of the second angle overlies the cement board layer.

10. The pre-manufactured floor-ceiling panel of claim 1, wherein the building is a low-rise building or a mid-rise building.

11. The pre-manufactured floor-ceiling panel of claim 1, further comprising utilities that run within spaces defined by the joists and that exit at a floor side and at a ceiling side of the pre-manufactured floor-ceiling panel for surface connection with other utilities.

12. The pre-manufactured floor-ceiling panel of claim 1, wherein the pre-manufactured floor ceiling panel forms a horizontal diaphragm that provides a load path for shear load, and wherein the shear load passes from the load bearing wall, then to the horizontal member, then to the second angle, then across the diaphragm, and then to a linking connection to a structural element of the building.

13. A multi-story building, comprising: a stair and elevator module at a ground level of the building; brace members that are guided into position by the stair and elevator module; a steel transfer structure that is linked to the brace members, wherein the steel transfer structure includes vertical columns and horizontal beams; pre-manufactured first floor-ceiling panels that are hung from the beams; pre-manufactured first load bearing walls positioned on top of the beams; pre-manufactured utility walls that are hung from the first load bearing walls; corridor panels that are hung from the utility walls; and pre-manufactured second floor-ceiling panels that are hung from

the first load bearing walls, wherein each of the pre-manufactured second floor-ceiling panels include: a plurality of parallel metal joists; an end member affixed to an end of the joists; a first angle having a horizontal section and a vertical section, wherein the horizontal section of the first angle is configured to be placed on top of a plate of a particular first load bearing wall of the building, and wherein the vertical section of the first angle is affixed to the end member; a second angle having a horizontal section and a vertical section, wherein the horizontal section of the second angle forms a fastening location for a horizontal member of the particular first load bearing wall, and wherein the vertical section of the second angle is affixed to the vertical section of the first angle, wherein the horizontal section of the first angle is formed with first holes for alignment with second holes formed in the plate of the particular first load bearing wall.

14. The building of claim 13, further comprising a spigot installed at an end of the particular first load bearing wall, wherein the horizontal section of the first angle is formed with at least one cutout that is sized and shaped to accommodate the spigot.

15. The building of claim 13, wherein the building is a low-rise building having five or less stories.

16. The building of claim 13, wherein the first holes are sized and shaped to receive temporary devices inserted into the first and holes and the second holes, and wherein the temporary holding devices hold the first angle in alignment with the plate of the particular first load bearing wall while the horizontal section of the first angle is affixed to the plate during installation and the temporary holding devices are removed thereafter.

17. The building of claim 13, wherein each of the pre-manufactured second floor-ceiling panels include: a first sheet of metal affixed, on a first side of each of the pre-manufactured second floor-ceiling panels, to the joists and the end member; a second sheet of metal affixed, on a second side of each of the pre-manufactured second floor-ceiling panels, to the joists and the end member, wherein the first and second sheets of metal provide structural strength, sound proofing, and increased fire rating for the pre-manufactured floor-ceiling panel, and wherein the first and second sheets of metal are affixed to the joists and end members with screws, including at least some closely spaced screws to increase the structural strength of the pre-manufactured second floor-ceiling panel.

18. The building of claim 17, wherein each of the pre-manufactured second floor-ceiling panels include: a cement board layer that overlies the first sheet of metal; two gypsum board layers that underlie the second sheet of metal, and wherein the screws include: a first set of screws that affix the cement board layer and the first sheet of metal to the joists and end members in tandem; a second set of screws that affix the second sheet of metal to the joists and end members in tandem; and a third set of screws, offset from the first set of screws, that affix the two gypsum board layers to the second sheet of metal.

19. The building of claim 13, wherein the pre-manufactured second floor ceiling panel forms a horizontal diaphragm that provides a load path for shear load, and wherein the shear load passes from the first load bearing walls, then to the horizontal member, then to the second angle, then across the diaphragm, and then to a linking connection to a structural element of the building.

20. A method to manufacture a floor-ceiling panel for a multi-story building that includes load bearing walls, the method comprising: arranging a plurality of metal joists in parallel; affixing an end member to ends of the joists; affixing a first angle and a second angle to each other, wherein: the first angle has a horizontal section and a vertical section, wherein the horizontal section of the first angle is configured to be placed on top of a plate of a load bearing wall of the building, the second angle has a horizontal section and a vertical section, wherein the horizontal section of the second angle forms a fastening location for a horizontal member of the load bearing wall, and the first angle and the second angle are affixed to each other by affixing the vertical section of the second angle to the vertical section of the first angle; affixing the vertical section of the first angle to the end member; forming first holes in the horizontal section of a first angle for alignment with

second holes formed in the plate of the load bearing wall; and forming at least one cutout in the horizontal section of the first angle to accommodate a spigot attached to the load bearing wall.

---