

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12383250
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Depenbusch; Michael Jerome

Devices for intraocular surgery

Abstract

An anterior chamber maintainer (ACM) is fastened to the cornea of a patient's eye at one or more, or potentially two or more, points of contact. The ACM can be inserted through a first and second incision. The ACM can be fastened to each of the two incisions using, for example, friction surfaces, ridges, a malleable tip, magnets, a segmented tip, or other types of fasteners. The ACM includes openings to provide irrigation solution to maintain the volume of the patient's eye during cataract surgery. The shape of the openings can be customized to reduce the amount of turbulence caused by the irrigation solution. By fastening the ACM to the cornea, the ACM is less likely to shift around or become dislodged from the eye during surgery. The ACM can be integrated with iris retractors to hold the position of a floppy iris during surgery.

Inventors:	Depenbusch; Michael Jerome (Chandler, AZ)
Applicant:	Michael Jerome Designs, LLC (Chandler, AZ)
Family ID:	61905940
Assignee:	Michael Jerome Designs, LLC (Chandler, AZ)
Appl. No.:	17/510070
Filed:	October 25, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220039787 A1	Feb. 10, 2022

Related U.S. Application Data

continuation parent-doc US 16338418 US 11179147 WO PCT/US2017/055797 20171009 child-doc US 17510070

Publication Classification

Int. Cl.: **A61B17/02** (20060101); **A61B17/00** (20060101); **A61F9/007** (20060101); **A61M3/02** (20060101)

U.S. Cl.:

CPC **A61B17/0231** (20130101); **A61F9/00745** (20130101); **A61M3/0266** (20130101); **A61B2017/00876** (20130101); **A61B2217/007** (20130101); **A61M2210/0612** (20130101)

Field of Classification Search

CPC: A61B (17/0231); A61B (17/02); A61B (2217/007); A61B (2017/00876); A61B (17/0293); A61B (17/0281)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6155975	12/1999	Urich et al.	N/A	N/A
6203513	12/2000	Yaron et al.	N/A	N/A
10159600	12/2017	Horvath	N/A	A61F 9/00781
11197779	12/2020	Van Meter	N/A	A61B 3/16
2004/0111050	12/2003	Smedley	604/9	A61F 9/00781
2004/0127843	12/2003	Tu	604/27	A61F 9/0017
2007/0118147	12/2006	Smedley	606/107	A61F 9/0017
2007/0191863	12/2006	De Juan	606/108	A61F 9/007
2009/0182421	12/2008	Silvestrini et al.	N/A	N/A
2010/0274259	12/2009	Yaron et al.	N/A	N/A
2010/0280435	12/2009	Raney et al.	N/A	N/A
2013/0215383	12/2012	Siminou	N/A	N/A
2014/0074011	12/2013	Charles	N/A	N/A
2014/0107428	12/2013	LaConte	600/249	A61B 3/117
2014/0163455	12/2013	Wilson et al.	N/A	N/A
2015/0148729	12/2014	Pinchuk	604/8	A61M 27/002
2017/0007451	12/2016	Depenbusch	N/A	A61M 1/85
2019/0209374	12/2018	Banko	N/A	A61F 9/00745

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO 2010/080356	12/2009	WO	N/A

OTHER PUBLICATIONS

PCT International Search Report and Written Opinion, PCT Application No. PCT/US2017/055797, Jan. 25, 2018, 16 pages. cited by applicant
United States Office Action, U.S. Appl. No. 16/338,418, filed Apr. 22, 2021, eight pages. cited by applicant
United States Office Action, U.S. Appl. No. 16/338,418, filed Oct. 20, 2020, 11 pages. cited by applicant

Primary Examiner: Robert; Eduardo C

Assistant Examiner: Lane; Holly Joanna

Attorney, Agent or Firm: Fenwick & West LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 16/338,418, filed Mar. 29, 2019, which is a 35 U.S.C. 371 national stage filing of International Application No. PCT/US2017/055797, filed on Oct. 9, 2017, which claims the benefit of and priority to U.S. Provisional Application No. 62/408,643, filed Oct. 14, 2016, and U.S. Provisional Application No. 62/408,640, filed Oct. 14, 2016, all of which are incorporated by reference herein in their entirety.

BACKGROUND

Field of Art

(1) This invention relates generally to the field of ocular surgery, and particularly to an anterior chamber maintainer and fluidic control system for surgery.

Description of the Related Art

(2) The anterior segment of the human eye includes the cornea, iris, and lens. A patient with an eye disease or disorder may require anterior segment surgery, for example, cataract surgery. Cataract surgery involves removing the lens of a patient's eye that has become cloudy due to cataract formation, and replacing the lens with a clear artificial lens. A physician begins by making incisions in the eye to facilitate the insertion of surgical instruments. The physician uses surgical instruments such as choppers to break a cataract into smaller fragments so that a vacuum can aspirate the fragments to remove them from the eye via an incision. Once the fragments are removed, the physician inserts the artificial lens through an incision. Phacoemulsification is a type of cataract surgical procedure that uses ultrasound to emulsify the cataract. In particular, a physician inserts a phacoemulsification tip to the location of the cataract, and the phacoemulsification tip vibrates at an ultrasonic frequency to break down the cataract. The phacoemulsification tip includes a lumen (a hollow cavity) such that cataract fragments can be vacuumed out of the eye through the phacoemulsification tip. Phacoemulsification can also be completed without ultrasound using a phacoemulsification tip by mechanically breaking up the cataract, such as with an instrument called a chopper, and aspirating through the tip.

(3) Existing phacoemulsification tips and other types of aspiration tips can also serve as an anterior chamber maintainer (ACM). An anterior chamber maintainer provides an irrigation solution at a certain pressure into the eye to maintain intraocular pressure (e.g., to maintain the anterior chamber shape of the eye) and cool the phacoemulsification tip during surgery. When a physician is aspirating fragments from the eye, irrigation solution at a higher pressure should be provided into the eye to help flush out the fragments (as well as to maintain the anterior chamber shape). Existing solutions provide solution at a single pressure level. For example, the solution is provided from a

bottle positioned at a particular height. To change the pressure level, existing solutions require significant pause during surgery since the physician, nurse, or a technician needs to manually change settings of the system to reposition the bottle. However, during the surgery (e.g., a 5-20 minute procedure), the physician may need to quickly change between a low pressure solution and a high pressure solution, which is not possible in the time that it takes to manually reposition the bottle.

(4) Existing anterior chamber maintainers are inserted into the eye through an incision in the cornea. Existing anterior chamber maintainers are difficult to stabilize in a fixed position and may also become dislodged from the eye during surgery. Further, due to the positioning of the anterior chamber maintainer, the irrigation solution can cause turbulence and fluid whirlpools that disrupts the physician performing the surgery. It is desirable and challenging to fasten an anterior chamber maintainer inside a patient's eye and provide the irrigation solution without causing turbulence and/or without causing the anterior chamber maintainer to become dislodged.

SUMMARY

(5) In an embodiment, an anterior chamber maintainer (ACM) is fastened to the cornea of a patient's eye at one or more, or potentially two or more, points of contact. The ACM can be inserted through a first incision and a second incision. The ACM can be fastened to each of the two incisions using, for example, friction surfaces, ridges, a malleable tip, magnets, a segmented tip, or other types of fasteners. The ACM includes openings to provide irrigation solution (e.g., a fluid) to maintain the volume of the patient's eye during cataract surgery. The shape of the openings can be customized to reduce the amount of turbulence caused by the irrigation solution. By fastening the ACM to the cornea, the ACM is less likely to shift around or become dislodged from the eye during surgery. The ACM can be integrated with iris retractors to enlarge the pupil and to hold the position of a floppy iris during surgery. Further, fastening the ACM to multiple points of contact on the eye enables the ACM to direct the flow of irrigation solution in certain directions.

(6) In various embodiments, an anterior chamber maintainer (ACM) includes an exterior wall and an interior wall forming a tubular structure. The tubular structure includes a first section including a first fastener configured to be fastened to a first location of a cornea of an eye, a second section including a second fastener configured to be fastened to a second location of the cornea, and a third section adjacent to the first section and the second section. The third section includes one or more openings configured to deliver fluid from a lumen, formed by the interior wall, into the eye. The ACM further includes a sharp edge positioned in the vicinity of the first section.

(7) In one or more embodiments, the one or more openings includes a plurality of openings each having a different size.

(8) In one or more embodiments, the one or more openings includes a first opening configured to direct the fluid in a direction into the eye, and a second opening configured to direct the fluid in a different direction into the eye.

(9) In one or more embodiments, the third section further includes one or more iris retractors configured to be fastened to a portion of an iris tissue of the eye.

(10) In one or more embodiments, at least one of the first fastener and the second fastener is a friction surface having a higher coefficient of friction than another coefficient of friction of a surface of the third section.

(11) In one or more embodiments, at least one of the first fastener and the second fastener is a plurality of ridges that physically contacts the first location or the second location.

(12) In one or more embodiments, at least one of the first fastener and the second fastener is a malleable tip.

(13) In one or more embodiments, at least one of the first fastener and the second fastener is a magnet.

(14) In one or more embodiments, the anterior chamber maintainer is coupled to a fluidic control system to receive the fluid at one of a plurality of different fluid pressures.

- (15) In one or more embodiments, the third section includes a first curved segment adjacent to the first section and a second curved segment adjacent to the second section.
- (16) In an embodiment, a fluidic control system includes at least two containers of fluid positioned at different heights. Alternatively, the system includes a container with two or more chambers each having different compression levels such as a low and a high compression. A physician can use the fluidic control system during cataract surgery (or other ocular surgeries) to provide solutions, corresponding to two different pressures (e.g., fluid pressures), into a patient's eye. A low pressure (lower height) solution can be used to maintain the eye's intraocular pressure, while a high pressure (higher height) solution can be used when the physician is aspirating fragments from the eye during surgery. The physician can use pedals or other input devices to control the delivery of the fluid. For example, the physician adjusts the pedal to a first position to deliver solution from one container and adjusts the pedal to a second position to deliver solution from another container.
- (17) In various embodiments, a method for using an anterior chamber maintainer includes cutting a first incision and a second incision in a cornea of an eye. The method further includes inserting the anterior chamber maintainer through the first incision, the anterior chamber maintainer being a tubular structure and including one or more openings along a longitudinal body of the anterior chamber maintainer. The method further includes inserting the anterior chamber maintainer through the second incision such that the one or more openings are positioned inside the eye. The method further includes fastening the anterior chamber maintainer to the first incision and the second incision. The method further includes providing fluid into the eye using the one or more openings of the anterior chamber maintainer.
- (18) In one or more embodiments, the method further includes fastening one or more iris retractors of the anterior chamber maintainer to a portion of an iris tissue of the eye.
- (19) In one or more embodiments, the method further includes manipulating another tool in the eye while the providing the fluid into the eye using the one or more openings of the anterior chamber maintainer.
- (20) In one or more embodiments, fastening the anterior chamber maintainer includes inserting another tool into the eye and manipulating the tool to position the anterior chamber maintainer.
- (21) In one or more embodiments, inserting the anterior chamber maintainer through the first incision includes inserting a needle through the first incision, where the needle positioned inside the tubular structure of the anterior chamber maintainer. The method further includes removing the needle from the tubular structure of the anterior chamber maintainer.
- (22) In one or more embodiments, the method further includes cutting a third incision in the cornea of an eye, and fastening the anterior chamber maintainer to the third incision.
- (23) In various embodiments, a system includes a stand coupled to a first container having a first compression level and a second container having a second compression level different than the first compression level. The system further includes a pedal including a lever. The system further includes an interface coupled to the pedal, the first container, and the second container. The interface is configured to provide first fluid from the first container in response to determining that the lever is at a first position and provide second fluid from the second container in response to determining that the lever is at a second position.
- (24) In one or more embodiments, the first container and the second container are positioned at different heights from each other on the stand.
- (25) In one or more embodiments, the system further includes an anterior chamber maintainer coupled to the interface and configured to receive the first fluid and the second fluid.
- (26) In one or more embodiments, the system further includes an alignment device for aligning a reference point of the stand to a patient receiving at least one of the first fluid and the second fluid.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1A shows a prior art phacoemulsification tip.
- (2) FIG. 1B shows a prior art anterior chamber maintainer.
- (3) FIG. 2A is a flowchart of a process of fastening an anterior chamber maintainer to an eye according to one embodiment.
- (4) FIG. 2B shows incisions cut into a cornea of an eye according to one embodiment.
- (5) FIG. 2C shows an anterior chamber maintainer inserted into the eye shown in FIG. 2B according to one embodiment.
- (6) FIG. 2D shows the anterior chamber maintainer shown in FIG. 2C fastened to the eye according to one embodiment.
- (7) FIG. 3A is another flowchart of a process of fastening an anterior chamber maintainer to an eye according to one embodiment.
- (8) FIG. 3B shows an anterior chamber maintainer with a needle according to one embodiment.
- (9) FIG. 3C shows the anterior chamber maintainer shown in FIG. 3B inserted into an eye according to one embodiment.
- (10) FIG. 3D shows the anterior chamber maintainer shown in FIG. 3C with the needle removed according to one embodiment.
- (11) FIG. 4A shows an anterior chamber maintainer with constant sized openings according to one embodiment.
- (12) FIG. 4B shows an anterior chamber maintainer with variable sized openings according to one embodiment.
- (13) FIG. 4C shows an anterior chamber maintainer with a single opening according to one embodiment.
- (14) FIG. 4D shows an anterior chamber maintainer with openings that direct fluid flow according to one embodiment.
- (15) FIG. 5A shows an anterior chamber maintainer with a sharp tip fastened to an eye according to one embodiment.
- (16) FIG. 5B shows an anterior chamber maintainer with friction surfaces fastened to an eye according to one embodiment.
- (17) FIG. 5C shows an anterior chamber maintainer with ridges fastened to an eye according to one embodiment.
- (18) FIG. 5D shows an anterior chamber maintainer with a malleable tip fastened to an eye according to one embodiment.
- (19) FIG. 5E shows an anterior chamber maintainer with a magnetic tip fastened to an eye according to one embodiment.
- (20) FIG. 5F shows an anterior chamber maintainer with a segmented tip fastened to an eye according to one embodiment.
- (21) FIG. 5G shows an anterior chamber maintainer and another tool inserted into an eye according to one embodiment.
- (22) FIG. 5H shows an anterior chamber maintainer and a forceps tool inserted into an eye according to one embodiment.
- (23) FIG. 5I shows an anterior chamber maintainer fastened to an eye at three points according to one embodiment.
- (24) FIG. 6 shows a prior art iris retractor.
- (25) FIG. 7 shows an anterior chamber maintainer integrated with an iris retractor according to one embodiment.
- (26) FIG. 8 shows an anterior chamber maintainer with curved segments according to one embodiment.
- (27) FIG. 9 shows a fluidic control system according to one embodiment.

(28) The figures depict embodiments of the present invention for purposes of illustration only. One skilled in the art will readily recognize from the following discussion that alternative embodiments of the structures and methods illustrated herein may be employed without departing from the principles of the invention described herein.

DETAILED DESCRIPTION

(29) Particular embodiments as described herein relate to phacoemulsification tips, which may also be referred to as phaco tips, phacoemulsification probes, phaco probes, phacoemulsification needles, phaco needles, vacuum tips, or aspiration tips. The fragments of cataracts or fragments of other anatomical tissues (e.g., corneal tissue) that are produced during a surgical procedure are referred to as fragments herein. A physician may conduct a surgery with the help of nurses or other types of assistants. For simplicity, each of these individuals may be referred to herein as a physician.

(30) The figures are not necessarily drawn to scale. In particular, certain features of anterior chamber maintainers (ACM), fluidic control system, other surgical tools, or parts of the eye have been enlarged for purposes of illustration and clarity. The ACMs described herein can be connected to a source of irrigation solution and a pump (e.g., a fluidic control system) to transfer the irrigation solution into the eye. Further, the phaco tips described herein can be connected to a pump or other systems (e.g., a fluidic control system) used to create vacuum or suction in the phaco tips to aspirate fragments from a patient's eye.

Example Prior Art

(31) FIG. 1A shows a prior art phacoemulsification tip **130**. A physician can use the phaco tip **130** during cataract surgery to provide an irrigation solution, e.g., a balanced salt solution (BSS), into an eye **100** of a patient. A lumen **140** of the phaco tip **130** is surrounded by a sleeve **145**. The irrigation solution (e.g., a fluid) enters a hand piece (not shown in FIG. 1A) coupled to the phaco tip **130** and then travels into the sleeve **145** surrounding the phaco tip **130**. The fluid then enters the eye **100** through a port **147** in the sleeve **145** to maintain intraocular pressure and cool the phaco tip **130** (e.g., functioning as a heat sink). Maintaining intraocular pressure is required to maintain the anterior chamber shape of the eye **100** (thus preventing the eye from collapsing) during surgery. The heat generated by ultrasound of the phaco tip **130** during phacoemulsification can burn surrounding tissue of the eye **100** if the phaco tip **130** is not cooled using the irrigation solution or using another cooling method.

(32) During a typical cataract surgery, a physician (e.g., a surgeon) cuts an incision **135** in the cornea **115** of the eye **100**. The physician inserts the phaco tip **130** with an irrigation sleeve into the eye **100** through the incision **135**. Since the phaco tip **130** and the irrigation sleeve are coupled to the eye **100** only at the interface of the incision **135** and held by the physician by a hand piece and manipulated as a tool, the phaco tip **130** may not remain in a stable position during surgery. Since the physician will be moving the phaco tip **130** to different positions in the eye **100**, there may be turbulence and unpredictable fluidics inside the eye **100**. Other disadvantages of providing irrigation solution through a sleeve of a phaco tip include variations in the fluid flow due to variations in the size or geometry of the phaco tip and/or sleeve, and a high likelihood of causing the anterior chamber of the eye to collapse during surgery. Additionally, the irrigation solution flowing out of the sleeve **145** can interfere with fragments being vacuumed into the lumen **140**, e.g., because the irrigation solution and fragments are trying to travel in opposing directions. Existing phaco tips can require up to 4 millimeters of clearance into the eye, e.g., the phaco tip **130** needs to be inserted approximately 4 millimeters through the incision **135**. Since the cornea **115** of humans has an average diameter of 11-12 millimeters, a 4 millimeter clearance can make it difficult for the phaco tip **130** to direct irrigation solution in tight corners inside the eye **100**. In addition, if the sleeve **145** becomes pulled into a wound of the eye **100**, the phaco tip **130** may overhydrate the wound with irrigation solution, which would interfere with maintaining the intraocular pressure.

(33) During cataract surgery, the physician can use additional surgical tools such as a chopper **120**

to break a cataract into smaller fragments. The physician inserts the chopper **120** via another incision **125** in the cornea **115**. The physician uses the chopper **120** to reach cataracts, which are located at the lens of the eye **100**. The lens of the eye **100** is behind the pupil **110**, which is the opening formed by the iris **105** tissue of the eye **100**. Phaco tips may also be used in other types of surgical procedures.

(34) FIG. **1B** shows a prior art anterior chamber maintainer **131**. The ACM **131** is a tube that includes a lumen and an opening at the distal end of the tube to provide irrigation solution into the eye **100**. The physician inserts the ACM **131** into the eye **100** through an incision in the cornea **115**. A physician may have difficulty manually maintaining a stable position of the ACM **131**. The ACM **131** frequently becomes dislodged unexpectedly during surgery because the ACM **131** is not securely fastened to the eye **100**. This “typical” ACM is not stable and the tip of the ACM can damage surrounding tissue (e.g. cornea, iris, or lens). The instability of the positioning of the “typical” ACM also causes the fluidics in the eye to be unpredictable.

(35) FIG. **1B** also shows another prior art phaco tip **132**. Similar to the phaco tip **130** shown in FIG. **1A**, the phaco tip **132** can also provide irrigation solution into the eye **100** through the port **147** of the sleeve **145**. Similar to the ACM **131**, the phaco tip **132** may also become dislodged unexpectedly during surgery because the phaco tip **132** is not securely fastened to the eye **100**.

Example Double Fastening an Anterior Chamber Maintainer

(36) FIG. **2A** is a flowchart of a process **200** of fastening an anterior chamber maintainer to an eye according to one embodiment. The process **200** may be performed by one or more physicians, a surgical robotic system, or any combination thereof. The process **200** may include different or additional steps than those described in conjunction with FIG. **2A** in some embodiments or perform steps in different orders than the order described in conjunction with FIG. **2A**. The process **200** is explained below with reference to FIGS. **2B-D**.

(37) FIG. **2B** shows incisions cut into a cornea **115** of an eye **100** according to one embodiment. The physician (or a surgical robotic system) cuts **202** a first incision **215** and a second incision **210** into the cornea **115** of the eye **100**. These can be incisions made with a scalpel or another instrument, or can be incisions made with a tip of the ACM itself as it is being inserted into the cornea **115** if the ACM has a sharp tip or has a removable attachment to the tip that is sharp.

(38) FIG. **2C** shows an ACM **220** inserted into the eye **100** shown in FIG. **2B** according to one embodiment. The physician inserts **204** the ACM **220** through the first incision **215**. The ACM **220** can have a sharp tip **230** to facilitate insertion through the first incision **215**.

(39) FIG. **2D** shows the ACM **220** shown in FIG. **2C** fastened to the eye **100** according to one embodiment. The physician inserts **206** the ACM **220** through the second incision **210**. The physician fastens **208** the ACM **220** to the second incision **210**. In some embodiments, the physician also fastens the ACM **220** to the first incision **215**.

(40) The ACM **220** includes one or more openings to provide irrigation solution into the eye **100** once the ACM **220** is fastened to the eye **100**. In the embodiment shown in FIG. **2D**, the ACM **220** includes three openings **240**, **245**, and **250**. The openings are located within the cornea **115** such that irrigation solution is not leaked outside of the eye **100**. In one embodiment, the length **260** of the ACM **220** located inside the cornea **115** is approximately 6 millimeters to 9 millimeters. In one embodiment, the lengths **255** and **265** of the ACM **220** that are each located outside of the cornea **115** after the ACM **220** has been fastened are approximately 3 millimeters to 6 millimeters. In other embodiments, the ACM **220** may have a different length located inside the cornea **115** and/or different lengths located outside of the cornea **115**. In one embodiment, the length **260** is 9 millimeters and the lengths **255** and **265** are each 3 millimeters, so the total length of the ACM **220** is 15 millimeters. The ACM **220** can include visual markers to indicate the length **260**, e.g., to assist the physician while inserting the ACM **220** into the eye **100**. The ACM **220** is coupled to an infusion line **270** by a port **275**. The infusion line **270** provides the irrigation solution from an irrigation solution source (not shown in FIG. **2D**) to the ACM **220**. For example, the irrigation

solution source may be a fluidic control system, further described below with reference to FIG. 9. Fastening the ACM **220** to the eye **100** may stabilize the movement of contents (e.g., cataract fragments and irrigation solution) inside the anterior chamber, and thus reduce the likelihood that the posterior capsule of the eye will rupture during surgery.

(41) The physician can cut another incision **290** in the cornea **115** to insert additional surgical tools during the surgery. For example, the physician inserts a phaco tip **280** through the incision **290** to operate in the eye **100**. In one embodiment, the phaco tip **280** is designed to be used without application of ultrasound or laser energy to the eye, such as the phaco tips described in U.S. patent application Ser. No. 15/196,844, filed on Jun. 29, 2016, which is hereby incorporated by reference herein in its entirety. In some embodiments, regardless of whether the phaco tip **280** uses ultrasound, the phaco tip **280** may not require a sleeve for liquid cooling using the irrigation solution. Thus, the irrigation solution can be provided by a separate ACM tool (e.g., the ACM **220**).

(42) FIG. 3A is another flowchart of a process **300** of fastening an anterior chamber maintainer to an eye according to one embodiment. The process **300** may be performed by one or more physicians, a surgical robotic system, or any combination thereof. The process **300** may include different or additional steps than those described in conjunction with FIG. 3A in some embodiments or perform steps in different orders than the order described in conjunction with FIG. 3A. The process **300** is explained below with reference to FIGS. 3B-D.

(43) FIG. 3B shows an anterior chamber maintainer **320** with a needle **325** according to one embodiment. The physician cuts **302** a first incision **215** and a second incision **210** into the cornea **115** of the eye **100**.

(44) FIG. 3C shows the ACM **320** shown in FIG. 3B inserted into an eye according to one embodiment. The physician inserts **304** the ACM **320** with the needle **325** through the first incision **215**. The needle **325** has a smaller radius than the ACM **320** and is positioned inside the ACM **320**, e.g., the needle **325** can slide within the lumen of the ACM **320**. In another embodiment, the needle **325** has a slightly larger radius than the ACM **320** and fits over the ACM **320** like a sleeve that can be withdrawn after insertion of the ACM **320**. Since the needle **325** has a sharp tip, the tip of the ACM **320** does not necessarily require a sharp tip to facilitate insertion of the ACM **320** through incisions in the cornea **115**. The physician inserts **306** the ACM **320** through the second incision **210**. The physician fastens **308** the ACM **320** to the second incision **210**.

(45) FIG. 3D shows the ACM **320** shown in FIG. 3C with the needle **325** removed according to one embodiment. The physician removes **310** the needle **325** from the ACM **320**, while leaving the ACM **320** fastened to the cornea **115** at the first incision **215** and the second incision **210**. The tip **330** of the ACM **320** forms a self-sealing waterproof seal after the needle **325** removed to prevent irrigation solution from leaking outside of the eye **100**.

Example Anterior Chamber Maintainer Openings for Fluid Flow

(46) FIG. 4A shows an anterior chamber maintainer **400** with constant sized openings according to one embodiment. The ACM **400** includes three openings **405**, **410**, and **415**. Each opening is the same size, and approximately 0.3 millimeters to 1.5 millimeters in length in one embodiment. Though the openings shown in FIG. 4A are ellipsoid, in other embodiments, the openings can have other types of shapes, e.g., rectangular, a shape with both straight and curved edges, etc. The openings of the ACM **400** are located along the longitudinal body of the ACM **400**. Since there is more surface area along the longitudinal body, the ACM **400** can facilitate larger sized openings compared to the ACM **130**, which can be advantageous to increase the throughput of irrigation solution. In some embodiments, the distal tip of the ACM **400** is sealed. In other embodiments, the distal tip of the ACM **400** also includes an opening. The opening at the distal tip of the ACM **400** can be waterproof sealed.

(47) The ACM **400** has an ellipsoid shaped cross sectional area **402**, e.g., a circular or oval shaped cross sectional area. In one embodiment with a circular cross sectional area **402**, the inner diameter (of an inner wall) of the ACM **400** is approximately 0.84 millimeters, and the outer diameter (of an

outer wall) of the ACM **400** is approximately 1.27 millimeters. In other embodiments, the inner and outer diameters of the ACM **400** may be different sizes, and the cross sectional area may be a different shape. The inner wall of the ACM **400** forms a lumen through which irrigation solution flows through. In some embodiments, an oval shaped cross sectional area **402** is advantageous because the oval shape stabilizes the ACM **400** fastened to the eye **100**. In particular, an ACM with an oval shaped cross sectional area is less likely to rotate along a longitudinal axis of the ACM, compared to another ACM with a circular shaped cross sectional area. In one embodiment, the minor axis of the oval shaped cross sectional area **402** is approximately 1.0 millimeters and the major axis of the oval shaped cross sectional area **402** is approximately 1.5 millimeters.

(48) FIG. **4B** shows an anterior chamber maintainer **420** with variable sized openings according to one embodiment. The ACM **420** includes a first opening **425** that has a length of approximately 1.5 millimeters, a second opening **430** of approximately 0.75 millimeters, and a third opening **435** of approximately 0.3 millimeters. The width of the openings **425**, **430**, and **435** are shown to be equal in FIG. **4B**, though in other embodiments, the width of the openings are not necessarily equal. Openings with variable lengths can be advantageous, for example, because the openings provide more uniform flow of the irrigation solution. In particular, since the fluid pressure is greater toward the distal end of the ACM **420** (e.g., the end further away from the irrigation solution source), the openings toward the distal end are larger the openings toward the proximal end. Thus, irrigation solution flow from the openings can have a more uniform pressure per surface area across the length of the ACM **420**.

(49) FIG. **4C** shows an anterior chamber maintainer **440** with a single opening **445** according to one embodiment. In some embodiments, the single opening **445** is advantageous because the throughput of irrigation fluid from the single opening **445** is greater than the throughput of irrigation fluid from the multiple openings that are smaller in size.

(50) FIG. **4D** shows an anterior chamber maintainer **450** with openings that direct fluid flow according to one embodiment. The ACM **450** includes a first opening **455** that directs the flow of irrigation solution toward the distal end of the ACM **450**. The ACM **450** includes a second opening **460** that directs the flow of irrigation solution toward the proximal end of the ACM **450**. In some embodiments, openings that direct fluid flow are advantageous because the direction of fluid flow can be designed to reduce the likelihood of causing turbulence in the eye **100**. Further, the direction of fluid flow can be designed to be directed toward the operation site in the eye **100**, e.g., the location of cataract fragments to be aspirated from the eye **100**. The edges of the first and second openings may be sharp or dull and may be beveled or non-beveled. Though the first and second openings shown in FIG. **4D** are funnel shaped, in other embodiments, the openings may have a different shape, e.g., cylindrical or a reverse-funnel shaped.

(51) The various embodiments of openings in the anterior chamber maintainers shown in FIGS. **4A-D** can be advantageous because the openings reduce or eliminate the likelihood that undesired turbulence or whirlpools occur inside the eye during surgery. In particular, the openings are designed to provide more control and uniform throughput of irrigation solution into the eye, compared to existing ACMs. Further, since the ACM is fastened to the cornea of the eye at two or more points (e.g., the first incision **215** and the second incision **210** shown in FIG. **2D** and FIG. **3D**), the ACM maintains a stable position and orientation in the eye while irrigation solution is provided via the openings. The ACM can be fastened to certain positions on the cornea to direct the flow of irrigation solution to an operative site, e.g., the location of cataracts to be aspirated from the eye. Fastening the ACM to the cornea at two or more points can also provide support for the cornea to retain its shape and not collapse during surgery. The ACM can be fastened to the first incision **215** or the second incision **210** using a variety of types of fasteners, which are further described below in Section IV. Fasteners for Anterior Chamber Maintainers. Though not shown in FIGS. **4A-D**, the ACM may be coupled (e.g., at a proximal end) to a fluidic control system (e.g., further described with respect to FIG. **9**) to provide irrigation solution or other types of fluid to the ACM.

(52) In some embodiments, one or more openings of an ACM facilitate aspiration of material from inside the eye. For example, the ACM is coupled to a vacuum pump (or syringe) and the ACM aspirates cataract fragments (or any other type of solid or viscoelastic material) from the eye through the openings. The vacuum force from the vacuum pump may attract cataract fragments to the openings, and/or a physician may feed cataract fragments to the openings, e.g., using a chopper. The ACM may include multiple openings and lumens for simultaneously providing irrigation solution and aspirating material. For example, a first set of openings is coupled to a first lumen coupled to source of irrigation solution, and a second set of openings is coupled to a second lumen coupled to a vacuum pump. In one embodiment, the ACM aspirates material using the openings and also includes a sleeve for providing the irrigation solution. An ACM fastened to the eye with integrated aspiration functionality is advantageous, for example, because the physician does not need to manually hold an aspiration device. Thus, the physician has a spare hand that can be used to hold or manipulate other surgical instruments.

Example Fasteners for Anterior Chamber Maintainers

(53) FIG. 5A shows an anterior chamber maintainer **500** with a sharp tip **505** fastened to an eye **100** according to one embodiment. A physician can use the sharp tip **505** to insert the ACM **500** into the incisions **215** and **210** of the cornea **115**. After inserting and fastening the ACM **500** to the cornea **115**, the physician can detach the sharp tip **505** from the ACM **500** (e.g., exposing a distal tip of the ACM **500** that is not sharp). Detaching the sharp tip **505** can be advantageous because the sharp tip **505** will not interfere with the physician while the physician performs a surgery.

(54) FIG. 5B shows an anterior chamber maintainer **510** with friction surfaces fastened to an eye **100** according to one embodiment. The ACM **510** includes a friction surface **515** that physically contacts the second incision **210** when the ACM **510** is inserted and fastened to the cornea **115**. The friction surface **515** can be a material with a higher coefficient of friction than that of the other surfaces of the ACM **510**. The friction surface **515** can also be formed by grooves in the ACM **510**. Thus, the friction surface **515** fastens the ACM **510** to the second incision **210**. In some embodiments, the ACM **510** also includes another friction surface that physically contacts the first incision **215**.

(55) FIG. 5C shows an anterior chamber maintainer **520** with ridges **525** fastened to an eye **100** according to one embodiment. The ridges **525** physically contact the second incision **210** when the ACM **520** is inserted and fastened to the cornea **115**. Thus, the ridges **525** fasten the ACM **520** to the second incision **210**. Though the ridges **525** illustrated in FIG. 5C include multiple sets of triangular ridges, in other embodiments, the ACM **520** can include different types of ridges or different numbers of ridges. For example, the ridges can be rounded or rectangular-shaped. Triangular ridges can be advantageous because the triangular shape facilitates insertion of the ACM **520** into the cornea **115**, but reduces the likelihood that the ACM **520** will become dislodged out of the cornea **115**. In some embodiments, the ACM **520** also includes another ridge (or ridges) that physically contact the first incision **215**. In some embodiments, the ridges are retractable such that the ridges can be retracted and flush with the outer surface of the ACM **520** during insertion into the cornea **115**. Thus, the ACM **520** may experience less friction while being inserted into the cornea **115**, and the ridges can be extended (from the retracted position) after insertion to fasten the ACM **520** in place.

(56) FIG. 5D shows an anterior chamber maintainer **530** with a malleable tip **535** fastened to an eye **100** according to one embodiment. The physician bends the malleable tip **535** (e.g., using tweezers) after inserting the ACM **530** through the first incision **215** and second incision **210** in the cornea **115**. Thus, the malleable tip **535** fastens the ACM **530** to the cornea **115**. The malleable tip **535** can be sharp to facilitate insertion of the ACM **530** through the incisions.

(57) FIG. 5E shows an anterior chamber maintainer **540** with a magnetic tip **542** fastened to an eye **100** according to one embodiment. A physician can fasten the ACM **540** to the cornea **115** by positioning a magnet **545** on the cornea **115**. In particular, the magnetic tip **542** is attracted by

magnetic force to the magnet **545**. The magnetic tip **542** can be sharp to facilitate insertion through the first incision **215**. In some embodiments, fastening the ACM **540** to the cornea **115** using magnetic force is advantageous because the physician only needs to cut one incision in the cornea **115**.

(58) FIG. 5F shows an anterior chamber maintainer **550** with a segmented tip **555** fastened to an eye **100** according to one embodiment. The physician folds out the segmented tip **555** (e.g., using tweezers) after inserting the ACM **550** through the first incision **215** and second incision **210** in the cornea **115**. The segmented tip **555** is folded in alignment longitudinally with the ACM **550** during insertion into the cornea **115** and folds out by rotating about the pivot **560**. Once the segmented tip **555** is folded out, the segmented tip **555** fastens the ACM **550** to the cornea **115**.

(59) FIG. 5G shows an anterior chamber maintainer **570** and another tool **575** inserted into an eye **100** according to one embodiment. A physician inserts the ACM **570** through the first incision **215** in the cornea **115** and inserts the other tool **575** through the second incision **210**. The physician can couple the ACM **570** to the other tool **575** inside the eye **100**. For example, the distal tip of the ACM **570** can be physically keyed into or hooked onto the distal tip of the other tool **575**. Once the ACM **570** is physically coupled to the other tool **575**, the physician can manipulate the ACM **570** using the other tool **575**. In particular, the physician positions the ACM **570** by removing the other tool from the second incision **210** such that the distal tip of the ACM **570** physically contacts the second incision **210**. After fastening the ACM **570** to the second incision **210**, the physician can uncouple the other tool **575** from the ACM **570**.

(60) FIG. 5H shows an anterior chamber maintainer **580** and a forceps tool **585** inserted into an eye **100** according to one embodiment. A physician inserts the ACM **580** through the first incision **215** in the cornea **115** and inserts the forceps tool **585** through the second incision **210**. The physician can couple the ACM **580** to the forceps tool **585** inside the eye **100**. In particular, pincers at the distal tip of the forceps tool **585** grab onto the distal tip of the ACM **580**. Similar to the other tool **575** shown in FIG. 5G, the physician can use the forceps tool **585** to manipulate the ACM **580**. Since the pincers can be folded into a compact form, the forceps tool **585** can have a smaller overall diameter than the ACM **580**. Thus, a smaller forceps tool **585** can be advantageous because the physician can cut a smaller second incision **210** (relative to the first incision **215**) to facilitate insertion of the forceps tool **585**.

(61) FIG. 5I shows an anterior chamber maintainer **590** fastened to an eye **100** at three points according to one embodiment. The ACM **590** has an additional segment **592** inserted through a third incision **594** in the cornea **115**. The segment **592** is movably coupled to the ACM **590**. The ACM **590** and the segment **592** can be fastened to the incisions **210**, **215**, and **594** using any of the fasteners previously described. Though FIGS. 5A-H show embodiments of ACMs that are fastened to the cornea at two points, in practice, the ACM can be fastened to the cornea at two or more points, as illustrated in FIG. 5I. For example, to fasten the ACM **590** at four points of the cornea **115**, the physician can insert a second additional segment through a fourth incision (not shown in FIG. 5I) in the cornea **115** that is also movably coupled to the ACM **590**. Fastening the ACM **590** to additional points of the cornea **115** can be advantageous, e.g., because it provides more stability to prevent the ACM **590** from shifting around during surgery.

Example Prior Art Iris Retractor

(62) FIG. 6 shows a prior art iris retractor. An iris retractor (also referred to as an iris hook) is a surgical tool that can be used to manipulate the iris tissue of a patient's eye. During cataract surgery, a physician can dilate (e.g., using dilating agents such as mydriatic drops) the patient's eye to increase accessibility to cataracts in the patient's eye. When dilated, the patient's eye muscles and iris tissue contract, increasing the size of the pupil, which is the opening to the lens of the eye where cataracts may form. However, some patients do not dilate well and/or experience intraoperative floppy iris syndrome where a patient's iris does not successfully dilate pharmacologically (and/or is “floppy”). Thus, a physician can mechanically dilate the patient's iris

by temporarily implanting iris retractors in the patient's eye.

(63) In one example conventional method for pupil expansion and stabilization, a physician inserts four iris retractors **610**, **620**, **630**, and **640** each through a different incision in the cornea **115**. Each of the iris retractors hooks onto a portion of the iris **105**. A challenge with existing iris retractors is that the iris can still shift or “flop,” which interferes with other surgical tools during cataract surgery. For example, the iris **105** can interfere with a phaco tip **650** (or an ACM) or an incision **660** through which the phaco tip **650** is inserted. Iris wings can also be used to expand the iris, though the iris wings are not fastened to the cornea, and thus may become dislodged or shift around during surgery.

Example Iris Retractor Integrated with an Anterior Chamber Maintainer

(64) FIG. 7 shows an anterior chamber maintainer **700** integrated with an iris retractor according to one embodiment. A physician inserts the ACM **700** through incisions in the cornea **115** and fastens the ACM **700** to the cornea **115**. The ACM **700** includes one or more iris retractor hooks, e.g., iris retractor hooks **710** and **720**. The iris retractor hooks physically attach to a portion of the iris **105**. In some embodiments, the physician can use another iris retractor (not shown in FIG. 7) to attach a portion of a floppy iris to the iris retractor hooks, e.g., because the iris retractor hooks do not reach the portion of the floppy iris. Though two iris retractor hooks are shown in FIG. 7, in other embodiments, the ACM **700** may include different types of iris retractors with varying sizes and shapes (e.g., a curved hook or a hook with a beveled tip).

(65) The physician can fasten the ACM **700** to a certain location in the eye (e.g., based on the location of two incisions in the cornea **115**) such that the ACM **700** prevents the iris **115** from interfering with other surgical instruments. For example, in contrast with the prior art iris retractor shown in FIG. 6, the ACM **700** physically prevents the iris **105** from reaching the distal tip of the phaco tip **650** or the incision **660** through which the phaco tip **650** is inserted. Integrating the iris retractor hooks with the ACM **700** can also be advantageous because the physician does not need to use separate iris retractors and ACMs. Consolidating the iris retraction and irrigation solution functionality to a single surgical tool can reduce costs and reduce the number of incisions that the physician needs to cut in a patient's cornea. Though only one ACM is shown in FIG. 7, in practice, the physician can insert and fasten multiple ACMs to the patient's cornea for a surgery. For example, a first ACM attaches to the iris on the right side of the cornea and a second ACM attaches to the iris on the left side of the cornea. In some embodiments, the ACM **700** includes iris retractors without necessarily including a lumen and openings to provide irrigation solution.

(66) In some embodiments, a physician uses the ACM **700** as a scaffolding structure that is coupled to other surgical instruments or devices, e.g., other types of iris retractors, irrigation sleeves, or aspiration nozzles. Thus, the other surgical instruments or devices are less likely to shift around inside the eye.

(67) FIG. 8 shows an anterior chamber maintainer **800** with curved segments according to one embodiment. Curved segments may be advantageous, for example, because the ACM **800** can more closely conform to the anatomy of the eye (e.g., the curvature of the cornea **115**) or can position the openings for providing irrigation solution closer toward the iris **105**. In some embodiments, the ACM **800** includes one or more malleable segments. For instance, the malleable segments may be bent to facilitate insertion or positioning of the ACM **800** in the eye.

Example Fluidic Control System

(68) FIG. 9 shows a fluidic control system **900** according to one embodiment. The fluidic control system **900**, also referred to herein as the system **900**, includes a stand **910**, a first container **920**, a second container **930**, a fluid interface **940**, a pedal **950**, and optionally a laser **960**, among other components. In one embodiment, the system **900** provides irrigation solution to a patient's eye **970** (e.g., the cornea of the eye in particular) during ocular surgery, for example, via an ACM according to any of the various embodiments described above.

(69) The stand **910** is coupled to the first container **920** and the second container **930**. In some

embodiments, the system **900** may include more than two containers coupled to the stand **910**. Each of the containers may be independently positioned at various heights along the stand **910**. For example, the first container **920** is positioned at a height that is higher than the position of the second container **930**. In some embodiments, the stand **910** includes two or more container holders to hold the containers. The container holders are movably coupled to the stand. For instance, the container holders slide along a rail of the stand and can be locked at a certain position using a braking mechanism. In one embodiment, the stand **910** includes a mechanism with an actuator (e.g., a motor) to automatically move the containers and/or container holders along the stand **910**. (70) The first container **920** and the second container **930** are configured to hold fluids, liquids, or aqueous solutions such as an irrigation solution for ocular surgery. The containers may be an intravenous (IV) plastic bag, a metal type container, a glass type container, or any other suitable type of container for holding solutions. The containers may be coupled to surgical instruments such as a phaco tip or an ACM (e.g., as shown in embodiments of the previous figures) via tubing, valves, and/or other types of interfacing components, e.g., fittings, junctions, and/or the fluid interface **940** described below. In one embodiment, the second container **930** is positioned approximately 30-50 centimeters (22-37 mmHg) above the eye **970**, and the first container **920** is positioned approximately 70-120 centimeters (51-88 mmHg) above the eye **970**. In other embodiments, a physician can position the containers at any other heights above the eye **970** based on the physician's particular preferences. Since the containers are positioned at a height above the eye **970**, solution from the containers can flow down toward the eye **970** due to gravitational force, e.g., thus not requiring the use of another actuator such as a fluid pump. In some embodiments, the containers may be compressed at two or more different pressures for systems that do not base the fluid flow and/or pressure of the solution by gravity.

(71) The fluid interface **940** is coupled to two or more containers, e.g., the first container **920** and the second container **930** via tubing. The fluid interface **940** may include a one-way valve to prevent high pressure solution of the first container **920** from entering the second container **930**. In one embodiment, the fluid interface **940** is coupled to surgical instruments (e.g., an ACM) via additional tubing. The fluid interface **940** controls whether solution from the first container **920** and/or the second container **930** is provided to the corresponding tubing for delivery to a surgical site, e.g., the eye **970**. For instance, the fluid interface **940** opens a first valve and/or a second valve to pass solution through tubing to a surgical tool (e.g., an ACM) from the first container **920** and/or the second container **930**, respectively. The fluid interface **940** can provide a continuous flow of solution from the first container **920** and/or the second container **930**. The fluid interface **940** may open or close the valves based on an input signal from an input device such as the pedal **950**.

(72) The pedal **950** is communicatively coupled to the stand **910**. In one embodiment, the pedal includes a lever that may be adjusted to two or more positions. For example, the pedal is placed on the ground and a physician adjusts the position of the lever by stepping on the pedal. During surgery, if the physician wants to deliver solution at a low pressure to manipulate fragments (and/or maintain the shape of the anterior chamber of the eye **970** using an ACM), the physician presses the pedal to move the lever to a first position corresponding to the second container **930** (lower than the first container **920**). Accordingly, the pedal **950** provides a first input signal to the fluid interface **940**. In response to receiving the first input signal, the fluid interface **940** provides a solution at the low pressure from the second container **930** via a surgical tool (e.g., a phaco tip or ACM) inserted into the cornea of the eye **970**. Additionally, if the physician wants to aspirate fragments using solution at a high pressure (relative to the low pressure), the physician presses the pedal to move the lever to a second position corresponding to the first container **920**, e.g., the physician presses the pedal further down. Accordingly, the pedal **950** provides a second input signal to the fluid interface **940**. In response to receiving the second input signal, the fluid interface **940** provides a solution at the high pressure from the first container **920** to the surgical tool (e.g., a phaco tip or ACM). In other embodiments, instead of a pedal, the system **900** includes any other

suitable type of input device (e.g., a joystick, mouse, keyboard, button, etc.) for providing input signals to the fluid interface **940**.

(73) In one embodiment, the system **900** includes two or more pedals (or input devices), each corresponding to a container. The fluid interface **940** provides solution from a container in response to receiving an input signal from the corresponding pedal.

(74) In some embodiments, a laser **960** is coupled to the stand **910**. A physician can use the laser **960** to visually align the containers (or any other reference point on the stand **910**) to the patient's eye **970** to prepare for a surgical procedure. By using an accurate alignment of the containers relative to the eye **970**, the system **900** can provide more granularity and control regarding the pressure of the solution provided to the eye **970**. Thus, the flow rate of the solution provided by the system **900** will be more accurate and consistent during surgery. In some embodiments, instead of a laser **960**, the system **900** may include any other suitable type of alignment device such as a lighted pointer or a mechanical visual guide.

(75) In one embodiment, the system **900** includes one container coupled to the stand **910** instead of two or more separate containers. The container includes two or more chambers (e.g., sub-containers) each having a compression level and containing solution. For example, the container includes a first chamber having a low compression level and a second chamber having a high compression level, relative to the low compression level. In some embodiments, the chambers or sub-containers may be at a same height. The fluid interface **940** delivers solution from the chambers based on input signals from an input device. For example, the fluid interface **940** delivers solution from the first chamber in response to the physician pressing the pedal **950** to a first position, and delivers solution from the second chamber in response to the physician pressing the pedal **950** to a second position. Since the system **900** includes both high and low pressure solutions, the system **900** can quickly—almost instantaneously—switch between providing one of the two (or more) solutions. Thus, as an example, the physician can deliver low pressure solution for the majority of a surgery and only switch to high pressure solution for a certain period of time when it is needed for the surgery.

ALTERNATIVE CONSIDERATIONS

(76) Upon reading this disclosure, those of skill in the art will appreciate still additional alternative structural and functional designs through the disclosed principles herein. Thus, while particular embodiments and applications have been illustrated and described, it is to be understood that the disclosed embodiments are not limited to the precise construction and components disclosed herein. Various modifications, changes and variations, which will be apparent to those skilled in the art, may be made in the arrangement, operation and details of the apparatus disclosed herein without departing from the spirit and scope defined in the appended claims. Features such as sharp tips (e.g., shown in FIGS. 2B-D), needles (e.g., shown in FIGS. 3B-D), different types of openings (e.g., shown in FIGS. 4A-D), different types of fasteners (e.g., shown in FIGS. 5A-I), and integrated iris retractors (e.g., shown in FIG. 7) may be used in any of the anterior chamber maintainer embodiments or designs described herein. In some embodiments, an ACM may include integrated iris retractors without necessarily including openings (or a lumen) for irrigation solution.

(77) As used herein any reference to “one embodiment” or “an embodiment” means that a particular element, feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment. The appearances of the phrase “in one embodiment” in various places in the specification are not necessarily all referring to the same embodiment.

(78) As used herein, the terms “comprises,” “comprising,” “includes,” “including,” “has,” “having” or any other variation thereof, are intended to cover a non-exclusive inclusion. For example, a process, method, article, or apparatus that comprises a list of elements is not necessarily limited to only those elements but may include other elements not expressly listed or inherent to such process, method, article, or apparatus. Further, unless expressly stated to the contrary, “or” refers to an inclusive or and not to an exclusive or. For example, a condition A or B is satisfied by any one

of the following: A is true (or present) and B is false (or not present), A is false (or not present) and B is true (or present), and both A and B are true (or present). In addition, use of the “a” or “an” are employed to describe elements and components of the embodiments herein. This is done merely for convenience and to give a general sense of the invention. This description should be read to include one or at least one and the singular also includes the plural unless it is obvious that it is meant otherwise.

Claims

1. A method for using an anterior chamber maintainer, the method comprising: cutting a first incision at a location of a cornea of an eye; cutting a second incision at a different location of the cornea; cutting a third incision at another different location of the cornea; inserting the anterior chamber maintainer through the first incision, the anterior chamber maintainer being a tubular structure including a first section, second section, and third section adjacent to the first section and the second section; fastening the first section to the first incision; fastening the second section to the second incision such that at least a first opening directed in a first direction a second opening directed in a second direction in the third section are positioned inside the eye, wherein the first direction is different than the second direction; fastening the anterior chamber maintainer to the third incision; directing fluid in the first direction through the first opening into the eye; and directing fluid in the second direction through the second opening into the eye.
2. The method of claim 1, wherein inserting the anterior chamber maintainer through the first incision comprises using a sharp edge positioned in vicinity of the first section.
3. The method of claim 1, wherein fastening the first section to the first incision or fastening the second section to the second incision comprises: using a friction surface having a higher coefficient of friction than another coefficient of friction of a surface of the third section.
4. The method of claim 1, wherein fastening the first section to the first incision or fastening the second section to the second incision comprises: using a magnet coupled to the first section or the second section.
5. The method of claim 1, wherein fastening the first section to the first incision or fastening the second section to the second incision comprises: using a plurality of ridges that physically contacts the first incision or the second incision.
6. The method of claim 1, further comprising: inserting a tool into the eye; and manipulating the tool to position the anterior chamber maintainer.
7. The method of claim 6, wherein the tool is a needle, and wherein the method further comprises: inserting the needle through the first incision, wherein the needle is positioned inside the tubular structure of the anterior chamber maintainer; and removing the needle from the tubular structure after the anterior chamber maintainer is positioned.
8. The method of claim 1, further comprising: coupling the anterior chamber maintainer to a fluidic control system to receive the fluid at a plurality of different fluid pressures; and selecting one of the plurality of different fluid pressures at which to provide the fluid into the eye.
9. The method of claim 1, further comprising: fastening one or more iris retractors of the anterior chamber maintainer to a portion of an iris tissue of the eye.
10. The method of claim 6, further comprising: manipulating another tool in the eye while providing the fluid into the eye.
11. A method for using an anterior chamber maintainer, the method comprising: cutting a first incision at a location of a cornea of an eye; cutting a second incision at a different location of the cornea; inserting the anterior chamber maintainer through the first incision, the anterior chamber maintainer being a tubular structure including a first section, second section, and third section adjacent to the first section and the second section; fastening the first section to the first incision; fastening the second section to the second incision such that at least a first opening directed in a

first direction a second opening directed in a second direction in the third section are positioned inside the eye, wherein the first direction is different than the second direction; inserting a tool into the eye; manipulating the tool to position the anterior chamber maintainer; directing fluid in the first direction through the first opening into the eye; directing fluid in the second direction through the second opening into the eye; and manipulating another tool in the eye while providing the fluid into the eye.

12. The method of claim 11, wherein inserting the anterior chamber maintainer through the first incision comprises using a sharp edge positioned in vicinity of the first section.

13. The method of claim 11, wherein fastening the first section to the first incision or fastening the second section to the second incision comprises: using a friction surface having a higher coefficient of friction than another coefficient of friction of a surface of the third section.

14. The method of claim 11, wherein the tool is a needle, and wherein the method further comprises: inserting the needle through the first incision, wherein the needle is positioned inside the tubular structure of the anterior chamber maintainer; and removing the needle from the tubular structure after the anterior chamber maintainer is positioned.

15. The method of claim 11, further comprising: cutting a third incision at another different location of the cornea; and fastening the anterior chamber maintainer to the third incision.

16. The method of claim 11, further comprising: coupling the anterior chamber maintainer to a fluidic control system to receive the fluid at a plurality of different fluid pressures; and selecting one of the plurality of different fluid pressures at which to provide the fluid into the eye.

17. The method of claim 11, further comprising: fastening one or more iris retractors of the anterior chamber maintainer to a portion of an iris tissue of the eye.
