

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250261007

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

ENDO; Hideyuki et al.

MOBILE TERMINAL TESTING DEVICE AND MOBILE TERMINAL TESTING METHOD

Abstract

There is provided a mobile terminal testing device that can improve measurement reproducibility at the same measurement position. The terminal testing device includes a positioner operation recording unit **16c** that stores an operation path of the DUT scanning mechanism **56** to the measurement position by tracing back from the measurement position to a preset number of the angular sample points PS, and a positioner operation control unit **16d** that controls the DUT scanning mechanism **56** according to the operation path stored in the positioner operation recording unit **16c** to adjust the DUT **100** to an angle of the measurement position when performing measurement at the measurement position.

Inventors: ENDO; Hideyuki (Kanagawa, JP), YOSHITO; Akihito (Kanagawa, JP),
SUZUKI; Keisuke (Kanagawa, JP), HATANO; Atsuya (Kanagawa, JP)

Applicant: ANRITSU CORPORATION (Kanagawa, JP)

Family ID: 96660350

Appl. No.: 19/025304

Filed: January 16, 2025

Foreign Application Priority Data

JP	2024-017863	Feb. 08, 2024
----	-------------	---------------

Publication Classification

Int. Cl.: H04W24/06 (20090101); G01R29/10 (20060101)

U.S. Cl.:

CPC H04W24/06 (20130101); G01R29/105 (20130101);

Background/Summary

TECHNICAL FIELD

[0001] The present invention relates to a mobile terminal testing device that tests a mobile terminal by exchanging signals while changing an angle of a positioner on which the mobile terminal is installed under an Over The Air (OTA) environment.

BACKGROUND ART

[0002] For a wireless terminal that has been developed in recent years and transmits and receives a radio signal corresponding to IEEE802.11ad, 5G cellular, and the like, in which a signal in a wide band of a millimeter wave band is used, a performance test is performed of measuring an output level and reception sensitivity of a transmitted radio wave determined for each communication standard with respect to a wireless communication antenna included in the wireless terminal, and determining whether or not a predetermined reference is satisfied.

[0003] For example, in a performance test in which a wireless terminal (hereinafter, referred to as a “5G wireless terminal”) for a New Radio System (NR system) of a fifth generation mobile communication system (hereinafter, also referred to as “5G”) is used as a Device Under Test (DUT), an OTA test using an anechoic box (OTA chamber) referred to as a Compact Antenna Test Range (CATR) that is not affected by a surrounding radio wave environment is performed.

[0004] As an example of a wireless terminal measurement device according to the related art capable of performing an OTA test, it is known that a wireless terminal is rotated around a reference point in a measurement space such as an anechoic box or an anechoic chamber, while radio waves transmitted from the wireless terminal are received by a measurement antenna, and radiation power characteristics (such as Equivalent Isotropic Radiated Power (EIRP), Equivalent Isotropic Sensitivity (EIS), Total Radiated Power (TRP)) of the wireless terminal are obtained from the received signal.

[0005] Patent Document 1 describes that, in the measurement of the DUT that is rotated to sequentially face all orientations of the spherical coordinate system under the OTA environment, the progress of the measurement at each measurement position is displayed.

RELATED ART DOCUMENT

[Patent Document]

[0006] [Patent Document 1] Japanese Patent No. 7227198

DISCLOSURE OF THE INVENTION

Problem that the Invention is to Solve

[0007] Measurements in the OTA environment are performed while changing the angle of the positioner on which the DUT is installed. However, it was found that the behavior of the antenna control on the DUT side, and the like changes depending on the operation path of the positioner to the measurement position, resulting in different measurement results.

[0008] Therefore, an object of the present invention is to provide a mobile terminal testing device that can improve measurement reproducibility at the same measurement position by reproducing the operation path of the positioner to the measurement position.

Means for Solving the Problem

[0009] According to the present invention, there is provided a mobile terminal testing device

including: a positioner that is provided in an internal space of an anechoic box, has an azimuth axis and a roll axis that are each rotationally drivable by a drive motor, and rotates a mobile terminal that is a device under test so that the mobile terminal sequentially faces a plurality of preset angular sample points of a spherical coordinate system, using a center of the spherical coordinate system as a reference point; a simulated measurement device connected to a test antenna in the internal space; an integrated control device that controls the simulated measurement device so that a measurement operation of transmitting a test signal from the test antenna to the mobile terminal, receiving a signal under measurement transmitted from the mobile terminal that has received the test signal by using the test antenna, and measuring a specific measurement item related to the mobile terminal based on the received signal under measurement is performed at a measurement position corresponding to each of the plurality of angular sample points; and a positioner operation recording unit that stores an operation path of the positioner to the measurement position by tracing back from the measurement position to a preset number of the angular sample points; and a positioner operation control unit that controls the positioner according to the operation path stored in the positioner operation recording unit to adjust the mobile terminal to an angle of the measurement position when performing measurement at the measurement position.

[0010] With this configuration, the operation path to the measurement position is stored by tracing back from the measurement position to a preset number of angular sample points, and the mobile terminal is adjusted to the angle of the measurement position according to the stored path when performing measurement at the measurement position. Therefore, measurement reproducibility at the same measurement position can be improved.

[0011] In the mobile terminal testing device according to the present invention, the positioner operation recording unit stores different operation paths up to a preset number in a case where the operation path of the positioner to the measurement position is an operation path different from the stored operation path.

[0012] With this configuration, in a case where the operation path to the measurement position is an operation path different from the stored operation path, different operation paths are stored up to a preset number. Therefore, measurement reproducibility at the same measurement position can be improved.

[0013] In addition, according to the present invention, there is provided a mobile terminal testing method of a mobile terminal testing device including a positioner that is provided in an internal space of an anechoic box, has an azimuth axis and a roll axis that are each rotationally drivable by a drive motor, and rotates a mobile terminal that is a device under test so that the mobile terminal sequentially faces a plurality of preset angular sample points of a spherical coordinate system, using a center of the spherical coordinate system as a reference point, a simulated measurement device connected to a test antenna in the internal space, and an integrated control device that controls the simulated measurement device so that a measurement operation of transmitting a test signal from the test antenna to the mobile terminal, receiving a signal under measurement transmitted from the mobile terminal that has received the test signal by using the test antenna, and measuring a specific measurement item related to the mobile terminal based on the received signal under measurement is performed at a measurement position corresponding to each of the plurality of angular sample points, the mobile terminal testing method including: a step of storing an operation path of the positioner to the measurement position by tracing back from the measurement position to a preset number of the angular sample points; and a step of controlling the positioner according to the stored operation path to adjust the mobile terminal to an angle of the measurement position when performing measurement at the measurement position.

[0014] In the mobile terminal testing method according to the present invention, the step of storing the operation path of the positioner is a step of storing different operation paths up to a preset number in a case where the operation path of the positioner to the measurement position is an operation path different from the stored operation path.

[0015] With this configuration, the operation path to the measurement position is stored by tracing back from the measurement position to a preset number of angular sample points, and the mobile terminal is adjusted to the angle of the measurement position according to the stored path when performing measurement at the measurement position. Therefore, measurement reproducibility at the same measurement position can be improved.

Advantage of the Invention

[0016] The present invention can provide a mobile terminal testing device that can improve measurement reproducibility at the same measurement position.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0017] FIG. 1 is a diagram showing a schematic configuration of an entire measurement device according to an embodiment of the present invention.

[0018] FIG. 2 is a block diagram showing a functional configuration of the measurement device according to the embodiment of the present invention.

[0019] FIG. 3 is a block diagram showing functional configurations of an integrated control device of the measurement device and a controlled system element thereof according to the embodiment of the present invention.

[0020] FIG. 4 is a block diagram showing a functional configuration of an NR system simulator in the measurement device according to the embodiment of the present invention.

[0021] FIGS. 5A and 5B are diagrams showing total spherical scanning images of a device under test in an OTA chamber of the measurement device according to the embodiment of the present invention, in which FIG. 5A shows a disposition mode of the device under test with respect to a center of a spherical coordinate system, and FIG. 5B shows a distribution mode of angular sample points PS in the spherical coordinate system.

[0022] FIG. 6 is a diagram explaining a disposition mode of a test antenna 5 in the OTA chamber of the measurement device according to the embodiment of the present invention using the spherical coordinate system (r , θ , ϕ) shown in FIGS. 5A and 5B.

[0023] FIG. 7 is a diagram showing a rotation drive image around an azimuth axis and a roll axis of a biaxial positioner related to the total spherical scanning of the DUT in the measurement device according to the embodiment of the present invention.

[0024] FIG. 8 is a diagram showing an example of measurement results based on paths to a measurement position of the measurement device according to the embodiment of the present invention.

[0025] FIG. 9 is a diagram showing an example of path reproduction to the measurement position of the measurement device according to the embodiment of the present invention.

BEST MODE FOR CARRYING OUT THE INVENTION

[0026] Hereinafter, a measurement device as a mobile terminal testing device according to an embodiment of the present invention will be described with reference to the drawings.

[0027] First, a configuration of a measurement device 1 according to the embodiment of the present invention will be described with reference to FIGS. 1 to 4. The measurement device 1 constitutes the mobile terminal testing device of the present invention. The measurement device 1 according to the present embodiment has an external structure as shown in FIG. 1 as a whole, and includes functional blocks as shown in FIG. 2. FIGS. 1 and 2 show a disposition mode of each component of an OTA chamber 50 in a state of being seen through from a side surface thereof.

[0028] The measurement device 1 is operated, for example, in a mode in which each of the above-described components is mounted on each rack 90a of a rack structure 90 having the structure shown in FIG. 1. FIG. 1 shows an example in which each of an integrated control device 10, an NR

system simulator **20**, and an OTA chamber **50** is mounted on each rack **90a** of the rack structure **90**.
[0029] As shown in FIG. 2, the measurement device **1** includes the integrated control device **10**, the NR system simulator **20**, a signal processing unit **23**, and the OTA chamber **50**.

[0030] For the configuration, the OTA chamber **50** will be described first. As shown in FIGS. 1 and 2, the OTA chamber **50** includes, for example, a metal housing main body **52** having a rectangular internal space **51**, and accommodates a DUT **100** having an antenna **110**, a test antenna **5**, a reflector **7**, and a DUT scanning mechanism **56** in the internal space **51**.

[0031] A radio wave absorber **55** is attached to a whole area of an inner surface of the OTA chamber **50**, that is, a bottom surface **52a**, a side surface **52b**, and a top surface **52c** of the housing main body **52**. As a result, in the OTA chamber **50**, each element (the DUT **100**, the test antenna **5**, the reflector **7**, and the DUT scanning mechanism **56**) disposed in the internal space **51** has an enhanced function of regulating intrusion of radio waves from the outside and radiation of the radio waves to the outside. In this way, the OTA chamber **50** realizes an anechoic box having the internal space **51** that is not affected by a surrounding radio wave environment. The anechoic box used in the present embodiment is, for example, an anechoic type.

[0032] Among those accommodated in the internal space **51** of the OTA chamber **50**, the DUT **100** is, for example, a wireless terminal such as a smartphone. Communication standards for the DUT **100** include cellular (LTE, LTE-A, W-CDMA (registered trademark), GSM (registered trademark), CDMA 2000, 1×EV-DO, TD-SCDMA, or the like), wireless LAN (IEEE 802.11b/g/a/n/ac/ad, or the like), Bluetooth (registered trademark), GNSS (GPS, Galileo, GLONASS, BeiDou, or the like), FM, and digital broadcasting (DVB-H, ISDB-T, or the like). Further, the DUT **100** may be a wireless terminal that transmits and receives a radio signal in a millimeter wave band corresponding to IEEE 802.11ad, 5G cellular, or the like.

[0033] In the present embodiment, the antenna **110** of the DUT **100** uses a radio signal in each regulated frequency band in conformity with, for example, LTE or 5G NR communication standard. The DUT **100** constitutes the device under test, that is, a mobile terminal in the present invention.

[0034] In the internal space **51** of the OTA chamber **50**, the DUT **100** is held by a part of mechanism of the DUT scanning mechanism **56**. The DUT scanning mechanism **56** is provided to extend in a vertical direction on the bottom surface **52a** of the housing main body **52** in the internal space **51** of the OTA chamber **50**. The DUT scanning mechanism **56** performs a total spherical scanning (refer to FIGS. 5A and 5B and FIG. 6), which will be described later, on the DUT **100** while holding the DUT **100** on which a performance test is performed.

[0035] As shown in FIG. 1, the DUT scanning mechanism **56** includes a turntable **56a**, a support column member **56b**, a DUT mounting portion **56c**, and a drive unit **56e**. The turntable **56a** includes a plate member having a disk shape, and has a configuration (refer to FIG. 3 and FIG. 7) that rotates around an azimuth axis (a rotation axis in the vertical direction). The support column member **56b** includes a columnar member disposed to extend in a direction perpendicular to a plate surface of the turntable **56a**.

[0036] The DUT mounting portion **56c** is disposed near an upper end of the support column member **56b** to be in parallel with the turntable **56a**, and has a mounting tray **56d** on which the DUT **100** is mounted. The DUT mounting portion **56c** has a configuration (refer to FIG. 3 and FIG. 7) capable of rotating around a roll axis (a rotation axis in a horizontal direction).

[0037] As shown in FIG. 3, the drive unit **56e** includes, for example, a drive motor **56f** that rotationally drives the azimuth axis, and a drive motor **56g** that rotationally drives the roll axis. The drive unit **56e** includes a biaxial positioner provided with a mechanism for performing rotations around the azimuth axis and the roll axis, respectively, by the drive motor **56f** and the drive motor **56g**. In this way, the drive unit **56e** can rotate the DUT **100** mounted on the mounting tray **56d** in biaxial (the azimuth axis and the roll axis) directions for each mounting tray **56d**. Hereinafter, there is a case where the entire DUT scanning mechanism **56** including the drive unit **56e** is referred to as

the biaxial positioner (refer to FIG. 3).

[0038] The DUT scanning mechanism (biaxial positioner) **56** performs total spherical scanning which sequentially changes a posture of the DUT **100** in a state in which the antenna **110** faces all orientations (a plurality of preset orientations) of a surface of the sphere while assuming that the DUT **100** mounted (held) on the mounting tray **56d** is disposed, for example, at a center **O1** of a sphere (refer to a sphere B in FIGS. 5A and 5B). Control of the DUT scanning in the DUT scanning mechanism **56** is performed by a DUT scanning control unit **16** which will be described later. The DUT scanning mechanism **56** constitutes the positioner in the present invention.

[0039] The test antenna **5** is attached to a required position on the bottom surface **52a** of the housing main body **52** of the OTA chamber **50** by using an appropriate holder (not shown). An attachment position of the test antenna **5** is a position at which visibility can be secured from the reflector **7** via an opening **67a** provided on the bottom surface **52a**. The test antenna **5** uses a radio signal in the frequency band of the same regulation (NR standard) as the antenna **110** of the DUT **100**.

[0040] In a case where measurement related to the NR of the DUT **100** is performed in the OTA chamber **50**, the test antenna **5** transmits a test signal from the NR system simulator **20** to the DUT **100** and receives a signal under measurement transmitted from the DUT **100** that has received the test signal. The test antenna **5** is disposed so that a light reception surface thereof becomes a focal position **F** of the reflector **7**. The reflector **7** is not always required in a case where the test antenna **5** can be disposed so that the light reception surface thereof faces the DUT **100** and appropriate light reception can be performed.

[0041] The reflector **7** is attached to a required position on the side surface **52b** of the OTA chamber **50** by using a reflector holder **58**. The reflector **7** realizes a radio wave path that returns the radio signal (the test signal and the signal under measurement) transmitted and received by the antenna **110** of the DUT **100** to the light reception surface of the test antenna **5**.

[0042] Subsequently, configurations of the integrated control device **10** and the NR system simulator **20** will be described.

[0043] As shown in FIG. 2, the integrated control device **10** is communicably connected to the NR system simulator **20** via a network **19** such as Ethernet (registered trademark). Further, the integrated control device **10** is also connected to a controlled system element in the OTA chamber **50**, for example, the DUT scanning control unit **16** via the network **19**.

[0044] The integrated control device **10** comprehensively controls the NR system simulator **20** and the DUT scanning control unit **16** via the network **19**, and includes, for example, a Personal Computer (PC). The DUT scanning control unit **16** may be independently provided accompanying with the OTA chamber **50** (refer to FIG. 2), or may be provided in the integrated control device **10** as shown in FIG. 3. Hereinafter, description will be performed while assuming that the integrated control device **10** has the configuration shown in FIG. 3.

[0045] As shown in FIG. 3, the integrated control device **10** includes a control unit **11**, an operation unit **12**, and a display unit **13**. The control unit **11** includes, for example, a computer device. The computer device includes a Central Processing Unit (CPU) **11a** that performs predetermined information processing to realize the function of the measurement device **1**, and performs comprehensive control on the NR system simulator **20**, and the DUT scanning control unit **16** as targets, a Read Only Memory (ROM) **11b** that stores an Operating System (OS) for starting up the CPU **11a**, the other programs, and control parameters, and the like, a Random Access Memory (RAM) **11c** that stores execution code, data, and the like of the OS or an application which is used for an operation by the CPU **11a**, an external I/F unit **11d**, an input and output port (not shown), and the like.

[0046] The external I/F unit **11d** is communicably connected to each of the NR system simulator **20** and the drive unit **56e** of the DUT scanning mechanism (biaxial positioner) **56** via the network **19**. An operation unit **12** and a display unit **13** are connected to the input and output port. The operation

unit **12** is a functional unit for inputting various information such as commands, and the display unit **13** is a functional unit for displaying various information such as an input screen, measurement results, and the like of the various information.

[0047] The computer device described above functions as the control unit **11** in such a way that the CPU **11a** executes a program stored in the ROM **11b** while using the RAM **11c** as a work area. As shown in FIG. **3**, the control unit **11** includes a call connection control unit **14**, a signal transmission and reception control unit **15**, a DUT scanning control unit **16**, a signal analysis control unit **17**, a setting control unit **18a**, and a rotation speed management control unit **18b**. The call connection control unit **14**, the signal transmission and reception control unit **15**, the DUT scanning control unit **16**, the signal analysis control unit **17**, the setting control unit **18a**, and the rotation speed management control unit **18b** are also realized by executing a predetermined program stored in the ROM **11b** in the work area of the RAM **11c** by the CPU **11a**.

[0048] The call connection control unit **14** drives the test antenna **5** via the NR system simulator **20** and the signal processing unit **23** to transmit and receive a control signal (radio signal) to and from the DUT **100**, thereby performing control to establish a call (a state where the radio signal can be transmitted and received) between the NR system simulator **20** and the DUT **100**.

[0049] The signal transmission and reception control unit **15** performs a control of monitoring a user operation in the operation unit **12**, transmitting a signal transmission command to the NR system simulator **20** after the call is established through call connection control, by being triggered with a predetermined measurement start operation related to the measurement of transmission and reception characteristics of the DUT **100** by the user, and transmitting the test signal from the NR system simulator **20** via the test antenna **5**, and a control of transmitting a signal reception command and receiving the signal under measurement via the test antenna **5**.

[0050] The DUT scanning control unit **16** drives and controls the drive motors **56f** and **56g** of the DUT scanning mechanism **56** to perform total spherical scanning of the DUT **100** mounted on the mounting tray **56d** of the DUT mounting portion **56c**.

[0051] Here, the total spherical scanning of the DUT **100** will be described with reference to FIGS. **5A** and **5B** to FIG. **7**. Generally, related to power measurement of a signal radiated by the DUT **100** (radiated power measurement), a method for measuring an Equivalent Isotropic Radiated Power (EIRP) and a method for measuring Total Radiated Power (TRP) are known. The EIRP is, for example, a power value measured at each measurement point (θ , ϕ) in a spherical coordinate system (r , θ , ϕ) shown in FIG. **5A**. On the other hand, the TRP is obtained by measuring the EIRP in all orientations of the spherical coordinate system (r , θ , ϕ), that is, at a plurality of angular sample points PS (refer to FIG. **5B**), which are regulated in advance, on a spherical surface equidistant from a center O1 (hereinafter, a reference point) of the total spherical scanning of the DUT **100**, and obtaining a total sum thereof.

[0052] In addition, regarding the reception sensitivity measurement, it is known to measure Equivalent Isotropic Sensitivity (EIS). The EIS is, for example, a reception sensitivity value measured at each measurement point (θ , ϕ) in a spherical coordinate system (r , θ , ϕ) shown in FIG. **5A**.

[0053] The total spherical scanning of the DUT **100** means a control operation of sequentially changing the DUT **100** mounted on the mounting tray **56d** in all orientations of a surface of a sphere B while using, for example, a center O1 of the sphere B (refer to FIGS. **5A** and **5B**) as a reference (center), that is, sequentially changing a posture of the DUT **100** in a state in which the antenna **110** faces the angular sample point PS.

[0054] In order to measure the EIRP or EIS at each angular sample point PS in accordance with the total spherical scanning of the DUT **100**, as shown in FIG. **6**, the test antenna **5** for receiving a signal radiated by the DUT **100** is disposed at a position of a specific angular sample point PS (one point) in the spherical coordinate system (r , θ , ϕ), as shown in FIG. **6**.

[0055] In the total spherical scanning, the DUT **100** is driven (scanned) so that the antenna surface

of the antenna **110** sequentially faces the light reception surface of the test antenna **5**. As a result, the test antenna **5** can transmit and receive a signal for the TRP measurement to and from the antenna **110** of the DUT **100** on which the total spherical scanning is performed. Here, the transmitted and received signal is a test signal that is transmitted from the NR system simulator **20** via the test antenna **5**, and a signal that is transmitted by the DUT **100**, which has received the test signal, using the antenna **110**, that is, a signal under measurement that is received via the test antenna **5**.

[0056] The total spherical scanning of the DUT **100** is realized by rotationally driving the azimuth axis and the roll axis by the drive motors **56f** and **56g** which constitutes the DUT scanning mechanism **56**. FIG. 7 shows a rotation drive image around the azimuth axis and the roll axis of the DUT scanning mechanism (biaxial positioner) **56** related to the total spherical scanning of the DUT **100** in the measurement device **1**. As shown in FIG. 7, the DUT scanning mechanism **56** of the measurement device **1** according to the present embodiment moves the DUT **100** in an angular direction of φ around the azimuth axis, for example, within a range of 180 degrees and moves the DUT **100** in an angular direction of θ around the roll axis, for example, within a range of 360 degrees, so that it is possible to perform the total spherical scanning (refer to FIGS. 5A and 5B and 6) in which the DUT **100** is rotated in all orientations based on the center **O1** thereof.

[0057] In FIG. 7, $\varphi_{\text{sub.0}}$ indicates a unit movement angle in a total movement angle (180 degrees) in the rotation direction (angular direction of φ) of the azimuth axis, and $\theta_{\text{sub.0}}$ indicates the unit movement angle (hereinafter, step angle) in the total movement angle (360 degrees) in the rotation direction (angular direction of θ) of the roll axis. $\varphi_{\text{sub.0}}$ and $\theta_{\text{sub.0}}$ are obtained by enabling, for example, the step angle having a desired value to be selectively set from a plurality of step angles having different values which are regulated in advance. The set $\varphi_{\text{sub.0}}$ and $\theta_{\text{sub.0}}$ regulate an angle between the adjacent angular sample points PS shown in FIG. 5B, and, as a result, regulates the angular sample point PS, that is, the number of measurement positions.

[0058] In order to realize control of the total spherical scanning of the DUT **100** by the DUT scanning control unit **16**, for example, a DUT scanning control table **16a** is prepared in the ROM **11b** in advance. The DUT scanning control table **16a** stores, for example, coordinates of each angular sample point PS (refer to FIG. 5B) in the spherical coordinate system (refer to FIG. 5A) related to the total spherical scanning of the DUT **100**, drive data of the drive motors **56f** and **56g** associated with the coordinates of each angular sample point PS, and control data associated with a stop time (measurement time) at each angular sample point PS. In a case where the drive motors **56f** and **56g** are, for example, stepping motors, for example, the number of drive pulses is stored as the drive data.

[0059] The ROM **11b** is further prepared with a rotation speed management table **16b** for managing rotation speeds of the drive motor **56f** and the drive motor **56g** of the DUT scanning mechanism **56**. The rotation speed management table **16b** manages the rotation speed of the drive motor **56g** that rotationally drives the roll axis, and, more specifically, the rotation speed of the drive motor **56g** in a case where the DUT scanning mechanism **56** is rotationally driven for each step angle.

[0060] Here, in a case where description is performed with reference to FIGS. 5A and 5B, the step angle indicates an angle between adjacent angular sample points PS (refer to FIG. 5B) in the spherical coordinate system (refer to FIG. 5A) related to the total spherical scanning. The angular sample point PS corresponds to the measurement position of the DUT **100**, and the number thereof can be appropriately set to be variable according to a measurement item, a measurement condition, and the like. That is, the unit step angle is obtained by regulating an angle between adjacent measurement positions and may be variable according to the measurement item, the measurement condition, and the like. For the DUT scanning mechanism **56** according to the present embodiment, it is possible to selectively set, for example, a value of 1 degree (deg), 3 degrees, 5 degrees, 7.5 degrees, 10 degrees, 15 degrees, 30 degrees, and 90 degrees for the step angle θ (refer to FIG. 7) of the roll axis by the drive motor **56g**.

[0061] The present embodiment is not limited thereto, instead of the rotation speed management table **16b** (first rotation speed management table), a second rotation speed management table may be provided which manages a rotation speed of the drive motor **56f**, which can minimize the movement time of the DUT scanning mechanism **56** in each step section to correspond to each step angle (corresponding to ϕ in FIG. 7) of the azimuth axis, for example, 5 degrees, 10 degrees, 15 degrees, or 30 degrees.

[0062] Further, instead of the first rotation speed management table and the second rotation speed management table, a third rotation speed management table may be provided which manages the rotation speed of the drive motor **56g** and the drive motor **56f**, which can minimize the movement time of the DUT scanning mechanism **56** in each step section to correspond to each step angle θ of the roll axis and each step angle ϕ of the azimuth axis.

[0063] The DUT scanning control unit **16** expands the DUT scanning control table **16a** into the work area of the RAM **11c**, and drives and controls the drive motors **56f** and **56g** of the DUT scanning mechanism **56** based on the control data stored in the DUT scanning control table **16a**. As a result, the total spherical scanning of the DUT **100** mounted on the DUT mounting portion **56c** is performed. In the total spherical scanning, the antenna surface of the antenna **110** of the DUT **100** is stopped for a regulated time (the stop time) toward the angular sample point PS for each angular sample point PS in the spherical coordinate system, and, thereafter, an operation of moving to a next angular sample point PS (scanning of the DUT **100**) is sequentially performed while targeting all the angular sample points PS.

[0064] Further, the DUT scanning control unit **16** performs rotation speed control on the drive motor **56g** related to the movement of the DUT scanning mechanism **56** targeting each step angle θ of the roll axis using the rotation speed management table **16b** under the control of the rotation speed management control unit **18b**, which will be described later, in accordance with the total spherical scanning of the DUT scanning mechanism **56** using the DUT scanning control table **16a**.

[0065] The signal analysis control unit **17** captures a radio signal, which is related to the NR and is received by the test antenna **5** in a case where the total spherical scanning of the DUT **100** is performed, via the NR system simulator **20**, and performs an analysis process (measurement process) on the radio signal as a signal of a specific measurement item.

[0066] The setting control unit **18a** is a functional unit for setting various information necessary to execute the rotation speed control of the drive motor **56f** using the rotation speed management table **16b** by the DUT scanning control unit **16**. In a case where the specific measurement item is measured, the setting control unit **18a** can selectively set a step angle of a desired value from among step angles (θ , ϕ) having a plurality of different values, for example, 5 degrees, 10 degrees, 15 degrees, and 30 degrees.

[0067] For example, the rotation speed management control unit **18b** performs the rotation speed control of the drive motor **56f** related to the movement of the DUT scanning mechanism **56** targeting each step angle θ of the roll axis in cooperation with the DUT scanning control unit **16** using the rotation speed management table **16b** in accordance with the total spherical scanning of the DUT scanning mechanism **56** in a case where the TRP measurement is performed.

[0068] As shown in FIG. 4, the NR system simulator **20** includes a signal generation unit **21a**, a signal measurement unit **21b**, a transmission and reception unit **21c**, a control unit **21d**, an operation unit **21e**, and a display unit **21f**. The NR system simulator **20** constitutes a simulated measurement device of the present invention.

[0069] The signal generation unit **21a** generates a signal (baseband signal) that becomes a source of the test signal. The transmission and reception unit **21c** functions as an RF unit that generates the test signal corresponding to a frequency of each communication standard from the signal generated by the signal generation unit **21a** and sends the generated test signal to the signal processing unit **23**, and restores the baseband signal from the signal under measurement which is sent from the signal processing unit **23**. The signal measurement unit **21b** performs a measurement process of the

signal under measurement based on the baseband signal restored by the transmission and reception unit **21c**.

[0070] The control unit **21d** comprehensively controls each of the functional units including the signal generation unit **21a**, the signal measurement unit **21b**, the transmission and reception unit **21c**, the operation unit **21e**, and the display unit **21f**. The operation unit **21e** is a functional unit for inputting various information such as commands, and the display unit **21f** is a functional unit for displaying various information such as an input screen and measurement results of the various information.

[0071] In the measurement device **1** having the above-described configuration, the DUT **100** is mounted on the mounting tray **56d** of the DUT scanning mechanism (biaxial positioner) **56** in the internal space **51** of the OTA chamber **50**. Therefore, it is possible to perform measurement of the specific measurement item, such as measurement of the EIRP at each measurement position and measurement of the TRP over all measurement positions, while moving (rotating) the DUT **100** by a preset step angle in the biaxial (azimuth axis and roll axis) direction for each mounting tray **56d**.

[0072] In such a measurement device **1**, in a case where the measurement is performed at each angular sample point PS, it was found that the behavior of the DUT **100**, such as the antenna control, changes, resulting in different measurement results depending on the operation path of the DUT scanning mechanism **56** to the measurement position.

[0073] As shown in FIG. **8**, in a case where the measurement of the measurement position indicated by the white point among the angular sample points PS defined by the rotation angle θ of the roll axis and the rotation angle ϕ of the azimuth axis indicated by the black points is performed, for example, the value of the EIRP measured in a case where the DUT scanning mechanism **56** is operated along a path indicated by the arrow A in FIG. **8** is different from the value of the EIRP measured in a case where the DUT scanning mechanism **56** is operated along a path indicated by the arrow B in FIG. **8**.

[0074] The values in the left column of “EIRP result (dBm)” of the table on the right side of FIG. **8** are values in a case where the DUT scanning mechanism **56** is operated along a path indicated by the arrow A in FIG. **8**, and the values in the right column are values in a case where the DUT scanning mechanism **56** is operated along a path indicated by the arrow B in FIG. **8**, and show the results of the five measurements.

[0075] Since the difference in the measurement results at the same measurement position is suppressed to improve the measurement reproducibility, the DUT scanning control unit **16** of the present embodiment stores the operation path of the DUT scanning mechanism **56** to the measurement position, and when performing the next measurement, reproduces the path to reach the measurement position.

[0076] Therefore, the DUT scanning control unit **16** includes a positioner operation recording unit **16c** and a positioner operation control unit **16d**.

[0077] The positioner operation recording unit **16c** stores the operation path of the DUT scanning mechanism **56** to the measurement position by tracing back from the measurement position to a preset number of angular sample points PS. In addition, the positioner operation recording unit **16c** stores different operation paths up to a preset number in a case where the operation path of the DUT scanning mechanism **56** to the measurement position is an operation path different from the stored operation path. The positioner operation recording unit **16c** stores the operation path of the DUT scanning mechanism **56** by, for example, storing the angle changes made by the DUT scanning mechanism **56**. The positioner operation recording unit **16c** may store measurement information such as the measurement results in association with the operation path.

[0078] When reproduction of an operation path is selected by the operation input of the user to the operation unit **12** and an operation path to be reproduced is selected from the operation paths stored in the positioner operation recording unit **16c**, the positioner operation control unit **16d** controls the DUT scanning mechanism **56** to adjust the DUT **100** to the angle of the measurement position by

the selected operation path.

[0079] For example, in a case where the measurement is advanced along a path of the angular sample points PS indicated by solid line arrows as shown on the left side of FIG. 9, the positioner operation recording unit **16c** stores the operation path. Then, in a case where the reproduction of the operation path is selected when performing measurement at the measurement position indicated by the white point shown on the right side of FIG. 9, the positioner operation control unit **16d** controls the DUT scanning mechanism **56** to change the angle of the DUT **100** to the measurement position along a path indicated by dotted line arrows.

[0080] As described above, the above-described embodiment includes a positioner operation recording unit **16c** that stores an operation path of the DUT scanning mechanism **56** to the measurement position by tracing back from the measurement position to a preset number of the angular sample points PS, and a positioner operation control unit **16d** that controls the DUT scanning mechanism **56** according to the operation path stored in the positioner operation recording unit **16c** to adjust the DUT **100** to an angle of the measurement position when performing measurement at the measurement position.

[0081] As a result, the operation path of the DUT scanning mechanism **56** to the measurement position is stored by tracing back from the measurement position to a preset number of angular sample points PS, and the DUT **100** is adjusted to the angle of the measurement position according to the stored path when performing measurement at the measurement position. Therefore, measurement reproducibility at the same measurement position can be improved.

[0082] In addition, the positioner operation recording unit **16c** stores different operation paths up to a preset number in a case where the operation path of the DUT scanning mechanism **56** to the measurement position is an operation path different from the stored operation path.

[0083] Accordingly, in a case where the operation path to the measurement position is an operation path different from the stored operation path, different operation paths are stored up to a preset number. Therefore, measurement reproducibility at the same measurement position can be improved.

[0084] Hitherto, the embodiments of the present invention have been disclosed, but it is clear that changes can be made by those skilled in the art without departing from the scope of the present invention. All such modifications and equivalents are intended to be included in the claims as follows.

DESCRIPTION OF REFERENCE NUMERALS AND SIGNS

[0085] **1**: Measurement device (mobile terminal testing device) [0086] **5**: Test antenna [0087] **10**: Integrated control device [0088] **16**: DUT scanning control unit [0089] **16c**: Positioner operation recording unit [0090] **16d**: Positioner operation control unit [0091] **20**: NR system simulator (simulated measurement device) [0092] **50**: OTA chamber (anechoic box) [0093] **51**: Internal space [0094] **56**: DUT scanning mechanism (positioner) [0095] **56f**, **56g**: Drive motor [0096] **100**: DUT (mobile terminal)

Claims

1. A mobile terminal testing device comprising: a positioner that is provided in an internal space of an anechoic box, has an azimuth axis and a roll axis that are each rotationally drivable by a drive motor, and rotates a mobile terminal that is a device under test so that the mobile terminal sequentially faces a plurality of preset angular sample points of a spherical coordinate system, using a center of the spherical coordinate system as a reference point; a simulated measurement device connected to a test antenna in the internal space; an integrated control device that controls the simulated measurement device so that a measurement operation of transmitting a test signal from the test antenna to the mobile terminal, receiving a signal under measurement transmitted from the mobile terminal that has received the test signal by using the test antenna, and measuring a

specific measurement item related to the mobile terminal based on the received signal under measurement is performed at a measurement position corresponding to each of the plurality of angular sample points; and a positioner operation recording unit that stores an operation path of the positioner to the measurement position by tracing back from the measurement position to a preset number of the angular sample points; and a positioner operation control unit that controls the positioner according to the operation path stored in the positioner operation recording unit to adjust the mobile terminal to an angle of the measurement position when performing measurement at the measurement position.

2. The mobile terminal testing device according to claim 1, wherein the positioner operation recording unit stores different operation paths up to a preset number in a case where the operation path of the positioner to the measurement position is an operation path different from the stored operation path.

3. A mobile terminal testing method of a mobile terminal testing device including a positioner that is provided in an internal space of an anechoic box, has an azimuth axis and a roll axis that are each rotationally drivable by a drive motor, and rotates a mobile terminal that is a device under test so that the mobile terminal sequentially faces a plurality of preset angular sample points of a spherical coordinate system, using a center of the spherical coordinate system as a reference point, a simulated measurement device connected to a test antenna in the internal space, and an integrated control device that controls the simulated measurement device so that a measurement operation of transmitting a test signal from the test antenna to the mobile terminal, receiving a signal under measurement transmitted from the mobile terminal that has received the test signal by using the test antenna, and measuring a specific measurement item related to the mobile terminal based on the received signal under measurement is performed at a measurement position corresponding to each of the plurality of angular sample points, the mobile terminal testing method comprising: a step of storing an operation path of the positioner to the measurement position by tracing back from the measurement position to a preset number of the angular sample points; and a step of controlling the positioner according to the stored operation path to adjust the mobile terminal to an angle of the measurement position when performing measurement at the measurement position.

4. The mobile terminal testing method according to claim 3, wherein the step of storing the operation path of the positioner is a step of storing different operation paths up to a preset number in a case where the operation path of the positioner to the measurement position is an operation path different from the stored operation path.
