

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12385943
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Kahn; Philippe Richard et al.

Program setting adjustments based on activity identification

Abstract

An electronic device monitors accelerations using a motion sensor. The electronic device determines a current motion state based on the accelerations. The electronic device identifies a plurality of applications that subscribe to a motion state identification service and notifies a subset of the applications of the current motion state, the subset meeting notification criteria associated with the current motion state.

Inventors: Kahn; Philippe Richard (Santa Cruz, CA), Kinsolving; Arthur (Santa Cruz, CA), Christensen; Mark Andrew (Santa Cruz, CA), Lee; Brian Y. (Santa Cruz, CA), Vogel; David (Santa Cruz, CA)

Applicant: Huawei Technologies Co., Ltd. (Shenzhen, CN)

Family ID: 41432105

Assignee: Huawei Technologies Co., Ltd. (Shenzhen, CN)

Appl. No.: 17/006387

Filed: August 28, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20200393488 A1	Dec. 17, 2020

Related U.S. Application Data

continuation parent-doc US 15791398 20171023 US 12196775 child-doc US 17006387
continuation parent-doc US 14673761 20150330 US 9797920 20171024 child-doc US 15791398
continuation parent-doc US 12490304 20090623 US 8996332 20150331 child-doc US 14673761
us-provisional-application US 61075330 20080624

Publication Classification

Int. Cl.: **G01P15/00** (20060101); **A61B5/11** (20060101); **A63B24/00** (20060101); **G01C22/00** (20060101); **G06F3/0346** (20130101)

U.S. Cl.:

CPC **G01P15/00** (20130101); **A61B5/1123** (20130101); **A63B24/0062** (20130101); **G01C22/00** (20130101); **G06F3/0346** (20130101); A61B2560/0209 (20130101); A61B2562/0219 (20130101); A63B2024/0071 (20130101); A63B2220/17 (20130101); A63B2220/44 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3939640	12/1975	Kahn	N/A	N/A
4238146	12/1979	Kitamura et al.	N/A	N/A
4285041	12/1980	Smith	N/A	N/A
4571680	12/1985	Wu	N/A	N/A
4578769	12/1985	Frederick	N/A	N/A
4700369	12/1986	Siegal et al.	N/A	N/A
4776323	12/1987	Spector	N/A	N/A
5192964	12/1992	Shinohara et al.	N/A	N/A
5198735	12/1992	Taylor	318/565	G05B 19/33
5313060	12/1993	Gast et al.	N/A	N/A
5323060	12/1993	Gast et al.	N/A	N/A
5323309	12/1993	Taylor et al.	N/A	N/A
5386210	12/1994	Lee	N/A	N/A
5387170	12/1994	Rawls et al.	N/A	N/A
5430480	12/1994	Allen et al.	N/A	N/A
5446725	12/1994	Ishiwatari	N/A	N/A
5446775	12/1994	Wright et al.	N/A	N/A
5454114	12/1994	Yach et al.	N/A	N/A
5485402	12/1995	Smith et al.	N/A	N/A
5506987	12/1995	Abramson et al.	N/A	N/A
5515419	12/1995	Sheffer et al.	N/A	N/A
5583776	12/1995	Levi et al.	N/A	N/A
5593431	12/1996	Sheldon	N/A	N/A
5654619	12/1996	Iwashita	N/A	N/A
5703786	12/1996	Conkright	N/A	N/A
5708863	12/1997	Satoh et al.	N/A	N/A
5717611	12/1997	Terui et al.	N/A	N/A
5737439	12/1997	Lapsley et al.	N/A	N/A
5771001	12/1997	Cobb	N/A	N/A

5778882	12/1997	Raymond et al.	N/A	N/A
5790490	12/1997	Satoh et al.	N/A	N/A
5890997	12/1998	Roth	N/A	N/A
5911065	12/1998	Williams et al.	N/A	N/A
5955667	12/1998	Fyfe	N/A	N/A
5955871	12/1998	Nguyen	N/A	N/A
5960085	12/1998	De La Huerga	N/A	N/A
5976083	12/1998	Richardson et al.	N/A	N/A
6013007	12/1999	Root et al.	N/A	N/A
6059576	12/1999	Brann	N/A	N/A
6061456	12/1999	Andrea et al.	N/A	N/A
6067608	12/1999	Perry	711/111	G06F 12/127
6122595	12/1999	Varley et al.	N/A	N/A
6129686	12/1999	Friedman	N/A	N/A
6135951	12/1999	Richardson et al.	N/A	N/A
6145389	12/1999	Ebeling et al.	N/A	N/A
6246321	12/2000	Rechsteiner et al.	N/A	N/A
6282496	12/2000	Chowdhary	N/A	N/A
6336891	12/2001	Fedrigon et al.	N/A	N/A
6353449	12/2001	Gregg et al.	N/A	N/A
6369794	12/2001	Sukarai et al.	N/A	N/A
6374054	12/2001	Schinner	N/A	N/A
6375572	12/2001	Masuyama et al.	N/A	N/A
6396883	12/2001	Yang et al.	N/A	N/A
6408330	12/2001	De La Huerga	N/A	N/A
6428490	12/2001	Kramer et al.	N/A	N/A
6470147	12/2001	Imada	N/A	N/A
6478736	12/2001	Mault	N/A	N/A
6493652	12/2001	Ohlenbusch et al.	N/A	N/A
6496695	12/2001	Kouji et al.	N/A	N/A
6513381	12/2002	Fyfe et al.	N/A	N/A
6522266	12/2002	Soehren et al.	N/A	N/A
6529144	12/2002	Nilsen et al.	N/A	N/A
6532419	12/2002	Begin et al.	N/A	N/A
6539336	12/2002	Vock et al.	N/A	N/A
6595929	12/2002	Stivoric et al.	N/A	N/A
6601016	12/2002	Brown et al.	N/A	N/A
6607493	12/2002	Song	N/A	N/A
6609004	12/2002	Morse et al.	N/A	N/A
6611789	12/2002	Darley	N/A	N/A
6628898	12/2002	Endo	N/A	N/A
6634992	12/2002	Ogawa	N/A	N/A
6665802	12/2002	Ober	N/A	N/A
6672991	12/2003	O'Malley	N/A	N/A
6685480	12/2003	Nishimoto et al.	N/A	N/A
6700499	12/2003	Kubo et al.	N/A	N/A
6703939	12/2003	Lehrman et al.	N/A	N/A
6731958	12/2003	Shirai	N/A	N/A
6766176	12/2003	Gupta et al.	N/A	N/A
6771250	12/2003	Oh	N/A	N/A

6786877	12/2003	Foxlin	N/A	N/A
6788980	12/2003	Johnson	N/A	N/A
6790178	12/2003	Mault et al.	N/A	N/A
6807564	12/2003	Zellner et al.	N/A	N/A
6813582	12/2003	Levi et al.	N/A	N/A
6823036	12/2003	Chen	N/A	N/A
6826477	12/2003	Ladetto et al.	N/A	N/A
6836744	12/2003	Asphahani et al.	N/A	N/A
6881191	12/2004	Oakley et al.	N/A	N/A
6885971	12/2004	Vock et al.	N/A	N/A
6895425	12/2004	Kadyk et al.	N/A	N/A
6898550	12/2004	Blackadar et al.	N/A	N/A
6928382	12/2004	Hong et al.	N/A	N/A
6941239	12/2004	Unuma et al.	N/A	N/A
6959259	12/2004	Vock et al.	N/A	N/A
6975959	12/2004	Dietrich et al.	N/A	N/A
6997852	12/2005	Watterson et al.	N/A	N/A
7002553	12/2005	Shkolnikov	N/A	N/A
7010332	12/2005	Irvin et al.	N/A	N/A
7020487	12/2005	Kimata	N/A	N/A
7027087	12/2005	Nozaki et al.	N/A	N/A
7028547	12/2005	Shiratori et al.	N/A	N/A
7042509	12/2005	Onuki	N/A	N/A
7054784	12/2005	Flentov et al.	N/A	N/A
7057551	12/2005	Vogt	N/A	N/A
7072789	12/2005	Vock et al.	N/A	N/A
7092846	12/2005	Vock et al.	N/A	N/A
7096619	12/2005	Jackson et al.	N/A	N/A
7141026	12/2005	Aminian et al.	N/A	N/A
7148797	12/2005	Albert	N/A	N/A
7148879	12/2005	Amento et al.	N/A	N/A
7149964	12/2005	Cottrille et al.	N/A	N/A
7155507	12/2005	Hirano et al.	N/A	N/A
7158912	12/2006	Vock et al.	N/A	N/A
7169084	12/2006	Tsuji	N/A	N/A
7171222	12/2006	Fostick	N/A	N/A
7171331	12/2006	Vock et al.	N/A	N/A
7173604	12/2006	Marvit et al.	N/A	N/A
7176886	12/2006	Marvit et al.	N/A	N/A
7176887	12/2006	Marvit et al.	N/A	N/A
7176888	12/2006	Marvit et al.	N/A	N/A
7177684	12/2006	Kroll et al.	N/A	N/A
7180500	12/2006	Marvit et al.	N/A	N/A
7180501	12/2006	Marvit et al.	N/A	N/A
7180502	12/2006	Marvit et al.	N/A	N/A
7200517	12/2006	Darley et al.	N/A	N/A
7212230	12/2006	Stavely	N/A	N/A
7212943	12/2006	Aoshima et al.	N/A	N/A
7216053	12/2006	Rakkola et al.	N/A	N/A
7220220	12/2006	Stubbs et al.	N/A	N/A

7233872	12/2006	Shibasaki et al.	N/A	N/A
7245725	12/2006	Beard	N/A	N/A
7254516	12/2006	Case et al.	N/A	N/A
7280096	12/2006	Marvit et al.	N/A	N/A
7280849	12/2006	Bailey	N/A	N/A
7280916	12/2006	Bang et al.	N/A	N/A
7297088	12/2006	Tsuji	N/A	N/A
7301526	12/2006	Marvit et al.	N/A	N/A
7301527	12/2006	Marvit et al.	N/A	N/A
7301528	12/2006	Marvit et al.	N/A	N/A
7301529	12/2006	Marvit et al.	N/A	N/A
7305323	12/2006	Skvortsov et al.	N/A	N/A
7308587	12/2006	Inui et al.	N/A	N/A
7328131	12/2007	Donofrio et al.	N/A	N/A
7328611	12/2007	Klees et al.	N/A	N/A
7334472	12/2007	Seo et al.	N/A	N/A
7353112	12/2007	Choi et al.	N/A	N/A
7365735	12/2007	Reinhardt et al.	N/A	N/A
7365736	12/2007	Marvit et al.	N/A	N/A
7365737	12/2007	Marvit et al.	N/A	N/A
7379999	12/2007	Zhou et al.	N/A	N/A
7382611	12/2007	Tracy et al.	N/A	N/A
7387611	12/2007	Inoue et al.	N/A	N/A
7397357	12/2007	Krumm et al.	N/A	N/A
7424385	12/2007	Cho et al.	N/A	N/A
7451056	12/2007	Flentov et al.	N/A	N/A
7457719	12/2007	Kahn et al.	N/A	N/A
7457872	12/2007	Aton et al.	N/A	N/A
7463997	12/2007	Pasolini et al.	N/A	N/A
7467060	12/2007	Kulach et al.	N/A	N/A
7474771	12/2008	Bang et al.	N/A	N/A
7489937	12/2008	Chung et al.	N/A	N/A
7502643	12/2008	Farringdon et al.	N/A	N/A
7512515	12/2008	Vock et al.	N/A	N/A
7526402	12/2008	Tanenhaus et al.	N/A	N/A
7602301	12/2008	Stirling et al.	N/A	N/A
7602761	12/2008	Lin et al.	N/A	N/A
7608050	12/2008	Shugg	N/A	N/A
7640804	12/2009	Daumer et al.	N/A	N/A
7647196	12/2009	Kahn et al.	N/A	N/A
7653508	12/2009	Kahn et al.	N/A	N/A
7664657	12/2009	Letzt et al.	N/A	N/A
7689107	12/2009	Enomoto	N/A	N/A
7705884	12/2009	Pinto et al.	N/A	N/A
7735025	12/2009	Lee et al.	N/A	N/A
7736272	12/2009	Martens	N/A	N/A
7752011	12/2009	Niva et al.	N/A	N/A
7753861	12/2009	Kahn et al.	N/A	N/A
7765553	12/2009	Douceur et al.	N/A	N/A
7774156	12/2009	Niva et al.	N/A	N/A

7788059	12/2009	Kahn et al.	N/A	N/A
7805759	12/2009	Tang et al.	N/A	N/A
7840346	12/2009	Huhtala et al.	N/A	N/A
7857772	12/2009	Bouvier et al.	N/A	N/A
7868489	12/2010	Amemiya et al.	N/A	N/A
7872638	12/2010	Sato	N/A	N/A
7881902	12/2010	Kahn et al.	N/A	N/A
7892080	12/2010	Dahl	N/A	N/A
7907901	12/2010	Kahn et al.	N/A	N/A
7938725	12/2010	Okamura	N/A	N/A
7987070	12/2010	Kahn et al.	N/A	N/A
8055469	12/2010	Kulach et al.	N/A	N/A
8187182	12/2011	Kahn et al.	N/A	N/A
8264456	12/2011	Ito et al.	N/A	N/A
8275635	12/2011	Stivoric et al.	N/A	N/A
8398546	12/2012	Pacione et al.	N/A	N/A
8458715	12/2012	Khosla et al.	N/A	N/A
8555282	12/2012	Kahn et al.	N/A	N/A
8562489	12/2012	Burton et al.	N/A	N/A
8790279	12/2013	Brunner	N/A	N/A
9183044	12/2014	Kahn et al.	N/A	N/A
2001/0047488	12/2000	Verplaetse et al.	N/A	N/A
2002/0006284	12/2001	Kim	N/A	N/A
2002/0022551	12/2001	Watterson et al.	N/A	N/A
2002/0027164	12/2001	Mault et al.	N/A	N/A
2002/0042830	12/2001	Bose et al.	N/A	N/A
2002/0044634	12/2001	Rooke et al.	N/A	N/A
2002/0054214	12/2001	Yoshikawa	N/A	N/A
2002/0089425	12/2001	Kubo et al.	N/A	N/A
2002/0109600	12/2001	Mault et al.	N/A	N/A
2002/0118121	12/2001	Lehrman et al.	N/A	N/A
2002/0122543	12/2001	Rowen	N/A	N/A
2002/0138017	12/2001	Bui et al.	N/A	N/A
2002/0142887	12/2001	O'Malley	N/A	N/A
2002/0150302	12/2001	McCarthy et al.	N/A	N/A
2002/0151810	12/2001	Wong	N/A	N/A
2002/0173295	12/2001	Nykanen	N/A	N/A
2002/0190947	12/2001	Feinstein	N/A	N/A
2002/0193124	12/2001	Hamilton et al.	N/A	N/A
2002/0193702	12/2001	Yamazaki et al.	N/A	N/A
2003/0018430	12/2002	Ladetto et al.	N/A	N/A
2003/0033411	12/2002	Kavoori et al.	N/A	N/A
2003/0048218	12/2002	Milnes et al.	N/A	N/A
2003/0083596	12/2002	Kramer et al.	N/A	N/A
2003/0093187	12/2002	Walker et al.	N/A	N/A
2003/0101260	12/2002	Dacier et al.	N/A	N/A
2003/0109258	12/2002	Mantyljarvi et al.	N/A	N/A
2003/0139692	12/2002	Barrey et al.	N/A	N/A
2003/0139908	12/2002	Wegerich et al.	N/A	N/A
2003/0149526	12/2002	Zhou et al.	N/A	N/A

2003/0151672	12/2002	Robins et al.	N/A	N/A
2003/0187683	12/2002	Kirchhoff et al.	N/A	N/A
2003/0208110	12/2002	Mault et al.	N/A	N/A
2003/0208113	12/2002	Mault et al.	N/A	N/A
2003/0227487	12/2002	Hugh	N/A	N/A
2003/0236625	12/2002	Brown et al.	N/A	N/A
2004/0017300	12/2003	Kotzin et al.	N/A	N/A
2004/0024846	12/2003	Randall et al.	N/A	N/A
2004/0043760	12/2003	Rosenfeld et al.	N/A	N/A
2004/0044493	12/2003	Coulthard	N/A	N/A
2004/0047498	12/2003	Mulet-Parada et al.	N/A	N/A
2004/0078219	12/2003	Kaylor et al.	N/A	N/A
2004/0078220	12/2003	Jackson	N/A	N/A
2004/0081441	12/2003	Sato et al.	N/A	N/A
2004/0106421	12/2003	Tomiyoshi et al.	N/A	N/A
2004/0106958	12/2003	Mathis et al.	N/A	N/A
2004/0122294	12/2003	Hatlestad et al.	N/A	N/A
2004/0122295	12/2003	Hatlestad et al.	N/A	N/A
2004/0122296	12/2003	Hatlestad et al.	N/A	N/A
2004/0122297	12/2003	Stahmann et al.	N/A	N/A
2004/0122333	12/2003	Nisslia	N/A	N/A
2004/0122484	12/2003	Hatlestad et al.	N/A	N/A
2004/0122485	12/2003	Stahmann et al.	N/A	N/A
2004/0122486	12/2003	Stahmann et al.	N/A	N/A
2004/0122487	12/2003	Hatlestad et al.	N/A	N/A
2004/0125073	12/2003	Potter et al.	N/A	N/A
2004/0130628	12/2003	Stavely	N/A	N/A
2004/0135898	12/2003	Zador	N/A	N/A
2004/0146048	12/2003	Cotte	N/A	N/A
2004/0148340	12/2003	Cotte	N/A	N/A
2004/0148341	12/2003	Cotte	N/A	N/A
2004/0148342	12/2003	Cotte	N/A	N/A
2004/0148351	12/2003	Cotte	N/A	N/A
2004/0176067	12/2003	Lakhani et al.	N/A	N/A
2004/0185821	12/2003	Yuasa	N/A	N/A
2004/0210419	12/2003	Kela et al.	N/A	N/A
2004/0219910	12/2003	Beckers	N/A	N/A
2004/0225467	12/2003	Vock et al.	N/A	N/A
2004/0236500	12/2003	Choi et al.	N/A	N/A
2004/0242202	12/2003	Torvinen	N/A	N/A
2004/0247030	12/2003	Wiethoff	N/A	N/A
2004/0259494	12/2003	Mazar	N/A	N/A
2005/0015768	12/2004	Moore	N/A	N/A
2005/0027567	12/2004	Taha	N/A	N/A
2005/0033200	12/2004	Soehren et al.	N/A	N/A
2005/0038691	12/2004	Babu	N/A	N/A
2005/0048945	12/2004	Porter	N/A	N/A
2005/0048955	12/2004	Ring	N/A	N/A
2005/0064913	12/2004	Kim	N/A	N/A
2005/0078197	12/2004	Gonzales	N/A	N/A

2005/0079873	12/2004	Caspi et al.	N/A	N/A
2005/0079877	12/2004	Ichimura	N/A	N/A
2005/0081200	12/2004	Rutten et al.	N/A	N/A
2005/0093705	12/2004	Humbard	N/A	N/A
2005/0101841	12/2004	Kaylor et al.	N/A	N/A
2005/0102167	12/2004	Kapoor	N/A	N/A
2005/0107944	12/2004	Hovestadt et al.	N/A	N/A
2005/0113649	12/2004	Bergantino	N/A	N/A
2005/0113650	12/2004	Pacione et al.	N/A	N/A
2005/0125797	12/2004	Gabrani et al.	N/A	N/A
2005/0131736	12/2004	Nelson et al.	N/A	N/A
2005/0141522	12/2004	Kadar et al.	N/A	N/A
2005/0143106	12/2004	Chan et al.	N/A	N/A
2005/0146431	12/2004	Hastings et al.	N/A	N/A
2005/0157181	12/2004	Kawahara et al.	N/A	N/A
2005/0165719	12/2004	Greenspan et al.	N/A	N/A
2005/0168587	12/2004	Sato et al.	N/A	N/A
2005/0182824	12/2004	Cotte	N/A	N/A
2005/0183086	12/2004	Abe et al.	N/A	N/A
2005/0202934	12/2004	Olrik et al.	N/A	N/A
2005/0203430	12/2004	Williams et al.	N/A	N/A
2005/0210300	12/2004	Song et al.	N/A	N/A
2005/0212751	12/2004	Marvit et al.	N/A	N/A
2005/0212752	12/2004	Marvit et al.	N/A	N/A
2005/0212753	12/2004	Marvit et al.	N/A	N/A
2005/0212760	12/2004	Marvit et al.	N/A	N/A
2005/0216403	12/2004	Tam et al.	N/A	N/A
2005/0222801	12/2004	Wulf et al.	N/A	N/A
2005/0232388	12/2004	Tsuji	N/A	N/A
2005/0232404	12/2004	Gaskill	N/A	N/A
2005/0234676	12/2004	Shibayama	N/A	N/A
2005/0235058	12/2004	Rackus et al.	N/A	N/A
2005/0238132	12/2004	Tsuji	N/A	N/A
2005/0240375	12/2004	Sugai	N/A	N/A
2005/0243178	12/2004	McConica	N/A	N/A
2005/0245988	12/2004	Miesel	N/A	N/A
2005/0248718	12/2004	Howell et al.	N/A	N/A
2005/0256414	12/2004	Kettunen et al.	N/A	N/A
2005/0258938	12/2004	Moulson	N/A	N/A
2005/0262237	12/2004	Fulton et al.	N/A	N/A
2005/0272564	12/2004	Pyles et al.	N/A	N/A
2005/0281289	12/2004	Huang et al.	N/A	N/A
2006/0009243	12/2005	Dahan et al.	N/A	N/A
2006/0017692	12/2005	Wehrenberg et al.	N/A	N/A
2006/0020177	12/2005	Seo	600/300	A61B 5/222
2006/0020421	12/2005	Darley et al.	N/A	N/A
2006/0026212	12/2005	Tsukerman et al.	N/A	N/A
2006/0029284	12/2005	Stewart	N/A	N/A
2006/0040793	12/2005	Martens	N/A	N/A
2006/0060068	12/2005	Hwang et al.	N/A	N/A

2006/0063980	12/2005	Hwang et al.	N/A	N/A
2006/0064276	12/2005	Ren et al.	N/A	N/A
2006/0068919	12/2005	Gottfurcht	N/A	N/A
2006/0073807	12/2005	Baker	N/A	N/A
2006/0080551	12/2005	Mantylarvi et al.	N/A	N/A
2006/0090088	12/2005	Choi et al.	N/A	N/A
2006/0090161	12/2005	Bodas et al.	N/A	N/A
2006/0098097	12/2005	Wach et al.	N/A	N/A
2006/0100546	12/2005	Silk	N/A	N/A
2006/0107822	12/2005	Bowen	N/A	N/A
2006/0109113	12/2005	Reyes et al.	N/A	N/A
2006/0136173	12/2005	Case et al.	N/A	N/A
2006/0140422	12/2005	Zurek et al.	N/A	N/A
2006/0149516	12/2005	Bond et al.	N/A	N/A
2006/0154642	12/2005	Scannell, Jr.	N/A	N/A
2006/0161079	12/2005	Choi et al.	N/A	N/A
2006/0161377	12/2005	Rakkola et al.	N/A	N/A
2006/0161459	12/2005	Rosenfeld et al.	N/A	N/A
2006/0164393	12/2005	Wu	345/163	G06F 3/0346
2006/0167387	12/2005	Bucholz et al.	N/A	N/A
2006/0167647	12/2005	Krumm et al.	N/A	N/A
2006/0167943	12/2005	Rosenberg et al.	N/A	N/A
2006/0172706	12/2005	Griffin et al.	N/A	N/A
2006/0174685	12/2005	Skvortsov et al.	N/A	N/A
2006/0187847	12/2005	Pelton et al.	N/A	N/A
2006/0201964	12/2005	Diperna et al.	N/A	N/A
2006/0204214	12/2005	Shah et al.	N/A	N/A
2006/0205406	12/2005	Pekonen et al.	N/A	N/A
2006/0206258	12/2005	Brooks	N/A	N/A
2006/0223547	12/2005	Chin et al.	N/A	N/A
2006/0227862	12/2005	Campbell	375/240	G06T 7/254
2006/0249683	12/2005	Goldberg et al.	N/A	N/A
2006/0252999	12/2005	Devaul et al.	N/A	N/A
2006/0256082	12/2005	Cho et al.	N/A	N/A
2006/0257042	12/2005	Ofek et al.	N/A	N/A
2006/0259268	12/2005	Vock et al.	N/A	N/A
2006/0284979	12/2005	Clarkson	N/A	N/A
2006/0288781	12/2005	Daumer et al.	N/A	N/A
2006/0289819	12/2005	Parsons et al.	N/A	N/A
2007/0004451	12/2006	Anderson	N/A	N/A
2007/0005988	12/2006	Zhang et al.	N/A	N/A
2007/0013659	12/2006	Nagata	345/158	G06F 3/0346
2007/0017136	12/2006	Mosher et al.	N/A	N/A
2007/0024441	12/2006	Kahn et al.	N/A	N/A
2007/0027585	12/2006	Wulff	N/A	N/A
2007/0037605	12/2006	Logan et al.	N/A	N/A
2007/0037610	12/2006	Logan	N/A	N/A
2007/0038364	12/2006	Lee et al.	N/A	N/A
2007/0040892	12/2006	Aoki et al.	N/A	N/A
2007/0050157	12/2006	Kahn et al.	N/A	N/A

2007/0060446	12/2006	Asukai et al.	N/A	N/A
2007/0063850	12/2006	Devaul et al.	N/A	N/A
2007/0067094	12/2006	Park et al.	N/A	N/A
2007/0072158	12/2006	Unuma et al.	N/A	N/A
2007/0072581	12/2006	Aerrabotu	N/A	N/A
2007/0073482	12/2006	Churchill et al.	N/A	N/A
2007/0074619	12/2006	Vergo	N/A	N/A
2007/0075127	12/2006	Rosenberg	N/A	N/A
2007/0075965	12/2006	Huppi et al.	N/A	N/A
2007/0078324	12/2006	Wijisiriwardana	N/A	N/A
2007/0079691	12/2006	Turner	84/612	G10H 1/40
2007/0082789	12/2006	Nisslia et al.	N/A	N/A
2007/0102525	12/2006	Orr et al.	N/A	N/A
2007/0104479	12/2006	Machida	N/A	N/A
2007/0106991	12/2006	Yoo	N/A	N/A
2007/0124703	12/2006	Sohn	715/863	G06F 3/0346
2007/0125852	12/2006	Rosenberg et al.	N/A	N/A
2007/0130582	12/2006	Chang et al.	N/A	N/A
2007/0142715	12/2006	Banet et al.	N/A	N/A
2007/0143068	12/2006	Pasolini et al.	N/A	N/A
2007/0145680	12/2006	Rosenberg	N/A	N/A
2007/0150136	12/2006	Doll et al.	N/A	N/A
2007/0154872	12/2006	Sako et al.	N/A	N/A
2007/0156364	12/2006	Rothkopf	N/A	N/A
2007/0161410	12/2006	Huang et al.	N/A	N/A
2007/0164993	12/2006	Kao et al.	N/A	N/A
2007/0165790	12/2006	Taori	N/A	N/A
2007/0169126	12/2006	Todokori et al.	N/A	N/A
2007/0176898	12/2006	Suh	N/A	N/A
2007/0185644	12/2006	Hirose	N/A	N/A
2007/0192483	12/2006	Rezvani et al.	N/A	N/A
2007/0195784	12/2006	Allen et al.	N/A	N/A
2007/0204744	12/2006	Sako et al.	N/A	N/A
2007/0208531	12/2006	Darley et al.	N/A	N/A
2007/0208544	12/2006	Kulach et al.	N/A	N/A
2007/0213085	12/2006	Fedora	N/A	N/A
2007/0213126	12/2006	Deutsch et al.	N/A	N/A
2007/0219708	12/2006	Brasche et al.	N/A	N/A
2007/0221045	12/2006	Terauchi et al.	N/A	N/A
2007/0225935	12/2006	Ronkainen et al.	N/A	N/A
2007/0233788	12/2006	Bender	N/A	N/A
2007/0239399	12/2006	Sheynblat et al.	N/A	N/A
2007/0250261	12/2006	Soehren	N/A	N/A
2007/0254271	12/2006	Burlik et al.	N/A	N/A
2007/0259685	12/2006	Engblom et al.	N/A	N/A
2007/0259716	12/2006	Mattice et al.	N/A	N/A
2007/0259717	12/2006	Mattice et al.	N/A	N/A
2007/0260418	12/2006	Ladetto et al.	N/A	N/A
2007/0260482	12/2006	Nurmela et al.	N/A	N/A
2007/0263995	12/2006	Park et al.	N/A	N/A

2007/0281762	12/2006	Barros et al.	N/A	N/A
2007/0290998	12/2006	Choi et al.	N/A	N/A
2007/0296696	12/2006	Nurmi	N/A	N/A
2008/0005738	12/2007	Imai et al.	N/A	N/A
2008/0030586	12/2007	Helbing et al.	N/A	N/A
2008/0046888	12/2007	Appaji	N/A	N/A
2008/0052716	12/2007	Theurer	N/A	N/A
2008/0068195	12/2007	Ritter et al.	N/A	N/A
2008/0072014	12/2007	Krishnan et al.	N/A	N/A
2008/0082994	12/2007	Ito et al.	N/A	N/A
2008/0086734	12/2007	Jensen et al.	N/A	N/A
2008/0102785	12/2007	Childress et al.	N/A	N/A
2008/0109158	12/2007	Huhtala et al.	N/A	N/A
2008/0113689	12/2007	Bailey	N/A	N/A
2008/0114538	12/2007	Lindroos	N/A	N/A
2008/0117167	12/2007	Aonuma et al.	N/A	N/A
2008/0125959	12/2007	Doherty et al.	N/A	N/A
2008/0140338	12/2007	No et al.	N/A	N/A
2008/0153671	12/2007	Ogg et al.	N/A	N/A
2008/0161072	12/2007	Lide et al.	N/A	N/A
2008/0165022	12/2007	Herz et al.	N/A	N/A
2008/0168361	12/2007	Forstall et al.	N/A	N/A
2008/0171918	12/2007	Teller et al.	N/A	N/A
2008/0182724	12/2007	Guthrie	482/8	A61B 5/1118
2008/0192005	12/2007	Elgoyhen et al.	N/A	N/A
2008/0214358	12/2007	Ogg et al.	N/A	N/A
2008/0231713	12/2007	Florea et al.	N/A	N/A
2008/0231714	12/2007	Estevez et al.	N/A	N/A
2008/0232604	12/2007	Dufresne et al.	N/A	N/A
2008/0243432	12/2007	Kato et al.	N/A	N/A
2008/0254944	12/2007	Muri et al.	N/A	N/A
2008/0282595	12/2007	Clark et al.	N/A	N/A
2008/0284650	12/2007	MacIntosh et al.	N/A	N/A
2008/0303681	12/2007	Herz et al.	N/A	N/A
2008/0311929	12/2007	Carro et al.	N/A	N/A
2009/0017880	12/2008	Moore et al.	N/A	N/A
2009/0024233	12/2008	Shirai et al.	N/A	N/A
2009/0031319	12/2008	Fecioru	N/A	N/A
2009/0043531	12/2008	Kahn et al.	N/A	N/A
2009/0047645	12/2008	Dibenedetto et al.	N/A	N/A
2009/0067826	12/2008	Shinohara et al.	N/A	N/A
2009/0082994	12/2008	Schuler et al.	N/A	N/A
2009/0088204	12/2008	Culbert et al.	N/A	N/A
2009/0093992	12/2008	Wimmer	N/A	N/A
2009/0098880	12/2008	Lindquist	N/A	N/A
2009/0099668	12/2008	Lehman et al.	N/A	N/A
2009/0124348	12/2008	Yoseloff et al.	N/A	N/A
2009/0124938	12/2008	Brunner	N/A	N/A
2009/0128448	12/2008	Riechel	N/A	N/A
2009/0132197	12/2008	Rubin et al.	N/A	N/A

2009/0174782	12/2008	Kahn et al.	N/A	N/A
2009/0209344	12/2008	Okamura	N/A	N/A
2009/0213002	12/2008	Rani et al.	N/A	N/A
2009/0215502	12/2008	Griffin	N/A	N/A
2009/0234614	12/2008	Kahn et al.	N/A	N/A
2009/0274317	12/2008	Kahn et al.	N/A	N/A
2009/0296951	12/2008	De Haan	N/A	N/A
2009/0319221	12/2008	Kahn et al.	N/A	N/A
2009/0325705	12/2008	Filer et al.	N/A	N/A
2010/0056872	12/2009	Kahn et al.	N/A	N/A
2010/0057398	12/2009	Darley et al.	N/A	N/A
2010/0130890	12/2009	Matsumura et al.	N/A	N/A
2010/0199189	12/2009	Ben-Aroya et al.	N/A	N/A
2010/0245131	12/2009	Graumann	N/A	N/A
2010/0277489	12/2009	Geisner et al.	N/A	N/A
2010/0283742	12/2009	Lam	N/A	N/A
2011/0003665	12/2010	Burton et al.	N/A	N/A
2012/0092157	12/2011	Tran	N/A	N/A
2014/0369522	12/2013	Asukai et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1723848	12/2005	CN	N/A
1758795	12/2005	CN	N/A
1819014	12/2005	CN	N/A
1926496	12/2006	CN	N/A
1989483	12/2006	CN	N/A
101002985	12/2006	CN	N/A
101029985	12/2006	CN	N/A
101075156	12/2006	CN	N/A
100399994	12/2007	CN	N/A
101317188	12/2007	CN	N/A
101506868	12/2008	CN	N/A
833537	12/2001	EP	N/A
1271099	12/2002	EP	N/A
2431813	12/2006	EP	N/A
1926029	12/2007	EP	N/A
1104143	12/2008	EP	N/A
7020547	12/1994	JP	N/A
2000090069	12/1999	JP	N/A
2001079699	12/2000	JP	N/A
2005309691	12/2004	JP	N/A
2006026092	12/2005	JP	N/A
20066118909	12/2005	JP	N/A
2006239398	12/2005	JP	N/A
2007075172	12/2006	JP	N/A
2007080219	12/2006	JP	N/A
2007115200	12/2006	JP	N/A
2007142511	12/2006	JP	N/A
2007206748	12/2006	JP	N/A

2007215134	12/2006	JP	N/A
2007215784	12/2006	JP	N/A
2007226855	12/2006	JP	N/A
2007325722	12/2006	JP	N/A
2008113248	12/2007	JP	N/A
200722143	12/2006	TW	N/A
9922338	12/1998	WO	N/A
0063874	12/1999	WO	N/A
02088926	12/2001	WO	N/A
2006008790	12/2005	WO	N/A
2006082809	12/2005	WO	N/A
2006119344	12/2005	WO	N/A
2007097324	12/2006	WO	N/A
2009049302	12/2008	WO	N/A
2010008900	12/2009	WO	N/A

OTHER PUBLICATIONS

Ricoh, "Advanced digital technology changes creativity," <<http://www.ricoh.com/r.sub.--dc/gx/gx200/features2.html>>, Accessed May 12, 2011, 4 pages. cited by applicant

Shen, Chien-Lung, et al, Wearable Band Using a Fabric-Based Sensor for Exercise ECG Monitoring, IEEE Int. Symp. on Wearable Computers, 2006, 2 pages. cited by applicant

Wapia, Emmanuel Munguia, et al, "Real-Time Recognition of Physical Activities and Their Intensities Using Wireless Accelerometers and a Heart Rate Monitor," IEEE Cont. on Wearable Computers, Oct. 2007, 4 pages. cited by applicant

Wech, Ang Wei, "Real-time Image Stabilizer,"

<<http://www.mae.ntu.edu.sg/ABOUTMAE/DIVISIONS/RRC.sub.-BIOROBOTICS/Pages/rtimage.aspx>>, Mar. 23, 2009, 3 pages. cited by applicant

Wang, Shu, et al, "Location Based Services for Mobiles: Technologies and Standards, LG Electronics MobileComm," IEEE ICC 2008, Beijing, pp. 1-66 (part 1 of 3). cited by applicant

Wang, Shu, et al, "Location Based Services for Mobiles: Technologies and Standards, LG Electronics MobileComm," IEEE ICC 2008, Beijing, pp. 67-92 (part 2 of 3). cited by applicant

Wang, Shu, et al, "Location Based Services for Mobiles: Technologies and Standards, LG Electronics MobileComm," IEEE ICC 2008, Beijing, pp. 93-123 (part 3 of 3). cited by applicant

Weckesser, P, et al, "Multiple Sensorprocessing for High-Precision Navigation and Environmental Modeling with a Mobile Robot," IEEE, 1995, pp. 453-458. cited by applicant

Weinberg, Harvey, "MEMS Motion Sensors Boost Handset Reliability" Jun. 2006,

<http://www.mwrf.com/Articles/Print.cfm?ArticleID=12740>, Feb. 21, 2007, 4 pages. cited by applicant

Weinberg, Harvey, "Minimizing Power Consumption of iMEMS.RTM. Accelerometers," Analog Devices, <<http://www.1malog.com/static/imported-files/application.sub.-notes/5-935151853362884599AN601.pdf>>, 2002, 5 pages. cited by applicant

Wixted, Andrew J., et al., "Measurement of Energy Expenditure in Elite Athletes Using MEMS-Based Triaxial Accelerometers," IEEE Sensors Journal, vol. 7, No. 4, Apr. 2007, pp. 481-488. cited by applicant

Wu, Winston H, et al, "Context-Aware Sensing of Physiological Signals," IEEE Int. Conf. on Engineering for Medicine and Biology, Aug. 23-26, 2007, pp. 5271-5275. cited by applicant

Yoo, Chang-Sun, et al, "Low Cost GPS/INS Sensor Fusion System for UAV Navigation," IEEE, 2003, 9 pages. cited by applicant

Saponas et al., "iLearn on the iPhone: Real-Time Human Activity Classification on Commodity Mobile Phones," pp. 1-4 (2008). cited by applicant

EP 09798529.5, EPO Examination Report, Dated Aug. 19, 2016, 5 pages. cited by applicant

EP 09798529.5, European Search Opinion, Dated Jan. 8, 2014, 2 pages. cited by applicant

EP 09798529.5, Supplementary European Search Report, 2 pages. cited by applicant

Japanese Patent Application No. 2011-516623, Office Action dated Oct. 5, 2014, 2 pages. cited by applicant

Japanese Patent Application No. 2011-516623, Office Action, Mar. 16, 2014, 2 pages. cited by applicant

Japanese Patent Application No. 2011-516623, Search Report by Registered Searching Organization, Oct. 24, 2013. 10 pages. cited by applicant

PCT/US2009/048523, International Preliminary Report on Patentability, Date of Issuance Jan. 5, 2011, 6 pages. cited by applicant

PCT/US2009/048523, International Preliminary Report on Patentability, mailing date Jan. 13, 2011, 7 pages. cited by applicant

PCT/US2009/48523, International Search Report and Written Opinion, mailing date Aug. 27, 2009, 8 pages. cited by applicant

PCT/US2009/48523, International Search Report, Mailed Aug. 7, 2009, 1 page. cited by applicant

Japanese Patent Application No. 2011-516623, Arguments and Claim Amendments—1. cited by applicant

Japanese Patent Application No. 2011-516623, Arguments and Claim Amendments—2. cited by applicant

Japanese Patent Application No. 2011-516623, Arguments and Claim Amendments—3. cited by applicant

EP 09798529.5, Arguments and Claim Amendments. cited by applicant

Access and Terminals (AT); Multimedia Message Service (MMS) for Communication Between a Fixed Network Multimedia Message Terminal PSTN/ISDN; Multimedia Message Equipment and a Multimedia Message Service Centre, ETSI AT-F Rapporteur Meeting, Feb. 4-6, 2003, Gothenburg, DES/AT-030023 V0.0.1 (Mar. 2003). cited by applicant

“Decrease Processor Power Consumption using a CoolRunner CPLD,” Xilinx XAPP347 (v1 .0), May 16, 2001, 9 pages. cited by applicant

Heart Rate Monitor Sports Bra, <www.numetrex.com/about/heart-rate-monitor-sports-bra>, Accessed Aug. 9, 2013, 2 Pages. cited by applicant

“Sensor Fusion,” <www.u-dynamics.com>, accessed Aug. 29, 2008, 2 pages. cited by applicant

“Smart Underwear With Biosensors Availability in the Market Kudos to Modern Inkjet Printer Technology,” Accessed Aug. 9, 2013, 2 pages. cited by applicant

Anderson, Ian, et al, “Shakra: Tracking and Sharing Daily Activity Levels with Unaugmented Mobile Phones,” Mobile Netw. Appl., Aug. 3, 2007, pp. 185-199. cited by applicant

Ang, Wei Tech, et al, “Zero Phase Filtering for Active Compensation of Period Physiological Motion,” Proc 1st IEEE/RAS-EMBS International Conference on Biomedical Robotics and Biomechatronics, Feb. 20-22, 2006, pp. 182-187. cited by applicant

Aylward, Ryan, et al, “Senseable: A Wireless, Compact, Multi-User Sensor System for Interactive Dance,” International Conference on New Interfaces for Musical Expression (NIME06), Jun. 4-8, 2006, pp. 134-139. cited by applicant

Baca, Arnold, et al, “Rapid Feedback Systems for Elite Sports Training,” IEEE Pervasive Computing, Oct.-Dec. 2006, pp. 70-76. cited by applicant

Bakhru, Kesh, “A Seamless Tracking Solution for Indoor and Outdoor Position Location,” IEEE 16th International Symposium on Personal, Indoor, and Mobile Radio Communications, 2005, pp. 2029-2033. cited by applicant

Symposium on Personal, Indoor, and Mobile Radio Communications, 2005, pp. 2029-2033. cited by applicant

Bliley, Kara E, et al, “A Miniaturized Low Power Personal Motion Analysis Logger Utilizing

MEMS Accelerometers and Low Power Microcontroller,” IEEE EMBS Special Topic Conference on Microtechnologies in Medicine and Biology, May 12-15, 2005, pp. 92-93. cited by applicant

Bourzac, Katherine, Wearable Health Reports, Technology Review, Feb. 28, 2006, 3 pages, <http://www.techreview.com/printer.sub.-friendly.sub.--article.sub.-aspx-?id+16431>, accessed Mar. 22, 2007. cited by applicant

Cheng, et al., “Periodic Human Motion Description for Sports Video Databases”, Proceedings of the Pattern Recognition (2004). cited by applicant

Dao, Ricardo, “Inclination Sensing with Thermal Accelerometers”, MEMS IC, May 2002, 3 pages. cited by applicant

EP 09798529.5, Extended European Search Report, Dated Jan. 8, 2014, 5 pages. cited by applicant

EP 09798529.5, Extended European Search Report, Dated Nov. 8, 2014, 5 pages. cited by applicant

Fang, Lei, et al, “Design of a Wireless Assisted Pedestrian Dead Reckoning System—The NavMote Experience,” IEEE Transactions on Instrumentation and Measurement, vol. 54, No. 6, Dec. 2005, pp. 2342-2358. cited by applicant

Healey, Jennifer, et al, “Wearable Wellness Monitoring Using ECG and Accelerometer Data,” IEEE Int. Symposium on Wearable Computers (ISWC'05), 2005, 2 pages. cited by applicant

Hemmes, Jeffrey, et al, “Lessons Learned Building TeamTrak: An Urban/Outdoor Mobile Testbed,” 2007 IEEE Int. Conf. on Wireless Algorithms, Aug. 1-3, 2007, pp. 219-224. cited by applicant

Japanese Patent Application No. 2011-516623, Final Office Action mailed Apr. 15, 2014, 6 pages. cited by applicant

Japanese Patent Application No. 2011-516623, Office Action mailed Oct. 31, 2013, 9 pages. cited by applicant

Jones, L, et al, “Wireless Physiological Sensor System for Ambulatory Use,” <<http://ieeexplore.ieee.org/xpl/freeabs.sub.-all.jsp?tp=&arnumber=1612917&isnumber=33861>>, Apr. 3-5, 2006. cited by applicant

Jovanov, Emil, et al, “A Wireless Body Area Network of Intelligent Motion Sensors for Computer Assisted Physical Rehabilitation,” Journal of NeuroEngineering and Rehabilitation, Mar. 2005, 10 pages. cited by applicant

Kalpaxis, Alex, “Wireless Temporal-Spatial Human Mobility Analysis Using Real-Time Three Dimensional Acceleration Data,” IEEE Intl. Multi-Cont. on Computing in Global IT (ICCGI'07), 2007, 7 pages. cited by applicant

Lee, Hyunseok, et al, A Dual Processor Solution for the MAC Layer of a Software Defined Radio Terminal, Advanced Computer Architecture Laboratory, University of Michigan, 25 pages. cited by applicant

Lee, Sean-Woo, et al., “Recognition of Walking Behaviors for Pedestrian Navigation,” ATR Media Integration & Communications Research Laboratories, Kyoto, Japan, 4 pages. cited by applicant

Margaria, Rodolfo, “Biomechanics and Energetics of Muscular Exercise”, Chapter 3, pp. 105-125, Oxford: Clarendon Press 1976. cited by applicant

Meinhold, Bridgette, “Adidas by Stella McCartney's Tennis Bra Includes Built-In Heart Sensor,” <www.ecouterre.com/adidas-by-stella-mccartneys-tennis-bra-includes-built-in-heart-sensor/>, Mar. 23, 2012, 2 pages. cited by applicant

Milenkovic, Milena, et al, “An Accelerometer-Based Physical Rehabilitation System,” IEEE SouthEastern Symposium on System Theory, 2002, pp. 57-60. cited by applicant

Mizell, David, “Using Gravity to Estimate Accelerometer Orientation”. Seventh IEEE International Symposium on Wearable Computers, 2003, 2 pages. cited by applicant

Ormoneit, D., et al., “Learning and Tracking Cyclic Human Motion,” 7 pages. cited by applicant

Otto, Chris, et al, “System Architecture of a Wireless Body Area Sensor Network for Ubiquitous Health Monitoring,” Journal of Mobile Multimedia, vol. 1, No. 4, 2006, pp. 307-326. cited by applicant

Park, Chulsung, et al, “Eco: An Ultra-Compact Low-Power Wireless Sensor Node for Real-Time

Motion Monitoring,” EEE Int. Symp. on Information Processing in Sensor Networks, 2005, pp. 398-403. cited by applicant
PCT International Search Report and Written Opinion for PCT/US2009/48523, mailed Aug. 27, 2009, 8 pages. cited by applicant
U.S. Appl. No. 12/490,304, filed Jun. 23, 2009. cited by applicant
U.S. Appl. No. 17/006,307, filed Aug. 28, 2020. cited by applicant
U.S. Appl. No. 17/171,737, filed Feb. 9, 2021. cited by applicant
U.S. Appl. No. 15/791,398, filed Oct. 23, 2017. cited by applicant
U.S. Appl. No. 14/673,761, filed Mar. 30, 2015. cited by applicant

Primary Examiner: Turner; Shelby A

Assistant Examiner: Becker; Brandon J

Attorney, Agent or Firm: Leydig, Voit & Mayer, Ltd.

Background/Summary

CROSS-REFERENCE RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 15/791,398, filed on Oct. 23, 2017, which is a continuation of U.S. patent application Ser. No. 14/673,761 filed on Mar. 30, 2015, now U.S. Pat. No. 9,797,920, which is a continuation of U.S. patent application Ser. No. 12/490,304, filed Jun. 23, 2009, now U.S. Pat. No. 8,996,332, which claims priority under 35 U.S.C. § 119(e) of U.S. Provisional Application No. 61/075,330, filed Jun. 24, 2008, all of which are herein incorporated by reference.

FIELD OF THE INVENTION

(1) This invention relates to a method of monitoring human activity, and more particularly to identifying user motion states and adjusting program settings based on the user motion state.

BACKGROUND

(2) The development of Micro-Electro-Mechanical Systems (MEMS) technology has enabled manufacturers to produce inertial sensors (e.g., accelerometers) of sufficiently small size, cost, and power consumption to fit into portable electronic devices. Such inertial sensors can be found in a limited number of commercial electronic devices such as cellular phones, portable music players, pedometers, game controllers, and portable computers.

(3) Step counting devices (e.g., pedometers) are used to monitor an individual's daily activity by keeping track of the number of steps that he or she takes. Steps are counted by sensing accelerations caused by user motion. Step counting devices are not able to detect or count motions other than steps. Nor are step counting devices capable of differentiating between different user activities.

(4) Some step counting devices may be attached to and receive input from external sensors (e.g., a bike cadence sensor) to detect a motion other than a step. However, such step counting devices rely on external sensors for such monitoring capability. These devices are not capable of detecting or counting motions other than steps without the input from external sensors.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The present invention is illustrated by way of example, and not by way of limitation, and can be more fully understood with reference to the following detailed description when considered in

connection with the following figures:

- (2) FIG. 1 is a block diagram illustrating an electronic device, in accordance with one embodiment of the present invention;
- (3) FIG. 2 is a block diagram illustrating a motion identification system, in accordance with one embodiment of the present invention;
- (4) FIG. 3A illustrates a first exemplary motion cycle graph that shows a user engaged in a first user activity;
- (5) FIG. 3B illustrates a second exemplary motion cycle graph **350** that shows a user engaged in a second user activity;
- (6) FIG. 4A illustrates a flow diagram for a method of monitoring user motion state with an inertial sensor, in accordance with one embodiment of the present invention;
- (7) FIG. 4B illustrates a flow diagram for a method of recording a motion state, in accordance with one embodiment of the present invention;
- (8) FIG. 5 shows a state diagram for the behavior of a system for monitoring user motion state, in accordance with one embodiment of the present invention;
- (9) FIG. 6 illustrates a flow diagram for a method of operating an electronic device in sleep mode, in accordance with one embodiment of the present invention;
- (10) FIG. 7A illustrates a flow diagram for a method of operating an electronic device in entry mode, in accordance with one embodiment of the present invention;
- (11) FIG. 7B illustrates a flow diagram for a method of operating an electronic device in entry mode, in accordance with another embodiment of the present invention;
- (12) FIG. 8 illustrates a flow diagram for a method of operating an electronic device in an active mode, in accordance with one embodiment of the present invention;
- (13) FIG. 9 illustrates a flow diagram for a method of operating an electronic device in an exit mode, in accordance with one embodiment of the present invention;
- (14) FIG. 10 illustrates a flow diagram for a method of recognizing a user motion state, in accordance with one embodiment of the present invention;
- (15) FIG. 11 illustrates a flow diagram for a method of monitoring user motion state using an inertial sensor, in accordance with one embodiment of the present invention;
- (16) FIG. 12 illustrates a flow diagram for a method of using user motion state related information to modify program settings; and
- (17) FIG. 13 illustrates a block diagram of a machine in the exemplary form of a computer system within which a set of instructions may be executed in accordance with an embodiment of the present invention.

DETAILED DESCRIPTION

(18) Embodiments of the present invention are designed to monitor a user's motion state using an inertial sensor. In one embodiment, accelerations are monitored, and a current user motion state is identified from multiple recognizable user motion states based on the accelerations. These motion states include any activities based on periodic human motions, including, for example: walking, running, inline skating, bicycling, exercising on an elliptical machine, exercising on a rowing machine, and cross country skiing, as well as other types of motions such as riding in a car, on a train, on an escalator, etc. In one embodiment, periodic human motions that are appropriate to the current user activity are counted. In one embodiment, the system provides user data on each of the activities that were performed. In this way, a user can monitor his or her overall activity level throughout the day, as well individual activities.

(19) FIG. 1 is a block diagram illustrating a particular machine or electronic apparatus **100**, in accordance with one embodiment of the present invention. In one embodiment, the electronic device **100** is a portable electronic device that includes one or more inertial sensors. The inertial sensors may measure accelerations along a single axis or multiple axes. The inertial sensors may measure linear as well as rotational (angular) accelerations. In one embodiment, the inertial sensors

may be two axis or three axis accelerometers. In one embodiment, the inertial sensors may be gyroscopes, or other sensors.

(20) The electronic device **100** may be used to identify user motion states and count periodic human motions appropriate to identified user activities. In one embodiment, electronic device **100** operates in conjunction with a server (not shown) to identify user motion states and count periodic human motions. In one embodiment, periodic human motions may be accurately counted regardless of the placement and/or orientation of the device **100** on a user. For example, the electronic device **100** may be carried in a backpack, pocket, purse, hand, or elsewhere, and accurate motion state may be identified. Furthermore, the periodic human motions may still be accurately counted. In one embodiment, the device **100** is optimally placed in a particular one of multiple locations on a human for a particular type of motion, to facilitate detection of user motion state and counting of periodic motions. For example, the electronic device **100** may be optimally placed in a pocket while bicycling to ensure the greatest accuracy in counting pedal motions. However, the electronic device **100** may be placed elsewhere and still correctly detect user motion state and count periodic motions. Periodic human motions may be accurately counted whether the electronic device **100** maintains a fixed orientation or changes orientation during use.

(21) The electronic device **100** in one embodiment comprises an acceleration measuring logic **105**, a motion state identification engine **110**, a motion processor **120**, and a motion log **125**. The acceleration measuring logic **105** may be an inertial sensor or other acceleration sensitive instrument. The acceleration measuring logic **105** may continuously take measurements of acceleration data. The measurements of acceleration data are taken at a sampling rate that may be fixed or variable. In one embodiment, the acceleration measuring logic **105** receives a timing signal from a timer (not shown) in order to take measurements at the sampling rate. In one embodiment, the acceleration measuring logic **105** is coupled to the activity identification engine **110** and to the motion processor **120**, and acceleration measurement data is sent to the activity identification engine **110** and to the motion processor **120** for processing.

(22) In one embodiment, measurement data is processed by the motion state identification engine **110** to identify a user's motion state. The motion state identification engine **110** uses the motion data to identify the user motion state from a plurality of identifiable motion states. The motion state identification engine **110** may identify a motion state by monitoring for different events, each event indicative of a type of motion state. In one embodiment, when enough events indicative of a particular motion state are detected without contraindication, the motion state identification engine **110** notifies the motion processor **120** that the user is in the identified motion state. For example, if a number of running steps are detected, without intervening stops or other motion types, the motion state identification engine **110** identifies the user as being in a running motion state.

(23) The motion processor **120** may process acceleration measurement data to detect periodic human motions. In one embodiment, a series of motion criteria are applied to the acceleration measurement data. If each of the motion criteria is satisfied, a periodic human motion may be identified, and counted. In one embodiment, a different set of motion criteria may apply for each user activity. In one embodiment, criteria may include positive criteria (ones that must be met to classify a motion in a certain way) and negative criteria (ones that cannot be met to classify a motion in a certain way). Once the motion state identification engine **110** has identified a user activity, the motion processor **120** may apply the set of motion criteria specific to the identified activity to detect appropriate periodic human motions for that activity. When an appropriate periodic human motion is detected, it may be recorded in the motion log **125**. In one embodiment, the method described in U.S. patent application Ser. No. 12/069,267, entitled "Human Activity Monitoring Device With Activity Identification," filed on Feb. 8, 2008, is utilized to identify activities. That application is herein incorporated by reference.

(24) If no motion state has been identified by the motion state identification engine **110**, in one embodiment possible periodic human motions are buffered by the motion processor **120** in a

memory (not shown). Once the motion state identification engine **110** identifies the user motion state, these buffered periodic human motions may be recorded in the motion log **125** as periodic human motions appropriate to the identified user motion state. For example, if the user starts to jog, the first few step counts may be buffered to ensure that the system identifies jogging. Once the user's motion state—jogging—is positively identified, the buffered step counts are added to the step counter. This ensures that even if positive identification of the user motion state takes time, activity performed during the identification period is still tracked.

(25) The motion log **125** may maintain separate data sets for each type of periodic human motion. For example, the motion log **125** may have a first record of the number of steps walked in a day and a second record of the number of strides a user has inline skated in a day. The motion log **125** may also include additional statistics for different periodic human motions, for example the average walking speed, the length of time and time in a day during which a particular activity was performed, etc. In one embodiment, the user may be provided with a total activity level evaluation as well, based on the various activities performed.

(26) In one embodiment, the electronic device **100** includes one or more programs or modules **130**, which may include applications, system managers, etc. The applications may include applications that use acceleration measurement data (e.g., a pedometer application, a gesture recognition application, a motion sensitive game, etc.) and/or applications that do not directly use acceleration measurement data (e.g., a telephony application, a music player application, a video application, etc.). The system managers may include power managers, screen controllers, volume controllers, and other systems. The programs **130** may receive an identification of a current user motion state from the motion state identification engine **110**. In one embodiment, a program **130** receives an identification of a current user motion state when the program is initially activated. In one embodiment, the program **130** receives user motion state updates periodically (e.g., once every second, once every 10 seconds, once every minute, etc.) or continuously. In one embodiment, the program **130** receives a user motion state update when the motion state changes. The program **130** may then modify one or more settings based on the motion state.

(27) FIG. 2 is a block diagram illustrating a motion state identification system **200**, in accordance with one embodiment of the present invention. The motion state identification system **200** in one embodiment includes an electronic device. In one embodiment, the electronic device is a portable electronic device that includes one or more inertial sensors. In another embodiment, the motion state identification system **200** includes an electronic device coupled to a server. The distribution of the functionality between the portable device and the server may vary. In one embodiment, data acquisition is handled by the portable device, while the server and the portable device share processing of the data. In one embodiment, temporary data storage is handled by the portable device, but historical data is stored on the server. In one embodiment, the motion state identification system **200** comprises a filter **220**, a cadence logic **232**, a rolling average logic **235**, a dominant axis logic **227**, a motion state identification engine **280**, a motion processor **230** and a motion log **275**.

(28) The acceleration measuring logic **205** may be an inertial sensor or other acceleration sensitive instrument. The acceleration measuring logic **205** may continuously take measurements of acceleration data at a sampling rate that may be fixed or variable. In one embodiment, the acceleration measuring logic **205** receives a timing signal from a timer (not shown) in order to take measurements at the sampling rate. In one embodiment, the acceleration measuring logic **205** is a 3-dimensional accelerometer. In one embodiment, the sampling rate of the acceleration measuring logic **205** may be based on a level of activity detected. In one embodiment, for slower motions, the sampling rate is decreased.

(29) In one embodiment, the acceleration measuring logic **205** is coupled to the filter **220**. Measurement data may be processed by the filter **220** to remove noise. The filter **220** may be implemented in hardware, software, or both hardware and software. In one embodiment, the filter

220 includes multiple filters, and a determination of which filters to apply to the measurement data is made based upon the type of user activity detected. For example, a low pass filter may be used to remove high frequency noise that would interfere with step counting when a user is walking. In contrast, a high pass filter may be used when quick motions are to be monitored. The filters may, in one embodiment, include one or more of high pass filters, low pass filters, bandpass filters, and band gap filters. In one embodiment, the filters have adjustable frequency ranges. In one embodiment, one or more filters may be applied to different data sets. For example, a low pass filter may be used to remove jitter data from the inertial data, while the user is jogging. At the same time, in one embodiment, a low pass filter may be applied to the audio stream being played to the user.

(30) Many types of motions that are useful to keep track of have a periodic set of movements. Specific periodic human motions may be characteristic of different types of user activity. For example, to walk, an individual must lift a first leg, move it forward, plant it, and then repeat the same series of motions with a second leg. In contrast, a person inline skating performs a repeated sequence of pushing, coasting and liftoff for each leg. For a particular individual, the sequence of walking motions will usually occur in about the same amount of time, and the sequence of skating motions will usually occur in about the same amount of time. The repeated set of motions can be considered a unit, and defines a motion cycle. The amount of time that it takes to complete one motion cycle defines the motion cycle's period, and the number of motion cycles that occur in a given unit of time define the motion cycle's frequency, or cadence.

(31) In one embodiment, filtered measurement data may be passed on to the cadence logic **232**. The cadence logic **232** may determine a period and/or cadence of a motion cycle. The period and/or cadence of the motion cycle are based upon user activity (e.g. inline skating, biking, running, walking, etc). In one embodiment, the motion cycle's period is verified or updated after each periodic human motion. The current motion cycle period in one embodiment is a rolling average of the motion cycle periods, based on a recent set of motions of the same activity type. This rolling average data may be received from the rolling average logic **235**, as discussed in more detail below.

(32) In one embodiment, the cadence logic **232** maintains one or more cadence windows. A cadence window is a window of time since a last periodic human motion was counted that is looked at to detect a new periodic human motion. When motion criteria (e.g., threshold conditions) are met within a cadence window, a periodic human motion is detected, whereas when motion criteria are met outside of the cadence windows no periodic human motion is detected. A cadence window may be used to facilitate accurate measurement of a periodic human motion (e.g., a step, inline skating stride, bicycle pedal, rowing stroke, etc.).

(33) A cadence window may be set based on the period and/or cadence of the actual motion cycle (e.g., a stepping period), on set limits, and/or on other factors. In one embodiment, the cadence window is determined by using the period of the current periodic human motion. In one embodiment, the cadence window may be a multiple of the current period (e.g. if the user is jogging at 180 steps per minute, e.g. three steps per second, the cadence window may be 0.66 seconds, e.g. twice the expected period between steps). In one embodiment, the cadence window is a dynamic cadence window that continuously updates as a user's cadence changes during a particular activity. For example, using a dynamic cadence window, the cadence window length may be verified or adjusted after each periodic human motion. If no previous periodic human motions have been detected, or if less than a set number of periodic human motions to determine a dynamic cadence window have been detected, a default cadence window may be used. Once enough periodic human motions have been detected to determine a dynamic motion cycle cadence or period, the cadence window may be set to the determined motion cycle period plus or minus an error factor. In one embodiment, a count of between about two to about ten periodic human motions is sufficient to set a dynamic cadence window.

(34) In one embodiment, a separate default cadence window may be maintained for each

identifiable user activity. In one embodiment, a separate default cadence window may be maintained for each user, for each identifiable user activity. Each identifiable user activity may have, for example, a unique default cadence window. When no specific current user activity has yet been identified, these separate cadence windows may be maintained concurrently for each of the possible user activities, in order to correctly identify the actual user motion state. Periodic human motions that occur outside of a default cadence window may indicate that the user motion state has changed.

(35) Once the motion cycle's period is detected, the cadence logic **232** may set one or more sample periods for the rolling average logic **235** to use based upon the motion cycle's period. A sample period can include a specified time frame over which obtained measurements are used to perform a calculation. In one embodiment, the sample period(s) is approximately the length of the motion cycle's period. In one embodiment, a sample period is set such that it is a multiple of the motion cycle's period.

(36) In one embodiment, the rolling average logic **235** may receive filtered measurement data from the filter **220** and one or more sample periods from the cadence logic **232**. The rolling average logic **235** creates one or more rolling averages of accelerations as measured by the inertial sensor(s) over the sample period(s) set by the cadence logic **232**. The rolling averages of accelerations may be used for determining an orientation of the electronic device, for determining thresholds to compare acceleration measurements against, and/or for other purposes. In one embodiment, the rolling average logic **235** creates one or more rolling averages of accelerations for determining an orientation of the electronic device **200**, at least one rolling average having a period that is at least the motion cycle's period. In one embodiment, the rolling average logic **235** creates a rolling average of accelerations for determining a lower threshold to compare acceleration measurements against, the rolling average having a sample period that is at least twice the stepping period.

(37) The rolling average logic **235** may create one or more rolling averages of data other than accelerations. In one embodiment, the rolling average logic **235** creates a rolling average of motion cycle periods, where the rolling average is the rolling average of the periodic human motions. In one embodiment, the rolling average of motion cycle periods is calculated over the past four counted periodic human motions. The rolling average of the motion cycle periods may be used by the cadence logic **232** to dynamically determine a cadence window and a current motion cycle cadence.

(38) In one embodiment, rolling averages may be maintained in memory registries that keep track of rolling average values and the number of samples that were used to calculate current rolling average values. When a new measurement is taken, it can be incorporated into the rolling average value, and the registry can then be updated with a new rolling average value. Alternatively, the rolling averages may be maintained by buffering the measurements used to calculate the rolling averages. In one embodiment FIFO buffers may be used, such that as the buffers fill, oldest measurement data is discarded and replaced by new measurement data. The measurements in the buffer can be averaged after each measurement to determine a new rolling average.

(39) In one embodiment, the dominant axis logic **227** receives at least filtered acceleration data from the filter **220**, and rolling averages of accelerations from the rolling average logic **235**. In one embodiment, the dominant axis logic **227** receives only rolling averages of accelerations from the rolling average logic **235**. The dominant axis logic **227** may assign a dominant axis based on the received information.

(40) In one embodiment, the dominant axis logic **227** determines an orientation of the electronic device and/or the inertial sensor(s) within the motion identification system **200**. The orientation may be determined based upon the rolling averages of accelerations created by the rolling average logic **235**. In one embodiment, once the orientation is determined, a dominant axis is assigned based upon the orientation. Determining an orientation of the electronic device may include identifying a gravitational influence. The axis with the largest absolute rolling average may be the

axis most influenced by gravity, which may change over time (e.g. as the electronic device is rotated). Therefore, a new dominant axis may be assigned when the orientation of the electronic device and/or the inertial sensor(s) attached to or embedded in the electronic device changes.

(41) In one embodiment, the axis with the largest absolute rolling average over the sample period is assigned as the dominant axis. In one embodiment, the dominant axis does not correspond to one of the actual axes of the inertial sensor(s) in a current orientation, but rather to an axis that is defined as approximately aligned to gravity. In one embodiment, the dominant axis corresponds to a virtual axis that is a component of a virtual coordinate system. In one embodiment, the dominant axis setting logic **240** assigns the dominant axis by performing a true gravity assessment, such as by doing trigonometric calculations on the actual axes based on the gravitational influence. In one embodiment, the dominant axis setting logic **240** assigns the dominant axis by comparing the gravitational influence to a data structure such as a lookup table, associative array, hash table, adjacency matrix, etc.

(42) In one embodiment, the dominant axis is determined based on criteria other than a device orientation in relation to gravity. For example, the dominant axis may be determined based on an axis that has a greatest peak to peak variation within a motion cycle. In one embodiment, multiple dominant axes are assigned, each dominant axis being associated with a different user activity. The dominant axis may be assigned based on criteria specific to an associated user activity. For example, a first dominant axis may be assigned to the user activity of walking based on an axis that is most influenced by gravity, and a second dominant axis may be assigned to the user activity of bicycling based on an axis that has the greatest peak to peak variance.

(43) The motion state identification engine **280** may receive as an input filtered acceleration measurement data from the filter **220**. The motion state identification engine **280** may also receive a cadence and/or period of a current motion cycle and a current cadence window from the cadence logic **232**, rolling averages (e.g., of accelerations) from the rolling average logic **235**, and one or more dominant axes from the dominant axis logic **227**.

(44) In one embodiment, the motion state identification engine **280** includes multiple motion state identification logics **285**. In one embodiment, each of the motion state identification logics **285** is set up to determine whether the current acceleration data defines a particular activity, movement, or other type of motion state. Alternatively, motion state identification logic **285** may be capable of identifying two or more possible motion states. In one embodiment, the motion state identification engine **280** includes only a single motion state identification logic **285**, which is used to identify all identifiable user motion states. Alternatively, there may be separate motion state identification logic **285** for each activity, there may be separate motion state identification logics **285** for each activity type, or there may be separate motion state identification logics **285** based on some other criteria. In one embodiment, there is a separate motion state identification logic **285** for motion states associated with periodic human motion (e.g. walking, running, bicycling, etc.) and motion states not associated with such motions (e.g. riding in a car, escalator, elevator, etc.)

(45) Motion state identification logic **285** identifies a specific user motion state by monitoring for acceleration data indicative of that type of motion state. The acceleration data is analyzed, and the motion state identification logic **285** may make its determination based on one or more of the received acceleration data, motion cycle cadence, motion cycle period, cadence windows, rolling averages, and dominant axes. In one embodiment, when enough events indicative of a particular user motion state are detected by motion state identification logic **285**, the motion state identification engine **280** notifies the motion processor **230** that the user is in the identified motion state. In one embodiment, each time motion state identification logic **285** detects an event indicative of a particular type of motion, that event is forwarded to the motion processor **230**. The motion processor **230** may then determine whether the user is performing an activity associated with the received event or received events. In one embodiment, the motion state identification logic **285** also monitor for negative events that indicate that a user is not performing a particular user

activity, or is not in a particular motion state. These negative events may also be used by the motion state identification engine **280** and/or the motion processor **230** to identify a current user motion state.

(46) In one embodiment, the motion state identification engine **280** determines the probability that a user is in a particular motion state. For example, the motion state identification engine **280** may determine that there is a 95% confidence that the user is running. At the same time, the motion state identification engine **280** may also determine that there is a 25% confidence that the user is bicycling. In one embodiment, this indicates that 19 out of 20 indicators suggest that the user's motion state is running, while 1 out of 4 indicators suggest the user's motion is bicycling. There may be one counter indicator, or one other motion state identification engine **280** that has identified the activity as something other than running. The confidence/probability that a user is in a particular motion state may be determined based on a number of positive and/or negative events that are satisfied for that user motion state. The confidence/probability may also be determined based on the how close an acceleration measurement is to a threshold of a positive or negative event. For example, if a walking positive event includes an upper acceleration threshold of 3 m/s.², and the positive event was satisfied with a reading of 2.99 m/s.², then a confidence rating may be lower than if the positive event was satisfied with a reading of 2.6 m/s.².

(47) FIGS. **3A** and **3B** illustrate examples of motion data which may be used by a motion state identification logic that identifies bicycling by monitoring for positive and negative motion events associated with bicycling, in accordance with embodiments of the present invention. FIG. **3A** illustrates a first exemplary motion cycle graph **300** that shows a user engaged in a first user activity as analyzed by a motion state identification logic that identifies bicycling, in accordance with one embodiment of the present invention. The exemplary motion-cycle graph **300** shows acceleration data taken with a single tri-axis inertial sensor. The acceleration at a given period of time is represented for a first axis **303**, a second axis **305**, and a third axis **307**.

(48) The motion state identification engine associated with identifying bicycling, which can be referred to as the bicycling identification logic, monitors for positive events and negative events that occur when certain motion criteria are satisfied. In one embodiment, the bicycling identification logic uses a dominant axis that is defined by measuring the axis with the largest peak to peak difference. This is because in bicycling the user's leg moves in a circle around the axis of the pedal with the downward motion displaying a largest peak to peak difference. In the illustrated figure, the first axis **303** is the dominant axis, because it has the greatest peak to peak difference. In one embodiment, the bicycling identification logic only examines acceleration data along the dominant axis.

(49) In one embodiment, the bicycling identification logic uses a rolling average of accelerations **310** for the dominant axis to set a first threshold **315** and a second threshold **320**. The first threshold **315** and second threshold **320** may be set based on offsets from the rolling average of accelerations **310**. Alternatively, the first threshold **315** and second threshold **320** may be set based on a percentage of the peak to peak difference, on a percentage of the average of the peak to peak difference, on a percentage of half of the peak to peak difference, or on other criteria. For example, the first threshold **315** may be set at 25% of the peak to peak difference, and the second threshold **320** may be set at 75% of the peak to peak difference.

(50) A first periodic human motion may be detected when the first threshold **315** is first crossed **325** (moving away from zero). This may trigger a positive bicycling event. A second periodic human motion may be detected when the first threshold **315** is crossed a second time **330** (moving away from zero). In one embodiment, if the first threshold **315** is crossed a second time **330** while within a cadence window **345**, a positive bicycling event may be triggered. If the first threshold **315** is not crossed **330** while within the cadence window **345**, a negative bicycling event may be triggered. The cadence window **345** has a cadence window minimum **343** that opens the cadence window **345** some period of time after the first threshold **315** is first crossed **325**, and a cadence

window maximum **347** that closes the cadence window **345** some period of time thereafter. In the illustrated example, the first threshold **315** is crossed within the cadence window **345**, triggering a positive bicycling event.

(51) The second threshold **320** may be used by the bicycling identification logic to determine a peak shape for the acceleration measurements along the first axis **303**. In one embodiment, the bicycling identification logic notes each time the second threshold **320** is crossed. In one embodiment, if the time between when the second threshold **320** is first crossed **335** and second crossed **340** is less than a peak window **350**, then a negative bicycling event may be triggered. In one embodiment, unless the time between when the second threshold **320** is first crossed **335** and crossed the second time **340** is greater than or equal to the peak window **350**, then a negative bicycling event is triggered. In one embodiment, if the second threshold **320** is crossed within 25-35% or 65-75% of the average of the motion cycle's period, the peak is too steep, and a negative event is triggered. In one embodiment, if the second threshold **320** is crossed within certain percentages of the average of the motion cycle's cadence, a negative event is triggered. In the illustrated example, no negative bicycling events are triggered. Moreover, the illustrated example shows an embodiment in which a sufficient number of positive events are triggered to identify the current user activity as bicycling.

(52) FIG. **3B** illustrates a second exemplary motion cycle graph **350** that shows a user engaged in a second user activity as analyzed by a motion state identification logic that identifies bicycling, in accordance with one embodiment of the present invention. The exemplary motion-cycle graph **350** shows acceleration data taken with a single tri-axis inertial sensor. The acceleration at a given period of time is represented for a first axis **353**, a second axis **355**, and a third axis **357**.

(53) The bicycling identification logic monitors for positive events and negative events that occur when certain motion criteria are satisfied. In one embodiment, the bicycling identification logic uses a dominant axis that is defined by measuring the axis with the largest peak to peak difference. In the illustrated figure, the second axis **355** is the dominant axis, because it has the greatest peak to peak difference.

(54) In one embodiment, the bicycling identification logic uses a rolling average of accelerations **360** for the dominant axis to set a first threshold **365** and a second threshold **370**. A first periodic human motion may be detected when the first threshold **365** is first crossed **375** (moving away from zero). This may trigger a positive bicycling event. A second periodic human motion may be detected when the first threshold **365** is crossed a second time **380** (moving away from zero). In one embodiment, if the first threshold **320** is crossed a second time **380** while within a cadence window **398**, a positive bicycling event may be triggered. If the first threshold **365** is not crossed **380** while within the cadence window **398**, a negative bicycling event may be triggered. In the illustrated example, the first threshold **365** is crossed within the cadence window **398**, triggering a positive bicycling event.

(55) The second threshold **370** may be used by the bicycling identification logic to determine a peak shape for the acceleration measurements along the second axis **355**. In one embodiment, the bicycling identification logic notes each time the second threshold **370** is crossed. The time between when the second threshold **370** is first crossed **385** and second crossed **388** is less than a peak window **390**, triggering a negative bicycling event. The negative bicycling event may reset a counter that counts a number of positive bicycling events. Each illustrated peak would trigger a negative bicycling event. Therefore, not enough positive bicycling events are triggered to identify the current user activity as bicycling. FIGS. **3A** and **3B** illustrate the analysis performed by the bicycle identification logic. Similar analysis is performed for other types of motions.

(56) Returning to FIG. **2**, the motion processor **230** may receive positive and negative events from the motion state identification logics **285** of the motion state identification engine **280**. The motion processor **230** may also receive dominant axis data from the dominant axis logic **227**, rolling average data from the rolling average logic **235**, a cadence and period for a current motion cycle

from the cadence logic **232**, cadence windows from the cadence logic **232**, and filtered acceleration data from the filter **220**. The motion processor **230** may include a counting logic **260**, mode logic **255**, and one or more count buffers **265**.

(57) In one embodiment, the mode logic **255** receives positive and negative events from the motion state identification logics **285**. The mode logic **255** may then determine an appropriate mode for the counting logic **260** based on the received events. The mode logic **255** may also use count buffers **265** in making this determination. Count buffers track periodic human motions, to ensure that the count is maintained while the motion state is correctly identified. In one embodiment, each motion state which is potentially being identified has a separate count buffer. In one embodiment, while in an entry mode, the first count buffer to reach a predetermined value determines which active mode to initiate. In one embodiment, the mode logic **255** includes a plurality of active modes, each active mode corresponding to a different activity. In one embodiment, the mode logic **255** includes an entry mode, an exit mode and a sleep mode. Operating modes are discussed in greater detail below in reference to FIG. 5.

(58) The counting logic **260** may receive data from the dominant axis logic **227**, rolling average logic **235**, cadence logic **232**, and filter **220**. The counting logic **260** may use this data to count periodic human motions. In one embodiment, the behavior of the counting logic **260** is determined by its current operating mode.

(59) The counting logic **260** may determine which measurements to use to determine if a periodic human motion has occurred. In one embodiment, the counting logic **260** may monitor accelerations relative to the dominant axis, and select only those measurements with specific relations to the dominant axis for measurement. For example, only accelerations that are along the dominant axis may be selected (e.g., in walking active mode), or alternatively, only accelerations that are approximately perpendicular to the dominant axis may be selected (e.g., in rowing active mode). In one embodiment, the counting logic **260** uses only measurements of acceleration data along the dominant axis. In alternative embodiments, measurements of acceleration data along other axes may also be used.

(60) Selected measurements may be compared to motion criteria to determine whether a periodic human motion has occurred, and to determine what type of periodic human motion has occurred. Examples of motion criteria include comparisons of current measurements to previous measurements, comparisons of current measurements to threshold values, slope analysis, curve fitting analysis, peak analysis, etc. In one embodiment, the same criteria that are used to identify events by the activity identification logics are also used to count periodic human motions. Alternatively, different criteria may be used. In one embodiment, crossing threshold(s) in a motion is used to count. In one embodiment, the motion criteria used are dependent on a current operating mode of the counting logic **260**.

(61) The count buffers **265** keep track of a probable count of periodic human motions. In one embodiment, the motion processor **230** includes a plurality of count buffers **265**, each associated with a different user activity. Alternatively, a single count buffer may be used to buffer periodic human motions for two or more user activities. In one embodiment, a single count buffer **265** maintains buffers for all user activities.

(62) The behavior of the count buffers **265** may depend on the operating mode of the counting logic **260**. For example, in entry mode, a separate count buffer may be maintained for each possible user activity. When the system identifies a periodic human motion that meets the criteria of a particular user activity, the count buffer corresponding to that user activity may be incremented. A detected periodic human motion may meet the criteria for a number of different user activities. Until a current user activity is identified, in one embodiment such motion would be counted by each of the corresponding count buffers **265**.

(63) Depending on the current mode, when one of the count buffers **265** reaches a certain number, the motion log **275** may be updated the count from the count buffer. This may also cause the

motion logic **255** to place the counting logic **260** in an active mode, for the user motion state associated with the count buffer. In one embodiment, all count buffers **265** are then reset. Thus, the “false motions” counted by the other count buffers **265** are discarded. The number of periodic human motions that are counted by the count buffer before they are moved to the motion log **275** may vary from two to ten or more, depending on the current operating mode. Moreover, in one embodiment count buffers corresponding to different user activities may have different count requirements.

(64) The motion log **275** keeps track of the total number of periodic human motions that have occurred, and the associated activities. In one embodiment, this data is transmitted to a server or remote database. The output of the motion log **275**, in one embodiment, is made available to the user. In one embodiment, the user can view the various activities, and associated data through a web page. In one embodiment, the user can see an overall activity level on a per hour, per day, per week, or other basis, in addition to being able to see the individual activities comprising the overall activity level.

(65) In one embodiment, one or more programs **290** are coupled to the motion state identification system **200**. The one or more programs **290** may receive an identification of a current user motion state from the motion state identification system **200**. In one embodiment, the programs **290** receive motion state identification information from the motion state identification engine **280**. In another embodiment, the programs **290** receive motion state identification information from the motion processor **230**. In one embodiment, the identification of the current user motion state is received along with a confidence rating for the current user motion state. For example, a program may receive information indicating that there is a 98% chance that the user is walking. In another embodiment, the identification of multiple possible current user motion states is received along with confidence ratings for each possible user motion state. For example, a program may receive an indication that there is a 70% confidence that the user is running and a 30% confidence that the user is bicycling.

(66) In one embodiment, the programs **290** receive additional information from the motion identification system **200**. The additional information may be information that is derived from the acceleration measurements (hereinafter referred to as motion related information). For example, the programs **290** may receive information on a user's current cadence, a user's current rolling average, a current dominant axis, counted periodic human motions, etc.

(67) In one embodiment, the programs **290** poll the motion identification system **200** to determine a current user motion state and/or additional user motion related information. The programs **290** may poll the motion identification system **200** continuously, periodically, or upon occurrence of predefined events (e.g., when a music player application begins to play a new song). Alternatively, current motion related information may be posted to a current motion related information cache (not shown). In one embodiment, the motion related information cache may be maintained with current up-to-date information by motion identification system **200**. Programs **290** may then obtain data from the cache to determine a current user motion state, including current cadence, current dominant axis, etc.

(68) In one embodiment, the programs subscribe to one or more motion related information services through subscription logic **292**. Each subscription entry may identify what types of motion related information that the subscription logic **292** of motion identification system **200** is to send to the programs **290**. Each subscription entry may also identify when to send updated motion related information to the programs **290**. For example, a subscription may cause the motion state identification system **200** to send cadence updates every 10 seconds and user activity updates every 5 seconds. Alternatively, a subscription may cause the subscription system **292** to send a current user activity update whenever a current user motion state changes.

(69) In one embodiment, a program **290** uses the received user motion state information to adjust settings of the program **290**. For example, if the program **290** is a music player application, it may

adjust a volume level and/or the music tempo based on the detected user motion state. If, for example, a user is detected to be running, the volume and/or music tempo may be increased. In another example, if the program is a telephony application, the ringer and/or speaking volume may be increased or decreased based on the detected user motion state. Other settings, such as what user gestures are used as commands may also be adjusted based on the detected user motion state.

(70) In another embodiment, the program uses the received motion state information to adjust settings of the program **290**. For example, a music player application may adjust a music tempo to match a detected user cadence. In another example, the music application may generate a playlist of songs that match a user's current cadence. This makes it easier for the user to maintain a cadence by matching the music tempo. Moreover, the music application may be integrated with a user fitness application that indicates for the user to speed up or slow down by selecting songs that are faster or slower in tempo than the user's current cadence.

(71) FIG. **4A** illustrates a flow diagram for a method **400** of determining a motion state, in accordance with one embodiment of the present invention. The method may be performed by processing logic that may comprise hardware (e.g., circuitry, dedicated logic, programmable logic, microcode, etc.), software (such as instructions run on a processing device), or a combination thereof. In one embodiment, method **400** is performed by the electronic device **100** of FIG. **1**. In one embodiment, method **400** is performed by the motion identification system **200** of FIG. **2**.

(72) Referring to FIG. **4A**, method **400** begins with monitoring accelerations (block **405**). Accelerations may be monitored with an inertial sensor, or other acceleration monitoring device. The monitored acceleration may include filtered and processed acceleration data, as described above. At block **410**, the motion is identified as corresponding to one of a plurality of motion states based on the accelerations. The motion states may include user activities involving periodic human motions, or other motion states which do not require a user to be performing periodic human motions. At block **415**, the process determines whether the motion state corresponds to an activity that includes periodic human motions. If so, at block **420**, periodic human motions are counted appropriate to the identified activity. Examples of identifiable user activities include, walking, running, inline skating, rowing, exercising on an elliptical machine, and bicycling. Other user activities may also be identified. The process then returns to block **410**, to continue monitoring accelerations. If the motion state does not correspond to an activity with periodic motions, the process returns to block **410**, to continue monitoring accelerations.

(73) Periodic human motions corresponding to multiple different predetermined user activities may be identified in embodiments of the present invention. Moreover, in one embodiment, new user activities may be added to the list of recognized periodic human motions. To add such periodic human motions to the predetermined user activities, a user may record a new user activity.

(74) FIG. **4B** illustrates a flow diagram for a method **450** of recording a motion profile, in accordance with one embodiment of the present invention. Method **450** may be used to record new user motion states or activities, or to calibrate existing activities to a particular user. Calibration of existing user activities may improve counting accuracy. Calibration may be useful when the user's activity is performed in an unusual way. For example, if the user is riding a recumbent bicycle, the motions will not match the traditional "bicycling" motion cycle graph. The method **450** may be performed by processing logic that may comprise hardware (e.g., circuitry, dedicated logic, programmable logic, microcode, etc.), software (such as instructions run on a processing device), or a combination thereof. Method **450** may be performed by the electronic device **100** of FIG. **1**, and by the motion identification system **200** of FIG. **2**.

(75) Referring to FIG. **4B**, the method **450** begins by receiving a command to record a motion profile (block **455**). At block **460**, input is received that indicates the user activity for which the motion profile will be recorded. In one embodiment, the system may enable the user to select one of a displayed list of existing user activities. In one embodiment, the user may select one of the displayed user activities or may choose to identify a new user activity to be associated with the

motion profile. If a motion profile is to be recorded for a new user activity, the user may be prompted to enter a name for the new user activity.

(76) At block **465**, a command is received to begin recording. At block **470**, measurements of accelerations are recorded. The measurements of accelerations are recorded while a user performs the user activity for which a motion profile is to be recorded.

(77) At block **475**, the process determines whether the recorded measurements define a unique pattern. In one embodiment, measurements of accelerations are recorded until a unique pattern can be determined. A unique pattern differentiates the recorded pattern from other motion profiles.

(78) If a unique pattern has not yet been identified, the process determines if the user has stopped the recording and/or motion, at block **480**. In one embodiment, if the user stops recording before such a unique pattern is identified, the system prompts the user to continue recording, at block **485**. The process then returns to block **470** to continue recording motion data. If the user has not stopped the recording, the process continues directly to block **470**. The time to determine a pattern may range from recording a single motion cycle, to recording many motion cycles, which may occur over a single second to minutes or even longer. In one embodiment, user input may be received to specify the period of a current motion cycle. For example, a user may push a button, make a certain movement, make a loud noise, etc. each time a new periodic human motion ends (e.g., each time a step is completed). This may reduce the number of motion cycles that need to be recorded in order to determine a pattern from the recorded measurements. Alternatively, the period of the motion cycle is determined without user input. In one embodiment, the system utilizes at least two full motion cycles to identify the pattern. Without any user input as to the period or motion type, it is likely that more than two motion cycles would be needed to identify the pattern.

(79) If at block **475**, a unique pattern has been identified, the process continues to block **490**. In one embodiment, the user is notified that the new activity pattern has been successfully identified. At block **490**, in one embodiment a motion cycle average may be determined for the activity. Once a unique pattern of accelerations is determined for the activity, at block **495**, the motion profile may be added to either an existing user activity or to a new user activity.

(80) The unique pattern of accelerations may also be used to determine (set) positive and/or negative events for the activity. For example, if the unique pattern of accelerations shows a repeated sharp acceleration peak along a dominant axis, a sharp acceleration peak along the dominant axis may be added as a new positive event and/or a gradual peak along the dominant axis may be added as a new negative event. If method **450** was initiated to calibrate an existing user profile, the calibration may include adding new positive and/or negative events to the existing positive and/or negative events. If method **450** was initiated to record a new activity, new positive and/or negative events may be assigned to facilitate future identification of the new activity. It is possible that the motion recording does not define a unique pattern even after a considerable time. In one embodiment, after a period the system may indicate to the user that the motion cycle matches an existing activity. The user may concur that the existing activity does match the attempted new motion cycle pattern. In that case, the motion cycle pattern may be used to adjust the motion cycle associated with the identified activity. Alternatively, in one embodiment the recording process may fail.

(81) FIG. 5 shows a state diagram for the behavior **500** of a system for monitoring user motion states, in accordance with one embodiment of the present invention. The system may have multiple operating modes (states) that are navigated between by processing logic that may comprise hardware (e.g., circuitry, dedicated logic, programmable logic, microcode, etc.), software (such as instructions run on a processing device), or a combination thereof. In one embodiment, behavior **500** is the behavior of the electronic device **100** or a subset of the device shown in FIG. 1. In one embodiment, behavior **500** is the behavior of the electronic device or inertial sensor(s) within motion identification system **200** of FIG. 2.

(82) The behavior **500** may include multiple operating modes for monitoring human activity: a

sleep mode, an entry mode, one or more active modes, and an exit mode. In alternative embodiments, more or fewer modes may be used. In one embodiment, only two modes are used: active mode and non-active mode. The active mode is entered once periodic human motions are detected, while the non-active mode is used for all other states. In alternative embodiments, multiple inactive modes and/or active modes are used. To navigate between modes, certain conditions must be met. The conditions may include exit conditions for terminating an active mode and entry conditions for initiating inactive modes. Each mode has one or more exit and entry conditions.

(83) Use of different conditions for different operating modes increases the reliability of the device that is monitoring the human activity. For example, once an object (e.g., a person) is moving, they are more likely to remain moving than to stop. Likewise, if a person is not moving, they are more likely not to move than to begin moving. Moreover, if a person is running, he is more likely to continue running than to begin bicycling. These principles can be applied by requiring more stringent conditions to be met for a device to initiate an active mode than to continue the active mode. The different modes may each have rules that reflect what is more likely to happen for subsequent measurements. This may reduce or eliminate the number of uncounted periodic human motions and/or false periodic human motion counts.

(84) Referring to FIG. 5, operating modes in one embodiment include a sleep mode **505**, an entry mode **515**, an active mode **525**, and an exit mode **535**. In one embodiment, the power level of the system or device is linked to these modes.

(85) The first mode is the sleep mode **505**. When no activity (acceleration) is detected, the system remains in sleep mode **505**. When acceleration is detected, an entry mode **515** is initiated. In one embodiment, in sleep mode **505** the inertial sensor has a slow sample rate, thereby reducing power consumption of the system. In one embodiment, in sleep mode **505** only those portions of the processor needed to monitor the accelerometer are awake, and the remaining parts of the processor are placed in a sleep mode.

(86) Once in entry mode **515**, in one embodiment the sampling rate of the inertial sensor is increased to ensure that acceleration is monitored to detect periodic human motions. In entry mode **515**, periodic human motions appropriate to all identifiable user activities may be monitored. Therefore, in one embodiment, the sampling rate is sufficiently high to properly detect the fastest possible activity. In another embodiment, the sampling rate is adjusted based on the actual observed motion level. For example, when the user is strolling, the sampling rate need not be as fast as when the user is utilizing gesture commands or riding a bicycle.

(87) When entry conditions are satisfied for a particular user activity, an appropriate active mode **525** is initiated. The sampling rate is then adjusted to be appropriate for the activity being detected, in one embodiment. In one embodiment, if no entry conditions for any of the identifiable user activities are detected in a period of time, sleep mode **505** is reinitiated. In another embodiment, sleep mode **505** is only initiated if no motion is detected.

(88) Once in the appropriate active mode **525**, acceleration data is monitored to count periodic human motions according to a predefined set of rules or motion criteria as discussed above. According to one of these criteria, periodic human motions are expected to occur within a set interval (e.g., within a cadence window). When a periodic human motion is counted within the set interval, then the current active mode **525** is continued. When a periodic human motion is not detected within the set interval, an expected periodic human motion has not occurred, and an exit mode **535** is initiated.

(89) In exit mode **535**, processing logic determines whether re-entry conditions are met. Reentry conditions are met when subsequent periodic human motions consistent with the last active mode are observed. By using an exit mode to verify that the activity has ceased, the system reduces the chances that a single stumble by the user triggers a full re-analysis of the motion. When the re-entry conditions are met, the appropriate active mode **525** is reinitiated. If the re-entry conditions are not

met within a certain time frame, the process initiates entry mode **515** again. From entry mode **515**, any appropriate active mode **525** may again be entered into if certain entry conditions are satisfied, or the process may return to sleep mode **505**.

(90) FIG. **6** illustrates a flow diagram for a method **600** of operating an electronic device in sleep mode, in accordance with one embodiment of the present invention. In one embodiment, method **600** corresponds to the sleep mode **505** of FIG. **5**. In one embodiment, the method **600** may begin when no relevant acceleration has been detected for a predetermined time interval, or when no periodic human motions have been detected for a predetermined time interval. In one embodiment, when no acceleration above a threshold value is detected for a set period of time, the sleep function is initiated. In another embodiment, when only motion signatures indicative of an activity that does not need to be monitored is detected, the sleep function is initiated. For example, when the motion signature of driving is detected, the sleep function may be initiated. The time period that elapses before the sleep mode is initiated may be fixed, or it may be adjusted automatically by processing logic or based on user input (e.g. in response to a user selection of desired battery longevity versus desired performance, or based on the last measured cadence window).

(91) Referring to FIG. **6**, method **600** begins with setting a sleep mode sampling rate (block **605**). In one embodiment, a low sampling rate is set. This reduces power consumption and prolongs battery life. In one embodiment, the sleep mode sampling rate is a fixed value. In alternative embodiments, the sleep mode sampling rate can be modified automatically by processing logic based on certain criteria such as time of day, user behavior patterns, etc., or based on user input.

(92) In one embodiment, a sampling function is periodically executed in sleep mode, wherein the sampling function samples acceleration data at a set sampling rate for a set time period. For example, the sampling function may be executed every ten seconds for the duration of one second, and a sampling rate of fifty measurements per second may be set for that one second of operation. In one embodiment, the sampling function repeats at a relatively slow rate (e.g., once every 10 seconds), and the sampling rate within the sampling function is relatively high (e.g., 50 Hz). The sampling function may be used to detect unwanted motion signatures, or to maintain a device in low power sleep mode, for example, while a user is driving in a car.

(93) In one embodiment, the sleep mode sampling rate is set to zero. The sleep mode sampling rate may be set to zero, for example, when an inertial sensor has ‘inertial wakeup’ functionality. Inertial wakeup functionality enables processing logic to switch from sleep mode to entry mode when an acceleration exceeding a set threshold is detected. The inertial wakeup may be used to simultaneously exit sleep mode and power-up additional functionality.

(94) At block **610**, measurements of acceleration data are taken. At block **615**, processing logic determines whether or not relevant acceleration is detected. Relevant acceleration includes acceleration that meets certain criteria. In one embodiment, the criteria include a lower threshold and an upper threshold. In alternative embodiments, other criteria may also be used, such as a requirement that acceleration be continuously measured for a preset time period.

(95) When no relevant acceleration is detected, or when the ‘inertial wakeup’ pin has not triggered (for inertial sensors having ‘inertial wakeup functionality’), sleep mode continues, and further measurements of acceleration data are taken at the set sleep mode sampling rate (block **610**). When acceleration is detected, sleep mode is terminated and entry mode is initiated (block **620**). In one embodiment, the acceleration that is detected and its rate of change must meet certain criteria to terminate sleep mode.

(96) FIG. **7A** illustrates a flow diagram for a method **700** of operating an electronic device in entry mode, in accordance with one embodiment of the present invention. In one embodiment, method **700** corresponds to the entry mode **515** of FIG. **5**. The entry mode may be initiated when a user first begins an activity in which periodic human motions may be detected. In one embodiment, the method **700** begins when any relevant acceleration is detected. In one embodiment, entry mode is initiated when a measurement of acceleration that meets certain criteria has been detected. In one

embodiment, method **700** is initiated when a sleep mode is terminated. In one embodiment, method **700** is performed concurrently by each of the activity identification logics **285** of FIG. **2** when the motion identification system **200** and/or the counting logic **260** of the electronic device are in entry mode.

(97) Referring to FIG. **7A**, method **700** begins by setting the sampling rate to an active sampling rate (block **704**). The active sampling rate is set to facilitate accurate measurements of motion states, and periodic human motions, and may be a fixed or a dynamically variable rate. A variable sampling rate may automatically adjust depending on detected motion frequency/level, a period of a detected motion cycle's cadence, may be user adjusted, may adjust based on applications being run by processing logic, or other aspects of the motion data or device state. The active sampling rate may be set to anywhere between about 10 and about 200 Hz in one embodiment. In one embodiment, the active sampling rate is set to about 15 to 40 Hz.

(98) At block **710**, a first periodic human motion is recognized. A periodic human motion, in one embodiment, is a motion cycle which includes at least two recognized states, at least one of which recurs. For example, the motion cycle may be motion A, B, C, repeating. A periodic human motion is recognized, in one embodiment, when motions A, B, C, A (or B, C, A, B) are identified. Since no previous periodic human motions have been measured, and there is no cadence window, the first periodic human motion may be recognized at any time. Once a first periodic human motion is recognized, a default cadence window is set (block **714**). The default cadence window may have a minimum and maximum such that periodic human motions will be counted for most or all possible motion cycle cadences. A different default cadence window may be set for each activity. In one embodiment, a separate instance of method **700** is run for each instance of activity identification logic.

(99) In one embodiment, an initial default value for the cadence window is set wide enough to accommodate all users. In one embodiment, the default cadence window is then dynamically adjusted to match the specific user. Processing logic may 'learn' (adapt to) a particular user, and may become more accurate as periodic human motions are counted. Processing logic that has the ability to learn or adapt to different users may create an individualized profile for each user. Multiple profiles may also be created for each user, the different profiles reflecting different user activities. For example, a first profile might be created for a user's running and a second profile may be created for a user's walking. Processing logic may switch between different profiles automatically or manually based on user input. In one embodiment, processing logic compares a current cadence and/or motion cycle pattern to stored profiles. When a current cadence or motion cycle pattern matches that of a stored profile, that profile may be activated.

(100) At block **720**, a buffered count is set to one. At block **724**, processing logic determines whether an additional periodic human motion is recognized. An additional periodic human motion may be recognized if the motion cycle meets all the necessary criteria. Different criteria may be used for each of the different user activities. One embodiment of these criteria is discussed below with reference to FIG. **10**.

(101) Returning to FIG. **7A**, if an additional periodic human motion is recognized, method **700** continues to block **744**. If no additional periodic human motions are recognized, then processing logic determines whether the time is still within the cadence window (block **730**). If there is still time within the cadence window, the process returns to block **724** to determine whether an additional periodic human motion is recognized. If the cadence window has closed, then the buffered count is reset to zero (block **734**). The process then continues to block **740**.

(102) At block **740**, processing logic determines whether any relevant acceleration is detected. If no relevant acceleration is detected, then sleep mode is initiated (block **742**). If some relevant acceleration is detected, then processing logic returns to block **710** to monitor acceleration data and attempt to identify a periodic human motion.

(103) If at block **724** an additional periodic human motion was recognized, the process continues to

block **744**. At block **744**, an additional periodic human motion is added to the buffered count. Processing logic then checks whether any negative events have been recognized (block **745**). A negative event is an indicator that the motion does not belong the activity category being tested. If a negative event is recognized, then the process continues to block **734**, and the buffered count is reset to zero. If no negative events are recognized, then the process continues to block **746**.

(104) At block **746** the process determines whether another user activity associated with a different instance of method **700** has been identified. That is, it determines whether another activity has been conclusively identified. If another user activity has been identified, then the buffer is emptied and the process ends. If no other user activity has been identified yet, then the process continues to block **748**.

(105) At block **748**, processing logic checks whether there are N periodic human motions in the buffered count. N may be preset, or may be based on a confidence interval detected. If not, the process returns to block **724** to continue in entry mode. When the number of periodic human motions in the buffered count reaches N, the buffered periodic human motions are added to a motion log, and an appropriate active mode is entered into (block **749**). The entry mode then terminates, and all buffers are reset to zero.

(106) FIG. 7B illustrates a flow diagram for a method **750** of operating an electronic device in entry mode, in accordance with another embodiment of the present invention. In one embodiment, method **750** corresponds to the entry mode **515** of FIG. 5. The entry mode may be initiated when a user first begins an activity in which periodic human motions may be detected. In one embodiment, the method **750** begins when any relevant acceleration is detected. In one embodiment, entry mode is initiated when a measurement of acceleration that meets certain criteria has been detected. In one embodiment, method **750** is initiated when a sleep mode is terminated.

(107) Referring to FIG. 7B, method **750** begins by setting the sampling rate to an active sampling rate (block **754**). The sampling rate, in one embodiment, depends on the highest sampling rate required by a potentially recognizable activity.

(108) At block **757**, a first periodic human motion is recognized for each identifiable user activity. Since no previous periodic human motions have been measured, and there is no cadence window, the first periodic human motion may be recognized at any time. Once a first periodic human motion is recognized, default cadence windows are set (block **760**). Default cadence windows may be set for each type of identifiable user activity.

(109) At block **763**, a buffered count is set to one for each of the identifiable user activities. At block **765**, processing logic determines whether additional periodic human motions are recognized for each of the identifiable user activities. Different criteria may be used to separately determine whether an additional periodic human motion is recognized for each of the user activities.

(110) For user activities for which an additional periodic human motion is recognized, method **750** continues to block **783**. Concurrently, for user activities for which no additional periodic human motion is recognized, the process continues to block **770**. At block **770**, the process determines whether the time is still within the appropriate cadence window for each appropriate user activity. If there is still time within the appropriate cadence window, the process returns to block **765** for that user activity. If the cadence window has closed, then the appropriate buffered count is reset to zero (block **775**). The process then continues to block **777**.

(111) At block **777**, processing logic determines whether any relevant acceleration is detected. If no relevant acceleration is detected for any of the user activities, then sleep mode is initiated (block **779**). If some relevant acceleration is detected for any user activity, then processing logic returns to block **757** to await recognition of another first periodic human motion for the appropriate user activity.

(112) If at block **765** an additional periodic human motion was recognized, the process continues to block **783** for the appropriate user activity, and an appropriate periodic human motion is added to an appropriate buffer count.

(113) At block **788**, processing logic checks whether any negative events have been recognized for each appropriate user activity. For user activities for which a negative event is recognized, the process continues to block **775**, and the appropriate buffered count is reset to zero. For user activities for which no negative event is recognized, the process continues to block **790**.

(114) At block **790** the process determines whether sufficient periodic human motions have been recognized to identify a current user activity. If sufficient periodic human motions have been recognized for a particular user activity, the process continues to block **795**. At block **795**, the entries in the appropriate buffered count are added to the motion log, and an active mode is initiated for the identified activity.

(115) FIG. **8** illustrates a flow diagram for a method **800** of operating an electronic device in an active mode, in accordance with one embodiment of the invention. In one embodiment, method **800** corresponds to the appropriate active mode **525** of FIG. **5**. The active mode may be initiated when a particular motion state has been identified. In one embodiment, method **800** is initiated when an entry mode is terminated, and/or when an exit mode is terminated.

(116) Referring to FIG. **8**, method **800** begins by setting a cadence window (block **810**). The cadence window may be set based on previous measurement data. In one embodiment, the cadence window is set based on a rolling average of motion cycle periods. In one embodiment, the cadence window may be identical to an appropriate cadence window used during entry mode. Once the cadence window is set, measurement data is checked to determine whether an additional periodic human motion is recognized (block **815**). If an additional periodic human motion is recognized, then it is added to the motion log (block **820**). If no additional periodic human motion is recognized, then the process determines whether a negative event has been recognized **822**. If a negative event has been recognized, the process continues to block **830**, and exit mode is initiated. If no negative event has been recognized, the process continues to block **825**.

(117) At block **825**, the process determines whether the current measurement was taken within the cadence window. If the cadence window is still open, the process returns to block **815**. If the cadence window has elapsed, then an expected periodic human motion was not identified, and an exit mode is initiated (block **830**).

(118) FIG. **9** illustrates a flow diagram for a method **900** of operating an electronic device in exit mode, in accordance with one embodiment of the present invention. In one embodiment, method **900** corresponds to the exit mode **535** of FIG. **5**. The exit mode may be entered into when an expected periodic human motion is not identified in an active mode.

(119) In one embodiment, the requirement(s) for changing from exit mode to an active mode are less strict than the requirement(s) for switching from entry mode to an active mode. Processing logic may assume that when a user has recently performed a periodic human motion, the user is most likely repeat the same periodic human motion. For example, a user who is inline skating is much more likely to continue skating movements than to break into a jog. Furthermore, momentary interruptions of activities occur when people stumble, or miss a step, or otherwise do something unexpected while continuing the underlying activity. Processing logic may also assume that if a user is currently inactive, it is most likely that the user will remain inactive. These assumptions may be implemented by imposing more stringent requirements to switch from entry mode to an active mode than to change from exit mode to an active mode. The requirements to remain in an active mode may be even less stringent than the requirements to initiate the active mode, whether from the entry mode or from the exit mode.

(120) An expected periodic human motion may not be identified, for example, when a user stops moving, when extraneous movements such as gestures are made that interfere with the periodic human motion count, or when a device orientation is changed as a periodic human motion occurs. In one embodiment, the exit mode assumes that a periodic human motion has been missed, so that if the exit mode determines that a user is still continuing the same activity, the originally uncounted periodic human motion is not missed.

(121) The process begins by initiating a timer (block **905**). The timer measures the amount of time that has passed since a periodic human motion has been identified. In one embodiment, the timer is a countdown timer that terminates exit mode when the timer reaches zero. In one embodiment, the timer starts counting when a cadence window minimum is reached, and stops counting when a cadence window maximum is reached. In an alternative embodiment, the timer starts counting as soon as the exit mode is initiated, and stops counting when a cadence window maximum is reached.

(122) At block **910**, a periodic human motion is added to a buffered count. At block **915**, processing logic determines whether the buffered count is equal to X, where X is the number of identified periodic human motions that, when reached, return processing logic to an appropriate active mode. In one embodiment, X is between 3 and 8. In one embodiment, the value of X is dependent upon the specific active mode that exit mode was initiated from. If the buffered count is equal to X, then the buffered periodic human motions are added to motion log and the previous (appropriate) active mode is reinitiated (block **920**). If the buffered count is not equal to X, then processing logic proceeds to block **925**.

(123) At block **925**, processing logic determines whether the timer has timed out (allotted time has elapsed). In one embodiment, the timer times out when no periodic human motions are counted within a cadence window. In one embodiment, the timer times out when no periodic human motions are counted in two or more cadence windows. If the allotted time has elapsed, then the buffered count is cleared, and entry mode is initiated (block **930**). If the allotted time has not elapsed, then processing logic determines whether a negative event has occurred (block **932**). If a negative event has occurred, the method returns to block **930**. If no negative event has occurred, the method proceeds to block **935**.

(124) At block **935**, processing logic determines whether an additional periodic human motion is recognized. If an additional periodic human motion is recognized, then the timer is reset (block **905**), the buffered count is incremented by one (block **910**), and on the process continues to block **915**. If a periodic human motion is not recognized, then processing logic returns to block **925** to determine whether the timer has elapsed.

(125) FIG. **10** illustrates a flow diagram for a method **1000** of recognizing a periodic human motion, in accordance with one embodiment of the present invention. In one embodiment, method **1000** may be executed by one or more of blocks **710** and **724** of FIG. **7A**, blocks **757** and **765** of FIG. **7B**, block **815** of FIG. **8** and block **935** of FIG. **9**. In one embodiment, method **1000** is performed by electronic device **100** of FIG. **1**, or the motion identification system **200** of FIG. **2**.

(126) Referring to FIG. **10**, the process begins with measurements of acceleration data being received (block **1005**). Measurements are taken according to a sampling rate, which may vary. In one embodiment, the sampling rate may range from one measurement per second to many measurements a second, depending on the operating mode being used.

(127) At processing block **1010**, in one embodiment measurements are filtered. Measurements can be filtered to remove high frequency data and/or low frequency data. In one embodiment, what data to filter depends on the type of user activity being detected. At processing block **1012**, in one embodiment the inertial sensor is oriented by assigning a dominant axis. Assigning a dominant axis may include calculating rolling averages of acceleration and assigning the dominant axis based on the rolling averages of acceleration. Assigning the dominant axis may also include determining which axis has the largest peak to peak difference. In one embodiment, filtering may simply remove acceleration data not along the dominant axis.

(128) At block **1015**, processing logic determines whether a measurement is within a cadence window. If the measurement is not within a cadence window, then no periodic human motion may be recognized or counted for that measurement (block **1040**). If the measurement is within the cadence window, the process continues to block **1017**.

(129) At block **1017**, processing logic determines whether motion criteria are met. For example, in

one embodiment the process may determine whether acceleration along the dominant axis is greater than a lower threshold. In one embodiment, the process may determine whether the measurement exceeds the rolling average by a set margin. In one embodiment, processing logic may determine whether acceleration along the dominant axis is greater than previous measurements. Other criteria than those mentioned herein may also be used.

(130) If all required motion criteria are met, then the appropriate periodic human motions are counted (block **1035**). In one embodiment, the data from the detected motion is also added to the rolling averages, as described above. Furthermore, as noted above, this process continues while the device is monitoring for periodic human motions.

(131) FIG. **11** illustrates a flow diagram for a method **1100** of determining and utilizing a motion state using an inertial sensor, in accordance with one embodiment of the present invention. The method may be performed by processing logic that may comprise hardware (e.g., circuitry, dedicated logic, programmable logic, microcode, etc.), software (such as instructions run on a processing device), or a combination thereof. In one embodiment, method **1100** is performed by the electronic device **100** of FIG. **1**. In one embodiment, method **1100** is performed by the motion identification system **200** of FIG. **2**.

(132) Referring to FIG. **11**, method **1100** begins with monitoring accelerations (block **1105**). Accelerations may be monitored with an inertial sensor, or other acceleration monitoring device. The monitored acceleration may include filtered and processed acceleration data, as described above. At block **1110**, the motion is identified as corresponding to one or more of a plurality of possible motion states based on the accelerations. In one embodiment, a single motion state is identified. In another embodiment, multiple possible motion states are identified, each with an accompanying confidence rating. For example, it may be determined that there is a 90% confidence that a user is walking and a 10% confidence that the user is hopping. The motion states include user activities (e.g. walking, bicycling, inline skating, using an elliptical machine, using a rowing machine, running, hopping, walking up stairs, etc.) as well as non-active motion states (e.g. standing, sitting, riding in a vehicle, being in an elevator, going on an escalator, etc.)

(133) At block **1115**, a user motion state identification service subscription list is scanned to determine whether any programs are subscribed to a motion related information service. If one or more programs are subscribed to the service, the method continues to block **1120**. Otherwise the method returns to block **1105** to continue monitoring motion states.

(134) At block **1120**, entries in the user motion state service subscription list are scanned to determine notification criteria. Examples of notification criteria include, a change in user motion state, a predetermined time interval, etc. If the criteria in an entry are satisfied, the method continues to block **1125**. Otherwise the method returns to block **1105**.

(135) At block **1125**, the program corresponding to the entry in the user motion state subscription list is notified of the identified user motion state. The method then returns to block **1105**.

(136) FIG. **12** illustrates a flow diagram for a method **1200** of using motion related information to modify program settings. The method may be performed by processing logic that may comprise hardware (e.g., circuitry, dedicated logic, programmable logic, microcode, etc.), software (such as instructions run on a processing device), or a combination thereof. In one embodiment, method **1200** is performed by the electronic device **100** of FIG. **1**. In one embodiment, method **1200** is performed by a program **290** that is coupled to the motion identification system **200** of FIG. **2**.

(137) Referring to FIG. **12**, method **1200** begins with a program receiving current user motion state information (block **1205**). In one embodiment, the program polls a motion identification system and/or a cache to receive the motion state data. In another embodiment, the motion state identification system sends the motion state data to the program without being polled. In one embodiment, the program subscribes to a user motion state identification service or other motion related information service. The motion identification system may send the user motion state identification to all programs that subscribe to the service when predefined conditions are satisfied.

For example, the motion identification system may send updates of a current user motion state whenever the current user motion state changes, or may send updates based on other subscription criteria.

(138) In one embodiment, a single user motion state is identified. In another embodiment, multiple different possible user motion states are identified, each with an accompanying confidence rating. For example, it may be determined that there is a 90% confidence that a user is walking and a 10% confidence that the user is riding in a car.

(139) In one embodiment, additional motion related information is received from the motion identification system. For example, the program may receive cadence information, dominant axis information, etc.

(140) At block **1215**, the program determines whether the motion state has changed. If the current motion state has not changed, then the method ends. If the current motion state has changed, the method continues to block **1220**.

(141) At block **1220**, the program determines whether to modify one or more of its settings based on the current motion state. One or more of the settings may also be adjusted based on the additional motion related information. The settings that are modified may depend on the type of program, and the change in motion state. For example, a music application or telephony application may adjust volume based on the identified motion state, a gesture application may alter the motions available, a screen may be turned off, a noise reduction system may be enabled, etc. If the new motion state leads to a change in settings, at block **1230**, the appropriate settings are altered in the program. The process then ends. If no change in settings is applicable, the method ends.

(142) FIG. **13** illustrates an exemplary block diagram of a specific machine in the exemplary form of a computer system **1300** that may implement the present invention. The exemplary computer system **1300** includes a processing device (processor) **1305**, a memory **1310** (e.g., read-only memory (ROM), flash memory, a storage device, a static memory, etc.), and an input/output **1315**, which communicate with each other via a bus **1320**. Embodiments of the present invention may be performed by the computer system **1300**, and/or by additional hardware components (not shown), or may be embodied in machine-executable instructions, which may be used to cause processor **1305**, when programmed with the instructions, to perform the method described above.

Alternatively, the method may be performed by a combination of hardware and software.

(143) Processor **1305** represents one or more general-purpose processing devices such as a microprocessor, central processing unit, or the like. More particularly, the processor **1305** may be a complex instruction set computing (CISC) microprocessor, reduced instruction set computing (RISC) microprocessor, very long instruction word (VLIW) microprocessor, or a processor implementing other instruction sets or processors implementing a combination of instruction sets. The processor **1305** may also be one or more special-purpose processing devices such as an application specific integrated circuit (ASIC), a field programmable gate array (FPGA), a digital signal processor (DSP), network processor, or the like.

(144) The present invention may be provided as a computer program product, or software, that may be stored in memory **1310**. Memory **1310** may include a machine-readable medium having stored thereon instructions, which may be used to program exemplary computer system **1300** (or other electronic devices) to perform a process according to the present invention. Other machine-readable mediums which may have instruction stored thereon to program exemplary computer system **1300** (or other electronic devices) include, but are not limited to, floppy diskettes, optical disks, CD-ROMs, and magneto-optical disks, ROMs, RAMs, EPROMs, EEPROMs, magnetic or optical cards, flash memory, or other type of media or machine-readable mediums suitable for storing electronic instructions.

(145) Input/output **1315** may provide communication with additional devices and/or components. In one embodiment, input/output **1315** may transmit data to and receive data from, for example, networked computers, servers, mobile devices, etc. Input/output **1315** may include a screen,

speaker, or other mechanism to communicate with the user, as well as buttons, keys, touch sensitive areas or other means of enabling the user to provide input to the device. In one embodiment, the device further includes networking **1320**, which enables device to communicate with a server (not shown) or another computer. In one embodiment, the device does not include any user interface features, and the input/output **1315** is designed to interact with a computer system, local or remote, to which the device can be connected. For example, the user may perform configuration and interactions with the device via a web interface, or a local computer program.

(146) In the foregoing description, numerous specific details have been set forth such as examples of specific systems, languages, components, etc. in order to provide a thorough understanding of the present invention. It will be apparent, however, to one skilled in the art that these specific details need not be employed to practice the present invention. In other instances, well known materials or methods have not been described in detail in order to avoid unnecessarily obscuring the present invention. The invention has been described with reference to specific exemplary embodiments. It will, however, be evident that various modifications and changes may be made thereto without departing from the broader spirit and scope of the invention as set forth in the appended claims. The specification and drawings are, accordingly, to be regarded in an illustrative rather than a restrictive sense.

Claims

1. A method for processing motion information, comprising: operating, by an electronic device, in a first mode corresponding to a first sampling rate, wherein the first mode is a sleep mode; obtaining, by the electronic device, acceleration data from a sensor; based on the obtained acceleration data, operating, by the electronic device, in a second mode corresponding to a second sampling rate, wherein the second mode is an entry mode, wherein the second sampling rate is higher than the first sampling rate, and wherein operating in the second mode consumes more power than operating in the first mode; operating, by the electronic device, in a third mode, wherein the third mode is a first active mode out of a plurality of active modes, and wherein the first active mode corresponds to a user of the electronic device performing a first activity out of a plurality of activities; and in response to a lack of periodic motion being detected while in the third mode, transitioning, by the electronic device, from the third mode to a fourth mode, wherein the fourth mode is an exit mode corresponding to a lack of periodic motion by the user of the electronic device; wherein the method further comprises: determining, by the electronic device, based on an analysis of motion information obtained by the electronic device while in the entry mode, whether entry conditions for transitioning from the entry mode to the first active mode are met; and based on the entry conditions being met, transitioning, by the electronic device, from the entry mode to the first active mode; wherein the method further comprises: determining, by the electronic device, based on an analysis of motion information obtained by the electronic device while in the exit mode, whether re-entry conditions for transitioning from the exit mode to the first active mode are met; and based on the re-entry conditions being met, transitioning, by the electronic device, from the exit mode to the first active mode; wherein the entry conditions for transitioning from the entry mode to the first active mode are more stringent than the re-entry conditions for transitioning from the exit mode to the first active mode.

2. The method according to claim 1, wherein the entry conditions for transitioning from the entry mode to the first active mode include detecting periodic motions based on the motion information obtained by the electronic device while in the entry mode.

3. The method according to claim 1, further comprising: remaining in the sleep mode while no acceleration is detected; and wherein the entry mode is initiated in response to acceleration being detected.

4. The method according to claim 1, wherein, during operation in the sleep mode, portions of a

processor for monitoring the sensor are awake and other portions of the processor are in a sleep state.

5. The method according to claim 1, wherein, in the entry mode, acceleration is monitored to detect periodic motions corresponding to different activities, and wherein the second sampling rate is set for detecting a fastest activity of the different activities.

6. The method according to claim 1, wherein, in the entry mode, the second sampling rate is adjusted based on an observed motion level.

7. The method according to claim 1, wherein each of the plurality of active modes has a respective sampling rate corresponding to a respective activity.

8. The method according to claim 1, further comprising: transitioning from the second mode to the first mode based on no identifiable activity being detected in a period of time.

9. The method according to claim 1, further comprising: transitioning from the first active mode to the exit mode based on a periodic motion not being detected within a set interval.

10. The method according to claim 1, further comprising: transitioning from the exit mode back to the first active mode based on reentry conditions being met within a set timeframe.

11. The method according to claim 1, further comprising: transitioning from the exit mode to the second mode based on reentry conditions not being met within a set timeframe.

12. The method according to claim 1, further comprising: transitioning from the second mode to the first mode based on entry conditions for the plurality of active modes not being met.

13. An electronic device for processing motion information, comprising: a sensor configured to generate acceleration data; and a processor, configured to: operate the electronic device in a first mode corresponding to a first sampling rate, wherein the first mode is a sleep mode; obtain the acceleration data from the sensor; based on the obtained acceleration data, operate the electronic device in a second mode corresponding to a second sampling rate, wherein the second mode is an entry mode, wherein the second sampling rate is higher than the first sampling rate, and wherein operating in the second mode consumes more power than operating in the first mode; operate the electronic device in a third mode, wherein the third mode is a first active mode out of a plurality of active modes; wherein the first active mode corresponds to a user of the electronic device performing a first activity out of a plurality of activities; and in response to a lack of periodic motion being detected while in the third mode, transition the electronic device from operating in the third mode to operating in a fourth mode, wherein the fourth mode is an exit mode corresponding to a lack of periodic motion by the user of the electronic device; wherein the processor is further configured to: determine, based on an analysis of motion information obtained by the electronic device while in the entry mode, whether entry conditions for transitioning from the entry mode to the first active mode are met; and based on the entry conditions being met, transition the electronic device from the entry mode to the first active mode; wherein the processor is further configured to: determine, based on an analysis of motion information obtained by the electronic device while in the exit mode, whether re-entry conditions for transitioning from the exit mode to the first active mode are met; and based on the re-entry conditions being met, transition the electronic device from the exit mode to the first active mode; wherein the entry conditions for transitioning from the entry mode to the first active mode are more stringent than the re-entry conditions for transitioning from the exit mode to the first active mode.

14. The electronic device according to claim 13, wherein the entry conditions for transitioning from the entry mode to the first active mode include detecting periodic motions based on the motion information obtained by the electronic device while in the entry mode.

15. A non-transitory computer-readable medium having processor-executable instructions stored thereon for processing motion information, wherein the processor-executable instructions, when executed, facilitate: operating an electronic device in a first mode corresponding to a first sampling rate, wherein the first mode is a sleep mode; obtaining acceleration data from a sensor; based on the obtained acceleration data, operating the electronic device in a second mode corresponding to a

second sampling rate, wherein the second mode is an entry mode, wherein the second sampling rate is higher than the first sampling rate, and wherein operating in the second mode consumes more power than operating in the first mode; operating in a third mode, wherein the third mode is a first active mode out of a plurality of active modes, and wherein the first active mode corresponds to a user of the electronic device performing a first activity out of a plurality of activities; and in response to a lack of periodic motion being detected while in the third mode, transitioning the electronic device from operating in the third mode to operating in a fourth mode, wherein the fourth mode is an exit mode corresponding to a lack of periodic motion by the user of the electronic device; wherein the processor-executable instructions, when executed, further facilitate:

determining, based on an analysis of motion information obtained by the electronic device while in the entry mode, whether entry conditions for transitioning from the entry mode to the first active mode are met; and based on the entry conditions being met, transitioning the electronic device from the entry mode to the first active mode; wherein the processor-executable instructions, when executed, further facilitate: determining, based on an analysis of motion information obtained by the electronic device while in the exit mode, whether re-entry conditions for transitioning from the exit mode to the first active mode are met; and based on the re-entry conditions being met, transitioning the electronic device from the exit mode to the first active mode; wherein the entry conditions for transitioning from the entry mode to the first active mode are more stringent than the re-entry conditions for transitioning from the exit mode to the first active mode.

16. The non-transitory computer-readable medium according to claim 15, wherein the entry conditions for transitioning from the entry mode to the first active mode include detecting periodic motions based on the motion information obtained by the electronic device while in the entry mode.

17. The method according to claim 1, further comprising: determining, by the electronic device, based on an analysis of motion information obtained by the electronic device while in the first active mode, whether conditions for remaining in the first active mode are met; and based on the conditions for remaining in the first active mode being met, remaining, by the electronic device, in the first active mode; wherein the conditions for remaining in the first active mode are less stringent than the re-entry conditions.
