

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250263112

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

YOSHIDA; Keita et al.

MOTOR CONTROL DEVICE, ELECTRIC ACTUATOR PRODUCT, AND ELECTRIC POWER STEERING DEVICE

Abstract

A motor control device including: a current command value calculation unit configured to calculate a current command value for driving a motor; a current value detection unit configured to detect current flowing through the motor; a current control unit configured to output a first voltage command value according to deviation between a current detected value, the current detected value being a detected value of current detected by the current value detection unit, and the current command value; a voltage disturbance control unit configured to calculate a second voltage command value by adding output from a delay element to the first voltage command value and also input the second voltage command value to the delay element; and a driving circuit configured to drive the motor, based on the second voltage command value.

Inventors: YOSHIDA; Keita (Tokyo, JP), HOSHI; Yuzuru (Fujisawa-shi, Kanagawa, JP), SUGAWARA; Takayoshi (Tokyo, JP)

Applicant: NSK LTD. (Tokyo, JP)

Family ID: 1000008616410

Assignee: NSK LTD. (Tokyo, JP)

Appl. No.: 19/105569

**Filed (or PCT
Filed):** May 19, 2023

PCT No.: PCT/JP2023/018754

Foreign Application Priority Data

JP 2022-142039

Sep. 07, 2022

Publication Classification

Int. Cl.: B62D5/04 (20060101)

U.S. Cl.:

CPC B62D5/0463 (20130101); B62D5/0409 (20130101);

Background/Summary

TECHNICAL FIELD

[0001] The present invention relates to a motor control device, an electric actuator product, and an electric power steering device.

BACKGROUND ART

[0002] In PTL 1 described below, a technology for compensating for back electromotive voltage by estimating the back electromotive voltage, based on a back electromotive voltage constant and motor rotational speed and adding a correction value canceling the back electromotive voltage to a voltage command value (hereinafter, sometimes referred to as “feedforward-type back electromotive voltage compensation”) is described.

CITATION LIST

Patent Literature

[0003] JP 2017-175834 A

SUMMARY OF INVENTION

Technical Problem

[0004] There has been a problem in that the feedforward-type back electromotive voltage compensation has a low robustness against disturbance factors, such as variation in motor characteristics caused by an individual difference of a motor to be used and change in physical properties due to temperature change or aging.

[0005] An object of the present invention is to provide a motor control device the robustness of which against disturbance factors, such as variation in motor characteristics caused by an individual difference of a motor to be used and change in physical properties due to temperature change or aging, is improved.

Solution to Problem

[0006] In order to achieve the above-described object, according to an aspect of the present invention, there is provided a motor control device including: a current command value calculation unit configured to calculate a current command value for driving a motor; a current value detection unit configured to detect current flowing through the motor; a current control unit configured to output a first voltage command value according to deviation between a current detected value, the current detected value being a detected value of current detected by the current value detection unit, and the current command value; a voltage disturbance control unit configured to calculate a second voltage command value by adding output from a delay element to the first voltage command value and also input the second voltage command value to the delay element; and a driving circuit configured to drive the motor, based on the second voltage command value.

[0007] According to another aspect of the present invention, there is provided an electric actuator product including: the motor control device described above; and a motor controlled by the motor control device.

[0008] According to still another aspect of the present invention, there is provided an electric power steering device including: the motor control device described above; and a motor controlled by the motor control device, wherein the electric power steering device provides a steering system of a vehicle with a steering assist force, using the motor.

[0009] According to the present invention, it is possible to provide a motor control device the robustness of which against disturbance factors, such as variation in motor characteristics caused by an individual difference of a motor to be used and change in physical properties due to temperature change or aging, is improved.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0010] FIG. 1 is a configuration diagram illustrative of an outline of an example of an electric power steering device of an embodiment;

[0011] FIG. 2 is a block diagram illustrative of an example of a functional configuration of a steering assist function performed by a controller illustrated in FIG. 1;

[0012] FIG. 3 is a block diagram in which a first example of a system in which a motor is driven based on a current command value is represented by transfer functions;

[0013] FIGS. 4A and 4B are a Bode plot of an example of a frequency characteristic when a numerator of a common term in a transfer function of the system in FIG. 3 is set to 1;

[0014] FIGS. 5A and 5B are a Bode plot of an example of a control filter 52 in FIG. 3;

[0015] FIGS. 6A and 6B are a Bode plot of an example of a transfer function obtained by removing transfer functions of a delay element 56 and a filter 54 from the numerator of the common term in the transfer function of the system in FIG. 3;

[0016] FIGS. 7A and 7B are a Bode plot of an example of a transfer function of a component representing influence of disturbance voltage Δv on motor current i ;

[0017] FIGS. 8A and 8B are a Bode plot illustrative of a simulation result of a comparative example;

[0018] FIGS. 9A and 9B are a Bode plot illustrative of a simulation result of the embodiment;

[0019] FIG. 10 is a block diagram in which a second example of the system in which the motor is driven based on the current command value is represented by transfer functions;

[0020] FIG. 11 is a block diagram in which a third example of the system in which the motor is driven based on the current command value is represented by transfer functions; and

[0021] FIG. 12 is a configuration diagram illustrative of an outline of an example of a linear motion table device in which the motor control device of the present invention is used.

DESCRIPTION OF EMBODIMENTS

[0022] Embodiments of the present invention will be described in detail with reference to the drawings. Note that the embodiments of the present invention to be described below indicate devices and methods to embody the technical idea of the present invention by way of example, and the technical idea of the present invention does not limit the constitution, arrangements, and the like of the constituent components to those described below. The technical idea of the present invention can be subjected to a variety of alterations within the technical scope prescribed by the claims described in CLAIMS.

(Configuration)

[0023] FIG. 1 is a configuration diagram illustrative of an outline of an example of an electric power steering device of an embodiment. A steering shaft (steering wheel shaft) 2 of a steering wheel 1 is connected to steered wheels 8L and 8R by way of a reduction gear (worm gear) 3 that constitutes a speed reduction mechanism, universal joints 4a and 4b, a pinion rack mechanism 5, and tie rods 6a and 6b and further via hub units 7a and 7b.

[0024] The pinion rack mechanism 5 includes a pinion 5a that is coupled to a pinion shaft to which steering force is transmitted from the universal joint 4b and a rack 5b that meshes with the pinion 5a, and converts rotational motion transmitted to the pinion 5a to linear motion in the vehicle width

direction by means of the rack **5b**. To the steering shaft **2**, a torque sensor **10** configured to detect steering torque T_h is disposed. To the steering shaft **2**, a steering angle sensor **14** configured to detect a steering angle θ_h of the steering wheel **1** is also disposed.

[0025] A motor **20** configured to assist steering force of the steering wheel **1** is also connected to the steering shaft **2** via the reduction gear **3**. To a controller **30** configured to control the electric power steering (EPS) device, power is supplied from a battery **13** and an ignition key signal is also input by way of an ignition (IGN) key **11**.

[0026] Note that means for providing a steering assist force is not limited to a motor, and various types of actuators can be used.

[0027] The controller **30** is an electronic control unit (ECU) configured to perform calculation of a current command value of an assist control command, based on steering torque T_h detected by the torque sensor **10**, vehicle speed V_h detected by a vehicle speed sensor **12**, and a steering angle θ_h detected by the steering angle sensor **14** and control current to be supplied to the motor **20** in accordance with a voltage control command value V_{ref} obtained by performing compensation and the like on the calculated current command value.

[0028] Note that the steering angle sensor **14** is not an essential component and the steering angle θ_h may be calculated by adding a torsion angle of a torsion bar in the torque sensor **10** to a rotation angle acquired from a rotation angle sensor configured to detect a rotation angle of the rotation shaft of the motor **20**.

[0029] In addition, a turning angle of the steered wheels **8L** and **8R** may be used in place of the steering angle θ_h . The turning angle may be detected by, for example, detecting a displacement amount of the rack **5b**.

[0030] The controller **30** includes, for example, a computer including a processor and peripheral components, such as a storage device. The processor may be, for example, a central processing unit (CPU) or a micro-processing unit (MPU).

[0031] The storage device may include one of a semiconductor storage device, a magnetic storage device, and an optical storage device. The storage device may include registers, a cache memory, or a memory, such as a read only memory (ROM) and a random access memory (RAM), that is used as a main storage device.

[0032] Functions of the controller **30**, which will be described below, are achieved by, for example, the processor of the controller **30** executing computer programs stored in the storage device.

[0033] Note that the controller **30** may be formed by use of dedicated hardware for executing each type of information processing that will be described below.

[0034] For example, the controller **30** may include functional logic circuits that are set in a general-purpose semiconductor integrated circuit. For example, the controller **30** may have a programmable logic device (PLD), such as a field-programmable gate array (FPGA), or the like.

[0035] Next, with reference to FIG. 2, an example of a functional configuration of a steering assist function performed by the controller **30** will be described.

[0036] The steering torque T_h and the vehicle speed V_h are input to a current command value calculation unit **41** configured to calculate a current command value I_{ref0} . The current command value calculation unit **41** calculates the current command value I_{ref0} that is a control target value of current to be supplied to the motor **20**, using an assist map or the like, based on the input steering torque T_h and vehicle speed V_h .

[0037] An adder **42A** adds a compensation signal CM from a compensation signal generation unit **44** to the current command value I_{ref0} and thereby calculates a current command value $I_{ref} = I_{ref0} + CM$, and inputs the current command value I_{ref} to a current limiting unit **43**. A characteristic compensation of the steering system is performed by adding the compensation signal CM , and convergence, an inertia characteristic, and the like are improved. The compensation signal generation unit **44** adds convergence **44-1**, inertia **44-2**, and self-aligning torque (SAT) **44-3** to one another by adders **44-4** and **44-5** and thereby calculates the compensation signal CM .

[0038] A current command value I_{refm} the maximum current of which is limited by the current limiting unit **43** is input to a subtracter **42B**, deviation $\Delta I (=I_{refm}-I_m)$ between the current command value I_{refm} and a fed-back motor current value I_m is calculated, and the deviation ΔI is input to a proportional-integral (PI) control unit **45** for characteristic improvement in steering operation. A voltage control command value V_{ref} the characteristics of which have been improved in the PI control unit **45** is input to a PWM control unit **46**, and further, the motor **20** is PWM-driven via an inverter **47** serving as a driving unit. The current value I_m of the motor **20** is detected by a motor current detector **48** and fed back to the subtracter **42B**.

[0039] Note that the controller **30** may perform vector control in which a q-axis current command value that is a component for generating torque and a d-axis current command value that is a component for generating a magnetic field are calculated as the current command values I_{ref} and a voltage command value is generated based on deviation between a motor current detected value of the q-axis and the q-axis current command value and deviation between a motor current detected value of the d-axis and the d-axis current command value.

[0040] FIG. **3** is a block diagram in which a system in which the motor **20** is driven based on the current command value I_{ref} is represented by transfer functions. The current command value I_{ref} goes through a control filter ($G_{ref}(s)$) **50** and is input to a subtracter **51**, and the subtracter **51** calculates deviation between output from the control filter **50** and the current value I_m of the motor **20** detected by the motor current detector **48**. A control filter ($A(s)$) **52** calculates a first voltage command value according to the deviation between the output from the control filter **50** and the current value I_m of the motor **20** and inputs the calculated first voltage command value to an adder **53**. The control filter **52** is an example of a “current control unit” described in the claims.

[0041] The adder **53** calculates a second voltage command value by adding output from the adder **53** that is delayed by a delay element (G_{dly}) **55** to the first voltage command value and integrating the first voltage command value. The adder **53** is an example of a “voltage disturbance control unit” described in the claims.

[0042] The delay element **55** may be a delay element that provides a delay equivalent to, for example, a length of the control cycle in current control of motor current of the motor **20** performed by the controller **30**. For example, the adder **53** calculates the second voltage command value by adding an output value from the adder **53** in a previous cycle in the current control to the first voltage command value in a current cycle.

[0043] The output from the adder **53** goes through a filter ($G_{sub.LPF}(s)$) **54** configured to reduce noise in the second voltage command value and is input to the delay element **55** and a delay element ($GDLY$) **56**. That is, the filter **54** is a filter configured to reduce noise in an added value of the first voltage command value and the output from the delay element **55**. The filter **54** may be, for example, a low-pass filter. When detected noise in the current value I_m of the motor **20** detected by the motor current detector **48** is negligible, the filter **54** may be omitted.

[0044] The delay element **56** may be a delay element that provides a delay equivalent to a hardware delay in the controller **30**. For example, the delay provided by the delay element **56** may be a delay after the current value I_m of the motor **20** is detected by the motor current detector **48** until a PWM signal from the PWM control unit **46** is output using the detected current value I_m .

[0045] From and to the output from the delay element **56**, back electromotive voltage EMF of the motor is subtracted and disturbance voltage Δv is also added by a calculation unit **57**. The calculation unit **57** is a calculation unit implemented by modeling influence of back electromotive voltage EMF actually occurring in the motor on the output (control voltage) from the delay element **56**.

[0046] A calculation result of the calculation unit **57** is converted to motor current i by being divided by impedance $E(s)=L.Math.s+R$ of the motor **20** by an electrical characteristic unit ($1/E(s)$) **58** of the motor **20**. Note that the constants L and R are an inductance value and a resistance value of the motor **20**, respectively.

[0047] The motor current i is converted to torque τ by being multiplied by a torque coefficient (K_t) **59**. The torque τ is converted to a motor rotation angle θ by a mechanical characteristic unit ($1/M(s)$) **61**. A denominator of a transfer function of the mechanical characteristic unit **61** is, for example, $M(s) = J s^2 + (D + G_{sub} CF) s + K$, where the constants J , D , $G_{sub} CF$, and K are an inertia moment, a viscosity coefficient, a coulomb friction coefficient, and a spring coefficient of the motor, respectively.

$$i = \frac{A(s)G_{\text{LPF}}(s)\text{GDLY}}{(1 - G_{\text{LPF}}(s)\text{Gdly})E(s) + \frac{A(s)G_{\text{LPF}}(s)\text{GDLY} + \frac{(1 - G_{\text{LPF}}(s)\text{Gdly})\text{KeKts}}{M(s)}}{r}} \quad (1)$$

negligible.

[0051] In the present embodiment, a characteristic of a transfer function of the control filter **52** is set in such a way that variation in a frequency response of a transfer function obtained by removing the transfer function (GDLY) of the delay element **56** and the transfer function (G.sub.LPF(s)) of the filter **54** from a numerator of the common term in the above formula (1)

$$[00005][\text{Math. 5}] \frac{A(s)}{(1 - G_{\text{LPF}}(s)G_{\text{dly}})E(s) + A(s)G_{\text{LPF}}(s)GDLY + \frac{(1 - G_{\text{LPF}}(s)G_{\text{dly}})KeKts}{M(s)}}$$

is small (that is, the transfer function has a flat frequency characteristic) and a transfer function of a component representing influence of the disturbance voltage Δv on the motor current i

$$[00006][\text{Math. 6}] \frac{A(s)G_{\text{LPF}}(s)GDLY}{(1 - G_{\text{LPF}}(s)G_{\text{dly}})E(s) + A(s)G_{\text{LPF}}(s)GDLY + \frac{(1 - G_{\text{LPF}}(s)G_{\text{dly}})KeKts}{M(s)}} \left(\frac{1 - G_{\text{LPF}}(s)G_{\text{dly}}}{A(s)G_{\text{LPF}}(s)GDLY} \right)$$

has a characteristic of a high-pass filter (that is, the transfer function has a characteristic of attenuating low frequency components).

[0052] The transfer function of the control filter (A(s)) **52** may be set as, for example, the following formula.

$$[00007][\text{Math. 7}] A(s) = Kp(1 + \frac{c}{2s} + \frac{s}{2c})$$

[0053] The above formula is an example of a formula representing a PID (proportional-integral-derivative) controller, and characteristics of the transfer function of the control filter **52** can be appropriately adjusted by changing, for example, parameters Kp, ζ , and ω_c .

[0054] When the transfer function of the control filter **52** is set in this way, variation in a frequency response of the transfer function obtained by removing the transfer function (GDLY) of the delay element **56** and the transfer function (G.sub.LPF(s)) of the filter **54** from the numerator of the common term becomes small, and an excellent response characteristic that is hardly influenced by frequency of the current command value Iref can be achieved.

[0055] In addition, when the vector control is performed, back electromotive voltage and an interference term between a d-axis component and a q-axis component can be treated as a signal that has a low frequency (for example, less than or equal to 10 Hz) approximately equal to a steering frequency of the steering wheel **1** in a dq-axis rotational coordinate system. Thus, the feature that the transfer function of the component representing influence of the disturbance voltage Δv on the motor current i has a characteristic of a high-pass filter with a cutoff frequency that attenuates low frequency components enables influence of the back electromotive voltage and other disturbance voltages to be suppressed.

[0056] For example, when a transfer function when the numerator of the common term in the transfer function expressed by the above formula (1) is replaced by 1

$$[00008][\text{Math. 8}] \frac{1}{(1 - G_{\text{LPF}}(s)G_{\text{dly}})E(s) + A(s)G_{\text{LPF}}(s)GDLY + \frac{(1 - G_{\text{LPF}}(s)G_{\text{dly}})KeKts}{M(s)}}$$

[0057] has a frequency characteristic illustrated as an example in FIGS. **4A** and **4B**, in order to reduce variation in the frequency response of the transfer function obtained by removing the transfer functions of the delay element **56** and the filter **54** (GDLY and G.sub.LPF(s)) from the numerator of the common term

$$[00009][\text{Math. 9}] \frac{A(s)}{(1 - G_{\text{LPF}}(s)G_{\text{dly}})E(s) + A(s)G_{\text{LPF}}(s)GDLY + \frac{(1 - G_{\text{LPF}}(s)G_{\text{dly}})KeKts}{M(s)}},$$

the transfer function A(s) of the control filter **52** is set in such a way that the transfer function A(s) has an inverse characteristic to the frequency characteristic illustrated as an example in FIGS. **4A** and **4B**.

[0058] FIGS. **5A** and **5B** are a Bode plot of an example of the control filter **52** that is set in such a way as to have an inverse characteristic to the frequency characteristic of the denominator of the

common term.

[0059] When the frequency characteristic of the control filter **52** is set as illustrated in FIGS. **5A** and **5B**, the frequency characteristic of the transfer function obtained by removing the transfer functions of the delay element **56** and the filter **54** (GDLY and G.sub.LPF(s)) from the numerator of the common term becomes a frequency characteristic as illustrated in FIGS. **6A** and **6B**.

[0060] As illustrated in FIGS. **6A** and **6B**, variation in the frequency response of the transfer function obtained by removing the transfer functions of the delay element **56** and the filter **54** (GDLY and G.sub.LPF(s)) from the numerator of the common term is suppressed, and a comparatively flat frequency characteristic is achieved.

[0061] In addition, when the frequency characteristic of the control filter **52** is set as illustrated in FIGS. **5A** and **5B**, the transfer function of the component representing the influence of the disturbance voltage Δv on the motor current i

[00010][Math . 10]
$$\frac{A(s)G_{LPF}(s)GDLY}{(1 - G_{LPF}(s)Gdly)E(s) + A(s)G_{LPF}(s)GDLY + \frac{(1 - G_{LPF}(s)Gdly)KeKts}{M(s)}} \left(\frac{1 - G_{LPF}(s)Gdly}{A(s)G_{LPF}(s)GDLY} \right)$$

[0062] becomes a transfer function as illustrated in FIGS. **7A** and **7B**. The feature that the transfer function of the component representing the influence of the disturbance voltage Δv on the motor current i has a characteristic of a high-pass filter enables influence of the back electromotive voltage and other disturbance voltages to be suppressed, as described above.

[0063] Next, with reference to FIGS. **8A**, **8B**, **9A**, and **9B**, advantageous effects of the embodiment will be described. FIGS. **8A** and **8B** are a Bode plot illustrative of simulation results of the frequency characteristic of the motor current i with respect to the current command value I_{ref} when a conventional feedforward-type back electromotive voltage compensation is performed as a comparative example, and FIGS. **9A** and **9B** are a Bode plot illustrative of simulation results of the frequency characteristic of the motor current i with respect to the current command value I_{ref} when the motor current control by the controller **30** of the embodiment is performed.

[0064] Solid lines indicate reference frequency characteristics, dashed lines indicate frequency characteristics at a normal temperature, dotted lines indicate frequency characteristics at -40°C. , and dashed-dotted lines indicate frequency characteristics at 100°C.

[0065] When FIG. **8A** and FIG. **9A** are compared, it is revealed that while in the case where the conventional feedforward-type back electromotive voltage compensation is performed, reductions in the gain occur in a frequency band lower than or equal to 100 Hz due to influence of a low-pass filter suppressing influence of current detection noise, in the case where the motor current control according to the embodiment is performed, reductions in the gain are suppressed in the frequency band less than or equal to 100 Hz.

[0066] In addition, it is also revealed that in the case where the motor current control according to the embodiment is performed, change in the gain in association with change in temperature is suppressed in the low frequency band. In addition, the higher the temperature is, the better variation in the gain is suppressed. An electric actuator product and an electric power steering device are often operated in normal temperature conditions or high temperature conditions rather than in extremely low temperature conditions since the electric actuator product and the electric power steering device generate heat by themselves due to energization. Characteristics of the motor current control of the embodiment are characteristics suitable for such operation conditions.

(Variation 1)

[0067] FIG. **10** is a block diagram in which a second example of the system in which the motor **20** is driven based on the current command value I_{ref} is represented by transfer functions. The system of the second example may separately include, in place of the filter (G.sub.LPF(s)) **54** in FIG. **3**, a filter (G.sub.LPF(s)) **54a** configured to reduce noise in the output from the control filter (A(s)) **52** (that is, the first voltage command value) and a filter (G.sub.LPF(s)) **54b** configured to reduce noise in the output from the delay element (Gdly) **55**.

[0068] For example, it may be configured such that by arranging the filter **54a** between the control filter **52** and the adder **53** and also arranging the filter **54b** between the delay element **55** and the adder **53**, the first voltage command value having noise reduced by the filter **54a** and the output from the delay element **55** having noise reduced by the filter **54b** are added to each other by the adder **53** and the second voltage command value is thereby calculated.

[0069] In addition, it may be configured such that the filter **54a** is arranged at the preceding stage of the control filter **52** and the output from the subtracter **51** having noise reduced by the filter **54a** is input to the control filter **52**. Such a configuration enables noise in the output from the control filter **52** (that is, the first voltage command value) to be reduced by the filter **54a**. Likewise, it may be configured such that the filter **54b** is arranged at the preceding stage of the delay element **55** and the output from the adder **53** having noise reduced by the filter **54b** is input to the delay element **55**. Such a configuration enables noise in the output from the delay element **55** to be reduced by the filter **54b**.

(Variation 2)

[0070] FIG. **11** is a block diagram in which a third example of the system in which the motor **20** is driven based on the current command value I_{ref} is represented by transfer functions.

[0071] In place of the control filter ($A(s)$) **52** in FIG. **10**, a control filter ($A(s)$) **52a** similar to the control filter **52** may be disposed at the preceding stage of the subtracter **51** (that is, between the control filter ($G_{ref}(s)$) **50** and the subtracter **51**), and a control filter ($A(s)$) **52b** similar to the control filter **52** may also be disposed in a feedback path of the current value I_m detected by the motor current detector **48** (that is, between the motor current detector **48** and the subtracter **51**). Such a configuration is equivalent to the transfer function of the system illustrated in FIG. **10**.

[0072] In addition, the system of the third example may separately include, in place of the filter ($G_{sub.LPF}(s)$) **54a**, a filter ($G_{sub.LPF}(s)$) **54a1** configured to reduce noise in the output from the control filter **52a** and a filter ($G_{sub.LPF}(s)$) **54a2** configured to reduce noise in the output from the control filter **52b**. The filter **54a1** reduces noise in the current command value I_{ref} , and the filter **54a2** reduces noise in the current detected value I_m .

[0073] A sequence of connection of the control filter **50**, the control filter **52a**, and the filter **54a1** is not limited to the sequence in FIG. **11**, and, for example, it may be configured such that the filter **54a1** is disposed at the succeeding stage of the control filter **50** to which the current command value I_{ref} is input and the control filter **52a** is also disposed at the succeeding stage of the filter **54a1** and the output from the control filter **52a** is input to the subtracter **51**.

[0074] In addition, it may be configured such that the control filter **50** is disposed at the succeeding stage of the control filter **52a** to which the current command value I_{ref} is input and the filter **54a1** is also disposed at the succeeding stage of the control filter **50** and the output from the filter **54a1** is input to the subtracter **51**, or it may be configured such that the filter **54a1** is disposed at the succeeding stage of the control filter **52a** to which the current command value I_{ref} is input and the control filter **50** is also disposed at the succeeding stage of the filter **54a1** and the output from the control filter **50** is input to the subtracter **51**.

[0075] In addition, it may be configured such that the control filter **50** is disposed at the succeeding stage of the filter **54a1** to which the current command value I_{ref} is input and the control filter **52a** is also disposed at the succeeding stage of the control filter **50** and the output from the control filter **52a** is input to the subtracter **51**, or it may be configured such that the control filter **52a** is disposed at the succeeding stage of the filter **54a1** to which the current command value I_{ref} is input and the control filter **50** is also disposed at the succeeding stage of the control filter **52a** and the output from the control filter **50** is input to the subtracter **51**.

[0076] In addition, an arrangement sequence of the control filter **52b** and the filter **54a2** in the feedback path of the current value I_m is not limited to the sequence in FIG. **11**, and, for example, it may be configured such that current value I_m detected by the motor current detector **48** is input to the filter **54a2**, the control filter **52b** is disposed at the succeeding stage of the filter **54a2**, and the

output from the control filter 52b is input to the subtracter 51.

[0077] In addition, although both the control filter (A(s)) and the filter (G.sub.LPF(s)) are arranged at the preceding stage of the subtracter 51 and in the feedback path of the current value I_m , only one of the control filter (A(s)) and the filter (G.sub.LPF(s)) may be arranged at the preceding stage of the subtracter 51 and in the feedback path of the current value I_m and the other filter may be arranged at the succeeding stage of the subtracter 51.

Advantageous Effects of Embodiment

[0078] (1) The motor control device of the embodiment includes: the current command value calculation unit 41 configured to calculate a current command value I_{ref} for driving the motor 20; the current value detection unit 48 configured to detect current flowing through the motor 20; the control filter 52 configured to output a first voltage command value according to deviation between a current detected value I_m , the current detected value I_m being a detected value of current detected by the current value detection unit 48, and the current command value I_{ref} ; the adder 53 configured to calculate a second voltage command value by adding output from the delay element 55 to the first voltage command value and also input the second voltage command value to the delay element 55; and the inverter 47 configured to drive the motor 20, based on the second voltage command value.

[0079] Although the conventional feedforward-type back electromotive voltage compensation requires a model of motor characteristics, such as a back electromotive voltage constant, such a model is not used in the present invention. Since because of this configuration, even when the back electromotive voltage constant changes due to variation in motor characteristics caused by an individual difference of a motor to be used, change in physical properties due to temperature change or aging, or the like, disturbance voltage generated by the change in the back electromotive voltage constant can be suppressed, robustness against disturbance factors can be improved.

[0080] In addition, although since motor rotational speed to be used for the conventional feedforward-type back electromotive voltage compensation is calculated from a sampling value of a motor angle, there is a risk that estimation error occurs influenced by detection error, detection noise, or the like, in the present invention, since the motor rotational speed is not used for control of disturbance voltage, influence of detection error or detection noise in the motor rotational speed can be avoided.

[0081] Note that when a voltage command value is calculated by the vector control as described above, the current command value calculation unit 41 may calculate a d-axis current command value and a q-axis current command value. The current detected value I_m may be converted to a motor current detected value of the q-axis and a motor current detected value of the d-axis. The control filter (current control unit) 52 may calculate the first voltage command value according to deviation between the motor current detected value of the q-axis and the q-axis current command value and deviation between the motor current detected value of the d-axis and the d-axis current command value. [0082] (2) The control filter 52 may have a characteristic of a high-pass filter with respect to disturbance voltage applied to the motor 20.

[0083] As described above, back electromotive voltage and an interference term between a d-axis component and a q-axis component can be treated as a signal that has a low frequency approximately equal to a steering frequency of the steering wheel 1 in a dq-axis rotational coordinate system. The feature that the control filter 52 has a characteristic of a high-pass filter with respect to disturbance voltage enables influence of back electromotive voltage and other disturbance voltages to be suppressed.

(Variation)

[0084] The motor control device according to the present invention is not limited to the above-described embodiment, and various modification can be made without departing from the spirit and scope of the present invention.

[0085] For example, although in the above-described embodiment, as an application example of the

motor control device according to the present invention, the electric power steering device **10** including the motor control device was described as an example, a scope of application of the motor control device according to the present invention is not limited to the electric power steering device and is applicable to various types of mechanical devices using a motor control device.

[0086] FIG. **12** is a configuration diagram illustrative of an outline of an example of a linear motion table device in which the motor control device of the present invention is used.

[0087] The linear motion table device includes a feed screw device, a table **71**, two linear guides (linear motion guide devices), and a base **74**.

[0088] The feed screw device includes a screw shaft **70**, a nut **76**, and a motor **77**, and the screw shaft **70** is inserted into the nut **76**. A feed screw mechanism in the feed screw device is a ball screw in which a spiral groove of the screw shaft **70** and a spiral groove of the nut **76** come into point contact with each other via balls (rolling elements). The motor **77** is coupled to one end in the axial direction of the screw shaft **70**.

[0089] Each of the two linear guides includes a guide rail **72**, two sliders (mobile units) **73**, and a plurality of rolling elements. In each linear guide, the guide rail **72** and each of the sliders **73** have raceway surfaces that form rolling paths for the rolling elements at positions facing each other. Both raceway surfaces extend in the longitudinal direction of the guide rail **72**, and the sliders **73** linearly move along the guide rail **72** via the rolling elements rolling in the rolling paths while being loaded.

[0090] The linear guides are arranged at both ends in a direction perpendicular to a movement direction Y of the table **71** on the base **74**, and the feed screw device is arranged between the two linear guides. The guide rails **72** and the screw shaft **70** are arranged in parallel with the movement direction Y of the table **71**.

[0091] In the arrangement, the guide rails **72** are fixed to the base **74**. Rolling bearings are attached at both ends in the axial direction of the screw shaft **70**, a housing **75** is fixed to an outer ring of each of the rolling bearings, and each of the housing **75** is fixed to the base **74**. Because of this configuration, the screw shaft **70** is rotatably supported with respect to the base **74**.

[0092] The table **71** is arranged above the two sliders **73** of each of the linear guides and the nut **76** of the feed screw device, and is directly fixed to the sliders **73** and is fixed to the nut **76** via a bracket. That is, the two sliders **73** of each of the linear guides and the nut **76** of the feed screw device are fixed to one surface of the table **71**.

[0093] In the linear motion table, when the motor **77** is driven and the feed screw device is operated, the screw shaft **70** rotates and the nut **76** linearly moves by the ball screw mechanism. In association with this movement, the table **71** linearly moves while being guided by the linear guides.

[0094] A controller **78** sets current command values to drive the motor **77** and, by performing the same processing as the processing performed by the controller **30** of the above-described embodiment, calculates voltage control command values V_{ref} from the current command values and controls currents to be supplied to the motor **20**.

REFERENCE SIGNS LIST

[0095] **1** Steering wheel [0096] **2** Steering shaft [0097] **3** Reduction gear [0098] **4a, 4b** Universal joint [0099] **5** Pinion rack mechanism [0100] **5a** Pinion [0101] **5b** Rack [0102] **6a, 6b** Tie rod [0103] **7a, 7b** Hub unit [0104] **8L, 8R** Steered wheel [0105] **10** Torque sensor [0106] **11** Key [0107] **12** Vehicle speed sensor [0108] **13** Battery [0109] **14** Steering angle sensor [0110] **20** Steering assist motor [0111] **20, 77** Motor [0112] **30, 78** Controller [0113] **41** Current command value calculation unit [0114] **42A, 44-4, 44-5, 53** Adder [0115] **42B, 51** Subtractor [0116] **43** Current limiting unit [0117] **44** Compensation signal generation unit [0118] **44-1** Convergence [0119] **44-2** Inertia [0120] **44-3** Self-aligning torque [0121] **45** (Proportional-integral) control unit [0122] **46** PWM control unit [0123] **47** Inverter [0124] **48** Motor current detector [0125] **50, 52, 52a, 52b** Control filter [0126] **53** Voltage disturbance control unit [0127] **54, 54a, 54a1, 54a2, 54b**

Filter [0128] **55, 56** Delay element [0129] **57** Calculation unit [0130] **58** Electrical characteristic unit [0131] **59** Torque coefficient [0132] **60** Addition unit [0133] **61** Mechanical characteristic unit [0134] **62** Back electromotive force generation unit [0135] **70** Screw shaft [0136] **71** Table [0137] **72** Guide rail [0138] **73** Slider [0139] **74** Base [0140] **75** Housing [0141] **76** Nut

Claims

1-10. (canceled)

11. A motor control device comprising: a current command value calculation unit configured to calculate a current command value for driving a motor; a current value detection unit configured to detect current flowing through the motor; a current control unit configured to output a first voltage command value according to deviation between a current detected value and the current command value, and having characteristics of proportional control, integral control, and derivative control for the deviation, the current detected value being a detected value of current detected by the current value detection unit; a voltage disturbance control unit arranged at the succeeding stage of the current control unit and configured to calculate a second voltage command value by adding output from a delay element to the first voltage command value and also input the second voltage command value to the delay element, the delay element providing a delay of a length of one control cycle of the current control unit to an input signal input in a previous control cycle of the current control unit and outputting the input signal as a delay signal in a current control cycle of the current control unit; and a driving circuit configured to drive the motor, based on the second voltage command value.

12. The motor control device according to claim 11 comprising a first filter configured to reduce noise in the second voltage command value.

13. The motor control device according to claim 12, wherein the first filter is a filter configured to reduce noise in an added value of the first voltage command value and output from the delay element.

14. The motor control device according to claim 13, wherein the output from the first filter is inputted to the delay element.

15. The motor control device according to claim 12, wherein the first filter separately includes a second filter configured to reduce noise in the first voltage command value and a third filter configured to reduce noise in output from the delay element, and the voltage disturbance control unit calculates the second voltage command value by adding the first voltage command value having noise reduced by the second filter and output from the delay element having noise reduced by the third filter.

16. The motor control device according to claim 11, wherein the motor control device separately includes a filter configured to reduce noise in the current command value, a filter configured to reduce noise in the current detected value, and a filter configured to reduce noise in output from the delay element.

17. The motor control device according to claim 11, wherein the current control unit has a characteristic of a high-pass filter with respect to disturbance voltage applied to the motor.

18. An electric actuator product comprising: the motor control device according to claim 11; and a motor controlled by the motor control device.

19. An electric power steering device comprising: the motor control device according to claim 11; and a motor controlled by the motor control device, wherein the electric power steering device provides a steering system of a vehicle with a steering assist force, using the motor.
