

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250255747

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

KIM; Sung et al.

MANDIBULAR ADVANCEMENT DEVICE

Abstract

Disclosed herein are mandibular advancement devices comprising an upper splint and a lower splint, where the upper splint comprises one or more upper fins, where each upper fin is located at a distance UD from back of the upper splint; the lower splints comprise one or more lower fins, where each lower fin is located at a distance LD from back of the lower splint; where the position of the upper and lower fins is unchangeable. Also disclosed are methods of reducing partial constriction of airway during sleep for a patient, the method comprising identifying a patient in need thereof; and administering to the patient the disclosed mandibular advancement device. Also disclosed are methods of manufacturing a mandibular advancement device, the method comprising obtaining measurements from a patient's dentition; digitally designing a mandibular advancement device; and milling the mandibular advancement device.

Inventors: KIM; Sung (Pleasanton, CA), KUHNS; David W. (Pleasanton, CA), LIPTAK; Leonard A. (Pleasanton, CA)

Applicant: ProSomnus Sleep Technologies, Inc. (Pleasanton, CA)

Family ID: 79025413

Appl. No.: 18/957588

Filed: November 22, 2024

Related U.S. Application Data

parent US continuation 18387227 20231106 parent-grant-document US 12186232 child US 18957588

parent US continuation 18113012 20230222 parent-grant-document US 11813193 child US 18387227

parent US continuation 17667439 20220208 parent-grant-document US 11617677 child US 18113012

parent US continuation 15987816 20180523 parent-grant-document US 11291580 child US 17667439

parent US continuation 15913548 20180306 parent-grant-document US 11207207 child US 15987816
parent US continuation 15416666 20170126 parent-grant-document US 9949868 child US 15913548
parent US continuation 14809208 20150725 parent-grant-document US 9820882 child US 15416666
parent US continuation PCT/US2014/072398 20141224 PENDING child US 14809208
us-provisional-application US 61922016 20131230

Publication Classification

Int. Cl.: **A61F5/56** (20060101); **A61C7/08** (20060101); **A61C7/36** (20060101); **B23C3/00** (20060101)

U.S. Cl.:

CPC **A61F5/566** (20130101); **A61C7/08** (20130101); **A61C7/36** (20130101); **B23C3/00** (20130101); B23C2226/61 (20130101)

Background/Summary

RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/387,227, filed Nov. 6, 2023, which is a continuation of U.S. patent application Ser. No. 18/113,012, filed Feb. 22, 2023, U.S. Pat. No. 11,813,193, which is a continuation of U.S. patent application Ser. No. 17/667,439, filed Feb. 8, 2022, U.S. Pat. No. 11,617,677, which is a continuation of U.S. patent application Ser. No. 15/987,816, filed May 23, 2018, U.S. Pat. No. 11,291,580, which is a continuation of U.S. patent application Ser. No. 15/913,548, filed Mar. 6, 2018, U.S. Pat. No. 11,207,207, which is a continuation of U.S. patent application Ser. No. 15/416,666, filed Jan. 26, 2017, U.S. Pat. No. 9,949,868, which is a continuation of U.S. patent application Ser. No. 14/809,208, filed Jul. 25, 2015, U.S. Pat. No. 9,820,882, which is a continuation of and claims priority to International Application No. PCT/US2014/072398, filed Dec. 24, 2014, which designates the U.S. and claims priority to U.S. Provisional Application No. 61/922,016, filed Dec. 30, 2013, the entire disclosures of all the above applications are hereby expressly incorporated by reference, including all the drawings, for all purposes.

FIELD OF THE INVENTION

[0002] The present invention is in the field of medical devices, and in particular it is in the field of mandibular advancement devices.

BACKGROUND OF THE DISCLOSURE

[0003] Snoring and mild sleep apnea are generally thought to be the result of a reduced or partial constriction of the airway during sleep. This may be attributed to soft tissue sinking and applying pressure on the airway during sleep including the mandible dropping and moving backwards. Mandibular advancement devices are designed to move the mandible forward to relieve the force applied from soft tissue during sleep and assisting in opening the airway. Depending on the patient, the advancement of the mandible may vary based on the response of the patient. Optimizing the adjustment is referred to as titration.

[0004] Many devices are on the market today that serve to advance the mandible. A dual arch device comprising fins and an adjustment screw block are represented by Somnomed's Somnodent (U.S. Pat. No. 6,604,527), the Dynflex

[0005] Dorsal Appliance, and Dr. Nordstrom's NorSnor II produced by Murdock Labs since the 1980's. Each device has an adjustable upper screw mechanism with block, which upon adjustment applies a force against a lower fin or bite block that then moves the mandible forward. The threaded screw system, requires that the user apply an Allen wrench to adjust the screw for titration. These devices are handmade and built up using polymethylmethacrylate (PMMA) and the corresponding monomer, methylmethacrylate. The device is cured in the dental lab and custom designed for each patient. Reproduction of the quality and accuracy of the device is subject to human skill.

[0006] Alternatively, there are devices that make an adjustment by changing out straps of different lengths to titrate the mandible forward. Examples of these are the Silent Nite (U.S. Pat. No. 5,365,945) produced by Glidewell, and the Narval (U.S. Pat. No. 7,146,982) produced by Resmed. These devices offer a possibly lower profile than the screw adjustment devices and also connect the upper and lower arch together.

[0007] Several limitations exist with these existing sleep apnea devices. First, the manual, artisanal fabrication method used by these devices limits the ability to consistently and precisely transfer the prescription into the device design. This limitation results in the need for additional adjustments. Second, the manual artisanal fabrication method requires the layering of monomers, which can subject the patient to higher levels of residual monomers. Third, existing device designs feature multiple components, straps, and screws that decrease durability, reliability, and ease of use. Fourth, the materials used in the manual, artisanal fabrication method require the device to be of a certain size to effectively withstand the normal intraoral forces that the device is subjected to. This size limitation results in decreased patient comfort and patient compliance.

[0008] Therefore a need exists to provide a mandibular advancement device that provides advancement of the lower jaw through a series of splints digitally designed and milled to provide accurate increments of advancement for easy titration of the mandible, without the need for an adjustment screw mechanism or adjustment straps.

SUMMARY OF THE INVENTION

[0009] Disclosed herein are mandibular advancement devices comprising an upper splint and a lower splint, where the upper splint comprises one or more upper fins, where each upper fin is located at a distance UD from back of the upper splint; the lower splints comprise one or more lower fins, where each lower fin is located at a distance LD from back of the lower splint; where the position of the upper and lower fins is unchangeable. Also disclosed are methods of reducing partial constriction of airway during sleep for a patient, the method comprising identifying a patient in need thereof; and administering to the patient the disclosed mandibular advancement device. Also disclosed are methods of manufacturing a mandibular advancement device, the method comprising obtaining measurements from a patient's dentition; digitally designing a mandibular advancement device; and milling the mandibular advancement device. Also disclosed are methods of selecting a mandibular advancement device for a patient, the method comprising a) obtaining two or more upper splints of the mandibular advancement device, wherein each upper splint comprises one or more upper fins, wherein each upper fin is located at a distance UD from back of the upper splint, and wherein the distance UD of any of the two or more upper splints is different than the distance UD of any other of the two or more upper splints; and obtaining two or more lower splints of the mandibular advancement device, wherein each lower splint comprises one or more lower fins, wherein each lower fin is located at a distance LD from back of the lower splint, and wherein the distance LD of any of the two or more lower splints is different than the distance LD of any other of the two or more lower splints; b) choosing a combination of one upper splint and one lower splint for the patient; c) observing the clinical outcome of the chosen combination of one upper splint and one lower splint; d) choosing a different combination of one upper splint and one lower splint for the patient if the clinical outcome of step c) is unacceptable; and e) repeating steps b)-d) until an acceptable clinical outcome is obtained.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] FIG. 1A illustrates a front view of an embodiment of the disclosed mandibular advancement device as it is worn in the mouth.

[0011] FIG. 1B shows a side view of an embodiment of the disclosed mandibular advancement device as it is worn in the mouth.

[0012] FIG. 2A illustrates an embodiment of the upper splint of the disclosed mandibular advancement devices where the rake angle is set in a neutral orientation.

[0013] FIG. 2B is an illustration of an embodiment of the lower splint.

[0014] FIG. 3A illustrates an embodiment of the disclosed mandibular advancement device where the rake angle is set in a recline orientation.

[0015] FIG. 3B illustrates an embodiment of the disclosed mandibular advancement device where the rake angle is set in a procline orientation.

[0016] FIG. 4A illustrates an embodiment of the fin design in a predesigned digital library of fins.

[0017] FIG. 4B illustrates another embodiment of the fin design in a predesigned digital library of fins.

[0018] FIG. 4C illustrates another embodiment of the fin design in a predesigned digital library of fins.

[0019] FIG. 4D illustrates another embodiment of the fin design in a predesigned digital library of fins.

[0020] FIG. 4E illustrates that a fin design from the library is incorporated into an embodiment of the disclosed mandibular advancement device.

[0021] FIG. 5 illustrates an embodiment of the disclosed mandibular advancement device where there exists a gap between the lower fin and the lower splint.

[0022] FIG. 6 illustrates varying the plane of the splint with respect to the occlusal plane.

[0023] FIG. 7 shows the occlusal side of a splint with cutouts designed into the device to accurately place ball clasps.

[0024] FIG. 8A shows a free standing upper splint with the retention arms.

[0025] FIG. 8B shows the graphics of how the upper splint and the retention arms fit into the mouth of the patient.

[0026] FIG. 9 illustrates the mechanism of titration when using multiple upper splints with one lower splint. Each illustrated upper fin belongs to a separate upper splint.

DETAILED DESCRIPTION OF THE EMBODIMENTS

[0027] In one aspect provided herein is a digitally designed and milled mandibular advancement device comprising an upper splint and a lower splint, wherein the upper and lower splints independently further comprise one or more fins. In some embodiments, the splints provide accurate increments of advancement of the lower jaw for titration of the mandible. The terms “dental splint” and “splint” as used herein refers to several types of orthodontic devices that are designed to address dental problems such as loose teeth and bruxism, in addition to problems with snoring and apnea.

[0028] A patient in need of the disclosed mandibular advancement devices wears the upper splint on the upper dentition and the lower splint on the lower dentition during sleep. The splints are designed to remain attached to the dentition until the patient removes them. The fins of the upper and lower splints cause a precise placement of the mandible in relation to the maxilla. The mandible is caused to stay in a forward position and does not relax and fall back. The airway constriction during the sleep is thereby minimized.

[0029] In one embodiment the device creates an offset between the upper and lower splint by using upper and lower fins as boundary surfaces to restrict movement while the mouth is closed or

reasonably opened.

[0030] In some embodiments, the devices disclosed herein were digitally designed and then milled as a single unit. In some of these embodiments, a computer aided design (CAD) process were used to design and manufacture the mandibular advancement devices disclosed herein. A plaster model of the patient's dental impression were first obtained using well-known techniques in the art. Then, scans of the plaster models were imported into the CAD software. In other embodiments, the 3D files of the patient's impression are imported from other sources, such as a direct scan of the patient dentition using an Intra Oral Scan (IOS) Device, e.g., the 3M TruDef™ scanner, or a direct scan of the impression from either an IOS or Cone Beam Computed Tomography (CBCT) device. In these embodiments, the files enable the design of the mandibular advancement splint in 3D space in a CAD software such as 3-Matic by Materialise™.

[0031] In other embodiments, the different components of the disclosed devices, for example the splint, the fins, the retention arms, etc., are milled or manufactured separately and then attached together after the manufacturing. This approach allows for the use of interchangeable parts.

[0032] In one embodiment the digitally designed and milled splints are reproduced accurately without manual polymer buildup. In some embodiments, accurate reproduction results in accurate replacement devices. In other embodiments, it results in reproducible titration settings. In some embodiments the splints are digitally designed and milled to provide access to pre-cured polymeric materials, and wherein the device has minimal residual monomers.

[0033] In one embodiment one or more identifying information, e.g., the patient's name, order number, and other relevant tracking information, are designed into the device. The identifying information appears on the device through the milling process.

[0034] In one embodiment, the device is designed to comfortably fit on to a patient's upper and lower arches, maintain a maximum amount of space for the tongue, and keep the mandible advanced forward per a doctor's prescription while still allowing the patient to reasonably open their mouth and move their jaw from left to right for comfort. This contact serves as a barrier to keep the lower fin in a position forward of this fin engagement surface.

[0035] The disclosed devices can be made from any material that can withstand the oral environment for an extended period of time, for example overnight. Furthermore, the material can be any material that is capable of being milled to form the devices disclosed herein. Examples of materials include plastics and other polymers, whether hard or soft, transparent or opaque. Some suitable polymers include, but are not limited to, a polyetheretherketone (PEEK), polystyrene, polyvinyl chloride, rubber, synthetic rubber, or an acrylate polymer, such as a polymer made up of methyl methacrylate, methyl acrylate, ethyl acrylate, 2-chloroethyl vinyl ether, 2-ethylhexyl acrylate, hydroxyethyl methacrylate, butyl acrylate, butyl methacrylate, or trimethylolpropane triacrylate (TMPTA).

[0036] Embodiments of the device are further described with reference to the accompanying drawings.

[0037] FIG. 1 illustrates an embodiment of the disclosed mandibular advancement device, **100**.

FIG. 1a shows a front view of the device as it is worn in the mouth, whereas FIG. 1b shows a side view of the same embodiment. The device **100** comprises an upper splint **102** and a lower splint **104**. The splint **102** is configured to fit snugly onto the upper dentition **106**, while the lower splint **104** is configured to fit snugly onto the lower dentition **108**. Each splint provides enough retention to keep the device on during normal wear but allowing the user to pull off the device with minimal effort. The two splints contact each other along the occlusal plane **110**, i.e., the plane passing through the biting surfaces of the teeth.

[0038] In one embodiment the thickness of the upper splint **102** and lower splint **104** is independently varied to create a fixed amount of jaw opening between the patient's arches.

[0039] The devices **100** disclosed herein are prepared individually and specially for a particular patient. For this reason, while preparing the digital design of the disclosed devices, the

idiosyncrasies of the patient's oral and dentition structures are taken into account. For instance, in some embodiments, the opposing surfaces of the splint are designed in variance with each other to accommodate the patient's oral structure to achieve maximum comfort. The surfaces can be flat, or be made to touch at one or more points. This is true of any other feature of the devices **100**. For example, the height, width and shape of the fins; the rake angle; the offset position of the fins; the location of retention arms, if any; the dental impressions; inter alia, are designed specifically for the particular patient. This feature is easily enabled with a device that is digitally pre-designed. The currently available devices are handmade, making it difficult for the artisan to accurately take into account the specific oral features of a particular patient.

[0040] Each upper splint **102** comprises at least one upper fin **114**, and preferably two upper fins **114**. The fin **114** is located to the side of the upper splint **102** such that when the splint **102** is worn by the patient, the fin **114** is near the molars. Each upper fin **114** protrudes downwardly.

[0041] Similarly, each lower splint **104** comprises at least one lower fin **116**, and preferably two lower fins **116**. The fin **116** is located to the side of the lower splint **104** such that when the splint **104** is worn by the patient, the fin **116** is near the molars. Each lower fin **116** protrudes upwardly.

[0042] Throughout the present disclosure, the terms “up,” “upper,” or “upward,” and “down,” “lower,” or “downward” refer to the relative position of the upper jaw and the lower jaw. Thus, “protruding downwardly” means protruding away from the upper jaw and towards the lower jaw. Similarly, the words “front” or “forward” and “back” or “backward” refer to the relative position of components in the mouth. Thus, “front” means towards the lips, whereas “back” means towards the throat, when the device is in the mouth.

[0043] FIG. 2A shows the embodiment of the upper splint that is shown in FIG. 1 and FIG. 2B shows the embodiment of the lower splint that is shown in FIG. 1. FIG. 2 depicts the splints by themselves and without being worn on the teeth.

[0044] The upper fin **114** comprises a front surface **202** and the lower fin **116** comprises a back surface **204**. When the device is worn in the mouth, the lower fin **116** is located in front of the upper fin **114**. The front surface **202** of the upper fin **114** contacts the back surface **204** of the lower fin **116**. This contact serves as a barrier to keep the lower fin in a position forward of this fin engagement surface. That is, the contact prevents the lower jaw from moving backward relative to the upper jaw. Thus, once the device is worn, the relative forward position of the upper and lower jaws becomes fixed. The patient would be able to open and close their mouth and move the lower jaw from left to right for comfort. However, the patient would not be able to move the lower jaw backwards beyond the point of contact of the two surfaces **202,204**.

[0045] In one embodiment the device is digitally designed and milled to provide optimal strength with reduced interference to the tongue creating a comfortable and durable device. As seen in FIGS. 2A & 2B, the two splints each form an arch with an empty center **206**. The empty center **206** provides room for the patient's tongue when the device is in use. The type of design that allows room for the tongue is referred to as lingual-less. Thus, some embodiments of the present device **100** are lingual-less designs.

[0046] The upper fin **114** is located at a distance UD (**208**) from the back of the upper splint **102**. Similarly, the lower fin **116** is located at a distance LD (**210**) from the back of the lower splint **104**. Distances **208,210** are also referred to as fin offset. The relative positioning of the fins determines the degree to which the lower jaw is protruded forward, i.e., the jaw offset. As discussed below, in some embodiments, the distances **208** and **210** are manipulated to provide the best fit for the patient.

[0047] In one embodiment, the upper and lower fins vary in angular shape at the contact surfaces of each fin to provide the most anatomically correct position and comfort during the motion of opening and closing the mouth. The embodiment shown in FIG. 1 comprises vertical contact surfaces. In these embodiments, the contact surfaces **202** and **204** are perpendicular to the occlusal plain **110**. In this embodiment, the rake angle, i.e., the angle that surface **202** makes with the

occlusal plane **110**, is 90° to the occlusal plane, i.e., a neutral angle. In other embodiments, for example those shown in FIGS. **3A** and **3B**, the contact surfaces are at a non-neutral angle. For example, in the embodiment shown in FIG. **3A**, the rake angle is set in a recline orientation. In this embodiment, the surface **202** angles backward. Conversely, in the embodiment shown in FIG. **3B**, the rake angle is set in a procline orientation. In this embodiment, the surface **202** angles forward. The rake angle is configured to drive a directional movement during the opening and closing of the mouth. The particular angle, i.e., whether neutral, incline, or procline, and the angle degree, are chosen based on clinician prescription and patient comfort.

[0048] In one embodiment, the fins are selected from a predesigned digital library of fins. FIG. **4** shows additional embodiments of the fin design. FIGS. **4A-4D** show some of the embodiments used in a fin library. In some embodiments, a designer calls from a library of fin designs, for example those shown in FIGS. **4A-4D**, select one fin type (for example that shown in FIG. **4C**), and place onto the custom patient splint design, as shown in FIG. **4E**.

[0049] In some embodiments, for example that shown in FIG. **5**, there exists a gap **502** between the lower fin **116** and the lower splint **104**. While the fin **116** is attached to the splint **104** at the base, the fin **116** protrudes slightly outwards before protruding upward. In some embodiments, a corresponding gap exists between the upper fin **114** and the upper splint **102**. The gap **502**, if present, is designed into the device based on the prescription and patient anatomy and comfort. The gap **502** further allows for the side to side motion of the lower jaw with respect to the upper jaw.

[0050] When the device is worn by a patient and the patient's mouth is closed, the bottom surface of the upper splint and the top surface of the lower splint contact each other along the curve of the device, i.e., the arch of the mouth. The two surfaces contact each other along the plane of the splint. In one embodiment the opposing surfaces of the splint are designed such that the plane of the splint equals the occlusal plane. In some embodiments the plane of the splint is at an angle to the occlusal plane. FIG. **6** illustrates the ability to design devices in varying degrees of angle of the plane **110** of the splint to the occlusal plane **602**. In CAD, the angle of the plane **110** of the splint can be adjusted within the sagittal plane relative to the patient's anatomical occlusal plane **602**. Moreover the angle of the plane **110** can be adjusted within the frontal plane relative to the patient's occlusal plane **602**.

[0051] Both adjustments are useful to the clinician to affect changes to the relative positioning of the mandible and maxillae. The path of the movement of the upper and lower arches, for the opening and closing of the mouth, is affected by the engagement surface **604**, i.e., where the contact surfaces **202** and **204** meet. If the engagement surface **604** is not properly designed, then the upper and lower arches open and close along an unnatural arc, causing pain for the patient. In manufacturing the disclosed devices **100**, the natural arc of the patient's jaw movement is taken into account in the digital design. The engagement surface **604** is then designed to fit the natural arc.

[0052] In some embodiments, the device **100** is made of transparent materials, for example transparent plastic, to allow the clinician to see the patient's dentition through the device **100** to ensure good fit. Thus, in some embodiments, the clinician can insert a generic device **100** into the patient's mouth and mark the various measurements on the transparent device **100** instead of preparing a dental impression. In other embodiments, a transparent device **100** is prepared first, and relatively inexpensively, and the fit is tested before a more expensive and permanent device is manufactured.

[0053] In some embodiments the fins vary in length. In certain embodiments, the fins are adjusted to the patient's open mouth dimensions. In some embodiments, the fins vary in length related to the opposing fin to optimize the length required to maintain mandible offset position while considering comfort such that each fin is the same length or a fraction of the length of the opposing fin. The sum of the heights of an upper fin **114** and lower fin **116** is the total range of contact along the engagement surface before the two splints are separated. At the point of separation, the two splints do not exert pressure on each other and do not provide any jaw offset. In some embodiments, the upper fin **114** and lower fin **116** are of equal heights. In these embodiments, the total range is

optimized while minimizing the height of either fin. The ratio of the heights of each fin can also be adjusted for patient comfort or clinical reasons.

[0054] In some embodiments, the thickness of each fin can be adjusted to apply more or less pressure against the cheek. The pressure on the cheek stimulates the body to adjust the muscles in the mouth area, e.g., the airway muscles, for patient comfort or clinical reasons.

[0055] In one embodiment the device embeds one or more structural features that create strength using less material. In some embodiments the structural feature is made from a single material. The term “embed” as used herein refers to a single material with design geometries or purposefully milled slots or other geometries that enable another material to be added as a support member, in the same way a rebar can strengthen a concrete block. In some embodiments the structural feature is made from a combination of materials, such a metal alloy. In some embodiments the metal or metal alloy is in the shape of a ball clasp, retention wire, or treatment wire. In some embodiments the treatment wires comprise of wires to aid in a clinical result deemed important by the practicing doctor, such as retention wires, alignment wires, or a tongue behavior modification wire such as spikes or barbs to affect tongue thrust.

[0056] A patient inserts the disclosed devices **100** into the patient's mouth before sleep and removes them after sleep. The devices should be retained in the mouth snugly enough so that the device does not fall out while the patient is sleeping. However, the fit cannot be too snug so that the patient cannot easily remove the device after waking up. The retention of the device **100** in the mouth is achieved using a combination of one or more of a variety of retention devices and gaps in space between the device and tissue.

[0057] In one embodiment the device is retained onto the teeth of a patient using patient specific retention arms. In some embodiments, the retention arms replace or improve the classic use of ball clasps. In the embodiments where ball clasps are used, space for their placement can easily be designed into the splint. In one embodiment, FIG. 7 shows the occlusal side of a splint with cutouts **702** designed into the device to accurately place ball clasps.

[0058] In some embodiments, for example that shown in FIG. 8, the device **100** comprises retention arms **802**, built into either or both of the upper splint **102** and lower splint **104**. The retention arms **802** allow for a more secure placing of the splints into the mouth. FIG. 8A shows a free standing upper splint **102** with the retention arms **802**, while FIG. 8B shows the graphics of how the upper splint **102** and the retention arms fit into the mouth of the patient. In some embodiments, the retention arms **802** take on the shape of the classic ball clasp, while in other embodiments, the retention arms **802** perfectly conform to the patient's anatomy to optimize strength and surface area for retention while allowing for maximum space for the tongue.

[0059] In some embodiments, a gap is designed between a particular device surface and one or more surfaces of a patient's anatomy. A purpose of the gaps is to allow the device **100** to be installed easily, stay retained under normal conditions, and be removed easily as well. In some embodiments, the gap is uniform across the entire contact region between the device and the patient's tissue. In other embodiments, the gap is strategically placed with properly designed spacing to provide easy installation of the device in the mouth, optimal device retention onto the patient's dentition, or ease of use of the device. The gap is easily programed into the CAD digital design. Because the disclosed device can be prepared quickly and inexpensively, the clinician or the designer can experiment with a series of different gap placings until the best fit is obtained.

[0060] It is possible, through a series of steps, called titration, to choose the device having the most clinically relevant mandibular advancement setting for the patient. Thus, in another aspect, disclosed herein methods of selecting a mandibular advancement device for a patient, the method comprising: [0061] a) obtaining two or more upper splints of the mandibular advancement device, wherein each upper splint comprises one or more upper fins, wherein each upper fin is located at a distance UD from back of the upper splint, and wherein the distance UD of any of the two or more upper splints is different than the distance UD of any other of the two or more upper splints; and

[0062] obtaining two or more lower splints of the mandibular advancement device, wherein each lower splint comprises one or more lower fins, wherein each lower fin is located at a distance LD from back of the lower splint, and wherein the distance LD of any of the two or more lower splints is different than the distance LD of any other of the two or more lower splints; [0063] b) choosing a combination of one upper splint and one lower splint for the patient; [0064] c) observing the clinical outcome of the chosen combination of one upper splint and one lower splint; [0065] d) choosing a different combination of one upper splint and one lower splint for the patient if the clinical outcome of step c) is unacceptable; [0066] and [0067] e) repeating steps b)-d) until an acceptable clinical outcome is obtained.

[0068] Once a digital scan of the patient's dentition is obtained, a number of upper and lower splints are milled for the patient. Each of the upper and lower splints has a different fin offset setting. The clinician chooses one set of upper and lower splints for the patient. If the patient's condition is not improved sufficiently, the clinician then chooses another set of splints. This process is continued until a set of splints providing the best clinical outcome is chosen. An advantage of the devices and methods disclosed herein is that by digitally designing the splints and automatedly manufacturing them, several splints can be prepared relatively quickly and inexpensively. Further, the digital design allows for a precise positioning of the fins. A more effective mandibular advancement can then be obtained than by using a hand-milled and hand-cranked device.

[0069] In some embodiments, the titration settings provide for a flexible positioning of the fins in the mouth in the mesial-distal direction. In some embodiments, the fit of the device **100** on a patient is titrated through the use of devices **100** with varying distances **208** and **210** (see FIG. 2). In certain embodiments, the device **100** is milled directly from a CAD file such that the accuracy of the data from the impression of the patient's anatomy, the fit of the device to that data, and the design of the device are precisely transferred to the milling machine. This enables very precise design adjustment in positioning each of the fins in the splint, i.e., the measurement of the distances **208** and **210**, and in their position relative to each other in a reproducible and manufacturable way.

[0070] For example, in one embodiment, three different upper splints **102** were manufactured having increasingly longer distances **208**, i.e., longer fin offset. Also, two different lower splints **104** were manufactured having two different distances **210**. Thus, pairing one lower splint **104** with one upper splint **102** provided one jaw offset, while pairing the same upper splint **102** with a different lower splint **104** provided another jaw offset, and so on.

[0071] An illustrative example is shown in Table 1. To compile this table, five different upper splints **102** were prepared having 0.0 mm, 1.0 mm, 2.0 mm, 3.0 mm, and 4.0 mm fin offset (distance **208**), respectively. Also, four different lower splints **104** were prepared having 0.0 mm, 0.5 mm, 1.0 mm, and 2.0 mm fin offset (distance **210**), respectively. The combination of the two different splints can provide a jaw offset ranging from 0.0 mm to 6.0 mm, as shown in Table 1, where U-1 to U-5 are the upper splint offsets (shown in parentheses) and L-A to L-D are the lower splint offsets (shown in parentheses).


TABLE-US-00001	TABLE 1	U-1	U-2	U-3	U-4	U-5	(0.0 mm)	(1.0 mm)	(2.0 mm)	(3.0 mm)	(4.0 mm)
L-A	0.0 mm	1.0 mm	2.0 mm	3.0 mm	4.0 mm	(0.0 mm)	L-B	0.5 mm	1.5 mm	2.5 mm	3.5 mm
4.5 mm	(0.5 mm)	L-C	1.0 mm	2.0 mm	3.0 mm	4.0 mm	5.0 mm	(1.0 mm)	L-D	2.0 mm	3.0 mm
4.0 mm	5.0 mm	6.0 mm	(2.0 mm)								

[0072] Thus, twenty different mandibular advancements can be obtained with only nine different splints, four lower splints and five upper splints.

[0073] Depending on the clinician's prescription need, the clinician chooses any reasonable value for the offset of the upper fin relative to the lower fin, and as many offsets as the clinician desires. Since the digital manufacturing process accurately and precisely reproduces the splints, the combination of splints is repeatable, regardless of when the clinician orders several splints or splints with other offset distances.

[0074] Another advantage of the disclosed splint combination is enabling the creation of the same

offset with different combinations of upper and lower splint positions. For example, as shown in Table 1, a 3.0 mm offset may be created using three different combinations of upper and lower fins (L-A/U-4, L-C/U-3, and L-D/U-2). Varying the combined position of the two fins allow better alignment of the fins within the mouth for reasons of patient comfort and clinical requirements. [0075] FIG. 9 illustrates the titration. Three separate upper splints **102** are provided, one having an upper fin offset of 1 mm (**114-A**), one having an upper fin offset of 2 mm (**114-B**), and one having an upper fin offset of 3 mm (**114-B**) (FIG. 9 shows all three of these upper splints superimposed on each other for illustration purposes. In actuality, they are separate splints.) One lower splint **104**, having a lower fin offset of 0.5 mm (**116**) is also provided. Not shown is a lower splint **104** having a lower fin offset of 0 mm. The following combinations of splints provide the mandibular advancements of Table 2.

TABLE-US-00002 TABLE 2 Upper  1.0 mm 2.0 mm 3.0 mm Lower .Math. 0.0 mm 1.0 mm 2.0 mm 3.0 mm 0.5 mm 1.5 mm 2.5 mm 3.5 mm

[0076] In another aspect, disclosed herein are methods of reducing partial constriction of airway during sleep for a patient, the method comprising identifying a patient in need thereof, and administering to the patient the mandibular advancement device as disclosed herein.

[0077] In another aspect, disclosed herein are methods of manufacturing a mandibular advancement device, the method comprising obtaining measurements from a patient's dentition; digitally designing a mandibular advancement device; and milling the mandibular advancement device. In some embodiments, the obtaining measurement step comprises obtaining a dental impression.

Claims

1. A set of mandibular repositioning devices for a patient, comprising: at least one upper splint, each upper splint comprising a respective imprint of an upper dentition of the patient configured to fit onto the upper dentition and at least one upper fin affixed to the upper splint located at an unchangeable first distance (UD) from a back of the upper splint; at least one lower splint, each lower splint comprising a respective imprint of a lower dentition of the patient configured to fit onto the lower dentition and at least one lower fin located at an unchangeable first distance (LD) from a back of the lower splint; wherein the total number of upper splint(s) plus the total number of lower splint(s) is at least three, and if the set of mandibular repositioning devices comprises more than one: (i) upper splint, then each upper splint has a different first UD, resulting in a different mandibular repositioning offset when the upper and the lower splints are fitted onto the upper and lower dentitions, respectively, to generate a first mandibular repositioning and a second mandibular repositioning, or (ii) lower splint, then each lower splint has a different first LD, resulting in a different mandibular repositioning offset when the upper and the lower splints are fitted onto the upper and lower dentitions, respectively, to generate a first mandibular repositioning and a second mandibular repositioning; wherein the at least one upper fin comprises an upper fin front surface and the at least one lower fin comprises a lower fin back surface, such that when the at least one upper splint and the at least one lower splint are worn by the patient at the same time, the front surface of the at least one upper fin contacts the back surface of the at least one lower fin, thereby causing a defined mandibular repositioning for the patient.

2. The set of mandibular repositioning devices of claim 1, wherein: (i) the upper splint comprises an upper left fin and an upper right fin, wherein the upper right fin has the same unchangeable first distance (UD) from a back of the upper splint as the upper left fin, and (ii) the lower splint comprises a lower left fin and a lower right fin, wherein the lower right fin has the same unchangeable first distance (LD) from a back of the lower splint as the lower left fin.

3. The set of mandibular repositioning devices of claim 1, wherein: each of the at least one upper splint comprises a second upper fin located at a second distance UD from the back of the upper

splint; and each of the at least one lower splint comprises a second lower fin located at a second distance LD from the back of the respective lower splint; and wherein the second upper fin comprises an upper fin front surface and the second lower fin comprises a lower fin back surface, such that when an upper splint and a lower splint are worn at the same time by the patient, the upper fin front surface of the second upper fin contacts the lower fin back surface of the second lower fin, thereby causing a defined mandibular repositioning for the patient.

4. The set of mandibular repositioning devices of claim 1, wherein the set comprises one lower splint and at least two upper splints, and each upper splint has a different first unchangeable first distance (UD), resulting in a different mandibular repositioning offset when the upper and the lower splints are fitted onto the upper and lower dentitions, respectively

5. The set of mandibular repositioning devices of claim 1, wherein the set comprises one upper splint and at least two lower splints, and each lower splint has a different first unchangeable first distance (LD), resulting in a different mandibular repositioning offset when the upper and the lower splints are fitted onto the upper and lower dentitions, respectively

6. The set of mandibular repositioning devices of claim 1, wherein the first and second mandibular repositionings are in increments of from between about 0.5 mm to 6.0 mm.

7. The set of mandibular repositioning devices of claim 1, wherein the first mandibular repositioning is an repositioning prescribed by a doctor, and the second mandibular repositioning is a non-zero increment from the first mandibular repositioning.

8. The set of mandibular repositioning devices of claim 1, wherein the total number of the at least one upper splint plus the total number of the at least one lower splint is at least four to generate a third combination of upper splint and lower splint to generate a third mandibular repositioning when an upper splint and a lower splint are worn at the same time by the patient, wherein the third mandibular repositioning is different than the first mandibular repositioning and the second mandibular repositioning.

9. The set of mandibular repositioning devices of claim 5, wherein the first, second and third mandibular repositionings each differ by an increment of from 0.5 mm to 6.0 mm, in no particular order.

10. The set of mandibular repositioning devices of claim 6, wherein the first mandibular repositioning is a mandibular repositioning prescribed by a doctor, and the second mandibular repositioning and third mandibular repositioning are non-zero increments from the first mandibular repositioning.

11. The set of mandibular repositioning devices of claim 1, wherein one imprint or image of an upper dentition is used to make each of the at least one upper splints, and one imprint or image of a lower dentition is used to make each of the at least one lower splints.

12. The set of mandibular repositioning devices of claim 1, wherein each of the at least one upper splints and each of the at least one lower splints independently comprise an open center, wherein the open center provides room for a tongue of a patient when wearing the mandibular repositioning devices.

13. The set of mandibular repositioning devices of claim 1, wherein the at least one upper splint and the at least one lower splint are milled using a milling machine using a computer aided design (CAD) file to direct the milling such that the accuracy of data from an impression of a patient's anatomy, the fit of the at least one upper splint and the at least one lower splint to that data, and the design of the at least one upper splint and the at least one lower splint are precisely transferred to the milling machine.

14. The set of mandibular repositioning devices of claim 1, wherein the at least one upper splint and the at least one lower splint comprise ball clasps and/or retention arms.

15. The set of mandibular repositioning devices of claim 1, wherein the at least one upper fin is affixed to the upper splint buccal to the buccal surface of maxillary teeth, and the at least one lower fin is affixed to the lower splint buccal to the buccal surface of the mandibular teeth.

- 16.** The set of mandibular repositioning devices of claim 15, wherein (a) the at least one upper fin is affixed to the upper splint buccal to the buccal surface of maxillary teeth, and when the upper splint is fit onto maxillary dentition the upper fin protrudes downward below the occlusal plane of the upper splint; (b) the at least one lower fin is affixed to the lower splint buccal to the buccal surface of mandibular teeth, and when the lower splint is fit onto mandibular dentition the lower fin protrudes upward above the occlusal plane of the lower splint; or (c) a combination of (a) and (b).
- 17.** The set of mandibular repositioning devices of claim 1, wherein a rake angle of the upper fin front surface or a rake angle of the lower fin back surface is selected from the group consisting of a neutral angle, a recline angle, and a procline angle.
- 18.** The set of mandibular repositioning devices of claim 1, wherein the upper splint and the lower splint are placed on the maxillary and mandibular dentition, respectively, and the patient's mouth is closed, the upper splint and the lower splint contact each other along a plane substantially similar to the patient's occlusal plane.
- 19.** The set of mandibular repositioning devices of claim 1, wherein the upper splint and the lower splint comprise a transparent material.
- 20.** The set of mandibular repositioning devices of claim 1, wherein (a) there is a gap between the at least one upper fin and the upper splint; (b) there is a gap between the at least one lower fin and the lower splint; or (c) a combination of (a) and (b).
-