US Patent & Trademark Office
Patent Public Search | Text View

United States Patent	12404645
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Johnson; Lisa

Canine feces rake device

Abstract

A canine feces rake device for manually removing canine feces with a plurality of prongs includes a handle. A foam wrap is enwrapped around an exterior surface of the handle and provides an area fore the user to grasp the handle. A shaft protrudes out from an end of the foam wrap. An end of the shaft can be inserted in a port of a rake. The port has a pair of holes and each of the holes has threading. A pair of screws engages by threading with the pair of holes and helps retain the shaft in a fixed position relative to the rake. A plurality of prongs extends out from an edge of the rake and has a curvature. The plurality of prongs scoops the canine feces and transports the canine feces to a waste container.

Inventors: **Johnson; Lisa (Billings, MT)**

Applicant: **Johnson; Lisa** (Billings, MT)

Family ID: **88095378**

Appl. No.: **17/700592**

Filed: **March 22, 2022**

Prior Publication Data

Document Identifier	Publication Date
US 20230304239 A1	Sep. 28, 2023

Publication Classification

Int. Cl.: **E01H1/12** (20060101)

U.S. Cl.:

CPC **E01H1/1206** (20130101);

Field of Classification Search

CPC: E01H (1/1206)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3735574	12/1972	Heckner	172/380	A01D 7/00
4097082	12/1977	Orofino	N/A	N/A
4179145	12/1978	Shinsako	N/A	N/A
4741566	12/1987	Byung-Do	N/A	N/A
6230367	12/2000	Riedl	16/436	B25H 3/006
6736436	12/2003	Tsou	294/1.4	E01H 1/1206
8002319	12/2010	Hahn	N/A	N/A
8635750	12/2013	Ginocchio	24/30.5 R	H02G 3/32
8777283	12/2013	McNair	N/A	N/A
9775272	12/2016	Gilbert	N/A	B25G 1/06
9850632	12/2016	Hays	N/A	A01K 23/005
D860550	12/2018	Filmer	N/A	N/A
2009/0058114	12/2008	Diehl	294/1.4	E01H 1/1206
2011/0099765	12/2010	Youssefieh	15/147.1	A01D 7/00
2012/0192540	12/2011	Macyszyn	56/400.01	A01D 7/00
2012/0235431	12/2011	Beaton	294/1.3	A01K 23/005
2012/0274089	12/2011	Green	N/A	N/A
2016/0153158	12/2015	Karius	294/1.3	E01H 1/1206
2017/0191235	12/2016	Bean	N/A	A01K 23/005
2018/0058025	12/2017	Filmer	N/A	E01H 1/1206
2018/0184568	12/2017	Martin	N/A	A01B 1/16
2019/0224837	12/2018	Hoell, III	N/A	B25G 1/102
2019/0246867	12/2018	Ziamandanis	N/A	B25G 1/04
2019/0338480	12/2018	Fulbrook	N/A	E01H 1/1206
2019/0390421	12/2018	Seibold	N/A	A01D 7/06
2020/0128793	12/2019	Fredrickson	N/A	A01B 1/026

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2459912	12/2008	GB	B25G 1/04
WO2016140586	12/2015	WO	N/A

Primary Examiner: Lazo; Thomas E

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS
(1) Not Applicable
STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

(2) Not Applicable
THE NAMES OF THE PARTIES TO A JOINT RESEARCH AGREEMENT
(3) Not Applicable
INCORPORATION-BY-REFERENCE OF MATERIAL SUBMITTED ON A COMPACT DISC OR AS A TEXT FILE VIA THE OFFICE ELECTRONIC FILING SYSTEM
(4) Not Applicable
STATEMENT REGARDING PRIOR DISCLOSURES BY THE INVENTOR OR JOINT INVENTOR
(5) Not Applicable
BACKGROUND OF THE INVENTION
(1) Field of the Invention
(6) The disclosure relates to animal feces removal devices and more particularly pertains to a new animal feces removal device for manually removing canine feces with a plurality of prongs.
(2) Description of Related Art Including Information Disclosed Under 37 CFR 1.97 and 1.98
(7) The prior art relates to animal feces removal devices. Known prior art includes a variety of animal feces removal devices comprising a shaft with a scooping mechanism coupled to the end of said shaft. Known prior art lacks an animal feces removal device including a plurality of prongs for manual removal of canine feces with a loop at an end of the shaft for securing the device to a fastener.
BRIEF SUMMARY OF THE INVENTION
(8) An embodiment of the disclosure meets the needs presented above by generally comprising a handle. The handle has an exterior surface. A foam wrap is enwrapped about the exterior surface of the handle. The handle is configured for providing an area for the user to grasp the handle. A shaft is protruding out from an end of the foam wrap. The shaft has an end. A rake has a port, and the port has an interior space. The interior space defines a space for the end of the shaft to be nested within. The port has a pair of holes. Each of the holes has threading. A pair of screws has threading and the pair of screws is configured for engaging by threading with the pair of holes. A plurality of prongs is positioned on an edge of the rake. The plurality of prongs protrudes out from the rake. The plurality of prongs is configured for scooping canine feces and transporting the canine feces to a waste container.
(9) There has thus been outlined, rather broadly, the more important features of the disclosure in order that the detailed description thereof that follows may be better understood, and in order that the present contribution to the art may be better appreciated. There are additional features of the disclosure that will be described hereinafter and which will form the subject matter of the claims appended hereto.
(10) The objects of the disclosure, along with the various features of novelty which characterize the disclosure, are pointed out with particularity in the claims annexed to and forming a part of this disclosure.

Description

BRIEF DESCRIPTION OF SEVERAL VIEWS OF THE DRAWING(S)
(1) The disclosure will be better understood and objects other than those set forth above will become apparent when consideration is given to the following detailed description thereof. Such description makes reference to the annexed drawings wherein:
(2) FIG. **1** is a perspective view of a canine feces rake device according to an embodiment of the disclosure.
(3) FIG. **2** is an exploded view of an embodiment of the disclosure.
(4) FIG. **3** is a side view of an embodiment of the disclosure.

(5) FIG. **4** is an in-use view of an embodiment of the disclosure.

DETAILED DESCRIPTION OF THE INVENTION

(6) With reference now to the drawings, and in particular to FIGS. **1** through **4** thereof, a new animal feces removal device embodying the principles and concepts of an embodiment of the disclosure and generally designated by the reference numeral **10** will be described.

(7) As best illustrated in FIGS. **1** through **4**, the canine feces rake device **10** generally comprises a handle **12**. The handle **12** is a cylindrical rod. The handle **12** has an end **14**, and the end **14** of the handle **12** has an aperture **16**. The aperture **16** of the handle **12** is circular. The aperture **16** is configured for a variety of fasteners to attach to the handle **12**. The aperture **16** allows the canine feces rake device **10** the ability to be suspended by a hook. Furthermore, the handle **12** has an exterior surface **18**. A foam wrap is enwrapped about the exterior surface **18** of the handle **12**. The foam wrap **20** ameliorates the grasp of the handle **12** while also providing comfort to the hands of the user.

(8) A grip **21** is able to couple to the handle **12**. The grip **21** is an attachable handle and is configured for being positioned perpendicular relative to the handle **12** when attached. The grip **21** has a clasp **23** that is cylindrical shaped. The clasp **23** has a cavity that defines a space for enwrapping around the exterior surface **18** of the handle **12**. The clasp **23** can be positioned in an open or closed position. A hinge **27** is coupled to the clasp **23** and to the grip **21**. The hinge **27** defines a junction to adjust the positioning between the clasp **23** and the grip **21** to an open and close position. The clasp **23** has a latch **29** that secures the clasp **23** in a closed position by fastening the clasp **23** to the grip **21**.

(9) A shaft **22** is positioned at an end **24** of the foam wrap **20**. The shaft **22** is a cylindrical shaped tube that protrudes out from the end **24** of the foam wrap **20**. The clasp **23** of the grip **21** can attach to the shaft **22** as well as the handle **12**. The shaft **22** has an end **26** which is a free end and provides an area for the shaft to be inserted into a port **28** of a rake **30**. The port **28** of the rake **30** has a cylindrical shape with an interior space **32**. The interior space **32** defines a space for the end **26** of the shaft **22** to be nested within. The port **28** has a pair of holes **34**. Each of the holes **34** is circular and each of the holes **34** has threading. Each of the holes **34** is parallel to each other and the pair of holes **34** is coplanar to a longitudinal axis of the shaft **22**.

(10) Each screw **36** of a pair of screws **36** has threading and the pair of screws **36** is complementary to the pair of holes **34** of the rake **30**. Each of the screws **36** is a set screw that is configured for being easily inserted into the pair of holes **34** and pressed against the end **26** of the shaft **22** to help retain the shaft **22** in a fixed position relative to the rake **30**. The pair of screws **36** is configured for engaging by threading with the pair of holes **34** of the rake **30**.

(11) A plurality of prongs **38** is positioned on an edge **40** of the rake **30**. Each of the prongs **38** protrudes outward from the edge **40** of the rake **30**, and each of the prongs **38** has a curvature **42**. The curvature **42** of each of the prongs **38** helps define a concave shape **44** of the rake **30**. The concave shape **44** of the rake **30** provides an area for the canine feces **48** to be stored within when in-use. Each of the prongs **38** has an end **46**, and the end **46** of each of the prongs **38** is pointed. The end **46** of each of the prongs **38** facilitates the process of scooping up canine feces **48** and other animal feces from the terrain surface **50** where the canine feces **48** are located.

(12) In use, the user grasps the foam wrap **20** of the handle **12**. The user positions the end **46** of each of the prongs **38** at the base of the canine feces **48**. Therefrom, the user can push the plurality of prongs **38** of the rake **30** forward to gather a majority of the canine feces **48**. The user repeats this process until the canine feces **48** are gathered within the rake **30**. The user can then transport the canine feces **48** to a waste container for disposal. The rake **30** can be removed from the shaft **22** by removing the pair of screws **36** from the pair of holes **34** of the rake **30**. Once removed, the rake **30** can be cleaned for further use. The shaft **22** can be secured to a hook or other fasteners by using the aperture **16** at the end **14** of the handle **12**.

(13) With respect to the above description then, it is to be realized that the optimum dimensional

relationships for the parts of an embodiment enabled by the disclosure, to include variations in size, materials, shape, form, function and manner of operation, assembly and use, are deemed readily apparent and obvious to one skilled in the art, and all equivalent relationships to those illustrated in the drawings and described in the specification are intended to be encompassed by an embodiment of the disclosure.

(14) Therefore, the foregoing is considered as illustrative only of the principles of the disclosure. Further, since numerous modifications and changes will readily occur to those skilled in the art, it is not desired to limit the disclosure to the exact construction and operation shown and described, and accordingly, all suitable modifications and equivalents may be resorted to, falling within the scope of the disclosure. In this patent document, the word “comprising” is used in its non-limiting sense to mean that items following the word are included, but items not specifically mentioned are not excluded. A reference to an element by the indefinite article “a” does not exclude the possibility that more than one of the element is present, unless the context clearly requires that there be only one of the elements.

Claims

1. A canine feces rake device comprising: a handle, said handle having an exterior surface, a foam wrap being enwrapped about said exterior surface of said handle, said handle being configured for providing an area for the user to grasp said handle; a grip, said grip being an attachable handle, said grip having a clasp, said clasp being a cylindrical shape, said clasp having a cavity, said cavity defining a space to be enwrapped around said exterior surface of said handle, said clasp being configured for being positioned in an opening and closing position, a hinge being coupled to said clasp and to said grip, said clasp having a latch, said latch being configured for securing said clasp in a closed position, said grip being configured for attaching perpendicular relative to said handle; a shaft, said shaft protruding out from an end of said foam wrap, said shaft having an end; a rake, said rake having a port, said port having an interior space, said interior space defining a space for said end of said shaft to be nested within, said port having a pair of holes, each of said holes having threading; a pair of screws, said pair of screws having threading, said pair of screws being configured for engaging by threading with said pair of holes; and a plurality of prongs, said plurality of prongs being positioned on an edge of said rake, said plurality of prongs protruding out from said rake, said plurality of prongs being configured for scooping canine feces and transporting the canine feces to a waste container.
2. The canine feces rake device of claim 1, further comprising said handle being a cylindrical rod.
3. The canine feces rake device of claim 1, further comprising said handle having an end, said end having an aperture, said aperture being circular.
4. The canine feces rake device of claim 3, further comprising said aperture being configured for a variety of fasteners attaching to said handle.
5. The canine feces rake device of claim 1, further comprising said shaft being a tube.
6. The canine feces rake device of claim 1, further comprising said shaft being a cylindrical shape.
7. The canine feces rake device of claim 1, further comprising said end of said shaft being a free end.
8. The canine feces rake device of claim 1, further comprising said port being a cylindrical shape.
9. The canine feces rake device of claim 8, further comprising each of said prongs having an end.
10. The canine feces rake device of claim 1, further comprising each of said holes of said rake being circular.
11. The canine feces rake device of claim 10, further comprising said end of each of said prongs being pointed.
12. The canine feces rake device of claim 1, further comprising each of said screws being a set screw.

13. The canine feces rake device of claim 1, further comprising said pair of screws being complementary to said pair of holes.
14. The canine feces rake device of claim 1, further comprising each of said prongs having a curvature.
15. A canine feces rake device comprising: a handle, said handle being a cylindrical rod, said handle having an end, said end having an aperture, said aperture being circular, said aperture being configured for a variety of fasteners attaching to said handle, said handle having an exterior surface, a foam wrap being enwrapped about said exterior surface of said handle, said handle being configured for providing an area for the user to grasp said handle; a grip, said grip being an attachable handle, said grip having a clasp, said clasp being a cylindrical shape, said clasp having a cavity, said cavity defining a space to be enwrapped around said exterior surface of said handle, said clasp being configured for being positioned in an opening and closing position, a hinge being coupled to said clasp and to said grip, said clasp having a latch, said latch being configured for securing said clasp in a closed position, said grip being configured for attaching perpendicular relative to said handle; a shaft, said shaft being a tube, said shaft protruding out from an end of said foam wrap, said shaft being a cylindrical shape, said shaft having an end, said end being a free end; a rake, said rake having a port, said port being a cylindrical shape, said port having an interior space, said interior space defining a space for said end of said shaft to be nested within, said port having a pair of holes, each of said holes being circular, each of said holes having threading; a pair of screws, each of said screws being a set screw, said pair of screws having threading, said pair of screws being configured for engaging by threading with said pair of holes, said pair of screws being complementary to said pair of holes; and a plurality of prongs, said plurality of prongs being positioned on an edge of said rake, said plurality of prongs protruding out from said rake, each of said prongs having a curvature, each of said prongs having an end, said end of each of said prongs being pointed, said plurality of prongs being configured for scooping canine feces and transporting the canine feces to a waste container.