



US012390611B2

(12) **United States Patent**  
**Barlow et al.**

(10) **Patent No.:** **US 12,390,611 B2**

(45) **Date of Patent:** **Aug. 19, 2025**

(54) **PATIENT INTERFACE SYSTEMS**

(71) Applicant: **ResMed Pty Ltd**, Bella Vista (AU)

(72) Inventors: **Adam Francis Barlow**, Sydney (AU);  
**Rupert Christian Scheiner**, Sydney  
(AU); **Justin John Formica**, Sydney  
(AU); **Aaron Samuel Davidson**,  
Sydney (AU); **Kai Stuebiger**, Sydney  
(AU)

(73) Assignee: **ResMed Pty Ltd**, Bella Vista (AU)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 1065 days.

(21) Appl. No.: **17/330,490**

(22) Filed: **May 26, 2021**

(65) **Prior Publication Data**

US 2021/0275768 A1 Sep. 9, 2021

**Related U.S. Application Data**

(63) Continuation of application No. 16/032,722, filed on  
Jul. 11, 2018, now Pat. No. 11,045,619, which is a  
(Continued)

(51) **Int. Cl.**

**A61M 16/06** (2006.01)

**A61M 16/00** (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC .... **A61M 16/0666** (2013.01); **A61M 16/0057**  
(2013.01); **A61M 16/06** (2013.01);  
(Continued)

(58) **Field of Classification Search**

CPC ..... A61M 16/0057; A61M 16/06; A61M  
16/0605; A61M 16/0611; A61M 16/0616;  
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,192,186 A 7/1916 Greene

1,229,050 A 6/1917 Donald

(Continued)

FOREIGN PATENT DOCUMENTS

AU 2009902524 6/2009

AU 2009906101 12/2009

(Continued)

OTHER PUBLICATIONS

Proceeding Correspondence dated May 24, 2024 issued in New  
Zealand Application No. 761751 (2 pages).

(Continued)

*Primary Examiner* — Annette Dixon


(74) *Attorney, Agent, or Firm* — Nixon & Vanderhye P.C.

(57)

**ABSTRACT**

A patient interface structure for delivery of respiratory therapy to a patient includes a cushion assembly having a mouth seal configured to seal around the patient's mouth and a nasal seal configured to seal against at least an underside of the patient's nose. A cushion clip is attached to the cushion assembly and adds rigidity to the cushion assembly, while a frame with a plurality of headgear attachment points is configured to snap onto the cushion clip. In addition, an air inlet passage along a posterior surface of the frame includes a first end that is configured to attach to an air delivery tube and a second end that is configured to sealingly attach to an opening in the chamber that is at least partially formed by the cushion assembly and the cushion clip. The patient interface structure also includes headgear attachable to the headgear attachment points on the frame.

**23 Claims, 95 Drawing Sheets**



**Related U.S. Application Data**

continuation of application No. 14/645,457, filed on Mar. 12, 2015, now Pat. No. 10,052,448, which is a continuation of application No. 13/876,624, filed as application No. PCT/AU2011/001258 on Sep. 30, 2011, now Pat. No. 9,010,330.

- (60) Provisional application No. 61/528,524, filed on Aug. 29, 2011, provisional application No. 61/457,981, filed on Jul. 27, 2011, provisional application No. 61/443,623, filed on Feb. 16, 2011, provisional application No. 61/388,357, filed on Sep. 30, 2010.

(51) **Int. Cl.**

*A61M 16/08* (2006.01)

*A61M 16/20* (2006.01)

(52) **U.S. Cl.**

CPC .... *A61M 16/0611* (2014.02); *A61M 16/0616* (2014.02); *A61M 16/0622* (2014.02); *A61M 16/0683* (2013.01); *A61M 16/0694* (2014.02); *A61M 16/0816* (2013.01); *A61M 16/0825* (2014.02); *A61M 16/0875* (2013.01); *A61M 16/20* (2013.01); *A61M 16/208* (2013.01); *A61M 2202/0225* (2013.01); *A61M 2205/0216* (2013.01); *A61M 2210/0618* (2013.01); *A61M 2210/0625* (2013.01)

(58) **Field of Classification Search**

CPC ..... *A61M 16/0622*; *A61M 16/0666*; *A61M 16/0683*; *A61M 16/0694*; *A61M 16/0816*; *A61M 16/0825*; *A61M 16/0875*; *A61M 16/20*; *A61M 16/208*; *A61M 2202/0085*; *A61M 2202/0225*; *A61M 2205/0216*; *A61M 2210/0618*; *A61M 2210/0625*; *A62B 7/12*

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,362,766	A	12/1920	McGargill
1,445,010	A	2/1923	Feinberg
3,682,171	A	8/1972	Dall et al.
4,248,218	A	2/1981	Fischer
4,263,908	A	4/1981	Mizerak
4,676,236	A *	6/1987	Piorkowski ..... A62B 18/04 128/201.25
5,005,571	A	4/1991	Dietz
5,375,593	A	12/1994	Press
5,438,981	A *	8/1995	Starr ..... A62B 7/12 128/205.24
5,513,634	A	5/1996	Jackson
5,560,354	A	10/1996	Berthon-Jones et al.
6,119,694	A	9/2000	Correa et al.
6,123,071	A	9/2000	Berthon-Jones et al.
6,418,928	B1	7/2002	Bordewick et al.
6,584,975	B1	7/2003	Taylor
6,644,315	B2	11/2003	Ziaee
6,860,270	B2	3/2005	Snidach
7,152,602	B2	12/2006	Bateman
7,174,575	B1	2/2007	Scherer
7,174,893	B2	2/2007	Walker et al.
7,448,386	B2	11/2008	Ho
7,509,958	B2	3/2009	Amarasinghe et al.
7,523,754	B2	4/2009	Lithgow et al.
7,658,189	B2	2/2010	Davidson
7,909,035	B2	3/2011	Thornton
8,028,699	B2	10/2011	Ho et al.
8,042,538	B2	10/2011	Ging et al.
8,402,971	B2	3/2013	Scheiner
8,550,084	B2	10/2013	Ng et al.

9,010,330	B2	4/2015	Barlow et al.
10,052,448	B2	8/2018	Barlow et al.
10,449,317	B2	10/2019	Barlow et al.
10,456,545	B2	10/2019	Barlow et al.
10,537,696	B2	1/2020	Barlow et al.
11,344,641	B2	5/2022	Baarman
11,464,931	B2 *	10/2022	Barlow ..... A61M 16/0816
11,931,514	B2 *	3/2024	Barlow ..... A61M 16/0816
2002/0134388	A1	9/2002	Chang
2003/0172936	A1	9/2003	Wilkie
2004/0067333	A1	4/2004	Amarasinghe
2005/0121030	A1	6/2005	Bateman et al.
2005/0199240	A1	9/2005	Hall
2006/0112962	A1	6/2006	Tebbutt
2006/0124131	A1 *	6/2006	Chandran ..... A61M 16/0666 128/206.28
2006/0174887	A1	8/2006	Chandran et al.
2006/0207597	A1	9/2006	Wright
2006/0237017	A1	10/2006	Davidson et al.
2006/0283461	A1	12/2006	Lubke
2007/0006879	A1	1/2007	Thornton
2007/0125385	A1 *	6/2007	Ho ..... A61M 16/0683 128/206.26
2007/0186930	A1	8/2007	Davidson et al.
2007/0272249	A1	11/2007	Chandran
2008/0110466	A1	5/2008	Armitstead
2009/0032026	A1	2/2009	Price et al.
2009/0038619	A1	2/2009	Ho et al.
2009/0050156	A1	2/2009	Ng et al.
2009/0078259	A1	3/2009	Kooij et al.
2009/0114229	A1	5/2009	Frater et al.
2009/0277452	A1	11/2009	Lubke et al.
2010/0018534	A1	1/2010	Veliss et al.
2010/0139662	A1	6/2010	Chang
2010/0199992	A1	8/2010	Ho et al.
2011/0056497	A1	3/2011	Scheiner et al.
2011/0308526	A1	12/2011	Ho et al.
2013/0213400	A1	8/2013	Barlow et al.
2015/0190602	A1	7/2015	Barlow et al.
2016/0074613	A1	3/2016	Davidson
2018/0318540	A1	11/2018	Barlow et al.
2020/0376222	A1	12/2020	Barlow et al.
2020/0376223	A1	12/2020	Barlow et al.
2021/0030992	A1	2/2021	Barlow et al.
2021/0275768	A1	9/2021	Barlow et al.

FOREIGN PATENT DOCUMENTS

AU	2010902359	5/2010
CN	1919376	2/2007
CN	101237902	8/2008
CN	101252965	8/2008
DE	40 04 157	4/1991
EP	0634186	B1 8/2000
GB	01085	A 12/1909
GB	2 385 533	8/2003
JP	2011-104096	6/2011
WO	WO 03/076020	9/2003
WO	WO 2004/052438	6/2004
WO	WO 2005/063328	7/2005
WO	2006/130903	A1 12/2006
WO	WO 2007/008725	1/2007
WO	WO 2007/130067	11/2007
WO	WO 2007/133332	11/2007
WO	WO 2007/139531	12/2007
WO	WO 2008/007985	1/2008
WO	2008/106716	A1 9/2008
WO	WO 2009/052560	4/2009
WO	WO 2009/108995	9/2009
WO	2010/066004	A1 6/2010
WO	2010/067235	A1 6/2010
WO	WO 2010/135785	12/2010
WO	WO 2010/139014	12/2010

(56)

**References Cited**

## FOREIGN PATENT DOCUMENTS

WO 2012/040791 A1 4/2012  
 WO WO 2012/040792 4/2012

## OTHER PUBLICATIONS

Deadline for Opponent to File Evidence dated Jun. 13, 2024 issued in New Zealand Application No. 761751 (2 pages).  
 Examination Report dated Jun. 7, 2024 issued New Zealand Application No. 810831 (1 page).  
 Examination Report dated Jul. 22, 2024 issued New Zealand Application No. 810831 (2 page).  
 Proceeding Correspondence dated Aug. 13, 2024 issued in New Zealand Application No. 761751 (2 pages).  
 Request for Extension of Time dated Sep. 13, 2024 filed by Fisher & Paykel Healthcare Limited in New Zealand Application No. 761751 (2 pages).  
 Deadline for Applicant to File Evidence dated Oct. 3, 2024 issued in New Zealand Application No. 761751 (2 pages).  
 Request for Re-Examination for Lack of Fair Basis dated Aug. 6, 2024 filed by Fisher & Paykel Healthcare Limited in New Zealand Application No. 761751 (15 pages).  
 Statutory Declaration of Lee James Veliss dated Sep. 17, 2024 filed by Fisher & Paykel Healthcare Limited in New Zealand Application No. 761751 (30 pages).  
 Office Action dated Jul. 13, 2021 issued in U.S. Appl. No. 17/076,368 (37 pages).  
 First Examination Report dated Aug. 17, 2021 issued in New Zealand Application No. 777323 (1 page).  
 Further Examination Report dated Jan. 22, 2024 issued in New Zealand Application No. 777323 (3 pages).  
 Deadline for Counterstatement dated Jan. 31, 2024 issued in New Zealand Application No. 761751 (2 pages).  
 Proceeding Halt dated Jan. 31, 2024 issued in New Zealand Application No. 761751 (1 page).  
 Notice of Opposition to Amendment to Specification Under Section 38 filed Jan. 22, 2024 by Fisher & Paykel Healthcare Limited in New Zealand Application No. 761751 (9 pages).  
 Proceeding Correspondence dated Jan. 23, 2024 issued in New Zealand Application No. 761751 (2 pages).  
 Deadline for Counterstatement dated May 30, 2023 issued in New Zealand Application No. 780432 (2 pages).  
 Amended Notice of Opposition without markups dated Jan. 27, 2023 filed in NZ Application No. 780432 (3 pages).  
 Amended Notice of Opposition with markups dated Jan. 27, 2023 filed in NZ Application No. 780432 (3 pages).  
 Amended Statement of Case without markups dated Mar. 20, 2023 filed in NZ Application No. 780432 (18 pages).  
 Amended Statement of Case with markups dated Mar. 20, 2022 filed in NZ Application No. 780432 (19 pages).

Statement of Case dated Feb. 28, 2022 filed in NZ Application No. 761751 (13 pages).  
 Amended Notice of Opposition without markups dated Feb. 28, 2022 filed in NZ Application No. 761751 (2 pages).  
 Amended Notice of Opposition with markups dated Feb. 28, 2022 filed in NZ Application No. 761751 (3 pages).  
 Letter to Patent Office Proceeding No. 6306 dated Feb. 28, 2022 filed in NZ Application No. 761751 (12 pages).  
 Office Action dated Jun. 29, 2018 issued in European Application No. 11827828.2 (4 pages).  
 Further Examination Report dated Sep. 18, 2017 issued in New Zealand Application No. 728600 (3 pages).  
 First Examination Report dated May 9, 2017 issued in New Zealand Application No. 728600 (2 pages).  
 First Examination Report dated Nov. 9, 2015 issued in New Zealand Application No. 713455 (2 pages).  
 Extended Search Report dated Mar. 31, 2017 issued in European Application No. 11827828.2 (8 pages).  
 Notice of Allowance dated Jan. 23, 2017 issued in Japanese Application No. 2013-530493 (3 pages).  
 Further Examination Report dated Dec. 13, 2016 issued in New Zealand Application No. 713455 (2 pages).  
 Office Action dated May 9, 2016 issued in Japanese Application No. 2013-530493 with English Translation (6 pages).  
 Notification of Third Office Action dated Oct. 10, 2015 issued in Chinese Application No. 201180047871.3 with English language translation (22 pages).  
 Notice of Reasons for Rejection dated Aug. 3, 2015 issued in Japanese Application No. 2013-530493 with English translation (8 pages).  
 Notification of Second Office Action dated Apr. 10, 2015 issued in Chinese Application No. 201180047871.3 with English translation (26 pages).  
 International Search Report for PCT/AU2011/001258 mailed Dec. 13, 2011.  
 First Examination Report issued in corresponding New Zealand Application No. 625429, dated Jun. 18, 2014.  
 Notification of First Office Action dated Nov. 4, 2014 issued in Chinese Application No. 201180047871.3.  
 U.S. Appl. No. 17/076,368, filed Oct. 21, 2020 of Barlow et al., entitled "Patient Interface Systems," 250 pages.  
 U.S. Appl. No. 16/994,904, filed Aug. 17, 2020 of Barlow et al., entitled "Patient Interface Systems," 211 pages.  
 U.S. Appl. No. 16/997,189, filed Aug. 19, 2020 of Barlow et al., entitled "Patient Interface Systems," 245 pages.  
 Extended European Search Report dated May 18, 2020 issued in European Application No. 19207219.7 (10 pages).  
 Further Examination Report dated Mar. 8, 2019 issued in New Zealand Application No. 746885 (2 pages).  
 Extended European Search Report dated Mar. 18, 2025 issued in European Application No. 24209275.7 (8 pages).  
 Extended European Search Report dated Apr. 23, 2025 issued in European Application No. 25153642.1 (9 pages).

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3





FIG. 4








FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10






FIG. 11






FIG. 14






FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22






FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32






FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40






FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45






FIG. 46





**FIG. 48**







FIG. 49









FIG. 51




**FIG. 52**



**FIG. 53**








FIG. 56





FIG. 57





**FIG. 58**





FIG. 59



**FIG. 60**




FIG. 61






FIG. 62



**FIG. 63**



**FIG. 64**




FIG. 65




FIG. 66




FIG. 67






FIG. 68







**FIG. 69**



**FIG. 70**



**FIG. 71**



**FIG. 72**




FIG. 73




FIG. 74




FIG. 75






FIG. 76



**FIG. 77**



**FIG. 78**




FIG. 79




FIG. 80






FIG. 81




FIG. 82








FIG. 83







**FIG. 86**




**FIG. 87**




**FIG. 88**




**FIG. 89**





**FIG. 90**





**FIG. 91**






**FIG. 92**



**FIG. 94**










FIG. 100








FIG. 101







**FIG. 104**




**FIG. 105**




**FIG. 106**




**FIG. 107**




**FIG. 108**




**FIG. 109**



**FIG. 110**



**FIG. 111**



**FIG. 112**





FIG. 113






FIG. 115




FIG. 116




FIG. 117




FIG. 118






FIG. 119




FIG. 120




FIG. 121




FIG. 122




FIG. 123







FIG. 124







FIG. 128

**FIG. 129**




FIG. 130








FIG. 131




**FIG. 132**







**FIG. 135**



**FIG. 136**

1

**PATIENT INTERFACE SYSTEMS****CROSS REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of U.S. application Ser. No. 16/032,722, filed Jul. 11, 2018, now allowed, which is a continuation of U.S. application Ser. No. 14/645,457, filed Mar. 12, 2015, now U.S. Pat. No. 10,052,448, which is a continuation of U.S. application Ser. No. 13/876,624, now U.S. Pat. No. 9,010,330, filed Mar. 28, 2013, which is the U.S. national phase of International Application No. PCT/AU2011/001258 filed 30 Sep. 2011 which designated the U.S. and claims the benefit of U.S. Provisional Applications 61/388,357, 61/443,623, 61/457,981, and 61/528,524, filed Sep. 30, 2010, Feb. 16, 2011, Jul. 27, 2011, and Aug. 29, 2011, respectively, the entire contents of each being incorporated herein by reference in its entirety.

**FIELD OF THE INVENTION**

The present technology relates to a patient interface, or mask, system for treatment of sleep disordered breathing (SDB).

**BACKGROUND**

Treatment of sleep disordered breathing (SDB), such as obstructive sleep apnea (OSA), by continuous positive airway pressure (CPAP) flow generator systems involves the continuous delivery of air (or other breathable gas) pressurized above atmospheric pressure to the airways of a human via a conduit and a mask. Typically, the mask fits over or in the mouth and/or nose of the patient. Pressurized air flows to the mask and to the airways of the patient via the nose and/or mouth. Pressurized air is delivered to the mask by a conduit connected to the CPAP device and the mask.

The mask should be comfortable and unobtrusive so that a patient may tolerate therapy and maintain usage. Some patients may prefer a pillows or prongs type mask (as known in the art), or a nasal mask or a full face mask. Some patient's may prefer to use one or a combination of these masks interchangeably. However, this would require the purchase of a number of different mask systems, which may be expensive and/or may not be covered by insurance.

In addition, masks including oro-nasal masks typically include a rigid frame. Patients may not find this comfortable. The frame may also dislodge the sealing portion of the mask away from the face of the patient if it is contacted or forced by bed clothing, pillows, etc.

**BRIEF SUMMARY**

One aspect of the present technology relates to patient interface, or mask, systems that provide integrated nose and mouth seals that are less obtrusive than currently available systems.

Another aspect of the present technology relates to patient interface systems that have reduced part counts compared to currently available systems.

A further aspect of the present technology relates to patient interface systems, for example oro-nasal masks, that provide a visible mouth region of the patient.

Still another aspect of the present technology relates to patient interface systems, for example oro-nasal masks, that do not obstruct the patient's line of sight.

2

Further aspects of the present technology relate to patient interface systems, for example oro-nasal masks, that are easier and/or more intuitive to assemble, fit, and use by patients, dealers, and clinicians, and provide improved fitting and sealing.

Yet another aspect of the present technology relates to patient interface systems, for example oro-nasal masks, that provide size selection from remote locations, and without assistance and/or instruction.

Another aspect of the present technology relates to patient interface systems, for example oro-nasal masks, that are considered physiologically non-threatening and will increase patient selection of the system and adherence to therapy.

Further aspects of the present technology relate to patient interface systems, for example oro-nasal masks, that seal the mouth and nasal airways but have no nasal bridge touch points and/or fewer total points of contacts with the patient's face than current systems.

Another aspect of the present technology relates to patient interface systems, for example oro-nasal masks, that comprises a substantially planar fascia that may provide a visible mouth region of the patient.

Another aspect of the present technology relates to patient interface systems, for example oro-nasal masks, that comprises a substantially curved and/or smooth fascia that may provide a visible mouth region of the patient.

Another aspect of the present technology relates to patient interface systems, for example oro-nasal masks, that comprises a substantially curved and/or smooth fascia that may have no ridges, connector portions or other obstructions in the region of the patient's mouth, so that the fascia may provide a visible mouth region of the patient.

Another aspect of the present technology relates to patient interface systems, for example oro-nasal masks, that comprises a substantially smooth fascia that may have no complex shapes, connector portions or other obstructions in the region of the patient's mouth, so that the fascia may provide a visible mouth region of the patient.

Another aspect of the present technology relates to patient interface systems, for example oro-nasal masks, that comprises an air delivery tube connection, the air delivery tube connection positioned on the cushion.

Another aspect of the present technology relates to patient interface systems, for example oro-nasal masks, that comprises an air delivery tube connection, the air delivery tube connection positioned on the fascia and offset from the centre of the fascia, that may provide a visible mouth region of the patient.

Another aspect of the present technology relates to patient interface systems, for example oro-nasal masks, that are substantially comprised of flexible components.

Another aspect of the present technology relates to patient interface systems, for example oro-nasal masks, that are stabilised at the nose sealing portion separately to the mouth sealing portion.

A patient interface structure for delivery of respiratory therapy to a patient according to an example embodiment of the present technology comprises a front plate configured to conform to the shape of the patient's face; a mouth cushion defining a breathing chamber and provided to the front plate and configured to seal around the patient's mouth; and a nasal cushion configured to seal the patient's nasal airways, wherein the nasal cushion is supported by the mouth cushion, does not contact a bridge of the patient's nose in use, and extend at least partially into the breathing chamber.

A patient interface structure for delivery of respiratory therapy to a patient according to an example embodiment of the present technology comprises a front plate configured to conform to the shape of the patient's face; a mouth cushion defining a breathing chamber and provided to the front plate and configured to seal around the patient's mouth; and a nasal cushion configured to seal the patient's nasal airways, wherein the nasal cushion is supported by the mouth cushion, does not contact a bridge of the patient's nose in use, and is raised above the breathing chamber.

A patient interface system according to an example embodiment of the present technology comprises a patient interface structure according to the present technology and a patient interface structure positioning system configured to position, stabilize and secure the patient interface structure in sealing engagement with the patient's face.

A patient interface system according to an example embodiment of the present technology comprises a cushion adapted to sealingly engage with a patient's airways, the cushion comprising a slot adapted to receive a headgear connecting portion of a fascia.

Other aspects, features, and advantages of this technology will become apparent from the following detailed description when taken in conjunction with the accompanying drawings, which are a part of this disclosure and which illustrate, by way of example, principles of this technology.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings facilitate an understanding of the various embodiments of this technology. In such drawings, in which like reference symbols indicate like features:

FIGS. 1-6 are front isometric, front, rear, left, right, and bottom views, respectively, of an example embodiment of a patient interface system according to the present technology;

FIGS. 7-13 are front isometric, front, rear, top, bottom, right and left side views, respectively, of a fascia, or front plate, of the patient interface system of FIGS. 1-6;

FIGS. 14-19 are front isometric, front, left side, right side, rear and bottom views, respectively, of a patient interface system according to another example embodiment of the present technology;

FIGS. 20-25 are front, rear, rear isometric, top, bottom, and left side views, respectively, of a fascia, frame or front plate, of the patient interface system of FIGS. 14-19;

FIG. 26 is a front isometric view of a patient interface according to another example embodiment of the present technology and FIGS. 27-33 are front isometric, front, rear, right side, left side, top, and bottom views, respectively, of a fascia, frame or front plate, of the patient interface system of FIG. 26;

FIGS. 34-40 are front isometric, front, rear, left side, right side, top, and bottom views, respectively, of a patient interface system according to another example embodiment of the present technology;

FIGS. 41-47 are front isometric, front, rear, left side, right side, top, and bottom views, respectively, of the fascia, frame or front plate, including an elbow and the patient interface positioning system of the patient interface system of FIGS. 34-40;

FIG. 48 is a front isometric view of the fascia, or front plate, including the elbow, and the seal (e.g. cushion) of the patient interface system of FIGS. 34-30;

FIGS. 49-55 are front isometric, front, rear, right side, left side, top, and bottom views, respectively, of the fascia,

frame or front plate, including the elbow, of the patient interface system of FIGS. 34-40;

FIGS. 56-62 are front isometric, front, rear, rear isometric, right side, top, and bottom views, respectively, of a patient interface positioning system according to an example embodiment of the present technology;

FIGS. 63-69 are front isometric, front, rear, top, bottom, right side, and left side views, respectively, of a mouth seal, or cushion, according to an example embodiment of the present technology;

FIGS. 70-76 are front/bottom isometric, front, rear, top, bottom, side, and front/top isometric views, respectively, of a nasal seal, or cushion, according to an example embodiment of the present technology;

FIGS. 77-83 are front isometric, front, rear isometric, rear, right side, top, and bottom views, respectively, of a seal, or cushion, including the mouth and nasal seals, or cushions, of FIGS. 63-69 and 70-76, respectively, according to an example embodiment of the present technology;

FIG. 84 is a front view of a patient interface system according to another example embodiment of the present technology;

FIG. 85 is a front view of a patient interface system according to another example embodiment of the present technology;

FIG. 86 is a front isometric view of a patient interface system according to another example embodiment of the present technology;

FIG. 87 is a rear view of a patient interface system according to another example embodiment of the present technology;

FIGS. 88-94 are views of a patient interface system according to another example embodiment of the present technology;

FIG. 95 is a front isometric view of a patient interface system according to another example embodiment of the present technology;

FIG. 96 is a front view of a patient interface system according to another example embodiment of the present technology;

FIG. 97 is a front view of a patient interface system according to another example embodiment of the present technology;

FIG. 98 is a front view of a patient interface system according to another example embodiment of the present technology;

FIG. 99 is a front view of a patient interface system according to another example embodiment of the present technology;

FIG. 100 is a front view of a patient interface system according to another example embodiment of the present technology;

FIG. 101 is a front isometric view of a patient interface system according to another example embodiment of the present technology;

FIG. 102 is an exploded assembly view of a patient interface system according to another example embodiment of the present technology;

FIG. 103 is a front isometric view of a patient interface system according to another example embodiment of the present technology;

FIG. 104 is a rear view of a mouth seal, or cushion, according to an example embodiment of the present technology;

FIG. 105 is a left side view of the mouth seal, or cushion, of FIG. 104;

5

FIG. 106 is a schematic illustration of a fascia, or front plate, and a seal, or cushion, including an anti-asphyxia valve according to an example embodiment of the present technology;

FIG. 107 is a schematic illustration of a fascia, or front plate, and a seal, or cushion, including an anti-asphyxia valve according to another example embodiment of the present technology;

FIG. 108 is a schematic illustration of a fascia, or front plate, and a seal, or cushion, including a gusseted side wall according to an example embodiment of the present technology;

FIG. 109 is a schematic illustration of a strap, for example a rear strap, of a patient interface positioning system (e.g. headgear) according to an example embodiment of the present technology;

FIG. 110 is schematic illustration of the strap of FIG. 109 connected to a delivery tube or conduit or hose;

FIG. 111 is a schematic illustration of a strap, for example a rear strap, of a patient interface positioning system (e.g. headgear) according to another example embodiment of the present technology;

FIG. 112 is a schematic illustration of a strap, for example a rear strap, of a patient interface positioning system (e.g. headgear) according to another example embodiment of the present technology;

FIG. 113 is a schematic illustration of a fascia, or front plate, including a venting arrangement according to an example embodiment of the present technology;

FIG. 114 is a schematic illustration of a patient interface system rotatably connectable to a patient interface positioning system according to an example embodiment of the present technology;

FIG. 115 is a rear view of a cushion assembly, including a mouth seal or cushion and a nasal seal or cushion;

FIG. 116 is a front view of the cushion assembly of FIG. 115 including a cushion clip;

FIG. 117 is a cross section view of the cushion assembly and cushion clip along line 117-117 in FIG. 116;

FIG. 118 is a detailed view of the connection of the cushion assembly and the cushion clip at a lower portion of the cushion assembly;

FIG. 119 is a detailed view of FIG. 118;

FIG. 120 is a detailed view of the connection of the cushion assembly and the cushion clip at an upper portion of the cushion assembly;

FIG. 121 is a detailed view of FIG. 120;

FIG. 122 is a top view of the cushion assembly and cushion clip;

FIG. 123 is a rear view of the cushion clip;

FIG. 124 is a front view of the cushion clip;

FIG. 125 is a cross section view of the cushion clip along line 125-125 in FIG. 124;

FIG. 126 is a left side view of the cushion clip;

FIG. 127 is a detailed view of FIG. 125;

FIG. 128 is a top view of the cushion clip;

FIG. 129 is a rear isometric view of a cushion assembly according to an embodiment of the present technology;

FIG. 130 is a rear view of the cushion assembly of FIG. 129;

FIG. 131 is a cross section view of the cushion assembly along line 131-131 in FIG. 130;

FIG. 132 is a rear isometric view of a cushion according to an embodiment of the present technology;

FIG. 133 is a rear view of the cushion assembly of FIG. 132;

6

FIG. 134 is a cross section view of the cushion assembly along line 134-134 in FIG. 133;

FIG. 135 is a front isometric view of the cushion assembly and cushion clip of FIG. 125; and

FIG. 136 is a left side view of the cushion assembly and cushion clip of FIG. 135.

#### DETAILED DESCRIPTION OF ILLUSTRATED EMBODIMENTS

The following description is provided in relation to several embodiments which may share common characteristics and features. It is to be understood that one or more features of any one embodiment may be combinable with one or more features of the other embodiments. In addition, any single feature or combination of features in any of the embodiments may constitute additional embodiments.

In this specification, the word “comprising” is to be understood in its “open” sense, that is, in the sense of “including”, and thus not limited to its “closed” sense, that is the sense of “consisting only of”. A corresponding meaning is to be attributed to the corresponding words “comprise”, “comprised” and “comprises” where they appear.

The term “air” will be taken to include breathable gases, for example air with supplemental oxygen. It is also acknowledged that the blowers described herein may be designed to pump fluids other than air.

#### Patient Interface Systems

Referring to FIGS. 1-13 and 56-62, a patient interface system or mask 10 system 10 in accordance with an example embodiment of the present technology comprises a patient interface structure or mask structure 20 that is positioned, stabilized and secured on a patient's head in sealing engagement with the patient's mouth and nasal airways by a patient interface positioning system 30, e.g. a headgear. The patient interface structure 20 comprises a fascia or lens or front plate or front panel or frame 21 having a mouth seal, or cushion 23 that is connected to the front plate 21. The front plate 21 includes patient interface positioning system connectors 22 (e.g. headgear connectors) to connect the patient interface positioning system (e.g. headgear) 30 to the patient interface structure (e.g. mask) 20. The patient interface structure further comprises a nasal seal, or cushion 24 connected to the mouth seal, or cushion 23 to seal the patient's nasal airways. A vent (or vent holes) 25 may be provided in the front plate 21 to vent exhaled gases in a breathing chamber defined by the front plate 21, the mouth cushion 23 and the nasal cushion 24. The vents may be provided in the front plate 21 proximate the nares and/or mouth of the patient to improve CO<sub>2</sub> washout. The array of vent holes 25 may be laser cut, molded or otherwise formed in an upper region of front plate 21.

#### Patient Interface Positioning System

The patient interface positioning system 30 comprises a crown strap 31 adapted to cup or encircle the crown of the patient's head. Top side (or upper side straps) 32 extend from the crown strap 31 and connect to the front plate 21 through slots 27. The ends 33 of the top side straps 32 may be looped through the slots 27 and connect to the top side straps 32 by, for example, hook and loop material. It should also be appreciated that other connections, for example buckles, may be used to secure the ends 33 of the top side straps 32. The top side straps 32 may be thickened or widened at the region where they connect to the crown strap 31 to allow ends 33 a larger space to connect to and also a range of angles to position ends 33 relative to slots 27, thereby improving the fit range of the headgear 30. Such an

arrangement may also improve comfort and/or to assist in stabilizing and positioning the top side straps **32** on the patient's cheek bone regions.

The crown strap **31** may further comprise a loop **40** through which a right bottom, or lower side strap **35** may pass and connect to a left bottom, or lower side strap **34**. It should also be appreciated that the loop may be formed in the lower side strap(s) **34** and/or **35**, for example as shown in U.S. Applications 61/443,623 and 61/457,981, each of which is incorporated by reference herein in its entirety. It should further be appreciated that other headgear may be used with the patient interface system, for example as disclosed in U.S. Patent Application Publication 2008/0110466 A1, the entire contents of which are incorporated herein by reference. The bottom right side strap **35** may comprise a first end **38** in the form of a loop or slot and a first end **36** of the bottom left side strap **34** may connect to the first end **38** by passing through the loop or slot and connecting through hook and loop material or buckles or other connectors. The second end **37** of the bottom left side strap **34** and the second end **39** of the bottom right side strap **35** may be connected to the front plate **21** through slots **26** in the connectors **22**.

Headgear **30** may be formed from a composite e.g. fabric and foam, which may be flame laminated and may be ultrasonically die cut or welded along its edge to create a rounded, more comfortable edge.

Front Plate/Fascia/Lens

The front plate **21** is configured to conform to or accommodate the shape of the patient's face. The front plate **21** may be flexible to allow the front plate to follow the shape of the patient's face. The front plate **21** may be formed of, for example, a flexible polymer that is able to bend and conform around the patient's mouth once the front plate **21** is connected to the patient interface positioning system **30** and fitted to the patient. The front plate **21** may also be malleable to allow the front plate to conform to the shape of the patient's face. A rib(s) **28** may be provided to the front plate **21**. The ribs **28** may be provided along the top and bottom of the front plate **21** and aid in alignment and engagement with the cushion **23**, as well as providing strength to the fascia.

Front plate **21** may be substantially planar, curved and/or smooth. Masks known in the art tend to include complex shapes and/or structures on the frame, and these complex shapes and/or structures make it difficult to see the patient's mouth clearly and to clean the frame. For example, these complex shapes and/or structures may include elbows, elbow connectors, ports, ridges, contours, headgear connectors, etc. Front plate **21** is adapted to be substantially smooth and without complex shapes or structures i.e. having a substantially planar surface in the region of the patient's mouth, to act as a window to permit clear visibility to the patient's mouth.

As shown on FIGS. **14** and **15**, the patient interface structure **20** may be generally rectangularly or trapezoidally shaped and comprise the front panel **21** that wraps across the face of the patient **1**, and the cushion **23**, **24** attached to the front plate **21**. The cushion **23** may comprise the integrated mouth seal or cushion **23** and the nasal seal or cushion **24**. The front plate **21** may be generally convex when viewed from the non-patient contacting side, curved or rounded shaped and adapted to follow the contour of the patient's face. The bottom side strap connector slots **26** and the top side strap connector slots **27** of the connectors **22** on either side of the front plate **21** may receive the headgear straps **32**, **34**, **35** and the tension or force from the headgear straps **32**,

**34**, **35** may bend or flex the front plate **21** to conform to the shape of the patient's face. The top side strap connector slots **27** are directed generally upwards and are adapted to aid sealing of the nasal cushion **24** and direct the headgear away from the patient's eyes **4**, and the bottom side strap connector slots **26** are adapted to aid sealing of the mouth cushion **23** and direct the headgear straps **34**, **35** under the ears **2** of the patient **1**.

The fascia or lens or front plate **21** is positioned in front of the patient's mouth, and is adapted to provide support to the other components of the patient interface system **10** and aid in positioning these other components, for example the front plate has headgear connectors **22** and a cushion connection portion adapted to receive the patient interface positioning system **30** and a cushion **23** and position these components relative to one another. The front plate **21** also provides some structure to the patient interface system **10** due to the comparatively greater rigidity of the front plate **21** when compared to the cushion **23**.

The front plate **21** may take the form of a lens made from a clear material such as nylon, polycarbonate or nearly clear material such as polypropylene. The lens may be shaded, selectively shaded (e.g. gradient, patterned, random assortment of shapes), printed on or otherwise coloured. The lens may also have colour changing properties e.g. it may be clear when the light is on, and may be opaque when the light is off. The lens may also be customizable. The lens may be provided with a skin or adhesive layer that may customize or otherwise alter the lens. The lens may be surface treated e.g. frosted. The lens may be die cut, drape formed, vacuum formed, molded, cast, ultrasonically cut or formed in any other method to create the desired shape. The lens may also be formed with vent holes. The vent holes may be molded in, laser cut or otherwise formed with the lens. The lens may be flexible or capable of being shaped to fit the patient's face.

Cushion/Seal

Referring to FIGS. **63-83**, the cushion or seal of the patient interface system may comprise two components the mouth cushion or seal **23** and the nasal cushion or seal **24**. The cushions **23**, **24** may be molded together or otherwise permanently attached (e.g. glue, weld). The mouth cushion **23** provides the mouth sealing portion and also the support for the nasal cushion **24**. The mouth cushion **23** also connects to the front plate **21**. The nasal cushion **24** is a nares sealing portion that may be molded from the same or alternative material to mouth cushion **23**. Separating the cushion into two components allows use of a lower durometer (i.e. lower hardness) material for the nasal seal or cushion **24**, and the tooling required to mold the nasal seal or cushion **24** with the mouth seal or cushion **24** is difficult, so molding them in two steps rather than one facilitates manufacturing.

The cushions **23**, **24** may be made from a single material such as silicone, TPE, TPU. However, combinations of materials and/or hardnesses of materials may be used. For example, the mouth seal or cushion **23** may have a TPE or silicone body, with a seal portion or flap adapted to interface with the patient. The nasal seal **24** may comprise a seal portion formed of an alternative material, for example a lower hardness silicone, TPU, fabric, etc.

Referring to FIGS. **63-69**, the mouth cushion **23** comprises a groove or channel **231** around a front portion **238** that is adapted to receive the front plate **21**. The channel **231** may have a flap (or sealing wall) **232** around the inner side of the channel that is adapted to seal against the face of the patient around the patient's mouth. The flap **232** may

comprise a single wall seal, although it should be appreciated that the flap **232** may comprise more than one wall, for example two or three walls. The mouth cushion **23** may be constructed from a deformable material such as TPE, TPU, silicone, foam (skinned or unskinned), or gel.

It should be appreciated that the mouth cushion **23** may be insert, over, or co-moulded to the front plate **21**. It should be further appreciated that a cushion clip may be provided to the cushion to clip to the front plate **21**. The clip may be insert, over, or co-moulded into the cushion **23** as one part. The cushion clip may add stiffness and rigidity to the cushion **23** where required, provide patient interaction points, and allow for a locating and attaching method of the cushion **23** to the front plate **21**, e.g. the cushion clip may snap onto the front plate **21**. The cushion clip may simplify the process of attaching the cushion **23** to the front plate **21** by reducing stretching and warping of the cushion **23** during assembly.

Slots **234** are provided in side walls **233** of the cushion **23** and are adapted to receive the connectors **22** of the front plate **21**. Slots **234** may be generally rectangular, however any other shape may be possible, such that slots **234** may be complimentary to the shape of connectors **22**. Connectors **22** may sealingly engage with side walls **233**, for example side walls **233** may comprise a lip seal or other arrangement adapted to seal against connectors **22**.

The upper portion **237** of the mouth seal or cushion **23** has a greater depth when compared with the lower portion **239** of the mouth seal or cushion **23**, i.e. the distance of the seal portion to the clip portion of the upper portion may be longer than the distance from the seal portion to the clip portion of the lower portion, to tilt the cushion **23** when in use to reduce the profile of the mask **20** when in use. The upper portion **237** of the mouth seal or cushion **23** may also have a greater depth than the lower portion **239** to accommodate nasal seal or cushion **24** and patients with long noses.

Flaps **252** are provided on nares support portions **235** to assist in positioning and stabilizing the nasal seal or cushion **24** to engage with the sides of the patient's nose or the patient's top lip. Raised portions **253** on the nares support portion **235** aid in positioning the nasal seal **24** against the flares of the patient's nostrils. A connecting structure **254** in the form of indents or apertures is formed in the nasal support portions **235** and are adapted to receive lugs **241** on nasal seal or cushion **24** to aid in alignment.

A channel **251** may be provided around the nares support portions **235** to form a flexible region (e.g. could be localized thinning of material) adapted to permit movement of the nasal seal or cushion **24** to accommodate varying anthropometrics.

The side walls **233** of the mouth seal or cushion **23** may have a "question mark" cross section, i.e. the mouth seal portion does not have a straight wall section but rather has a gusseted side wall that acts as a built-in spring so that the mouth seal portion can flex to fit varying patient anthropometrics. Such a side wall cross section is disclosed in, for example, U.S. Patent Application Publication 2008/0110464 A1, the entire contents of which are incorporated herein by reference.

The front portion **238**, the side walls **233** and the flap **232** of the mouth cushion **23** may have different hardnesses. For example, the front portion **238** may have a Shore A durometer of about 30-50, for example about 40. The side walls **233** and/or the flap **232** may have a Shore A durometer of 5-10, for example about 7.

Referring to FIGS. **104** and **105**, the cushion or seal may be formed of a foam, gel, or low durometer material to seal

with the patient. Two gusset or spring portions **288**, **289** may be formed behind the seal portion to aid in adjustment of the positioning of the seal portion. The corner **287** of the nose region may be raised to ensure the seal abuts the patient's face and seals in this region.

Referring to FIG. **108**, a gusset type arrangement may be provided to permit flexibility of the cushion and aid sealing under air pressure, with the flap **232** turning outwards. This arrangement may increase the fit range.

Referring to FIGS. **70-76**, the nasal seal or cushion **24** may comprise lugs **241** adapted to be received in indents **254** of the nares support portions **235** of the mouth seal or cushion **23**. The nasal seal or cushion **24** may have a geometry the same as or similar to that disclosed in, for example, WO 2010/139014 A1, the entire contents of which are incorporated herein by reference. The nares support portions **235** and the cradle wall **236** form a trampoline type join with the nasal seal or cushion **24**. The nasal seal or cushion **24** may have a Shore A durometer of about 30-50, for example about 40. The nasal seal or cushion **24** may have a Shore A durometer of about 5-10, for example about 7.

Referring to FIGS. **77-83**, in the assembled condition, the flaps **252** of the nares support portions **235** of the mouth seal or cushion **23** attach to the respective sides of the nasal seal or cushion **24**. A central portion **242** of the nasal seal or cushion **24** is left unsupported by the nares support portions **235** to allow the flexibility of the central portion **242** accommodate varying shaped lip regions of patients. As shown in FIG. **78**, the upper portion **237** of the mouth seal or cushion **23** is generally in line with or vertically aligned to the nasal seal or cushion **24** so the patient's nose is likely to rest inside the cushion. The nasal seal or cushion **24** is positioned to reside within the mouth cushion **23** which reduces visual bulk and streamlines the outer edge of the mask. As shown in FIG. **79**, the slots **234** for the connectors **22** of the front plate **21** are positioned below the nasal seal **24** so as to direct the headgear straps **34**, **35** along or below the patient's cheeks. It should be appreciated that the patient interface system may comprise a number of nasal seals or cushions **24**. For example, a single mouth cushion **23** may be provided to fit a large percentage of the patient population and two or more nasal seals or cushions **24** may be provided to provide a more custom fit for individual patients nose sizes.

Referring to FIG. **96**, it should be appreciated that a nasal seal or cushion comprising nasal pillows may be provided to the mouth cushion. It should be appreciated that a plurality of nasal seals or cushions having different size nasal pillows may be provided to the patient interface system.

Referring to FIG. **97**, the tube connector may comprise an elbow **269** that is rotatably connected to the front plate **21**. Elbow **269** may be lockable in the two positions as show, i.e. left and right horizontal orientations.

Referring to FIG. **98**, the patient interface structure **20** may include an anti-asphyxia valve **360** provided in the front plate **21**.

Referring to FIG. **99**, the front plate **21** may include a receptacle **270** configured to receive a clip **271** provided on a strap **35** of the patient interface positioning system. As shown in FIG. **100**, the front plate **21** may include receptacles **270** on opposing sides, each configured to receive a clip **271** attached to a strap **34**, **35**. The clips and receptacles may also be magnetic.

Cushion/Seal—Cushion Clip

Referring to FIGS. **115-128**, **135** and **136**, a seal or cushion assembly includes a mouth seal or cushion **23** and a nasal seal or cushion **24**. The cushion assembly may be

11

similar to that disclosed with respect to FIGS. 63-83 except as otherwise described herein. The cushion assembly may comprise a cushion clip 400 attached to the cushion assembly and configured to attach the cushion assembly to a fascia or front plate or lens as described herein. The cushion clip 400 may comprise detents 402 on opposite sides to retain the cushion assembly on the fascia. As shown in, for example, FIG. 128, the cushion clip 400 may have a curved portion 401 that curves away from the cushion assembly to allow the nasal seal 24 to have a greater depth than a top surface of the mouth cushion 23. This may allow the nasal seal 24 to accommodate long noses. As shown in FIG. 116, the central portion 242 of the mouth cushion 23 may dip or curve downwards towards the patient's lip to avoid contacting the patient's septum. As shown on FIG. 115, nasal seal 24 may comprise raised upper corner regions, these raised upper corner regions adapted to engage a patient's nostrils or nasal flares, thereby reducing the force on the patient's nose tip.

Referring to FIG. 115, the height of the aperture in the mouth cushion may be about 25-35 mm. Preferably, the height of the aperture on the mouth cushion may be about 25-30 mm. The height is measured from the lowest portion of the opening at the chin region to the dip or curve of the opening at the top lip region. The height of the aperture may increase towards the cheek or left and right side regions.

Referring to FIG. 122, the height of the aperture in the nose cushion may be about 5-15 mm. Preferably, the height of the aperture in the nose cushion may be about 7-12 mm. The height of the aperture in the nose cushion may be less in the central region of the aperture compared to the height of the aperture at the side regions. That is, the nose cushion aperture may have a dip or curved portion at the central region. Such an arrangement may aid in alignment of the cushion, avoid placing excess pressure on the patient's septum and/or ensure that the lower portion of the nasal cushion is not under tension and therefore may not exert pressure on the patient's top lip.

Referring to FIG. 115, the width of the aperture in the mouth cushion may be about 60-70 mm. Preferably the width of the aperture in the mouth cushion may be about 63-68 mm. Such a width may accommodate varying mouth widths of patient's.

Referring to FIG. 122, the total width of the nose and mouth cushion may be about 90-105 mm. Preferably, the total width of the nose and mouth cushion may be about 95-100 mm. Such a width may accommodate varying patient anthropometrics.

Referring to FIG. 115, the total height of the nose and mouth cushion may be about 60-75 mm. Preferably, the total height of the nose and mouth cushion may be about 65-75 mm. Such a height may accommodate varying patient anthropometrics.

The patient contacting portion of the nose and/or mouth cushions may be about 0.3-1.5 mm thick. Preferably, patient contacting portion of the nose and/or mouth cushions may be about 0.3-0.7 mm thick. Such a thickness may ensure conformability of the cushion and comfort for the patient.

Referring to FIG. 116, the height of the clip may be about 40-55 mm. Preferably, the height of the clip may be about 45-55 mm. The height of the clip may be greater than the height of the mouth cushion aperture. Such an arrangement may be simpler to engage the clip with a fascia (for example) and may increase the structural integrity of the cushion.

Referring to FIG. 116, the width of the clip may be about 70-85 mm. Preferably, the width of the clip may be about 75-80 mm. The width of the clip may be greater than the width of the mouth cushion aperture. Such an arrangement

12

may be simpler to engage the clip with a fascia (for example) and may increase the structural integrity of the cushion.

As shown in, for example, FIG. 124, the cushion clip may be generally trapezoidal, with the top portion being wider than the lower portion. Such an arrangement may mean that the overall shape of the mask is shaped to match the general shape of a human's face i.e. taper from a greater width at the top lip region to a lower width at the chin region. The top portion may be, for example, about 75-85 mm wide. The lower portion may be, for example, about 65-75 mm wide.

As shown in, for example, FIGS. 117-121, the cushion may be integrally formed in one piece. The mouth cushion 23 may have a single sealing wall 232 and the nasal cushion 24 may have a dual wall construction comprising a sealing wall 243 and a supporting wall 244. It should be appreciated that the mouth cushion 23 and the nasal cushion 24 may each include a single wall, or each may include multiple walls. The sealing walls 232 and 243 of the mouth cushion 23 and the nasal cushion 24 may curve inwards toward a breathing chamber or cavity formed by the cushions. As shown in FIG. 117, only a portion of the supporting wall 244 of the nasal cushion 24 may be present, for example, at the tip of the nose region and not at the top of the lip region. Referring to FIG. 122, a parting line 245 of the mould used to form the cushion assembly may be provided so as to be above the patient contacting areas of the cushion assembly.

Referring to FIG. 136, the cushion assembly and the cushion clip 400 may be formed integrally in one piece. The cushion assembly may be insert, over, or co-moulded into the cushion 23 as one part. Alternatively, the cushion assembly and the cushion clip 400 may be chemically or mechanically bonded together. The cushion assembly and cushion clip 400 may also be repeatably attachable and detachable from one another. For example, the cushion clip 400 may include a flange configured to be received in a channel in the cushion assembly.

As shown in FIGS. 117-121, 126 and 127, the cushion clip 400 may include a flange or rib 403 to increase the surface area of the cushion clip 400 to enhance the bond between the cushion clip 400 and the cushion assembly. The cushion assembly, for example the mouth cushion 23, may include a thickened region 310 to provide support for the sealing wall 232 and to improve the bond to the cushion clip 400. Rib 403 may have a varying height around the perimeter of the cushion clip 400. This varying height may support the cushion more in some regions (i.e. the regions with a greater rib height such as sensitive regions of the face such as the top lip) compared to support in other regions (i.e. regions with a lower rib height such as less sensitive regions of the face such as the cheeks).

#### Cushion Assembly—Continuous Sealing Surface

Referring to FIGS. 129-131, a cushion assembly including a mouth cushion 23 and a nasal cushion 24 may comprise a continuous sealing surface 246. As shown in FIG. 131, the sealing surface 246 is continuous with the mouth cushion sealing wall 232 and the nasal cushion sealing wall 243. The curvature of the sealing surface 246 may be constant or approximately constant. Such an arrangement may be comfortable for the patient as there are no ridges or undulations that may mark or otherwise irritate the patient's skin. In this arrangement, the definition between the nose and mouth seal portions is not distinct, such that the seal is continuous.

#### Cushion Assembly—Separate Sealing Surfaces

Referring to FIGS. 132-134, a cushion assembly including a mouth cushion 23 and a nasal cushion 24 includes separate sealing surfaces 247, 248. A channel 249 is pro-



13

vided to separate the nasal sealing surface **247** from the mouth sealing surface **248**. Such an arrangement may be preferable as the nose and mouth seal portions are visually distinct which may assist the patient with aligning the device.

Patient Interface Systems—Tube Connection—Behind Connector

Referring to FIGS. **14-25**, a patient interface system **10** according to an example embodiment of the present technology includes a delivery hose, or tube, or conduit **11** that is connected to the front panel **21** by a connector **12**, e.g. a swivel connector. The tube **11** may be as disclosed in, for example, U.S. Patent Application Publication 2009/0078259 A1, the entire contents of which are incorporated herein by reference. The front panel includes an air inlet or elbow **29** that may be integrally formed with the front plate **21**. It should be appreciated that the elbow **29** may be formed separately from the front plate **21** and attached or connected to the front plate **21** or the cushion **23**, for example by adhesive or mechanical fasteners. The elbow **29** is positioned behind or adjacent to the connector **22** of the front plate **21** on the left side, although it should be appreciated that the elbow **29** may be provided on the right side of the front plate **21**. The shape of the elbow **29** is curved to avoid obscuring the headgear connector **22**. However other configurations would be possible if the headgear connector **22** was located in an alternative position.

The tube connection portion of the elbow **29** is adapted to receive the tube **11** in a longitudinal (e.g. vertical) direction, however other orientations are possible. The elbow **29** is not visible from the front as it is hidden behind the headgear connector **22** of the front plate **21**. This arrangement is advantageous as it reduces the part count (i.e. no separate elbow is required) and the design may be more visually appealing. The tube **11** is connected at the side of the patient interface or mask system **10** so as to permit clear view to the patient's mouth. Because the tube connection is positioned behind the headgear connector **22** at the front plate **21**, the tube **11** is less obtrusive. The eyes **4** of the patient **1** are unobstructed and in the case of the front plate **21** being in the form of a lens, for example a clear polymer (e.g. polycarbonate), the patient's mouth would also be visible.

The elbow **29** may comprise a lip or protruding edge **41**, in the form of for example a chamfer, adapted to receive a slot or aperture of the cushion. The cushion **23** may comprise a slot that may be positioned to abut or align with the chamfer to aid alignment, and also ensure an air tight seal between the cushion **23** and the front plate **21** is achieved.

The patient interface structure **20** sits under the patient's nose **3** and the nasal cushion **24** seals around or in the nares. The mouth cushion **23** sits in the crease of the patient's chin **5**. The crown strap **31** of the headgear **30** is positioned over the top of the patient's crown and generally in line with the patient's ears **2**, although it should be appreciated that the positioning of the crown strap **31** may vary between patients.

Although the front plate **21** shown in FIGS. **20-25** includes only the bottom side strap connector slots **26**, it should be appreciated that the embodiment shown in FIGS. **20-25** may also comprise top sides strap connector slots **27**. It should also be appreciated that the front plate **21** may be provided with a vent, or alternatively another component, such as the tube **11**, the connector **12**, or the elbow **29** may have a vent.

Referring to FIG. **101**, a tube connector **272** may be positioned either on the front plate **21** or molded with the cushion **23**. The tube connector **272** may receive an intermediate portion or portion **274** of a tube **273** that may

14

interface with the tube connector **272** by an interference fit. The interference fit may be achieved by pinching or otherwise misshaping the intermediate portion or portion **274** of the tube **273** and placing it within the tube connector **272**.

When the pinch or other force is released, the intermediate portion or portion **274** of the tube **273** may resiliently flex back to its original shape and interface with an inner surface of the tube connector **272**. In an alternative arrangement, tube **273** that may interface with the tube connector **272** by an interference fit such as an isometric taper or a quarter turn lock.

Patient Interface Systems—Tube Connection—Front Surface

Referring to FIGS. **26-33**, a patient interface system **10** according to another example embodiment of the present technology comprises a patient interface structure **20** comprising a front plate **21**, a mouth cushion **23** provided to the front plate **21**, and a nasal cushion **24** provided to the mouth cushion **23**. The front plate **21** comprises a tube connector **42** on a front surface that is configured to receive a tube in a horizontal direction.

A tube may connect directly to the tube connector **42** or may have an intermediate structure such as an elbow or swivel between the tube and the tube connector **42**, possibly shaped to avoid the tube obscuring the headgear connector **22**. The tube connector **42** may have vent holes **25** molded or otherwise formed in it. The tube connector **42** may also have a lip or protruding edge **43**, which may aid in sealing the tube connector **42** to the tube or intermediate structure. The tube connector **42** may have an anti-asphyxia valve (AAV) in form of a flap built in (described in more detail below) that may occlude or block some of the vent holes **25** when air is delivered from the tube and through the tube connector **42**. When air pressure is not supplied, the AAV may flip away from the vent holes to permit the patient to breathe in sufficient atmospheric air.

The rear face of the front plate **21** may have an aperture **44** adapted to permit the flow of air from the tube connector into the mask. The vents **25** may have a thicker cross section than the rest of the tube connector **42** (e.g. they are on a raised rectangular portion) to improve manufacturability. This may also be to increase the length of the vent holes **25** as longer vent holes are typically quieter than comparatively shorter vent holes. The tube connector **42** may follow the same general curvature of the front plate to reduce the visual bulk (i.e. more streamlined look) of the mask and aid in tube management.

Patient Interface Systems—Tube Connection—Elbow

Referring to FIGS. **34-55**, a patient interface system **10** according to another example embodiment of the present technology may comprise an elbow **45** connected substantially perpendicular to the front plate **21**. The elbow **45** may be a swivel elbow or may be a ball joint elbow. The elbow **45** may be removably attachable or molded with the front plate **21**.

Patient Interface Systems—Vents

Referring to FIG. **84**, a patient interface system **10** may comprise a front plate **21** having a vent **25** comprising a plurality of vent holes provided around a perimeter of the front plate **21**. The perimeter arrangement aids diffusivity of the exhaust gases and reduces the visibility of the vent **25**.

Referring to FIG. **85**, a patient interface system **10** may comprise a front plate **21** having a vent **25** that comprises micro-perforated holes over the front surface of the front plate **21**.

Referring to FIG. **113**, a tortuous vent path through front plate **21** may be provided for reducing noise. The tortuous

15

path will slow down the exhaled gases 296 as it moves through the tortuous path, thereby having a lower sound power. The mouth seal may have an interface seal 293 and a flap or castellation 294 that obstructs the vent holes 25, with the exhaled gases 296 moving through the vented pathway 295 of a raised portion 292 of the front plate 21 rather than directly out of the vent holes 25 to increase the length of the path for exhaled gases to get out of the mask. Patient Interface Systems—Tube Cuff

Referring to FIG. 86, a patient interface system 10 may include a mouth cushion 23 having a tube cuff 255 attached to, for example, the side wall 233 of the cushion 23. The tube cuff 255 may be moulded onto the side wall 233 and may have a hardness greater than that of the side wall 233.

Referring to FIG. 95, a tube cuff 268 may be moulded onto the cushion 23 that is configured to be connected to a connector 12, e.g. a swivel connector, that is configured to be connected to a tube 11, for example a tube as disclosed in U.S. Patent Application Publication 2009/0078259 A1, the entire contents of which are incorporated herein by reference. It should be appreciated that the tube cuff 268 may be connected to the cushion by, for example, adhesive or mechanical connectors.

Referring to FIG. 103, a gap 286 between a tube connector 283 and a cuff 284 (having less width when compared to the tube connector for example) may be adapted to receive a headgear strap that extends in a substantially vertical direction. The cuff 284 may include a link or slot 285 to receive a headgear strap that extends in a substantially horizontal direction. The cuff 284 may be soft or relatively flexible. The cuff 284 may be glued on or otherwise attached to the tube connector 283. The cuff 284 may be formed with the tube connector 283.

Patient Interface Systems—Anti-Asphyxia Valves (AAV)

Referring to FIG. 87, a patient interface system 10 may comprise a front plate or lens 21 having a hole 256. An anti-asphyxia valve in the form of a flap 257 formed in the mouth seal or cushion 23 is forced against the front plate 21 and covers the hole 256 when a flow of pressurized gas is delivered through a tube or hose or conduit 258. In the absence of the flow, the flap 257 is released from contact with the front plate 21 and uncovers the hole 256, allowing the patient to breathe ambient air through the hole 256 in the front plate 21.

Referring to FIGS. 88-95, a patient interface system 10 may comprise a front plate 21 having a tube connector 42 configured for connection with a tube or hose or conduit 259. The tube connector 42 comprises an aperture or window 264 that may be closed by an anti-asphyxia valve 260. The anti-asphyxia valve 260 comprises a flap 261 that is configured to open and close the aperture 264. The flap 261 may comprise a vent 25 for venting exhalation gases when the flap 261 closes the aperture 264. The anti-asphyxia valve further includes a tab 262 that secures the anti-asphyxia valve 260 in the tube connector 42 through a slot 265 in the tube connector 42. The flap 261 is pivotably connected to the tab 262 by a hinge 263, e.g. a living hinge. As shown in FIG. 94, in the absence of a flow of gas in the tube connector 42, the flap 261 extends across the tube connector, and the patient may breathe through the aperture 264. When gas flow 266 is delivered to the tube connector 42, the pressure of the gas flow 266 pivots the flap 261 in the direction shown by arrow 267 to close the aperture 264. Exhalation gases may be vented through the vent 25. Referring to FIG. 92, the flap 261 may include elongated vent holes 25 to reduce venting noise and increase diffusivity of the vent flow.

16

Referring to FIGS. 106 and 107, the cushion may have a flap or thin portion 290 around its perimeter that interfaces or otherwise abuts the front plate 21. The flap 290 may be pressure activated i.e. when air is delivered under pressure into the mask, the flap 290 may be forced to abut the front plate 21 causing an air tight seal. If air is no longer delivered to the mask, the flap 290 may relax and permit air from atmosphere into the mask via a gap 291 created between the flap 290 and the front plate 21.

10 Patient Interface Systems—Materials

Referring to FIG. 102, a patient interface system 10 may comprise a polyester front plate or window 279 having a TPE “macro” seal 280 and a low durometer nasal seal 281 comprising pillows, or a seal as disclosed in WO 2010/139014 A1, the entire contents of which are incorporated herein by reference. A foam “micro” seal 275 may be attached to the seal 280. A TPE or TPU headgear 276 may be provided to position the patient interface system on the patient’s head. Elastic webbing or ultrasonic die cut spacer fabric 277 may be provided. A tube connect 278 may be connected to a textile sock 282.

Patient Interface Systems—Headgear Strap and Tube Attachment

Referring to FIGS. 109-112, a headgear strap, e.g. a lower headgear strap that is positioned under the patient’s ears and loops through a slot in the crown strap, may be connected to an air delivery tube. The air delivery tube 298 may connect to an end of the headgear strap 297, with gases being delivered through the headgear clip 299. The clips 299, 300 may interface with the front plate. As shown in FIGS. 111 and 112, the headgear strap 301 may be configured to deliver gases through an air delivery tube 302 and the clips 303, 304 may be formed in such a way that the strap 301 can be oriented either left (FIG. 111) to right or right to left (FIG. 112).

Patient Interface Structure—Patient Interface Positioning System Connection

Referring to FIG. 114, the front plate 21 may include a plurality of attachment locations 305 for the patient interface positioning system, e.g. headgear, and/or a rotatable attachment location 306 that provides adjustment of the angle between the patient interface structure, e.g. mask, and the patient interface positioning system, e.g. headgear. The attachment locations may be in the form of rings 307.

45 Patient Interface Structure—Fascia

The fascia, frame or lens portion may comprise a fixed elbow connection, the elbow connection directed horizontally. Such an arrangement can be seen in, for example, FIG. 99. The fascia be structured and arranged to be flipped or rotated, such that the direction of the elbow may be changed from pointing to the left, for example, to pointing to the right. This means that the fascia may be symmetrical.

While the technology has been described in connection with what are presently considered to be the most practical and preferred embodiments, it is to be understood that the invention is not to be limited to the disclosed embodiments, but on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the invention. Also, the various embodiments described above may be implemented in conjunction with other embodiments, e.g., aspects of one embodiment may be combined with aspects of another embodiment to realize yet other embodiments. Further, each independent feature or component of any given assembly may constitute an additional embodiment. Furthermore, each individual component of any given assembly, one or more portions of an individual component of any given assembly, and various

17

combinations of components from one or more embodiments may include one or more ornamental design features. In addition, while the invention has particular application to patients who suffer from OSA, it is to be appreciated that patients who suffer from other illnesses (e.g., congestive heart failure, diabetes, morbid obesity, stroke, bariatric surgery, etc.) can derive benefit from the above teachings. Moreover, the above teachings have applicability with patients and non-patients alike in non-medical applications.

What is claimed is:

1. A patient interface structure for delivery of respiratory therapy to a patient, the patient interface structure comprising:

a cushion assembly comprising a mouth seal configured to seal around the patient's mouth, a nasal seal configured to seal against at least an underside of the patient's nose, and a pair of nares support portions supporting respective lateral sides of the nasal seal;

a frame attachment structure that is attached to the cushion assembly and adds rigidity to the cushion assembly, the cushion assembly and the frame attachment structure combining to form at least part of a chamber; and  
a frame with a plurality of headgear attachment and a posterior side configured to snap onto the frame attachment structure, the frame comprising:

a first opening on lower side of the frame that is oriented to receive an air delivery tube from a substantially downward direction and direct air in a substantially upward direction;

a second opening on a posterior side of the frame that is oriented to face a second direction to direct air in the second direction; and

an air inlet passage connecting the first opening to the second opening and comprising a first end at the first opening and a second end at the second opening and is configured to sealingly attach to an opening in the chamber,

wherein the air inlet passage is configured to change the direction of air flowing through the air inlet passage from the substantially upward direction at the first end to the second direction at the second end.

2. The patient interface structure of claim 1, wherein the frame is malleable to conform to the shape of the patient's face.

3. The patient interface structure of claim 1, wherein an anterior surface of the frame is substantially planar.

4. The patient interface structure of claim 1, wherein an anterior surface of the frame is generally convex.

5. The patient interface structure of claim 1, wherein the frame is more rigid than the cushion assembly.

6. The patient interface structure of claim 1, wherein the air inlet passage is integrally formed with a main body of the frame.

7. The patient interface structure of claim 1, wherein the air inlet passage is in the form of an elbow.

8. The patient interface structure of claim 1, wherein the air inlet passage is configured to receive the pressurized respiratory gas from below the frame.

9. The patient interface structure of claim 1, wherein the air inlet passage is fixed relative to a main body of the frame.

10. The patient interface structure of claim 1, wherein the second end of the air inlet passage projects from a posterior side of a main body of the frame.

11. The patient interface structure of claim 1, further comprising headgear attachable to the headgear attachment points on the frame,

18

wherein the headgear is configured to support the cushion assembly on the patient's face, and  
wherein the headgear comprises a crown strap configured to cup the crown of the patient's head in use.

12. The patient interface structure of claim 1, wherein the headgear attachment points on the frame include a pair of upper connector slots positioned on opposite lateral sides of the frame.

13. The patient interface structure of claim 12, further comprising headgear attachable to the headgear attachment points on the frame,

wherein the headgear is configured to support the cushion assembly on the patient's face,

wherein the frame comprises a pair of laterally extending arms, and

wherein the upper connector slots are located at respective ends of the laterally extending arms.

14. The patient interface structure of claim 13, wherein the headgear comprises a pair of upper side straps configured to extend over the patient's ears in use, and wherein the upper connector slots are configured to secure the upper side straps to the frame.

15. The patient interface structure of claim 14, wherein the headgear comprises a pair of lower side straps configured to extend below the patient's ears in use, wherein the headgear attachment points on the frame include a pair of lower connector slots positioned on opposite lateral sides of the frame, and wherein the lower connector slots are configured to secure the lower side straps to the frame.

16. The patient interface structure of claim 15, wherein the headgear comprises a rear panel configured to be positioned at a rear of the patient's head in use, and wherein the upper and lower side straps are connected to the rear panel.

17. The patient interface structure of claim 1, wherein the frame comprises a guide for aligning the frame with the cushion assembly.

18. The patient interface structure of claim 1, wherein the air inlet passage comprises an anti-asphyxia valve.

19. The patient interface structure of claim 18, wherein the anti-asphyxia valve comprises a flap configured to cover an aperture in the air inlet passage in use when the pressurized respiratory gas is delivered to the patient interface structure.

20. The patient interface structure of claim 1, wherein the nasal seal comprises raised portions configured to position the nasal seal in use against the flares of the patient's nostrils.

21. The patient interface structure of claim 1, further comprising headgear attachable to the headgear attachment points on the frame,

wherein the headgear is configured to support the cushion assembly on the patient's face,

wherein the frame is malleable to conform to the shape of the patient's face,

wherein an anterior surface of the frame is substantially planar,

wherein the anterior surface of the frame is generally convex,

wherein the frame is more rigid than the cushion assembly,

wherein the air inlet passage is integrally formed with a main body of the frame,

wherein the air inlet passage is in the form of an elbow,

wherein the air inlet passage is configured to receive the pressurized respiratory gas from below the frame,

wherein the air inlet passage is fixed relative to a main body of the frame,

19

wherein the air inlet passage projects in the posterior direction from a main body of the frame,

wherein the headgear comprises a crown strap configured to cup the crown of the patient's head in use,

wherein the headgear attachment points on the frame include a pair of upper connector slots positioned on opposite lateral sides of the frame and a pair of lower connector slots positioned on opposite lateral sides of the frame,

wherein the frame comprises a pair of laterally extending arms, and wherein the upper connector slots are located at respective ends of the laterally extending arms,

wherein the headgear comprises a pair of upper side straps configured to extend over the patient's ears in use, and wherein the upper connector slots are configured to secure the upper side straps to the frame,

wherein the headgear comprises a pair of lower side straps configured to extend below the patient's ears in use, and wherein the lower connector slots are configured to secure the lower side straps to the frame,

20

wherein the headgear comprises a rear panel configured to be positioned at a rear of the patient's head in use, and wherein the upper and lower side straps are connected to the rear panel,

wherein the frame comprises a guide for aligning the frame with the cushion assembly,

wherein the air inlet passage comprises an anti-asphyxia valve,

wherein the anti-asphyxia valve comprises a flap configured to cover an aperture in the air inlet passage in use when the pressurized respiratory gas is delivered to the patient interface structure, and

wherein the nasal seal comprises raised portions configured to position the nasal seal in use against the flares of the patient's nostrils.

**22.** The patient interface structure of claim 1, wherein the pair of nares support portions are configured to support the nasal seal against the sides of the patient's nares.

**23.** The patient interface structure of claim 1, wherein the frame, the cushion assembly, and the frame attachment structure are all configured to be positioned below the patient's eyes, in use.

\* \* \* \* \*