

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12394850
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Hayashi; Yutaka

---

### Battery mounting case

---

#### Abstract

A battery mounting case includes a case main body, a connector, a temporary placing table, and an exchange preparation mechanism. The case main body has a battery storage part that stores a battery, and a battery mounting port that opens to an upper side of the battery storage part. The connector is conductively connected to the battery stored in the case main body. The temporary placing table is movable between a battery storage position in the battery storage part and a battery extracting position outside the battery storage part. The exchange preparation mechanism moves the connector to a detachment position where the connector is separated from the battery and moves the temporary placing table to a position where the battery is able to be supported before moving the temporary placing table from the battery storage position to the battery extracting position.

---

<b>Inventors:</b>	<b>Hayashi; Yutaka (Wako, JP)</b>
<b>Applicant:</b>	<b>HONDA MOTOR CO., LTD. (Tokyo, JP)</b>
<b>Family ID:</b>	<b>1000008762197</b>
<b>Assignee:</b>	<b>HONDA MOTOR CO., LTD. (Tokyo, JP)</b>
<b>Appl. No.:</b>	<b>17/954440</b>
<b>Filed:</b>	<b>September 28, 2022</b>

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20240106051 A1	Mar. 28, 2024

---

#### Publication Classification

**Int. Cl.:** H01M50/244 (20210101); H01M50/262 (20210101); H01M50/271 (20210101);  
H01M50/528 (20210101)

## U.S. Cl.:

CPC     **H01M50/244** (20210101); **H01M50/262** (20210101); **H01M50/271** (20210101);  
**H01M50/528** (20210101); H01M2220/20 (20130101)

## Field of Classification Search

**CPC:**     H01M (50/20); H01M (50/244); H01M (50/271); H01M (2220/20); H01M (6/50); H01M (6/5072); H01M (6/52); H01M (10/42)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2012/0018237	12/2011	Kovach	180/68.5	H01M 50/249
2021/0300167	12/2020	Yamada	N/A	A01D 34/78
2021/0313647	12/2020	Itai et al.	N/A	N/A

### FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103140392	12/2012	CN	N/A
2020/017324	12/2019	WO	N/A

### OTHER PUBLICATIONS

CN103140392 English translation. Yazawa et al. China. Jun. 5, 2013. (Year: 2013). cited by examiner

---

*Primary Examiner:* Domone; Christopher P

*Attorney, Agent or Firm:* Amin, Turocy & Watson, LLP

---

## Background/Summary

### BACKGROUND OF THE INVENTION

#### Field of the Invention

(1) The present invention relates to a battery mounting case that stores a battery therein.

#### Background Art

(2) In electrically powered equipment such as an electric ship, an electric vehicle, or the like, a portable chargeable battery (battery pack) may be used. In this case, in the electrically powered equipment, a battery mounting case for mounting a battery is installed. The battery mounting case includes a battery storage part that stores the battery, and a connector that is able to be connected to the battery in the battery storage part (for example, see PCT International Publication No. 2020/017324).

(3) In the battery mounting case disclosed in Patent Document 1, the battery storage part and the connector are provided in a case main body, and a battery mounting port is formed on a front surface of the case main body. An opening/closing lid that is able to be opened and closed forward and downward while pivoting on a pivot shaft on a lower end side is attached to the front surface of the case main body. A lid-side guide section having an upper surface side on which a battery can be

placed and slidably moved in a state in which the opening/closing lid opens upon exchange of the battery is provided on a surface of the opening/closing lid facing the inside of the case main body.

(4) The battery mounting case can facilitate attaching/detaching work of a battery by a worker by supporting a load of the battery, which is a heavy object, using a lid-side guide section of the opening/closing lid upon exchange of the battery.

#### SUMMARY OF THE INVENTION

(5) In the battery mounting case disclosed in Patent Document 1, upon exchange of the battery, it is necessary to temporarily extract a used battery from the battery storage part and temporarily place it on a floor surface or the like, and then store a charged battery in the battery storage part.

However, if the extracted used battery is placed on a placing surface such as a nearby floor surface and there is water on the placing surface, the water may adhere to a connector connecting portion of the battery.

(6) In addition, when the used battery is extracted from the battery storage part, a worker may temporarily place a charged battery transported from another place on a placing surface such as a nearby floor surface or the like. Even in this case, when there is water on the placing surface, the water may adhere to the connector connecting portion of the battery.

(7) Accordingly, the present invention is directed to providing a battery mounting case with which exchange work of a battery can be performed without temporarily placing a used battery or a charged battery on a nearby floor surface or the like.

(8) A battery mounting case according to an aspect of the present invention includes: a case main body having a battery storage part that stores a battery and a battery mounting port that opens to an upper side of the battery storage part; a connector that is conductively connected to the battery stored in the case main body; a temporary placing table that is movable between a battery storage position in the battery storage part and a battery extracting position outside the battery storage part; and an exchange preparation mechanism that moves the connector to a detachment position where the connector is separated from the battery and moves the temporary placing table to a position where the battery is able to be supported before moving the temporary placing table from the battery storage position to the battery extracting position.

(9) In the configuration described above, when a used battery in the battery storage part is exchanged with another charged battery, the connector is moved to the detachment position by operating the exchange preparation mechanism, and the battery is supported by the temporary placing table in the battery storage part. After that, the temporary placing table is moved from the battery storage position to the battery extracting position. Accordingly, the used battery is moved to the battery extracting position outside the battery storage part, and a space that can store another battery is formed in the battery storage part. After that, a worker stores the charged battery in the battery storage part through the battery mounting port, and then the used battery on the temporary placing table can be extracted.

(10) The exchange preparation mechanism may include an operation part that is operated by a worker; and an interlocking mechanism that moves the connector to the detachment position and moves the temporary placing table to a position where the battery is able to be supported in conjunction with an operation of the operation part in one direction.

(11) In this case, when a worker operates the operation part in one direction, the connector is moved to the detachment position in conjunction with the operation, and the temporary placing table is moved to the position where the battery can be supported. For this reason, when this configuration is employed, extraction preparation of the battery can be completed by a worker with a simple operation.

(12) The battery mounting case may further include an upward biasing portion that biases the connector upward; a displacement restricting portion that restricts upward displacement of the connector; and a restriction release portion that releases displacement restriction of the connector by the displacement restricting portion when the temporary placing table is moved from the battery

storage position to the battery extracting position.

(13) In this case, upon exchange of the battery, in a state in which an operation part is operated in one direction, when the temporary placing table on which the used battery is placed is moved from the battery storage position to the battery extracting position, displacement restriction of the connector by the displacement restricting portion is released by the restriction release portion. Thereby, the connector is biased by the upward biasing portion to protrude upward. After that, when the charged battery is placed on the connector from the battery mounting port, the charged battery receives a biasing force of the upward biasing portion to be held at a predetermined height. When the temporary placing table is operated to move from the battery extracting position toward the battery storage position from this state, the temporary placing table is smoothly inserted below the charged battery.

(14) The battery mounting case may further include a restart function part that restarts displacement restriction of the connector by the displacement restricting portion when the temporary placing table is moved from the battery extracting position toward the battery storage position.

(15) In this case, when the temporary placing table is operated to move from the battery extracting position toward the battery storage position, displacement restriction of the connector by the displacement restricting portion is restarted in a state in which the temporary placing table is inserted below the charged battery. As a result, constant attitudes or heights of the connector and the battery supported by the connector are maintained.

(16) The interlocking mechanism may move the connector to a connecting position to the battery and move the temporary placing table to a position where the table is separated from the battery in conjunction with the operation of the operation part in another direction when the operation part is operated in the other direction after the restriction release portion restarts displacement restriction of the connector by the displacement restricting portion.

(17) In this case, in a state in which the temporary placing table has returned to the battery storage position, when the operation part is operated in the other direction, the interlocking mechanism moves the connector to the connecting position to connect the connector to the charged battery, and the temporary placing table is separated from the battery. Accordingly, when this configuration is employed, connection of the connector to the battery and returning of the temporary placing table to the initial position can be completed by the operation of the operation part in the other direction.

(18) The operation part may be constituted of a lid member that opens and closes the battery mounting port, and the one direction may be a direction in which the lid member opens.

(19) In this case, when the lid member is opened at the time of exchange of the battery, the connector is moved to the detachment position in conjunction with the opening operation of the lid member, and the temporary placing table is moved to a position where the battery can be supported. Accordingly, when the present configuration is employed, the exchange work of the battery can be efficiently performed.

(20) The temporary placing table may be constituted of a pair of rail-shaped members that extend in a direction in which the battery storage position and the battery extracting position are connected, the pair of rail-shaped members may be disposed to be separated in a direction crossing the extension direction of the rail-shaped members, and the connector may be disposed between the pair of rail-shaped members when seen in a direction along the extension direction of the rail-shaped members.

(21) In this case, the pair of rail-shaped members and the connector, which constitute the temporary placing table, can be compactly disposed in the limited space in the battery storage part. In addition, the pair of rail-shaped members can support the battery with good balance at both side positions with the connector connecting portion of the battery sandwiched therebetween.

(22) The interlocking mechanism may include: a lever portion that has a pair of engagement pieces extending in an opposite direction from a pivoting center and pivots in conjunction with the operation part; a connector-side link mechanism that is linked to one of the engagement pieces and

moves the connector to the detachment position by pivoting of the lever portion in one direction; and a temporary placing-table-side link mechanism that is linked to another of the engagement pieces and moves the temporary placing table to a position where the battery is able to be supported by pivoting of the lever portion in one direction.

(23) In this case, when the operation part is operated in one direction, the lever portion is pivoted in one direction in conjunction with the operation part. At this time, the connector and the temporary placing table are operated in an opposite direction in conjunction with the pivoting operation of the lever portion by the connector-side link mechanism and the temporary placing-table-side link mechanism. Accordingly, when the present configuration is employed, the operation of the connector to the detachment position and the moving operation of the temporary placing table to the battery support position can be smoothly performed with a simple configuration.

#### Effects of the Invention

(24) In the battery mounting case according to the aspect of the present invention, upon exchange of the battery, the connector can be moved to the detachment position by the exchange preparation mechanism, and the temporary placing table can be moved to the position where the battery can be supported. Then, in the battery mounting case according to the aspect of the present invention, the charged battery can be stored in the battery storage part through the battery mounting port, and then the used battery can be extracted from the temporary placing table by moving the temporary placing table to the battery extracting position from this state.

(25) Accordingly, when the battery mounting case according to the aspect of the present invention is employed, the exchange work of the battery can be performed without temporarily placing the used battery or the charged battery on a nearby floor surface or the like.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a perspective view of a battery mounting case of an embodiment.

(2) FIG. 2 is a cross-sectional view along line II-II of FIG. 1.

(3) FIG. 3 is a cross-sectional view along line of FIG. 1.

(4) FIG. 4 is a cross-sectional view similar to FIG. 3 showing an operation of the battery mounting case of the embodiment.

(5) FIG. 5 is a cross-sectional view similar to FIG. 3 showing another operation of the battery mounting case of the embodiment.

(6) FIG. 6 is a cross-sectional view similar to FIG. 3 showing still another operation of the battery mounting case of the embodiment.

### EMBODIMENTS

(7) Hereinafter, an embodiment of the present invention will be described with reference to the accompanying drawings.

(8) <Configuration of Embodiment>

(9) FIG. 1 is a perspective view showing a battery mounting case 1 of an embodiment. FIG. 2 is a cross-sectional view along line II-II of FIG. 1 of the battery mounting case 1, and FIG. 3 is a cross-sectional view along line of FIG. 1 of the battery mounting case 1.

(10) The battery mounting case 1 is installed on a power supply mounting portion of something such as an electric ship, an electric vehicle, or the like. The overall shape of the battery mounting case 1 is a substantially parallelepiped shape that is horizontally elongated, and a plurality of batteries 2 can be mounted therein. In the battery mounting case 1 of the embodiment, two batteries 2 can be installed side by side in a longitudinal direction. However, the number of batteries 2 mounted is not limited to two, and may be one or three or more.

(11) The battery mounting case 1 includes a substantially parallelepiped case main body 11 having

two battery storage parts **10**. The case main body **11** opens on an upper surface and one horizontally elongated side surface among six surfaces surrounding the outside of the two battery storage parts **10**. The inside of the case main body **11** is divided into the two battery storage parts **10** by a partition wall **12**.

(12) Hereinafter, for the convenience of description, a side where a side surface opens when seen from an inner side of the case main body **11** is referred to as “front.” In addition, the longitudinal direction of the case main body **11** is referred to as “a widthwise direction.” In addition, at appropriate places in the drawings, an arrow UP indicates a vertically upward direction and an arrow FR indicates a forward direction.

(13) An opening of the case main body **11** on the side of the upper surface is a battery mounting port **13** that opens toward an upper side of the battery storage parts **10**. When the battery **2** is stored in each of the battery storage parts **10**, the corresponding battery **2** is inserted in the battery mounting port **13** from above. The battery mounting port **13** can be opened and closed by a lid member **14**.

(14) An opening of a side surface of the case main body **11** is a battery extraction port **15** that opens toward a front side of the battery storage part **10**. The battery extraction port **15** enables movement of the batteries **2** to the front outside when the batteries **2** are extracted from the battery storage parts **10**. The battery extraction port can be opened and closed by a front wall **16** that is movable forward and rearward.

(15) Further, a caster that abuts and rolls on a floor surface of an installation portion of the battery mounting case **1** may be provided at a lower end of the front wall **16**.

(16) A pair of connectors **17** electrically connected to the batteries **2** accommodated in the battery storage parts **10** are disposed on a bottom wall **11b** of the case main body **11** to be able to move up and down. The connectors **17** are disposed at the bottom portions of each of the two battery storage parts **10**. A power cable and a signal cable (not shown) are connected to each of the connectors **17**. The power cable and the signal cable are extracted to the outside of the case main body **11** and connected to another instrument that requires power supply. In addition, each of the connectors **17** is disposed in the case main body **11** such that a connecting portion to the batteries **2** is directed vertically upward.

(17) The batteries **2** are chargeable portable batteries, and the outside of the battery main body is covered with a resin. A grip portion (not shown) that can be gripped by a worker is formed on an upper surface side of the battery **2**. In addition, a concave connector connecting portion **2c** to which the corresponding connector **17** is detachably connected is provided in a substantially central portion of the bottom surface of the battery **2**. A plurality of terminals (not shown) that can be connected to a wiring on the side of the connector **17** are disposed on the connector connecting portion **2c**. A terminal of the connector connecting portion **2c** is connected to an electrode (not shown) of a main body portion of the battery **2** via a control device (not shown).

(18) The lid member **14** is pivotably connected to an upper end portion of the front wall **16** via a pivot hinge (not shown). The pivot hinge has a pivot shaft in a widthwise direction, and the lid member **14** can pivot with the pivot shaft as a pivot point. The lid member **14** is formed in a substantially rectangular shape when seen in a plan view. The lid member **14** is pivoted to a position that is substantially horizontal to close an upper side of the battery mounting port **13** when the front wall **16** is located at an initial position where the battery extraction port **15** is closed. Accordingly, the upper side of the two battery storage parts **10** in the case main body **11** is closed by the lid member **14**.

(19) A handle **18** that can be gripped by a worker adheres to the front surface of the front wall **16** in the vicinity of the upper portion. The worker can grip the handle **18** to operate the front wall **16** to slide forward and rearward. In addition, a lock portion (not shown) configured to fix the lid member **14** closing the battery mounting port **13** to the case main body **11** is provided between the lid member **14** and the case main body **11**.

(20) Two pairs of rail-shaped members **19** configured to support the batteries **2** on the side of the upper surface protrude from the rear surface of the front wall **16** facing the inside of the battery storage parts **10**. Each of the pairs of rail-shaped members **19** is provided to correspond to one of the two battery storage parts **10** in the case main body **11**. Each of the rail-shaped members **19** extends substantially horizontally in a forward/rearward direction of the battery mounting case **1**. In other words, each of the rail-shaped members **19** extends in a direction in which a battery storage position and a battery extracting position in the battery storage parts **10** are connected. The pairs of rail-shaped members **19** are each separated in the widthwise direction and disposed parallel to each other.

(21) Further, in the embodiment, each of the pairs of rail-shaped members **19** constitutes a temporary placing table that is movable between the battery storage position and the battery extracting position. The batteries **2** can be placed on upper surfaces of each of the pairs of rail-shaped members **19**.

(22) One pair of rail-shaped members **19** are located at both positions in the widthwise direction of the one connector **17** in the case main body **11** when seen in a direction along an extension direction of the rail-shaped members **19**. Similarly, the other pair of rail-shaped members **19** are located at both positions in a widthwise direction of the other connector **17** in the case main body **11** when seen in the direction along the extension direction of the rail-shaped members **19**. In other words, each of the connectors **17** in the case main body **11** is disposed between the corresponding pair of rail-shaped members **19** when seen in the direction along the extension direction of the rail-shaped members **19**.

(23) A base end portion of each of the rail-shaped members **19** is supported by a first link plate **20** disposed in the front wall **16**. The first link plate **20** is constituted by a metal plate member lengthily extending in the upward/downward direction. A major portion of the first link plate **20** is disposed to be raised and lowered in the front wall **16**. A lower end portion of the first link plate **20** is connected to the rail-shaped members **19** via a connecting member **21** extending substantially horizontally on a rear side of the front wall **16**. The rail-shaped members **19** are movable integrally with the first link plate **20** in the upward/downward direction.

(24) An upper end portion of the first link plate **20** can protrude upward from the upper surface of the front wall **16**. A first engagement plate **22** is pivotably connected to an upper end portion of the first link plate **20**. The first engagement plate **22** is engaged with a lever portion **23** pivotably installed inside a front region of the lid member **14** (a region disposed in the pivot hinge). The lever portion **23** is pivotably supported on the upper end portion of the front wall **16**. The two first engagement plates **22** connected to the two rail-shaped members **19** that form a pair are arranged in the widthwise direction and engaged with the common lever portion **23**. The two lever portions **23** correspond to accommodating regions of the accommodated batteries **2** and are disposed to be separated from each other in the widthwise direction. A specific configuration of the lever portion **23** will be described below.

(25) In addition, a second link plate **24** parallel to the first link plate **20** is disposed in the front wall **16**. Like the first link plate **20**, the second link plate **24** is constituted by a metal plate member lengthily extending in the upward/downward direction. A major portion of the second link plate **24** is disposed to be raised or lowered in the front wall **16**. A connector restricting plate **25** extending substantially horizontally on a rear side of the front wall **16** is connected to the lower end portion of the second link plate **24**. The connector restricting plate **25** is constituted by a metal plate member lengthily extending in the forward/rearward direction. The connector restricting plate **25** has a forward/rearward length in which the extension end (rear end portion) substantially reaches the rear end portion of the connector **17** when a width in the widthwise direction is smaller than a width of the connector **17** in the widthwise direction and the front wall **16** is located at an initial position (a position where the battery extraction port **15** is closed).

(26) An upper end portion of the second link plate **24** can protrude upward from the upper surface

of the front wall **16**. A second engagement plate **26** is pivotably connected to the upper end portion of the second link plate **24**. The second engagement plate **26** is engaged with the lever portion **23** installed in the front region of the lid member **14** (the region in which the pivot hinge is disposed). The second engagement plate **26** and the second link plate **24** are disposed between the pair of first engagement plate **22** and the first link plate **20** arranged in the widthwise direction.

(27) The lever portion **23** pivots around a pivoting center **c1** in the front region of the lid member **14**. The pivoting center **c1** is a center of a support shaft (not shown) disposed on an upper side of the front wall **16**. The support shaft extends in the widthwise direction. The lever portion **23** pivots in conjunction with an opening/closing operation (pivoting movement) of the lid member **14**.

(28) The lever portion **23** includes a pair of engagement pieces **35a** and **35b** extending in opposite directions about the pivoting center **c1**. Each of the engagement pieces **35a** and **35b** has a recessed portion **36** that opens in the radial direction about the pivoting center **c1**. The one engagement piece **35a** is engaged with the first engagement plate **22** in the recessed portion **36**. The other engagement piece **35b** is engaged with the second engagement plate **26** in the recessed portion **36**.

(29) FIG. **4** is the same cross-sectional view as FIG. **3** showing a state in which the lid member **14** opens the battery mounting port **13** of the case main body **11**. Further, FIG. **3** shows a state in which the lid member **14** closes the battery mounting port **13** of the case main body **11**.

(30) When the lever portion **23** is in a state in which the lid member **14** closes the battery mounting port **13**, as shown in FIG. **3**, the recessed portion **36** of the one engagement piece **35a** is directed downward on a rear side of the pivoting center **c1**, and the recessed portion **36** of the other engagement piece **35b** is directed upward on a front side of the pivoting center **c1**.

(31) Here, the one engagement piece **35a** pushes the first engagement plate **22** downward into a substantially vertical attitude, and the other engagement piece **35b** pushes the second engagement plate **26** upward into a substantially horizontal attitude. Accordingly, the first link plate **20** is displaced downward in the front wall **16**, and the rail-shaped members **19** connected to the lower end of the first link plate **20** are located at drop positions in the battery storage parts **10**. When the rail-shaped members **19** are located at the drop positions, the upper surfaces of the rail-shaped members **19** are separated from the lower surfaces of the batteries **2** in the battery storage parts **10** from below (not in contact with the lower surfaces of the batteries **2**). In addition, here, the second link plate **24** is displaced upward in the front wall **16**, and the connector restricting plate **25** connected to the lower end of the second link plate **24** is located at a rising position.

(32) When the lid member **14** is pivoted in an opening direction as shown in FIG. **4** from this state, the lever portion **23** is in conjunction with the opening operation of the lid member **14** and pivoted in the same direction as the lid member **14**. Here, the lever portion **23** is provided such that the recessed portion **36** of the one engagement piece **35a** is directed upward on a rear side of the pivoting center **c1** and the recessed portion **36** of the other engagement piece **35b** is directed downward on a front side of the pivoting center **c1**.

(33) Accordingly, the one engagement piece **35a** pushes the first engagement plate **22** upward in a substantially horizontal attitude, and the other engagement piece **35b** pushes the second engagement plate **26** downward in a substantially vertical attitude. Here, the first link plate **20** is displaced upward in the front wall **16**, and the rail-shaped members **19** are moved to the rising position in the battery storage parts **10**. The rail-shaped members **19** abut the lower surfaces of the batteries **2** in the middle of movement to the rising position, and slightly raise the batteries **2** upward from the bottom portions of the battery storage parts **10**. In addition, here, the second link plate **24** is displaced downward in the front wall **16**, and the connector restricting plate **25** moves to a drop position.

(34) The connectors **17** are biased vertically upward by a pair of coil springs **50** that are upward biasing portions below the battery storage parts **10**. Each of the coil springs **50** is disposed on the bottom wall **11b** of the case main body **11**, and the upper surface abuts the lower surface of the connector **17**. In addition, an insertion hole **40** passing in the forward/rearward direction is formed



in the connector **17**.

(35) The connector restricting plate **25** connected to the lower end of the second link plate **24** can be inserted into the insertion hole **40**. The connector restricting plate **25** restricts upward and downward displacement of the connector **17** while being inserted into the insertion hole **40**. The connector restricting plate **25** is located on an outer side of the insertion hole **40** (an outer side of the connector **17**) in a state in which the front wall **16** is moved to the battery extracting position (see FIG. 5). Here, displacement restriction of the connector **17** by the connector restricting plate **25** in the upward/downward direction is released. In addition, the connector restricting plate **25** is located in the insertion hole **40** when the front wall **16** is moved from the battery extracting position toward the battery accommodating position.

(36) As shown in FIG. 2, the insertion hole **40** of the connector **17** has a hole with a substantially rectangular cross section. As shown in FIG. 3 and FIG. 4, a lower surface **40a** of an upper wall of the insertion hole **40** is constituted by a flat surface that substantially horizontally connect the front end position and the rear end portion. Meanwhile, an upper surface **40b** of the lower wall of the insertion hole **40** is constituted by a substantially horizontal flat surface from the rear end portion to a predetermined position on the front side, and the front side of the predetermined position is constituted by an inclined surface **45** inclined downward toward the front side.

(37) The connector restricting plate **25** is inserted into the insertion hole **40** of the connector **17**, and restricts downward displacement of the connector **17** by abutting the lower surface **40a** of the upper wall of the insertion hole **40**. In addition, the connector restricting plate **25** is inserted into the insertion hole **40** of the connector **17**, and restricts upward displacement of the connector **17** by abutting the upper surface **40b** of the lower wall of the insertion hole **40**. In the embodiment, the connector restricting plate **25** constitutes a displacement restricting portion configured to restrict upward displacement of the connector **17** in a state in which the lid member **14** opens (a state in which an operation part is operated).

(38) Further, the connector restricting plate **25** abuts the upper surface **40b** of the lower wall of the insertion hole **40** and restricts excessive upward displacement of the connectors **17** by the coil springs **50** in a state in which the batteries **2** are not stored in the battery storage parts **10**. In addition, the connector restricting plate **25** abuts the lower surface **40a** of the upper wall of the insertion hole **40** and restricts excessive downward displacement of the connectors **17** due to the weight of the batteries **2** in a state in which the batteries **2** are stored in the battery storage parts **10**.

(39) The connector restricting plate **25** is located at the rising position together with the second link plate **24** in a state in which the lid member **14** is closed as described above (see FIG. 3). Here, the connectors **17**, positions of which are restricted by the connector restricting plate **25**, are located at positions to which the connector connecting portions **2c** of the batteries **2** can be connected. In the embodiment, the height positions of the connectors **17** are connecting positions to which the batteries **2** can be connected.

(40) In addition, the connector restricting plate **25** is located at a drop position together with the second link plate **24** in a state in which the lid member **14** opens as described above (see FIG. 4). Here, the connectors **17**, positions of which are restricted by the connector restricting plate **25**, are located at positions where they are separated downward from the connector connecting portions **2c** of the batteries **2**. In the embodiment, the height positions of the connectors **17** are detachment position where the connectors **17** are separated from the connector connecting portions **2c** of the batteries **2**.

(41) In the embodiment, the first link plate **20** and the first engagement plate **22** constitute a connector-side link mechanism configured to move the connectors **17** to the detachment positions according to pivoting of the lever portion **23** in one direction. In addition, the second link plate **24** and the second engagement plate **26** constitute a temporary placing table-side link mechanism configured to move the pair of rail-shaped members **19** (temporary placing table) to positions, where the batteries **2** can be supported, according to pivoting of the lever portion **23** in one

direction.

(42) Further, in the embodiment, the connector-side link mechanism (the first link plate **20**, first engagement plate) and the temporary placing table-side link mechanism (the second link plate **24**, the second engagement plate **26**), which are above-mentioned, constitute an interlocking mechanism together with the lever portion **23**. The interlocking mechanism is in conjunction with an operation (opening operation) of the operation part (the lid member **14**) in one direction to move the connectors **17** to the detachment positions, and move the pair of rail-shaped members **19** (temporary placing table) to positions where the batteries **2** can be supported (see FIG. **4**). In the embodiment, the lid member **14** that is an operation part and the above-mentioned interlocking mechanism constitute an exchange preparation mechanism. The exchange preparation mechanism moves the connectors **17** to the detachment position and moves the pair of rail-shaped members **19** (temporary placing table) to a position where the batteries **2** can be supported, before moving the pair of rail-shaped members **19** (temporary placing table) from the battery storage position to the battery extracting position.

(43) FIG. **5** is the same cross-sectional view as FIG. **3** showing an operation when the front wall **16** is extracted forward to exchange the batteries **2**. FIG. **6** is the same cross-sectional view as FIG. **3** showing an operation when the front wall **16** is closed after the used batteries **2** are extracted.

(44) When the used batteries **2** are exchanged with the charged batteries **2(N)**, for example, a worker grips the handle **18** to move the front wall **16** forward from a state shown in FIG. **4** (a state in which the connectors **17** are separated from the batteries **2** and the pair of rail-shaped members **19** support the batteries **2**). Accordingly, the batteries **2** supported by the pair of rail-shaped members **19** are moved forward together with the front wall **16**.

(45) Here, when the front wall **16** moves to the battery extracting position shown in FIG. **5**, the connector restricting plate **25** extending rearward from the front wall **16** comes off forward from end portions of the connectors **17** on a front side of the insertion hole **40**, and displacement restriction of the connectors **17** by the connector restricting plate **25** is released. As a result, the connectors **17** become free and protrude upward due to the biasing force of the coil springs **50**. Here, spaces in which other batteries **2** can be stored are secured in the battery storage parts **10** of the case main body **11**.

(46) Further, in the embodiment, a portion of the connector **17** deviated forward from the end portion of the insertion hole **40** on the front side (a portion not in contact with the connector restricting plate **25** on the front end side of the insertion hole **40**) constitutes a restriction release portion **42**.

(47) Next, as shown by a downward arrow in FIG. **5**, the charged batteries **2(N)** is inserted into new spaces created in the battery storage parts **10** through the battery mounting port **13**. In this way, when the charged batteries **2(N)** are inserted into the battery storage parts **10**, the batteries **2(N)** are fitted to the connectors **17** and placed on upper portions of the connectors **17**. Here, loads of the batteries **2(N)** are applied to the connectors **17**, and the connectors **17** sink slightly against the biasing force of the coil springs **50**. The charged batteries **2(N)** are held by the connectors **17** and the coil springs **50** at this time.

(48) After that, a worker extracts the used batteries **2** on the pair of rail-shaped members **19** at the battery extracting position. Here, for example, the worker grabs upper grip portions of the batteries **2** and lifts them.

(49) After that, the worker pushes the front wall **16** in an initial position direction on the rear side as shown by a leftward arrow in FIG. **6**. Here, a tip portion of the connector restricting plate **25** protruding rearward from the front wall **16** abuts the inclined surface **45** of the connector **17** on the front side of the insertion hole **40**, and pushes the connector **17** downward as shown by a downward arrow in FIG. **6** using a cam action by the inclined surface **45**. The connector restricting plate **25** is inserted into a region of the insertion hole **40** with no inclined surface **45** when the tip portion exceeds an apex of the inclined surface **45**. During this time, the pair of rail-shaped

members **19** are inserted into the lower surfaces of the batteries **2(N)** at both side positions of the connectors **17** and support the batteries **2(N)** from below.

(50) Further, in the embodiment, the inclined surface **45** of the insertion hole **40** constitutes a restart function part configured to restart displacement restriction of the connectors **17** by the connector restricting plate **25** again after the displacement restriction of the connectors **17** by the connector restricting plate **25** is released by the restriction release portion **42**.

(51) As described above, when the front wall **16** returns to the initial position shown in FIG. **3**, the lid member **14** is operated in a closing direction after that. When the lid member **14** is operated in the closing direction in this way, the lever portion **23** is in conjunction with the lid member **14** to pivot the lid member **14** in the same direction. Here, the first engagement plate **22** is pushed downward in a substantially vertical attitude, and the pair of rail-shaped members **19** move to the drop position together with the first link plate **20**. As a result, the pair of rail-shaped members **19** are separated from below the batteries **2(N)**. In addition, here, the second engagement plate **26** is pushed upward in a substantially horizontal attitude, and the second link plate **24** moves to the rising position together with the connector restricting plate **25**. As a result, the connectors **17** are conductively connected to the batteries **2(N)** at the connector connecting position.

(52) <Effects of Embodiment>

(53) The battery mounting case **1** of the embodiment includes the temporary placing table (the pair of rail-shaped members **19**) movable between the battery storage position and the battery extracting position, and the exchange preparation mechanism. The exchange preparation mechanism moves the connectors **17** to the detachment position and moves the temporary placing table to the position where support of the batteries **2** is possible, before moving the temporary placing table from the battery storage position to the battery extracting position. For this reason, upon exchange of the batteries **2**, the connectors **17** can be moved to the detachment position by the exchange preparation mechanism, and the temporary placing table can be moved to a position where the batteries **2** can be supported. In the battery mounting case **1** of the embodiment, the charged batteries **2(N)** are stored in the battery storage parts **10** through the battery mounting port **13** by moving the temporary placing table to the battery extracting position from this state, and then, the used batteries **2** can be extracted from the temporary placing table.

(54) Accordingly, when the battery mounting case **1** of the embodiment is employed, the exchange work of the batteries **2** can be performed without temporarily placing the used batteries **2** or the charged batteries **2(N)** on the nearby floor surface or the like.

(55) In addition, in the battery mounting case **1** of the embodiment, the exchange preparation mechanism includes the operation part (the lid member **14**) operated by a worker, and the interlocking mechanism in conjunction with an operation of the operation part in one direction to move the connectors **17** to the detachment position and move the temporary placing table (the pair of rail-shaped members **19**) to the battery support position. For this reason, the connectors **17** can be moved to the detachment position in conjunction with the operation of the operation part in the one direction by the worker, and the temporary placing table can be moved to the battery support position.

(56) Accordingly, when the configuration is employed, the exchange preparation of the batteries **2** can be completed by a simple operation by the worker.

(57) In addition, the battery mounting case **1** of the embodiment includes the upward biasing portion (the coil springs **50**) configured to bias the connectors **17** upward, the displacement restricting portion (the connector restricting plate **25**) configured to restrict upward displacement of the connectors **17**, and the restriction release portion **42** configured to release displacement restriction of the connectors **17** by the displacement restricting portion. Then, the restriction release portion **42** releases displacement restriction of the connectors **17** by the displacement restricting portion when the temporary placing table (the pair of rail-shaped members **19**) is moved from the battery storage position to the battery extracting position in a state in which the operation part (the

lid member **14**) is operated by the worker in one direction.

(58) For this reason, upon exchange of the batteries **2**, in a state in which the operation part (the lid member **14**) is operated in one direction, when the temporary placing table on which the used batteries **2(N)** are placed is moved from the battery storage position to the battery extracting position, displacement restriction of the connectors **17** is released by the restriction release portion **42**. As a result, the connectors **17** can be biased by the upward biasing portion and protrude upward, and the charged batteries **2(N)** stored in the battery storage parts **10** can be held at a predetermined height by a biasing force due to the upward biasing portion. Accordingly, when the temporary placing table is operated to move from the battery extracting position to the battery storage position after that, the temporary placing table can be smoothly inserted under the charged batteries **2(N)**.

(59) Accordingly, when the configuration is employed, the temporary placing table can be smoothly returned to the position below the batteries **2(N)** after the charged batteries **2(N)** are disposed in the battery storage parts **10**.

(60) Further, in the battery mounting case **1** of the embodiment, when the temporary placing table (the pair of rail-shaped members **19**) are moved from the battery extracting position toward the battery storage position, the restart function part (the inclined surface **45**) restarts displacement restriction of the connectors **17** by the displacement restricting portion (the connector restricting plate **25**). For this reason, when the temporary placing table is operated to move from the battery extracting position toward the battery storage position, displacement restriction of the connectors **17** by the displacement restricting portion is restarted in a state in which the temporary placing table is inserted below the charged batteries **2(N)**. For this reason, when the temporary placing table is returned to the battery storage position from the battery extracting position, constant attitudes or positions of the connectors **17** and the batteries **2(N)** supported by the connectors **17** can be maintained.

(61) In addition, in the battery mounting case **1** of the embodiment, when the operation part (the lid member **14**) is operated in the other direction after the restriction release portion **42** restarts displacement restriction of the connectors **17** by the displacement restricting portion (the connector restricting plate **25**), the interlocking mechanism moves the connectors **17** to the connecting position and moves the temporary placing table to a position where the temporary placing table (the pair of rail-shaped members **19**) is separated from the batteries **2(N)**. Accordingly, when the configuration is employed, connection of the connectors **17** to the batteries **2(N)** and returning of the temporary placing table to the initial position can be completed by the operation of the operation part in the other direction.

(62) In addition, in the battery mounting case **1** of the embodiment, the operation part is constituted by the lid member **14**, and movement of the connectors **17** to the detachment position and movement of the temporary placing table (the pair of rail-shaped members **19**) to the battery support position are executed in conjunction with the opening operation of the lid member **14**. Accordingly, when the configuration is employed, since there is no need to operate a dedicated operation part separately from the opening operation of the lid member **14**, an exchange work of the batteries **2** can be efficiently performed.

(63) Further, in the battery mounting case **1** of the embodiment, the temporary placing table is constituted by the pair of rail-shaped members **19** extending in the forward/rearward direction, and the pair of rail-shaped members **19** are disposed while being separated in the widthwise direction. Then, the connectors **17** are disposed between the pair of rail-shaped members **19** when seen in the forward/rearward direction. For this reason, when the configuration is employed, the pair of rail-shaped members **19** and the connectors **17**, which are the temporary placing table, can be disposed compactly in the space limited in the battery storage parts **10**. Further, when the configuration is employed, the batteries **2** can be supported with good balance by the pair of rail-shaped members **19** on both sides with the connector connecting portion **2c** sandwiched therebetween.

(64) In addition, in the battery mounting case **1** of the embodiment, the interlocking mechanism includes the lever portion **23**, the connector-side link mechanism (the first link plate **20** and the first engagement plate **22**), and the temporary placing table-side link mechanism (the second link plate **24** and the second engagement plate **26**). Then, the lever portion **23** has the pair of engagement pieces **35a** and **35b** extending in opposite directions about the pivoting center **c1**, and pivots in conjunction with the operation part (the lid member **14**). The connector-side link mechanism is linked to the one engagement piece **35a** to move the connectors **17** to the detachment position according to pivoting of the lever portion **23** in one direction, and the temporary placing table-side link mechanism is linked to the other engagement piece **35b** to move the temporary placing table to the support position of the batteries **2** according to pivoting of the lever portion **23** in one direction. (65) For this reason, the connectors **17** and the temporary placing table (the pair of rail-shaped members **19**) can be operated vertically in opposite directions in conjunction with the pivoting operation of the lever portion **23** by the connector-side link mechanism and the temporary placing table-side link mechanism. Accordingly, when the configuration is employed, the operation of the connectors **17** to the detachment position and the moving operation of the temporary placing table to the battery support position can be smoothly performed while providing the simple configuration.

(66) Further, the present invention is not limited to the above-mentioned embodiment and various design changes may be made without departing from the scope of the present invention.

(67) For example, while the temporary placing table movable between the battery storage position and the battery extracting position is constituted by the pair of rail-shaped members **19** in the above-mentioned embodiment, the temporary placing table is not limited to the rail-shaped member. The temporary placing table may be of any other structure as long as the batteries **2** can be supported when moved.

(68) In addition, while each of the connector-side link mechanism and the temporary placing table-side link mechanism is constituted by the first link plate **20**, the first engagement plate **22**, the second link plate **24**, and the second engagement plate **26** in the above-mentioned embodiment, the components that constitute these link mechanisms do not necessarily have to be plate members. They can also be constituted by, for example, rod-shaped members.

(69) Further, while the link mechanism is employed as the interlocking mechanism configured to move the connectors to the detachment position in conjunction with the operation of the operation part in one direction and move the temporary placing table to the battery support position in the above-mentioned embodiment, the interlocking mechanism is not limited to the link mechanism. The interlocking mechanism can also employ another mechanical mechanism such as a cam mechanism, a gear mechanism, or the like.

(70) In addition, while the exchange preparation mechanism is constituted by the operation part and the mechanical interlocking mechanism (link mechanism) in the above-mentioned embodiment, the exchange preparation mechanism is not limited to the configuration. For example, the exchange preparation mechanism may include a switch operated by a worker, and an actuator configured to move a connector and a temporary placing table in response with an operation of the switch.

#### DESCRIPTION OF REFERENCE NUMERALS

(71) **1** Battery mounting case **2** Battery **10** Battery storage part **11** Case main body **13** Battery mounting port **14** Lid member (operation part) **17** Connector **19** Rail-shaped member (temporary placing table) **20** First link plate (interlocking mechanism, temporary placing table-side link mechanism, exchange preparation mechanism) **22** First engagement plate (interlocking mechanism, temporary placing table-side link mechanism, exchange preparation mechanism) **23** Lever portion (interlocking mechanism, exchange preparation mechanism) **24** Second link plate (interlocking mechanism, connector-side link mechanism, exchange preparation mechanism) **26** Second engagement plate (interlocking mechanism, connector-side link mechanism, exchange preparation mechanism) **35a**, **35b** Engagement pieces **40** Insertion hole (displacement restricting portion) **42**

Restriction release portion **45** Inclined surface (restart function part) **50** Coil spring (upward biasing portion) **c1** Pivoting center

## Claims

1. A battery mounting case comprising: a case main body having a battery storage part that stores a battery and a battery mounting port that opens to an upper side of the battery storage part; a connector that is conductively connected to the battery stored in the case main body; a temporary placing table that is movable between a battery storage position in the battery storage part and a battery extracting position outside the battery storage part; and an exchange preparation mechanism that moves the connector to a detachment position where the connector is separated from the battery and moves the temporary placing table to a position where the battery is able to be supported before moving the temporary placing table from the battery storage position to the battery extracting position.
2. The battery mounting case according to claim 1, wherein the exchange preparation mechanism comprises: an operation part that is operated by a worker; and an interlocking mechanism that moves the connector to the detachment position and moves the temporary placing table to a position where the battery is able to be supported in conjunction with an operation of the operation part in one direction.
3. The battery mounting case according to claim 2, further comprising: an upward biasing portion that biases the connector upward; a displacement restricting portion that restricts upward displacement of the connector; and a restriction release portion that releases displacement restriction of the connector by the displacement restricting portion when the temporary placing table is moved from the battery storage position to the battery extracting position.
4. The battery mounting case according to claim 3, further comprising: a restart function part that restarts displacement restriction of the connector by the displacement restricting portion when the temporary placing table is moved from the battery extracting position toward the battery storage position.
5. The battery mounting case according to claim 4, wherein the interlocking mechanism moves the connector to a connecting position to the battery and moves the temporary placing table to a position where the table is separated from the battery in conjunction with the operation of the operation part in another direction when the operation part is operated in the other direction after the restriction release portion restarts displacement restriction of the connector by the displacement restricting portion.
6. The battery mounting case according to claim 2, wherein the operation part is constituted of a lid member that opens and closes the battery mounting port, and the one direction is a direction in which the lid member opens.
7. The battery mounting case according to claim 1, wherein the temporary placing table is constituted of a pair of rail-shaped members that extend in a direction in which the battery storage position and the battery extracting position are connected, the pair of rail-shaped members are disposed to be separated in a direction crossing the extension direction of the rail-shaped members, and the connector is disposed between the pair of rail-shaped members when seen in a direction along the extension direction of the rail-shaped members.
8. The battery mounting case according to claim 2, wherein the temporary placing table is constituted of a pair of rail-shaped members that extend in a direction in which the battery storage position and the battery extracting position are connected, the pair of rail-shaped members are disposed to be separated in a direction crossing the extension direction of the rail-shaped members, and the connector is disposed between the pair of rail-shaped members when seen in a direction along the extension direction of the rail-shaped members.
9. The battery mounting case according to claim 2, wherein the interlocking mechanism comprises:

a lever portion that has a pair of engagement pieces extending in an opposite direction from a pivoting center and pivots in conjunction with the operation part; a connector-side link mechanism that is linked to one of the engagement pieces and moves the connector to the detachment position by pivoting of the lever portion in one direction; and a temporary placing-table-side link mechanism that is linked to another of the engagement pieces and moves the temporary placing table to a position where the battery is able to be supported by pivoting of the lever portion in one direction.

10. The battery mounting case according to claim 5, wherein the interlocking mechanism comprises: a lever portion that has a pair of engagement pieces extending in an opposite direction from a pivoting center and pivots in conjunction with the operation part; a connector-side link mechanism that is linked to one of the engagement pieces and moves the connector to the detachment position by pivoting of the lever portion in one direction; and a temporary placing-table-side link mechanism that is linked to another of the engagement pieces and moves the temporary placing table to a position where the battery is able to be supported by pivoting of the lever portion in one direction.

---