

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250267114

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Heikkinen; Christie Marie et al.

MEDIA REQUEST SYSTEM

Abstract

A media request system to perform operations that include: receiving, at a client device, a response to a request, the response comprising media content; adding the media content from the response to a collection of media content within a media folder associated with the request at the client device; causing display of a notification at the client device in response to the receiving the response to the request, the notification including an identification of the request; receiving an input that selects the notification; and causing display of a presentation of the collection of media content in response to the input that selects the notification, the presentation of the collection of media content including the media content from the response, according to certain example embodiments.

Inventors: Heikkinen; Christie Marie (Sherman Oaks, CA), Mourkogiannis; Celia Nicole (Los Angeles, CA), Taitz; David Phillip (Los Angeles, CA)

Applicant: Snap Inc. (Santa Monica, CA)

Family ID: 1000008589322

Appl. No.: 19/203985

Filed: May 09, 2025

Related U.S. Application Data

parent US continuation 18054789 20221111 parent-grant-document US 12335214 child US 19203985

parent US continuation 16885007 20200527 parent-grant-document US 11601388 child US 18054789

Publication Classification

Int. Cl.: H04L51/18 (20220101); G06F3/04817 (20220101); G06F3/04845 (20220101); G06F16/432 (20190101); G06F16/48 (20190101); H04L51/10 (20220101);

U.S. Cl.:

CPC H04L51/18 (20130101); G06F3/04817 (20130101); G06F3/04845 (20130101);
G06F16/432 (20190101); G06F16/48 (20190101); H04L51/10 (20130101);
H04L51/224 (20220501); H04L51/226 (20220501); H04L51/52 (20220501);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION [0001] This application is a continuation of U.S. patent application Ser. No. 18/054,789, filed Nov. 11, 2022, which application is a continuation of U.S. patent application Ser. No. 16/885,007, filed May 27, 2020, now issued as U.S. Pat. No. 11,601,388, which are incorporated by reference herein in their entireties.

TECHNICAL FIELD

[0002] Embodiments of the present disclosure relate generally to mobile computing technology and, more particularly, but not by way of limitation, to systems for generating a media folder based on messages received at a client device.

BACKGROUND

[0003] Social messaging applications are platforms that enable the sharing and distribution of various forms of media content. Users of social messaging applications may send and receive messages that include multimedia to one another, wherein the multimedia may include images, videos, or other content.

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[0004] To easily identify the discussion of any particular element or act, the most significant digit or digits in a reference number refer to the figure number in which that element is first introduced.

[0005] FIG. 1 is a block diagram showing an example messaging system for exchanging data (e.g., messages and associated content) over a network in accordance with some embodiments, wherein the messaging system includes a media request system.

[0006] FIG. 2 is block diagram illustrating further details regarding a messaging system, according to example embodiments.

[0007] FIG. 3 is a block diagram illustrating various modules of a media request system, according to certain example embodiments.

[0008] FIG. 4 is a flowchart depicting a method of receiving a response to a request for media content at a client device, according to certain example embodiments.

[0009] FIG. 5 is a flowchart depicting a method of generating a request for media content at a client device, according to certain example embodiments.

[0010] FIG. 6 is a flowchart depicting a method of generating composite media based on a response to a request, according to certain example embodiments.

[0011] FIG. 7 is an interface flow-diagram depicting interfaces presented by a media request system, according to certain example embodiments.

[0012] FIG. 8 is an interface diagram depicting a graphical user interface to access a media folder, according to certain example embodiments.

[0013] FIG. 9 is an interface diagram depicting a graphical user interface to display a collection of media content, according to certain example embodiments.

[0014] FIG. 10 is an interface diagram depicting composite media generated by a media request

system, according to certain example embodiments.

[0015] FIG. 11 is a block diagram illustrating a representative software architecture, which may be used in conjunction with various hardware architectures herein described and used to implement various embodiments.

[0016] FIG. 12 is a block diagram illustrating components of a machine, according to some example embodiments, able to read instructions from a machine-readable medium (e.g., a machine-readable storage medium) and perform any one or more of the methodologies discussed herein.

DETAILED DESCRIPTION

[0017] As discussed above, social messaging applications enable users to share and distribute various forms of media content. For example, users of social messaging applications may send and receive messages that include multimedia to one another, wherein the multimedia may include images, videos, or other content. While existing messaging applications provide users with functionality to distribute media to one another via messages, users are always seeking new and different ways of sharing content with one another.

[0018] Accordingly, the disclosed system seeks to provide users with new and unique methods for interacting with one another by creating and sharing content. In certain example embodiments, a media request system is configured to perform operations that include: receiving, at a client device, a response to a request, the response comprising media content; adding the media content from the response to a collection of media content within a media folder associated with the request at the client device; causing display of a notification at the client device in response to the receiving the response to the request, the notification including an identification of the request; receiving an input that selects the notification; and causing display of a presentation of the collection of media content in response to the input that selects the notification, the presentation of the collection of media content including the media content from the response, according to certain example embodiments.

[0019] A user may generate the request for media to be distributed simultaneously to one or more users. For example, the media request system may cause display of a graphical user interface (GUI) to configure the request, wherein the GUI comprises a presentation of a set of icons that include a “request icon.” According to such embodiments, by selecting the request icon, a user may generate and configure a request which may then be distributed to one or more users. In some embodiments, the request icon may include a “sticker.” A sticker is an illustration, or graphical icon, which may be placed or added at a user-defined position upon media, such as a message, image, or video. In its simplest form, it may be described as an emoticon, developed to add more depth and breadth of expression than what is possible with traditional punctuation or message content. Accordingly, a user may provide an input that selects and moves the request icon to a position on media presented within a GUI at a client device in order to generate the request.

[0020] In some example embodiments, the request generated by the user may include request data that defines a set of media attributes, and wherein a response to the request may be based on the set of media attributes. For example, the request may include a selection of a media filter or lens. A recipient of the request may generate media content to be applied to a response to the request based on the selection of the media filter or lens from the request.

[0021] Responsive to receiving responses to the request, a user may select media content from the responses in order to generate and distribute composite media, wherein the composite media includes the media content from the response.

[0022] Consider an illustrative example from a user perspective. A user may access the media request system at a client device through a specially configured GUI. The media request system presents a GUI that includes a display of a set of sticker, wherein a sticker from among the set of stickers is a “request icon” which the user may move to a position within media presented within the GUI. In some embodiments, the user may additionally select a lens or media filter to be distributed with the request. The media request system may then generate and distribute the request

configured by the user to a plurality of client devices, wherein the request comprises a display of media, such as an image, which includes the request icon at a position defined by the user within the image.

[0023] Recipients of the request (i.e., social network connections of the user) may provide inputs to interact with the request in order to generate a response. For example, a recipient of the request may provide an input that selects the request icon displayed within the media content. In response to receiving the input that selects the request icon, the media request system may present a GUI to generate media based on the selected lens or media filter from the request. The recipient of the request may then send back a response to the request that includes the media content generated based on the selected lens or media filter.

[0024] The media request system may present responses to the request to the user that generated the request in a common media folder at a client device of the user. The user may then navigate through the media folder to view responses to the request. In certain embodiments, the user may select the media content from the media folder in order to generate composite media based on the responses. For example, the composite media may include the media received in a request, along with new media generated by the user. The user may then share the composite media to a plurality of user connections.

[0025] FIG. 1 is a block diagram showing an example messaging system **100** for exchanging data (e.g., messages and associated content) over a network. The messaging system **100** includes one or more client device **102** which host a number of applications including a messaging client application **104**. Each messaging client application **104** is communicatively coupled to other instances of the messaging client application **104** and a messaging server system **108** via a network **106** (e.g., the Internet).

[0026] Accordingly, each messaging client application **104** is able to communicate and exchange data with another messaging client application **104** and with the messaging server system **108** via the network **106**. The data exchanged between messaging client applications **104**, and between a messaging client application **104** and the messaging server system **108**, includes functions (e.g., commands to invoke functions) as well as payload data (e.g., text, audio, video or other multimedia data).

[0027] The messaging server system **108** provides server-side functionality via the network **106** to a particular messaging client application **104**. While certain functions of the messaging system **100** are described herein as being performed by either a messaging client application **104** or by the messaging server system **108**, it will be appreciated that the location of certain functionality either within the messaging client application **104** or the messaging server system **108** is a design choice. For example, it may be technically preferable to initially deploy certain technology and functionality within the messaging server system **108**, but to later migrate this technology and functionality to the messaging client application **104** where a client device **102** has a sufficient processing capacity.

[0028] The messaging server system **108** supports various services and operations that are provided to the messaging client application **104**. Such operations include transmitting data to, receiving data from, and processing data generated by the messaging client application **104**. In some embodiments, this data includes, message content, client device information, geolocation information, media annotation and overlays, message content persistence conditions, social network information, and live event information, as examples. In other embodiments, other data is used. Data exchanges within the messaging system **100** are invoked and controlled through functions available via GUIs of the messaging client application **104**.

[0029] Turning now specifically to the messaging server system **108**, an Application Program Interface (API) server **110** is coupled to, and provides a programmatic interface to, an application server **112**. The application server **112** is communicatively coupled to a database server **118**, which facilitates access to a database **120** in which is stored data associated with messages processed by

the application server **112**.

[0030] Dealing specifically with the Application Program Interface (API) server **110**, this server receives and transmits message data (e.g., commands and message payloads) between the client device **102** and the application server **112**. Specifically, the Application Program Interface (API) server **110** provides a set of interfaces (e.g., routines and protocols) that can be called or queried by the messaging client application **104** in order to invoke functionality of the application server **112**. The Application Program Interface (API) server **110** exposes various functions supported by the application server **112**, including account registration, login functionality, the sending of messages, via the application server **112**, from a particular messaging client application **104** to another messaging client application **104**, the sending of media files (e.g., images or video) from a messaging client application **104** to the messaging server application **114**, and for possible access by another messaging client application **104**, the setting of a collection of media data (e.g., story), the retrieval of a list of friends of a user of a client device **102**, the retrieval of such collections, the retrieval of messages and content, the adding and deletion of friends to a social graph, the location of friends within a social graph, opening and application event (e.g., relating to the messaging client application **104**).

[0031] The application server **112** hosts a number of applications and subsystems, including a messaging server application **114**, an image processing system **116**, a social network system **122**, and media request system **124**. In certain embodiments, the media request system **124** is configured to perform operations that include: receiving, at a client device, a response to a request, the response comprising media content; adding the media content from the response to a collection of media content within a media folder associated with the request at the client device; causing display of a notification at the client device in response to the receiving the response to the request, the notification including an identification of the request; receiving an input that selects the notification; and causing display of a presentation of the collection of media content in response to the input that selects the notification, the presentation of the collection of media content including the media content from the response. Further details of the media request system **124** can be found in FIG. 3 below.

[0032] The messaging server application **114** implements a number of message processing technologies and functions, particularly related to the aggregation and other processing of content (e.g., textual and multimedia content) included in messages received from multiple instances of the messaging client application **104**. As will be described in further detail, the text and media content from multiple sources may be aggregated into collections of content (e.g., called stories or galleries). These collections are then made available, by the messaging server application **114**, to the messaging client application **104**. Other processor and memory intensive processing of data may also be performed server-side by the messaging server application **114**, in view of the hardware requirements for such processing.

[0033] The application server **112** also includes an image processing system **116** that is dedicated to performing various image processing operations, typically with respect to images or video received within the payload of a message at the messaging server application **114**.

[0034] The social network system **122** supports various social networking functions services, and makes these functions and services available to the messaging server application **114**. To this end, the social network system **122** maintains and accesses an entity graph **304** within the database **120**. Examples of functions and services supported by the social network system **122** include the identification of other users of the messaging system **100** with which a particular user has relationships or is “following,” and also the identification of other entities and interests of a particular user.

[0035] The application server **112** is communicatively coupled to a database server **118**, which facilitates access to a database **120** in which is stored data associated with messages processed by the messaging server application **114**.

[0036] FIG. 2 is block diagram illustrating further details regarding the messaging system **100**, according to example embodiments. Specifically, the messaging system **100** is shown to comprise the messaging client application **104** and the application server **112**, which in turn embody a number of some subsystems, namely an ephemeral timer system **202**, a collection management system **204** and an annotation system **206**.

[0037] The ephemeral timer system **202** is responsible for enforcing the temporary access to content permitted by the messaging client application **104** and the messaging server application **114**. To this end, the ephemeral timer system **202** incorporates a number of timers that, based on duration and display parameters associated with a message, collection of messages (e.g., a collection of media), or graphical element, selectively display and enable access to messages and associated content via the messaging client application **104**. Further details regarding the operation of the ephemeral timer system **202** are provided below.

[0038] The collection management system **204** is responsible for managing collections of media (e.g., collections of text, image video and audio data). In some examples, a collection of content (e.g., messages, including images, video, text and audio) may be organized into an “event gallery” or an “event story.” Such a collection may be made available for a specified time period, such as the duration of an event to which the content relates. For example, content relating to a music concert may be made available as a “story” for the duration of that music concert. The collection management system **204** may also be responsible for publishing an icon that provides notification of the existence of a particular collection to the user interface of the messaging client application **104**.

[0039] The collection management system **204** furthermore includes a curation interface **208** that allows a collection manager to manage and curate a particular collection of content. For example, the curation interface **208** enables an event organizer to curate a collection of content relating to a specific event (e.g., delete inappropriate content or redundant messages). Additionally, the collection management system **204** employs machine vision (or image recognition technology) and content rules to automatically curate a content collection. In certain embodiments, compensation may be paid to a user for inclusion of user generated content into a collection. In such cases, the curation interface **208** operates to automatically make payments to such users for the use of their content.

[0040] The annotation system **206** provides various functions that enable a user to annotate or otherwise modify or edit media content associated with a message. For example, the annotation system **206** provides functions related to the generation and publishing of media overlays for messages processed by the messaging system **100**. The annotation system **206** operatively supplies a media overlay (e.g., a filter, lens) to the messaging client application **104** based on a geolocation of the client device **102**. In another example, the annotation system **206** operatively supplies a media overlay to the messaging client application **104** based on other information, such as, social network information of the user of the client device **102**. A media overlay may include audio and visual content and visual effects. Examples of audio and visual content include pictures, texts, logos, animations, and sound effects, as well as animated facial models. An example of a visual effect includes color overlaying. The audio and visual content or the visual effects can be applied to a media content item (e.g., a photo or video) at the client device **102**. For example, the media overlay including text that can be overlaid on top of a photograph generated taken by the client device **102**. In another example, the media overlay includes an identification of a location overlay (e.g., Venice beach), a name of a live event, or a name of a merchant overlay (e.g., Beach Coffee House). In another example, the annotation system **206** uses the geolocation of the client device **102** to identify a media overlay that includes the name of a merchant at the geolocation of the client device **102**. The media overlay may include other indicia associated with the merchant. The media overlays may be stored in the database **120** and accessed through the database server **118**.

[0041] In one example embodiment, the annotation system **206** provides a user-based publication

platform that enables users to select a geolocation on a map, and upload content associated with the selected geolocation. The user may also specify circumstances under which a particular media overlay should be offered to other users. The annotation system **206** generates a media overlay that includes the uploaded content and associates the uploaded content with the selected geolocation. [0042] In another example embodiment, the annotation system **206** provides a merchant-based publication platform that enables merchants to select a particular media overlay associated with a geolocation via a bidding process. For example, the annotation system **206** associates the media overlay of a highest bidding merchant with a corresponding geolocation for a predefined amount of time

[0043] FIG. **3** is a block diagram illustrating components of the media request system **124** that configure the media request system **124** to perform operations to generate media request at a client device **102**, according to certain example embodiments.

[0044] The media request system **124** is shown as including a request module **302**, a media module **304**, and a presentation module **306**, all configured to communicate with each other (e.g., via a bus, shared memory, or a switch). Any one or more of these modules may be implemented using one or more processors **308** (e.g., by configuring such one or more processors to perform functions described for that module) and hence may include one or more of the processors **308**. In certain embodiments, the media request system **124** may include or have access to the database **120**, wherein the database **120** may comprise a collection of media content indexed based on user attributes and astrological signs.

[0045] Any one or more of the modules described may be implemented using hardware alone (e.g., one or more of the processors **308** of a machine) or a combination of hardware and software. For example, any module described of the media request system **124** may physically include an arrangement of one or more of the processors **308** (e.g., a subset of or among the one or more processors of the machine) configured to perform the operations described herein for that module. As another example, any module of the media request system **124** may include software, hardware, or both, that configure an arrangement of one or more processors **308** (e.g., among the one or more processors of the machine) to perform the operations described herein for that module.

Accordingly, different modules of the media request system **124** may include and configure different arrangements of such processors **308** or a single arrangement of such processors **308** at different points in time. Moreover, any two or more modules of the media request system **124** may be combined into a single module, and the functions described herein for a single module may be subdivided among multiple modules. Furthermore, according to various example embodiments, modules described herein as being implemented within a single machine, database, or device may be distributed across multiple machines, databases, or devices.

[0046] FIG. **4** is a flowchart depicting a method **400** for receiving a response to a request for media content at a client device **102**, according to certain example embodiments. Operations of the method **400** may be performed by the modules described above with respect to FIG. **3**. As shown in FIG. **4**, the method **400** includes one or more operations **402**, **404**, **406**, and **408**.

[0047] At operation **402**, a client device **102** receives a response to a request generated by a user of the client device **102**, wherein the response includes media content. In some embodiments, a user of the client device **102** may generate a request for media content that includes a selection of one or more media elements, such as lenses or media filters, and wherein the media content of the response to the request is based on the selection of the one or more media elements of the request.

[0048] At operation **404**, the media module **304** adds the media content received in the response to the request to a collection of media content within a media folder associated with the request. For example, in certain embodiments, responsive to the user generating the request at the client device **102**, the media module **304** may create a folder that corresponds with the request. In some embodiments, the folder may be provisioned locally at the client device **102** or at the databases **120**.

[0049] At operation **406**, the presentation module **306** presents a notification at the client device **102** in response to receiving the response to the request generated by the user at the client device **102**. The notification may for example include an identification of the request.

[0050] At operation **408**, the presentation module **306** causes display of a presentation of the media content in response to an input that selects the notification at the client device **102**. In some embodiments, responsive to receiving an input that selects the notification, the presentation module **306** may access the media folder associated with the request to cause display of a presentation of the collection of media content from the media folder.

[0051] FIG. **5** is a flowchart depicting a method **500** of generating a request for media content at a client device **102**, according to certain example embodiments. Operations of the method **500** may be performed by the modules described above with respect to FIG. **3**. As shown in FIG. **5**, the method **500** includes one or more operations **502**, **504**, **506**, **508** and **510**, that may be performed as a part (i.e., a subroutine) of operation **402** of the method **400**.

[0052] At operation **502**, the presentation module **306** causes display of a GUI that includes a set of icons. For example, as seen in the interface flow diagram **700** of FIG. **7**, the presentation module **306** may generate and cause display of a GUI, such as the GUI **705**, to configure media content to be distributed in a message from the user to a plurality of recipients. The set of icons presented within the GUI **705** may therefore include stickers that the user of the client device **102** may select and position within media content displayed within the GUI **705** (i.e., the image **715**).

[0053] At operation **504**, the media module **304** receives an input that selects a first icon from among the set of icons presented within the GUI generated by the presentation module **306** (i.e., the GUI **705**), wherein the first icon includes a “request icon.” According to certain embodiments, inclusion of the request icon in a message may cause the media request system **124** to perform operations discussed in the method **400** that include generating a media folder that corresponds with the request.

[0054] At operation **506**, the request module **302** receives one or more user identifiers. For example, a user of the client device **102** may provide an input that selects the one or more user identifiers from among a list of user identifiers (i.e., a list of user connections), or in some embodiments, the user of the client device **102** may provide an input that selects or otherwise specifies a user distribution group, wherein the user distribution group comprises a list of the one or more user identifiers.

[0055] At operation **508**, the request module **302** generates a request based on the inputs received from the user of the client device **102**, including the selection of the request icon, the one or more user identifiers, and media content presented within the GUI **705**. For example, as seen in the interface flow diagram **700** of FIG. **7**, the request generated based on the user inputs may include the request **720**. According to certain embodiments, at operation **510**, the media request system **124** may distribute the request **720** based on the one or more user identifiers selected by the user.

[0056] FIG. **6** is a flowchart depicting a method **600** of generating composite media based on a response to a request, according to certain example embodiments. Operations of the method **600** may be performed by the modules described above with respect to FIG. **3**. As shown in FIG. **6**, the method **600** includes one or more operations **602**, **604**, and **606**.

[0057] According to certain embodiments, a user of the media request system **124** may share the media received in responses to the requests. For example, the user may add the media to a story, or media collection, associated with a corresponding user profile. Accordingly, in such embodiments, at operation **602**, the media module **304** receives a selection of the media content received in a response to a request from among a presentation of a collection of media content within a media folder associated with the request. The interface diagram **900** of FIG. **9** illustrates an exemplary media folder **905** that corresponds with a request generated by the user of the media request system **124**.

[0058] For example, the user of the media request system **124** may provide an input to display the

media collection of the media folder **905**, and in response, the presentation module **306** accesses the media collection of the media folder **905**, and causes display of a presentation of the media collection, as seen in the interface diagram **900**.

[0059] At operation **604**, responsive to receiving the selection of the media content from among the presentation of the collection of media content of the media folder, the media module **304** generates composite media based on the selected media content. In some embodiments, the user of the media request system **124** may provide one or more inputs to configure the composite media content. For example, as seen in FIG. **10**, the composite media content **1005** may comprise a display of the selected media content **1010** at a position within an image **1015** generated or selected by the user of the media request system **124**. The user of the media request system **124** may apply text or other graphics to the composite media, such as the text **1020**.

[0060] At operation **606**, the media module **304** generates a message that includes the composite media. The user of the media request system may distribute the composite media to one or more users by providing an input that selects or otherwise identifies the one or more users, or a distribution group that includes the one or more users. In further embodiments, the user of the media request system **124** may send the message to a story, or media collection associated with a corresponding user profile, such that social network connections of the user may access and view the composite media by accessing the user profile.

[0061] FIG. **7** is an interface flow diagram **700** depicting interfaces presented by the media request system **124** to generate a media request, according to certain example embodiments. A request for media content may be generated by a user of the media request system **124** via the GUI **705**.

[0062] As seen in the GUI **705**, an icon **710** (i.e., a media request icon) may be presented among a set of graphical icons within the GUI **705**, along with media, such as the image **715**. A user of the media request system may provide an input **725** that selects the icon **710** and moves the icon **710** to a position within the image **715**. As seen in the flow diagram **700**, the media request system **124** may generate the request **720** based on inputs received from the user of the media request system **124**, via the GUI **705**. The request **720** may be distributed to one or more users.

[0063] FIG. **8** is an interface diagram **800** depicting a GUI **805** to access a media folder **810**, according to certain example embodiments. As seen in the diagram **800**, the GUI **805** may include a display of a list **815** of users that received or otherwise accessed the request generated by the user, as well as an indication **820** of a number of responses to the request which were received.

[0064] FIG. **9** is an interface diagram **900** depicting a GUI **905** to display a collection of media content **910**, according to certain example embodiments. As discussed above, the collection of media content **910** may be associated with a media folder, such as the media folder **810** depicted in FIG. **8**. A user of the media request system **124** may provide an input to select media content from among the collection of media content **910** in order to generate composite media, as depicted in FIG. **10**.

[0065] FIG. **10** is an interface diagram **1000** depicting composite media **1005** generated by the media request system **124**, according to certain example embodiments. As seen in the interface diagram **1000**, the composite media **1005** may comprise media content **1010**, an image **1015**, and text **1020**.

[0066] For example, according to certain example embodiments, a user of the media request system **124** may provide an input that selects a display of the media content **1010** from among a collection of media content associated with a request, such as the collection of media content **905** of the interface diagram **900** depicted in FIG. **9**. The media request system **124** may provide the user with one or more interfaces to generate the composite media **1005**, by providing inputs to select the image **1015**, and to define the text **1020**. Accordingly, the composite media **1005** may be distributed to a plurality of users via a message generated by the media request system **124**, or by adding the composite media **1005** to a story associated with a user profile of the user.

[0067] FIG. 11 is a block diagram illustrating an example software architecture **1106**, which may be used in conjunction with various hardware architectures herein described. FIG. 11 is a non-limiting example of a software architecture and it will be appreciated that many other architectures may be implemented to facilitate the functionality described herein. The software architecture **1206** may execute on hardware such as machine **1200** of FIG. 12 that includes, among other things, processors **1204**, memory **1214**, and I/O components **1218**. A representative hardware layer **1152** is illustrated and can represent, for example, the machine **1100** of FIG. 11. The representative hardware layer **1152** includes a processing unit **1154** having associated executable instructions **1104**. Executable instructions **1104** represent the executable instructions of the software architecture **1106**, including implementation of the methods, components and so forth described herein. The hardware layer **1152** also includes memory and/or storage modules memory/storage **1156**, which also have executable instructions **1104**. The hardware layer **1152** may also comprise other hardware **1158**.

[0068] In the example architecture of FIG. 11, the software architecture **1106** may be conceptualized as a stack of layers where each layer provides particular functionality. For example, the software architecture **1106** may include layers such as an operating system **1102**, libraries **1120**, applications **1116** and a presentation layer **1114**. Operationally, the applications **1116** and/or other components within the layers may invoke application programming interface (API) API calls **1108** through the software stack and receive a response as in response to the API calls **1108**. The layers illustrated are representative in nature and not all software architectures have all layers. For example, some mobile or special purpose operating systems may not provide a frameworks/middleware **1118**, while others may provide such a layer. Other software architectures may include additional or different layers.

[0069] The operating system **1102** may manage hardware resources and provide common services. The operating system **1102** may include, for example, a kernel **1122**, services **1124** and drivers **1126**. The kernel **1122** may act as an abstraction layer between the hardware and the other software layers. For example, the kernel **1122** may be responsible for memory management, processor management (e.g., scheduling), component management, networking, security settings, and so on. The services **1124** may provide other common services for the other software layers. The drivers **1126** are responsible for controlling or interfacing with the underlying hardware. For instance, the drivers **1126** include display drivers, camera drivers, Bluetooth® drivers, flash memory drivers, serial communication drivers (e.g., Universal Serial Bus (USB) drivers), Wi-Fi® drivers, audio drivers, power management drivers, and so forth depending on the hardware configuration.

[0070] The libraries **1120** provide a common infrastructure that is used by the applications **1116** and/or other components and/or layers. The libraries **1120** provide functionality that allows other software components to perform tasks in an easier fashion than to interface directly with the underlying operating system **1102** functionality (e.g., kernel **1122**, services **1124** and/or drivers **1126**). The libraries **1120** may include system libraries **1144** (e.g., C standard library) that may provide functions such as memory allocation functions, string manipulation functions, mathematical functions, and the like. In addition, the libraries **1120** may include A PI libraries **1146** such as media libraries (e.g., libraries to support presentation and manipulation of various media format such as MPREG4, H.264, MP3, AAC, AMR, JPG, PNG), graphics libraries (e.g., an OpenGL framework that may be used to render 2D and 3D in a graphic content on a display), database libraries (e.g., SQLite that may provide various relational database functions), web libraries (e.g., WebK it that may provide web browsing functionality), and the like. The libraries **1120** may also include a wide variety of other libraries **1148** to provide many other APIs to the applications **1116** and other software components/modules.

[0071] The frameworks/middleware **1118** (also sometimes referred to as middleware) provide a higher-level common infrastructure that may be used by the applications **1116** and/or other software components/modules. For example, the frameworks/middleware **1118** may provide

various graphic user interface (GUI) functions, high-level resource management, high-level location services, and so forth. The frameworks/middleware **1118** may provide a broad spectrum of other A PIs that may be utilized by the applications **1116** and/or other software components/modules, some of which may be specific to a particular operating system **1102** or platform.

[0072] The applications **1116** include built-in applications **1138** and/or third-party applications **1140**. Examples of representative built-in applications **1138** may include, but are not limited to, a contacts application, a browser application, a book reader application, a location application, a media application, a messaging application, and/or a game application. Third-party applications **1140** may include an application developed using the ANDROID™ or IOS™ software development kit (SDK) by an entity other than the vendor of the particular platform, and may be mobile software running on a mobile operating system such as IOS™, ANDROID™, WINDOWS® Phone, or other mobile operating systems. The third-party applications **1140** may invoke the API calls **1108** provided by the mobile operating system (such as operating system **1102**) to facilitate functionality described herein.

[0073] The applications **1116** may use built in operating system functions (e.g., kernel **1122**, services **1124** and/or drivers **1126**), libraries **1120**, and frameworks/middleware **1118** to create user interfaces to interact with users of the system. Alternatively, or additionally, in some systems interactions with a user may occur through a presentation layer, such as presentation layer **1114**. In these systems, the application/component “logic” can be separated from the aspects of the application/component that interact with a user.

[0074] FIG. **12** is a block diagram illustrating components of a machine **1200**, according to some example embodiments, able to read instructions from a machine-readable medium (e.g., a machine-readable storage medium) and perform any one or more of the methodologies discussed herein. Specifically, FIG. **12** shows a diagrammatic representation of the machine **1200** in the example form of a computer system, within which instructions **1210** (e.g., software, a program, an application, an applet, an app, or other executable code) for causing the machine **1200** to perform any one or more of the methodologies discussed herein may be executed. As such, the instructions **1210** may be used to implement modules or components described herein. The instructions **1210** transform the general, non-programmed machine **1200** into a particular machine **1200** programmed to carry out the described and illustrated functions in the manner described. In alternative embodiments, the machine **1200** operates as a standalone device or may be coupled (e.g., networked) to other machines. In a networked deployment, the machine **1200** may operate in the capacity of a server machine or a client machine in a server-client network environment, or as a peer machine in a peer-to-peer (or distributed) network environment. The machine **1200** may comprise, but not be limited to, a server computer, a client computer, a personal computer (PC), a tablet computer, a laptop computer, a netbook, a set-top box (STB), a personal digital assistant (PDA), an entertainment media system, a cellular telephone, a smart phone, a mobile device, a wearable device (e.g., a smart watch), a smart home device (e.g., a smart appliance), other smart devices, a web appliance, a network router, a network switch, a network bridge, or any machine capable of executing the instructions **1210**, sequentially or otherwise, that specify actions to be taken by machine **1200**. Further, while only a single machine **1200** is illustrated, the term “machine” shall also be taken to include a collection of machines that individually or jointly execute the instructions **1210** to perform any one or more of the methodologies discussed herein.

[0075] The machine **1200** may include processors **1204**, memory **1206**, and I/O components **1218**, which may be configured to communicate with each other such as via a bus **1202**. The memory **1206** may include a memory **1214**, such as a main memory, or other memory storage, and a storage unit **1216**, both accessible to the processors **1204** such as via the bus **1202**. The storage unit **1216** and memory **1214** store the instructions **1210** embodying any one or more of the methodologies or functions described herein. The instructions **1210** may also reside,

completely or partially, within the memory **1214**, within the storage unit **1216**, within at least one of the processors **1204** (e.g., within the processor's cache memory), or any suitable combination thereof, during execution thereof by the machine **1200**. Accordingly, the memory **1214**, the storage unit **1216**, and the memory of processors **1204** are examples of machine-readable media.

[0076] The I/O components **1218** may include a wide variety of components to receive input, provide output, produce output, transmit information, exchange information, capture measurements, and so on. The specific I/O components **1218** that are included in a particular machine **1200** will depend on the type of machine. For example, portable machines such as mobile phones will likely include a touch input device or other such input mechanisms, while a headless server machine will likely not include such a touch input device. It will be appreciated that the I/O components **1218** may include many other components that are not shown in FIG. **12**. The I/O components **1218** are grouped according to functionality merely for simplifying the following discussion and the grouping is in no way limiting. In various example embodiments, the I/O components **1218** may include output components **1226** and input components **1228**. The output components **1226** may include visual components (e.g., a display such as a plasma display panel (PDP), a light emitting diode (LED) display, a liquid crystal display (LCD), a projector, or a cathode ray tube (CRT)), acoustic components (e.g., speakers), haptic components (e.g., a vibratory motor, resistance mechanisms), other signal generators, and so forth. The input components **1228** may include alphanumeric input components (e.g., a keyboard, a touch screen configured to receive alphanumeric input, a photo-optical keyboard, or other alphanumeric input components), point based input components (e.g., a mouse, a touchpad, a trackball, a joystick, a motion sensor, or other pointing instrument), tactile input components (e.g., a physical button, a touch screen that provides location and/or force of touches or touch gestures, or other tactile input components), audio input components (e.g., a microphone), and the like.

[0077] In further example embodiments, the I/O components **1218** may include biometric components **1230**, motion components **1234**, environmental environment components **1236**, or position components **1238** among a wide array of other components. For example, the biometric components **1230** may include components to detect expressions (e.g., hand expressions, facial expressions, vocal expressions, body gestures, or eye tracking), measure biosignals (e.g., blood pressure, heart rate, body temperature, perspiration, or brain waves), identify a person (e.g., voice identification, retinal identification, facial identification, fingerprint identification, or electroencephalogram based identification), and the like. The motion components **1234** may include acceleration sensor components (e.g., accelerometer), gravitation sensor components, rotation sensor components (e.g., gyroscope), and so forth. The environment components **1236** may include, for example, illumination sensor components (e.g., photometer), temperature sensor components (e.g., one or more thermometer that detect ambient temperature), humidity sensor components, pressure sensor components (e.g., barometer), acoustic sensor components (e.g., one or more microphones that detect background noise), proximity sensor components (e.g., infrared sensors that detect nearby objects), gas sensors (e.g., gas detection sensors to detection concentrations of hazardous gases for safety or to measure pollutants in the atmosphere), or other components that may provide indications, measurements, or signals corresponding to a surrounding physical environment. The position components **1238** may include location sensor components (e.g., a Global Position system (GPS) receiver component), altitude sensor components (e.g., altimeters or barometers that detect air pressure from which altitude may be derived), orientation sensor components (e.g., magnetometers), and the like.

[0078] Communication may be implemented using a wide variety of technologies. The I/O components **1218** may include communication components **1240** operable to couple the machine **1200** to a network **1232** or devices **1220** via coupling **1222** and coupling **1224** respectively. For example, the communication components **1240** may include a network interface component or other suitable device to interface with the network **1232**. In further examples, communication

components **1240** may include wired communication components, wireless communication components, cellular communication components, Near Field Communication (NFC) components, Bluetooth® components (e.g., Bluetooth® Low Energy), Wi-Fi® components, and other communication components to provide communication via other modalities. The devices **1220** may be another machine or any of a wide variety of peripheral devices (e.g., a peripheral device coupled via a Universal Serial Bus (USB)).

[0079] Moreover, the communication components **1240** may detect identifiers or include components operable to detect identifiers. For example, the communication components **1240** may include Radio Frequency Identification (RFID) tag reader components, NFC smart tag detection components, optical reader components (e.g., an optical sensor to detect one-dimensional bar codes such as Universal Product Code (UPC) bar code, multi-dimensional bar codes such as Quick Response (QR) code, Aztec code, Data Matrix, Dataglyph, MaxiCode, PDF417, Ultra Code, UCC RSS-2D bar code, and other optical codes), or acoustic detection components (e.g., microphones to identify tagged audio signals). In addition, a variety of information may be derived via the communication components **1240**, such as, location via Internet Protocol (IP) geo-location, location via Wi-Fi® signal triangulation, location via detecting a NFC beacon signal that may indicate a particular location, and so forth.

Glossary

[0080] “CARRIER SIGNAL” in this context refers to any intangible medium that is capable of storing, encoding, or carrying instructions for execution by the machine, and includes digital or analog communications signals or other intangible medium to facilitate communication of such instructions. Instructions may be transmitted or received over the network using a transmission medium via a network interface device and using any one of a number of well-known transfer protocols.

[0081] “CLIENT DEVICE” in this context refers to any machine that interfaces to a communications network to obtain resources from one or more server systems or other client devices. A client device may be, but is not limited to, a mobile phone, desktop computer, laptop, portable digital assistants (PDAs), smart phones, tablets, ultra books, netbooks, laptops, multi-processor systems, microprocessor-based or programmable consumer electronics, game consoles, set-top boxes, or any other communication device that a user may use to access a network.

[0082] “COMMUNICATIONS NETWORK” in this context refers to one or more portions of a network that may be an ad hoc network, an intranet, an extranet, a virtual private network (VPN), a local area network (LAN), a wireless LAN (WLAN), a wide area network (WAN), a wireless WAN (WWAN), a metropolitan area network (MAN), the Internet, a portion of the Internet, a portion of the Public Switched Telephone Network (PSTN), a plain old telephone service (POTS) network, a cellular telephone network, a wireless network, a Wi-Fi® network, another type of network, or a combination of two or more such networks. For example, a network or a portion of a network may include a wireless or cellular network and the coupling may be a Code Division Multiple Access (CDMA) connection, a Global System for Mobile communications (GSM) connection, or other type of cellular or wireless coupling. In this example, the coupling may implement any of a variety of types of data transfer technology, such as Single Carrier Radio Transmission Technology (1xRTT), Evolution-Data Optimized (EVDO) technology, General Packet Radio Service (GPRS) technology, Enhanced Data rates for GSM Evolution (EDGE) technology, third Generation Partnership Project (3GPP) including 3G, fourth generation wireless (4G) networks, Universal Mobile Telecommunications System (UMTS), High Speed Packet Access (HSPA), Worldwide Interoperability for Microwave Access (WiMAX), Long Term Evolution (LTE) standard, others defined by various standard setting organizations, other long range protocols, or other data transfer technology.

[0083] “EMPIERICAL MESSAGE” in this context refers to a message that is accessible for a time-limited duration. An ephemeral message may be a text, an image, a video and the like. The

access time for the ephemeral message may be set by the message sender. Alternatively, the access time may be a default setting or a setting specified by the recipient. Regardless of the setting technique, the message is transitory.

[0084] “MACHINE-READABLE MEDIUM” in this context refers to a component, device or other tangible media able to store instructions and data temporarily or permanently and may include, but is not be limited to, random-access memory (RAM), read-only memory (ROM), buffer memory, flash memory, optical media, magnetic media, cache memory, other types of storage (e.g., Erasable Programmable Read-Only Memory (EEPROM)) and/or any suitable combination thereof. The term “machine-readable medium” should be taken to include a single medium or multiple media (e.g., a centralized or distributed database, or associated caches and servers) able to store instructions. The term “machine-readable medium” shall also be taken to include any medium, or combination of multiple media, that is capable of storing instructions (e.g., code) for execution by a machine, such that the instructions, when executed by one or more processors of the machine, cause the machine to perform any one or more of the methodologies described herein. Accordingly, a “machine-readable medium” refers to a single storage apparatus or device, as well as “cloud-based” storage systems or storage networks that include multiple storage apparatus or devices. The term “machine-readable medium” excludes signals per se.

[0085] “COMPONENT” in this context refers to a device, physical entity or logic having boundaries defined by function or subroutine calls, branch points, application program interfaces (APIs), or other technologies that provide for the partitioning or modularization of particular processing or control functions. Components may be combined via their interfaces with other components to carry out a machine process. A component may be a packaged functional hardware unit designed for use with other components and a part of a program that usually performs a particular function of related functions. Components may constitute either software components (e.g., code embodied on a machine-readable medium) or hardware components. A “hardware component” is a tangible unit capable of performing certain operations and may be configured or arranged in a certain physical manner. In various example embodiments, one or more computer systems (e.g., a standalone computer system, a client computer system, or a server computer system) or one or more hardware components of a computer system (e.g., a processor or a group of processors) may be configured by software (e.g., an application or application portion) as a hardware component that operates to perform certain operations as described herein. A hardware component may also be implemented mechanically, electronically, or any suitable combination thereof. For example, a hardware component may include dedicated circuitry or logic that is permanently configured to perform certain operations. A hardware component may be a special-purpose processor, such as a Field-Programmable Gate Array (FPGA) or an Application Specific Integrated Circuit (ASIC). A hardware component may also include programmable logic or circuitry that is temporarily configured by software to perform certain operations. For example, a hardware component may include software executed by a general-purpose processor or other programmable processor. Once configured by such software, hardware components become specific machines (or specific components of a machine) uniquely tailored to perform the configured functions and are no longer general-purpose processors. It will be appreciated that the decision to implement a hardware component mechanically, in dedicated and permanently configured circuitry, or in temporarily configured circuitry (e.g., configured by software) may be driven by cost and time considerations. Accordingly, the phrase “hardware component” (or “hardware-implemented component”) should be understood to encompass a tangible entity, be that an entity that is physically constructed, permanently configured (e.g., hardwired), or temporarily configured (e.g., programmed) to operate in a certain manner or to perform certain operations described herein. Considering embodiments in which hardware components are temporarily configured (e.g., programmed), each of the hardware components need not be configured or instantiated at any one instance in time. For example, where a hardware component comprises a

general-purpose processor configured by software to become a special-purpose processor, the general-purpose processor may be configured as respectively different special-purpose processors (e.g., comprising different hardware components) at different times. Software accordingly configures a particular processor or processors, for example, to constitute a particular hardware component at one instance of time and to constitute a different hardware component at a different instance of time. Hardware components can provide information to, and receive information from, other hardware components. Accordingly, the described hardware components may be regarded as being communicatively coupled. Where multiple hardware components exist contemporaneously, communications may be achieved through signal transmission (e.g., over appropriate circuits and buses) between or among two or more of the hardware components. In embodiments in which multiple hardware components are configured or instantiated at different times, communications between such hardware components may be achieved, for example, through the storage and retrieval of information in memory structures to which the multiple hardware components have access. For example, one hardware component may perform an operation and store the output of that operation in a memory device to which it is communicatively coupled. A further hardware component may then, at a later time, access the memory device to retrieve and process the stored output. Hardware components may also initiate communications with input or output devices, and can operate on a resource (e.g., a collection of information). The various operations of example methods described herein may be performed, at least partially, by one or more processors that are temporarily configured (e.g., by software) or permanently configured to perform the relevant operations. Whether temporarily or permanently configured, such processors may constitute processor-implemented components that operate to perform one or more operations or functions described herein. As used herein, “processor-implemented component” refers to a hardware component implemented using one or more processors. Similarly, the methods described herein may be at least partially processor-implemented, with a particular processor or processors being an example of hardware. For example, at least some of the operations of a method may be performed by one or more processors or processor-implemented components. Moreover, the one or more processors may also operate to support performance of the relevant operations in a “cloud computing” environment or as a “software as a service” (SaaS). For example, at least some of the operations may be performed by a group of computers (as examples of machines including processors), with these operations being accessible via a network (e.g., the Internet) and via one or more appropriate interfaces (e.g., an Application Program Interface (API)). The performance of certain of the operations may be distributed among the processors, not only residing within a single machine, but deployed across a number of machines. In some example embodiments, the processors or processor-implemented components may be located in a single geographic location (e.g., within a home environment, an office environment, or a server farm). In other example embodiments, the processors or processor-implemented components may be distributed across a number of geographic locations.

[0086] “PROCESSOR” in this context refers to any circuit or virtual circuit (a physical circuit emulated by logic executing on an actual processor) that manipulates data values according to control signals (e.g., “commands”, “op codes”, “machine code”, etc.) and which produces corresponding output signals that are applied to operate a machine. A processor may, for example, be a Central Processing Unit (CPU), a Reduced Instruction Set Computing (RISC) processor, a Complex Instruction Set Computing (CISC) processor, a Graphics Processing Unit (GPU), a Digital Signal Processor (DSP), an Application Specific Integrated Circuit (ASIC), a Radio-Frequency Integrated Circuit (RFIC) or any combination thereof. A processor may further be a multi-core processor having two or more independent processors (sometimes referred to as “cores”) that may execute instructions contemporaneously.

[0087] “TIMESTAMP” in this context refers to a sequence of characters or encoded information identifying when a certain event occurred, for example giving date and time of day, sometimes

accurate to a small fraction of a second.

[0088] “LIFT” in this context is a measure of the performance of a targeted model at predicting or classifying cases as having an enhanced response (with respect to a population as a whole), measured against a random choice targeting model.

[0089] “PHONEME ALIGNMENT” in this context, a phoneme is a unit of speech that differentiates one word from another. One phoneme may consist of a sequence of closure, burst, and aspiration events; or, a diphthong may transition from a back vowel to a front vowel. A speech signal may therefore be described not only by what phonemes it contains, but also the locations of the phonemes. Phoneme alignment may therefore be described as a “time-alignment” of phonemes in a waveform, in order to determine an appropriate sequence and location of each phoneme in a speech signal.

[0090] “AUDIO-TO-VISUAL CONVERSION” in this context refers to the conversion of audible speech signals into visible speech, wherein the visible speech may include a mouth shape representative of the audible speech signal.

[0091] “TIME DELAYED NEURAL NETWORK (TDNN)” in this context, a TDNN is an artificial neural network architecture whose primary purpose is to work on sequential data. An example would be converting continuous audio into a stream of classified phoneme labels for speech recognition.

[0092] “BI-DIRECTIONAL LONG-SHORT TERM MEMORY (BLSTM)” in this context refers to a recurrent neural network (RNN) architecture that remembers values over arbitrary intervals. Stored values are not modified as learning proceeds. RNNs allow forward and backward connections between neurons. BLSTM are well-suited for the classification, processing, and prediction of time series, given time lags of unknown size and duration between events.

Claims

1. A method comprising: receiving a media request from a client device, the media request including an identification of one or more recipients that include a recipient, and a selection of a media overlay from among a plurality of media overlays, the identification of the recipient including a user identifier, and the media overlay comprising a set of media attributes; provisioning a folder associated with the media request at the client device, responsive to receiving the media request; receiving a response from the recipient of the media request, the response including media content generated based on the set of media attributes of the media overlay identified by the selection; adding the media content to the folder associated with the media request at the client device, the folder comprising a plurality of media content included within responses to the media request; causing display of the plurality of media content included within responses to the media request; receiving a selection of a piece of media content from the plurality of media content; generating a user interface creating a composite media content, the composite media content comprising a selection of an image, a text input, and the piece of media content; and adding the composite media content to a message and distributing the message to a plurality of users.
2. The method of claim 1, wherein the user identifier includes a graphical avatar.
3. The method of claim 1, further comprising adding the composite media to a story associated with the client device.
4. The method of claim 1, further comprising displaying a collection of media content and receiving a user input to select media content from the collection of media content.
5. The method of claim 4, further comprising generating composite media based on the user input.
6. The method of claim 1, wherein the response from the recipient of the media request includes a text string entered via a text input field.
7. The method of claim 6, further comprising adding the text string to the folder associated with the media request.

8. A system comprising: a memory; and at least one hardware processor coupled to the memory and comprising instructions that causes the system to perform operations comprising: receiving a media request from a client device, the media request including an identification of one or more recipients that include a recipient, and a selection of a media overlay from among a plurality of media overlays, the identification of the recipient including a user identifier, and the media overlay comprising a set of media attributes; provisioning a folder associated with the media request at the client device, responsive to receiving the media request; receiving a response from the recipient of the media request, the response including media content generated based on the set of media attributes of the media overlay identified by the selection; adding the media content to the folder associated with the media request at the client device, the folder comprising a plurality of media content included within responses to the media request; causing display of the plurality of media content included within responses to the media request; receiving a selection of a piece of media content from the plurality of media content; generating a user interface creating a composite media content, the composite media content comprising a selection of an image, a text input, and the piece of media content; and adding the composite media content to a message and distributing the message to a plurality of users.

9. The system of claim 8, wherein the user identifier includes a graphical avatar.

10. The system of claim 8, further comprising adding the composite media to a story associated with the client device.

11. The system of claim 8, further comprising displaying a collection of media content and receiving a user input to select media content from the collection of media content.

12. The system of claim 11, further comprising generating composite media based on the user input.

13. The system of claim 11, wherein the response from the recipient of the media request includes a text string entered via a text input field.

14. The system of claim 11, further comprising adding the text string to the folder associated with the media request.

15. A non-transitory machine-readable storage medium comprising instructions that, when executed by one or more processors of a machine, cause the machine to perform operations comprising: receiving a media request from a client device, the media request including an identification of one or more recipients that include a recipient, and a selection of a media overlay from among a plurality of media overlays, the identification of the recipient including a user identifier, and the media overlay comprising a set of media attributes; provisioning a folder associated with the media request at the client device, responsive to receiving the media request; receiving a response from the recipient of the media request, the response including media content generated based on the set of media attributes of the media overlay identified by the selection; adding the media content to the folder associated with the media request at the client device, the folder comprising a plurality of media content included within responses to the media request; causing display of the plurality of media content included within responses to the media request; receiving a selection of a piece of media content from the plurality of media content; generating a user interface creating a composite media content, the composite media content comprising a selection of an image, a text input, and the piece of media content; and adding the composite media content to a message and distributing the message to a plurality of users.

16. The non-transitory machine-readable storage medium of claim 15, wherein the user identifier includes a graphical avatar.

17. The non-transitory machine-readable storage medium of claim 15, further comprising adding the composite media to a story associated with the client device.

18. The non-transitory machine-readable storage medium of claim 15, further comprising displaying a collection of media content and receiving a user input to select media content from the collection of media content.

19. The non-transitory machine-readable storage medium of claim 18, further comprising generating composite media based on the user input.
