

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12392403
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Wickliffe; Christoper A.

---

### Bicycle chainring with offset and full wide teeth

---

#### Abstract

A bicycle chain ring having a plurality of teeth extending radially about an axis of the chain ring, the plurality of teeth including a first group of teeth and a second group of teeth. The first group of teeth has a first width at a tooth base that is sized to be received within a chain cavity defined between parallel links of a bicycle chain. The second group of teeth has a second width at the tooth base, the second width being different from the first width. Further, the first group of teeth have a tooth tip that is substantially centered on a plane defined between an inner surface and an outer surface of the chain ring and the second group of teeth is at least partially offset from the plane.

---

<b>Inventors:</b>	<b>Wickliffe; Christoper A. (Ogden, UT)</b>
<b>Applicant:</b>	<b>WICK WERKS LLC (Ogden, UT)</b>
<b>Family ID:</b>	<b>1000008764378</b>
<b>Assignee:</b>	<b>WICK WERKS LLC (Ogden, UT)</b>
<b>Appl. No.:</b>	<b>17/943507</b>
<b>Filed:</b>	<b>September 13, 2022</b>

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20230366457 A1	Nov. 16, 2023

#### Related U.S. Application Data

us-provisional-application US 63342583 20220516

---

#### Publication Classification

**Int. Cl.:** F16H55/30 (20060101); B62M9/00 (20060101)

## U.S. Cl.:

CPC      **F16H55/30** (20130101); **B62M9/00** (20130101); B62M2009/005 (20130101)

## Field of Classification Search

**CPC:**      F16H (55/30); F16H (7/18); B62M (9/30)

**USPC:**    474/152; 474/140

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9062758	12/2014	Reiter	N/A	N/A
9291250	12/2015	Reiter et al.	N/A	N/A
9463844	12/2015	Fukunaga	N/A	B62M 9/10
9731791	12/2016	Reiter et al.	N/A	N/A
10352397	12/2018	Kamada	N/A	B62M 9/10
10358186	12/2018	Sugimoto	N/A	B62M 9/105
10378638	12/2018	Chin	N/A	F16H 55/30
10451166	12/2018	Winans	N/A	F16G 13/06
10563746	12/2019	Barefoot	N/A	B62M 9/00
10808824	12/2019	Sugimoto	N/A	B62M 9/10
2015/0239528	12/2014	Barefoot	474/152	F16H 55/30
2016/0053882	12/2015	Watarai	474/152	F16H 55/30
2016/0208903	12/2015	Goates	N/A	B62M 9/105
2016/0347409	12/2015	Watarai	N/A	B62M 9/02
2017/0234418	12/2016	Barefoot	474/156	F16H 55/30
2018/0112764	12/2017	Sugimoto	N/A	B62M 9/00
2018/0347680	12/2017	Akanishi	N/A	F16H 55/30
2020/0149621	12/2019	Barefoot	N/A	F16H 55/30

---

*Primary Examiner:* Momper; Anna M

*Assistant Examiner:* Campos, Jr.; Juan J

*Attorney, Agent or Firm:* Taft Stettinius & Hollister LLP

---

## Background/Summary

CROSS REFERENCE TO RELATED DISCLOSURE (1) The present disclosure claims the benefit of U.S. Provisional Application No. 63/342,583 filed May 16, 2022, the contents of which are incorporated herein by reference in entirety.

### FIELD OF THE DISCLOSURE

(1) The present disclosure relates to a bicycle chain ring and more specifically to a bicycle chain ring with teeth having offset widths.

### BACKGROUND

(2) This invention relates to bicycle components, and in particular to chainrings used in bicycles. Bicycles commonly use a roller chain to transfer force from a pedal through a crank to a sprocket (a chainring) or set of sprockets (chainrings) in a crankset, and then via the chain to another sprocket or set of sprockets connected to the axle of the wheel to be turned by the force. Sprockets at either the front or rear transfer torque from the cyclist by engaging sprocket teeth between the rollers of the bicycle drive chain—a chain made up of segments or links—with the links typically made with plates that are joined via pins passing through the link plates and rollers. The links are assembled with one set of joining plates inside (nearer the rollers) and one of joining plates set outside, thus creating the inner and outer chain links. Thus there is a side-to-side spacing difference for the inner and outer links.

(3) The teeth of the sprocket extend into the spaces or gaps bounded between rollers longitudinally, and between the side plates axially. To match as exactly as practical these spaces, one prior solution is to make every other tooth of the sprocket wider, so as to fit closely between the outer links of the chain. Then, each narrow tooth (every other tooth in the arrangement) is made to fit loosely between the inner links of the chain. This configuration is frequently called “Narrow-Wide” in the bicycling industry, and will be referred to as “Narrow-Wide” hereinafter. This Narrow-Wide configuration offers some advantages in 1) chain retention (when the bicycle is ridden on very rough terrain, as in mountain biking, the chain can be violently jostled but stay in place); and 2) keeping the chain tracking onto the chainring even when front and rear sprockets are not co-planar.

(4) Traditional chainrings with teeth of all the same width in a straight alignment, with no tooth that is “wide” or “narrow” compared to the other teeth, are also used for bicycle applications. These chainrings have been the most common, but have been known to “throw” the chain in really rough terrain—especially when the chain alignment is such that the front sprocket on the crankset and the rear sprocket on the wheel axle are not aligned upon the same plane.

#### SUMMARY

(5) One embodiment of this disclosure is a bicycle chain ring that has a plurality of teeth extending radially about an axis of the chain ring, the plurality of teeth including a first group of teeth and a second group of teeth. The first group of teeth have a first width at a tooth base that is sized to be received within a chain cavity defined between parallel links of a bicycle chain. The second group of teeth has a second width at the tooth base, the second width being different from the first width. Further, the first group of teeth have a tooth tip that is substantially centered on a plane defined between an inner surface and an outer surface of the chain ring and the second group of teeth are at least partially offset from the plane.

(6) In one example of this embodiment, the second width is less than the first width.

(7) Another example of this embodiment has a third group of teeth having a third width that is different from the first width. In one aspect of this example the third width is less than the first width. In another aspect of this example the second group of teeth is offset to an inward side of the plane and the third group of teeth is offset to an outward side of the plane.

(8) In yet another example of this embodiment, the first width is about the width of the space between two outer chain links of a bicycle chain. In one aspect of the example, the second width is less than the width of the space between two inner chain links of a bicycle chain. One aspect of this example has a series of teeth that is a first tooth from the first group of teeth followed by a second tooth from the second group of teeth followed by a third tooth from the third group of teeth. In one part of this aspect, the series of teeth continues around the entire circumference of the chain ring.

(9) Another aspect of this example is a sequence of teeth around the chain ring that is a first tooth from the first group of teeth followed by a second tooth from the second group of teeth followed by a third tooth from the first group of teeth. In a further aspect of this example, the third tooth is followed by a fourth tooth from the second group of teeth followed by a fifth tooth from the third group of teeth followed by a sixth tooth from the second group of teeth followed by a seventh tooth from the first group of teeth.

---

## Description

### BRIEF DESCRIPTION OF THE FIGURES

- (1) FIG. 1a is a right side perspective view of an embodiment of a chainring of the invention installed in a bicycle crankset, with a segment of roller chain engaged on the chainring.
- (2) FIG. 1b is a left side perspective view of an embodiment of a chainring of the invention installed in a bicycle crankset, with a segment of roller chain engaged on the chainring.
- (3) FIG. 2 is a side perspective view of a segment of a conventional roller chain.
- (4) FIG. 3 is a top view of a segment of the roller chain of FIG. 2.
- (5) FIG. 4 is a side view of a segment of the roller chain of FIG. 2.
- (6) FIG. 5 is a right side perspective view of an embodiment of a chainring of the invention.
- (7) FIG. 6 is an enlarged view of a portion of a periphery of the chainring as shown in FIG. 5.
- (8) FIG. 7 is a left side perspective view of the chainring of the invention
- (9) FIG. 8 is an enlarged view of a portion of a periphery of the chainring as shown in FIG. 7.
- (10) FIG. 9 is a right side view of the chainring of the invention.
- (11) FIG. 10 is a top view of the chainring of the invention.
- (12) FIG. 11 is a left side view of the chainring of the invention.
- (13) FIG. 12 is a top view of the chainring.
- (14) FIG. 13 is an enlarged view of a portion of the chainring as shown in FIG. 12.
- (15) FIG. 14 is a right side view of an embodiment of the chain drive of the invention.
- (16) FIG. 15 is a top view of a chainring of this disclosure with a chain partially thereon.
- (17) FIG. 16 is an enlarged view of a portion of the chainring and chain shown in FIG. 15.
- (18) FIG. 17 is right side view of an embodiment of the chain drive of this disclosure with a chain thereon.
- (19) FIG. 18 is a top view of another embodiment of a chainring with a chain thereon.
- (20) FIG. 19 is an enlarged view of the chainring and chain of FIG. 18.
- (21) FIG. 20 is a side view of the chainring and chain from FIG. 18.
- (22) FIG. 21 is a comparison of a Narrow-Wide chainring configuration and a Custom-Wide configuration of this disclosure.
- (23) FIG. 22 is an illustrative embodiment of one tooth arrangement configuration of this disclosure.
- (24) FIG. 23 is an illustrative embodiment of another traditional tooth configuration compared to one embodiment of a custom-wide configuration contemplated herein.
- (25) FIG. 24 is an illustrative embodiment of one tooth arrangement configuration of this disclosure.
- (26) FIG. 25 is an illustrative embodiment of one tooth arrangement configuration of this disclosure.
- (27) FIG. 26 is an illustrative embodiment of another tooth arrangement configuration of this disclosure.
- (28) FIG. 27 is an illustrative embodiment of a chainring having an offset tooth arrangement and a curved tooth configuration.
- (29) FIG. 28 is a top view of the chainring of FIG. 27.
- (30) FIG. 29 is a back view of the chainring of FIG. 27.
- (31) FIG. 30 is a top view of the chainring of FIG. 27 with a chain thereon.
- (32) FIG. 31 is a detail section view of FIG. 30.
- (33) FIG. 32 is a side view of FIG. 30.
- (34) FIG. 33 is a side view of one embodiment of a 28 tooth chainring.
- (35) FIG. 34 is a side view of one embodiment of a 30 tooth chainring.
- (36) FIG. 35 is a side view of one embodiment of a 32 tooth chainring.

- (37) FIG. **36** is a side view of one embodiment of a 34 tooth chainring.  
(38) FIG. **37** is a side view of one embodiment of a 36 tooth chainring.  
(39) FIG. **38** is a side view of one embodiment of a 38 tooth chainring.  
(40) FIG. **39** is a section view through a full wide tooth of a chainring of this disclosure.  
(41) FIG. **40** is a section view through an offset left tooth of a chainring of this disclosure.  
(42) FIG. **41** is a section view through an offset wider right tooth of a chainring of this disclosure.  
(43) FIG. **42** is a side view of one embodiment of a full wide outer and inner link configuration.  
(44) FIG. **43** is an embodiment of the tooth pattern from the embodiment of FIG. **42**.  
(45) FIG. **44** is a side view of one embodiment of full wide inner links with patterned offset right links.  
(46) FIG. **45** is an embodiment of the tooth pattern from the embodiment of FIG. **44**;  
(47) FIG. **46** is a side view of an embodiment having full inner links with offset wider left links;  
(48) FIG. **47** is an embodiment of the tooth pattern from the embodiment of FIG. **46**.  
(49) FIG. **48** is a side view of one embodiment of full wide inner links with patterned offset right links.  
(50) FIG. **49** is an embodiment of the tooth pattern from the embodiment of FIG. **48**.  
(51) The drawings illustrate exemplary embodiments for carrying out the invention. Like reference numerals refer to like parts in different views or embodiments of the present invention in the drawings.

#### DETAILED DESCRIPTION

- (52) The embodiments of the present disclosure described below are not intended to be exhaustive or to limit the disclosure to the precise forms in the following detailed description. Rather, the embodiments are chosen and described so that others skilled in the art may appreciate and understand the principles and practices of the present disclosure.
- (53) FIGS. **1A** and **1B** illustrate a chainring of this disclosure coupled to a crankset in one configuration. FIGS. **1A** and **1B** do not specifically illustrate the remaining component of a bicycle, but a person skilled in the art understands that the crankset would typically be mounted to a frame and pedals and the chain would be connected to a rear sprocket to drive the rear sprocket and rear wheel as the crankset is rotated via the chain.
- (54) The chain may be a typical chain **100** known in the industry and formed of alternating outer links **302** and inner links **304** spaced parallel from one another as illustrated in FIGS. **2-4**. Pairs of parallel outer links **302** may be pivotally coupled to adjacent pairs of parallel inner links **304** through a pivot pin **306**. Any number of outer **302** and inner links **304** may be coupled to one another to form a chain **100** of the appropriate length for the application. Once the appropriate length of the chain **100** is determined, the links **302**, **304** of the chain may be coupled together to form a closed loop that is directed around the chainring and sprocket of the bicycle. The space between the outer links **302** may have a wide width cavity **308** there between while the space between the inner links **304** may have a narrow width cavity **310** there between. The wide width **308** may be wider than the narrow width **310**. In use, the chain **100** wraps partially around a chainring coupled to a crankset and back around a sprocket of a rear wheel. When a user applies torque to the crankset through pedaling, the teeth of the chainring contact the pivot pins **306** and transfer the torque to teeth of the sprocket of the rear wheel which in turn rotates the rear wheel.
- (55) Referring now to FIGS. **5-20**, different embodiments of a chainring of this disclosure are illustrated having combinations of full wide teeth and offset teeth arranged about the chainring. More specifically with reference to FIGS. **6** and **8**, one embodiment of a chainring **500** of this disclosure is illustrated. The chainring **500** has teeth that are offset right **502**, offset left **504**, and teeth that are full **506**. The chainring **500** may have a central plane **1602** formed substantially parallel to, and between, a first plane **1604** and a second plane **1606**. The first plane **1606** may be defined along an inner surface of a chain link **302**, **304** of a cavity **308**, **310** while the second plane **1604** may be defined along an inner surface of an opposite chain link **302**, **304** of the cavity **308**,

**310** when a corresponding chain **300** is properly positioned along the chainring **500**. In other words, the central plane **1602** runs substantially through the center of any chain **300** properly positioned and tensioned around the chainring.

(56) The offset wider right teeth **502** may have a section that is at least partially offset to the right, of the central plane **1602**. The offset wider right teeth **502** may contact or otherwise be biased towards the first plane **1604** of the corresponding cavity **308** of the chain when positioned therein. Further, the offset wider right teeth **502** may provide at least a slightly spaced portion in the cavity **310** of the chain when properly positioned therein. In this configuration, a portion of the offset wider right teeth **502** may contact or otherwise be positioned adjacent to the inner side surface **1610** of the chain when positioned thereon but be at least slightly spaced from an inner surface **1608** of the chain. This allows the side surface **1610** of the offset wider right **502** teeth to maintain the proper aligning of the chain while providing a gap on the inner surface **1608** to allow debris and the like to be cleaned from the cavity **308**, **310** of the chain.

(57) Similarly, the chainring **500** may have offset left teeth **504** positioned there around as well. The offset left teeth **504** may be offset or biased towards the one side of the central plane **1602**. The offset left teeth **504** may contact or otherwise be biased towards the one side of the corresponding cavity **308**, **310** of the chain when positioned therein. Further, the offset left teeth **504** may be at least a slightly spaced from the side surface **1610** in the cavity **308**, **310** of the chain when properly positioned therein. In this configuration, a portion of the offset left teeth **504** may contact or otherwise be positioned adjacent to the inner surface **1608** of the chain cavity **308**, **310** when positioned thereon but be at least slightly spaced from the inner side surface **1610** of the chain cavity **308**, **310**. This allows the side surface of the offset left teeth **504** to maintain the proper aligning of the surface **1608** of the chain while providing a gap along the side surface **1610** to allow debris and the like to be cleaned from the cavity **308**, **310** of the chain.

(58) The chainring **500** may also have one or more full teeth **506**. The full teeth **506** may be sized to substantially span the width of the cavity **308**, **310** formed between pairs of chain links. The full teeth **506** may be sized to have a width at or around the base of the full teeth **506** that is about the width of the corresponding cavity **308**, **310** formed in the chain such that the chain does not have substantial room to slide relative to the central plane **1602** during use.

(59) Referring now to FIGS. **21** and **23**, a conventional chainring tooth arrangement **2102** is illustrated adjacent to one embodiment of this disclosure of a chainring having an offset left **2104** bias and one embodiment of this disclosure of a chainring having an offset right **2106** bias. FIG. **23** illustrates the same with a chain overlaid to more clearly illustrate the position of the teeth within the cavity of the chain. The conventional chainring tooth arrangement **2102** may be a wide tooth **2108** followed by a narrow tooth **2110**. The full wide tooth **2108** may have a width that is about as wide as the cavity **308** and the narrow tooth **2110** may have a width that is about as wide as cavity **310**. In this configuration, the full wide tooth **2108** can fit within the cavity **308** while being positioned adjacent to corresponding chain links to prevent substantial side movement of the chain. Similarly, the narrow wide tooth **2110** can fit within the cavity **310** while being positioned adjacent to corresponding chain links to prevent substantial side movement of the chain **300**.

(60) The tooth pattern of the conventional chainring **2102** may alternate between the wide tooth **2108** and the narrow tooth **2110** about the entire radius of the chainring **2102**. The wide tooth **2108** may be sized to substantially span the width of the corresponding cavity **308** of the chain when positioned therein while the narrow tooth **2110** may be sized to span the width of the adjacent chain link surfaces when positioned in the cavity **310** of the chain **300**.

(61) The chainring having an offset left **2104** is one embodiment of this disclosure having full wide teeth **2108**, offset left teeth **2112**, and offset wide right teeth **2114** in a pattern about the chainring **2104**. More specifically, the teeth may alternate in type as follows: full wide tooth **2108**, offset left tooth **2112**, offset wide right tooth **2114**, and offset left tooth **2112**. This pattern can repeat about the chainring **2104**. FIG. **22** illustrates a repeated pattern of the offset left chainring **2104**.

(62) As used herein, a full wide tooth **2108** is a tooth that has a width that is about the same as the width of the larger cavity **308** of the chain **300**. The offset left tooth **2112** has an offset to one side of the small cavity **310** so the offset side is positioned adjacent to a chain link while the opposite side is at least partially spaced from the opposing chain link. The offset wider right tooth **2408** has an offset to an opposite side relative to the offset left tooth **2112** of the larger cavity **308** so the offset side is positioned adjacent to a chain link in the larger cavity **308** while the opposite side is at least partially spaced from the opposing chain link. Accordingly, the term “offset wider” right or left may refer to an offset sized to fit in the larger cavity **308** of the chain **300** while the term “offset left” or “offset right” may refer to an offset sized to be positioned in the smaller cavity **310**.

(63) Alternatively, the offset right chainring **2106** may also have alternating teeth types. More specifically, the offset right chainring **2106** may have the following pattern: full wide tooth **2108**, offset right tooth **2114**, offset left tooth **2112**, offset right tooth **2114**. This pattern can repeat about the chainring **2106**.

(64) Referring now to FIG. **24**, two more chainring embodiments **2402**, **2404** are illustrated. One chainring **2402** may have the following tooth pattern: full wide tooth **2108**, offset left tooth **2112**, offset wide right tooth **2408**, offset left tooth **2112**, full wide tooth **2108**, offset right tooth **2114**, offset wider left **2406**, offset right **2114**. This pattern can repeat about the chainring **2402**.

(65) Chain ring **2404** may also have a unique tooth pattern. More specifically, the chain ring **2404** may arrange the teeth in the following pattern: offset left tooth **2112**, full wide tooth **2108**, offset left tooth **2112**, offset wider right tooth **2408**, offset left tooth **2112**, offset wider right tooth **2408**, offset left tooth **2112**. This pattern can continue about the chainring **2404**.

(66) In one aspect of this disclosure, each tooth of the chainring may be specifically sized to fit within either the wide cavity **308** or the narrow cavity **310** of the chain. In other words, the offset teeth may be offset to be positioned substantially adjacent to the inner surface of the chain link of the cavity within which the tooth is supposed to be positioned. For example, an offset left tooth **2112** may be offset sufficiently left to become adjacent to the corresponding inner surface of the chain in the narrow cavity **310**. Alternatively, the offset wider left tooth **2406** may be offset sufficiently left to become adjacent to the corresponding inner surface of the chain in the wide cavity **310**. That is to say, the offset wider left tooth **2406** may extend slightly farther to the left than the offset left tooth **2112**. The offset right tooth **2114** and offset wider right tooth **2408** may be similarly sized to be appropriately offset for the corresponding cavity **308**, **310** of the chain.

(67) In view thereof, the teachings of this disclosure contemplate utilizing the appropriately sized full wide tooth and offset tooth for the corresponding cavity for which they are intended to be positioned. Accordingly, many different tooth combination are considered implementing the offset and pattern designs disclosed here.

(68) Yet another embodiment of this disclosure is a chain ring **2500** illustrated in FIG. **25**. The chain ring **25** may have a unique tooth pattern to ensure the chain stays properly positioned on the chainring **25** while also cleaning the cavities of the chain to prevent debris buildup and other issues that can affect proper tracking of the chain on the chainring **2500**. More specifically, the chainring **2500** may have teeth arranged in the following pattern: full wide tooth **2108**, offset left tooth **2112**, full wide tooth **2108**, offset left tooth **2112**, offset wider right tooth **2408**, offset left tooth **2112**. This pattern may repeat about the chainring **2500**.

(69) The offset teeth allow dirt, mud, or other debris from clogging the chain in between the teeth and preventing or impeding the chain from fully meshing onto the ring among other thing. Further, the full wide teeth help to keep the chain aligned with the center of the rings teeth and provide enhanced chain retention among other things.

(70) In the embodiments illustrated and described herein, the chain ring is shown having a direct mount. However, a person skilled in the art understands that a traditional mount style using a spider and specific Bolt Circle Diameter mount could alternatively be used. Accordingly, this disclosure contemplates using any known mounting system for the chainring.

(71) In one aspect of this disclosure, the chain is permitted some lateral play on the offset teeth between the full wide teeth. This allows the chain to flex in the direction of the respective lateral force which will decrease the drag on the chain when pedaling. The full wide teeth help keep the chain aligned with the center of the ring's teeth and help prevent the dropping of the chain while riding in rough terrain. The offset wider teeth may provide some additional security to the chain's retention on the ring.

(72) A person skilled in the art understands that in the configurations of the embodiments presented herein the number of teeth may be reduced or added by a quantity of two teeth to get the desired number of teeth (i.e., 30t, 32t, 34t, 36t, 38t, 40t, 42t, 44t etc.), the teeth removed or added depends on the embodiment or teeth configuration being used. The specific tooth pattern utilized will need to be appropriate for the number of teeth on the chainring.

(73) Referring now to FIG. 26, yet another embodiment of this disclosure is illustrated. More specifically, FIG. 26 illustrates a chainring **2600** having 32 total teeth in a wide, offset left, offset right configuration. More specifically, one pattern may be a Full-Wide tooth followed by an Offset-Left tooth followed by a Full-Wide tooth followed by an Offset-Left tooth followed by a Full-Wide tooth. The following pattern repeats around the rest of the ring of an Offset-Left tooth followed by an Offset-Wider-Right tooth followed by an Offset-Left tooth followed by a Full-Wide tooth followed by an Offset-Left tooth followed by a Full-Wide tooth followed by an Offset-Left tooth followed by an Offset-Wider-Right tooth followed by an Offset-Left tooth followed by a Full-Wide tooth followed by an Offset-Left tooth followed by a Full-Wide. This pattern may continue around the chainring **2600** to accommodate the appropriate number of teeth. This pattern will be the same for a 32t, 36t, 40t, 44t, 48t, 52t with the three Full-Wide grouped together; Full-Wide, Offset-Left, Full-Wide, Offset-Left, Full-Wide then the normal pattern repeating.

(74) The pattern described herein for the chain ring **2600** will be substantially the same for a 36 tooth, 40 tooth, 44 tooth, 48 tooth, and 52 tooth chain ring with the three Full-Wide tooth, Offset-Left tooth, Full-Wide tooth, Offset-Left tooth, Full-Wide tooth then the normal pattern repeating.

(75) One embodiment for this disclosure may be substantially similar to that of the chain ring **2600** except for a 30 tooth, 34 tooth, 38 tooth, 42 tooth, 46 tooth, and 50 tooth chain ring will not have the three Full-Wide tooth, Offset-Left tooth, Full-Wide tooth, Offset-Left tooth, Full-Wide tooth grouped together, they'll have the normal pattern repeating around the entire ring of a Full-Wide tooth, Offset-Left tooth, Full-Wide tooth, Offset-Left tooth, Offset-Wider-Right tooth, Offset-Left tooth, Full-Wide tooth. Offset-Left tooth, Full-Wide tooth. In another aspect of this disclosure, the offset teeth may have a curved profile along a leading edge as illustrated in a chainring **2700** in FIGS. 27-32. In this embodiment, not only can any of the teeth have any of the offset or full wide configurations **2108**, **2112**, **2408**, discussed herein, the teeth may also have a curved leading surface **2702**. The curved leading surface **2702** may be a surface profile on one side of any given tooth that is not the same as the profile on the other side of the same tooth when viewed from a side view as illustrated in FIGS. 27 and 29. The curved profile **2702** may ensure clean and secure engagement with the pivot pin **306** of the chain **300**. This ensures that as a rider applies torque to the crankset, the chainring **2700** adequately contacts the pivot pins **306** of the chain **300** to transfer the torque to the rear sprocket without causing the chain **300** to jump off the chainring **2700**. In this embodiment, each tooth may have any of the configurations discussed herein regarding the width of the tooth within the cavity **308**, **310** of the chain **300**, but additionally have the curved profile **2702** along the leading and/or trailing portion of the tooth.

(76) FIGS. 33-38 illustrate several embodiments of this disclosure having different tooth configurations. A person skilled in the art understands the particular pattern of tooth width configurations **2108**, **2112**, **2408**, on the chainrings depends on the number of teeth on the chainring. As such, FIGS. 33-38 illustrate certain examples of tooth width patterns considered for this disclosure. However, other chainrings have more or less teeth than those specifically illustrated are also considered herein.



(77) Referring now to FIGS. **42-51**, another embodiment of the present disclosure is illustrated. In this embodiment, a full wide inner tooth **4202** may be utilized to increase chain retention on the corresponding chain ring. In one aspect of this disclosure, the full wide inner tooth **4202** may be sized to have an inner tooth width **5102** that is slightly less than the width of an inner chain link gap **5002** between inner walls of inner chain links. In one example, the full wide inner tooth **4202** may have an inner tooth width **5102** that is about 91% of the inner chain link gap **5002**. Further, the full wide inner tooth **4202** may be slightly offset to one side or the other of the inner chain link gap **5002**. In other embodiments, the inner tooth width **5102** may be less than 91% of the inner chain link gap **5002**. Further still, in other embodiments contemplated herein the inner tooth width **5102** may be between 91% and about 100% the inner chain link gap **5002**.

(78) In one non-exclusive example, the inner chain link gap **5002** may be about 2.270 mm while the full wide inner tooth **4202** width may be about 2.070 mm. In this embodiment, a typical offset of the full wide inner tooth **4202** when a chain **5004** is tracking as expected along the chain ring positions the full wide inner tooth **4202** within the corresponding inner chain link gap **5002** such that one side of the full wide inner tooth **4202** has a slight gap of about 0.080 mm between the full wide inner tooth **4202** and the adjacent inner chain link wall while the opposing side has a gap of about 0.120 mm between the full wide inner tooth **4202** and the adjacent inner chain link wall.

(79) Similarly, an outer chain link gap **5006** may be formed between the inner surfaces of corresponding links of the chain **5004** for the wider chain sections. A full wide outer tooth **5008** may have a full wide tooth width **5010** that is about 96% the outer chain link gap **5006**. In other embodiments, the full wide tooth width **5010** may be less than 96% of the outer chain link gap **5006**. Further still, in other embodiments contemplated herein the full wide tooth width **5010** may be between 96% and about 100% the outer chain link gap **5006**.

(80) In one non-exclusive embodiment, the outer chain link gap **5006** may be about 3.820 mm while the corresponding full wide tooth width **5010** may be about 3.670 mm. This embodiment may have a full wide tooth gap **5012** equally spaced on either side of the full wide outer tooth **5008** within the outer link gap **5006** when the chain **5004** is centrally positioned along the chain ring. In one aspect of this disclosure, the full wide outer tooth **5008** may have a full wide tooth gap **5012** of about 0.075 mm. However, other dimensions and orientations of the full wide tooth **5008** within the full wide tooth width **510** are contemplated herein as well.

(81) While specific example dimensions and offsets are discussed herein, other embodiments contemplated by this disclosure contain different dimensions and offsets of the full wide inner tooth **4202** within the inner chain link gap **5002**. For example, the full wide inner tooth **4202** may be substantially centered within the inner chain link gap **5002** in one embodiment. Further still, in one embodiment the full wide inner tooth **4202** may have a width that is about the same as the inner chain link gap **5002**. Accordingly, this disclosure contemplates many different dimensions and offset orientations of the full wide inner tooth **4202** within the corresponding inner chain link gap **5002**.

(82) Referring now to FIGS. **42-43**, one embodiment of this disclosure may be a chain ring **4200** having alternating full wide outer teeth **5008** and full wide inner teeth **4202**. This chain ring **4200** may alter between a full wide outer tooth **5008** and a full wide inner tooth **4202** about the entire chain ring. In one example of this disclosure, the chain ring **4200** may have 32 teeth about the perimeter. However, this disclosure also contemplates chain rings that alternate full wide outer teeth **5008** and full wide inner teeth **4202** with different numbers of total teeth.

(83) Referring now to FIGS. **44-45**, yet another embodiment of this disclosure is illustrated. In this embodiment, a chain ring **4400** may have full wide outer teeth **5008**, full wide inner teeth **4202**, and offset wider right teeth **2408** about the perimeter. This chain ring **4400** may have any number of teeth able to accommodate the discussed pattern.

(84) Referring now to FIGS. **46-47**, yet another embodiment of this disclosure is illustrated. In this embodiment, a chain ring **4600** may have full wide outer teeth **5008**, full wide inner teeth **4202**,

and offset wider left teeth **2406** about the perimeter. The offset wider left teeth **2406** may be sized to fit within the inside outer link width **5006** but be biased to a left side such that one side of the offset wider left teeth **2406** is positioned closer to the adjacent outer link than the other side of the teeth **2406**. This chain ring **4600** may have a pattern of teeth about the perimeter that is a full wide outer tooth **5008** followed by a full wide inner tooth **2406**, followed by the offset wider left tooth **2406** and repeating around the chain ring **4600**. This chain ring **4600** may have any number of teeth able to accommodate the discussed pattern.

(85) Referring now to FIGS. **48-49**, yet another embodiment of this disclosure is illustrated. In this embodiment, a chain ring **4800** may have full wide outer teeth **5008**, full wide inner teeth **4202**, and offset wider right teeth **2408** about the perimeter. More specifically, the teeth may be in the pattern of full wide outer tooth **5008**, full wide inner tooth **4202**, full wide outer tooth **5008**, full wide inner tooth **4602**, offset wider right tooth **2408** repeating. This chain ring **4800** may have any number of teeth able to accommodate the discussed pattern.

(86) Referring now to FIGS. **52-53**, yet another aspect of this disclosure is illustrated. More specifically, any of the teeth discussed herein may be a tooth **5200** that has a modified leading end **5202** compared to a trailing end **5204**. The modified leading end **5202** may be then end that typically engages the chain when force is being transferred there through as a corresponding chain ring rotates in the propelling direction **5206**. The modified leading end **5202** may have a taper that extends a greater length of the tooth **5200** than the trailing end **5204**. The modified leading end **5202** may provide smoother chain engagement that prevents the chain from transitioning off of the corresponding chain ring among other things.

(87) While this disclosure has been described with respect to at least one embodiment, the present disclosure can be further modified within the spirit and scope of this disclosure. This application is therefore intended to cover any variations, uses, or adaptations of the disclosure using its general principles. Further, this application is intended to cover such departures from the present disclosure as come within known or customary practice in the art to which this disclosure pertains and which fall within the limits of the appended claims.

## Claims

1. A bicycle chain ring, comprising: a plurality of teeth extending radially about an axis of the chain ring, the plurality of teeth comprising: a first group of teeth having a first width that is at least 96% the width of an outer link gap of a bicycle chain; a second group of teeth that are at least partially offset from a central plane to a first side and have a second width; and a third group of teeth that are at least partially offset from a central plane to a second side opposite the first side; wherein, the first group of teeth have a base that is sized to be centered on a central plane defined through a center portion of the chainring; wherein the chain ring has a repeating series of teeth comprising: a first tooth from the first group of teeth; a second tooth from the second group of teeth; a third tooth from the first group of teeth; a fourth tooth from the second group of teeth; a fifth tooth from the third group of teeth; and a sixth tooth from the second group of teeth; wherein the repeating series repeats at least two times consecutively around the chain ring.
2. The bicycle chain ring of claim 1, further wherein the second width is less than the first width.
3. The bicycle chain ring of claim 1, wherein the third group of teeth have a third width that is different from the first width.
4. The bicycle chain ring of claim 3, further wherein the third width is less than the first width.
5. The bicycle chain ring of claim 3, wherein second group of teeth is offset to an inward side of the central plane and the third group of teeth is offset to an outward side of the central plane.
6. The bicycle chain ring of claim 1, further wherein the second width is less than the width of the space between two inner chain links of a bicycle chain.
7. A bicycle chain ring, comprising: a plurality of teeth extending radially about an axis of the chain

ring, the plurality of teeth including a first group of teeth and a second group of teeth and a third group of teeth; wherein the first group of teeth has a first width at a tooth base that is sized to be received within a chain cavity defined between parallel outer links of a bicycle chain, the first width being at least 96% a chain cavity width defined between the parallel outer links; wherein the second group of teeth are at least partially offset from a central plane to a first side and have a second width at the tooth base, the second width being different from the first width; wherein the third group of teeth that are at least partially offset from the central plane to a second side opposite the first side; wherein the chain ring has a repeating series of teeth comprising: a first tooth from the first group of teeth; a second tooth from the second group of teeth; a third tooth from the first group of teeth; a fourth tooth from the second group of teeth; a fifth tooth from the third group of teeth; and a sixth tooth from the second group of teeth; wherein the repeating series repeats at least two times consecutively around the chain ring.

8. The bicycle chain ring of claim 7, further wherein at least one tooth of the chain ring has a modified leading end compared to a trailing end.

9. The bicycle chain ring of claim 7, wherein the second width is at least 91% of the size of an inner chain link gap defined by the chain cavity.

10. A bicycle chain ring, consisting of: a first group of teeth having a first width that is at least 96% the width of an outer link gap of a bicycle chain; a second group of teeth that are at least partially offset from a central plane to a first side and have a second width; and a third group of teeth that are at least partially offset from a central plane to a second side opposite the first side; wherein the chain ring has a repeating series of teeth comprising the following consecutive order of teeth: a first tooth from the first group of teeth; a second tooth from the second group of teeth; a third tooth from the first group of teeth; a fourth tooth from the second group of teeth; a fifth tooth from the third group of teeth; and a sixth tooth from the second group of teeth.

---