

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12395954
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Monajemi; Pooya et al.

Collision avoidance in multi link device (MLD) make before break roaming (MBBR)

Abstract

Collision avoidance in Multi Link Device (MLD) Make Before Break Roaming (MBBR) may be provided. It may be determined that a client device may comprise an MBBR client device. Next, a Request To Send (RTS) may be sent to the client device. In response to sending the RTS to the client device, a Clear To Send (CTS) may be received from the client device. In response to receiving the CTS, data may be sent to the client device.

Inventors:	Monajemi; Pooya (Irvine, CA), Smith; Malcolm Muir (Richardson, TX)
Applicant:	Cisco Technology, Inc. (San Jose, CA)
Family ID:	1000008764534
Assignee:	Cisco Technology, Inc. (San Jose, CA)
Appl. No.:	17/815061
Filed:	July 26, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240040525 A1	Feb. 01, 2024

Publication Classification

Int. Cl.: H04W56/00 (20090101); H04W74/00 (20090101)

U.S. Cl.:

CPC H04W56/0025 (20130101); H04W74/004 (20130101); H04W74/006 (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2005/0053037	12/2004	Ginzburg	370/333	H04W 24/00
2012/0178488	12/2011	Jonker	455/517	H04W 8/005
2019/0253967	12/2018	Xiao	N/A	H04W 28/0284
2020/0374802	12/2019	Chu	N/A	H04W 28/08
2020/0404549	12/2019	Verma	N/A	H04W 24/10
2021/0377856	12/2020	Chu et al.	N/A	N/A
2022/0007417	12/2021	Xin et al.	N/A	N/A
2022/0029736	12/2021	Chu et al.	N/A	N/A
2022/0053560	12/2021	Xin et al.	N/A	N/A
2022/0159571	12/2021	Zhou	N/A	H04W 76/15
2022/0272630	12/2021	Shafin	N/A	H04W 52/0219
2023/0023779	12/2022	Shafin	N/A	H04W 76/15
2023/0163808	12/2022	Lou	455/101	H04W 74/002
2023/0199641	12/2022	Naik	370/318	H04W 76/15
2023/0254739	12/2022	Kim	370/331	H04W 36/0061
2023/0319922	12/2022	Lu	370/328	H04W 76/15
2024/0007889	12/2023	Lopez	N/A	H04W 28/0958
2024/0276405	12/2023	Hirata	N/A	H04W 28/0278
2025/0106613	12/2024	Chu	N/A	H04W 76/15

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2022032150	12/2021	WO	N/A

Primary Examiner: Sweet; Lonnie V

Attorney, Agent or Firm: Merchant & Gould P.C.

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates generally to collision avoidance in Multi Link Device (MLD) Make Before Break Roaming (MBBR).

BACKGROUND

(2) In computer networking, a wireless Access Point (AP) is a networking hardware device that allows a Wi-Fi compatible client device to connect to a wired network and to other client devices. The AP usually connects to a router (directly or indirectly via a wired network) as a standalone device, but it can also be an integral component of the router itself. Several APs may also work in coordination, either through direct wired or wireless connections, or through a central system,

commonly called a Wireless Local Area Network (WLAN) controller. An AP is differentiated from a hotspot, which is the physical location where Wi-Fi access to a WLAN is available.

(3) Prior to wireless networks, setting up a computer network in a business, home, or school often required running many cables through walls and ceilings in order to deliver network access to all of the network-enabled devices in the building. With the creation of the wireless AP, network users are able to add devices that access the network with few or no cables. An AP connects to a wired network, then provides radio frequency links for other radio devices to reach that wired network. Most APs support the connection of multiple wireless devices. APs are built to support a standard for sending and receiving data using these radio frequencies.

Description

BRIEF DESCRIPTION OF THE FIGURES

- (1) The accompanying drawings, which are incorporated in and constitute a part of this disclosure, illustrate various embodiments of the present disclosure. In the drawings:
- (2) FIG. 1 is a block diagram of an operating environment for providing collision avoidance in Multi Link Device (MLD) Make Before Break Roaming (MBBR);
- (3) FIG. 2 is a flow chart of a method for providing collision avoidance in MLD MBBR;
- (4) FIG. 3 is a flow chart of a method for providing collision avoidance in MLD MBBR;
- (5) FIG. 4 is a flow chart of a method for providing collision avoidance in MLD MBBR;
- (6) FIG. 5 is a flow chart of a method for providing collision avoidance in MLD MBBR;
- (7) FIG. 6 is a flow chart of a method for providing collision avoidance in MLD MBBR;
- (8) FIG. 7 illustrates using auxiliary radio assistance for providing collision avoidance in MLD MBBR; and
- (9) FIG. 8 is a block diagram of a computing device.

DETAILED DESCRIPTION

Overview

(10) Collision avoidance in Multi Link Device (MLD) Make Before Break Roaming (MBBR) may be provided. It may be determined that a client device may comprise an MBBR client device. Next, a Request To Send (RTS) may be sent to the client device. In response to sending the RTS to the client device, a Clear To Send (CTS) may be received from the client device. In response to receiving the CTS, data may be sent to the client device. Embodiments of the disclosure may include other processes.

(11) Both the foregoing overview and the following example embodiments are examples and explanatory only, and should not be considered to restrict the disclosure's scope, as described and claimed. Furthermore, features and/or variations may be provided in addition to those described. For example, embodiments of the disclosure may be directed to various feature combinations and sub-combinations described in the example embodiments.

Example Embodiments

(12) The following detailed description refers to the accompanying drawings. Wherever possible, the same reference numbers are used in the drawings and the following description to refer to the same or similar elements. While embodiments of the disclosure may be described, modifications, adaptations, and other implementations are possible. For example, substitutions, additions, or modifications may be made to the elements illustrated in the drawings, and the methods described herein may be modified by substituting, reordering, or adding stages to the disclosed methods. Accordingly, the following detailed description does not limit the disclosure. Instead, the proper scope of the disclosure is defined by the appended claims.

(13) Make Before Break Roaming (MBBR) may comprise a moving client device initialing communication with a next Access Point (AP) while still being in contact with a current AP in

order to not lose connectivity. In the Wi-Fi 7 Multi-Link Device (MLD) context, there may be three possible implementations of a station (i.e., client device): i) Simultaneous Transmit (TX)/Receive (RX) (STR) devices; ii) Non-STA (NSTR) devices; and iii) Enhanced Multi-Link Single Radio (eMLSR) devices.

(14) STR devices may have two independent Transceivers (TXRX) capable of simultaneous and unrestricted operation on a given set of links (e.g., any channel in 2.4 GHz plus any channel in 5 GHz, 5 GHz plus 6 GHz, etc.). This mode may deliver significant instantaneous throughput gains and improved latency.

(15) NSTR devices may contain two radios that may be constrained such that when one transmits, the other may not receive. This may place a restriction on the AP MLD to align its Presentation Protocol Data Unit (PPDU) transmissions across multiple links such that it may not require the Station (STA) (i.e., client device) to TX and RX at the same time (e.g., aligning the end of the Downlink (DL) PPDU from each AP-STA link such the STA may TX both acknowledgements (ACKs) simultaneously, but may not need to RX any PPDU during that time). This mode may also deliver significant instantaneous throughput gains and improved latency, but only when PPDU may be aligned in the respective direction.

(16) An eMLSR device may comprise a client device that may contain one TXRX capable of sending and receiving data frames on one channel/link and one simplified receiver on another link. Then the AP may select the link on which the client device is expected to receive a PPDU via an initial control frame (e.g., Multi User Request to Send MU-RTS) that the client device may concurrently listen for on two links allowing it to switch its single TXRX to the appropriate link for PPDU decoding and ACK generation. In this way, the client device may have better latency due to link diversity, but it may not use two links for improved instantaneous throughput.

(17) An MLD device that may be operating in an MBBR mode may maintain a 5 GHz link with one AP and a 6 GHz link with another physical AP separated by a Local Area Network (LAN). For client devices, this mode may be simple to achieve because the links in a client device may be independent and may easily be hosted on distinct physical (i.e., non-co-located) APs. However TX/RX dependencies between links required by eMLSR and NSTR, especially those that change with each Transmit Opportunity (TXOP), may be difficult to manage in an MBBR mode. Embodiments of the disclosure may address these synchronization issues for the above types of constrained devices. In other words, embodiments of the disclosure may avoid eMLSR and NSTR MLD PPDU constraint conflicts (i.e., collisions) during an MBBR event (i.e., while the client device has one link connected to one AP and another link connected to another non-co-located AP).

(18) FIG. 1 shows an operating environment **100** for providing collision avoidance in Multi Link Device (MLD) Make Before Break Roaming (MBBR). As shown in FIG. 1, operating environment **100** may comprise a controller **105** and a coverage environment **110**. Coverage environment **110** may comprise, but is not limited to, a Wireless Local Area Network (WLAN) comprising a plurality of Access Points (APs) that may provide wireless network access (e.g., access to the WLAN for client devices). The plurality of APs may comprise a first AP **115** and a second AP **120**. The plurality of APs may provide wireless network access to a client device **125** as it moves within coverage environment **110**. Client device **125** may comprise, but is not limited to, a smart phone, a personal computer, a tablet device, a mobile device, a telephone, a remote control device, a set-top box, a digital video recorder, an Internet-of-Things (IoT) device, a network computer, a router, a Virtual Reality (VR)/Augmented Reality (AR) device, an Automated Transfer Vehicle (ATV), a drone, an Unmanned Aerial Vehicle (UAV), or other similar microcomputer-based device. Each of the plurality of APs may be compatible with specification standards such as, but not limited to, the Institute of Electrical and Electronics Engineers (IEEE) 802.11be specification standard for example.

(19) Controller **105** may comprise a Wireless Local Area Network controller (WLC) and may provision and control coverage environment **110** (e.g., a WLAN). Controller **105** may allow client

device **125** to join coverage environment **110**. In some embodiments of the disclosure, controller **105** may be implemented by a Digital Network Architecture Center (DNAC) controller (i.e., a Software-Defined Network (SDN) controller) that may configure information for coverage environment **110** in order to provide collision avoidance in MLD MBBR.

(20) First AP **115**, second AP **120**, and client device **125** may comprise Multi Link Devices (MLDs). For example, client device **125** may be simultaneously connected to first AP **115** via a first radio **130** (e.g., over a 5 GHz link) and to first AP **115** via a second radio **135** (e.g., over a 6 GHz link). As client device **125** roams within coverage environment **110**, the second radio **135** link between client device **125** and first AP **115** may be broken and then the second radio **135** link between client device **125** and second AP **120** may be made. Accordingly, client device **125** may be simultaneously connected to first AP **115** via first radio **130** (e.g., over a 5 GHz link) and to second AP **120** via second radio **135** (e.g., over a 6 GHz link). First AP **115**, second AP **120**, or both first AP **115** and second AP **120** also include an auxiliary radio that, for example, may be used to sniff packets from other APs.

(21) The elements described above of operating environment **100** (e.g., controller **105**, first AP **115**, second AP **120**, or client device **125**) may be practiced in hardware and/or in software (including firmware, resident software, micro-code, etc.) or in any other circuits or systems. The elements of operating environment **100** may be practiced in electrical circuits comprising discrete electronic elements, packaged or integrated electronic chips containing logic gates, a circuit utilizing a microprocessor, or on a single chip containing electronic elements or microprocessors.

Furthermore, the elements of operating environment **100** may also be practiced using other technologies capable of performing logical operations such as, for example, AND, OR, and NOT, including but not limited to, mechanical, optical, fluidic, and quantum technologies. As described in greater detail below with respect to FIG. **8**, the elements of operating environment **100** may be practiced in a computing device **800**.

(22) With embodiments of the disclosure, a client device that performs an MBBR roam may be detected either by explicit signaling by the client device or by a network (e.g., network controller) noticing concurrent associations on neighboring APs. The appropriate collision avoidance process may then be selected at a network level based on the network's knowledge of the client device's capability and constraints (e.g., STR or NSTR) on the links that may be involved in the roam.

(23) Embodiments of the disclosure may include asynchronous and synchronous processes. The asynchronous processes may include: i) Downlink (DL) Request To Send (RTS) Protection; ii) Uplink (UL) Multi User (MU) Disablement; iii) Non-overlapping Target Wake Times (TWT) Setup; and iv) Auxiliary Radio Assistance. The asynchronous processes may avoid simultaneous TX/RX operation across a set of APs in MBBR mode for client device **125** without requiring any per-TXOP coordination between the APs themselves (i.e., all that may be required is the exchange of MBBR state). This approach may address both NSTR and eMLSR and may achieve a better outcome of higher reliability and seamless handover with MBBR, which may only be active in a cell overlap region and may not be a permanent state.

(24) Downlink (DL) Request to Send (RTS) Protection

(25) FIG. **2** is a flow chart setting forth the general stages involved in a method **200** consistent with embodiments of the disclosure for providing collision avoidance in MLD MBBR. Method **200** may be implemented using a computing device **800** as described in more detail below with respect to FIG. **8**. Ways to implement the stages of method **200** will be described in greater detail below.

(26) Method **200** may begin at starting block **205** and proceed to stage **210** where computing device **800** may determine that client device **125** is an MBBR client device. For example, client device **125** may comprises an NSTR device or an eMLSR device.

(27) From stage **210**, where computing device **800** determines that client device **125** is an MBBR client device with NSTR or eMLSR constraint, method **200** may advance to stage **220** where computing device **800** may send, prior to each TXOP involving the MBBR client, a Request To

Send (RTS) to client device **125**. For example, when an MBBR client device is detected, all downlink frames may then be protected by RTS.

(28) Once computing device **800** sends, in response to determining that client device **125** is an MBBR client device, the RTS to client device **125** in stage **220**, method **200** may continue to stage **230** where computing device **800** may receive, in response to sending the RTS to the client device, a Clear To Send (CTS) from client device **125**. For example, reception of the CTS from client device **125** may ensure that the constrained client device (e.g., client device **125**) may not be busy on an alternate link with a neighboring AP.

(29) After computing device **800** receives, in response to sending the RTS to the client device, the CTS from client device **125** in stage **230**, method **200** may proceed to stage **240** where computing device **800** may send, in response to receiving the CTS, data to client device **125**. Once computing device **800** sends, in response to receiving the CTS, data to client device **125** in stage **240**, method **200** may then end at stage **250**.

(30) Uplink (UL) Multi User (MU) Disablement

(31) FIG. **3** is a flow chart setting forth the general stages involved in a method **300** consistent with embodiments of the disclosure for providing collision avoidance in MLD MBBR. Method **300** may be implemented using a computing device **800** as described in more detail below with respect to FIG. **8**. Ways to implement the stages of method **300** will be described in greater detail below.

(32) Method **300** may begin at starting block **305** and proceed to stage **310** where computing device **800** may determine that client device **125** is an MBBR client device. For example, client device **125** may comprises an NSTR device or an eMLSR device.

(33) From stage **310**, where computing device **800** determines that client device **125** is an MBBR client device, with a NSTR or eMLSR constraint method **300** may advance to stage **320** where computing device **800** may disable, in response to determining that client device **125** is an MBBR client device, Uplink (UL) triggers. For example, UL triggers may be disabled during an MBBR roam (i.e., equivalent to UL MU opt out). This may be because a triggering AP may not know about the state of the client device on another link, and a client device that gets triggered may not be able to send a trigger response due to constraints from the other link for example. Once computing device **800** allows client device **125** to choose the link for UL TXOPs in stage **330**, method **300** may then end at stage **340**.

(34) Non-Overlapping Target Wake Times (TWT) Setup

(35) FIG. **4** is a flow chart setting forth the general stages involved in a method **400** consistent with embodiments of the disclosure for providing collision avoidance in MLD MBBR. Method **400** may be implemented using a computing device **800** as described in more detail below with respect to FIG. **8**. Ways to implement the stages of method **400** will be described in greater detail below.

(36) Method **400** may begin at starting block **405** and proceed to stage **410** where computing device **800** may determine that client device **125** is an MBBR client device. For example, client device **125** may comprises an NSTR device or an eMLSR device.

(37) From stage **410**, where computing device **800** determines that client device **125** is an MBBR client device with a NSTR or eMLSR constraint, method **400** may advance to stage **420** where computing device **800** may create non-overlapping Target Wake Times (TVVTs) respectively associated with two links used by client device **125**. For example, TWT negotiations with non-overlapping windows may be set for each link involved in a roam as soon as the MBBR mode is active. The coordination of the TWT windows may be performed by client device **125** to suggest TWT times such that overlap may not occur between the links. They may also be coordinated by the network (e.g., controller **105**), taking into account Target Beacon Transmission Time (TBTT) offsets between the links involved in the roam. The TWT approach may be applicable to a single radio client also. In some embodiments of the disclosure, a client device (e.g., client device **125**) may create the non-overlapping Target Wake Times (TVVTs) rather than computing device **800**.

(38) Once computing device **800** creates non-overlapping TVVTs respectively associated with two

links used by client device **125** in stage **420**, method **400** may continue to stage **430** where computing device **800** may take down the TWTs after a roam has been completed. For example, the TWT agreements may be torn down once the roam is complete. Because the TWT may not be used for power saving purpose, the awake-window duty cycle may be set close to 50% for example. Once computing device **800** takes down the TVVTs after the roam has been completed in stage **430**, method **400** may then end at stage **440**.

(39) Auxiliary Radio Assistance

(40) FIG. 5 is a flow chart setting forth the general stages involved in a method **500** consistent with embodiments of the disclosure for providing collision avoidance in MLD MBBR. Method **500** may be implemented using a computing device **800** as described in more detail below with respect to FIG. 8. Ways to implement the stages of method **500** will be described in greater detail below.

(41) Method **500** may begin at starting block **505** and proceed to stage **510** where computing device **800** (e.g., disposed in second AP **120**) may detect, by an auxiliary radio (e.g., disposed in second AP **120**), a transmission of first Downlink (DL) data **705** from first AP **115** to an MBBR client device (e.g., client device **125**) as illustrated in FIG. 7. For example, an auxiliary RX-only radio on second AP **120** may be assigned to first AP **115**'s 5 GHz channel during a roam (and vice versa). Both UL and DL transmissions from client device **125** may be detected and reported to second AP **120**'s 6 GHz radio. Second AP **120**'s auxiliary radio may detect transmission of first DL data **705** to client device **125** (state **710**).

(42) From stage **510**, where computing device **800** detects, by the auxiliary radio, the transmission of first DL data **705** from first AP **115** to an MBBR client device with a NSTR constraint, method **500** may advance to stage **520** where computing device **800** (e.g., disposed in second AP **120**) may initiate a transmission of second DL data **715** from second AP **120** to the MBBR client device (e.g., client device **125**) during a transmission time for first DL data **705**. For example, TXOP collisions may be avoided when second AP **120**'s auxiliary radio detects a TXOP involving a roaming client (i.e., client device **125**) on the neighboring AP (i.e., first AP **115**). Embodiments of the disclosure may either avoid TXOP collision and not transmit during the detected TXOP on a neighbor AP (could be done for both eMLSR clients and NSTR clients) or embodiments of the disclosure may transmit and align the end times as described below (only for NSTR clients).

(43) Once computing device **800** sends the transmission of second DL data **715** from second AP **120** to the MBBR client device (e.g., client device **125**) during the transmission time for first DL data **705** in stage **520**, method **500** may continue to stage **530** where computing device **800** (e.g., disposed in second AP **120**) may align an end of first DL data **705** with an end of second DL data **715**. For example, for the PPDU end-time alignment for NSTR devices, when a DL PPDU for the roaming client is detected by the auxiliary radio on the neighboring AP, any locally transmitted DL PDUs may also be aligned with the detected PPDU's end time. Padding **720** may be added to second AP **120**'s second DL data **715** to align it to the end time of first AP **115**'s first DL data **705** (state **725**). A first UL acknowledgement **730** associated with the reception of first DL data **705** and a second UL acknowledgement **735** associated with the reception of the second DL data **715** may be transmitted substantially simultaneously to first AP **115** and second AP **120** respectively (state **740**). Once computing device **800** aligns the end of first DL data **705** with the end of second DL data **715** in stage **530**, method **500** may then end at stage **540**.

(44) Synchronous

(45) FIG. 6 is a flow chart setting forth the general stages involved in a method **600** consistent with embodiments of the disclosure for providing collision avoidance in MLD MBBR. Method **600** may be implemented using a computing device **800** as described in more detail below with respect to FIG. 8. Ways to implement the stages of method **600** will be described in greater detail below.

(46) Method **600** may begin at starting block **605** and proceed to stage **610** where computing device **800** (e.g., disposed in controller **105**) may determine that client device **125** is an MBBR client device. For example, client device **125** may comprises an NSTR device or an eMLSR device.

(47) From stage **610**, where computing device **800** determines that client device **125** is an MBBR client device, method **600** may advance to stage **620** where computing device **800** (e.g., disposed in controller **105**) may synchronize a transmission of first Downlink (DL) data from first AP **115** to client device **125** and a transmission of second DL data from second AP **120** to client device **125**. For example, embodiments of the disclosure may avoid colliding DL schedules for the same eMLSR client (e.g., client device **125**) or ensure PPDU end-time alignment for the same NSTR client (e.g., client device **125**) by specifying accurate PPDU transmission times to each MBBR AP (e.g., first AP **115** and second AP **120**).

(48) Once computing device **800** synchronizes the transmission of first DL data from first AP **115** to client device **125** and the transmission of the second DL data from second AP **120** to client device **125** in stage **620**, method **600** may continue to stage **630** where computing device **800** may align an end of the first DL data with an end of the second DL data. For example, specifying an accurate PPDU transmission times may cause the ends to be aligned.

(49) The synchronous process may work well for APs predominantly in Basic Service Set (BSS) scheduled access mode (e.g., Wi-Fi 6E) or inter-BSS scheduled access mode (e.g., Wi-Fi7) because: i) there may be few unexpected TXOPs; and ii) with Wi-Fi7, the WLC may have the AP's future schedule. The WLC may schedule a slightly future time considering the message transport transit time.

(50) In addition, the synchronous process may emulate per-TXOP synchronization, but may avoid direct per-TXOP synchronization between neighboring MBBR APs themselves. This approach may leverage Wireless Time Sensitive Networking (WTSN) capabilities (e.g., based on 802.1AS and 802.1Qbv time-aware-scheduling) that may provide, for example, approximately 1 us time sync and PPDU transmission alignment between neighboring APs (e.g., among different bands/channels). Once computing device **800** aligns the end of the first DL data with the end of the second DL data in stage **630**, method **600** may then end at stage **640**.

(51) FIG. **8** shows computing device **800**. As shown in FIG. **8**, computing device **800** may include a processing unit **810** and a memory unit **815**. Memory unit **815** may include a software module **820** and a database **825**. While executing on processing unit **810**, software module **820** may perform, for example, processes for providing collision avoidance in MLD MBBR as described above with respect to FIG. **2**, FIG. **3**, FIG. **4**, FIG. **5**, and FIG. **6**. Computing device **800**, for example, may provide an operating environment for controller **105**, first AP **115**, second AP **120**, or client device **125**. Controller **105**, first AP **115**, second AP **120**, or client device **125** may operate in other environments and are not limited to computing device **800**.

(52) Computing device **800** may be implemented using a Wi-Fi access point, a tablet device, a mobile device, a smart phone, a telephone, a remote control device, a set-top box, a digital video recorder, a cable modem, a personal computer, a network computer, a mainframe, a router, a switch, a server cluster, a smart TV-like device, a network storage device, network relay devices, or other similar microcomputer-based device. Computing device **800** may comprise any computer operating environment, such as hand-held devices, multiprocessor systems, microprocessor-based or programmable sender electronic devices, minicomputers, mainframe computers, and the like. Computing device **800** may also be practiced in distributed computing environments where tasks are performed by remote processing devices. The aforementioned systems and devices are examples and computing device **800** may comprise other systems or devices.

(53) Embodiments of the disclosure, for example, may be implemented as a computer process (method), a computing system, or as an article of manufacture, such as a computer program product or computer readable media. The computer program product may be a computer storage media readable by a computer system and encoding a computer program of instructions for executing a computer process. The computer program product may also be a propagated signal on a carrier readable by a computing system and encoding a computer program of instructions for executing a computer process. Accordingly, the present disclosure may be embodied in hardware and/or in

software (including firmware, resident software, micro-code, etc.). In other words, embodiments of the present disclosure may take the form of a computer program product on a computer-usable or computer-readable storage medium having computer-usable or computer-readable program code embodied in the medium for use by or in connection with an instruction execution system. A computer-usable or computer-readable medium may be any medium that can contain, store, communicate, propagate, or transport the program for use by or in connection with the instruction execution system, apparatus, or device.

(54) The computer-usable or computer-readable medium may be, for example but not limited to, an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system, apparatus, device, or propagation medium. More specific computer-readable medium examples (a non-exhaustive list), the computer-readable medium may include the following: an electrical connection having one or more wires, a portable computer diskette, a random access memory (RAM), a read-only memory (ROM), an erasable programmable read-only memory (EPROM or Flash memory), an optical fiber, and a portable compact disc read-only memory (CD-ROM). Note that the computer-usable or computer-readable medium could even be paper or another suitable medium upon which the program is printed, as the program can be electronically captured, via, for instance, optical scanning of the paper or other medium, then compiled, interpreted, or otherwise processed in a suitable manner, if necessary, and then stored in a computer memory.

(55) While certain embodiments of the disclosure have been described, other embodiments may exist. Furthermore, although embodiments of the present disclosure have been described as being associated with data stored in memory and other storage mediums, data can also be stored on or read from other types of computer-readable media, such as secondary storage devices, like hard disks, or a CD-ROM, a carrier wave from the Internet, or other forms of RAM or ROM. Further, the disclosed methods' stages may be modified in any manner, including by reordering stages and/or inserting or deleting stages, without departing from the disclosure.

(56) Furthermore, embodiments of the disclosure may be practiced in an electrical circuit comprising discrete electronic elements, packaged or integrated electronic chips containing logic gates, a circuit utilizing a microprocessor, or on a single chip containing electronic elements or microprocessors. Embodiments of the disclosure may also be practiced using other technologies capable of performing logical operations such as, for example, AND, OR, and NOT, including but not limited to, mechanical, optical, fluidic, and quantum technologies. In addition, embodiments of the disclosure may be practiced within a general purpose computer or in any other circuits or systems.

(57) Embodiments of the disclosure may be practiced via a system-on-a-chip (SOC) where each or many of the element illustrated in FIG. 1 may be integrated onto a single integrated circuit. Such an SOC device may include one or more processing units, graphics units, communications units, system virtualization units and various application functionality all of which may be integrated (or "burned") onto the chip substrate as a single integrated circuit. When operating via an SOC, the functionality described herein with respect to embodiments of the disclosure, may be performed via application-specific logic integrated with other components of computing device **800** on the single integrated circuit (chip).

(58) Embodiments of the present disclosure, for example, are described above with reference to block diagrams and/or operational illustrations of methods, systems, and computer program products according to embodiments of the disclosure. The functions/acts noted in the blocks may occur out of the order as shown in any flowchart. For example, two blocks shown in succession may in fact be executed substantially concurrently or the blocks may sometimes be executed in the reverse order, depending upon the functionality/acts involved.

(59) While the specification includes examples, the disclosure's scope is indicated by the following claims. Furthermore, while the specification has been described in language specific to structural features and/or methodological acts, the claims are not limited to the features or acts described

above. Rather, the specific features and acts described above are disclosed as example for embodiments of the disclosure.

Claims

1. A method comprising: determining a Make Before Break Roaming (MBBR) action from a client device, wherein the client device is a multi-link device comprising a first link established with a first Access Point (AP) and a second link established with a second AP, and wherein the first AP and the second AP are non-co-located APs, and wherein the client device is with one of a Non-Simultaneous Transmit/Receive (NSTR) and an Enhanced Multi Link Single Radio (eMLSR); creating non-overlapping Target Wake Times (TWTs) respectively associated with two links used by the client device; and taking down the TWTs after a roam has been completed.
 2. The method of claim 1, wherein an awake-window duty cycle for each of the TWTs is less than 50%.
 3. The method of claim 1, wherein creating the non-overlapping TWTs comprises creating the non-overlapping TWTs by the client device.
 4. The method of claim 1, wherein creating the non-overlapping TWTs comprises creating the non-overlapping TWTs by a controller of a network.
 5. A system comprising: a memory storage; and a processing unit coupled to the memory storage, wherein the processing unit is operative to: determine a Make Before Break Roaming (MBBR) action from a client device, wherein the client device is a multi-link device comprising a first link established with a first Access Point (AP) and a second link established with a second AP, and wherein the first AP and the second AP are non-co-located APs, and wherein the client device is one of a Non-Simultaneous Transmit/Receive (NSTR) and an Enhanced Multi Link Single Radio (eMLSR); create non-overlapping Target Wake Times (TWTs) respectively associated with two links used by the client device; and take down the TWTs after a roam has been completed.
 6. The system of claim 5, wherein an awake-window duty cycle for each of the TWTs is less than 50%.
 7. The system of claim 5, wherein the processing unit being operative to create the non-overlapping TWTs comprises the processing unit being operative to create the non-overlapping TWTs by the client device.
 8. The system of claim 5, wherein the processing unit being operative to create the non-overlapping TWTs comprises the processing unit being operative to create the non-overlapping TWTs by a controller of a network.
 9. A non-transitory computer-readable medium that stores a set of instructions which when executed by a processor perform a method executed by the set of instructions comprising: determining a Make Before Break Roaming (MBBR) action from a client device, wherein the client device is a multi-link device comprising a first link established with a first Access Point (AP) and a second link established with a second AP, and wherein the first AP and the second AP are non-co-located APs, and wherein the client device is one of a Non-Simultaneous Transmit/Receive (NSTR) and an Enhanced Multi Link Single Radio (eMLSR); creating non-overlapping Target Wake Times (TWTs) respectively associated with two links used by the client device; and taking down the TWTs after a roam has been completed.
 10. The non-transitory computer-readable medium of claim 9, wherein an awake-window duty cycle for each of the TWTs is less than 50%.
 11. The non-transitory computer-readable medium of claim 9, wherein creating the non-overlapping TWTs comprises creating the non-overlapping TWTs by the client device.
 12. The non-transitory computer-readable medium of claim 9, wherein creating the non-overlapping TWTs comprises creating the non-overlapping TWTs by a controller of a network.
-

