

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250258682

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

PINTO; Oscar P.

PLUGIN FRAMEWORK MECHANISM TO MANAGE COMPUTATIONAL STORAGE DEVICES

Abstract

A system is disclosed. The system may include a processor, a storage device, and aa computational device. A plugin may be associated with a service on the computational device. A framework may be implemented in software and configured to be executed on the processor. The framework may include a receiver to receive a service request from an application configured to be executed on the processor and a service response from the plugin. The service request may identify a service requested by the application. The framework may also include a plugin selector to select the plugin based at least in part on the service. The framework may also include a transmitter to deliver the service request to the plugin and the service response to the application. The application may be agnostic to the plugin and the computational device.

Inventors: PINTO; Oscar P. (San Jose, CA)

Applicant: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Family ID: 81748783

Appl. No.: 19/197958

Filed: May 02, 2025

Related U.S. Application Data

parent US continuation 17502023 20211014 PENDING child US 19197958

us-provisional-application US 63196667 20210603

Publication Classification

Int. Cl.: G06F9/445 (20180101); G06F13/40 (20060101); H04L67/51 (20220101)

U.S. Cl.:

Background/Summary

[0001] RELATED APPLICATION DATA [0002] This application is a continuation of U.S. patent application Ser. No. 17/502,023, filed Oct. 14, 2021, now allowed, which claims the benefit of U.S. Provisional Patent Application Ser. No. 63/196,667, filed Jun. 3, 2021, both of which are incorporated by reference herein for all purposes. [0003] This application is related to U.S. patent application Ser. No. 17/359,495, filed Jun. 25, 2021, which claims the benefit of U.S. Provisional Patent Application Ser. No. 63/073,922, filed Sep. 2, 2020, U.S. Provisional Patent Application Ser. No. 63/141,970, filed Jan. 26, 2021, U.S. Provisional Patent Application Ser. No. 63/142,485, filed Jan. 27, 2021, and U.S. Provisional Patent Application Ser. No. 63/144,469, filed Feb. 1, 2021, all of which are incorporated by reference herein for all purposes. [0004] This application is related to U.S. patent application Ser. No. 17/234,780, filed Apr. 19, 2021, which claims the benefit of U.S. Provisional Patent Application Ser. No. 63/073,922, filed Sep. 2, 2020, and U.S. Provisional Patent Application Ser. No. 63/144,469, filed Feb. 1, 2021, all of which are incorporated by reference herein for all purposes.

FIELD

[0005] The disclosure relates generally to storage devices, and more particularly to managing communication with storage devices without learning about the specifics of the storage devices.

BACKGROUND

[0006] When a host processor sends a request to a storage device—whether to read data, write data, or for some near-storage processor to process data—the host needs to know particulars about the storage device. For example, the host needs to know which particular storage device is to execute the request. This makes the host dependent on the availability of the storage device: if the storage device is removed, or if the application being executed by the host is moved to another host, the application might fail to execute correctly.

[0007] A need remains to support hosts using storage devices without the host having to know the specifics of the storage devices.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] The drawings described below are examples of how embodiments of the disclosure may be implemented, and are not intended to limit embodiments of the disclosure. Individual embodiments of the disclosure may include elements not shown in particular figures and/or may omit elements shown in particular figures. The drawings are intended to provide illustration and may not be to scale.

[0009] FIG. 1 shows a system including a computational storage unit that supports plugins, according to embodiments of the disclosure.

[0010] FIG. 2 shows details of the machine of FIG. 1, according to embodiments of the disclosure.

[0011] FIG. 3A shows a first example arrangement of a computational storage unit that may be associated with the storage device of FIG. 1, according to embodiments of the disclosure.

[0012] FIG. 3B shows a second example arrangement of a computational storage unit that may be associated with the storage device of FIG. 1, according to embodiments of the disclosure.

[0013] FIG. 3C shows a third example arrangement of a computational storage unit that may be associated with the storage device of FIG. 1, according to embodiments of the disclosure.

[0014] FIG. 3D shows a fourth example arrangement of a computational storage unit that may be associated with the storage device of FIG. 1, according to embodiments of the disclosure.

[0015] FIG. 4 shows an application running on the machine of FIG. 1 issuing requests to the computational storage unit of FIG. 1 via a framework and plugins, according to embodiments of the disclosure.

[0016] FIG. 5 shows the plugins of FIG. 4 abstracting the transport protocol used for communicating with the computational storage unit of FIG. 1, according to embodiments of the disclosure.

[0017] FIG. 6 shows the plugins of FIG. 4 abstracting the type of the computational storage unit of FIG. 1, according to embodiments of the disclosure.

[0018] FIG. 7 shows the plugins of FIG. 4 abstracting a feature of the computational storage unit of FIG. 1, according to embodiments of the disclosure.

[0019] FIG. 8 shows details of the framework of FIG. 1, according to embodiments of the disclosure.

[0020] FIG. 9 shows an exchange of messages among the machine of FIG. 1, the framework of FIG. 1, and the plugin of FIG. 1, according to embodiments of the disclosure.

[0021] FIG. 10 shows details of a mapping between services and the plugin of FIG. 1, as may be used by the framework of FIG. 1, according to embodiments of the disclosure.

[0022] FIG. 11 shows an exchange of messages between the framework of FIG. 1 and the plugin of FIG. 1, according to embodiments of the disclosure.

[0023] FIG. 12A shows a flowchart of an example procedure for the plugins of FIG. 4 to process a request to access data on the storage device of FIG. 1, according to embodiments of the disclosure.

[0024] FIG. 12B continues the flowchart of the example procedure for the plugins of FIG. 4 to process a request to access data on the storage device of FIG. 1, according to embodiments of the disclosure.

[0025] FIG. 12C continues the flowchart of the example procedure for the plugins of FIG. 4 to process a request to access data on the storage device of FIG. 1, according to embodiments of the disclosure.

[0026] FIG. 13 shows a flowchart of an example procedure for the framework of FIG. 1 to process the service request of FIG. 9 from the application of FIG. 1 using the plugins of FIG. 4, according to embodiments of the disclosure.

[0027] FIG. 14A shows a flowchart of another example procedure for the framework of FIG. 1 to process the service request of FIG. 9 from the application of FIG. 1 using the plugins of FIG. 4, according to embodiments of the disclosure.

[0028] FIG. 14B continues the flowchart of the other example procedure for the framework of FIG. 1 to process the service request of FIG. 9 from the application of FIG. 1 using the plugins of FIG. 4, according to embodiments of the disclosure.

[0029] FIG. 15 shows a flowchart of an example procedure for the framework of FIG. 1 to identify the plugin of FIG. 1 as capable of processing the service request of FIG. 9 from the application of FIG. 4, according to embodiments of the disclosure.

[0030] FIG. 16 shows a flowchart of another example procedure for the framework of FIG. 1 to identify the plugin of FIG. 1 as capable of processing the service request of FIG. 9 from the application of FIG. 4, according to embodiments of the disclosure.

SUMMARY

[0031] Embodiments of the disclosure include a storage device that may support a data retention period. When the storage device receives a write request, the storage device may determine the retention period for the data. This information may be used to select where (and/or how) to program the data onto the storage device.

DETAILED DESCRIPTION

[0032] Reference will now be made in detail to embodiments of the disclosure, examples of which

are illustrated in the accompanying drawings. In the following detailed description, numerous specific details are set forth to enable a thorough understanding of the disclosure. It should be understood, however, that persons having ordinary skill in the art may practice the disclosure without these specific details. In other instances, well-known methods, procedures, components, circuits, and networks have not been described in detail so as not to unnecessarily obscure aspects of the embodiments.

[0033] It will be understood that, although the terms first, second, etc. may be used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another. For example, a first module could be termed a second module, and, similarly, a second module could be termed a first module, without departing from the scope of the disclosure.

[0034] The terminology used in the description of the disclosure herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the disclosure. As used in the description of the disclosure and the appended claims, the singular forms “a”, “an”, and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will also be understood that the term “and/or” as used herein refers to and encompasses any and all possible combinations of one or more of the associated listed items. It will be further understood that the terms “comprises” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof. The components and features of the drawings are not necessarily drawn to scale.

[0035] Many applications issue requests with a particular storage device intended to execute the request. This design may tie the application to the storage device. For example, if the storage device is removed from the system, or the application is moved to another host, the application may fail to execute correctly. This problem may occur even if the data on the storage device is moved with the application: for example, if the application assumes a particular compression or encryption algorithm is applied to the data, a change in the storage device may result in a different compression or encryption algorithm being used. As a result, the application may make assumptions about the storage device that might not be true forever.

[0036] Embodiments of the disclosure support a framework for plugins. A plugin may support a feature of one or more storage devices, and a single storage device may use one or more plugins for various features of the storage device. For example, a storage device may include a plugin to manage reading data from and/or writing data to the storage device, and another plugin to permit an application to execute a service offered by the storage device. These plugins may register with a framework.

[0037] When an application wants to issue a request for a feature of a storage device, the request may be issued using an Application Programming Interface (API) without identifying a particular storage device. The API may interface with the framework to determine what storage devices are available, and what features are offered by those storage devices. An appropriate plugin may be used to forward the request to an appropriate storage device.

[0038] FIG. 1 shows a system including a computational storage unit that supports plugins, according to embodiments of the disclosure. In FIG. 1, machine 105, which may also be termed a host or a system, may include processor 110, memory 115, and storage device 120. Processor 110 may be any variety of processor. (Processor 110, along with the other components discussed below, are shown outside the machine for ease of illustration: embodiments of the disclosure may include these components within the machine.) While FIG. 1 shows a single processor 110, machine 105 may include any number of processors, each of which may be single core or multi-core processors, each of which may implement a Reduced Instruction Set Computer (RISC) architecture or a Complex Instruction Set Computer (CISC) architecture (among other possibilities), and may be

mixed in any desired combination.

[0039] Processor **110** may be coupled to memory **115**. Memory **115** may be any variety of memory, such as flash memory, Dynamic Random Access Memory (DRAM), Static Random Access Memory (SRAM), Persistent Random Access Memory, Ferroelectric Random Access Memory (FRAM), or Non-Volatile Random Access Memory (NVRAM), such as Magnetoresistive Random Access Memory (MRAM) etc. Memory **115** may also be any desired combination of different memory types, and may be managed by memory controller **125**. Memory **115** may be used to store data that may be termed “short-term”: that is, data not expected to be stored for extended periods of time. Examples of short-term data may include temporary files, data being used locally by applications (which may have been copied from other storage locations), and the like.

[0040] Processor **110** and memory **115** may also support an operating system under which various applications may be running. These applications may issue requests (which may also be termed commands) to read data from or write data to either memory **115** or storage device **120**. Storage device **120** may be accessed using device driver **130**.

[0041] Storage device **120** may be associated with computational storage unit **135**. As discussed below with reference to FIGS. 3A-3D, computational storage unit **135** may be part of storage device **120**, or it may be separate from storage device **120**. The phrase “associated with” is intended to cover both a storage device that includes a computational storage unit and a storage device that is paired with a computational storage unit that is not part of the storage device itself. In other words, a storage device and a computational storage unit may be said to be “paired” when they are physically separate devices but are connected in a manner that enables them to communicate with each other.

[0042] In addition, the connection between the storage device and the paired computational storage unit might enable the two devices to communicate, but might not enable one (or both) devices to work with a different partner: that is, the storage device might not be able to communicate with another computational storage unit, and/or the computational storage unit might not be able to communicate with another storage device. For example, the storage device and the paired computational storage unit might be connected serially (in either order) to the fabric, enabling the computational storage unit to access information from the storage device in a manner another computational storage unit might not be able to achieve.

[0043] Processor **105** and storage device **120** are shown as connecting to fabric **140**. Fabric **140** is intended to represent any fabric along which information may be passed. Fabric **140** may include fabrics that may be internal to machine **105**, and which may use interfaces such as Peripheral Component Interconnect Express (PCIe), Serial AT Attachment (SATA), Small Computer Systems Interface (SCSI), among others. Fabric **140** may also include fabrics that may be external to machine **105**, and which may use interfaces such as Ethernet, InfiniBand, or Fibre Channel, among others. In addition, fabric **140** may support one or more protocols, such as Non-Volatile Memory (NVM) Express (NVMe), NVMe over Fabrics (NVMe-oF), or Simple Service Discovery Protocol (SSDP), among others. Thus, fabric **140** may be thought of as encompassing both internal and external networking connections, over which commands may be sent, either directly or indirectly, to storage device **120** (and more particularly, the computational storage unit associated with storage device **120**).

[0044] To aid in abstracting away the details of storage device **120** and/or computational storage unit **135**, machine **105** may also include framework **145** and plugin **150**. Framework **145** may manage the registration, deregistration, and use of plugins such as plugin **150**. Plugin **150** may communicate with computational storage unit **135**, enabling an application to access a service offered by storage device **120** and/or computational storage unit **135** with the application having to know the particulars of storage device **120** and/or computational storage unit **135**. That is, the application may issue a request for a particular service. Framework **145** may identify plugin **150** as being associated with storage device **120** and/or computational storage unit **135**, and is capable of

carrying out the service requested by the application. Framework **145** may then deliver the service request to plugin **150**, which may then interface with storage device **120** and/or computational storage unit **135** to have the requested service executed. Plugin **150** may then receive a result of the service execution from storage device **120** and/or computational service unit **135** and return that result to framework **145**, which may return the result to the application. Framework **145** and plugin **150** are discussed further below.

[0045] While FIG. **1** shows one storage device **120**, one computational storage unit **135**, and one plugin **150**, there may be any number of storage devices, computational storage units, and plugins in machine **105**. For example, plugin **150**, like device driver **130**, may support any number of storage devices **120** and/or computational storage units **135**. In addition, as discussed below with reference to FIG. **7**, (single) computational storage unit **135** may be associated with two (or more) plugins **150**.

[0046] In addition, in some embodiments of the disclosure, plugin **150** may offer a host level abstraction. An application may have been originally implemented on a system that includes some particular functionality: for example, storage device **120** may support compression and/or encryption of data stored thereon. If the application is ported to another system, or if storage device **120** and/or computational storage unit **135** are replaced with another storage device and/or computational storage unit, the storage device/computational storage unit with which the application now interfaces might no longer implement the service offered the previous storage device or computational storage unit. In such situations, plugin **150** may permit processor **110** to perform the service previously performed by storage device **120** and/or computational storage unit **135**. In this manner, the application may continue to function despite the fact that the hardware currently supporting the application may not be capable of carrying of the specific services. This approach avoids the need for the application to be modified simply because it is ported to a new machine or the machine's hardware is modified. This host level abstraction plugin may therefore process a service request into commands (one or more) that may be executed by processor **110**.

[0047] While FIG. **1** uses the generic term “storage device”, embodiments of the disclosure may include any storage device formats that may benefit from the use of data quality metrics, examples of which may include hard disk drives and Solid State Drives (SSDs). Any reference to “SSD” below should be understood to include such other embodiments of the disclosure. In addition, while the discussion above (and below) focuses on storage device **120** as being associated with a computational storage unit, embodiments of the disclosure may extend to devices other than storage devices that may include or be associated with a computational storage unit. Any reference to “storage device” above (and below) may be understood as also encompassing other devices that might be associated with a computational storage unit.

[0048] FIG. **2** shows details of machine **105** of FIG. **1**, according to embodiments of the disclosure. In FIG. **2**, typically, machine **105** includes one or more processors **110**, which may include memory controllers **120** and clocks **205**, which may be used to coordinate the operations of the components of the machine. Processors **110** may also be coupled to memories **115**, which may include random access memory (RAM), read-only memory (ROM), or other state preserving media, as examples. Processors **110** may also be coupled to storage devices **125**, and to network connector **210**, which may be, for example, an Ethernet connector or a wireless connector. Processors **110** may also be connected to buses **215**, to which may be attached user interfaces **220** and Input/Output (I/O) interface ports that may be managed using I/O engines **225**, among other components.

[0049] FIGS. **3A-3D** show various arrangements of computational storage unit **135** of FIG. **1** (which may also be termed a “computational device” or “device”) that may be associated with storage device **120** of FIG. **1**, according to embodiments of the disclosure. In FIG. **3A**, storage device **305** and computational device **310-1** are shown. Storage device **305** may include controller **315** and storage **320-1**, and may be reachable across queue pairs: queue pairs **325** may be used both for management of storage device **305** and to control I/O of storage device **305**.

[0050] Computational device **310-1** may be paired with storage device **305**. Computational device **310-1** may include any number (one or more) processors **330**, which may offer one or more services **335-1** and **335-2**. To be clearer, each processor **330** may offer any number (one or more) services **335-1** and **335-2** (although embodiments of the disclosure may include computational device **310-1** including exactly two services **335-1** and **335-2**). Computational device **310-1** may be reachable across queue pairs **340**, which may be used for both management of computational device **310-1** and/or to control I/O of computational device **310-1**.

[0051] Processor(s) **330** may be thought of as near-storage processing: that is, processing that is closer to storage device **305** than processor **110** of FIG. 1. Because processor(s) **330** are closer to storage device **305**, processor(s) **330** may be able to execute commands on data stored in storage device **305** more quickly than for processor **110** of FIG. 1 to execute such commands. While not shown in FIG. 3A, processor(s) **330** may have associated memory which may be used for local execution of commands on data stored in storage device **305**. This associated memory may include local memory similar to memory **115** of FIG. 1, on-chip memory (which may be faster than memory such as memory **115**, but perhaps more expensive to produce), or both.

[0052] While FIG. 3A shows storage device **305** and computational device **310-1** as being separately reachable across fabric **140**, embodiments of the disclosure may also include storage device **305** and computational device **310-1** being serially connected (as shown in FIG. 1). That is, commands directed to storage device **305** and computational device **310-1** might both be received at the same physical connection to fabric **140** and may pass through one device to reach the other. For example, if computational device **310-1** is located between storage device **305** and fabric **140**, computational device **310-1** may receive commands directed to both computational device **310-1** and storage device **305**: computational device **310-1** may process commands directed to computational device **310-1**, and may pass commands directed to storage device **305** to storage device **305**. Similarly, if storage device **305** is located between computational device **310-1** and fabric **140**, storage device **305** may receive commands directed to both storage device **305** and computational device **310-1**: storage device **305** may process commands directed to storage device **305** and may pass commands directed to computational device **310-1** to computational device **310-1**.

[0053] Services **335-1** and **335-2** may offer a number of different functions that may be executed on data stored in storage device **305**. For example, services **335-1** and **335-2** may offer pre-defined functions, such as encryption, decryption, compression, and/or decompression of data, erasure coding, and/or applying regular expressions. Or, services **335-1** and **335-2** may offer more general functions, such as data searching and/or SQL functions. Services **335-1** and **335-2** may also support running application-specific code. That is, the application using services **335-1** and **335-2** may provide custom code to be executed using data on storage device **305**. Services **335-1** and **335-2** may also any combination of such functions. Table 1 lists some examples of services that may be offered by processor(s) **330**.

TABLE-US-00001 TABLE 1 Service Types Compression Encryption Database filter Erasure coding RAID Hash/CRC RegEx (pattern matching) Scatter Gather Pipeline Video compression Data Deduplication Operating System Image Loader Container Image Loader Berkeley packet filter (BPF) loader FPGA Bitstream loader Large Data Set

[0054] Processor(s) **330** (and, indeed, computational device **310-1**) may be implemented in any desired manner. Example implementations may include a local processor, such as Central Processing Unit (CPU) or some other processor, a Graphics Processing Unit (GPU), a General Purpose GPU (GPGPU), a Data Processing Unit (DPU), and a Tensor Processing Unit (TPU), among other possibilities. Processor(s) **330** may also be implemented using a Field Programmable Gate Array (FPGA) or an Application-Specific Integrated Circuit (ASIC), among other possibilities. If computational device **310-1** includes more than one processor **330**, each processor may be implemented as described above. For example, computational device **310-1** might have one

each of CPU, TPU, and FPGA, or computational device **310-1** might have two FPGAs, or computational device **310-1** might have two CPUs and one ASIC, etc.

[0055] Depending on the desired interpretation, either computational device **310-1** or processor(s) **330** may be thought of as a computational storage unit.

[0056] Whereas FIG. 3A shows storage device **305** and computational device **310-1** as separate devices, in FIG. 3B they may be combined. Thus, computational device **310-2** may include controller **315**, storage **320-1**, and processor(s) **330** offering services **335-1** and **335-2**. As with storage device **305** and computational device **310-1** of FIG. 3A, management and I/O commands may be received via queue pairs **340**. Even though computational device **310-2** is shown as including both storage and processor(s) **330**, FIG. 3B may still be thought of as including a storage device that is associated with a computational storage unit.

[0057] In yet another variation shown in FIG. 3C, computational device **310-3** is shown. Computational device **310-3** may include controller **315** and storage **320-1**, as well as processor(s) **330** offering services **335-1** and **335-2**. But even though computational device **310-3** may be thought of as a single component including controller **315**, storage **320-1**, and processor(s) **330** (and also being thought of as a storage device associated with a computational storage unit), unlike the implementation shown in FIG. 3B controller **315** and processor(s) **330** may each include their own queue pairs **325** and **340** (again, which may be used for management and/or I/O). By including queue pairs **325**, controller **315** may offer transparent access to storage **320-1** (rather than requiring all communication to proceed through processor(s) **330**).

[0058] In addition, processor(s) **330** may have proxied storage access **345** to use to access storage **320-1**. Thus, instead of routing access requests through controller **315**, processor(s) **330** may be able to directly access the data from storage **320-1**.

[0059] In FIG. 3C, both controller **315** and proxied storage access **345** are shown with dashed lines to represent that they are optional elements, and may be omitted depending on the implementation.

[0060] Finally, FIG. 3D shows yet another implementation. In FIG. 3D, computational device **310-4** is shown, which may include controller **315** and proxied storage access **345** similar to FIG. 3C. In addition, computational device **310-4** may include an array of one or more storage **320-1** through **320-4**. While FIG. 3D shows four storage elements, embodiments of the disclosure may include any number (one or more) of storage elements. In addition, the individual storage elements may be other storage devices, such as those shown in FIGS. 3A-3D.

[0061] Because computational device **310-4** may include more than one storage element **320-1** through **320-4**, computational device **310-4** may include array controller **350**. Array controller **350** may manage how data is stored on and retrieved from storage elements **320-1** through **320-4**. For example, if storage elements **320-1** through **320-4** are implemented as some level of a Redundant Array of Independent Disks (RAID), array controller **350** may be a RAID controller. If storage elements **320-1** through **320-4** are implemented using some form of Erasure Coding, then array controller **350** may be an Erasure Coding controller.

[0062] FIG. 4 shows an application running on machine **105** of FIG. 1 issuing requests to computational device **135** of FIG. 1 via framework **145** of FIG. 1 and plugin **150** of FIG. 1, according to embodiments of the disclosure. In FIG. 4, application **405** may send requests for services that are intended to be executed by storage device **120** of FIG. 1 and/or computational device **135** of FIG. 1. These service requests may include reading data from storage, writing data to storage, or executing some other service that may involve data on storage device **120** of FIG. 1, such as compression/decompression, encryption/decryption, or other processing, to name some examples.

[0063] Application **405** may send these service requests using an Application Programming Interface (API), that may be offered by Computational Service (CS) API library **410**. Using an API may enable application **405** to issue service requests in a manner that is generic, without application **405** needing to know what storage devices **120** and/or computational devices **135** are

available from machine **105** of FIG. **1**. More specifically, application **405** may issue such service requests without needing to format the service requests in a particular manner expected by storage devices **120** and/or computational devices **135**: application **405** may leave it to CS API library **410** and related elements to pass the service request to the appropriate module (such as storage device **120** or computational device **135**).

[0064] But while using APIs from CS API library **410** may simplify the implementation of application **405**, CS API library **410** would be responsible for passing the service request to storage device **120** and/or computational device **135**. While it is not necessarily difficult for CS API library **410** to know such information, CS API library **410** may need to be augmented every time a new module (be it storage device **120** or computational device **135**) is implemented, so as to be able to support the use of such a module if it is added to machine **105**.

[0065] By adding framework **145** and plugins **150**, CS API library **410** may avoid modification every time a new module is implemented. Instead, when a new module is installed, the system administrator may register one or more plugins **150** appropriate to the module with framework **145**. This approach shifts the formatting and other delivery issues from CS API library **410** to plugins **150**, and only the plugins needed to support the installed modules may be registered with framework **145**. Plugins **150** may receive requests in a manner that CS API library **410** may use (regardless of which plugin **150** ultimately receives the service request), and plugins **150** may handle the particulars of how the service requests are delivered to the appropriate module.

[0066] In FIG. **4**, NVMe plugin **150-1**, FPGA plugin **150-2**, and file system plugin **150-3** are shown. NVMe plugin **150-1** may be responsible for handling service requests to be delivered to an NVMe storage device. FPGA plugin **150-2** may be responsible for handling service requests to be delivered to an FPGA. File system plugin **150-3** may be responsible for handling file system requests and converting them into a format appropriate for the storage device that may ultimately carry out the service request. File system plugin **150-3** is discussed further with reference to FIGS. **7** and **12A-12C** below.

[0067] While FIG. **4** shows NVMe plugin **150-1**, FPGA plugin **150-2**, and file system plugin **150-3** as registered with framework **145**, embodiments of the disclosure may include or omit these particular plugins as appropriate for modules included in machine **105**. Embodiments of the disclosure may also include other plugins not shown in FIG. **4**, as appropriate for modules included in machine **105**.

[0068] If machine **105** includes more than one NVMe storage device, NVMe plugin **150-1** may be responsible for delivering service requests to all such devices. Similarly, if machine **105** includes more than one FPGA, FPGA plugin **150-2** may be responsible for delivering service requests to all such FPGAs. But in some embodiments of the disclosure, there may be more than one NVMe plugin **150-1** and/or more than one FPGA plugin **150-2** to support different NVMe storage devices and/or different FPGAs. The same concept may hold true for plugins associated with other types of modules.

[0069] One particular type of plugin not shown in FIG. **4** is an NVMe-oF plugin. But framework **145** may support an NVMe-oF plugin intended to support service requests executed by an NVMe-oF storage device. An NVMe-oF storage device may be physically remote from machine **105** of FIG. **1** (in the sense that the NVMe-oF storage device may be accessed across some sort of network, be it a local area network (LAN), a wide area network (WAN), a metropolitan area network (MAN) or a global network). But because the NVMe-oF storage device is accessible from machine **105** of FIG. **1**, the NVMe-oF storage device is logically included in machine **105**. Thus, the phrase “included in” and its variants, in this context, are intended to encompass both modules that are physically inside machine **105** of FIG. **1** and modules that are accessible from machine **105** of FIG. **1**, even if not physically inside machine **105** of FIG. **1**.

[0070] FIG. **4** also shows a custom plugin. The custom plugin of FIG. **4** is intended to represent any other plugins not specifically described. In addition, the custom plugin may represent plugins

that may support execution of requests by storage device **120** and/or computational device **135** but might not be standardized. For example, a vendor might offer a special function, not offered by other vendors (and possibly not offered in other modules of the vendor), built into a storage device and/or computational device. Or, the storage device/computational device may offer a function not supported by the standard plugin for the module (as may happen if a single plugin is designed to support two or more different types of devices). The custom plugin may provide a mechanism by which these functions may be accessed, and is discussed further with reference to FIG. 7 below.

[0071] The presence of custom plugin thus illustrates that the relationship between plugins and modules may be one-to-one, one-to-many, many-to-one, or many-to-many. That is, a single plugin might be associated with one or more different modules, a single module may be associated with multiple plugins, and multiple plugins may each be associated with multiple modules.

[0072] As an example, consider a system that includes two NVMe storage devices, one of which offers a special function not generally offered by NVMe storage device, and one computational device implemented as an FPGA. NVMe plugin **150-1** may support services offered by both NVMe storage devices, FPGA plugin **150-2** may support services offered by the FPGA computational device, and a custom plugin may support the special function of the one NVMe storage device. In this example, FPGA plugin **150-2** is associated with one FPGA computational device (a one-to-one relationship), NVMe plugin **150-1** is associated with two NVMe storage devices (a one-to-many relationship), and the one NVMe storage device may also be associated with the custom plugin (a many-to-one relationship) (the latter two relationships combined may also be considered as a many-to-many relationships).

[0073] As discussed above, plugins **150-1**, **150-2**, **150-3**, and the custom plugin may receive service request from framework **145** and process them for delivery to the device drivers **130-1**, **130-2**, **130-3**, and the custom driver. Thus, for example, NVMe plugin **150-1** may receive a service request from framework **145** and process the service request for delivery to NVMe driver **130-1**. In a similar manner, FPGA plugin **150-2** may receive a service request from framework **145** and process the service request for delivery to FPGA driver **130-2**, file system plugin **150-3** may receive a service request from framework **145** and process the service request for delivery to file system driver **130-3**, and the custom plugin may receive a service request from framework **145** and process the service request for delivery to the custom driver. Drivers **130-1**, **130-2**, **130-3**, and the custom driver may then deliver the service request to the appropriate modules, be they storage device **120** and/or computational device **135**. The specifics of how plugins **150-1**, **150-2**, **150-3**, and the custom plugin perform this processing may depend on the manner in which delivery to storage device **120** and/or computational device **135** may be achieved, and thus may vary from plugin to plugin. For example, NVMe plugin **150-1** may process the service request to produce an NVMe request (such as an NVMe read request or an NVMe write request, among other possibilities), whereas FPGA plugin **150-2** may process the service request to load the data into a memory of computational device **135** and request that a particular service (such as services **335-1** and/or **335-2** of FIGS. 3A-3D) be executed on that data.

[0074] In FIG. 4, plugins **150-1**, **150-2**, **150-3**, and the custom plugin are shown as including elements operating in both the user space and the kernel space. In some embodiments of the disclosure, this implementation may be used when the architecture includes a user space and a kernel space. But other architectures may support other implementations. For example, when a Storage Performance Development Kit (SPDK) is used, the device drivers may operate in user space. In such embodiments of the disclosure, there may be no kernel space portion of the plugins **150-1**, **150-2**, **150-3**, or the custom plugin. In other embodiments of the disclosure, CS API library **410** may reside within the kernel space, in which case there may be no user space portion of plugins **150-1**, **150-2**, **150-3**, or the custom plugin. But regardless of the underlying operating system architecture, framework **145** and plugins **150-1**, **150-2**, **150-3**, and the custom plugin, may function similarly from the perspective of application **405** (albeit with potentially different

underlying implementations).

[0075] One element not touched on above is application adaptor **415**. Application adaptor **415** may include a pre-programmed set of API calls that may be used in a particular use case. For example, if computational device **135** implements a particular Structured Query Language (SQL) command, application adaptor **415** may include the particular API calls that load data into a memory of computational device **135** and invoke the SQL command. In this manner, application **405** may use application adaptor **415** to execute such a pre-programmed set of API calls and avoid having to understand how to make the individual API calls. While FIG. **1** shows one application adaptor, embodiments of the disclosure may include any number (zero or more) application adaptors **415**. Because application adaptor **415** may issue API calls just like application **405**, such API calls may involve service requests that framework **145** may pass to plugins **150-1**, **150-2**, **150-3**, and/or the custom plugin.

[0076] FIG. **5** shows plugins **150** of FIG. **4** abstracting the transport protocol used for communicating with computational device **135** of FIG. **1**, according to embodiments of the disclosure. In FIG. **5**, application **405**, application adaptor **415**, CS API library **410**, and framework **145** may operate as described with reference to FIG. **4** above.

[0077] Plugin **150-1** may represent a plugin that may communicate with local computational device **135-1** that may be accessed, for example, across a PCIe bus in machine **105**, using PCIe protocol **505**. (While FIG. **5** shows plugin **150-1** communicating with computational device **135-1**, embodiments of the disclosure may have plugin **150-1** communicating with storage device **120** of FIG. **1**; and reference to a computational device should be understood as also including a storage device.)

[0078] Plugin **150-2** may represent a plugin that may communicate with remote computational device **135-2** that may be accessed, for example, across a network using NVMe-oF protocol **510**.

[0079] Plugin **150-3** may represent a plugin that may communicate with a remote computational device **135-3**. But unlike plugins **150-1** and **150-2** that may be communicating using well-defined protocols, plugin **150-3** may establish its own protocol stack. For example, protocol stack **515** includes a Remote Direct Memory Access (RDMA) protocol, which feeds into an InfiniBand (IB) protocol, which feeds into a Fibre Channel (FC) protocol, which feeds into a Transmission Control Protocol (TCP). The information handled by this protocol stack may then feed into translator **520-1**, which may handle the actual transmission of the data across fabric **140** to computational device **135-3**. Note that remote computational device **135-3** may need its own translator **520-2** to process the information from protocol stack **515**.

[0080] While FIG. **5** shows remote computational devices **135-2** and/or **135-3** receiving service requests in the “native language” of computational devices **135-2** and/or **135-3**, what is not shown is whether the service request is translated into the “native language” of computational devices **135-2** and/or **135-3** before or after transmission across fabric **140** to the remote computational devices. In some embodiments of the disclosure, this processing may be done by the portion of the plugin resident on machine **105** of FIG. **1**, with the service request already in the “native language” of the remote computational device (but packaged for transmission across fabric **140**). In other embodiments of the disclosure, this processing may be done by the portion of the plugin resident on the remote machine where computational devices **135-2** and/or **135-3** are housed. That is, plugins **150-2** and/or **150-3** may simply package the service request as received from framework **145** for transmission across fabric **140**, and after unpackaging the service request by the plugin on the remote machine, the plugin on the remote machine may process the request into the “native language” of remote computational devices **135-2** and/or **135-3**.

[0081] FIG. **6** shows plugins **150** of FIG. **4** abstracting the type of computational device **135** of FIG. **1**, according to embodiments of the disclosure. In FIG. **6**, application **405**, application adaptor **415**, CS API library **410**, and framework **145** may operate as described with reference to FIG. **4** above.

[0082] As far as framework **145** (and application **405** and CS API library **410** as well) is concerned, plugins **150-1**, **150-2**, and **150-3** are all essentially equivalent. Framework **145** may understand that different plugins may be associated with different storage devices and/or computational devices, but framework **145** may be agnostic regarding what storage devices/computational devices are associated with any particular plugins. Thus, framework **145** may not know that plugin **140-1** is associated with computational device **135-1**, which may be an FPGA, that plugin **150-2** is associated with computational device **135-2**, which may be an ASIC, or that plugin **150-3** is associated with computational device **135-3**, which may be an embedded CPU. In this manner, the particular computational device **135** that handles a request processed by plugins **150** is abstracted away from framework **145** (and from all elements “before” framework **145** in the hierarchy).

[0083] FIG. 7 shows plugins **150** of FIG. 4 abstracting a feature of computational device **135** of FIG. 1, according to embodiments of the disclosure. As discussed above with reference to FIG. 4, sometimes a plugin, such as plugin **150-1**, may not be able to completely process a request to be executed by the associated device. While FIG. 7 shows plugin **150-1** as NVMe plugin **150-1**, embodiments of the disclosure may include any plugin that may use a helper plugin.

[0084] This situation may occur, for example, if application **405** issues a file system request, but the device in question (such as computational device **135**) may expect a request to use a different storage model (for example, a block-based request, a key-value (KV) request, or (more generally) an object request). Future storage devices also may not expose the device or its internal memory to application **405**, in which case computational device **135** may not support file system calls, and a helper plugin may be needed.

[0085] This situation may also occur if the associated device offers a feature not supported by the primary plugin associated with the device. For example, computational device **135** may support the use of containers or offer an extended Berkeley Packet Filter (cBPF) feature. cBPF (or, more generally, BPF) is a feature that permits source code to be validated and compiled into a portable byte code using the eBPF instruction set. This portable byte code may then be compiled or interpreted to execute on the target hardware. There are limits to what may be executed using the BPF feature: for example, the source code might not be permitted to include unbounded loops, jumps, or execution of code outside the portable byte code (such as a remote procedure call). eBPF features may be added to future or even existing computational devices, since they may execute somewhat general code using appropriate computational device hardware. But if the plugin that normally communicates with the device driver does not know how to process eBPF code, a helper plugin may be needed.

[0086] Another example of a situation where this may occur is, for example, in the use of a portable byte code to be executed by computational storage unit **135**.

[0087] In such situations, NVMe plugin **150-1** may use helper plugin **150-2** to process the portion of the service request that NVMe plugin **150-1** does not know how to process. For example, NVMe plugin **150-1** may call helper plugin **150-2** to convert a file system call into a block-based request (or a KV request, or an object request, or any other type of request, depending on the requests accepted by the associated module). Or, NVMe plugin **150-1** may call helper plugin **150-2** to handle the part of the request related to the feature that is not processed by NVMe plugin **150-1**. Once helper module **150-2** has completed its processing, NVMe plugin **150-1** may complete the processing of the service request and may deliver the request to NVMe driver **130** for ultimate delivery to the module.

[0088] Framework **145** may support a call that enables NVMe plugin **150-1** to query for available helper plugins **150-2**. Using such calls, NVMe plugin **150-1** may be able to identify what plugins are registered with framework **145** and may be able to act as helper plugin **150-2**.

[0089] While the above discussion suggests that NVMe plugin **150-1** is called first, and may then call helper plugin **150-2**, embodiments of the disclosure may operate in other sequences as well. For example, helper plugin **150-2** may initially receive the service request, handle the portion of the

service request that is unfamiliar to NVMe plugin **150-1**, and then transfer the (partially processed) service request to NVMe plugin **150-1**. Or, helper plugin **150-2** may initially receive the request, handle its portion of the service request, then return the (partially processed) service request back to framework **145** so that framework **145** may identify NVMe plugin **150-1** to continue processing the service request.

[0090] Because converting a file system call into a request that is appropriate for the device may be done on the host system (before NVMe plugin **150-1** may process the service request and deliver the service request to NVMe driver **130**), a file system plugin may be an example of a host level abstraction (where the processing is performed by the host rather than requesting a particular feature of storage device **120** of FIG. **1** or computational device **135** be used).

[0091] While the above discussion focuses on NVMe plugin **150-1** using a file system plugin as helper plugin **150-2**, embodiments of the disclosure may include any plugin that may use helper plugin **150-2**. Further, embodiments of the disclosure may include any plugin, and not just a file system plugin, operating as helper plugin **150-2**.

[0092] Because one plugin may call another plugin, plugins **150-1** and/or **150-2** may expose methods to enable such inter-plugin calls.

[0093] FIG. **8** shows details of framework **145** of FIG. **1**, according to embodiments of the disclosure. In FIG. **8**, framework **145** is shown as including receiver **805**, plugin selector **810**, and transmitter **815**. Receiver **805** may receive a request from machine **105**, which may be a service request from application **405** of FIG. **4**, or a request to register or deregister plugin **150** of FIG. **1** with framework **145**. Receiver **805** may also receive a service response from plugin **150** after plugin **150** and its associated module has completed processing of the service request from application **405** of FIG. **4**. Plugin selector **810** may select plugin **150** to process a service request from application **150**. Plugin selector **810** is discussed further with reference to FIGS. **10-11** below. Finally, transmitter **815** may transmit a service request received from application **405** of FIG. **4** to plugin **150** of FIG. **1**, and may transmit a service response received from plugin **150** of FIG. **1** to application **405** of FIG. **4**.

[0094] FIG. **9** shows an exchange of messages among machine **105** of FIG. **1**, framework **145** of FIG. **1**, and plugin **150** of FIG. **1**, according to embodiments of the disclosure. In FIG. **9**, system **105** may transmit registration request **905** to framework **145**, which framework **145** may receive using receiver **805** of FIG. **8**. Registration request **905** may be used to register a new plugin **150** with framework **145**. Registration request may be sent by a system administrator, or may be sent automatically when new hardware is added or a new hardware feature becomes available. A new plugin may be registered when a new module is added that may require a new plugin, or when a new plugin is to be added to support a new feature offered by an existing module. At block **910**, after framework **145** has completed the registration of the new plugin **150**, framework **145** may transmit registration response **910** to system **105** using transmitter **815** of FIG. **8**. Registration response **910** may be omitted, as shown by the dashed lines for registration response **910**.

[0095] Note that while registration request **905** may be sent every time a new module is added to system **105**, this fact does not mean that a new plugin **150** is registered every time registration request **905** is sent. As discussed above, a single plugin may be associated with multiple different modules. Thus, if the plugin being registered using registration request **905** is already registered with framework **145**, then registration response **910** may indicate that registration was not performed because plugin **150** was already registered. In this manner, the system administrator does not need to track which plugins are registered with framework **145**: framework **145** may decide whether or not to register any particular plugin by comparing the plugin being registered with the previously registered plugins. Of course, if the system administrator knows that plugin **150** is already registered, then the system administrator may skip sending registration request **905** in the first place, even if a new module is added.

[0096] Once plugin **150** is registered with framework **145**, application **405** of FIG. **4** may send

service request **915-1**, which framework **145** may receive using receiver **805** of FIG. **8**. Framework **145** may use plugin selector **810** of FIG. **8** to select plugin **150** to process service request **915-1**, and may forward service request **915-2** to plugin **150** using transmitter **145**. Plugin **150** may then process service request **915-2**.

[0097] Once plugin **150** has completed processing service request **915-2**, plugin **150** may send service response **920-1** to framework **145**, which framework **145** may receive using receiver **805** of FIG. **8**. Framework **145** may then transmit service response **920-2** to application **405** of FIG. **4** using transmitter **815**.

[0098] Note that plugin **150** may process any number of service requests from application **405** (or other applications on system **105**): there is no requirement that the exchange of messages among system **105**, framework **145**, and plugin **150** include exactly one service request.

[0099] Eventually, the system administrator may decide plugin **150** is not needed anymore. The system administrator may then send deregistration request **925** to framework **145**, which framework **145** may receive using receiver **805** of FIG. **8**. Framework **145** may then deregister plugin **150**, and may send deregistration response **930** back to the system administrator using transmitter **815** of FIG. **8**. Deregistration response **930** may be omitted, as shown by the dashed lines for deregistration response **930**.

[0100] Note that while framework **145** may check for plugin duplication upon registration, framework **145** may not have any way to check whether deregistration of a plugin is appropriate. For example, it might be that there is still a module in system **105** that might depend on plugin **150**: if plugin **150** is deregistered, that module might not be accessible for service request **915-1** from application **405** of FIG. **4**. But framework **145** may not be able to determine this fact, and may therefore deregister plugin **150** even when plugin **150** might still be useful: framework **145** may rely on the system administrator being correct in deregistering plugin **150**.

[0101] FIG. **10** shows details of a mapping between services and plugin **150** of FIG. **1**, as may be used by framework **145** of FIG. **1**, according to embodiments of the disclosure. In FIG. **10**, table **1005** is shown. Table **1005** is one example representation of how to map services to plugins; other mappings may also be used without limitation. Table **1005** shows three services, which map to various plugins. For example, service **1010** is shown as mapping to plugin **1**, plugin **2**, and plugin **3**. Table **1005** may include any number (zero or more) of mappings between services and plugins, and each service may map to any number (zero or more) plugins. Further, while table **1005** shows each plugin being mapped to by a single service, embodiments of the disclosure may include multiple services mapping to a single plugin. For example, computational devices **310-1** through **310-4** of FIGS. **3A-3D** are shown as offering services **335-1** and **335-2** of FIGS. **3A-3D**. If a single plugin is capable of processing both of these service requests, then a two or more services in table **110** may map to a single plugin.

[0102] Framework **145** of FIG. **1** may learn which services may be processed by a single plugin when the system administrator registers the plugin. That is, the plugin itself, as part of the registration process, may identify which services it can process. Framework **145** of FIG. **1** may use this information to build table **1005**.

[0103] In a similar manner, when application **405** of FIG. **4** issues service request **915-1** of FIG. **9**, service request **915-1** of FIG. **9** may identify the particular service being requested. Framework **145** (more particularly, plugin selector **810** of FIG. **8**) may use this information with table **1005** to identify which plugins to query to process service request **915-1** of FIG. **9**.

[0104] Note that “service” in the context of table **1005** may mean a general type of service, rather than a particular function. For example, service request **915-1** of FIG. **9** may request a function that may require an embedded CPU, or may request a function that would be implemented using an FPGA or an ASIC. In accessing table **1005** to select a plugin to execute service request **915-1** of FIG. **9**, framework **145** of FIG. **4** may simply use the generic type of service being sought, rather than the particular function to be executed. But in other embodiments of the disclosure the

“service” identified in table **1005** may have a more fine-grained definition, perhaps all the way down to the individual function to be executed.

[0105] Note that for most services in table **1005**, there may be at least one plugin to which the service maps. This plugin would be the host level abstraction, discussed with reference to FIG. **1**. Since the host level abstraction should be available to execute services for application **405** of FIG. **4** if the expected hardware is not available, the host level abstraction may be associated with most services. (One exception may be for services that involve reading data from or writing data to storage device **120** of FIG. **1**, as it may not be possible to emulate with processor **110** of FIG. **1** the reading of data from or the writing of data to a particular storage device.) In some embodiments of the disclosure, if there a plugin associated with a module that may execute a service request, using such a plugin instead of a host level abstraction plugin would be desirable, as such operation would reduce the load on processor **110**. In other embodiments of the disclosure, the host level abstraction plugin may be selected by plugin selector **810**, even if other plugins may be capable of carrying out the service request.

[0106] Note that FIG. **10** does not show a relationship between plugins and associated devices. This is because it is up to the individual plugins to track which associated devices they support. All that matters to framework **145** of FIG. **1** is that plugin **150** of FIG. **1** provides correct information about what services it supports and that plugin **150** of FIG. **1** conforms to the interface with framework **145** of FIG. **1**. As far as framework **145** of FIG. **1** is concerned, once service request **915-1** of FIG. **1** is delivered to plugin **150** of FIG. **1**, it is up to plugin **150** of FIG. **1** to complete the execution of service request **915-2** of FIG. **9**. How plugin **150** of FIG. **1** completes service request **915-2** of FIG. **9**—what plugin **150** of FIG. **1** does once it has received service request **915-2** of FIG. **9**—is not relevant to framework **145** of FIG. **1**.

[0107] In general, plugin **150** of FIG. **1**, once it has received service request **915-2** of FIG. **9**, may identify the appropriate module to carry out service request **915-2** of FIG. **9**. Plugin **150** of FIG. **1** may include its own table, similar to table **1005**, identifying which services may be performed by which modules. For example, plugin **150** may include a range of addresses (which may be logical addresses used by application **405** of FIG. **1**) that may be mapped to particular storage devices **120** of FIG. **1**, and may include its own list of services offered by the various associated modules. In this manner, plugin **150** of FIG. **1** may process service request **915-2** of FIG. **9** into a form expected by the device driver and may send the request to the appropriate device driver **130** (and ultimately to the appropriate module).

[0108] As may be seen in in table **1005**, there may be more than one plugin that may be associated with a particular service. But this fact does not automatically mean that any plugin associated with a particular service may execute a particular service request. For example, just because service request **915-1** of FIG. **9** from application **405** of FIG. **4** includes a request for service **1010**, it does not automatically follow that any of plugin **1**, plugin **2**, or plugin **3** may be asked to perform the service. For example, consider the situation where application **405** of FIG. **4** requests that data be read from storage device **120** of FIG. **1**: it may be that only the plugin associated with storage device **120** of FIG. **1** may be able to execute this service request (plugins associated with other storage devices may not be able to access storage device **120** of FIG. **1**, and therefore may not be able to read the requested data). Or, consider the situation where there are two computational devices **135** of FIG. **1**, each including ASIC, each ASIC implementing a different function: only the computational device **135** of FIG. **1** that includes the ASIC that actually implements the requested function may be able to service the request. The question then becomes how does framework **145** of FIG. **1** (more particularly, plugin selector **810** of FIG. **8**) select the appropriate plugin to execute the request.

[0109] The answer is that plugin selector **810** of FIG. **8** may query individual plugins associated with the service to find one that will accept service request **915-1** of FIG. **9**. That is, plugin selector **810** of FIG. **8** may ask each plugin associated with the service in table **1005** if it will accept a

particular service request: the plugin that accepts the service request may then process the service request.

[0110] One way for plugin selector **810** of FIG. **8** to operate is to send a multicast message to all plugins associated with the request service: the plugin that sends back the first affirmative response (meaning that the plugin may process the service request) may be asked to process the service request. But this approach may involve a large number of messages travelling between framework **145** of FIG. **1** and plugins **150** of FIG. **1**.

[0111] Another approach is shown in FIG. **11**, involving an exchange of messages between framework **145** of FIG. **1** and plugins **150-1** and **150-2** of FIG. **4**, according to embodiments of the disclosure. Plugin selector **810** (as part of framework **145** of FIG. **1**) may send query **1105** to plugin **150-1**, asking if plugin **150-1** may carry out service request **915-1** of FIG. **9**. In the example shown in FIG. **11**, plugin **150-1** is shown sending negative response **1110**, meaning that plugin **150-1** may not carry out service request **915-1** of FIG. **9**. Plugin selector **810** may then send query **1115** to plugin **150-2**, asking if plugin **150-2** may carry out service request **915-1** of FIG. **9**. In the example shown in FIG. **11**, plugin **150-2** is shown sending affirmative response **1120**, meaning that plugin **150-1** may carry out service request **915-1** of FIG. **9**. Upon receiving affirmative response **1120**, plugin selector **810** may select plugin **150-2** to execute service request **915-1** of FIG. **9**. The approach shown in FIG. **11** may avoid sending a large number of queries to plugins at the same time (potentially saturating bandwidth); but by querying plugins **150** individually, it may take a little longer to find plugin **150-2** to process service request **915-1** of FIG. **9**.

[0112] While FIG. **11** shows only one plugin **150-1** sending negative response **1110** to plugin selector **810**, embodiments of the disclosure may include any number of negative responses **1110** from any number of plugins **150**. That is, plugin selector **810** may find a plugin that accepts service request **915-1** of FIG. **1** after querying only one plugin, or plugin selector **810** may receive negative responses **1110** from any number (zero or more) plugins **150** before receiving affirmative response **1120** from plugin **150-2**. In addition, plugin selector **810** might not receive affirmative response **1120** from any plugin **150**, in which case the host level abstraction plugin might be used to execute service request **915-1** of FIG. **9**.

[0113] There are various reasons why plugin **150-1** might send negative response **1110**. One reason might be because the device associated with plugin **150-1** may lack the necessary hardware to carry out service request **915-1** of FIG. **1**. Another reason might be because the device associated with plugin **150-1** might not have access to the data to be processed. But plugin **150-1** might also send negative response **1110** because plugin **150-1** (or its associated device) has a backlog of requests to process, and another plugin **150** might be able to process service request **915-1** of FIG. **9** faster. Another reason why plugin **150** might send negative response **1110** is because plugin **150-1** does not know how to handle the request, but may be able to process the request after a helper plugin (such as helper plugin **150-2** of FIG. **7**) processes the request.

[0114] There is one risk associated with plugin **150-1** sending negative response **1110** even though plugin **150-1** is capable of processing service request **915-1** of FIG. **9**: what if plugin **150-1** is the only plugin capable of processing service request **915-1** of FIG. **9**? There are at least two ways to reduce this risk. One approach may involve recalling that the host level abstraction plugin should be available in most cases to process service request **915-1** of FIG. **9**, which means that if plugin **150-1** refuses to process service request **915-1** of FIG. **9**, there is still at least one plugin that may process service request **915-1** of FIG. **9**. (If service request **915-1** of FIG. **9** involves reading data from or writing data to storage device **120** of FIG. **1** or some other request that requires the device associated with plugin **150-1**, then plugin **150-1** should not refuse service request **915-1** of FIG. **9** even if the associated device has a large number of requests pending). Another approach may involve plugin **150-1** not refusing service request **915-1** of FIG. **9** outright, but instead returning a representation of the interest in plugin **150-1** to process service request **915-1** of FIG. **9**. For example, a value of **0** could mean that plugin **150-1** outright refuses to process service request **915-**

1 of FIG. 9 (which would mean that the module associated with plugin 150-1 lacks the appropriate hardware to execute service request 915-1 of FIG. 9); any other number may indicate the number of requests already pending with plugin 150-1 (and therefore roughly indicating how long it may take plugin 150-1 to process service request 915-1 of FIG. 9). Plugin selector 810 may then select the plugin with the lowest non-zero response to process service request 915-1 of FIG. 9. (Of course, framework 145 of FIG. 1 may track how many service requests 915-2 of FIG. 9 have been sent to plugin 150-1 for which service responses 920-1 of FIG. 9 have not yet been received, in which case plugin 150-1 may simply indicate that it is capable of processing service request 915-1 of FIG. 1 and leave it to plugin selector 810 to decide which plugin 150 of FIG. 1 may process service request 915-1 of FIG. 1.)

[0115] Another possibility would be for plugin 150-1 to use values between 0 and 10 to indicate interest in processing service request 915-1 of FIG. 1, with 0 indicating no interest and 10 indicating complete interest: plugin selector 810 may then select plugin 150 of FIG. 1 that returns the highest level of interest in processing service request 915-1 of FIG. 9.

[0116] The values and ranges used above are merely examples. Embodiments of the disclosure may use any values and/or ranges (including non-numeric values and/or ranges).

[0117] FIGS. 12A-12C show a flowchart of an example procedure for plugins 150 of FIG. 4 to process a request to access data on storage device 120 of FIG. 1, according to embodiments of the disclosure. In FIG. 12A, a request to access data may be received. Framework 145 of FIG. 1 may determine the type of the access request: the access request may include a file system request, a block-based request, a KV request, an object request, or a custom request.

[0118] If the request is a file system request, then at block 1205 framework 145 of FIG. 1 may determine if the device buffer is mapped. If the device buffer is mapped, then the device may support native file system requests, and at block 1210 the native file system request may be used to access the device.

[0119] If the device buffer is not mapped, then the device may not support native file system requests and may need an interpreter to map the filesystem request into a low level block request by mapping the file's offset/length co-ordinates to logical block addresses (LBAs): a service that file system plugin 150-3 of FIG. 3 may be able to provide. In that case, file system plugin 150-3 of FIG. 4 may be used to convert the file system request into a form appropriate for the device. At block 1215 (FIG. 12B), framework 145 of FIG. 1 may check to see if the file system request has been mapped previously and is currently cached in a cache. If the mapping is already cached, then at block 1220 framework 145 of FIG. 1 may skip invoking file system plugin 150-3 of FIG. 4 and just access the native request (which may also be called the mapped request) for the device from the cache. Otherwise, at block 1225, framework 145 of FIG. 1 may locate file system plugin 150-3 of FIG. 4, and at block 1230 file system plugin 150-3 of FIG. 4 may map the file system request into the native request for the device. Either way, at block 1235, the native request may be sent to the plugin associated with the device. As discussed above with reference to FIG. 7, this transmission of the native request to the plugin associated with the device may be accomplished by file system plugin 150-3 of FIG. 4 calling the plugin associated with the device, by file system plugin 150-3 of FIG. 4 returning the native request to the plugin associated with the device in response to a call from that plugin, or by file system plugin 150-3 returning the native request to framework 145 of FIG. 1 and asking framework 145 of FIG. 1 to forward the native request to the plugin associated with the device. Note that regardless of the manner in which the native request is passed to the plugin associated with the device, the result is as though the example flowchart of FIGS. 12A-12C was restarted but now using the native request rather than the file system request.

[0120] If the request received by framework 145 of FIG. 1 was not a file system request, then the request was already in a native format for the device. In that case, the native request may be delivered to the plugin associated with the device. As shown in FIG. 12C, block requests may be processed in block 1240, KV requests may be processed in block 1245, object requests (which may

be generalized versions of KV requests) may be processed in block **1250**, and custom requests may be processed in block **1255**. Regardless of the form actually taken by the native request, the appropriate plugin that may execute the native request may be identified by plugin selector **810**, and the request may be delivered to the appropriate module using that identified plugin.

[0121] FIG. **13** shows a flowchart of an example procedure for framework **145** of FIG. **1** to process service request **915-1** of FIG. **9** from the application of FIG. **1** using plugins **150** of FIG. **4**, according to embodiments of the disclosure. In FIG. **13**, at block **1305**, receiver **805** of FIG. **8** may receive service request **915-1** of FIG. **9** from application **405** of FIG. **4**. At block **1310**, plugin selector **810** of FIG. **8** may select plugin **150** of FIG. **1** to process service request **915-1** of FIG. **9**. At block **1315**, transmitter **815** of FIG. **8** may deliver service request **915-2** of FIG. **9** to plugin **150** of FIG. **1**. At block **1320**, receiver **805** of FIG. **8** may receive service response **920-1** of FIG. **9** from plugin **150** of FIG. **1**. Finally, at block **1325**, transmitter **815** of FIG. **8** may transmit service response **920-2** of FIG. **9** to application **405** of FIG. **4**.

[0122] FIGS. **14A-14B** show a flowchart of another example procedure for framework **145** of FIG. **1** to process service request **915-1** of FIG. **9** from the application of FIG. **1** using plugins **150** of FIG. **4**, according to embodiments of the disclosure. In FIG. **14A**, at block **1405**, receiver **805** of FIG. **8** may receive registration request **905** of FIG. **9** from the system administrator on machine **105** of FIG. **1**. At block **1410**, framework **145** of FIG. **1** may register plugin **150** of FIG. **1**.

[0123] At block **1305**, receiver **805** of FIG. **8** may receive service request **915-1** of FIG. **9** from application **405** of FIG. **4**. At block **1310**, plugin selector **810** of FIG. **8** may select plugin **150** of FIG. **1** to process service request **915-1** of FIG. **9**. At block **1315**, transmitter **815** of FIG. **8** may deliver service request **915-2** of FIG. **9** to plugin **150** of FIG. **1**. At block **1415**, plugin **150** of FIG. **1** may deliver service request **915-2** of FIG. **9** (after processing into a form acceptable to device driver **130** and/or the associated module (which may be, for example, storage device **120** of FIG. **1** and/or computational device **135** of FIG. **1**).

[0124] At block **1420** (FIG. **14B**), plugin **150** of FIG. **1** may receive the result of service request **915-2** of FIG. **9** as executed by the associated module. At block **1320**, receiver **805** of FIG. **8** may receive service response **920-1** of FIG. **9** from plugin **150** of FIG. **1**. At block **1325**, transmitter **815** of FIG. **8** may transmit service response **920-2** of FIG. **9** to application **405** of FIG. **4**. Processing may then optionally return to block **1305** of FIG. **14A** to process more service requests **915-1** of FIG. **9**.

[0125] At block **1425**, receiver **805** of FIG. **8** may receive deregistration request **925** of FIG. **9** from the system administrator on machine **105** of FIG. **1**. At block **1430**, framework **145** of FIG. **1** may deregister plugin **150** of FIG. **1**.

[0126] FIG. **15** shows a flowchart of an example procedure for framework **145** of FIG. **1** to identify plugin **150** of FIG. **1** as capable of processing service request **915-1** of FIG. **9** from the application of FIG. **4**, according to embodiments of the disclosure. At block **1505**, plugin selector **810** of FIG. **8** may select plugin **150** of FIG. **1** associated with the service requested in service request **915-1** of FIG. **9**. At block **1510**, plugin selector **810** of FIG. **8** may send query **1105** or **1115** of FIG. **11** to plugin **150** of FIG. **1**. At block **1515**, plugin **150** of FIG. **1** may decide whether to accept or reject the request. If plugin **150** of FIG. **1** rejects the request, then at block **1520** plugin selector **810** of FIG. **8** may receive negative response **1110** of FIG. **11** from plugin **150** of FIG. **1**, and processing may return to block **1505** to select another plugin **150** of FIG. **1** to query. If plugin **150** of FIG. **1** accepts the request, then at block **1525** plugin selector **810** of FIG. **8** may receive affirmative response **1120** of FIG. **11**, and plugin selector **810** of FIG. **8** may select plugin **150** of FIG. **1** to process service request **915-1** of FIG. **1**.

[0127] Note that blocks **1505-1520** might result in an endless loop, if no plugin **150** of FIG. **1** accepts query **1105** or **1115** of FIG. **11**. One solution to avoid this endless loop is for block **1505** to be modified so that plugin selector **805** of FIG. **8** selects plugins **150** of FIG. **1** that have not been selected before for query **1105** or **1115** of FIG. **11**. That is, if plugin **105** of FIG. **1** has previously

issued negative response **1110** of FIG. **11**, then plugin selector **805** of FIG. **8** may avoid selecting plugin **105** of FIG. **1** again for query **1105** or **1115** of FIG. **11**.

[0128] FIG. **16** shows a flowchart of another example procedure for framework **145** of FIG. **1** to identify plugin **150** of FIG. **1** as capable of processing service request **915-1** of FIG. **9** from the application of FIG. **4**, according to embodiments of the disclosure. In FIG. **16**, at block **1605**, plugin selector **810** of FIG. **8** may broadcast/multicast to all plugins **150** mapped from the requested service that service request **915-1** of FIG. **9** has been received. At block **1610**, plugin selector **810** of FIG. **8** may receive affirmative response **1120** of FIG. **11** from plugin **150** of FIG. **1**, at which point plugin **150** of FIG. **1** may be selected (and negative responses **1110** of FIG. **11** received from other plugins **150** of FIG. **1** may be ignored, since such plugins **150** of FIG. **1** might not accept service request **915-1** of FIG. **9**).

[0129] In FIGS. **12A-16**, some embodiments of the disclosure are shown. But a person skilled in the art will recognize that other embodiments of the disclosure are also possible, by changing the order of the blocks, by omitting blocks, or by including links not shown in the drawings. All such variations of the flowcharts are considered to be embodiments of the disclosure, whether expressly described or not.

[0130] Computational Storage (CS) devices, such as computational device **135** of FIG. **1**, may be derived from different offloads. For example, CS devices may include Field Programmable Gate Arrays (FPGAs), dedicated hardware Application-Specific Integrated Circuits (ASICs), embedded Central Processing units (CPUs) (which may implement Advanced Reduced Instruction Set Computing (RISC) Machines (ARM), RISC and its variations, and/or x86 architectures, among other possibilities), Graphics Processing Units (GPUs), etc. There may be different types of CS devices: despite using the term “storage”, not all CS devices may provide storage. For example, an FPGA in isolation may be a CS device but not include storage that may be directly used by an application. Some CS devices may include abstractions, such as a Berkeley Packet Filter (BPF) or containers. Such CS devices, even though lacking their own host-accessible storage, may interface with storage devices and filesystems to provide near storage compute benefits. CS devices may also be direct attached (for example, connected to the host processor via a bus such as a Peripheral Component Interconnect Express (PCIe) bus), or network attached via a fabric (such as Ethernet, Fibre Channel, InfiniBand, etc.).

[0131] These variations—CS devices with or without storage, with or without abstractions, directly attached or network attached—may introduce complexities that may impact how applications running on the host processor may access the CS devices.

[0132] Embodiments of the disclosure may define a plugin framework mechanism (which may be termed a framework, such as framework **145** of FIG. **1**) in the Application Programming Interface (API) library. The plugin framework may offer a layered architecture, may be transparent to the host, may seamlessly interface with the API library, and may define plugin interface methods and methods for interfacing between plugins, such as plugin **150** of FIG. **1**.

[0133] The plugin framework **145** of FIG. **1** may provide abstract mechanisms for transport (Non-Volatile Memory Express (NVMe), NVMe over Fabrics (NVMe-oF), or other fabric attached devices), computation resources (CPU, FPGA, ASIC, GPU, etc.), and storage (filesystem, block, object, etc.). The plugin framework may support featured offloads, such as BPF, io_uring, containers, etc. The plugin framework may also abstract kernel-space/user-space models and/or virtual devices.

[0134] CS technology may be applied to different classes of devices. While individual CS devices may have APIs that may provide a uniform and generic interface to the individual device, an underlying mechanism to support access to CS devices is beneficial. Plugins, such as plugin **150** of FIG. **1**, may be one such mechanism to help in these translations.

[0135] Embodiments of the disclosure may define a plugin framework mechanism, such as framework **145** of FIG. **1**, that interfaces with the API library. The plugin framework may provide

the ability to register/deregister plugins. The plugin framework may seamlessly interface with the API library/libraries. The plugin framework may be transparent to the host. The plugin framework may define plugin interface methods and methods for interfacing between plugins.

[0136] The plugin framework, such as framework **145** of FIG. **1**, may offer a layered architecture. Each layer may connect to other layers by interfaces. Each module/plugin may expose an interface to support use via the API and/or to support connections to other layers.

[0137] The plugin framework, such as framework **145** of FIG. **1**, may define mechanisms to abstract. These mechanisms may include transport, computation, and/or storage. These mechanisms may also include offloads, such as BPF, io_uring, containers, and others. These mechanisms may also abstract kernel-space/user-space models, and provide for a host plugin.

[0138] The plugin framework, such as framework **145** of FIG. **1**, may define abstracted usage model across CS device types, and may provide a catch-all solution to support device limitations.

[0139] Embodiments of the disclosure may use the plugin framework, such as framework **145** of FIG. **1**, to hide different transports through plugins. Some abstractions may be implicit: for example, direct PCIe, NVMe, and NVMe-oF, among others. Other abstractions may be explicit: for example, network fabrics such as Remote Direct Memory Access (RDMA), Transmission Control Protocol (TCP), Fibre Channel (FC), and InfiniBand (IB), among others. As a result, for example, an FPGA may be hidden behind a network through a network plugin.

[0140] The compute plugin, such as plugin **150** of FIG. **1**, may interface with a generic network or provide its own network.

[0141] This abstraction may provide a seamless experience to the user. The user does not have to worry about network attachment specifics. In establishing the abstractions, a hint may be provided during Discovery of the CS devices.

[0142] Embodiments of the disclosure may support plugins, such as plugin **150** of FIG. **1**, to handle different compute types. For example, FPGAs, NVMe CS devices, embedded CPUs, etc., may be accessed through different plugins.

[0143] The plugin framework, such as framework **145** of FIG. **1**, may help to abstract APIs over different device implementations through plugins. Device-specific handling may be hidden in the plugins.

[0144] One plugin may utilize other plugins for some work.

[0145] Embodiments of the disclosure may support plugins, such as plugin **150** of FIG. **1**, that may provide storage abstraction by handling I/O by file, block, key-value (KV), object, streams, etc. Since the plugins may hide the details, the plugin framework may be extensible to support other types of storage access, including custom file system services.

[0146] The plugin framework, such as framework **145** of FIG. **1**, may shuffle the request till a plugin accepts. The plugin framework may cache the acceptor as an optimization for later requests.

[0147] Plugins, such as plugin **150** of FIG. **1**, may handle host visible and opaque device memories. Plugins may provide translations from file to block (or between other storage access forms, as appropriate) when needed.

[0148] Embodiments of the disclosure may permit applications, such as application **405** of FIG. **4**, to write to CS APIs. Because the APIs may access the plugins, the plugin framework may provide a consistent user experience. The applications may avoid being modified when the underlying hardware changes. Similarly, the plugin framework may avoid exposing local and remote attach requirements.

[0149] Certain usages of the plugin framework, such as framework **145** of FIG. **1**, may expect applications to be portable, either across hardware or where there is no hardware. A software plugin may provide a device abstraction when hardware is absent, enabling portability.

[0150] Embodiments of the disclosure may permit specific compute features that may be abstracted through plugins, such as plugin **150** of FIG. **1**. For example, a plugin used to communicate with a particular CS device may hide feature-specific details from the main plugin. The plugin framework

may compensate for device limitations, and may serve as a catch-all for changing technology/definitions.

[0151] As an example, a BPF plugin may abstract following paths. The BPF plugin may download BPF programs, provide memory and map abstractions, and may support program execution and parameter setup. This configuration may enhance download options at API level: for example, by integrating BPF tools. This configuration may also enhance device implementation options.

[0152] Plugins, such as plugin **150** of FIG. **1**, may enable additional features and functionality. Plugins may register with the framework. They may describe their type and interface functions. They may expose methods callable by other plugins.

[0153] To support plugins, the CS APIs may include various functions, such as `csQueryLibrarySupport()`, `csQueryPlugin()`, `csRegisterPlugin()`, and `csDeregisterPlugin()`, as well as other functions (other names for these functions may be used without limitation).

[0154] The plugin framework, such as framework **145** of FIG. **1**, may provide a seamless interface between local & remote attached CS devices.

[0155] The plugin framework, such as framework **145** of FIG. **1**, may provide consistent interface when library/framework is used in different environments. For example, the plugin framework may support a user library frame with kernel drivers, a user library with user space drivers (SPDK), and/or a kernel library with kernel drivers. The plugin framework may include definitions to seamlessly abstract BPF technology (or other feature services) outside transport.

[0156] Embodiments of the disclosure offer technical advantages over the prior art. By using plugins and a framework, details associated with the actual hardware may be abstracted away from applications and the framework. Applications may issue Application Programming Interface (API) calls using a standardized structure. The framework may then identify a plugin to process the request based on the request service. The framework, like the application, does not have to know or understand which hardware may execute the request or even how to communicate with that hardware: the plugin may handle the mechanics of translating the API call and its associated data into a request that may be processed by the hardware.

[0157] The use of the framework and plugins may abstract away the type of hardware—embedded central processing unit (CPU), graphics processing unit (GPU), Field Programmable Gate Array (FPGA), Application-Specific Integrated Circuit (ASIC), etc.—that may execute the request, the transport used for communicating with the hardware, the fabric used to communicate with the hardware, whether the hardware is local or remote, the form a storage request—block, key-value, object, etc.—may take, the availability of particular features, the user space/kernel space model used by the operating system, and even the presence of virtual devices. In addition, a host level abstraction plugin may be available to implement, using a host processor, a software service that might be offered by hardware not currently available in the system.

[0158] The following discussion is intended to provide a brief, general description of a suitable machine or machines in which certain aspects of the disclosure may be implemented. The machine or machines may be controlled, at least in part, by input from conventional input devices, such as keyboards, mice, etc., as well as by directives received from another machine, interaction with a virtual reality (VR) environment, biometric feedback, or other input signal. As used herein, the term “machine” is intended to broadly encompass a single machine, a virtual machine, or a system of communicatively coupled machines, virtual machines, or devices operating together. Exemplary machines include computing devices such as personal computers, workstations, servers, portable computers, handheld devices, telephones, tablets, etc., as well as transportation devices, such as private or public transportation, e.g., automobiles, trains, cabs, etc.

[0159] The machine or machines may include embedded controllers, such as programmable or non-programmable logic devices or arrays, Application Specific Integrated Circuits (ASICs), embedded computers, smart cards, and the like. The machine or machines may utilize one or more connections to one or more remote machines, such as through a network interface, modem, or other

communicative coupling. Machines may be interconnected by way of a physical and/or logical network, such as an intranet, the Internet, local area networks, wide area networks, etc. One skilled in the art will appreciate that network communication may utilize various wired and/or wireless short range or long range carriers and protocols, including radio frequency (RF), satellite, microwave, Institute of Electrical and Electronics Engineers (IEEE) 802.11, Bluetooth®, optical, infrared, cable, laser, etc.

[0160] Embodiments of the present disclosure may be described by reference to or in conjunction with associated data including functions, procedures, data structures, application programs, etc. which when accessed by a machine results in the machine performing tasks or defining abstract data types or low-level hardware contexts. Associated data may be stored in, for example, the volatile and/or non-volatile memory, e.g., RAM, ROM, etc., or in other storage devices and their associated storage media, including hard-drives, floppy-disks, optical storage, tapes, flash memory, memory sticks, digital video disks, biological storage, etc. Associated data may be delivered over transmission environments, including the physical and/or logical network, in the form of packets, serial data, parallel data, propagated signals, etc., and may be used in a compressed or encrypted format. Associated data may be used in a distributed environment, and stored locally and/or remotely for machine access.

[0161] Embodiments of the disclosure may include a tangible, non-transitory machine-readable medium comprising instructions executable by one or more processors, the instructions comprising instructions to perform the elements of the disclosures as described herein.

[0162] The various operations of methods described above may be performed by any suitable means capable of performing the operations, such as various hardware and/or software component(s), circuits, and/or module(s). The software may comprise an ordered listing of executable instructions for implementing logical functions, and may be embodied in any “processor-readable medium” for use by or in connection with an instruction execution system, apparatus, or device, such as a single or multiple-core processor or processor-containing system.

[0163] The blocks or steps of a method or algorithm and functions described in connection with the embodiments disclosed herein may be embodied directly in hardware, in a software module executed by a processor, or in a combination of the two. If implemented in software, the functions may be stored on or transmitted over as one or more instructions or code on a tangible, non-transitory computer-readable medium. A software module may reside in Random Access Memory (RAM), flash memory, Read Only Memory (ROM), Electrically Programmable ROM (EPROM), Electrically Erasable Programmable ROM (EEPROM), registers, hard disk, a removable disk, a CD ROM, or any other form of storage medium known in the art.

[0164] Having described and illustrated the principles of the disclosure with reference to illustrated embodiments, it will be recognized that the illustrated embodiments may be modified in arrangement and detail without departing from such principles, and may be combined in any desired manner. And, although the foregoing discussion has focused on particular embodiments, other configurations are contemplated. In particular, even though expressions such as “according to an embodiment of the disclosure” or the like are used herein, these phrases are meant to generally reference embodiment possibilities, and are not intended to limit the disclosure to particular embodiment configurations. As used herein, these terms may reference the same or different embodiments that are combinable into other embodiments.

[0165] The foregoing illustrative embodiments are not to be construed as limiting the disclosure thereof. Although a few embodiments have been described, those skilled in the art will readily appreciate that many modifications are possible to those embodiments without materially departing from the novel teachings and advantages of the present disclosure. Accordingly, all such modifications are intended to be included within the scope of this disclosure as defined in the claims.

[0166] Embodiments of the disclosure may extend to the following statements, without limitation:

[0167] Statement 1. An embodiment of the disclosure includes a system, comprising: [0168] a processor; [0169] a storage device; [0170] a computational device; [0171] a plugin associated with a service on the computational device; and [0172] a framework implemented in software and configured to be executed on the processor, the framework including: [0173] a receiver to receive a service request from an application configured to be executed on the processor and a service response from the plugin, the service request identifying a service requested by the application; [0174] a plugin selector to select the plugin based at least in part on the service; and [0175] a transmitter to deliver the service request to the plugin and the service response to the application, [0176] wherein the application is agnostic to the plugin and the computational device.

[0177] Statement 2. An embodiment of the disclosure includes the system according to statement 1, wherein the plugin is configured to deliver the service request to the computational device and to receive the service response from the computational device.

[0178] Statement 3. An embodiment of the disclosure includes the system according to statement 1, wherein the application is agnostic to a transport protocol used to deliver the service request from the plugin to the computational device.

[0179] Statement 4. An embodiment of the disclosure includes the system according to statement 1, wherein the plugin represents a transport protocol used by the plugin to communicate with the computational device.

[0180] Statement 5. An embodiment of the disclosure includes the system according to statement 1, wherein the plugin represents a fabric used to communicate with the computational device.

[0181] Statement 6. An embodiment of the disclosure includes the system according to statement 1, wherein the plugin represents the hardware implementation of the computational device.

[0182] Statement 7. An embodiment of the disclosure includes the system according to statement 1, wherein the plugin represents a storage mechanism used by the computational device.

[0183] Statement 8. An embodiment of the disclosure includes the system according to statement 1, wherein the plugin supports a feature that complements a second plugin associated with the computational device.

[0184] Statement 9. An embodiment of the disclosure includes the system according to statement 1, wherein the plugin selector is configured to select the plugin from at least the plugin and a second plugin.

[0185] Statement 10. An embodiment of the disclosure includes the system according to statement 9, wherein the plugin selector is configured to select the plugin from at least the plugin and the second plugin based at least in part on the plugin and the second plugin being associated with the service.

[0186] Statement 11. An embodiment of the disclosure includes the system according to statement 9, wherein the plugin selector is configured to select the second plugin to process the service request, query the second plugin based at least in part on the service, receive a negative response from the second plugin, query the plugin to process the service request, and receive an affirmative response from the plugin.

[0187] Statement 12. An embodiment of the disclosure includes the system according to statement 1, wherein the plugin selector is configured to broadcast the service request to the plugin and the second plugin and receiving an affirmative response from the plugin.

[0188] Statement 13. An embodiment of the disclosure includes the system according to statement 1, wherein the framework is configured to register the plugin based at least in part on the receive receiving a registration request for the plugin.

[0189] Statement 14. An embodiment of the disclosure includes the system according to statement 13, wherein the framework is further configured to deregister the plugin based at least in part on the receive receiving a deregistration request for the plugin.

[0190] Statement 15. An embodiment of the disclosure includes a method, comprising: [0191] receiving a service request from an application running on a host at a framework on the host, the

service request identifying a service requested by the application; [0192] identifying a plugin to process the service request, the plugin associated with the service on a computational device, the computational device associated with a storage device; [0193] delivering the service request from the framework to the plugin; [0194] receiving a service response from the plugin at the framework; and [0195] delivering the service response from the framework to the application, [0196] wherein the application is agnostic to the plugin and the computation storage unit.

[0197] Statement 16. An embodiment of the disclosure includes the method according to statement 15, further comprising: [0198] delivering the service request from the plugin to the computational device; and [0199] receiving the service response from the computational device at the plugin.

[0200] Statement 17. An embodiment of the disclosure includes the method according to statement 15, wherein the application is agnostic to a transport protocol used to deliver the service request from the plugin to the computational device.

[0201] Statement 18. An embodiment of the disclosure includes the method according to statement 15, wherein the plugin represents a transport protocol used by the plugin to communicate with the computational device.

[0202] Statement 19. An embodiment of the disclosure includes the method according to statement 15, wherein the plugin represents a fabric used to communicate with the computational device.

[0203] Statement 20. An embodiment of the disclosure includes the method according to statement 15, wherein the plugin represents the hardware implementation of the computational device.

[0204] Statement 21. An embodiment of the disclosure includes the method according to statement 15, wherein the plugin represents a storage mechanism used by the computational device.

[0205] Statement 22. An embodiment of the disclosure includes the method according to statement 15, wherein the plugin supports feature that complements a second plugin associated with the computational device.

[0206] Statement 23. An embodiment of the disclosure includes the method according to statement 15, wherein identifying the plugin to process the service request includes selecting the plugin from at least the plugin and a second plugin.

[0207] Statement 24. An embodiment of the disclosure includes the method according to statement 23, wherein selecting the plugin from at least the plugin and the second plugin includes selecting the plugin from at least the plugin and the second plugin based at least in part on the plugin and the second plugin being associated with the service.

[0208] Statement 25. An embodiment of the disclosure includes the method according to statement 23, wherein selecting the plugin from at least the plugin and the second plugin includes: [0209] selecting the second plugin to process the service request; [0210] querying the second plugin based at least in part on the service; [0211] receiving a negative response from the second plugin; [0212] querying the plugin to process the service request; and [0213] receiving an affirmative response from the plugin.

[0214] Statement 26. An embodiment of the disclosure includes the method according to statement 15, wherein selecting the plugin from at least the plugin and the second plugin includes: [0215] broadcasting the service request to the plugin and the second plugin; and [0216] receiving an affirmative response from the plugin.

[0217] Statement 27. An embodiment of the disclosure includes the method according to statement 15, further comprising: [0218] receiving at the framework on the host a registration request for the plugin; [0219] registering the plugin with the framework on the host.

[0220] Statement 28. An embodiment of the disclosure includes the method according to statement 27, further comprising: [0221] receiving at the framework on the host a deregistration request for the plugin; and [0222] deregistering the plugin with the framework on the host.

[0223] Statement 29. An embodiment of the disclosure includes an article, comprising a non-transitory storage medium, the non-transitory storage medium having stored thereon instructions that, when executed by a machine, result in: [0224] receiving a service request from an application

running on a host at a framework on the host, the service request identifying a service requested by the application; [0225] identifying a plugin to process the service request, the plugin associated with the service on a computational device, the computational device associated with a storage device; [0226] delivering the service request from the framework to the plugin; [0227] receiving a service response from the plugin at the framework; and [0228] delivering the service response from the framework to the application, [0229] wherein the application is agnostic to the plugin and the computation storage unit.

[0230] Statement 30. An embodiment of the disclosure includes the article according to statement 29, the non-transitory storage medium having stored thereon further instructions that, when executed by the machine, result in: [0231] delivering the service request from the plugin to the computational device; and [0232] receiving the service response from the computational device at the plugin.

[0233] Statement 31. An embodiment of the disclosure includes the article according to statement 29, wherein the application is agnostic to a transport protocol used to deliver the service request from the plugin to the computational device.

[0234] Statement 32. An embodiment of the disclosure includes the article according to statement 29, wherein the plugin represents a transport protocol used by the plugin to communicate with the computational device.

[0235] Statement 33. An embodiment of the disclosure includes the article according to statement 29, wherein the plugin represents a fabric used to communicate with the computational device.

[0236] Statement 34. An embodiment of the disclosure includes the article according to statement 29, wherein the plugin represents the hardware implementation of the computational device.

[0237] Statement 35. An embodiment of the disclosure includes the article according to statement 29, wherein the plugin represents a storage mechanism used by the computational device.

[0238] Statement 36. An embodiment of the disclosure includes the article according to statement 29, wherein the plugin supports feature that complements a second plugin associated with the computational device.

[0239] Statement 37. An embodiment of the disclosure includes the article according to statement 29, wherein identifying the plugin to process the service request includes selecting the plugin from at least the plugin and a second plugin.

[0240] Statement 38. An embodiment of the disclosure includes the article according to statement 37, wherein selecting the plugin from at least the plugin and the second plugin includes selecting the plugin from at least the plugin and the second plugin based at least in part on the plugin and the second plugin being associated with the service.

[0241] Statement 39. An embodiment of the disclosure includes the article according to statement 37, wherein selecting the plugin from at least the plugin and the second plugin includes: [0242] selecting the second plugin to process the service request; [0243] querying the second plugin based at least in part on the service; [0244] receiving a negative response from the second plugin; [0245] querying the plugin to process the service request; and [0246] receiving an affirmative response from the plugin.

[0247] Statement 40. An embodiment of the disclosure includes the article according to statement 29, wherein selecting the plugin from at least the plugin and the second plugin includes: [0248] broadcasting the service request to the plugin and the second plugin; and [0249] receiving an affirmative response from the plugin.

[0250] Statement 41. An embodiment of the disclosure includes the article according to statement 29, the non-transitory storage medium having stored thereon further instructions that, when executed by the machine, result in: [0251] receiving at the framework on the host a registration request for the plugin; [0252] registering the plugin with the framework on the host.

[0253] Statement 42. An embodiment of the disclosure includes the article according to statement 41, the non-transitory storage medium having stored thereon further instructions that, when

executed by the machine, result in: [0254] receiving at the framework on the host a deregistration request for the plugin; and [0255] deregistering the plugin with the framework on the host. [0256] Consequently, in view of the wide variety of permutations to the embodiments described herein, this detailed description and accompanying material is intended to be illustrative only, and should not be taken as limiting the scope of the disclosure. What is claimed as the disclosure, therefore, is all such modifications as may come within the scope and spirit of the following claims and equivalents thereto.

Claims

1. A system, comprising: a processor; a storage device; a computational device including a first service and a second service; an operation associated with the first service on the computational device; and an interface implemented in software and configured to be executed on the processor, the interface including: a receiver to receive a service request from an application configured to be executed on the processor and a service response from the operation, the service request identifying the first service requested by the application; a plugin selector to select the operation based at least in part on the first service; and a transmitter to deliver the service request to the operation and to deliver the service response to the application.
2. The system according to claim 1, wherein the operation includes a compute-based operation.
3. The system according to claim 1, wherein the operation represents at least one of a transport protocol used by the operation to communicate with the computational device, a fabric used to communicate with the computational device, a hardware implementation of the computational device, or a storage mechanism used by the computational device.
4. The system according to claim 1, wherein the operation supports a feature that complements a second operation associated with the computational device, wherein a first of the operation and a second operation calls a second of the operation and the second operation.
5. The system according to claim 1, wherein the selector is configured to select the operation from at least the operation and a second operation.
6. The system according to claim 1, wherein the first service on the computational storage unit processes a first data stored on the storage device to generate a second data, the second data different from the first data.
7. The system according to claim 1, wherein the service response is generated based at least in part on the computational device executing the first service.
8. A method, comprising: receiving a service request from an application running on a host at an interface on the host, the service request identifying a first service requested by the application; identifying an operation to process the service request, the operation associated with the first service on a computational device, the computational device associated with a storage device, the computational device offering a second service; delivering the service request from the interface to the operation; receiving a service response from the operation at the interface based at least in part on the computational device executing the first service; and delivering the service response from the interface to the application.
9. The method according to claim 8, wherein the operation includes a compute-based operation.
10. The method according to claim 8, wherein identifying the operation to process the service request includes selecting the operation from at least the operation and a second operation.
11. The method according to claim 10, wherein selecting the operation from at least the operation and the second operation includes selecting the operation from at least the operation and the second operation based at least in part on the operation and the second operation being associated with the first service.
12. The method according to claim 10, wherein selecting the operation from at least the operation and the second operation includes: querying the second operation to process the service request;

receiving a negative response from the second operation; querying the operation to process the service request; and receiving an affirmative response from the operation.

13. The method according to claim 8, further comprising: receiving at the interface on the host a registration request for the operation; registering the operation with the interface on the host.

14. The method according to claim 13, further comprising: receiving at the interface on the host a deregistration request for the operation; and deregistering the operation with the interface on the host.

15. The method according to claim 8, wherein the service response is generated based at least in part on the computational device executing the first service.

16. An article, comprising a non-transitory storage medium, the non-transitory storage medium having stored thereon instructions that, when executed by a machine, result in: receiving a service request from an application running on a host at an interface on the host, the service request identifying a first service requested by the application; identifying an operation to process the service request, the operation associated with the first service on a computational device, the computational device associated with a storage device, the computational device offering a second service; delivering the service request from the interface to the operation; receiving a service response from the operation at the interface based at least in part on the computational device executing the first service; and delivering the service response from the interface to the application.

17. The article according to claim 16, wherein the operation includes a compute-based operation.

18. The article according to claim 16, wherein identifying the operation to process the service request includes selecting the operation from at least the operation and a second operation.

19. The article according to claim 18, wherein selecting the operation from at least the operation and the second operation includes selecting the operation from at least the operation and the second operation based at least in part on the operation and the second operation being associated with the first service.

20. The article according to claim 18, wherein selecting the operation from at least the operation and the second operation includes: querying the second operation to process the service request; receiving a negative response from the second operation; querying the operation to process the service request; and receiving an affirmative response from the operation.
