

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250259152

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Bowles; Mark Vincent

SECONDARY MARKET AND VENDING SYSTEM FOR DEVICES

Abstract

A recycling kiosk for recycling and financial remuneration for submission of a mobile telephone is disclosed herein. The recycling kiosk includes an inspection area with at least one camera and a plurality of electrical connectors in order to perform a visual analysis and an electrical analysis of the mobile telephone for determination of a value of the mobile telephone. The recycling kiosk also includes a processor, a display and a user interface.

Inventors: Bowles; Mark Vincent (San Diego, CA)

Applicant: ecoATM, LLC (San Diego, CA)

Family ID: 42286074

Assignee: ecoATM, LLC (San Diego, CA)

Appl. No.: 18/926173

Filed: October 24, 2024

Related U.S. Application Data

parent US continuation 18462213 20230906 parent-grant-document US 12182773 child US 18926173

parent US continuation 17394255 20210804 parent-grant-document US 11790328 child US 18462213

parent US continuation 15901526 20180221 parent-grant-document US 11107046 child US 17394255

parent US continuation 13862395 20130413 parent-grant-document US 9904911 child US 15901526

parent US continuation 13562292 20120730 parent-grant-document US 8423404 child US 13862395

parent US continuation 13017560 20110131 parent-grant-document US 8239262 child US 13562292

parent US continuation 12727624 20100319 parent-grant-document US 7881965 child US
13017560
parent US continuation-in-part 12573089 20091002 parent-grant-document US 8195511 child US
12727624
us-provisional-application US 61102304 20081002
us-provisional-application US 61183510 20090602

Publication Classification

Int. Cl.: **G06Q10/30** (20230101); **G06Q30/02** (20230101); **G06Q30/0207** (20230101); **G07F7/06** (20060101); **H04M1/02** (20060101)

U.S. Cl.:

CPC **G06Q10/30** (20130101); **G06Q30/0237** (20130101); **G06Q30/0278** (20130101);
G07F7/06 (20130101); **H04M1/0287** (20130101); Y02W30/82 (20150501); Y02W90/00
(20150501)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) [0001] This application is a continuation of U.S. patent application Ser. No. 18/462,213 filed Sep. 6, 2023, which is a continuation of U.S. patent application Ser. No. 17/394,255 filed Aug. 4, 2021, now U.S. Pat. No. 11,790,328, which is a continuation of U.S. patent application Ser. No. 15/901,526 filed Feb. 21, 2018, now U.S. Pat. No. 11,701,046, which is a continuation of U.S. patent application Ser. No. 13/862,395, filed Apr. 13, 2013, now U.S. Pat. No. 9,904,911, which is a continuation of U.S. patent application Ser. No. 13/562,292, filed Jul. 30, 2012, now U.S. Pat. No. 8,423,404, which is a continuation of U.S. patent application Ser. No. 13/017,560, filed Jan. 31, 2011, now U.S. Pat. No. 8,239,262, which is a continuation of U.S. patent application Ser. No. 12/727,624, filed Mar. 19, 2010, now U.S. Pat. No. 7,881,965, which is a continuation-in-part of United States U.S. patent application Ser. No. 12/573,089, filed Oct. 2, 2009, now U.S. Pat. No. 8,195,511, which claims priority to and the benefit of U.S. Provisional Patent Application No. 61/102,304, filed Oct. 2, 2008, and U.S. Provisional Patent Application No. 61/183,510, filed Jun. 2, 2009, each of which is incorporated herein by referenced in its entirety.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH

[0002] Not Applicable

TECHNICAL FIELD

[0003] The present invention generally relates to recycling of mobile phones. More specifically, the present invention relates to a kiosk for analyzing mobile phones and providing remuneration to an owner for recycling of the mobile phone.

BACKGROUND

[0004] There has been a large increase in the number of electronic devices used by the typical consumer. These devices include cell phones, PDA's, mp3 players, GPS devices, cameras, beepers, remote controls, cordless phones, calculators, etc. The rapid pace at which new technology and models of electronic devices are introduced creates a situation where many consumers upgrade or replace one or more recyclable device on a frequent basis. Often, the consumer does not dispose of the prior electronic device, but rather just stops using it and begins using the new device. This may happen over several generations of such devices.

[0005] In addition to the electronic devices mentioned above, there are many other types of devices that have relatively high frequency replacement rates, including portable mobile electronic devices, such as cell phones, MP3 players, etc., and non-portable electronic devices, such as computers, printers, and the like. In addition to electronic devices, there are content based digital media such as games on CD, DVD, or cartridge, or entertainment mass storage items such as CDs, DVDs, BluRay, etc. There is a need for handling of such items in an ecologically friendly manner, both via recycling or by proper disposal procedures. It has not been convenient for owners of electronic devices to either recycle such devices or to properly dispose of such devices. There is currently little incentive for a device owner to “do the right thing” with a used device. When the owner just stops using a device and simply puts it in storage: the opportunity for recycling or re-use by another party is lost. If the owner just throws the device away in normal trash containers, the proper recycling or safe disposing of the device is thwarted.

[0006] One particular problem associated with this phenomenon can be illustrated by an example of mobile phones. There are more than 3.6 billion mobile phone users in the world with an annual growth of 10% per annum. The replacement rate of mobile handsets is roughly every 18 months as new models have more features and new standards evolve. Wireless carriers also offer new phones below cost, or free, as incentives to get customers to sign lucrative two-year service contracts ensuring a constant build-up of old mobile phones. Old mobile phones and other mobile devices (pagers, PDAs) present a growing threat to the environment. As of 2007, there are more than 750 million mobile phones waiting to be recycled in the US, either in drawers or already in the waste stream. Another 150+ million or so are added every year. Once in the waste stream, these devices may leak Lead, Mercury, Cadmium, Arsenic and other toxic substances into the water supply. Municipalities often incinerate their waste, instantly putting these toxic elements into the air, and they return to earth in rain water. A problem that needs to be solved is to make it easy and accessible for the public to recycle or resell their mobile phones and other recyclable devices. Two reasons why mobile phones are not being recycled or resold are difficult access to recycling or reselling facilities, and secondly security concerns about the information stored on the mobile phone. In addition to mobile phones, the same problems apply to many other electronic devices.

[0007] Technology has not yet provided a resolution to this problem. One invention is Bishop, U.S. Pat. No. 4,951,308 for Automated Vending Of Cellular Hand-Held Telephones And Cellular Telephone Services, which discloses a vending machine that dispenses cellular telephones purchased by consumers through the vending machine. Bishop essentially adds to the problem by making it easier to acquire mobile phones.

[0008] Taylor et al., U.S. Patent Publication Number 2009/0190142, for a Method And System For Connecting A Data Storage Device To A Kiosk, discloses a kiosk with a docking port and an optical recognition device for identifying a data port on a data storage device. Taylor is directed at printing digital images at a photo kiosk.

[0009] The prior art has failed to recognize the problems associated with recycling mobile phones in a manner that is enticing to a consumer yet financially rewarding to the recycler.

SUMMARY

[0010] The present invention enables one to securely recycle, donate, trade-in, and/or sell mobile phones in a publicly accessible location. In an embodiment where mobile phones are recycled, the invention is used by a mobile phone owner to submit his/her mobile phone for recycling via a recycling kiosk and receive compensation in some manner. The compensation might be dispersed via cash, voucher, credit or debit card, or other magnetic or electronic transaction methods.

[0011] In one embodiment, a method for conducting the collection of previously used mobile phones for the purpose of recycling and refurbishing uses a kiosk in a publicly accessible location. The kiosk displays one or more transaction options. The method further includes interaction between the user and the kiosk display options which may include powering the mobile phone, testing and optical scanning, erasing of the stored data in the mobile phone, determination and

acceptance by consumer of compensation for the mobile phone's value. The method may further include selection by consumers through interaction with the kiosk a variety of compensation methods including dispensing of cash, or redeemable voucher via coupon, or credit card debiting or crediting, electronic donation to user specified charity or charities, or other electronic payment methods.

[0012] One aspect of the present invention is a kiosk for analysis of a mobile phone and financial remuneration to a user for submission of the mobile phone. The kiosk includes a housing, a user interface, at least one camera, a plurality of electrical connectors, an electrical connector dispensing device and a processor. The housing has an inspection area for placement of a mobile phone therein. The user interface is positioned on an exterior surface of the housing for a user to input information. The at least one camera is focused on a field of view within the inspection area of the housing. The at least one camera is capable of acquiring an image of a portion of a mobile phone placed within the inspection area including at least an image of a display screen of the mobile phone. At least one electrical connector of the plurality of electrical connectors is capable of connecting to the mobile phone placed within the inspection area. The electrical connector dispensing device dispenses one electrical connector of the plurality of electrical connectors to the inspection area. The processor is positioned within the housing and is in communication with the at least one camera, each of the plurality of electrical connectors and the user interface. The processor is configured to identify the brand and model number of the mobile phone based on at least one of the information from the user and the images from the at least one camera. The processor is configured to determine the at least one electrical connector to dispense to the inspection area. The processor is configured to perform a visual analysis of the display of the mobile phone. The processor is configured to perform an electrical analysis of the mobile phone. The processor is configured to determine a financial remuneration value for the mobile phone.

[0013] Another aspect of the present invention is a method for analysis of a mobile phone and financial remuneration to a user for submission of the mobile phone. The method includes placing a mobile phone in an inspection area of a recycling kiosk. The method also includes acquiring an image of a portion of the mobile phone placed within the inspection area including at least an image of a display of the mobile phone. The method also includes identifying the model and make of the mobile phone. The method also includes determining an electrical connector that connects with a data port of the mobile phone. The method also includes performing an electrical analysis of the mobile phone using the electrical connector connected to the mobile phone to determine if the mobile phone is capable of activation, if a display of the mobile phone is not defective, and if the mobile phone can operate as intended. The method also includes determining a financial remuneration value for the mobile phone.

[0014] Having briefly described the present invention, the above and further objects, features and advantages thereof will be recognized by those skilled in the pertinent art from the following detailed description of the invention when taken in conjunction with the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0015] FIG. 1 is a perspective diagram of an embodiment of a recycling kiosk.

[0016] FIG. 2 is a diagram illustrating a system of a network of recycling kiosks.

[0017] FIG. 3 is a flow diagram of an operation of recycling a mobile phone using a recycling kiosk.

[0018] FIG. 4 is a flow diagram of an operation of recycling a mobile phone using a recycling kiosk.

[0019] FIG. 5A is an image on a display screen of a recycling kiosk.

[0020] FIG. 5B is an image on a display screen of a recycling kiosk.
[0021] FIG. 5C is an image on a display screen of a recycling kiosk.
[0022] FIG. 5D is an image on a display screen of a recycling kiosk.
[0023] FIG. 5E is an image on a display screen of a recycling kiosk.
[0024] FIG. 6 illustrates an embodiment of the inspection area of a recycling kiosk.
[0025] FIG. 6A is an isolated view of an inspection area of a recycling kiosk with a mobile phone positioned within a field of view of a camera for visual inspection.
[0026] FIG. 7 illustrates an internal back of a recycling kiosk.
[0027] FIG. 8 is an isolated view of an inspection area of a recycling kiosk.
[0028] FIG. 8A is an isolated view of an electrical connector dispenser with multiple electrical connectors.
[0029] FIG. 8B is an isolated view of an inspection area of a recycling kiosk with a mobile phone connected to an electrical connector.
[0030] FIG. 9 is a block diagram of the components of a recycling kiosk.

DETAILED DESCRIPTION

[0031] The invention provides a path for consumers and others to sell, recycle, or donate their recyclable electronic devices in a one-stop environment. One aspect of the invention is a single kiosk for recycling a mobile phone. Such mobile phones can preferably be portioned into three basic shapes: 1) a flip phone or clam shell type such as the MOTOROLA RAZR; 2) a slider phone which exposes a keyboard or screen such as the MOTOROLA DROID; and 3) a bar shape phone such as the Apple iPHONE or the Research in Motion BLACKBERRY. Another aspect of the invention is a system preferably including a network of kiosks in public spaces that perform a combination of recycling processing steps that receive, identify, visually inspect, electrically test, electrically erase, grade quality, containerize (bag), label, and inventory recyclable electronic devices. Each kiosk determines some form of compensation to an owner of the device. This compensation is preferably in the form of a direct payment, a credit on an account, a donation to a charity, a discount coupon for future purchases, or some similar form of compensation. The device owner has the choice to accept the offered compensation or reverse the transaction and retrieve the device.

[0032] In the following description, an example is given with respect to mobile phones. However, those skilled in the pertinent art will recognize that the system can be implemented with any number of other devices or items, including other recyclable devices, without departing from the spirit and scope of the system. The system applies to, among others, any pre-owned electronic device or other consumer electronic and electric devices.

[0033] FIG. 1 illustrates a partially schematic front isometric view of a recycling kiosk **100** for analyzing a mobile phone and financial remuneration to a user for submission of the mobile phone. The kiosk **100** is of a typical size and shape of a vending machine, such as a soda machine, coin changing machine, can recycling machine, or other vending machines.

[0034] The kiosk **100** has a housing **105** to protect the internal components of the kiosk **100** and to secure mobile phones submitted for recycling. The housing **105** is preferably constructed of a metal material, such as steel or aluminum, to prevent authorized access to the kiosk **100**.

[0035] The recycling kiosk **100** preferably includes a sealable mobile phone inspection area **106**, bill and voucher acceptor/dispenser **107**, card reader and receipt dispenser **104**, mobile phone collector for mobile phones to be refurbished **112**, mobile phone collection receptacle **108** (quick drop) for mobile phones to be recycled and computing and communications facility (not shown).

[0036] The inspection area **106** is preferably designed to permit a detailed visual inspection of a mobile phone and a detailed electrical inspection of a mobile phone. The size of the inspection area **106** is preferably 30 centimeters ("cm") in length, by 30 cm in width and 20 cm in height.

However, those skilled in the pertinent art will recognize that the dimensions of the inspection area **106** can vary without departing from the scope and spirit of the present invention.

[0037] The couplings from the kiosk **100** and to a remote computer are preferably a single coupling to a communications network such as the internet via wired LAN, wireless LAN, cellular or any other proprietary communications system. The Kiosk **100** preferably includes a processor **160** for processing the information obtained from the mobile phone and for controlling the components of the kiosk **100**. Preferably, the processor **160** is a standard personal computer (“PC”) or other type of embedded computer running any operating system such as Linux or MAC OS. The processor **160** is most preferably a small form factor PC with integrated hard disk drive (“HDD”), central processing unit (“CPU”) and universal serial bus (“USB”) ports to communicate with the other components of the kiosk **100**. One most preferred CPU is a DELL PC OPTIPLEX **780**.

Alternatively, the processing means is a microprocessor with a standalone motherboard which interfaces to a discrete HDD, power supply and the other components of the kiosk **100**. The kiosk **100** preferably includes a memory **161** or other storage device, such as a disk drive, that stores the executable applications, test software, databases and other software required to operate the recycling kiosk **100**.

[0038] The external communication component for the kiosk **100** preferably includes a wired Ethernet to provide connection to the internet, or alternatively the external communication component includes a wireless modem such as GSM, CDMA, 3G and 4G technologies for data communications.

[0039] The kiosk **100** preferably also includes a bar code reader **125**, bag/package dispenser **120**, fingerprint reader **128**, and digital signature pad **130**. Referring to FIG. **6**, the inspection area **106** preferably includes one or more cameras **601-604**, and optionally includes magnification tools (i.e., magnifying glass), bar code scanners, weight scales, heat detectors, UV reader/detector, and the like.

[0040] As shown in FIG. **8**, a mobile phone **150** is placed within a fixture assembly **142** that is preferably movable on tracks **143** within the inspection area **106**. Also shown is an electrical connector dispenser **140** with an electrical connector **141** for insertion into a data port of the mobile phone **150** to conduct an electrical analysis of the mobile phone. The tracks **143** allow for a data port **151** of the mobile phone to be positioned for connection to the electrical connector **141**.

[0041] The visual inspection of a mobile phone **150** in the inspection area **106** is preferably performed by at least one camera **601**. Alternatively, the visual inspection is performed by multiple cameras **601-604** as shown in FIG. **6**. A preferred camera **601** is a 1 megapixel machine vision camera. If a single camera **601**, as shown in FIG. **6A**, is utilized in the inspection area **106**, the camera **601** preferably is movable to increase a field of view **625** of the inspection area **106** to inspect the mobile phone fixed in the fixture assembly **142**. The camera **161** is preferably movable along an arc-like track along a ceiling of the inspection area **106**. Preferably the camera **601** is movable to inspect a data port **151** of the mobile phone **150** to determine the type of electrical connector **141** for the mobile phone **150**. Alternatively, mirrors are positioned in the inspection area **106** to permit a greater visual inspection of a mobile phone **150** as the mobile phone **150** is fixed in the fixture assembly **142**.

[0042] The fixture assembly **142** optionally operates as a weight scale to obtain a mass of the mobile phone **150** for use in determining a remuneration value for the mobile phone **150**. For example, if the mass of the mobile phone **150** is less than set forth in a vendor specification for the mobile phone **150**, then one or more components of the mobile phone **150** may be missing, such as the battery for the mobile phone **150**.

[0043] Preferably, visual inspection and recognition software is utilized by the kiosk **100** to analyze a mobile phone **150**. In one preferred method, a recognition algorithm is applied to a specific make and model of a mobile phone **150**. The visual inspection and recognition software determines the borders of a mobile phone **150** under inspection to determine the external dimensions of the mobile phone **150**. The external dimensions are utilized to determine a subset of possible mobile phones from a master database of mobile phones stored in the memory **161** of the kiosk **100** or available

online to the kiosk **100** using external communications. The visual inspection and recognition software then preferably uses a set of secondary and tertiary features to further distinguish the mobile phone **150**. These secondary and tertiary features can include placement and size of the display screen, placements and size of the keyboard, unique buttons, placement of ports, and other distinguishing features. Once an exact make and model of the mobile phone is determined, the visual inspection and recognition software subtracts an image of the mobile phone **150** from an image of a perfect mobile phone for the same make and model. The result of the subtraction is preferably a quantifiable number of pixels that are calibrated into categories of broken or missing parts, cracked screen, and low, medium or high wear.

[0044] Alternatively, the visual inspection is performed using neural network pattern recognition techniques to identify the mobile phone **150**, then filter algorithms are utilized to determine defects such as cracked screens. Further, those skilled in the pertinent art will recognize that other visual inspection techniques may be employed without departing from the scope and spirit of the present invention.

[0045] Further, visual inspection optionally includes obtaining a heat signature for the mobile phone **150**. One preferred method of obtaining a heat signature of a mobile phone **150** is to raster a laser across the mobile phone to characterize a heat decay profile of the submitted mobile phone **150**. This heat decay profile is then compared to a heat decay profile for a perfect sample of the same mobile phone **150**. The heat decay profile indicates the wear of the external surface of the mobile phone **150**, which is used in calculating the financial remuneration for the mobile phone **150**.

[0046] The electrical analysis of a mobile phone **150** is preferably performed using an electrical connector **141** connected to a data port of a mobile phone **150**. Typically, a single port is used to charge a mobile phone **150** and transfer data to and from a mobile phone **150**. As shown in FIG. **8A**, the kiosk **100** preferably has an electrical connector dispenser **140** that includes a plurality of electrical connectors **141a-141h** since there currently is no single universal electrical connector for all mobile phones. Once the make and model of the mobile phone **150** is determined, either by visual inspection or user input using a user interface **118** as discussed below, the correct electrical connector **141** is dispensed by the electrical connector dispenser **140** for connection to the data port of the mobile phone **150**. The connection of the electrical connector **141** to the mobile phone **150** is preferably performed automatically by the kiosk **100**. Alternatively, the proper choice of electrical connector **141** is illuminated or in some other way presented to the consumer for manual connection of the electrical connector **141** to the data port of the mobile phone **150**. An electrical connector **141** connected to a data port **151** of a mobile phone **150** is shown in FIG. **8B**. Electrical analysis software is preferably utilized by the kiosk **100** to interact with the mobile phone **150**. The electrical analysis preferably determines if the mobile phone is capable of activation, maintaining a charge, performing correctly, powering a display screen of the mobile phone **150**, providing make, model, serial number and other pertinent information about the mobile phone **150**, and other relevant information.

[0047] One method for determining a value of a mobile phone is an eight grade scale based on power up of the mobile phone **150**, the liquid crystal display ("LCD") and the mechanical condition of the mobile phone **150**. The grading is based on a yes/no response for the mobile phone **150**. Table One is an example of such a grading table.

TABLE-US-00001 TABLE ONE GRADE POWER UP LCD MECHANICAL A Y Y Y B N Y Y C Y N Y D N N Y E Y Y N F N Y N G Y N N H N N N

[0048] The recycling kiosk **100** preferably further includes a user interface device, such as a touch screen display **118** projected on a display screen **119** of the kiosk **100**. The touch screen display **118** preferably includes a keypad, user selection buttons **115A-115D**, soft keys, and other similar components. The touch screen display **118** is used to enable quick and easy access to various features and functions of the recycling kiosk **100**. The display screen **119** displays information in

color, monochrome, or "gray-scale." and is used to display elements of a user interface, advertisements, or other information. The recycling kiosk **100** preferably dispenses various forms of payment, including cash, credit cards, debit cards, chip cards, gift cards from the kiosk's host location or other gift cards, and other magnetic striped cards or electronic payment methods. In one embodiment of a user interface device of the recycling kiosk **100**, a telephone handset is included (not shown) to enable a customer to communicate with advertisers, providers of products advertised on the recycling kiosk, and to access assistance in using the recycling kiosk **100**. In other embodiments, a microphone/speaker arrangement is used for a similar purpose. The recycling kiosk **100** also includes a digital camera to record the image of the user for purposes of complying with the Second Hand Dealer Laws of various States. The kiosk **100** also preferably includes a supply of sealable plastic bags in a bag dispenser area **120** that have pre-printed barcode labels affixed thereto. The kiosk **100** also includes a bar code reader **125** to scan the bar code and associate it with a phone that is being transacted at the kiosk **100**. The bar code reader and/or ultraviolet ("UV") detector is used to scan an identifying bar code or other form of encoded information to identify the product model or product number. The kiosk **100** also uses the barcode reader to read the barcode identification on the inside of the battery pack. The UV detector is used for reading "invisible" barcodes in use by certain vendors such as Apple and others. The bar code reader, camera, and/or UV detector of the kiosk **100** is another technique used to identify the product model, IMEI #, and/or FCC ID. Alternatively, the kiosk **100** communicates with the mobile phone **150** using BLUETOOTH or WiFi communications to test and if necessary erase data from the mobile phone **150**.

[0049] FIG. **9** is a block diagram of the main components of the kiosk **100**. A processor **160** is preferably in communication with the other components of the kiosk **100**. The memory **161** preferably contains a database of information on multiple mobile phones including images, physical characteristics, prices and other similar information. The external communications **167** preferably communicates through a wireless connection or Ethernet with a network to receive and transmit information to a remote site. The power supply **170** is preferably received through a plug-in connection to a wall outlet. The mechanical components **165** include the electrical connector dispenser **140**, the bag/package dispenser **120**, the fixture assembly **142**, and other similar components. The camera **161** or cameras, electrical connectors **141** and user interface **118** interact with the processor **160** as discussed above. FIG. **7** illustrates an internal back of a recycling kiosk **100**. As shown a processor **160** is preferably a personal computer having a battery backup **170a**, a wireless connection **167** for external communications, an electrical connector **140**, receipt dispenser **104** and a display screen **119**.

[0050] The processor **160** identifies the mobile phone **150** submitted for recycling using information from the visual inspection and user interface. The processor **160** also determines the proper electrical connector **141** for connection to the data port **151** of the mobile phone **150** using information obtained during the visual inspection or from the user interface. The processor **160** also directs and receives information from the electrical analysis of the mobile phone **150** performed using the electrical connector **141** connected to the data port **151** of the mobile phone **150**. The processor also determines a financial remuneration for the submitted mobile phone **150** based on the visual inspection, the electrical analysis and data stored in the memory **161** of the kiosk or information provided externally through the external communication component **167**.

[0051] In one use of the kiosk **100**, a consumer is asked to pre-bag, pre-box or place a barcode label on the consumer electronic ("CE") device at some point before or during the inspection process. The consumer is instructed to use wheels, slides or levers to drop the mobile phone into a bag, box or directly into a bin. If dropped into a bag or box, the consumer is instructed to use wheels, slides or levers to seal the outer package.

[0052] Each kiosk **100** preferably bins mobile phones according to parameters including but not limited to: vendor/model, condition, value, visual quality, physical damage, water damage, locked

or unlocked, carrier compatibility, frequency of phone, type of cellular standard supported (CDMA, GSM, etc.), or combinations of these parameters. The inventory of each kiosk **100** is then preferably automatically transmitted from the kiosk **100** to an online web posting whereby auctions, or live auctions are held allowing buyers to bid and purchase specific bins from specific kiosks in real time. The bins are shipped directly from each specific kiosk **100** to the bid winner during the next time the kiosk **100** is serviced. Bins are preferably associated with a single model or group of models. In other cases the bins are associated with a particular type of phone (e.g., CDMA), or another specific-type grouping. Bins are also associated with devices that are to be recycled for their material value, and should only ship when the bin is full. While other devices are binned to distinguish that they need to ship as quickly as possible because the device has immediate aftermarket re-sale demand and the real-time connection to the kiosk **100** enables real-time inventory tracking and binning of recycled devices.

[0053] In one embodiment, the display of the kiosk **100** displays current purchase prices for different models of mobile phones. This current pricing is used to encourage and provide incentive to customers to bring their used phones to the kiosk **100** for resale or recycling. The kiosk **100** is in regular and periodic communication with a server to receive such data and update its display accordingly. The pricing data provided to the kiosk is called the Offer Price to the consumer, and is preferably based upon aftermarket sales prices which vary on a regular basis (e.g., daily) for each make/model of recycled device. The offer price presented to the consumer is preferably determined by subtracting the recycling fee from the pricing data provided by the aftermarket reseller.

[0054] The kiosk **100** also preferably monitors all of its consumables (paper, ink, etc.) and requests new supplies automatically so that the kiosk **100** is substantially constantly operational. The kiosk **100** also preferably monitors the inventory of items collected by the kiosk and provides a shipment report to the reverse logistics vendors to determine the number, size, and weight of items to be collected from the kiosk **100**.

[0055] FIG. 2 illustrates a network topology **200** configured in accordance with an embodiment of a system. In one aspect of this embodiment, several recycling kiosks **202** are coupled via communications links **204** or **210** to a communications network **206**. While two forms of connecting recycling kiosks are shown in FIG. 2, several embodiments are anticipated. Examples of embodiments of recycling kiosks include various forms of vending machines, Open Mobile Service Interface based kiosks, and other retail automated machines. Also coupled to the communications network **206** via a communications link **212** is a recycling kiosk server **214**.

[0056] Transactions selected by customers at the recycling kiosks **202** or **208** are routed to the recycling kiosk server **214**. In another aspect of this embodiment, the recycling kiosk server **214** is coupled to a database **215**. The database **215** is preferably stored on the same or another recycling kiosk server **214**, or resides in a separate server (not shown). One familiar with the relevant art will understand how software executing on a recycling kiosk server **214** is able to retrieve data stored in the database **215**, whether that database **215** is stored on the same or separate servers. The database **215** preferably stores information including unique identifiers that have been provided to customer via the Touch Screen user interface or by way of wired or wireless communications to mobile device relating to vouchers, a personal identification number associated with each unique identifier, a telephone number, a credit amount, an indication of whether the voucher identified has already been used, and other pertinent information relating to providing recycling services on any recycling kiosk **202** or **208**. In one aspect of this embodiment, the database transfers media content or executable applications to be delivered to the users' mobile device by way of wired or wireless communications.

[0057] In yet another aspect of this embodiment, the recycling kiosk server **214** is coupled via a communications link to a biometrics server **216** and a content server **218**. The biometrics server **216** conducts various fraud detection and prevention activities, including prevention of fraudulent credit cards. The content server **218** performs various activities, including storing user interface

content and advertising for use on the recycling kiosks **202** and **208**. One familiar with the relevant art will understand how content stored on the content server **218** is transferred via various communications links and protocols to recycling kiosks **202** and **208** for rendering the content. [0058] The content stored on a content server **218** preferably includes images, Extensible Markup Language (“XML”) documents, hypertext markup language (“HTML”) documents, audio, video, text, etc., and instructions to enable a recycling kiosk **202** or **208** to render the content correctly. As an example, advertising and other content specifically targeted to consumer demographics on a kiosk or time-of-day basis is rendered on recycling kiosks **202** and **208** after retrieval from the content server **218**. A recycling kiosk **202** located in a department store displays different advertisements than a recycling kiosk **208** located at a convenience store. Additionally, a recycling kiosk **202** located in a department store shows different advertisements during weekdays than during evenings and weekends to target different demographics. Further, a recycling kiosk **202** located in a sporting goods department shows different advertisements than a recycling kiosk **202** located in an electronics department.

[0059] Recycling kiosks **202** are preferably located in many public or otherwise accessible locations including shopping centers, street sidewalks, gas stations, DVD rental stores, grocery stores, and restaurants in addition to department and convenience stores. The recycling kiosk server **214** is also coupled via a communications link **222** to a recycling kiosk communications network **224**. Multiple service provider systems **228** are also coupled to the recycling kiosk communications network **224** via communications links **226**. Examples of service provider systems **228** include systems operated by eBay, cellular telephone companies, bankcard companies, and aggregators of services from service providers. These various service provider systems **228** operate independently on different computer systems and may use different communications protocols. The recycling kiosk server **214** is able to exchange information with multiple service provider systems **228** independently or jointly and in parallel or sequentially despite using the same or different communications protocols or system software.

[0060] A possible use scenario of the embodiment described in FIG. **1** and FIG. **2** is shown in FIG. **3**. At step **301** a customer elects to sell or recycle a mobile phone. The customer checks to see if his mobile phone is supported for sale/refurbishing from a list on the screen of the kiosk. The customer activates the on-screen menu system and either enters the phone model directly or goes through a series of menus to determine if the phone is eligible for sale or only for recycling. After identifying the model phone, the customer may optionally at step **301** select a charity to which to donate proceeds and/or identify a fund raising group so that appropriate credit can be given to that group. In other embodiments, the steps can be done at a later time. In one embodiment, the kiosk **100** takes a picture of the customer and associates it with the phone and the transaction, to prevent fraud claims or to identify potential customers who are selling stolen phones.

[0061] At decision block **302** it is determined if the phone is only available for recycling. If yes, (i.e., it is not on the list of phones available for reselling) the customer can insert the mobile phone into receptacle **106** at step **303** and the phone falls into bin **112** for recycling. A tax voucher might be presented through **107** for the recycled phone.

[0062] If the phone is supported for refurbishment/resale the customer is then encouraged to engage the testing/rating operation of the system. At step **304**, the system has determined the correct connector to couple to the phone. Connectivity options and are not limited to cable, standard or proprietary connectors, hard docks, reading removable or external physical memory or other wireless methods like WiFi, Bluetooth, RFID, NFC, and the like. In one embodiment, the system includes a plurality of connectors for known phone models. Based on the input from the user as to the identity of the phone model, the system can select the correct connector and offer it to the customer. In other embodiments, a plurality of connectors is available and identified (by name, color, etc.) and the user is informed as to which one to use. In another embodiment, a universal connector is used to connect to the phone. After the phone is connected, the system presents a cage

or cradle in which to place the phone. This is designed so that the phone is in a known or unknown initial position so that it can be visually inspected using photographic or other equipment.

[0063] At step **305** the phone is connected and inserted into inspection area **106**. If this has been done correctly, the customer is given some indication (e.g., a green light) and the system proceeds to step **306**. For instance, the software may direct the consumer to place the device in the “inspection bin” in a certain orientation. The consumer is then asked to manually change the orientation. Alternatively, the user is asked to turn wheels or use slides or levers to change the orientation. The consumer may be asked to open a device such as a clam shell phone, open doors or view finders on video cameras, pop open features such as flashes, slide open covers, etc. and then place the item back in the inspection area. The user may also be asked to attach cables. The user may also be asked to attach restraints and/or use wheels, slides and/or levers to invoke restraint on the device.

[0064] At step **306** the phone is tested for operation using diagnostics and operating via, for example, the OMSI interface. The diagnostics preferably includes electrical and physical testing including testing the phone's battery, screen, memory, button functionality and structural integrity.

[0065] In one embodiment, the phone is photographed and analysis software is used to identify scratches, cracks, wear patterns, dents, broken or missing pieces, inclusion of features such as lenses, buttons, connectors, badges, labeling and/or branding. Identification may be done by image comparison or other similar methods where the photograph taken of the phone is normalized and compared to a reference image. Other inspection methods may be used in conjunction with visual and/or electrical testing including weighing each device in the kiosk to determine specific weight and use that data to further refine verification of manufacturer and verification of exact device model. In another embodiment, the photographic image is used to identify the correct manufacturer and model number/product number. Visual identification could include any combination of the following: calculations based upon measurement, physical (e.g., mm, inches), pixel count or other. Identification based upon phone dimensions, location/size of buttons, LCD and other physical characteristics. One camera or multiple cameras may be used to determine height, width, depth as needed. Identification based on OCR (Optical Character Recognition) of identifiers such as Carrier (for phone), brand, model, serial number, other identifiers. Identification based upon barcodes. Consumer may be asked to orient CE on its front, back, side and then asked to change orientation as needed. Consumer may even be asked to remove CE cover(s), batteries and the like in order to gain access to identifiable items, such alphanumeric or barcode data. The kiosk **100** provides a way to use visual inspection with electrical inspection to identify a device, determine its value, and reduce possible fraud. The kiosk **100** determines a preliminary identification of the phone with the visual system, and then present or light up the correct cable for that phone so the consumer can plug in the correct cable. The kiosk **100** then confirms by electrical test that the visual identification was indeed correct, then tests the phone to determine its functionality and value.

[0066] Identification is made by comparing collected information and comparing that to a database. The correct model identity is used by the kiosk **100** to determine the correct electrical connector from a database of device specification information for the purpose of performing electrical test, erase or re-programming of the device. For consumer electronic devices such as stereos, computers, DVD players, game consoles, etc., that can be evaluated electronically, in addition to or instead of visually identifying the device; it may be necessary to identify the cable connector type for electronic inspection. This is preferably done by visually identifying the dimensions and shape of a connector receptacle. This could also include identification of the pins or connector points in the receptacle. The kiosk **100** preferably automatically connects the electrical interface to the mobile device or instructs the user how to connect the electrical connector to the electronic device. In another embodiment, the image is electronically transferred to a human operator who performs a visual evaluation and grading of the cosmetic condition of the phone. In another embodiment, if the customer does not agree with the assigned grade or rating, the kiosk **100** includes a call button to

provide two way communications with a human operator to discuss the rating.

[0067] In another embodiment, a “micro-kiosk” has the same facilities for visual/electrical inspection but does not necessarily bin and store the products it evaluates. The micro-kiosk is used by an operator, perhaps with a group of discrete peripheral devices (computer, camera, a plurality of cable connectors, printer, barcode scanner, fingerprint reader, signature pad, etc.). This micro-kiosk requires an operator, store clerk, or technician, to complete transactions and guard against fraud. The micro-kiosk is preferably a more appropriate solution than a full kiosk for some venues such as floor-space limited retailers, high-customer-clerk-engagement model retailers, and phone processors and/or refurbishers.

[0068] In one embodiment, the kiosk **100** communicates with the carrier associated with the phone to collect any information that could be germane to the device, including, for example, validation or authentication, registered ownership, account status, time in service, and the like. In some cases, when the customer's identification information does not match the registered owner information, the kiosk **100** automatically contacts the assumed owner in some manner (automated telephone call, email, text message, etc.) to alert the owner of the phone of the possible transaction.

[0069] Another feature of an embodiment of the kiosk **100** is to determine if there is personal information on the phone. This is determined by the presence of data in particular storage registers in the memory (e.g., quick-key stored numbers) or by looking at file types (jpegs, mp3's, etc.), or just assuming all non-default storage locations must contain personal data. The customer is offered the chance to erase the data from the phone. One option allows the customer to request that the data be first downloaded and then sent to a location designated by the customer (e.g., email address, website, etc.). In another embodiment, there is a slot for the customer to enter a memory card (e.g., USB drive memory stick, etc.) whereupon the kiosk **100** uploads the data to the memory device. In still another embodiment, the kiosk **100** offers a web location from which the user retrieves the data at some later time if desired. In another embodiment, the user elects to have the data placed in another phone purchased by the customer at the kiosk **100** or in the location of the kiosk **100** or some other store. The customer preferably selects a user name and password to access the system provided storage location.

[0070] Based on the results of the diagnostics, the kiosk **100** assigns the phone a rating. The rating is a selection of one of a plurality of categories (e.g., excellent, fair, average, poor), a letter grade (A, B, C, D, F), or a ranking on a numerical scale. The kiosk **100** then accesses a database to determine a real-time value for the phone based on current resale values. The kiosk **100** uses real time or batch connectivity for updating pricing of used devices, connecting to an auction system or pre-auction system.

[0071] This data can be scraped from online sites such as eBay or Craigslist, it may be generated by the kiosk **100** and updated periodically, it may be based on a consumer guide, or any other suitable method for determining a current value for the phone. The value is determined by a current market price obtained via communication to the recycling server **214** using the communications network **206**. The recycling server **214** obtains a current market price for the phone from one of the service providers and stores, on a regular basis, market prices on the database. In the embodiment described in FIG. 2, a mechanism is available to update audiovisual or other user interface content or other aspects of the recycling kiosks **202** and **208**. As an example, when content needs to be updated, the content only needs to be updated at the content server **218**. The recycling kiosks **202** and **208** retrieve the updated content via the communications network **206** from the content server **218**. As described above, the content used by a recycling kiosk **202** is preferably the same or different than content used by other recycling kiosks **208** or even another recycling kiosk **202**. Once the value is determined, the value is provided at step **307** to the kiosk. The kiosk **202** then offers the customer a price or other remuneration for the phone that is typically less than the resale value. In other embodiments, the kiosk **202** offers the customer a price or remuneration that is at the current real-time market price.

[0072] At step **308** it is determined if the user wishes to accept the offer. If not, the kiosk **100** proceeds to step **309** and opens the cage door and releases the phone back to the customer. If the user wishes to accept the offer, the kiosk **100** proceeds to step **310**. At a point where the user accepts a price, the kiosk **100** may then lock down the inspection area to prevent further access to the phone by the user. The kiosk **100** then disconnects any cables that have been attached. At step **310**, the user indicates acceptance of the decision by confirming on the keypad or touch-screen. In one embodiment, the kiosk **100** has a multi-stage process to determine user acceptance so that the customer can back out if a mistake was made. At this point the kiosk **100** proceeds with deleting the personal data from the phone. In addition, once the transaction is confirmed, the kiosk **100** tags the phone with a transaction number that is associated with the diagnostic data and the transaction itself. This is preferably a printed adhesive label that is affixed physically to the phone and/or the loading of electronic data corresponding to the transaction number onto the phone itself for traceability purposes.

[0073] At step **311**, the kiosk **100** completes any additional testing and diagnostics of the phone, disconnects the cable from the phone, and prints a receipt for the customer. Transfer of funds may be authorized via the kiosk **100** by crediting a customer credit card or account by dispensing cash, or by dispensing a voucher or coupon. In other embodiments, the kiosk **100** issues a receipt to the customer who then can take it to, for example, a store associated with the location of the kiosk, for payment. If the user has elected to donate the value of the phone to charity, the customer then is issued a donation receipt and settlement is accomplished later with the charity.

[0074] At step **312** the kiosk **100** updates its inventory database and transmits the update via the communications network **206** to the kiosk server **214**.

[0075] Each kiosk **100** bins the phones according to parameters including but not limited to: vendor/model, condition, value of device, shipping priority, locked or unlocked, carrier compatibility, frequency of phone, type of cellular standard supported (CDMA, GSM, etc.), or combinations of these parameters. The inventory of each kiosk bin is then be transmitted from the kiosk to and online web posting whereby live auctions can be held allowing buyers to bid and purchase specific bins from specific kiosks in real time. The bins then are shipped directly from each specific kiosk **100** to the bid winner during the next time the kiosk **100** is serviced.

[0076] The generation of these online offers is preferably automated. Appropriate text for each model of phone is prepared in advance. Descriptions of the phone are also automated based on the perceived condition of the phone. Finally, the inspection photograph(s) is included in the online offer by electronically communicating them to the kiosk server. The diagnostics and testing information is provided as part of the offer, as well as information about whether the phone is locked or unlocked, includes a sim card, expanded memory, or other descriptive information and features.

[0077] In other embodiments, the phones are first collected from the kiosk and then put into a resale channel. In some cases, the phones may be refurbished, reconditioned, or upgraded prior to resale. In another embodiment, the kiosk **100** automatically updates the firmware in the mobile phone while it is attached to the connector. Any updates or improvements that can be made electronically are preferably accomplished automatically at the kiosk **100**.

[0078] Many phones and recyclable devices include proprietary chargers. One embodiment contemplates the ability for the user to plug in the charger and insert the connector into a receptacle so that the charger can be tested as well. The system then tags the charger with the same transaction number and includes its value in the price and resale.

[0079] The kiosk **100** not only rates the cosmetic condition of the phone, but also preferably rates the condition of the battery. Once connected, the kiosk **100** determines the ability of the battery to hold a charge, measures the voltage and current, and assigns a rating to the battery as well.

[0080] FIG. **4** is a diagram illustrating another embodiment of the operation of the system. The diagram of FIG. **4** is described in conjunction with embodiments of touch screen display images of

FIGS. 5A-5E. At step **401** the operation begins. The display screen **119** of the kiosk **100** is shown in FIG. 5A. An upper part of the screen may include a number of selectable options such as Recycle My Cell Phone **501**, Printer Recycle Offer **502**, Computer Recycle Offer **503** (this may be a branded or sponsored recycle offer, such as from a single company such as Dell) and Device Recycle Offer **504** (this button may be used for other devices and recyclable items that are not covered by the first three buttons). If desired, an attract loop (i.e., movie) may be provided in a lower region **505** of the display. The attract loop may also be used to teach the user how to use the system.

[0081] In one embodiment, the kiosk **100** can broadcast WiFi to push content to WiFi enabled phones. The system can make users aware of its existence by alerting them via such wireless transmissions. In addition, the kiosk **100** could play and/or broadcast content for the store location and/or third parties as an additional revenue source.

[0082] After the user selects the type of transaction at step **401**, the kiosk **100** moves to the next screen. For purposes of example, it is presumed that the user has elected to recycle a cell phone. The user selects the type of cell phone as shown in FIG. 5B by choosing smart phone **506** or cell phone **507**.

[0083] At step **402** the user chooses a brand of phone, such as by selecting a brand in FIG. 5C. If the users' brand is not shown in FIG. 5C, a "more" selection is available. In one embodiment, a keyboard is provided and the user can type in the brand, with an optional auto-complete feature provided. At step **403**, the user is presented with a number of models for the particular manufacturer, as shown at FIG. 5D. The user selects the model at step **403**.

[0084] At step **404**, the user is instructed to get a bag from bag bin **120**. At step **405** the user places the phone in the bag and seals it using a zip lock or some other suitable means. In one embodiment, each bag has pre-printed bar code label affixed thereto. In another embodiment, the kiosk **100** can print out a bar-coded self-adhesive label that the user can place on the bag. At step **406** the user scans the bar code using the bar code reader **125** of the kiosk **100**.

[0085] At step **407** the kiosk may automatically bag the device or the user places the sealed bag into the inspection bin **106** of the kiosk **100**. At step **408** the user is presented with a default value such as shown in FIG. 5E. This default value is for a typical phone of that type in unknown condition. The value may be determined by accessing a locally stored database or by accessing a dynamically updated database via network communication between the kiosk and a central location.

[0086] At decision block **409** it is determined if the user wants to accept the initial price. If so, the kiosk **100** proceeds to step **413**. If not, the kiosk **100** proceeds to step **410** and a series of questions to determine a possible higher value for the phone. The user is first asked to identify the carrier at step **410**. At step **411** the user is asked other questions about the phone such as whether it powers on, if the display works properly and whether the phone is water damaged.

[0087] At step **412**, a new value is presented to the user. In some cases, the new value is higher, while in others it may be lower, all depending on the responses provided by the user. During this time, the kiosk **100** preferably performs an automated inspection of the phone via a camera built into the inspection bin. In other instances, the user is asked to plug the phone into a connector so that an automated electronic analysis of the phone can be accomplished.

[0088] If the user accepts the new value at step **412** or at step **408**, the kiosk **100** proceeds to collect personal information from the user at step **413**. This may be accomplished by entering a customer loyalty number associated with a retailer where the kiosk is located, swiping a credit/debit card, by swiping a drivers license, or by manual entry using a keyboard presented on the touch screen of the kiosk.

[0089] At step **414** the user selects one of a plurality of compensation methods, such as store credit, charge card credit discount coupon, etc. After the user selects a payment method, the user is prompted to enter a fingerprint by placing a thumb or finger on print reader **128** of kiosk **100**. At

step **416** the user signs an electronic signature pad **130** on kiosk **100** and the transaction completes at step **417**.

[0090] In an alternate embodiment, the kiosk **100** provides a network of inter-connected kiosks which communicate with centralized servers for the purpose of proving real-time pricing for a plurality of electronic devices that can be recycled using the kiosk **100**, including larger electronic devices such as personal computers, microwaves, or any other recyclable electronic device. The kiosk **100** implements functionality related to pricing, credit and interaction, but provides a number of different implementations for receiving and transferring the recycled goods. The kiosk **100** may also include a web version that can be an initial entry into the system with physical transfer taking place in other methods.

[0091] The User Interface (“UI”) instructs users how to determine the value of a recycled item or item being returned to a retail store for a trade-in value.

[0092] The kiosk **100** uses a variety of inspection techniques to determine the value of the device digital media. The inspection techniques include the combination of visual inspection, and electrical testing using standard (USB, HDMI, DVI, etc.) electrical interfaces and proprietary (Apple, Nokia, etc.) electrical interfaces for identification & classification to uniquely identify the manufacturer and model number and software revision.

[0093] The electronic recycling kiosk collects information that when compiled for the retailer, can be used to substantiate their compliance with States' eWaste and 2nd hand Dealer Laws.

[0094] The recycling kiosk **100** is also used to take personal information such as a photograph and fingerprint to identify people selling pre-owned goods, and as needed provide this information to local law enforcement authorities to determine if stolen goods have been moved through the recycling process, and by whom.

[0095] To prevent or reduce fraud, the system may incorporate a number of tests and analysis such as: weighing the device—this is prone to errors (case, no case, battery, no battery); visually inspecting the device to detect slight design features to detect fakes; visible light or laser scan a device to derive an heat absorption/decay signature for a given device. The theory is that the decay signature is different for every make/model of device and varies with the orientation of the scan on the same device. Fake or empty devices do not have the proper signature and will not be accepted for immediate payment. In this case, the user has the option to get paid after the phone is inspected by a human.

[0096] From the foregoing it is believed that those skilled in the pertinent art will recognize the meritorious advancement of this invention and will readily understand that while the present invention has been described in association with a preferred embodiment thereof, and other embodiments illustrated in the accompanying drawings, numerous changes modification and substitutions of equivalents may be made therein without departing from the spirit and scope of this invention which is intended to be unlimited by the foregoing except as may appear in the following appended claim. Therefore, the embodiments of the invention in which an exclusive property or privilege is claimed are defined in the following appended claims.

Claims

1. (canceled)

2. A kiosk for evaluating an electronic device, the kiosk comprising: a housing; a support surface positioned within the housing and configured to receive and support the electronic device; one or more cameras; and one or more processors configured to— cause relative movement between the support surface and at least one of the one or more cameras to facilitate an evaluation of the electronic device within the kiosk, the evaluation including a visual evaluation of one or more images obtained via the one or more cameras; and provide, to a user, an offer to purchase the electronic device for a price based at least partially on the evaluation.

3. The kiosk of claim 2 wherein the one or more processors are operably coupled to the support surface and configured to cause the support surface to move relative to the at least one of the one or more cameras.
4. The kiosk of claim 2 wherein the one or more processors are operably coupled to the at least one of the one or more cameras and configured to cause the at least one of the one or more cameras to move relative to the support surface.
5. The kiosk of claim 2 wherein the one or more processors are operably coupled to the support surface and configured to cause the support surface to move relative to the housing to position the electronic device within a field of view of one or more of the one or more cameras.
6. The kiosk of claim 2 wherein the one or more cameras include a first camera and a second camera, and wherein the one or more processors are operably coupled to the support surface and configured to cause the support surface to move relative to the housing and position the electronic device between the first camera and the second camera.
7. The kiosk of claim 2 wherein the one or more processors are further configured to: obtain, via the one or more cameras, the one or more images of the electronic device; determine a physical condition of the electronic device based at least partially on the visual evaluation of the one or more images; and determine the price based at least partially on the physical condition of the electronic device.
8. The kiosk of claim 2 wherein the one or more processors are further configured to perform the evaluation including the visual evaluation of the one or more images, wherein the evaluation further includes an electrical inspection of the electronic device, and wherein the one or more processors are further configured to: cause the support surface to move the electronic device from a first position within the housing to a second position within the housing, and perform the electrical inspection while the electronic device is in the second position.
9. The kiosk of claim 2 wherein the electronic device is a mobile phone and wherein the support surface is configured to support the mobile phone thereon for the evaluation.
10. A system for evaluating an electronic device, the system comprising: a kiosk, including— a housing; an inspection area within the housing; a support surface positioned within the housing, wherein the support surface is configured to receive the electronic device from a user and support the electronic device within the inspection area; and one or more cameras having a field of view that includes at least a portion of the inspection area; and one or more processors configured to— cause relative movement between the support surface and at least one of the one or more cameras to facilitate an evaluation of the electronic device within the kiosk, the evaluation including a visual evaluation of one or more images obtained via the one or more cameras; and provide, to the user, an offer to purchase the electronic device for a price, wherein the price is based at least partially on the evaluation.
11. The system of claim 10 wherein the one or more processors are operably coupled to the support surface and configured to cause the support surface to move relative to the at least one of the one or more cameras.
12. The system of claim 10 wherein the one or more processors are operably coupled to the support surface and configured to cause the support surface to move relative to the inspection area to position the electronic device within the field of view of one or more of the one or more cameras.
13. The system of claim 10 wherein the one or more cameras include a first camera and a second camera, and wherein the one or more processors are operably coupled to the support surface and configured to cause the support surface to move relative to the inspection area and position the electronic device between the first camera and the second camera.
14. The system of claim 10 wherein the evaluation further includes an electrical inspection of the electronic device, and wherein the one or more processors are further configured to: cause the support surface to move the electronic device from a first position within the housing to a second position within the housing, and perform the electrical inspection while the electronic device is in

the second position.

- 15.** The system of claim 10 wherein the electronic device is a mobile phone and wherein the support surface is configured to support the mobile phone in the inspection area for the evaluation.
 - 16.** A method of evaluating an electronic device at a kiosk having one or more cameras, the method comprising: receiving, from a user, the electronic device on a support surface within a housing of the kiosk; causing, via one or more processors operably associated with the kiosk, relative movement between the support surface and at least one of the one or more cameras to facilitate an evaluation of the electronic device within the kiosk, the evaluation including a visual evaluation of one or more images obtained via the one or more cameras; and provide, to the user, an offer to purchase the electronic device for a price, wherein the price is based at least partially on the evaluation.
 - 17.** The method of claim 16 wherein causing the relative movement includes causing the support surface to move relative to the at least one of the one or more cameras.
 - 18.** The method of claim 16 wherein causing the relative movement includes causing the support surface to move relative to the housing to position the electronic device within a field of view of one or more of the one or more cameras.
 - 19.** The method of claim 16 wherein the one or more cameras include a first camera and a second camera, and wherein causing the relative movement includes causing the support surface to move relative to the housing and position the electronic device between the first camera and the second camera.
 - 20.** The method of claim 16 wherein the evaluation further includes an electrical inspection of the electronic device, and wherein the method further comprises: causing the support surface to move the electronic device from a first position within the housing to a second position within the housing, and performing the electrical inspection while the electronic device is in the second position.
 - 21.** The method of claim 16 wherein the electronic device is a mobile phone and wherein receiving the electronic device on the support surface includes receiving the mobile phone on the support surface.
-