

US012390047B2

(12) United States Patent Hughes

(10) Patent No.: US 12,390,047 B2

(45) **Date of Patent:** Aug. 19, 2025

(54) DRAIN DA FAT

(71) Applicant: **Ewart Fitzmore Hughes**, Massapequa, NY (US)

(72) Inventor: Ewart Fitzmore Hughes, Massapequa,

NY (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 295 days.

(21) Appl. No.: 17/566,671

(22) Filed: Dec. 30, 2021

(65) Prior Publication Data

US 2022/0386812 A1 Dec. 8, 2022

Related U.S. Application Data

- (60) Provisional application No. 63/205,613, filed on Dec. 30, 2020.
- (51) **Int. Cl.** *A47J 37/07* (2006.01)

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

9,155,422	B1 *	10/2015	Wohld A47J 43/18
10,598,383	B1*	3/2020	Schoettle A47J 37/0786
10,709,293	B1 *	7/2020	Nathans C08J 11/14
2012/0055346	A1*	3/2012	Navare A47J 37/10
			99/446
2013/0233183	A1*	9/2013	Brinckerhoff A47J 37/1295
			99/403
2017/0143161	A1*	5/2017	Masterson A47J 36/26
2017/0258271	A1*	9/2017	Man A47J 37/1223
2019/0069723	A1*	3/2019	McClellan A23L 5/11
2020/0260911	A1*	8/2020	Brennan A47J 36/16
2021/0007552	A1*	1/2021	Tanaka A47J 37/1276
2021/0022552	A1*	1/2021	Porraro A47J 37/0786
2021/0338010	A1*	11/2021	Hamel A47J 37/0786


^{*} cited by examiner


Primary Examiner - Ko-Wei Lin


(57) ABSTRACT


Described herein are examples of an apparatus which includes a metal frame and metal grill. The metal frame has a handle, an upper ring and an lower ring, and the frame is fitted over the perimeter of a pan while the metal grill is lowered below the perimeter of the pan and held in place above the cooking oil by a support.

7 Claims, 3 Drawing Sheets









10

15

1 DRAIN DA FAT

CROSS REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of U.S. non provisional patent application Ser. No. 17/566,671 filed Dec. 30, 2021.

FIELD OF THE INVENTION

The present Inventory relates to the field of health and in particular diet and nutrition as its applied to reduction in the consumption of excess grease associated with deep fried foods.

BACKGROUND TO THE INVENTION

Among many studies with similar conclusions, a study by Harvard University School of Public Health found that people who eat a lot of fried foods may have a higher risk 20 of developing heart disease and type 2 diabetes. The findings were based on data examining 100000 men and women over a 25-year period. Before the pandemic, heart disease was the leading cause of death in the US. This is not suggesting that all those heart disease deaths were tied to consumption of 25 fried foods, but it has been a factor according to research.

Deep fried foods are still very popular among millions of people in the US. This Innovation seeks to limit the intake of excess grease associated with fried foods and type 2 diabetes and cardiovascular diseases and as a result promote ³⁰ longevity and well been.

The devise comprises a metal frame and a drip tray or grill. The frame has a handle and is fitted over the perimeter of a boiling pan of deep fried food while the inner grill is submerged below the perimeter but help in place above the oil by a support that is a part of the frame. The grill has 2 flaps or opening so the non-fried foods can be placed into the boiling oil while fried ones are removed and placed on the dripping tray.

Presently most people might use a separate cooling rack ⁴⁰ to drip oil but this leaves the food cold, or they might use napkins to remove excess oil but this makes the food soggy.

BRIEF SUMMARY OF THE INVENTION

It is the object of the present invention to provide a device that can help to drain excess oil from fried food while keeping them warm and crispy. This is so because the dripping tray is suspended above the oil in the pan.

It is the object of the present invention to avoid the 50 inconvenience of using a separate drain rack that is not immediately over the heat thus causing the food to get cold and less crispy or to avoid having to use napkins inside a plate to sap up excess grease since this causes the food to reabsorb the grease and becoming soggy. This invention 55 helps to keep the fried foods crispy and less soggy. It also voids the need for additional counter space.

It is another object of the present invention to be able to access fried foods for stirring or removal without having to remove the drip rack that is suspended above the cooking 60 oil. This is possible since the grill has two flaps or opening on opposite ends that can rotate to allow removal and immersion. This is also possible since the grill is not welded onto the support but rest on it so it can slide around to any desired position for access.

It is the object of the invention to provide an apparatus that is versatile and convenient. The metal frame of the 2

invention hangs over the perimeter of the pan and has a handle that allows it to be placed or remove effortlessly. Similarly, the inner grill can be placed and removed effortlessly and allows easily sliding it around on the support from the frame.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a 3/4 view of the he metal frame.

FIG. 2 is a 3/4 view of the inner grill.

FIG. 2a is a top view square pattern inner grill.

FIG. 2b is a $\frac{3}{4}$ view of the square pattern inner grill.

FIG. 2c is a top view of the line pattern inner grill.

FIG. 2d is a $\frac{3}{4}$ view of line pattern grill.

DETAILED SPECIFICATIONS

The outer frame has a handle that is 3.81 cm at its widest point and is 20.32 cm in length.

For smaller pans the upper ring is 27.94 and the lower ring is 22.86 cm 27.94 cm for smaller pans. The v shaped metal support connecting both upper and lower rings, starts from the lower ring then goes in a 1.27 cm horizontal direction then rises 2.54 cm and then 1.27 cm right angle where its attached to the upper ring.

The Inner Grill

The second part is the inner grill that is circular in shape and fits inside the outer frame. It is 26.16 cm in diameter and sits on the lower ring which is a part of the outer frame. This circular grill is comprised of 3 parts, a center piece and two rotating ends on either side of the center piece. These sizes vary depending on the amount of space needed to insert remove and drip deep fried foods.

The opening Flaps are usually 25.5 cm wide and 9.88 cm deep but can be 10.73 cm in some to provide a larger opening for easier handling of fried foods. The grill has a square pattern or straight line. For the squares pattern each square is 8.33 cm wide. The rotating ends are attached to the inner piece by a hooked rod that acts as the hinges. The outer sides rotate up or down.

The Outer Frame

The Outer frame has an upper ring that is 13 inches in diameter. This ring is attached to a lower ring that is 10 inches in diameter, and are held together by 4 v shaped posts that rise 1 inch from the bottom ring to the height of the top but extends 0.5 inches at a 90 degrees angle.

The outer frame has a handle that is 1.5 inches at its widest point and is 8 inches in length.

The Inner Grill

The second part is the inner grill that is circular in shape and fits inside the outer frame. It is 10.3 inches in diameter and sits on the lower ring which is a part of the outer frame. This circular grill is comprised of 3 parts, a center piece and two rotating ends on either side of the center piece. Each piece is 3.33 inches in width. The rotating ends are attached to the inner piece by a hooked rod that acts as the hinges. The outer sides rotate up or down.

What is claimed is:

1. An apparatus comprising a metal frame,

wherein the metal frame is configured to support a grill and be suspended over a pan comprising cooking oil, the metal frame further comprising:

a handle,

an upper ring,

wherein the handle extends horizontally distal from the upper ring,

a lower ring, and

10

a metal grill,

wherein the handle is connected to the upper ring and the lower ring,

wherein the upper ring comprises a diameter configured to the pan.

wherein a diameter of the lower ring is less than the diameter of the upper ring,

wherein the upper ring is configured to be supported by a perimeter of the pan via a support that connects the lower ring to the upper ring,

wherein the support extends inward horizontally from said upper ring, bends at a 90-degree angle downward, extends vertically downward towards the lower ring, and then bends at an angle inwards and extends horizontally to connect to the lower 15 ring,

wherein the support:

attaches to the lower ring approximately one inch below the upper ring,

wherein the lower ring has a diameter approximately three inches less than the diameter of the upper ring, and

wherein the support has a v shape, wherein a base of the v shaped support is attached to the lower ring and a top of the v shaped support is ²⁵ attached at two points to the upper ring,

wherein the lower ring is configured to support the metal grill,

wherein the metal grill further comprises two rotating ends on opposite sides of the metal grill,

wherein the metal grill is not attached to the metal frame,

wherein the metal grill is configured to allow cooked food to drip oil into the cooking oil while the metal frame rests on the pan, and

wherein the two rotating ends are configured to open and allow a user to place food from the cooking oil onto the metal grill.

2. The apparatus of claim 1, comprising three additional v shaped supports.

3. The apparatus of claim 1, wherein the metal grill comprises straight line grates.

4. The apparatus of claim **1**, wherein the handle is approximately eight inches in length.

5. The apparatus of claim 1, wherein the metal grill 45 comprises:

a center piece, and

wherein the rotating ends are configured to fold onto the center piece to allow food to be removed from the cooking oil and placed on the metal grill. 4

6. The apparatus of claim 1, wherein the rotating ends are attached to the center piece via hinges comprising hooked rods.

7. An apparatus comprising a metal frame,

wherein the metal frame is configured to support a grill and be suspended over a pan comprising cooking oil, the metal frame further comprising:

a handle,

an upper ring,

wherein the handle extends horizontally distal from the upper ring,

a lower ring, and

a metal grill,

wherein the handle is connected to the upper ring and the lower ring,

wherein the upper ring comprises a diameter configured to the pan,

wherein a diameter of the lower ring is less than the diameter of the upper ring,

wherein the upper ring is configured to be supported by a perimeter of the pan via a support that connects the lower ring to the upper ring,

wherein the support extends inward horizontally from said upper ring, bends downward, extends vertically downward towards the lower ring, and then bends inwards and extends horizontally to connect to the lower ring,

wherein the support:

attaches to the lower ring approximately one inch below the upper ring,

wherein the lower ring has a diameter approximately three inches less than the diameter of the upper ring, and

wherein the support has a v shape, wherein a base of the v shaped support is attached to the lower ring and a top of the v shaped support is attached at two points to the upper ring,

wherein the lower ring is configured to support the metal grill,

wherein the metal grill further comprises two rotating ends on opposite sides of the metal grill,

wherein the metal grill is not attached to the metal frame.

wherein the metal grill is configured to allow cooked food to drip oil into the cooking oil while the metal frame rests on the pan, and

wherein the two rotating ends are configured to open and allow a user to place food from the cooking oil onto the metal grill.

* * * * *