

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250255211

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

GARNER; Elijah B. et al.

SYSTEMS AND METHODS FOR SELECTIVE FERTILIZER PLACEMENT

Abstract

Locations of seeds in a field can be identified using event-based processing or frequency-based processing. A material is applied to the field, based upon the seed locations.

Inventors: GARNER; Elijah B. (Bettendorf, IA), SIGNER; Todd N. (Bettendorf, IA), HUBNER; Cary S. (Geneseo, IL), WONDERLICH; Grant J. (Milan, IL), HERRMANN; Kenneth E. (Port Byron, IL)

Applicant: Deere & Company (Moline, IL)

Family ID: 72234720

Appl. No.: 19/054025

Filed: February 14, 2025

Related U.S. Application Data

parent US continuation 17947734 20220919 parent-grant-document US 12256664 child US 19054025

parent US continuation 16551291 20190826 parent-grant-document US 11445658 child US 17947734

Publication Classification

Int. Cl.: A01C7/10 (20060101); A01C5/06 (20060101); A01C7/06 (20060101)

U.S. Cl.:

CPC A01C7/102 (20130101); A01C5/062 (20130101); A01C7/06 (20130101); A01C7/105 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION [0001] The present application is a continuation of and claims priority of U.S. patent application Ser. No. 17/947,734, filed Sep. 19, 2022, which is a continuation of and claims priority of U.S. patent application Ser. No. 16/551,291, filed Aug. 26, 2019; the contents of each of these applications are hereby incorporated by reference in their entirety.

FIELD OF THE DESCRIPTION

[0002] The present description relates to agricultural machines. More specifically, the present description relates to controlling application of material to a field, using an agricultural machine.

BACKGROUND

[0003] There is a wide variety of different types of agricultural machines that apply material to an agricultural field. Some such agricultural machines include sprayers, tillage machines with side dressing bars, air seeders, and planters that have row units.

[0004] As one example, a row unit is often mounted to a planter with a plurality other row units. The planter is often towed by a tractor over soil where seed is planted in the soil, using the row units. The row units on the planter follow the ground profile by using a combination of a down force assembly that imparts a down force to the row unit to push disk openers into the ground and gauge wheels to set depth of penetration of the disk openers.

[0005] Row units can also be used to apply material to the field (e.g., fertilizer to the soil, to a seed, etc.) over which they are traveling. In some scenarios, each row unit has a valve that is coupled between a source of material to be applied, and an application assembly. As the valve is actuated, the material passes through the valve, from the source to the application assembly, and is applied to the field.

[0006] Many current systems apply the material in a substantially continuous way. For instance, where the application machine is applying a liquid fertilizer, it actuates the valve to apply a substantially continuous strip of the liquid fertilizer. The same is true of materials that provide other liquid substances, or granular substances, as examples.

[0007] The discussion above is merely provided for general background information and is not intended to be used as an aid in determining the scope of the claimed subject matter.

SUMMARY

[0008] Locations of seeds in a field can be identified using event-based processing or frequency-based processing. A material is applied to the field, based upon the seed locations.

[0009] Example 1 is a planting machine, comprising: [0010] a furrow opener that opens a furrow as the planting machine moves across a field; [0011] a seed delivery system that delivers seeds to seed locations in the furrow; [0012] a device that is actuated to apply a material to the field; [0013] a device actuation timing system that generates a device actuation timing indicator indicative of a timing for actuating the device to apply the material at material placement locations relative to the seed locations; and [0014] a device control signal generator that receives the device actuation timing indicator and generates a device actuation signal based on the device actuation timing indicator to control the device to apply the material to the field.

[0015] Example 2 is the planting machine of any or all previous examples wherein the device actuation timing system comprises: [0016] a frequency driven processing system configured to generate an a priori seed pattern indicative of a relative placement of seeds in the field, relative to a reference point.

[0017] Example 3 is the planting machine of any or all previous examples wherein the reference point comprises a location of a known planting operation, and wherein the frequency driven processing system comprises:

[0018] a planting operation start detector configured to detect when the planting machine [0019] is at the location of the known planting operation and to generate a planting operation reference signal indicative of the reference point.

[0020] Example 4 is the planting machine of any or all previous examples wherein the frequency driven processing system comprises: [0021] time to actuation calculator logic configured to generate the device actuation timing [0022] indicator based on the a priori seed pattern and the planting operation reference signal.

[0023] Example 5 is the planting machine of any or all previous examples wherein the frequency driven processing system comprises: [0024] a seed pattern verification system configured to intermittently verify that the a priori seed pattern is accurate based on a detected actual seed pattern.

[0025] Example 6 is the planting machine of any or all previous examples wherein the seed pattern verification system comprises: [0026] an actual seed pattern detection system configured to detect an actual seed pattern; [0027] a pattern correction value identifier configured to identify a pattern correction value based on the a priori seed pattern and the actual seed pattern; and [0028] seed pattern correction logic configured to apply the pattern correction value to the [0029] a priori seed pattern to generate a corrected seed pattern.

[0030] Example 7 is the planting machine of any or all previous examples and further comprising: [0031] a seed sensor configured to detect a seed and generate a seed sensor signal indicative of the detected seed.

[0032] Example 8 is the planting machine of any or all previous examples wherein the device actuation timing system comprises: [0033] an event driven processing system configured to generate the device actuation timing indicator based on the seed sensor signal.

[0034] Example 9 is the planting machine of any or all previous examples wherein the seed sensor is located at a seed sensor location on the planting machine and wherein the event driven processing system comprises: [0035] a time stamp generator configured to generate a time stamp corresponding to the seed sensor signal indicating a detected seed.

[0036] Example 10 is the planting machine of any or all previous examples wherein the event driven processing system comprises: [0037] a system delay generator that generates a seed travel time delay value indicative of a time delay between the time stamp and a time when the detected seed will be in a final seed position.

[0038] Example 11 is the planting machine of any or all previous examples wherein the event driven processing system is configured to generate the device actuation timing indicator based on a device position of the device on the planting machine and based on the seed travel time delay value.

[0039] Example 12 is the planting machine of any or all previous examples wherein the event driven processing system comprises: [0040] a device time offset generator configured to generate a device time offset value indicative of a time delay between generating the device actuation signal and a time when the material is applied to the field based on a responsiveness of the device.

[0041] Example 13 is the planting machine of any or all previous examples wherein the event driven processing system comprises: [0042] a pulse timing generator configured to generate a pulse timing output indicative of a time when the device control signal generator is to generate the device control signal to actuate the device to apply the material.

[0043] Example 14 is the planting machine of any or all previous examples wherein the event driven processing system comprises: [0044] a pulse duration generator configured to output a pulse duration signal indicative of a duration for which the device control signal generator is to generate the device control signal to actuate the device.

[0045] Example 15 is the planting machine of any or all previous examples wherein the event driven processing system comprises: [0046] a travel distance generation system configured to identify a seed travel distance and generate an output indicative of when the seed is in the final seed

location based on the seed travel distance.

[0047] Example 16 is the planting machine of any or all previous examples and further comprising:
[0048] a seed firmer, wherein the seed sensor is mounted to the seed firmer.

[0049] Example 17 is the planting machine of any or all previous examples wherein the valve is mounted to the seed firmer.

[0050] Example 18 is the planting machine of any or all previous examples wherein the valve is mounted to the seed delivery system

[0051] Example 19 is the planting machine of any or all previous examples wherein the seed sensor is configured to sense the seed in the furrow.

[0052] Example 20 is a method of controlling a planting machine, comprising: [0053] opening a furrow as the planting machine moves across a field; [0054] delivering seeds to seed locations in the furrow; [0055] generating a device actuation timing indicator indicative of a timing for actuating a device to apply material at material placement locations relative to the seed locations; and [0056] generating a device actuation signal based on the device actuation timing indicator to control the device to apply the material to the field. This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter. The claimed subject matter is not limited to implementations that solve any or all disadvantages noted in the background.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0057] FIG. 1 is a top view of one example of a planting machine, shown in a partial pictorial and partial schematic form.

[0058] FIG. 2 is a side view showing one example of a row unit of the planting machine illustrated in FIG. 1.

[0059] FIG. 2A is a view of an application unit.

[0060] FIG. 3 is a side view showing another example of a row unit of the planting machine illustrated in FIG. 1.

[0061] FIG. 4 is a side view showing another example of a row unit of the planting machine illustrated in FIG. 1.

[0062] FIG. 5 is a perspective view of a portion of a seed metering system.

[0063] FIG. 6 shows an example of a seed delivery system that can be used with a seed metering system.

[0064] FIG. 7 shows another example of a delivery system that can be used with a seed metering system.

[0065] FIG. 8 is a block diagram showing one example of a material application control system.

[0066] FIG. 9 is a flow diagram illustrating one example of the operation of the material application control system shown in FIG. 8.

[0067] FIG. 10 is a block diagram showing one example of an event driven processing system.

[0068] FIG. 11 is a flow diagram showing example of the operation of event driven processing.

[0069] FIG. 12 is a flow diagram showing one example of the operation of a travel distance generation system.

[0070] FIG. 13 is a flow diagram showing one example of the operation of a time delay generation system.

[0071] FIG. 14 is a block diagram showing one example of a frequency driven processing system.

[0072] FIGS. 15A and 15B (collectively referred to herein as FIG. 15) show a flow diagram

illustrating one example of the operation of the frequency driven processing system illustrated in FIG. 14.

[0073] FIG. 16 shows one example of the architecture illustrated in FIG. 1, deployed in a remote server environment.

[0074] FIGS. 17-19 show examples of mobile devices that can be used as operator interface mechanisms in the architectures shown in the previous Figures.

[0075] FIG. 20 is a block diagram showing one example of a computing environment that can be used in the architectures shown in the previous Figures.

DETAILED DESCRIPTION

[0076] As discussed above, many current systems apply material to a field in a relatively continuous way. This can result in wasted material. For instance, some material that is applied at certain locations between seeds or plants in a field may be unnecessary. This can result in lower productivity and lower efficiency. This problem can be exacerbated in instances where the material is applied at a relatively high rate, such as in the case of high rate fertilizer application.

[0077] The present description thus proceeds with respect to a system that identifies a specific location, e.g., a seed location, and controllably dispenses or applies material, based upon the seed location (and/or position) in a field. The system can do this by sensing seeds, as they are planted in the soil, and then calculating a time when an application valve or actuator, e.g., a pump, should be actuated to apply the material, based upon the location of the valve or actuator relative to the location of the seed. Similarly, an a priori seed map can be obtained indicating where seeds will be planted (e.g., seed locations) and the system controllably dispenses or applies material based on those a priori locations. The seeds can then be planted later. Further, the system can be used to apply the material and generate a material map of the locations where it was applied. A seed map can be generated based on the material map, and seeds can be planted based on that seed map. Other things can be considered as well, such as the responsiveness of the valve or actuator, the material properties of the material being applied, etc.

[0078] Also, the present description proceeds with respect to the examples being deployed on a row unit of a planter. They could just as easily be deployed on a sprayer, an air seeder, a tillage machine with a side-dress bar, or other piece of agricultural equipment that is used to apply a material.

[0079] FIG. 1 is a partial pictorial, partial schematic top view of one example of an architecture 90 that includes agricultural planting machine 100, towing vehicle 94, that is operated by operator 92, and material application control system 113, which can be on one or more individual parts of machine 100, centrally located on machine 100, or on towing vehicle 94. Operator 92 can illustratively interact with operator interface mechanisms 96 to manipulate and control vehicle 94, system 113, and some or all portions of machine 100.

[0080] Machine 100 is a row crop planting machine that illustratively includes a toolbar 102 that is part of a frame 104. FIG. 1 also shows that a plurality of planting row units 106 are mounted to the toolbar 102. Machine 100 can be towed behind towing vehicle 94, such as a tractor. FIG. 1 shows that material can be stored in a tank 107 and pumped through a supply line 111 so the material can be dispensed in or near the rows being planted. In one example, a set of devices (e.g., actuators) 109 is provided to perform this operation. For instance, actuators 109 can be individual pumps that service individual row units 106 and that pump material from tank 107 through supply line 111 so it can be dispensed on the field. In such an example, material application control system 113 controls the pumps 109. In another example, actuators 109 are valves and one or more pumps 115 pump the material from tank 107 to valves 109 through supply line 111. In such an example, material application control system 113 controls valves 109 by generating valve or actuator control signals, e.g., on a per-seed basis, as described below. The control signal for each valve or actuator can, in one example, be a pulse width modulated control signal. The flow rate through the corresponding valve 109 can be based on the duty cycle of the control signal (which controls the amount of time the valve is open and closed). It can be based on multiple duty cycles of multiple valves or based

on other criteria. Further, the material can be applied in varying rates on a per-seed or per-plant basis. For example, fertilizer may be applied at one rate when it is being applied at a location spaced from a seed location and at a second, higher, rate when it is being applied closer to the seed location. These are examples only.

[0081] FIG. 2 is a side view of one example of a row unit **106**, with actuator **109** and system **113** shown as well. Actuator **109** is shown in five possible locations labeled as **109**, **109A**, **109B**, **109C** and **109D**. Row unit **106** illustratively includes a chemical tank **110** and a seed storage tank **112**. It also illustratively includes one or more disc openers **114**, a set of gauge wheels **116**, and a set of closing wheels **118**. Seeds from tank **112** are fed into a seed meter **124**, e.g., by gravity or from a centralized commodity distribution system (e.g., exploiting pneumatic commodity distribution to each row unit). The seed meter **124** controls the rate at which seeds are dropped into a seed tube **120** or other seed delivery system, such as a brush belt or flighted belt (shown in FIGS. 6-7, respectively), from seed storage tank **112**. The seeds can be sensed by a seed sensor **122**.

[0082] In the example shown in FIG. 2, liquid material is passed, e.g., pumped or otherwise forced, through supply line **111** to an inlet end of actuator **109**. Actuator **109** is controlled by control system **113** to allow the liquid to pass from the inlet end of actuator **109** to an outlet end.

[0083] As liquid passes through actuator **109**, it travels through an application assembly **117** from a proximal end (which is attached to an outlet end of actuator **109**) to a distal tip (or application tip) **119**, where the liquid is discharged into a trench, or proximate a trench or furrow **162**, opened by disc opener **114** (as is described in more detail below).

[0084] Some parts of row unit **106** will now be discussed in more detail. First, it will be noted that there are different types of seed meters **124**, and the one that is shown is shown for the sake of example only and is described in greater detail below. However, in one example, each row unit **106** need not have its own seed meter. Instead, metering or other singulation or seed dividing techniques can be performed at a central location, for groups of row units **106**. The metering systems can include finger pick-up discs and/or vacuum meters (e.g., having rotatable discs, rotatable concave or bowl-shaped devices), among others. The seed delivery system can be a gravity drop system (such as seed tube **120** shown in FIG. 2) in which seeds are dropped through the seed tube **120** and fall (via gravitational force) through the seed tube and out the outlet end **121** into the seed trench **162**. Other types of seed delivery systems may be or may include assistive systems, in that they do not simply rely on gravity to move the seed from the metering system into the ground. Instead, such assistive systems actively assist the seeds in moving from the meter to a lower opening, where they exit or are deposited into the ground or trench. These can be systems that physically capture the seed and move it from the meter to the outlet end of the seed delivery system or they can be pneumatic systems that pump air through the seed tube to assist movement of the seed. The air velocity can be controlled to control the speed at which the seed moves through the delivery system. Some examples of assistive systems are described in greater detail below with respect to FIGS. 6 and 7.

[0085] A downforce actuator **126** is mounted on a coupling assembly **128** that couples row unit **106** to toolbar **102**. Actuator **126** can be a hydraulic actuator, a pneumatic actuator, a spring-based mechanical actuator or a wide variety of other actuators. In the example shown in FIG. 2, a rod **130** is coupled to a parallel linkage **132** and is used to exert an additional downforce (in the direction indicated by arrow **134**) on row unit **106**. The total downforce (which includes the force indicated by arrow **134** exerted by actuator **126**, plus the force due to gravity acting on row unit **106**, and indicated by arrow **136**) is offset by upwardly directed forces acting on closing wheels **118** (from ground **138** and indicated by arrow **140**) and disc opener **114** (again from ground **138** and indicated by arrow **142**). The remaining force (the sum of the force vectors indicated by arrows **134** and **136**, minus the force indicated by arrows **140** and **142**) and the force on any other ground engaging component on the row unit (not shown), is the differential force indicated by arrow **146**. The differential force may also be referred to herein as the downforce margin. The force indicated by

arrow **146** acts on the gauge wheels **116**. This load can be sensed by a gauge wheel load sensor, which may be located anywhere on row unit **106** where it can sense that load. The gauge wheel load sensor can also be placed where it may not sense the load directly, but a characteristic indicative of that load. For example, it can be disposed near a set of gauge wheel control arms (or gauge wheel arm) **148** that movably mount gauge wheels **116** to shank **152** and control an offset between gauge wheels **116** and the discs in double disc opener **114**, to control planting depth. [0086] Arms (or gauge wheel arms) **148** illustratively abut against a mechanical stop (or arm contact member—or wedge) **150**. The position of mechanical stop **150** relative to shank **152** can be set by a planting depth actuator assembly **154**. Control arms **148** illustratively pivot around pivot point **156** so that, as planting depth actuator assembly **154** actuates to change the position of mechanical stop **150**, the relative position of gauge wheels **116**, relative to the double disc opener **114**, changes, to change the depth at which seeds are planted.

[0087] In operation, row unit **106** travels generally in the direction indicated by arrow **160**. The double disc opener **114** opens a furrow **162** in the soil **138**, and the depth of the furrow **162** is set by planting depth actuator assembly **154**, which, itself, controls the offset between the lowest parts of gauge wheels **116** and disc opener **114**. Seeds are dropped through seed tube **120**, into the furrow **162** and closing wheels **118** close the furrow **162**, e.g., push soil back into the furrow **162**.

[0088] As the seeds are dropped through seed tube **120**, they can be sensed by seed sensor **122**. Some examples of seed sensor **122** are described in greater detail below. Some examples of seed sensor **122** may include an optical or reflective sensor, which includes a radiation transmitter component and a receiver component. The transmitter component emits electro-magnetic radiation and the receiver component then detects the radiation and generates a signal indicative of the presence or absence of a seed adjacent the sensors. In another example, row unit **106** may be provided with a seed firmer that is positioned to travel through the furrow **162**, after seeds are placed in furrow **162**, to firm the seeds in place. A seed sensor can be placed on the seed firmer and generate a sensor signal indicative of a seed. Again, some examples of seed sensors are described in greater detail below.

[0089] The present description proceeds with respect to the seed sensor being located to sense a seed passing it in seed tube **120**, but this is for the sake of example only. Material application control system **113** illustratively receives a signal from seed sensor **122**, indicating that a seed is passing sensor **122** in seed tube **120**. It then determines when to actuate actuator **109** so that material being applied through application assembly **117** (and out distal tip **119** of application assembly **117**) will be applied at a desired location relative to the seed in trench or furrow **162**. This is all described in greater detail herein as well. One brief example will be described now, by way of overview.

[0090] Material application control system **113** illustratively is programmed with, or detects a distance, e.g., a longitudinal distance, that the distal tip **119** is from the exit end **121** of seed tube **120**. It also illustratively senses, or is provided (e.g., by another component, such as a GPS unit or a tractor, etc.), the ground speed of row unit **106**. As the row units **106** on an implement being towed by a prime mover (e.g., a tractor) may move faster or slower than the tractor during turns, particularly as the width of the implement increases, the material application control system **113** may sense or be provided the ground speed of each row unit **106** of the implement. By way of example, the material application control system **113** may sense or be provided information when the implement is turning right indicating that the rightmost row unit **106** is travelling slower, i.e., has a lower ground speed, than the leftmost row unit **106**. Further, the material application control system **113** detects, is provided, or is programmed with, system data indicating the responsiveness of actuator **109** under certain conditions (such as under certain temperature conditions, certain humidity conditions, certain elevations, when spraying a certain type of fluid, etc.) and it also detects, is provided, or programmed with one or more properties of the material being applied through actuator **109** (as this may affect the speed at which actuator **109** responds, the time it takes

for the material to travel through application assembly **117** to the distal **8** tip **119** and be applied to furrow **162**, etc.). Further, material application control system **113** illustratively detects (or is provided with a sensor signal indicative of) the forward speed of row unit **106** in the direction generally indicated by arrow **160**.

[0091] With this type of information, once system **113** receives a seed sensor signal indicating that a seed is passing sensor **122** in seed tube **120**, system **113** determines the amount of time it will take for the seed to drop through the outlet end of seed tube **121** and into furrow **162** to reside at its final seed location and position in furrow **162**. It then determines when tip **119** will be in a desired location relative to that final seed location and it actuates valve **109** to apply the material at the desired location. By way of example, it may be that some material is to be applied directly on the seed. In that case, system **113** times the actuation of actuator **109** so that the applied material will be applied at the seed location. In another example, it may be desirable to apply some material at the seed location and also a predetermined distance on either side of the seed location. In that case, system **113** controls the signal used to control actuator **109** so that the material is applied in the desired fashion. In other examples, it may be that the material is to be applied at a location between seeds in furrow **162**. By way of example, relatively high nitrogen fertilizer may be most desirably applied between seeds, instead of directly on the seed. In that case, system **113** has illustratively been programmed with the desired location of the applied material, relative to seed location, so that it can determine when to actuate actuator **109** in order to apply the material between seeds. Further, as discussed above, actuator **109** can be actuated to dispense material at a varying rate. It can dispense more material on the seed location and less at locations spaced from the seed location, or vice versa, or according to other patterns.

[0092] It will be noted that a wide variety of different configurations are contemplated herein. For instance, in one example, FIG. **2** shows that actuator **109** may be placed closer to the distal tip **119** (such as indicated by actuator **109A** and **109C**). In this way, there is less uncertainty as to how long it will take the material to travel from the actuator **109A** and **109C** to the distal tip **119**. In yet another example, the valve is disposed at a different location (such as on seed tube **120**) as indicated by actuator **109B** and **109D**. In those scenarios, again, actuator **109B** and **109D** are closer to the distal tip **119B** and the material may be applied before and/or after the seed drops into furrow **162**. For instance, when seed sensor **120** detects a seed, system **113** may be able to actuate valve **109B** or **109D** to apply material to furrow **162**, before the seed exits the exit end **121** of seed tube **120**. However, by the time the seed drops through distal end **121** of seed tube **120**, the final seed location may be directly on the applied material. In yet another example, system **113** can control actuator **109B** or **109D** so that it applies material, but then stops applying it before the seed exits distal end **121**. In that case, the material may be applied at a location behind the seed in furrow **162**, relative to the direction indicated by arrow **160**. This actuation timing enables the material to be applied between seeds, on seeds, or elsewhere. All of these and other configurations are contemplated herein.

[0093] FIG. **2A** is a side perspective view of an applicator unit **105**. Some items are similar to those shown in FIG. **2** and they are similarly numbered. Briefly, in operation, applicator unit **105** attaches to a side-dress bar that is towed behind a towing vehicle **94**, so unit **105** travels between rows (if the rows are already planted). However, instead of planting seeds, it simply applies material at a location between rows of seeds (or, if the seeds are not yet planted, between locations where the rows will be, after planting). When traveling in the direction indicated by arrow, disc opener **114** (in this example, it is a single disc opener) opens furrow **162** in the ground **136**, at a depth set by gauge wheel **116**. When actuator **109** is actuated, material is applied in the furrow **162** and closing wheels **118** then close the furrow **162**.

[0094] As unit **105** moves, material application control system **113** controls actuator **109** to dispense material. This can be done relative to seed or plant locations, if they are sensed or are already known or have been estimated. It can also be done before the seed or plant locations are

known. In this latter scenario, the locations where the material is applied can be stored so that seeds can be planted later, relative to the locations of the material that has been already dispensed. [0095] FIG. 2A shows that actuator **109** can be mounted to one of a plurality of different positions on unit **105**. Two of the positions are shown at **109G** and **109H**. These are examples and the actuator **109** can be located elsewhere as well. Similarly, multiple actuators can be disposed on unit **105** to dispense multiple different materials or to dispense it in a more rapid or more voluminous way than is done with only one actuator **109**.

[0096] FIG. 3 is similar to FIG. 2, and similar items are similarly numbered. However, instead of the seed delivery system being a seed tube **120**, which relies on gravity to move the seed to the furrow **162**, the seed delivery system shown in FIG. 3 is an assistive seed delivery system **166**. Assistive seed delivery system **166** also illustratively has a seed sensor **122** disposed therein. Assistive seed delivery system **166** captures the seeds as they leave seed meter **124** and moves them in the direction indicated by arrow **168** toward furrow **162**. System **166** has an outlet end **170** where the seeds exit assistive system **166**, into furrow **162**, where they again reach their final resting location.

[0097] In such a system, material application control system **113** considers the speed at which delivery system **166** moves the seed from seed sensor **122** to the exit end **170**. It also illustratively considers the speed at which the seed moves from the exit end **170** into furrow **162**. For instance, in one example the seed simply drops from exit end **170** into furrow **162** under the force of gravity. In another example, however, the seed can be ejected from delivery system **166** at a greater or lesser speed than that which would be reached under the force of gravity. Similarly, it may be that the seed drops straight downward into furrow **162** from the outlet end **170**. In another example, however, it may be that the seed is propelled slightly rearwardly from the outlet end **170**, to accommodate for the forward motion of the row unit **106**, so that the travel path of the seed is more vertical and so the seed rolls less once it reaches the furrow. Further, the seed can be ejected rearwardly and trapped against the ground by a trailing member (such as a pinch wheel) which functions to stop any rearward movement of the seed, after ejection, and to force the seed into firm engagement with the ground. Again, FIG. 3 also shows that valve **109** can be placed at any of a wide variety of different locations, some of which are illustrated by values **109A**, **109B**, **109C** and **109D**. There can be a more than one seed sensor, seed sensors of different types, different locations for seed sensors, etc.

[0098] FIG. 4 is similar to FIG. 3 and similar items are similarly numbered. However, in FIG. 4, row unit **106** is also provided with members **172** and/or **174**. Members **172** and/or **174** can be spring biased into engagement with the soil, or rigidly attached to the frame of row unit **106**. In one example, member **172** can be a furrow shaper, which contacts the soil in the area within or closely proximate the furrow, and immediately after the furrow is opened, but before the seed is placed therein. Member **172** can thus contact the side(s) of the furrow, the bottom of the furrow, an area adjacent the furrow, or other areas. It can be fitted with a sensor **176**, e.g., seed sensor **176**, as well. [0099] In another example, member **172** can be positioned so that it moves through the furrow after the seed is placed in the furrow. In such an example, member **172** may act as a seed firmer, which firms the seed into its final seed location.

[0100] In either case, member **172** can include a seed sensor **176**, which senses the presence of the seed. It may be an optical sensor, which optically senses the seed presence as member **172** moves adjacent to, ahead of, or over the seed. It may be a mechanical sensor that senses the seed presence, or it may be another type of sensor that senses the presence of the seed in the furrow. Sensor **176** illustratively provides a signal to material application control system **113** indicating the presence of the sensed seed.

[0101] In such an example, it may be that actuator **109** is placed at the location of actuator **109E**, shown in FIG. 4, and the outlet end of the application assembly is shown at **119C**. In the example shown in FIG. 4, outlet end **119C** is shown closely behind member **172** relative to the direction

indicated by arrow **160**. It can be disposed on the opposite side of member **172** as well (such as forward of member **172** in the direction indicated by arrow **160**). In such an example, the seed sensor senses the seed at a location that corresponds to its final seed location, or that is very closely proximate its final seed location. This may increase the accuracy with which seed sensor senses the final seed location.

[0102] Also, in the example shown in FIG. **4**, row unit **106** can have member **174** in addition to, or instead of, member **172**. Member **174** can also be configured to engage the soil within, or closely proximate, the trench or furrow. It can have a seed sensor **178** that senses the presence of a seed (or a characteristic from which seed presence can be derived). It can be placed so that it closely follows the exit end **121** of the seed tube **120**, or the exit end **170** of the assistive delivery system **166**. Also, actuator **109** can be placed at the position illustrated at **109F**.

[0103] FIG. **5** shows one example of a rotatable mechanism that can be used as part of the seed metering system (or seed meter) **124**. The rotatable mechanism includes a rotatable disc, or concave element, **180**. Rotatable element **180** has a cover (not shown) and is rotatably mounted relative to the frame of the row unit **106**. Rotatable element **180** is driven by a motor (not shown) and has a plurality of projections or tabs **182** that are closely proximate corresponding apertures **184**. A seed pool **186** is disposed generally in a lower portion of an enclosure formed by rotating mechanism **180** and its corresponding cover. Rotatable element **180** is rotatably driven by its motor (such as an electric motor, a pneumatic motor, a hydraulic motor, etc.) for rotation generally in the direction indicated by arrow **188**, about a hub. A pressure differential is introduced into the interior of the metering mechanism so that the pressure differential influences seeds from seed pool **186** to be drawn to apertures **184**. For instance, a vacuum can be applied to draw the seeds from seed pool **186** so that they come to rest in apertures **184**, where the vacuum holds them in place.

Alternatively, a positive pressure can be introduced into the interior of the metering mechanism to create a pressure differential across apertures **184** to perform the same function.

[0104] Once a seed comes to rest in (or proximate) an aperture **184**, the vacuum or positive pressure differential acts to hold the seed within the aperture **184** such that the seed is carried upwardly generally in the direction indicated by arrow **188**, from seed pool **186**, to a seed discharge area **190**. It may happen that multiple seeds are residing in an individual seed cell. In that case, a set of brushes or other members **194** that are located closely adjacent the rotating seed cells tend to remove the multiple seeds so that only a single seed is carried by each individual cell. Additionally, a seed sensor **193** can also illustratively be mounted adjacent to rotating element **180**. It generates a signal indicative of seed presence and this may be used by system **113**, as will be discussed in greater detail below.

[0105] Once the seeds reach the seed discharge area **190**, the vacuum or other pressure differential is illustratively removed, and a positive seed removal wheel or knock-out wheel **191**, can act to remove the seed from the seed cell. Wheel **191** illustratively has a set of projections **195** that protrude at least partially into apertures **184** to actively dislodge the seed from those apertures. When the seed is dislodged (such as seed **171**), it is illustratively moved by the seed tube **120**, seed delivery system **166** (some examples of which are shown above in FIGS. **2-4** and below in FIGS. **6** and **7**) to the furrow **162** in the ground.

[0106] FIG. **6** shows an example of a seed metering system and a seed delivery system, in which the rotating element **180** is positioned so that its seed discharge area **190** is above, and closely proximate, seed delivery system **166**. In the example shown in FIG. **6**, seed delivery system **166** includes a transport mechanism such as a belt **200** with a brush that is formed of distally extending bristles **202** attached to belt **200** that act as a receiver for the seeds. Belt **200** is mounted about pulleys **204** and **206**. One of pulleys **204** and **206** is illustratively a drive pulley while the other is illustratively an idler pulley. The drive pulley is illustratively rotatably driven by a conveyance motor, which can be an electric motor, a pneumatic motor, a hydraulic motor, etc. Belt **200** is driven generally in the direction indicated by arrow **208**

[0107] Therefore, when seeds are moved by rotating element **180** to the seed discharge area **190**, where they are discharged from the seed cells in rotating element **180**, they are illustratively positioned within the bristles **202** by the projections **182** that push the seed into the bristles **202**. Seed delivery system **166** illustratively includes walls that form an enclosure around the bristles **202**, so that, as the bristles **202** move in the direction indicated by arrow **208**, the seeds are carried along with them from the seed discharge area **190** of the metering mechanism, to a discharge area **210** either at ground level, or below ground level within a trench or furrow **162** that is generated by the furrow opener **114** on the row unit **106**.

[0108] Additionally, a seed sensor **203** is also illustratively coupled to seed delivery system **166**. As the seeds are moved within bristles **202**, sensor **203** can detect the presence or absence of a seed. It should also be noted that while the present description will proceed as having sensors **122**, **193** and/or **203**, it is expressly contemplated that, in another example, only one sensor is used. Or additional sensors can also be used. Similarly, the seed sensor **203** shown in FIG. **6** can be disposed at a different location, such as that shown at **203A**. Having the seed sensor closer to where the seed is ejected from the system can reduce error in identifying the final seed location. Again, there can be multiple seed sensors, different kinds of seed sensors, and they can be located at many different locations.

[0109] FIG. **7** is similar to FIG. **6**, except that seed delivery system **166** does not include a belt with distally extending bristles. Instead, it includes a flighted belt (transport mechanism) in which a set of paddles **214** form individual chambers (or receivers), into which the seeds are dropped, from the seed discharge area **190** of the metering mechanism. The flighted belt moves the seeds from the seed discharge area **190** to the exit end **210** of the flighted belt, within the trench or furrow **162**.

[0110] There are a wide variety of other types of delivery systems as well, that include a transport mechanism and a receiver that receives a seed. For instance, they include dual belt delivery systems in which opposing belts receive, hold, and move seeds to the furrow, a rotatable wheel that has sprockets, which catch seeds from the metering system and move them to the furrow, multiple transport wheels that operate to transport the seed to the furrow, and an auger, among others. The present description will proceed with respect to an endless member (such as a brush belt, a flighted belt) and/or a seed tube, but many other delivery systems are contemplated herein as well.

[0111] Before continuing with the description of applying material relative to seed location, a brief description of some examples of seed sensors **122**, **193** and **203** will first be provided. Sensors **122**, **193** and **203** are illustratively coupled to seed metering system **124** and seed delivery system **120**, **166**. Sensors **122**, **193** and **203** sense an operating characteristic of seed metering system **124** and seed delivery systems **120**, **166**. In one example, sensors **122**, **193** and **203** are seed sensors that are each mounted at a sensor location to sense a seed within seed tube **120**, seed metering system **124**, and delivery system **166**, respectively, as the seed passes the respective sensor location. In one example, sensors **122**, **193**, and **203** are optical or reflective sensors and thus include a transmitter component and a receiver component. The transmitter component emits electromagnetic radiation into seed tube **120**, seed metering system **180**, and/or delivery system **166**. In the case of a reflective sensor, the receiver component then detects the reflected radiation and generates a signal indicative of the presence or absence of a seed adjacent to sensor **122**, **193**, and **203** based on the reflected radiation. With other sensors, radiation such as light, is transmitted through the seed tube **120**, seed metering system **124**, or the delivery system **166**. When the light beam is interrupted by a seed, the sensor signal varies, to indicate a seed. Thus, each sensor **122**, **193**, and **203** generates a seed sensor signal that pulses or otherwise varies, and the pulses or variations are indicative of the presence of a seed passing the sensor location proximate the sensor.

[0112] For example, in regards to sensor **203**, bristles **202** pass sensor **203** and are colored to absorb a majority of the radiation emitted from the transmitter. As a result, absent a seed, reflected radiation received by the receiver is relatively low. Alternatively, when a seed passes the sensor location where sensor **203** is mounted, more of the emitted light is reflected off the seed and back

to the receiver, indicating the presence of a seed. The differences in the reflected radiation allow for a determination to be made as to whether a seed is, in fact, present. Additionally, in other examples, sensors **122**, **193**, and **203** can include a camera and image processing logic that allow visual detection as to whether a seed is present within seed metering system **124**, seed tube **120**, and/or seed delivery system **166**, at the sensor location proximate the sensor. They can include a wide variety of other sensors (such as RADAR or LIDAR sensors) as well.

[0113] For instance, where a seed sensor is placed on a seed firmer, it may be mechanical or other type of sensor that senses contact with the seed as the sensor passes over the seed. Also, while the speed of the seed in the delivery system (or as it is ejected) can be identified by using a sensor that detects the speed of the delivery system, in some examples, the speed and/or other characteristics of movement of the seed can be identified using seed sensors. For instance, one or more seed sensors can be located to sense the speed of movement of the seed, its trajectory or path, its instantaneous acceleration, its presence, etc. This can be helpful in scenarios in which the seed delivery system changes speed.

[0114] FIG. **8** is a block diagram showing one example of material application control system **113** in more detail. In the example, it is assumed that actuators **109** are valves and that the material to be applied is pumped to actuators **109** by pump **115**. Of course, this is just one example and actuators **109** could be pumps or other actuators as well. In the example shown in FIG. **8**, system **113** illustratively includes one or more processors **250**, communication system **252**, data store **254**, valve actuation identification system **256**, valve control signal generator **258**, fluid pressure control signal generator **260**, operator interface logic **262**, and it can include a wide variety of other items **264**. FIG. **8** also shows that valve actuation identification system **256** can include event driven processing system **266** and/or frequency driven processing system **268**. It illustratively includes queue generation system **270**, and it can include a wide variety of other items **272**. Fluid pressure control signal generator **260** illustratively includes pump pressure controller **274** and/or variable orifice controller **276**. It can include other items **278** as well.

[0115] Data store **254** can include a wide variety of different types of information. The information can be pre-configured or pre-programmed into data store **254**, or it can be sensed by sensors and stored in data store **254** intermittently (such as periodically, or it can be regularly updated based on those sensor inputs). By way of example, data store **254** illustratively includes system information **280**, material information **282**, planting information **284**, and it can include a wide variety of other information **286**. System information **280** illustratively includes information about the planter **100**, the delivery system **120**, **166**, and/or other items that are used to plant seed. It includes information that can be used to identify when to apply material relative to the seed location of a seed in furrow **162**. Therefore, it can include information that allows valve actuation identification system **256** to identify a timing of when the valves **109** should be opened to apply the material, relative to the seed location.

[0116] As examples, system information **280** can include machine dimensions **282**. These dimensions can include dimensions that indicate where the valve is placed relative to the outlet opening of the seed delivery system. It can include dimensional information indicating where the valve is placed relative to the seed sensor. It can include information such as the size, e.g., one or more dimensions, of the seed delivery system **120**, **166**, so that the distance between the seed sensor and the furrow **162** can be identified. It can include a wide variety of other machine dimension information **282** as well.

[0117] System information **280** can also include machine part speed information **284**. This information can include the speed of an endless member used to deliver seed (such as the brush belt **200** delivery system or the flighted belt **214** delivery system). Where the speed of those mechanisms changes with the ground speed of the planter, information **284** can identify the different belt speeds relative to this sensed ground speed or provide a correlation so the belt speed can be calculated given the ground speed. It can include other machine part speed information as

well such as the speed of metering system **124**, etc.

[0118] System information **280** also illustratively includes valve/actuator responsiveness information **286**. Information **286** can indicate the responsiveness of the actuator **109** that is being used to apply the material. In one example, the actuator **109** may be a solenoid valve so that there is a latency between when a valve open signal is applied and when the solenoid actually opens the valve. The same is true for closing the valve. That is, there may be a latency between when the valve close signal is applied and when the valve actually closes. In addition, the actuator responsiveness may change based upon the particular properties of the material that is flowing through the valve. It may change based upon the type of nozzle that is being used, and it may change under different ambient conditions (e.g., it may take longer to cycle when the weather is cold than when the weather is warm, etc.). The valve/actuator responsiveness information **286** can indicate valve responsiveness given these and other types of information. System information **280** can include a wide variety of other information **288**, as well.

[0119] Material information **282** illustratively identifies properties of the material that is being applied by the system. For instance, material information **282** may include an exit velocity information **290** that identifies a velocity at which the material exits the valve or actuator or nozzle that is being used to apply it. Again, the exit velocity of the material may change based on the material, under different conditions, and the exit velocity information **290** may indicate this as well.

[0120] Where the material is a liquid material, then material information **282** may also include viscosity information **292**, which identifies the viscosity or other liquid properties of the material. The viscosity may change at different temperatures or under other circumstances, and viscosity information **292** will illustratively indicate this. The material information **282** can include a wide variety of other information **294** indicative of other properties of the material being applied.

[0121] Planting information **284** can include a wide variety of different types of information indicative of the planting operation. For example, it can include target population information **296** that identifies a target seed population. It can include target application rate information **298** that indicates a target application rate for the material being applied. It can include application placement relative to seed information **300** that indicates placement properties of the application, or application pattern, for the material. For instance, where the material is liquid material and is being applied in a band of liquid, it may indicate the length of each application band to be applied by the valve or actuator. It may indicate a placement of that band relative to the seed location. For instance, where the band is to be four inches long, the placement information may indicate a relative placement of the center of the band (along its longitudinal length) relative to seed location. In this way, where the material is to be applied at the seed location, then the center of the band will illustratively correspond to the seed location. However, where the material is to be applied at a location other than the seed location, then the center of the band will illustratively be offset from the seed location by a desired amount. Similarly, the application rate may vary within an application band. For instance, the material may be applied more heavily near the center of the band than at either end of the band or vice versa. This type of information can be included in information **300**. The planting information **284** can include a wide variety of other information **302**, indicative of the planting operation, as well.

[0122] FIG. **8** also shows that material application control system **113** illustratively receives one or more seed sensor signals **304** that may be generated from one or more of seed sensors **122**, **193** or **203**, or another seed sensor located at a different location. Seed sensor signal **304** may illustratively indicate when the particular sensor senses the presence of a seed.

[0123] FIG. **8** also shows that, in one example, system **113** includes an input from ground speed sensor **306**, which senses the ground speed of row unit **106**. The sensor may be located on the towing vehicle or elsewhere, and illustratively provides a sensor signal indicative of ground speed.

[0124] As discussed above, some of the information stored in data store **254** may be pre-configured or pre-defined. In another example, it may be sensed by various sensors. Therefore, in one

example, system **113** receives the valve/actuator responsiveness information **286** from a valve/actuator responsiveness sensor **308**. Sensor **308** may illustratively sense the movement of a solenoid, or other actuator, to sense how responsive the actuator or valve is to the control signals that are applied to it. Thus, it may provide a signal indicative of the latency between applying a valve open signal (or pump on signal) and when the valve actually opens (or the pump turns on), and indicative of latency between applying a valve close signal (or pump off signal) and when the valve actually close (or the pump turns off), among other things.

[0125] The machine part speeds information **284** may also be sensed by machine part speed sensors **310**. Those sensors may illustratively sense the speed at which the seed delivery system **166** is moving, the speed at which the seed metering system **124** is moving, or the speed of a wide variety of other machine parts that are needed to generate the actuator signals used to apply material, as desired.

[0126] Similarly, the material information **282** can be sensed as well, by material property sensors **312**. Those sensors may sense such things as material temperature, material viscosity, among other things.

[0127] System **113** can also receive an input from a position sensor **314**. Position sensor **314** may include a GPS system, a LORAN system, a cellular triangulation system, or another type of position system that provides a signal indicative of the position of the sensor **314** in a global or local coordinate system. Such a sensor can also be used to determine ground speed, among other things.

[0128] System **113** also illustratively receives an input from a planting start signal generator **316**. Generator **316** can cause any of a wide variety of different signals from any of a wide variety of different sensors, actuators or control inputs, indicating that the planting operation has begun. For instance, it may be that the operator **92** of the towing vehicle **94** depresses a button or provides another input through a user interface mechanism **96** to start the planting operation. This may be sensed by signal generator **316** and used to generate a signal indicating that the planting operation has begun. In another example, generator **316** may include a sensor indicating that either metering system **124** or seed delivery system **166** has begun moving. In another example, generator **316** may include a sensor indicating that a seed has passed the sensors **122**, **193** and/or **203**. It may generate a signal based on this, which is indicative of the planting operation beginning.

[0129] System **113** can also receive an input from verification trigger generator **318**. Generator **318** provides an input, under certain circumstances, which are described in greater detail elsewhere herein, indicating when system **113** is to perform a verification operation, especially where frequency driven processing system **268** is used.

[0130] When a verification operation is to be performed, signals may be received by system **113** from a variety of different verification sensors **320**. Examples of these sensors are described elsewhere herein.

[0131] Valve control signal generator **258** illustratively generates control signals **322** that are sent and/or applied to the valves or actuators **109** in order to apply the material. This is also described in greater detail herein.

[0132] In some examples, the material being applied is a fluid that is provided as fluid under pressure by pump **115**. In that case, the pump displacement may be controlled to control the pressure. Similarly, the valves or nozzles may be provided with a variable orifice. In that case, the variable orifice may be controlled as well. Therefore, fluid pressure control signal generator **260** illustratively generates outputs **324** that illustratively control the pump and/or variable orifice, in those scenarios. In a scenario in which actuators **109** are pumps, outputs **324** can control those pumps as well.

[0133] System **113** can include a wide variety of other inputs and it can generate a wide variety of other outputs as well. This is indicated by block **326**.

[0134] FIG. **8** also shows that, in one example, operator interface logic **262** may generate signals

that are output to operator interface mechanisms **96**, and it can receive information from those mechanisms as well. This is indicated by block **328**.

[0135] Before describing the overall operation of material application control system **113**, a brief description of some of the items in system **113** will first be provided. Communication system **252** can be any of a wide variety of different types of communication systems that allow material application control system **113** to communicate with a control system on towing vehicle **94** and/or operator interface mechanisms **96**. It can also allow items on system **113** to communicate with one another, and to communicate with one or more different remote computing systems. Therefore, for instance, communication system **252** can include a controller area network—CAN—communication system, a local area network, a wide area network, a near field communication system, a cellular communication, or any of a wide variety of other networks or combinations of networks and communication systems.

[0136] Valve actuation identification system **256** illustratively receives some of the inputs discussed above and identifies when the valves **109** are to be actuated in order to apply material at a desired location relative to the location of the seeds being placed in furrow **162**. In one example, it includes event driven processing system **266**, which determines when the valves are to be actuated based on an event, such as based upon receiving an indication from seed sensors signal **304** that a seed has been sensed. For instance, referring to FIG. **3**, assume that seed sensor **122** detects a seed in delivery system **166**. Event driven processing system **266** calculates a time that it will take that seed to travel to the outlet end **170** of delivery system **166**, based upon the speed of delivery system **166**, as indicated by machine part speed sensors **310**. It then calculates a time delay, during which the seed will move from the outlet end **170** of the seed delivery system **166** to its final resting place is furrow **162**. Then, based upon the location of the valve **109** on row unit **106**, the valve/actuator responsiveness, the exit velocity or viscosity of the material being applied, the ground speed of row unit **106**, and based upon the desired placement of the material relative to the seed location (as indicated by the corresponding information in data store **254** or based on the inputs from the sensors discussed above), event driven processing system **266** calculates when the valves **109** should be actuated in order to apply the material at the desired place, relative to the seed location.

[0137] In another example, valve actuation identification system **256** can include frequency driven processing system **268**. Frequency driven processing system **268** need not necessarily receive an input from a seed sensor, but instead is a controlled system, e.g., a highly controlled system, that knows the speeds of the various parts of row unit **106**, it knows the valve placement on row unit **106**, valve responsiveness, and the material properties. Therefore, frequency driven processing system **268** knows, in an a priori fashion, when seeds will be placed in the furrow **162**, and thus when to actuate the valves **109**. In such a tightly controlled system, frequency driven processing system **268** simply needs to know when the planting operation begins, e.g., when the first seed is deposited into the furrow **162**. It can then calculate the theoretical time when seeds will be deposited in the furrow, and thus when to actuate the valves to apply the material at the desired location relative to the seeds. Therefore, in that scenario, system **268** receives a signal from planting start signal generator **316**, which is indicative of when the planting operation begins. Based on that information, frequency driven processing system **268** calculates when the valves **109** are to be actuated and provides an indication of that to valve control signal generator **258**, which generates the corresponding valve control signals.

[0138] Also, in one example, it may be that frequency driven processing system **268** occasionally verifies that it is actuating the valves according to the correct pattern, e.g., that the timing calculated by the system **268** aligns properly with the deposition of seeds into the furrow **162** (relative to the seeds in the furrow **162**). In that case, frequency driven processing system **268** may intermittently receive an input from seed sensor signal **304** identifying where an actual seed was sensed. It can then determine whether the a priori pattern it is using to actuate valves **109** is correct based upon the actual seed sensor signal. In some examples, the frequency driven processing

system **268** uses a periodically sensed single seed (e.g., the seed sensor signal **304** identifies and reports a single seed in one or more of space and time). In some examples, the frequency driven processing system **268** uses a periodically sensed multiple seeds (e.g., the seed sensor signal **304** identifies and reports multiple seeds, such as strings of 2 seeds, 3 seeds 4 seeds 5 seeds, 6 seeds, or any other number of seeds necessary or helpful to the frequency driven processing system **268**). In some examples, the frequency of verification by the frequency driven processing system **268** is loosely inversely related to the number of seeds reported by the seed sensor signal **304**. For example, verification may occur more frequently when only a single seed is sensed and reported, whereas verification may occur less frequently when two or more seeds are sensed and reported. If a correction is needed, then it can make that correction to the pattern it is using, and use the corrected pattern going forward. The frequency driven processing system **268** can intermittently re-verify that pattern as well.

[0139] Thus, in one example, frequency driven processing system **268** receives an input from verification trigger generator **318** indicating that a verification operation is to be performed. The triggers can include one or more of a wide variety of different triggers (the system may be initiated by a single trigger or it may be initiated when only two or more triggers are received). For instance, the system may be triggered to verify its a priori pattern after a certain number of seeds have been planted (the number of seeds may be identified substantially exactly using a seed sensor, or the number of seeds may be estimated or calculated using system inputs, such as, but not limited, to seed population and prime mover travel speed). It may be triggered after a certain distance has been traveled by row unit **106** (as mentioned, the triggering distance may vary based on the set seed population, e.g., a higher seed population may trigger the system after a shorter distance than a lower seed population). It may be triggered after a specific time has elapsed. These are just examples of triggers. Once the verification operation has been triggered, then frequency driven processing system **268** may receive other sensor signal inputs from verification sensors **320**, that are used to verify the pattern that system **268** is using to apply the material. Some of these are discussed in greater detail elsewhere herein.

[0140] In another example, queue generation system **270** generates a set of valve actuation timing signals, indicating when valves **109** should be actuated, for a future sequence of actuations. For instance, queue generation system **270** may generate a queue of timing signals that are generated either by event driven processing system **266** or frequency driven processing system **268**, and provide that plurality of queued timing signals to valve control signal generator **258**. Valve control signal generator **258** can receive that set of signals and generate valve actuator control signals based upon the queued sequence of timing signals. In this way, the network bandwidth for communication between valve actuation identification system **256** and valve control signal generator **258** need not be as high. By communicating a plurality of valve actuation timing signals as a queued sequence of signals, the frequency with which those signals need to be sent can be greatly reduced over an implementation in which each valve actuation timing signal is sent, individually and separately, for each valve actuation.

[0141] Valve control signal generator **258** can generate the valve control signals in a wide variety of different ways. It can generate those signals and apply them through a hardware wiring harness, through wireless communication, or in other ways.

[0142] In some examples, the fluid pressure of the material to be applied is to be controlled. For instance, by increasing the fluid pressure, this may increase the exit velocity of the material as it is applied by the valve or nozzle being controlled. Similarly, where the valve or nozzle is not directed vertically, but has a horizontal component to its orientation, increasing the fluid pressure may change the trajectory of the fluid after it exits the valve or nozzle. This will change the location on the ground where the material is applied.

[0143] In the same way, where the valve or nozzle is provided with a variable orifice, varying the orifice may change the trajectory or exit velocity of the material as well. Thus, pump pressure

controller **274** can control the pump pressure to obtain a desired exit velocity and/or trajectory of the material being applied. Variable orifice controller **276** can variably control the orifice to also achieve a desired exit velocity and/or trajectory of the applied material. In some examples, variable orifice controller **276** and pump pressure controller **274** can work in concert to control the exit velocity and/or trajectory of the material being applied.

[0144] Operator interface logic **262** can generate information that is provided to operator interface mechanisms **96** so that operator **92** can interact with that information. Similarly, operator interface logic **262** can receive information indicative of operator inputs from operator **92** through operator interface mechanisms **96**. It can communicate that information to the various items or components on/of material application control system **113**.

[0145] FIG. **9** is a flow diagram illustrating one example of the overall operation of material application control system **113**. It is first assumed that the planting machine (e.g., row unit **106**) begins the planting operation. This is indicated by block **340** in the flow diagram of FIG. **9**. Based upon the various inputs, valve actuation identification system **256** calculates when to actuate the valves to apply the material relative to the seed location in the furrow **162**. This is indicated by block **342**. In one example, the material can be liquid. This is indicated by block **344**. In one example, system **256** can determine when to actuate the valves using event driven processing system **266**. This is indicated by block **346** in the flow diagram of FIG. **9**. In another example, system **256** can determine when the valves are to be actuated using frequency driven processing system **268**. This is indicated by block **348**. In one example, frequency driven processing system **268** can be used in conjunction with event driven processing system **266**. Further, the timing indicators, indicating when the valves **109** are to be actuated, may be sent individually or they may be grouped together by queue generation system **278** and sent, as groups, to valve control signal generator **258**. Sending them individually or queuing the actuation events and sending them to valve control signal generator **258**, in groups, is indicated by block **350** in the flow diagram of FIG. **9**. Valve actuation identification system **256** can identify when the valves are to be actuated and output an indication of that to valve control signal generator **258**, in other ways as well. This is indicated by block **352** in the flow diagram of FIG. **9**.

[0146] Valve control signal generator **258** then generates control signals to control valve actuation, based upon the output from valve actuation identification system **256**. The control signals control valves **109** so that the material being applied is applied at the desired location in the furrow, e.g., relative to the seed location. Generating control signals to control valve actuation is indicated by block **354** in the flow diagram of FIG. **9**.

[0147] In one example, there is a single valve that controls a single nozzle, per row being planted. Controlling a single valve is indicated by block **356**. In another example, it may be that the nozzles or valves do not have a high enough bandwidth, e.g., max operating frequency, in order to apply the material at the desired frequency. In that case, there may be multiple valves per row being planted that can be controlled in order to achieve a higher application rate. These same types of configurations can be used when actuators **109** are pumps instead of valves.

[0148] For example, the seed population (e.g., seeds/acre) and row spacing are used to determine the seed-to-seed spacing in the furrow **162**. This spacing, and the travel speed of planter **100**, can be used to identify how quickly a valve is to respond in order to administer per-seed application (e.g., on each seed or between adjacent seeds/grains). A target seed rate of, for instance, 36,000 seeds/acre, with the planter traveling at 10 mph and with a thirty-inch row spacing, means that a nozzle on the planter will pass thirty seeds per second, or one seed every thirty three milliseconds. Some current fertilizer valves operate at about 10-15 Hz. Additionally, the opening time and closing time for some current valves can be approximately 7-8 milliseconds. This is often not fast enough to place fertilizer (or other material) on a per seed basis. Thus, the present system can have two or more valves (e.g., solenoids or other valves) per row operating out of phase (e.g., evenly out of phase) with one another to increase the overall frequency with which material can be applied in

a row. While one valve is closing, another can be opening. Each valve can have its own nozzle or multiple valves can share a nozzle or multiple valves can provide material to multiple nozzles. These multiple valves per row can be placed proximate one another in the valve locations identified above in FIG. 2-4 or elsewhere. They can be controlled using control signals timed as described herein for a single valve, except that the valve control signals can be spread across the multiple valves to obtain the desired material application rate, timing and placement.

[0149] Further, it may be desirable to apply multiple different materials per row. In that case, there may be multiple different valves, per row, each dispensing a different material. Thus, valve actuation identification system **256** can provide an indication as to when to actuate each of the valves to apply the corresponding material, so that it is applied at the desired location relative to the seed, and valve control signal generator **258** generates control signals for the different valves, based upon the output from system **256**. For example, one valve or valve set may apply a first commodity directly to the seed while another valve or valve set may apply a second commodity, e.g., a hot commodity, between seeds. Controlling multiple valves per row is indicated by block **358**. Valve control signal generator **258** can generate control signals to control the valves in a wide variety of other ways as well, and this is indicated by block **360**.

[0150] This continues until the planting operation is complete. This is indicated by block **362** in the flow diagram of FIG. 9.

[0151] FIG. 10 is a block diagram showing one example of event driven processing system **266**, in more detail. System **266** illustratively includes time stamp generator **364**, time delay generation system **366**, travel distance generation system **368**, valve/nozzle time offset generator **370**, pulse timing generator **372**, pulse duration generator **374**, and it can include a wide variety of other items **376**. FIG. 10 also shows that, in one example, event driven processing system **266** receives the one or more seed sensor signals **304**, and endless member speed indicator **284** that indicates the speed of the delivery system **166** and/or meter **124**, delivery system and meter dimension data **282** that indicates such things as the meter and/or delivery system size, the distance that the seed will drop after it exits the delivery system to the furrow, etc. System **266** receives valve/nozzle properties (such as valve location and responsiveness). This corresponds to the information **282**, **284**, and **286** discussed above. It can receive target liquid placement indicator **300**, that identifies where the material is to be applied, e.g., relative to the seed in the furrow. It can receive the material properties **282**. It can also receive an input indicative of ground speed **378**. This can come from ground speed sensor **306** (discussed with respect to FIG. 8) or elsewhere. It can receive a wide variety of other information **380** as well. As discussed above, the inputs to event driven processing system **266** can include information from data store **254** or from various different sensors, or from a combination of those things.

[0152] Time stamp generator **364** illustratively receives seed sensor signal **304** and generates a time stamp indicating when signal **304** indicates the presence of a seed. Time delay generation system **366** then generates a time delay indicative of the amount of time it will take the seed to travel from the particular seed sensor that sensed it, to an outlet opening of the seed delivery system **166** or seed tube **120**. For instance, meter/delivery system delay generator **382** illustratively calculates the amount of time it will take the seed to travel from wherever it was sensed (meter **124**, seed delivery system **120** or **166**, or elsewhere) to the exit end of the seed delivery system, based upon the type of seed delivery system, the type of meter, etc. Where the seed is sensed in the seed meter, generator **382** obtains the speed of the seed meter and the speed of the delivery system **166**, along with the size of both (e.g., the distance the seed must travel at the two different speeds) to identify a time when the seed will exit the seed delivery system. If the seed delivery system **166** is a seed tube **120**, then the travel time through the seed tube will correspond, at least partially, to the acceleration of gravity, as the seed passes through the seed tube (other factors may impact the calculation, such as the forward travel speed of the row unit **106** and the coefficient of friction of both the seed and the inner surface(s) of the seed tube, among others). If the delivery system **166** is an assistive system,

then the time will include the delay of that system in moving the seed from wherever it was sensed, to the outlet end of the delivery system. This may be based on the speed of an endless member, the velocity of a pneumatic assistance system, etc. If the seed sensor is located closer proximate the outlet end of the delivery system, then the time calculated by meter/delivery system delay generator **382** will be less, because the seed will be detected closer to the exit end of the delivery system. Depending on the response time of the valves **109**, a seed sensor may be located as close as possible to the outlet end of the delivery system (or elsewhere, such as on a seed firmer) to minimize, if not eliminate, the time calculated by meter/delivery system delay generator **382**. System **366** can include other items **384** as well.

[0153] In the example where time delay generation system **366** identifies the time delay, then valve/nozzle time offset generator **370** illustratively calculates a time offset corresponding to the responsiveness of the valve being controlled, under the current conditions. For instance, the responsiveness may vary based upon the particular valve or actuator, based on the properties of the material being applied, based upon the ambient conditions, based on the pump pressure, or based on other things. Valve/nozzle time offset generator **370** generates an output indicative of a time offset that corresponds to a latency in actuation of the valve.

[0154] Pulse timing generator **372** then generates a timing output indicative of a time when the valve should be actuated, based upon the time delay generated by meter/delivery system delay generator **382** and the offset generated by valve/nozzle time offset generator **370**. In short, meter/delivery system delay generator **382** calculates the amount of time it will take for the seed to move from where it was sensed to its final seed location in furrow **162**, and valve/nozzle time offset generator **370** will calculate how long it will take to begin applying the material, based upon the properties of the valve or actuator, once the valve actuation control signal is applied. Pulse timing generator **372** then generates a time when the actuator control signal should be applied to the valve/actuator, based upon the delay time generated by generator **382** and the offset generated by generator **370**, and based upon the time stamp generated by time stamp generator **364**.

[0155] Pulse duration generator **374** generates an output indicative of how long the valve should stay on, e.g., open. This can include determining the latency in the valve response between the time that it is commanded to close and when it actually closes. This may vary based upon the type of material being applied, based upon ambient conditions, etc. The two timing signals (the pulse time indicating when the actuator should be actuated, and generated by generator **372**, and the pulse duration output by pulse duration generator **374**) are provided to valve control signal generator **258**. Valve control signal generator **258** generates valve control signals to actuate the valve at the time indicated by pulse timing generator **372**, and to keep the valve actuated for a duration indicated by pulse duration generator **374**. The rate at which the material is applied can also be varied. For example, the valve may be a proportional valve so more or less material can be applied.

[0156] In another example, where the seed metering system or delivery system changes speeds during planting, instead of using time delay generation system **366** (or in addition to it), event driven processing system **266** can include travel distance generation system **368**. Instead of calculating the time that will be needed to move the seed from the location where it was sensed, e.g., in the meter or the seed delivery system, into the furrow, meter/delivery system speed integrator **386** can integrate acceleration (that arises from changes in velocity) to obtain the velocity of the system and it can then integrate the velocity to obtain a signal indicative of the location of the seed (or the distance it has traveled) to determine when the seed exits the seed delivery system, and final seed location estimator **388** determines where the seed will be in its final seed location in furrow **162**.

[0157] As an example, meter/delivery system speed integrator **386** integrates the acceleration and speed of the seed meter (if the seed sensor is disposed on the seed meter), and/or the acceleration and speed of the seed delivery system **166** (if the seed sensor is disposed on the seed delivery system). This provides a distance indicator that indicates the distance traveled by the seed. This

distance is compared to the dimensions of the meter and/or delivery system **166** to determine when the seed has traveled a sufficient distance that it has reached the exit end of the seed delivery system **166**. When this occurs, integrator **386** provides an output indicating that the seed should now be exiting the seed delivery system **166**.

[0158] Final seed location estimator **388** estimates when the seed has reached its final location based upon the distance it must travel from the exit end of the seed delivery system **166** to the bottom of the furrow **162**. It may include factors that accommodate for possible rolling of the seed, or other movement of the seed after it reaches the ground. Final seed location estimator then generates an output indicating that the seed has reached its final location.

[0159] Knowing that the seed is in its final location, valve/nozzle time offset generator **370** can generate an output indicating any time offset corresponding to the valve/actuator latency or responsiveness. Pulse timing generator **372** and pulse duration generator **374** generate the timing for the valve/actuator control signal and its duration, as described above.

[0160] FIG. **11** is a flow diagram showing one example of the operation of event driven processing system **266** (discussed with respect to FIG. **10**), in more detail. It is first assumed that row unit **106** is configured for planting. This is indicated by block **392** in the flow diagram of FIG. **11**. It has thus illustratively sensed or obtained the system information, such as the system dimensions, valve placement, etc. This is indicated by block **394**. It has also illustratively obtained or sensed valve responsiveness as indicated by block **396** and the properties of the material (e.g., liquid) being applied. This is indicated by block **398**. It can receive or detect row spacing as indicated by block **400**, target population as indicated by block **402**, and target application rate as indicated by block **404**. It can detect or receive the application placement. In the present example, it will be assumed that liquid material is to be applied in a band. In that case, it detects the distance from the seed location to the center of the band (in some examples, the valve/nozzle may be laterally adjustable such that the center of the band may be selectively placed relative to an actual or theoretical seed location). This is indicated by block **406**. It can detect or receive the desired band length as indicated by block **408**, and a wide variety of other information as indicated by block **410**.

[0161] At some point, the planting operation begins so that row unit **106** is performing the planting operation. This is indicated by block **412**. Because FIG. **11** is discussing the operation of event driven processing system **266**, that means that controlling the application of the material is based on an event, such as a seed detection. Therefore, system **266** receives the seed sensor signal **304** indicating that a seed has been detected. This is indicated by block **414** in the flow diagram of FIG. **11**. The seed can be detected by a sensor **203** that is on the seed delivery system **166** (such as on the brush belt or flighted belt) as indicated by block **416**. The seed sensor can be sensor **122** on the seed tube **120** as indicated by block **418**. It can be sensor **193** on the seed meter as indicated by block **420**, or it can be arranged so that it detects the seed after it is at its final seed location in the furrow, as indicated by block **422**. It can be placed on or near a seed firmer as indicated by block **424**, or it can be placed in a wide variety of other locations, as indicated by block **426**. The seed can be detected using a camera, as indicated by block **428**. It can be detected using another type of optical sensor, such as the sensors discussed above, as indicated by block **430**. It can be detected using a physical sensor (such as a deflectable finger sensor that deflects when the seed travels past it, as indicated by block **432**. It can be detected using RADAR or LIDAR or a wide variety of other types of sensors as well, and this is indicated by block **434**.

[0162] Event driven processing system **266** also illustratively detects (or is provided) the ground speed **378**. This is indicated by block **436** in the flow diagram of FIG. **11**.

[0163] Event driven processing system **266** then calculates the timing of when to control the valves **109** to apply the material. This is indicated by block **438** in the flow diagram of FIG. **11**. It can do this using the delivery system velocity or timing, such as by using timing delay generation system **366**. Calculating the timing for controlling the valves in this way is indicated by block **440** in the flow diagram of FIG. **11**. It can also do it by using the delivery system travel distance, such as by

using travel distance generation system **368**. This is indicated by block **442** in the flow diagram of FIG. **11**. Calculating the control signal timing using the time delay generation system **366** is discussed in greater detail elsewhere herein, including with respect to FIG. **12**. Calculating the control signal timing using travel distance generation system **368** is discussed in greater detail elsewhere herein, including with respect to FIG. **13**.

[0164] The timing of the valve actuation control signals can be calculated based upon the properties of the liquid being applied (such as the desired exit velocity, viscosity, etc.). This is indicated by block **444**. It can be calculated based on the valve/actuator responsiveness as indicated by block **446**. It can be based upon the desired material placement relative to the final seed location. This is indicated by block **448**. It can be calculated based upon the ground speed of row unit **106**, as indicated by block **450**. It can be calculated based on the valve location (such as the horizontal or vertical location of the valve **109** on row unit **106**). This is indicated by block **452** in the flow diagram of FIG. **11**.

[0165] At block **452**, for instance, the valve may have a camera located on it so that the seed can be sensed in close proximity to the valve. The camera may be on a seed firmer so that it detects the final location of the seed in the furrow. In any of these cases, the valve location on row unit **106** is known, at least relative to other items so that it can be actuated at the appropriate or desired time.

[0166] The timing can be calculated in a wide variety of other ways as well, and based on a wide variety of other criteria. This is indicated by block **454**.

[0167] Once the timing is calculated (of when and for what duration to control the valves to apply the material), at block **438**, this is provided to valve control signal generator **258** (shown in FIG. **8**), which generates valve control signals to control the valves/actuators based upon the calculated timing. This is indicated by block **456** in the flow diagram of FIG. **11**.

[0168] FIG. **12** is a flow diagram illustrating one example of the operation of event driven processing system **266**, where it uses travel distance generation system **368** to calculate the timing for valve actuation. Thus, in the example described with respect to FIG. **12**, time stamp generator **364** receives seed sensor signal **304** and generates a time stamp when signal **304** indicates that a seed has been detected. This is indicated by block **458** in the flow diagram of FIG. **12**.

[0169] Meter/delivery system speed integrator **386** then integrates the meter and/or delivery system acceleration and speed (depending upon where the seed was sensed) to identify a distance that the seed has traveled, since it was sensed. This is indicated by block **460**. For instance, where the seed is sensed in meter **124**, it will integrate over the meter acceleration and speed. This is indicated by block **462**. Where it is sensed in the endless member (or delivery system **166**) it will integrate the endless member acceleration and speed, as indicated by block **464**. It will be noted that if the seed is detected in the meter, the integration will be performed both over the meter acceleration and speed (until the seed exits meter **124** into delivery system **166**) and then over the endless member or delivery system acceleration and speed, as indicated by block **464**. Where the delivery system is a seed tube, then it will be integrated (or double integrated) over the gravity drop speed or acceleration of the seed, as indicated by block **466** (of course, other factors may be taken into account, such as friction and forward travel speed of the row unit). The integration can be performed in other ways as well, and this is indicated by block **468**.

[0170] For instance, once the seed exits the seed delivery system **166**, the integration may also be performed over the speed or acceleration of the seed, as it drops into furrow **162**. This will account for the change in seed position after it leaves the delivery system. In a scenario where the seed is ejected from delivery system **166** with a velocity that is equal in magnitude but opposite in direction relative to the forward travel direction of row unit **106**, then it will fall substantially only under the influence of gravity, after it leaves delivery system **166**.

[0171] Final seed location estimator **388** then detects when the distance traveled meets the distance from where the seed was sensed, to the final seed location in the furrow **162**. This is indicated by block **470**. This can be based upon the machine dimensions (such as the size of the meter, delivery

system, etc.). This is indicated by block **472**. It can be based on other items as well, and this is indicated by block **474**.

[0172] Event driven processing system **266** then calculates the timing of when to actuate the valves to apply the material based upon the final seed location. This is indicated by block **476** in the flow diagram of FIG. **12**. Valve/nozzle time offset generator **370** illustratively generates a time offset that corresponds to the location of the valve on row unit **106**. For instance, if it is located well behind the seed delivery system, then the time delay may be longer. If it is located closely proximate the seed delivery system, then the time delay may be shorter. Calculating a time delay based on valve position is indicated by block **478** in the flow diagram of FIG. **12**.

[0173] Valve/nozzle time offset generator **370** can also illustratively generate an offset value based upon the properties of the material being applied (such as its exit velocity, viscosity, etc.). This is indicated by block **480**. It can generate a time delay based upon the valve or actuator responsiveness, as indicated by block **482**, and it can generate a delay or offset based upon the desired placement of the material relative to the final seed location. This is indicated by block **484**. It can generate these time offsets based upon the ground speed of row unit **106** as well. This is indicated by block **486**.

[0174] Based upon the timing, and the time stamp corresponding to the seed, pulse timing generator **372** generates a timing output indicating when the valve **109** should be actuated. This is indicated by block **488**. Pulse duration generator **374** provides an output indicating how long the valve should be actuated. This is indicated by block **490**. The timing of when to actuate the valves to apply the material based on the final seed location can be done in a wide variety of other ways as well, and this is indicated by block **492** in the flow diagram of FIG. **12**.

[0175] FIG. **13** is a flow diagram showing one example of the operation of event driven processing system **266** in an implementation in which it uses time delay generation system **366**. It is first assumed that time stamp generator **364** receives an input from seed sensor signal **304** indicating that a seed has been detected. It generates a time stamp for that event, as indicated by block **494** in the flow diagram of FIG. **13**. Time delay generation system **366** then generates a time delay incurred by the seed as it moves through to the meter or delivery system (depending upon where the seed was sensed) so that the valve actuation signals can be generated to actuate **13** the valves to place the material at the desired location, relative to the final seed location. Calculating a time delay to the seed exit from the delivery system **166**, based on the meter/delivery system speed is indicated by block **496** in the flow diagram of FIG. **13**. Meter/delivery system delay generator **382** can calculate the time delay based upon the speed of the meter and the delivery system (where the seed was detected in the meter) and/or based upon just the speed of the delivery system (where the seed was detected in the delivery system). This is indicated by block **498**. Where the delivery system is a seed tube, the time delay for the delivery system can be calculated based upon how long it will take the seed to drop from the seed sensor to the ground, under the force of gravity (considering things such as friction with the seed tube, forward velocity of the row unit, etc.). This is indicated by block **500**. The time delay for the meter/delivery system can be calculated in other ways as well, and this is indicated by block **502**.

[0176] Time delay generation system **366** also calculates the time delay that will be incurred by the seed as it moves from the exit of the seed delivery system **166** to its final location in the furrow **162**. This delay, along with the delay attributable to the meter/delivery system, will be the total time delay. This is indicated by block **504** in the flow diagram of FIG. **13**. The time delay incurred from the exit of the delivery system **166** to the final seed location can be based upon that distance, as indicated by block **506**. It can also be based on an expected seed roll, where the seed is expected to roll before it settles to its final location. This is indicated by block **508**. The time delay can be calculated in other ways as well, such as based on the velocity at which the seed is ejected from the delivery system **166**, and this is indicated by block **510**.

[0177] Valve/nozzle time offset generator **370** then calculates a time offset between the time when

the seed will be in its final location and when the valve/nozzle **109** should be actuated. This is indicated by block **512** in the flow diagram of FIG. **13**. This can be based upon the valve location on row unit **106**, as indicated by block **514**. It can be based upon the valve/nozzle responsiveness as indicated by block **516** and based on the fluid or material properties of the material being applied, as indicated by block **518**. It can be based upon the target placement of the material relative to the final seed location, as indicated by block **520**. It can be based on the ground speed of row unit **106**, as indicated by block **522**, and it can be based on a wide variety of other information as well, as indicated by block **524**.

[0178] Pulse timing generator **372** and pulse duration generator **374** then identify a time when the valve is to be actuated, based upon the total time delay and the time offset discussed above. This is indicated by block **526**. For instance, pulse timing generator **372** generates an output indicative of when the valve/actuator control signal is to be applied to the valve to open it, based upon the time stamp, the total time delay, and the time offset, as discussed above. This is indicated by block **528**. Pulse duration generator **374** generates an output indicative of how long the valve should be on/open. This is indicated by block **530**. If the application rate is to vary over the pulse duration, then the valve position can be controlled as well, as indicated by block **531**. The time when the valve should be actuated, and the duration and position, can be identified in other ways as well, and this is indicated by block **532**.

[0179] FIG. **14** is a block diagram showing one example of the frequency driven processing system **268** (briefly discussed above with respect to FIG. **8**) in more detail. The present discussion proceeds with respect to generating an a priori seed pattern and then applying material based on that pattern. However, the opposite can be done as well. The material can be applied first, to obtain an a priori material pattern. The seeds can then be planted, relative to the material, based on the a priori material pattern. For instance, where the material is fertilizer, the fertilizer can be applied first, and the seeds can be planted later, based on the pattern used to apply the fertilizer. Also, while the present discussion proceeds with respect to generating the a priori seed pattern, it could instead be a plant pattern where the material is applied relative to the location of plant, instead of seeds.

[0180] FIG. **14** shows that system **268** can illustratively receive a variety of inputs, some of which are the same as those discussed above, and are similarly numbered. System **268** also illustratively receives a planting start indicator **534** that can be generated from planting start signal generator **316**. Some examples of this are discussed elsewhere herein. It can receive a verification trigger **536** generated from verification trigger generator **318**. It can also receive verification sensor inputs **538** that are generated by verification sensors **320**. It can receive a wide variety of other information **540** as well.

[0181] In the example shown in FIG. **14**, frequency driven processing system **268** illustratively includes seed pattern identification system **542**, planting operation start detector **544**, time to actuation calculator logic **546**, seed pattern verification system **548**, and it can include other items **550**. Seed pattern verification system **548**, itself, illustratively includes verification trigger detector **552**, actual pattern detection system **554**, pattern correction value identifier **556**, seed pattern correction logic **558**, and it can include other items **560**.

[0182] Seed pattern identification system **542** generates an a priori seed pattern that identifies, once the seeding operation begins, where seeds will eventually be placed. Planting operation start detector **544** detects when the planting operation begins based on the planting start indicator **534**, and time to actuation calculator logic **546** calculates timing for when the valves **109** should be actuated to apply the material, based upon the seed locations in the a priori seed pattern, based upon the current position of row unit **106**, and based upon its ground speed. Thus, frequency driven processing system **268** can apply the material before the seeds are placed in furrow **162**, or after they are placed there, or simultaneously with seed placement. This is because the a priori seed pattern identifies how often seeds will be planted, once row unit **106** begins the operation. This, along with the system information that defines where the valve is on the row unit **106** relative to

the different parts of the row unit **106**, and the ground speed information indicating how quickly the row unit **106** is traveling, can be used to actuate the valves in order to apply the material at desired locations, relative to the seed positions.

[0183] It may be, however, that the a priori seed pattern is slightly inaccurate, or becomes less accurate over time. Thus, seed pattern verification system **548** can be used to verify and correct the a priori seed pattern. Verification trigger detector **552** detects when a verification trigger is present, indicating that a verification operation should be performed. The a priori seed pattern can be verified at certain time intervals, at intervals of distance traveled by row unit **106**, at intervals of a number of seeds that have been planted (or should have been planted), at intervals corresponding to material application rate, or the trigger can be a wide variety of other items.

[0184] Again, while the present description proceeds with respect to correcting the a priori seed pattern, this is just one example. When an a priori fertilizer pattern is generated, it can be corrected based on a verification input verifying that the pattern is correct, such as a moisture sensor input that senses increased moisture due to liquid fertilizer, a dye sensor (such as an optical or other sensor) a temperature sensor, etc. These sensor inputs indicate the actual presence of liquid fertilizer and can thus be used to correct the a priori fertilizer pattern.

[0185] Once triggered, actual pattern detection system **554** detects the actual seed pattern. For instance, system **554** can be event driven processing system **266** that detects the actual seed pattern based upon an actual event, such as a seed detection. The actual pattern can be detected in a wide variety of other ways as well, and using the event driven approach discussed above is only one example.

[0186] Pattern correction value identifier **556** can compare the actual seed pattern to the a priori seed pattern that is being used by frequency driven processing system **268** in order to apply the material. It can identify an error value that indicates how the a priori seed pattern may be inaccurate, based upon the actual seed pattern. For instance, for a wide variety of different reasons, it may be that the a priori seed pattern has shifted timing of the material application so it is a distance, e.g., several inches, from where it is actually desired. Detecting the actual seed pattern and calculating a correction value can be performed by pattern correction value identifier **556**.

[0187] The correction value is illustratively provided to seed pattern correction logic **558**, which performs a correction on the a priori seed pattern to generate a corrected a priori seed pattern. The corrected a priori seed pattern can then be used by frequency driven processing system **268** in applying the material, in the future. It will be noted that the verification process can be repeated and the corrected a priori seed pattern can, itself, be corrected should it become inaccurate.

[0188] FIGS. **15A** and **15B** (collectively referred to herein as FIG. **15**) show a flow diagram illustrating one example of the operation of frequency driven processing system **268** in more detail. It is first assumed that row unit **106** is configured for planting. This is indicated by block **562** in the flow diagram of FIG. **15**. It will illustratively have obtained or be configured to sense, system information **280**. It will also be configured to obtain or sense planting information **284**, material information **282**, and it can be configured in a wide variety of other ways as well, as indicated **564**.

[0189] An a priori seed pattern is then obtained. This is indicated by block **566**. It can be downloaded from a remote site (in an example in which it was previously generated and stored). This is indicated by block **567**. Seed pattern identification system **542** can calculate an a priori seed pattern. This can be done using a pattern model where inputs include values for the different systems, planting and material variables, along with a priori information, and other information. When that information is applied to the model, the model may generate a seed pattern that can be used by frequency driven processing system **268**. Generating the pattern using a pattern model is indicated by block **568**. Seed pattern identification system **542** can generate the seed pattern dynamically using a dynamic pattern calculation mechanism that considers the variable values. This is indicated by block **570**. The seed pattern can be calculated in other ways as well, and this is indicated by block **578**.

[0190] The a priori seed pattern will identify such things as seed placement timing, the offsets between when a seed is placed and when the various actuator signals should be applied to valves **109**, among other things. Thus, once the planting operation has started, the a priori seed pattern can be used to generate actuator control signals to control the actuators to apply the material where desired, relative to the seed positions, based on the timing indicated in the a priori seed pattern. [0191] At some point, the planting operation will begin, and this can be detected by planting operation start detector **544**. Detecting the start of the planting operation is indicated by block **580**. This can be done in a wide variety of different ways. For instance, a seed sensor can generate a signal indicating the presence of a seed in the delivery system. This may indicate that the planting operation has begun. This is indicated by block **582**. It may be that operator **92** actuates an operator input mechanism in the operating compartment of the towing vehicle to start the planting operation. This actuation may be detected as indicated by block **584**. It may be that movement of row unit **106**, or the delivery system or seed meter may be detected as the beginning of the planting operation. This is indicated by block **586**. The start of the planting operation can be detected in a wide variety of other ways as well, and this is indicated by block **588**.

[0192] Time to actuation calculator logic **546** then calculates the time when the valves **109** are to be controlled to apply the material, relative to the seed placement timing identified in the a priori seed pattern. This is indicated by block **590** in the flow diagram of FIG. **15**. It may be that the material is to be placed before the seed is planted. This can be done because the timing for the seed to arrive at its final location is already known, in the a priori seed pattern. Placing the material prior to placing the seed is indicated by block **592**. The material may be placed after the seed is placed, again based upon the estimated seed placement timing in the a priori seed pattern. This is indicated by block **594**. The timing can be generated based upon the detected ground speed, valve **6** placement and/or any of the other system information, material information, planting information or sensor value inputs. This is indicated by block **596**. The timing can be calculated in a wide variety of other ways as well, and this is indicated by block **598**.

[0193] The timing is then provided to valve control signal generator **258** (shown in FIG. **8**), which generates the valve control signals and applies them to valves **109** according to the calculated timing. This is indicated by block **600** in the flow diagram of FIG. **15**.

[0194] In some implementations, it may be that the a priori seed pattern is to occasionally be verified and/or corrected. This is indicated by block **602**. If not, processing proceeds at block where the operation continues until the planting operation is complete.

[0195] However, if, at block **602**, it is determined that the a priori seed pattern is to be verified and/or corrected, then at some point verification trigger detector **552** detects a verification trigger indicating that a verification and/or correction operation is to be performed. This is indicated by block **606** in the flow diagram of FIG. **15**. The trigger can be a time-based trigger, as indicated by block **608**. It can be distance-based trigger as indicated by block **610**. It can be a number of seeds-based trigger as indicated by block **612**, or the trigger can be any of a wide variety of other triggers, as indicated by block **614**.

[0196] Actual pattern detection system **554** illustratively detects the actual seed pattern to identify whether the material is being applied, as desired. If the actual seed pattern is shifted from the a priori seed pattern, or is different in another way, then it is likely that the material is not being applied, as desired. Detecting the actual seed pattern is indicated by block **616** in the flow diagram of FIG. **15**.

[0197] There are a wide variety of different ways to detect whether the material is being applied, as desired. These can be the same as how the material is sensed in a scenario in which an a priori fertilizer pattern is generated instead of an a priori seed pattern. For instance, it may be that the material has dye added to it and the dye can be easily sensed by an optical sensor, such as a camera, which may also be equipped to detect the seed as well. In that case, actual pattern detection system **554** can detect whether the dyed material is being applied at the desired placement, relative to the

seed location. In another example, a camera can be used, in conjunction with a position detector, to detect actual seed location. Detecting the actual seed location using dye sensing is indicated by block **618** and detecting it with a camera is indicated by block **620**.

[0198] In another example, the material being applied can be sensed in different ways. Where it is a liquid material, a moisture sensor can be used to detect where the material is applied. The moisture sensor may indicate an elevated moisture level in areas where the liquid material has just been applied, over the areas where it has not been applied. Detecting the actual pattern using a moisture sensor is indicated by block **622**.

[0199] The actual pattern can also be detected using a temperature sensor. For instance, where the material being applied is warmer or cooler than the ground, a temperature sensor can be used to sense that temperature difference to provide an indication of where the material is being applied. Sensing the pattern using a temperature sensor is indicated by block **624**.

[0200] As discussed herein, the event driven processing system **266**, which senses the seed position based upon an actual event (such as an output from the seed sensor) can also be used to detect or verify the a priori seed pattern. This is indicated by block **626**. The actual seed pattern can be detected in a wide variety of other ways as well, and this is indicated by block **628**.

[0201] Based upon the actual pattern detected by system **554**, pattern correction value identifier **556** identifies any pattern correction values to the a priori seed pattern. This is indicated by block **630**. By way of example, the correction values may be distance values which indicate a difference in geographic position, or relative position, of the seed location in the a priori seed pattern versus the actual seed location. The correction values may be timing values, which correct the timing of the valve/actuator control signals. For instance, it may be that the a priori pattern has the valve/actuator signals being triggered too frequently, or not frequently enough. Thus, the correction values may be timing values.

[0202] Once the correction values are identified, seed pattern correction logic **558** illustratively corrects the calculated, a priori seed pattern, based upon the correction values. This is indicated by block **632**. In doing so, it can recalculate the entire a priori seed pattern using the correction values. This is indicated by block **634**. It can simply apply the correction values to the already calculated a priori seed pattern. This is indicated by block **636**. It can correct the a priori seed pattern in other ways as well, and this is indicated by block **638**.

[0203] Until the planting operation is complete, operation reverts to block **590** where the system continues to identify the timing for generating the valve/control signals to actuate the valve/actuators **109** using the a priori seed pattern or corrected pattern. This is indicated by block **604**.

[0204] The present discussion has mentioned processors and servers. In one example, the processors and servers include computer processors with associated memory and timing circuitry, not separately shown. They are functional parts of the systems or devices to which they belong and are activated by, and facilitate the functionality of the other components or items in those systems.

[0205] Also, a number of user interface displays have been discussed. They can take a wide variety of different forms and can have a wide variety of different user actuatable input mechanisms disposed thereon. For instance, the user actuatable input mechanisms can be text boxes, check boxes, icons, links, drop-down menus, search boxes, etc. They can also be actuated in a wide variety of different ways. For instance, they can be actuated using a point and click device (such as a track ball or mouse). They can be actuated using hardware buttons, switches, a joystick or keyboard, thumb switches or thumb pads, etc. They can also be actuated using a virtual keyboard or other virtual actuators. In addition, where the screen on which they are displayed is a touch sensitive screen, they can be actuated using touch gestures. Also, where the device that displays them has speech recognition components, they can be actuated using speech commands.

[0206] A number of data stores have also been discussed. It will be noted they can each be broken into multiple data stores. All can be local to the systems accessing them, all can be remote, or some

can be local while others are remote. All of these configurations are contemplated herein.

[0207] Also, the figures show a number of blocks with functionality ascribed to each block. It will be noted that fewer blocks can be used so the functionality is performed by fewer components.

Also, more blocks can be used with the functionality distributed among more components.

[0208] Further, as discussed elsewhere herein, the present discussion has proceeded primarily with respect to fertilizer or other material application being controlled based on a priori seed location or seed pattern. However, this is just one example. In another example, seed location can be controlled based on a priori fertilizer (or other material) location or pattern. Similarly, instead an a priori or seed location, an a priori plant location can be used as well.

[0209] FIG. **16** is a block diagram of the architecture, shown in FIG. **1**, except that it communicates with elements in a remote server architecture **640.sub.4**. In an example, remote server architecture **640** can provide computation, software, data access, and storage services that do not require end-user knowledge of the physical location or configuration of the system that delivers the services. In various embodiments, remote servers can deliver the services over a wide area network, such as the internet, using appropriate protocols. For instance, remote servers can deliver applications over a wide area network and they can be accessed through a web browser or any other computing component. Software or components shown in FIG. **8** as well as the corresponding data, can be stored on servers at a remote location. The computing resources in a remote server environment can be consolidated at a remote data center location or they can be dispersed. Remote server infrastructures can deliver services through shared data centers, even though they appear as a single point of access for the user. Thus, the components and functions described herein can be provided from a remote server at a remote location using a remote server architecture. Alternatively, they can be provided from a conventional server, or they can be installed on client devices directly, or in other ways.

[0210] In the example shown in FIG. **16**, some items are similar to those shown in FIGS. **1** and **8** and they are similarly numbered. FIG. **16** specifically shows that frequency driven processing system **268** and data store **254** can be located at a remote server location **642**. Therefore, system **113** accesses those systems through remote server location **642**.

[0211] FIG. **16** also depicts another example of a remote server architecture. FIG. **16** shows that it is also contemplated that some elements of FIGS. **1** and **8** can be disposed at remote server location **642** while others are not. By way of example, data store **254** can be disposed at a location separate from location **642**, and accessed through the remote server at location **642**. Regardless of where they are located, they can be accessed directly by system **113**, through a network (either a wide area network or a local area network), they can be hosted at a remote site by a service, or they can be provided as a service, or accessed by a connection service that resides in a remote location. Also, the data can be stored in substantially any location and intermittently accessed by, or forwarded to, interested parties. For instance, physical carriers can be used instead of, or in addition to, electromagnetic wave carriers. In such an example, where cell coverage is poor or nonexistent, another mobile machine (such as a fuel truck) can have an automated information collection system. As the planter comes close to the fuel truck for fueling, the system automatically collects the information from the planter using any type of ad-hoc wireless connection. The collected information can then be forwarded to the main network as the fuel truck reaches a location where there is cellular coverage (or other wireless coverage). For instance, the fuel truck may enter a covered location when traveling to fuel other machines or when at a main fuel storage location. All of these architectures are contemplated herein. Further, the information can be stored on the planter until the planter enters a covered location. The planter, itself, can then send the information to the main network.

[0212] It will also be noted that the elements of FIGS. **1** and **8**, or portions of them, can be disposed on a wide variety of different devices. Some of those devices include servers, desktop computers, laptop computers, tablet computers, or other mobile devices, such as palm top computers, cell

phones, smart phones, multimedia players, personal digital assistants, etc.

[0213] FIG. **17** is a simplified block diagram of one illustrative example of a handheld or mobile computing device that can be used as a user's or client's hand held device **16**, in which the present system (or parts of it) can be deployed. For instance, a mobile device can be deployed in the operator compartment of towing vehicle **94** for use in generating, processing, or displaying the application data. FIGS. **18-19** are examples of handheld or mobile devices.

[0214] FIG. **17** provides a general block diagram of the components of a client device **16** that can run some components shown in FIGS. **1** and **8**, that interacts with them, or both. In the device **16**, a communications link **13** is provided that allows the handheld device to communicate with other computing devices and in some examples provides a channel for receiving information automatically, such as by scanning. Examples of communications link **13** include allowing communication through one or more communication protocols, such as wireless services used to provide cellular access to a network, as well as protocols that provide local wireless connections to networks.

[0215] In other examples, applications can be received on a removable Secure Digital (SD) card that is connected to an interface **15**. Interface **15** and communication links **13** communicate with a processor **17** (which can also embody processors from previous FIGURES) along a bus **19** that is also connected to memory **21** and input/output (I/O) components **23**, as well as clock **25** and location system **27**.

[0216] I/O components **23**, in one example, are provided to facilitate input and output operations. I/O components **23** for various examples of the device **16** can include input components such as buttons, touch sensors, optical sensors, microphones, touch screens, proximity sensors, accelerometers, orientation sensors and output components such as a display device, a speaker, and or a printer port. Other I/O components **23** can be used as well.

[0217] Clock **25** illustratively comprises a real time clock component that outputs a time and date. It can also, illustratively, provide timing functions for processor **17**.

[0218] Location system **27** illustratively includes a component that outputs a current geographical location of device **16**. This can include, for instance, a global positioning system (GPS) receiver, a LORAN system, a dead reckoning system, a cellular triangulation system, or other positioning system. It can also include, for example, mapping software or navigation software that generates desired maps, navigation routes and other geographic functions.

[0219] Memory **21** stores operating system **29**, network settings **31**, applications **33**, application configuration settings **35**, data store **37**, communication drivers **39**, and communication configuration settings **41**. Memory **21** can include all types of tangible volatile and non-volatile computer-readable memory devices. It can also include computer storage media (described below). Memory **21** stores computer readable instructions that, when executed by processor **17**, cause the processor to perform computer-implemented steps or functions according to the instructions. Processor **17** can be activated by other components to facilitate their functionality as well.

[0220] FIG. **18** shows one example in which device **16** (from FIG. **17**) is a tablet computer **644**. In FIG. **18**, computer **644** is shown with user interface display screen **646**. Screen **646** can be a touch screen or a pen-enabled interface that receives inputs from a pen or stylus. It can also use an on-screen virtual keyboard. Of course, it might also be attached to a keyboard or other user input device through a suitable attachment mechanism, such as a wireless link or USB port, for instance. Computer **644** can also illustratively receive voice inputs as well.

[0221] FIG. **19** shows that the device can be a smart phone **71**. Smart phone **71** has a touch sensitive display **73** that displays icons or tiles or other user input mechanisms **75**. Mechanisms **75** can be used by a user to run applications, make calls, perform data transfer operations, etc. In general, smart phone **71** is built on a mobile operating system and offers more advanced computing capability and connectivity than a feature phone.

[0222] Note that other forms of the devices **16** are possible.

[0223] FIG. 20 is one example of a computing environment in which elements of FIGS. 1 and 8, or parts of it, (for example) can be deployed. With reference to FIG. 20, an example system for implementing some embodiments includes a general-purpose computing device in the form of a computer 810. Components of computer 810 may include, but are not limited to, a processing unit 820 (which can comprise processors from previous Figures), a system memory 830, and a system bus 821 that couples various system components including the system memory to the processing unit 820. The system bus 821 may be any of several types of bus structures including a memory bus or memory controller, a peripheral bus, and a local bus using any of a variety of bus architectures. Memory and programs described with respect to FIGS. 1 and 8 can be deployed in corresponding portions of FIG. 20.

[0224] Computer 810 typically includes a variety of computer readable media. Computer readable media can be any available media that can be accessed by computer 810 and includes both volatile and nonvolatile media, removable and non-removable media. By way of example, and not limitation, computer readable media may comprise computer storage media and communication media. Computer storage media is different from, and does not include, a modulated data signal or carrier wave. It includes hardware storage media including both volatile and nonvolatile, removable and non-removable media implemented in any method or technology for storage of information such as computer readable instructions, data structures, program modules or other data. Computer storage media includes, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks (DVD) or other optical disk storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium, which can be used to store the desired information and which can be accessed by computer 810. Communication media may embody computer readable instructions, data structures, program modules or other data in a transport mechanism and includes any information delivery media. The term “modulated data signal” means a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal.

[0225] The system memory 830 includes computer storage media in the form of volatile and/or nonvolatile memory such as read only memory (ROM) 831 and random access memory (RAM) 832. A basic input/output system 833 (BIOS), containing the basic routines that help to transfer information between elements within computer 810, such as during start-up, is typically stored in ROM 831. RAM 832 typically contains data and/or program modules that are immediately accessible to and/or presently being operated on by processing unit 820. By way of example, and not limitation, FIG. 20 illustrates operating system 834, application programs 835, other program modules 836, and program data 837.

[0226] The computer 810 may also include other removable/non-removable volatile/nonvolatile computer storage media. By way of example only, FIG. 20 illustrates a hard disk drive 841 that reads from or writes to non-removable, nonvolatile magnetic media, an optical disk drive 855, and nonvolatile optical disk 856. The hard disk drive 841 is typically connected to the system bus 821 through a non-removable memory interface such as interface 840, and optical disk drive 855 are typically connected to the system bus 821 by a removable memory interface, such as interface 850.

[0227] Alternatively, or in addition, the functionality described herein can be performed, at least in part, by one or more hardware logic components. For example, and without limitation, illustrative types of hardware logic components that can be used include Field-programmable Gate Arrays (FPGAs), Application-specific Integrated Circuits (e.g., ASICs), Application-specific Standard Products (e.g., ASSPs), System-on-a-chip systems (SOCs), Complex Programmable Logic Devices (CPLDs), etc.

[0228] The drives and their associated computer storage media discussed above and illustrated in FIG. 20, provide storage of computer readable instructions, data structures, program modules and other data for the computer 810. In FIG. 20, for example, hard disk drive 841 is illustrated as storing operating system 844, application programs 845, other program modules 846, and program

data **847**. Note that these components can either be the same as or different from operating system **834**, application programs **835**, other program modules **836**, and program data **837**.

[0229] A user may enter commands and information into the computer **810** through input devices such as a keyboard **862**, a microphone **863**, and a pointing device **861**, such as a mouse, trackball or touch pad. Other input devices (not shown) may include a joystick, game pad, satellite dish, scanner, or the like. These and other input devices are often connected to the processing unit **820** through a user input interface **860** that is coupled to the system bus, but may be connected by other interface and bus structures. A visual display **891** or other type of display device is also connected to the system bus **821** via an interface, such as a video interface **890**. In addition to the monitor, computers may also include other peripheral output devices such as speakers **897** and printer **896**, which may be connected through an output peripheral interface **895**.

[0230] The computer **810** is operated in a networked environment using logical connections (such as a controller area network-CAN, local area network-LAN, or wide area network WAN) to one or more remote computers, such as a remote computer **880**.

[0231] When used in a LAN networking environment, the computer **810** is connected to the LAN **871** through a network interface or adapter **870**. When used in a WAN networking environment, the computer **810** typically includes a modem **872** or other means for establishing communications over the WAN **873**, such as the Internet. In a networked environment, program modules may be stored in a remote memory storage device. FIG. **20** illustrates, for example, that remote application programs **885** can reside on remote computer **880**.

[0232] It should also be noted that the different examples described herein can be combined in different ways. That is, parts of one or more examples can be combined with parts of one or more other examples. All of this is contemplated herein.

[0233] Although the subject matter has been described in language specific to structural features and/or methodological acts, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described above. Rather, the specific features and acts described above are disclosed as example forms of implementing the claims.

Claims

1-20. (canceled)

21. A mobile agricultural planting machine comprising: a furrow opener configured to open a furrow as the mobile agricultural planting machine moves across a field; a commodity distribution system configured to dispense a commodity to the furrow; a sensor configured to sense a characteristic relative to the furrow; and a control system configured to control an operating parameter of the commodity distribution system in response to the sensed characteristic relative to the furrow.

22. The mobile agricultural planting machine of claim 21, wherein the characteristic relative to the furrow comprises a temperature.

23. The mobile agricultural planting machine of claim 22, wherein the commodity comprises liquid.

24. The mobile agricultural planting machine of claim 22, wherein the commodity comprises fertilizer.

25. The mobile agricultural planting machine of claim 22, wherein the commodity distribution system comprises a first commodity distribution system configured to dispense a first commodity to the furrow, wherein the mobile agricultural planting machine further comprises a second commodity distribution system configured to dispense a second commodity, different than the first commodity, to the furrow, wherein the control system is configured to control the operating parameter of the first commodity distribution system to control the placement of the first commodity in the furrow relative to a location of the second commodity in the furrow based on the

sensed temperature relative to the furrow.

26. The mobile agricultural planting machine of claim 25, wherein the placement comprises one of: (i) before the location of the second commodity; (ii) after the location of the second commodity; (iii) on the location of the second commodity; or (iv) a combination of (i), (ii), and (iii).

27. The mobile agricultural planting machine of claim 22, wherein the operating parameter comprises an actuation timing for an actuator of the commodity distribution system.

28. The mobile agricultural planting machine of claim 22, wherein the operating parameter comprises an actuation duration for an actuator of the commodity distribution system.

29. The mobile agricultural planting machine of claim 22, wherein the operating parameter comprises a speed of the commodity distribution system.

30. A computer implemented method of controlling a mobile agricultural planting machine comprising: sensing, with a sensor on the mobile agricultural planting machine, a characteristic relative to a furrow opened by the mobile agricultural planting machine as the mobile agricultural planting machine moves across a field; generating, with sensor, a sensor signal indicative of the characteristic relative to the furrow; identifying, based on the sensor signal, the characteristic relative to the furrow; controlling, in response to the characteristic relative to the furrow, an operating parameter of commodity distribution system of the mobile agricultural planting machine to controllably dispense commodity to the furrow.

31. The computer implemented method of claim 30, wherein sensing the characteristic relative to the furrow comprises sensing a temperature relative to the furrow.

32. The computer implemented method of claim 31, wherein the commodity comprises liquid.

33. The computer implemented method of claim 31, wherein the commodity comprises fertilizer.

34. The computer implemented method of claim 31, wherein the commodity distribution system comprises a first commodity distribution system configured to dispense a first commodity to the furrow, wherein the mobile agricultural planting machine further comprises a second commodity distribution system configured to dispense a second commodity, different than the first commodity, to the furrow, wherein the control system is configured to control the operating parameter of the first commodity distribution system to control the placement of the first commodity in the furrow relative to a location of the second commodity in the furrow based on the temperature relative to the furrow.

35. The computer implemented method of claim 34, wherein the placement comprises one of: (i) before the location of the second commodity; (ii) after the location of the second commodity; (iii) on the location of the second commodity; or (iv) a combination of (i), (ii), and (iii).

36. The computer implemented method of claim 31, wherein the operating parameter comprises an actuation timing for an actuator of the commodity distribution system.

37. The computer implemented method of claim 31, wherein the operating parameter comprises an actuation duration for an actuator of the commodity distribution system.

38. The computer implemented method of claim 31, wherein the operating parameter comprises a speed of the commodity distribution system.

39. A mobile agricultural planting machine comprising: a row unit comprising: a furrow opener configured to open a furrow as the mobile agricultural planting machine moves across a field; a first commodity distribution system configured to dispense a first commodity to the furrow; a second commodity distribution system configured to dispense a second commodity, different than the first commodity, to the furrow; and a sensor configured to sense a characteristic relative in the furrow; and a control system configured to control an operating parameter of the first commodity distribution system in response to the sensed characteristic in the furrow.

40. The mobile agricultural planting machine of claim 39, wherein the characteristic in the furrow comprises a temperature in the furrow and wherein the control system is configured to control the operating parameter of the first commodity distribution system to control the placement of the first

commodity in the furrow relative to a location of the second commodity in the furrow based on the sensed temperature relative to the furrow.
