

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12392499
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Chimurkar; Ishan Prakashrao et al.

Oven appliance having one or more cooling airflow features

Abstract

An oven appliance may include a cabinet, an insulated cooking chamber, and a plurality of internal ridge. The cabinet may include a plurality of outer panels. The cabinet may define an airflow path extending through the cabinet. The insulated cooking chamber may be disposed within the cabinet. The airflow path may be defined between the outer panels and the insulated cooking chamber. The plurality of internal ridges may be disposed within the cabinet. The plurality of internal ridges may extend along the airflow path and define a guided segment thereof. The plurality of internal ridges may be spaced apart along the airflow path and thereby define a cross-path gap between adjacent ridges of the plurality of internal ridges.

Inventors: Chimurkar; Ishan Prakashrao (Layfayette, GA), Hellwig; Frank Jacob (East Ridge, TN), Warren, Jr.; Willie D. (Ringgold, GA)

Applicant: Haier US Appliance Solutions, Inc. (Wilmington, DE)

Family ID: 1000008766024

Assignee: Haier US Appliance Solutions, Inc. (Wilmington, DE)

Appl. No.: 17/724673

Filed: April 20, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230341132 A1	Oct. 26, 2023

Publication Classification

Int. Cl.: F24C15/00 (20060101); F24C15/12 (20060101)

U.S. Cl.:

CPC F24C15/006 (20130101); F24C15/12 (20130101);

Field of Classification Search

CPC: F24C (15/006); F24C (15/12); F24C (15/08)

USPC: 126/21R

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7954485	12/2010	Cadima et al.	N/A	N/A
2006/0151492	12/2005	Bray	219/756	A47J 36/027
2015/0075513	12/2014	Paller	126/198	F24C 15/006
2017/0292713	12/2016	Boedicker	N/A	F24C 15/006
2020/0408419	12/2019	Diehl	N/A	F24C 15/101
2021/0207812	12/2020	Bhogal	N/A	F24C 15/006
2021/0388995	12/2020	Dulak	N/A	F24C 15/322

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
203671679	12/2013	CN	N/A
208176498	12/2017	CN	N/A
100214627	12/1998	KR	N/A
100693147	12/2006	KR	N/A
20180119743	12/2017	KR	F28D 1/0226

OTHER PUBLICATIONS

Korean to English machine translation of KR20180119743A. cited by examiner

Korean to English machine translation of KR20180119743A (Year: 2018). cited by examiner

Primary Examiner: Hoang; Michael G

Assistant Examiner: Laughlin; Elizabeth Ann

Attorney, Agent or Firm: Dority & Manning, P.A.

Background/Summary

FIELD OF THE INVENTION

(1) The present disclosure relates generally to an oven appliance, or more specifically, to an oven appliance having one or more features to ensure cooling of an outer surface.

BACKGROUND OF THE INVENTION

(2) Oven appliances generally define one or more enclosures supporting one or more heating elements. For instance, oven appliances can include a cabinet defining an insulated cooking chamber therein for receipt of food items for cooking. Heating elements, such as a bake heating element or broil heating element may be positioned within the cooking chamber to provide heat to

food items located therein. The bake heating element is positioned at a bottom of the cooking chamber. The broil heating element positioned at a top of the cooking chamber. One or more electronic components may be housed within the cabinet outside of the cooking chamber.

(3) In general, it can be desirable to manage heat or temperatures at outer surface of the cabinet or enclosure. Recently, certain government or trade group standards having even incorporated requirements that accessible portions of an oven cabinet being maintained below one or more temperature thresholds during use. One such requirement is included in the updated UL858 standard (as is intended to take effect in November 2022), which adopts temperature thresholds for the increase in temperature for surfaces below 31 inches of installation height from the floor during a 475° Fahrenheit (i.e., 246° Celsius) oven bake operation for the surfaces that are accessible by a specified access probe—such surfaces may be required to be measured by an International Electrotechnical Commission (IEC)-compliant temperature probe. For instance, a temperature threshold for bare or painted metal is 33° Celsius, hence the metal may be required to stay at or below is 58° Celsius in a 25° Celsius ambient environment.

(4) Existing appliances may have difficulties meeting the updated standards or otherwise cooling the cabinet. For instance, it may be difficult to ensure a sufficient cooling airflow is available throughout the airflow path for cooling air within certain portions of the cabinet (e.g., without requiring larger or more numerous fans, which can complicate assembly and increase expenses).

(5) As a result, it would be useful to provide an oven appliance with one or more features to cool an outer surface (e.g., accessible by a standardized probe) of the oven appliance. In particular, it may be advantageous to include one or more features to disperse or more evenly distribute a cooling airflow through the cabinet of an oven appliance.

BRIEF DESCRIPTION OF THE INVENTION

(6) Aspects and advantages of the invention will be set forth in part in the following description, or may be obvious from the description, or may be learned through practice of the invention.

(7) In one exemplary aspect of the present disclosure, an oven appliance is provided. The oven appliance may include a cabinet, an insulated cooking chamber, and a plurality of internal ridge. The cabinet may include a plurality of outer panels. The cabinet may define an airflow path extending through the cabinet. The insulated cooking chamber may be disposed within the cabinet. The airflow path may be defined between the outer panels and the insulated cooking chamber. The plurality of internal ridges may be disposed within the cabinet. The plurality of internal ridges may extend along the airflow path and define a guided segment thereof. The plurality of internal ridges may be spaced apart along the airflow path and thereby define a cross-path gap between adjacent ridges of the plurality of internal ridges.

(8) In another exemplary aspect of the present disclosure, an oven appliance is provided. The oven appliance may include a cabinet, an insulated cooking chamber, and a plurality of internal ridges. The cabinet may include a plurality of outer panels including a top panel, a rear panel, and a bottom panel. The cabinet may define an airflow path extending through the cabinet. The insulated cooking chamber may be disposed within the cabinet. The airflow path may be defined between the outer panels and the insulated cooking chamber. The plurality of internal ridges may be formed on the bottom panel within the cabinet. The plurality of internal ridges may extend along the airflow path and define a guided segment thereof. The plurality of internal ridges may be spaced apart along a transverse direction and thereby define a lateral cross-path gap between adjacent ridges of the plurality of internal ridges.

(9) These and other features, aspects and advantages of the present invention will become better understood with reference to the following description and appended claims. The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and, together with the description, serve to explain the principles of the invention.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) A full and enabling disclosure of the present invention, including the best mode thereof, directed to one of ordinary skill in the art, is set forth in the specification, which makes reference to the appended figures.
- (2) FIG. 1 provides a perspective view of an oven appliance according to exemplary embodiments of the present disclosure.
- (3) FIG. 2 provides a section view of the exemplary oven appliance of FIG. 1, taken along the lines 2-2.
- (4) FIG. 3 provides a magnified section view of a bottom portion of the exemplary oven appliance of FIG. 1.
- (5) FIG. 4 provides a perspective view of a bottom panel of a cabinet of an oven appliance according to exemplary embodiments of the present disclosure.
- (6) FIG. 5 provides a perspective view the exemplary bottom panel of FIG. 4, wherein the flow of across the bottom panel is illustrated.
- (7) FIG. 6 provides a perspective view of a bottom panel of a cabinet of an oven appliance according to other exemplary embodiments of the present disclosure.
- (8) FIG. 7 provides a perspective view of a bottom panel of a cabinet of an oven appliance according to still other exemplary embodiments of the present disclosure.
- (9) FIG. 8 provides a magnified perspective view of a portion of the exemplary bottom panel of FIG. 7.

DETAILED DESCRIPTION

- (10) Reference now will be made in detail to embodiments of the invention, one or more examples of which are illustrated in the drawings. Each example is provided by way of explanation of the invention, not limitation of the invention. In fact, it will be apparent to those skilled in the art that various modifications and variations can be made in the present invention without departing from the scope of the invention. For instance, features illustrated or described as part of one embodiment can be used with another embodiment to yield a still further embodiment. Thus, it is intended that the present invention covers such modifications and variations as come within the scope of the appended claims and their equivalents.
- (11) As used herein, the terms “first,” “second,” and “third” may be used interchangeably to distinguish one component from another and are not intended to signify location or importance of the individual components. The terms “includes” and “including” are intended to be inclusive in a manner similar to the term “comprising.” Similarly, the term “or” is generally intended to be inclusive (i.e., “A or B” is intended to mean “A or B or both”). In addition, here and throughout the specification and claims, range limitations may be combined or interchanged. Such ranges are identified and include all the sub-ranges contained therein unless context or language indicates otherwise. For example, all ranges disclosed herein are inclusive of the endpoints, and the endpoints are independently combinable with each other. The singular forms “a,” “an,” and “the” include plural references unless the context clearly dictates otherwise.
- (12) Approximating language, as used herein throughout the specification and claims, may be applied to modify any quantitative representation that could permissibly vary without resulting in a change in the basic function to which it is related. Accordingly, a value modified by a term or terms, such as “generally,” “about,” “approximately,” and “substantially,” are not to be limited to the precise value specified. In at least some instances, the approximating language may correspond to the precision of an instrument for measuring the value, or the precision of the methods or machines for constructing or manufacturing the components or systems. For example, the approximating language may refer to being within a 10 percent margin (i.e., including values

within ten percent greater or less than the stated value). In this regard, for example, when used in the context of an angle or direction, such terms include within ten degrees greater or less than the stated angle or direction (e.g., “generally vertical” includes forming an angle of up to ten degrees in any direction, such as, clockwise or counterclockwise, with the vertical direction V).

(13) The word “exemplary” is used herein to mean “serving as an example, instance, or illustration.” In addition, references to “an embodiment” or “one embodiment” does not necessarily refer to the same embodiment, although it may. Any implementation described herein as “exemplary” or “an embodiment” is not necessarily to be construed as preferred or advantageous over other implementations. Moreover, each example is provided by way of explanation of the invention, not limitation of the invention. In fact, it will be apparent to those skilled in the art that various modifications and variations can be made in the present invention without departing from the scope of the invention. For instance, features illustrated or described as part of one embodiment can be used with another embodiment to yield a still further embodiment. Thus, it is intended that the present invention covers such modifications and variations as come within the scope of the appended claims and their equivalents.

(14) The terms “upstream” and “downstream” refer to the relative flow direction with respect to fluid flow in a fluid pathway. For example, “upstream” refers to the flow direction from which the fluid flows, and “downstream” refers to the flow direction to which the fluid flows.

(15) FIGS. 1 and 2 depict an exemplary oven appliance **10** that may be configured in accordance with aspects of the present disclosure. FIG. 1 provides a perspective view of oven appliance **10** according to an exemplary embodiment of the present disclosure. FIG. 2 provides a cross sectional view of oven appliance **10** taken along the 2-2 line of FIG. 1. For the particular embodiment of FIGS. 1 and 2, oven appliance **10** defines a vertical direction V, a lateral direction L and a transverse direction T. The vertical, lateral and transverse directions are mutually perpendicular and form an orthogonal direction system. As will be understood by those skilled in the art, oven appliance **10** is provided by way of example only, and the present subject matter may be used in any suitable oven appliance. Thus, the present subject matter may be used with other oven appliances having different configurations.

(16) Oven appliance **10** includes a cabinet **12** with an insulated cooking chamber **14** disposed within cabinet **12**. Insulated cooking chamber **14** is configured for the receipt of one or more food items to be cooked. Oven appliance **10** includes a door **16** rotatably mounted to cabinet **12**, e.g., with a hinge (not shown). A handle **18** is mounted to door **16** and assists a user with opening and closing door **16** in order to access insulated cooking chamber **14**. For example, a user can pull on handle **18** to open or close door **16** and access insulated cooking chamber **14**.

(17) Various chamber walls define insulated cooking chamber **14**. For example, insulated cooking chamber **14** includes a top wall **25** and a bottom wall **26** which are spaced apart along the vertical direction V. A pair of sidewalls **28** extend between the top wall **25** and bottom wall **26**, and are spaced apart along the lateral direction L. A rear wall **29** may additionally extend between the top wall **25** and bottom wall **26** as well as between the pair of sidewalls **28**, and is spaced apart from door **16** along the transverse direction T. In this manner, when door **16** is in the closed position, a cooking cavity is defined by door **16** and top wall **25**, bottom wall **26**, sidewalls **28**, and rear wall **29**, of insulated cooking chamber **14**.

(18) According to the illustrated embodiment, the chamber walls of insulated cooking chamber **14** are depicted as simple blocks of insulating material surrounding the cooking cavity. However, one skilled in the art will appreciate that the insulating material may be constructed of one or more suitable materials and may take any suitable shape. For example, the insulating material may be encased in one or more rigid structural members, such as sheet metal panels, which provide structural rigidity and a mounting surface for attaching, for example, heating elements, temperature probes, rack sliding assemblies, and other mechanical or electronic components.

(19) Cabinet **12** includes multiple outer panels that enclose insulated cooking chamber **14**. For

example, cabinet **12** includes a top panel **30** and a bottom panel **31** which are spaced apart along the vertical direction V. Left panel **32** and right panel **33** (as defined according to the view as shown in FIG. 1) extend between the top panel **30** and bottom panel **31**, and are spaced apart along the lateral direction L. A rear panel **34** may additionally extend between the top panel **30** and bottom panel **31** as well as between the left panel **32** and right panel **33**, and is spaced apart from door **16** along the transverse direction T. When door **16** is in the closed position, it may sit flush with a front panel **35** of cabinet **12**.

(20) According to the illustrated embodiment, the panels of cabinet **12** are single ply sheet metal panels, but one skilled in the art will appreciate that one or more of the panels may include other suitably rigid panels while remaining within the scope of the present subject matter. For example, according to an exemplary embodiment, one or more panels may be constructed from a suitably rigid and thermally resistant plastic. In addition, one or more panels may include multiple layers made from the same or different materials, and may be formed in any suitable shape.

(21) In some embodiments, a lower heating assembly, e.g., bake heating assembly **40**, is included in oven appliance **10**, and may include one or more heating elements, e.g. bake heating elements **42**. Bake heating elements **42** may be disposed within insulated cooking chamber **14**, such as adjacent bottom wall **26**. In exemplary embodiments as illustrated, the bake heating elements **42** are electric heating elements, as is generally understood. Alternatively, the bake heating elements **42** may be gas burners or other suitable heating elements having other suitable heating sources. Bake heating elements **42** may generally be used to heat insulated cooking chamber **14** for both cooking and cleaning of oven appliance **10**.

(22) In additional or alternative embodiments, an upper heating assembly, e.g., broil heating assembly **46**, is included in oven appliance **10**, and may include one or more upper heating elements, e.g., broil heating elements **48**. Broil heating elements **48** may be disposed within insulated cooking chamber **14**, such as adjacent top wall **25**. In exemplary embodiments as illustrated, the broil heating elements **48** are electric heating elements, as is generally understood. Alternatively, the broil heating elements **48** may be gas burners or other suitable heating elements having other suitable heating sources. Broil heating elements **48** may additionally generally be used to heat insulated cooking chamber **14** for both cooking and cleaning of oven appliance **10**.

(23) In optional embodiments, oven appliance **10** includes a convection heating assembly **50**. Convection heating assembly **50** may have a fan **52** and a convection heating element **54**. Convection heating assembly **50** is configured for selectively urging a flow of heated air into insulated cooking chamber **14**. For example, fan **52** can pull air from insulated cooking chamber **14** into convection heating assembly **50** and convection heating element **54** can heat such air. Subsequently, fan **52** can urge such heated air back into insulated cooking chamber **14**. As another example, fan **52** can cycle heated air from insulated cooking chamber **14** within insulated cooking chamber **14** in order to generate forced convective air currents without use of convection heating element **54**. Like heating elements **42**, **48** discussed above, convection heating element **54** may be, for example, a gas, electric, or microwave heating element or any suitable combination thereof. According to an alternative exemplary embodiment, convection heating assembly **50** need not include fan **52**.

(24) Oven appliance **10** is further equipped with a controller **58** to regulate operation of the oven appliance **10**. For example, controller **58** may regulate the operation of oven appliance **10** including heating elements **42**, **48**, **54** (and heating assemblies **40**, **46**, **50** generally). Controller **58** may be in communication (via for example a suitable wired or wireless connection) with the heating elements **42**, **48**, **54** and other suitable components of the oven appliance **10**, as discussed herein. In general, controller **58** may be operable to configure the oven appliance **10** (and various components thereof) for cooking. Such configuration may be based on a plurality of cooking factors of a selected operating cycles, sensor feedback, etc.

(25) By way of example, controller **58** may include one or more memory devices and one or more

microprocessors, such as general or special purpose microprocessors operable to execute programming instructions or micro-control code associated with an operating cycle. The memory may represent random access memory such as DRAM, or read only memory such as ROM or FLASH. In one embodiment, the processor executes programming instructions stored in memory. The memory may be a separate component from the processor or may be included onboard within the processor.

(26) Controller **58** may be positioned in a variety of locations throughout oven appliance **10**. In the illustrated embodiment, controller **58** may be located within a user interface panel **60** of oven appliance **10** as shown in FIG. **1**. In such an embodiment, input/output (“I/O”) signals may be routed between the control system and various operational components of oven appliance **10** along wiring harnesses that may be routed through cabinet **12**. Typically, controller **58** is in communication with user interface panel **60** and controls **62** through which a user may select various operational features and modes and monitor progress of oven appliance **10**. In one embodiment, user interface panel **60** may represent a general purpose I/O (“GPIO”) device or functional block. In one embodiment, user interface panel **60** may include input components or controls **62**, such as one or more of a variety of electrical, mechanical or electro-mechanical input devices including rotary dials, push buttons, and touch pads. User interface panel **60** may include a display component, such as a digital or analog display device **64** designed to provide operational feedback to a user.

(27) User interface panel **60** may be in communication with controller **58** via one or more signal lines or shared communication busses. Controller **58** may also be in communication with one or more sensors, e.g., a temperature sensor that is used to measure temperature inside insulated cooking chamber **14** and provide such measurements to controller **58**. The temperature sensor may be a thermocouple, a thermistor, a resistance temperature detector, or any other device suitable for measuring the temperature within insulated cooking chamber **14**. In this manner, controller **58** may selectively control heating elements **42**, **48**, **54** in response to user manipulation of user interface panel **60** and temperature feedback from the temperature sensor. Controller **58** can also receive temperature measurements from the temperature sensor placed within insulated cooking chamber **14** and e.g., provide a temperature indication to the user with display **64**.

(28) It should be appreciated that the invention is not limited to any particular style, model, or configuration of oven appliance **10**. The exemplary embodiment depicted in the figures is for illustrative purposes only. For example, except as otherwise indicated, different locations may be provided for user interface panel **60**, different configurations may be provided for the baking rack or ribs **24**, different cooling air flow paths may be utilized, and other differences may be applied as well.

(29) Turning especially to FIGS. **2** and **3**, in some embodiments, door **16** defines an intake **76**, an internal conduit or channel **74**, and an exhaust **78**. In some embodiments, intake **76** of door **16** is positioned at or adjacent bottom lip of door **16** and permits air therethrough. Conversely, exhaust **78** of door **16** is positioned at or adjacent top lip of door **16**. Channel **74** extends between intake **76** of door **16** and exhaust **78** of door **16** (e.g., such that intake **76** and exhaust **78** are in fluid communication with each other when door **16** is in the closed position). During use, channel **74** permits the flow of air to flow through door **16** from intake **76** to exhaust **78**. Exhaust **78** may be located at top surface of the door **16**, a front surface of door **16**, or a combination thereof.

(30) The flow of air through door **16** can assist with limiting or reducing heat transfer along the transverse direction T (e.g., during operation of bottom or top heating elements **42** and **48** of oven range appliance **10**). As an example, an inner surface of door **16** faces and is positioned adjacent cooking chamber **14** of cabinet **12** when door **16** is in the closed position. Conversely, an outer surface of door **16** is positioned opposite inner surface of door **16** and faces away from cooking chamber **14** of cabinet **12** when door **16** is in the closed position. The flow of air can be cool relative to the inner surface of door **16** such that the flow of air limits or reduces heat transfer

between the inner surface of door **16** and the outer surface of door **16** during operation of bottom or top heating elements **48** and **42** of oven range appliance **10** (e.g., such that the outer surface of door **16** is cool relative to the inner surface of door **16**). In such a manner, the outer surface of door **16** can be insulated.

(31) Separate from or in addition to the internal channel **74** of door **16**, the cabinet **12** may generally define an airflow path **100** that extends (e.g., continuously) through the cabinet **12**. During use, the airflow path **100** may direct a cooling airflow through the cabinet **12** and about the cooking chamber **14** (e.g., to reduce the temperature of the outer panels or otherwise reduce the transmission of heat from the walls of the cooking chamber **14** to the outer panels). In the illustrated embodiment, the airflow path **100** extends within the cabinet **12** from an upper air intake **102** to a lower air exhaust **104**. As shown, air intake **102** may be defined at an upper portion of the front end of cabinet **12** (e.g., above door **16**). Air exhaust **104** may be defined at a lower portion of the front end (e.g., below door **16**).

(32) The outer panels may serve to define (e.g., at least in part) one or more segments of the airflow path **100**. For instance, airflow path **100** may be at least partially defined by the open region or gap provided between an outer panel and a wall of cooking chamber **14**. A top segment **110** may be defined between the top panel **30** and the insulated cooking chamber **14** (e.g., at top wall **25**). The top segment **110** may extend along the transverse direction T (e.g., from the front to the rear of cabinet **12**) while spanning a lateral portion of the cabinet **12** (e.g., between the left and right panels). A rear segment **112** may be defined downstream from the top segment **110** between the rear panel **34** and the insulated cooking chamber **14** (e.g., at rear wall **29**). The rear segment **112** may extend along the vertical direction V (e.g., from the top to the bottom of cabinet **12**) while spanning a lateral portion of the cabinet **12** (e.g., between the left and right panels). A bottom segment **114** may be defined downstream from the rear segment **112** between the bottom panel **31** and the insulated cooking chamber **14** (e.g., at bottom wall **26**). The bottom segment **114** may extend along the transverse direction T (e.g., from the rear to the front of cabinet **12**) while spanning a lateral portion of the cabinet **12** (e.g., between the left and right panels **32**, **33**).

(33) Although the airflow path **100** is defined between an internal surface **120** of outer panels and an exterior surface of the walls of cooking chamber **14**, it is noted that one or more intermediate elements (e.g., on or surrounding the exterior surface of cooking chamber **14**) may serve to further limit or define the airflow path **100**.

(34) A fan **90** is mounted within the cabinet **12** along the airflow path **100** and is configured for motivating air therethrough. According to the illustrated embodiment, fan **90** is a tangential fan that is positioned toward a back end of duct **130** proximate rear panel **34** of cabinet **12**. In particular, fan **90** is mounted such that a rotation axis A of fan **90** is disposed above (e.g., at a higher position relative to the vertical direction V). In the pictured embodiments, fan **90** is mounted on the left side of cabinet **12**. Alternatively, though, fan **90** could be mounted on the right side or at the center of cabinet **12**. Moreover, one skilled in the art will appreciate that any other suitable fan type, position, configuration, or number may be used while remaining within the scope of the present subject matter. For example, fan could instead be a radial fan positioned toward a front end of airflow path **100**. Additionally or alternatively, multiple fans may be provided (e.g., parallel tangential fans spaced apart along the lateral direction L).

(35) Turning now generally to FIGS. 4 through 8, various perspective views are provided of an outer panel of cabinet **12**, which forms a portion of the airflow path **100** (e.g., bottom segment **114**—FIG. 2). In particular, an exemplary bottom panel **31** is shown. As such, bottom panel **31** may be included with or provided as the bottom panel **31** shown in FIGS. 1 through 3. During use, air may thus flow across the internal surface **120** of bottom panel **31** (as indicated by arrows **118**—FIG. 5). Notably, bottom panel **31** allows for a generally even or balanced airflow spread across the lateral width of panel **31** (e.g., regardless of where fan **90** is mounted) and may cool front lower exterior surfaces.

(36) As shown, multiple guide ridges **122** may be provided along airflow path **100** to help direct air toward the air exhaust **104**. In some embodiments, guide ridges **122** may further support the weight of the appliance **10**. Together, the guide ridges **122** may form discrete sub-channels or guided segments **124** of airflow path **100**. For instance, in the illustrated embodiments, multiple guide ridges **122** extend along a length of the airflow path **100** (e.g., parallel to the transverse direction T). Each guide ridge **122** thus defines a length E along the airflow path **100** (e.g., parallel to the transverse direction T). In some embodiments, one or more guide ridges **122** are transversely spaced apart from a rear end of the bottom panel **31** (e.g., to form a space or gap between a proximal tip of guide ridge **122** and the rear end). In additional or alternative embodiments, one or more guide ridges **122** terminates at a front end of the bottom panel **31**.

(37) As shown in FIG. 6, optional embodiments may further include one or more divider trims **126** that extend above (e.g., at a higher height along the vertical direction V than) the guide ridges **122**. For instance, a divider trim **126** may extend vertically from the bottom panel **31** and forward along the transverse direction T from a rear end of the bottom panel **31**. In some such embodiments, a divider trim **126** may server to separate parallel portions of the airflow segment. In the illustrated embodiments, the divider trim **126**(s) are disposed laterally inward from one or more guide ridges **122** (e.g., to further apportion or divide a central flow of air from a flow proximal to the lateral ends of the bottom panel **31**).

(38) Returning generally to FIGS. 4 through 8, along with extending along a length of the airflow path **100**, the guide ridges **122** may extend toward the cooking chamber **14** (e.g., vertically) from the bottom panel **31**. Such guide ridges **122** may be formed directly on the bottom panel **31** (e.g., as a portion thereof). As an example, one or more guide ridges **122** may be raised embossings elevated relative to the rest of internal surface **120**. Moreover, such embossings may have an embossed inverse U-shaped channel (e.g., when viewed along the transverse direction T) extending inward toward the cooking chamber **14**. Nonetheless, alternative embodiments may have an embossed inverse V-shaped channel or otherwise be shaped in another suitable manner.

(39) In some embodiments, one or more of the guide ridges **122** are formed as a ridge set **132** having a plurality of internal ridges **134**. In a ridge set **132**, adjacent ridges **134** (e.g., adjacent along the direction of air flow for airflow path **100** or relative to the transverse direction T) may be at least partially spaced apart. Specifically, adjacent ridges **134** may be separated along the airflow path **100** (e.g., along the direction of air flow for airflow path **100**), such as along the transverse direction T. Adjacent ridges **134** may further be aligned along the airflow path **100**, such that a straight line may extend parallel to the airflow path **100** (or transverse direction T) through adjacent internal ridges **134**. In turn, a cross-path gap **136** may be defined between adjacent ridges **134**. As shown, the cross-path gap **136** creates an opening (e.g., extending at an angle relative to the airflow path **100**, such as along the lateral direction L) through which a portion of air in the airflow path **100** may pass. Thus, additional air may pass, for instance, from a high-flow center segment to an outer low-flow segment, as illustrated by FIG. 5.

(40) Notably, the volume of cooling air (and thus heat transfer effect) is increased to portions of airflow path **100** that would otherwise be omitted or have a reduced flow of air.

(41) Generally, the plurality of internal ridges **134** and cross-path gaps **136** may be formed from any suitable shape. As noted above, the internal ridges **134** may embossed inverse U-shaped channel extending inward toward the cooking chamber **14**. In certain embodiments, such as those illustrated in FIGS. 4 through 6, the cross-path gaps **136** may be V-shaped (e.g., as viewed along the lateral direction L) to define an opening perpendicular to the airflow path **100** or transverse direction T. In other embodiments, though, such as those illustrated in FIGS. 7 and 8, the cross-path gaps **136** may be angled relative to the airflow path **100** or transverse direction. For instance, each cross-path gap **136** may extend at a non-parallel, non-orthogonal angle relative to the airflow path **100** or transverse direction T, such that air may pass forward and outward through the cross-path gap **136** (from a high-flow center segment to an outer low-flow segment).

(42) Similar to shape, any suitable number of internal ridges **134** (and thus cross-path gaps **136**) may be provided. In the illustrated embodiments, at least three internal ridges **134** are provided to define two discrete cross-path gaps **136** for a corresponding ridge set **132**.

(43) In optional embodiments, multiple discrete ridge sets **132** are provided, such as a first ridge set **132** and a second ridge set **132**. As shown, each ridge set **132** includes its own plurality of internal ridges **134** defining one or more cross-path gaps **136**. Such ridge sets **132** may be spaced apart from each other in a direction distinct from the airflow path **100** (e.g., perpendicular to the airflow path **100** or along the lateral direction L). Multiple ridge sets **132** may be formed or otherwise provided in parallel to each other (e.g., parallel to the airflow path **100** or transverse direction T). Additionally or alternatively, cross-path gaps **136** of separate ridge sets **132** may be parallel to each other (e.g., along the lateral direction L).

(44) In additional or alternative embodiments, one or more continuous ridge **142s** are included with the guide ridges **122**. As shown, the continuous ridge **142** generally extends uninterrupted along its length E and does not define any cross-path gaps. The continuous ridge **142** may be spaced apart from the ridge set **132** in a direction distinct from the airflow path **100** (e.g., perpendicular to the airflow path **100** or along the lateral direction L). The continuous ridge **142** may be formed or otherwise provided in parallel to one or more ridge set **132** (e.g., parallel to the airflow path **100** or transverse direction T). Optionally, the length E of the continuous ridge set **132** may be greater than or equal to the length E of the ridge set **132**.

(45) This written description uses examples to disclose the invention, including the best mode, and also to enable any person skilled in the art to practice the invention, including making and using any devices or systems and performing any incorporated methods. The patentable scope of the invention is defined by the claims, and may include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims if they include structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal languages of the claims.

Claims

1. A oven appliance defining a vertical direction, a lateral direction, and a transverse direction, the oven appliance comprising: a cabinet comprising a plurality of outer panels and defining an airflow path extending through the cabinet; an insulated cooking chamber disposed within the cabinet, the airflow path being defined between the outer panels and the insulated cooking chamber; and a plurality of internal ridges disposed within the cabinet along the airflow path, each internal ridge of the plurality of internal ridges having a maximum-length edge extending along and parallel to the airflow path and defining a guided segment of the airflow path, the plurality of internal ridges being spaced apart along the airflow path and thereby define a cross-path gap between adjacent ridges of the plurality of internal ridges, wherein the maximum-length edge is an edge wherein no other respective edge on each internal ridge exceeds its length.
2. The oven appliance of claim 1, wherein each internal ridge of the plurality of internal ridges comprises an embossed inverse U-shaped channel extending inward toward the insulated cooking chamber.
3. The oven appliance of claim 1, wherein the plurality of outer panels comprises a top panel, a rear panel, and a bottom panel, and wherein the plurality of internal ridges is disposed between the bottom panel and the insulated cooking chamber.
4. The oven appliance of claim 3, wherein the plurality of internal ridges are formed on the bottom panel.
5. The oven appliance of claim 3, wherein the airflow path comprises a top segment between the top panel and the insulated cooking chamber, a rear segment downstream from the top segment

between the rear panel and the insulated cooking chamber, and a bottom segment downstream from the rear segment between the bottom panel and the insulated cooking chamber.

6. The oven appliance of claim 3, further comprising a fan mounted within the cabinet along the airflow path to motivate air therethrough, the fan defining a rotation axis above the insulated cooking chamber.

7. The oven appliance of claim 1, wherein the plurality of internal ridges comprise at least three internal ridges defining a plurality of cross-path gaps.

8. The oven appliance of claim 1, wherein the plurality of internal ridges is a first plurality of ridges forming a first ridge set, wherein the oven appliance further comprises a second ridge set comprising a second plurality of ridges spaced apart along the airflow path and thereby defining a cross-path gap between adjacent ridges of the second plurality of ridges, and wherein the second ridge set is parallel to the first ridge set and spaced apart therefrom along a direction distinct from the airflow path.

9. The oven appliance of claim 1, wherein the plurality of internal ridges is a first plurality of ridges forming a first ridge set having a length along the airflow path, wherein the oven appliance further comprises a continuous ridge having a length along the airflow path greater than or equal to a length of the first ridge set, and wherein the continuous ridge is parallel to the first ridge set and spaced apart therefrom along a direction distinct from the airflow path.

10. The oven appliance of claim 1, further comprising a divider trim extending above the plurality of internal ridges and spaced apart therefrom along a direction distinct from the airflow path, the divider trim separating parallel portions of the airflow path.

11. A oven appliance defining a vertical direction, a lateral direction, and a transverse direction, the oven appliance comprising: a cabinet comprising a plurality of outer panels and defining an airflow path extending through the cabinet, the plurality of outer panels comprises a top panel, a rear panel, and a bottom panel; an insulated cooking chamber disposed within the cabinet, the airflow path being defined between the outer panels and the insulated cooking chamber; and a plurality of internal ridges formed on the bottom panel within the cabinet, each internal ridge of the plurality of internal ridges having a maximum-length edge extending along and parallel to the airflow path and defining a guided segment of the airflow path, the plurality of internal ridges being spaced apart along the transverse direction and thereby defining a lateral cross-path gap between adjacent ridges of the plurality of internal ridges, wherein the maximum-length edge is an edge wherein no other respective edge on each internal ridge exceeds its length.

12. The oven appliance of claim 11, wherein each internal ridge of the plurality of internal ridges comprises an embossed inverse U-shaped channel extending inward toward the insulated cooking chamber.

13. The oven appliance of claim 12, wherein the airflow path comprises a top segment between the top panel and the insulated cooking chamber, a rear segment downstream from the top segment between the rear panel and the insulated cooking chamber, and a bottom segment downstream from the rear segment between the bottom panel and the insulated cooking chamber.

14. The oven appliance of claim 12, further comprising a fan mounted within the cabinet along the airflow path to motivate air therethrough, the fan defining a rotation axis above the insulated cooking chamber.

15. The oven appliance of claim 11, wherein the plurality of internal ridges comprise at least three internal ridges defining a plurality of cross-path gaps.

16. The oven appliance of claim 11, wherein the plurality of internal ridges is a first plurality of ridges forming a first ridge set, wherein the oven appliance further comprises a second ridge set comprising a second plurality of ridges spaced apart along the airflow path and thereby defining a cross-path gap between adjacent ridges of the second plurality of ridges, and wherein the second ridge set is parallel to the first ridge set and spaced apart therefrom along a direction distinct from the airflow path.

17. The oven appliance of claim 11, wherein the plurality of internal ridges is a first plurality of ridges forming a first ridge set having a length along the airflow path, wherein the oven appliance further comprises a continuous ridge having a length along the airflow path greater than or equal to a length of the first ridge set, and wherein the continuous ridge is parallel to the first ridge set and spaced apart therefrom along a direction distinct from the airflow path.

18. The oven appliance of claim 11, further comprising a divider trim extending above the plurality of internal ridges and spaced apart therefrom along a direction distinct from the airflow path, the divider trim separating parallel portions of the airflow path.

19. A oven appliance defining a vertical direction, a lateral direction, and a transverse direction, the oven appliance comprising: a cabinet comprising a plurality of outer panels and defining an airflow path extending through the cabinet, the plurality of outer panels comprising a bottom panel defining a high-flow center segment and an outer low-flow segment; an insulated cooking chamber disposed within the cabinet, the airflow path being defined between the bottom panel and the insulated cooking chamber; and a plurality of internal ridges disposed within the cabinet at the bottom panel below and outside of the insulated cooking chamber, each internal ridge of the plurality of internal ridges having a maximum-length edge extending along and parallel to the airflow path and defining a guided segment thereof, the plurality of internal ridges being spaced apart along the airflow path and thereby define a cross-path gap between adjacent ridges of the plurality of internal ridges permitting a portion of air in the airflow path from the high-flow center segment to the outer low-flow segment, wherein the maximum-length edge is an edge wherein no other respective edge on each internal ridge exceeds its length.

20. The oven appliance of claim 19, wherein the plurality of internal ridges is a first plurality of ridges forming a first ridge set, wherein the oven appliance further comprises a second ridge set comprising a second plurality of ridges spaced apart along the airflow path and thereby defining a cross-path gap between adjacent ridges of the second plurality of ridges, and wherein the second ridge set is parallel to the first ridge set and spaced apart therefrom along a direction distinct from the airflow path.
