

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12385689
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Park; Kyutae et al.

---

### Refrigerator

---

#### Abstract

A refrigerator includes: a cabinet forming a storage space; a door for opening and closing the storage space and provided with a receiving space; a see-through portion extending through the door and communicating with the receiving space; a door light for illuminating a rear space of the door; a transparent panel assembly for shielding the see-through portion and becoming transparent or opaque so as to selectively visualize the see-through portion according to On/Off states of the door light; and a heat insulating member, formed along a perimeter of the transparent panel assembly, for insulating a perimeter portion of the transparent panel assembly.

---

**Inventors:** Park; Kyutae (Seoul, KR), Kim; Minsub (Seoul, KR), Oh; Kyongsok (Seoul, KR), Lee; Sangmyung (Seoul, KR), Lee; Hangbok (Seoul, KR)

**Applicant:** LG Electronics Inc. (Seoul, KR)

**Family ID:** 61300907

**Assignee:** LG Electronics Inc. (Seoul, KR)

**Appl. No.:** 18/583596

**Filed:** February 21, 2024

#### Prior Publication Data

Document Identifier	Publication Date
US 20240191937 A1	Jun. 13, 2024

#### Foreign Application Priority Data

KR	10-2016-0110370	Aug. 29, 2016
----	-----------------	---------------

#### Related U.S. Application Data

continuation parent-doc US 18378516 20231010 US 12111096 child-doc US 18583596  
continuation parent-doc US 18137161 20230420 US 12007161 child-doc US 18378516  
division parent-doc US 16329457 US 11674742 20230613 WO PCT/KR2017/008473 20170804  
child-doc US 18137161

---

## Publication Classification

**Int. Cl.:** **H04L12/28** (20060101); **E06B3/70** (20060101); **E06B7/30** (20060101); **F25D23/02** (20060101); **F25D27/00** (20060101); **F25D29/00** (20060101)

**U.S. Cl.:**

**CPC** **F25D23/028** (20130101); **E06B3/70** (20130101); **E06B7/30** (20130101); **F25D23/02** (20130101); **F25D27/00** (20130101); **F25D29/00** (20130101); **H04L12/28** (20130101);

## Field of Classification Search

**CPC:** H04L (12/28)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10126849	12/2017	Lee et al.	N/A	N/A
2006/0260341	12/2005	Meyvis	N/A	N/A
2012/0105424	12/2011	Lee et al.	N/A	N/A
2013/0026900	12/2012	Oh	312/401	E05D 7/00
2014/0078407	12/2013	Green et al.	N/A	N/A
2014/0144083	12/2013	Artwohl et al.	N/A	N/A
2014/0232958	12/2013	Venturas et al.	N/A	N/A
2015/0276302	12/2014	Roh et al.	N/A	N/A
2016/0117022	12/2015	Kim	345/82	F24C 15/02

### FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2927628	12/2014	EP	N/A
3505853	12/2018	EP	N/A
2004-028542	12/2003	JP	N/A
2004-061734	12/2003	JP	N/A
10-2006-0000340	12/2005	KR	N/A
10-2008-0038965	12/2007	KR	N/A
10-2012-0044874	12/2011	KR	N/A
10-2015-0036321	12/2014	KR	N/A
10-2016-0045545	12/2015	KR	N/A
10-2016-0084020	12/2015	KR	N/A
WO 2012/057457	12/2011	WO	N/A

### OTHER PUBLICATIONS

Notice of Allowance in Korean Appln. No. 10-2024-0042810, mailed on Nov. 28, 2024, 6 pages (with English translation). cited by applicant

Extended European Search Report in European Application No. 17846858.3, dated Mar. 3, 2020, 8 pages. cited by applicant

Notice of Allowance in European Appln. No. 17846858.3, mailed on May 22, 2023, 9 pages. cited by applicant

Office Action in Chinese Appln. No. 201780049869.7, dated Apr. 21, 2020, 18 pages (with English translation). cited by applicant

Office Action in Korean Appln. No. 10-2016-0110370, mailed on Nov. 29, 2022, 12 pages (with English translation). cited by applicant

Refrigerators And Refrigerator Interior Illumination Device, Apr. 22, 2010; Publication of KR20100041055A (Year: 2010). cited by applicant

---

*Primary Examiner:* Wu; Jerry

*Attorney, Agent or Firm:* Fish & Richardson P.C.

---

## **Background/Summary**

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 18/378,516, filed on Oct. 10, 2023, which is a continuation of U.S. application Ser. No. 18/137,161, filed on Apr. 20, 2023, which is a divisional of U.S. application Ser. No. 16/329,457, filed on Feb. 28, 2019, now U.S. Pat. No. 11,674,742, which is a National Stage application under 35 U.S.C. § 371 of International Application No. PCT/KR2017/008473, filed on Aug. 4, 2017, which claims the benefit of Korean Patent Application No. 10-2016-0110370, filed on Aug. 29, 2016. The disclosures of the prior applications are incorporated by reference in their entirety.

### **TECHNICAL FIELD**

(1) The present invention relates to a refrigerator.

### **BACKGROUND**

(2) In general, refrigerators are home appliances for storing foods at a low temperature in a storage space that is covered by a door. For this, refrigerators cool the inside of the storage space by using cool air generated by being heat-exchanged with a refrigerant circulated through a refrigeration cycle to store foods in an optimum state.

(3) In recent years, refrigerators have become increasingly multi-functional with changes of dietary lives and gentrification of products, and refrigerators having various structures and convenience devices for convenience of users and for efficient use of internal spaces have been released.

(4) The storage space of the refrigerator may be opened/closed by the door. Also, refrigerators may be classified into various types according to an arranged configuration of the storage space and a structure of the door for opening and closing the storage space.

(5) In general, the refrigerator has a problem in that when the door is not opened, internal food may not be identified. That is, the door should be opened to identify whether desired food is received in a space in the refrigerator or in a separate storage space provided in the door. Further, when a user does not exactly know where the food is stored, an opening time of the door may increase or the number of times the door is opened may increase. At this time, unnecessary outflow of cold air may occur.

(6) In recent years, to solve such a limitation, a refrigerator has been developed while allows a

portion of a door thereof to be transparent or allows the inside thereof to be visible from the outside.

## SUMMARY

(7) An object of an embodiment of the present invention is to provide a refrigerator in which a see-through part that is selectively transparent by user's manipulation is provided in at least a portion of a refrigerator door, and dew condensation is prevented from occurring on the see-through part.

(8) Another object of an embodiment of the present invention is to provide a refrigerator in which at least a portion of a refrigerator door is selectively transparent by user's manipulation to allow the user to see the inside of the refrigerator even though the refrigerator door is closed, and simultaneously, to selectively output a screen.

(9) Another object of an embodiment of the present invention is to provide a refrigerator in which a see-through part of a door is capable of being transparent or opaque or outputting a screen according to selective turn-on/off of a door light or a display light.

(10) Another object of an embodiment of the present invention is to provide a refrigerator in which a transparent display is disposed on the see-through part, and a wire and a PCB within a door are not exposed through the see-through part.

(11) Another object of an embodiment of the present invention is to provide a refrigerator in which a transparent panel assembly that is viewing the inside thereof and displaying a screen is provided, and a door having a compact structure is provided.

(12) Another object of an embodiment of the present invention is to provide a refrigerator in which a transparent panel assembly is easily assembled and mounted.

(13) Another object of an embodiment of the present invention is to provide a refrigerator in which a screen displayed through a display is more clearly displayed.

(14) Another object of an embodiment of the present invention is to provide a refrigerator which is capable of being insulated without damaging a display within a door.

(15) Another object of an embodiment of the present invention is to provide a refrigerator having a slim door structure even though a display and a door light are provided in a door.

(16) Another object of an embodiment of the present invention is to provide a refrigerator in which a PCB within a door is easily dissipated.

(17) Another object of an embodiment of the present invention is to provide a refrigerator in which a PCB within a door is easily prevented from being contaminated by foreign substances while being easily dissipated.

(18) Another object of an embodiment of the present invention is to provide a refrigerator in which a screen that is capable of being touched to be manipulated is displayed on a see-through part through which an inner accommodation space is visible.

(19) Another object of an embodiment of the present invention is to provide a refrigerator which is capable of wirelessly communicating with home appliances and capable of being manipulated to output and control information of the home appliances through a see-through part through which an inner accommodation space is visible.

(20) A refrigerator according to an embodiment of the present invention includes: a cabinet defining a storage space; a door configured to open and close the storage space and provide an accommodation space; a see-through part passing through the door to communicate with the accommodation space; a door light configured to illuminate a rear space of the door; a transparent panel assembly configured to cover the see-through part and being transparent or opaque so as to allow the see-through part to be selectively visible according to turn on/off of the door light; and an insulation member disposed along a circumference of the transparent panel assembly to thermally insulate a circumferential portion of the transparent panel assembly.

(21) The transparent panel assembly may include: a front panel made of a transparent material to define a front surface of the transparent panel assembly and exposed through the see-through part; a rear panel made of a transparent material to define a rear surface of the transparent panel

assembly and spaced apart from the front panel; and an outer spacer configured to connect the front panel to the rear panel, defining an outer appearance of a circumferential surface of the transparent panel assembly, and configured to seal a gap between the front panel and the rear panel.

(22) A low-emission coating layer for the insulation may be disposed on the rear panel.

(23) A space between the front panel and the rear panel may be thermally insulated by vacuum or injecting an insulation gas.

(24) A transparent plate may be further disposed between the front panel and the rear panel, a spacer for maintaining a distance between the front panel and the rear panel may be disposed on a circumference of each of front a rear surfaces of the transparent plate, and the transparent plate and the spacer may be disposed in an inner space of the outer spacer.

(25) A heating member configured to heat a circumference of the front panel may be disposed on a circumference of a rear surface of the see-through part contacting the circumference of the front panel.

(26) An opaque bezel may be disposed on a circumference of the front panel, and a heating member configured to heat the circumference of the front panel may be disposed on the bezel.

(27) The front panel may further protrude outward than the rear panel, and the bezel may be disposed on a rear surface of the protruding portion of the front panel.

(28) The door may include an out plate which defines an outer appearance of a front surface and through which the see-through part is opened, and an inner frame which is disposed along a circumference of the see-through part and on which a protruding end of the front panel is seated.

(29) A bent part that is bent along the see-through part may be disposed on the out plate, an accommodation groove into which an end of the bent part is inserted may be defined in the inner frame, and a space between the see-through part and the front panel may be covered by the inner frame.

(30) A rib supporting an end of the front panel may be disposed on the rear surface of the inner frame.

(31) The transparent panel assembly may include: a display configured to output a screen and being transparent; and a display light configured to emit light for so as to output the screen on the display, wherein the door light and the display light are disposed along a circumference of the transparent panel assembly.

(32) The door light may be disposed along each of left and right ends of the transparent panel assembly, and the display light may be disposed along each of upper and lower ends of the transparent panel assembly.

(33) When the see-through part is in the opaque state, the transparent panel assembly output a black screen, and the display light may be turned on to heat the circumference of the transparent panel assembly.

(34) When the see-through part is in the opaque state, the display light may be periodically turned on.

(35) When the see-through part is in the opaque state, all of the display light and the door light may be turned on.

(36) The insulation member may be assembled and mounted after being molded into a plurality of parts, and, when assembled, the insulation member may have a rectangular frame shape surrounding a circumferential surface of the transparent panel assembly.

(37) A supplement member configured to support the transparent panel assembly may be further disposed between the insulation member and the transparent panel assembly.

(38) The supplement member may include an adhesive or a sealing member for fixing the insulation member and the transparent panel assembly.

(39) The supplement member may be made of an elastic material to fix the transparent panel member and prevent an impact from being applied to the transparent panel member.

(40) The supplement member may include: a first supplement member made of an elastic material

to press and support the circumference of the transparent panel assembly; and a second supplement member disposed between the first supplement member and the insulation member to allow the first supplement member and the insulation member to adhere to each other.

(41) The following effects may be expected in the refrigerator according to the proposed embodiments.

(42) In the refrigerator according to the embodiment of the present invention, the insulation may be disposed on the circumference of the transparent panel assembly to prevent the dew condensation from occurring on the circumference of the transparent panel assembly.

(43) Also, the heating member may be disposed on the bezel of the transparent panel assembly to more effectively prevent the dew condensation from occurring on the transparent panel assembly.

(44) Also, the door light and the display light may be provided on the circumference of the transfer panel assembly, and when the see-through part outputs the screen that is in the black state, the door light and/or the display light may be turned on to heat the circumference of the transparent panel assembly, thereby preventing the dew condensation from occurring on the circumference of the transparent panel assembly.

(45) Also, the low-emission coating layer may be disposed on the rear panel of the transparent panel assembly to improve the insulation performance and prevent the dew condensation from occurring on the transparent panel assembly.

(46) Also, the inside of the transparent panel assembly may be provided with the multilayered panel structure, and the vacuum or the insulation gas may be injected into the transparent panel assembly to improve the insulation performance, thereby more preventing the dew condensation from occurring on the transparent panel assembly.

(47) Also, the supplement member may be disposed between the transparent panel assembly and the insulation member to prevent the gap from occurring between the transparent panels, thereby more stably supporting the transparent panels.

(48) Also, the see-through part through which the accommodation space is visible may be provided in the door. The see-through part may include the transparent display and be selectively transparent or opaque according to the turn-on/off of the door light and the display light. Thus, the user may confirm the accommodation space through the see-through part by the user's manipulation without opening the door to improve the user's convenience and reduce the power consumption.

(49) Also, in the see-through part, the display may operate according to the user's manipulation to display various screens and thereby to provide various information for the user's convenience and allow the user to input the manipulation thereof, thereby improving the user's convenience.

(50) Also, in the state in which the see-through part is transparent, the screen of the display may be outputted. Thus, see-through part may provide the same use environment as the augmented reality through the see-through part to more improve the use convenience.

(51) Also, at least a portion of the cable connected to the transparent display within the door, the cable connecting the door light to the display light, and the PCBs for controlling the cables may be provided with the same structure as the flexible flat cable and thus be disposed along the circumference of the transparent panel assembly. Thus, the cables may not be exposed through the see-through part to more improve the outer appearance.

(52) Also, the plurality of wires may be disposed along the circumference of the transparent display panel to minimize the space which the wires are accommodated, thereby realizing the compact door.

(53) Also, the PCB may be disposed in the upper portion of the door and be guided in the form of the wire to the outside of the door to minimize the portion through which the wires are accessible and provide the structure to be easily connected to the main control unit.

(54) Also, the PBC provided in the upper portion of the door may be covered by the upper cap decor. The heat dissipation hole may be defined in the upper decor so that the heat generated in the PCB is easily released.

(55) Also, the heat dissipation hole guide may be provided in the heat dissipation hole to easily release the heat, and also, the contaminants may not be directly introduced into the PCB to secure the safety.

(56) Also, the adaptor and the display PCB, each of which has the relatively large volume, of the PCBs for driving the electronic components within the door may be disposed on the main PCB disposed on the cabinet to realize the slim structure of the door.

(57) Also, the front panel defining the front surface of the transparent panel assembly may have the size greater than that of the see-through part so as to be stably supported on the inner surface of the door. In addition, the front panel may be assembled and mounted later to improve the durability and also improve the assemblability and productivity.

(58) Also, the front panel may have the size greater than that of the display, and thus, when the touch sensor is disposed, the front panel may be disposed to be touched on the entire area of the display, thereby improving the usability.

(59) Also, the insulation member that is previously molded along the circumference of the transparent panel assembly may be assembled and mounted inside the door to improve the assemblability and the productivity and also prevent the display and the PCB from being damaged when being foamed.

(60) Also, the supplement member may be provided between the insulation member and the transparent panel assembly to buffer the impact applied to the transparent panel assembly to fix the transparent panel assembly and the previously molded insulation member with respect to each other and fill the gap between the transparent panel assembly and the insulation member.

(61) Also, the supplement member may be made of the material having the adhesion and sealing property so that the insulation member is firmly fixed to the out plate and the door liner inside the door.

(62) Also, the communication module that communicates with the external device may be provided in the main control unit to output the image or information of the terminal that is portable by the user or the remote personal computer through the see-through part.

(63) Also, the communication module and the plurality of home appliances in the home may be connected to communicate with each other, thereby establishing the home network. Also, the information output and the operation control of the home appliances may be enabled through the see-through part to more improve the use convenience.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a front view of a refrigerator according to a first embodiment of the present invention.
- (2) FIG. 2 is a perspective view of the refrigerator.
- (3) FIG. 3 is a perspective view of the refrigerator with a sub door opened.
- (4) FIG. 4 is a perspective view of the refrigerator with a main door opened.
- (5) FIG. 5 is an exploded perspective view illustrating a coupling structure of the main door and the sub door.
- (6) FIG. 6 is a partial perspective view illustrating a hinge-coupled structure of the main door and an upper end of the sub door.
- (7) FIG. 7 is a partial perspective view illustrating a state in which a hinge cover is mounted on the main door and the sub door.
- (8) FIG. 8 is a partial perspective view illustrating a top surface of the refrigerator.
- (9) FIG. 9 is a partial perspective view illustrating a hinge-coupled structure of a lower end of the main door.
- (10) FIG. 10 is a perspective view of the sub door when viewed from a front side.

- (11) FIG. 11 is a perspective view of the sub door when viewed from a rear side.
- (12) FIG. 12 is an exploded perspective view of the sub door.
- (13) FIG. 13 is a perspective view of an out plate when viewed from the rear side according to a first embodiment of the present invention.
- (14) FIG. 14 is a perspective view of an inner frame when viewed from the rear side according to the first embodiment of the present invention.
- (15) FIG. 15 is an exploded perspective view of the inner frame when viewed from the rear side.
- (16) FIG. 16 is an exploded perspective view of the inner frame when viewed from the front side.
- (17) FIG. 17 is a perspective view of a transparent panel assembly according to the first embodiment of the present invention.
- (18) FIG. 18 is an exploded perspective view of the transparent panel assembly.
- (19) FIG. 19 is a cross-sectional view of the transparent panel assembly.
- (20) FIG. 20 is a perspective view of a spacer according to the first embodiment of the present invention.
- (21) FIG. 21 is a cross-sectional view of the spacer.
- (22) FIG. 22 is a perspective view of an outer spacer according to the first embodiment of the present invention.
- (23) FIG. 23 is a cross-sectional view of the outer spacer.
- (24) FIG. 24 is an exploded perspective view illustrating an arranged structure of a PCB on an upper portion of the sub door.
- (25) FIG. 25 is a cross-sectional view illustrating an upper portion of the sub door.
- (26) FIG. 26 is a perspective view of an insulation member according to the first embodiment of the present invention.
- (27) FIG. 27 is a perspective view of a door liner when viewed from the front side according to the first embodiment of the present invention.
- (28) FIG. 28 is a perspective view of the door liner when viewed from the rear side.
- (29) FIG. 29 is a perspective view of a door light according to the first embodiment of the present invention.
- (30) FIG. 30 is an exploded perspective view of the door light.
- (31) FIG. 31 is a block diagram illustrating a flow of a control signal of the refrigerator.
- (32) FIG. 32 is a longitudinal cross-sectional view of a refrigerating compartment door.
- (33) FIG. 33 is a cross-sectional view taken along line 33-33' of FIG. 10.
- (34) FIG. 34 is a cross-sectional view taken along line 34-34' of FIG. 11.
- (35) FIG. 35 is a transversely cross-sectional view of the refrigerating compartment door.
- (36) FIG. 36 is a cross-sectional view taken along line 36-36' of FIG. 10.
- (37) FIG. 37 is a cross-sectional view taken along line 37-37' of FIG. 11.
- (38) FIG. 38 is a front view when the refrigerator is in an opaque mode.
- (39) FIG. 39 is a transversely schematic cross-sectional view illustrating an example of a turn-on state when the refrigerator is in the opaque mode.
- (40) FIG. 40 is a transversely schematic cross-sectional view illustrating another example of a turn-on state when the refrigerator is in the opaque mode.
- (41) FIG. 41 is a front view when the refrigerator is in a transparent mode.
- (42) FIG. 42 is a transversely schematic cross-sectional view illustrating an example of a turn-on state when the refrigerator is in the transparent mode.
- (43) FIG. 43 is a transversely schematic cross-sectional view illustrating another example of a turn-on state when the refrigerator is in the transparent mode.
- (44) FIG. 44 is a front view when the refrigerator is in a transparent output mode.
- (45) FIG. 45 is a transversely schematic cross-sectional view a turn-on state when the refrigerator is in a screen output mode.
- (46) FIG. 46 is a front view of the refrigerator in a state in which an image is played in the screen



output mode.

(47) FIG. **47** is a front view of the refrigerator in a state in which an Internet connection page is shown in the screen output mode.

(48) FIG. **48** is a front view of the refrigerator in a state in which a standby screen is outputted in the screen output mode.

(49) FIG. **49** is a front view of a state in which a refrigerator manipulation screen is outputted when the transparent display is in a screen output state.

(50) FIG. **50** is a schematic view of a home network constituted by using the refrigerator.

(51) FIG. **51** is a perspective view of a sub door when viewed from a rear side according to a second embodiment of the present invention.

(52) FIG. **52** is an exploded perspective view of a transparent panel assembly according to a third embodiment of the present invention.

(53) FIG. **53** is a perspective view of a sub door when viewed from a front side according to a fourth embodiment of the present invention.

(54) FIG. **54** is an exploded perspective view of a sub door according to a fifth embodiment of the present invention.

(55) FIG. **55** is a transversely cross-sectional view of a sub door according to a sixth embodiment of the present invention.

(56) FIG. **56** is an exploded perspective view of a sub door according to a seventh embodiment of the present invention.

(57) FIG. **57** is an exploded perspective view of a sub door according to an eighth embodiment of the present invention.

#### DETAILED DESCRIPTION

(58) Hereinafter, detailed embodiments of the present invention will be described in detail with reference to the accompanying drawings. However, the scope of the present disclosure is not limited to proposed embodiments, and other regressive inventions or other embodiments included in the scope of the spirits of the present disclosure may be easily proposed through addition, change, deletion, and the like of other elements.

(59) FIG. **1** is a front view of a refrigerator according to a first embodiment of the present invention. Also, FIG. **2** is a perspective view of the refrigerator.

(60) Referring to FIGS. **1** and **2**, a refrigerator **1** according to a first embodiment of the present invention includes a cabinet **10** defining a storage space and a door that opens or closes the storage space. Here, an outer appearance of the refrigerator **1** may be defined by the cabinet **10** and the door.

(61) The inside of the cabinet **10** is partitioned into upper and lower portions by a barrier **11**. A refrigerating compartment **12** may be defined in the upper portion of the cabinet **10**, and a freezing compartment **13** may be defined in the lower portion of the cabinet **10**.

(62) The door may include a refrigerating compartment door and a freezing compartment door **30**. The refrigerating compartment door **20** may be opened and closed by rotating an opened front surface of the refrigerating compartment **12**, and the freezing compartment door **30** may be switched by rotating an opened front surface of the freezing compartment **13**.

(63) Also, the refrigerating compartment door **20** may be provided in a pair of left and right doors. Thus, the refrigerating compartment **12** is covered by the pair of doors. The freezing compartment door **30** may be provided in a pair of left and right doors. Thus, the freezing compartment **13** may be opened and closed by the pair of doors. Alternatively, the freezing compartment door **30** may be withdrawable in a draw type as necessary and provided as one or more doors.

(64) Also, various accommodation members such as shelves, drawers, or baskets may be provided in the refrigerating compartment **12** and the freezing compartment **13**. Each of the accommodation members may be accessible as necessary in a state in which the refrigerating compartment door **20** and the freezing compartment door **30** are opened and also may accommodate and store foods

through insertion and withdrawal thereof.

(65) Although a refrigerator in which, a French type door in which a pair of doors rotate to open and close one space is applied to a bottom freezer type refrigerator in which the freezing compartment **13** is provided at a lower portion, is described as an example in the first embodiment of the present invention, the present invention may be applied to all types of refrigerators including door without being limited to shapes of the refrigerators.

(66) When viewed from a front side, the refrigerating compartment door **20** and the freezing compartment door **30** may define the overall outer appearance and made of a metal material so that the whole of the refrigerator has a texture of the metal material. Also, as necessary, a dispenser for dispensing water or ice may be provided in one refrigerating compartment door **20** of the pair of refrigerating compartment doors **20**.

(67) Also, recessed handle grooves **201** and **301** may be provided in a lower end of the refrigerating compartment door **20** and an upper end of the freezing compartment door **30**. A user may insert a his/her hand into the handle groove **201** or **301** to open and close the refrigerating compartment door **20** or the freezing compartment door **30**.

(68) At least one door may be provided so that the interior of the refrigerator is visible through the door. For example, as illustrated in FIG. 2, a see-through part **21** that is an area, through which the storage space in the rear surface of the door and/or the inside of the refrigerator are visible, may be provided in the refrigerating compartment door **20**. The see-through part **21** may constitute at least a portion of a front surface of the refrigerating compartment door **20**. The see-through part **21** may be selectively transparent or opaque according to user's manipulation. Thus, foods accommodated in the refrigerator may be accurately identified through the see-through part **21**.

(69) Also, although the structure in which the see-through part **21** is provided in the refrigerating compartment door **20** is described as an example in the first embodiment of the present invention, the see-through part **21** may be provided in different types of refrigerator doors such as the freezing compartment door **30** according to a structure and configuration of the refrigerator.

(70) FIG. 3 is a perspective view of the refrigerator with a sub door opened. Also, FIG. 4 is a perspective view of the refrigerator with a main door opened.

(71) As illustrated in FIGS. 3 and 4, the refrigerating compartment door **20**, which is disposed at the right side (when viewed in FIG. 3), of the pair of refrigerating compartment doors **20** may be doubly opened and closed. In detail, the refrigerating compartment door **20**, which is disposed at the right side, may include a main door **40** that opening and closing the refrigerating compartment **12** and a sub door **50** rotatably disposed on the main door **40** to open and close an opening defined in the main door **40**.

(72) The main door **40** may have the same size as that of the refrigerating compartment door **20**, which is disposed at the left side (when viewed in FIG. 1), of the pair of refrigerating compartment doors **20**. The main door **40** may be rotatably mounted on the cabinet **10** by an upper hinge **401** and a lower hinge **402** to open at least a portion of the refrigerating compartment door **12**.

(73) Also, an opening **41** that is opened with a predetermined size is defined in the main door **40**. A door basket **431** may be mounted on the rear surface of the main door **40** as well as the inside of the opening **41**. Here, the opening **41** may have a size that occupies most of the front surface of the main door **40** except for a portion of a circumference of the main door **40**.

(74) Also, a main gasket **45** may be disposed on a circumference of the rear surface of the main door **40** to prevent cool air within an internal space of the cabinet **10** from leaking when the main door **40** is opened.

(75) The sub door **50** may be rotatably mounted on the front surface of the main door **40** to open and close the opening **41**. Thus, the sub door **50** may be opened to expose the opening **41**.

(76) The sub door **50** may have the same size as the main door **40** to cover the entire front surface of the main door **40**. Also, when the sub door **50** is closed, the main door **40** and the sub door **50** may be coupled to each other to provide the same size and configuration as those of the left

refrigerating compartment door **20**. Also, a sub gasket **503** may be disposed on the rear surface of the sub door **50** to seal a gap between the main door **40** and the sub door **50**.

(77) A transparent panel assembly **60** that selectively sees the inside and outputs a screen may be disposed at a center of the sub door **50**. Thus, even though the sub door **50** is closed, the inside of the opening **41** may be selectively visible, and also an image inside the opening **41** may be outputted. The see-through part **21** may be a portion of the sub door **50**, through which the inside of the refrigerator **1** is visible. However, the see-through part **21** may not necessarily match the entirety of the transparent panel assembly **60**.

(78) The transparent panel assembly **60** may be configured to be selectively transparent or opaque according to user's manipulation. Thus, only when the user desires, the transparent panel assembly **60** may be transparent so that the interior of the refrigerator **1** is visualized, otherwise, be maintained in the opaque state. Also, the transparent panel assembly **60** may output a screen in the transparent or opaque state.

(79) A sub upper hinge **501** and a sub lower hinge **502** may be respectively provided on upper and lower ends of the sub door **50** so that the sub door **50** is rotatably mounted on the front surface of the main door **40**. Thus, the sub door **50** may independently rotate in a state in which the main door **40** is closed to open and close the opening **41**.

(80) Also, an opening device **59** may be provided on the sub door **50**. A locking unit **42** may be provided on the main door **40** to correspond to the opening device **59**. Thus, the sub door **50** may be maintained in the closed state by the coupling between the opening device **59** and the locking unit **42**. When the coupling between the opening device **59** and the locking unit **42** is released by manipulation of the opening device **59**, the sub door **50** may be opened with respect to the main door **40**.

(81) Also, in a state in which the sub door **50** is closed, the state in which the opening device **59** and the locking unit **42** are coupled to each other may be maintained. In this state, when the handle groove **201** is grasped and pulled, the main door **40** may rotate to open the refrigerating compartment **12**.

(82) In the sub door **50** is closed, when the user manipulates the opening device **59** of the sub door **50**, the opening device **59** and the locking unit **42** may be separated from each other, and thus, only the sub door **50** may rotate. Also, the opening device **42** may be opened by the rotation of the sub door **50**.

(83) Also, a damping device **504** may be provided on a lower end of the sub door **50**. The damping device **504** may protrude from a rear surface of the sub door **50** and be disposed on an edge portion of each of lower and side ends of the sub door **50** adjacent to the sub lower hinge **502**.

(84) In the state in which the sub door **50** is closed, when the opening device **59** is manipulated, the coupling between the opening device **59** and the locking unit **42** may be released, and the sub door **50** may naturally rotate by elastic restoring force of an elastic member supporting the damping device **504**.

(85) Also, when the sub door **50** is closed in the opened state, even though the sub door **50** rapidly rotates due to user's carelessness, the damping device **504** may first contact the main door **40** before the sub door **50** and the main door **40** collide with each other. Then, the rotation of the sub door **50** may be decelerated to be buffered while the elastic member is compressed.

(86) An accommodation case **43** may be provided in the rear surface of the main door **40**. The accommodation case **43** may define an accommodation space of the rear surface of the main door **40**, and a plurality of door baskets **431** may be disposed in the accommodation case **43**.

(87) The accommodation case **43** may be accessible through the opening **41**. When the sub door **50** is opened, an opened front surface of the accommodation case **43**, i.e., the opening **41** may be exposed, and the user may take the foods in or out through the opening **41**.

(88) A rear surface of the accommodation case **43** may be exposed when the main door **40** is opened. Also, a case door **432** may be provided to open at least a portion of the rear surface of the

accommodation case **43**. When the main door **40** is opened, the case door **432** may be opened.

Here, the user may take the foods in or out through the opened side of the accommodation case **43**.  
(89) That is, the accommodation case **43** may be accessible to the sub door **50** or the main door **40** when the sub door **50** or the main door **40** are opened.

(90) Also, an opening may be defined in each of the accommodation case **43** and the case door **432** so that cold air within the refrigerator is introduced into the accommodation case **43**. Thus, the inside of the accommodation case **43** may be maintained at the same temperature as that of the inside of the refrigerating compartment **12**.

(91) Also, a molded end on which the door basket **431** is mounted may be disposed on the rear surface of the main door **40**, more particularly, each of both side surfaces of the opening **41**. The molded end may have an uneven structure and be configured so that the door basket **431** is detachable.

(92) FIG. 5 is an exploded perspective view illustrating the coupling structure of the main door and the sub door. Also, FIG. 6 is a partial perspective view illustrating a hinge-coupled structure of the main door and an upper end of the sub door. Also, FIG. 7 is a partial perspective view illustrating a state in which a hinge cover is mounted on the main door and the sub door. Also, FIG. 8 is a partial perspective view illustrating the top surface of the refrigerator.

(93) As illustrated in the drawings, an upper hinge mounting part **441** on which an upper hinge **401** is mounted may be recessed to be defined in an upper end of the main door **40**. The upper hinge **401** may be fixed to be mounted on the cabinet **10**. Here, a hinge shaft **401a** may be inserted into a hinge hole **441a** of the upper hinge mounting part **441** so that the main door **40** is rotatably mounted on the cabinet **10**.

(94) Also, a sub upper hinge mounting part **541** on which the sub upper hinge **501** is mounted is recessed in an upper end of the sub door **50**. The sub upper hinge **501** may be fixed to be mounted on the upper hinge mounting part **441**, and the hinge shaft **501a** may be inserted into the hinge hole **541a** of the upper hinge mounting part **541** so that the sub door **50** is rotatably mounted on the main door **40**.

(95) The upper hinge **401** and the sub upper hinge **501** may be accommodated inside a main hinge cover **45** and a sub hinge cover **58**. The main hinge cover **45** and the sub hinge cover **58** may have a structure connected to each other. A wire L guided to the outside through a wire hole **542** of the sub door **50** may be guided to the main control unit **14** through the inside of the main hinge cover **45** by passing through the inside of the sub hinge cover **58**. Thus, the wire L may be guided to the main control unit **14** in a state in which the exposure of the wire L is minimized.

(96) In detail, the wire L within the sub door **50** may be guided to the outside through the wire hole **542** of the rear surface of the upper end of the sub door **50**. The wire hole **542** may be defined in a door liner **56** or an upper cap decor **54**, which constitutes the sub door **50**.

(97) Also, the wire L may be connected to electronic components provided in the sub door **50**. For example, the wire L may be connected to the electronic components such as a T-CON board **623**, a touch PCB **613**, a light PCB **683**, and a door light **57**, which will be described below. Thus, the number of wires L may increase, and the wire L may increase in volume. As a result, the wire L may be exposed to the outside of the sub door **50** through the wire hole **542**. The wires L exposed to the outside may be protected by a separate constitute such as a contraction tube.

(98) A cover hole **581** may be defined in the sub hinge cover **58** corresponding to the wire hole **542**. The cover hole **581** may provide a passage through which the wire L exposed through the wire hole **542** is introduced into the sub hinge cover **58**. The wire hole **542** and the cover hole **581** may be disposed at positions adjacent to the hinge shaft **501a** of the sub upper hinge **501** so as to be maintained in the shortest distance even though the sub door **50** is opened and closed. Thus, the exposure of the wire L exposed when the sub door **50** is opened and closed may be minimized.

(99) The main hinge cover **45** may have an opened lower side. Also, a space that is recessed inward may be defined in the main hinge cover **45** to accommodate the whole of the upper hinge **401**. The

main hinge cover **45** may be fixed and mounted through a structure matching one side of the cabinet **10** or a structure that is coupled by a separate coupling member. Also, a portion of the main hinge cover **45** extends to the upper hinge mounting part **441** of the main door **40**.

(100) An extension part **451** extending in a direction of a rotation axis of the upper hinge **401** may be further provided at one side of the main hinge cover **45**. Also, a main connection part **452** may be disposed on an end of the extension part **451**. The main connection part **452** may be stepped downward from the end of the extension part **451**. Also, the main connection part **452** may have a circular shape. A center of the main connection part **452** may be disposed in the same extension line as the hinge shaft **501a** of the upper hinge **401**. Also, a connection part hole **453** may be opened in a top surface of the main connection part **452** so that the wire L is accessible.

(101) The sub hinge cover **58** may have an opened lower side. Also, a space that is recessed inward may be defined in the main hinge cover **45** to accommodate the whole of the sub upper hinge **501**. The sub hinge cover **58** may be fixed and mounted on the upper hinge mounting part **441**. Also, a portion of the sub hinge cover **58** may extend to the sub upper hinge mounting part **541** to cover the sub upper hinge **501**.

(102) A cover fixing part **582** that is recessed downward may be provided at one side of the sub upper hinge **501**, and a coupling member such as a screw may pass through the cover fixing part **582** and then be coupled to the sub upper hinge mounting part **541** to fix the sub hinge cover **58**.

(103) The sub hinge cover **58** may have a shape corresponding to a space between the sub upper hinge mounting part **541** and the main hinge cover **45** in the state in which the sub door **50** is closed to prevent the sub door **50** and the main door **40** from interfering with each other when the sub door **50** and the main door **40** are opened and closed.

(104) Also, a sub connection part **583** is disposed at one side of the sub hinge cover **58**. The sub connection part **583** may extend to the main door **40** and be seated on the top surface of the main connection part **452**. Here, the sub connection part **583** may have an opened bottom surface. The inside of the sub connection part **583** may communicate with the inside of the main connection part **452** by the connection hole **453**. The sub connection part **583** may have a circular cross-section like the main connection part **452** and be disposed in the same extension line as a center of the rotation shaft of the upper hinge **401**.

(105) That is, the center of the rotation shaft of the upper hinge **401** and the center of each of the main connection part **452** and the sub connection part **583** may be concentric to each other. Thus, in a state in which the main door **40** and the sub door **50** rotate, the rotation shaft of the upper hinge **401**, and the main connection part **452**, and the sub connection part **583** may stably rotate without moving. Also, in the state in which the main door **40** or the sub door **50** rotate, the wire L guided through the sub hinge cover **58** may successively pass through the sub connection part **583** and the main connection part **452** and then be guided to the inside of the main hinge **45**.

(106) Here, when the electronic components such a heater are provided in the main door **40**, the other wire L passing through the rotation shaft of the upper hinge **401** may be introduced. Here, the other wire L together with the wire L introduced into the sub door **50** may be connected to the main control unit **14** through the main hinge cover **45**.

(107) Also, the wire L may be guided from the inside of the main hinge cover **45** to the inside of the cabinet **10** to extend along the inside of the cabinet **10** and then to be connected to the main control unit **14**.

(108) A main control unit **14** may be disposed on the top surface of the cabinet **10**. The main control unit **14** may control an overall operation of the refrigerator **1** and be connected to the wires L guided to the outside through the sub door **50**. The main control unit **14** may protrude from a central portion of the top surface of the cabinet **10** and be disposed between the pair of main hinge covers **45**.

(109) The wire L guided to the outside through the sub door **50** sequentially passes through the sub hinge cover **58** and the main hinge cover **45**. The wire L guided to the top surface of the cabinet **10**

through the main hinge cover **45** may be guided toward the main control unit **14** and then be connected to the main control unit **14**. Thus, the main control unit **14** may be connected to the electronic components inside the sub door **50** to receive operation information of the electronic components and also control the electronic components as necessary.

(110) In detail, the main control unit **14** may include a main PCB **141** controlling an overall operation of the refrigerator and a display PCB **142** controlling an operation of the transparent panel assembly **60**. The display PCB **142** may be configured to control an operation of the transparent panel assembly **60** and also control the screen outputted through the transparent panel assembly **60**. Particularly, the display PCB **142** may have a function of outputting a moving picture and an Internet screen through the transparent panel assembly **60** and also a function for connection with an external device and a function for communication with the transparent panel assembly **60**.

(111) The display PCB **142** may be a portion of the constituents for controlling the operation of the transparent panel assembly **60**. That is, the constituents for controlling the transparent panel assembly **60** may be divided into a plurality of constituents. At least a portion of the plurality of constituents may be disposed in the main control unit **14** to minimize a size and kind of the PCBs **601** disposed inside the sub door **50**. For this, the PCBs for controlling the transparent panel assembly **60** may be divided for a function or size. Here, the relatively large constituents or the constituents that are easily disposed at a remote distance through the wires may be disposed in the main control unit.

(112) The adaptor **143** for converting power supplied to the transparent panel assembly **60** may be further disposed on the main control unit **14**. DC power may be converted into AC power that is suitable for driving the transparent panel assembly **60** by the adaptor **143**. Also, since the adaptor **143** has a relatively large size and generate large amount of heat, it may be efficient when the adaptor **143** is disposed in the main control unit **14** rather than the sub door **50**. As necessary, other PCBs disposed in the sub door **50** may be further disposed in the main control unit **14**.

(113) Also, the PCBs disposed in the main control unit **14** may be disposed in spaces that are partitioned from each other. Thus, the PCBs may be disposed to be selectively combined according to specification of the refrigerator **1**.

(114) At least a portion of the main control unit **14** may include a control unit cover that is openable. Thus, the main control unit **14** may be easily connected to the wires **L** disposed in the sub door **50**. Also, the control unit cover **144** may be opened and closed to easily perform service operations for the main control unit **14** and the constituents connected to the main control unit **14**.

(115) A lower hinge **402** supporting a lower end of the main door **40** is mounted on one side of a front surface of the cabinet **10**. Also, a sub lower hinge **502** supporting the sub door **50** is mounted on a lower end of the main door **40**.

(116) FIG. **9** is a partial perspective view illustrating a hinge-coupled structure of a lower end of the main door.

(117) As illustrated in the drawing, the lower hinge **402** may be mounted on the front surface of the cabinet **10** so that the main door **40** is rotatably supported. The lower hinge **402** may be fixed and mounted on the front surface of the cabinet **10** so that the lower end of the main door **40** is rotatably supported. Thus, the main door **40** may rotate with respect to the center of a rotation shaft **402a** of the lower hinge **402**.

(118) Also, the sub lower hinge **502** may be disposed at a front side of the lower hinge **402** and fixed and mounted on the lower end of the main door **40**. The sub lower hinge **502** may be mounted on a sub lower hinge mounting part **551** that is recessed in the lower end of the front surface of the main door **40**.

(119) The lower end of the sub door **50** may be supported by the sub door hinge **502** to rotate with respect to the hinge shaft **501a**. A sub lower cap decor **55** may be disposed on the lower end of the sub door **50**. The sub lower cap decor **55** may define the bottom surface of the sub door **50**, and a decor member **554** may be coupled to a lower end of the front surface of the lower cap decor **55**.

The decor member **554** may be a constituent for decoration such as chrome plating.

(120) Also, the decor member **554** may be disposed on the lower end of the sub door **50**, in which the handle groove **201** is disposed, and user's eyes are drawn. The decor member **554** may be made of a plastic material that is surface-treated, like the chrome plating. Also, the decor member **554** may be disposed at a position in which the handle groove **201** is defined. Thus, an appearance of the handle groove **201** may be enhanced, and the handle groove **201** may increase in discrimination. The decor member **554** may also be disposed on an upper end of the freezing compartment door **30** in addition to the lower end of the refrigerating compartment door **20**.

(121) A shaft mounting part **552** on which the rotation shaft **502a** of the sub lower hinge **502** is mounted may be recessed in one end of the sub lower cap decor **55**. A lower boss **553** may be provided on the shaft mounting part **552**. The lower boss **553** may have a rotation shaft hole **553b** into which the rotation shaft **502a** is inserted and have a cylindrical shape or a cylindrical shape having a closed top surface. Also, the lower boss **553** may be made of an engineering plastic material having excellent strength and abrasion resistance.

(122) Since the heavy transparent panel assembly **60** is disposed on the sub door **50**, the whole sub door **50** may increase in weight. Thus, the shaft mounting part **552** may have a sufficient thick thickness to stably support the sub door **50** and prevent the sub door **50** from being damaged while rotating.

(123) Also, mounting part groove **552a** may be defined in the shaft mounting part **552**, and a boss protrusion **553a** may be disposed on the lower boss **553**. In detail, the mounting part groove **552a** extending in a vertical direction may be defined in an inner surface of the shaft mounting part **552**. The mounting part groove **552a** may be provided in plurality at predetermined intervals along a circumference of the inner surface of the shaft mounting part **552**. Thus, a load applied to the shaft mounting part **552** may be dispersed to prevent the shaft mounting part **552** from being damaged.

(124) Also, the plurality of boss protrusions **553a** may be disposed on an outer surface of the lower boss **553**. The boss protrusions **553a** may be provided at positions and in number corresponding to the mounting part grooves **552a**. When the lower boss **553** is mounted, the boss protrusions **553a** and the mounting part grooves **552a** may be coupled to each other. Thus, the lower boss **553** may also be reinforced and prevented from being damaged.

(125) FIG. **10** is a perspective view of the sub door when viewed from the front side. FIG. **11** is a perspective view of the sub door when viewed from the rear side. FIG. **12** is an exploded perspective view of the sub door.

(126) As illustrated in the drawings, the sub door **50** may include an out plate **51** defining an outer appearance of the sub door **50**, a door liner **56** mounted to be spaced apart from the out plate **51**, the transparent panel assembly **60** mounted on an opening of the out plate **51** and the door liner **56**, and upper and lower cap decors **54** and **55** defining the top and bottom surfaces of the sub door **50**. The above-described constituents may be coupled to define the whole outer appearance of the sub door **50**.

(127) The out plate **51** may constitute an outer appearance of the front surface of the sub door **50** and a portion of a peripheral surface of the sub door **50** and be made of a stainless steel material. Also, a plate opening **511** in which the transparent panel assembly **60** is disposed may be defined in a center of the out plate **51**. The plate opening **511** may be a space through which the inside of the opening **411** of the main door **40** is visible and have a size that is equal or similar to that of the opening **41**.

(128) The door liner **56** defines the rear surface of the sub door **50** and has a door liner opening **561** in the area on which the transparent panel assembly **60** is disposed. Also, a sub gasket **503** for sealing a gap between the sub door **50** and the main door **40** may be mounted on the rear surface of the door liner **56**.

(129) Also, a door light **57** may be provided on each of both sides of the door liner opening **561**. The door light **57** may illuminate the rear surface of the sub door **50** and a rear side of the

transparent panel assembly **60**.

(130) Thus, the door light **57** may illuminate an inner space of the accommodation case **43**, and simultaneously, serve as an auxiliary backlight function of the transparent panel assembly **60** to more clearly output a screen of the transparent panel assembly **60**. When the door light **57** is turned on, the inside of the accommodation case **43** may be brightened up, and thus, the inside of the refrigerator **1** may be more brightened up than the outside of the refrigerator **1** so that the inside of the refrigerator **1** may be visualized through the transparent panel assembly **60**.

(131) The door light **57** may be disposed on both sides of the transparent panel assembly **60** in directions facing each other. The mounted position of the door light **57** may variously vary as long as the door light **57** has sufficient brightness at the rear side of the sub door.

(132) Also, the opening device **59** and the damping device **504** may be mounted on the door liner **56**.

(133) The upper cap decor **54** may define atop surface of the sub door **50** and be coupled to upper ends of the out plate **51** and the door liner **56**. Also, a sub upper hinge mounting part **541** may be disposed on one end of the upper cap decor **54**, and a hinge hole **541a** into which a hinge shaft **401a** of the upper hinge **401** is inserted may be defined in the sub upper hinge mounting part **541**.

(134) The lower cap decor **55** may define a bottom surface of the sub door **50** and be coupled to lower ends of the out plate **51** and the door liner **56**.

(135) The transparent panel assembly **60** may be disposed between the out plate **51** and the door liner **56**. Also, the transparent panel assembly **60** may be configured to cover the plate opening **511** and the door liner opening **561**. Also, the transparent panel assembly **60** may be selectively manipulated to one state of transparent, translucent, opaque, and screen output states by the user.

(136) Thus, the user may selectively see through the inner space of the sub door **50** through the transparent panel assembly **60** and see the screen outputted through the transparent panel assembly **60**.

(137) The inner frame **52** is mounted between the out plate **51** and the transparent panel assembly **60**. The transparent panel assembly **60** may be fixed to and mounted on the out plate **51** by the inner frame **52**. A frame opening **521** may be defined in a center of the inner frame **52**. The frame opening **521** may have a size and shape corresponding to those of the plate opening **511**. Also, the inner frame **52** may have a coupling structure with the out plate **51**. Here, the out plate **51** and the transparent panel assembly **60** may be sealed therebetween with respect to each other.

(138) The insulation member **53** may be mounted on the out plate **51** in the state in which the inner frame **52** and the transparent panel assembly **60** are mounted. The insulation member **53** may be configured to insulate the sub door **50** and thus insulate the circumference of the transparent panel assembly **60**.

(139) In general, although the door of the refrigerator has a structure in which a foaming solution is injected to foam the insulation material, when the foaming solution is filled to foam the insulation material in the same manner as that according to the first embodiment of the present invention, the electronic components within the sub door **50** may be damaged by high-temperature heat. Particularly, the transparent panel assembly may be damaged by high-temperature heat and static electricity when being foamed. Thus, the sub door **50** according to the first embodiment of the present invention has a structure in which the insulation member **53** that is previously molded is assembled and mounted on the sub door **50**.

(140) The insulation member **53** may be molded to match the internal shape of the sub door **50**. The previously molded insulation member **53** may be inserted and mounted along the circumference of the transparent panel assembly **60** while the insulation member **53** is assembled with the sub door **50**. The insulation member **53** may be foam-molded by using a foamed polystyrene material and may be made of various materials that are inserted into the sub door **50** as necessary.

(141) A space may be defined in a central portion of the insulation member **53**. The transparent panel assembly **60** may be disposed in the space defined by mounting the insulation member **53**.



That is, the insulation member **53** may be configured to support at least a portion of an edge of the transparent panel assembly **60**.

(142) The insulation member **53** may have a rectangular frame shape in which the transparent panel assembly **60** is accommodated in a central portion thereof and be seated on the inner frame **52**.

Also, at least one or more insulation members **53** may be provided to be assembled with the inside of the sub door **50**.

(143) Also, the insulation member **53** may have a corresponding shape so as not to interfere with other constituents provided in the sub door **50**. As necessary, the insulation members **53** may be assembled through a groove and a hole or a stepped portion so as not to interfere with each other.

(144) Particularly, a predetermined space in which the plurality of electronic components are disposed may be defined in an upper region of the sub door **50**, more particularly, above the transparent panel assembly **60**. Thus, an upper end of the insulation member **53**, which corresponds to the upper region of the sub door **50**, may have a somewhat thin thickness to secure the space for locating the electronic component and releasing heat within the sub door **50**.

(145) After the insulation member **53** is assembled and mounted, the door liner **56** may be coupled to the out plate **51**, and then, the upper cap decor **54** and the lower cap decor **55** may be assembled with each other. Also, the opening device **59** and the damping device **504** may be mounted on the door liner **56**. Then, the door light **57** and the sub gasket **503** may be mounted on the door liner **56**.

(146) The opening device **59** may include a manipulation lever **591** disposed on the lower door of the sub door **50** and manipulated by the user and a latch **592** protruding from the rear surface of the sub door **50** backward to the main door. The latch **592** may move when the manipulation lever **591** is manipulated and be separated from the locking unit **42**.

(147) The locking unit **42** may be disposed on the front surface of the main door **40** corresponding to the latch **592** and include a latch hole **421** into which the latch **592** is inserted. When the sub door **50** is closed, if the latch **592** is inserted into the latch hole **421**, the latch **592** may be restricted within the latch hole **421**. Also, when the user manipulates the manipulation lever **591**, the latch **592** may move so that the restriction of the latch **592** within the latch hole **421** is released. Thus, the latch **592** may be separated from the latch hole **421**.

(148) The opening device **59** and the locking unit **42** may be variously provided to be selectively coupled to each other in addition to the structure according to the first embodiment of the present invention.

(149) FIG. **13** is a perspective view of the out plate when viewed from the rear side according to the first embodiment of the present invention.

(150) As illustrated in the drawing, the out plate **51** may be made of a plate-shaped metal material and constitute a portion of the outer appearance of the sub door **50** as well as the front surface of the sub door **50**. Also, the out plate **51** may be made of the same material of the front surface of each of the refrigerating compartment door **20** and the freezing compartment door **30**. Various surface treatments such as coating or film attachment so as to realize anti-fingerprint coating, hair lines, colors, or patterns may be performed on the front surface of the out plate **51**.

(151) The out plate **51** may include a front part **512** defining the outer appearance of the front surface and a side part **513** defining an outer appearance of the side surface that is exposed to the outside. Also, a plate opening **511** may be defined at a center of the front part **512**. Here, the plate opening **511** may be covered by the transparent panel assembly **60**. Also, since the inside of the refrigerator **1** is visible through the transparent panel assembly **60** covering the plate opening **511**, the inside of the plate opening **511** is called the see-through part **21**.

(152) The front part **512** may have a curvature that gradually decreases outward from a central side of the refrigerator **1** as a whole. The front part **512** may be rounded to correspond to the front surface of the refrigerating compartment door **20**, which is adjacent to the front part **512**. Thus, the outer appearance of the front surface of the refrigerator **1** may be three-dimensionally viewed as a whole.

(153) Also, an opening bent part **514** that is bent backward may be disposed on a circumferential surface of the plate opening **511**. The opening bent part **514** may be disposed along a circumference of the plate opening **511** and extend by a predetermined length so as to be fixed to an inner frame **52**. Thus, the plate opening **511** may be defined by the opening bent part **514**.

(154) The side part **513** that is bent backward may be disposed on each of both ends of the front part **512**. The side part **513** may define an outer appearance of the side surface of the sub door **50** and have different widths on both left and right sides thereof. A side bent part **515** coupled to the door liner **56** may be disposed on each of upper and lower ends of the side part **513**.

(155) A bent part **516** may be further disposed on each of upper and lower ends of the out plate **51**. The bent part **516** may be coupled to the upper cap decor **54** and the lower cap decor **55**. Thus, the out plate **51** may define the outer appearance of the sub door **50** by being coupled to the door liner **56** and the upper and lower cap decors **54** and **55**.

(156) FIG. **14** is a perspective view of the inner frame when viewed from the rear side according to the first embodiment of the present invention. FIG. **15** is an exploded perspective view of the inner frame when viewed from the rear side. FIG. **16** is an exploded perspective view of the inner frame when viewed from the front side.

(157) As illustrated in the drawings, the inner frame **52** has a rectangular frame shape, and the frame opening **521** is defined in the center of the inner frame **52**. Also, the inner frame **52** may have a plate shape having a predetermined width so as to easily adhere to the out plate **51** and to be easily coupled to the transparent panel assembly **60**.

(158) The inner frame **52** may have a front surface contacting the rear surface of the out plate **51**. Here, since an adhesion member or an adhesive such as a double-sided tape is applied to the inner frame **52**, the inner frame **52** may be attached and fixed to the out plate **51**. Also, the transparent panel assembly **60** may be fixed and mounted on the rear surface of the inner frame **52**. Thus, the transparent panel assembly **60** may be fixed inside the sub door **50** by the inner frame **52**.

(159) Also, the inner frame **52** may include an upper frame **522**, a lower frame **523**, and a pair of side frames respectively disposed both ends of the upper and lower frames **522** and **523** to connect both the ends of each of the upper and lower frames **522** and **523** to each other. The upper frame **522**, the lower frame **523**, and the side frames **524** may be coupled to each other to form the same shape as a rectangular frame. Here, the frame opening **521** is defined in a center of the rectangular frame shape.

(160) In more detail, the upper frame **522** may define an upper portion of the inner frame **52**, and a bottom surface of the upper frame **522** may be closely attached to the upper portion of the out plate **51**.

(161) An upper accommodation groove **522a** into which an upper end of the opening bent part **514** is inserted may be defined in a lower end of the upper frame **522**. The upper accommodation groove **522a** may be recessed at a position corresponding to the upper end of the opening bent part **514**, which defines the plate opening **511**.

(162) Also, an upper coupling groove **522b** may be defined in each of both sides of the upper accommodation groove **522a**. An upper side protrusion **524b** that will be described below may be hooked with and restricted by the upper coupling groove **522b**. For this, an upper insertion groove **522c** into which the upper side protrusion **524b** is inserted may be defined in each of both sides of the lower end of the upper frame **522**, and the upper insertion groove **522c** and the upper coupling groove **522b** may communicate with each other.

(163) Thus, the upper side protrusion **524b** having a hook shape may be inserted into the upper insertion groove **522c** and then be restricted by the upper coupling groove **522b**. Since the upper side protrusion **524b** and the upper coupling groove **522b** are coupled to each other, the coupled state between the upper frame **522** and the side frame **524** may be maintained.

(164) An upper rib **522d** for supporting the upper end of the front surface of the transparent panel assembly **60** may be disposed on the rear surface of the upper frame **522**. The upper rib **522d**

extends from one end to the other end of the upper frame **522** to protrude backward.

(165) Also, a PCB mounting part **522e** on which a plurality of PCBs for driving the transparent panel assembly **60** are mounted may be disposed on the upper portion of the upper frame **522** with respect to the upper rib **522d**.

(166) The PCB mounting part **522e** may be a portion on which at least one or more PCBs **601** of the PCBs **601** for driving the transparent panel assembly **26** and thus may be disposed at a portion corresponding to the upper end of the sub door **50**.

(167) The PCB mounting part **522e** may be disposed on the upper portion of the rear surface of the upper frame **522**, and a plurality of PCB supports **522f** may be disposed on the PCB mounting part **522e**. The PCB supports **522f** may extend backward from the PCB mounting part **522e**, and the PCBs **601** may be disposed at positions that are spaced apart from the rear surface of the upper frame **522** by the PCB supports **522f**.

(168) That is, the PCBs **601** may be disposed in an upper space of the sub door, i.e., a space between the out plate **51** and the upper frame **522**. Thus, the PCBs **601** may be easily cooled by external air introduced through the upper cap decor **54** when heat is generated in the PCBs **601**. The location and cooling structure of each of the PCBs **601** will be described below in more detail.

(169) The lower frame **523** may define a lower portion of the inner frame **52**, and a front surface of the lower frame **523** may be closely attached to the lower portion of the out plate **51**.

(170) A lower accommodation groove into which a lower end of the bent part of the out plate **51** is inserted may be defined in the upper end of the lower frame **523**. The lower accommodation groove **523a** may be recessed at a position corresponding to the upper end of the opening bent part **514**, which defines the plate opening **511**.

(171) Also, a lower coupling groove **523b** may be defined in each of both sides of the lower accommodation groove **523a**. A lower side protrusion **524c** that will be described below may be hooked with and restricted by the lower coupling groove **523b**. For this, a lower insertion groove **523c** into which the lower side protrusion **524c** is inserted may be defined in each of both sides of the lower end of the lower frame **523**, and the lower insertion groove **523c** and the lower coupling groove **523b** may communicate with each other. Here, the lower insertion groove **523c** and the lower coupling groove **523b** may have the same structures as the upper insertion groove **522c** and the upper coupling groove **522b**, respectively.

(172) Also, the lower side protrusion **524c** having a hook shape may be inserted into the lower insertion groove **523c** and then be restricted by the lower coupling groove **523b**. Since the lower side protrusion **524c** and the lower coupling groove **523b** are coupled to each other, the coupled state between the lower frame **523** and the side frame **524** may be maintained.

(173) A lower rib **523d** for supporting the lower end of the front surface of the transparent panel assembly **60** may be disposed on the rear surface of the lower frame **523**. The lower rib **523d** extends from one end to the other end of the lower frame **523** to protrude backward. Also, an auxiliary rib **524d** extending upward from each of both sides of the lower frame **523** and connected to a side rib **524d** disposed on the side frame **524** may be further provided.

(174) The side frame **524** may be disposed between the upper frame **522** and the lower frame **523** and also be disposed on each of both sides therebetween. The side frame **524** may define both sides of the inner frame **52**, and a front surface of the side frame **524** may be closely attached to both sides of the rear surface of the out plate **51**.

(175) A side accommodation groove **524a** which extends vertically and into which both left and right ends of the opening bent part **514** may be defined in the front surface of the side frame **524**. The side accommodation groove **524a** may be recessed at a position corresponding to each of both side ends of the opening bent part **514**, which defines the plate opening **511**.

(176) In the state in which the upper frame **522**, the lower frame **523**, and the side frame **524** are coupled to each other, the side accommodation groove **524a**, the upper accommodation groove **522a**, and the lower accommodation groove **523a** may be connected to each other so as to have the

same shape as the bent shape of the opening bent part **514**.

(177) Thus, in the state in which the inner frame **52** is assembled, the stably coupled state between the inner frame **52** and the out plate **51** may be realized to define an outer appearance of the circumference of the see-through part **21** without exposing the end of the out plate **51**. Also, the circumference of the inside of the inner frame may serve as an edge covering a gap between the out plate and the front surface of the transparent panel assembly.

(178) Although the front surface of the out plate **51** has a curved shape, the transparent panel assembly **60** has a planar shape. Thus, when the transparent panel assembly **60** is mounted, a space may necessarily occur between the out plate **51** and the transparent panel assembly **60**. Since the front surface of the inner frame **52** is coupled to the out plate **51**, and the rear surface of the inner frame **52** is coupled to the transparent panel assembly **60**, the space between the out plate **51** and the transparent panel assembly **60** may be covered to form a circumference of the see-through part **21**.

(179) The upper side protrusion **524b** and the lower side protrusion **524c** may be disposed on upper and lower ends of the lower accommodation groove **523a**, respectively. Thus, each of the upper frame **522** and the lower frame **523** may be coupled with respect to the side frame **524**.

(180) A side rib **524d** may be disposed on the rear surface of the side frame **524**. The side rib **524d** may extend from the upper end to the lower end of the side frame **524** to support both left and right ends of the transparent panel assembly **60**.

(181) The side rib **524d** may protrude backward and have the same height as each of the upper rib **522d** and the lower rib **523d**. In the state in which the inner frame **52** is assembled, the side rib **524d** may be connected to the upper rib **522d** and the lower rib **523d**.

(182) FIG. **17** is a perspective view of the transparent panel assembly according to the first embodiment of the present invention. Also, FIG. **18** is an exploded perspective view of the transparent panel assembly. Also, FIG. **19** is a cross-sectional view of the transparent panel assembly.

(183) As illustrated in the drawings, the transparent panel assembly **60** may have a size that is enough to cover the plate opening **511** and the liner opening **561** inside the sub door **50**. Also, the see-through part **21** may be provided in the transparent panel assembly **60** so that the inner space of the refrigerator is selectively visible, and a screen is outputted.

(184) In more detail with respect to the transparent panel assembly **60**, the transparent panel assembly **60** may have an outer appearance that is defined by the front panel **61** and the rear panel **65**, which define the front and rear surfaces of the transparent panel assembly **60**, and an outer spacer **67** connecting the front panel **61** to the rear panel **65**.

(185) Also, a display **62** and a light guide plate **64** may be disposed between the front panel **61** and the rear panel **65**. In addition, a spacer **63** for supporting the display **62** and the light guide plate **64** may be further provided, and a display light **68** for emitting light to the light guide plate **64** may be provided.

(186) In more detail, the front panel **61** may be made of a transparent glass material (e.g., blue glass) that defines an outer appearance of the front surface of the transparent panel assembly **60**. The front panel **61** may be made of a different material through which the inside of the front panel **61** is visible, and a touch input is enabled.

(187) The front panel **61** may have a size greater than that of the plate opening **511** and be supported by the inner frame **52**. That is, when the transparent panel assembly **60** is assembled and mounted from the rear side, a circumferential portion of the front panel **61** may be supported by the rear surface of the inner frame **52**.

(188) In detail, the front panel may further protrude outward than the rear panel **65** and thus may have a longer length in all of vertical and horizontal directions. Also, the front panel **61** defining the front surface of the transparent panel assembly **60** may further extend outward from the plate opening **511** and then be stably fixed and mounted due to characteristics of the transparent panel

assembly **60** mounted on at the rear side of the out plate **51**.

(189) Thus, when the transparent panel assembly **60** is mounted, each of the extending ends of the front panel **61** may be supported by the inner frame **52**, and thus, the transparent panel assembly **60** may be stably maintained through the plate opening **511** in the mounted state without being the separated.

(190) Also, when the front panel **61** may have a larger size greater than that of the display **62**, the touch sensor **612** disposed on the front panel **61** may have an area corresponding to or greater than that of the display **62**. Thus, the touchable area may be maximally secured through the front panel **61**, and at least the area of the display **62** or the entire area of the see-through part **21** may be configured to be touchable.

(191) A bezel **611** may be disposed on the circumference of the rear surface of the front panel **61**. The bezel **611** may be printed with a black color and have a predetermined width so that the outer spacer **67** and the spacer **63** are covered without being exposed to the outside.

(192) Also, a heater may be disposed along the bezel **611**. The heater may be provided in the form a wire or a film and be disposed on the circumference of the front panel **61** along the bezel **611**. The circumference of the front surface of the front panel **61** may be heated by the heater. Thus, dew condensation may be prevented from occurring on the front panel **61**. Alternatively, the heater may be provided as a transparent heater so as to be disposed on the entire surface of the front panel **61**.

(193) The touch sensor **612** may be disposed on an inner area of the bezel **611**. The touch sensor **612** may be formed on the rear surface of the front panel **61** in a printing manner and be configured to detect user's touch manipulation of the front panel **61**. Alternatively, the touch sensor **612** may be formed in various manners such as an adhesion manner, rather than the printing manner, so that the user touches the front panel **61** to perform the touch input.

(194) A touch PCB **613** connected to the touch sensor **612** may be disposed on the upper end of the front panel **61**. The touch PCB **613** may include a flexible film-shaped cable **614** such as a flexible flat cable (FFC), a flexible print cable or flexible print circuit board (FPC), or the like.

(195) The display **62** may be disposed on the rear surface of the front panel **61**. The display **62** may be provided as an LCD module for outputting a screen. Also, the display **62** may be transparent so that the user sees the inside through the display **62** when the screen is not outputted.

(196) A source board **621** may be disposed on one side of the display **62**. The source board **621** may also include a flexible film-shaped cable structure. The source board **621** may extend along the side surface of the transparent panel assembly **60** and be connected to the T-CON board **623** at the upper portion of the sub door **50**.

(197) In detail, when the source board **621** is disposed on the rear surface of the display **62**, the source board **621** may be exposed to the outside through the see-through part **21** due to the characteristics of the display **62** that is transparent. Thus, the source board **621** may be disposed on an end of a circumferential side of the display **62** and bent to come into contact with an outer surface of the outer spacer **67** outside the outer spacer **67**. The source board **621** may have the FFC or FPC structure that is easily bent. Thus, the source board **621** may be disposed along the outer spacer **67**. Also, the source board **621** may have a size corresponding to that of the outer spacer **67** without getting out of a region of the outer spacer **67** in a state of being closely attached to the outer spacer **67**.

(198) Alternatively, the source board **621** may be disposed on the upper or lower end of the display **62**. However, when the horizontal width is greater than the vertical length, and thus, the source board **621** is disposed on one end of both left and right ends of the display **62** due to the structural characteristics of the display **62**, a sufficient space in which the source board **621** is capable of being disposed may be provided.

(199) Both ends of the display **62** may be supported by the spacer **63**. The spacer **63** may have a rod shape that extending from an upper end to the lower end of the display **62** and be constituted by a first spacer **631** and a second spacer **632**.

(200) The first spacer **631** may have a stepped seating part **631a** so that one end of the display **62** is seated on an edge. Thus, when the display **62** is supported by the first spacer **631**, the display **62** and the light guide plate **64** may be maintained at a set distance therebetween.

(201) The second spacer **632** may support the other end of the display **62**, on which the source board **621** is disposed. The second spacer **632** may maintain a set distance between the first display **62** and the light guide plate **64** like the first spacer **631**. The source board **621** may extend outward by passing through the second spacer **632** and also extend upward in a state of being closely attached to the outer spacer **67**.

(202) The light guide plate **64** may be disposed at a rear side of the display and disposed to be spaced a predetermined distance from the display **62** by the first spacer **631** and the second spacer **632**. There may be a difference in depth feeling of the screen outputted from the display **62** according to the position of the light guide plate **64**.

(203) Thus, the light guide plate **64** may be disposed further forward than an intermediate point between the front panel **61** and the rear panel **65** so that the screen outputted by the display **62** is felt closer to the front panel **61**. As a result, a height of each of the first spacer **631** and the second spacer **632** may be determined.

(204) The light guide plate **64** may diffuse or scatter light emitted from the display light **68** and be made of various materials. For example, the light guide plate **64** may be made of a polymer material or formed by forming a pattern or attaching a film on a surface thereof. The light guide plate **64** may illuminate the display **62** from the rear side of the display **62** when the display light **68** is turned on. For this, the light guide plate **64** may have a plate shape having a size equal to or somewhat greater than that of the display **62**. The display light **68** may be disposed at a position corresponding to each of upper and lower ends of the light guide plate **64**.

(205) The rear panel **65** may be disposed at a rear side of the light guide plate **64**. The rear panel **65** may define the rear surface of the transparent panel assembly **60** and have a size greater than that of the light guide plate and less than that of the front panel **61**. Also, the rear panel **65** may have a size greater than that of the liner opening **561** to cover the liner opening **561**.

(206) The rear panel **65** may be made of low-c glass to realize thermal insulation. A low-emission coating layer may be formed on a surface of glass for general insulation to form the low-c glass, and thus, the low-c glass may have excellent thermal insulation. As a result, the rear panel **65** may prevent heat of cool air within the refrigerator from being transferred to the outside through the transparent panel assembly **60**.

(207) A spacer **66** may be disposed between the rear panel **65** and the light guide plate **64**. The spacer **66** may have a rectangular frame shape disposed along a circumference of the light guide plate **64** and adhere to the light guide plate **64** and the rear panel **64** to maintain a predetermined distance between the light guide plate **64** and the rear panel **65**.

(208) The distance between the front panel **61** and the light guide plate **64** may be maintained in fixed distance so as to output the screen of the display **62**. Also, the distance between the light guide plate **64** and the rear panel **65** may be determined according to a thickness of the sub door **50** or the total thickness of the transparent panel assembly **60**. That is, the spacer **66** may be adjusted in thickness to determine the total thickness of the transparent panel assembly **60** so as to be mounted to match a specification of the sub door **50**.

(209) The rear panel **65** may come into contact with the door light **57**. Thus, a distance between the display **62** and the door light **57** may be determined according to the position of the rear panel **65**. In a state in which the door light **57** is turned on, the door light **57** may serve as an auxiliary backlight function of the display **62**. Thus, the door light **57** may be disposed at a set position. Also, the position of the rear panel **65** and the total thickness of the transparent panel assembly **60** may be determined by the position of the door light **57**.

(210) In detail, a distance between the display **62** and the door light **58** may range from 5 cm to 15 cm. When the distance between the display **62** and the door light **57** is less than about 5 cm, a shade

may occur. When the distance between the display **62** and the door light **57** exceeds 5 cm, the door light may not serve as the backlight. Thus, to maintain the distance between the display **62** and the door light **57**, the rear panel **65** may also be maintained to be spaced a predetermined distance from the display **62**, and thus, the width of the spacer **66** may be determined.

(211) A gap between the light guide plate **64** and the rear panel **65** may be sealed by the spacer **66**. Thus, a space between the spacer **66** and the light guide plate **64** may become to a vacuum state, or an insulative gas such as argon may be injected for the thermal insulation to more improve the thermal insulation performance.

(212) In the state in which the rear panel **65** adheres to the spacer **66**, an outer end of the rear panel **65** may further extend outward from the spacer **66**. Also, the outer spacer **67** may be mounted on the outer end of the rear panel **65** so that the rear panel **65** and the front panel **61** are fixed to each other.

(213) The outer spacer **67** may connect the rear surface of the front panel **61** to the front surface of the rear panel **65** and also define the circumferential surface of the transparent panel assembly **60**.

Also, a space in which the display light **68** is mounted may be provided inside the outer spacer **67**.

(214) FIG. **20** is a perspective view of the spacer according to the first embodiment of the present invention. Also, FIG. **21** is a cross-sectional view of the spacer.

(215) As illustrated in the drawings, the spacer **66** may include a side spacer **663** disposed on each of both sides of the spacer **66** and upper and lower spacers **661** and **662** disposed in a vertical direction. The side spacer **663**, the upper spacer **661**, and the lower spacer **662** may have the same cross-sectional shape, i.e., a polygonal shape. Thus, each of a surface on which the light guide plate **64** and the rear panel **65** contact each other, a surface disposed between the light guide plate **64** and the rear panel **65**, and an outer surface facing the surface between the light guide plate **64** and the rear panel **65** may have a planar shape.

(216) Also, each of the side spacer **663** and the upper or lower spacer **661** or **662** may have a hollow and be made of a lightweight material to decrease in weight of the sub door **50**.

(217) The side spacer **663** may have opened upper and lower ends, and both side ends of the upper and lower spacers **661** and **662** may be opened. Here, the side spacer **663** may have the same cross-section as that of each of the upper and lower spacers **661** and **662**.

(218) Also, a corner connection member **664** may be disposed on each of four corners of the spacer **66**. The corner connection member **664** may connect the side spacer **663** to the upper or lower spacer **663** or **661**. The corner connection member **664** may be inserted into the side spacer **663** and the upper or lower spacer **661** or **662**, and the side spacer **663** and the upper or lower spacer **661** or **662** may be disposed at a right angle.

(219) The corner connection member **664** may be constituted by a first insertion part **664a** extending in one direction, a second insertion part **664b** extending in a direction perpendicular to the first insertion part **664a**, and an intermediate part **664c** disposed between the first insertion part **664a** and the second insertion part **664b**.

(220) The first insertion part **664a** and the second insertion part **664b** may have the same structure and shape except that the first and second insertion parts **664a** and **664b** extend in different directions. Thus, the first insertion part **664a** and the second insertion part may be inserted into openings of the side spacer **663** and the upper or lower spacer **661** or **662**, which have the same shape, respectively.

(221) Also, a plurality of support ribs **664d** may be disposed on the first insertion part **664a** and the second insertion part **664b**. The first insertion part **664a** and the second insertion part **664b** may be inserted into the side spacer **663** and the upper or lower spacer **661** or **662** to support inner surfaces of the side spacer **663** and the upper or lower spacer **661** or **662**. The support rib **664d** may be provided in plurality at equal intervals. A protrusion **664e** having a size and shape different from those of the support rib **664d** may be further disposed at a position adjacent to the opening of each of the side spacer **663** and the upper or lower spacer **661** or **662**.

(222) The intermediate part **664c** may be disposed between the first insertion part **664a** and the second insertion part **664b** to extend in a direction crossing each of the first insertion part **664a** and the second insertion part **664b**. Also, the intermediate part **664c** may have a rounded outer surface and be exposed to the outside between the side spacer **663** and the upper or lower spacer **661** or **662**. Thus, the intermediate part **664c** may define an outer appearance of the edge of the spacer **66**.

(223) FIG. **22** is a perspective view of the outer spacer according to the first embodiment of the present invention. FIG. **23** is a cross-sectional view of the outer spacer.

(224) As illustrated in the drawings, the outer spacer **67** may have a rectangular frame shape. Also, the outer spacer **67** may have a size in which the light guide plate **64** and the spacer **63** are accommodated. The outer spacer **67** includes a pair of side frames **671** spaced apart from each other to define both left and right surfaces thereof and an upper frame **672** and a lower frame **673** connecting upper and lower ends of the pair of side frames **671** to each other. The outer spacer **67** may have a hollow therein to decrease in weight thereof and be made of a lightweight metal material such as aluminum.

(225) The side frame **671** may connect the front panel **61** to the rear panel **65** and also define both the side surfaces of the transparent panel assembly **60**. The upper frame **672** and the lower frame **673** may also connect the front panel **61** to the rear panel **65** and also define the shapes of the top and bottom surfaces of the transparent panel assembly **60**. The upper frame **672** and the lower frame **673** may have the same shape except for vertical mounted positions thereof.

(226) The lower frame **523** may include a light mounting part **674** and a spacer part **675**. The light mounting part **674** connects the front panel **61** to the rear panel **65** and also provides a light accommodation part **674a**, in which the display light **68** is mounted, in a top surface thereof.

(227) The display light **68** may be longitudinally disposed along the light mounting part **674** and include a plurality of first LEDs **681** and a first LED board **682** on which the first LEDs **681** are continuously mounted at predetermined intervals. Alternatively, the display light **68** may have a different structure for emitting light except for the LED.

(228) The first LED **681** may be disposed at a position corresponding to a lower end of the light guide plate **64**. Thus, light emitted through the first LED **681** may be directed to an end of the light guide plate **64** and then move along the light guide plate **64** so that the entire surface of the light guide plate **64** emits light.

(229) When the display light **68** is mounted, the first LED board **682** may be closely attached to the spacer part **675** so that the first LED **681** is accurately disposed at the lower end of the light guide plate **64**. That is, in the state in which the first LED board **682** is closely attached to the spacer part **675**, the first LED **681** may be disposed right below the light guide plate **64**. Also, for this, the light accommodation part **674a** may be recessed to inside of the spacer part **675**.

(230) The spacer part **675** may extend upward from one end of the light mounting part **674**. Here, the spacer part **675** may be disposed between the front panel **61** and the light guide plate **64** so that the rear surface of the front panel **61** and the front surface of the light guide plate **64** may adhere to each other. Here, the spacer part **675** may have the same thickness of each of the first spacer **631** and the second spacer **632**.

(231) Thus, both left and right sides of the front panel **61** and the light guide plate **64** may be supported in a sealed state by the first spacer **631** and the second spacer **632**, and upper and lower sides of the front panel **61** and the light guide plate **64** may be supported in a sealed state by the spacer part **675**. As described above, the upper frame **672** and the lower frame **673** may adhere to each other so that the front panel **61** and the rear panel **65** are sealed with respect to each other and also may be fixed so that the front panel **61** and the light guide plate **64** are sealed with respect to each other.

(232) A display support **675a** on which an end of the display **62** is seated may be disposed on an edge of the upper end of the spacer part **675**. The display support **675a** may be configured so that the upper and lower ends of the display **62** are seated to allow the display **62** to be mounted at an



accurate position in the rear side of the front panel **61**.

(233) The upper frame **672** may have the same structure as the lower frame **673** except for the arrangement thereof. Thus, the light guide plate **64** may be illuminated by the display light **68** provided in the upper and lower frames **672** and **673**, and thus, the screen outputted on the display **62** may be more clear.

(234) FIG. **24** is an exploded perspective view illustrating an arranged structure of a PCB on the upper portion of the sub door. FIG. **25** is a cross-sectional view illustrating the upper portion of the sub door.

(235) As illustrated in the drawings, in the state in which the transparent panel assembly **60** is mounted, a plurality of PCBs **601** for an operation of the display **62** may be disposed on an upper portion of the inside of the sub door **50**. Thus, wires connected to the plurality of PCBs **601** may lead to the sub upper hinge **401** through the upper cap decor **54** at the shortest distance.

(236) In more detail, a T-CON board **613**, a touch PCB **613**, and a light PCB **683** may be disposed on the upper portion of the sub door **50**. The T-CON board **623** may include a cable **614** for driving the display **62**. The touch PCB **613** may process a touch input signal of the touch sensor **612** and include a cable **624** connected to the touch sensor **612**. The light PCB **683** may be configured to control the display light **68** and include a cable **684** connected to each of the display lights **68** that are vertically disposed.

(237) Each of the cables connecting the plurality of PCBs **601** may be provided in a flexible film type of FFC or FPC. Thus, the cables **602** may be disposed without occupying a large space inside the sub door **50** and also disposed along the edge of the transparent panel assembly **60**, more particularly, the outer surface of the outer spacer **67**. Thus, the connection structure of the PCBs may also be simplified, and when the insulation member **53** is assembled, the PCBs may not interfere with each other.

(238) Particularly, all of the cables **602** may be disposed along the circumference of the transparent panel assembly **60** or the edge of the transparent panel assembly **60**. For this, the cables **602** may be bent or curved.

(239) Also, the plurality of PCBs may be connected to an electric wire having a wire shape. For this, a connector that is capable of being converted from the connection structure into the general wire type structure. Thus, the wires **L** connected to the plurality of PCBs **601** may be gathered to be guided to the outside through wire holes **542** opened in the rear surface of the sub door **50**, more particularly, the upper cap decor **54**. That is, each of the plurality of cables **602** connected to the PCBs **601** may have a very large width, and thus, the hole for guiding the plurality of cables **602** to the outside of the sub door **50** at once may be very large to deteriorate efficiency. Thus, the wire **L** may be connected to an output-side of the PCB **601** and guided to the outside of the sub door **50** to reduce a volume and space for guiding the wire **L**.

(240) All of the T-CON board **623**, the touch PCB **613**, and the light PCB **693** may be disposed above the transparent panel assembly **60** and also be disposed on the upper portion of the sub door **50**. Also, the T-CON board **623**, the touch PCB **613**, and the light PCB **693** may be disposed on the PCB mounting part **522e** of the inner frame **52** and also be disposed to be spaced apart from each other on the PCB mounting part **522e** by the PCB support **522**.

(241) Also, the insulation member corresponding to an area, on which the PCBs **601** are mounted, of the insulation members within the sub door **50** may have an upper end having a thin thickness to provide a space in which the PCBs **601** disposed on the upper portion of the sub door **50** are mounted to release heat.

(242) To mount all of the T-CON board **623**, the touch PCB **613**, and the light PCB **683** in the limited space in the upper portion of the sub door **50**, at least a portion of the plurality of PCBs **601** may be disposed to overlap each other. Here, the PCB supports **522f** respectively supporting the PCBs **601** may have heights different from each other. Here, air may flow between the PCBs **601** overlapping each other to effectively dissipate the PCBs **601**.

(243) A plurality of heat dissipation holes **543** may be defined in the upper cap decor **54** defining the top surface of the sub door **50**. Thus, heat generated in the T-CON board **623**, the touch PCB **613**, and the light PCB **683**, which are provided inside the sub door **50**, may be released through the heat dissipation hole **543**.

(244) The heat dissipation hole **543** may be defined in the top surface of the upper cap decor **54**. Thus, when the heat is released to the outside of the sub door **50**, the heat may be prevented from being transmitted to the user. Also, a heat dissipation hole guide **544** may be disposed in the heat dissipation hole **543**. The heat dissipation hole guide **544** may be disposed along a portion of a circumference of the heat dissipation hole **543** and be inclined or rounded downward. Thus, the heat within the sub door **50** may be released, and dusts or foreign substances may be prevented from being introduced through the heat dissipation hole **543**.

(245) Particularly, the heat dissipation hole guide **544** may be opened to a side that is far away from the disposed positions of the PCBs **601**, i.e., the front surface of the sub door **50** and also may extend to the front surface of the sub door **50** to prevent water or foreign substances, which damage the PCBs **601**, from directly dropping into the PCBs **601**.

(246) FIG. **26** is a perspective view of the insulation member according to the first embodiment of the present invention.

(247) As illustrated in drawing, the insulation member **53** may have a shape corresponding an internal shape of the sub door **50** so as to be mounted in the sub door **50** along the circumference of the transparent panel assembly **60**. The insulation member **53** may be assembled and mounted inside the sub door **50** in the state of being foam-molded.

(248) The insulation member **53** may be constituted by an upper insulation member **531**, a lower insulation member **532**, and a pair of side insulation members **533** so as to be more easily mounted inside the sub door **50**. Each of the upper insulation member **531**, the lower insulation member **532**, and the pair of side insulation members **533** may be separately molded and may adhere to each other in the state of being mounted on the sub door **50** to provide a rectangular frame shape.

(249) The upper insulation member **531** may be disposed above the transparent panel assembly **60**. Here, the upper insulation member may have a somewhat thin thickness to provide a space in which the plurality of PCBs **601** mounted on the upper portion of the sub door **50** are disposed and a space in which the PCBs **601** is cooled.

(250) The lower insulation member **532** may be disposed below the transparent panel assembly **60**. Also, the lower insulation member **532** may have a corresponding shape to fill a space between the out plate **51** and the door liner **56**. Here, a first molded end **532a** for avoiding the damping device **504** or the constitute for mounting the damping device **504** may be disposed on a portion corresponding to the portion on which the damping device **504** is mounted.

(251) The side insulation members **533** may be disposed on both sides of the transparent panel assembly **60**, respectively. Also, the lower insulation member **532** may have a corresponding shape to fill a space between the out plate **51** and the door liner **56**. Here a second molded end **533a** for avoiding the opening device **59** or the constitute for mounting the opening device **59** may be disposed on a portion corresponding to the portion on which the opening device **59** is mounted.

(252) Also, a surface of the insulation member **53**, which contacts the door liner **56**, may have a shape corresponding to that of the door liner **56**. Thus, the insulation member **53** may be coupled in a state of being closely attached to the door liner **56**. For example, a third molded end corresponding to a liner protrusion **566** disposed on the door liner **56** may be disposed on a rear surface of the insulation member **53**. The third molded end **530** may have a shape corresponding to that of the door liner. Thus, when the insulation member **53** is mounted, the third molded end **530** and the linear protrusion **566** may be coupled to each other.

(253) FIG. **27** is a perspective view of the door liner when viewed from the front side according to the first embodiment of the present invention. FIG. **28** is a perspective view of the door liner when viewed from the rear side.

(254) As illustrated in the drawings, the door liner **56** may be injection-molded by using a plastic material and molded to define an outer appearance of the rear surface of the sub door **50**. Also, a structure in which the plurality of constituents mounted on the door liner **56** are capable of being mounted may be provided.

(255) In detail, the door liner **56** may have a rectangular frame shape, and a liner opening **561** may be defined in a center of the door liner **56**. The liner opening **561** may be covered by the transparent panel assembly **60**.

(256) A liner coupling part **562** coupled to both side ends of the out plate **51** may be disposed on each of both side ends of the front surface of the door liner that is directed to the out plate **51**. That is, the liner coupling part **562** may extend up to an upper end of the door liner **56** so as to be coupled to a rear end of the side surface of the out plate **51**.

(257) Also, the upper and lower ends of the door liner **56** are coupled to the upper cap deco **54** and the lower cap deco **55**, respectively.

(258) Also, a latch accommodation part **563** is defined at one side of the door liner **56**, which is far away from the rotation shaft of the sub door **50**. The latch accommodation part **563** may be disposed at a central position in a vertical length of the door liner **56**. The latch accommodation part **563** may be configured to accommodate a latch **592** constituting the opening device **59** so that the latch **592** is rotatable.

(259) The latch accommodation part **562** may be opened through the rear surface of the door liner **56**, and the opening of the latch accommodation part **593** may be covered by an accommodation cover **563a**. The latch **592** may protrude by passing through a cover opening defined in the accommodation cover **563a** and vertically rotate to be selectively coupled to the locking unit **42**.

(260) Also, a rod guide **563b** may be disposed below the latch accommodation part **563**. The rod guide **563b** may be provided in plurality at equal intervals up to a lower end of the door liner **56**. A connecting rod **592** connected to the manipulation member **591** of the opening device **59** may pass through the rod guide **563b**.

(261) The connecting rod **592** may have an upper end connected to the latch **592** inside the latch accommodation part **563** and a lower end connected to the manipulation member disposed on a lower end of the lower cap decor **55**. Thus, when the manipulation member **591** is manipulated, the latch **592** may rotate by the connecting rod **592**.

(262) A damper mounting part **564** may be disposed on the lower end of the door liner **56** that is close to the rotation shaft of the sub door **50**. The damper mounting part **564** may be recessed from the rear surface of the door liner **56** so that the damping device **504** is inserted and mounted. The damping device **504** may pass through a damper cover covering the damper mounting part **564** to protrude. The damping device **504** may be supported by an elastic member such as a spring so as to be accessible inside the damper mounting part **564**.

(263) Thus, while the sub door **50** is closed, the damping device **504** may contact the front surface of the main door **40** to relieve an impact. Also, while the sub door **50** is opened, elastic force may be provided so that the sub door **50** rotates in a direction in which the sub door **50** is opened.

(264) Also, a portion of the damper cover **564a** may be disposed on the gasket groove **565** and be fixed and mounted on the door liner **56** by a coupling member **564b** such as a screw. Also, the coupling member **564b** may be covered by the sub gasket **503** mounted on the gasket groove **565**.

(265) The gasket groove **565** recessed along a circumference of the liner opening **561** may be defined in the rear surface of the door liner **56**. The sub gasket **503** may be fixed and mounted on the gasket groove **565** and be disposed on a circumference of a liner protrusion **566** protruding from the rear surface of the door liner **56**.

(266) A display accommodation part **567** having a size corresponding to that of the transparent panel assembly **60** may be provided in the front surface of the door liner **56**. The display accommodation part **567** may be recessed to accommodate at least a portion of the transparent panel assembly **60** from a rear side thereof. Also, the inside of the display accommodation part **567**

may be stepped. Thus, when the door liner is coupled, the circumference and a portion of the rear surface of the transparent panel assembly **60** may be supported by the display accommodation part **567**. That is, when the door liner **56** and the out plate **51** are coupled to each other, the transparent panel assembly **60** may be maintained in the state of being stably fixed inside the display accommodation part **567**.

(267) The liner opening **561** may be defined in an inner region of the display accommodation part **567**. Also, the liner protrusion **566** may be disposed on a circumference of the liner opening **561**. The liner protrusion **566** may protrude backward from the rear surface of the door liner **56** and have a size and shape corresponding to those of the opening **41** of the main door **40**.

(268) When the sub door **50** is closed, the liner protrusion **566** may be inserted into the opening of the main door **40** to contact an inner surface of the opening **41**, thereby primarily preventing cold air within the opening **41** from leaking. Also, the sub gasket **503** disposed on the circumference of the liner protrusion **566** may be closely attached to the circumference of the opening to secondarily prevent the cold air within the opening **41** from leaking.

(269) Also, the liner protrusion **566** may have a shape in which a side of the liner protrusion **566**, which is close to the rotation shaft of the sub door **50** further protrudes than a side of the liner protrusion **566**, which is far away from the rotation shaft and thus may be inclined or rounded. The liner protrusion **566** may be opposite to the rounded or inclined shape of the front surface of the sub door **50** and thus be closely attached to the front surface of the main door **40**, which has the planar shape.

(270) A door light mounting part **568** on which the door light **57** is mounted may be disposed on each of both left and right sides of an inner surface of the liner protrusion **566**. The door light **57** may be configured to illuminate the rear region of the transparent panel assembly **60** and be mounted on the door light mounting part **568**.

(271) The door light mounting part **568** may be recessed from each of both the left and right surfaces of the inner surface of the liner protrusion **566**. Also, in the state in which the door light **57** is mounted on the door light mounting part **568**, an outer surface of the door light **57** may cover an opened surface of the door light mounting part **568** to define a portion of the inner surface of the liner protrusion **566**.

(272) Also, a door light fixing part **568a** for fixing the door light **57** may be disposed on each of top and bottom surfaces of the door light mounting part **568**. The door light fixing part **568a** may be recessed so that a fixing protrusion disposed on each of upper and lower ends of the door light is inserted.

(273) FIG. **29** is a perspective view of the door light according to the first embodiment of the present invention. FIG. **30** is an exploded perspective view of the door light.

(274) As illustrated in the drawings, the door light **57** may have a size that is enough to be inserted into the door light mounting part **568** and be lengthily disposed in a vertical direction. The door light **57** may have a vertical length corresponding to that of the transparent panel assembly **60** to uniformly illuminate the entire rear surface of the transparent panel assembly **60**.

(275) In more detail, the door light **57** may include a light housing **571**, a lighting module **575**, and a light cover **574**.

(276) The light housing **571** may provide a space in which the lighting module **575** is accommodated and be inserted into the door light mounting part **568**. The light housing **571** may have a box shape having an opened one surface. Here, the opened surface may be disposed on the opening of the door light mounting part **568**.

(277) A fixing protrusion **571a** may be disposed on each of top and bottom surfaces of the light housing **571** and inserted into a door light fixing part **568a** inside the door light mounting part **568**. An inclined surface may be provided on the top surface of the fixing protrusion **571a**. When the door light **57** is mounted, the inclined surface may be inserted while contacting the inner surface of the door light mounting part **568**.

(278) The light housing **571** may include a mounting surface **572** on which the lighting module **575** is mounted and a reflection surface **573** disposed on a surface facing the mounting surface **572**. The mounting surface **572** may have a planar shape so that the lighting module **575** is mounted.

(279) Also, the reflection surface **573** may extend from one end of the mounting surface **572** to extend in an inclined or rounded shape in a direction facing the mounting surface **572**. The reflection surface **573** may be configured to reflect light emitted from the lighting module **575**. The light emitted from the lighting module **575** may be reflected to proceed to the light cover **574**. For this, the inside of the reflection surface **573** may be painted, coated, or surface treated to enhance the light reflection efficiency.

(280) A wire entrance **572a** through which the wire L connected to the lighting module **575** is accessible may be provided in one surface of the light housing **571**. The wire entrance **572a** may pass through an upper end of the mounting surface **572** to extend outward. Thus, the wire L connected to the lighting module **575** may be easily disposed.

(281) Also, a fixing hook **572b** and a side protrusion **572c** for fixing and mounting the lighting module **575** may be disposed on the mounting surface **572**. The fixing hook **572b** may have a hook shape to restrict an outer end of the lighting module **575** and be disposed at a position corresponding to each of upper and lower ends of the lighting module **575**. Also, the fixing hook **572b** may be configured so that the lighting module **575** is press-fitted and fixed when the lighting module **575** is mounted. Also, the side protrusion **572c** may contact both side ends of the lighting module **575** so that the lighting module **575** is disposed at its regular position. The side protrusion **572c** may be continuously disposed in the vertical direction to fix the light module **575** at its regular position as a whole.

(282) A reinforcement rib **571b** may be disposed on an outer surface of the light housing **571**. The reinforcement rib **571b** may be disposed on an outer surface of the reflection surface **573** along a curvature of the reflection surface **573**. Also, the reinforcement rib **571b** may be provided in plurality that are continuously disposed and disposed at predetermined intervals in the vertical direction of the light housing **571**.

(283) The reinforcement rib **571b** may allow the light housing **571** to contact the inner surface of the door light mounting part **568**. Thus, the reinforcement rib **571b** may be maintained in the stably mounted state without deformation or movement of the light housing **571** inside the door light mounting part **568**.

(284) Also, a plurality of cover grooves **571c** may be defined in the opened end of the light housing **571**. The cover protrusion **574a** of the light cover **574** may be coupled to the cover groove **571c** to allow the light cover **574** to be fixed and coupled to the opening of the light housing **571**.

(285) The light cover **574** may cover the opening of the housing and allow the light emitted from the lighting module **575** to be transmitted after being reflected by the reflection surface **573**. For this, the light cover **574** may be made of a material through the light is transmitted or diffused. Also, a plurality of grooves or protrusions may be disposed on a surface of the light cover **574** so that the transmitted light is more effectively diffused. Alternatively, an unevenness or pattern may be disposed on the surface, a film may be attached to the surface, or coating is performed on the surface. Also, as necessary, when the light cover **574** is injection-molded, particles or materials **574c** for diffusing the light may be added.

(286) Also, the cover protrusion **574a** may be disposed on a circumference of the light cover **574** and coupled to the cover groove **571c** of the light housing **571** to cover the opened surface of the light housing **571**. Also, the light cover **574** may be disposed on the opening of the door light mounting part **568**.

(287) The lighting module **575** may include a plurality of second LEDs **575a** emitting light and a second LED board **575b** on which the plurality of second LEDs **575a** are mounted. The plurality of second LEDs **575a** may be continuously disposed along the second LED board **575b** at predetermined intervals. Also, the second LED board **575b** may be configured to be mounted on

the mounting surface **572** of the light housing **571** and fixed to the mounting surface **572** by the fixing hook **572b**.

(288) Thus, the lighting module **575** may be disposed in a direction crossing the light cover **574**. Also, the light emitted from the second LEDs **575a** may be emitted to the reflection surface **573**, and the light emitted to the reflection surface **573** may pass through the light cover **574** and be emitted to the outside.

(289) As described above, the light emitted from the lighting module **575** may be reflected to pass through the light cover **574**, thereby preventing the light from being locally illuminated at the position of the second LEDs **575a** on the light cover **574**. When the whole of the light cover **574** is brightly illuminated so as to be seen as a surface emission when viewed from the outside.

(290) In a state in which the door light **57** is turned on, the rear surface of the transparent panel assembly **60** may be brightened, and also, the inside of the accommodation case **43** may be brightened. Here, the door light **57** may have brightness that is enough to distinguish the inside of the accommodation case **43** from the outside through the transparent panel assembly **60**.

(291) In detail, the door light **57** may be selectively turned on/off according to user's manipulation. When the door light **57** is turned on, an accommodation space defined in the accommodation case **43** may be brightened. When the door light **57** is turned on to allow the accommodation space of the main door **40**, i.e., the inside of the refrigerator to be more brightened than the outside of the refrigerator, the light emitted by the door light **57** may pass through the transparent panel assembly **60**. Thus, the user may transparently recognize the transparent panel assembly **60** and see the storage space inside the main door **40** through the sub door **50** from the outside.

(292) Hereinafter, the turn-on/off states of the display light and the door light will be described in more detail with reference to the accompanying drawings.

(293) FIG. **31** is a longitudinal cross-sectional view of a refrigerating compartment door. FIG. **32** is a sectional view taken along line **32-32'** of FIG. **10**. Also, FIG. **33** is a cross-sectional view taken along line **33-33'** of FIG. **10**.

(294) As illustrated in the drawings, in the state in which the display light **58** is turned off, and the display **62** is turned off, the light guide plate **64** and the display **62** may be transparent. Also, since the front panel **61** and the rear panel **65** are transparent, the transparent panel assembly **60** may be in a state in which the inside of the transparent panel assembly **60** is visible.

(295) In this state, when the door light **57** is turned on to illuminate the inner space of the accommodation case **43**, the user may see the inner space of the accommodation case **43** through the see-through part **21**.

(296) Also, when the user manipulates the front panel **61** disposed on the front surface of the refrigerator **1**, the transparent panel assembly **60** may output a screen. Here, the manipulation of the front panel **61** may be inputted as one of a specific position, the touch number, or a pattern. As occasion demands, a separate physical button or sensor may be used to detect the user's manipulation.

(297) The display **62** may be turned on to output the screen by manipulating the front panel **61**. A set specific screen may be outputted on the display **62**. The user may additionally manipulate the front panel **61** to output various screens through the display **62**. The screen output through the display **62** according to various embodiments will be described below.

(298) The display light **69** disposed on each of the upper and lower ends of the light guide plate **64** may be turned on together with the display **62** by the user's manipulation. The display light **68** may be disposed along the outer spacer **67** and also disposed to correspond to a width of the light guide plate **64**. Also, the display light **68** may be disposed close to upper and lower ends of the light guide plate **64**. Thus, the light guide plate **64** may irregularly reflect and diffuse light of the display light **68** by the turn-on of the display light **68** to emit light having generally uniform brightness to the front display **62**.

(299) Also, light may be emitted to the display **62** from the rear side of the display **62** by the light

guide plate **64**, and simultaneously, a screen based on inputted image information may be outputted on the display **62**. Thus, the user may confirm the clearly outputted screen through the see-through part **21**.

(300) In the state in which a screen is being outputted through the display **62**, the inner space of the refrigerator **1**, i.e., the rear space of the sub door **50** may be selectively seen through the see-through part **21**. To allow the rear space of the sub door **50** to be visible through the see-through part **21**, the door light **57** may be turned on.

(301) A turn on/off combination of the display light **68** and the door light **57** may be variously realized according to a degree of seeing of the inside of the accommodation case **43** through the see-through part **21**. A difference in transparency by this combination will be described in more detail below.

(302) FIG. **34** is a transversely cross-sectional view of the refrigerating compartment door. FIG. **35** is a sectional view taken along line **35-35'** of FIG. **10**. Also, FIG. **36** is a cross-sectional view taken along line **36-36'** of FIG. **10**.

(303) As illustrated in the drawings, in a state in which the latch **592** of the opening device **59** is inserted into the latch hole **421** of the locking unit **42**, the sub door **50** may be maintained in a closed state. In this state, the door light **57** may be maintained in a turn-off state. An opened or closed state of the sub door **50** may be detected through a door switch that is separately provided.

(304) In the turn-off state of the door light **57**, the rear space of the sub door **50** may be dark, and thus, the inside of the refrigerator **1** may not be seen through the see-through part **21**. Thus, in the closed state of the sub door **50**, if separate manipulation is not performed, the door light **57** may be maintained in the turn-off state, and the interior of the refrigerator **1** may not be visible through the see-through part **21**.

(305) In this state, the user may manipulate the front panel **51** to turn on the door light **57**. When the door light **57** is turned on, light emitted from a lighting module **575** may be emitted to positions of both rear left and right sides of the rear panel **65**, which face each other.

(306) The door light **57** may extend from the upper end to the lower end of the rear panel **65**. That is, the light emitted by the door light **57** may illuminate the entire rear region of the rear panel **65** from both the left and right sides of the rear panel **65**.

(307) Here, when the display light **68** is in the turn-on state together with the door light **57**, light may be emitted upward and downward by the display light **68**, and thus the light may be emitted from left and right sides by the door light **57**. As a result, the light may be emitted to the see-through part **21** in all directions to maximally illuminate an area of the see-through part **21**.

(308) Also, the light emitted by the door light **57** may be emitted in directions facing each other, and a surface onto which the light is emitted, i.e., the light cover **574** may be disposed perpendicular to the rear panel **65**. In this state, when the door light **57** is turned on to emit light, the light cover **574** may be exposed when viewed from the outside.

(309) The lighting module **575** may be disposed in parallel to the rear panel **65**, and the light cover **574** may be disposed perpendicular to the rear panel **65**. Thus, the light emitted from the lighting module may be reflected by the reflection surface **573** to proceed to the light cover **574** so that the light emitted from the lighting module **575** is emitted to the rear panel **65**.

(310) In the indirect emission manner as described above, a phenomenon in which the portion locally brightened by the second LEDs **575a** when the user sees the see-through part **21** in the state in which the door light **57** is turned on is formed in a droplet shape on the light cover **574** may be prevented. That is, the surface of the light cover **574** seen through the see-through part **21** is in an evenly bright state, and thus, the same effect as the surface emission may be expected.

(311) The door light **57** may emit light in directions facing each other in a state of being close to the rear panel **65**. The light emitted by the door light **57** may brighten up an inner case of the accommodation case **43** and also illuminate the front region over the rear panel **65**. Thus, the door light **57** may serve as a lighting for illuminating the inner space of the refrigerator **1**, which is

visible through the see-through part **21** and also serve as an auxiliary backlight for allow the display **62** to be more clearly displayed.

(312) FIG. **37** is a cross-sectional view taken along line **37-37'** of FIG. **11**.

(313) As illustrated in the drawing, an overall operation of the refrigerator **1** may be controlled by the main control unit **14**. The main PCB **141** may be provided in the main control unit **14**, and the main PCB **141** may be connected to the display PCB **142** to receive operation information of the transparent panel assembly **60**.

(314) Also, a plurality of constituents such as a compressor, a fan motor, a valve, and the like, which constitute a refrigeration cycle, may be connected to the main PCB **141** and controlled in operation. Also, a camera **145** for photographing the inside of the refrigerator **1** so as to utilize image information may be connected to the main PCB **141**. Also, a speaker **146** for outputting a voice may be connected to the main PCB **141**. Here, the speaker **146** may be connected to the main PCB **141** by wireless communication such as Bluetooth. Also, a separate communication module **147** for communication with an external device and a server may be connected to the main PCB **141**.

(315) Also, the display PCB **142** may constitute the main control unit **14** together with the adaptor **143** and be disposed on the top surface of the cabinet **10**. The display PCB **142** may be configured to control the operation of the display **62**. The display PCB **142** may output an image, a picture, an Internet screen, and a preset system screen through the display **62**.

(316) Also, the main control unit **14** may further include a light driver **148** for controlling an operation of the display light **68** and/or the door light **57**. Here, the light driver **148** may be integrated with the display PCB **142**.

(317) The touch PCB **613** connected to the touch sensor **612**, the T-CON board **623** connected to the display **62**, and the light PCB **683** connected to the display light **68** may be provided in the sub door **50**. Also, each of the touch PCB **613**, the T-CON board **523**, and the light PCB **683** may have a structure that is connected to the display PCB **142** by passing through the sub door **50**.

(318) In this structure, the selective viewing and screen output of the inside of the refrigerator through the transparent panel assembly **60** may be enabled by combination of the operations of the display **62**, the display light **68**, and the door light **57**.

(319) Hereinafter an operation of the refrigerator having the above-described structure will be described.

(320) FIG. **38** is a front view when the refrigerator is in an opaque mode.

(321) As illustrated in the drawing, the refrigerator **1** may operate in an opaque mode in which the inside of the accommodation case **43** is invisible when viewed from the outside by the user's manipulation.

(322) The user may touch the front panel **51** to be converted into the opaque mode. Also, the refrigerator **1** may automatically operate in the opaque mode when a predetermined time elapses without a separate input in the closed state of the sub door **50**.

(323) In the opaque mode, since the inside is not seen through the see-through part **21**, the overall outer appearance may be clearly seen, and the see-through part **21** may be expressed in a black color to form a portion of the front surface of the refrigerator **1** in which the inside of the refrigerator **1** is not viewed.

(324) In this state, it may mean a standby state in which the user does not use the refrigerator **1** and does not perform an external operation from the outside. Also, this state may include a state in which an opaque screen is outputted through the transparent panel assembly **60**.

(325) FIG. **39** is a transversely schematic cross-sectional view illustrating an example of a turn-on state when the refrigerator is in the opaque mode.

(326) As illustrated in the drawing, in the opaque mode, both the door light **57** and the display light **68** may be turned off. That is, the screen may not be outputted on the see-through part **21** in the state in which all of the door light **57** and the display light **68** are turned off.



(327) When all of the door light **57** and the display light **68** are turned off, the rear region of the sub door **50**, i.e., the inside of the accommodation case **43** may not be visible through the see-through part **21**.

(328) Also, since power consumption of the refrigerator **1** is minimized when all of the door light **57** and the display light **68** are turned off, in the case in which it is not necessary to check the internal state, it is desirable to maintain such a state to reduce the power consumption.

(329) However, in the state in which all of the door light **57** and the display light **68** are turned off, when the transparent panel assembly **60** is blocked to be completely invisible by 100%, the inner space of the accommodation case **43** may be blurredly seen when a portion of external light is penetrated into the refrigerator, or the user the inside of the refrigerator at a position that is very close to the see-through part **21**. Alternatively, in this state, the see-through part **21** may be opaque at the manipulation distance of a general refrigerator, and in fact, the inside of the accommodation case **43** may be invisible.

(330) FIG. **40** is a transversely schematic cross-sectional view illustrating another example of a turn-on state when the refrigerator is in the opaque mode.

(331) As illustrated in the drawing, in the opaque mode, the door light **57** may be turned off, and the display light **68** may be turned on. That is, although the display light **68** may be turned on, a black color or another dark color may be outputted on the display **62** so that the inside of the accommodation case **43** is not visible through the see-through part **21**.

(332) In this state, the display light **68** may be turned on to illuminate the display **62** and output a screen to the outside. Here, if the outputted screen is black monochrome, the display **62** may be seen as the black color as a whole. Thus, the display **62** having the black color may be seen only when viewing the see-through part **21** from the outside, and the inside of the accommodation case **43** may not be visible.

(333) In FIGS. **39** and **40**, the inner space of the accommodation case **43** may be actually invisible through the see-through part **21** in a normal use state because of the opaque state. However, in FIG. **40**, the see-through part **21** may have a completely black color so that the inside of the accommodation case **43** is completely invisible through the see-through part **21**. Also, the inner space of the accommodation case **43** may not be visible when the display **62** outputs a dark color but the black color.

(334) In the case of FIG. **40**, even in the opaque mode, since the display light and the display are turned on, there is a disadvantage in that more power is consumed compared to the state shown in FIG. **39**.

(335) However, as illustrated in FIG. **40**, when the display light **68** is turned on, heat may be generated at the portion at which the display unit **68** is disposed. That is, when the display light **68** is driven, dew condensation may be prevented from occurring on the upper and lower ends of the transparent display **62** by the generated heat.

(336) Thus, to prevent the dew condensation from occurring, the display light **68** may be turned on, and the display **62** may output the block color so that the see-through part **21** is opaque. Also, to improve the power consumption, the display light **68** may be periodically turned on. In this case, the state of FIG. **39** and the state of FIG. **40** may be alternately and repeatedly performed.

(337) Also, while the display **62** outputs the black color, even though the door light **57** as well as the display light **68** is turned on, the see-through part **21** may be opaque due to the screen outputted on the display **62**. Thus, this state may be a state in which all of the display light **68** and the door light **57** are turned on. In this case, both left and right ends of the transparent panel assembly **60** may be heated by the heat generated when the door light **57** is driven. Thus, the whole of the circumference of the see-through part **21** may be heated to effectively prevent the dew condensation from occurring.

(338) FIG. **41** is a front view when the refrigerator is in a transparent mode.

(339) As illustrated in the drawing, the refrigerator may be converted into the transparent mode, in

which the inside of the see-through part **21**, i.e., the inner space of the accommodation case **43** is visible through the see-through part **21**, by the user's manipulation.

(340) In the transparent mode, since the inside of the accommodation case **43** is visible through the see-through part **21**, the user may confirm foods accommodated in the accommodation case **43** from the outside.

(341) After the user grasps the location and type of the foods from the outside, the user may quickly take out the desired food after opening the sub door **50**, and an operation for storing other foods may be enabled.

(342) In the transparent mode, the space behind the transparent panel assembly **60** may be illuminated to allow the see-through **21** to be visible. The transparent mode may be implemented in various forms according to the brightness of the inside of the refrigerator, which is visible through the see-through part **21**.

(343) FIG. **42** is a transversely schematic cross-sectional view illustrating an example of the turn-on state when the refrigerator is in the transparent mode.

(344) As illustrated in the drawing, when the refrigerator **1** is in the transparent mode, the door light **57** may be turned on, and the display light **68** may be turned off. In this state, the rear side of the sub door may be illuminated by the door light **57**.

(345) The inside of the accommodation case **43** may be illuminated by the light emitted from both sides of the rear surface of the sub door **50**. Thus, when the see-through part **21** is viewed from the outside, the see-through part **21** may be clearly seen.

(346) In this state, since the display light **68** is turned off, only the inside of the accommodation case **43** may be illuminated. Thus, the portion of the transparent panel assembly **60** inside the sub door **50** viewed from the outside may not be in the illuminated state. Thus, the see-through part **21** may be transparent so that the inside thereof is visible and also may be in a relatively dark state.

(347) FIG. **43** is a transversely schematic cross-sectional view illustrating another example of the turn-on state when the refrigerator is in the transparent mode.

(348) As illustrated in the drawing, when the refrigerator **1** is in the transparent mode, all of the door light **57** and the display light **68** may be turned on. In this state, the rear side of the sub door **50** may be illuminated by the door light **57**, and simultaneously, the transparent panel assembly **60** itself may be illuminated by the display light **68**.

(349) The inside of the accommodation case **43** may be illuminated by the light emitted from both sides of the rear surface of the sub door **50**. In addition, the see-through part **21** may be more illuminated by the emission of the light guide plate **64**. Here, the display **62** may not output a separate screen because of the turned-off state.

(350) Thus, when the see-through part **21** is viewed from the outside, the see-through part **21** may be clearly seen, and also, the transparent panel assembly **60** may be in the illuminated and clear state by the emission of the light guide plate **64**. Although the brightness of the see-through part **21** itself more increases, since the see-through part **21** is visible through the light guide plate **64**, the inner space of the accommodation case **43** may be somewhat blurred.

(351) In FIGS. **42** and **43**, the see-through part **21** may be transparent, and thus, the inside of the refrigerator may be visible. However, in the state of FIG. **42**, the see-through part **21** may be clearly seen in the relatively dark state. On the other hand, in the state of FIG. **43**, the see-through part **21** may be blurred in the relatively bright state. Such brightness and visibility may be selected according to the user's preference.

(352) FIG. **44** is a front view when the refrigerator is in a transparent output mode.

(353) As illustrated in the drawing, the refrigerator **1** may operate in a transparent output mode in which a screen is outputted while the inner space of the accommodation case **43** is visible through the see-through part **21**.

(354) In the transparent output mode, the door light **57** may be turned on so that the inner space of the accommodation case **43** is visible, and the display light **68** may also be turned on for the output

of the screen on the display **62**. That is, as illustrated in FIG. **43**, the display **62** may output the screen in the state in which all of the door light **57** and the display light **68** are turned on.

(355) In this state, the foods stored in the accommodation case **43** may be visible, and also, information may be outputted on the display **62**. Thus, the screen linked with the foods stored in the accommodation case **43** may be outputted by using the see-through part **21** to realize augmented reality.

(356) For example, as illustrated in FIG. **44**, information of the corresponding food may be displayed at a specific position in a state in which the foods stored in the accommodation case **43** is visible through the sight portion **21**.

(357) When the fruit **433** is stored in the accommodation case **43**, a separate window **622** may be outputted on the display **62** at a position corresponding to the storage position of the fruit **433** to display various pieces of information such as a time limit, a recipe using fruits, and the like together with the fruit **433** stored through the see-through part **21**.

(358) Also, when a beverage **434** is stored, a separate window **623** may be displayed on the display **62** at a position corresponding to the beverage **434** to display a type of beverage **434** and an expiration date and a message to be transmitted to other users with the information of the beverage **434**. For example, a message such as “Do not drink beverage of daddy” may be directly inputted through the touch of the see-through part **21** and then inputted to the corresponding screen.

(359) Also, the display **62** may also output the window **624** for displaying other information that is not related to the stored fruit **433** or beverage **434**. A general memo, a notice, or the like may be outputted on the window **624**.

(360) The outputted windows **622**, **623**, and **524** may move and be edited by the user's touch operation. Also, the food information outputted through the see-through part **21** may be inputted by a short distance communication, bar code, or QR code method or may be inputted by using the touch input function of the transparent panel assembly **60** itself. Various input methods through the front panel **61** such as a touch pen or a virtual keyboard may be used for the input method through the transparent panel assembly **60**. Also, the inputting of the food information outputted through the see-through part **21** may be freely inputted and processed by a terminal or a PC connected to the communication module **147** through communication.

(361) FIG. **45** is a transversely schematic cross-sectional view the turn-on state when the refrigerator is in a screen output mode. FIG. **46** is a front view of the refrigerator in a state in which an image is played in the screen output mode.

(362) As illustrated in the drawings, the refrigerator may operate in the screen output mode in which a screen is outputted on a screen through the see-through part **21**. The screen output mode may display a screen **211** outputted from the display **62** in a state in which the inside of the accommodation case **43** is not visible through the see-through part **21**.

(363) For the screen output mode, the display light **68** may be turned on, and the display **62** may output the screen in the state in which the door light **57** is turned off. Thus, the inner space of the accommodation case **43** may be a dark state and may not be visible through the see-through part **21**. As a result, the screen **211** outputted from the display **62** by the emission of the light guide plate **64** may be clearly seen through the see-through part **21**. The see-through part **21** may be used as a display **62** for displaying the screen **211** without visualizing the inside of the accommodation case **43**.

(364) As illustrated in FIG. **46**, the screen **211** outputted through the see-through part **21** may output an image. The image may be an image on the communication module **147** and a portable terminal **2** or a remote PC by near field communication such as Internet or Zigbee, WiFi, NFC, or the like.

(365) For example, an image stored in the user's portable telephone or the image being reproduced may be transmitted to the refrigerator **1** through the communication with the communication module **147** of the main control unit **14** and also be visible through the screen **211**. Alternatively,

the output image may be an image stored in the main control unit **14**, or a separate storage device may be connected to the main control unit **14** to output the image stored in the storage device.

(366) Hereinafter, various examples of screens outputted on the see-through part **21** in the screen output mode will be described.

(367) FIG. **47** is a front view of the refrigerator in a state in which an Internet connection page is shown in the screen output mode.

(368) As illustrated in the drawing, in the screen output mode, the see-through part **21** may output an Internet screen **212**. The Internet screen **212** may be outputted through a general PC or a portable terminal and may be outputted from the entire see-through part **21** or at least a portion of the see-through part **21**.

(369) The Internet screen **212** outputted through the see-through part **21** may be selected by the user's manipulation of the front panel **61** and may be connected to an input device **3** such as an external keyboard or a mouse by the wireless communication and then manipulated to be selected.

(370) FIG. **48** is a front view of the refrigerator in a state in which a standby screen is outputted in the screen output mode.

(371) As illustrated in the drawing, in the screen output mode, the see-through part **21** may output a standby screen. The standby screen **213** may output an item set by the user on the screen displayed on the refrigerator **1** without any additional operation.

(372) For example, general life information such as weather and temperature may be outputted, or a user-specified photograph may be output. A black screen may be outputted to prevent dew condensation from occurring on the see-through part **21**.

(373) The standby screen **213** may be periodically displayed to reduce power consumption, or the standby screen **213** and the opaque mode may be repeatedly and alternately realized.

(374) FIG. **49** is a front view of a state in which a refrigerator manipulation screen is outputted when the transparent display is in a screen output state.

(375) As illustrated in the drawing, in the screen output mode, a manipulation screen **214** for manipulating a general refrigerator may be outputted on the see-through part **21**.

(376) A separate button for displaying or manipulating may not be provided on the refrigerator **1**, and an operation of the refrigerator **1** may be displayed through the see-through part **21** so that the see-through part **21** is touched to manipulate the operation of the refrigerator **1**.

(377) The temperature information and various functions of the refrigerator **1** may be displayed on the see-through part **21** and may be displayed in the form of an icon **625** so that the user performs the touch operation. Also, more information may be displayed through screen switching.

(378) FIG. **50** is a schematic view of a home network constituted by using the refrigerator.

(379) As illustrated in the drawing, the refrigerator **1** may constitute a home network with other electronic devices in the home.

(380) The refrigerator **1** may be in a state in which the refrigerator communicates with other home appliances by the communication module **147**. Thus, the manipulation screen **214** outputted through the see-through part **21** of the sub door **50** may output states of other home appliances connected to the communication module **147** of the refrigerator **1** or smart devices in the home in addition to the operation state and manipulation of the refrigerator **1**. Also, operations of the electronic devices in the home may be controlled through the see-through part **21**.

(381) That is, since the refrigerator **1** is in a state of being supplied with power for 24 hours due to the characteristics in its use, the refrigerator **1** may function as a main controller of the home network. That is, the refrigerator **1** may be connected to the electronic device in the home to control an operation of each of the electronic devices, output states of the electronic devices, and process and output the related information.

(382) For example, the refrigerator **1** may reserve a set operation at a designated time from the on/off of a television **4**, a washing machine **5**, a cooling appliance **6** such as microwave oven, a lighting **7**, and the like, may be connected to an interphone **8** to open and close a door or a window,

and may display a temperature or a degree of air pollution in the room to drive an air conditioner **9**.

(383) The manipulation screen **214** may be set as the standby screen and may be switched by a user's manipulation in a state of outputting another screen by the see-through part **21**.

(384) In addition to the first embodiment of the present inventions, various embodiments may be exemplified. Hereinafter, other embodiments of the present invention will be described with reference to the accompanying drawings. Since other embodiments of the present invention are the same as the first embodiment of the present invention except for some configurations, detailed description of the same configuration will be omitted, and also, the same configuration will be denoted by the same reference numerals.

(385) FIG. **51** is a perspective view of a sub door when viewed from a rear side according to a second embodiment of the present invention.

(386) The second embodiment of the present invention will be the same as the foregoing first embodiment except for only a door light disposed in a sub door.

(387) Referring to the drawing, a sub door **50** may be constituted by coupling a front panel **61** and a rear panel **65**. A transparent panel assembly **60** may provide a see-through part **21** in a state of being mounted on the sub door **50**, and a screen may be outputted through a display **62**.

(388) A liner opening **561** may be defined in a door liner **56**, and a liner protrusion **566** may protrude along the liner opening **561**. Also, a liner protrusion **566** contacting a main door **40** to seal a space between the main door **40** and the sub door **50** may be disposed on a circumference of the liner protrusion **566**.

(389) A door light **57'** may be disposed on a rear surface of the liner protrusion **566**. The door light **57'** may be disposed on each of both left and right sides of a rear end of the liner protrusion **566**. The door light **57'** may extend from an upper end to a lower end of the liner protrusion **566**. Also, as necessary, the door light **57'** may be disposed along a circumference of the liner protrusion **566**.

(390) The door light **57'** may emit light to a rear side of the liner protrusion **566** to illuminate the inside of an accommodation case **43**. The door light **57'** may concentratedly illuminate the accommodation case **43** rather than the above-described door light **57'**.

(391) Also, the door light **57'** may include a lighting module **575'** mounted on the liner protrusion **566** and a light cover covering the lighting module **575'**. Light emitted from the lighting module **575'** may pass through the light cover **574'** and then be reflected and diffused to uniformly illuminate the inside of the accommodation case **43**.

(392) FIG. **52** is an exploded perspective view of a transparent panel assembly according to a third embodiment of the present invention.

(393) A third embodiment of the present invention is the same as the foregoing first embodiment except for a configuration of a transparent panel assembly.

(394) As illustrated in the drawing, a transparent panel assembly **70** according to the third embodiment of the present invention may be mounted inside a sub door **50** to provide a see-through part **21**. The see-through part **21** may include the transparent panel assembly **70**. The inside of an accommodation case **43** may be visible through a see-through part **21**, or an outputted screen may be displayed on the see-through part **21**.

(395) The transparent panel assembly **70** may include a front glass **71** defining an outer appearance of a front surface, a display **74** disposed at a rear side of the front glass **71**, a rear glass to which a PDLC film **75** is attached to illuminate the display **74** at a rear side of the display **74**, and an outer spacer **77** fixing the front glass **71**, the display **74**, and the rear glass **76**.

(396) In more detail, the front glass **71** may be disposed at a front side of the transparent display **74** and exposed to the outside through a see-through part **21**. The front glass **71** may be provided as a blue glass, and a touch film **72** may be attached to a rear surface of the front glass **71**. Thus, when a user touches the front glass **71**, the front glass **71** may recognize the user's touch. Also, a touch PCB **721** may be mounted on one side of the touch film **72**.

(397) The display **74** may be mounted on the rear side of the front glass **71** to which the touch film

72 is attached. Also, the display frame 73 may be disposed between the display 74 and the front glass 71. The display frame 73 may have a rectangular frame shape disposed along a circumference of the display 74. Also, the display frame 73 may adhere between the display 74 and the front glass 71 to maintain a predetermined distance between the front glass 71 and the display 74 and support the display 74.

(398) The display 74 may be provided as a transparent LCD display. Thus, although the display 74 does not output a screen, the inside of the refrigerator 1 may be visible through the display 94 as if glass. Also, a T-CON board 741 for controlling the display 74 may be mounted on one end of the display 74. Also, a source board 742 for outputting the display 74 may be disposed on one end of the display 74.

(399) The rear glass 76 may define an outer appearance of a rear surface of the transparent panel assembly 70 and be exposed to the door liner 56. The rear glass 76 may be made of low-F glass to realize thermal insulation.

(400) The PDLC film 75 may be attached to the front surface of the rear glass 76. The PDLC film 75 may be selectively transparent or opaque according to applying of power. Thus, the user may selectively see the inside of the refrigerator according to the state of the PDLC film 75. Also, a PDLC PCB 751 may be disposed on one side of the PDLC film 75 to control an operation of the PLDC film 75.

(401) The outer spacer 77 may define a circumferential surface of the transparent panel assembly 70. Also, the outer spacer 77 may fix the front glass 71, the display 74, and the rear glass 76 to maintain a preset space between the front glass 71, the display 74, and the rear glass 76. Also, the transparent panel assembly 70 may be fixed and mounted on a sub door 50 when the transparent panel assembly 70 is completely assembled.

(402) Also, in a state in which the display 74 does not output a screen, and the PDLC film 75 is transparent, a see-through part 21 may be transparent. In this state, when a door light 57 is turned on, a space inside the accommodation case 43 may be visible through the see-through part 21 from the outside.

(403) In the state in which the display 74 does not output the screen, the PDLC film 75 may be opaque. Then, the door light may also be turned off, and the see-through part 21 may be opaque. Thus, an inner space of the accommodation case 43 may be visible.

(404) The see-through part 21 may output a screen by driving the display 74. In this case, in the state in which the door light 57 is turned on, and the PDLC film 75 is transparent, the door light 57 may serve as a backlight that illuminates the display 74 so that the display 74 is more clearly displayed.

(405) FIG. 53 is a perspective view of a sub door when viewed from a front side according to a fourth embodiment of the present invention.

(406) A fourth embodiment of the present invention is the same as the foregoing first embodiment except for only a heating member.

(407) As illustrated in the drawing, a sub door 50 may have a plate opening 511 in an out plate 51, and a transparent panel assembly 60 may be mounted to cover the plate opening 511. Also, a front surface of the transparent panel assembly 60, which is exposed through the plate opening 511, may be defined as a see-through part 21.

(408) Also, the inside of the refrigerator, i.e., the inside of the accommodation case 43 may be selectively visible through the see-through part 21, or a screen of the inside may be outputted according to an output of a screen on a display 62 constituting the transparent panel assembly 60 and a combination of a display light 68 and a door light 57.

(409) In a state in which the display 62 operates, or the display light 68 and the door light 57 operate, a circumference of the transparent panel assembly 60 may be heated. Thus, dew condensation may be prevented from occurring on the circumference of the transparent panel 60, more particularly, an out plate 51 corresponding to a circumference of the see-through part 21.

(410) However, in a state in which the display **62**, the display light **68**, and the door light **57** do not operate, dew condensation may occur on a front surface of the out plate **51**, which corresponds to the circumference of the see-through part **21**.

(411) Thus, a heating member **517** for preventing the dew condensation from occurring on the out plate **51** may be provided in the sub door **50**.

(412) The transparent panel assembly **60** may include a front panel **61** defining a front surface thereof. The front panel **61** may have a size greater than that of a plate opening **511** and thus be supported on a rear surface of the out plate **51**.

(413) Also, the heating member **517** may be disposed on a circumference of the front panel **61** contacting the rear surface of the out plate **51**. Thus, the front surface of the out plate **51**, on which the dew condensation may occur, may be heated by heat of the heating member **517** to prevent the dew condensation from occurring. Various types of heaters, which are disposed between the out plate **51** and the front panel **61**, such as a wire-type heating line or a film-type film heater may be used as the heating member **517**.

(414) The heating member **517** may be periodically turned on and off to prevent the dew condensation from occurring. Also, while the display **62**, the display light **68**, and the door light **57** operate, the heating member **517** may be turned off. When the display **62**, the display light **68**, and the door light **57** do not operate, the heating member **517** may be turned on.

(415) FIG. **54** is an exploded perspective view of a sub door according to a fifth embodiment of the present invention.

(416) A fifth embodiment of the present invention is the same as the foregoing first embodiment except for only a mounted structure of a PCB.

(417) As illustrated in the drawing, a sub door **50** may have a plate opening **511** in an out plate **51**, and a transparent panel assembly **60** may be mounted to cover the plate opening **511**. Also, a front surface of the transparent panel assembly **60**, which is exposed through the plate opening **511**, may be defined as a see-through part **21**.

(418) Also, the inside of the refrigerator, i.e., the inside of the accommodation case **43** may be selectively visible through the see-through part **21**, or a screen of the inside may be outputted according to an output of a screen on a display **62** constituting the transparent panel assembly **60** and a combination of a display light **68** and a door light **57**.

(419) Also, a PCB accommodation part **505** that is opened upward may be defined in an upper side of the inside of the sub door **50**. The PCB accommodation part **505** may be defined in a door liner defining a rear surface of the sub door **50** and be recessed downward to form a space for accommodating a PCB **601'**. Alternatively, the PCB accommodation part **505** may not be defined in the door liner **56** but be provided by an injection molding or a previously molded insulation member **53**, which is separately assembled.

(420) Also, the PCB accommodation part **505** may be covered by an upper cap decor **54** defining a top surface of the sub door **50**. A heat dissipation hole **543** for releasing heat generated in the PCB **601'** may be defined in an area of the upper cap decor **54**, which corresponds to the PCB accommodation part **505**.

(421) The PCB **601'** may be configured to control operations of a touch sensor **612**, a display **62**, and a display light **68**, which constitute the transparent panel assembly **60**, and may be provided in the form of a module. Also, the PCB **601'** may also control the door light **57** and/or the heating member **517**. The PCB **601'** may be provided as one PCB module for controlling one or more constituents. As necessary, the PCB **601'** may be provided by connecting one or more constituents to each other.

(422) Also, a PCB connector **603** may be provided on the PCB **601'**. The PCB connector **603** may be connected to an assembly connector **604** connected to the transparent panel assembly **60** while being assembled.

(423) While the sub door **50** is assembled, the assembly connector **604** may be exposed to the

inside of the PCB accommodation part **505**. While the PCB **601'** is mounted, the assembly connector **604** and the PCB connector **603** may be connected to each other. After the PCB **601'** is completely mounted, the upper cap decor **54** may be mounted to assemble the sub door **50**.

(424) FIG. **55** is a transversely cross-sectional view of a sub door according to a sixth embodiment of the present invention.

(425) A fourth embodiment of the present invention is the same as the foregoing first embodiment except for only a heating member and a supplement member.

(426) As illustrated in the drawing, an outer appearance of a sub door **50** is defined by an out plate **51**, a door liner **56**, an upper cap decor **54**, and a lower cap decor **55**. Also, a transparent panel assembly **60** may be disposed in the sub door **50** to cover a plate opening **511** and a liner opening **561**.

(427) A space may be defined in left and right sides of a space in which the transparent panel assembly **60** is disposed, and an insulation member **534** for insulating may be provided in the space. The sub door **50** may have a structure in which the transparent panel assembly **60** is mounted after the insulation member **534** is assembled. Thus, after the insulation member **534** is assembled, while the transparent panel assembly **60** is assembled and mounted, a gap may occur between a circumference of the transparent panel assembly **60** and the insulation member **534**.

(428) A supplement member **535** may be provided between the circumference of the transparent panel assembly **60** and the insulation member **534**. The gap between the transparent panel assembly **60** and the insulation member **534** may be filled with the supplement member **535**.

(429) At least one or more supplement members **535** may be provided. For example, a first supplement member **535a** made of a material having elasticity may be provided on a portion contacting the transparent panel assembly **60**. Thus, the first supplement member **535a** may press and support a circumferential surface of the transparent panel assembly **60** to prevent the gap from occurring. Also, even though the sub door **50** rotates, or an impact is applied to the sub door **50**, the transparent panel assembly **60** may be stably protected.

(430) Also, a second supplement member **535b** may be disposed between the first supplement member **535a** and the insulation member **534**. The second supplement member **535b** may be provided as an adhesive so that the first supplement member **535a** and the insulation member **534** adhere to each other. Also, the second supplement member **535b** may be made of an insulation material that is capable of being injected from the outside to provide additional insulation.

(431) Alternatively, the supplement member **535** may be provided as a single constituent. In this case, the supplement member **535** may be provided in the form of the first supplement member **535a** or the second supplement member **535b**.

(432) An inner region of the sub door **50** outside the transparent panel assembly **60** may be filled with the supplement member **535**. Thus, insulation performance may be improved, and also, the inner space may be filled to provide a structure in which the out plate **51** and the door liner **56** are closely attached to each other.

(433) Also, the supplement member **535** may have a structure that adheres to the out plate **51** and the door liner **56** to prevent the out plate **51** and the door liner **56** from being deformed.

(434) FIG. **56** is an exploded perspective view of a sub door according to a seventh embodiment of the present invention.

(435) A third embodiment of the present invention is the same as the foregoing first embodiment except for a mounted structure of a transparent panel assembly.

(436) As illustrated in the drawing, an outer appearance of a sub door **50** is defined by an out plate **51**, a door liner **56**, an upper cap decor **54**, and a lower cap decor **55**. Also, a transparent panel assembly **60** may be disposed in the sub door **50** to cover a plate opening **511** and a liner opening **561**.

(437) Although the transparent panel assembly **60** has the same structure as that according to foregoing first embodiment, a front panel **60'** may have a size corresponding to a plate opening **511**.



Thus, the transparent panel assembly **60** may be inserted and mounted from a front side through the plate opening **511**.

(438) Also, a supplement member **536** may be disposed on a circumference of the transparent panel assembly **60**. The supplement member **536** may be disposed on the whole or a portion of the circumference of the transparent panel assembly **60**. An outer surface of the transparent panel assembly **60** and the inside of the sub door **50** may be supported by each other. Thus, a gap between the circumference of the transparent panel assembly **60** and the inner surface of the sub door **50** may be covered by the supplement member **536**.

(439) The supplement member **536** may be made of a rubber, resin, or silicon material. Thus, the transparent panel assembly **60** may be assembled in a state in which the supplement member **536** is applied to the circumference of the transparent panel assembly **60** or the inner surface of the sub door **50**.

(440) A seating part **569** on which the transparent panel assembly **60** is seated may be disposed inside the plate opening **511**. The seating part **569** may protrude inward to support a circumference of a rear surface of the transparent panel assembly **60** and define the liner opening **561**. Thus, the seating part **569** may be provided by the door liner **56** or provided by another constituent provided in the sub door **50**.

(441) A sealing member or adhesive **569a** may be disposed on a front surface of the seating part **569**. Thus, the rear surface of the transparent panel assembly **60** may be adhered and fixed to the seating part **569**.

(442) FIG. **57** is an exploded perspective view of a sub door according to an eighth embodiment of the present invention.

(443) A fourth embodiment of the present invention is the same as the foregoing first embodiment except for only an arrangement of a see-through part.

(444) As illustrated in the drawing, a refrigerator **1** according to a seventh embodiment of the present invention includes a refrigerating compartment **12** and a freezing compartment, which are respectively provided in upper and lower portions thereof. Also, a refrigerating compartment door **20** may be rotatably provided on the refrigerating compartment **12**, and a freezing compartment door **30** may be provided on the freezing compartment **13**.

(445) The refrigerating compartment door **20** and the freezing compartment door **30** may be respectively configured to open and close the refrigerating compartment **12** and the freezing compartment **13** by the rotation thereof. Each of the refrigerating compartment door **20** and the freezing compartment door **30** may be provided in a pair at left and right sides to partially or wholly open and close the refrigerating compartment **12** or the freezing compartment **13**.

(446) A right refrigerating compartment door **20** of the refrigerating compartment door **20** may be constituted by a main door **40** and a sub door **50**. An opening **41** and an accommodation case **43** may be provided in the main door **40**, and the opening **41** may be opened and closed by the sub door **50**.

(447) Also, a see-through part **21** through which the inside of the accommodation case **43** is visible may be provided in the sub door **50**. The see-through part **21** may include a transparent panel assembly **60** mounted inside the sub door **50**. The see-through part **21** may be selectively transparent or output a screen by a combination of a display **62**, a display light **68**, and a door light **57** of the transparent panel assembly **60**.

(448) A see-through part **21'** may be provided in a left refrigerating compartment door **20**. The see-through part **21'** may be selectively transparent or output a screen by the transparent panel assembly **60**. The see-through part **21** may be provided by mounting the transparent panel assembly **60** having the same structure as the see-through part **21'** except for the position thereof. Also, the see-through part **21'** may be provided in the refrigerating compartment door **20** to illuminate an inner space of a cabinet **10**. As necessary, the left refrigerating compartment door **20** may also include the main door **40** and the sub door **50** and may selectively visualize the inside of the

accommodation case **43** through the see-through part **21'**.

(449) That is, a stored state of foods in all of the pair of refrigerating compartment doors **20** that are respectively provided at the left right sides may be selectively visible through the see-through parts **21** and **21'**. Also, the screen may be outputted through the see-through part **21** and **21'**.

(450) A refrigerator according to an embodiment includes: a see-through part passing through a door to communicate with an accommodation space; a transparent panel assembly covering the see-through part and outputting a screen; a display light provided in the transparent panel assembly to serve as a backlight when the screen is outputted; and a door light provided in the door behind a transparent display to selectively illuminate the accommodation member so that the inside of an accommodation space is visible through the see-through part, wherein the see-through part is displayed in one state of transparent, opaque, and screen output states by a combination of the display light and the door light.

(451) The display light may be vertically disposed to emit light in directions facing each other, and the door light may be disposed on each of both sides to emit light in directions facing each other.

(452) The door light may be disposed on a rear surface of the transparent display panel to emit light in a direction that is parallel to the transparent display panel.

(453) The transparent display panel includes: a front panel made of a transparent material to define an outer appearance of a front surface of the transparent panel assembly and exposed through the see-through part; a display disposed behind the front panel to output a screen and being transparent; a light guide plate provided behind the display; a rear panel made of a transparent material to define an outer appearance of a rear surface of the transparent panel assembly and spaced apart from the front panel; and an outer spacer configured to connect the front panel to the rear panel and defining an outer appearance of a circumferential surface of the transparent panel assembly, wherein the display light is mounted on the outer spacer to emit light toward the light guide plate at positions corresponding to upper and lower ends of the light guide plate.

(454) A heating member for preventing dew condensation from occurring may be disposed between the front panel and the front surface of the door outside the see-through part.

(455) A spacer may be disposed between both left and right sides of the front panel and the light guide plate, and the spacer may be disposed at a further front side than an intermediate point of a thickness of the transparent panel assembly.

(456) The outer spacer may include: a light mounting part which extends upward and downward from the light guide plate and on which the display light is mounted; and a spacer part extending to one side of the light mounting part to support a portion between the front panel and the light guide plate.

(457) The door light may include: a lighting module emitting light backward; a light housing including a reflection part for reflecting the light emitted from the lighting module in a lateral direction; and a light cover that covers an opening of the light housing and through which the light reflected by the reflection part passes.

(458) The front panel may have a size greater than that of the see-through part and further protrude outward than the display, the light guide plate, and the rear panel.

(459) An inner frame disposed along a circumference of the see-through part may be disposed outside the door, and a circumference of the front panel may be seated on the inner frame.

(460) The inner frame may have an accommodation groove into which an opening bent part that is bent along the circumference of the see-through part is inserted, and a space between the see-through part and the front panel may be covered by the inner frame.

(461) A rib supporting an end of the front panel may be disposed on the rear surface of the inner frame.

(462) A PCB mounting part on which a PCB for controlling an operation of the transparent panel assembly is mounted may be disposed on an upper portion of the inner frame, and the PCB mounting part may be disposed above the transparent panel assembly.

(463) An upper cap decor defining a top surface of the door may be disposed above the PCB mounting part, and a heat dissipation hole for cooling the PCB may be defined in the upper cap decor.

(464) A heat dissipation hole guide for guiding foreign substance passing through the heat dissipation hole to the outside of the PCB may be further defined in a circumference of the heat dissipation hole.

(465) The PCB may include a T-CON board for controlling the display, a light PCB for controlling the display light, and a touch PCB for controlling a touch sensor attached to the front panel.

(466) The PCB, the touch sensor, the display, and the display light may be connected to each other through an FFC or EEP type cables, and the cables may be disposed along the circumference of the transparent panel assembly.

(467) A connector that is connected to be converted into a wire-type electric wire may be provided on the PCB.

(468) The wire may pass through the upper cap decor and a hinge cover covering a hinge of the door and be guided to the outside of the door.

(469) The PCB may be connected to the main control unit on the top surface of the cabinet by the wire, and the main control unit may include: a main PCB controlling an overall operation of the refrigerator; a display PCB connected to the PCB to control the transparent panel assembly and the door light; and an adaptor converting input power to transmit the power to the PCB.

(470) A communication module may be connected to the display PCB, home appliances may be connected to each other by the communication module, and an operation state of each of the connected home appliances may be outputted to be manipulated.

(471) A source board may be connected to at least one end of both left and right ends of the display, and the source board may be bent to the outside of the outer spacer to extend along the outer spacer.

(472) An insulation member that is inserted and mounted in a molded shape along the circumference of the transparent panel assembly may be provided in the door.

(473) A supplement member configured to support the transparent panel assembly may be further disposed between the insulation member and the transparent panel assembly.

(474) The supplement member may be provided as an adhesive, a sealing member, or an elastic material.

(475) The door may include: a main door rotatably mounted on the cabinet and having an accommodation space and a front opening communicating with the accommodation space; and a sub door rotatably mounted on the main door and including the see-through part.

(476) A liner protrusion protruding backward and accommodated in the opening may be disposed on the sub door, and the door light may be disposed at a position facing each other on the liner protrusion.

## INDUSTRIAL APPLICABILITY

(477) According to the embodiment of the present invention, since the use convenience is improved, the industrial possibility is high.

## Claims

1. A refrigerator comprising: a cabinet that defines a storage compartment; a door configured to open and close at least a portion of the storage compartment; a hinge that rotatably connects the door to the cabinet, the hinge having (i) a first portion that has a plate shape and is coupled to the cabinet and (ii) a second portion comprising a hinge shaft that is coupled to the door; a wire that is disposed above the hinge and extends from the cabinet toward the door; and a hinge cover that is disposed above the hinge and covers at least a portion of the wire, the hinge cover defining a connection hole above the second portion of the hinge, wherein the wire extends through a wire passage defined below the hinge cover and then extends to an outside of the hinge cover through

the connection hole, wherein the connection hole is defined above the hinge shaft and aligned with the hinge shaft, wherein the hinge cover defines the connection hole at an end of the wire passage, and wherein the wire passes through the connection hole and extends to an upper portion of the hinge cover.

2. The refrigerator of claim 1, wherein the second portion of the hinge is curved from the first portion of the hinge outward toward a side edge of the door.
  3. The refrigerator of claim 2, wherein the wire is curved along the second portion of the hinge and extends outward toward the side edge of the door.
  4. The refrigerator of claim 2, wherein the hinge cover comprises an extension part that is disposed above the door and extends toward the hinge shaft along the second portion of the hinge.
  5. The refrigerator of claim 1, wherein the wire extends from the first portion of the hinge to the second portion of the hinge through the wire passage of the hinge cover.
  6. The refrigerator of claim 1, wherein a portion of the wire is disposed outside the hinge cover and extends laterally along a front surface of the door.
  7. The refrigerator of claim 1, wherein the wire is disposed at an upper surface of the first portion of the hinge and extends to an upper surface of the cabinet.
  8. The refrigerator of claim 1, wherein the door comprises a hinge mounting part that is disposed at an upper surface of the door and defines a hinge hole receiving the hinge shaft.
  9. The refrigerator of claim 8, wherein the hinge hole is one of a plurality of openings defined at the upper surface of the door.
  10. The refrigerator of claim 1, wherein the connection hole has a circular shape.
  11. The refrigerator of claim 1, wherein an extension line of the hinge shaft passes through the connection hole.
  12. The refrigerator of claim 1, wherein the wire extends along an upper surface of the hinge, and an end of the wire extends to an inside of the cabinet.
  13. The refrigerator of claim 1, wherein the first portion of the hinge is fixed to an upper surface of the cabinet, and the second portion of the hinge is disposed above an upper surface of the door, and wherein the hinge shaft extends through the upper surface of the door and rotatably connects the door to the cabinet.
  14. The refrigerator of claim 1, wherein at least a portion of the wire is configured to move together with the door based on the door opening and closing the storage compartment.
  15. A refrigerator comprising: a cabinet that defines a storage compartment; a door configured to open and close at least a portion of the storage compartment; a hinge that rotatably connects the door to the cabinet, the hinge having (i) a first portion that has a plate shape and is coupled to the cabinet and (ii) a second portion comprising a hinge shaft that is coupled to the door; a wire that is disposed above the hinge and extends from the cabinet toward the door; and a hinge cover that is disposed above the hinge and covers at least a portion of the wire, the hinge cover defining a connection hole above the second portion of the hinge, wherein the hinge that is disposed closer to a first side of the door than to a second side of the door opposite to the door, wherein the wire extends in an upward direction through the connection hole of the hinge cover and then extends in a direction from the first side of the door toward the second side of the door, wherein the connection hole is defined above the hinge shaft and aligned with the hinge shaft, wherein the hinge cover defines the connection hole at an end of a wire passage defined below the hinge cover, and wherein the wire passes through the connection hole and extends to an upper portion of the hinge cover.
  16. The refrigerator of claim 15, wherein the connection hole is defined at a position closer to the first side of the door than to the second side of the door opposite to the door.
  17. The refrigerator of claim 15, wherein the wire extends through the wire passage and then extends to an outside of the hinge cover through the connection hole.
-

