



US012390344B2

(12) **United States Patent**
To et al.

(10) **Patent No.:** **US 12,390,344 B2**

(45) **Date of Patent:** **Aug. 19, 2025**

(54) **DISTRIBUTING GRAFT MATERIAL FROM AN EXPANDABLE CAGE**

(71) Applicant: **INTEGRITY IMPLANTS INC.**, Palm Beach Gardens, FL (US)

(72) Inventors: **John To**, Newark, CA (US); **John J. Flynn**, Walnut Creek, CA (US); **Paul J. Birkmeyer**, Marshfield, MA (US)

(73) Assignee: **INTEGRITY IMPLANTS INC.**, Palm Beach Gardens, FL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 597 days.

(21) Appl. No.: **17/553,136**

(22) Filed: **Dec. 16, 2021**

(65) **Prior Publication Data**

US 2022/0160517 A1 May 26, 2022

Related U.S. Application Data

(63) Continuation of application No. 16/444,888, filed on Jun. 18, 2019, now Pat. No. 11,234,837, which is a (Continued)

(51) **Int. Cl.**
A61F 2/44 (2006.01)
A61F 2/46 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A61F 2/447** (2013.01); **A61F 2/442** (2013.01); **A61F 2/4611** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC **A61F 2/4455–2/447**; **A61F 2250/0004–2250/001**; **A61F 2250/0048**;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,309,777 A 1/1982 Patil
4,733,665 A 3/1988 Palmaz
(Continued)

FOREIGN PATENT DOCUMENTS

CN 101909548 7/2014
DE 10 2018 206693 2/2019
(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 17/380,897, filed Jul. 20, 2020, Shoshtaev—owned by Applicant.

(Continued)


Primary Examiner — Ellen C Hammond

(74) *Attorney, Agent, or Firm* — McNees Wallace & Nurick LLC

(57) **ABSTRACT**

An expansion member for distributing graft material through a cage and into an intervertebral space is provided. The expansion member has a central beam with an entry port in fluid communication with an exit port for distribution of the graft material. The central beam is inserted into a cage having a reversible collapse from an expanded state into a collapsed state, the expanded state forming a graft distribution window. The expanded state, for example, can be configured to open the graft distribution window which at least substantially closes upon the reversible collapse.

20 Claims, 19 Drawing Sheets



Related U.S. Application Data

continuation of application No. 16/169,049, filed on Oct. 24, 2018, now Pat. No. 10,786,366, which is a continuation of application No. 15/091,535, filed on Apr. 5, 2016, now Pat. No. 10,149,773, which is a continuation of application No. 14/157,504, filed on Jan. 16, 2014, now Pat. No. 9,333,092, which is a continuation of application No. 13/815,787, filed on Mar. 15, 2013, now Pat. No. 8,663,332.

- (60) Provisional application No. 61/737,054, filed on Dec. 13, 2012.

(51) Int. Cl.

A61F 2/28 (2006.01)

A61F 2/30 (2006.01)

(52) U.S. Cl.

CPC *A61F 2002/2817* (2013.01); *A61F 2002/2835* (2013.01); *A61F 2002/30019* (2013.01); *A61F 2002/30556* (2013.01); *A61F 2002/30579* (2013.01); *A61F 2002/30581* (2013.01); *A61F 2002/30593* (2013.01); *A61F 2002/30594* (2013.01); *A61F 2002/30777* (2013.01); *A61F 2002/30779* (2013.01); *A61F 2002/30785* (2013.01); *A61F 2/30965* (2013.01); *A61F 2/441* (2013.01); *A61F 2002/4435* (2013.01); *A61F 2002/444* (2013.01); *A61F 2/4684* (2013.01); *A61F 2310/00011* (2013.01); *A61F 2310/00023* (2013.01); *A61F 2310/00029* (2013.01); *A61F 2310/00047* (2013.01); *A61F 2310/00053* (2013.01); *A61F 2310/00071* (2013.01); *A61F 2310/00179* (2013.01); *A61F 2310/00293* (2013.01)

(58) Field of Classification Search

CPC *A61F 2/4611*; *A61F 2002/30593*; *A61F 2002/30594*; *A61F 2/4601*

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

4,759,766 A 7/1988 Buettner-Janz et al.
 4,820,305 A 4/1989 Harms et al.
 4,997,432 A 3/1991 Keller
 5,192,327 A 3/1993 Brantigan
 5,221,261 A 6/1993 Termin et al.
 5,609,635 A 3/1997 Michelson
 5,658,336 A 8/1997 Pisharodi
 5,976,187 A 11/1999 Richelsoph
 5,980,522 A 11/1999 Koros
 5,980,552 A 11/1999 Pinchasik et al.
 6,039,761 A 3/2000 Li et al.
 6,102,950 A 8/2000 Vaccaro
 6,126,689 A 10/2000 Brett
 6,176,882 B1 1/2001 Biedermann
 6,193,757 B1 2/2001 Foley et al.
 6,368,351 B1 4/2002 Glenn et al.
 6,375,682 B1 4/2002 Fleischmann et al.
 6,395,031 B1 5/2002 Foley et al.
 6,409,766 B1 6/2002 Brett
 6,419,705 B1 7/2002 Erickson
 6,425,919 B1 7/2002 Lambrecht et al.
 6,432,107 B1 8/2002 Ferree
 6,436,119 B1 8/2002 Erb et al.
 6,443,989 B1 9/2002 Jackson
 6,482,235 B1 11/2002 Lambrecht et al.
 6,488,710 B2 12/2002 Besselink
 6,491,724 B1 12/2002 Ferree
 6,575,899 B1 6/2003 Foley et al.

6,582,439 B1 6/2003 Sproul
 6,582,441 B1 6/2003 He et al.
 6,582,467 B1 6/2003 Teitelbaum
 6,595,998 B2 7/2003 Johnson et al.
 6,666,891 B2 12/2003 Boehm, Jr. et al.
 6,821,276 B2 11/2004 Lambrecht et al.
 6,821,298 B1 11/2004 Jackson
 6,893,464 B2 5/2005 Kiester
 7,018,415 B1 3/2006 McKay
 7,083,650 B2 8/2006 Moskowitiz et al.
 7,087,055 B2 8/2006 Lim et al.
 7,204,853 B2 4/2007 Gordon et al.
 7,214,243 B2 5/2007 Taylor
 7,217,293 B2 5/2007 Branch
 7,316,686 B2 1/2008 Dorchak et al.
 7,544,208 B1 6/2009 Mueller et al.
 7,621,950 B1 11/2009 Globerman et al.
 7,643,884 B2 1/2010 Pond et al.
 7,655,046 B2 2/2010 Dryer et al.
 7,678,148 B2 3/2010 Peterman
 7,731,751 B2 6/2010 Butler et al.
 7,771,473 B2 8/2010 Thramann
 7,819,921 B2 10/2010 Grotz
 7,828,845 B2 11/2010 Estes et al.
 7,828,849 B2 11/2010 Lim
 7,846,206 B2 12/2010 Oglaza et al.
 7,850,733 B2 12/2010 Baynham et al.
 7,862,618 B2 1/2011 White et al.
 7,879,098 B1 2/2011 Simmons, Jr.
 7,909,872 B2 3/2011 Zipnick
 7,918,888 B2 4/2011 Hamada
 7,951,202 B2 5/2011 Ralph et al.
 8,062,375 B2 11/2011 Glerum et al.
 8,070,754 B2 12/2011 Fabian et al.
 8,070,813 B2 12/2011 Grotz et al.
 8,083,744 B2 12/2011 Dorchak
 8,088,163 B1 1/2012 Kleiner
 8,105,382 B2 1/2012 Olmos et al.
 8,110,004 B2 2/2012 Valdevit et al.
 8,118,870 B2 2/2012 Gordon et al.
 8,123,810 B2 2/2012 Gordon et al.
 8,167,950 B2 5/2012 Aferzon et al.
 8,182,538 B2 5/2012 O'Neil et al.
 8,187,332 B2 5/2012 McLuen
 8,236,058 B2 8/2012 Fabian et al.
 8,241,363 B2 8/2012 Sommerich et al.
 8,267,939 B2 9/2012 Cipoletti et al.
 8,273,129 B2 9/2012 Baynham et al.
 8,353,961 B2 1/2013 McClintock
 8,353,963 B2 1/2013 Glerum
 8,398,713 B2 3/2013 Weiman
 8,435,298 B2 5/2013 Weiman
 8,491,659 B2 7/2013 Weiman et al.
 8,518,120 B2 8/2013 Glerum et al.
 8,523,944 B2 9/2013 Jimenez et al.
 8,551,173 B2 10/2013 Lechmann et al.
 8,556,979 B2 10/2013 Glerum et al.
 8,628,578 B2 1/2014 Miller et al.
 8,632,595 B2 1/2014 Weiman
 8,663,332 B1 3/2014 To
 8,685,098 B2 4/2014 Glerum et al.
 8,777,993 B2 7/2014 Siegal et al.
 8,845,731 B2 9/2014 Weiman
 8,852,279 B2 10/2014 Weiman et al.
 8,882,840 B2 11/2014 McClintock et al.
 8,894,712 B2 11/2014 Varela
 8,900,307 B2 12/2014 Hawkins et al.
 8,906,099 B2 12/2014 Poulos
 8,926,704 B2 1/2015 Glerum et al.
 8,936,641 B2 1/2015 Cain
 8,940,048 B2 1/2015 Butler
 8,940,052 B2 1/2015 Lechmann et al.
 8,986,387 B1 3/2015 To
 9,034,041 B2 5/2015 Wolters
 9,039,771 B2 5/2015 Glerum et al.
 9,044,342 B2 6/2015 Perloff et al.
 9,060,876 B1 6/2015 To
 9,066,813 B2 6/2015 Farris et al.
 9,138,328 B2 9/2015 Butler et al.

References Cited

U.S. PATENT DOCUMENTS

References Cited			U.S. PATENT DOCUMENTS				
			10,869,769	B2	12/2020	Eisen et al.	
			10,898,340	B2	1/2021	Koch et al.	
			11,076,968	B2	8/2021	To	
			2002/0035400	A1	3/2002	Bryan et al.	
9,155,628	B2	10/2015	2002/0040243	A1	4/2002	Attali	
9,186,259	B2	11/2015	2003/0074075	A1	4/2003	Thomas et al.	
9,216,095	B2	12/2015	2003/0083746	A1	5/2003	Kuslich	
9,241,806	B2	1/2016	2004/0010315	A1	1/2004	Song	
9,278,008	B2	3/2016	2004/0024463	A1	2/2004	Thomas et al.	
9,320,610	B2	4/2016	2005/0256576	A1	11/2005	Moskowitz et al.	
9,333,092	B2	5/2016	2006/0100706	A1	5/2006	Shaddock	
9,351,848	B2	5/2016	2006/0122701	A1	6/2006	Kiester	
9,402,733	B1	8/2016	2006/0167547	A1	7/2006	Suddaby	
9,402,739	B2	8/2016	2006/0287729	A1	12/2006	Segal et al.	
9,421,110	B2	8/2016	2007/0118222	A1	5/2007	Lang	
9,439,782	B2	9/2016	2007/0173939	A1	7/2007	Kim et al.	
9,445,918	B1	9/2016	2007/0219634	A1	9/2007	Greenhalgh	
9,463,052	B2	10/2016	2008/0009876	A1	1/2008	Sankaran et al.	
9,474,625	B2	10/2016	2008/0021556	A1 *	1/2008	Edie	A61F 2/44
9,480,574	B2	11/2016					623/17.11
9,480,576	B2	11/2016	2008/0021559	A1	1/2008	Thramann	
9,545,316	B2	1/2017	2008/0147193	A1	6/2008	Matthis	
9,561,116	B2	2/2017	2008/0154263	A1 *	6/2008	Janowski	A61F 2/442
9,566,168	B2	2/2017					623/17.16
9,597,200	B2	3/2017	2008/0234687	A1	9/2008	Schaller	
9,636,154	B2	5/2017	2008/0281346	A1	11/2008	Greenhalgh	
9,655,744	B1	5/2017	2008/0281424	A1	11/2008	Parry et al.	
9,662,224	B2	5/2017	2009/0018524	A1	1/2009	Greenhalgh	
9,675,466	B2	6/2017	2009/0076607	A1	3/2009	Aalsma et al.	
9,675,469	B2	6/2017	2009/0138083	A1	5/2009	Biyani	
9,717,601	B2	8/2017	2009/0222043	A1	9/2009	Altarac	
9,730,803	B2	8/2017	2009/0234389	A1	9/2009	Chuang	
9,737,411	B2	8/2017	2009/0281551	A1	11/2009	Frey	
9,795,493	B1	10/2017	2010/0010542	A1	1/2010	Jackson	
9,801,640	B2	10/2017	2010/0010633	A1	1/2010	Kohm	
9,801,733	B2	10/2017	2010/0042218	A1	2/2010	Nebosky et al.	
9,801,734	B1	10/2017	2010/0082109	A1	4/2010	Greenhalgh et al.	
9,839,528	B2	12/2017	2010/0198352	A1	8/2010	Edie	
9,883,953	B1	2/2018	2010/0217325	A1	8/2010	Hochschuler	
9,889,019	B2	2/2018	2010/0222884	A1	9/2010	Greenhalgh	
9,907,673	B2	3/2018	2010/0234956	A1	9/2010	Attia	
9,913,727	B2	3/2018	2010/0286783	A1 *	11/2010	Lechmann	A61F 2/4455
9,913,736	B2	3/2018					623/17.11
9,974,662	B2	5/2018	2010/0292796	A1	11/2010	Greenhalgh	
9,987,143	B2	6/2018	2011/0022090	A1	1/2011	Gordon	
9,999,517	B2	6/2018	2011/0029082	A1	2/2011	Hall	
10,052,215	B2	8/2018	2011/0046748	A1	2/2011	Martin	
10,058,350	B2	8/2018	2011/0130835	A1	6/2011	Ashley	
10,080,592	B2	9/2018	2011/0172774	A1	7/2011	Varela	
10,085,849	B2	10/2018	2011/0190816	A1	8/2011	Sheffer	
10,098,757	B2	10/2018	2011/0282453	A1	11/2011	Greenhalgh	
10,105,238	B2	10/2018	2011/0301712	A1	12/2011	Palmatier	
10,137,007	B2	11/2018	2011/0319997	A1	12/2011	Glerum	
10,143,565	B2	12/2018	2012/0029636	A1	2/2012	Ragab	
10,143,569	B2	12/2018	2012/0029645	A1	2/2012	Fabian et al.	
10,149,773	B2	12/2018	2012/0035729	A1	2/2012	Glerum et al.	
10,154,911	B2	12/2018	2012/0046748	A1	2/2012	Weiman	
10,182,851	B2	1/2019	2012/0083889	A1	4/2012	Purcell	
10,206,788	B2	2/2019	2012/0089185	A1	4/2012	Gabelberger	
10,226,356	B2	3/2019	2012/0109319	A1	5/2012	Perisic	
10,226,360	B2	3/2019	2012/0136442	A1 *	5/2012	Kleiner	A61F 2/4455
10,238,503	B2	3/2019					623/17.11
10,251,759	B2	4/2019	2012/0209386	A1	8/2012	Triplett et al.	
10,265,192	B2	4/2019	2012/0271396	A1	10/2012	Zheng	
10,322,014	B2	6/2019	2012/0290090	A1	11/2012	Glerum et al.	
10,342,675	B2	7/2019	2012/0303126	A1	11/2012	Kirschman	
10,383,743	B2	8/2019	2013/0023996	A1	1/2013	McCormack	
10,413,419	B2	9/2019	2013/0184822	A1	7/2013	Kleiner	
10,426,634	B1	10/2019	2014/0039625	A1	2/2014	To	
10,441,430	B2	10/2019	2014/0243981	A1	8/2014	Davenport et al.	
10,470,891	B2	11/2019	2015/0100128	A1	4/2015	Glerum et al.	
10,470,894	B2	11/2019	2015/0148908	A1	5/2015	Marino et al.	
10,485,675	B2	11/2019	2015/0190242	A1	7/2015	Blain et al.	
10,492,918	B2	12/2019	2015/0374508	A1	12/2015	Sandul	
10,531,964	B2	1/2020	2016/0015530	A1	1/2016	To	
10,624,756	B2	4/2020	2016/0256291	A1	9/2016	Miller	
10,631,996	B2	4/2020	2016/0317315	A1	11/2016	Weiman	
10,682,239	B2	6/2020	2016/0338854	A1	11/2016	Serhan et al.	
10,687,876	B2	6/2020	2017/0119540	A1	5/2017	Greenhalgh	

(56)

References Cited

U.S. PATENT DOCUMENTS

2017/0209282	A1	7/2017	Aghayev et al.
2017/0224504	A1	8/2017	Butler et al.
2017/0224505	A1	8/2017	Butler et al.
2017/0231780	A1	8/2017	D'urso
2017/0239063	A1	8/2017	Predick
2017/0281358	A1	10/2017	Wagner et al.
2017/0333198	A1	11/2017	Robinson
2017/0333203	A1	11/2017	Glerum
2017/0354512	A1	12/2017	Weiman et al.
2018/0042735	A1	2/2018	Schell et al.
2018/0185163	A1	7/2018	Weiman et al.
2018/0193164	A1	7/2018	Shoshtaev
2018/0214221	A1	8/2018	Crawford et al.
2018/0256357	A1	9/2018	To
2018/0296361	A1	10/2018	Butler et al.
2018/0303626	A1	10/2018	Rogers et al.
2018/0360489	A1	12/2018	Geist
2018/0360617	A1	12/2018	Fabian et al.
2019/0053913	A1	2/2019	To
2019/0060085	A1	2/2019	Geist
2019/0076263	A1	3/2019	Emstad
2019/0091033	A1	3/2019	Dewey et al.
2019/0099278	A1	4/2019	Farris et al.
2019/0110900	A1	4/2019	Suddaby
2019/0110902	A1	4/2019	Vigliotti et al.
2019/0117409	A1	4/2019	Shoshtaev
2019/0117827	A1	4/2019	Roth
2019/0201209	A1	7/2019	Branch et al.
2019/0209339	A1	7/2019	To
2019/0240039	A1	8/2019	Walker et al.
2019/0254836	A1	8/2019	Cowan et al.
2019/0254841	A1	8/2019	To
2019/0269521	A1	9/2019	Shoshtaev
2019/0290448	A1	9/2019	Predick et al.
2019/0307573	A1	10/2019	Sicotte et al.
2019/0328544	A1	10/2019	Ashley et al.
2019/0336299	A1	11/2019	Bernard et al.
2020/0000607	A1	1/2020	To
2020/0015985	A1	1/2020	Rogers et al.
2020/0030110	A1	1/2020	Sharabani et al.
2020/0093609	A1	3/2020	Shoshtaev
2020/0113706	A1	4/2020	Robinson
2020/0129307	A1	4/2020	Hunziker et al.
2020/0229939	A1	7/2020	To
2020/0352732	A1	11/2020	To
2021/0045893	A1	2/2021	To
2021/0196470	A1	7/2021	Shoshtaev
2021/0330472	A1	10/2021	Shoshtaev

FOREIGN PATENT DOCUMENTS

EP	1011503	2/1998
EP	1233732	2/2001
EP	2327377	3/2002
EP	1532949	11/2003
EP	2237748	1/2009
JP	2009/505686	7/2005
WO	WO 1996/040015	6/1996
WO	WO 2000/044319	1/2000
WO	WO 2001/066047	7/2001
WO	WO 2005/112834	12/2005
WO	WO 2008/005627	5/2007
WO	WO 2007/076374	7/2007
WO	WO 2008/035849	7/2007
WO	WO 2008/033457	3/2008
WO	WO 2008/089252	7/2008
WO	WO 2008/121162	10/2008
WO	WO 2010/077359	7/2010
WO	WO 2012/135764	10/2012
WO	WO 2013/148176	10/2013
WO	WO 2014/164625	10/2014
WO	WO 2016/019241	2/2016
WO	WO 2017/004503	1/2017
WO	WO 2017/035155	3/2017

OTHER PUBLICATIONS

U.S. Appl. No. 17/546,816, filed Jul. 24, 2017, To—owned by Applicant.

U.S. Appl. No. 60/666,945 (priority for U.S. Pat. No. 7,731,751, cited herein), filed Mar. 31, 2005, Butler, et al.

U.S. Appl. No. 61/585,724 (priority for U.S. Pat. No. 9,463,052, cited herein), filed Jan. 12, 2012, Geist—owned by Applicant.

U.S. Appl. No. 61/737,054, filed Dec. 15, 2013, To—owned by Applicant.

U.S. Appl. No. 61/875,688, filed Oct. 4, 2013, To—owned by Applicant.

U.S. Appl. No. 62/232,021 (priority for U.S. Pat. No. 10,058,350, cited herein), filed Sep. 24, 2015, Geist—owned by Applicant.

U.S. Appl. No. 62/444,663 (priority for U.S. 2018/0193164, cited herein), filed Jan. 10, 2017, Shoshtaev—owned by Applicant.

U.S. Appl. No. 62/471,206 (priority for U.S. 2018/0193164, cited herein), filed Jan. 10, 2017, Shoshtaev—owned by Applicant.

U.S. Appl. No. 62/481,565 (priority for U.S. 2018/0193164, cited herein), filed Jan. 10, 2017, Shoshtaev—owned by Applicant.

U.S. Appl. No. 62/536,335 (priority for PCT/US2018/43517, cited herein), filed Jul. 24, 2017, To—owned by Applicant.

U.S. Appl. No. 62/550,557 (priority for U.S. Appl. No. 16/113,040, cited herein), filed Aug. 25, 2017, Geist—owned by Applicant.

PCT/US2013/052799, To—owned by Applicant, Jul. 31, 2012.

Written opinion and search report for PCT/US2013/052799, To—owned by Applicant, Dec. 2, 2012.

PCT/US2013/073435 Published as WO 2014/093136, To—owned by Applicant, Dec. 5, 2013.

Written opinion and search report for PCT/US2013/073435, To—owned by Applicant, Apr. 30, 2012.

PCT/US2014/054437, To—owned by Applicant, Feb. 26, 2014.

Written opinion and search report for PCT/US2014/054437, To—owned by Applicant, Jan. 6, 2015.

PCT/US2016/014100, To—owned by Applicant, Dec. 17, 2015.

Written opinion and search report for PCT/US2016/014100, To—owned by Applicant, Jan. 6, 2015.

PCT/US2017/52708, To—owned by Applicant, Sep. 21, 2017.

Written opinion and search report for PCT/US2017/52708, To—owned by Applicant, Sep. 21, 2017.

PCT/US2016/053467 Published as WO 2017/053813, Geist—owned by Applicant, Sep. 24, 2015.

Written opinion and search report for PCT/US2016/053467, Geist—owned by Applicant, Sep. 24, 2015.

PCT/US2018/13207 Published as WO 2018/132502, Shoshtaev—owned by Applicant, Jan. 10, 2018.

Written opinion and search report for PCT/US2018/13207, Shoshtaev—owned by Applicant, Jan. 10, 2018.

PCT/US2018/43517, To—owned by Applicant, Jul. 24, 2018.

Written opinion and search report for PCT/US2018/43517, To—owned by Applicant, Jul. 24, 2018.

PCT/US2019/20354, Shoshtaev—owned by Applicant, Mar. 1, 2018.

Written opinion and search report for PCT/US2019/20354, Shoshtaev—owned by Applicant, Mar. 1, 2018.

PCT/US2021/42392, Shoshtaev—owned by Applicant, Jul. 20, 2020.

Written opinion and search report for PCT/US2021/42392, Shoshtaev—owned by Applicant, Jul. 20, 2020.

European search report for EP 13862126, Dec. 5, 2013, To—owned by Applicant.

European search report for EP 14842880, Jun. 22, 2016, To—owned by Applicant.

European search report for EP 16740662, Nov. 29, 2017, To—owned by Applicant.

European search report for EP 17853887.2, Jul. 31, 2019, To—owned by Applicant.

European search report for EP 18738659.4, Jan. 10, 2018, Shoshtaev—owned by Applicant.

European search report for EP 19162909.6, Dec. 5, 2013, To—owned by Applicant.

European search report for EP 19760773.2, Dec. 2, 2020, Shoshtaev—owned by Applicant.

(56)

References Cited**OTHER PUBLICATIONS**

Basho, R. et al. Lateral interbody fusion: Indications and techniques. *Operative techniques in orthopaedics* 21(3): 204-207 (Sep. 2011).

Caliber. [www.globusmedical.com \[online\] URL: http://www.globusmedical.com/mis/166-caliber](http://www.globusmedical.com/mis/166-caliber) [retrieved on Jul. 27, 2012].

Cole, D. et al. Comparison of low back fusion techniques: transforaminal lumbar interbody fusion (TLIF) or posterior lumbar interbody fusion (PLIF) approaches. *Curr rev Musculoskelet med* 2(2): 118-126 published online Apr. 29, 2009 Doi: 1007/s12178-009-9053-B10 [retrieved Jun. 2009].

Capstone® PEEK spinal system PLIF and TLIF surgical technique. Medtronic Sofamor Danek 1-36 (2009).

Coalign. Introducing AccuLIF expandable lumbar interbody fusion technology. [online] URL: <http://www.coalign.com> [retrieved on Jul. 27, 2012].

Chapman, C. A. Design of an expandable intervertebral cage utilizing shape memory alloys. University of Toledo and OhioLINK, 2011. [online] URL: http://etd.ohiolink.edu/view.cgi?acc_num=toledo1302226375 [retrieved Feb. 13, 2013].

Dorso-Lumbar Vertebral Body Cages DSC, Sintea Plustek. [online] URL: http://www.sintea-plustek.com/spine_dsc_eng.html [retrieved on Feb. 13, 2013].

"Integrity Implants" (Integrity Implants) URL: <http://www.integrityimplants.com/> [retrieved from internet Sep. 17, 2018].

"Integrity Implants v3" (Integrity Implants) URL: <https://vimeo.com/232697959> ; [retrieved from the internet Nov. 16, 2017].

Interbody Fusion Cage (Neo IC) Source, www.tradekorea.com [online] URL: http://www.tradekorea.com/product-detail/P00015150/Interbody_Fusion_Cage_Neo_IC_.html [retrieved Feb. 13, 2013].

Kaech, D.L. et al. Spinal restabilization procedures, diagnostic and therapeutic aspects of intervertebral fusion cages, artificial discs and mobile implants. Elsevier Science B.V. Part II: 121-204(2002).

Kiapour, A. et al. A biomechanical finite element study of subsidence and migration tendencies in stand-alone fusion procedures—comparison of an in situ expandable device with a rigid device. *J Spine* 1(4): 5 pages (2012).

Le Huec, J.C. et al. Endoscope surgery of the spine, a review of 4 years? *Practice, maîtrise orthopédique*. Jan. 1999 [online] URL: http://www.maitrise-orthop.com/viewPage_us.do?id=435 [retrieved on Feb. 5, 2013].

Powerbuilt. Powerbuilt 940378 medium tailpipe expander set. [online] URL: <http://www.amazon.com/Powerbuilt-940377-Tailpipe-Expander-Series/dp/B004KED6A> [retrieved on Feb. 17, 2013].

PR Newswire. Benvenue Medical starts enrolling patients in the post-market lift study on the luna interbody spacer system for degenerative disc disease. Mar. 20, 2012, [online] URL: <http://www.prnewswire.com/news-releases/benvenue-medical-starts-enrolling-patients-in-the-post-market-lift-study-on-the-luna-interbody-spacer-system-for-degenerative-disc-disease-143441246.html> [retrieved on Jan. 27, 2013].

Sasani, M. et al. Single-stage posterior corpectomy and expandable cage placement for treatment of thoracic or lumbar burst fractures. *Spine* 34(1): E33-E40 (Jan. 1, 2009).

Spineology. OptiMesh 1500E deploying grafting system. [online] URL: http://www.spineology.com/fb/intl/products/products/optimesh_1500e.html (retrieved Jun. 3, 2013).

Staxx XD, www.spinewave.com. [online] URL: http://www.spinewave.com/products/xd_us.html [retrieved on Jan. 27, 2013].

Synfix-LR System. Instruments and implants for stand-alone anterior lumbar interbody fusion (ALIF). Synthes SynFix-LR system technique guide 52 pages (2010).

Transforaminal Lumbar Interbody Fusion (TLIF). Virginia spine institute, Reston Virginia. [online] URL: <http://www.spinemd.com/operative-treatments/tlif-transforaminal-lumbar-interbody-fusion.com> 1-6 (2013). [retrieved on Jun. 16, 2013].

Uchida, K. et al. Anterior expandable strut cage replacement for osteoporotic thoracolumbar vertebral collapse. *J Neurosurg Spine* 4(6): 454-462 (Jun. 2006).

Xenos. Cage mesh system for spine. Biotek Chetan Meditech Pvt. Ltd. [online] URL: <http://www.biotekortho.net/spine-treatment.html> [retrieved on Feb. 13, 2013].

Zeus-O, [online] URL: <http://www.amendia.com/zeuso.html> [retrieved on Jan. 27, 2013].

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 1D







FIG. 1E








FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 2E




FIG. 2F




FIG. 3A

FIG. 3B




FIG. 3C

FIG. 3D




FIG. 4A








FIG. 4B






FIG. 6




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D




FIG. 7E














FIG. 7F










FIG. 11A




FIG. 11B




FIG. 12A




FIG. 12B




FIG. 12C




FIG. 13A




FIG. 13B




FIG. 13C




FIG. 13D

1

DISTRIBUTING GRAFT MATERIAL FROM AN EXPANDABLE CAGE

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 16/444,888, filed Jun. 18, 2019, which is a continuation of U.S. patent application Ser. No. 16/169,049, filed Oct. 24, 2018, now U.S. Pat. No. 10,786,366, which is a continuation of U.S. patent application Ser. No. 15/091,535, filed Apr. 5, 2016, now U.S. Pat. No. 10,149,773, which is a continuation of U.S. patent application Ser. No. 14/157,504, filed Jan. 16, 2014, now U.S. Pat. No. 9,333,092, which is a continuation of U.S. patent application Ser. No. 13/815,787, filed Mar. 15, 2013, now U.S. Pat. No. 8,663,332, which claims the benefit of U.S. Provisional Application No. 61/737,054, filed Dec. 13, 2012, each of which is hereby incorporated herein by reference in its entirety.

BACKGROUND

Field of the Invention

The teachings herein are directed to a system for distributing bone graft material in an intervertebral disc space.

Description of the Related Art

Bone grafts are used in spinal fusion, for example, which is a technique used to stabilize the spinal bones, or vertebrae, and a goal is to create a solid bridge of bone between two or more vertebrae. The fusion process includes “arthrodesis”, which can be thought of as the mending or welding together of two bones in a spinal joint space, much like a broken arm or leg healing in a cast. Spinal fusion may be recommended for a variety of conditions that might include, for example, a spondylolisthesis, a degenerative disc disease, a recurrent disc herniation, or perhaps to correct a prior surgery.

Bone graft material is introduced for fusion and a fusion cage can be inserted to help support the disc space during the fusion process. In fact, fusion cages are frequently used in such procedures to support and stabilize the disc space until bone graft unites the bone of the opposing vertebral endplates in the disc space. A transforaminal lumbar interbody fusion (TLIF), for example, involves placement of posterior instrumentation (screws and rods) into the spine, and the fusion cage loaded with bone graft can be inserted into the disc space. Bone graft material can be pre-packed in the disc space or packed after the cage is inserted. TLIF can be used to facilitate stability in the front and back parts of the lumbar spine promoting interbody fusion in the anterior portion of the spine. Fusion in this region can be beneficial, because the anterior interbody space includes an increased area for bone to heal, as well as to handle increased forces that are distributed through this area.

Unfortunately, therein lies a problem solved by the teachings provided herein. Currently available systems can be problematic in that the methods of introducing the fusion cage and bone graft material leaves pockets in regions of the intervertebral space that are not filled with bone graft material, regions in which fusion is desired for structural support. These pockets can create a premature failure of the fused intervertebral space due to forces that are distributed through the regions containing the pockets, for example, when the patient stands and walks.

2

Traditional fusion cages, such as the Medtronic CAPSTONE cage, are designed to be oversized relative to the disc space to distract the disc space as the entire cage is inserted. However, this makes it difficult to insert and position properly. In response to the problem, the art has developed a number of new fusion cages, such as the Globus CALIBER cage which can be inserted at a low height and expanded vertically to distract the disc space. Unfortunately, these types of devices have the typical graft distribution problem discussed above, in that they do not provide a path for bone graft to be inserted and fill in the space surrounding the cage or within the cage. They have other problems as well, including that the annulotomy must be large to accommodate a large enough cage for stability, and this large opening necessitates more trauma to the patient. Moreover, they can also create the additional problem of “backout”, in that they cannot expand laterally beyond the annulotomy to increase the lateral footprint of the cage relative to lateral dimension of the annulotomy. Since it takes several months for the fusion to occur to completion in a patient, the devices have plenty of time to work their way out of the space through the large annulotomy.

Accordingly, and for at least the above reasons, those of skill in the art will appreciate bone graft distribution systems that facilitate an improved distribution of graft material throughout the intervertebral space. Such systems are provided herein, the systems configured to (i) effectively distribute bone graft material both from the system, and around the system, to improve the strength and integrity of a fusion; (ii) reduce or eliminate the problem of failures resulting from a poor bone graft distribution; (iii) have a small maximum dimension in a collapsed state for a low-profile insertion into the annulus in a minimally-invasive manner, whether using only a unilateral approach or a bilateral approach; (iv) laterally expand within the intervertebral space to avoid backout of the system through the annulotomy; (v) vertically expand for distraction of the intervertebral space; and, (vi) provide an expansion in the intervertebral space without contracting the system in length to maintain a large footprint and an anterior position adjacent to the inner, anterior annulus wall, distributing load over a larger area, anteriorly, against the endplates.

SUMMARY

The teachings herein are generally directed to a system for distributing bone graft material in an intervertebral disc space. The graft distribution systems can have, for example, a central beam having a proximal portion having an end, a grafting portion having a top and a bottom, a distal portion having an end, a central beam axis, a graft distribution channel having an entry port at the end of the proximal portion, a top exit port at the top of the grafting portion, and a bottom exit port at the bottom of the grafting portion. These systems can also include a laterovertically-expanding frame having a lumen, a first top beam, a second top beam, a first bottom beam, and a second bottom beam, each having a proximal portion and a distal portion, and each operably connected to each other at their respective proximal portions and distal portions with connector elements to form the laterovertically-expanding frame that is operable for a reversible collapse from an expanded state into a collapsed state. The expanded state, for example, can be configured to have an open graft distribution window that at least substantially closes upon the reversible collapse. In these embodiments, the laterovertically-expanding frame is

adapted for receiving an insertion of the central beam to form the graft distribution system.

In some embodiments, the graft distribution systems can have a central beam with a central beam axis, a graft distribution channel with an entry port in fluid communication with a top exit port, and a bottom exit port. The central beam can also have a proximal portion having an end with the entry port, a grafting portion having the top exit port and the bottom exit port, and a distal portion. The central beam can also be sized to have a transverse cross-section having a maximum dimension ranging from 5 mm to 15 mm for placing the central beam into an intervertebral space through an annular opening having a maximum lateral dimension ranging from 5 mm to 15 mm, the intervertebral space having a top vertebral plate and a bottom vertebral plate. The central beam can also have a top surface with a first top-lateral surface and a second top-lateral surface, a bottom surface with a first bottom-lateral surface and a second bottom-lateral surface, a first side surface with a first top-side surface and a first bottom-side surface, and a second side surface with a second top-side surface and a second bottom-side surface.

The graft distribution system can also comprise a laterovertically-expanding frame configured for operably contacting the central beam to create a graft distribution system in vivo, the frame having a collapsed state with a transverse cross section having a maximum dimension ranging from 5 mm to 15 mm for placing the frame in the intervertebral space through the annular opening for expansion. Likewise, the frame can also have an expanded state with a transverse cross section having a maximum dimension ranging from 6.5 mm to 18 mm for retaining the frame in the intervertebral space, the expanded state operably contacting with the central beam in the intervertebral space. The frame can be defined as including a proximal portion having an end, a grafting portion, a distal portion having an end, and a central frame axis of the expanded state.

The frame can be configured to have a first top beam including a proximal portion having an end, a grafting portion, and a distal portion having an end, the first top beam configured for contacting the first top-lateral surface of the central beam and the first top-side surface of the central beam in the expanded state, the central axis of the first top beam at least substantially on (i) a top plane containing the central axis of the first top beam and the central axis of a second top beam and (ii) a first side plane containing the central axis of the first top beam and the central axis of a first bottom beam. Likewise, the frame can be configured to have a second top beam including a proximal portion having an end, a grafting portion having an end, and a distal portion (not shown) having an end, the second top beam configured for contacting the second top-lateral surface of the central beam and the second top-side surface of the central beam in the expanded state, the central axis of the second top beam at least substantially on (i) the top plane and (ii) a second side plane containing the central axis of the second top beam and the central axis of a second bottom beam. Likewise, the frame can be configured to have a first bottom beam including a proximal portion having an end, a grafting portion, and a distal portion having an end, the first bottom beam configured for contacting the first bottom-lateral surface of the central beam and the first bottom-side surface of the central beam in the expanded state, the central axis of the first bottom beam at least substantially on (i) a bottom plane containing the central axis of the first bottom beam and the central axis of a second top beam and (ii) the first side plane. Likewise, the frame can be configured to have a second

bottom beam including a proximal portion having an end, a grafting portion having an end, and a distal region having an end, the second bottom beam configured for contacting the second bottom-lateral surface of the central beam and the second bottom-side surface of the central beam in the expanded state, the central axis of the second bottom beam being at least substantially on (i) the bottom plane and (ii) a second side plane containing the central axis of the second bottom beam and the second top beam.

The beams of the laterovertically-expanding frame can be operably connected through connector elements. As such, the frame can include a plurality of proximal top connector elements configured to expandably connect the proximal portion of the first top beam to the proximal portion of the second top beam, the expanding consisting of a flexing at least substantially on a top plane containing the central axis of the first top beam and the central axis of the second top beam. Likewise the frame can be configured to have a plurality of distal top connector elements configured to expandably connect the distal portion of the first top beam to the distal portion of the second top beam, the expanding consisting of a flexing at least substantially on the top plane.

Likewise, the frame can be configured to have a plurality of proximal bottom connector elements configured to expandably connect the proximal portion of the first bottom beam to the proximal portion of the second bottom beam, the expanding consisting of a flexing at least substantially on a bottom plane containing the central axis of the first bottom beam and the central axis of the second bottom beam. Likewise, the frame can be configured to have a plurality of distal bottom connector elements configured to expandably connect the distal portion of the first bottom beam to the distal portion of the second bottom beam, the expanding consisting of a flexing at least substantially on the bottom plane.

Likewise, the frame can be configured to have a plurality of proximal first side connector elements configured to expandably connect the proximal portion of the first top beam to the proximal portion of the first bottom beam, the expanding consisting of a flexing at least substantially on a first side plane containing the central axis of the first top beam and the central axis of the first bottom beam; a plurality of distal first side connector elements (not shown) configured to expandably connect the distal portion of the first top beam to the distal portion of the first bottom beam, the expanding consisting of a flexing at least substantially on the first side plane. Likewise the frame can be configured to have a plurality of proximal second side connector elements configured to expandably connect the proximal portion of the second top beam to the proximal portion of the second bottom beam, the expanding consisting of a flexing at least substantially on a second side plane containing the central axis of the second top beam and the central axis of the second bottom beam; a plurality of distal second side connector elements configured to expandably connect the distal portion of the second top beam to the distal portion of the second bottom beam, the expanding consisting of a flexing at least substantially on the second side plane;

The frame can be configured for slidably engaging with the central beam in vivo following placement of the central beam in the intervertebral space through the annular opening, the slidably engaging including translating the central beam into the frame from the proximal end of the frame toward the distal end of the frame in vivo; the translating including keeping the central beam axis at least substantially coincident with the central frame axis during the translating to create the graft distribution system in vivo through the

5

annular opening. The graft distribution system can also be configured to form a top graft-slab depth between the top surface of the central beam and the top vertebral endplate; and, a bottom graft-slab depth between the bottom surface of the central beam and the bottom vertebral endplate in vivo. And, in some embodiments, the transverse cross-section of the graft distribution system in vivo is greater than the maximum lateral dimension of the annular opening to avoid backout.

The distal end of the frame can be configured to have a laterovertically operable connection with a guide plate connectable to the guidewire that restricts the first top beam, the first bottom beam, the second top beam, and the second bottom beam to laterovertical movement relative to the guide plate and the guidewire when converting the frame from the collapsed state to the expanded state in vivo. And, in some embodiments, the laterovertically-expandable frame has a lumen, and the guide plate has a luminal side with connector for reversibly receiving a guide wire for inserting the laterovertically-expandable frame into the intervertebral space.

One of skill will appreciate that the central beam can have any configuration that would be operable with the teachings provided herein. In some embodiments, criteria for a suitable central beam may include a combination of a material and configuration that provides a suitable stiffness. In some embodiments, the central beam can comprise an I-beam.

One of skill will further appreciate that the central beam can have any one or any combination of graft port configurations that would be operable with the teachings provided herein. In some embodiments, criteria for a suitable graft port configuration may include a combination of port size, number of ports, and placement of ports. In some embodiments, the central beam can comprise a side graft port.

One of skill will further appreciate that the connector elements can vary in design but should meet the constraints as taught herein. In some embodiments, for example each of the connector elements can have a cross-sectional aspect ratio of longitudinal thickness to transverse thickness ranging from 1:2 to 1:8.

In some embodiments, each of the plurality of proximal connector elements are proximal struts configured in an at least substantially parallel alignment in the expanded state; and, each of the distal connector elements are distal struts configured in an at least substantially parallel alignment in the expanded state. Likewise, in some embodiments, each of the plurality of proximal connector elements are proximal struts configured in an at least substantially parallel alignment in the collapsed state; and, each of the distal connector elements are distal struts configured in an at least substantially parallel alignment in the collapsed state. Moreover, in some embodiments, each of the plurality of proximal connector elements are proximal struts configured in an at least substantially parallel alignment in the expanded state and the collapsed state; and, each of the distal connector elements are distal struts configured in an at least substantially parallel alignment in the expanded state and the collapsed state.

In some embodiments, each plurality of proximal top connector elements and proximal bottom connector elements are proximal struts configured in an at least substantially parallel alignment in the expanded state and the collapsed state; and, each plurality of distal top connector elements and distal bottom connector elements are distal struts configured in an at least substantially parallel alignment in the expanded state and the collapsed state. In some embodiments, the proximal top struts are configured monolithically integral to the first top beam and the second top

6

beam and adapted to flex toward the distal top struts during collapse; and, the distal top struts are configured monolithically integral to the first top beam and the second top beam and adapted to flex toward the proximal top struts during collapse. Likewise, in some embodiments, the proximal bottom struts are configured monolithically integral to the first bottom beam and the second bottom beam and adapted to flex toward the distal bottom struts during collapse; and, the distal bottom struts are configured monolithically integral to the first bottom beam and the second bottom beam and adapted to flex toward the proximal bottom struts during collapse. And, in these embodiments, the top and bottom of the laterovertically-expanding frame are each configured to open a graft distribution window upon expansion to facilitate graft distribution within the intervertebral space.

In some embodiments, the central beam further comprises a first side graft port and a second side graft port. In these embodiments, each plurality of proximal connector elements can be configured as proximal struts in an at least substantially parallel alignment in the expanded state and the collapsed state; and, each plurality distal connector elements are distal struts can be configured in an at least substantially parallel alignment in the expanded state and the collapsed state. As such, the proximal top struts can be configured monolithically integral to the first top beam and the second top beam and adapted to flex toward the distal top struts during collapse; and, the distal top struts can be configured monolithically integral to the first top beam and the second top beam and adapted to flex toward the proximal top struts during collapse. Likewise, the proximal bottom struts can be configured monolithically integral to the first bottom beam and the second bottom beam and adapted to flex toward the distal bottom struts during collapse; and, the distal bottom struts can be configured monolithically integral to the first bottom beam and the second bottom beam and adapted to flex toward the proximal bottom struts during collapse. Likewise, the proximal first side struts can be configured monolithically integral to the first top beam and the first bottom beam and adapted to flex toward the distal first side struts during collapse; and, the distal first side struts can be configured monolithically integral to the first top beam and the first bottom beam and adapted to flex toward the proximal first side struts during collapse. Likewise, the proximal second side struts can be configured monolithically integral to the second top beam and the second bottom beam and adapted to flex toward the distal second side struts during collapse; and, the distal second side struts can be configured monolithically integral to the second top beam and the second bottom beam and adapted to flex toward the proximal second side struts during collapse. As such, in some embodiments, the top, bottom, first side, and second side of the laterovertically-expanding frame can be configured to form a monolithically integral frame, each adapted to open a graft distribution window **188** upon expansion to facilitate graft distribution within the intervertebral space.

The teachings are also directed to a method of fusing an intervertebral space using any of the graft distribution systems taught herein. The methods can include creating a single point of entry into an intervertebral disc, the intervertebral disc having a nucleus pulposus surrounded by an annulus fibrosis, and the single point of entry having the maximum lateral dimension created through the annulus fibrosis. The methods can also include removing the nucleus pulposus from within the intervertebral disc through the single point of entry, leaving the intervertebral space for expansion of the graft distribution system within the annulus fibrosis, the intervertebral space having the top vertebral

plate and the bottom vertebral plate. The methods can also include inserting the laterover vertically expanding frame in the collapsed state through the single point of entry into the intervertebral space; and, inserting the central beam into the frame to form the graft distribution system. Moreover, the methods can also include adding a grafting material to the intervertebral space through the entry port.

The bone graft distribution systems provided herein include bone graft windows defined by the connector elements, the bone graft windows opening upon expansion of the laterover vertically expanding frame. In some embodiments, the method further comprises opening a bone graft window, wherein the connector elements include v-shaped struts that (i) stack either proximally or distally in a closed-complementary configuration in the collapsed state to minimize void space for a low profile entry of the system both vertically and laterally into the intervertebral space, and (ii) deflect upon expansion to open the bone graft window.

The bone graft distribution systems provided herein also allow for independent expansion laterally and vertically by expanding in steps. In some embodiments, the expanding includes selecting an amount of lateral expansion independent of an amount of vertical expansion. And, in some embodiments, the lateral expansion exceeds the width of the annular opening that is the single point of entry into the intervertebral space. For example, the lateral dimension of the single point of entry can range from about 5 mm to about 15 mm in some embodiments. As such, in some embodiments, the expanding includes expanding the laterover vertically expanding frame laterally to a width that exceeds the width of the single point of entry; and, inserting the central beam to expand the laterover vertically expanding frame vertically to create the graft distribution system.

The bone graft distribution systems provided herein also have means for retaining the central beam in the laterover vertically expanding frame. In some embodiments, the inserting of the central beam into the laterover vertically expanding frame includes engaging a ratchet mechanism comprising a protuberance on the central beam that engages with the laterover vertically-expanding frame to prevent the central beam from backing out of the laterover vertically-expanding frame after the expanding.

The bone graft distribution systems provided here can be in the form of a kit. The kits can include, for example, a graft distribution system taught herein, a cannula for inserting the graft distribution system into the intervertebral space, a guidewire adapted for guiding the central beam into the laterover vertically expanding frame, and an expansion handle for inserting the central beam into the laterover vertically expanding frame to form the graft distribution system.

BRIEF DESCRIPTION OF THE FIGURES

FIGS. 1A-1I illustrate components of the graft distribution system, according to some embodiments.

FIGS. 2A-2F illustrate a method of using a bidirectionally-expandable cage, according to some embodiments.

FIGS. 3A-3D illustrate a bidirectionally-expandable cage for fusing an intervertebral disc space, according to some embodiments.

FIGS. 4A and 4B illustrate collapsed and expanded views of a bidirectionally-expandable cage having a bone graft window on each wall for fusing an intervertebral disc space, according to some embodiments.

FIGS. 5A-5D illustrate system for fusing an intervertebral disc space, according to some embodiments.

FIG. 6 is a diagram of a method of using a bidirectionally-expandable cage, according to some embodiments.

FIGS. 7A-7F illustrate some additional features of graft distribution systems, according to some embodiments.

FIGS. 8A-8D illustrate components of a graft distribution kit, according to some embodiments.

FIGS. 9A-9C illustrate the expansion of a laterover vertically-expandable frame in an intervertebral space, according to some embodiments.

FIGS. 10A-10C illustrate profiles of an expanded graft distribution system to highlight the exit ports and bone graft windows, according to some embodiments.

FIGS. 11A and 11B compare an illustration of the graft distribution in place to a test placement in a cadaver to show relative size, according to some embodiments.

FIGS. 12A-12C show x-rays of a placement in a cadaver, according to some embodiments.

FIGS. 13A-13D show orientations of the first top beam relative to the second top beam, first bottom beam relative to the second bottom beam, first top beam relative to the first bottom beam, and the second top beam relative to the second bottom beam, according to some embodiments.

DETAILED DESCRIPTION OF THE INVENTION

The teachings herein are generally directed to a system for distributing bone graft material in an intervertebral disc space. The graft distribution systems can have, for example, a central beam having a proximal portion having an end, a grafting portion having a top and a bottom, a distal portion having an end, a central beam axis, a graft distribution channel having an entry port at the end of the proximal portion, a top exit port at the top of the grafting portion, and a bottom exit port at the bottom of the grafting portion. These systems can also include a laterover vertically-expanding frame having a lumen, a first top beam, a second top beam, a first bottom beam, and a second bottom beam, each having a proximal portion and a distal portion, and each operably connected to each other at their respective proximal portions and distal portions with connector elements to form the laterover vertically-expanding frame that is operable for a reversible collapse from an expanded state into a collapsed state. The expanded state, for example, can be configured to have an open graft distribution window that at least substantially closes upon the reversible collapse. In these embodiments, the laterover vertically-expanding frame is adapted for receiving an insertion of the central beam to form the graft distribution system.

In some embodiments, the graft distribution systems can also include a laterover vertically-expanding frame having a first top beam, a second top beam, a first bottom beam, and a second bottom beam; wherein, the beams are in an at least substantially parallel arrangement with each other, each having a proximal portion, a grafting portion, and a distal portion, and each operably connected to each other at their respective proximal portions and distal portions to form the laterover vertically-expanding frame in a square, cylindrical shape that is operable for a reversible collapse from an expanded state into a collapsed state. The expanded state, for example, can be configured to have an open graft distribution window that at least substantially closes upon the reversible collapse. In these embodiments, the laterover vertically-expanding frame is adapted for receiving an insertion of the central beam to form the graft distribution system.

The term "subject" and "patient" can be used interchangeably in some embodiments and refer to an animal such as a

mammal including, but not limited to, non-primates such as, for example, a cow, pig, horse, cat, dog; and primates such as, for example, a monkey or a human. As such, the terms “subject” and “patient” can also be applied to non-human biologic applications including, but not limited to, veterinary, companion animals, commercial livestock, and the like. Moreover, terms of degree are used herein to provide relative relationships between the position and/or movements of components of the systems taught herein. For example, the phrase “at least substantially parallel” is used to refer to a position of one component relative to another. An axis that is at least substantially parallel to another axis refers to an orientation that is intended, for all practical purposes to be parallel, but it is understood that this is just a convenient reference and that there can be variations due to stresses internal to the system and imperfections in the devices and systems. Likewise, the phrase “at least substantially on a . . . plane” refers to an orientation or movement that is intended, for all practical purposes to be on or near the plane as a convenient measure of the orientation or movement, but it is understood that this is just a convenient reference and that there can be variations due to stresses internal to the system and imperfections in the devices and systems. Likewise, the phrase “at least substantially coincident” refers to an orientation or movement that is intended, for all practical purposes to be on or near, for example, an axis or a plane as a convenient measure of the orientation or movement, but it is understood that this is just a convenient reference and that there can be variations due to stresses internal to the system and imperfections in the devices and systems.

FIGS. 1A-1I illustrate components of the graft distribution system, according to some embodiments. As shown in FIG. 1A, the graft distribution systems **100** can have a central beam **101** with a central beam axis **105**, a graft distribution channel with an entry port **135** in fluid communication with a top exit port **140**, and a bottom exit port **141**. The central beam **101** can also have a proximal portion **111** having an end with the entry port **135**, a grafting portion **112** having the top exit port **140** and the bottom exit port **141**, and a distal portion (not shown). The central beam **101** can also be sized to have a transverse cross-section **110** having a maximum dimension ranging from 5 mm to 15 mm for placing the central beam **101** into an intervertebral space through an annular opening having a maximum lateral dimension ranging from 5 mm to 15 mm, the intervertebral space having a top vertebral plate and a bottom vertebral plate. The central beam **101** can also have a top surface **115** with a first top-lateral surface **117** and a second top-lateral surface **119**, a bottom surface **120** with a first bottom-lateral surface **122** and a second bottom-lateral surface **124**, a first side surface **125** with a first top-side surface **127** and a first bottom-side surface **129**, and a second side surface **130** with a second top-side surface **132** and a second bottom-side surface **134**.

In some embodiments, the central beam can have transverse cross-sectional lateral dimension ranging from about 5 mm to about 15 mm. In some embodiments, the vertical dimension of the central beam can range from about 4 mm to about 12 mm, about 5 mm to about 11 mm, about 6 mm to about 10 mm, and about 7 mm to about 9 mm, about 6 mm to about 8 mm, about 6 mm, or any range or amount therein in increments of 1 mm. In some embodiments, the lateral dimension of the central beam can range from about 5 mm to about 15 mm, about 6 mm to about 14 mm, about 7 mm to about 13 mm, about 8 mm to about 12 mm, about 10 mm, or any range or amount therein in increments of 1 mm. In

some embodiments, transverse cross-section of the central beam has an area with an effective diameter ranging from about 2 mm to about 20 mm, from about 3 mm to about 18 mm, from about 4 mm to about 16 mm, from about 5 mm to about 14 mm, from about 6 mm to about 12 mm, from about 7 mm to about 10 mm, or any range therein. In some embodiments, the low profile has an area with a diameter of 2 mm, 4 mm, 6 mm, 8 mm, 10 mm, 12 mm, 14 mm, 16 mm, 18 mm, or any range therein, including any increment of 1 mm in any such diameter or range therein. In some embodiments, the width (mm)×height (mm) of the central beam can be 9.0×5.0, 9.0×6.0, 9.0×7.0, 9.0×8.0, 9.0×9.0, and 9.0×10.0, or any deviation in dimension therein in increments of +/−0.1 mm. And, in some embodiments, the central beam can have a transverse cross-sectional lateral or vertical dimension that ranges from 6.5 mm to 14.0 mm.

As shown in FIGS. 1B and 10, the graft distribution system **100** can also comprise a laterovertically-expanding frame **149** configured for operably contacting the central beam **101** to create a graft distribution system **100** in vivo, the frame **149** having a collapsed state **149c** with a transverse cross section **149ct** having a maximum dimension ranging from 5 mm to 15 mm for placing the frame **149** in the intervertebral space through the annular opening for expansion. Likewise, the frame **149** can also have an expanded state **149e** with a transverse cross section **149et** having a maximum dimension ranging from 6.5 mm to 18 mm for retaining the frame **149** in the intervertebral space, the expanded state operably contacting with the central beam **101** in the intervertebral space. The frame **149** can be defined as including a proximal portion **111** having an end, a grafting portion **112**, a distal portion (not shown) having an end, and a central frame axis **113** of the expanded state **149e**.

In some embodiments, the frame can have transverse cross-sectional lateral dimension in the collapsed state ranging from about 5 mm to about 15 mm. In some embodiments, the vertical dimension of the frame in the collapsed state can range from about 4 mm to about 12 mm, about 5 mm to about 11 mm, about 6 mm to about 10 mm, and about 7 mm to about 9 mm, about 6 mm to about 8 mm, about 6 mm, or any range or amount therein in increments of 1 mm. In some embodiments, the lateral dimension of the frame in the collapsed state can range from about 5 mm to about 15 mm, about 6 mm to about 14 mm, about 7 mm to about 13 mm, about 8 mm to about 12 mm, about 10 mm, or any range or amount therein in increments of 1 mm. In some embodiments, transverse cross-section of the frame in the collapsed state has an area with an effective diameter ranging from about 2 mm to about 20 mm, from about 3 mm to about 18 mm, from about 4 mm to about 16 mm, from about 5 mm to about 14 mm, from about 6 mm to about 12 mm, from about 7 mm to about 10 mm, or any range therein. In some embodiments, the low profile has an area with a diameter of 2 mm, 4 mm, 6 mm, 8 mm, 10 mm, 12 mm, 14 mm, 16 mm, 18 mm, or any range therein, including any increment of 1 mm in any such diameter or range therein. In some embodiments, the width (mm)×height (mm) of the frame in the collapsed state can be 9.0×5.0, 9.0×6.0, 9.0×7.0, 9.0×8.0, 9.0×9.0, and 9.0×10.0, or any deviation in dimension therein in increments of +/−0.1 mm. In some embodiments, the frame can have a transverse cross-sectional dimension, lateral or vertical in the expanded state ranging from 4.0 mm to 18 mm, from 5.0 mm to 19.0 mm, from 6.0 mm to 17.5 mm, from 7.0 mm to 17.0 mm, from 8.0 mm to 16.5 mm, from 9.0 mm to 16.0 mm, from 9.0 mm to 15.5 mm, from 6.5 mm to 15.5 mm, or any range or amount therein in increments of +/−0.1 mm.

11

The term “collapsed state” can be used to refer to a configuration of the frame in which the transverse cross-sectional area, or profile, is at least substantially at its minimum, and the term “expanded state” can be used to refer to a configuration of the frame that is expanded at least substantially beyond the collapsed state. In this context, a frame is expanded at least “substantially” beyond the collapsed state when a bone graft window of the frame has opened from the closed configuration by at least a 20% increase area of the bone graft window from the collapsed state. In some embodiments, the frame is expanded at least “substantially” beyond the collapsed state when a bone graft window of the frame has opened by at least a 15%, 20%, 25%, 30%, 35%, 40%, 45%, 50%, 60%, 70%, 80%, 90%, 100%, 150%, 200%, 250%, 300%, or more when compared to the bone graft window from the collapsed state. In some embodiments, the frame is expanded at least “substantially” beyond the collapsed state when a bone graft window of the frame has opened by at least 2x, 3x, 5x, 10x, 15x, 20x, or more when compared to the bone graft window from the collapsed state.

In some embodiments, the lateroververtically expandable frames are created in an expanded state. And the expanded state can include a state that is at least 30%, at least 40%, at least 50%, at least 60%, at least 70%, at least 80%, at least 90%, or at least 95% of the full expansion. The term “full expansion” can be used to refer to an extent of expansion upon which a connector element begins to fatigue, fail, or crack; or, in some embodiments, strain beyond 10%, 20%, or 30%.

The frame 149 can be configured to have a first top beam 150 including a proximal portion 111 having an end, a grafting portion 112, and a distal portion (not shown) having an end, the first top beam 150 configured for contacting the first top-lateral surface 117 of the central beam and the first top-side surface 127 of the central beam 101 in the expanded state 149e, the central axis of the first top beam at least substantially on (i) a top plane containing the central axis of the first top beam and the central axis of a second top beam and (ii) a first side plane containing the central axis of the first top beam and the central axis of a first bottom beam. Likewise the frame 149 can be configured to have a second top beam 160 including a proximal portion 111 having an end, a grafting portion 112 having an end, and a distal portion (not shown) having an end, the second top beam 160 configured for contacting the second top-lateral surface 119 of the central beam 101 and the second top-side surface 132 of the central beam 101 in the expanded state 149e, the central axis of the second top beam at least substantially on (i) the top plane and (ii) a second side plane containing the central axis of the second top beam and the central axis of a second bottom beam. Likewise the frame 149 can be configured to have a first bottom beam 170 including a proximal portion 111 having an end, a grafting portion 112, and a distal portion (not shown) having an end, the first bottom beam 170 configured for contacting the first bottom-lateral surface 122 of the central beam 101 and the first bottom-side surface 129 of the central beam 101 in the expanded state 149e, the central axis of the first bottom beam at least substantially on (i) a bottom plane containing the central axis of the first bottom beam and the central axis of a second top beam and (ii) the first side plane. Likewise the frame 149 can be configured to have a second bottom beam 180 including a proximal portion 111 having an end, a grafting portion 112 having an end, and a distal region (not shown) having an end, the second bottom beam 160 configured for contacting the second bottom-lateral surface 124

12

of the central beam 101 and the second bottom-side surface 134 of the central beam 101 in the expanded state 149e, the central axis of the second bottom beam being at least substantially on (i) the bottom plane and (ii) a second side plane containing the central axis of the second bottom beam and the second top beam.

In some embodiments, the central axis of the first top beam 150 can be at least substantially parallel to the central beam axis 105. Likewise the frame 149 can be configured to have a second top beam 160 including a proximal portion 111 having an end, a grafting portion 112 having an end, and a distal portion (not shown) having an end, the second top beam 160 configured for contacting the second top-lateral surface 119 of the central beam 101 and the second top-side surface 132 of the central beam 101 in the expanded state 149e, the central axis of the second top beam 160 being at least substantially parallel to the central beam axis 105. Likewise the frame 149 can be configured to have a first bottom beam 170 including a proximal portion 111 having an end, a grafting portion 112, and a distal portion (not shown) having an end, the first bottom beam 170 configured for contacting the first bottom-lateral surface 122 of the central beam 101 and the first bottom-side surface 129 of the central beam 101 in the expanded state 149e, the central axis of the first bottom beam 170 being at least substantially parallel to the central beam axis 105. Likewise the frame 149 can be configured to have a second bottom beam 180 including a proximal portion 111 having an end, a grafting portion 112 having an end, and a distal region (not shown) having an end, the second bottom beam 160 configured for contacting the second bottom-lateral surface 124 of the central beam 101 and the second bottom-side surface 134 of the central beam 101 in the expanded state 149e, the central axis of the second bottom beam 180 being at least substantially parallel to the central beam axis 105.

As shown in FIG. 1D, the graft distribution systems provided herein have the layered effect from the frame on the central beam that provides an additive dimension, both laterally and vertically. The added dimension allows for a low profile entry of the system into the intervertebral disc space, a wide lateral profile after expansion in vivo to avoid backout, as well as a sleeve for safe insertion of the central beam between the top endplate and bottom endplate in the intervertebral space. In some embodiments, the first top beam, second top beam, first bottom beam, and second bottom beam can each have a transverse cross-sectional wall thickness adding to the respective central beam dimension, the thickness ranging from about 0.5 mm to about 5.0 mm, from about 0.75 mm to about 4.75 mm, from about 1.0 mm to about 4.5 mm, from about 1.25 mm to about 4.25 mm, from about 1.5 mm to about 4.0 mm, from about 1.75 mm to about 3.75 mm, from about 2.0 mm to about 3.5 mm, from about 2.25 mm to about 3.25 mm, or any range therein in increments of 0.05 mm. In some embodiments, the first top beam, second top beam, first bottom beam, and second bottom beam can each have a transverse cross-sectional wall thickness adding to the respective central beam dimension, the thickness ranging from about 1.5 mm to about 2.5 mm, including 1.5, 1.75, 2.0, 2.25, 2.5, or an amount therein in increments of 0.05 mm.

The beams of the lateroververtically-expanding frame 149 can be operably connected through connector elements. As such, the frame 149 can include a plurality of proximal top connector elements 191 configured to expandably connect the proximal portion 111 of the first top beam 150 to the proximal portion 111 of the second top beam 160, the expanding consisting of a flexing at least substantially on a

13

top plane containing the central axis of the first top beam 150 and the central axis of the second top beam 160. Likewise the frame 149 can be configured to have a plurality of distal top connector elements (not shown) configured to expandably connect the distal portion of the first top beam 150 to the distal portion of the second top beam 160, the expanding consisting of a flexing at least substantially on the top plane.

Likewise the frame 149 can be configured to have a plurality of proximal bottom connector elements 193 configured to expandably connect the proximal portion 111 of the first bottom beam 170 to the proximal portion 111 of the second bottom beam 180, the expanding consisting of a flexing at least substantially on a bottom plane containing the central axis of the first bottom beam 170 and the central axis of the second bottom beam 180. Likewise the frame 149 can be configured to have a plurality of distal bottom connector elements (not shown) configured to expandably connect the distal portion of the first bottom beam 170 to the distal portion of the second bottom beam 180, the expanding consisting of a flexing at least substantially on the bottom plane.

Likewise the frame 149 can be configured to have a plurality of proximal first side connector elements 195 configured to expandably connect the proximal portion 111 of the first top beam 150 to the proximal portion 111 of the first bottom beam 170, the expanding consisting of a flexing at least substantially on a first side plane containing the central axis of the first top beam 150 and the central axis of the first bottom beam 170; a plurality of distal first side connector elements (not shown) configured to expandably connect the distal portion of the first top beam 150 to the distal portion of the first bottom beam 170, the expanding consisting of a flexing at least substantially on the first side plane. Likewise the frame 149 can be configured to have a plurality of proximal second side connector elements 197 configured to expandably connect the proximal portion 111 of the second top beam 160 to the proximal portion 111 of the second bottom beam 170, the expanding consisting of a flexing at least substantially on a second side plane containing the central axis of the second top beam 160 and the central axis of the second bottom beam 180; a plurality of distal second side connector elements (not shown) configured to expandably connect the distal portion of the second top beam 160 to the distal portion of the second bottom beam 180, the expanding consisting of a flexing at least substantially on the second side plane.

In some embodiments, each plurality of proximal connector elements can be configured as proximal struts in an at least substantially parallel alignment in the expanded state and the collapsed state; and, each plurality distal connector elements are distal struts can be configured in an at least substantially parallel alignment in the expanded state and the collapsed state. As such, the proximal top struts can be configured monolithically integral to the first top beam and the second top beam and adapted to flex toward the distal top struts during collapse; and, the distal top struts can be configured monolithically integral to the first top beam and the second top beam and adapted to flex toward the proximal top struts during collapse. Likewise, the proximal bottom struts can be configured monolithically integral to the first bottom beam and the second bottom beam and adapted to flex toward the distal bottom struts during collapse; and, the distal bottom struts can be configured monolithically integral to the first bottom beam and the second bottom beam and adapted to flex toward the proximal bottom struts during collapse. Likewise, the proximal first side struts can be configured monolithically integral to the first top beam and

14

the first bottom beam and adapted to flex toward the distal first side struts during collapse; and, the distal first side struts can be configured monolithically integral to the first top beam and the first bottom beam and adapted to flex toward the proximal first side struts during collapse. Likewise, the proximal second side struts can be configured monolithically integral to the second top beam and the second bottom beam and adapted to flex toward the distal second side struts during collapse; and, the distal second side struts can be configured monolithically integral to the second top beam and the second bottom beam and adapted to flex toward the proximal second side struts during collapse.

As shown in FIG. 1D, the frame 149 can be configured for slidably engaging with the central beam 101 in vivo following placement of the central beam 101 in the intervertebral space through the annular opening, the slidably engaging including translating the central beam 101 into the frame 149 from the proximal end 11 of the frame 149 toward the distal end of the frame 149 in vivo; the translating including keeping the central beam axis 105 at least substantially coincident with the central frame axis 113 during the translating to create the graft distribution system 100 in vivo through the annular opening. The graft distribution system 100 can also be configured to form a top graft-slab depth 199a between the top surface 115 of the central beam 101 and the top vertebral endplate; and, a bottom graft-slab depth 199b (not shown) between the bottom surface 120 of the central beam 101 and the bottom vertebral endplate in vivo. And, in some embodiments, the transverse cross-section 110 of the graft distribution system 100 in vivo is greater than the maximum lateral dimension of the annular opening to avoid backout.

One of skill will appreciate that the central beam can have any configuration that would be operable with the teachings provided herein. In some embodiments, criteria for a suitable central beam may include a combination of a material and configuration that provides a suitable stiffness. In some embodiments, the central beam can comprise an I-beam. An example of an I-beam configuration and a complementary laterovertically expandable cage are shown in FIGS. 1E and 1F.

One of skill will further appreciate that the central beam can have any one or any combination of graft port configurations that would be operable with the teachings provided herein. In some embodiments, criteria for a suitable graft port configuration may include a combination of port size, number of ports, and placement of ports. In some embodiments, the central beam can comprise a side graft port.

One of skill will further appreciate that the connector elements can vary in design but should meet the constraints as taught herein. In some embodiments, for example each of the connector elements 191, 193, 195, 197 can have a cross-sectional aspect ratio of longitudinal thickness to transverse thickness ranging from 1:2 to 1:8. A section of a connector element is shown in FIG. 1G.

As such, the systems can also include an improved, low-profile, intervertebral disc cage that expands bidirectionally. Consistent with the teachings herein, the cages offer several improvements to the art that include, for example, preventing the cage from backing out of the annulus fibrosis after expansion in an intervertebral disc space. As such, the terms "cage," "scaffold" and "scaffolding", for example, can be used interchangeably with "laterovertically expandable frame", "expandable frame", or "frame", in some embodiments. The cages have the ability to at least (i) laterally expand within the intervertebral space to avoid backout of the device through the annulotomy, (ii) vertically expand for

distraction of the intervertebral space, (iii) provide additional space within the device in the annulus for the introduction of graft materials; (iv) maintain a large, footprint to distribute load over a larger area against the endplate, for example, by not contracting in length to expand in height and/or width; and, (v) insert into the annulus in a minimally-invasive manner using only a unilateral approach.

FIGS. 2A-2F illustrate a method of using a bidirectionally-expandable cage, according to some embodiments. As shown in FIGS. 2A-2B, an annulus 205 is prepared with an annulotomy serving as a single point of entry 210 and an intervertebral space 215 for insertion of a bidirectionally expandable cage system 250. As shown in FIGS. 2C-2F, the system 250 has a cage 255 having a proximal end 256, a distal end 257, and a lumen 258 that communicates with the intervertebral space 215 through an expandable/collapsible bone graft window 259; a shim core 260 having a tapered nose 262 at the distal end of the shim core 260; a releasably attachable rail beam 265; a pusher 270 that slidably translates over the shim core 260 and the rail beam 265; a trial shim 275 having a shoulder 277 and slidably translating over the rail beam 265 and shim core 260 into the lumen 258 of the cage 255, and a permanent shim 280 having a shoulder 282 and slidably translating over the rail beam 265 and shim core 260 into the lumen 258 of the cage 255.

The procedure for implanting the cage 255 begins in FIG. 2A, including inserting a cannula (not shown) with a bullet-nosed obturator through the single point of entry 210 and inside the intervertebral disc space 215 until contacting the opposing wall of the annulus 205. The cannula (not shown) depth is used to select the desired length of the cage 255. The shim core 260 is loaded with bone graft material and the rail beam 265 is releasably attached to the shim core 260. The cage 255 is loaded onto the rail beam 265 and pushed onto the shim core 260 and into the cannula (not shown) using the pusher 270 until the distal end 257 of the cage 255 contacts the back of the tapered nose 262 of the shim core 260 as shown in FIG. 2A. The assembly of the shim core 260 and the cage 255 are inserted into the intervertebral space 215, and the cannula (not shown) is removed as shown in FIG. 2B. The lumen 258 of the cage 255 is loaded with bone graft material, and the trial shim 275 is slidably translated over the rail beam 265 and the shim core 260 into the lumen 258 of the cage 255 as shown in FIG. 2C. A variety of sizes of the trial shim 275 can be tested until the largest trial shim 275 that will fit is found, or until the trial shim having the desired vertical and lateral dimensions for expansion is used, in order to lateroververtically expand the cage 255 as desired. The trial shim 275 is then removed, and the lumen 258 of the cage 255 is again filled with bone graft material with the shim core 260 remaining in place as shown in FIG. 2D. The permanent shim 280 is then slidably translated along the rail beam 265 and the shim core 260 into the intervertebral space 215 using the pusher 270 until the distal end 257 of the cage 255 contacts the back of the tapered nose 262 of the shim core 260 to maintain the desired lateroververtical expansion of the cage 255 as shown in FIG. 2E. The rail beam 265 is then disconnected from the shim core 260 as shown in FIG. 2F.

It should be appreciated that the annulotomy can have nearly any dimension considered desirable to one of skill in the art. The annulotomy can have a vertical dimension, for example, that is the distance between a top vertebral plate and a bottom vertebral plate, the top vertebral plate and the bottom vertebral plate defining the upper and lower borders of the intervertebral disc space. In some embodiments, the vertical dimension can range from about 4 mm to about 12 mm, about 5 mm to about 11 mm, about 6 mm to about 10

mm, and about 7 mm to about 9 mm, about 6 mm to about 8 mm, about 6 mm, or any range or amount therein in increments of 1 mm. In some embodiments, the lateral dimension of the single point of entry can range from about 5 mm to about 15 mm, about 6 mm to about 14 mm, about 7 mm to about 13 mm, about 8 mm to about 12 mm, about 10 mm, or any range or amount therein in increments of 1 mm. In some embodiments, the single point of entry has an area with a diameter ranging from about 2 mm to about 20 mm, from about 3 mm to about 18 mm, from about 4 mm to about 16 mm, from about 5 mm to about 14 mm, from about 6 mm to about 12 mm, from about 7 mm to about 10 mm, or any range therein. In some embodiments, the low profile has an area with a diameter of 2 mm, 4 mm, 6 mm, 8 mm, 10 mm, 12 mm, 14 mm, 16 mm, 18 mm, or any range therein, including any increment of 1 mm in any such diameter or range therein. The low profile dimensions of the cages taught herein are designed to fit within these dimensions.

One of skill will also appreciate that there are several methods and devices that could be used to expand the cage. In some embodiments, the expanding includes using a means for (i) lateroververtically expanding the cage and (ii) creating a convex surface that at least substantially complements the concavity of a surface of a vertebral endplate that contacts the pair of top beams or the pair of bottom beams.

One of skill will also appreciate a method that distracts the intervertebral space and laterally expands the cage to avoid back-out. As such, in some embodiments, the expanding includes introducing a lateroververtical expansion member into the intervertebral space through the single point of entry and into the cage, the lateroververtical expansion member configured to provide a vertical force through the cage and into the top vertical endplate and bottom vertical endplate to distract the intervertebral space; and, a lateral force on the first side wall and the second side wall to expand the cage to a width that is greater than the lateral dimension of the single point of entry to prevent the bidirectionally-expandable cage from backing out of the annulus fibrosis after the expanding.

One of skill will also appreciate having a method for passing bone grafting material into the intervertebral space. As such, the lateroververtical expansion member can include a port for introducing the grafting material into the intervertebral space. The methods and systems provided herein include the use of bone graft materials known to one of skill. Materials which may be placed or injected into the intervertebral space include solid or semi-solid grafting materials, bone from removed from patient's facet, an iliac crest harvest from the patient, and bone graft extenders such as hydroxyapatite, demineralized bone matrix, and bone morphogenic protein. Examples of solid or semi-solid grafting material components include solid fibrous collagen or other suitable hard hydrophilic biocompatible material. Some materials may also include swelling for further vertical expansion of the intervertebral disc space.

One of skill will also appreciate having a method for retaining the lateroververtical expansion member in the cage. As such, the introducing can include engaging a ratchet mechanism comprising a protuberance on the lateroververtical expansion member that engages with a strut of the cage to prevent the cage from backing out of the annulus fibrosis after the expanding. The ratchet mechanism can be, for example, similar to a zip-tie ratchet mechanism having a gear component and a pawl component. In some embodiments, the cage has the gear component, for example, including the struts; and, the lateroververtical expansion member is a shim device having the pawl component, for

example, a projection that can angle toward the proximal end of the expansion member or away from the direction of insertion of the shim device. In some embodiments, the cage has the pawl component, for example, including the struts; and, the laterovertical expansion member is a shim device having the gear component, for example, a series of projections. In some embodiments, a projection can angle from about 5° to about 75° toward the proximal end of the expansion member or away from the direction of insertion of the shim device.

One of skill will also appreciate having a method of designing the shape of the cage upon expansion. As such, in some embodiments, the expanding includes selecting a shim configured to create a convex surface on the top surface of the top wall to at least substantially complement the concavity of the respective top vertebral plate, and/or the bottom surface of the bottom wall to at least substantially complement the concavity of the respective bottom vertebral plate. In some embodiments, the expanding includes selecting a shim configured to vertically expand the distal end of the cage more than the proximal end of the cage. And, in some embodiments, the expanding includes selecting a shim configured to laterally expand the distal end of the cage more than the proximal end of the cage.

FIGS. 3A-3D illustrate collapsed and expanded views of a bidirectionally-expandable cage for fusing an intervertebral disc space, according to some embodiments. FIGS. 3A and 3C show an expanded configuration, and FIGS. 3B and 3D show a collapsed configuration. The cage **300** can comprise at least 4 walls **302,304,306,308** that form a cylinder having a long axis **309**, the at least 4 walls **302,304,306,308** including a top wall **302** forming a top plane and having a top surface with protuberances (not shown) adapted to contact the top vertebral plate (not shown); a bottom wall **304** forming a bottom plane and having a bottom surface with protuberances (not shown) adapted to contact the bottom vertebral plate (not shown); a first side wall **306** forming a first side wall plane; and, a second side wall **308** forming a second side wall plane. In these embodiments, each of the walls **302,304,306,308** can have at least 2 longitudinal beams, such that a rectangular cylinder can have a total of 4 longitudinal beams **312,314,316,318**; and, a plurality of struts **333** that (i) stack in the collapsed state of the cage **300**, as shown in FIGS. 3B and 3D, to minimize void space in their respective wall for a low profile entry of the cage **300** both vertically and laterally into a single point of entry (not shown) into an intervertebral disc space (not shown) and (ii) deflect upon expansion to separate the at least 2 longitudinal beams of the total of 4 longitudinal beams **312,314,316,318** in the rectangular cylinder in their respective wall **302,304,306,308**. In addition, the cage **300** can be configured to expand laterally in the intervertebral space (not shown) to a size greater than a lateral dimension of the single point of entry (not shown) to prevent the bidirectionally-expandable cage **300** from backing out of the annulus fibrosis (not shown) after the expanding shown in FIGS. 3A and 3C.

It should be appreciated that the collapsed configuration includes the design of a low profile entry through the annulus fibrosis to allow for a minimally-invasive procedure. In order to facilitate the use of a minimally-invasive procedure, the low profile entry of the collapsed configuration should be a substantially small area of entry having a diameter ranging, for example, from about 5 mm to about 12 mm for the single point of entry through the annulus fibrosis. In some embodiments, the low profile has an area with a diameter ranging from about 2 mm to about 20 mm, from

about 3 mm to about 18 mm, from about 4 mm to about 16 mm, from about 5 mm to about 14 mm, from about 6 mm to about 12 mm, from about 7 mm to about 10 mm, or any range therein. In some embodiments, the low profile has an area with a diameter of 2 mm, 4 mm, 6 mm, 8 mm, 10 mm, 12 mm, 14 mm, 16 mm, 18 mm, or any range therein, including any increment of 1 mm in any such diameter or range therein.

One of skill will appreciate that a variety of strut configurations may be contemplated to minimize void space for the low profile entry of the cage into the intervertebral space. In some embodiments, each wall of the cage has a series of v-shaped struts **333** that (i) stack in a closed-complementary configuration **344** in the collapsed state to minimize void space in their respective wall for the low profile entry of the cage both vertically and laterally into the intervertebral space, and (ii) deflect upon expansion in a plane that is at least substantially parallel to the plane of their respective wall to an open-complementary configuration **355** to separate the at least 2 longitudinal beams of the total of 4 longitudinal beams **312,314,316,318** in the rectangular cylinder in their respective wall and open a bone graft window **366** to pass a bone graft material into the intervertebral space in the expanded configuration. In some embodiments, the cage **300** is configured to accommodate the lateral dimension of the single point of entry ranging from about 5 mm to about 15 mm.

The v-shaped struts can be “V” shaped slots projected through each of the cage walls starting at a distance of 2 mm (0.5-4) from each corner of the cage to effectively render the “V” shaped struts in the mid region of the wall faces, in which the struts can be fabricated as continuous with L shaped beams on the corners. The slots can be cut such that they are projected perpendicular to the faces or angled distally from the outside of the cage to the inside of the cage. The distally angled projection can facilitate insertion of the shims taught herein. And, the proximal faces of the corners of the beams can also have inward, distally angled chamfers to facilitate insertion of the shims taught herein. The struts can be uniform in thickness in the proximal-distal direction. In some embodiments, the struts range from about 0.2 mm to about 1.0 mm, from about 0.3 mm to about 0.9 mm, from about 0.4 mm to about 0.8 mm, from about 0.5 mm to about 0.7 mm in thickness, or any range therein in increments of about 0.1 mm. The vertex of the “V” strut can trace along the center axis of the each of the side faces and can be radiused to dimension of 0.031" (0.005-0.062"), in some embodiments, to prevent stress cracking. Moreover, the shape of the strut or the slot projections can also be C, U, or W, in some embodiments. The struts can be 4 times thicker in the direction perpendicular to the long axis of the cage than in the direction of the long axis of the cage. In some embodiments, this thickness ratio can range from about 2× to about 8×, from about 3× to about 7×, from about 4× to about 6×, about 5×, or any range therein in increments of 1×. This thickness can help maintain a high structural stiffness and strength in the direction perpendicular to the proximal-distal axis so that the transverse cross section (perpendicular to the proximal-distal axis) shape is maintained during and after insertion of the cage into the intervertebral disc space.

In some embodiments, the angle of each strut can range from about 140°-170° as measured at the vertex in the non-stressed state. In these embodiments, the angle facilitates flexion of the legs of each strut towards each other upon moderate inward pressure to collapse the cage for insertion into the disc space. Furthermore the angled strut lies in a plane at least substantially parallel to the plane of its

respective wall, and in some embodiments to the long axis of the cage, so that the flexion does not alter the side wall thickness. This helps to maintain the low profile for insertion while maximizing the lumen size. This geometry combined with the solid beams on the corners helps ensure that the implant has a minimal change in length, less than 15% reduction in length as measured along the long axis, when expanded more than 20% vertically and/or horizontally. As such, the top and bottom of the cage that support the vertebra remain at least substantially constant in length regardless of expansion.

In some embodiments, the cage 300 has v-shaped struts 333 and a bone graft window 366 that (i) complements the v-shaped struts 333 in the collapsed configuration and (ii) opens upon expansion to pass a bone graft material into the intervertebral space in the open-complementary configuration 355, which can also be referred to as an expanded configuration. And, in some embodiments, the cage 300 has a proximal region 311, a proximal end 322, a distal region 388, a distal end 399, and at least one of the at least 4 walls 302, 304, 306, 308 having a first series of v-shaped struts 333 that are configured to stack in a closed-complementary configuration 344 in the collapsed state to minimize void space for the low profile entry of the cage 300 into the intervertebral space; and, deflect upon expansion to an open-complementary configuration 355 to separate the at least 2 longitudinal beams of the total of 4 longitudinal beams 312, 314, 316, 318 in the rectangular cylinder in their respective wall and open a bone graft window 366 adapted to pass a bone graft material into the intervertebral space in the expanded configuration; wherein, the first series of v-shaped struts 333F is located in the proximal region of the cage, the vertices of the first series of v-shaped struts 333F pointing away from the proximal end 322 of the cage 300 and toward the distal end 399 of the cage 300. In some embodiments, the cage 300 can further comprise a second series of v-shaped struts 333S that stack in a closed-complementary configuration 344 in the collapsed state to minimize void space for the low profile entry of the cage 300 into the intervertebral space; and, deflect upon expansion to an open-complementary configuration 355 to separate the at least 2 longitudinal beams of the total of 4 longitudinal beams 312, 314, 316, 318 in the rectangular cylinder in their respective wall and open a bone graft window 366 adapted to pass a bone graft material into the intervertebral space in the expanded configuration; wherein, the second series of v-shaped struts 333S is located in the distal region 388 of the cage 300, the vertices of the second series of v-shaped struts 333S pointing away from the distal end 399 of the cage 300 and toward the proximal end 322 of the cage 300. In such embodiments, the strut configuration can result in the expansion of the first series of v-shaped struts 333F and the second series of v-shaped struts 333S creating a bone graft window 366 that opens to the bow-tie configuration shown in FIGS. 3A and 3C.

One of skill will also appreciate that the cage design provides flexibility in the relative amounts of lateral expansion and vertical expansion, as well as the relative amounts of expansion proximally and distally across the cage in either the lateral or vertical expansions. As such, in some embodiments, the cage is configured such that the ratio of the amount of lateral expansion to the amount of vertical expansion is variable. And, in some embodiments, the cage is configured such that the ratio of the amount of proximal expansion to the amount of distal expansion is variable for lateral expansion or vertical expansion.

FIGS. 4A and 4B illustrate collapsed and expanded views of a bidirectionally-expandable cage having a bone graft window on each wall for fusing an intervertebral disc space, according to some embodiments. FIG. 4A shows the cage 400 in the collapsed configuration for a low-profile entry into a single point of entry into an intervertebral disc space, and FIG. 4B shows the cage 400 in the expanded configuration to distract the intervertebral disc space and avoid back-out of the cage through the single point of entry after the expansion. As shown, each wall contains a bone graft window 466 for passing bone graft material into the intervertebral disc space.

FIGS. 5A-5D illustrate system for fusing an intervertebral disc space, according to some embodiments. As shown, the system 550 has a cage 555 having an expandable/collapsible bone graft window 566; a shim core 560 having a tapered nose 562 at the distal end of the shim core 560 and a bone graft window 566; a releasably attachable rail beam 565; a pusher (not shown) that slidably translates over the shim core 560 and the rail beam 565; a trial shim 575 having a shoulder 577 and slidably translating over the rail beam 565 and shim core 560 into the cage 555, and a permanent shim 580 having a shoulder 582 and slidably translating over the rail beam 565 and shim core 560 into the cage 555. The system can comprise a bidirectionally-expandable cage having at least 4 walls that form a cylinder having a long axis. The at least 4 walls can include, for example, a top wall forming a top plane and having a top surface with protuberances adapted to contact the top vertebral plate; a bottom wall forming a bottom plane and having a bottom surface with protuberances adapted to contact the bottom vertebral plate; and, a first side wall forming a first side wall plane, and a second side wall forming a second side wall plane. Each of the walls can have at least 2 longitudinal beams; and, a plurality of struts that (i) stack in the collapsed state to minimize void space in their respective wall for a low profile entry of the cage both vertically and laterally into a single point of entry into an intervertebral disc; and, (ii) deflect upon expansion to separate the at least 2 longitudinal beams in their respective wall. In some embodiments, the cage can be configured to expand laterally in the intervertebral space to a size greater than a lateral dimension of the single point of entry to prevent the bidirectionally-expandable cage from backing out of the annulus fibrosis after the expanding. Moreover, the system can include a laterovertical expansion member configured to induce the laterally expanding and the vertically expanding of the cage; and, a core configured to guide the laterovertical expansion member into the cage to induce the laterally expanding and the vertically expanding of the cage.

One of skill will appreciate that the laterovertical expansion member can also be configured to slidably engage with the core to translationally enter the cage in along the long axis of the cage. In some embodiments, the lateral expansion can occur concurrent with the vertical expansion and, in some embodiments, the lateral expansion can occur prior to the vertical expansion, for example, to reduce frictional stress on the cage during the lateral expansion. A two stage shim, for example, can be used. A first stage shim can be inserted to expand the cage laterally before inserting a second stage shim to expand the cage vertically. In some embodiments, the second stage shim can slidably translate along the first stage shim. The shim can be made of any material considered desirable to one of skill, for example, a metal or a polymer. In some embodiments, the shim can comprise a non-resorbable polymer material, an inorganic material, a metal, an alloy, or bone.

21

One of skill will appreciate that a system can include all or any combination of the above. As such, the teachings also include system for fusing an intervertebral disc space, the system comprising a bidirectionally-expandable cage having a proximal region, a proximal end, a distal region, a distal end, and at least 4 walls, the cage fabricated as a continuous single piece. In these embodiments, the at least 4 walls form a cylinder having a long axis and include a top wall forming a top plane and having a top surface with protuberances adapted to contact the top vertebral plate; a bottom wall forming a bottom plane and having a bottom surface with protuberances adapted to contact the bottom vertebral plate; and, a first side wall forming a first side wall plane, and a second side wall forming a second side wall plane. Each of the walls can have at least 2 longitudinal beams and a plurality of struts.

At least one of the walls can have a first series of v-shaped struts that are configured to stack in a closed-complementary configuration in the collapsed state to minimize void space for a low profile entry of the cage through a single point of entry into an intervertebral disc space; and, deflect upon expansion to an open-complementary configuration to separate the at least 2 longitudinal beams in their respective wall and open a bone graft window adapted to pass a bone graft material into the intervertebral space in the expanded configuration. The first series of v-shaped struts can be located in the proximal region of the cage, the vertices of the first series of v-shaped struts pointing away from the proximal end of the cage and toward the distal end of the cage; and, the cage can be configured to expand laterally in the intervertebral space to a size greater than a lateral dimension of the single point of entry to prevent the bidirectionally-expandable cage from backing out of the annulus fibrosis after the expanding. A laterovertical expansion member can be configured to induce the laterally expanding and the vertically expanding of the cage; and, a core can be configured to guide the laterovertical expansion member into the proximal end of the cage, and along the long axis of the cage, to expand the cage laterally and vertically. Moreover, the laterovertical expansion member can slidably engage with the core to translationally enter the cage along the long axis of the cage.

One of skill will appreciate that the systems and system components can be manufactured using any method known to one of skill in the manufacture of such intricate metal and/or polymeric components. For example, the cage can be fabricated in a partially expanded state or a fully expanded state. Moreover, the cage can be manufactured to have no internal stress or strain in the partially or fully expanded state when no external loading is applied.

The system components can comprise any suitable material, or any combination of materials, known to one of skill. For example, all components can be metal, all components can be plastic, or the components can be a combination of metal and plastic. One of skill will appreciate that the cages can have performance characteristics that are near that of a bone structure, in some embodiments, such that the scaffoldings are not too stiff or hard, resulting in a localized loading issue in which the scaffolding puts too much pressure on native bone tissue, and likewise such that the scaffoldings are too flexible or soft, resulting in a localized loading issue in which the bone tissue puts too much pressure on the scaffolding. A radio-opaque material can be employed to facilitate identifying the location and position of the scaffolding in the spinal disc space. Examples of such materials can include, but are not limited to, platinum, tungsten, iridium, gold, or bismuth.

22

One of skill can select materials on the basis of desired material performance characteristics. For example, one of skill will look to performance characteristics that can include static compression loading, dynamic compression loading, static torsion loading, dynamic torsion loading, static shear testing, dynamic shear testing, expulsion testing, and subsidence testing. The parameters for upper and lower limits of performance for these characteristics can fall within the range of existing such spinal devices that bear the same or similar environmental conditions during use. For example, a desired static compression loading can be approximately 5000N. A desired dynamic compression loading can have an asymptotic load level of $\geq 3000\text{N}$ at 5×10^6 cycles or $\geq 1500\text{N}$ at 10×10^6 cycles. The desired load level can range, for example, from about $1.0 \times$ to about $2.0 \times$, from about $1.25 \times$ to about $1.75 \times$, or any range therein in increments of $0.1 \times$, the vertebral body compression strength. Examples of standard procedures used to test such performance characteristics include ASTM F2077 and ASTM F2624.

Examples of suitable materials can include non-reinforced polymers, carbon-reinforced polymer composites, PEEK (polyether ketone) and PEEK composites, polyetherimide (ULTEM), polyimide, polyamide or carbon fiber. Other examples include metals and alloys comprising any one or more components including, but not limited to, shape-memory alloys, nickel, titanium, titanium alloys, cobalt chrome alloys, stainless steel, ceramics and combinations thereof. In some embodiments, the components are all titanium or titanium alloy; all PEEK; or a combination of titanium or titanium alloy and PEEK. In some embodiments, the cage comprises titanium or titanium alloy, and the shim comprises PEEK. In some embodiments, the scaffolding can comprise a metal frame and cover made of PEEK or ULTEM. Examples of titanium alloys can include alloys of titanium, aluminum, and vanadium, such as $\text{Ti}_6\text{Al}_4\text{V}$ in some embodiments.

In some embodiments, the cage can be fabricated from strong and ductile polymers having a tensile modulus of about 400,000 psi or more, and a tensile strength of about 14,000 psi or more. Such polymers may also have the ability to strain more than 4% to break, and perhaps at least 20% to break in some embodiments. The materials can be stiffened by being filled with glass fibers or carbon fibers in some embodiments.

Bone ingrowth is desirable in many embodiments. As such, the scaffolding can comprise materials that contain holes or slots to allow for such bone ingrowth. Consistently, the scaffoldings can be coated with hydroxyapatite, or other bone conducting surface, for example, bone morphogenic protein, to facilitate bone ingrowth. Moreover, the surfaces of the scaffoldings can be formed as rough surfaces with protuberances, insets, or projections of any type known to one of skill, such as teeth or pyramids, for example, to grip vertebral endplates, avoid migration of the scaffolding, and encourage engagement with bone ingrowth.

The methods and systems provided herein include the use of bone graft materials known to one of skill. Materials which may be placed or injected into the intervertebral space include solid or semi-solid grafting materials, bone from removed from patient's facet, an iliac crest harvest from the patient, and bone graft extenders such as hydroxyapatite, demineralized bone matrix, and bone morphogenic protein. Examples of solid or semi-solid grafting material components include solid fibrous collagen or other suitable hard

hydrophilic biocompatible material. Some materials may also include swelling for further vertical expansion of the intervertebral disc space.

The systems taught herein can be provided to the art in the form of kits. A kit can contain, for example, a cage, a vertical expansion member, and a bone graft material. In some embodiments, the kit will contain an instruction for use. The vertical expansion member can be any vertical expansion mechanism or means taught herein. For example, the vertical expansion member can be a shim. In some embodiments, the kit includes a graft-injection shim for temporarily distracting the intervertebral space, the graft-injection shim having a port for receiving and distributing the bone graft material in the intervertebral space. In these embodiments, the graft-injection shim can remain as a permanent shim or be removed and replaced with a permanent shim.

FIG. 6 is a flowchart of a method of using a bidirectionally-expandable cage, according to some embodiments. The methods can include creating **605** a single point of entry into an intervertebral disc, the intervertebral disc having a nucleus pulposus surrounded by an annulus fibrosis, and the single point of entry having a lateral dimension created through the annulus fibrosis. The methods can also include removing **615** the nucleus pulposus from within the intervertebral through the single point of entry, leaving an intervertebral space for expansion of a bidirectionally-expandable cage within the annulus fibrosis, the intervertebral space having a top vertebral plate and a bottom vertebral plate. The methods can also include inserting **625** a bidirectionally-expandable cage through the single point of entry into the intervertebral space. Moreover, the methods can include expanding **635** the cage in the intervertebral space both laterally and vertically, adding **645** a grafting material to the intervertebral space through the single point of entry, and inserting **665** a permanent shim into the cage.

One of skill will appreciate having the ability to control the amounts of vertical expansion and lateral expansion of the cage to accommodate a variety of applications, for example, to accommodate a variety annulotomy dimensions used for the single point of entry. As such, in some embodiments, the expanding **635** includes selecting **655** an amount of lateral expansion independent of an amount of vertical expansion. The lateral expanding of the cage can be selected, for example, to exceed the lateral dimension of the single point of entry through an annulotomy by a desired amount to avoid, or prevent, the cage from backing out of the intervertebral space after expansion.

As such, methods of fusing an intervertebral space are provided herein using any of the graft distribution systems taught herein. The methods can include creating a single point of entry into an intervertebral disc, the intervertebral disc having a nucleus pulposus surrounded by an annulus fibrosis, and the single point of entry having the maximum lateral dimension created through the annulus fibrosis. The methods can also include removing the nucleus pulposus from within the intervertebral disc through the single point of entry, leaving the intervertebral space for expansion of the graft distribution system within the annulus fibrosis, the intervertebral space having the top vertebral plate and the bottom vertebral plate. The methods can also include inserting the lateroververtically expanding frame in the collapsed state through the single point of entry into the intervertebral space; and, inserting the central beam into the frame to form the graft distribution system. Moreover, the methods can also include adding a grafting material to the intervertebral space through the entry port.

FIGS. 7A-7F illustrate some additional features of graft distribution systems, according to some embodiments. The graft distribution systems **700** provided herein have at least a top exit port **740** and a bottom exit port **741** in the grafting portion of the central beam **701**, but they can also contain side ports **742, 743**, such that there at least 4 graft distribution ports in some embodiments. In some embodiments, the central beam **701** further comprises a first side graft port **742** and a second side graft port **743**, in addition to a locking clip **702** at the proximal end of the central beam. In some embodiments, the lateroververtically-expanding frame **749** can be a monolithically integral frame, optionally having a "bullet nose" **703** at the distal end of the frame for safe position of the cage against the anterior inner annulus in vivo, and adapted to open a graft distribution window **788** on at least the top and bottom sides, as well as the first side and second side in some embodiments containing side ports, upon expansion of the connector elements to facilitate graft distribution within the intervertebral space.

The distal end of the frame **749** can be configured to have a lateroververtically operable connection with a guide plate **707** that restricts the first top beam, the first bottom beam, the second top beam, and the second bottom beam to lateroververtical movement relative to the guide plate when converting the frame from the collapsed state to the expanded state in vivo. And, in some embodiments, the lateroververtically-expandable frame has a lumen, and the guide plate has a luminal side with a connector **708** for reversibly receiving a guide wire for inserting the lateroververtically-expandable frame into the intervertebral space. In some embodiments, the frame has a chamfer inside the proximal end of the frame beams to facilitate insertion of central beam. And, in many embodiments, the frames have means for creating friction between the vertebral endplates and the frame, such as protuberances, for example cleat-type structures **704**, to further avoid backout.

As can be seen in at least FIG. 7, the bone graft distribution systems provided herein include bone graft windows defined by the connector elements, the bone graft windows opening upon expansion of the lateroververtically expanding frame. In some embodiments, the method further comprises opening a bone graft window, wherein the connector elements include v-shaped struts that (i) stack either proximally or distally in a closed-complementary configuration in the collapsed state to minimize void space for a low profile entry of the system both vertically and laterally into the intervertebral space, and (ii) deflect upon expansion to open the bone graft window.

It should be appreciated that the bone graft distribution systems provided herein also allow for independent expansion laterally and vertically by expanding in steps. In some embodiments, the expanding includes selecting an amount of lateral expansion independent of an amount of vertical expansion. And, in some embodiments, the lateral expansion exceeds the width of the annular opening that is the single point of entry into the intervertebral space. For example, the lateral dimension of the single point of entry can range from about 5 mm to about 15 mm in some embodiments. As such, in some embodiments, the expanding includes expanding the lateroververtically expanding frame laterally to a width that exceeds the width of the single point of entry; and, inserting the central beam to expand the lateroververtically expanding frame vertically to create the graft distribution system.

The bone graft distribution systems provided herein also have additional means for retaining the central beam in the lateroververtically expanding frame. In some embodiments, the inserting of the central beam into the lateroververtically

25

expanding frame includes engaging a ratchet mechanism comprising a protuberance on the central beam that engages with the laterover vertically-expanding frame to prevent the central beam from backing out of the laterover vertically-expanding frame after the expanding.

Moreover, the bone graft distribution systems provided herein can be in the form of a kit. The kits can include, for example, a graft distribution system taught herein, a cannula for inserting the graft distribution system into the intervertebral space, a guidewire adapted for guiding the central beam into the laterover vertically expanding frame, and an expansion handle for inserting the central beam into the laterover vertically expanding frame to form the graft distribution system.

FIGS. 8A-8D illustrate components of a graft distribution kit, according to some embodiments. FIGS. 8A and 8B illustrate a 4-sided funnel cannula **805** as taught herein having a shaft **810** forming a channel **815**, a funnel **820** for guiding a laterover vertically expandable frame into an annulus in a low-profile configuration, the cannula shown with an obturator **825** in the channel **815** of the cannula **805**, the cannula **805** inserted posterolaterally through an annulotomy **877** in the annulus **888**, into an intervertebral space **899**, with the distal end of the cannula **805** position near the inner anterior wall of the annulus **888**. FIG. 8C illustrates FIG. 8A with a guidewire used to insert the laterover vertically expandable frame **749** into the funnel **820** of the cannula **805** to guide the frame **749** into the annulus **888** in the low profile, collapsed state of the frame **749**. FIG. 8D illustrates an expansion handle **855** having trigger **856** that pushes a pushrod **857** along the guidewire **866** while holding the guidewire to push on the proximal end of the central beam **701** to insert the central beam **701** into the frame **749** to expand the frame **749** by applying equal, or substantially equal forces: a proximally-directed force, F_p , at the connection **708** between the guide plate **707** and the guide wire **866** onto the distal portion of the beams of the frame **749**, and a distally-directed force, F_D , at the proximal end of the central beam **701**.

FIGS. 9A-9C illustrate the expansion of a laterover vertically-expandable frame in an intervertebral space, according to some embodiments. FIG. 9A shows a collapsed frame **949** receiving a central beam **901** along a guidewire **966**. FIG. 9B shows the central beam **901** partially inserted into the frame **949** in an expanded state, the guidewire **966** still in place. FIG. 9C shows how the expanded state may appear when inserted posterolaterally and expanded in the intervertebral space in an annulus **988**. Side ports **942, 943** for bone graft distribution are shown through an open bone graft window in the expanded frame **749**.

FIGS. 10A-10C illustrate profiles of an expanded graft distribution system to highlight the exit ports and bone graft windows, according to some embodiments. Profiles of an expanded frame **1049**, highlighting bone graft windows **1088** and graft ports **1040, 1041, 1042, 1043** as they may appear in an intervertebral space after an implant procedure. The guidewire **1066** is shown as remaining in place.

FIGS. 11A and 11B compare an illustration of the graft distribution in place to a test placement in a cadaver to show relative size, according to some embodiments. Likewise, FIGS. 12A-12C show x-rays of a placement in a cadaver, according to some embodiments.

As described above, the frame **149** can be configured such that the central axis of the first top beam **150** is at least substantially on (i) the top plane and (ii) the first side plane; the central axis of the second top beam **160** is at least substantially on (i) the top plane and (ii) the second side

26

plane; the central axis of the first bottom beam **170** is at least substantially on (i) the bottom plane and (ii) the first side plane; and, the central axis of the second bottom beam being at least substantially on (i) the bottom plane and (ii) the second side plane. It should be appreciated that this configuration provides a “top face” framed by the first top beam and the second top beam, a “bottom face” framed by the first bottom beam and the second bottom beam, a “first side face” framed by the first top beam and the first bottom beam, and a “second side face” framed by the second top beam and the second bottom beam.

In some embodiments, it can be desirable to have the frame expand to shape that is predesigned to fit between the top endplate and the bottom endplate of the intervertebral space in a manner that calls, for example, for opposing faces of the frames to be something other than “at least substantially parallel.” For example, it may be desired to have the two opposing sides of the frame expand such that the central axis of the first top beam is no longer at least substantially parallel to the central axis of the second top beam. Likewise, it may be desired to have the two opposing sides of the frame expand such that the central axis of the first bottom beam is no longer at least substantially parallel to the central axis of the second bottom beam. Likewise, it may be desired to have the opposing top and bottom sides of the frame expand such that the central axis of the first top beam is no longer at least substantially parallel to the central axis of the first bottom beam. Likewise, it may be desired to have the opposing top and bottom sides of the frame expand such that the central axis of the second top beam is no longer at least substantially parallel to the central axis of the second bottom beam. Or, any combination of the above may be desired. The laterover vertically expandable frames taught herein enable each of these desirable configurations.

FIGS. 13A-13D show orientations of the first top beam relative to the second top beam, first bottom beam relative to the second bottom beam, first top beam relative to the first bottom beam, and the second top beam relative to the second bottom beam, according to some embodiments. FIG. 13A shows the first top beam **150** relative to the second top beam **160**, in which the angle Θ_T is formed by the two beams to shape the top face of the frame. FIG. 13B shows the first bottom beam **170** relative to the second bottom beam **180**, in which the angle Θ_B is formed by the two beams to shape the bottom face of the frame. FIG. 13C shows the first top beam **150** relative to the first bottom beam **170**, in which the angle Θ_{FS} is formed by the two beams to shape the first side face of the frame. FIG. 13D shows the second top beam **160** relative to the second bottom beam **180**, in which the angle Θ_{SS} is formed by the two beams to shape the second side face of the frame. In some embodiments, each of Θ_T , Θ_B , Θ_{FS} , and Θ_{SS} can be independently selected and each can range from 0° to 32° , from 0.5° to 31.5° , from 0.1° to 31.0° , from 1.5° to 30.5° , from 2.0° to 30.0° , from 2.5° to 29.5° , from 3.0° to 29.0° , from 3.5° to 28.5° , from 4.0° to 28.0° , from 4.5° to 27.5° , from 5.0° to 27° , from 5.5° to 26.5° , from 6.0° to 26.0° , from 6.5° to 25.5° , from 7.0° to 25.0° , from 7.5° to 24.5° , from 8.0° to 24.0° , from 8.5° to 23.5° , from 9.0° to 23.0° , from 9.5° to 22.5° , from 10.0° to 22.0° , from 10.5° to 21.5° , from 11.0° to 21.0° , from 11.5° to 20.5° , from 12.0° to 20.0° , from 12.5° to 19.5° , from 13.0° to 19.0° , from 13.5° to 18.5° , from 14.0° to 18.0° , from 14.5° to 17.5° , from 15.0° to 17.0° , from 15.5° to 16.5° , from 16.0° to 16.0° , from 16.5° to 15.5° , from 17.0° to 14.5° , or any range therein in increments of 0.1° . In some embodiments, each of Θ_T , Θ_B , Θ_{FS} , and Θ_{SS} can be independently selected and each can be about 1° , 2° , 3° , 4° , 5° , 6° , 7° , 8° , 9° , 10° , 11° , 12° , 13° , 14° , 15° , 16° , 17° , 18° , 19° ,

27

20°, 21°, 22°, 23°, 24°, 25°, 26°, 27°, 28°, 29°, 30°, 31°, 32°, 33°, 34°, 35°, or any angle therein in increments of 0.1°.

It should be appreciated that the beams can each be independently designed to have its own, independently selected curvature, whether convex or concave, and the curvatures can be the same or different between beams that share a face of the frame. And, the curvatures can be opposing for beams that form opposing faces of the frame. Moreover, the frame can have a mixture of one or more straight and one or more curved beams.

Given the above, it should be appreciated that the frames can be designed according to nearly any opening bordered by the top vertebral endplate and bottom vertebral endplate of an intervertebral space, as well as according to a given clinical treatment regardless of the opening dimensions prior to treatment. In some embodiments, the top face of the frame can be at least substantially parallel to the bottom face of the frame, whereas the first side face of the frame and the second side face of the frame can be oriented at angles Θ_T and Θ_B , wherein Θ_T and Θ_B can be independently selected to be the same or different. Likewise, in some embodiments, the first side face of the frame can be at least substantially parallel to the second side face of the frame, whereas the top face of the frame and the bottom face of the frame can be oriented at angles Θ_{FS} and Θ_{SS} , wherein Θ_{FS} and Θ_{SS} can be independently selected to be the same or different. In some embodiments, each of Θ_T , Θ_B , Θ_{FS} , and Θ_{SS} can be independently selected to range from about 5° to about 32°, from about 7° to about 22°, and from about 8° to about 16°, in some embodiments. As such, any of a variety of frames can be constructed from any of a variety of quadrilateral structures having the angles taught herein.

One of skill will appreciate that the teachings provided herein are directed to basic concepts that can extend beyond any particular embodiment, embodiments, figure, or figures. It should be appreciated that any examples are for purposes of illustration and are not to be construed as otherwise limiting to the teachings. For example, it should be appreciated that the devices provided herein can also be used as implants in other areas of the body. The devices provided herein can be used, for example, in intravertebral body procedures to support or distract intervertebral bodies in the repair of, for example, collapsed, damaged or unstable vertebral bodies suffering from disease or injury.

We claim:

1. An expansion member for distributing graft material through an expandable cage and into an intervertebral space between a top vertebral plate and a bottom vertebral plate, the expansion member comprising:

a central beam with a central beam axis, the central beam having a graft distribution channel with an entry port in fluid communication with an exit port;

wherein the central beam is configured for insertion into the expandable cage to form a graft distribution system within the intervertebral space; and

wherein the central beam is configured to expand the expandable cage during insertion of the central beam into the expandable cage.

2. The expansion member of claim 1, wherein the entry port is in fluid communication with a top exit port and a bottom exit port.

3. The expansion member of claim 1, wherein the central beam further comprises a side graft port.

4. The expansion member of claim 1, the central beam having a transverse cross-section having a maximum dimension ranging from 5 mm to 15 mm, the transverse cross-section configured for placing the central beam into an

28

intervertebral space through an annular opening having a maximum lateral dimension ranging from 5 mm to 15 mm.

5. The expansion member of claim 1, wherein the expandable cage expands laterovertically, and the central beam has a lateral dimension that expands the cage laterally beyond the lateral dimension of an annular opening into the intervertebral space to avoid back-out.

6. The expansion member of claim 1, the central beam having a configuration that is complementary to the expandable cage.

7. The expansion member of claim 1, the central beam having an I-beam configuration.

8. The expansion member of claim 1, the expandable cage having a collapsed state and an expanded state, the central beam having a configuration that passes graft material through a graft distribution window in the expandable cage, the graft distribution window being at least substantially closed in the collapsed state and opening upon an expansion of the expandable cage.

9. The expansion member of claim 1, the central beam having a configuration that passes graft material through a graft distribution window that opens in each wall of the expandable cage upon expansion of the expandable cage.

10. The expansion member of claim 1, the central beam having a configuration wherein the exit port is aligned with a graft distribution window created in the expandable cage after insertion of the central beam into the expandable cage.

11. A method of distributing graft material through an expandable cage and into an intervertebral space between a top vertebral plate and a bottom vertebral plate, the expandable cage having a collapsed state and an expanded state, the method comprising:

inserting the expandable cage into the intervertebral space in the collapsed state;

inserting a central beam into the expandable cage, the central beam having a central beam axis and a graft distribution channel with an entry port in fluid communication with an exit port, wherein the central beam is configured for insertion into the expandable cage to form a graft distribution system within the intervertebral space, and wherein the central beam is configured to expand the expandable cage during insertion of the central beam into the expandable cage; and

thereafter distributing the graft material into the intervertebral space through the central beam.

12. The method of claim 11, wherein the expanding includes expanding the expandable cage into the intervertebral space in stages, the expanding including

expanding the expandable cage laterally in the intervertebral space; and,

expanding the expandable cage vertically in the intervertebral space.

13. The method of claim 12, wherein the expanding laterally occurs independent of the expanding vertically.

14. The method of claim 11, wherein

the inserting of the expandable cage into the intervertebral space is through an annular opening having a width; and

the expanding of the expandable cage laterally in the intervertebral space includes expanding the expandable cage to a width that exceeds the width of the annular opening to avoid backout.

15. The method of claim 11, the expandable cage having a collapsed state and an expanded state, the central beam having a configuration that passes graft material through a graft distribution window in the cage, the graft distribution

29

window being at least substantially closed in the collapsed state and opening upon an expansion of the expandable cage.

16. The method of claim 11, wherein the expanding opens a graft distribution window in each wall of the expandable cage, and the distributing of the graft material occurs through each wall of the expandable cage. 5

17. The method of claim 11, wherein the distributing of the graft material reduces the formation of pockets in the intervertebral space that are not filled with the graft material.

18. The method of claim 11, wherein:

the expandable cage has a top comprising a first top beam and a second top beam, a bottom comprising a first bottom beam and a second bottom beam, a first side comprising the first top beam and the first bottom beam, and a second side comprising the second top beam and the second bottom beam; and

the expanding further comprises expanding the first top beam and the first bottom beam to form an angle Θ_{FS} ,

30

the second top beam and the second bottom beam to form an angle Θ_{SS} , and each of Θ_{FS} and Θ_{SS} are independently selected as something other than 0° , such that (i) the first top beam and the first bottom beam or (ii) the second top beam and the second bottom beam, are not substantially parallel in the expanded state.

19. The method of claim 18, further comprising selecting

Θ_{FS} and Θ_{SS} to each independently range from about 0.5° to 31.5° . 10

20. The method of claim 18, further comprising selecting

Θ_{FS} and Θ_{SS} to each independently be about 1° , 2° , 3° , 4° , 5° , 6° , 7° , 8° , 9° , 10° , 11° , 12° , 13° , 14° , 15° , 16° , 17° , 18° , 19° , 20° , 21° , 22° , 23° , 24° , 25° , 26° , 27° , 28° , 29° , 30° , 31° , 32° , 33° , 34° , 35° , or any angle therein in increments of 0.1° . 15

* * * * *