

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12390988
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Song; Sung-eun et al.

3D printer

Abstract

A 3D printer according to an embodiment of the disclosure includes: a resin tank accommodating a resin material; a molding plate movable up and down in the resin tank, and supporting a printed object formed by stacking a plurality of unit forming layers in sequence; an up-and-down movement actuator actuating at least one of the resin tank and the molding plate to move up and down; an exposure unit emitting light toward the molding plate; and a lens sheet including a first material layer including a molding surface facing the molding plate and a light receiving surface facing the exposure unit, disposed between the molding plate and the exposure unit, formed with a plurality of fine lens units for converging and diffusing the light from the exposure unit on one surface, and having a high refractive index, and a second material layer including a concavo-convex portion to be engaged with the fine lens unit of the first material layer, and having a low refractive index.

Inventors:	Song; Sung-eun (Seoul, KR), Cho; Hyeon-soo (Seoul, KR), Lee; Kwang-min (Seoul, KR)
Applicant:	CARIMA CO., LTD. (Seoul, KR)
Family ID:	1000008767968
Assignee:	CARIMA CO., LTD. (Seoul, KR)
Appl. No.:	17/799116
Filed (or PCT Filed):	February 05, 2021
PCT No.:	PCT/KR2021/001585
PCT Pub. No.:	WO2021/162365
PCT Pub. Date:	August 19, 2021

Prior Publication Data

Foreign Application Priority Data

KR	10-2020-0016265	Feb. 11, 2020
KR	10-2021-0012881	Jan. 29, 2021

Publication Classification

Int. Cl.: **B29C64/264** (20170101); **B29C64/135** (20170101); **B29C64/232** (20170101); **B29C64/245** (20170101); **B29C64/255** (20170101); B33Y10/00 (20150101); B33Y30/00 (20150101)

U.S. Cl.:

CPC **B29C64/135** (20170801); **B29C64/232** (20170801); **B29C64/245** (20170801); **B29C64/255** (20170801); **B29C64/264** (20170801); B33Y10/00 (20141201); B33Y30/00 (20141201)

Field of Classification Search

CPC: B29C (64/264)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3706486	12/1971	de Montebello	359/620	G03B 35/24
2008/0174877	12/2007	Chung	N/A	N/A
2010/0320648	12/2009	Jamar	264/401	B29C 64/129
2012/0057143	12/2011	Jamar	355/67	G03F 7/70391
2013/0295215	12/2012	Wu	425/174.4	B29C 64/112
2018/0126663	12/2017	Jun et al.	N/A	N/A
2019/0111622	12/2018	Khalip	N/A	B29C 64/268

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
110524874	12/2018	CN	B29C 64/129
2015-171820	12/2014	JP	N/A
10-0841438	12/2007	KR	N/A
10-2011-0053010	12/2010	KR	N/A
10-2016-0113062	12/2015	KR	N/A
2006/074812	12/2005	WO	N/A

OTHER PUBLICATIONS

Machine translation of CN 110524874, retrieved from USPTO database Jun. 21, 2024 (Year: 2024). cited by examiner

International Search Report for PCT/KR2021/001585 dated Jul. 26, 2021. cited by applicant

Korean Office Action for Korean Application No. 10-2021-0012881 dated Sep. 13, 2021, 8 pages. cited by applicant

Primary Examiner: Kennedy; Timothy

Attorney, Agent or Firm: Sughrue Mion, PLLC

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This application is a National Stage of International Application No. PCT/KR2021/001585 filed Feb. 5, 2021, claiming priority based on Korean Patent Application No. 10-2020-0016265 filed Feb. 11, 2020 and Korean Patent Application No. 10-2021-0012881 filed Jan. 29, 2021.

TECHNICAL FIELD

(2) The disclosure relates to a 3D printer, and more particularly to a 3D printer which can form a printed object as a photocurable resin material is additively constructed through exposure and curing.

BACKGROUND ART

(3) A digital light processing (DLP) type 3D printer constructs a desired 3D printed object by curing a photocurable resin material on a molding surface in a resin tank storing the resin material, and additively constructing the resin material in sequence on a molding plate. The 3D printer needs a process of separating the 3D printed object cured and additively constructed on the molding plate from the molding surface in order to additively construct the next unit forming layer every time when the unit forming layer is additively constructed on the molding plate.

(4) Although a continuous additive-construction method is used instead of an intermittent additive-construction method by which every unit forming layer is completely separated and additively constructed, a space is required for the construction to fill the resin material between the molding surface and the molding plate.

(5) Further, it is relatively easy to separate the 3D printed object from the cured surface when the surface area of the cured unit forming layer is small, but it is not easy to separate the 3D printed object when the surface area of the cured unit forming layer is large.

(6) As a method of improving this, oxygen or a release agent may for example be used in separating the printed object from the molding surface. However, in the case of using oxygen or the release agent, sloshing occurs when the molding plate moves up and down with respect to the resin tank, and thus there are problems in that the speed of printing is very slow because the printing should be carried out after the sloshing is stabilized, and the printing has poor quality when the speed of printing is increased.

DISCLOSURE

Technical Problem

(7) Accordingly, an aspect of the disclosure is to provide a 3D printer which can improve the quality of printing while increasing the speed of printing.

Technical Solution

(8) According to an embodiment of the disclosure, 3D printer includes: a resin tank accommodating

a resin material; a molding plate movable up and down in the resin tank, and supporting a printed object formed by stacking a plurality of unit forming layers in sequence; an up-and-down movement actuator actuating at least one of the resin tank and the molding plate to move up and down; an exposure unit emitting light toward the molding plate; and a lens sheet including a first material layer including a molding surface facing the molding plate and a light receiving surface facing the exposure unit, disposed between the molding plate and the exposure unit, formed with a plurality of fine lens units for converging and diffusing the light from the exposure unit on one surface, and having a high refractive index, and a second material layer including a concavo-convex portion to be engaged with the fine lens unit of the first material layer, and having a low refractive index.

(9) The fine lens unit may be formed to make the light formed on the molding surface have an area within a predefined range.

(10) The fine lens unit may protrude being shaped like a convex lens on one surface of the first material layer.

(11) According to an embodiment of the disclosure, the 3D printer further includes a controller configured to: control the exposure unit to emit light corresponding to an image of the unit forming layer, and control the up-and-down movement actuator to move the molding plate up to be spaced apart from the lens unit while the exposure unit emits light.

(12) According to an embodiment of the disclosure, a method of manufacturing a lens sheet for minimizing a curing surface area of a unit forming layer includes: forming a second material layer with a concavo-convex portion by pressing a sheet against a mold on which a plurality of fine lens patterns is embossed; preparing a transparent material by mixing a coating agent and a curing agent; and forming a first material layer with a fine lens unit by evenly applying the mixed transparent material to the concavo-convex portion of the second material layer and curing the applied mixed transparent material

(13) According to an embodiment of the disclosure, a method of manufacturing a lens sheet for minimizing a curing surface area of a unit forming layer includes: forming a first material layer with a fine lens unit by pressing a sheet against a mold on which a plurality of fine lens patterns is engraved; preparing a transparent material by mixing a coating agent and a curing agent; and forming a second material layer with a concavo-convex portion by evenly applying the mixed transparent material to the fine lens unit of the first material layer and curing the applied mixed transparent material.

Advantageous Effects

(14) According to the disclosure, light from an exposure unit is refracted by a lens sheet to have the minimum area on a molding surface, thereby improving the quality of printing while increasing the speed of printing.

Description

DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a view for explaining a 3D printer according to an embodiment of the disclosure.

(2) FIG. 2 is a view for explaining a lens sheet according to an embodiment of the disclosure.

(3) FIG. 3 is a view for explaining a lens sheet according to another embodiment of the disclosure.

(4) FIG. 4 is a view showing an operation of a 3D printer according to an embodiment of the disclosure.

(5) FIG. 5 is a scanning electron microscope (SEM) image of a printed object additively constructed by a 3D printer according to an embodiment of the disclosure.

(6) FIG. 6 is a control block diagram of a 3D printer according to the disclosure.

(7) FIG. 7 is a flowchart showing a method of manufacturing a lens sheet according to an

embodiment of the disclosure.

MODE FOR INVENTION

(8) Below, a 3D printer **1** according to embodiments of the disclosure will be described in detail with reference to the accompanying drawings.

(9) FIG. **1** is a view for explaining a 3D printer according to an embodiment of the disclosure.

(10) The 3D printer **1** includes a resin tank **10**, a molding plate **20**, an up-and-down movement actuator **30**, an exposure unit **40**, a lens sheet **50**, and a controller **60**.

(11) The disclosure will be described based on a bottom-up 3D printer **1** in which additive construction is performed while the molding plate **20** is moving up in the resin tank **10** as shown in FIG. **1**, but may also be applied to a top-down 3D printer in which additive construction is performed while the molding plate is moving down. Likewise, the disclosure will be described based on a resin tank type, but is not limited to the 3D printer **1** of the resin tank type.

(12) The resin tank **10** stores a photocurable resin material, and has an opened top and a transparent bottom. In this case, the resin tank **10** is divided into an upper frame and a lower frame as shown in FIG. **1**, in which the upper frame is coupled to the lens sheet **50** to form a storage space for accommodating the resin material, and the lower frame is coupled to and support it. In this case, a protrusion may be formed on the bottom of the upper frame in order to easily fix the lens sheet **50**, and the protrusion has an effect on increasing tension on the surface of the lens sheet **50** made of a material having an elongation rate.

(13) In the case of using a structure in which the resin tank **10** is divided into the upper frame and the lower frame, a sealing material may be added to prevent the resin material accommodated in the resin tank **10** from leaking out.

(14) However, the resin tank **10** is not limited to this structure, but may have various structures. For example, the resin tank may be shaped like an integrated tank having a transparent bottom and the lens sheet **50** is coated or put on the bottom.

(15) The molding plate **20** is movable up and down inside the resin tank **10** by the up-and-down movement actuator **30**, and is shaped like a plate to support a printed object **2** printed as a plurality of unit forming layers **2-1** is gradually and additively constructed.

(16) The up-and-down movement actuator **30** makes at least one of the resin tank **10** and the molding plate **20** move up and down. The up-and-down movement actuator **30** includes an elevating rail, and an elevating motor for moving the elevating rail up and down. The elevating rail is coupled supporting at least one of the resin tank **10** and the molding plate **20**.

(17) The exposure unit **40** is disposed under the resin tank **10** and emits ultraviolet light for curing the photocurable resin material in an upward direction toward a light receiving surface of the lens sheet **50**.

(18) The lens sheet **50** is disposed between the molding plate **20** and the exposure unit **40**, and the light emitted from the exposure unit **40** passes through the lens sheet **50** and cures the resin material on the molding surface. In this case, the lens sheet **50** refracts the light emitted from the exposure unit **40** so as to minimize an exposure area where the cured resin material is in contact with the molding surface of the lens sheet **50**, thereby guiding the unit forming layers **2-1** to be exposed to the light in an additive constructing direction. More detailed descriptions about the lens sheet **50** will be made with reference to FIGS. **2** and **3**.

(19) The controller **60** controls the exposure unit **40** to emit light corresponding to an image of the unit forming layer **2-1**, and controls the up-and-down movement actuator **30** to move the molding plate **20** up to be spaced apart from the lens sheet **50**. The controller **60** may control the exposure unit **40** and the up-and-down movement actuator **30** sequentially or simultaneously according to constructing methods of the 3D printer **1**.

(20) FIG. **2** is a view for explaining a lens sheet according to an embodiment of the disclosure.

(21) FIG. **2** shows a first lens sheet **51** as an example of the lens sheet **50** of FIG. **1**. The first lens sheet **51** is based on combination of a first material layer **511** having a high refractive index and a

second material layer **512** having a low refractive index, which are made of different materials. The first lens sheet **51** has the molding surface facing the molding plate **20** and the light receiving surface facing the exposure unit **40**.

(22) The first material layer **511** of the first lens sheet **51** includes a plurality of fine lens units formed on the molding surface and converging and diffusing the light emitted from the exposure unit **40**. The second material layer **512** of the first lens sheet **51** includes a concavo-convex portion to be engaged with the fine lens units formed on the first material layer **511**.

(23) The controller **60** controls the exposure unit **40** to emit light corresponding to an image of each unit forming layer **2-1**, and the emitted light passes through the first lens sheet **51** and cures the resin material on the molding surface.

(24) Here, the travel path of the emitted light in the first lens sheet **51** will be described. The light emitted from the exposure unit **40** passes through the fine lens units of the first material layer **511** via the light receiving surface of the first lens sheet **51**, and is refracted by difference in the refractive index between the first material layer **511** and the second material layer **512** while entering the second material layer **512**. The refracted light converges and diffuses on the molding surface of the first lens sheet **51**. The diffused light has an inverted pyramid shape as shown therein, and the resin material in the resin tank **10** is cured along the inverted pyramid shape. In the first lens sheet **51**, the first material layer **511** has a higher refractive index than the second material layer **512**.

(25) Therefore, the fine lens unit of the first material layer **511** protrudes from the surface of the first material layer **511** while being shaped like a convex lens so as to serve as the convex lens.

(26) The light refracted in the fine lens unit converges and diffuses on the molding surface. At this time, the surface area of the resin to be cured is varied depending on the surface area of the light formed on the molding surface, and it is therefore preferable that the vertex of the inverted pyramid is cured on the molding surface in order to minimize the surface area of the resin to be adhered to the molding surface. However, the fine lens unit according to the disclosure is formed to make the area of the light formed on the molding surface be within a predefined range even though some errors may occur due to the difference in the refractive index between the second material layer **512** and the first material layer **511**, the lens curvature of the fine lens unit, etc.

(27) On the other hand, the second material layer **512** includes the concavo-convex portion formed having recessed shapes and engaged with the fine lens units formed on the first material layer **511**. One of the first material layer **511** or the second material layer **512** has physical properties to minimize deformation due to external force. For example, the first material layer **511** may be thicker **10** times than the second material layer **512**, and may be made of a material having low strain per unit area. As the first material layer **511** and the second material layer **512** are engaged with and coupled to each other, the fine lens units are less deformed even though the molding plate **20** is moved during a printing process, and thus stable printing is possible.

(28) Unlike a manner in which one surface of the unit forming layer is cured having the same shape on the molding surface, a manner according to the disclosure in which the exposure is performed in the form of the inverted pyramid minimizes the area of the cured surface of the resin material being in contact with the molding surface into an area corresponding to the vertex of the inverted pyramid, thereby making it easy to separate the printed object from the molding surface, minimizing a phenomenon that the first lens sheet **51** is partially lifted, and minimizing the shaking of the resin tank **10** even though the molding plate **20** is moved up and down. As the shaking of the resin tank **10** is minimized, shock or vibration is significantly reduced while the printed object is additively constructed and the molding plate **20** is moved up and down, thereby increasing the quality of the printed object.

(29) Further, the first lens sheet **51** is formed by completely coupling the first material layer **511** and the second material layer **512**, and it is therefore possible to prevent the fine lens units of the first material layer **511** from being deformed even when the first lens sheet **51** is partially lifted as

the printed object is adhered to the first lens sheet **51** when the molding plate **20** is moved up and down, thereby minimizing change in the travel path of the light. Thus, focal distances at which the light passing through the fine lens units converges are uniformly maintained, thereby carrying out stable printing, preventing non-uniform printing due to different points in time at which proper exposure is completed, and improving printing quality.

(30) FIG. **3** is a view for explaining a lens sheet according to another embodiment of the disclosure. FIG. **3** shows a second lens sheet **52** as an alternative example to the lens sheet **50** of FIG. **1**. In FIG. **3**, descriptions will be made focusing difference from FIG. **2**.

(31) FIG. **2** shows that the fine lens units of the first material layer **511** are convexly formed facing upward, and the second material layer **512** is formed on the first material layer **511**. Likewise, FIG. **3** shows that the second lens sheet **52** is based on combination of a first material layer **521** having a high refractive index and a second material layer **522** having a low refractive index, but the fine lens units of the first material layer **521** are convexly formed facing downward and the second material layer **522** is formed beneath the first material layer **521** unlike the first lens sheet **51**. Like the first lens sheet **51**, the second material layer **522** of the second lens sheet **52** includes a concavo-convex portion having a recessed shape and engaged with the fine lens units of the first material layer **521**.

(32) Two travel paths of the light passing through the first and second lens sheets **51** and **52** respectively shown in FIGS. **2** and **3** are consequently the same, thereby having the same effect. However, the travel paths may be varied depending on the refractive indexes of the materials of the first material layers **511** and **521** and the second material layers **512** and **522**.

(33) Below, the travel path of the emitted light in the second lens sheet **52** shown in FIG. **3** will be described. The light emitted from the exposure unit **40** passes through the second material layer **512**, and is refracted by difference in the refractive index between the second material layer **522** and the first material layer **521** while entering the fine lens units of the first material layer **521**. The refracted light converges and diffuses on the molding surface of the second lens sheet **52**. The diffused light has an inverted pyramid shape as shown therein, and the resin material in the resin tank **10** is cured along the inverted pyramid shape. In the first lens sheet **51**, the first material layer **511** has a higher refractive index than the second material layer **512**.

(34) Therefore, the fine lens unit of the first material layer **521** protrudes from the surface of the first material layer **521** while being shaped like a convex lens so as to serve as the convex lens. Likewise, the first material layer **521** has a higher refractive index than the second material layer **522**.

(35) According to an embodiment of the disclosure, sheets different in material from each other are used to form the fine lens units, and therefore the structure of the lens sheet is not limited so that the second lens sheet **52** can serve as a lens according to the materials for the sheets and have the effects according to the disclosure.

(36) FIG. **4** is a view showing an operation of a 3D printer according to an embodiment of the disclosure.

(37) Referring to (a) of FIG. **4**, the light emitted from the exposure unit **40** is refracted by the fine lens units of the lens sheet **50** and illuminates the molding plate **20**. In this case, the light refracted by the plurality of fine lens units has the minimum area on the molding surface of the lens sheet **50** and is then refracted to become wider, thereby illuminating the resin material disposed between the molding plate **20** and the molding surface.

(38) Referring to (b) of FIG. **4**, when the molding plate **20** is moved up by the up-and-down movement actuator **30** while the light is being emitted from the exposure unit **40** toward the molding plate **20**, the photocurable resin material is continuously filled between the molding surface of the lens sheet **50** and the molding plate **20**, thereby continuously and additively constructing the unit forming layers **2-1**. Because the molding plate **20** moves up while the light is emitted in the form of the inverted pyramid, a plurality of inverted pyramid layers are continuously

stacked to overlap in such manner that one inverted pyramid layer is partially cured and then an upper layer is additionally cured while the next inverted pyramid layer is partially cured in succession.

(39) With the foregoing 3D printer **1**, the light emitted from the exposure unit **40** is refracted by the lens sheet **50** and performs curing while forming the minimum area on the molding surface of the lens sheet **50**, so that the unit printed object cured as the molding plate moves up can have the minimum resistance to release. Therefore, according to the disclosure, a 3D printed object with high quality is continuously and rapidly manufactured without interruption even though special mechanical solutions are not used.

(40) FIG. **5** is a scanning electron microscope (SEM) image of a printed object additively constructed by a 3D printer according to an embodiment of the disclosure. As described above with reference to FIGS. **2** to **4**, the light emitted from the exposure unit **40** is refracted while passing through the lens sheet **50**, and converges and diffuses on the molding surface of the lens sheet **50**. The light is diffused in the form of the inverted pyramid, and the resin material in the resin tank **10** is cured along the shapes of the diffused light. Therefore, the unit forming layers **2-1** are cured in the form of the inverted pyramid and additively constructed, and the SEM image obtained by photographing the surface of the printed object showed that the unit forming layers were stacked as described above.

(41) FIG. **6** is a control block diagram of a 3D printer according to the disclosure. The controller **60** controls the exposure unit **40** to emit light corresponding to an image of each unit forming layer based on image data obtained by dividing the printed object into the unit forming layers, and controls the up-and-down movement actuator **30** to move the molding plate **20** up or down.

(42) FIG. **7** is a flowchart showing a method of manufacturing the first lens sheet **51** shown in FIG. **2** and the second lens sheet **52** shown in FIG. **3**.

(43) According to an embodiment of the disclosure, the second material layer **512** of FIG. **2** or the first material layer **521** of FIG. **3** is formed by pressing a sheet against a mold formed with a plurality of fine lens patterns (**S710**).

(44) The sheet refers to a film having an elongation rate and made of a material easily formed when pressed against a mold, and the material may have high releasability when forming the molding surface like one surface of the second material layer **512** of FIG. **2** or one surface of the first material layer **521** of FIG. **3**. Further, the sheet needs to have properties that transmits light well. For example, the sheet may include fluorinated ethylene propylene (FEP), perfluoroalkoxy alkanes (PFA), ethylene tetra fluoro ethylene (ETFE), poly tetra fluoro ethylene (PTFE), etc.

(45) The mold may be made of nickel or the like metal material, and the plurality of fine lens patterns are engraved or embossed thereon. For example, when the sheet is pressed against the embossed mold, the concavo-convex portion is engraved like the second material layer **512** as shown in FIG. **2**.

(46) Further, when the sheet is pressed against the engraved mold, the concavo-convex portion is embossed like the first material layer **521** as shown in FIG. **3**. Meanwhile, like the first material layer **521** of FIG. **3** may be made of a material excellent in releasability. Alternatively, a third material layer (not shown) excellent in releasability may be formed on the molding surface of the first material layer **521**.

(47) The sheet may have a thickness of 200 μm to 500 μm . When the thickness of the sheet is smaller than 200 μm , the sheet is likely to tear or is not properly formed with the fine lens units when the sheet is pressed against the mold. When the thickness of the sheet is greater than 500 μm , the focal distance is so long that the light cannot reach the molding surface, and it is difficult to expect the effects according to the disclosure.

(48) According to an embodiment of the disclosure, a transparent material is prepared by mixing a curing agent with a coating agent (**S720**).

(49) The coating agent is made of a silicone material, and its fluidity is controllable so that the

coating agent itself or the coating agent mixed into the transparent material can have fluidity, thereby being cured after a predetermined period of time elapses after being coated on the sheet. Silicone oil (polymeric organosilicon compounds) of polydimethylsiloxane (PDMS) may be representatively used as the coating agent, and may be replaced with any material as long as it is a transparent and inert material among silicon-based organic polymers. The curing agent helps the transparent material to be more easily cured when applied to the sheet.

(50) Further, the refractive index of the transparent material may be adjusted according to ratios of the coating agent and the curing agent. According to the disclosure, the fine lens units are formed on a layer having a higher refractive index. Therefore, the transparent material is used as materials for the first material layer **511** of FIG. 2 and the second material layer **522** of FIG. 3, and its refractive index needs to be appropriately adjusted according to the materials.

(51) In this case, a vacuum defoamer may be used to remove air bubbles from the transparent material so that the transparent material can be completely coupled without any space between the layer having the fine lens unit and the layer having the concavo-convex portion

(52) According to an embodiment of the disclosure, the mixed transparent material is evenly applied to the concavo-convex portion of the second material layer **512** of FIG. 2 or the fine lens unit of the first material layer **521** of FIG. 3, and then cured, thereby forming the first lens sheet **51** or the second lens sheet **52** (**S730**).

(53) In FIG. 2, the transparent material is applied to the concavo-convex portion of the second material layer **512**. In FIG. 3, the transparent material is applied to the fine lens unit of the first material layer **521**.

(54) After applying the transparent material, the transparent material is cured at room temperature for 1 to 2 days. The transparent material holds and supports the plurality of fine lens patterns formed in the sheet, thereby minimizing vibration, damage, focus shifting, etc., which may occur during a 3D printing process.

(55) Referring to the 3D printer **1** shown in FIG. 2, the first lens sheet **51** is formed by combination of the second material layer **512** formed with the engraved concavo-convex portion by pressing the sheet against the mold, and the first material layer **511** formed with the fine lens unit by evenly applying the transparent material to the concavo-convex portion.

(56) In FIG. 2, the first material layer **511** serves as a lens in the first lens sheet **51**, and the first material layer **511** has a higher refractive index than the second material layer **512**, so that the light can be refracted in the fine lens unit of the first material layer **511** and converge on the molding surface of the second material layer **512**.

(57) Likewise, referring to the 3D printer **1** shown in FIG. 3, the second lens sheet **52** is formed by combination of the first material layer **521** formed with the embossed fine lens unit by pressing the sheet against the mold, and the second material layer **522** formed with the concavo-convex portion by evenly applying the transparent material to the fine lens unit.

(58) In FIG. 3, the first material layer **521** serves as a lens in the second lens sheet **52**, and the first material layer **521** has a higher refractive index than the second material layer **522**, so that the light can be refracted in the fine lens unit of the first material layer **521** and converge on the molding surface of the first material layer **521**.

Claims

1. A 3D printer comprising: a resin tank accommodating a resin material; a molding plate movable up and down in the resin tank, and supporting a printed object formed by stacking a plurality of unit forming layers in sequence; an up-and-down movement actuator actuating at least one of the resin tank and the molding plate to move up and down; an exposure unit emitting light toward the molding plate; and a lens sheet comprising: a first material layer comprising a molding surface facing the molding plate and a light receiving surface facing the exposure unit, disposed between

the molding plate and the exposure unit, formed with a plurality of fine lens units for converging and diffusing the light from the exposure unit on one surface, and a second material layer comprising a concavo-convex portion to be engaged with the fine lens unit of the first material layer, wherein the first material layer has a higher refractive index than the second material layer, wherein the first material layer is thicker than the second material layer, and wherein in a state in which an external force is applied to at least of the first material layer or the second material layer, the first material layer is that is less deformable than the second material layer.

2. The 3D printer of claim 1, wherein the plurality of fine lens units is formed to make the light formed on the molding surface have an area within a predefined range such that an area of the molding surface, of which the light is formed, is minimized.

3. The 3D printer of claim 1, wherein the plurality of fine lens units protrude from one surface of the first material layer and are shaped like a convex lens.

4. The 3D printer of claim 1, further comprising a controller configured to: control the exposure unit to emit light corresponding to an image of the unit forming layer, and control the up-and-down movement actuator to move the molding plate up to be spaced apart from the lens unit while the exposure unit emits light.

5. The 3D printer of claim 1, wherein the wherein the first material layer is ten times thicker than the second material layer.
