

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12394319
Kind Code	B1
Date of Patent	August 19, 2025
Inventor(s)	Salman; Salman

Airport management system with gate performance UI and related methods

Abstract

An airport management system is for an airport with gates. The airport management system includes a server, and image sensors respectively at the gates. Each image sensor is configured to generate image data for an apron of a respective gate. The server is configured to receive the image data from each of the image sensors, detect objects and apron events within the apron of the respective gate based upon a machine learning model, and generate a gate performance UI for viewing the detected objects and the detected apron events. The gate performance UI includes a timeline menu of the detected apron events for each respective gate.

Inventors:	Salman; Salman (Coral Gables, FL)
Applicant:	Synaptic Aviation Inc. (Coral Gables, FL)
Family ID:	1000006768132
Assignee:	SYNAPTIC AVIATION INC. (Coral Gables, FL)
Appl. No.:	18/049467
Filed:	October 25, 2022

Publication Classification

Int. Cl.: G08G5/22 (20250101); G06F3/0482 (20130101); G06V10/25 (20220101); G06V10/70 (20220101); G06V20/54 (20220101); G08G5/51 (20250101)

U.S. Cl.:

CPC G08G5/22 (20250101); G06F3/0482 (20130101); G06V10/25 (20220101); G06V10/70 (20220101); G06V20/54 (20220101); G08G5/51 (20250101);

Field of Classification Search

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6542086	12/2002	Baumgartner et al.	N/A	N/A
9862501	12/2017	Small et al.	N/A	N/A
9934693	12/2017	Joyson et al.	N/A	N/A
9950812	12/2017	Agrawal	N/A	N/A
10296860	12/2018	Agrawal et al.	N/A	N/A
10592749	12/2019	Coppock et al.	N/A	N/A
11006078	12/2020	Patel et al.	N/A	N/A
11142306	12/2020	Cox et al.	N/A	N/A
11151491	12/2020	Basanets et al.	N/A	N/A
2012/0194358	12/2011	Alon	340/945	G08G 5/0026
2013/0329052	12/2012	Chew	348/159	G08G 5/51
2018/0012499	12/2017	Madhusudan	N/A	G08G 5/727
2020/0377232	12/2019	Gonzalez Parra et al.	N/A	N/A
2022/0172592	12/2021	Hough	N/A	G06V 20/40

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
110807525	12/2019	CN	G06N 3/0454
WO2019186594	12/2018	WO	N/A

OTHER PUBLICATIONS

Lu, et al., Airport Gate Operation Monitoring Using Computer Vision Techniques, 16th AIAA Aviation Technology, Integration, and Operations Conference, p. 3912 (2016) (Year: 2016). cited by examiner

Primary Examiner: Guiliano; Charles

Attorney, Agent or Firm: Allen, Dyer, Doppelt + Gilchrist, PA

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates to the field of airport monitoring, and, more particularly, to an airport management system for gate performance and related methods.

BACKGROUND

(2) Airports are critical hubs for transportation in modern society. Indeed, every airport comprises many entities working together to receive and process aircraft. Pre-COVID, there were annually over 40 million flights worldwide. Due to the scale of the effort, there is a desire to enhance time efficiency throughout the airport. Of course, there is also a wide range of regulatory rules that must be adhered to for maintaining safe air service. For airline operators, this is a delicate balance since safety cannot be compromised, and the typical customer is notoriously price sensitive.

(3) In early approaches, statistics for flight performance were cataloged manually. For example, the data would indicate that a certain percentage of flights were late for a gate, but there would be no context for why the delays occurred. Moreover, these approaches may provide no input on compliance with required procedure, for example, required foreign object debris (FOD) walks.

SUMMARY

(4) Generally, an airport management system is for an airport with a plurality of gates. The airport management system comprises a server, and a plurality of image sensors respectively at the plurality of gates. Each image sensor is configured to generate image data for an apron of a respective gate. The server is configured to receive the image data from each of the plurality of image sensors, detect a plurality of objects and a plurality of apron events associated therewith and within the apron of the respective gate based upon a machine learning model, and generate a gate performance user interface (UI) for viewing the detected plurality of objects and the detected plurality of apron events. The gate performance UI comprises a timeline menu of the detected plurality of apron events for each respective gate.

(5) More specifically, the gate performance UI may comprise a video menu, and the server may be configured to, when a given detected apron event is selected in the timeline menu, generate the video menu to comprise a video associated with the given detected apron event. The video menu may comprise a plurality of boundary boxes respectively over the detected plurality of objects in the video associated with the given detected apron event, and a plurality of confidence values respectively for the plurality of boundary boxes.

(6) Also, the timeline menu may comprise a duration indicator for each of the detected plurality of apron events. The server may be configured to generate an airport performance UI for viewing the detected plurality of objects and the detected plurality of apron events for the plurality of gates. The airport performance UI may include a gate performance menu comprising, for each gate, a number and a length of air traffic holdouts, a number of early arrivals, a passenger loading bridge extension delay, and a gate utilization metric. The airport performance UI may comprise a dashboard menu comprising a number of flights for the airport, an average turn time for the airport, a gate utilization metric, and an on-time arrival metric.

(7) The airport performance UI may comprise an event performance menu comprising average time durations for each type of detected apron events. The airport performance UI may comprise a compliance menu comprising compliance metrics for a plurality of user-defined safety rules for the plurality of gates. The detected plurality of apron events may include a Foreign Object Debris (FOD) walk, a ground power unit connection, a fuel hose connection, a belt loader connection, a passenger loading bridge connection, and a cargo event, for example. In some embodiments, each gate may have a single image sensor configured to generate the image data. In other embodiments, each gate may have a plurality of image sensors configured to generate the image data.

(8) Another aspect is directed to a method for management of an airport with a plurality of gates. The method comprises operating a plurality of image sensors respectively at the plurality of gates, each image sensor configured to generate image data for an apron of a respective gate. The method further includes operating a server to receive the image data from each of the plurality of image sensors, detect a plurality of objects and a plurality of apron events associated therewith and within the apron of the respective gate based upon a machine learning model, and generate a gate performance UI for viewing the detected plurality of objects and the detected plurality of apron

events. The gate performance UI comprises a timeline menu of the detected plurality of apron events for each respective gate.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a schematic diagram of a first embodiment of an airport management system, according to the present disclosure.
- (2) FIG. 2A is a screenshot of a video menu from a gate performance UI from the airport management system of FIG. 1.
- (3) FIG. 2B is an enlarged screenshot of the video menu of FIG. 2A.
- (4) FIGS. 3-7 are screenshots of the gate performance UI from the airport management system of FIG. 1.
- (5) FIG. 8A is a screenshot of the video menu from the gate performance UI from the airport management system of FIG. 1.
- (6) FIG. 8B is an enlarged screenshot of the video menu of FIG. 8A.
- (7) FIGS. 9-10 are screenshots of an operations dashboard UI from the airport management system of FIG. 1.
- (8) FIGS. 11A-11E are screenshots of an airport performance UI from the airport management system of FIG. 1.
- (9) FIG. 12 is a screenshot of a detection log UI from the airport management system of FIG. 1.
- (10) FIGS. 13A-13B are screenshots of a live view UI from the airport management system of FIG. 1, according to a first embodiment.
- (11) FIGS. 13C-13D are screenshots of the live view UI from the airport management system of FIG. 1, according to a second embodiment.
- (12) FIG. 14 is a screenshot of a raw data UI from the airport management system of FIG. 1.
- (13) FIG. 15 is a screenshot of a daily alert UI from the airport management system of FIG. 1.
- (14) FIG. 16 is a schematic diagram of a second embodiment of the airport management system, according to the present disclosure.
- (15) FIG. 17 is a screenshot of an alert message from the airport management system of FIG. 1.

DETAILED DESCRIPTION

- (16) The present disclosure will now be described more fully hereinafter with reference to the accompanying drawings, in which several embodiments of the invention are shown. This present disclosure may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the present disclosure to those skilled in the art. Like numbers refer to like elements throughout.
- (17) Referring initially to FIGS. 1 & 2A-2B, an airport management system **100** is for an airport **101** with a plurality of gates **102a-102d**. For drawing clarity, only one airport **101** and four gates are depicted **102a-102d**, but it should be appreciated that the airport management system **100** may be deployed in multiple airports and in a large number of gates in some embodiments.
- (18) The airport management system **100** comprises a server **103**, and a plurality of image sensors **104a-104d** (e.g. infrared capable video sensors, visible light spectrum cameras) respectively positioned at the plurality of gates and communicatively coupled to the server (e.g. via a local area network (LAN), or the Internet). The server **103** illustratively includes a processor **105** and a memory **106** coupled thereto. As will be appreciated by the skilled person, the server **103** may comprise a stand-alone computing device, a distributed computing network, or provisioned resources within a cloud computing platform (e.g. Amazon Web Services, Microsoft Azure).
- (19) Also, each of the plurality of image sensors **104a-104d** may comprise a high resolution video

sensor (e.g. 4k or 8k resolution). Each image sensor **104a-104d** is configured to generate image data for an apron **107a-107d** (i.e. the safety envelope-proper position of an aircraft) of a respective gate **102a-102d**. In particular, the image data may comprise video data, and/or a sequence of image data frames with a known capture frequency. In some embodiments, each gate **102a-102d** may have a single image sensor configured to generate the image data. In other embodiments, each gate **102a-102d** may have a plurality of image sensors for provide multiple views of the apron **107a-107d** and adjacent areas. In yet other embodiments, each gate **102a-102d** may include an image sensor **104a-104d** configured to monitor passenger traffic within a passenger loading bridge (i.e. a jet way).

(20) The server **103** is configured to receive the image data from each of the plurality of image sensors **104a-104d**. The image data from each of the plurality of image sensors **104a-104d** may be transmitted to the server **103** in batches on a periodic schedule, or in advantageous embodiments, streamed in real-time. The server **103** is configured to detect a plurality of objects **110a-110n** and a plurality of apron events associated with the plurality of objects and within the apron **107a-107d** of the respective gate **102a-102d** based upon a machine learning model. In the illustrated image data of FIGS. 2A-2B & 8A-8B, the plurality of objects **110a-110f** comprises a safety envelope of the apron **107a-107d**, an aircraft, aircraft engines, gate personnel, an aircraft tug device, a tow bar, service vehicles, aircraft landing gear, and a passenger bridge.

(21) In some embodiments, the server **103** may comprise a plurality of devices. For example, the plurality of devices may comprise a machine learning computing device (e.g. computing cluster of one or more processing units, such as graphics processing units) configured to operate the machine learning model, and a database device configured to store image data associated with the detected events and the detected objects. Helpfully, due to bandwidth concerns at airport, the machine learning computing device may be locally deployed at the airport in some embodiments, and the database device may be located remote to the airport, such as within a cloud computing platform. Of course, in some embodiments, both the machine learning computing device and the database computing device may be located at the airport. While the plurality of image sensors **104a-104d** is configured to stream their image data to the server **103** (i.e. the machine learning computing device) in real time in some embodiments, the machine learning computing device is configured to periodically upload the image data associated with the detected events and the detected objects to the database device in batches. Of course, the image data associated with the detected events and the detected objects could be streamed in real time, but this may consume bandwidth at the airport **101**.

(22) In embodiments where each gate **102a-102d** includes a plurality of image sensors **104a-104d** for providing multiple views of the apron **107a-107d**, the server **103** may comprise a plurality of machine learning computing devices, each assigned to a subset of the plurality of gates **102a-102d**. In some embodiments, the machine learning model comprises a TensorFlow artificial intelligence engine. As will be appreciated by the skilled person, the machine learning model must be trained. The machine learning model and its source code are then configured uniquely to each individual gate camera. In particular, once a respective image sensor **104a-104d** is positioned, the apron **107a-107d** (safety envelope) is annotated within the vision input of the image sensor. In some applications, there is additional training required for gate specific equipment. For example, if a fuel truck hose attachment mechanism is unique to a gate, the machine learning model must be trained to recognize the unique piece of equipment. In some applications, the angle of the position for the respective image sensor **104a-104d** is canted or perhaps at a different elevation. Again, the machine learning model may be trained to accommodate the gate specific feature.

(23) In the illustrated embodiment, the machine learning model utilizes one camera, which faces the apron **107a-107d**. Once the machine learning model is successfully configured and connected to one of the plurality of image sensors **104a-104d**, a computer vision system (e.g. OpenCV) is used to receive the video frames from each image sensor. The frames are processed by our machine

learning model to determine objects **110a-110f** and event detections. The machine learning model analyzes the movement of objects, which allows for the model to be agnostic to flight data information. Therefore, Federal Aviation Administration (FAA)/Airline Flight schedule data is not required for the machine learning model to determine event processing times and object detection. As each object is identified, the machine learning model passes the object detection level of confidence, the object identification, date/time values for acquisition, x-y coordinates of the object, and size of object information to a database stored in the server **103**. Along with storing these data points, the machine learning model simultaneously uploads the corresponding images and videos (i.e. 1 minute snippets) associated with each significant object and event detection to the database.

(24) Referring now additionally to FIGS. 3-4, the server **103** is configured to generate a gate performance UI **120** for viewing the detected plurality of objects **110a-110f** and the detected plurality of apron events. The gate performance UI **120** comprises a timeline menu **121** of the detected plurality of apron events for each respective gate **102a-102d**. The timeline menu **121** illustratively includes a date fly down menu **122** for selecting a date for the gate performance statistics, a location fly down menu **123** for selecting the airport, a gate fly down menu **124** for selecting a gate, and a flight fly down menu **125** for selecting a flight.

(25) The timeline menu **121** illustratively includes a two-dimensional timeline chart **126** having the apron events **127a-127m** along the vertical axis **130a**, and time along the horizontal axis **130b**. Also, the timeline menu **121** may comprise a duration indicator (e.g. the illustrated horizontal bars) for each of the detected plurality of apron events **127a-127m**, and a scheduled arrival indicator **131**. Also, when a user selects any one of the detected plurality of apron events **127a-127m**, the server **103** is configured to generate a context menu **132** providing additional data, for example, time duration, and start/end times. The detected plurality of apron events **127a-127m** may include a Foreign Object Debris (FOD) walk, a ground power unit connection, a fuel hose connection, a belt loader connection, a passenger loading bridge extension/retraction/connection, a cargo event, an aircraft tax-in, aircraft hold out, an aircraft arrival/departure, an aircraft being stationary, a placement of chocks on the aircraft, an aircraft tug device (i.e. push truck) being in position, for example.

(26) In some embodiments, the server **103** is configured to cooperate with a third party database, and correlate the data from the third party database with the detected events and the detected objects. For example, aircraft hold outs outside the view of the respective image sensor **104a-104d** would not be detected by the server **103**. In this instance, the server **103** is configured to monitor the movement of the aircraft from landing to approach of the gate **102a-102d** via a third party database with geolocation coordinates of the aircraft.

(27) Further, the gate performance UI **120** illustratively comprises a video menu **133**, and the server **103** is configured to, when a given detected apron event **127h** is selected in the timeline menu **121**, generate the video menu to comprise a video associated with the given detected apron event. As illustrated in FIG. 3, the given detected apron event **127h** comprises the precondition air (PCA) unit being connected. Here, the video menu **133** comprises a video **134** of the given detected apron event **127h**.

(28) Referring specifically to FIGS. 2A-2B, which shows the video **134** of the given detected apron event **127h**, the video menu **133** comprises a plurality of boundary boxes **135a-135k** respectively over the detected plurality of objects **110a-110f** in the video associated with the given detected apron event. The video menu **133** also comprises a plurality of confidence values **136a-136k** respectively for the plurality of boundary boxes. As will be appreciated, the plurality of confidence values **136a-136k** represent the relative confidence of the machine learning model classification of the object **110a-110f**.

(29) Referring now to FIG. 5, the gate performance UI **120** illustratively comprises a video menu **133** where the given detected apron event **127c** comprises the aircraft being stationary. Helpfully, when the selected event is longer, for example, being greater than 2 hours in length, the video **134**

of the given event is compressed (i.e. cut to a shorter length) to the initial portion of the given detected apron event **127c**. In some embodiments, the video **134** of the given event is compressed to a 1 minute length video clip. Referring now to FIG. **6**, the gate performance UI **120** illustratively comprises a video menu **133** where the given detected apron event **127a** comprises the aircraft taxi-in.

(30) Referring now to FIG. **7**, the gate performance UI **120** illustratively comprises a video menu **133** where the given detected apron event **127k** comprises the push truck being in position. Referring now additionally to FIGS. **8A** & **8B**, which shows the video **134** of the given detected apron event **127k**, the video menu **133** comprises a plurality of boundary boxes **135a-135k** respectively over the detected plurality of objects **110a-110f**.

(31) Referring now additionally to FIGS. **9-10**, the server **103** is configured to generate an operations dashboard UI **140**. The operations dashboard UI **140** illustratively comprises a turnaround time by flight chart **141**, an approach time by flight chart **142**, a baggage load time by flight chart **143**, and a fuel service time by flight chart **144**. The operations dashboard UI **140** illustratively includes a date fly down menu **145** for selecting a date for the performance statistics, a gate fly down menu **146** for selecting a gate, and a location fly down menu **147** for selecting an airport.

(32) Referring now additionally to FIGS. **11A-11E**, the server **103** is configured to generate an airport performance UI **150** for viewing the detected plurality of objects **110a-110f** and the detected plurality of apron events **127a-127m** for the plurality of gates **102a-102d**. The airport performance UI **150** illustratively comprises a gate performance menu **151** comprising, for each gate **102a-102d**, a number of flights, a number of delayed flights, a number and a length of air traffic holdouts, a number of early arrivals, a passenger loading bridge extension delay, and a gate utilization metric. The airport performance UI **150** comprises a latest video menu **152** showing the latest processed image data from the plurality of image sensors **104a-104d**. The airport performance UI **150** further comprises a dashboard menu **153** comprising a number of flights for the airport, an average turn time for the airport, a gate utilization metric, and an on-time arrival metric. When one of the plurality of gates **102a-102d** is selected from the gate performance menu **151**, the server **103** is configured to generate the airport performance UI **150** to comprise a flight menu **154** showing the flights departing from the selected gate (e.g. the selected F2). Also, as perhaps best seen in FIG. **11C**, when one of the flights is selected from the flight menu **154**, the server **103** is configured to transition to the gate performance UI **120** for the selected gate and flight.

(33) The airport performance UI **150** illustratively comprises an event performance menu **155** comprising average time durations for each type of detected apron events **127a-127m**. The airport performance UI **150** comprises a compliance menu **156** comprising compliance metrics for a plurality of user-defined safety rules for the plurality of gates **102a-102d**. The plurality of user-defined safety rules may comprise Pre-FOD walk completion, the jet way being clear of the safety envelope, and placement of safety cones.

(34) Referring now additionally to FIG. **12**, the server **103** is configured to generate a detection log UI **160** comprising a mosaic interface **161** for viewing recorded videos from the plurality of image sensors **104a-104d**. For each video within the mosaic interface **161**, the mosaic interface also includes a time stamp and apron event classification. Also, the detection log UI **160** illustratively comprises a plurality of filter fly down menus **162a-162i** for selecting filter values for videos within the mosaic interface **161**.

(35) Referring now additionally to FIGS. **13A-13B**, the server **103** is configured to generate a live view UI **170**. The live view UI **170** illustratively comprises a location fly down menu **171a** for selecting an airport, and a gate fly down menu **171b** for selecting a gate. Once the airport and gate are selected, the server **103** is configured to generate the live view UI **170** to comprise a predicted departure menu **172** for a current flight with current event times, a gate average performance menu **173** showing the average time duration for the gate, and past flight menus **174a-174b** showing the

time stamps for apron events of past flights at the selected gate.

(36) In some embodiments, the live view UI **170** may include a predicted off block time (POBT) provided for each flight. This POBT time value predicts the time of departure based upon past performance at the respective gate. The machine learning model takes into account that the time of turnaround activities (e.g. fueling) and passenger movement have a strong correlation with departure time. More so, in embodiments with an image sensor in the jet way, the live view UI **170** may include automatic boarding updating.

(37) The live view UI **170** illustratively comprises a compliance menu **175** showing safety rule compliance for the current flight, and a turnaround timeline menu **176**. As perhaps best seen in FIG. **13B**, the turnaround timeline menu **176** includes a time line with scheduled and actual arrival of the current flight, and other apron events **127a-127m**, including marks for average duration of certain apron events. For example, in the illustrated example, the actual time of the when the baggage loader was connected is marked in overlay with the average time duration for connection of the baggage loader. Helpfully, the turnaround timeline menu **176** shows that the ground crew performance at the gate is above average for this flight.

(38) Referring now to FIG. **13C**, another embodiment of the live view UI **270** is shown. This live view UI **270** illustratively includes a live video **277** of the selected gate, and a map menu **278** showing the location of aircraft at the airport **100**. The live view UI **270** includes a predicted departure time menu **279**. As will be appreciated, the predicted departure time is based upon the machine learning model and past performance the selected gate. The departure time menu **279** also includes a list of recent detected events, for example, the illustrated pre-arrival FOD walk, the placement of safety cones, the baggage loader being attached and detached, and the push-truck being in position.

(39) In the map menu **278**, one or more gates with flagged safety/on-time issues may be color coded red. In the illustrated example, the gate G14 is flagged with the dashed box. Upon selecting the flagged gate, the live view UI **270** transitions to the flagged gate (i.e. G14), shown in FIG. **13D**, which shows that the safety cones were not placed for the current flight in the predicted departure time menu **279**. The map menu **278** may flag a gate **102a-102d**, for example, when a safety condition is violated (e.g. the safety cones not being placed), or when a delay condition has occurred (i.e. flights estimated to depart late). Indeed, the server **103** may be configured to flag gates **102a-102d** based upon any known metric.

(40) Furthermore, the map menu **278** illustratively includes personnel icons at gates G13 and G14. The personnel icons indicate that the airport management system **100** has detected support personnel at the gate. As shown in the live video **277** of gate G13, there are personnel present at the gate.

(41) Referring now additionally to FIG. **14**, the server **103** is configured to generate a raw data UI **180** comprising a table listing **181** of the received videos. Also, the raw data UI **180** illustratively comprises a plurality of filter fly down menus **182a-182e** for selecting filter values for videos within the table listing **181**.

(42) Referring now additionally to FIG. **15**, the server **103** is configured to generate a daily alert UI **190** comprising an alert menu **191** of the received videos. In the illustrated embodiment, the alert menu **191** includes apron events **127a-127m** including safety envelope violations, and delays in support equipment connection, but it also may include other events of interest, such as aircraft idling. Also, the daily alert UI **190** illustratively comprises a plurality of filter fly down menus **192a-192c** for selecting filter values for videos within the alert menu **191**. In some embodiments, the airport management system **100** may include a monitor and associated output indicator (e.g. audio speaker) configured to display the live view UI **170**, **270** for each gate in a grid arrangement. When any gate creates an alert condition, the server **103** is configured to cause the output indicator to generate an alert indication (e.g. audio alert).

(43) Another aspect is directed to a method for management of an airport **101** with a plurality of

gates **102a-102d**. The method comprises operating a plurality of image sensors **104a-104d** respectively at the plurality of gates **102a-102d**, each image sensor configured to generate image data for an apron **107a-107d** of a respective gate. The method further includes operating a server **103** to receive the image data from each of the plurality of image sensors **104a-104d**, detect a plurality of objects **110a-110f** and a plurality of apron events **127a-127m** associated therewith and within the apron **107a-107d** of the respective gate **102a-102d** based upon a machine learning model, and generate a gate performance UI **120** for viewing the detected plurality of objects **110a-110f** and the detected plurality of apron events. The gate performance UI **120** comprises a timeline menu **121** of the detected plurality of apron events **127a-127m** for each respective gate **102a-102d**.

(44) In some embodiments (FIG. 17), the server **103** is configured to send one or more alert messages to the user based upon the received image data. In the illustrated example, the alert message **300** includes a description and screenshot of the associated video generating the alert condition. In these embodiments, the alert messages may be derived from the alert menu **191**. For example, the alert messages may comprise an e-mail message, a SMS text message, or a push notification message on a mobile device (e.g. via a native software application in communication with the server **103**). The server **103** may be configured to store one or more trigger rules for causing the transmission of the alert messages. In some embodiments, the alert messages may be sent when threshold performance metrics are exceeded, such as a set percentage of delayed flights, a set average turn time for the airport, or a set gate utilization metric. Also, the alert messages may be sent when safety rule compliance falls below a set threshold.

(45) In some embodiments, the server **103** may render the above described UIs within a web browser. Of course, in other embodiments, the server **103** may operate in tandem with native software installed on work stations.

(46) The airport management system **100** may provide an approach to the potential drawbacks of existing airport management systems. In particular, the airport management system **100** may provide for enhanced visibility with regards to ground operations at the airport **101**. In particular, beyond performance metrics on delayed flights, the airport management system **100** may provide insight into specific ground functions that are causing delays at individual gates. More so, since the airport management system **100** is powered by a machine learning model, this data aggregation and characterization is done without onerous user interaction. The airport management system **100** may allow airline operators to determine which links in the support chain of their operations are causing delays.

(47) Moreover, the airport management system **100** may provide for cost reductions by preventing unnecessary aircraft holdouts for gates that are not ready. As a consequence of reduced aircraft holdouts, the airport management system **100** may reduce greenhouse gas emissions. Moreover, beyond using the compliance metrics for encouraging personnel compliance with safety regulations, the airport management system **100** provides ample teaching videos for operators. Of course, this will promote improved safety for support personnel. Since all apron events **127a-127m** are recorded, classified, and stored, the airport management system **100** may permit easy compliance with safety audits from regulatory authorities.

(48) In some embodiments, the server **103** is configured to operate the machine learning model for additional training for customer specific equipment. Also, the apron **107a-107d** (i.e. the safety envelope-proper position of an aircraft) may be customized based upon customer specific parameters.

(49) In some embodiments, a customer may make customized changes to the machine learning model of the server **103**. In particular, when the airport management system **100** is deployed initially, the customer may need to annotate the safety envelope **107a-107d** for each gate **102a-102d**, and annotate the proper position of supporting equipment, such as the passenger loading bridge. Subsequently, the customer may need to update these customer defined parameters when equipment is changed, for example, when the image sensors **104a-104d** are replaced or

repositioned.

(50) Referring now additionally to FIG. 16, another embodiment of the airport management system 200 is now described. In this embodiment of the airport management system 200, those elements already discussed above with respect to FIGS. 1-15 are incremented by 100 and most require no further discussion herein. This embodiment differs from the previous embodiment in that this airport management system 200 illustratively includes each gate 202a-202d having multiple image sensors 204a-204h for provide multiple views of the apron 207a-207d and adjacent areas. Many modifications and other embodiments of the present disclosure will come to the mind of one skilled in the art having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is understood that the present disclosure is not to be limited to the specific embodiments disclosed, and that modifications and embodiments are intended to be included within the scope of the appended claims.

Claims

1. An airport management system for an airport with a plurality of gates, the airport management system comprising: a server; and a plurality of image sensors respectively at the plurality of gates, each image sensor configured to generate image data for an apron of a respective gate; the server configured to receive the image data from each of the plurality of image sensors, detect a plurality of objects and a plurality of apron events associated therewith and within the apron of the respective gate based upon a machine learning model, for each object, generate an object detection level of confidence value, an object identification, date/time values for acquisition, x-y coordinates of the object, and a size value of the object, generate a gate performance user interface (UI) for viewing the detected plurality of objects and the detected plurality of apron events, the gate performance UI comprising a timeline menu of the detected plurality of apron events for each respective gate, a video menu, and a context menu, when a given detected apron event is selected in the timeline menu, generate and display the video menu to comprise a video associated with the given detected apron event, a plurality of boundary boxes respectively displayed over the detected plurality of objects in the video associated with the given detected apron event, and respective object detection level of confidence values for each of the plurality of boundary boxes displayed with the detected plurality of objects, and when the given detected apron event is selected in the timeline menu, generate and display the context menu for the given detected apron event comprising a time duration for the given detected apron event, and start/end times for the given detected apron event.
2. The airport management system of claim 1 wherein the machine learning model is uniquely trained for each gate.
3. The airport management system of claim 1 wherein the timeline menu comprises a duration indicator for each of the detected plurality of apron events.
4. The airport management system of claim 1 wherein the server is configured to generate an airport performance UI for viewing the detected plurality of objects and the detected plurality of apron events for the plurality of gates, the airport performance UI comprising a gate performance menu comprising, for each gate, a number and a length of air traffic holdouts, a number of early arrivals, a passenger loading bridge extension delay, and a gate utilization metric.
5. The airport management system of claim 4 wherein the airport performance UI comprises a dashboard menu comprising a number of flights for the airport, an average turn time for the airport, a gate utilization metric, and an on-time arrival metric.
6. The airport management system of claim 4 wherein the airport performance UI comprises an event performance menu comprising average time durations for each type of detected apron events.
7. The airport management system of claim 4 wherein the airport performance UI comprises a compliance menu comprising compliance metrics for a plurality of user-defined safety rules for the

plurality of gates.

8. The airport management system of claim 1 wherein the detected plurality of apron events comprises a Foreign Object Debris (FOD) walk, a ground power unit connection, a fuel hose connection, a belt loader connection, a passenger loading bridge connection, and a cargo event.

9. The airport management system of claim 1 wherein each gate has a single image sensor configured to generate the image data.

10. The airport management system of claim 1 wherein each gate has a plurality of image sensors configured to generate the image data.

11. An airport management system for an airport with a plurality of gates, the airport management system comprising: a server; and a plurality of image sensors respectively at the plurality of gates, each image sensor configured to generate image data for an apron of a respective gate; the server configured to receive the image data from each of the plurality of image sensors, detect a plurality of objects and a plurality of apron events associated therewith and within the apron of the respective gate based upon a machine learning model, the machine learning model being uniquely trained for each gate, for each object, generate an object detection level of confidence value, an object identification, date/time values for acquisition, x-y coordinates of the object, and a size value of the object, generate a gate performance user interface (UI) for viewing the detected plurality of objects and the detected plurality of apron events, the gate performance UI comprising a timeline menu of the detected plurality of apron events for each respective gate, the timeline menu comprising a duration indicator for each of the detected plurality of apron events, a video menu, and a context menu, when a given detected apron event is selected in the timeline menu, generate and display the video menu to comprise a video associated with the given detected apron event, a plurality of boundary boxes respectively displayed over the detected plurality of objects in the video associated with the given detected apron event, and respective object detection level of confidence values for each of the plurality of boundary boxes displayed with the detected plurality of objects, and when the given detected apron event is selected in the timeline menu, generate and display the context menu for the given detected apron event comprising a time duration for the given detected apron event, and start/end times for the given detected apron event.

12. The airport management system of claim 11 wherein the server is configured to generate an airport performance UI for viewing the detected plurality of objects and the detected plurality of apron events for the plurality of gates, the airport performance UI comprising a gate performance menu comprising, for each gate, a number and a length of air traffic holdouts, a number of early arrivals, a passenger loading bridge extension delay, and a gate utilization metric.

13. The airport management system of claim 12 wherein the airport performance UI comprises a dashboard menu comprising a number of flights for the airport, an average turn time for the airport, a gate utilization metric, and an on-time arrival metric.

14. The airport management system of claim 12 wherein the airport performance UI comprises an event performance menu comprising average time durations for each type of detected apron events.

15. The airport management system of claim 12 wherein the airport performance UI comprises a compliance menu comprising compliance metrics for a plurality of user-defined safety rules for the plurality of gates.

16. The airport management system of claim 11 wherein the detected plurality of apron events comprises a Foreign Object Debris (FOD) walk, a ground power unit connection, a fuel hose connection, a belt loader connection, a passenger loading bridge connection, and a cargo event.

17. The airport management system of claim 11 wherein each gate has a single image sensor configured to generate the image data.

18. A method for management of an airport with a plurality of gates, the method comprising: operating a plurality of image sensors respectively at the plurality of gates, each image sensor configured to generate image data for an apron of a respective gate; and operating a server to receive the image data from each of the plurality of image sensors, detect a plurality of objects and

a plurality of apron events associated therewith and within the apron of the respective gate based upon a machine learning model, for each object, generate an object detection level of confidence value, an object identification, date/time values for acquisition, x-y coordinates of the object, and a size value of the object, generate a gate performance user interface (UI) for viewing the detected plurality of objects and the detected plurality of apron events, the gate performance UI comprising a timeline menu of the detected plurality of apron events for each respective gate, a video menu, and a context menu, and when a given detected apron event is selected in the timeline menu, generate and display the video menu to comprise a video associated with the given detected apron event, a plurality of boundary boxes respectively displayed over the detected plurality of objects in the video associated with the given detected apron event, and respective object detection level of confidence values for each of the plurality of boundary boxes displayed with the detected plurality of objects, and when the given detected apron event is selected in the timeline menu, generate and display the context menu for the given detected apron event comprising a time duration for the given detected apron event, and start/end times for the given detected apron event.

19. The method of claim 18 wherein the machine learning model is uniquely trained for each gate.

20. The method of claim 18 wherein the timeline menu comprises a duration indicator for each of the detected plurality of apron events.
