

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12395454
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Dandison; John Patrick Francis et al.

Two-way real time communication system that allows asymmetric participation in conversations across multiple electronic platforms

Abstract

Methods, systems, and apparatuses, including computer programs encoded on computer-readable media, for receiving a first communication request, from a web browser of a user. A first responder requests information and a response to the request for information is received as part of a conversation. A conversation identifier is used to store the conversation. Based on the conversation, the conversation is determined to stop and a second responder is identified. The conversation is then transferred to the second responder.

Inventors: Dandison; John Patrick Francis (Lake Wylie, SC), Johnson; James Allen (Mobile, AL), Schottland; Paul Joseph Lyman (Fort Mill, SC)

Applicant: Disintermediation Services, Inc. (Lake Wylie, SC)

Family ID: 1000008767642

Assignee: DISINTERMEDIATION SERVICES, INC. (St. Clair, MI)

Appl. No.: 18/225987

Filed: July 25, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230379275 A1	Nov. 23, 2023

Related U.S. Application Data

continuation parent-doc US 17868970 20220720 US 11855936 child-doc US 18225987
continuation parent-doc US 17740526 20220510 US 11418466 20220816 child-doc US 17868970
continuation parent-doc US 17572958 20220111 US 11349787 20220531 child-doc US 17740526
continuation parent-doc US 17036709 20200929 US 11240183 20220201 child-doc US 17572958

continuation parent-doc US 15892129 20180208 US 10841253 20201117 child-doc US 17036709
continuation parent-doc US 14814337 20150730 US 9894019 20180213 child-doc US 15892129
continuation parent-doc US 13653119 20121016 US 9106599 20150811 child-doc US 14814337
us-provisional-application US 61627714 20111017

Publication Classification

Int. Cl.: **H04L51/04** (20220101); **G06F11/07** (20060101); **G06F11/16** (20060101); **G06F21/31** (20130101); **H04L9/40** (20220101); **H04L51/066** (20220101); **H04L51/56** (20220101); **H04L65/1104** (20220101); **H04L67/02** (20220101); **H04L67/14** (20220101); **H04L67/141** (20220101); **H04L69/18** (20220101); H04L51/02 (20220101)

U.S. Cl.:

CPC **H04L51/04** (20130101); **G06F11/0787** (20130101); **G06F11/1612** (20130101); **G06F21/31** (20130101); **H04L51/066** (20130101); **H04L51/56** (20220501); **H04L63/08** (20130101); **H04L65/1104** (20220501); **H04L67/02** (20130101); **H04L67/14** (20130101); **H04L67/141** (20130101); **H04L69/18** (20130101); H04L51/02 (20130101)

Field of Classification Search

CPC: H04L (51/04); H04L (51/066); H04L (51/56); H04L (63/08); H04L (65/1104); H04L (67/02); H04L (67/14); H04L (67/141); H04L (69/18); H04L (51/02); G06F (11/0787); G06F (11/1612); G06F (21/31)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1062886	12/1912	Carlson	N/A	N/A
5961601	12/1998	Iyengar	N/A	N/A
6442590	12/2001	Inala et al.	N/A	N/A
6879994	12/2004	Matsliach et al.	N/A	N/A
7171478	12/2006	Lueckhoff et al.	N/A	N/A
7346671	12/2007	Hankejh et al.	N/A	N/A
7428303	12/2007	Campbell et al.	N/A	N/A
7441199	12/2007	Zenith	N/A	N/A
7639672	12/2008	Foote	N/A	N/A
7769144	12/2009	Yao et al.	N/A	N/A
7861176	12/2009	Weisberg	N/A	N/A
7925702	12/2010	Rood et al.	N/A	N/A
7930267	12/2010	Samn	N/A	N/A
7958453	12/2010	Taing	N/A	N/A
8095400	12/2011	Herde et al.	N/A	N/A
8219689	12/2011	Kumar	N/A	N/A
8279779	12/2011	Singh et al.	N/A	N/A
8365205	12/2012	Chen et al.	N/A	N/A
8412785	12/2012	Wu et al.	N/A	N/A
8438227	12/2012	Mo et al.	N/A	N/A

8472612	12/2012	Goringe et al.	N/A	N/A
8738739	12/2013	Makar et al.	N/A	N/A
8880627	12/2013	Davenport et al.	N/A	N/A
8934477	12/2014	McCormack et al.	N/A	N/A
8949377	12/2014	Makar et al.	N/A	N/A
9009603	12/2014	Moyers et al.	N/A	N/A
9015155	12/2014	Levinson et al.	N/A	N/A
9076129	12/2014	Grewal et al.	N/A	N/A
9106599	12/2014	Dandison et al.	N/A	N/A
9215320	12/2014	Dahan	N/A	N/A
9218604	12/2014	Kumar	N/A	N/A
9245253	12/2015	Markman et al.	N/A	N/A
9473638	12/2015	Billman	N/A	N/A
9495661	12/2015	Zhuang et al.	N/A	N/A
9514424	12/2015	Kleinbart et al.	N/A	N/A
9515966	12/2015	Reynolds et al.	N/A	N/A
9535891	12/2016	Raheja et al.	N/A	N/A
9621500	12/2016	Hsiao et al.	N/A	N/A
9842295	12/2016	Fisher, Jr.	N/A	N/A
9894019	12/2017	Dandison et al.	N/A	N/A
10200335	12/2018	Richter et al.	N/A	N/A
10200420	12/2018	Kannan et al.	N/A	N/A
10298700	12/2018	Borden et al.	N/A	N/A
10503386	12/2018	Kilchenko et al.	N/A	N/A
10528922	12/2019	Narayanaswamy	N/A	N/A
10986057	12/2020	Taylor et al.	N/A	N/A
2003/0163516	12/2002	Perkins	709/213	H04L 67/535
2005/0105712	12/2004	Williams et al.	N/A	N/A
2005/0141694	12/2004	Wengrovitz	379/265.09	H04M 3/5191
2006/0184886	12/2005	Chung et al.	N/A	N/A
2007/0033249	12/2006	Samdadiya	709/204	H04L 65/1069
2007/0156910	12/2006	Christie et al.	N/A	N/A
2007/0162549	12/2006	Jin	709/206	H04L 67/142
2008/0075074	12/2007	Elumalai	370/389	H04L 12/6418
2008/0080677	12/2007	Samdadiya et al.	N/A	N/A
2008/0133671	12/2007	Kalaboukis	N/A	N/A
2008/0262911	12/2007	Altberg et al.	N/A	N/A
2008/0263446	12/2007	Altberg et al.	N/A	N/A
2009/0063188	12/2008	Schoenberg	N/A	N/A
2009/0198562	12/2008	Wiesinger et al.	N/A	N/A
2009/0204673	12/2008	Tian et al.	N/A	N/A
2009/0276408	12/2008	Auerbach et al.	N/A	N/A
2009/0284348	12/2008	Pfeffer	340/7.3	G08B 25/006
2010/0005402	12/2009	George	715/758	H04L 51/04

2010/0020967	12/2009	Kailash et al.	N/A	N/A
2010/0037153	12/2009	Rogers	N/A	N/A
2010/0088607	12/2009	Dumpeti et al.	N/A	N/A
2010/0257230	12/2009	Kroeger et al.	N/A	N/A
2010/0312836	12/2009	Serr et al.	N/A	N/A
2010/0325216	12/2009	Singh et al.	N/A	N/A
2011/0003585	12/2010	Wang et al.	N/A	N/A
2011/0044319	12/2010	Younis et al.	N/A	N/A
2011/0055309	12/2010	Gibor et al.	N/A	N/A
2012/0016981	12/2011	Clemm et al.	N/A	N/A
2012/0167182	12/2011	Rice et al.	N/A	N/A
2012/0259925	12/2011	Braudes	N/A	N/A
2012/0297031	12/2011	Danielsson Fan et al.	N/A	N/A
2013/0007150	12/2012	Hertz et al.	N/A	N/A
2013/0024786	12/2012	Dayal	N/A	N/A
2014/0250145	12/2013	Jones et al.	N/A	N/A
2015/0341288	12/2014	Dandison et al.	N/A	N/A
2016/0044142	12/2015	Hsiao et al.	N/A	N/A
2016/0088259	12/2015	Anderson et al.	N/A	N/A
2016/0285712	12/2015	Mankovskii	N/A	H04L 67/02
2018/0167343	12/2017	Dandison et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102158492	12/2013	CN	H04L 29/06
20020009399	12/2001	WO	N/A
2013059199	12/2012	WO	N/A

OTHER PUBLICATIONS

Shi, “Web Certification Method, Device and Network Device, English Translation”, Mar. 12, 2014, CN 102158492 B, 15 Pages. (Year: 2014). cited by examiner

Unified Patents PATROLL Winning Submission for U.S. Pat. No. 11,240,183 B2, date unknown, 27 pages. cited by applicant

The WebGreeter Experience User Manual 1.3, LiveAdmins LLC, Copyright 2002, 46 pages. cited by applicant

Features—Jappix Project, <https://jappix.org/features.html>, last accessed Dec. 1, 2021. cited by applicant

GitHub—Jappix/jappix: Jappix, a full-featured XMPP web-client (Jappix Desktop, Jappix Mobile & Jappix Mini)., <https://github.com/jappix/jappix>, last accessed Dec. 1, 2021. cited by applicant

Jabber.org; The Wayback Machine—

<https://web.archive.org/web.archive.org/web/20111009052501/http://www.jabber.org:80/faq/>; 4 pgs. cited by applicant

Jabber.org; About; The Wayback Machine—

<https://web.archive.org/web/20111010184319/http://www.jabber.org:80/about/>; 2 pgs. cited by applicant

Getting Started with Trillian for Web; Help Center Resources to help you quickly find a solutions;

<https://web.archive.org/web/20110921015618/http://www.trillian.im/guide/web/>; (Sep. 21, 2011); 3 pgs. cited by applicant

Olark; live chat should never be in the way.; The Wayback Machine—
<https://web.archive.org/web/20111017222119/http://www.olark.com:80/features>; 5 pgs. cited by applicant

Olark; Live chat just got real; Create trust, loyalty, & happy customers; The Wayback Machine—
<https://web.archive.org/web/20111016032243/http://www.olark.com:80/>; 2 pgs. cited by applicant

Olark; Commands with a bang!; The Wayback Machine—
<https://web.archive.org/web/20110926012950/http://www.olark.com:80/blog/2011/commands-wi> . . . ; 3 pgs. cited by applicant

Omegle; Talk to Strangers!; The Wayback Machine—
<https://web.archive.org/web/20111016191204/http://www.omegle.com:80/>; 1 pg. cited by applicant

Pidgin; About Pidgin; The Wayback Machine—
<https://web.archive.org/web/20111019155849/http://www.pidgin.im:80/about/>; 2 pgs. cited by applicant

Pidgin; IM all your friends in one place; The Wayback Machine—
<https://web.archive.org/web/20111016110159/http://pidgin.im/>; 1 pg. cited by applicant

Pidgin; Using Pidgin; The Wayback Machine—
<https://web.archive.org/web/20111018211550/http://developer.pidgin.im:80/wiki/Using%20Pidgin>; 11 pgs. cited by applicant

Trillian; Chat everywhere, at home, at work, or in your pocket, Trillian redefines seamless conversation.; <https://web.archive.org/web/20111016084241/http://www.trillian.im/>; (Oct. 16, 2011); 2 pgs. cited by applicant

Artificial Linguistic Internet Computer Entity; Wikipedia; https://en.wikipedia.org/w/index.php?title=Artificial_Linguistic_Internet_Computer_Entity&oldid=447417620; (Aug. 30, 2011); 2 pgs. cited by applicant

Crushgrams; Send anonymous crushgrams!; The Wayback Machine—
<https://web.archive.org/web/20110811035545/http://www.crushgram.com:80/>; 2 pgs. cited by applicant

GitHub—jappix/jappix: Japis, a full-featured XMPP web-client (Jappix Desktop, Jappix Mobile & Jappix Mini)., <https://github.com/jappix/jappix>, last accessed Dec. 1, 2021. cited by applicant

“U.S. Appl. No. 14/814,337, Final Office Action dated Jul. 20, 2017”, 15 pgs. cited by applicant

“U.S. Appl. No. 14/814,337, Non Final Office Action dated Dec. 28, 2016”, 14 pgs. cited by applicant

“U.S. Appl. No. 14/814,337, Notice of Allowance dated Oct. 6, 2017”, 11 pgs. cited by applicant

“U.S. Appl. No. 14/814,337, Response filed Jun. 28, 2017 to Non Final Office Action dated Dec. 28, 2016”, 14 pgs. cited by applicant

“U.S. Appl. No. 14/814,337, Response to Final Office Action dated Jul. 20, 2017”, 12 pgs. cited by applicant

“International Application Serial No. PCT/US2012/060432, International Preliminary Report on Patentability dated May 1, 2014”, 6 pgs. cited by applicant

“International Application Serial No. PCT/US2012/060432, International Search Report dated Dec. 17, 2012”, 2 pgs. cited by applicant

“International Application Serial No. PCT/US2012/060432, Written Opinion dated Dec. 17, 2012”, 4 pgs. cited by applicant

PCT International Search Report, PCT Application No. PCT/US2012/060432, dated Dec. 17, 2012. cited by applicant

PCT International Search Report, International Appln. No. PCT/2012/060432, dated Dec. 17, 2012, 7 pages. cited by applicant

Primary Examiner: Gillis; Brian J.

Assistant Examiner: Ling; Chhian (Amy)

Attorney, Agent or Firm: Panitch Schwarze Belisario & Nadel LEP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 17/868,970, filed Jul. 20, 2022, now U.S. Pat. No. 11,855,936, which is a continuation of U.S. application Ser. No. 17/740,526, now U.S. Pat. No. 11,418,466, filed May 10, 2022, which is a continuation of U.S. application Ser. No. 17/572,958, filed Jan. 11, 2022, now U.S. Pat. No. 11,349,787, which is a continuation of U.S. application Ser. No. 17/036,709, filed Sep. 29, 2020, now U.S. Pat. No. 11,240,183, which is a continuation of U.S. application Ser. No. 15/892,129, filed Feb. 8, 2018, now U.S. Pat. No. 10,841,253, which is a continuation of U.S. application Ser. No. 14/814,337, filed Jul. 30, 2015, now U.S. Pat. No. 9,894,019, which is a continuation of U.S. application Ser. No. 13/653,119, filed Oct. 16, 2012, now U.S. Pat. No. 9,106,599, which claims the benefit of U.S. Provisional Application No. 61/627,714, filed Oct. 17, 2011, all of which are incorporated by reference herein in its entirety.

BACKGROUND

(1) The following description is provided to assist the understanding of the reader. None of the information provided or references cited is admitted to be prior art.

(2) Real-time communication (RTC) is the generalized term for multiple systems which allow real time, or near real-time exchange of information over various protocols. The most common categories of RTC include instant messaging and text messaging. Electronic mail can be used for RTC as well, though it is slightly slower than the other media of RTC. The critical element of RTC comes in the nearly instant exchange of information using internet or telecommunications protocols.

(3) The instant messaging category of RTC allows real-time text-based chat communication between two or more people using computing devices. Typically, instant messaging operates in a push mode where chats are sent directly to the receiver without the receiver having to poll for data. Instant messaging can enable people to chat over a network, such as the internet. In addition, some instant messaging clients allow for other features such as live voice, file sharing, video calls, etc.

(4) The text messaging category of RTC is commonly called SMS (“Short Message Service”) and is a text messaging service component of phone, web, or mobile communication systems, that uses standardized communication protocols that allow the exchange of short text messages between the devices. RTC and SMS also include additional instant messaging technologies such as multimedia messaging services (MMS) which extends the RTC capabilities onto the mobile telephone network of devices. Using MMS, photos, videos, ringtones, etc., can be sent to mobile devices. The electronic mail category of RTC is commonly called email, and allows an author to exchange of digital messages with one or more recipients. The digital messages can include attachments such as image files, video files, and/or other documents.

(5) Known systems have been used to provide RTC communications. The traditional methods for the RTC communications include but are not necessarily limited to: (1) both parties sharing a common communications protocol (email, text messaging/SMS, instant messaging, etc.); (2) the initiating party being required to know the recipients addresses or other identifying information prior to being able to initiate a communication; (3) both parties being identified to the other during the course of the communication by the RTC systems.

(6) While RTC can be utilized in a number of different ways on various computing devices, the various modes of RTC are not interconnected. For example, two people chatting must use the same communication protocols and, in some instances, the same software to be able to chat.

SUMMARY

(7) In general, one aspect of the subject matter described in this specification can be embodied in methods for receiving from each of a plurality of responders conversation selection criteria and a mode of communication information that includes at least one of an email address, a telephone number, or an instant message identifier. A request for a conversation is received, from an initiator using a first communication mode, that includes conversation information that identifies a topic of the conversation, but does not identify any responders. A conversation identifier associated with the request is created. One or more possible responders are determined based at least upon the topic of the conversation and the conversation selection criteria. A mode of communication is determined for each of the one or more possible responders based at least on the received mode of communication information. The topic of the conversation is sent to the one or more possible responders, without identifying the initiator, using the determined mode of communication associated with each of the one or more possible responders. The initiator is anonymous to each of the one or more possible responders. At least one of the determined modes of communication of the one or more possible responders is a second communication mode that is different than the first communication mode. A first response from a first responder is received using the second communication mode. The first response is mapped to the conversation associated with the initiator based in part on the conversation identifier. The response is sent to the initiator using the first communication mode such that the first responder is anonymous to the initiator. Other implementations of this aspect include corresponding systems, apparatuses, and computer-readable media configured to perform the actions of the method.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The foregoing and other features of the present disclosure will become more fully apparent from the following description and appended claims, taken in conjunction with the accompanying drawings. Understanding that these drawings depict only several embodiments in accordance with the disclosure and are, therefore, not to be considered limiting of its scope, the disclosure will be described with additional specificity and detail through use of the accompanying drawings.

(2) FIG. 1 is a diagram of a RTC system in accordance with an illustrative embodiment.

(3) FIG. 2 is a flow diagram illustrating a process allowing RTC in accordance with an illustrative embodiment.

(4) FIG. 3 is a flow diagram illustrating a process allowing RTC in accordance with an illustrative embodiment.

(5) FIG. 4 is a block diagram of a computer system in accordance with an illustrative implementation.

(6) In the following detailed description, reference is made to the accompanying drawings, which form a part hereof. In the drawings, similar symbols typically identify similar components, unless context dictates otherwise. The illustrative embodiments described in the detailed description, drawings, and claims are not meant to be limiting. Other embodiments may be utilized, and other changes may be made, without departing from the spirit or scope of the subject matter presented here. It will be readily understood that the aspects of the present disclosure, as generally described herein, and illustrated in the figures, can be arranged, substituted, combined, and designed in a wide variety of different configurations, all of which are explicitly contemplated and make part of this disclosure.

DETAILED DESCRIPTION

(7) Described herein are illustrative systems and methods involving the computer, protocol, communications, and internet-related fields. Various implementations add features which allows RTC to occur without the initiator of a communication being required to share a common RTC application or RTC protocol with the recipient(s) or responder(s) to that communication. Various implementations also provide for management of the communication between the initiator from a website or dedicated application, to various responders using a variety of RTC communication methods. In one implementation, these various responses are managed in such a way that the initiator sees them as unified responses within the internet website which the initiator is viewing and communicating with the responders. In some implementations, the initiator does not need to provide a destination address for the communication, and the initiator may remain anonymous to both the system and the responders. In other implementations, the initiator may identify himself to responders. In another implementation, asymmetric management of the conversation can occur, so that the initiator sees all communications from all responders but a responder only see the initiator's responses to the responder but not the responses of the other responders unless authorized to do so by the initiator or administration.

(8) FIG. 1 is a diagram of a RTC system **100** in accordance with an illustrative embodiment. An initiator **102** can create a line of communication with a responder **110**. The initiator **102** can use a web browser to visit a website or connect through a dedicated application to a server **104**. From the website or application, the initiator **102** can send a communication to the server **104**. The server can identify one or more responders along with one or more protocols that can be used to communicate each responder. For example, the server **104** can communicate with a responder through various protocols such as, but not limited to, SMS **108a**, XMPP **108b**, SIP **108c**, RTP, SMTP, POP, etc. Accordingly, the responder **110** can communicate with the server using any number of devices **112** such as, but not limited to, desktop computers, notebooks, personal digital assistants, tablets, smartphones, cell phones, etc.

(9) In various implementations, it is not necessary for the initiator **102** to identify themselves in any way to the server **104**, nor to the potential responders. In one implementation, the initiator's request can be mapped to one or more potential responders based upon preferences of the responders. In one implementation, the preferences of the responders can be stored in a data store **106**. The data store **106** can also store other information, such as mappings, conversations, etc. As an example of using preferences, the initiator **102** can include a selected category that is related to the initiator's desired communication. The server **104** can use the selected category in determining the potential one or more responders.

(10) Once one or more responders have been identified, the server **104** can route the communication to the appropriate destination addresses, using RTC channels (e.g., instant messaging addresses, email addresses, text message/SMS addresses, etc.) which the one or more responders have previously provided. As described in greater detail below, the server **104** can map the various RTC channels that were used to initiate communication with each responder. This mapping can be used to allow continued communication between the initiator **102** and the responder **110**.

(11) In one implementation, the responders do not need to identify themselves in any way to the initiator. Any responses which the responders send will be managed by the system to be provided to the initiator, within the web browser window or application. These responses can be presented to the initiator and may be delivered to the initiator without presenting the originating source's identifying information (instant message address or SMS/text number). If there are multiple responders to the initiator, each responder may be visually indicated so as to separate the responses in the web browser window or application by responder, though the separation need not identify the responder. Each party is of course free to identify themselves within the actual words sent or received by them within the conversation (e.g., an initiator could send any message, "I am Sam

Davis and I trust you so I am giving you my number it is (704) 555-1212"). The initiator can be presented with multiple responders' communications if multiple responders reply or may be presented with the first responder only, or other selection criteria. However, in one implementation, each responder sees only their text and replies from the initiator directed to them. The responder does not see the other responders' responses. In another implementation, the text communications are sent to all parties, e.g., the initiator and the one or more responders.

(12) As mentioned above, potential responders can provide in advance, the RTC communication addresses on which they wish to receive messages, any specific criteria for which they wish to receive messages, and the times of the day in which they wish to receive messages. Other criteria are also possible to allow further specification for messages which recipients would like to receive transmissions on their pre-defined criteria (e.g., specific keywords or jurisdictions, etc). In addition, a responder can provide criteria for when they are not available. For example, at certain times of the day, days of the week, a responder can configure their criteria to avoid getting any requests from initiators. While communication occurs in real time, the initiator and the responder are not required to share a common RTC protocol.

(13) Accordingly, the system **100** can connect internet or application communications to real-time and near real-time technologies and back to the internet or applications. In one implementation, the system **100** allows web users (HTTP and internet-related protocols) to converse with real-time device users (SMS, XMPP, SIP, MMS, and RTC related protocols) in a two-way conversation, all while providing optional anonymity to either or both parties from the other party. As described, the system **100** allows for either the web-based use (or application user) to initiate the conversation with an RTC responder, or this system provides the description of the RTC party initiating the conversation with another RTC party or web-based user (or application user). No common software is required for the participants in the discussion (for example, each party does not need to be a subscriber to a common service).

(14) In one implementation, the server **104** can select one or more potential responders randomly from a pool of available responders. In other implementations, the one or more potential responders are selected using some criteria. For example, one or more of user selected topics, website specific addresses, word-choice in the communication, meta-data describing the conversation topics, geographic location, RTC protocol preferences, past communications, etc. can be used to select the one or more potential responders. The initiator and potential responders do not need to know one another's profiles, addresses, real-time communication sources, or any other identifying information; since this is handled by a server that sits between the initiator and each responder. The initiator and potential responders also do not need to share a common real-time communication protocol, medium, nor software; since the sourcing, routing, and exchanging of questions and answers to the parties is handled by the server.

(15) As an example, in one implementation a person may visit a website or use a dedicated application to initiate a discussion, ask a question, or find information about a particular good or service offered by responders. Information about the subject matter of the good, service, or information being offered may be available on the website or dedicated application. The visitor can have learned of the website in any number of manners including internet search engine results, paid advertising link, direct connect to website using domain name, link through a related website, etc. In another implementation, a user can initiate communication via a link to discuss the good, service, or information being offered. Once the initiator visits the website or opens the application there can be a portal which will allow the initiator to connect with one or more live respondents to get more information about the subject matter of the website or application. There can also be a series of drop-down items or selections which the initiator can make to aid in identifying the particular area of expertise, product, or information sought by the initiator. However, it is also possible that the initiator can begin their inquiry without being required to enter any identifying or qualifying information whatsoever. The respondents who use or subscribe to the service may have

an interest in responding to inquiries or providing information about particular goods or services in a limited geographic region based on preliminary qualifying information so that functionality is built into the system and can be used based upon settings selected by the administrator, users, and/or responders.

(16) Once the initiator asks a question, makes a statement, or enters any preliminary qualifying information which may be needed as discussed above, a chat window can open showing the beginning of a conversation thread. The initiator can be identified generically as “User, Customer, Client, Person, etc . . . ” and is not required to disclose their name, e-mail address, phone number, home address, or any other identifying information to initiate the conversation. Of course, the initiator can do so on their own or after being prompted by the administrator or the responder. Not initially requiring the disclosure of information allows the initiator to feel free to engage the responders in an open dialogue about the information, goods, or services that they are seeking. Once the initiator feels comfortable with the information they have received and/or decides to purchase the goods, information, or services being offered by the responders, the initiator can then be encouraged to disclose any personal identification or contact information which may be necessary to complete the transaction. In various implementations, the initiators are able to obtain information without having to “subscribe” to any service or pay any fee to engage the responders through the use of this real-time two-way communication system. In some implementations, however, the ability to chat with initiators can be offered to the responders on a subscription, connection, auction, and/or impression basis. Ecommerce functionality can also be built into various implementations so the potential subscription, connection, auction and/or impression fees and charges can be automated.

(17) In various implementations, the initiator can request a communication without providing any information. In one implementation, the initiator can be prompted to ask a question or provide information relevant to the subject matter disclosed on the web site or application. This information, along with any preliminary qualifying information obtained, and any information which may be available based upon the initiator's domain, etc., can be instantaneously transmitted to a pool of subscribing respondents via e-mail, SMS, and instant message who have previously provided their e-mail addresses, cellular telephone numbers, and instant message user names. For example, when after disclosing that the initiator lives in “Alaska,” the initiator types “I would like information about X” all subscribers who have agreed to handle inquiries from residents of the State of Alaska will receive an e-mail, text message (SMS), and instant message that says something like “User from Alaska would like information about X.” In order to provide some time for the respondents to receive, read, and respond to the communication in one implementation the initiator can be asked questions about the subject matter of the website by the use of a concierge or virtual assistant. This virtual assistant serves two important purposes, it stalls for time to allow the respondents the opportunity to respond and it engages the initiator so they do not feel like they are on hold waiting for a response. These questions can even start just after the initiator has entered the preliminary qualifying information such as “Alaska” but before the initiator has an opportunity to send the first communication. Accordingly, the responders will have additional time to engage the initiator while the concierge/virtual assistant is asking questions. Once the pre-programmed questions have been asked or the potential responders begin responding the questions can be programmed to stop.

(18) The entire pool of potential responders can receive an SMS, MMS, e-mail, or instant message notification when an initiator has entered sufficient criteria (i.e. state, subject matter, answers to questions) that match the criteria that the responders desire to communicate with the initiator about. In one implementation, the initiator's request, question, statement, or text can be sent, without requiring any criteria, to the recipient's SMS, MMS, email, instant message or other RTC destination. In one implementation, a number of the potential responders, which number can be pre-determined by the administrator, subscribers, and/or initiator, can respond to the initiator using

a real time communication of the responder's choice. For example, when a potential responder receives a SMS text message notification from the system that A user from Alaska would like additional information about product X, the responder can reply directly from his cell phone using the SMS capability of that phone or via e-mail or instant message. As another example, a web visitor, seeing a real-estate property about which they are interested, can click on a link and initiate a conversation. The conversation request can be received by a listing agent (or additional other agents on duty) for the real-estate property. In one implementation, only the first replying agent would be allowed to communicate with the initiator. In other implementations, multiple responders can communicate with the initiator. These parties, both initiator as well as the responder are not required to identify themselves to each other. The web visitor would not be required to share any software in common with the real estate agents, nor would the real-estate agents need to share any software in common with the web-visitor. The real-estate agents could be using a variety of different RTC communication methods, and all would work to affect their responses so that the web-visitor could see them in the chat window. In one implementation, the responses of the various responders and the initiator are shared with each party. In another implementation, the initiator has a separate and distinct conversation with each responder.

(19) In one implementation, initiators are matched with responders based upon state, subject matter, answers to pre-programmed questions, IP address, metadata, syntax of language that appears in a message or response to a question, etc. An administrator, subscriber, and/or user can set a quantity limit on the number of responders who are allowed to respond to the initiator and a limit on the length of time it takes to respond.

(20) To facilitate allowing communication using disparate forms of RTC, an intermediary proxy can handle message stream convergence and routing. The following is one example of how to technically construct a specific implementation, and in no way limits the patent to these specific technologies, as the over-arching claims extend outside specific technologies.

(21) FIG. 2 is a flow diagram illustrating a process **200** allowing RTC in accordance with an illustrative embodiment. The process **200** can be implemented on a computing device. In one implementation, the process **200** is encoded on a computer-readable medium that contains instructions that, when executed by a computing device, cause the computing device to perform operations of process **200**.

(22) In the illustrated process **200**, an initiator can ask a question or provide input within a web-based user interface (**202**). The question or input can be sent to a server that matches the question or input to criteria of potential responders (**204**). The mode of communication for each potential responder is determined (**206**). Using the identified modes of communication, the initiator's question is sent to the one or more responders (**208**). The server receives a response from one or more of the responders (**210**). Using information associated with the received response, the server can map the response to the initiator's question (**212**). After mapping, the response can be sent to the initiator and displayed in the web-based user interface (**214**). Communication between the initiator and the responder can continue by the server mapping the responses from the initiator and responder.

(23) FIG. 3 is a flow diagram illustrating a process **300** allowing RTC in accordance with an illustrative embodiment. The process **300** can be implemented on a computing device. In one implementation, the process **300** is encoded on a computer-readable medium that contains instructions that, when executed by a computing device, cause the computing device to perform operations of process **300**.

(24) In the illustrated process **300**, a client provides criteria related to a conversation that the client wishes to initiate (**302**). The criteria is provided to a server over a network, such as using HTTP over the internet. For example, a user can use a web browser client or application to send the criteria. Upon receipt, the server can create a conversation identifier that identifies one specific conversation associated with the client (**304**). For example, the conversation identifier can be a

randomly generate number. The server can determine potential responders for the client's request (306). As described above, potential respondents can provide criteria for conversations that they are willing to participate in. Criteria can be based upon the time of day, day of the week, the type of question being asked, location of the client, etc. In one implementation, a data store can be queried to search for responders whose criteria match the current conversation request. For each potential responder, the mode of communication associated with the responder is determined (308). The mode of communication can also be based upon criteria, such as time of day, day of week, etc., that is provided by each responder. Information associated with the client can then be sent to each responder using the responder's requested mode of communication (310). For example, information provided by the user can be sent to one or more potential responders using various different modes of communication. For example, the client's information can be sent to a first responder as an instant message and the client's information can be sent to another responder using SMS. The server can store information associated with each message sent. This information can be used to map responses from the responders to the appropriate conversation. For example, the IP address or telephone number of a responder can be used to identify responses from responders. The server can receive one or more responses from the responders (312). If a responder has multiple possible communication mediums, the communication that the response is received on can be used as the current or active communication media for that responder. For example, if a responder can receive initiator requests through instant messaging and email, the one used by the responder to respond will be deemed the active medium. Future data from the initiator for that conversation will be sent only to the active medium. It is possible for a responder to switch communication mediums. This can be achieved by the responder replying via any medium that is not the active medium. For example, if the responder initially used email to respond, the responder can later respond using instant messaging or SMS. The server can determine the responder from the information received as part of the instant message or SMS. Once the responder is determined, the appropriate conversation can then be determined and the responders reply routed to the correct initiator as part of the on-going conversation.

(25) In addition to a responder being able to switch communication mediums, the initiator can also switch to a different form of communication. For example, the initiator can initially ask a question using a web interface as described above. At some point during the conversation, the initiator can provide information regarding a new mode of communication to use for this conversation. For example, the initiator can provide an email address, telephone number, or instant message handle, etc. The server can use this information to forward responses from the responders to the new mode of communication rather than the initial web interface.

(26) Using information associated with the response, the server can determine the appropriate conversation that the response belongs to (314). For example, the server can use the phone number from an SMS response and determine the conversation identifier associated with the phone number. In addition, the IP address or email address of the responder can be used to determine the appropriate conversation identifier. Other information that can be used to map a response to an established conversation includes the receiving address. For example, the phone number used to receive a response from a responder can be used alone or in conjunction with the sending telephone number to map to the correct conversation. In another implementation, the conversation identifier is sent to the responders and any response from a responder contains the conversation identifier.

(27) The response can be formatted prior to sending to the client (316). In one implementation, any identifying information can be removed from the response. For example, a telephone number, email address, and/or IP address can be removed from the response. After mapping the response to a conversation, the response can be sent to the client (318). In one implementation, the response for the client is stored in a database. The client can poll the server and the server can send any needed responses in response to a poll. Responses from the client can also be stored in the database, thus, providing a record of the entire conversation that can be accessed at a later time by either the client

or the responder.

(28) An initiator can use any of the following to initiate a conversation: a web browser, an application utilizing XML/SOAP, WCF, binary transfer, HTTP, etc. The RTC communication between a server and a responder can use any of the following SMS, MMS, XMPP, SIP, etc. Communications can be delivered to a responder at a corresponding address specific to that communication type to initiate the conversation.

(29) In one implementation, the initiator is able to start a conversation by visiting a website and submitting a question by typing into a text-box on the website. Alternatively, the initiator could also use a locally installed application of this system, which acts as a client to the request initiation of a conversation with the server.

(30) The question can be inserted into a data store, for example a conversation database used to temporarily store conversations, and that conversation session is issued a Communication Identifier (CID). Each conversation string submitted may be stored in a unique table for that conversation, so that subsequent communications within that same conversation are kept together. This can be accomplished by matching the session created by the initiator and all subsequent text-based communication between the initiator and responders. The website can also contain software which provides a user interface to allow the initiator to input criteria to define their question. Examples to illustrate criteria would be a specific application like a tax preparation application, or a preferred language of the initiator, or describe which state of the United States they are seeking assistance, e.g., Missouri. Criteria can be created by explicit action by the initiator, e.g., selecting a term or category to describe the question. The criteria can also be created by implicit information, e.g., the real-estate case described above could put an address-specific link to identify the criteria for all specific conversations which are initiated from that address-specific link. As another example of implicit information, a geographic location of an initiator can be determined using the IP address of the initiator. The criteria may also be created by implicit information, e.g., a specific website address or specific sub-site can act to provide criteria. Determining the potential responders can be determined from either or both the implicit information and the explicit actions. It is also possible that no criteria could be required of the initiator. The initiator does not need to provide any contact or user-specific identification to submit to this system. The initiator can only submit their question, statement, or any text to initiate a conversation. These criteria (whether explicitly selected or implicitly determined) are submitted to a server to find any (all) matching responders with those criteria. A software process within the system then manages the communication to the appropriate responders for the specific criteria. The software process provides the text of the initiator's question to the matching responders, using the RTC communication media which each responder has provided. Multiple RTC destinations and media are possible for each specific responder. All matching responders are contacted using each of the pre-defined RTC communication channels for all matching responders.

(31) To facilitate communications between initiators and responders, RTC address information of potential responders can be stored in a database. Each responder is treated individually, with each record maintaining the responder's instant messaging, text messaging, email addresses, as well as any additional RTC contact information for that specific responder. Each responder may also provide any criteria by which they seek to be connected to initiator's with questions. Examples of an RTC address would be:

(32) Example_responders_address@domainname.com; an SMS/text message contact number; and instant messaging address similar to example_responders_IM_address@jabber.org. Examples of explicit criteria for a responder would be "English Language Questions" or "tax preparation software" or questions pertaining to "Missouri." A simple example of the implicit criteria for a responder would be simply the specific URL or link which directs all the questions submitted by initiators to the SMS address/contact number of the responders. Simply by visiting that URL (E.g., <http://moredeets.com/1234me>) the implicit information provided to the routing rules would

transmit all questions submitted by users to the SMS address/contact number of one or more specific responders.

(33) All of this information can be stored in a database for matching of criteria, and also providing the system with RTC addresses for matches to the criteria. A hunter service can contact the database to determine matches to the criteria provided by an initiator asking a question. The hunter service provides the RTC addresses to the software process which communicates over the RTC communication media. The software process sends the text which the initiator provided to the system, over the RTC addresses provided by the hunter service. Examples to illustrate this aspect of the process would include the following; using an email service or plug-in to send the text of the initiator's question to the potential responder's email address; using an SMS/text message service the software process sends the text of the initiator's question to all potential responders' SMS/text message addresses (phone number); and/or using an instant messaging service to send the initiator's question to all potential responders' instant messaging addresses. The CID is preserved so that responses can be mapped back into the Conversation Database, to the appropriate conversation. The message formatting service accepts all incoming messages from responders, regardless of RTC media, and standardizes the text of the responses so that they appear within the Communication database with no differentiation between the RTC method(s) used by responders.

(34) In one implementation, all responses to the initiator's request are posted into the database. This can be configured to minimize the number of accepted responses to an initiator. The logic of the posting service is configurable. It may be configured in specific instances to allow only one responder's message to be sent through the system to the initiator, or give preference to specific RTC media types, or may allow only the first two responders to be sent through the system to the initiator, or similar rules to the above. The responder's responses which are posted to the database are retrieved by the client-side software running on the web, application, or could even be another RTC mechanism acting as an initiator.

(35) The initiator does not have to provide any identifying information, and the responders receive no identifying information about the initiator, because all communications are coming from the addresses used by the system itself. This can be accomplished across all existing RTC communications media, as well as any additional communications media deemed appropriate for providing responses to initiators. The responders do not have to provide any identifying information to the initiator, because all communications from the responders are managed by the system, and no source address information is provided to the initiator.

(36) The system also provides a concierge or virtual assistant service. This is provided via a software service wherein the initiator is asked pre-created questions, which are possibly different for any criteria selected. As discussed in the real-estate example above, the questions asked could be different for each real estate address/property. The routing rules for responders could be different as well for each real estate address/property. The responses by the initiator can determine the next action by the system; e.g., a "Yes" answer can continue other pre-created questions, while a "No" can cause a different text-based response from the virtual assistant or concierge. These responses can also be broadcast to the potential responders, using the same mechanisms described above. These pre-created questions can continue up to the time a responder chooses to communicate with the initiator.

(37) In some implementations, allows an auction or bidding capability. The auction or bidding capability can not allow for responders to send in responses until the responder purchases the ability to communicate with the initiator. This can be a reverse auction or bidding service which occurs prior to connecting responders with the initiator. The initiator's question and subsequent responses to the concierge service are communicated to the potential responders. Using this information, the potential responders determine if the price at auction, reverse-auction, or bidding minimum, etc. are acceptable. If they are acceptable, the payment commitment is communicated using the above system, and then the successful bidders are allowed to communicate via the

system, to the initiator.

(38) FIG. 4 is a block diagram of a computer system in accordance with an illustrative implementation. The computing system **400** can be used to implement the web server, search service, advertisement service, etc., and includes a bus **405** or other communication component for communicating information and a processor **410** or processing circuit coupled to the bus **405** for processing information. The computing system **400** can also include one or more processors **410** or processing circuits coupled to the bus for processing information. The computing system **400** also includes main memory **415**, such as a random access memory (RAM) or other dynamic storage device, coupled to the bus **405** for storing information, and instructions to be executed by the processor **410**. Main memory **415** can also be used for storing position information, temporary variables, or other intermediate information during execution of instructions by the processor **410**. The computing system **400** may further include a read only memory (ROM) **410** or other static storage device coupled to the bus **405** for storing static information and instructions for the processor **410**. A storage device **425**, such as a solid state device, magnetic disk or optical disk, is coupled to the bus **405** for persistently storing information and instructions.

(39) The computing system **400** may be coupled via the bus **405** to a display **435**, such as a liquid crystal display, or active matrix display, for displaying information to a user. An input device **430**, such as a keyboard including alphanumeric and other keys, may be coupled to the bus **405** for communicating information and command selections to the processor **410**. In another implementation, the input device **430** has a touch screen display **435**. The input device **430** can include a cursor control, such as a mouse, a trackball, or cursor direction keys, for communicating direction information and command selections to the processor **410** and for controlling cursor movement on the display **435**.

(40) According to various implementations, the processes described herein can be implemented by the computing system **400** in response to the processor **410** executing an arrangement of instructions contained in main memory **415**. Such instructions can be read into main memory **415** from another computer-readable medium, such as the storage device **425**. Execution of the arrangement of instructions contained in main memory **415** causes the computing system **400** to perform the illustrative processes described herein. One or more processors in a multi-processing arrangement may also be employed to execute the instructions contained in main memory **415**. A computer storage medium can be, or be included in, a computer-readable storage device, a computer-readable storage substrate, a random or serial access memory array or device, or a combination of one or more of them. Moreover, while a computer storage medium is not a propagated signal, a computer storage medium can be a source or destination of computer program instructions encoded in an artificially-generated propagated signal. The computer storage medium can also be, or be included in, one or more separate components or media (e.g., multiple CDs, disks, or other storage devices). Accordingly, the computer storage medium is both tangible and non-transitory.

(41) While this specification contains many specific implementation details, these should not be construed as limitations on the scope of any inventions or of what may be claimed, but rather as descriptions of features specific to particular implementations of particular inventions. Certain features described in this specification in the context of separate implementations can also be implemented in combination in a single implementation. Conversely, various features described in the context of a single implementation can also be implemented in multiple implementations separately or in any suitable subcombination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination may be directed to a subcombination or variation of a subcombination.

(42) Similarly, while operations are depicted in the drawings in a particular order, this should not be understood as requiring that such operations be performed in the particular order shown or in

sequential order, or that all illustrated operations be performed, to achieve desirable results. In certain circumstances, multitasking and parallel processing may be advantageous. Moreover, the separation of various system components in the implementations described above should not be understood as requiring such separation in all implementations, and it should be understood that the described program components and systems can generally be integrated in a single software product or packaged into multiple software products.

(43) Thus, particular implementations of the invention have been described. Other implementations are within the scope of the following claims. In some cases, the actions recited in the claims can be performed in a different order and still achieve desirable results.

Claims

1. A system comprising one or more electronic processors configured to: receive, from a web browser of an unidentified user of a first web page, an indication that the unidentified user has entered into a conversation using a chat window of a chat program associated with the first web page; create a conversation identifier for the conversation, which conversation identifier and the conversation are stored in one or more persistent data stores; generate a first communication of the conversation comprising a first responder's request for information from the unidentified user; send the first communication to the web browser of the unidentified user; receive, from the web browser of the unidentified user using the chat window of the chat program associated with the first web page, a second communication of the conversation comprising a response to the request for information; receive a request for the conversation from the web browser of the unidentified user on a second web page that is different from the first web page; retrieve, from the one or more persistent data stores, the conversation based on the conversation identifier; and send the conversation to the web browser of the unidentified user via the second web page, wherein the sending of the conversation to the web browser of the unidentified user allows for the unidentified user and the first responder to continue the conversation using the second web page, wherein the unidentified user continues the conversation using a chat window of a chat program associated with the second web page.
2. The system of claim 1, wherein the one or more electronic processors are further configured to: route the conversation from the first responder to a second responder that is different from the first responder, wherein the routing of the conversation from the first responder to the second responder causes the one or more electronic processors to continue the conversation between the unidentified user and the second responder, and discontinue the conversation between the unidentified user and the first responder.
3. The system of claim 2, wherein the one or more electronic processors are further configured to: retrieve, from the one or more persistent data stores, the conversation based on the conversation identifier; and send the conversation to a computing device of the second responder.
4. The system of claim 3, wherein the one or more electronic processors are further configured to: route based on the conversation.
5. The system of claim 1, wherein the one or more electronic processors are further configured to: create the conversation identifier in response to receiving the indication that the unidentified user has entered into the conversation.
6. The system of claim 1, wherein the one or more electronic processors are further configured to: create the conversation identifier prior to the generation of the first communication of the conversation.
7. The system of claim 1, wherein the one or more electronic processors are further configured to: create the conversation identifier in response to generating the first communication of the conversation.
8. The system of claim 1, wherein the second communication does not include personally

identifying information of the identified user.

9. The system of claim 1, wherein the first responder is a virtual responder.

10. A system comprising one or more electronic processors configured to: receive, from a web browser of an unidentified user of a first web page, an indication that the unidentified user has entered into a conversation using a chat window of a chat program associated with the first web page; create a conversation identifier for the conversation, which conversation identifier and the conversation are stored in one or more persistent data stores; generate a first communication of the conversation comprising a first responder's request for information from the unidentified user, wherein the first responder is a virtual responder; send the first communication to the web browser of the unidentified user; receive, from the web browser of the unidentified user using the chat window of the chat program associated with the first web page, a second communication of the conversation comprising a response to the request for information; receive a request for the conversation from the web browser from a second web page that is different from the first web page; retrieve, from the one or more persistent data stores, the conversation based on the conversation identifier; send the conversation to the web browser of the unidentified user via the second web page, wherein the sending of the conversation to the web browser of the unidentified user allows for the unidentified user and the first responder to continue the conversation using the second web page, wherein the unidentified user continues the conversation using a chat window of a chat program associated with the second web page; route the conversation from the first responder to the second responder that is different from the first responder based on the conversation, wherein the routing of the conversation from the first responder to a second responder causes the one or more electronic processors to continue the conversation between the unidentified user and the second responder, and discontinue the conversation between the unidentified user and the first responder; retrieve, from the one or more persistent data stores, the conversation based on the conversation identifier; and send the conversation to a computing device of the second responder.

11. The system of claim 10, wherein the one or more electronic processors are further configured to create the conversation identifier in response to receiving the indication that the unidentified user has entered into the conversation.

12. The system of claim 10, wherein the one or more electronic processors are further configured to create the conversation identifier prior to the generation of the first communication of the conversation.

13. The system of claim 10, wherein the one or more electronic processors are further configured to create the conversation identifier in response to generating the first communication of the conversation.

14. A system comprising one or more electronic processors configured to: receive, from a web browser of an unidentified user of a first web page, an indication that the unidentified user has entered into a conversation using a chat window of a chat program associated with the first web page; create a conversation identifier for the conversation, which conversation identifier and the conversation are stored in one or more persistent data stores; generate a first communication of the conversation comprising a first responder's request for information from the unidentified user, wherein the first responder is a virtual responder; send the first communication to the web browser of the unidentified user; receive, from the web browser of the unidentified user using the chat window of the chat program associated with the first web page, a second communication of the conversation comprising a response to the request for information; receive a request for the conversation from the web browser from a second web page that is different from the first web page; retrieve, from the one or more persistent data stores, the conversation based on the conversation identifier; send the conversation to the web browser of the unidentified user via the second web page, wherein the sending of the conversation to the web browser of the unidentified user allows for the unidentified user and the first responder to continue the conversation using the

second web page, wherein the unidentified user continues the conversation using a chat window of a chat program associated with the second web page; identify a second responder that is different from the first responder; determine a communication protocol used by a computing device of the second responder; route the conversation from the first responder to the second responder, wherein the routing of the conversation from the first responder to the second responder causes the one or more electronic processors to continue the conversation between the unidentified user and the second responder, and discontinue the conversation between the unidentified user and the first responder; retrieve, from the one or more persistent data stores, the conversation based on the conversation identifier; and send the conversation to the computing device of the second responder based on the communication protocol used by the computing device of the second responder.

15. The system of claim 14, wherein the one or more electronic processors are further configured to: receive a third communication from the computing device of the second responder; and send the third communication to the web browser of the unidentified user.

16. The system of claim 15, wherein the third communication does not include the communication address of the computing device of the second responder.

17. The system of claim 14, wherein the one or more electronic processors are further configured to: create the conversation identifier in response to receiving the indication that the unidentified user has entered into the conversation.

18. The system of claim 14, wherein the one or more electronic processors are further configured to: determine a communication address of the computing device of the second responder that is associated with the communication protocol used by the computing device of the second responder; and send the conversation to the computing device of the second responder using the communication address.
