

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250262563

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Liu; Feng-Yu

Wastewater Storage Bucket Capable of Accelerately Recycling Waste Liquids

Abstract

A wastewater storage bucket contains a body. The body including: an outlet, an inlet, and a motor configured to drive a stirrer to rotate. The stirrer is vertically inserted into a bottom of an inner wall of the body and is configured to rotatably stir the waste liquids evenly. The body also includes a circular tube fixed on a top of the inner wall thereof, multiple spray heads defined on the circular tube and configured to molecularize the waste liquids, multiple heaters arranged on the outer wall of the body away from the motor and configured to heat the water liquids in the body, and a discharge orifice defined on a center of a bottom of the inner wall of the body and configured to discharge the waste liquids.

Inventors: Liu; Feng-Yu (Taichung City, TW)

Applicant: Liu; Feng-Yu (Taichung City, TW)

Family ID: 1000007716007

Appl. No.: 18/582881

Filed: February 21, 2024

Publication Classification

Int. Cl.: B01D1/20 (20060101); B01D1/22 (20060101); B01D5/00 (20060101)

U.S. Cl.:

CPC B01D1/20 (20130101); B01D1/225 (20130101); B01D5/0027 (20130101);

Background/Summary

TECHNICAL FIELD

[0001] The present disclosure relates to a wastewater storage bucket which is capable of accelerately recycling waste liquids by using multiple spray heads to spray mists to condense the steams of water of the waste liquids into the liquids, thus recycling the liquids purely and accelerately.

BACKGROUND

[0002] Taiwan is a major semiconductor manufacturing country and contributes considerable output value every year, but it also produces a large amount of waste. Wastewater produced by IC manufacturing plants, and most of wastewater are discharged from cleaning wafers, removing photoresist and etching. In the era of circular economy, how to convert waste into raw materials is something that both industry and government should pay attention to.

[0003] Conventionally, the traditional waste liquid recovery device mainly allows the waste water to reach a low-temperature boiling point between 30° C. and 60° C. in a vacuum distiller, and the water vapor condenses into water through the condenser. However, the traditional distiller cannot convert the large molecules of the recovered water into small molecules, resulting in poor purity, and the flow rate cannot be increased.

[0004] The present invention has arisen to mitigate and/or obviate the afore-described disadvantages.

SUMMARY

[0005] A primary aspect of the present invention is to provide a wastewater storage bucket which is capable of accelerately recycling waste liquids by using multiple spray heads to spray mists to condense the steams of water of the waste liquids into the liquids, thus recycling the liquids purely and accelerately.

[0006] To obtain above-mentioned aspect, a wastewater storage bucket provided by the present invention contains a body, and the body includes: [0007] an outlet defined on a top of an outer wall of the body, an inlet formed on the top of the outer wall of the body opposite to the outlet, and a motor fixed on a center of the top of the outer wall of the body and configured to drive a stirrer to rotate. The stirrer is vertically inserted into a bottom of an inner wall of the body and is configured to rotatably stir the waste liquids evenly; [0008] The body also includes a circular tube fixed on a top of the inner wall thereof, multiple spray heads defined on the circular tube and configured to molecularize the waste liquids, multiple heaters arranged on the outer wall of the body away from the motor and configured to heat the water liquids in the body, and a discharge orifice defined on a center of a bottom of the inner wall of the body and configured to discharge the waste liquids.

[0009] Other objects and features will be in part apparent and in part pointed out hereinafter.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] FIG. 1 is a cross sectional view showing the assembly of a wastewater storage bucket capable of accelerately recycling waste liquids according to a preferred embodiment of the present invention.

[0011] FIG. 2 is a cross sectional view taken along the line B-B of FIG. 1.

[0012] FIG. 3 is a cross sectional view showing the operation of the wastewater storage bucket capable of accelerately recycling waste liquids according to the preferred embodiment of the present invention.

DETAILED DESCRIPTION

[0013] FIG. 1 is a cross sectional view showing the assembly of a wastewater storage bucket capable of accelerately recycling waste liquids according to a preferred embodiment of the present invention. FIG. 2 is a cross sectional view taken along the line B-B of FIG. 1. The wastewater

storage bucket comprises a body **10**, and the body **10** includes an outlet **11** defined on a top of an outer wall thereof, an inlet **12** formed on the top of the outer wall of the body **10** opposite to the outlet **11**, a motor M fixed on a center of the top of the outer wall of the body **10** and configured to drive a stirrer **13** to rotate, wherein the stirrer **13** is vertically inserted into a bottom of an inner wall of the body **10** and is configured to rotatably stir the waste liquids evenly, the body **10** also includes a circular tube **14** fixed on a top of the inner wall thereof, multiple spray heads **15** defined on the circular tube **14** and configured to molecularize the waste liquids, multiple heaters **16** arranged on the outer wall of the body **10** away from the motor M and configured to heat the water liquids in the body **10**, and a discharge orifice **17** defined on a center of a bottom of the inner wall of the body **10** and configured to discharge toxic solvents or cleaning fluids of the waste liquids.

[0014] FIG. **3** is a cross sectional view showing the operation of the wastewater storage bucket capable of accelerately recycling waste liquids according to the preferred embodiment of the present invention. In operation, the motor M drives the stirrer **13** to rotatably stir the waste liquids evenly, thus separating the toxic solvents of the waste liquids from water. In the meantime, the multiple heaters **16** heat the water to steams. When the steams float upward, the multiple spray heads **15** of the circular tube **14** spray mists to condense the steams into the liquids, thus recycling the liquids. Thereafter, the liquids are purified to be recycled.

[0015] When introducing elements of the present invention or the preferred embodiments thereof, the articles “a”, “an”, “the” and “said” are intended to mean that there are one or more of the elements. The terms “comprising”, “including” and “having” are intended to be inclusive and mean that there may be additional elements other than the listed elements.

[0016] In view of the above, it will be seen that the several objects of the invention are achieved and other advantageous results attained.

[0017] As various changes could be made in the above constructions, products, and methods without departing from the scope of the invention, it is intended that all matter contained in the above description and shown in the accompanying drawings shall be interpreted as illustrative and not in a limiting sense.

Claims

1. A wastewater storage bucket comprising a body, and the body including: an outlet defined on a top of an outer wall of the body, an inlet formed on the top of the outer wall of the body opposite to the outlet, and a motor fixed on a center of the top of the outer wall of the body and configured to drive a stirrer to rotate, wherein the stirrer is vertically inserted into a bottom of an inner wall of the body and is configured to rotatably stir the waste liquids evenly; wherein the body also includes a circular tube fixed on a top of the inner wall thereof, multiple spray heads defined on the circular tube and configured to molecularize the waste liquids, multiple heaters arranged on the outer wall of the body away from the motor and configured to heat the water liquids in the body, and a discharge orifice defined on a center of a bottom of the inner wall of the body and configured to discharge the waste liquids.
