

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12393885
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Sarawgi; Aditya et al.

Determining and providing predetermined location data points to service providers

Abstract

A system and method for managing a network service is described. A system can provide a map interface for a user that includes a location pin. The system can detect a user input that sets the location pin at a selected pickup location on the map interface. In response to detecting the user input, the system can (i) determine an alternative pickup location based at least in part on historical information corresponding to clustered trip entries of the network service, and (ii) cause the map interface to dynamically and visually relocate the location pin to the alternative pickup location. The system may then receive a transport request from the mobile computing device of the user, and in response to receiving the transport request, select a transport provider to rendezvous with the user at the alternative pickup location.

Inventors: Sarawgi; Aditya (San Francisco, CA), Cui; Sophia (San Francisco, CA), Sweeney; Matthew (San Francisco, CA)

Applicant: Uber Technologies, Inc. (San Francisco, CA)

Family ID: 1000008766898

Assignee: Uber Technologies, Inc. (San Francisco, CA)

Appl. No.: 18/663562

Filed: May 14, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240296391 A1	Sep. 05, 2024

Related U.S. Application Data

continuation parent-doc US 17208238 20210322 US 12026641 child-doc US 18663562
continuation parent-doc US 14818053 20150804 US 11010693 20210518 child-doc US 17208238
us-provisional-application US 62033013 20140804

Publication Classification

Int. Cl.: **G06Q10/02** (20120101); **G06Q10/00** (20230101); **G06Q50/40** (20240101)

U.S. Cl.:

CPC **G06Q10/02** (20130101); **G06Q10/00** (20130101); G06Q50/40 (20240101)

Field of Classification Search

CPC: G06Q (10/02); G06Q (10/00); G06Q (50/40); G06Q (10/083); G06Q (50/43); G06Q (50/47); G06Q (50/50); H04L (12/14); H04M (3/00); H04M (15/00); H04M (17/00); H04W (4/24)

USPC: 705/5

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5557522	12/1995	Nakayama	N/A	N/A
5948040	12/1998	DeLorme	N/A	N/A
6058339	12/1999	Takiguchi	N/A	N/A
6233517	12/2000	Froeberg	N/A	N/A
6321158	12/2000	DeLorme	N/A	N/A
7263437	12/2006	Hirose	N/A	N/A
7822426	12/2009	Wuersch	N/A	N/A
8005488	12/2010	Staffaroni	N/A	N/A
8565789	12/2012	Staffaroni	N/A	N/A
9075136	12/2014	Joao	N/A	N/A
9158414	12/2014	Gluzberg	N/A	N/A
9547307	12/2016	Cullinane	N/A	N/A
9562785	12/2016	Racah	N/A	N/A
9599477	12/2016	Aula	N/A	N/A
9613386	12/2016	Arden	N/A	N/A
9631933	12/2016	Aula	N/A	G01C 21/3438
9702714	12/2016	Botea	N/A	N/A
9715233	12/2016	Mandeville-Clarke	N/A	N/A
9733096	12/2016	Colijn	N/A	N/A
10731998	12/2019	Rahematpura	N/A	N/A
2004/0249818	12/2003	Isaac	N/A	N/A
2006/0235739	12/2005	Levis	N/A	N/A
2007/0150375	12/2006	Yang	N/A	N/A

2007/0233373	12/2006	Choi	N/A	N/A
2008/0275645	12/2007	Hoshino	N/A	N/A
2008/0277183	12/2007	Huang	N/A	N/A
2009/0054081	12/2008	Tsai	N/A	N/A
2009/0156241	12/2008	Staffaroni	N/A	N/A
2009/0216600	12/2008	Hill	N/A	N/A
2009/0326991	12/2008	Wei	N/A	N/A
2011/0320232	12/2010	Staffaroni	N/A	N/A
2012/0004840	12/2011	Lee	N/A	N/A
2012/0130627	12/2011	Islam	N/A	N/A
2013/0073327	12/2012	Edelberg	N/A	N/A
2013/0132140	12/2012	Amin	N/A	N/A
2013/0132246	12/2012	Amin	705/34	G06Q 30/0284
2013/0159028	12/2012	Lerenc	N/A	N/A
2013/0164228	12/2012	Jaracz et al.	N/A	N/A
2014/0011522	12/2013	Lin	N/A	N/A
2014/0082069	12/2013	Varoglu	709/204	G06Q 50/40
2014/0129135	12/2013	Holden	N/A	N/A
2014/0365250	12/2013	Ikeda	N/A	N/A
2015/0002319	12/2014	Jin	N/A	N/A
2015/0006072	12/2014	Goldberg	N/A	N/A
2015/0067878	12/2014	Steelberg	N/A	N/A
2015/0081362	12/2014	Chadwick	N/A	N/A
2015/0143275	12/2014	Lee	N/A	N/A
2015/0161564	12/2014	Sweeney	N/A	N/A
2015/0219464	12/2014	Beaurepaire	701/538	G01C 21/3617
2015/0228192	12/2014	Kawamoto	N/A	N/A
2015/0248689	12/2014	Paul	N/A	N/A
2015/0254581	12/2014	Brahme	N/A	N/A
2015/0278618	12/2014	Nuscheler	N/A	N/A
2015/0302342	12/2014	Yeh	N/A	N/A
2015/0317568	12/2014	Grasso	N/A	N/A
2015/0339923	12/2014	Konig	N/A	N/A
2015/0339928	12/2014	Ramanujam	N/A	N/A
2016/0027306	12/2015	Lambert	N/A	N/A
2016/0027307	12/2015	Abhyanker	N/A	N/A
2016/0034828	12/2015	Sarawgi	N/A	N/A
2016/0034845	12/2015	Hiyama	N/A	N/A
2016/0042303	12/2015	Medina	N/A	N/A
2016/0048804	12/2015	Paul	N/A	N/A
2016/0055769	12/2015	Angelescu	N/A	N/A
2016/0071411	12/2015	Stenneth	N/A	N/A
2016/0187150	12/2015	Sherman	N/A	N/A
2016/0301698	12/2015	Katara	N/A	N/A
2016/0320195	12/2015	Liu	N/A	N/A
2016/0320198	12/2015	Liu	N/A	N/A
2016/0321771	12/2015	Liu	N/A	N/A
2016/0370194	12/2015	Colijn	N/A	N/A

2017/0038948	12/2016	Cun	N/A	N/A
2017/0052034	12/2016	Magazinik	N/A	N/A
2017/0059347	12/2016	Flier	N/A	G06Q 10/08355
2017/0098377	12/2016	Marco	N/A	N/A
2017/0103490	12/2016	Haparnas	N/A	N/A
2017/0132540	12/2016	Haparnas	N/A	N/A
2017/0153714	12/2016	Gao	N/A	N/A
2017/0160092	12/2016	Botea	N/A	N/A
2017/0169366	12/2016	Klein	N/A	N/A
2017/0193404	12/2016	Yoo	N/A	G06Q 10/06
2017/0213308	12/2016	Wellborn	N/A	N/A
2017/0277191	12/2016	Fairfield	N/A	N/A
2017/0286884	12/2016	Shoval	N/A	N/A
2017/0293950	12/2016	Rathod	N/A	N/A
2017/0300848	12/2016	Shoval	N/A	G06Q 10/063114
2017/0309171	12/2016	Zhao	N/A	N/A
2017/0314948	12/2016	Racah	N/A	N/A
2017/0337810	12/2016	Abe	N/A	N/A
2017/0365030	12/2016	Shoham	N/A	N/A
2018/0156623	12/2017	West	N/A	N/A
2018/0158325	12/2017	Bernhardt	N/A	N/A
2018/0189918	12/2017	Lu	N/A	N/A
2018/0202820	12/2017	Yu	N/A	N/A
2018/0202821	12/2017	Yu	N/A	N/A
2018/0338298	12/2017	Pan	N/A	N/A
2018/0342035	12/2017	Sweeney	N/A	N/A
2018/0356239	12/2017	Marco	N/A	N/A
2018/0374032	12/2017	Pan	N/A	N/A
2019/0137288	12/2018	Rahematpura	N/A	N/A
2019/0306258	12/2018	Yamashita	N/A	N/A
2020/0103242	12/2019	Chachra	N/A	G06F 16/29
2020/0160709	12/2019	Ramot	N/A	N/A
2020/0249042	12/2019	Warr	N/A	N/A
2020/0292335	12/2019	Rahematpura	N/A	N/A
2020/0305227	12/2019	Pan	N/A	N/A
2021/0140774	12/2020	Zhao	N/A	G01C 21/3811
2021/0209520	12/2020	Sarawgi	N/A	N/A
2021/0251041	12/2020	Pan	N/A	N/A
2021/0285783	12/2020	Warr	N/A	N/A
2022/0101207	12/2021	Gu	N/A	G06Q 50/40
2022/0418039	12/2021	Pan	N/A	N/A
2023/0337328	12/2022	Pan	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2395065	12/2000	CA	N/A

103617450	12/2013	CN	N/A
104567891	12/2014	CN	N/A
104575072	12/2014	CN	N/A
104931063	12/2014	CN	N/A
205751273	12/2015	CN	N/A
108701413	12/2017	CN	N/A
2010-208195	12/1997	JP	N/A
2007121528	12/2006	JP	N/A
3934985	12/2006	JP	N/A
2012-73995	12/2011	JP	N/A
2004-073639	12/2014	JP	N/A
2015122108	12/2014	JP	N/A
20040096684	12/2003	KR	N/A
20160104230	12/2015	KR	N/A
20170041237	12/2016	KR	N/A
WO 2002006994	12/2001	WO	N/A
WO 2011069170	12/2010	WO	N/A
WO-2014106617	12/2013	WO	N/A
WO 2015/0089207	12/2014	WO	N/A
WO 2016/0022587	12/2015	WO	N/A
WO 2017128927	12/2016	WO	N/A
WO 2017172415	12/2016	WO	N/A
WO-2017215322	12/2016	WO	G06F 3/048
WO 20190037549	12/2023	WO	N/A

OTHER PUBLICATIONS

Z. Liu, H. Zhang, G. Ouyang, J. Chen and K. Wu, “Data-Driven Pick-Up Location Recommendation for Ride-Hailing Services,” in IEEE Transactions on Mobile Computing, vol. 23, No. 2, pp. 1001-1015, <https://ieeexplore.ieee.org/abstract/document/9899740> (Year: 2022). cited by examiner

International Search Report in PCT/US2015/043654 dated Nov. 26, 2015. cited by applicant
IPRP in PCT/US2015/043654 dated Feb. 16, 2017. cited by applicant

International Search Report in PCT/US2016/066030 dated Feb. 28, 2017. cited by applicant

Written Opinion in SG 11201700671P dated Oct. 13, 2017. cited by applicant

EESR in EP 15830335.4 dated Nov. 29, 2017. cited by applicant

IPRP in PCT/US2016/066030 dated Jun. 21, 2018. cited by applicant

2nd Written Opinion in SG 11201700671P dated Aug. 29, 2018. cited by applicant

ESER in EP 16874019.9 dated Aug. 22, 2018. cited by applicant

ISR and Written Opinion in PCT/US2018/013583 dated Apr. 20, 2018. cited by applicant

ISR and Written Opinion in PCT/US2018/059230 dated Jan. 2, 2019. cited by applicant

Andrew J. Hawkins, Lyft is now suggesting more convenient pickup locations, because a little walking won't kill you. Jun. 26, 2017 The Verge (www.theverge.com). cited by applicant

Office Action in EP 15830335.4 dated Mar. 21, 2019. cited by applicant

Office Action in JP 2017-505856 dated Feb. 6, 2019. cited by applicant

Mark H. Walker, “Microsoft Office Visio 2003 Official Manual”, Initial Pressing, Nikkei BP Soft Press, Apr. 4, 2005, First Edition, pp. 423-425. cited by applicant

ISR dated Oct. 3, 2018 in PCT/US2018/039830. cited by applicant
Borison, Rebecca, "Uber Brings its SUV Fleet to NYC", Jul. 30, 2014, Business Insider, p. 1. cited by applicant
Hilen, Brittany, Uber and Google bring WIFI to cars in Philadelphia, Slashgear, dated Jul. 24, 2014, p. 1, <https://web.archive.org/web/20140724201314/http://www.slashgear.com/uber-and-google-bring-wifi-to-cars-in-philadelphia-22338326>. cited by applicant
Jain, "Contextual Adaptive User Interface for Android Devices", Annual IEEE India Conference (INDICON), IEEE, pp. 1-4 (2013). cited by applicant
IPRP in PCT/US2019/039830 dated Jun. 26, 2019. cited by applicant
Pelzer, et al., "A Partition-Based Match Making Algorithm for Dynamic Ridesharing", IEEE Transactions on Intelligent Transportation Systems, vol. 16, Issue: 5, pp. 2587-2596 (2015). cited by applicant
Office Action in EP 15830335.4 dated Nov. 21, 2019. cited by applicant
First Office Action in CN 201580043970 dated Apr. 22, 2020. cited by applicant
Pre-Examination Office Action in BR 112017002174-9 dated May 6, 2020. cited by applicant
Examination Report No. 1 for AU 2015301178 dated Jun. 11, 2020. cited by applicant
Office Action in EP 16874019.9 dated Jun. 9, 2020. cited by applicant
Pre-Exam Office Action in BR 112018011694-7 dated Jul. 13, 2020. cited by applicant
Exam Report No. 1 in AU 2018207620 dated Apr. 6, 2021. cited by applicant
EESR in EP 18873921.3 dated Jul. 14, 2021. cited by applicant
Lin et al. A Model of Multimodel Ridesharing and it's Analysis, 2016 17th IEEE International Conference on Mobile Data Management, pp. 164-173, Jun. 13-16, 2016 (2016). cited by applicant
Constine, John, "Uber is Now Testing 'Suggested Pickup Points'", <https://techcrunch.com/2015/07/08/uber-suggested—Feb. 24, 2024 pickup-points/> (Jul. 8, 2015). cited by applicant

Primary Examiner: Campbell; Shannon S

Assistant Examiner: Ma; Lisa

Attorney, Agent or Firm: Mahamedi IP Law LLP

Background/Summary

RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/208,238, filed on Mar. 22, 2021; which is a continuation of U.S. patent application Ser. No. 14/818,053, filed Aug. 3, 2015, now U.S. Pat. No. 11,010,693, issued on May 18, 2021, which claims the benefit of priority to U.S. Provisional Patent Application No. 62/033,013, filed Aug. 4, 2014; the aforementioned priority applications being hereby incorporated by reference in their entireties.

BACKGROUND

(1) Systems exist that can arrange for a service to be provided by a service provider through the use of computing devices. For example, a user can make a request for a service using her mobile device and a system can arrange for that service to be provided for the user by selecting a service provider. In many instances, the performance of the service can be dependent on a location specified by the user.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 illustrates an example system to arrange an on-demand service, under an embodiment.
- (2) FIG. 2A illustrates an example method for determining a location data point for an on-demand service, according to an embodiment.
- (3) FIGS. 2B and 2C illustrate example diagrams depicting regions and clustered location data points.
- (4) FIG. 3 illustrates an example method for providing a clustered location data point to a user device, under an embodiment.
- (5) FIG. 4A illustrates an example method for determining a suitable or best-suited location for performing an on-demand service, according to an embodiment.
- (6) FIG. 4B illustrates an example diagram depicting regions and predetermined best-suited location data points.
- (7) FIG. 4C illustrates an example method for providing a suitable or best-suited location to a user device, under an embodiment.
- (8) FIG. 5 illustrates an example method for arranging an on-demand service for a user, according to an embodiment.
- (9) FIG. 6 is a block diagram that illustrates a computer system upon which embodiments described herein may be implemented.
- (10) FIG. 7 is a block diagram that illustrates a mobile computing device upon which embodiments described herein may be implemented.

DETAILED DESCRIPTION

- (11) Examples described herein provide for a system that assists or guides users and/or service providers to travel to a predetermined or particular location for purposes of fulfilling an on-demand service. The system can use data corresponding to services that have been previously performed in order to determine particular locations that are best suited for initiating performance of on-demand services (e.g., pin point the best location for a user and a service provider to meet). Information corresponding to such a location can be provided to a mobile device operated by a requesting user and/or to a mobile device operated by a selected service provider.
- (12) In one example, a transport arrangement system (implemented on or by a computing device, system, or data center) can provide a network service or platform to enable users and service providers to request and receive transport services using their respective computing devices. The system can receive a request for transport service from a user device over one or more networks. The request for transport service can include a requested pickup location data point. The system can identify a predetermined location data point associated with the requested pickup location data point, if any, where the predetermined location data point is different from the requested pickup location data point. For example, the predetermined location data point can correspond to a location that has been determined by the system as being the best-suited location for initiating the transport service for a particular region. The system can select a driver to perform the transport service for the user and transmit an invitation to the selected driver, including the predetermined location data point (e.g., as opposed to the requested pickup location data point).
- (13) According to some examples, the system can determine location data points for different regions based on information about previously requested and/or completed transport services. The system can store transport service entries in one or more memory resources, where each transport service entry (also referred to herein as a “trip entry”) corresponds to a transport service that has been previously requested and/or completed. For example, a trip entry can include a user identifier of the user that requested the transport service, a driver identifier of the driver that provided the transport service, a requested pickup location data point, an initiated location data point (e.g., the

location where the transport service had started), a destination location data point where the transport service was completed, and/or other information, such as the vehicle type, the price, the route taken, etc. As used herein, a location data point can correspond to a latitude and a longitude coordinate that specifies a particular location or position. In other examples, a location data point can correspond to a coordinate in a different type of coordinate system.

(14) The system can determine a set of trip entries that each includes a requested pickup location data point in a particular region, determine the initiated location data points for that set, and determine, from those initiated location data points, which location data point is best suited as the pickup location (e.g., the best-suited location for ease of both the user and the service provider for initiating performance). Based on these determinations, the system can associate the best-suited location(s) with the particular region (or a particular location) and store the information as an entry in a pickup mapping table (e.g., referred to herein as a “pickup entry”). For example, for a region, Region X, at the northwest street corner of Street A and Street B (e.g., corresponding to a building on that street corner), the best-suited location can correspond to a position on Street A next to the curb thirty feet west of the street corner. The pickup entry for Region X can be stored in the pickup mapping table and can associate Region X with the determined best-suited location data point. As an addition or an alternative, the pickup entry for Region X can be associated with multiple best-suited location data points. The system can store multiple pickup entries in the pickup mapping table for different regions.

(15) In some examples, when the system receives a request for transport service, including the requested pickup location data point, the system can access the pickup mapping table from memory to determine if the requested pickup location data point is positioned within a region identified in a pickup entry. If the requested pickup location is positioned within a specified region of a pickup entry, the system can identify the corresponding predetermined location data point (e.g., the best-suited location data point) associated with that region. The system can then transmit the predetermined location data point to the selected driver's device as the pickup location for the driver to get to in order to initiate the transport service, as opposed to the requested pickup location specified by the user in the request for transport service.

(16) Still further, in some examples, the system can also assist a user in selecting the best pickup location for requesting a transport service. A user can operate a designated service application on her mobile device that communicates with the transport arrangement system. When the designated service application is opened or launched, the application can display a map user interface in which the current location of the user's device is shown. A graphic indicator (referred to herein as a “pin”) can also be shown on the map user interface representing the location that the user wishes to be picked up at. The user can move the pin to select a different location before making the request for transport service via user input on the designated service application. In some cases, depending on the current location of the user's device, the system can provide a location data points to the user's device to automatically position the pin to a specific location on the map interface on behalf of the user.

(17) In another example, the system can determine a set of trip entries that each includes a requested pickup location data point in a particular region. The system can perform a clustering operation(s) on the requested pickup location data points of the set in order to determine a single location data point for the particular region (e.g., referred to herein as a “clustered location data point” or a “calculated location data point”). The system can store the information about the region and the associated clustered location data point as an entry (e.g., referred to herein as a “clustered entry”) in a cluster mapping table. At a later time, when the system determines that a service application has been opened on a user device that is positioned within the particular region, the system can cause the service application to automatically position the pin on the map user interface to a position corresponding to the clustered location data point associated with that particular region.

(18) Still further, using similar operations describe herein, the system can use the mapping table to provide one or more proposed location data points for the user to assist the user in selecting a suitable pickup location for requesting a transport service. For example, the system can determine a plurality of requested pickup location data point in an area and determine a plurality of corresponding initiated location data points where the transport services had started for those requested pickup location data points. The system can determine, from the plurality of initiated location data points, one or more proposed location data points that are suitable locations for initiating the transport service. When the user is in the process of selecting the pickup location, e.g., is moving the pin in the area on the map user interface, the system can provide the one or more proposed location data points to be displayed on the map user interface, which each indicates a suitable location for initiating the transport service. The user can then move the pin to a proposed location data point to designate as the pickup location for the request.

(19) Among other benefits and technical effect, as compared to any conventional approach, examples described herein promote the efficiency of initiating on-demand services, thereby increasing the collective efficiency of the network service. Some examples recognize that pickup locations specified by users for transport services may not necessarily be a suitable location for actual pick up. A pickup location specifying a building address, for example, does not actually correspond to a location that is feasible for a service provider to actually pick up the user, while a pickup location near a street, in another example, may not have an area where the service provider can actually stop to pick up the user. In other words, some pickup locations specified by users may not be efficient or safe for users and service providers. This can result in a user and a service provider not knowing where each other will be, thereby causing a delay in initiating the transport service (wasting time for both users and service providers) and/or resulting in a negative experience in which the user has to contact the service provider to arrange an actual meeting location (or vice versa). Examples described herein can perform data computations on an immense collection of data to intelligently establish location associations that can be used to enable individual users and service providers to quickly rendezvous together with little or no user interaction.

(20) Additionally, some examples further recognize that the interests of the individual driver and/or passenger may not be aligned with the interest of a service which arranges the transport services. For example, a transport arrangement service may select drivers for riders based on optimization criteria which serves a collective (e.g., total passenger wait time), while the interest of the driver may be to acquire the next ride that is nearby. In this regard, the process of communicating a better pickup location can be determined without influence from the driver or rider, each of whom may have alternative self-interests or ability to determine the better pickup location. For example, if the position of the rider at a current instance was known to the driver and the driver has the ability to suggest the pickup location, the driver may have motivation to choose a spot which may have additional risk to reach (e.g., rider needs to cross busy street). Likewise, if the rider could demand the pickup location in each instance, the driver may be forced into a busy street or one which was zoned against stoppage. In both rider and driver approach, the rider and driver may lack instant knowledge of the location and/or environment (e.g., traffic condition), and neither would be able to take into account an optimization for the collective (e.g., all riders in a square mile who are needing pickup). Accordingly, examples as described provide for a service which (i) selects a pickup location (after receiving a pickup request) in a manner that balances the interests of the rider, driver and/or other riders/drivers, using real-time information from a population of drivers and riders, and (ii) further makes the selection without interference or influence of driver/rider (other than rider's initial request).

(21) As used herein, a client device, a driver device, a computing device, and/or a mobile device refer to devices corresponding to desktop computers, cellular devices or smartphones, personal digital assistants (PDAs), laptop computers, tablet devices, etc., that can provide network connectivity and processing resources for communicating with the system over one or more

networks. Client devices and driver devices can each operate a designated service application (e.g., a client application and a driver application, respectively) that is configured to communicate with the transport service arrangement system. A driver device can also correspond to a computing device that is installed in or incorporated with a vehicle, such as part of the vehicle's on-board computing system.

(22) Still further, while some examples described herein relate to transport services, the system can enable other on-demand location-based services (for example, a food truck service, a delivery service, an entertainment service) to be arranged between users and service providers. For example, a user can request an on-demand service, such as a delivery service (e.g., food delivery service, messenger service, food truck service, or product shipping service) or an entertainment service (e.g., mariachi band, string quartet) using his or her mobile device, and the system can select a service provider, such as a driver, food provider, band, etc., to provide the on-demand service for the user.

(23) One or more examples described herein provide that methods, techniques, and actions performed by a computing device are performed programmatically, or as a computer-implemented method. Programmatically, as used herein, means through the use of code or computer-executable instructions. These instructions can be stored in one or more memory resources of the computing device. A programmatically performed step may or may not be automatic.

(24) One or more examples described herein can be implemented using programmatic modules, engines, or components. A programmatic module, engine, or component can include a program, a sub-routine, a portion of a program, or a software component or a hardware component capable of performing one or more stated tasks or functions. As used herein, a module or component can exist on a hardware component independently of other modules or components. Alternatively, a module or component can be a shared element or process of other modules, programs or machines.

(25) Some examples described herein can generally require the use of computing devices, including processing and memory resources. For example, one or more examples described herein may be implemented, in whole or in part, on computing devices such as servers, desktop computers, cellular or smartphones, personal digital assistants (e.g., PDAs), laptop computers, printers, digital picture frames, network equipment (e.g., routers) and tablet devices. Memory, processing, and network resources may all be used in connection with the establishment, use, or performance of any example described herein (including with the performance of any method or with the implementation of any system).

(26) Furthermore, one or more examples described herein may be implemented through the use of instructions that are executable by one or more processors. These instructions may be carried on a computer-readable medium. Machines shown or described with figures below provide examples of processing resources and computer-readable mediums on which instructions for implementing examples described herein can be carried and/or executed. In particular, the numerous machines shown with examples described herein include processor(s) and various forms of memory for holding data and instructions. Examples of computer-readable mediums include permanent memory storage devices, such as hard drives on personal computers or servers. Other examples of computer storage mediums include portable storage units, such as CD or DVD units, flash memory (such as carried on smartphones, multifunctional devices or tablets), and magnetic memory. Computers, terminals, network enabled devices (e.g., mobile devices, such as cell phones) are all examples of machines and devices that utilize processors, memory, and instructions stored on computer-readable mediums. Additionally, examples may be implemented in the form of computer-programs, or a computer usable carrier medium capable of carrying such a program.

(27) System Description

(28) FIG. 1 illustrates an example system to arrange an on-demand service for a user and a service provider, under an embodiment. As described herein, the system can process location data associated with previously requested and/or completed on-demand services in order to determine

informative location information for use with arranging on-demand services. The system can provide location information to user devices and/or services provider devices when users operate their respective designated service applications, when requests for on-demand services are made, and/or after service providers are selected.

(29) In the example of FIG. 1, the system **100** includes a dispatch **110**, a client device interface **120**, a driver device interface **130**, a location cluster **140**, a location match **142**, a location map **160**, and a plurality of databases. A plurality of client devices **180** and a plurality of driver devices **190** can communicate with the system **100** over one or more networks using, for example, respective designated service applications **181**, **191** that are configured to communicate with the system **100** via the client device interface **120** and the driver device interface **130**, respectively. The components of the system **100** can combine to process location data and to arrange a transport service for a requesting user using location data. Logic can be implemented with various applications (e.g., software) and/or with hardware of a computer system that implements the system **100**.

(30) Depending on implementation, one or more components of the system **100** can be implemented on network side resources, such as on one or more servers. The system **100** can also be implemented through other computer systems in alternative architectures (e.g., peer-to-peer networks, etc.). As an addition or an alternative, some or all of the components of the system **100** can be implemented on client devices, such as through applications that operate on the client devices **180** and/or the driver devices **190**. For example, a client service application **181** and/or a driver service application **191** can execute to perform one or more of the processes described by the various components of the system **100**. The system **100** can communicate over a network, via a network interface (e.g., wirelessly or using a wireline), to communicate with the one or more client devices **180** and the one or more driver devices **190**.

(31) The system **100** can communicate, over one or more networks, with client devices **180** and driver devices **190** using a client device interface **120** and a device interface **130**, respectively. The device interfaces **120**, **130** can each manage communications between the system **100** and the respective computing devices **180**, **190**. The client devices **180** and the driver devices **190** can individually operate client service applications **181** and driver service applications **191**, respectively, that can interface with the device interfaces **120**, **130** to communicate with the system **100**. According to some examples, these applications can include or use an application programming interface (API), such as an externally facing API, to communicate data with the device interfaces **120**, **130**. The externally facing API can provide access to the system **100** via secure access channels over the network through any number of methods, such as web-based forms, programmatic access via restful APIs, Simple Object Access Protocol (SOAP), remote procedure call (RPC), scripting access, etc.

(32) According to examples, the system **100** can provide information about the network service to both client applications **181** and driver applications **191**, including the state of the network service. The system **100** can arrange for a transport service to be provided for a user by receiving a request for the transport service from a client device **180** (through use of the client service application **181**) and by selecting a driver to perform the transport service for that user. The user may have specified by a pickup location data point by moving and positioning a graphic indicator (e.g., a pin) on the map user interface of the client service application **181** or by inputting an address, street intersection, or landmark in a text submission feature. Alternatively, a pickup location data point can correspond to the current location of the client device **180**, as determined by the client device **180** using one or more geo-aware resources of the client device **180**, such as a global positioning system (GPS) receiver. For example, the dispatch **110** can receive the request, access the client database **112** to determine user information, access the driver database **114** to determine which drivers are available to provide the transport service, and select a driver based on one or more specified parameters via the driver select component of the dispatch **110**.

(33) Once the transport service is arranged for the user, the system **100** can monitor the status or progress of driver and/or the transport service (e.g., by communicating with a driver device **190** of the selected driver through use of the driver service application **191**) and can determine a variety of information for that particular transport service. For example, during the transport service, the driver application **191** can periodically transmit location information of the driver device **190** (using the GPS receiver of the driver device **190**) and/or transmit state information of the driver application **191** to the system **100**. During and/or after completion of the transport service, information about the transport service can be stored as a trip entry **151** in a trips database **150**. Depending on implementation, the system **100** can store trip entries **151** in a single trips database **150** or in multiple trips databases **150** for different geographic areas (e.g., a neighborhood, a city, a metropolitan area, a county, a state, a country, etc.).

(34) A trip entry **151** can include a variety of information about a particular transport service. For example, for an individual transport service (or trip), the trip monitor component of the dispatch **110** can receive information (e.g., periodically and/or intermittently, in response to user input) from a driver device **190** of the selected driver once the trip is arranged. In one example, the trip monitor component can receive information from the driver device **190** about the time and/or its location when the driver provides input (using the driver service application **191**) to accept an invitation to perform the transport service. Similarly, the trip monitor can receive information from the driver device **190** about the time and/or its location when the driver provides input to initiate the transport service (e.g., the requested user has been picked up by the driver). The trip monitor can continue to monitor the progress of the transport service by receiving time and/or location information from the driver device **190** via the driver service application **191**, including when the transport service has been completed at the destination (where the user is dropped off).

(35) As such, in some examples, a trip entry **151** can include a trip identifier (ID), a user ID of the user that requested the transport service, a driver ID of the driver that provided the transport service, a requested pickup location data point (specified by the user in the request for the transport service), an initiated location data point where the transport service begun (e.g., the location of the driver device **190** when the driver provides input indicating that the transport service has begun), a destination location data point where the transport service was completed (e.g., the location of the driver device **190** when the driver provides input indicating that the transport service has been completed), and other information, such as the vehicle type, the price, the duration of the trip, the route taken, etc.

(36) In addition, in one example, a trip entry **151** can also include information whether the initiated location data point for the trip was a suitable or correct pickup location or an inadequate or poor pickup location for the user. For example, a suitable or correct pickup location can be a location that is (i) close enough for the user to quickly or easily get to (e.g., just around the corner or just outside the front door of the building the user is in), (ii) close to the requested pickup location data point requested of the user (e.g., within a short predetermined distance of the user), and/or (iii) near a street that enables the driver to move in the direction that the user wishes to travel in once the user is picked up at the location (e.g., without the driver having to perform a U-turn after picking up the user). Similarly, an inadequate or poor pickup location can be a location that is too far/too difficult for the user to get to, far from the requested pickup location data point requested by the user, and/or near a street that causes the driver to have to travel in inefficient or opposite directions once the user is picked up at the location (e.g., the driver has to make multiple right turns to get to a street going in the correct direction).

(37) Depending on implementation, for individual trips, the system **100** can determine whether an initiated location data point is suitable or inadequate based on one or more of a distance between the requested pickup location data point and the initiated location data point, positive or negative feedback provided by the user (e.g., a rating provided by the user, comments provided by the user, etc.), the route traveled by the driver to the user's destination during performance of the transport

service (e.g., whether the route was efficient or not as a result of the initiated location data point), or survey information **153**. In one example, a large number (e.g., more than a threshold number) of initiated pickup location data points that are within a small distance of each other (e.g., within a predetermined distance) can indicate that those initiated location data points are suitable location data points for pickup. In another example, after a user is picked up by a driver for a transport service, the user can be prompted via the client service application **181** to respond to a survey question of whether the pickup was at a suitable or correct pickup location (e.g., the user can simply provide an input of “yes” or “no”). Such survey information **153** can be associated with the trip entry **151** to identify whether the associated initiated location data point was suitable or not. As an addition or an alternative, the survey information **153** can be used to mark a positive or negative indication for the initiated location data point on the trip entry **151**.

(38) Using the location information from the stored trip entries **151**, the system **100** can determine which locations are most suitable or convenient for the performance of transport services in given regions and can provide location information to users and/or drivers when appropriate. According to an example, the location cluster **140** can access the trips database **150** to perform one or more clustering processes on requested pickup location data points. Similarly, the location cluster **140** can perform one or more clustering processes on initiated location data points. As described herein, a clustering process corresponds to a process or analysis that is used (e.g., once, multiple times, iteratively, etc.) to group sets of location data points together so that location data points in the same group are more similar to each other than to those in other groups (e.g., based on distance between location data points).

(39) In addition, in some examples, the location cluster **140** can also use map data **171** from a map database **170** to identify streets, determine landmarks or points of interest, and/or determine individual regions. For example, using map data **171**, the location cluster **140** can determine that a group of requested pickup location data points can be associated with or correspond to a particular region. Such a region can be a landmark, a particular building or portions of a building, a street corner region or portions of a street, a park, a city block, multiple city blocks, a section of a street, a neighborhood, multiple neighborhoods, a city, a county, etc. In examples described herein, a region can also be defined using three or more location data points that make up the perimeter or boundary of that region.

(40) Depending on implementation, the system **100** can determine and use clustered location data points for assisting the users and/or the drivers with identifying suitable locations for initiating transport services in different ways. Using one or more clustering processes (and/or map data **171**), the location cluster **140** can (i) determine groups of requested pickup location data points (where each group can be associated with a unique identifier or be associated with or correspond to a particular region, in some examples), and (ii) determine a clustered (or calculated) pickup location data point for each group or region. Similarly, the location cluster **140** can use one or more clustering processes to determine groups of initiated pickup location data points and determine a clustered initiated location data point for each group. Still further, in other examples, the location cluster **140** can also use one or more clustering processes to determine groups of destination location data points and determine a clustered destination location data point for each group. In one example, for a group or corresponding region, the clustered location data point can correspond to a location data point in which the sum of the distances from all location data points in that group is minimized. As such, a clustered location data point can be a substantially central or averaged location data point of a group of location points or a region. An example of a clustering operation is k-means clustering. The location cluster **140** can store the clustered location data point with the associated region as a cluster entry **147** in a cluster mapping database **145**.

(41) For example, the cluster mapping database **145** can store one or more tables with a plurality of cluster entries **147**. A cluster entry **147** can include (i) a corresponding identifier (ID) of the cluster entry **147**, (ii) a clustered location data point (and/or an associated ID of the clustered location data

point), (iii) an ID of the associated region or an ID of the group of location data points, and/or (iv) geographic data about the associated region, such as a set of three or more location points that make up the associated region, or geographic data to define the group of location data points. While a single cluster mapping database **145** is illustrated in FIG. **1**, depending on variations, the system **100** can store cluster entries **147** in a plurality of mapping tables in the cluster mapping database **145** or in multiple cluster mapping databases **145** for different location points, for different geographic areas and/or for different users or groups of users.

(42) Depending on implementation, the location cluster **140** can also determine cluster entries **147** for individual users, for groups of users, and/or for all users of the system **100**. As discussed, each trip entry **151** in the trips database **150** can be associated with a user ID. The location cluster **140** can communicate with the client database **112**, determine the requested pickup location data points for an individual user from the trip entries **151** for that user, perform one or more clustering processes in order to determine groups of requested pickup location data points for that user, where each group is associated with a region, and determine a clustered location data point for each group/region.

(43) As an example, a user, User **1**, may have previously requested and received five hundred trips in the San Francisco Bay Area, with two hundred previous trips having been made during a particular time of day (e.g., evening) and in a particular region (e.g., at a street corner near User **1**'s office in San Francisco), one hundred previous trips having been made during another particular time of day (e.g., morning) and in another region (e.g., on a street next to the train station in San Francisco), etc. As a result of performing the clustering operation(s), for User **1**, the location cluster **140** can determine different groups of requested pickup location data points—a first group of requested pickup location data points can correspond to a first region near User **1**'s office, a second group of requested pickup location data points can correspond to a second region near the train station, etc. The location cluster **140** can also determine a clustered location data point for each group/region using the clustering operation(s) and/or other operations.

(44) For User **1**, the location cluster **140** can then generate and store (i) a cluster entry **147** for the first group in the cluster mapping database **145**, in which the corresponding first group or region is associated the first clustered location data point, (ii) a cluster entry **147** for the second group in the cluster mapping database **145**, in which the corresponding second group or region is associated with the second clustered location data point, and so forth for other groups or regions and associated clustered location data points. As an addition or an alternative, in similar fashion, the location cluster **140** can determine groups/regions and their associated cluster location data points based on the requested pickup location data points for other individual users, for more than one user (e.g., groups of users), and/or for all users of the system **100**. In addition, in some examples, the location cluster **140** can use the requested pickup location data points for only the last predefined set of trips (e.g., the most recent three hundred trips, two thousand trips, etc.) in order to determine the cluster entries **147** for a user, multiple users, and/or all users. Still further, in other examples, the location cluster **140** can also generate and store cluster entries **147** based on different times of day.

(45) According to examples, the system **100** can use the cluster entries **147** to provide users with a suitable/beneficial initial location for requesting transport services. In examples described herein, a clustered pickup location data point can correspond to a location that represents a region or a group of location data points where a user and/or other users have previously requested transport services (e.g., a representative location data point for a group of location data points). As such, in one example, if a user is currently located in or is close to a region where that user (and/or a collection of other users) had made previous transport requests, the system **100** can enable an appropriate pickup location data point to be initially set for that user even before the user has to manually select or input the pickup location data point. For example, when the user operates the client service application **181**, the pin can be automatically placed at a particular location data point (that is

different from the user's current location) on the map user interface. The user can then change the pickup location or move the pin from that initial location if preferred.

(46) The system **100** leverages the notion that, typically, a user may mark or pin, on the map interface of the client service application **181**, a pickup location data point at a place that is close to a street or is accessible by a vehicle. In one example, when a user makes a request from her desk inside her office building (which can be very large), the user may move the pin to a specific street corner or a turnaround loop in front of the building entrance (as opposed making a request with the pickup location data point being specified as the user's current location at her desk). The user may continue to request an identical or similar location data point numerous times if that location was a suitable pickup location for transport service. Using this location information, the location cluster **140** can perform a clustering operation(s) to determine a clustered location data point for this region or group of pickup location data points, which can represent a suitable pickup location data point based on the user's previous requested pickup location data points.

(47) Once cluster entries **145** are stored in the cluster mapping database **145**, the system **100** can use the stored location and group/region information, if available and/or applicable, to provide clustered location data points to client devices **180**. For example, a user that wants to request a transport service can open or launch a service application **181** on her client device **180**. When the user opens the service application **181** on her client device **180** (or wakes up/activates the service application **181** from an inactive or sleep mode to an active mode), the service application **181** can exchange data with system **120** via the client device interface **120**. In one example, the location match **142** can receive status information **185** from the client device **180** via the client device interface **120**. The status information **185** can include, for example, the user's ID (and/or device ID) as well as the current location of the user's client device **180**. The location match **142** can access the appropriate cluster mapping database **145** to determine whether the current location of the client device **180** is within a region that is specified in a cluster entry **147** (and/or within a predefined distance from a region that is specified in a cluster entry **147**) when the service application **181** is opened or activated. In other words, the location match **142** can determine whether the user is in or is close to a region that has an associated clustered location data point. Alternatively, the location match **142** can determine whether the user's location corresponds to a location in the group of clustered locations (as opposed to a region), and can determine the associated clustered location data point. In such examples, the cluster mapping database **145** can associate individual location data points in the group with the associated clustered location data point.

(48) If the client device **180** is determined to be located within a region that is specified in a cluster entry **147** or within a predefined distance from a region that is specified in a cluster entry **147** (or alternatively, if the location of the client device **180** corresponds to a location in the group of clustered locations), the location match **142** can identify the cluster entry **147** and determine a corresponding clustered location data point that is associated with that region. The location match **142** then can provide the clustered location data point **187** to the client device **180** to cause the service application **181** to automatically position a graphic indicator (e.g., a pin) to a location on the map interface corresponding to the clustered location data point **187** on behalf of the user. The user can then select an input to make a request for the transport service without first having to separately specify a pickup location data point. The request can include the clustered location data point as the requested pickup location data point, e.g., as opposed to the current location of the user being the requested pickup location data point.

(49) As an addition or an alternative, the location match **142** can access the cluster mapping database **145** to determine whether the current location of the client device **180** is within or close to a specified region based on a predefined or user-configured hierarchy. For example, the location match **142** can first search or query the cluster entries **147** corresponding to the particular user (using the user's ID and/or device ID) before searching or querying the cluster entries **147** of groups of users and/or all users of the system **100**. If the location match **142** determines that the

client device **180** is not within or close to a region that is specified in a set of cluster entries **147** corresponding to that user, the location match **142** can then determine whether the client device **180** is within or is close to a region that is specified in another set of cluster entries **147** corresponding to both the user and other users (e.g., as other users' transport service pickup location data points can be helpful for identifying a commonly used or suitable/beneficial pickup location).

(50) If the client device **180** is determined to not be located in or close to a region that is specified in a cluster entry **147**, the location match **142** will not provide any clustered location data point to the client device **180**. For example, a cluster entry **147** for the region may not have yet been generated or stored by the system **100** if there are an insufficient number of transport requests that have been made in the region by the user and/or other users (e.g., a predetermined threshold number). As such, the service application **181** operating on the user's client device **180** can display, on the map interface, the pin at a default location (e.g., the current location of the user) as opposed to a clustered location data point.

(51) In this manner, the system **100** can guide the pin on the map interface to a convenient and suitable location for the user to make a transport request without having the user manually or separately specify a pickup location data point when operating the service application **181**. The clustered location data point can be representative of a location that the user should request pickup for a transport service based on the user's (and/or other users') prior history of specifying requested pickup location data points in the region.

(52) In another example, the location cluster **140** can determine a clustered initiated location data point for a group of initiated location data points and provide information about the clustered initiated location data point(s) to the client device **180**. Examples described herein recognize that the actual location where a transport service initiated does not necessarily correspond to the pickup location specified by the user in the transport request. For example, a given city block can include one or more large buildings (office building, apartment complex, etc.), in which users leaving those buildings have requested and received transport services. The city block, such as one that is bounded by Market Street to the north, Mission Street to the south, 11th Street to the west, and 10th Street to the east, can be located in a city, such as San Francisco, where certain areas of the streets surrounding the city block may not be suitable for initiating transport services. As a result, transport services may have initiated in certain locations on streets surrounding the city block. For a collection of trip entries **151** in which the respective transport services had initiated within a predetermined distance of the city block, for example, the location cluster **140** can determine that there are six best-suited pickup location data points on the surrounding streets based on the groupings of the initiated location data points. For example, the location cluster **140** can have determined a first best-suited pickup location data point from a first group of initiated location data points on 10th Street near the corner of 10th Street and Market Street, a second best-suited pickup location data point from a second group of initiated location data points on 11th Street near the corner of 11th Street and Market Street, and so forth. As a result, if a user that is near the city block or is considering getting picked up near the city block, the system **100** can propose one or more best-suited location data points (e.g., each corresponding to a clustered initiated location data point) to the user.

(53) In such an example, the system **100** can determine when the user is providing user input to reposition or move the pin on the map user interface of the client application **181**. The location match **142** can receive information about the user input and the location corresponding to the position of the pin on the map user interface (e.g., "the pin location") via the client device interface **120**. Based on the pin location, the location match **142** can determine the one or more clustered initiated location data points that are within a predetermined distance of that location by identifying cluster entries **147** in the cluster mapping database **145**. The one or more clustered initiated location data points can represent a location(s) that is suitable for initiating transport services in an area near the location (e.g., suggested pickup locations). The location match **142** can provide the one or more

clustered initiated location data points to the client application **181**, so that the client application **181** can display one or more corresponding graphic indicators on the map user interface. As an addition or an alternative, in some examples, the suggested location data points can correspond to clustered pickup location data points, as opposed to clustered initiated location data points, determined by the location cluster **140** and stored in the cluster mapping database **145**.

(54) As the user continues to move the pin location, the location match **142** can continue to provide updated one or more clustered initiated location data points to the client application **181** so that the client application **181** can dynamically display the graphic indicators corresponding to the one or more clustered initiated location points. The user can place the pin on one of the graphic indicators to set as a pickup location for a request for the transport service. In some examples, when the pin is moved close to a graphic indicator on the map user interface, the graphic indicator can dynamically expand in size from a default size (e.g., a circle with a predetermined radius or size) to a larger size to provide a visual feedback for the user, and if the user places the pin on the expanded graphic indicator (e.g., stops providing user input to move the pin), the pin can jump to or snap to the center of the graphic indicator. The graphic indicator can be reduced in size to the default size and/or removed from display on the map user interface once the pin is placed on the graphic indicator.

(55) According to some examples, the system **100** can also use location information from trip entries **151** to guide or assist users and/or drivers to travel to particular locations for enhancing the ease of pickups for providing transport services. In one example, the location mapping **160** can access the trips database **150** to determine, for a given region, a set of trip entries **151** each having a requested pickup location data point in the given region. Depending on implementation, the location mapping **160** can use map data **171** from the map database **170** to identify location points, identify streets, and/or determine landmarks or points of interest, etc., in order to determine individual regions. As an addition or an alternative, the location mapping **160** can also use information about determined clustered location data points for the associated groups of clustered location data points or regions **161** previously determined by the location clustering **140** and stored in the cluster mapping database **145**.

(56) For each of the set of trip entries **151** in a given region, the location mapping **160** can determine the initiated location data point (representing the driver's location when the transport service was initiated or where the user got into the vehicle). Typically, when a user makes a transport request and provides a pickup location data point, the selected driver may not actually be pick up the user at the exact pickup location data point. Instead, the driver may pull over or park at a location that is proximate to the requested pickup location data point, accessible by the vehicle, accessible by the user, etc. Accordingly, for the set of trip entries **151** in the given region, a plurality of initiated location data points can exist that are different from the requested pickup location data point. Based on the previous initiated location data points for a given region, the location mapping **160** can determine a suitable or best-suited location data point for the given region.

(57) For example, the location mapping **160** can determine, from the cluster mapping database **145**, the clustered initiated location data points. In another example, the location mapping **160** can determine the clustered initiated location data points from the cluster mapping database **145** that correspond to groups of initiated location data points that users had indicated as being a suitable or accurate pickup location (e.g., a sub-set of the set of trip entries **151** may have those initiated location data points previously indicated by users as being suitable or accurate pickup locations based on survey information **153**). As an addition or an alternative, the location mapping **160** can process the clustered initiated location data points (or a sub-set of the clustered initiated location data points) based on map data **171** so that the clustered initiated location data point can be fitted to a street, road, highway, turnaround, driveway, etc. Still further, a user of the system **100** can also provide input to configure, adjust, or select the clustered location data point for a given region (e.g., as part of an auditing process). Such a clustered initiated location data point can be representative

of the best-suited pickup location data point.

(58) The location mapping **160** can associate the best-suited pickup location data point with a given region or with a set of location data points and store the information as a pickup entry **167** in the pickup mapping database **165** (e.g., discussed below with FIGS. 4A through 4C). For example, a set of pickup location data points made on a certain street segment can be associated with a set of initiated location data points, and the clustered initiated location data point can correspond to the best-suited pickup location data point for the set of pickup location data points. Alternatively, the location mapping **160** can associate the best-suited pickup location data point with individual location data points as pickup entries **167** in the pickup mapping database **165**.

(59) According to some examples, the location mapping **160** can also associate text and/or an image(s) with each best-suited pickup location data point in a corresponding pickup entry **167**. Text and/or image(s) can be associated with a best-suited pickup location data point based on map data **171** and/or other input from users of the system **100**. Such text and/or image(s) (e.g., referred to herein as “associated information”) can correspond to the best-suited pickup location data point and provide information about that location data point. As an example, the associated information can provide text that informs a driver to go to a particular location, such as, “pull up to the loading zone,” “go to Door 2 at Terminal 1,” “the pickup location is on your right just in front of the bank,” etc. In this manner, the system **100** can use the information in the pickup mapping database **165** to assist or guide the driver for purposes of transport services and/or to provide supplemental information to improve user pickups.

(60) As an example, a user can make a transport request **183** by operating the client service application **181** on her client device **180**. The transport request **183** can include a pickup location data point **184** specified by the user. Such a pickup location data point **184** can correspond to a clustered location data point previously provided by the system **100** or one that is manually selected or inputted by the user (e.g., by moving the pin to a location and/or moving the pin to a suggested location data point). The dispatch **110** can receive the transport request **183**, and perform a driver selection process based on current conditions, including the pickup location data point **184**. The driver select component can access the driver database **114** to determine a pool of drivers to select a driver from based on one or more parameters (e.g., proximity or estimated travel times to the pickup location data point **184** and/or direction of travel of the drivers, etc.). Depending on implementation, the dispatch **110** can access the pickup mapping database **165** to determine whether the pickup location data point **184** is mapped to another predetermined location or is within a region specified in a pickup entry **167**. The dispatch **110** can make this determination in response to receiving the transport request **183**, and before, during, or after selecting the driver for the user.

(61) If the pickup location data point **184** is determined to not be located in a region that is specified in a pickup entry **167** or is determined to not have a corresponding best-suited pickup location, the dispatch **110** can send a transport service invitation **193** to the selected driver's device **190**, including the pickup location data point **184** specified by the user. For example, a pickup entry **167** for the pickup location data point **184** or the region may not have yet been generated or stored by the location mapping **160** if there are an insufficient number of transport requests that have been made in the region by the user and/or other users (e.g., a predetermined threshold number). The driver service application **191** can display a user interface that includes location information based on the pickup location data point **184** and an invitation feature to enable the driver to either accept or reject the invitation **193**. If the driver accepts the invitation **193**, the driver service application **191** can transmit an acceptance **195** and can display (through interaction with or use of other applications and/or services) a route and/or directions to the pickup location data point **184**.

(62) On the other hand, if the pickup location data point **184** is determined to be located in a region that is specified in a pickup entry **167** or is determined to have a corresponding best-suited pickup location, the dispatch **110** can determine a predetermined location data point **194** of that pickup

entry **167**. In other words, the dispatch **110** can determine that the pickup location data point **184** has an associated predetermined location data point **194** (as a result of it being in the given region). The dispatch **110** can transmit a transport invitation **193** to the selected driver's device **190** that includes the predetermined location data point **194** corresponding to that region. As described herein, the predetermined location data point **194** can correspond to a best-suited location data point for a given region or for a specific location data point that was previously determined by the location mapping **160** and subsequently stored as a pickup entry **167** in the pickup mapping database **165**. The driver service application **191** can receive the predetermined location data point **194** as opposed to the actual pickup location data point **184** specified by the user. If the driver accepts the invitation **193** that includes the predetermined location data point **194**, the driver service application **191** can transmit an acceptance **195** and can display (through interaction with or use of other applications and/or services) a route and/or directions to the predetermined location data point **194** as opposed to the pickup location data point **184**.

(63) In many situations, providing the predetermined location data point **194** that represents the best pickup location can be more beneficial than providing the requested pickup location data point **184**. For example, the user may have made the transport request **183** from his current location, which could be inside a building, such as a house. Such a pickup location data point may provide an address to the driver, but may not inform the driver where to actually pull up to the curb or park. Similarly, if the driver sees a corresponding pin of such a pickup location data point on the map interface of the service application **191**, the driver may not know exactly where to travel to. Accordingly, by determining the best-suited location data point based on historical location information (e.g., from stored trip entries) and providing that best-suited location data point to the driver, the driver can provide more accurate and efficient pickups for transport services.

(64) Still further, in some examples, from the corresponding pickup entry **167**, the dispatch **110** can also determine associated information, if any, that corresponds to the predetermined location data point **194**. According to an example, associated information can be stored in the respective pickup entry **167** corresponding to the given region. The associated information can provide textual and/or graphic information that guides the driver to a particular location that is associated with the predetermined location data point **194**. By providing such associated information to the driver device **190**, the service application **191** can display supplemental information, such as text, to inform the driver to travel to the best-suited location.

(65) As an addition or an alternative, if the user's pickup location data point **184** is in a given region of a pickup entry **167**, the dispatch **110** can provide both the pickup location data point **184** and the predetermined location data point **194** to the driver device **190** (and associated information, such as text). The driver service application **191** can receive both location data points and use each location data point for different purposes. According to an example, when the invitation **193** is received, the service application **191** can use the pickup location data point **184**, perform a reverse geocoding process to identify a corresponding address for the pickup location data point **184**, and display a user interface showing the user's location (e.g., on a map) along with the address. If the driver accepts the invitation **193**, the service application **191** can then use the predetermined location data point **194** to provide the driver with a more detailed, more accurate, and best-suited pick up location. In another example, as the driver approaches the pickup location data point **184** (e.g., is within a predefined distance from the pickup location), the service application **191** can then display the supplemental textual information based on the predetermined location data point **194**. As such, the driver can be generally familiarized with where to travel to get to the user, but also be provided with an exact location to pick up the user.

(66) The system **100** can continue to update the databases as transport services are continuously arranged by the dispatch **110**. In some examples, as the system **100** continuously updates the trips database **150** with trip entries **151**, the location clustering **140** and the location mapping **160** can also continue to update the cluster mapping database **145** and the pickup mapping database **165**.

Depending on variations, the components of the system **100** can update the respective databases periodically or intermittently based on input from a user of the system **100**. In another example, the components of the system **100** can update the respective databases each time one or a set of trip entries **151** are added to the trips database **150**.

(67) Still further, a user of the system **100** can control when the system **100** updates the cluster mapping database **145** and the pickup mapping database **165**, e.g., as a whole or depending on different regions. For example, based on user configuration, the location cluster **140** can update the cluster mapping database **145** periodically (e.g., at a first frequency), and the location mapping **160** can update the pickup mapping database **165** periodically (e.g., at a first frequency or a different frequency).

(68) In addition, while the location mapping **160** and the location clustering **140** are illustrated as different components in the example of FIG. **1**, in other examples, the location mapping **160** and the location clustering **140** can be combined as one component or the location clustering **140** can perform the functionality of both. Similarly, other components of FIG. **1** can be included with or be a part of another component.

(69) Methodology

(70) FIG. **2A** illustrates an example method for determining a location data point for an on-demand service, according to an embodiment. A method such as described by an embodiment of FIG. **2A** can be implemented using, for example, components described with an embodiment of FIG. **1**. Accordingly, references made to elements of FIG. **1** are for purposes of illustrating a suitable element or component for performing a step or sub-step being described.

(71) A system **100** can arrange transport services to be provided by drivers for requesting users through use of computing devices. The system **100** can store a trip entry for each transport service that has been requested by a user and/or completed in a data store. In some variations, the system **100** can arrange other on-demand services, such as a delivery service, a food service, an entertainment service, etc., to be performed. Referring to FIG. **2A**, the system **100** can store a plurality of on-demand service entries (e.g., trip entries) in a memory resource, including storing a set of on-demand service entries that corresponds to a particular region (**210**). Each on-demand service entry of the set can include a requested location data point (e.g., a requested pickup location data point). The system **100** can continue to generate and store on-demand service entries each time a request for an on-demand service is made and/or completed.

(72) In some examples, the system **100** can perform one or more clustering processes, such as k-means clustering, in order to group on-demand service entries together based on requested location data points and/or to determine regions for the groups. For example, the system **100** can determine hundreds of groups of location data points or regions including location data points within a geographic area, such as an area defined for San Francisco, California. In this geographic area, a given region can correspond to a group of requested location data points. The system **100** can determine a clustered location data point for the group of location data points or for the given region based, at least in part, on the requested location data points of the set (**220**). According to one example, the system **100** can perform one or more clustering processes, such as k-means clustering, to determine a clustered location data point for the given region. Such a clustered location data point can be a substantially central or averaged location data point for the group of requested location data points in the given region. Still further, depending on implementation, the system **100** can determine a clustered location data point for a given region for a particular user. For example, for an individual user, the system **100** can determine on-demand service entries for that user and determine requested location data points for a given region.

(73) For each region, the system **100** can then store the clustered location data point with the associated region in a cluster mapping table (**230**). For example, the system **100** can generate a cluster entry for each group of location data points or for each region that identifies that group or region (e.g., with a region ID and/or three or more location data points that define the region), the

associated clustered location data point, and/or a user ID, if the cluster entry is for a particular user. The system **100** can access the cluster mapping table at a later time for purposes of assisting a user in making an on-demand service request.

(74) As an addition or an alternative, the method described in FIG. 2A can also be performed with respect to other location data points stored in the set of trip entries. For example, rather than determining a clustered location data point based on a set of requested location data points, the system **100** can determine a clustered location data point based on a set of initiated location data points. Alternatively, the system **100** can determine a clustered location data point based on a set of destination location data points.

(75) FIG. 2B illustrates an example diagram depicting regions and clustered location data points. The diagram **250** illustrates an area corresponding to an intersection of two streets. Based on performing one or more clustering processes on requested location data points, the system **100** may have determined two groups of requested pickup location data points corresponding to two regions, Region A **260** and Region B **270**. While the area may include additional regions, for purposes of simplicity, only two regions are illustrated in the diagram **250**.

(76) As illustrated in FIG. 2B, Region A **260** corresponds to a region encompassing a first group of requested location data points and Region B **270** corresponds to a region encompassing a second group of requested location data points (each requested location data point being indicated by a white circle). Each requested location data point can correspond to a location data point specified in an on-demand service request by a user operating a client device. In addition, by performing one or more clustering processes, the system **100** can also determine a clustered location data point (CLDP) for each region.

(77) For example, the system **100** may have determined CLDP A **265** for Region A **260** and CLDP B **275** for Region B **270**. The system **100** can then generate and store, in a memory resource, a first cluster entry for Region A **260** with the associated CLDP A **265** (e.g., as a latitude and a longitude coordinate) and a second cluster entry for Region B **270** with the associated CLDP B **275** (e.g., as a latitude and a longitude coordinate). The system **100** can modify the cluster entries (e.g., modify the respective regions and/or the respective CLDPs) as additional on-demand service requests having requested location data points within the regions are made by users.

(78) FIG. 2C illustrates an example diagram depicting a portion of a user interface provided by a client service application running on the client device. According to an example, a user may have opened the client service application on her client device, such as after a period of inactivity, after the client service application was activated from a sleep or inactive mode on the device, etc. In response, the service application can automatically determine the current location of the client device (e.g., the user's current location) and transmit, over one or more networks (e.g., a cellular network), the current location data point to the system **100**.

(79) In this example, the system **100** had determined that the user's current location data point is within a specified region (e.g., Region A **260**) of a cluster entry (such as previously determined as illustrated in FIG. 2B) by accessing the clustering mapping table using the received current location data point. In response, the system **100** had determined the CLDP A **265** of that region, and had transmitted the CLDP A **265** to the client device.

(80) The diagram **280** illustrates a portion of the user interface of the service application, such as a portion of the map user interface, as a result of receiving the CLDP A **265** as a suitable pickup request location data point for the user. For example, after receiving the CLDP A **265** from the system **100**, the service application can automatically move or show the pin **290** at the corresponding CLDP A **265** on the user interface. Accordingly, the diagram **280** can provide a graphic indicator showing the user's current location **285** as well as the pin **290** at a different location. The user can then just select a feature to request the on-demand service without having to first manually move the pin **290** to a location on the map user interface. The automatic placement of the pin **290** to the CLDP A **265** can be extremely helpful in some situations, such as when the

client device has a large GPS error so that the user's current location **285** appears to be further away from where the user actually is located.

(81) FIG. **3** illustrates an example method for providing a clustered location data point to a user device, under an embodiment. A method such as described by an embodiment of FIG. **3** can be implemented using, for example, components described with an embodiment of FIG. **1**.

Accordingly, references made to elements of FIG. **1** are for purposes of illustrating a suitable element or component for performing a step or sub-step being described.

(82) For example, FIG. **3** illustrates a method performed by the system **100** in order to cause a client service application to automatically display a pin (such as the pin **290** illustrated in FIG. **2C**) on a map user interface. The system **100** can detect that the client service application has been opened or activated on a user's device (**310**). According to some examples, when the service application is opened or activated on the user's device, the service application can transmit information to the system **100**, such as a current location of the user's device, the device ID, and/or the user ID associated with the user's device.

(83) The system **100** can receive the current location of the user's device and determine whether the device is in a region that has an associated clustered location data point (**320**). For example, the system **100** can access the cluster mapping table in order to determine whether the current location is in a region specified in a cluster entry. If yes, the system **100** can identify the clustered location data point corresponding to the region, and transmit the clustered location data point to the user's device. In this manner, the system **100** can cause the service application on the user's device to automatically position, on the map user interface, a pin to a position corresponding to the clustered location data point (**330**). On the other hand, if no clustered location data point is specified for the current location of the user's device, the system **100** would not cause the service application to position the pin to a specified location (**340**). For example, the service application can display the pin at a default position (e.g., such as the user's current location data point).

(84) In this manner, when the user is in a specified region and opens or activates the service application, the graphic pin can be automatically moved to or positioned at a position corresponding to a suitable pickup location that is based on the user's previous service requests (and/or other users' previous service requests). This can enable the user to make a request for the on-demand service without having to manually select a suitable pickup location beforehand. If the clustered location data point is not the location the user would like, he or she can simply move the pin to another location via user input or input an address or a landmark specifying the preferred pickup location.

(85) FIG. **4A** illustrates an example method for determining a suitable or best-suited location for performing an on-demand service, according to an embodiment. A method such as described by an embodiment of FIG. **4A** can be implemented using, for example, components described with an embodiment of FIG. **1**. Accordingly, references made to elements of FIG. **1** are for purposes of illustrating a suitable element or component for performing a step or sub-step being described.

(86) The system **100** can store a plurality of on-demand service entries (e.g., trip entries) in a memory resource, including a set of on-demand service entries for a given region (**410**). Each on-demand service entry in the set has a requested location data point in the given region and an initiated location data point. As described herein, an initiated location data point corresponds to a location of a service provider when the service provider initiated performance of the on-demand service for the user. For example, for a transport service, the initiated location data point can correspond to a location where the driver was when the user entered the vehicle and/or when the driver provided input via the driver service application that transport service had started. In another example, for a delivery service, the initiated location data point can correspond to a location where the service provider received or picked up a product for delivery.

(87) Depending on implementation, the system **100** can perform one or more clustering processes, such as k-means clustering, in order to group on-demand service entries together based on

requested location data points and to determine regions for the groups. In another variation, the system **100** can use the same groups or regions previously determined and specified in cluster entries in a cluster mapping table or database. Still further, in another example, the system **100** can perform one or more clustering processes in order to group on-demand service entries together based on initiated location data points and to determine regions for the groups. For example, the system can perform clustering processes on the initiated location data points to first determine groups of initiated location data points and then determine, for each group of initiated location data points, the associated requested location data points. In this manner, each group of initiated location data points can have an associated group of requested location data points.

(88) In addition, by performing one or more clustering processes, the system **100** can determine a best-suited location data point for the on-demand service based, at least in part, on the initiated location data points of the set of on-demand service entries for the given region (e.g., based on historical data) (**420**). According to some examples, the system **100** can determine a sub-set of the set of on-demand service entries that have initiated location data points indicated by users as being a suitable or accurate initiation location for the on-demand service. From the sub-set, the system **100** can identify a corresponding sub-set of initiated location data points and perform one or more clustering processes to determine a best-suited location data point. Still further, the system **100** can determine the best-suited location data point using map data.

(89) The system **100** can then generate and store an entry for the best-suited initiated location data point with a given region in a mapping table (e.g., a pickup mapping table) (**430**). The system **100** can also associate text and/or an image(s) with the initiated location data point in a corresponding entry. Such entries can be used by the system **100** to assist service providers to travel to the best location for initiating on-demand services.

(90) FIG. **4B** illustrates an example diagram depicting regions and predetermined best-suited location data points for those regions. In one example, the diagram **450** graphically illustrates a plurality of entries created by the system **100** as described in the method of FIG. **4A**. For example, the entries can correspond to the pickup entries **167** stored in the pickup mapping database **165** as described in FIG. **1**. In this case, the diagram **450** illustrates three such entries that each associates a region with a best-suited location data point.

(91) The diagram **450** illustrates an area corresponding to an intersection of two streets. According to an example, for purposes of simplicity, the area illustrated in the diagram **450** can be the same area shown in the diagram **250** of FIG. **2B**. The diagram **450** illustrates that the system **100** has determined three regions in the area, Region A **460**, Region B **470**, and Region C **480**, and a best-suited location data points (BLDP) for each region, BLDP A **465**, BLDP B **475**, BLDP C **485**, respectively. In this manner, three corresponding entries have been created, with each entry identifying a region (e.g., using a region ID, using three or more location data points for the perimeter of the region, etc.) and a corresponding BLDP (e.g., a latitude and a longitude coordinate). In addition, in some examples, one or more entries can include associated information for the BLDP.

(92) While the area may include additional regions, for purposes of simplicity, only three regions are illustrated in the diagram **450**. Still further, depending on variations, one or more regions can be the same regions as previously determined with respect to the clustered location data point, such as described in FIGS. **2A** and **2B** (see Region B, for example).

(93) The regions shown in the diagram **450** indicate that when an on-demand service request is made with a requested location data point within a specified region, the system **100** can select a driver and provide the corresponding BLDP to the driver's device (e.g., as opposed to the requested location data point or concurrently with the requested location data point, depending on implementation). For example, if a user makes a transport service request specifying a pickup location data point in Region A **460**, the system **100** can receive the request, select a driver to perform the transport service, and transmit an invitation to the selected driver's device. As opposed

to transmitting the requested pickup location data point, the system **100** can transmit (e.g., along with the invitation or after the driver accepts the invitation) the associated BLDP A **465** to the driver device. The BLDP A **465** can provide a more accurate and more suitable location data point for the driver to travel to as the BLDP A **465** would be shown as a point on a road (contrasted with a location data point that is within a building as depicted on a map).

(94) FIG. **4C** illustrates an example method for providing a suitable or best-suited location to a user device, under an embodiment. A method such as described by an embodiment of FIG. **4C** can be implemented using, for example, components described with an embodiment of FIG. **1**.

Accordingly, references made to elements of FIG. **1** are for purposes of illustrating a suitable element or component for performing a step or sub-step being described.

(95) According to some examples, the system **100** can use data determined from analyzing historical pickup locations and/or historical initiated locations to provide suggested locations for a user. For example, the system **100** can store, in memory resources, a database that includes a plurality of cluster entries, where each cluster entry corresponds to a clustered location data point that is associated with a group of initiated pickup locations or region (or alternatively, a group of requested pickup locations). In some examples described herein, the clustered initiated location data point can be mapped to a particular streets using map data.

(96) Referring to FIG. **4C**, the system **100** can determine that a client service application has been opened or launched on the user device (**490**). When the service application is launched on the user device, the service application establishes a connection with the system **100** over one or more networks and provides a communication message indicating the status of the service application and/or user information (including the user location determined from the GPS receiver of the user device).

(97) The system **100** can determine that user input has been made by the user corresponding to the repositioning or moving of a graphic indicator (e.g., the pin) on the map user interface of the service application (**492**). For example, the user may move the pin by providing user input on the map user interface (e.g., touch input via a touch-sensitive screen of the user device) in order to specify a pickup location. As the user provides user input to reposition or move the pin on the map user interface of the service application, the system **100** can receive information about the user input (e.g., that the user is repositioning the pin) and/or the location corresponding to the position of the pin on the map user interface (e.g., “the pin location”).

(98) Based on the pin location, the system **100** can determine the one or more clustered initiated location data points that are within a predetermined distance of that location (or within a region of the pin location) by identifying cluster entries (**494**). The predetermined distance can be user-configured by an administrative user of the system **100** (e.g., 100 or 200 meters from the pin location). A clustered initiated location data point, as described herein, can correspond to a suitable location that would be efficient for the user's transport service, as it represents a location in which previous transport services had begun. The system **100** can cause one or more graphic features corresponding to the one or more suitable locations to be displayed on the map user interface of the user device (**496**). For example, the system **100** can provide the one or more clustered initiated location data points to the client application, so that the client application can display one or more corresponding graphic indicators on the map user interface.

(99) As an addition or an alternative, the system **100** can provide a set of clustered initiated location data points that are in a large area where the user is located (e.g., 1 mile or 2 miles from the user's location). For example, when the service application is initially opened, the system **100** can provide the set of clustered initiated location data points in the large area to the service application. The service application can store the data locally and when the user provides input to reposition the pin, the service application can display a sub-set of the set of clustered initiated location data points based on the pin location as graphic features on the map user interface. In this example, the suggested pick up locations can be pre-loaded so as to reduce wait times or delays as a result of

latency when the user repositions the pin frequently in a short amount of time.

(100) As the user continues to move the pin location, the system **100** can continue to provide updated one or more clustered initiated location data points to the service application so that the service application can dynamically display the graphic features corresponding to the one or more clustered initiated location points. The user can place the pin on one of the graphic features to specify as a pickup location for a request for the transport service and can make a request for a transport service. The system **100** can receive a request for the transport service from the user device (**498**). The request can include the pickup location, which can correspond to an arbitrary location or a clustered initiated location data point, depending on the user's input.

(101) FIG. 5 illustrates an example method for arranging an on-demand service for a user, according to an embodiment. A method such as described by an embodiment of FIG. 5 can be implemented using, for example, components described with an embodiment of FIG. 1.

Accordingly, references made to elements of FIG. 1 are for purposes of illustrating a suitable element or component for performing a step or sub-step being described.

(102) The system **100** can receive a request for a transport service from a user operating a client device (**510**). The request can include a requested pickup location data point, as well as other information, such as the user's ID, device ID, etc. In response to receiving the request, the system **100** can determine whether the requested pickup location data point is within a region that has an associated predetermined location data point (**520**). As described herein, a predetermined location data point can correspond to a best-suited location data point that was previously determined by the system **100** by performing one or more operations on historical data of previous transport services. Alternatively, the system **100** can determine whether the requested pickup location data point has a corresponding predetermined location data point.

(103) For example, in reference to FIG. 1, the dispatch **110** can perform a look up process or search operation in the pickup mapping database **165** to determine whether any pickup entries **167** specifies a region that the requested pickup location data point is positioned in. If the requested location data point is not in a region with an associated predetermined location data point, the dispatch **110** can continue with default operations, in which the dispatch **110** can select a driver to perform the transport service for the user based, at least in part, on the requested location data point, as well as based on other factors, such as the current locations of the drivers in the area (e.g., within a radius of the requested location data point), the status of the drivers in the area, etc. (**560**). The dispatch **110** can then transmit, to the selected driver's device, an invitation to perform the transport service for the user (**570**). The invitation can include the requested location data point so that the driver service application operating on the driver's device can use the requested location data point to inform the driver where the driver would have to travel to if he or she were to accept the invitation.

(104) On the other hand, if the dispatch **110** identifies a pickup entry **167** that specifies a region that the requested pickup location data point is positioned in, the dispatch **110** can determine the corresponding predetermined location data point associated with the region (**530**). The driver select component can select a driver to perform the transport service for the user based, at least in part, on the requested location data point (**540**). As an addition or an alternative, the system **100** can perform a driver selection process based, at least in part, on the predetermined location data point.

(105) Once a driver is selected, the dispatch **110** can transmit, to the selected driver's device, an invitation to perform the transport service, including the predetermined location data point, as opposed to the requested location data point (**550**). In another example, the invitation can also include the requested location data point. The driver service application operating on the driver's device can display information about the invitation and enable the driver to reject/ignore the invitation or accept the invitation via user input.

(106) Alternatively, the dispatch **110** can transmit the invitation to the driver's device with the requested pickup location data point, and the driver service application operating on the driver's

device can (i) perform a reverse geocoding process to identify a corresponding address for the requested pickup location data point, and (ii) display information about the invitation using the corresponding address. After the driver accepts the invitation, the dispatch **110** can transmit the predetermined location data point to the driver's device to enable the driver service application to assist or guide the driver using the predetermined location data point.

(107) In either implementation, once the driver accepts the invitation, the driver service application can display a map user interface showing the driver's current location, and in some examples, through interaction with another application (e.g., a map application or routing application), display a route and/or turn-by-turn directions from the driver's current location to the predetermined location data point. As an addition or an alternative, textual and/or graphical information associated (e.g., associated information) with the predetermined location data point can be provided to the driver's device to enable the driver service application to use the associated information to further inform the driver as to the precise location to travel to. For example, when the driver accepts the invitation, the driver service application can display (e.g., concurrently with the map user interface, route, and/or turn-by-turn directions) textual information associated with the predetermined location data point (e.g., "Pull Over On 10^{sup}.th St. Just After Passing Market St."). In another example, the driver service application can display associated information when it determines that the driver is a predetermined time and/or distance away from the predetermined location data point.

(108) While FIG. 5 illustrates step **540** and/or step **560** to be performed after step **520**, in other examples, the system **100** can perform a driver selection process after receiving a request for a transport service (step **510**) and before determining whether the requested location data point is in a region that has an associated predetermined location data point (step **520**). In another example, the system **100** can perform a driver selection process concurrently with determining whether the requested location data point is in a region that has an associated predetermined location data point (step **520**).

(109) For illustrative purposes, a use case scenario example is described below with respect to the method of FIG. 5. A user can be at San Francisco International Airport (SFO) and want a transport service to a destination (e.g., her home). The user may have arrived from a flight and may have made her way towards an exit in the arrivals terminal (on the 2nd level of SFO). When the user makes a request with a requested pickup location data point at this location, the system **100** can determine whether the requested pickup location data point is within a predefined region that has an associated predetermined location data point. In this example, the system **100** can determine that the requested pickup location is within a predefined region. The predefined region (e.g., corresponding to an area near the arrivals terminal on the 2nd level of SFO) can have an associated predetermined (and best-suited) location data point as well as associated textual and/or graphical information.

(110) As a result of processing a prior set of completed trip entries associated with the predefined region, the system **100** can have determined that the best-suited location data point for initiating transport services (e.g., picking up users) in the predefined region is actually just outside the departures terminal on the 3rd level of SFO as opposed to the arrivals terminal on the 2nd level of SFO. In addition, in some cases, because portions of actual roads may be on different levels of height and may overlap each other (e.g., one may be on top of the other), merely providing the latitude and longitude coordinate for the best-suited location data point to the driver service application may not be completely helpful for the driver. Accordingly, the system **100** can also provide the associated textual and/or graphical information to the driver device to inform the driver device to, for example, "Pick Up the User at the Departures Terminal on 3rd Level."

(111) Hardware Diagrams

(112) FIG. 6 is a block diagram that illustrates a computer system upon which embodiments described herein may be implemented. For example, in the context of FIG. 1, the system **100** may be implemented using a computer system such as described by FIG. 6. The system **100** may also be

implemented using a combination of multiple computer systems as described by FIG. 6.

(113) In one implementation, a computer system **600** includes processing resources **610**, a main memory **620**, a read only memory (ROM) **630**, a storage device **640**, and a communication interface **650**. The computer system **600** includes at least one processor **610** for processing information and the main memory **620**, such as a random access memory (RAM) or other dynamic storage device, for storing information and instructions to be executed by the processor **610**. The main memory **620** also may be used for storing temporary variables or other intermediate information during execution of instructions to be executed by the processor **610**. The computer system **600** may also include the ROM **630** or other static storage device for storing static information and instructions for the processor **610**. A storage device **640**, such as a magnetic disk or optical disk, is provided for storing information and instructions, including clustering instructions **642** and mapping instructions **644**.

(114) For example, the processor **610** can execute the clustering instructions **642** to implement logic for (i) determining clustered location data points based on stored information about previously requested and/or completed transport services, and (ii) generating cluster entries associating regions with clustered location data points, such as described in FIGS. **1** through **3**. The processor **610** can also execute the mapping instructions **644** to implement logic for (i) determining best-suited location data points based on stored information about previously initiated or at least partially performed transport services, and (ii) generating pickup entries associating regions with best-suited location data points, such as described in FIGS. **1** through **5**.

(115) The communication interface **650** can enable the computer system **600** to communicate with one or more networks **680** (e.g., cellular network) through use of the network link (wireless or wireline). Using the network link, the computer system **600** can communicate with one or more other computing devices and/or one or more other servers or datacenters. In some variations, the computer system **600** can receive a transport request **652** from a client device of a user via the network link. The transport request **652** can include the user's user ID, a requested pickup location data point, a destination location data point, and/or a vehicle type selection.

(116) The processor **610**, through execution of instructions, can select a driver to perform the transport service for the requesting user. The computer system **600** can then transmit an invitation **654** to the selected driver's device over the network link. In some examples, if the requested pickup location data point is determined to be within a specified region having an associated predetermined (or best-suited) location data point, the computer device **600** can transmit (e.g., along with or after transmitting the invitation **654**) the predetermined location data point **656** to the selected driver's device. The driver service application operating on the driver's device can use the predetermined location data point **656** for purposes of assisting or guiding the driver to a precise and best-suited pickup location for the driver.

(117) The computer system **600** can also include a display device **660**, such as a cathode ray tube (CRT), an LCD monitor, or a television set, for example, for displaying graphics and information to a user. One or more input mechanisms **670**, such as a keyboard that includes alphanumeric keys and other keys, can be coupled to the computer system **600** for communicating information and command selections to the processor **610**. Other non-limiting, illustrative examples of input mechanisms **670** include a mouse, a trackball, touch-sensitive screen, or cursor direction keys for communicating direction information and command selections to the processor **610** and for controlling cursor movement on the display **660**.

(118) Examples described herein are related to the use of the computer system **600** for implementing the techniques described herein. According to one embodiment, those techniques are performed by the computer system **600** in response to the processor **610** executing one or more sequences of one or more instructions contained in the main memory **620**. Such instructions may be read into the main memory **620** from another machine-readable medium, such as the storage device **640**. Execution of the sequences of instructions contained in the main memory **620** causes

the processor **610** to perform the process steps described herein. In alternative implementations, hard-wired circuitry may be used in place of or in combination with software instructions to implement examples described herein. Thus, the examples described are not limited to any specific combination of hardware circuitry and software.

(119) FIG. 7 is a block diagram that illustrates a mobile computing device upon which embodiments described herein may be implemented. In one embodiment, a computing device **700** may correspond to a mobile computing device, such as a cellular device that is capable of telephony, messaging, and data services. The computing device **700** can correspond to a client device or a driver device. Examples of such devices include smartphones, handsets or tablet devices for cellular carriers. The computing device **700** includes a processor **710**, memory resources **720**, a display device **730** (e.g., such as a touch-sensitive display device), one or more communication sub-systems **740** (including wireless communication sub-systems), input mechanisms **750** (e.g., an input mechanism can include or be part of the touch-sensitive display device), and one or more location detection mechanisms (e.g., GPS component) **770**. In one example, at least one of the communication sub-systems **740** sends and receives cellular data over data channels and voice channels.

(120) The processor **710** can provide a variety of content to the display **730** by executing instructions and/or applications that are stored in the memory resources **720**. For example, the processor **710** is configured with software and/or other logic to perform one or more processes, steps, and other functions described with implementations, such as described by FIGS. 1 through 6, and elsewhere in the application. In particular, the processor **710** can execute instructions and data stored in the memory resources **720** in order to operate a service application, as described in FIGS. 1 through 6. Still further, the processor **710** can cause one or more user interfaces **715** to be displayed on the display **730**, such as one or more user interfaces provided by the service application.

(121) A user can operate a client device (such as the computing device **700**) to operate the service application in order to make a request for a transport service. In one example, when the user opens or activates the service application on the computing device **700**, the service application can (i) automatically retrieve or receive a location data point **795** (such as a location data point corresponding to the current location of the computing device **700** that is determined from the GPS component **770**), and (ii) provide the location data point **795** to the transport arrangement system (not shown in FIG. 7). The transport arrangement system can wirelessly transmit a clustered location data point **745**, if any, to the computing device **700** via the communication sub-systems **740**, such as described in FIGS. 1 through 3. Such a clustered location data point **745** can be associated with a region that encompasses the coordinate of the location data point **795**. According to some examples, the processor **710** can execute the instructions for the service application to cause the service application to display a map user interface **715** showing a graphic pin that is positioned at a location corresponding to the clustered location data point **745**.

(122) While FIG. 7 is illustrated for a mobile computing device, one or more examples may be implemented on other types of devices, including full-functional computers, such as laptops and desktops (e.g., PC).

(123) It is contemplated for examples described herein to extend to individual elements and concepts described herein, independently of other concepts, ideas or system, as well as for examples to include combinations of elements recited anywhere in this application. Although examples are described in detail herein with reference to the accompanying drawings, it is to be understood that the concepts are not limited to those precise examples. Accordingly, it is intended that the scope of the concepts be defined by the following claims and their equivalents. Furthermore, it is contemplated that a particular feature described either individually or as part of an example can be combined with other individually described features, or parts of other examples,

even if the other features and examples make no mention of the particular feature. Thus, the absence of describing combinations should not preclude having rights to such combinations.

Claims

1. A computer-implemented method for managing a network service, the method comprising: providing a map interface for display on a mobile computing device of a user of the network service, the map interface including a location pin, the map interface enabling the user to select a pickup location; detecting a user input that sets the location pin at a first position representing a user-selected pickup location on the map interface; in response to detecting the user input, (i) determining an alternative pickup location near the user-selected pickup location based at least in part on historical information comprising corresponding to clustered trip entries of the network service, and (ii) causing the map interface to dynamically and visually relocate the location pin to a second position representing the alternative pickup location on the map interface; configuring the map interface to enable the user to transmit a transport request that automatically specifies the alternative pickup location without additional user input to change the user-selected pickup location; receiving a transport request from the mobile computing device of the user; and in response to receiving the transport request, selecting a transport provider to rendezvous with the user at the alternative pickup location.
2. The method of claim 1, wherein causing the map interface to dynamically and visually relocate the location pin to the alternative pickup location includes enlarging a first graphic indicator on the map interface as compared to a second graphic indicator, the first graphic indicator identifying the alternative pickup location and the second graphic indicator identifying the user-selected pickup location.
3. The method of claim 1, wherein causing the map interface to dynamically and visually relocate the location pin to the second position representing the alternative pickup location includes providing a first graphic indicator that moves from the user-selected pickup location to the alternative pickup location.
4. The method of claim 3, wherein the first graphic indicator is provided in response to detecting the user input.
5. The method of claim 1, wherein determining the alternative pickup location includes: determining a set of pickup locations in a specified region that includes a current location of the user by accessing a mapping table stored in one or more memory resources, the mapping table including the clustered trip entries that individually associate the specified regions with at least one corresponding pickup location of the set of pickup locations.
6. The method of claim 5, wherein the user-selected pickup location corresponds to a current location of the user, and wherein the alternative pickup location is within a predefined distance of the current location of the user.
7. The method of claim 5, wherein the mapping table identifies the alternative pickup location as being associated with the specified region that includes the current location of the user.
8. A non-transitory computer readable medium storing instructions for managing a network service, wherein the instructions, when executed by one or more processors, cause the one or more processors to: provide a map interface for display on a mobile computing device of a user of the network service, the map interface including a location pin, the map interface enabling the user to select a pickup location; detect a user input that sets the location pin at a first position representing a user-selected pickup location on the map interface; in response to detecting the user input, (i) determine an alternative pickup location near the user-selected pickup location based at least in part on historical information comprising clustered trip entries of the network service, and (ii) cause the map interface to dynamically and visually relocate the location pin to a second position representing the alternative pickup location on the map interface; configure the map interface to

enable the user to transmit a transport request that automatically specifies the alternative pickup location without additional user input to change the user-selected pickup location; receive a transport request from the mobile computing device of the user; and in response to receiving the transport request, select a transport provider to rendezvous with the user at the alternative pickup location.

9. The non-transitory computer readable medium of claim 8, wherein causing the map interface to dynamically and visually relocate the location pin to the alternative pickup location includes enlarging a first graphic indicator on the map interface as compared to a second graphic indicator, the first graphic indicator identifying the alternative pickup location and the second graphic indicator identifying the user-selected pickup location.

10. The non-transitory computer readable medium of claim 8, wherein causing the map interface to dynamically and visually relocate the location pin to the second position representing the alternative pickup location includes providing a first graphic indicator that moves from the user-selected pickup location to the alternative pickup location.

11. The non-transitory computer readable medium of claim 10, wherein the first graphic indicator is provided in response to detecting the user input.

12. The non-transitory computer readable medium of claim 8, wherein determining the alternative pickup location includes: determining a set of pickup locations in a specified region that includes a current location of the user by accessing a mapping table stored in one or more memory resources, the mapping table including the clustered trip entries that individually associate the specified regions with at least one corresponding pickup location of the set of pickup locations.

13. The non-transitory computer readable medium of claim 12, wherein the user-selected pickup location corresponds to a current location of the user, and wherein the alternative pickup location is within a predefined distance of the current location of the user.

14. The non-transitory computer readable medium of claim 12, wherein the mapping table identifies the alternative pickup location as being associated with the specified region that includes the current location of the user.

15. A computing system managing a network service, comprising: one or more processors; and a memory storing instructions that, when executed by one or more processors, cause the computing system to: provide a map interface for display on a mobile computing device of a user of the network service, the map interface including a location pin, the map interface enabling the user to select a pickup location; detect a user input that sets the location pin at a first position representing a user-selected pickup location on the map interface; in response to detecting the user input, (i) determine an alternative pickup location near the user-selected pickup location based at least in part on historical information comprising corresponding to clustered trip entries of the network service, and (ii) cause the map interface to dynamically and visually relocate the location pin to a second position representing the alternative pickup location on the map interface; configure the map interface to enable the user to transmit a transport request that automatically specifies the alternative pickup location without additional user input to change the user-selected pickup location; receive a transport request from the mobile computing device of the user; and in response to receiving the transport request, select a transport provider to rendezvous with the user at the alternative pickup location.

16. The computing system of claim 15, wherein causing the map interface to dynamically and visually relocate the location pin to the alternative pickup location includes enlarging a first graphic indicator on the map interface as compared to a second graphic indicator, the first graphic indicator identifying the alternative pickup location and the second graphic indicator identifying the user-selected pickup location.

17. The computing system of claim 15, wherein causing the map interface to dynamically and visually relocate the location pin to the second position representing the alternative pickup location includes providing a first graphic indicator that moves from the user-selected pickup location to the

alternative pickup location.

18. The computing system of claim 17, wherein the first graphic indicator is provided in response to detecting the user input.

19. The computing system of claim 15, wherein determining the alternative pickup location includes: determining a set of pickup locations in a specified region that includes a current location of the user by accessing a mapping table stored in one or more memory resources, the mapping table including the clustered trip entries that individually associate the specified regions with at least one corresponding pickup location of the set of pickup locations.

20. The computing system of claim 19, wherein the user-selected pickup location corresponds to a current location of the user, and wherein the alternative pickup location is within a predefined distance of the current location of the user.
