

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12395787
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Choi; YeongRak et al.

Sound generating apparatus

Abstract

A panel vibration type sound generating display device is disclosed. The display device includes a display panel for displaying an image; a sound generating actuator connected to the display panel and configured to vibrate the display panel to generate sound; a support structure spaced apart from the display panel with an air gap between the support structure and the display panel; and a baffle part disposed between the support structure and the display panel to surround the air gap.

Inventors: Choi; YeongRak (Paju-si, KR), Oh; ChangHo (Seoul, KR), Park; KwanHo (Incheon, KR), Lee; Sungtae (Incheon, KR)

Applicant: LG DISPLAY CO., LTD. (Seoul, KR)

Family ID: 1000008762668

Assignee: LG DISPLAY CO., LTD. (Seoul, KR)

Appl. No.: 18/217983

Filed: July 03, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230353934 A1	Nov. 02, 2023

Foreign Application Priority Data

KR	10-2016-0037118	Mar. 28, 2016
----	-----------------	---------------

Related U.S. Application Data

continuation parent-doc US 17228674 20210412 US 11736858 child-doc US 18217983
continuation parent-doc US 16696847 20191126 US 11019425 20210525 child-doc US 17228674

Publication Classification

Int. Cl.: **H04R1/32** (20060101); **G02F1/1333** (20060101); **G06F1/16** (20060101); **H04R1/02** (20060101); **H04R7/04** (20060101); **H04R9/02** (20060101); G09G3/3225 (20160101); G09G3/3266 (20160101); G09G3/3275 (20160101); H04R5/02 (20060101); H04R9/04 (20060101); H04R9/06 (20060101)

U.S. Cl.:

CPC **H04R1/323** (20130101); **G02F1/1333** (20130101); **G06F1/1605** (20130101); **H04R1/025** (20130101); **H04R1/028** (20130101); **H04R7/045** (20130101); **H04R9/02** (20130101); G02F1/133308 (20130101); G09G3/3225 (20130101); G09G3/3266 (20130101); G09G3/3275 (20130101); G09G2310/08 (20130101); H04R5/02 (20130101); H04R7/04 (20130101); H04R9/043 (20130101); H04R9/063 (20130101); H04R2400/03 (20130101); H04R2499/11 (20130101); H04R2499/15 (20130101)

Field of Classification Search

CPC: H04R (1/323); H04R (1/025); H04R (7/045); H04R (9/02); H04R (1/028); H04R (5/02); G02F (1/1333); G02F (1/133308); G06F (1/1605); H01L (51/5253); G02B (6/0011)

USPC: 381/333

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4675907	12/1986	Itagaki et al.	N/A	N/A
4891842	12/1989	Green	N/A	N/A
5025474	12/1990	Tanaka et al.	N/A	N/A
5535028	12/1995	Bae et al.	N/A	N/A
5796854	12/1997	Markow	N/A	N/A
5856819	12/1998	Vossler	N/A	N/A
6137890	12/1999	Markow	N/A	N/A
6208237	12/2000	Saiki et al.	N/A	N/A
6238755	12/2000	Harvey et al.	N/A	N/A
6342831	12/2001	Azima	N/A	N/A
6443586	12/2001	Azima et al.	N/A	N/A
6610237	12/2002	Azima et al.	N/A	N/A
6618487	12/2002	Azima et al.	N/A	N/A
6677384	12/2003	Ikemoto et al.	N/A	N/A
6751329	12/2003	Colloms et al.	N/A	N/A
6795561	12/2003	Bank	N/A	N/A
6819309	12/2003	Kishi	N/A	N/A
6826285	12/2003	Azima	N/A	N/A
6871149	12/2004	Sullivan et al.	N/A	N/A

6911901	12/2004	Bown	N/A	N/A
6922642	12/2004	Sullivan	N/A	N/A
6937124	12/2004	Nakamura et al.	N/A	N/A
6956957	12/2004	Azima et al.	N/A	N/A
6985596	12/2005	Bank et al.	N/A	N/A
7020302	12/2005	Konishi et al.	N/A	N/A
7050600	12/2005	Saiki et al.	N/A	N/A
7120264	12/2005	Saiki et al.	N/A	N/A
7157649	12/2006	Hill	N/A	N/A
7158651	12/2006	Bachmann et al.	N/A	N/A
7174025	12/2006	Azima et al.	N/A	N/A
7184898	12/2006	Sullivan et al.	N/A	N/A
7215329	12/2006	Yoshikawa et al.	N/A	N/A
7305248	12/2006	Mori	N/A	N/A
7372110	12/2007	Hatano	N/A	N/A
7376523	12/2007	Sullivan et al.	N/A	N/A
7382890	12/2007	Saiki et al.	N/A	N/A
7446826	12/2007	Ro et al.	N/A	N/A
7536211	12/2008	Saiki et al.	N/A	N/A
7545459	12/2008	Fujiwara et al.	N/A	N/A
7564984	12/2008	Bank et al.	N/A	N/A
7570771	12/2008	Whitewell et al.	N/A	N/A
7593159	12/2008	Yokoyama et al.	N/A	N/A
7657042	12/2009	Miyata	N/A	N/A
7664278	12/2009	Watanabe et al.	N/A	N/A
7764803	12/2009	Kang	N/A	N/A
7769191	12/2009	Lee et al.	N/A	N/A
7800702	12/2009	Tsuboi et al.	N/A	N/A
7843136	12/2009	Ishii et al.	N/A	N/A
7903091	12/2010	Lee et al.	N/A	N/A
8174495	12/2011	Takashima et al.	N/A	N/A
8174511	12/2011	Takenaka et al.	N/A	N/A
8180074	12/2011	Ko et al.	N/A	N/A
8194894	12/2011	Burton et al.	N/A	N/A
8274480	12/2011	Sullivan	N/A	N/A
8736558	12/2013	East et al.	N/A	N/A
8816977	12/2013	Rothkopf et al.	N/A	N/A
8830211	12/2013	Hill	N/A	N/A
8879766	12/2013	Zhang	N/A	N/A
8917168	12/2013	Kono et al.	N/A	N/A
8934228	12/2014	Franklin et al.	N/A	N/A
9001060	12/2014	Harris	N/A	N/A
9030447	12/2014	Hsu	N/A	N/A
9035918	12/2014	Harris et al.	N/A	N/A
9041662	12/2014	Harris	N/A	N/A
9046949	12/2014	Adachi et al.	N/A	N/A
9063256	12/2014	Liao	N/A	N/A
9107006	12/2014	Wang et al.	N/A	N/A
9122011	12/2014	Oh et al.	N/A	N/A
9131301	12/2014	Tsai et al.	N/A	N/A

9137592	12/2014	Yliaho et al.	N/A	N/A
9148716	12/2014	Liu et al.	N/A	N/A
9173014	12/2014	Park	N/A	N/A
9191749	12/2014	Nabata et al.	N/A	N/A
9197966	12/2014	Umehara et al.	N/A	N/A
9204223	12/2014	Nabata et al.	N/A	N/A
9285882	12/2015	Wang et al.	N/A	N/A
9288564	12/2015	Faerstain et al.	N/A	N/A
9300770	12/2015	Nabata et al.	N/A	N/A
9317063	12/2015	Kwon et al.	N/A	N/A
9332098	12/2015	Horii	N/A	N/A
9350832	12/2015	Horii	N/A	N/A
9357280	12/2015	Mellow et al.	N/A	N/A
9363591	12/2015	Ozasa et al.	N/A	N/A
9363607	12/2015	Ando	N/A	N/A
9380366	12/2015	Kang et al.	N/A	N/A
9389688	12/2015	Tossavainen et al.	N/A	N/A
9398358	12/2015	Louh	N/A	N/A
9436320	12/2015	Kang et al.	N/A	N/A
9544671	12/2016	Shi et al.	N/A	N/A
9575240	12/2016	Akanuma et al.	N/A	N/A
9609438	12/2016	Kim et al.	N/A	N/A
9654863	12/2016	Crosby et al.	N/A	N/A
9818805	12/2016	Choi et al.	N/A	N/A
9868137	12/2017	Kiyose et al.	N/A	N/A
10009683	12/2017	Choi et al.	N/A	N/A
10129646	12/2017	Choi et al.	N/A	N/A
10142738	12/2017	Choi et al.	N/A	N/A
10142739	12/2017	Choi et al.	N/A	N/A
10200772	12/2018	Ahn	N/A	H04R 1/028
10219079	12/2018	Choi et al.	N/A	N/A
10237656	12/2018	Lee et al.	N/A	N/A
10409325	12/2018	Choi et al.	N/A	N/A
10412500	12/2018	Lee et al.	N/A	N/A
10555073	12/2019	Choi et al.	N/A	N/A
11019425	12/2020	Choi et al.	N/A	N/A
2001/0040976	12/2000	Buos	N/A	N/A
2001/0043714	12/2000	Asada et al.	N/A	N/A
2002/0018574	12/2001	Okuno et al.	N/A	N/A
2002/0061115	12/2001	Chung et al.	N/A	N/A
2002/0064290	12/2001	Reynaga et al.	N/A	N/A
2002/0118856	12/2001	Croft et al.	N/A	N/A
2002/0141607	12/2001	Azima et al.	N/A	N/A
2003/0227581	12/2002	Sung et al.	N/A	N/A
2003/0233794	12/2002	Pylkki et al.	N/A	N/A
2004/0008859	12/2003	Zhao	N/A	N/A
2004/0184622	12/2003	Ohashi	N/A	N/A
2005/0129258	12/2004	Fincham	N/A	N/A
2005/0129265	12/2004	Nakajima et al.	N/A	N/A
2006/0010403	12/2005	Jeon	N/A	N/A

2006/0018503	12/2005	Endo	N/A	N/A
2006/0078153	12/2005	Sato	N/A	N/A
2006/0120542	12/2005	Lee	N/A	N/A
2006/0126885	12/2005	Combest	N/A	N/A
2006/0140437	12/2005	Watanabe et al.	N/A	N/A
2006/0140439	12/2005	Nakagawa	N/A	N/A
2006/0187140	12/2005	Brask	N/A	N/A
2006/0245155	12/2005	Konno et al.	N/A	N/A
2006/0290838	12/2005	Ro et al.	N/A	N/A
2007/0019134	12/2006	Park et al.	N/A	N/A
2007/0036388	12/2006	Lee et al.	N/A	N/A
2007/0132911	12/2006	Fujiwara et al.	N/A	N/A
2007/0187172	12/2006	Kaneda et al.	N/A	N/A
2007/0206822	12/2006	Whitewell et al.	N/A	N/A
2007/0290609	12/2006	Ishii et al.	N/A	N/A
2008/0085019	12/2007	Wagenaars et al.	N/A	N/A
2009/0021898	12/2008	Konno et al.	N/A	N/A
2009/0034174	12/2008	Ko et al.	N/A	N/A
2009/0034759	12/2008	Ko et al.	N/A	N/A
2009/0097692	12/2008	Sakamoto	N/A	N/A
2009/0141926	12/2008	Clair et al.	N/A	N/A
2009/0247237	12/2008	Mittleman et al.	N/A	N/A
2009/0267891	12/2008	Ali	N/A	N/A
2011/0248935	12/2010	Mellow et al.	N/A	N/A
2012/0034541	12/2011	Muraoka et al.	N/A	N/A
2012/0082317	12/2011	Pance et al.	N/A	N/A
2012/0162143	12/2011	Kai et al.	N/A	N/A
2012/0242592	12/2011	Rothkopf et al.	N/A	N/A
2012/0243719	12/2011	Franklin et al.	N/A	N/A
2012/0274570	12/2011	Kim	N/A	N/A
2013/0064401	12/2012	Wang et al.	N/A	N/A
2013/0077810	12/2012	Mellow et al.	N/A	N/A
2013/0089231	12/2012	Wilk et al.	N/A	N/A
2013/0106868	12/2012	Shenoy	N/A	N/A
2013/0250169	12/2012	Kim	N/A	N/A
2013/0250536	12/2012	Satake	N/A	N/A
2013/0335892	12/2012	Ha et al.	N/A	N/A
2013/0343564	12/2012	Darlington	N/A	N/A
2014/0029777	12/2013	Jang	N/A	N/A
2014/0049522	12/2013	Mathew et al.	N/A	N/A
2014/0145836	12/2013	Tossavainen et al.	N/A	N/A
2014/0146093	12/2013	Sako et al.	N/A	N/A
2014/0197380	12/2013	Sung et al.	N/A	N/A
2014/0241558	12/2013	Yliaho et al.	N/A	N/A
2014/0241564	12/2013	Kang et al.	N/A	N/A
2014/0296715	12/2013	Kiyose et al.	N/A	N/A
2014/0326402	12/2013	Lee et al.	N/A	N/A
2014/0334078	12/2013	Lee et al.	N/A	N/A
2015/0003659	12/2014	Theuss	N/A	N/A
2015/0010187	12/2014	Lee et al.	N/A	N/A

2015/0016658	12/2014	Lee	N/A	N/A
2015/0062101	12/2014	Kim et al.	N/A	N/A
2015/0078604	12/2014	Seo et al.	N/A	N/A
2015/0119834	12/2014	Locke et al.	N/A	N/A
2015/0138157	12/2014	Harris et al.	N/A	N/A
2015/0195630	12/2014	Yliaho et al.	N/A	N/A
2015/0341714	12/2014	Ahn et al.	N/A	N/A
2015/0350775	12/2014	Behles et al.	N/A	N/A
2016/0011442	12/2015	Lee et al.	N/A	N/A
2016/0050472	12/2015	Lee et al.	N/A	N/A
2016/0165327	12/2015	Crosby et al.	N/A	N/A
2016/0212513	12/2015	Honda et al.	N/A	N/A
2016/0261966	12/2015	Won	N/A	N/A
2016/0345102	12/2015	Tagami et al.	N/A	N/A
2017/0070811	12/2016	Mihelich et al.	N/A	N/A
2017/0194224	12/2016	Yang et al.	N/A	N/A
2017/0263886	12/2016	Oh et al.	N/A	N/A
2017/0280216	12/2016	Lee et al.	N/A	N/A
2018/0053813	12/2017	Choi et al.	N/A	N/A
2018/0343522	12/2017	Choi et al.	N/A	N/A
2019/0052963	12/2018	Choi et al.	N/A	N/A
2019/0215607	12/2018	Lee et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1358400	12/2001	CN	N/A
1500365	12/2003	CN	N/A
1547416	12/2003	CN	N/A
2733799	12/2004	CN	N/A
1717118	12/2005	CN	N/A
1755449	12/2005	CN	N/A
1780494	12/2005	CN	N/A
1790139	12/2005	CN	N/A
1812629	12/2005	CN	N/A
1856178	12/2005	CN	N/A
1892331	12/2006	CN	N/A
1930910	12/2006	CN	N/A
1980485	12/2006	CN	N/A
101040561	12/2006	CN	N/A
101093852	12/2006	CN	N/A
101233785	12/2007	CN	N/A
101766023	12/2009	CN	N/A
201663651	12/2009	CN	N/A
102483665	12/2011	CN	N/A
102547496	12/2011	CN	N/A
202652283	12/2012	CN	N/A
202663535	12/2012	CN	N/A
102917288	12/2012	CN	N/A
102946577	12/2012	CN	N/A
103067798	12/2012	CN	N/A

103190082	12/2012	CN	N/A
103278978	12/2012	CN	N/A
203181212	12/2012	CN	N/A
103416075	12/2012	CN	N/A
103489377	12/2013	CN	N/A
103698932	12/2013	CN	N/A
104062075	12/2013	CN	N/A
104068894	12/2013	CN	N/A
104254047	12/2013	CN	N/A
105096778	12/2014	CN	N/A
204929153	12/2014	CN	N/A
105225608	12/2015	CN	N/A
206993387	12/2015	CN	N/A
105933834	12/2015	CN	N/A
107561753	12/2017	CN	N/A
102014112962	12/2015	DE	N/A
1 507 438	12/2004	EP	N/A
1881731	12/2007	EP	N/A
2947857	12/2014	EP	N/A
55-25284	12/1979	JP	N/A
H02-001987	12/1989	JP	N/A
H03-132296	12/1990	JP	N/A
2696801	12/1997	JP	N/A
H11-44891	12/1998	JP	N/A
2000-138995	12/1999	JP	N/A
2001-61194	12/2000	JP	N/A
2002-511681	12/2001	JP	N/A
2002-264646	12/2001	JP	N/A
2003-211087	12/2002	JP	N/A
3578244	12/2003	JP	N/A
2004-343362	12/2003	JP	N/A
2005-175553	12/2004	JP	N/A
2005-244804	12/2004	JP	N/A
2006-138149	12/2005	JP	N/A
2006-186590	12/2005	JP	N/A
2006-279284	12/2005	JP	N/A
2006-319626	12/2005	JP	N/A
2006-325079	12/2005	JP	N/A
3896675	12/2006	JP	N/A
2007-267302	12/2006	JP	N/A
2007-528648	12/2006	JP	N/A
2007-300578	12/2006	JP	N/A
4150643	12/2007	JP	N/A
2009-100223	12/2008	JP	N/A
2009214060	12/2008	JP	N/A
2009-302924	12/2008	JP	N/A
2010-027845	12/2009	JP	N/A
2010-081142	12/2009	JP	N/A
4449605	12/2009	JP	N/A
2011-053744	12/2010	JP	N/A

2011-123696	12/2010	JP	N/A
2012-129247	12/2011	JP	N/A
2012-198407	12/2011	JP	N/A
5060443	12/2011	JP	N/A
2013-044912	12/2012	JP	N/A
2013-102360	12/2012	JP	N/A
2014-509028	12/2013	JP	N/A
2014-220237	12/2013	JP	N/A
2014-220802	12/2013	JP	N/A
2015-219528	12/2014	JP	N/A
10-2008-0002228	12/2007	KR	N/A
2008-0063698	12/2007	KR	N/A
10-2009-0019176	12/2008	KR	N/A
10-1026987	12/2010	KR	N/A
10-1061519	12/2010	KR	N/A
10-1404119	12/2013	KR	N/A
101410393	12/2013	KR	N/A
2015-0005089	12/2014	KR	N/A
10-2015-0031641	12/2014	KR	N/A
10-1499514	12/2014	KR	N/A
10-2015-0131428	12/2014	KR	N/A
2015-133918	12/2014	KR	N/A
10-2017-0135673	12/2016	KR	N/A
200706049	12/2006	TW	N/A
M451766	12/2012	TW	N/A
201319783	12/2012	TW	N/A
201503710	12/2014	TW	N/A
201545559	12/2014	TW	N/A
99/52322	12/1998	WO	N/A
2005-089014	12/2004	WO	N/A
2009-017280	12/2008	WO	N/A
2012/050771	12/2011	WO	N/A
2012090031	12/2011	WO	N/A
2012/129247	12/2011	WO	N/A
2013/109128	12/2012	WO	N/A
2014021608	12/2013	WO	N/A
2015-046288	12/2014	WO	N/A
2016/002230	12/2015	WO	N/A

OTHER PUBLICATIONS

Non-final Office Action from the U.S. Patent and Trademark Office issued in U.S. Appl. No. 16/038,075 dated Jan. 18, 2019. cited by applicant

Office Action issued in Japanese Patent Application No. 2017-131154 dated Dec. 11, 2018. cited by applicant

Office Action dated May 31, 2017, from the Taiwanese Patent Office in related Application No. 106121605. cited by applicant

Taiwanese Office Action dated May 15, 2018, issued in Taiwanese Application No. 106122586. cited by applicant

Japanese Office Action dated Jul. 3, 2018, issued in Japanese Application No. 2016-235794. cited by applicant

Japanese Office Action dated Jun. 5, 2018, issued in Japanese Application No. 2017-131154. cited by applicant

Notice of Allowance dated Jul. 5, 2021, issued in the Chinese Patent Application No. 202010363294.X. cited by applicant

Office Action dated Mar. 27, 2017 from the Korean Patent Office in related Application No. 10-2016-0146951 dated Jan. 3, 2018. cited by applicant

Japanese Office Action dated Aug. 23, 2018, issued in Japanese Application No. 2017-137757. cited by applicant

Japanese Office Action dated Aug. 23, 2018, issued in Japanese Application No. 2017-124022. cited by applicant

Japanese Office Action dated Sep. 25, 2018, issued in Japanese Application No. 2017-131143. cited by applicant

Communication dated Jun. 30, 2017 from the European Patent Office in related European application No. 16181195.5. cited by applicant

Office Action issued in Chinese Patent Application No. 201710599021.3 dated Mar. 20, 2019. cited by applicant

Office Action issued in Japanese Patent Application No. 2017-124022 dated Apr. 9, 2019. cited by applicant

Office Action dated Nov. 19, 2020, from the Chinese Patent Office in counterpart Chinese Application No. 202010363413.1. cited by applicant

Office Action dated Nov. 19, 2020, from the Chinese Patent Office in counterpart Chinese Application No. 202010368984.4. cited by applicant

Office Action dated Dec. 1, 2020, from the Chinese Patent Office in counterpart Chinese Application No. 202010363294.X. cited by applicant

Office Action dated Jan. 6, 2021, from the Chinese Patent Office in counterpart Chinese Application No. 202010364802.6. cited by applicant

Notice of Allowance dated Jul. 5, 2021 issued by the China National Intellectual Property Administration in the counterpart Chinese Application No. 202010363294.X. cited by applicant

Shim, Samsung claims double sided LCD, EDN, Jan. 2007. cited by applicant

Notice of Allowance dated Mar. 24, 2021, issued in the Chinese Patent Application No. 202010363413.1. cited by applicant

Chinese Office Action dated Jun. 5, 2019, issued in Chinese Application No. 201610823135.7. cited by applicant

Extended European Search Report issued in European Application No. 17183078.9 dated Jan. 16, 2018. cited by applicant

Extended European Search Report issued in European Application No. 17184428.5 dated Jan. 23, 2018. cited by applicant

Extended European Search Report issued in European Application No. 17184429.3 dated Jan. 26, 2018. cited by applicant

Japanese Office Action issued in Japanese Application No. 2016-216426 dated Nov. 24, 2017. cited by applicant

Taiwanese Office Action issued in Taiwanese Application No. 10720014270 dated Jan. 10, 2018. cited by applicant

Taiwanese Office Action issued in Taiwanese Application No. 10621325350 dated Jan. 3, 2018. cited by applicant

Office Action dated Sep. 26, 2017 from the Japanese Patent Office in related Japanese application No. 2016-190615. cited by applicant

Office Action dated Oct. 3, 2017 from the Japanese Patent Office in related Japanese application No. 2016-235794. cited by applicant

Communication dated Sep. 19, 2017 from the European Patent Office in related European

application No. 16181185.6. cited by applicant

Communication dated Sep. 5, 2017 from the European Patent Office in related European application No. 16181191.4. cited by applicant

Hermida, Alfred, "PC Screen Turns Into Speaker," BBC News, Technology, Mar. 31, 2003, pp. 1-2. cited by applicant

USPTO Office Action dated Oct. 26, 2017 in related U.S. Appl. No. 15/471,458. cited by applicant

USPTO Office Action dated Nov. 9, 2017 in related U.S. Appl. No. 15/471,173. cited by applicant

USPTO Office Action dated Aug. 10, 2017 in related U.S. Appl. No. 15/340,709. cited by applicant

USPTO Office Action dated Oct. 13, 2017 in related U.S. Appl. No. 15/471,184. cited by applicant

Primary Examiner: Elahee; Md S

Attorney, Agent or Firm: Morgan, Lewis & Bockius LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of co-pending U.S. patent application Ser. No. 17/228,674, filed Apr. 12, 2021, which is a continuation of U.S. patent application Ser. No. 16/696,847, filed Nov. 26, 2019, now U.S. Pat. No. 11,019,425, issued May 25, 2021, which is a continuation of U.S. patent application Ser. No. 15/987,267, filed May 23, 2018, now U.S. Pat. No. 10,555,073, issued Feb. 4, 2020, which is a continuation of U.S. patent application Ser. No. 15/374,566, filed Dec. 9, 2016, now U.S. Pat. No. 10,009,683, issued Jun. 26, 2018, which claims priority from Korean Patent Application No. 10-2016-0037118, filed on Mar. 28, 2016. Each of the above prior U.S. and Korean Patent Applications is hereby incorporated by reference for all purposes as if fully set forth herein.

1. FIELD OF THE INVENTION

(1) The present disclosure relates to a display device and, more specifically, to a display device for generating sound by directly vibrating a display panel thereof.

2. DESCRIPTION OF THE PRIOR ART

(2) With the development of various portable electronic devices, such as mobile communication terminals and notebook computers, there has been an increase in the requirement for a flat panel display device applicable thereto.

(3) The flat panel display devices being researched include a Liquid Crystal Display Device, a Plasma Display Panel, a Field Emission Display Device, a Light Emitting Diode Display Device, and an Organic Light Emitting Diode Display Device.

(4) Among these display devices, the Liquid Crystal Display (LCD) device includes: an array substrate including a thin film transistor; an upper substrate including a color filter and/or a black matrix; and a liquid crystal material layer formed therebetween, wherein an alignment state of the liquid crystal layer is controlled according to an electric field applied between opposite electrodes of a pixel area, and thereby the transmittance of light is adjusted to display an image.

(5) In a display panel of such a liquid crystal display device, an Active Area (AA) configured to provide an image to a user and a Non-active Area (NA), which is a peripheral area of the Active Area (AA), are defined. The display panel is usually manufactured by attaching a first substrate, which is an array substrate having a thin film transistor formed therein to define a pixel area, and a second substrate, which is an upper substrate having a black matrix and/or color filter layer formed thereon, to each other.

(6) The array substrate or first substrate, on which a thin film transistor is formed, includes a plurality of gate lines GS extending in a first direction and a plurality of data lines DL extending in

a second direction perpendicular to the first direction, and one pixel area P is defined by each gate line and each data line. One or more thin film transistors are formed in one pixel area P, and gate and source electrodes of each thin film transistor may be connected to a gate line and a data line, respectively.

(7) Among these display devices, the liquid crystal display device does not have its own light-emitting element and thus needs a separate light source. Therefore, the liquid crystal display device has a back-light unit having a light source, such as an LED, which is arranged at the rear surface thereof and irradiates a light toward a front surface of the liquid crystal panel thereof, thereby at last implementing a recognizable image.

(8) Meanwhile, an Organic Light Emitting Diode (OLED) display device, which has recently been in the spotlight as a display device has a fast response rate, a high light emitting efficiency, a high luminance and a wide viewing angle compared to other conventional devices, because an OLED emits light by itself, i.e., an additional backlight unit is not required.

(9) In the organic light emitting diode display device, sub-pixels including organic light emitting diodes are arranged in a matrix form, and the brightness of the sub-pixels selected by a scan signal is controlled according to a gray scale of the data. Further, the organic light emitting diode display device, which is an emissive element, consumes a smaller amount of power and has a high response speed, a high light emitting efficiency, a high luminance, and a wide viewing angle.

(10) Meanwhile, the above-described display device may be included in a set apparatus or finished produce, such as a television (TV), a computer monitor, or an advertising panel.

(11) Such a display device or set apparatus includes a sound output device, such as a speaker, for generating and outputting sound relating to an image.

(12) Conventionally, a company that manufactures a display device, such as a liquid crystal display device or an organic light emitting diode display device, manufactures only a display panel or display device, while another company that manufactures a sound output device assembles the sound output device, such as a speaker, with the manufactured display device, so as to finally complete a set apparatus capable of outputting both an image and sound.

(13) FIG. 1 is a schematic plan view of a speaker included in a conventional display device.

(14) As shown in FIG. 1, the conventional display device 1 includes a speaker 2 disposed at a rear or lower part of a display panel thereof.

(15) In this structure, the sound generated by the speaker 2 does not progress toward a viewer, who is viewing an image from the front side of the display device 1, but progresses toward the rear side or the underside of the display panel. Therefore, the sound may disturb the viewer's immersive experience.

(16) Further, when the sound generated from the speaker 2 progresses toward the rear side or underside of the display panel, the sound quality may be degraded due to an interference with sound reflected by a wall or floor.

(17) Also, the sound generated by a speaker included in conventional display devices is not oriented toward a viewer of the display device and may thus undergo diffraction, which decreases sound localization. Moreover, in configuring a set apparatus, such as a TV, a speaker may occupy a predetermined space, which imposes a restriction on the design and spatial arrangement of the set apparatus.

(18) Therefore, there has been an increasing interest in the development of technology which can improve the quality of sound output from a display device and prevent the viewer's immersive experience from being disturbed.

SUMMARY OF THE INVENTION

(19) The present disclosure has been made to overcome the above-mentioned problems of the prior art and, in one aspect, provide a panel vibration type sound generating display device, which can generate sound by directly vibrating a display panel of the display device.

(20) In another aspect, the present disclosure provides a display device including a panel vibration

type sound generating apparatus, which has a predetermined air gap formed between a display panel and a sound generating actuator and an actuator support hole formed in a support structure of the display device, so that the display device has a reduced thickness while having an excellent sound generation performance. The support structure may also be termed a support member or support part.

(21) In another aspect, the present disclosure provides a display device having a sound generation baffle part formed therein, which includes an adhesive member attached between the upper surface of the support structure and the lower surface of the display panel and a sealing part disposed outside the adhesive member, so that the display device can minimize sound leakage and improve a sound output characteristic. The adhesive member may be a double-sided tape.

(22) In another aspect, the present disclosure provides a display device, which includes one or more buffer members arranged between the inner surface of the support structure and the rear surface of the display panel adjacent to a source printed circuit board (PCB) or between the support structure disposed at the rear surface of the display panel and the source PCB to fix/support the sound generating actuator, to prevent interference and noise between the support structure and a Source PCB (S-PCB) for driving the display panel.

(23) The panel vibration type sound generating display device may further comprise a set PCB, which is disposed at an outer rear surface of the cover bottom and includes a control circuit configured to control the entire display device, wherein a cable passing hole through which a connection cable for electrically connecting the source PCB and the set PCB is to pass is disposed at an area of the cover bottom corresponding to the first area.

(24) In another aspect, the present disclosure provides a display device in which a sound generating actuator is placed at a first position of a support structure of the display device and a set PCB of a set apparatus is placed at a second position, which is different from the first position, so as to avoid interference between the sound generating actuator and the set PCB, and improve the sound characteristic.

(25) In still another aspect, the present disclosure provides a display device, which has a reinforcement member arranged inside the support structure of the display device when two or more sound generating actuators are used, so that the display device can prevent deformation of the support structure due to different vibration characteristics of the two or more sound generating actuators or prevent sound distortion by the vibration of the support structure.

(26) In view of the above aspects, a display device of the present embodiment includes: a display panel configured to display an image; and a sound generating actuator connected to a surface of the display panel configured to vibrate the display panel to generate sound. The surface may be an inner surface, for example.

(27) The display device may further include a support structure, such as a cover bottom, configured to cover and support at least a rear surface of the display panel, wherein the sound generating actuator is inserted in and fixed to a support hole formed at the cover bottom to be fixed to the support structure.

(28) The support structure of the panel vibration type sound generating display device may comprise: a cover bottom supporting the rear side of the display panel, a source PCB for driving the display panel is disposed on a rear surface of one side of the display panel, and a first buffer member spaced from the source PCB by a predetermined distance is placed on an inner surface of the cover bottom corresponding to the source PCB.

(29) The sound generating actuator may further include: a plate inserted in the support hole; a magnet disposed on the plate; a center pole disposed at a center of the plate; a bobbin disposed to surround the center pole and be in contact with the display panel; and a coil wound around the bobbin. The plate may be a lower plate, for example.

(30) The lower plate configuring the sound generating actuator may further include an extension part extending outward, and the extension part may be fixed to the lower surface of the cover

bottom through a bolt, a PEM™ nut, or an adhesive member.

(31) The extension part and the cover bottom of the panel vibration type sound generating display device, may be fixedly coupled to each other by one of a bolt fastened through a through-hole provided through the extension part to a screw hole disposed at the cover bottom and an adhesive member disposed between the extension part and the cover bottom.

(32) The panel vibration type sound generating display device may further comprise a baffle part disposed between the support structure and the lower surface of the display panel to define an air gap, which is a space in which the display panel can be vibrated by the sound generating actuator.

(33) An air gap is formed between the display panel and the support member, and the display device may further include a baffle part including an adhesive member and a sealing part arranged between the lower surface of the display panel and the upper surface of the support member at an edge of the air gap.

(34) The baffle part of the panel vibration type sound generating display device may comprise an adhesive member disposed at an edge of the air gap and attached to the lower surface of the display panel and the upper surface of the support structure, and a sealing part disposed outside the adhesive member.

(35) The sealing part of the panel vibration type sound generating display device may have a thickness larger than the thickness of the adhesive member.

(36) The support member includes a cover bottom supporting a rear side of the display panel and a middle cabinet supporting the edge of the display panel. The middle cabinet may include an area division member configured to separate a first area including a source PCB and a second area including a sound generating actuator.

(37) The support structure of the panel vibration type sound generating display device may comprise a cover bottom, which supports a rear side of the display panel, and a middle cabinet, which has a shape of a frame, coupled to the cover bottom to support a side surface of the display panel, and stably holds the edge of the display panel, the middle cabinet comprising an area division member configured to separate a first area including a source PCB for driving the display panel and a second area including the sound generating actuator.

(38) The baffle part of the panel vibration type sound generating display device may comprise an adhesive member attached to three sides of the middle cabinet corresponding to the second area, an upper surface of the area division member, and the lower surface of the display panel, and a sealing part disposed outside the adhesive member.

(39) A recessed part is formed on an upper surface of the cover bottom opposite to the source PCB placed on a rear surface of the display panel, and a first buffer member spaced a predetermined distance from the lower surface of the display panel may be disposed on the recessed part. The recessed part may be concave, for example.

(40) The cover bottom may have a second buffer member disposed thereon, which is in contact with the lower surface of the display panel and the upper surfaces of the cover bottom while separating a first area covering the source PCB and a second area covering the sound generating actuator.

(41) The sound generating actuator may include two or more actuators, which are symmetrically arranged and have different vibration characteristics, and the cover bottom may further have a reinforcement member disposed thereon, which passes through adjacent positions of the two or more actuators.

(42) An embodiment of the present disclosure as described above provides a display device including a panel vibration type sound generating display device, which generates sound by directly vibrating a display panel, thereby making it unnecessary to install a separate speaker to the display device or a set apparatus including the display device.

(43) Further, since the progressing direction of the sound coincides with the image output direction in the display device, the display device or the set apparatus can improve sound localization or

sound output characteristics, the mechanism of the set apparatus can be easily designed, and can have a reduced thickness thereof.

(44) A concave part of the panel vibration type sound generating display device may be disposed on the inner surface of the cover bottom corresponding to the source PCB and the first buffer member may be disposed on an upper surface of the concave part.

(45) The cover bottom of the panel vibration type sound generating display device may have a second buffer member disposed thereon, which is in contact with the lower surface of the display panel and the upper surfaces of the cover bottom while separating a first area covering the source PCB and a second area covering the sound generating actuator.

(46) The support structure of the panel vibration type sound generating display device may comprise a cover bottom supporting the rear side of the display panel. The display device may further comprise a set PCB, which is disposed at an outer rear surface of the cover bottom and includes a control circuit configured to control the entire display device, and a first position in which the sound generating actuator is disposed and a second position in which one or more boards configuring the set PCB are arranged do not overlap each other.

(47) The support structure of the panel vibration type sound generating display device may comprise a cover bottom supporting the rear side of the display panel, the sound generating actuator may comprise two or more actuators, which are symmetrically arranged and have different vibration characteristics, the cover bottom may have a reinforcement member disposed thereon, which passes through adjacent positions of the two or more actuators.

(48) The two or more actuators of the panel vibration type sound generating display device may comprise two left sound generating actuators and two right sound generating actuators, and the reinforcement member may be disposed to pass through a middle point of a segment connecting the two left sound generating actuators and a middle point of a segment connecting the two right sound generating actuators.

(49) The panel vibration type sound generating display device may further comprise a sound compensation member, which is lengthily disposed at a position spaced a certain distance apart from an edge of the display panel opposite to a moving direction of the sound generating actuator when the sound generating actuator moves to a destination position spaced a predetermined distance apart from an initial position.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The above and other objects, features and advantages of the present invention will be more apparent from the following detailed description taken in conjunction with the accompanying drawings, in which:

(2) FIG. 1 is a schematic plan view of a speaker included in a conventional display device;

(3) FIGS. 2A and 2B are schematic views of a panel vibration type sound generating apparatus according to an embodiment of the present disclosure wherein FIG. 2A is a plan view and FIG. 2B is a sectional view;

(4) FIGS. 3A and 3B are sectional views of two types of sound generating actuators used according to embodiments of the present disclosure;

(5) FIGS. 4A and 4B illustrate a state in which a sound generating actuator according to an embodiment of the present disclosure vibrates a display panel to generate sound;

(6) FIGS. 5A and 5B illustrate an example of a coupling state between a sound generating actuator according to an embodiment of the present disclosure and a cover bottom, which is a supporting structure of a display device;

(7) FIGS. 6A and 6B illustrate other embodiments of a coupling state between a sound generating

actuator and a cover bottom;

(8) FIGS. 7A to 7C illustrate an example of a baffle part formed between a display panel and a middle cabinet, which is one of the structures for supporting the display panel to form a sound transferring air gap between the display panel, which serves as a vibrating plate, and a cover bottom;

(9) FIG. 8 illustrates a structure of a baffle part according to another embodiment in which the adhesive member and the sealing part are placed directly on a cover bottom;

(10) FIGS. 9A and 9B illustrate a locational relation between a source PCB for driving a display panel and a set PCB for driving a set apparatus, which are arranged at the rear surface of a display device;

(11) FIGS. 10A and 10B illustrate an embodiment which further includes an area division member additionally formed on a middle cabinet, and a cable passing hole through which a connection cable (FFC) formed on a cover bottom passes;

(12) FIGS. 11A and 11B are schematic views showing the relative arrangement of the cover bottom and the source PCB for driving the display panel;

(13) FIGS. 12A and 12B illustrate an embodiment including a buffer member capable of preventing interference and noise between the source PCB and the cover bottom illustrated in FIGS. 11A and 11B;

(14) FIG. 13 is a graph illustrating a noise reduction effect when the buffer members of the embodiment illustrated in FIGS. 12A and 12B are used;

(15) FIG. 14 illustrates a relative arrangement between a sound generating actuator and a set PCB in a display device according to an embodiment of the present disclosure;

(16) FIGS. 15A and 15B illustrate a display device including two or more actuators symmetrically arranged therein, and a distortion of a cover bottom due to a difference of vibration quantity in the display device;

(17) FIGS. 16A and 16B illustrate a structure which has a reinforcement member disposed inside a cover bottom in order to prevent generation of sound distortion by twisting or vibration of the cover bottom;

(18) FIGS. 17A and 17B illustrate specific arrangements of reinforcement members on a cover bottom;

(19) FIGS. 18A and 18B illustrate an embodiment, which further includes a sound compensation member in order to maintain the sound output characteristics when the sound generating actuator has been vertically moved; and

(20) FIG. 19 is a graph illustrating a sound output characteristic when a panel vibration type sound generating apparatus according to the present embodiment is used, in comparison with a conventional speaker.

DETAILED DESCRIPTION OF THE EXEMPLARY EMBODIMENTS

(21) Hereinafter, embodiments of the present disclosure will be described with reference to the accompanying drawings. In assigning reference numerals to elements in the drawings, the same elements will be designated by the same reference numerals as far as possible although they are illustrated in different drawings. Further, in the following description of the present invention, a detailed description of known functions and configurations incorporated herein will be omitted when it may make the subject matter of the present invention rather unclear.

(22) In addition, terms, such as first, second, A, B, (a), (b) or the like may be used herein in describing elements of the present invention. Each of these terminologies is not used to define an essence, order or sequence of a corresponding component but used merely to distinguish the corresponding component from other component(s). In the case that it is described that a certain element “is connected to”, “is coupled to”, or “is connected with” another element, it should be understood that not only can the certain element be directly connected or coupled to the another element, but an additional element may also be “interposed” between the elements or the elements

may be connected or coupled to each other through an additional element.

(23) FIGS. 2A and 2B are schematic views of a panel vibration type sound generating apparatus according to an embodiment of the present disclosure, wherein FIG. 2A is a plan view and FIG. 2B is a sectional view.

(24) As shown in FIGS. 2A and 2B, a display device according to this embodiment includes a display panel **100** configured to display an image, and a sound generating actuator **200** which is attached to a surface of the display panel and vibrates the display panel to generate sound.

(25) The sound generating actuator **200**, which is described below in more detail with reference FIGS. 4A and 4B, includes a magnet, a plate supporting the magnet, a center pole protruding from a central area of the plate, and a bobbin disposed to surround the center pole and having a coil wound thereon, to which an electric current for generating sound is applied, wherein a distal end of the bobbin is attached to one surface of the display panel.

(26) As shown in FIG. 2B, the display device may include a support structure configured to support one or more of the rear surface or a side surface of the display panel, and the plate of the sound generating actuator may be fixed to the support structure.

(27) The support structure includes a cover bottom **300** disposed at the rear surface of the display panel, and may further include a middle cabinet **500** which is coupled to the cover bottom while surrounding the side surface of the display panel and receives and supports one side edge of the display panel.

(28) The cover bottom configuring the support structure may be a plate-shaped member made of metal or plastic extending over the entire rear surface of the display device.

(29) The cover bottom **300** in the present disclosure is not limited to the term thereof but may be used as other expressions, such as a plate bottom, a back cover, a base frame, a metal frame, a metal chassis, a chassis base, or m-chassis, and has a concept including all types of frames or plate-shaped structures, each of which may be arranged on the rear base part of the display device as a support for the display panel.

(30) In the present specification, the term “display device” not only describes a display device, such as an OLED module or a Liquid Crystal Module (LCM) including a display panel and a driving unit for driving the display panel, but this term also includes a set electronic apparatus or a set apparatus, such as a notebook computer, a television, a computer monitor, or a mobile electronic device such as a smartphone or an electronic pad, which are finished products including such an LCM or OLED module.

(31) For clarity, an LCM or OLED module configured by a display panel and a driving unit thereof may be expressed as a “display device”, and an electronic apparatus, as a finished product, including such an LCM or OLED module may be expressed as a “set apparatus”. For example, the display device may include an LCD or OLED display panel and a source PCB, which is a control unit for driving the display panel, and the set apparatus may further include a set PCB, which is a set control unit electrically connected to the source PCB to control the entire set apparatus.

(32) The display panel **100** used in the present embodiment includes all types of display panels including a liquid crystal display panel, an Organic Light Emitting Diode (OLED) display panel, and a Plasma Display Panel (PDP) and is not limited to a specific display panel, as long as the display panel is directly vibrated by the sound generating actuator **200** to generate sound wave.

(33) When the display panel is a liquid crystal display panel, the display panel may include: a plurality of gate lines; a plurality of data lines; pixels defined at intersecting areas between the gate lines and data lines; an array substrate including a thin-film transistor, which is a switching device configured to adjust a light transmission degree at each pixel; an upper substrate including a color filter and/or a black matrix; and a liquid crystal material layer formed therebetween.

(34) When the display panel is an OLED display panel, the display panel may include: a plurality of gate lines; a plurality of data lines; pixels defined at intersecting areas between the gate lines and data lines; an array substrate including a thin-film transistor, which is a switching device

configured to selectively apply a voltage to each pixel; an OLED layer disposed on the array substrate; and a sealing substrate or an encapsulation substrate disposed on the array substrate to cover the OLED layer. The sealing substrate protects the thin film transistor and the OLED layer from external impact and prevents moisture from permeating the OLED layer.

(35) Although there is no limitation in the type of the display device used in a display device according to this embodiment, it may be preferred that the display panel is an OLED display panel by the reasons described below.

(36) Specifically, a liquid crystal display panel has many laminated layers and requires an indirect light source type back-light having a separate light source disposed therein. Therefore, when the liquid crystal display panel is directly vibrated by the sound generating actuator **200**, the directivity of the liquid crystal material may be shaken and thus cause distortion of an image.

(37) In contrast, since the OLED device of the OLED display panel is an emissive element, the OLED display panel does not require a separate light source and has one panel in which multiple layers including a polarization layer, a glass layer, and an encapsulation layer are integrated. Therefore, even when the OLED display panel is directly vibrated by the sound generating actuator **200**, the vibration has nearly no influence on the light emitting property of the organic light emitting layer and thus causes no image distortion. Therefore, in an embodiment of the present disclosure, an OLED display panel is preferably used.

(38) The display panel used in a display device according to an embodiment of the present disclosure has a general structure, so a more specific description thereof will be omitted.

(39) The display device according to an embodiment of the present disclosure may further include a baffle part **400** configured to form an air gap, which is a space disposed between the display panel and a support structure, i.e., the cover bottom **300** or the middle cabinet **500**, to transfer the generated sound wave.

(40) That is, by coupling the display panel to the cover bottom at an edge of the air gap and sealing the same, the air gap may be defined as an area sealed in all directions, and such a sealed air gap may be expressed as a baffle structure.

(41) Referring to FIGS. 7A to 7C, the baffle part **400** may include an adhesive part **412** disposed at an edge of the cover bottom or middle cabinet and is attached to the lower surface of the display panel, and a sealing part **414** disposed outside the adhesive part to reinforce the sealing of the air gap **600**.

(42) The adhesive part **412** may be configured by a double sided tape. It is preferred that the height of the sealing part **414** is higher than the height of the adhesive part **412** as described below in more detail with reference to FIGS. 7A to 7C.

(43) FIGS. 3A and 3B are sectional views of two types of sound generating actuators used according to embodiments of the present disclosure.

(44) A sound generating actuator **200** used in these embodiments may include a magnet **220**, which is a permanent magnet, plates **210** and **210'** configured to support the magnet, a center pole **230** protruding from a central area of the plate **210**, a bobbin **250** disposed to surround the center pole **230**, and a coil **260** wound around the bobbin, wherein an electric current for generating sound is applied to the coil **260**.

(45) The sound generating actuator used in the present embodiment may include both a first structure in which the magnet is disposed outside the coil and a second structure in which the magnet is disposed inside the coil.

(46) FIG. 3A illustrates the first structure having the magnet disposed outside the coil, which may be called a dynamic type or an external magnet type.

(47) In the sound generating actuator of the first structure, the lower plate **210** is fixed to a support hole **310** formed at the cover bottom **300** and the magnet **220**, which is a permanent magnet having an annular shape, and is disposed on the lower plate and surrounding the center pole **230**.

(48) The upper plate **210'** is disposed on the magnet **220**, and an external frame **240** protruding

from the upper plate is disposed outside the upper plate.

(49) The center pole **230** protrudes from the central area of the lower plate **210** and the bobbin **250** surrounds the center pole **230**.

(50) The coil **260** is wound around a lower portion of the bobbin **250**, and the electric current for generating sound is applied to the coil.

(51) A damper **270** may be disposed between an upper part of the bobbin and the external frame **240**.

(52) The lower plate **210** and the upper plate **210'** fix the sound generating actuator **200** to the cover bottom **300** while supporting the magnet **220**, the lower plate **210** has a cylindrical shape as shown in FIG. 3A, the magnet **220** having a ring shape is disposed on the lower plate **210**, and the upper plate **210'** is disposed on the magnet.

(53) As the lower plate **210** and the upper plate **210'** are coupled to the cover bottom **300**, the magnet **220** disposed between the lower plate **210** and the upper plate **210'** can be fixedly supported.

(54) The plate may be formed of a material having a magnetic property, such as ferrite Fe. The plate is not limited to the term thereof and may be expressed by another term, such as a yoke.

(55) The center pole **230** and the lower plate **210** may be integrally formed.

(56) The bobbin **250** is a cylindrical structure formed by paper or aluminum sheet, and the coil **260** is wound around a predetermined lower area of the bobbin. A combination of the bobbin and the coil may be referred to as a voice coil.

(57) When the electric current is applied to the coil, a magnetic field is formed around the coil. Then, due to an external magnetic field formed by the magnet **220**, the entire bobbin moves upward while being guided by the center pole according to Fleming's Law.

(58) Meanwhile, since the distal end of the bobbin **250** is attached to the rear surface of the display panel **100**, the bobbin vibrates the display panel based on the application or non-application of the electric current, and such vibrations generate sound waves.

(59) The magnet **220** may be a sintered magnet, such a barium ferrite, or may be a cast magnet made from an alloy of ferric oxide (Fe_2O_3), barium carbonate (BaCO_3), strontium ferrite having an improved magnetic component, aluminum (Al), nickel (Ni), and cobalt (Co), without being limited thereto.

(60) A damper **270** is disposed between an upper part of the bobbin **250** and the external frame **240**, and the damper **270** has a wrinkle structure and thus contracts or expands to adjust the up-down vibration of the bobbin according to the up-down movement of the bobbin. That is, since the damper **270** is connected to the bobbin **250** and to the external frame **240**, the up-down vibration of the bobbin is restricted by the restoring force of the damper **270**. Specifically, when the bobbin **250** vibrates upward beyond a predetermined height or downward beyond a predetermined level, the restoring force of the damper **270** can return the bobbin to its original position.

(61) The damper may be expressed by another term, such as an edge.

(62) FIG. 3B illustrates the second structure having the magnet disposed inside the coil, which may be expressed as a micro type or an internal magnet type.

(63) In the sound generating actuator of the second structure, the lower plate **210** is fixed to a support hole **310** formed at the cover bottom **300**, the magnet **220** is disposed at a central area of the lower plate, and the center pole extends upward from the top of the magnet.

(64) The upper plate **210'** protrudes from a peripheral part of the lower plate **210**, and the external frame **240** is disposed on the edge of the upper plate **210'**.

(65) The bobbin **250** is disposed to surround the magnet **220** and the center pole **230**, and the coil **260** is wound around the bobbin.

(66) The damper **270** is disposed between the external frame **240** and the bobbin.

(67) The sound generating actuator of the second structure shown in FIG. 3B has a smaller leakage of magnetic flux than that of the first structure shown in FIG. 3A and thus, the corresponding

display device can have a smaller size. However, the sound generating actuator of the second structure may undergo reduction of magnetic flux due to a large current input and is difficult to manufacture.

(68) In these embodiments, both the actuators of the first structure and the second structure may be used, and the following description discusses the first structure as a representative for convenience of description.

(69) The sound generating actuator used in a display device according to an embodiment of the present disclosure is not limited to the type illustrated in FIGS. 3A and 3B, and includes other types of actuators as long as the actuators can vibrate a display panel up and down to generate sound in response to application of the electric current.

(70) FIGS. 4A and 4B illustrate a state in which a sound generating actuator according to an embodiment of the present disclosure vibrates a display panel to generate sound.

(71) FIG. 4A illustrates a state in which the electric current has been applied, wherein the center pole connected to the lower surface of the magnet serves as the N pole and the upper plate connected to the upper surfaces of the magnet serves as the S pole to establish an external magnetic field between coils.

(72) In this state, if an electric current for generating sound is applied to a coil, an applied magnetic field is generated around the coil. The applied magnetic field generates, together with the external magnetic field, a force of moving the bobbin upward.

(73) By the force, the bobbin moves upward and the display panel coupled to the distal end of the bobbin moves upward, as shown in FIG. 4A.

(74) In this state, if the application of the electric current is interrupted or the electric current is applied in the opposite direction, a force of moving the bobbin downward is generated in the same principle, and the display panel thus moves downward.

(75) In this way, according to the direction and magnitude of the electric current applied to the coil, the display panel vibrates up and down to generate sound wave.

(76) FIGS. 5A and 5B illustrate an example of a coupling state between a sound generating actuator according to an embodiment of the present disclosure and a cover bottom, which is a supporting structure of a display device.

(77) FIGS. 6A and 6B illustrate other embodiments of a coupling state between a sound generating actuator and a cover bottom.

(78) The sound generating actuator **200** according to an embodiment of the present disclosure may be inserted through and supported by a support hole formed on a cover bottom or back cover, which is a support structure of a display device. FIGS. 5A to 6B illustrate various support structures.

(79) In the support structure of FIG. 5, a support hole **310** is formed through the cover bottom **300**, and at least one among the lower plate **210** of the sound generating actuator **200**, the magnet **220**, and the upper plate **210'** is inserted and received in the support hole.

(80) An extension part **212** extending outward from the lower plate is additionally formed on the lower surface of the lower plate **210**, and the extension part **212** is fixed to the lower surface of the cover bottom **310** to allow the sound generating actuator **200** to be mounted to the cover bottom.

(81) In this way, when the sound generating actuator **200** is inserted in and fixed to the support hole formed through the cover bottom, the distance between the display panel and the cover bottom can be reduced to thereby reduce the thickness of the display device.

(82) In other words, although an air gap in which the display panel can vibrate should be arranged between the display panel and the cover bottom, the sound generating actuator inserted in/fixed to the support hole of the cover bottom can minimize the air gap due to the reduced height of the sound generating actuator disposed between the rear surface of the display panel and the inner surface of the cover bottom.

(83) In the structure illustrated in FIGS. 5A and 5B, a screw hole is formed on the rear surface of

the cover bottom, and a bolt **320** or a screw is fastened through the screw hole formed through the extension part **212** of the lower plate to the screw hole of the cover bottom to fix the sound generating actuator to the cover bottom.

(84) Meanwhile, in the structure illustrated in FIG. **6A**, which is not a simple screw-coupling structure, a PEM™ nut **330** or self-clinching nut is placed to secure a predetermined distance between the cover bottom **300** and the extension part **212** of the lower plate, and the actuator is then fixed by the bolt **320**.

(85) Use of the PEM nut **330** or self-clinching nut as shown in FIG. **6A** can secure a predetermined space between the sound generating actuator and the cover bottom, thereby minimizing the transfer of the vibrations from the actuator to the cover bottom.

(86) In the structure shown in FIG. **6B**, an adhesive member, such as a double-sided tape, is disposed between the cover bottom and the extension part **212** of the lower plate of the actuator to attach and fix them to each other.

(87) When the adhesive member as shown in FIG. **6B** has a properly adjusted elasticity and thickness, the adhesive member can function as a kind of damper to minimize the transfer of the vibrations from the actuator to the cover bottom.

(88) The structures as shown in FIGS. **5A** to **6B** in which the sound generating actuator **200** attached to the display panel to directly vibrate the display panel is inserted in and fixed to a support hole formed through the cover bottom can reduced the thickness of the display device in comparison with the structure in which the actuator is completely received in the display device.

(89) FIGS. **7A** to **7C** illustrate an example of a baffle part formed between a display panel and a middle cabinet, which is one of structures for supporting the display panel, in order to form an air gap between the display panel, which serves as a vibrating plate, and a cover bottom.

(90) As shown in FIG. **7A**, the panel vibration type sound generating apparatus according to this embodiment secures an air gap **600**, which is a space allowing the panel to be vibrated by the sound generating apparatus **200**, between the display panel **100** and a support structure (cover bottom **300**).

(91) Further, one side of the display panel is coupled to the support structure of the display panel to generate sound waves during the vibration of the display panel. Especially, the generated sound should not leak to the outside through a side, etc. of the display device.

(92) To this end, the display device according to this embodiment has a baffle part **400** formed between the lower surface of the display panel and the support structure.

(93) Specifically, it is preferred that a predetermined section (that is, air gap) is defined around the sound generating actuator, a baffle part is disposed between the upper surface of the cover bottom or middle cabinet and the lower surface of the display panel at an edge of the section, and the baffle part **400** includes an adhesive member **412**, such as a double-sided tape, attached between the lower surface of the display panel and the upper surface of the support structure of the display device, and a sealing part **414** disposed outside the adhesive member.

(94) The section in which the baffle part is formed may be the entire display panel area defined by four outer sides of the display panel. However, the section is not limited to such a definition and may be defined by an area excluding the area in which a source PCB is disposed, as described below.

(95) When two or more sound generating actuators are arranged to implement stereo or three-dimensional sound, two or more sections may be separately arranged to form the baffle part.

(96) As shown in FIGS. **7A** to **7C**, the support structure of the display device may include a middle cabinet **500**, which is coupled to the cover bottom and is configured to allow a part of the display panel to be stably placed thereon, in addition to the cover bottom **300** covering the entire rear surface of the display panel.

(97) The middle cabinet **500** is a frame-shaped member formed along the outer periphery of the display panel, and includes a horizontal support part **502** on which a part of the display panel is

stably placed, and a vertical support part **504** bent perpendicularly in opposite directions from the horizontal support part to cover the side surface of the cover bottom and the side surface of the display panel. Therefore, the middle cabinet may have a shape of a letter “T” in general.

(98) The middle cabinet **500** configures an external ornamental part of the side surface of the display device or set apparatus, and may not be used or integrally formed with the cover bottom in some cases.

(99) According to the embodiment of FIG. 7A, the adhesive member **412** configuring the baffle part **400** is a double-sided tape disposed between the upper surface of the horizontal support part of the middle cabinet **500** and the display panel and fixes the lower surfaces of the display panel to the middle cabinet.

(100) The sealing part **414** configuring the baffle part is placed outside of the adhesive member and preferably has a thickness or height larger than the thickness or height of the adhesive member.

(101) The sealing part **414** may be made from a material having a large elasticity, such as rubber, and has a thickness t_2 larger than the thickness t_1 of the adhesive member **412** as illustrated in FIG. 7B.

(102) That is, as illustrated in FIG. 7B, one adhesive surface of the adhesive member **412**, which is a double-sided tape having a thickness t_1 , is attached to the inner part of the upper surface of the horizontal support part **502** of the middle cabinet **500**, and the sealing part **414** made of an elastic material having a thickness larger than t_1 is disposed outside the adhesive member.

(103) In this state, the display panel **100** is attached to the other adhesive surface of the adhesive member **412**. Then, the display panel is attached to the middle cabinet while pressing, to a certain degree, the sealing part **414** having the larger thickness. (FIG. 7C)

(104) As a result, the sealing of the air gap around the sound generating actuator is further enhanced.

(105) The structure illustrated in FIG. 7C, in which the display panel **100** and the cover bottom **300** are coupled to each other while forming the air gap **600** to be as wide as the thickness of the adhesive member **412** and the horizontal support part **502** of the middle cabinet, can secure a vibration space in which the display panel can generate sound, and can prevent the internally generated sound waves from leaking to the outside along the side surface of the display device.

(106) The baffle part **400** disposed at an edge of the air gap, which has a double structure of the adhesive member **412** and the sealing part **414** while allowing the sealing part to have a larger thickness, can further enhance the sealing of the air gap and prevent leakage of the sound.

(107) It should be construed that the middle cabinet **500** used in the present specification may be replaced by another term, such as a guide panel, a plastic chassis, a p-chassis, a support main, a main support, or a mold frame, and includes all types of members, which are structures having a shape of a four-sided frame and having a sectional shape including multiple bent portions and are connected to the cover bottom to be used to support the display panel and the baffle part.

(108) The middle cabinet **500** may be made of synthetic resin, such as a polycarbonate, by injection molding, without being limited thereto.

(109) FIG. 8 illustrates a structure of a baffle part according to another embodiment in which the adhesive member and the sealing part are placed directly on a cover bottom.

(110) Although a middle cabinet is used to support the cover bottom and the display panel in the embodiment described above, the middle cabinet may not be always required.

(111) The embodiment illustrated in FIG. 8 shows a structure in which the cover bottom **300** supports one side of the display panel while forming an external appearance of the side surface of the display device without a middle cabinet.

(112) The structure illustrated in FIG. 8 includes a cover bottom **300** in which a step portion **360** protrudes upward from a base surface at one side of the cover bottom **300** and a side surface supporting part **362** vertically extends from the outside of the step portion **360**.

(113) A part of the edge of the display panel **100** is stably placed on and attached to the step portion

360 of the cover bottom **300**, the side surface support part **362** of the cover bottom surrounds and protects the side surface of the display panel **100**, and the cover bottom resultantly forms an external ornamental part of the entire side and rear surfaces of the display device.

(114) In this structure, in order to configure the baffle part **400** for generation of sound, the adhesive member **412** in the form of a double-sided tape is disposed inside the step portion **360** of the cover bottom and the sealing part **414** having a thickness larger than that of the adhesive member is disposed outside the adhesive member.

(115) In this state, the display panel **100** is placed on the step portion **360** of the cover bottom and is attached to one adhesive surface of the adhesive member **412**, so that the display panel is coupled to the cover bottom. Then, the sealing part **414** is compressed to secure and enhance the sealing of the air gap for transfer of sound.

(116) The embodiment of FIG. **8** has a simple structure without a middle support structure like the middle cabinet and includes the baffle part **400**, which is disposed at an edge of the air gap and has a double structure of the adhesive member **412** and the sealing part **414** while allowing the sealing part to have a larger thickness. Therefore, the embodiment of FIG. **8** can secure a vibration space in which the display panel can generate sound, and can prevent the internally generated sound waves from leaking to the outside along the side surface of the display device.

(117) The thickness of the air gap, that is, the distance G between the display panel and the cover bottom, may have a value of about 1.0 to 3.0 mm in an embodiment of the present disclosure. However, the thickness is not limited to the range and may have a value in a range different according to the degree of vibration of the display panel, etc.

(118) However, in order to reduce the thickness of the display device, it is preferable to minimize the thickness G of the air gap in consideration of the quantity of vibration of the display panel by the sound generating actuator, the range of sound to be output, and the quantity of output. In an embodiment of the present disclosure, an optimum thickness of the air gap G is about 2.0 mm.

(119) FIGS. **9A** and **9B** illustrate a locational relation between a source PCB for driving a display panel and a set PCB for driving a set apparatus, which are arranged at the rear surface of a display device.

(120) As shown in FIGS. **9A** and **9B**, the display device includes a source PCB, which is a circuit board including a Source Driver Integrated Circuit (S-DIC) for driving a display panel to drive data lines formed on the display panel and is referred to as simply "S-PCB".

(121) The display device or a set apparatus including the same is connected to the S-PCB and may further include a Control Printed Circuit Board (C-PCB) having control parts and various electric devices mounted thereon to generally control the display device or set apparatus.

(122) Specifically, an OLED display device, to which the present embodiment is applicable, may include: an OLED display panel **100** including a plurality of data lines DL, a plurality of gate lines, and a plurality of sub-pixel SP arranged thereon; a data driver configured to drive the plurality of data lines DL; a gate driver configured to drive the plurality of gate lines GL; and a controller configured to control the data driver and the gate driver.

(123) The controller supplies various control signals to the data driver and the gate driver to control the data driver and the gate driver, starts scanning according to a timing implemented in each frame, converts image data input from the outside into a data signal format used in the data driver and outputs a converted image data, and properly controls the driving of the data driver according to the scanning.

(124) The controller may be a timing controller used in a general display technology or may be a control apparatus including a timing controller to further perform another control function.

(125) The data driver supplies a data voltage to the plurality of data lines DL to drive the data lines DL. Herein, the data driver is also referred to as a "source driver".

(126) The data driver may include at least one Source Driver Integrated Circuit (S-DIC) to drive the plurality of data lines.

(127) The gate driver sequentially supplies a scan signal to the plurality of gate lines GL to sequentially drive the gate lines GL. The gate driver is also referred to as a “scan driver” and may include at least one Gate Driver Integrated Circuit (G-DIC).

(128) Each Source Driver Integrated Circuit (S-DIC) may be connected to a bonding pad of an OLED display panel either by a Tape Automated Bonding (TAB) method or a Chip On Glass (COG) method or directly. In some cases, S-DICs may be integrated and arranged in an OLED panel. Further, each S-DIC may be packaged on a film connected to an OLED display panel by a Chip On Film (COF) method.

(129) That is, a display device, to which the present embodiment is applicable, may include: at least one Source Printed Circuit Board (S-PCB) necessary for circuit connection of at least one Source Driver Integrated Circuit (S-DIC); and a Control Printed Circuit Board (C-PCB) or set PCB configured to mount control parts for controlling the entire display device and various electric devices thereon.

(130) Here, at least one S-DIC may be mounted on or a Chip-On Film (COF) having at least one S-DIC mounted thereof may be connected to the at least one source PCB.

(131) The C-PCB or set PCB **800** may include a controller configured to control operations of the data driver and the gate driver, and a Power Management IC (PMIC) configured to supply various voltages or currents to the display panel, the data driver, and the gate driver or control the various voltages or currents to be supplied.

(132) The source PCB is usually located at one side among the upper side and the lower side of a display panel. However, according to the driving scheme or panel design scheme, the source PCB may be arranged on both the upper side and the lower side.

(133) That is, as shown in FIGS. **9A** and **9B**, the source PCB **700** is connected to the display panel **100** and the COF **710** and is disposed on a lower rear surface of the display panel.

(134) The C-PCB or set PCB **800** may be disposed at the outer rear side of the cover bottom **300** and connected through a flexible cable to the source PCB **700** located inside the cover bottom.

(135) In the structure shown in FIGS. **9A** and **9B**, it is difficult to configure a baffle part as described above with reference to FIGS. **7A** to **7C**, at the lower side of the display panel having the sound generating actuator **200** mounted thereon.

(136) In other words, since the source PCB **700** and the chip-on film **710** connected thereto are arranged in the vicinity of the lower side of the display panel, it is difficult to arrange the baffle part **400** including the adhesive member **412** and the sealing part **414**, and the sealing of the air gap may be degraded even when the baffle part is arranged.

(137) Further, the generated sound may leak backward through a cable passing hole, which is formed through a part at the lower side of the cover bottom to enable a flexible cable for connection between the source PCB **700** disposed inside the cover bottom and the set PCB **800** disposed outside the cover bottom to pass therethrough.

(138) Therefore, in order to apply a sound generating apparatus of the present embodiment to a display device having the structure as shown in FIGS. **9A** and **9B**, it is necessary to solve the problems of degradation in the sealing of the baffle part and the sound leakage. In this respect, an embodiment, as shown in FIGS. **10A** and **10B**, is presented.

(139) The embodiment illustrated in FIGS. **10A** and **10B** has a structure, which further includes an area division member **510** configured to partition the middle cabinet into two or more areas and has a baffle part formed on the area division member, in order to solve the problems of the structure described above with reference to FIGS. **9A** and **9B**. This embodiment also includes a cable passing hole through which a connection cable (FFC) formed on a cover bottom passes.

(140) The area division member **510** divides the entire area of the middle cabinet surrounding the entire display panel into a first area A in which the source PCB is included and a second area B in which the source PCB is not included, wherein the sound generating actuator **200** is disposed in a part of the second area B.

(141) The area division member may be manufactured in the form of a bar having a thickness corresponding to the horizontal support part of the middle cabinet to be attached to the middle cabinet **500** through welding, etc. However, the present disclosure is not limited thereto and the entire middle cabinet including the area division member **510** may be integrally manufactured as one unit.

(142) As shown in FIG. **10A**, an area division member **510** is lengthily disposed in the horizontal direction of the display device, and an adhesive member **412** and a sealing part **414** are arranged on the upper side of the area division member **510** and three sides of the middle cabinet corresponding to the second area B.

(143) FIG. **10B** is a sectional view taken along line I-I' of FIG. **10A**, in which the adhesive member **412** and the sealing part **414** are arranged on the upper side of the area division member **510** to seal the second area B as an air gap.

(144) In a part of the lower area of the cover bottom **300**, specifically, among the areas divided by the area division member **510**, a cable passing hole **370**, through which a connection cable **810** connecting the source PCB **700** and the set PCB **800** is to pass, is formed in the first area A, which includes the source PCB.

(145) The structure as shown in FIGS. **10A** and **10B** in which only the second area B, which does not include a source PCB is formed as a sound generating area can minimize the degradation of the sealing of the sound generating area by interference of the source PCB.

(146) Further, the cable passing hole **370** disposed in the first area A including the source PCB can prevent sound leakage through the cable passing hole.

(147) FIGS. **11A** and **11B** are schematic views showing the relative arrangement of the cover bottom and the source PCB for driving the display panel.

(148) As shown in FIG. **11A**, a source PCB **700** including an S-DIC or data driver is connected to the display panel through a chip-on film, etc., and is disposed at one side (lower side) of the display panel.

(149) As shown in FIG. **11B**, a gap *g* is formed between the source PCB and the cover bottom in the area in which the source PCB is disposed, and is smaller than a gap between the source PCB and the cover bottom in the other area.

(150) Therefore, when the sound generating actuator **200** according to the present embodiment is arranged and vibrates the display panel, the source PCB, which integrally vibrates the display panel, may collide with the cover bottom in the area in which the source PCB is placed.

(151) The collision between the source PCB and the cover bottom may generate noise and may even damage the source PCB.

(152) Further, even without direct collision between the source PCB and the cover bottom, strong vibrations of the display panel at the time of sound generation may have an influence on the performance of the source PCB when the vibration is continuously transferred to the source PCB.

(153) In order to solve this problem, arranging a buffer member for protecting the source PCB between the source PCB and the cover bottom or between the display panel and the cover bottom is proposed.

(154) FIGS. **12A** and **12B** illustrate an embodiment including a buffer member capable of preventing interference and noise between the source PCB and the cover bottom illustrated in FIGS. **11A** and **11B**.

(155) In the embodiment of FIGS. **12A** and **12B**, a source PCB **700** including a circuit element for driving the display panel is disposed at the rear surface of the display panel, a recessed part **380** is formed in an area of the cover bottom, which faces the source PCB, and a first buffer member **910** having a predetermined elasticity is placed on the upper surface of the concave part **380**. The recessed part **380** may be concave, for example.

(156) Further, a second buffer member **920** extending along a length of one direction may be additionally disposed on the cover bottom.

(157) Specifically, as shown in FIG. 12A, the display panel may be divided into a first area A covering the source PCB and a second area B covering the sound generating actuator, and the second buffer member **920** is preferably disposed as being extended along a length of the first area A and second area B to separate the first area A and the second area B from each other.

(158) Of course, although not illustrated, the baffle part **400** including the adhesive member **412** and the sealing part **414** described above with reference to FIGS. 7A to 8 may be disposed on all of the four sides of the display panel in the embodiment of FIGS. 12A and 12B.

(159) The first buffer member **910** and the second buffer member **920** may be configured by a one-sided tape or double-sided tape. However, the present disclosure is not limited thereto, and the buffer member may include all types of members formed of rubber, plastic, paper, or other materials, which have a predetermined elasticity.

(160) It is preferred that the first buffer member **910** is disposed on the concave part **380** of the cover bottom while the upper surface of the first buffer member **910** is spaced a predetermined distance apart from the source PCB and the second buffer member **920** has one surface in contact with the cover bottom and the other surface in contact with the lower surface of the display panel.

(161) Of course, the first buffer member **910** may be placed on a part of the upper surface of the cover bottom, which faces the source PCB.

(162) As shown in FIG. 12B, the concave part **380** formed at the cover bottom area corresponding to the source PCB increases the gap between the source PCB and the cover bottom to reduce the possibility that the source PCB may collide with the cover bottom even when the display panel vibrates to generate sound.

(163) Moreover, the first buffer member **910** disposed on the concave part **380** of the cover bottom can buffer a large vibration of the display panel even when the source PCB moves toward the concave part of the cover bottom due to the larger vibrations, so as to reduce the generation of noise due to interference between the source PCB and the cover bottom and reduce the possibility of damage to the source PCB.

(164) Further, when the display panel vibrates in the second area B, which is the sound generation area, the second buffer member **920** can prevent the vibration from being transferred to the source PCB **700** disposed on the rear surface of the display panel to some degree, and thus can minimize the degradation of performance of the source PCB due to continuous vibration of the display panel.

(165) The location of the sound generating actuator may be changed according to the arrangement of the second buffer member **920**.

(166) That is, as shown in FIG. 12A, when the second buffer member **920** is spaced a distance d apart from the lower side of the display panel, the sound generating actuator **200** may be moved by about $2d$ from the initial position **P1** and is then installed at position **P2**.

(167) Changes in the sound output characteristics according to the installation of the second buffer member can be minimized by moving the sound generating actuator by about twice that of the space d between the second buffer member **920** and one side of the display panel.

(168) FIG. 13 is a graph illustrating a noise reduction effect in the case of using the buffer members of the embodiment illustrated in FIGS. 12A and 12B.

(169) As a result of actual experiments, it has been confirmed that, when the first buffer member **910** and the second buffer member **920** described above with reference to FIGS. 12A and 12B are not used, unnecessary excessive noise was generated in a low sound range of several dozens of Hz and in a sound range of 1000 Hz or higher, as noted from the dotted line of FIG. 13.

(170) In contrast, as noted from the solid line of FIG. 13, the noise is largely reduced in the corresponding bands when the buffer members of FIGS. 12A and 12B are used.

(171) FIG. 14 illustrates a relative arrangement between a sound generating actuator and a set PCB in a display device according to an embodiment of the present disclosure.

(172) In general, a display device or a set apparatus including the display device includes not only a source PCB including a control circuit (data driver IC, etc.) for driving a touch function or a data

line of a display panel, but also a set PCB connected to the source PCB to control the display device or the entire set apparatus and supply power thereto.

(173) As described above with reference to FIGS. **10A** and **10B**, the source PCB is attached to the rear surface of the display panel and the set PCB is attached to the outer side of the rear surface support structure of the display device, such as a cover bottom or a back cover.

(174) The embodiment of FIG. **14** provides a display device in which a sound generating actuator is placed at a first position of a support structure of the display device and a set PCB of a set apparatus is placed at a second position different from the first positions, so as to avoid interference between the sound generating actuator and the set PCB.

(175) As illustrated in FIG. **14**, the set PCB **800** placed on the rear surface of the cover bottom may include a power board **810** configured to supply power to the display panel, a timing controller **820** configured to generate a timing pulse or a timing signal for driving a gate line or data line, and a main board **830** including a control circuit for controlling the entire display device or set apparatus.

(176) Boards **810**, **820**, and **830** of the set PCB **800** are attached to the rear surface of the cover bottom **300**, and the sound generating actuator **200** is fixedly inserted in a support hole formed through the cover bottom as described above.

(177) Therefore, it is preferable to place the sound generating actuator **200** (first position) and the set PCB (second position) at different positions, as shown in FIG. **14**, to avoid interference therebetween.

(178) Even when the sound generating actuator **200** is fixed within the cover bottom, if the positions of the sound generating actuator and the set PCB overlap, the vibration of the sound generating actuator may be continuously transferred to the circuit elements of the set PCB to have a bad influence on the performance of the set PCB.

(179) Therefore, the arrangement of the sound generating actuator **200** (first position) and the set PCB (second position) at different positions as shown in FIG. **14** facilitates the arrangement design of elements and can minimize the degradation of the performance of the set PCB.

(180) FIGS. **15A** and **15B** illustrate a display device including two or more actuators symmetrically arranged therein, and a distortion of a cover bottom due to a difference of vibration quantity in the display device.

(181) According to the embodiment shown in FIGS. **15A** and **15B**, a plurality of sound generating actuators may be symmetrically arranged at left and right portions or upper and lower portions of the display panel to output different sounds at the areas.

(182) For example, as shown in FIG. **15A**, in order to implement stereo sound, one or two left sound generating actuators **1210** and **1210'** are arranged at the left side of the display panel, one or two right sound generating actuators **1220** and **1220'** are arranged at the right side of the display panel, and the left and right actuators may be differently vibrated.

(183) As shown in FIG. **15B**, which is a sectional view taken along line II-II' of FIG. **15A**, when the different vibrations of the left and right actuators **1210** and **1220** are continuously repeated, the vibration difference between the left side and right side of the cover bottom **1300** is continuously accumulated.

(184) Since the cover bottom is usually manufactured to have as thin a thickness as possible, the accumulation of the vibration difference between the left side and right side of the cover bottom may cause the cover bottom to be curved or deformed. That is, as shown in FIG. **15B**, the cover bottom **1300** may be twisted or deformed. Further, even when the cover bottom **1300** is not deformed, the vibration difference of the cover bottom due to the vibration difference between the left and right actuators may cause distortion of the generated sound.

(185) In order to solve this problem, a structure as shown in FIGS. **16A** and **16B**, which has a reinforcement member disposed inside a support structure of a display device while using two or more sound generating actuators is proposed.

(186) This structure prevents the generation of sound distortion by twisting or vibration of the

cover bottom.

(187) In the embodiment illustrated in FIGS. **16A** and **16B**, at least one reinforcement member **1310** may be disposed inside or outside of the cover bottom in order to prevent deformation of the cover bottom or sound distortion by the unbalanced vibration of the cover bottom in the case of using multiple sound generating actuators having different vibration characteristics as described with reference to FIGS. **15A** and **15B**.

(188) The reinforcement member **1310** may be formed to have a shape of a long bar passing through a portion adjacent to multiple sound generating actuators and are preferably arranged at particular positions to optimize the reinforcement characteristics.

(189) As shown in FIG. **16A**, when two left sound generating actuators **1210** and **1210'** and two right sound generating actuators **1220** and **1220'** are arranged, the reinforcement member **1310** may be disposed to extend through a middle point Q between the two left sound generating actuators **1210** and **1210'** and a middle point Q' between the two right sound generating actuators **1220** and **1220'**.

(190) This arrangement can optimize the reinforcement performance of the reinforcement member **1310** even when the two left and right sound generating actuators have different vibration characteristics.

(191) The reinforcement member **1310** may be manufactured in the form of a separate metal bar and is then attached to the inner surface of the cover bottom as shown in FIG. **16B**, to which the present disclosure is not limited.

(192) For example, the cover bottom may be manufactured through injection molding, and may have a reinforcement member **1310** integrally formed by protruding a part of the inner surface of the cover bottom.

(193) The reinforcement member **1310** is not inevitably disposed on the inner surface of the cover bottom, but may be disposed on the outer surface of the cover bottom. However, in consideration of an external appearance and the thickness of the display device, it is preferred that the reinforcement member is disposed on the inner surface of the cover bottom **1300**.

(194) FIGS. **17A** and **17B** illustrate specific arrangements of reinforcement members on a cover bottom.

(195) FIG. **17A** illustrates a structure in which three sound generating actuators are arranged at each of the left side and right side thereof and two reinforcement members **1310** and **1310'** are arranged, wherein a first reinforcement member **1310** is disposed to extend through middle points Q-Q' of segments, each of which connects to two upper actuators among the three left or right sound generating actuators, and a second reinforcement member **1310'** is disposed to extend through middle points S-S' of segments, each of which connects to two lower actuators among the three left or right sound generating actuators.

(196) FIG. **17B** illustrates a structure in which only one left actuator and only one right actuator are arranged and the reinforcement member **1310** is disposed to extend through centers of the left and right actuators **1210** and **1210'**. In this structure, two divided reinforcement members may be formed in consideration of the arrangement structure of the actuators inserted in and supported by the cover bottom.

(197) The symmetric arrangement of two or more sound generating actuators having different vibration characteristics as described above can prevent deformation (twisting) of the cover bottom due to the different vibration characteristics of the sound generating actuators or sound distortion by the vibration of the cover bottom.

(198) FIGS. **18A** and **18B** illustrate an embodiment, which further includes a sound compensation member in order to maintain the sound output characteristics when the sound generating actuator has been vertically moved by a reason of design.

(199) FIG. **18A** illustrates a state in which a sound generating actuator **200** is disposed at an initial position P3 having an optimal sound output characteristic.

(200) However, the sound generating actuator may have to be moved by a predetermined distance D from the initial position $P3$ in order to maintain a lower thickness of the upper end portion or by reasons relating to design or arrangement of parts.

(201) In this case, only a simple movement of the sound generating actuator changes the relative position with respect to the baffle part **400** and may thus degrade the sound output characteristics.

(202) Therefore, in such a case, if the sound generating actuator is moved to a destination position $P4$ spaced a movement distance D apart from the initial position $P3$, a lengthy sound compensation member **1400** is preferably placed at a position spaced $2D$ apart from an edge (side) opposite to the moving direction.

(203) That is, as shown in FIG. **18B**, when the sound generating actuator is moved downward to a position $P4$ spaced apart by D from the initial position $P3$ by a reason relating to design, a sound compensation member **1400** extending along the length of the horizontal direction is placed at a position spaced apart by $2D$ from the upper edge of the display panel. The arrangement of a sound compensation member at a position corresponding to twice that of the moving distance D of the sound generating actuator enables the moved actuator to be located in the middle of the changed air gap by the sound compensation member, thereby minimizing the change in the sound generation characteristics according to the movement of the actuator.

(204) The sound compensation member **1400** may be implemented by a double-sided tape disposed between the cover bottom and the display panel.

(205) As described above, when it is necessary to change the position of a sound generating actuator, a sound compensation member may be placed at a position proportional to the moving distance, to maintain the relative position of the actuator in the entire air gap, thereby preventing the sound characteristics from changing according to the movement of the actuator.

(206) FIG. **19** is a graph illustrating a sound output characteristic in the case of using a panel vibration type sound generating apparatus according to an embodiment of the present disclosure, in comparison with a conventional speaker.

(207) As a result of an actual experiment, a rapid sound intensity reduction (sound pressure reduction) as illustrated by a dotted line in FIG. **19** was observed in the middle/high sound range of 4000 Hz or higher when a speaker disposed at the rear surface or the lower end as shown in FIG. **1** separately from the display panel.

(208) In contrast, as illustrated by a solid line in FIG. **19**, the structure according to this embodiment, in which a sound generating actuator is fixed to a support structure to directly vibrate the display panel, can reduce the sound pressure in the middle/high sound range, and especially can greatly improve the sound output characteristic in the high sound range.

(209) As a result, use of the present embodiment can provide rich sound output in all sound ranges.

(210) According to the present embodiment as described above, one or more sound generating actuators are fixed to a support structure to directly vibrate the display panel. Therefore, the progressing direction of the sound coincides with the image output direction to enhance the sound localization and improve the sound output characteristics in a wide sound range.

(211) Further, since a display device or a set apparatus does not require a separate speaker, the mechanism of the set apparatus can be easily designed and the thickness of the display device or set apparatus can be reduced.

(212) Especially, a predetermined air gap is formed between the display panel and the sound generating actuator and the sound generating actuator is inserted in and fixed to a support hole formed at a support structure of the display device. Therefore, the display device has an excellent sound generation performance while having a reduced thickness.

(213) Further, a baffle part, which includes an adhesive member (double-sided tape) attached between the upper surface of the support structure and the lower surface of the display panel and a sealing part disposed outside the adhesive member, can minimize sound leakage and improve the sound generating performance.

(214) Further, the arrangement of one or more buffer members between a source PCB of the display panel and the support structure disposed at the rear surface of the display panel to fix/support the sound generating actuator or between the inner surface of the support structure and the rear surface of the display panel adjacent to the source PCB can prevent generation of interference and noise between the support structure of the display device and a source PCB (S-PCB) for driving the display panel.

(215) Also, the arrangement of a reinforcement member on the support structure of the display device when two or more sound generating actuators are used can prevent deformation of the support structure due to different vibrations of the two or more sound generating actuators.

(216) The above description and the accompanying drawings provide an example of the technical idea of the present invention for illustrative purposes only. Those having ordinary knowledge in the technical field, to which the present invention pertains, will appreciate that various modifications and changes in form, such as combination, separation, substitution, and change of a configuration, are possible without departing from the essential features of the present invention. Therefore, the embodiments disclosed in the present invention are intended to illustrate the scope of the technical idea of the present invention, and the scope of the present invention is not limited by the embodiment. The scope of the present invention shall be construed on the basis of the accompanying claims in such a manner that all of the technical ideas included within the scope equivalent to the claims belong to the present invention.

Claims

1. An apparatus, comprising: a vibrating plate; at least one sound generating actuator disposed at a rear of the vibrating plate and configured to vibrate the vibrating plate to generate sound; a support structure on a rear surface of the vibrating plate; a printed circuit at the rear of the vibrating plate; and an area division member at a rear portion of the vibrating plate, the area division member dividing an area at the rear portion of the vibrating plate into a first area including the printed circuit and a second area including the at least one sound generating actuator.
2. The apparatus of claim 1, further comprising a baffle part disposed between the support structure and the vibrating plate to form an air gap between the support structure and the vibrating plate.
3. The apparatus of claim 2, wherein the baffle part is disposed at a periphery of the second area between the support structure and the vibrating plate to surround the air gap in the second area.
4. The apparatus of claim 2, wherein the vibrating plate is configured to generate sound waves in the air gap when vibrated by the at least two sound generating actuators, and wherein the baffle part surrounds the air gap to reduce leakage of the sound waves out of the air gap.
5. The apparatus of claim 2, wherein the baffle part comprises at least one of an adhesive member and a sealing part disposed outside of the adhesive member.
6. The apparatus of claim 1, wherein the at least one sound generating actuator includes at least two sound generating actuators, and wherein the apparatus further comprises a reinforcement member extending between a sound generating actuator and another sound generating actuator among the at least two sound generating actuators.
7. The apparatus of claim 6, wherein the reinforcement member is disposed apart from the sound generating actuator and the other sound generating actuator.
8. The apparatus of claim 1, wherein the support structure comprises: a cover bottom covering the rear portion of the vibrating plate; and a middle cabinet supporting a periphery of the vibrating plate.
9. The apparatus of claim 1, wherein the support structure comprises: a recessed part disposed in an inner surface of the support structure, the recessed part being disposed opposite the printed circuit; and a first buffer member in the recessed part between the support structure and the printed circuit.
10. The apparatus of claim 1, wherein the at least one sound generating actuator includes at least

two sound generating actuators respectively disposed at different areas of the vibrating plate and respectively configured to vibrate the different areas of the vibrating plate to generate sound, and wherein each of the at least two sound generating actuators is configured to vibrate the vibrating plate to generate sound projecting in a direction coinciding with an image output direction of the vibrating plate to localize the output sound.

11. The apparatus of claim 10, further comprising a baffle part at a rear portion of the vibrating plate separating one of the different areas from another of the different areas.

12. The apparatus of claim 10, wherein the at least two sound generating actuators are configured to generate a stereo sound.

13. The apparatus of claim 10, wherein the at least two sound generating actuators are symmetrically arranged.

14. The apparatus of claim 10, wherein the at least two sound generating actuators are configured to generate different vibrations from one another to generate different sounds in the different areas of the vibrating plate.

15. The apparatus of claim 1, wherein the thickness of the air gap is from about 1.0 mm to 3.0 mm.

16. The apparatus of claim 1, further comprising a sound compensation member.
