

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12394937
Kind Code	B1
Date of Patent	August 19, 2025
Inventor(s)	Ruan; Lidan

Waterproof connector, cable extension cord and waterproof string light

Abstract

The present disclosure provides a waterproof connector which is configured to connect cables, the connector including: a first interface which includes: a plug handle; and a first waterproof cap which is sleeved on an outer side of the plug handle; and a second interface which includes: a socket handle. The plug is capable of being selectively inserted in the socket such that an end face of a first end of the plug handle is closely fitted with an end face of a first end of the socket handle.

Inventors:	Ruan; Lidan (Zhejiang, CN)
Applicant:	Ningbo Maoli Electric Appliance Co., Ltd (Zhejiang, CN)
Family ID:	1000008767845
Assignee:	NINGBO MAOLI ELECTRIC APPLIANCE CO., LTD (Zhejiang, CN)
Appl. No.:	18/900412
Filed:	September 27, 2024

Foreign Application Priority Data

CN	202420284391.3	Feb. 06, 2024
----	----------------	---------------

Related U.S. Application Data

continuation parent-doc US 18584723 20240222 US 12126114 child-doc US 18900412

Publication Classification

Int. Cl.: H01R13/00 (20060101); F21S4/10 (20160101); F21S9/03 (20060101); F21V23/06 (20060101); F21V31/00 (20060101); H01R13/52 (20060101); H01R13/622 (20060101); H02S40/34 (20140101)

U.S. Cl.:

CPC **H01R13/622** (20130101); **F21S4/10** (20160101); **F21S9/03** (20130101); **F21V23/06** (20130101); **F21V31/005** (20130101); **H01R13/5213** (20130101); **H02S40/34** (20141201);

Field of Classification Search

CPC: H01R (13/622); H02S (40/34); F21S (4/10); F21S (9/03); F21V (23/06); F21V (31/003)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5350315	12/1993	Cheng	N/A	N/A
6267342	12/2000	Huang	362/396	F21V 21/08
8888528	12/2013	Van Swearingen	439/578	H01R 9/05
2014/0273568	12/2013	Lin	N/A	N/A
2019/0003667	12/2018	Marasco	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2015125029	12/2014	WO	N/A

Primary Examiner: Nguyen; Phuong Chi Thi

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) The application is a continuation of U.S. patent application Ser. No. 18/584,723, which claims priority of Chinese patent application CN 202420284391.3, filed on Feb. 6, 2024, both of which are incorporated herein by reference in their entirety.

TECHNICAL FIELD

(1) The present disclosure relates to the technical field of illumination lights, in particular to a waterproof connector, a cable extension cord and a waterproof string light.

BACKGROUND

(2) String lights are not only widely applied to occasional decoration for various festivals, home decoration and various entertainment venues, but also widely applied to lighting projects of cities. Due to different application scenes, the lengths of the string lights are also different. In one case, there is no node in the string lights, and the string lights are cut off after the actual lengths are measured. If the applied shape is relatively complex, the difficulty in construction will be increased due to the excessively long string lights. In addition, the relatively long string lights are also adverse to later maintenance, and if one part of the string light breaks down, it is highly possible that the entire string light needs to be replaced. Therefore, during construction, a plurality of relatively short string lights are usually connected into a relatively long string light in a spliced manner. The splicing manner has multiple advantages, but also has some defects, particularly at the junctions of the string lights. The problems about waterproofness, falling-off prevention and convenience in connection at junctions need to be solved.

SUMMARY

(3) A first aspect of the present application provides the waterproof connector which is configured to connect cables, including: a first interface which includes a plug handle, a first end of the plug handle is provided with a plug extending outwards, a junction of the plug and the cable is encapsulated in the plug handle; a second interface which includes a socket handle, a first end of the socket handle is provided with a socket extending inwards, a junction of the socket and the cable is encapsulated in the socket handle; a first waterproof cap, sleeved on an outer side of the plug handle and an outer side of the socket handle; and the plug is capable of being selectively inserted in the socket, such that an end face of the first end of the plug handle is closely fitted with an end face of the first end of the socket handle.

(4) A second aspect of the present application provides the cable extension cord, including: a cable; and a waterproof connector which is configured to connect cables and includes: a first interface which includes: a plug handle, a first end of the plug handle is provided with a plug extending outwards, a junction of the plug and the cable is encapsulated in the plug handle; a second interface which includes a socket handle, a first end of the socket handle is provided with a socket extending inwards, a junction of the socket and the cable is encapsulated in the socket handle; a first waterproof cap, sleeved on an outer side of the plug handle and an outer side of the socket handle; the plug is capable of being selectively inserted in the socket such that an end face of the first end of the plug handle is closely fitted with an end face of the first end of the socket handle; a first end of the cable is provided with the first interface of the waterproof connector; and a second end of the cable is provided with the second interface of the waterproof connector.

(5) A third aspect of the present application provides the waterproof string light, including cables; and waterproof connectors which are configured to connect the cables, each of the waterproof connectors includes a first interface which includes a plug handle, a first end of the plug handle is provided with a plug extending outwards, a junction of the plug and the cable is encapsulated in the plug handle; a second interface which includes a socket handle, a first end of the socket handle is provided with a socket extending inwards, a junction of the socket and the cable is encapsulated in the socket handle; the plug is capable of being selectively inserted in the socket, such that an end face of the first end of the plug handle is closely fitted with an end face of the first end of the socket handle; a first end of each of the cables is provided with at least one of the first interface of the waterproof connectors, and a second end of the cable is provided with at least one of the second interface of the waterproof connectors; and the cables are provided with a plurality of light modules.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Drawings constituting part of the present application are used for providing a further understanding to the present disclosure. Schematic embodiments of the present disclosure and descriptions thereof are intended to explain the present disclosure, and should not be construed to unduly limit the present disclosure.

(2) FIG. 1 is an overall structural schematic diagram of a string light.

(3) FIG. 2 is a structural schematic diagram of a first embodiment of a waterproof connector.

(4) FIG. 3 is a structural schematic diagram of a first interface of the waterproof connector in FIG. 2.

(5) FIG. 4 is a structural schematic diagram of a second interface of the waterproof connector in FIG. 2.

(6) FIG. 5 is a structural schematic diagram of a second embodiment of the waterproof connector.

(7) FIG. 6 is a structural schematic diagram of a first interface of the waterproof connector in FIG.

5.

(8) FIG. 7 is a structural schematic diagram of a third embodiment of the waterproof connector.

(9) FIG. 8 is a structural schematic diagram of a second interface of the waterproof connector in FIG. 7.

(10) FIG. 9 is a structural schematic diagram of a fourth embodiment of the waterproof connector.

(11) FIG. 10 is a structural schematic diagram of a second waterproof cap of the waterproof connector in FIG. 9.

(12) FIG. 11 is a structural schematic diagram of a first embodiment of a light module.

(13) FIG. 12 is a structural schematic diagram of a second embodiment of the light module.

(14) FIG. 13 is a structural schematic diagram of a third embodiment of the light module.

(15) FIG. 14 is an overall structural schematic diagram of a string light with a solar power supply device.

(16) FIG. 15 is a structural schematic diagram of the second type of solar power supply device.

(17) FIG. 16 is a structural schematic diagram of the first type of mobile power supply apparatus.

(18) FIG. 17 is a structural schematic diagram of the second type of mobile power supply apparatus.

(19) FIG. 18 is a structural schematic diagram of the first type of cable extension cord.

(20) FIG. 19 is a structural schematic diagram of the second type of cable extension cord.

DETAILED DESCRIPTION OF EMBODIMENTS

(21) The present disclosure is described in detail below with reference to the accompanying drawings and in conjunction with embodiments. Each example is provided to explain the present disclosure instead of limiting the present disclosure. In fact, those skilled in the art will know that modifications and variations may be made in the present disclosure without departing from the scope or spirit of the present disclosure. For example, features shown or described as part of one embodiment may be used in another embodiment to produce yet another embodiment. Therefore, it is expected that the present disclosure includes such modifications and variations that fall within the scope of the appended claims and equivalents thereof.

(22) In the descriptions of the present disclosure, orientations or positional relationships indicated by the terms “longitudinal”, “transverse”, “upper”, “lower”, “front”, “rear”, “left”, “right”, “vertical”, “horizontal”, “top”, “bottom” and the like are orientations or positional relationships based on the drawings, are only for the purpose of facilitating describing of the present disclosure, and do not indicate that the present disclosure must be constructed and operated in the specific orientations. Therefore, they cannot be understood as limitations on the present disclosure. The terms “connection”, “connecting” and “arrangement” used in the present disclosure should be understood in a broad sense, for example, the connection may be fixed connection, and may also be detachable connection; the connection may be direct connection, and may also be indirect connection by means of intermediate components; the connection may be wired electrical connection and wireless electrical connection, and may also be wireless communication signal connection; and for those of ordinary skill in the art, the specific meanings of the above-mentioned terms can be understood according to the specific situations.

(23) The accompanying drawings show one or more examples of the present disclosure. Numeral and letter marks are used in the detailed descriptions to refer to the features in the accompanying drawings. Similar or like reference signs in the accompanying drawings and descriptions have been used to refer to similar or like parts of the present disclosure. As used herein, the terms “first”, “second”, “third” and the like are used interchangeably to distinguish one component from another, and are not intended to indicate the positions or importance of individual components.

(24) As shown in FIG. 1, according to an embodiment of the present disclosure, a waterproof string light **100** is provided and includes cables **200**, where the cables **200** are provided with a plurality of light modules **400**. Two string lights **100** are in circuit connection with each other by means of a connector **300** having a waterproof function.

(25) The connector **300** having the waterproof function includes a first interface **310** and a second interface **320** which can be separated from or combined with each other.

(26) Specifically, as shown in FIG. 2, FIG. 3 and FIG. 4, the first interface **310** includes a plug handle **312**, a first end **3121** of the plug handle **312** is provided with a plug **311** protruding outwards in an axial direction of the plug handle **312**, and the plug **311** is provided with a first electrical connection member; a second end of the plug handle **312** is provided with the cable **200**; and the plug **311** is electrically connected to the cable **200** inside the plug handle **312**. An outer side of the plug handle **312** is sleeved with a first waterproof cap **313**, and an inner wall of the first waterproof cap **313** is provided with an internal thread **3131**. The plug handle **312** is provided with an annular first protruding edge **314** extending outwards in a radial direction thereof. The bottom of the first waterproof cap **313** abuts against the first protruding edge **314**, such that the first waterproof cap **313** is limited on the plug handle **312**, thereby preventing the first waterproof cap **313** from falling off from the plug handle **312**.

(27) In some embodiments, a junction of the plug **311** and the cable **200** is encapsulated in the plug handle **312** in an injection-molded manner, which is beneficial to the waterproofness of the connector **300**.

(28) The second interface **320** includes a socket handle **322**, a first end **3221** of the socket handle **322** is provided with a socket **321** recessed inwards in an axial direction of the socket handle **322**, and the socket **321** is internally provided with a second electrical connection member; a second end of the socket handle **322** is provided with the cable **200**; and the socket **321** is electrically connected to the cable **200** inside the socket handle **322**. An outer wall of the first end **3221** of the socket handle **322** is provided with an external thread **3211** fitted with the internal thread **3131** of the first waterproof cap **313**.

(29) In some embodiments, a junction of the socket **321** and the cable **200** is encapsulated in the socket handle **322** in an injection-molded manner, which is beneficial to the waterproofness of the connector **300**.

(30) When the first interface **310** and the second interface **320** are combined and connected, the plug **311** can be inserted into the socket **321**, and the first interface **310** is in circuit connection with the second interface **320** by means of mutual fitting of the first electrical connection member and the second electrical connection member. By means of threaded connection between the first waterproof cap **313** and the socket handle **322**, an end face of the first end **3121** of the plug handle **312** can be closely fitted with an end face of the first end **3221** of the socket handle **322**, thereby achieving the waterproofness of the connection members.

(31) As shown in FIG. 5 and FIG. 6, in some embodiments, the outer side of the plug handle **312** is sleeved with an annular first waterproof gasket **315**, and the first waterproof gasket **315** is provided between the first waterproof cap **313** and the first protruding edge **314**. After the first waterproof cap **313** is in threaded connection with the socket handle **322**, the waterproofness between the first waterproof cap **313** and the first protruding edge **314** is improved by means of the first waterproof gasket **315**.

(32) In some embodiments, in order to improve the waterproofness of the connector **300**, a second waterproof gasket **316** is provided between the end face of the first end **3121** of the plug handle **312** and the end face of the first end **3221** of the socket handle **322**. After the first waterproof cap **313** is in threaded connection with the socket handle **322**, the waterproofness between the end face of the first end **3121** of the plug handle **312** and the end face of the first end **3221** of the socket handle **322** is improved by means of the second waterproof gasket **316**.

(33) As shown in FIG. 7 and FIG. 8, although the threaded connection has certain waterproofness, in order to further improve the waterproofness of a threaded end of the socket handle **322**, in some embodiments, the socket handle **322** is provided with an annular second protruding edge **323** extending outwards in a radial direction thereof. After the first waterproof cap **313** is in threaded connection and fastened with the socket handle **322**, an end of the first waterproof cap **313** abuts

against and is closely fitted with the second protruding edge **323**, thereby improving the waterproofness of the threaded end of the socket handle **322**.

(34) In some embodiments, an outer side of the socket handle **322** is sleeved with an annular third waterproof gasket **324**, and the third waterproof gasket **324** is provided between the first waterproof cap **313** and the second protruding edge **323**. After the first waterproof cap **313** is in threaded connection with the socket handle **322**, the waterproofness between the first waterproof cap **313** and the second protruding edge **323** is improved by means of the third waterproof gasket **324**.

(35) As shown in FIG. 8, FIG. 9 and FIG. 10, in some embodiments, a first end of the string light **100** is provided with the first interface **310**, and a second end of the string light **100** is provided with the second interface **320**. The first interface **310** is connected to a power supply end, and the second interface **320** can be selectively connected to the first interface **310** of another string light **100**. If the second interface **320** is a tail end, it needs to be sealed to prevent electric leakage or water inflow. Therefore, the connector **300** in the present application includes a second waterproof cap **330**, and the second interface **320** is sealed by means of the second waterproof cap **330**. Specifically, the second waterproof cap **330** is provided with a blind hole, and an inner wall of the blind hole is provided with an internal thread **3301** fitted and connected to the external thread **3211** of the socket handle **322**. After the second waterproof cap **330** is in threaded connection with the socket handle **322**, a bottom surface of the blind hole of the second waterproof cap **330** abuts against and is closely fitted with the end face of the first end **3221** of the socket handle **322**, thereby achieving the waterproof effect.

(36) In some embodiments, the bottom of the blind hole is provided with a fourth waterproof gasket **331**, which can further improve the waterproofness between the second waterproof cap **330** and the socket handle **322**.

(37) In the above embodiments, the plug **311** is a USB plug **311**, and the socket **321** is a USB socket **321**. The plug **311** is electrically connected to the socket **321** by means of a USB protocol. The plug and the socket have the advantages that the USB interface technology is relatively mature, the application range is relatively large, and the universality is high. The production cost and later maintenance cost of the product can be reduced. However, it is not excluded that the plug **311** and the socket **321** can be of other electric insertion connection structures.

(38) Each of the light modules **400** at least includes a light holder **402** and a bulb **401**, and the respective cable **200** is electrically connected to the light holder **402**.

(39) As shown in FIG. 11, in some embodiments, the light module **400** is further provided with a connection base **403**. The connection base **403** is a part of the light holder **402**, and an electrical connection node of the cable **200** and the light module **400** is provided in the connection base **403**.

(40) As shown in FIG. 12, in some embodiments, the light module **400** is further provided with a connection base **403**. The connection base **403** is separated from the light holder **402** and is electrically connected to the light holder by means of a wire **404**. An electrical connection node of the cable **200** and the light module **400** is provided in the connection base **403**.

(41) In some embodiments, the light module **400** is further provided with a hanging member, for example, as shown in FIG. 11 and FIG. 12, the hanging member is a hanging lug **405** provided on the light holder **402** or the connection base **403**; or as shown in FIG. 13, the hanging member is a hook **406** provided on the light holder **402**.

(42) The power supply end can be flexibly selected for the string light **100**.

(43) As shown in FIG. 14, in some embodiments, the power supply end includes a solar power supply device **500**. The solar power supply device **500** includes a circuit board, and a solar cell panel **501** and the first interface **310** or/and the second interface **320** of the connector **300** which are electrically connected to the circuit board, and further includes a support frame **502**. The first interface **310** or/and the second interface **320** of the connector **300** is/are electrically connected to the circuit board by means of a cable **503**; or as shown in FIG. 15, the first interface **310** or/and the

second interface **320** of the connector **300** can be directly provided on the circuit board. In some embodiments, the solar power supply device **500** is further provided with a cell, and the cell is electrically connected to the circuit board.

(44) As shown in FIG. **16**, in some embodiments, the power supply end includes a mobile power supply apparatus **600**. The mobile power supply apparatus **600** includes a cell and a circuit board electrically connected to the cell. The circuit board is provided with the first interface **310** or/and the second interface **320** of the connector **300**.

(45) As shown in FIG. **17**, in some embodiments, the power supply end includes a mobile power supply apparatus **600**. The mobile power supply apparatus **600** includes a mobile power source, and the mobile power source is provided with a USB power supply interface **601**. Of course, the first interface **310** or/and the second interface **320** of the string light **100** is/are corresponding USB power supply interfaces.

(46) Of course, the power supply end can use a universal power adapter, and the power adapter uses the USB power supply interfaces. The first interface **310** or/and the second interface **320** of the string light **100** is/are the corresponding USB power supply interfaces.

(47) As shown in FIG. **18**, the present application provides a cable extension cord, a first end of the cable extension cord being provided with the first interface **310** of the connector **300**, and a second end of the cable extension cord being provided with the second interface **320** of the connector **300**.

(48) In some embodiments, the second end of the cable extension cord is provided with the second interfaces **320** of a plurality of the connectors **300**. For example, as shown in FIG. **19**, the second end of the cable extension cord is provided with three independent second interfaces **320**.

(49) Of course, in some embodiments, the first end of the cable extension cord can also be provided with the first interfaces **310** of a plurality of the connectors **300**.

(50) The above is merely illustrative of the preferred embodiments of the present disclosure and is not intended to limit the present disclosure, and various modifications and variations may be made on the present disclosure by those skilled in the art. Any modification, equivalent substitution, improvement, etc. made within the spirit and principles of the present disclosure should be included in the scope of protection of the present disclosure.

Claims

1. A waterproof connector which is configured to connect cables, comprising: a first interface which comprises: a plug handle, wherein a first end of the plug handle is provided with a plug extending outwards, a junction of the plug and the cable is encapsulated in the plug handle; a second interface which comprises: a socket handle, wherein a first end of the socket handle is provided with a socket extending inwards, a junction of the socket and the cable is encapsulated in the socket handle; and a first waterproof cap, sleeved on an outer side of the plug handle and an outer side of the socket handle; wherein the plug is capable of being selectively inserted in the socket, such that an end face of the first end of the plug handle is closely fitted with an end face of the first end of the socket handle; the plug is of a USB interface structure; the socket is of a USB interface structure; and the plug is electrically connected to the socket by a USB protocol.
2. The connector according to claim 1, wherein an outer wall of the plug handle is circumferentially provided with a first protruding edge extending outwards, the first protruding edge limits at least one part of the first waterproof cap on a side of the plug handle away from the first end thereof.
3. The connector according to claim 2, wherein the outer side of the plug handle is sleeved with a first waterproof gasket, and the first waterproof gasket is provided between the first waterproof cap and the first protruding edge.
4. The connector according to claim 1, wherein an outer wall of the socket handle is circumferentially provided with a second protruding edge extending outwards, and the second protruding edge is provided on the side of the socket handle away from the first end thereof; and

the plug is capable of being selectively inserted in the socket, such that the first waterproof cap is closely fitted with the second protruding edge.

5. The connector according to claim 4, wherein the outer side of the socket handle is further sleeved with a third waterproof gasket, and the third waterproof gasket is provided between the first waterproof cap and the second protruding edge.

6. A cable extension cord, comprising: a cable; and a waterproof connector which is configured to connect cables and comprises: a first interface which comprises: a plug handle, wherein a first end of the plug handle is provided with a plug extending outwards, a junction of the plug and the cable is encapsulated in the plug handle, a second interface which comprises: a socket handle, wherein a first end of the socket handle is provided with a socket extending inwards, a junction of the socket and the cable is encapsulated in the socket handle; and a first waterproof cap, sleeved on an outer side of the plug handle and an outer side of the socket handle; the plug is capable of being selectively inserted in the socket, such that an end face of the first end of the plug handle is closely fitted with an end face of the first end of the socket handle; a first end of the cable is provided with the first interface of the waterproof connector; and a second end of the cable is provided with the second interface of the waterproof connector; wherein the plug is of a USB interface structure; the socket is of a USB interface structure; and the plug is electrically connected to the socket by a USB protocol.

7. The cable extension cord according to claim 6, wherein the first end of the cable is provided with the first interfaces of a plurality of the waterproof connectors, and/or the second end of the cable is provided with the second interfaces of a plurality of the waterproof connectors.

8. A waterproof string light, comprising: cables; and waterproof connectors which are configured to connect the cables, wherein each of the waterproof connectors comprises: a first interface which comprises: a plug handle, wherein a first end of the plug handle is provided with a plug extending outwards, a junction of the plug and the cable is encapsulated in the plug handle, a second interface which comprises: a socket handle, wherein a first end of the socket handle is provided with a socket extending inwards, a junction of the socket and the cable is encapsulated in the socket handle, a first waterproof cap, sleeved on an outer side of the plug handle and an outer side of the socket handle; wherein the plug is capable of being selectively inserted in the socket, such that an end face of the first end of the plug handle is closely fitted with an end face of the first end of the socket handle; a first end of each of the cables is provided with at least one of the first interface of the waterproof connectors, and a second end of the cable is provided with at least one of the second interface of the waterproof connectors; and the cables are provided with a plurality of light modules; wherein the waterproof string light further comprises a solar power supply device; the solar power supply device comprises a circuit board, and a solar cell panel and the first interface or/and the second interface of the at least one of the waterproof connectors which are electrically connected to the circuit board.

9. The waterproof string light according to claim 8, wherein the first interface or/and the second interface of the at least one of the waterproof connectors is/are electrically connected to the circuit board by a cable.

10. The waterproof string light according to claim 8, wherein the solar power supply device further comprises a support frame.

11. The waterproof string light according to claim 8, wherein the solar power supply device further comprises a cell, and the cell is electrically connected to the circuit board.

12. The waterproof string light according to claim 8, comprising a mobile power supply apparatus, wherein the mobile power supply apparatus comprises a cell and a circuit board electrically connected to the cell; and the circuit board is provided with at least one of the first interface or/and the second interface of the waterproof connectors.

13. The waterproof string light according to claim 8, wherein each of the light modules comprises a light holder and a bulb mounted on the light holder, and the respective cable is electrically

connected to the light holder.

14. The waterproof string light according to claim 13, wherein the light module further comprises a connection base, wherein the connection base is separated from the light holder and is electrically connected to the light holder by a wire.

15. The waterproof string light according to claim 13, wherein the light module further comprises a hanging member.
