

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250262015

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Boudreaux; Chad P.

---

## TORQUE-BASED TRANSITION BETWEEN OPERATING GEARS

---

### Abstract

A surgical tool configured to receive rotary inputs from a robotic surgical system. The surgical tool comprises a distal end effector comprising jaws for clamping tissue therebetween, an intermediate shaft portion coupled to the distal end effector, and a proximal housing coupled to the intermediate shaft portion. The proximal housing comprises an arrangement of rotary drives comprising a first rotary drive. The first rotary drive comprises an input shaft configured to receive a rotary input from the robotic surgical system, a transition nut slidably positioned on the input shaft, and an output gear. The first rotary drive further comprises a high-speed gear configured to selectively drive the output gear, a high-torque gear configured to selectively drive the output gear, and a spring arrangement configured to bias the transition nut along the input shaft from a high-speed operating state to a high-torque operating state upon obtaining a threshold torque.

---

**Inventors:** Boudreaux; Chad P. (Cincinnati, OH)

**Applicant:** Cilag GmbH International (Zug, CH)

**Family ID:** 1000008589291

**Appl. No.:** 19/068651

**Filed:** March 03, 2025

### Related U.S. Application Data

parent US continuation 17137852 20201230 parent-grant-document US 12239404 child US 19068651

---

### Publication Classification

**Int. Cl.:** A61B34/37 (20160101); A61B17/068 (20060101); A61B17/29 (20060101); A61B34/30 (20160101); B25J9/04 (20060101); B25J9/10 (20060101); B25J9/16 (20060101); B25J15/02 (20060101); B25J18/04 (20060101)

## U.S. Cl.:

CPC     **A61B34/37** (20160201); **A61B17/29** (20130101); **A61B17/2909** (20130101); **B25J9/04** (20130101); **B25J9/1035** (20130101); **B25J9/1633** (20130101); **B25J15/0213** (20130101); **B25J18/04** (20130101); A61B17/068 (20130101); A61B2017/2923 (20130101); A61B2017/2943 (20130101); A61B2034/304 (20160201); A61B2034/305 (20160201); A61B2034/306 (20160201)

---

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION [0001] This application is a continuation application claiming priority under 35 U.S.C. § 120 to U.S. patent application Ser. No. 17/137,852, entitled TORQUE-BASED TRANSITION BETWEEN OPERATING GEARS, filed Dec. 30, 2020, now U.S. Patent Application Publication No. 2022/0202514, the entire disclosure of which is hereby incorporated by reference herein.

### BACKGROUND

[0002] The present disclosure relates to robotic surgical systems. Robotic surgical systems can include a central control unit, a surgeon's command console, and a robot having one or more robotic arms. Robotic tools can be releasably mounted to the robotic arm(s). The number and type of robotic tools can depend on the type of surgical procedure. In certain instances, robotic surgical systems can be used in connection with one or more displays and/or one or more handheld surgical instruments during a surgical procedure.

### SUMMARY

[0003] In one aspect, the present disclosure provides a surgical tool configured to receive rotary inputs from a robotic surgical system. The surgical tool comprises a distal end effector comprising jaws for clamping tissue therebetween, an intermediate shaft portion coupled to the distal end effector, and a proximal housing coupled to the intermediate shaft portion. The proximal housing comprises an arrangement of rotary drives comprising a first rotary drive. The first rotary drive comprises an input shaft configured to receive a rotary input from the robotic surgical system, a transition nut slidably positioned on the input shaft, and an output gear. The first rotary drive further comprises a high-speed gear configured to selectively drive the output gear, a high-torque gear configured to selectively drive the output gear, and a spring arrangement configured to bias the transition nut along the input shaft from a high-speed operating state, in which the transition nut is in driving engagement with the high-speed gear, to a high-torque operating state, in which the transition nut is in driving engagement with the high-torque gear upon obtaining a threshold torque.

[0004] In another aspect, the present disclosure provides a surgical tool for a robotic surgical system. The surgical tool comprises a distal end effector comprising jaws for clamping tissue therebetween, an intermediate shaft portion coupled to the distal end effector, and a proximal housing coupled to the intermediate shaft portion. The proximal housing comprises an input shaft configured to receive a rotary input from the robotic surgical system, a transition nut slidably positioned on the input shaft, and an output gear. The proximal housing further comprises a first rotary drive configured to selectively drive the output gear, a second rotary drive configured to selectively drive the output gear, and a spring arrangement configured to bias the transition nut along the input shaft to couple the input shaft with either the first rotary drive or the second rotary drive based on a threshold torque applied to the transition nut.

[0005] In another aspect, the present disclosure provides a rotary drive system for rotating a drive screw in a robotic surgical tool. The rotary drive system comprises an input shaft configured to receive a rotary input from a robotic surgical system, a transition nut slidably positioned on the

input shaft, and an output gear drivingly coupled to an output shaft. The rotary drive system further comprises a first rotary drive configured to selectively drive the output gear, a second rotary drive configured to selectively drive the output gear, and a spring arrangement configured to bias the transition nut along the input shaft into engagement with either the first rotary drive or the second rotary drive based on a threshold torque applied to the transition nut.

---

## Description

### FIGURES

[0006] The novel features of the various aspects are set forth with particularity in the appended claims. The described aspects, however, both as to organization and methods of operation, may be best understood by reference to the following description, taken in conjunction with the accompanying drawings in which:

[0007] FIG. 1 is a schematic depicting an operating room including a robotic surgical system having multiple robotic arms, in accordance with at least one aspect of the present disclosure.

[0008] FIG. 2 is a perspective view of a robotic arm including a tool drive, and also depicting a robotic tool mounted to the tool drive, in accordance with at least one aspect of the present disclosure.

[0009] FIG. 3 is a perspective view of the tool drive of FIG. 2 and a proximal tool base of the robotic tool of FIG. 2 mounted to the tool drive, in accordance with at least one aspect of the present disclosure.

[0010] FIG. 4 is a perspective view of the tool drive of FIG. 2 without a robotic tool base mounted thereon, in accordance with at least one aspect of the present disclosure.

[0011] FIG. 5 is a plan view of a proximal portion of a robotic tool, in accordance with at least one aspect of the present disclosure.

[0012] FIG. 6 is a perspective view of a surgical stapling tool, in accordance with at least one aspect of the present disclosure.

[0013] FIG. 6A is a perspective, detail view of a portion of the surgical stapling tool of FIG. 6 depicting a proximal tool base and rotary drives housed therein, with certain components removed from the proximal tool base for clarity, in accordance with at least one aspect of the present disclosure.

[0014] FIG. 6B is a perspective, detail view of the portion of the proximal tool base of FIG. 6A and with certain components removed for clarity, in accordance with at least one aspect of the present disclosure.

[0015] FIG. 7 is a perspective view of a rotary drive system for the surgical stapling tool of FIG. 6, wherein the rotary drive system includes a transition nut slidably positioned between a high-torque gear assembly and a high-speed gear assembly, in accordance with at least one aspect of the present disclosure.

[0016] FIG. 8 is a perspective cross-sectional view of the rotary drive system of FIG. 7 with portions of the high-speed gear assembly removed for clarity, in accordance with at least one aspect of the present disclosure.

[0017] FIG. 9 is an elevation view of the rotary drive system of FIG. 7 in a high-speed operating state and with the transition nut shown as transparent to reveal component concealed therein, in accordance with at least one aspect of the present disclosure.

[0018] FIG. 10 is an elevation view of the rotary drive system of FIG. 7 in a transitional state and with portions of a high-torque gear shown as transparent to reveal an internal array of sloping recesses, in accordance with at least one aspect of the present disclosure.

[0019] FIG. 11 is an elevation view of the rotary drive system of FIG. 7 in a high-torque operating state and with portions of the high-torque gear shown as transparent to reveal the internal array of

sloping recesses, in accordance with at least one aspect of the present disclosure.

[0020] FIG. **12** is a schematic of a dual drive arrangement for a robotic surgical tool implementing a crosscheck procedure, in accordance with at least one aspect of the present disclosure.

[0021] FIG. **13** is a graphical representation of angular displacement and torque over time for the crosscheck procedure of FIG. **12**, in accordance with at least one aspect of the present disclosure.

[0022] FIG. **14** is a schematic of a control circuit for use with the drive arrangement of FIG. **12**, in accordance with at least one aspect of the present disclosure.

[0023] FIGS. **15** and **16** are schematics of the dual drive arrangement of FIG. **12** implementing a crosscheck procedure, in accordance with at least one aspect of the present disclosure.

[0024] FIG. **17** is a graphical representation of angular displacement and torque over time for the crosscheck procedure of FIGS. **15** and **16**, in accordance with at least one aspect of the present disclosure.

[0025] FIG. **18** is a graphical representation of angular displacement over time for a crosscheck procedure, in accordance with at least one aspect of the present disclosure.

[0026] FIG. **19** is a graphical representation of torque over time for the crosscheck procedure of FIG. **18**, in accordance with at least one aspect of the present disclosure.

[0027] FIG. **20** is a graphical representation of the torque of FIG. **19** relative to the angular displacement of FIG. **18** for the crosscheck procedure of FIGS. **18** and **19**, in accordance with at least one aspect of the present disclosure.

[0028] FIG. **21** is an elevation view of a robotic surgical tool including a drive housing, a surgical end effector, and an articulation joint between the drive housing and the surgical end effector, in accordance with at least one aspect of the present disclosure.

[0029] FIG. **22** is a schematic of a control circuit for use with two articulation input drives of FIG. **21**, in accordance with at least one aspect of the present disclosure.

[0030] FIG. **23** is a control schematic for a soft bump articulation control process for a robotic surgical tool, in accordance with at least one aspect of the present disclosure.

[0031] FIG. **24** is an elevation view of a portion of a robotic surgical tool including a drive housing, a surgical end effector, and an articulation joint between the drive housing and the surgical end effector, with certain features removed from the robotic surgical tool for clarity and to expose an interior of the drive housing, in accordance with at least one aspect of the present disclosure.

[0032] FIG. **25** is a cross-sectional view of the drive housing of FIG. **24** taken along the plane indicated in FIG. **24**, in accordance with at least one aspect of the present disclosure.

[0033] FIG. **26** is an elevation view of portions of a robotic surgical tool including an internal shaft, an articulation joint, a surgical end effector, and an articulation system including articulation yokes, in accordance with at least one aspect of the present disclosure.

[0034] FIG. **27** is a perspective view of a proximal portion of the articulation system including the articulation yokes and a portion of the internal shaft of the robotic surgical tool of FIG. **26**, in accordance with at least one aspect of the present disclosure.

[0035] FIG. **28** is an exploded, perspective view of rolling element pads for an articulation system of a robotic surgical tool, in accordance with at least one aspect of the present disclosure.

[0036] FIG. **29** is a flowchart describing the method of displaying an overlay feature on a visual display for a surgical imaging system, in accordance with at least one aspect of the present disclosure.

[0037] FIGS. **30A-D** are elevation views of a visual display for a surgical imaging system depicting portions of a robotic surgical tool during a surgical operation, the views depicting a process to convey information to a clinician with an end effector overlay feature in the visual display, in accordance with at least one aspect of the present disclosure.

[0038] FIG. **31** is a schematic view of a robotic surgical system, in accordance with at least one aspect of the present disclosure.

[0039] FIG. **32** is a perspective view of a surgical robot, in accordance with at least one aspect of

the present disclosure.

[0040] FIG. 33 is a perspective view of a tool driver for the robotic surgical system of FIG. 31 and the surgical robot of FIG. 32, in accordance with at least one aspect of the present disclosure.

[0041] FIG. 34 is an elevation view of a surgical tool for use with the tool driver of FIG. 33, in accordance with at least one aspect of the present disclosure.

[0042] FIG. 35 is a plan view of an actuation mechanism for actuating an end effector of the surgical tool of FIG. 34, in accordance with at least one aspect of the present disclosure.

[0043] FIG. 36 is an elevation view of an actuation mechanism for translating the surgical tool of FIG. 34 relative to the tool driver of FIG. 33, in accordance with at least one aspect of the present disclosure.

[0044] FIG. 37 is a cross-sectional elevation view of a portion of a surgical tool including an actuation mechanism for translating the surgical tool relative to a tool driver, in accordance with at least one aspect of the present disclosure.

[0045] FIG. 38 is a flowchart depicting a transection operation for a surgical tool, in accordance with at least one aspect of the present disclosure.

[0046] FIG. 39 is a control circuit diagram for implementing the transection operation, in accordance with at least one aspect of the present disclosure.

[0047] Corresponding reference characters indicate corresponding parts throughout the several views. The exemplifications set out herein illustrate certain embodiments of the invention, in one form, and such exemplifications are not to be construed as limiting the scope of the invention in any manner.

#### DESCRIPTION

[0048] Applicant of the present application also owns the following U.S. patent applications, filed on Dec. 30, 2020, each of which is herein incorporated by reference in its entirety: [0049] U.S. patent application Ser. No. 17/137,829, titled SURGICAL TOOL WITH TOOL-BASED TRANSLATION AND LOCK FOR THE SAME, now U.S. Pat. No. 12,059,170; [0050] U.S. patent application Ser. No. 17/137,846, titled ROBOTIC SURGICAL TOOLS HAVING DUAL ARTICULATION DRIVES, now U.S. Pat. No. 12,070,287; and [0051] U.S. patent application Ser. No. 17/137,857, titled DUAL DRIVING PINION CROSSCHECK, now U.S. Pat. No. 11,813,746. [0052] Applicant of the present application also owns U.S. patent application Ser. No. 16/553,725, titled ARTICULATING INCLUDING ANTAGONISTIC CONTROLS FOR ARTICULATION AND CALIBRATION, filed Aug. 28, 2019, which is incorporated by reference herein in its entirety.

[0053] Applicant of the present application also owns U.S. Provisional Patent Application No. 62/611,339, titled ROBOT ASSISTED SURGICAL PLATFORM, filed Dec. 28, 2017, which is incorporated by reference herein in its entirety.

[0054] Applicant of the present application also owns the following U.S. patent applications, filed on Mar. 29, 2018, each of which is herein incorporated by reference in its entirety: [0055] U.S. patent application Ser. No. 15/940,627, titled DRIVE ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS; [0056] U.S. patent application Ser. No. 15/940,676, titled AUTOMATIC TOOL ADJUSTMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS; and [0057] U.S. patent application Ser. No. 15/940,711, titled SENSING ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS.

[0058] Before explaining various aspects of a robotic surgical platform in detail, it should be noted that the illustrative examples are not limited in application or use to the details of construction and arrangement of parts illustrated in the accompanying drawings and description. The illustrative examples may be implemented or incorporated in other aspects, variations, and modifications, and may be practiced or carried out in various ways. Further, unless otherwise indicated, the terms and expressions employed herein have been chosen for the purpose of describing the illustrative examples for the convenience of the reader and are not for the purpose of limitation thereof. Also, it

will be appreciated that one or more of the following-described aspects, expressions of aspects, and/or examples, can be combined with any one or more of the other following-described aspects, expressions of aspects, and/or examples.

[0059] Minimally-invasive surgery (MIS), such as laparoscopic surgery, typically involves techniques intended to reduce tissue damage during a surgical procedure. For example, laparoscopic procedures can involve creating a number of small incisions in the patient (e.g., in the abdomen) and introducing one or more surgical tools (e.g., end effectors and an endoscope) through the incisions into the patient. Surgical procedures may then be performed using the introduced surgical tools and with visualization aid provided by the endoscope, for example. Exemplary surgical visualization systems are further described in the following references, which are incorporated by reference herein in their respective entireties: [0060] U.S. Patent Application Publication No. 2020/0015923 A1, titled SURGICAL VISUALIZATION PLATFORM, which published on Jan. 16, 2020; [0061] U.S. Patent Application Publication No. 2020/0015904 A1, titled SURGICAL VISUALIZATION CONTROLS, which published on Jan. 16, 2020; [0062] U.S. Patent Application Publication No. 2020/0015900 A1, titled CONTROLLING AN EMITTER ASSEMBLY PULSE SEQUENCE, which published on Jan. 16, 2020; [0063] U.S. Patent Application Publication No. 2020/0015668 A1, titled SINGULAR EMR SOURCE EMITTER ASSEMBLY, which published on Jan. 16, 2020; [0064] U.S. Patent Application Publication No. 2020/0015925 A1, titled COMBINATION EMITTER AND CAMERA ASSEMBLY, which published on Jan. 16, 2020; [0065] U.S. Patent Application Publication No. 2020/0015899 A1, titled SURGICAL VISUALIZATION WITH PROXIMITY TRACKING FEATURES, which published on Jan. 16, 2020; [0066] U.S. Patent Application Publication No. 2020/0015903 A1, titled SURGICAL VISUALIZATION OF MULTIPLE TARGETS, which published on Jan. 16, 2020; [0067] U.S. Pat. No. 10,792,034, titled VISUALIZATION OF SURGICAL DEVICES, which was issued on Oct. 6, 2020; [0068] U.S. Patent Application Publication No. 2020/0015897 A1, titled OPERATIVE COMMUNICATION OF LIGHT, which published on Jan. 16, 2020; [0069] U.S. Patent Application Publication No. 2020/0015924 A1, titled ROBOTIC LIGHT PROJECTION TOOLS, which published on Jan. 16, 2020; [0070] U.S. Patent Application Publication No. 2020/0015898 A1, titled SURGICAL VISUALIZATION FEEDBACK SYSTEM, which published on Jan. 16, 2020; [0071] U.S. Patent Application Publication No. 2020/0015906 A1, titled SURGICAL VISUALIZATION AND MONITORING, which published on Jan. 16, 2020; [0072] U.S. Patent Application Publication No. 2020/0015907 A1, titled INTEGRATION OF IMAGING DATA, which published on Jan. 16, 2020; [0073] U.S. Patent Application Publication No. 2020/0015806 A1, titled ROBOTICALLY-ASSISTED SURGICAL SUTURING SYSTEMS, which published on Jan. 16, 2020; [0074] U.S. Patent Application Publication No. 2020/0015901 A1, titled SAFETY LOGIC FOR SURGICAL SUTURING SYSTEMS, which published on Jan. 16, 2020; [0075] U.S. Patent Application Publication No. 2020/0015914 A1, titled ROBOTIC SYSTEMS WITH SEPARATE PHOTOACOUSTIC RECEIVERS, which published on Jan. 16, 2020; and [0076] U.S. Patent Application Publication No. 2020/0015902 A1, titled FORCE SENSOR THROUGH STRUCTURED LIGHT DEFLECTION, which published on Jan. 16, 2020. [0077] MIS may provide certain benefits, such as reduced patient scarring, less patient pain, shorter patient recovery periods, and/or lower medical treatment costs associated with patient recovery. Recent technological developments allow robotic systems to perform more MIS procedures. The robotic systems typically include one or more robotic arms for manipulating surgical tools based on commands from a remote operator (e.g. surgeon/clinician). A robotic arm may, for example, support at its distal end various surgical devices such as surgical end effectors, imaging devices, and cannulas for providing access to the patient's body cavity and organs. [0078] Existing robotically-assisted surgical systems typically consist of a surgeon console and a patient-side cart with one or more interactive robotic arms controlled from the console. For example, one robotic arm can support a camera and the other robotic arm(s) can support robotic

tools such as scalpels, scissors, graspers, and staplers, for example. Various exemplary robotic tools are further described herein.

[0079] A robotic surgical system disclosed herein can be a software-controlled, electro-mechanical system designed for surgeons to perform MIS procedures. The robotic surgical system can be used with an endoscope, compatible endoscopic instruments, and accessories. The system may be used by trained physicians in an operating room environment to assist in the accurate control of compatible endoscopic instruments during robotically-assisted urologic, gynecologic, gastrological, and other laparoscopic surgical procedures. The compatible endoscopic instruments and accessories for use with the surgical system are intended for endoscopic manipulation of tissue including stapling, grasping, cutting, blunt and sharp dissection, approximation, ligation, electrocautery, and suturing, for example.

[0080] An example operating room environment is shown in FIG. 1. A robotic surgical system **100** is shown in the operating room, and the robotic surgical system **100** includes a user console **110**, a control tower **130**, and a surgical robot **120** having one or more robotic surgical arms **122** mounted on a surgical platform **124** (e.g., a table or a bed). Clinicians can mount surgical tools with end effectors to the distal ends of the robotic arms **122** for executing a surgical procedure. The robotic arms **122** are table-mounted, but in other configurations, the robotic arms can be mounted to a cart, a floor, a ceiling, a sidewall, or other suitable support surfaces. In various instances, the robotic arms can be supported by a free-standing robot having a base and/or upright column, as further described in U.S. patent application Ser. No. 16/553,725, titled ARTICULATING INCLUDING ANTAGONISTIC CONTROLS FOR ARTICULATION AND CALIBRATION, filed Aug. 28, 2019. U.S. patent application Ser. No. 16/553,725, titled ARTICULATING INCLUDING ANTAGONISTIC CONTROLS FOR ARTICULATION AND CALIBRATION, filed Aug. 28, 2019 is incorporated by reference herein in its entirety.

[0081] Generally, a user, such as a surgeon or other operator, is positioned at the user console **110** to remotely manipulate the robotic arms **122** and/or surgical instruments via teleoperation. The user console **110** can be located in the same operating room as the robotic system **100**, as shown in FIG. 1. In other environments, the user console **110** can be located in an adjacent or nearby room, or tele-operated from a remote location in a different building, city, or country. The user console **110** can comprise a seat **112**, pedals **114**, one or more handheld user interface devices (UIDs) **116**, and a display **118** configured to display, for example, a view of the surgical site inside a patient. As shown in the exemplary user console **110**, a surgeon sitting in the seat **112** and viewing the open display **118** can manipulate the pedals **114** and/or handheld user interface devices **116** to remotely control the robotic arms **122** and/or surgical instruments mounted to the distal ends of the arms **122**. Exemplary robotic input devices are further described in the following references, which are incorporated by reference herein in their respective entireties: [0082] U.S. Patent Application Publication No. 2020/0289219 A1, titled INPUT CONTROLS FOR ROBOTIC SURGERY, which published on Sep. 17, 2020; [0083] U.S. Patent Application Publication No. 2020/0289228 A1, titled DUAL MODE CONTROLS FOR ROBOTIC SURGERY, which published on Sep. 17, 2020; [0084] U.S. Patent Application Publication No. 2020/0289216 A1, titled MOTION CAPTURE CONTROLS FOR ROBOTIC SURGERY, which published on Sep. 17, 2020; [0085] U.S. Patent Application Publication No. 2020/0289229 A1, titled ROBOTIC SURGICAL CONTROLS HAVING FEEDBACK CAPABILITIES, which published on Sep. 17, 2020; [0086] U.S. Patent Application Publication No. 2020/0289230 A1, titled ROBOTIC SURGICAL CONTROLS WITH FORCE FEEDBACK, which published on Sep. 17, 2020; [0087] U.S. Patent Application Publication No. 2020/0289217 A1, titled JAW COORDINATION OF ROBOTIC SURGICAL CONTROLS, which published on Sep. 17, 2020; [0088] U.S. Patent Application Publication No. 2020/0289220 A1, titled ROBOTIC SURGICAL SYSTEMS WITH MECHANISMS FOR SCALING SURGICAL TOOL MOTION ACCORDING TO TISSUE PROXIMITY, which published on Sep. 17, 2020; [0089] U.S. Patent Application Publication No. 2020/0289205 A1,

titled ROBOTIC SURGICAL SYSTEMS WITH MECHANISMS FOR SCALING CAMERA MAGNIFICATION ACCORDING TO PROXIMITY OF SURGICAL TOOL TO TISSUE, which published on Sep. 17, 2020; [0090] U.S. Patent Application Publication No. 2020/0289221 A1, titled ROBOTIC SURGICAL SYSTEMS WITH SELECTIVELY LOCKABLE END EFFECTORS, which published on Sep. 17, 2020; [0091] U.S. Patent Application Publication No. 2020/0289222 A1, titled SELECTABLE VARIABLE RESPONSE OF SHAFT MOTION OF SURGICAL ROBOTIC SYSTEMS, which published on Sep. 17, 2020; and [0092] U.S. Patent Application Publication No. 2020/0289223 A1, titled SEGMENTED CONTROL INPUTS FOR SURGICAL ROBOTIC SYSTEMS, which published on Sep. 17, 2020.

[0093] In some variations, a user can also operate the robotic surgical system **100** in an “over the bed” (OTB) mode, in which the user is at the patient's side and simultaneously manipulating a robotically-driven tool/end effector attached thereto (e.g., with a handheld user interface device **116** held in one hand) and a manual laparoscopic tool. For example, the user's left hand may be manipulating a handheld user interface device **116** to control a robotic surgical component, while the user's right hand may be manipulating a manual laparoscopic tool. In these variations, the user may perform both robotic-assisted MIS and manual laparoscopic surgery on a patient.

[0094] In some aspects, the communication between the surgical robot **120** and the user console **110** can be through the control tower **130**, which can translate user input from the user console **110** to robotic control commands and transmit the control commands to the surgical robot **120**. The control tower **130** can also transmit status and feedback from the robot **120** back to the user console **110**. The connections between the surgical robot **120**, the user console **110**, and the control tower **130** can be via wired and/or wireless connections, and can be proprietary and/or performed using any of a variety of data communication protocols. Any wired connections can be built into the floor and/or walls and/or ceiling of the operating room. The robotic surgical system **100** can provide video output to one or more displays, including displays within the operating room, as well as remote displays accessible via the Internet or other networks. The video output or feed can also be encrypted to ensure privacy and all or portions of the video output can be saved to a server or electronic healthcare record system.

[0095] The robotic surgical system **100** can uniquely identify each tool (endoscope and/or surgical tool) as soon as it is attached to an arm **122** thereof, and can display the tool type and arm location on the display **118** at the user console **110** and/or a touchscreen display on the control tower **130**. The corresponding tool functions can be enabled and activated using the master UIDs **116** and foot pedals **114**. The patient-side assistant can attach and detach the tools, as required, throughout the procedure. A surgeon seated at the user console **110** can begin to perform surgery using the tools controlled by two master UIDs **116** and foot pedals **114**. The system translates the surgeon's hand, wrist, and/or finger movements through the master UIDs **116** into precise real-time movements of the surgical tools. Therefore, the system constantly monitors every surgical maneuver of the surgeon and can pause instrument movement if the system is unable to precisely mirror the surgeon's hand motions.

[0096] A robotic arm **200** is shown in FIG. 2. The robotic arm **200** can be incorporated into the surgical robot **120** (FIG. 1). For example, the robotic arm **200** can correspond to one of the robotic arms **122** (FIG. 1) of the surgical robot **120**. The robotic arm **200** includes a tool drive **220** and a cannula **221**. A robotic surgical tool **250** is mounted to the tool drive **220** and is installed in the cannula **221**. The robotic arm **200** includes links (e.g., links **201**, **202**, **203**, **204**, **205**, **206**, **207**, **208A**, **208B**) and actuated joint modules (e.g., joints **211**, **212**, **213**, **214**, **215**, **216**, **217**) for actuating the plurality of links relative to one another. The joint modules can include various types, such as a pitch joint or a roll joint, which may substantially constrain the movement of the adjacent links around certain axes relative to others. The tool drive **220** is attached to the distal end of the robotic arm **200** and includes the sleeve or cannula **221** extending distally therefrom. The cannula **221** is configured to receive and guide the surgical tool **250** into the patient. The robotic tool **250**



also includes an articulation joint or wrist **256** and an end effector **258** (FIG. 2) disposed at the distal end. The joint modules **211**, **212**, **213**, **214**, **215**, **216**, **217** of the robotic arm **200** can be actuated to position and orient the tool drive **220**, which actuates the robotic wrist **256** and the end effector **258** for robotic surgery.

[0097] FIG. 3 depict the tool drive **220** with the surgical tool **250** mounted thereto and FIG. 4 depicts the tool drive **22** without a surgical tool mounted thereto. The tool drive **220** includes an elongated base (or “stage”) **222** having longitudinal tracks **223** and a tool carriage **224**, which is slidably engaged with the longitudinal tracks **223**. The stage **222** may be configured to couple to the distal end of a robotic arm **200** such that articulation of the robotic arm **200** positions and/or orients the tool drive **220** in space. Additionally, the tool carriage **224** is configured to receive a tool base **252** of the robotic tool **250**. The robotic tool **250** also includes a tool shaft **254** extending from the tool base **252** and through the cannula **221**.

[0098] Generally, the tool carriage **224** provides various degrees of freedom for the robotic tool **250** coupled to the tool carriage **224**. For example, longitudinal movement of the tool carriage **224** along the longitudinal tracks **223** provides a translational degree of freedom for the surgical tool **250** along a tool axis. Alternative translational degrees of freedom, e.g. along an insertion axis, are further described herein.

[0099] Additionally, the tool carriage **224** provides a rotational degree of freedom for rotation of the surgical tool **250** around a tool axis, as well as various degrees of freedom for actuation or articulation of an end effector of the surgical tool (e.g., grasping or cutting). For example, the tool carriage **224** includes one or more motor drives (e.g., linear axis drive or rotary axis drive) whose outputs may be coupled to the input driving mechanisms of a surgical tool. A first motor drive may actuate a first degree of freedom, a second motor drive may actuate a second degree of freedom, and so on for all the additional motor drives in the tool carriage. For example, at least one motor drive may actuate rotation of the tool shaft in a first direction (e.g., clockwise) and another motor drive may actuate rotation of the tool shaft in a second direction opposite the first (e.g., counter-clockwise) in antagonistic fashion. Alternatively, at least one motor drive may actuate rotation of the tool shaft in two directions (e.g., both clockwise and counter-clockwise). Such actuation of the tool may involve, for example, a cable-driven mechanism or set of mechanisms in the tool that are coupled to the output of the motor drives in the tool carriage. Exemplary variations of the tool carriage are further described below.

[0100] The tool carriage **224** is configured to actuate a set of articulated movements of the robotic wrist **256** and the end effector **258** through a system of gears, shafts, cables, and/or wires that are manipulated and controlled by actuated drives. Referring to FIG. 4, the tool carriage **224** includes six motors and six corresponding rotary drivers **260**, **262**, **264**, **266**, **268**, and **270**, which are rotary inputs to a robotic tool. The rotary drivers **260**, **262**, **264**, **266**, **268**, and **270** are arranged in two rows and extending longitudinally along the base. The rotary drivers **260**, **262**, **264**, **266**, **268**, and **270** in FIG. 4 are slightly staggered to reduce the overall width of the tool carriage **224** such that the tool carriage **224** is more compact. Rotary drives **260**, **264**, and **268** are arranged in a first row and rotary drivers **262**, **266**, and **270** are arranged in a second row that is slightly longitudinally offset from the first row. Tool carriages having six rotary drives are further described in U.S. Patent Application Publication No. 2020/0138534, titled ROBOTIC SURGICAL SYSTEM, which published on May 7, 2020 and U.S. patent application Ser. No. 16/553,725, titled ARTICULATING INCLUDING ANTAGONISTIC CONTROLS FOR ARTICULATION AND CALIBRATION, filed Aug. 28, 2019, for example. U.S. Patent Application Publication No. 2020/0138534, titled ROBOTIC SURGICAL SYSTEM, which published on May 7, 2020 and U.S. patent application Ser. No. 16/553,725, titled ARTICULATING INCLUDING ANTAGONISTIC CONTROLS FOR ARTICULATION AND CALIBRATION, filed Aug. 28, 2019, are incorporated by reference herein in their respective entireties.

[0101] In other instances, the tool carriage **224** may include a different configuration of actuated

drives. For example, U.S. Patent Application Publication No. 2019/0201111, titled DRIVE ARRANGEMENTS FOR ROBOTIC-ASSISTED SURGICAL PLATFORMS, which published on Jul. 4, 2019, describes tool carriages having various drive arrangements. U.S. Pat. No. 9,072,535, titled SURGICAL STAPLING INSTRUMENTS WITH ROTATABLE STAPLE DEPLOYMENT ARRANGEMENTS, which issued Jul. 7, 2015, also describes tool carriages having various drive arrangements. U.S. Pat. No. 9,072,535, titled SURGICAL STAPLING INSTRUMENTS WITH ROTATABLE STAPLE DEPLOYMENT ARRANGEMENTS, which issued Jul. 7, 2015, and U.S. Patent Application Publication No. 2019/0201111, titled DRIVE ARRANGEMENTS FOR ROBOTIC-ASSISTED SURGICAL PLATFORMS, which published on Jul. 4, 2019, are incorporated by reference herein in their respective entireties. Alternative drive arrangements are further described herein.

[0102] Referring now to FIG. 5, a proximal portion of a robotic tool **350** is shown. The robotic tool **350** can be similar to the robotic tool **250** (FIGS. 2 and 3) in many aspects and can be adapted for use with the tool drive **220** (FIGS. 2-4) and the surgical robot **120** (FIG. 1), for example. The proximal portion of the robotic tool **350** includes a tool base **352**; an elongate shaft **354** extends distally from the base **352** toward an end effector. The base **352** includes six rotary drives **360**, **362**, **364**, **366**, **368**, and **370** that are configured to mate with six rotary motor-driven inputs on a tool carriage, such as the rotary drivers **260**, **262**, **264**, **266**, **268**, and **270** on the tool carriage **224** (FIG. 4), for example. In various instances, each rotary drive **360**, **362**, **364**, **366**, **368**, and **370** can be associated with a degree of freedom of the robotic tool **350**. In other instances, one or more rotary drives can correspond to multiple degrees of freedom via a transmission. Exemplary drive arrangements for robotic tools are further described in U.S. Patent Application Publication No. 2019/0201111, titled DRIVE ARRANGEMENTS FOR ROBOTIC-ASSISTED SURGICAL PLATFORMS, which published on Jul. 4, 2019 and is incorporated by reference herein in its entirety.

[0103] Each rotary drive **360**, **362**, **364**, **366**, **368**, and **370** includes a rotatable disc or puck configured to align and mate with the corresponding rotary driver **260**, **262**, **264**, **266**, **268**, and **270** (FIG. 4). For example, the rotary drivers **260**, **262**, **264**, **266**, **268**, and **270** and rotary drives **360**, **362**, **364**, **366**, **368**, and **370** include one or more matable surface features **240** (FIG. 4) and **340** (FIG. 5), respectively, configured to facilitate mating engagement between the opposing surface features **240**, **340** such that movement (i.e. rotation) of a given rotary driver **260**, **262**, **264**, **266**, **268**, and **270** correspondingly moves (i.e. rotates) the associated rotary drive **360**, **362**, **364**, **366**, **368**, and **370**.

[0104] The tool carriage **224** can include torque sensors and rotary encoders, which may be incorporated into the motors of some or all of the rotary drivers **260**, **262**, **264**, **266**, **268**, and **270**. The torque sensors may be configured to measure the real-time torque loading on the motors, which corresponds to the torque loading assumed by the rotary drivers **260**, **262**, **264**, **266**, **268**, and **270** and/or rotary drives **360**, **362**, **364**, **366**, **368**, and **370** in the robotic tool **350** coupled thereto. The rotary encoders may measure the rotational motion or output of the motors, which corresponds to the rotational motion of the rotary drivers **260**, **262**, **264**, **266**, **268**, and **270** and/or rotary drives **360**, **362**, **364**, **366**, **368**, and **370**. Monitoring torque loading and rotational motion of the motors may help determine if the surgical tool **350** is operating in accordance with the commands provided by the control tower **130**. Additionally or alternatively, torque sensors and/or rotary encoders can be operatively coupled to one or more of the rotary drives **360**, **362**, **364**, **366**, **368**, and **370** in the robotic tool **350**.

[0105] Referring again to FIG. 5, the rotary drives **360**, **362**, **364**, **366**, **368**, and **370** in the tool base **352** can implement the various degrees of freedom of the robotic tool **350**. For example, the rotary drive **360** can correspond to a pitching motion of the robotic tool **350**, the rotary drive **362** can correspond to a rolling motion of the robotic tool **350**, the rotary drive **364** can correspond to a first yawing motion of the robotic tool **350**, the rotary drive **366** can correspond to a second yawing

motion of the robotic tool **350** in an opposite direction to the first yawing motion, for example, the rotary drive **368** can correspond to a clamping motion (e.g. closing of the jaws) of the robotic tool **350**, and the rotary drive **370** can correspond to a firing motion (e.g. cutting and stapling of tissue) of the robotic tool **350**. In such instances, a single rotary drive coupled to a single rotary input in the tool carriage is configured to close the jaws.

[0106] A transmission can allow a greater amount of degrees of freedom than an arrangement in which each motor and corresponding rotary input is dedicated to a single degree of freedom. In certain instances, to achieve a higher torque state—such as when firing a firing member through thick and/or tough tissue, which requires a high torque input—more than one rotary input on the tool carriage can be drivingly coupled to a degree of freedom. Such a drive arrangement is described in U.S. Patent Application Publication No. 2019/0201111, titled DRIVE ARRANGEMENTS FOR ROBOTIC-ASSISTED SURGICAL PLATFORMS, which published on Jul. 4, 2019, and which is incorporated by reference herein in its entirety. In other instances, as further described herein, a single rotary drive in the base **352** can selectively toggle between a high-speed mode and a high-torque mode via a torque transition member.

[0107] The robotic tool **350** can be a stapling tool that is configured to clamp, cut, and staple tissue. Referring now to FIG. 6, a surgical stapling tool **450** is shown. The surgical tool **450** is similar to the surgical tool **350** in many aspects and, therefore, may be used in conjunction with a robotic surgical system, such as the robotic surgical system **100** (FIG. 1) and with the robotic arm **200** (FIG. 2) and the tool drive **220** (FIGS. 2 and 3). The surgical stapling tool **450** includes a tool base, or proximal housing, **452** which is similar in many aspects to the tool base **352** (FIG. 5) and includes six rotary drives **460**, **462**, **464**, **466**, **468**, and **470** (FIGS. 6A and 6B) similar to the rotary drives **360**, **362**, **364**, **366**, **368**, and **370** (FIG. 5), for example. An elongate shaft **454** extends distally from the tool base **452**. A distal end effector **456** is coupled to a distal end of the elongate shaft **454** at an articulation joint, or wrist joint, **458**. The distal end effector **456** includes a first jaw **480** and a second jaw **482**. The first jaw **480** and the second jaw **482** are configured to clamp tissue therebetween. For example, the first jaw **480** is a movable anvil, and the second jaw **482** is configured to support a fastener cartridge therein.

[0108] In other instances, the distal end effector **456** can include a fixed anvil and movable fastener cartridge. In still other instances, both jaws **480**, **482** can be pivotable or otherwise movable between an open configuration and a clamped configuration to clamp tissue.

[0109] In other instances, the opposing jaws **480**, **482** may form part of other types of end effectors with jaws such as, but not limited to, a tissue grasper, surgical scissors, an advanced energy vessel sealer, a clip applier, a needle driver, a babcock including a pair of opposed grasping jaws, bipolar jaws (e.g., bipolar Maryland grasper, forceps, a fenestrated **20** grasper, etc.) One or both of the jaws **480**, **482** may be configured to pivot to actuate the end effector **456** between the open and closed positions.

[0110] The articulation joint **458** enables the end effector **456** to articulate or pivot relative to the shaft **454** and thereby position the end effector **456** at desired orientations and locations relative to a surgical site. In general, the articulation joint **458** includes a joint configured to allow pivoting movement of the end effector **456** relative to the shaft **454**. The degrees of freedom of the wrist **458** can be represented by three translational variables (i.e., surge, heave, and sway), and by three rotational variables (i.e., Euler angles or roll, pitch, and yaw). The translational and rotational variables describe the position and orientation of a component of a surgical system (e.g., the end effector **456**) with respect to a given reference Cartesian frame. “Surge” can refer to forward and backward translational movement, “heave” can refer to translational movement up and down, and “sway” can refer to translational movement left and right. With regard to the rotational terms, “roll” can refer to tilting side to side, “pitch” can refer to tilting forward and backward, and “yaw” can refer to turning left and right.

[0111] The pivoting motion can include pitch movement about a first axis of the articulation joint

458 (e.g., X-axis), yaw movement about a second axis of the articulation joint 458 (e.g., Y-axis), and combinations thereof to allow for 360° rotational movement of the end effector 456 about the articulation joint 458. In other applications, the pivoting motion at the articulation joint 458 can be limited to movement in a single plane, e.g., only pitch movement about the first axis of the articulation joint 458 or only yaw movement about the second axis of the articulation joint 458, such that the end effector 456 moves only in a single plane.

[0112] The surgical tool 450 includes drive members that form part of an actuation system configured to facilitate articulation of the articulation joint 458 and actuation (operation) of the end effector 456 (e.g., clamping, firing, rotation, articulation, energy delivery, etc.). Some drive members may extend to the articulation joint 458, and selective actuation of these drive members causes the end effector 456 to articulate relative to the shaft 454 at the articulation joint 458. The end effector 456 is depicted in an unarticulated position in FIG. 6, in which a longitudinal axis A2 of the end effector 456 is substantially aligned with a longitudinal axis A1 of the shaft 454, such that the end effector 456 is at a substantially zero angle relative to the shaft 454. In an articulated position, the longitudinal axes A1, A2 would be angularly offset from each other such that the end effector 456 is at a non-zero angle relative to the shaft 454.

[0113] Other drive members may extend to the end effector 456, and selective actuation of those drive members may cause the end effector 456 to actuate, operate, or implement a surgical function. In the illustrated embodiment, actuating the end effector 456 may comprise closing and/or opening the second jaw 480 relative to the first jaw 482 (or vice versa), thereby enabling the end effector 456 to grasp or clamp onto tissue. In addition, once tissue is grasped or clamped between the opposing jaws 480, 482, actuating the end effector 456 may further comprise “firing” the end effector 456, which may refer to causing a cutting element or knife to advance distally within a slot 484 defined in the second jaw 482. As the cutting element moves distally, it may transect any tissue grasped between the opposing jaws 480, 482. Moreover, as the cutting element advances distally, a plurality of staples contained within the staple cartridge, (e.g., housed within the first jaw 482) may be urged or cammed into deforming contact with corresponding anvil surfaces (e.g., staple-forming pockets), provided on the second jaw 480. The deployed staples may form multiple rows of staples that seal opposing sides of tissue that may be transected with the knife or other cutting element.

[0114] In some aspects of the present disclosure, the surgical tool 450 may be configured to apply energy to tissue, such as radio frequency (RF) energy. In such cases, actuating the end effector 456 may further include applying energy to tissue grasped or clamped between two opposing jaws to cauterize or seal the captured tissue, for example.

[0115] In some aspects of the present disclosure, the surgical tool 450 may further include a manual closure device 486 accessible to a user on the exterior of the tool base or drive housing 452. The manual closure device 486 includes a knob that a clinician may grasp and actuate. The manual closure device 486 may be operatively coupled to various gears and/or drive members within the drive housing 452 to allow a clinician to manually open and close the jaws 480, 482. In some cases, a clinician may be able to fully clamp and fully unclamp the jaws 480, 482 with the manual closure device 486. Manual closure devices are further described in U.S. patent application Ser. No. 16/553,725, titled ARTICULATING INCLUDING ANTAGONISTIC CONTROLS FOR ARTICULATION AND CALIBRATION, filed Aug. 28, 2019, for example.

[0116] Referring to FIGS. 6A and 6B, the upper portion of the drive housing 452 is omitted from this view to expose various internal working components and parts. Several components that would otherwise be included within the drive housing 452 are also omitted for clarity. The rotary drives 460, 462, 464, 466, 468, and 470 are housed in the tool base 452 and drivingly coupled to rotary drives on a tool drive (e.g. tool drive 220). The drive arrangements in FIGS. 6A and 6B are configured to transmit rotary motion from the rotary drives 460, 462, 464, 466, 468, and 470 along the shaft 454 and to the articulation joint 458 and/or the end effector 456. These drive arrangements are merely exemplary; alternative drive arrangements for conveying forces and motion from the

rotary drives 460, 462, 464, 466, 468, and 470 toward the end effector 456 are envisioned.

[0117] In various instances, it can be desirable to use a single rotary drive for applications requiring both high speed and high torque. For example, it can be desirable to maximize the speed output from a rotary drive in certain instances and to maximize the torque output from the rotary drive in other instances. A gear train can increase the speed of the rotary drive; however, such a gear train can correspondingly decrease the maximum torque that the rotary drive transmits via the gear train. In certain instances, a first rotary drive can be used for a high-torque degree of freedom (e.g. clamping of tissue) and a second rotary drive can be used for a high-speed degree of freedom (e.g. grasping of tissue). U.S. Patent Application Publication No. 2019/0201111, titled DRIVE ARRANGEMENTS FOR ROBOTIC-ASSISTED SURGICAL PLATFORMS, which published on Jul. 4, 2019, describes drive arrangements in which a first rotary drive corresponds to a “high force” degree of freedom and a second rotary drive corresponds to a “low force” degree of freedom. Relying upon two rotary drives makes both rotary drives unavailable for other simultaneous actuations and/or degrees of freedom. As a result, one fewer rotary drive is available for other degrees of freedom, such as for articulation of the end effector, for example.

[0118] The motors in the tool driver, which drive the rotary drives, can be limited to a maximum number of rotations per second. For example, a motor for the robotic tool can rotate with a maximum speed of four rotations per second, or 240 RPMs. Certain robotic stapling tools utilize a drive screw to close the jaws and/or fire fasteners therefrom. When using such a drive screw, eight to ten rotations of the drive screw may be required to close the jaws. In such instances, it can take two to three seconds to complete these rotations and fully close the jaws. Similarly, it can take two to three seconds to complete these rotations and fully open the jaws. Employing a gear train can increase the output speed and, thus, reduce the time required to open and close the jaws; however, such a gear train would also reduce the maximum torque output, which may be problematic for certain surgical functions, such as clamping, cutting, and/or firing of staples into thick and/or tough tissue. The foregoing maximum motor speed, estimated number of drive screw rotations, and time to open/close the jaws are exemplary. In other instances, motors having different motor speeds and/or different drive screw arrangements can be utilized.

[0119] In certain instances, a rotary drive can switch between a high-torque operating state and a high-speed operating state to selectively transmit higher speeds or higher torques. For example, higher speeds can be utilized during closing or grasping with the end effector jaws and higher torques can be utilized during clamping or firing of the end effector. A torque transition member in the proximal housing of a robotic tool can switch a rotary drive between high-speed gearing on a first side and high-torque gearing on a second side. In various instances, a threshold torque applied to the torque transition member can effect the transition. For example, upon reaching the threshold torque, a spring-activated ramped cam surface of the transition member can shift from the high-speed gearing toward the high-torque gearing to drivingly couple the rotary drive to the high-torque gearing and, thus transmit a high maximum torque to the output gear.

[0120] For example, a surgical tool for use with a robotic surgical system can be configured to receive rotary inputs from the robotic surgical system, and the surgical tool can include a distal end effector comprising jaws for clamping tissue therebetween, an intermediate shaft portion coupled to the distal end effector, and a proximal housing coupled to the intermediate shaft portion, the proximal housing comprising an arrangement of rotary drives comprising a first rotary drive. The first rotary drive can comprise an input shaft configured to receive a rotary input from the robotic surgical system, a transition nut slidably positioned on the input shaft, an output gear, a high-speed gear configured to selectively drive the output gear, a high-torque gear configured to selectively drive the output gear, and a spring arrangement configured to bias the transition nut along the input shaft from a high-speed operating state, in which the transition nut is in driving engagement with the high-speed gear, to a high-torque operating state, in which the transition nut is in driving engagement with the high-torque gear upon obtaining a threshold torque.

[0121] The foregoing arrangement utilizes a single rotary drive to achieve higher speeds during a first operating state and higher torques during a second operating state. As a result, the other rotary drives can be free for articulation or other surgical functions. The robotic tool can also achieve a quick or higher speed closure or grasping without requiring a quick-grasp mechanism in the jaws for speeding of the jaw closure, for example. Additionally, the torque transition feature can implement the transition between the high-speed operating state and the high-torque operating state upon receiving a threshold torque. Complex programming or mechanisms are not required to effect the transition, which can allow the jaws to open and close quickly to manipulate or grasp tissue while also delivering sufficient torque for clamping and/or cutting tissue, for example. Because robotic stapling tools typically require high-speeds to clamp the jaws onto tissue and high-torques to fire the staples and/or cut the tissue, the torque-transition feature in the tool base can seamlessly and automatically toggle between the operating states to meet the requisite torque and speed requirements in both instances.

[0122] Referring to FIGS. 7-11, a rotary drive system **500** is shown. The rotary drive system **500** is positioned in the tool base or proximal housing of a robotic tool, such as the tool base **352** of the robotic tool **350** (FIG. 5) or the tool base **452** of the robotic stapling tool **450** (FIG. 6), for example. The tool base includes a frame **590**, which supports rotary motion of components of the rotary drive system **500**. In such instances, the rotary drive system **500** is one of the rotary drives in the tool base and is selectively coupled to one of the rotary drivers **260**, **262**, **264**, **266**, **268**, and **270** in the carriage **224** of the tool driver **220** (FIG. 4). For example, the rotary drive system **500** can correspond to one of the rotary drives **360**, **362**, **364**, **366**, **368**, and **370** in the base **352** (FIG. 5) and a motor in the carriage **224** is configured to transmit rotary motion to the rotary drive system **500** during use.

[0123] As further described herein, the tool base for a robotic tool can include a different number of rotary drives, for example. Moreover, the rotary drive system **500** can be incorporated into various proximal housings and/or tool bases for different robotic tools having one or more different surgical functions, for example.

[0124] The rotary drive system **500** is configured to drive an output shaft **502**. The output shaft **502** is configured to drive a rotary drive screw in certain instances. Rotation of the rotary drive screw can effect an opening and closing motion of the jaws **480**, **482** (FIG. 6) to grasp and clamp tissue therebetween. Rotary drive screws are further described in U.S. Provisional Patent Application No. 63/057,430, titled SURGICAL INSTRUMENTS WITH TORSION SPINE DRIVE ARRANGEMENTS, filed Jul. 28, 2020.

[0125] Rotary drive shafts are described in U.S. Patent Application Publication No. 2014/0001231, titled FIRING SYSTEM LOCKOUT ARRANGEMENTS FOR SURGICAL INSTRUMENTS, which published Jan. 2, 2014. U.S. Provisional Patent Application No. 63/057,430, titled SURGICAL INSTRUMENTS WITH TORSION SPINE DRIVE ARRANGEMENTS, filed Jul. 28, 2020 and U.S. Patent Application Publication No. 2014/0001231, titled FIRING SYSTEM LOCKOUT ARRANGEMENTS FOR SURGICAL INSTRUMENTS, published Jan. 2, 2014, are incorporated by reference herein in their respective entireties.

[0126] The rotary drive system **500** includes an input shaft **504**, which is configured to receive a rotary input from the robotic surgical system. For example, a motor in the carriage **224** is configured to drive rotation of the input shaft **504** when the robotic tool is mounted to the tool driver **220** (FIG. 3). The rotary drive system **500** includes a transition nut **506** slidably positioned on the input shaft **504**. As further described herein, the transition nut **506** transitions the rotary drive system **500** between a high-speed operating state (FIG. 9) and a high-torque operating state (FIG. 11) based on the torque applied to the transition nut **506**. The rotary drive system **500** also includes a spring arrangement, which is configured to bias the transition nut **506** along the input shaft **504** from the high-speed operating state to the high-torque operating state. In the high-speed operating state, the transition nut **506** is in driving engagement with a high-speed gear train **521**. In

the high-torque operating state, the transition nut **506** is in driving engagement with a high-torque gear **530**.

[0127] Referring primarily to FIGS. **8** and **9**, the spring arrangement includes a biasing spring **528**, which exerts a force on the transition nut **506** and pushes the transition nut **506** toward the high-speed gear train **521**. The biasing spring **528** is a helical compression spring housed in an internal cavity between the frame **590** and the transition nut **506**. For example, the biasing spring **528** is aligned longitudinally with the input axis AI. A first end of the biasing spring **528** abuts the second portion **560** of the transition nut **506**, and a second end of the biasing spring **528** abuts the frame **590**. The biasing spring **528** is positioned to bias the transition nut **506** toward the high-speed operating state. Alternative spring arrangements and geometries are contemplated.

[0128] In the depicted arrangement, the high-speed gear train **521** includes a grasping gear **510**. An array of beveled teeth **512** on the grasping gear **510** extend toward the transition nut **506**, as further described herein.

[0129] The high-speed gear train **521** and the high-torque gear **530** are configured to selectively drive an output gear **501**. The high-speed gear train **521** includes a high-speed gear **520**, along with additional gear(s) (e.g. gear **524**). The gears **520** and **524** form the gear train **521**, which is configured to increase the maximum output speed to the output gear **501** and, thus, the output shaft **502**. The output shaft **502** is aligned longitudinally with the output axis AO. In other instances, the gear train **521** can include a different number and/or arrangement of gears, which can similarly reduce the maximum torque and increase the maximum speed that the gear train **521** can transmit to the output gear **501**. For example, the gear train **521** can define a speed ratio that is greater than one and a torque ratio that is less than one. A first bevel gear **532** couples the gear train **521** and high-speed gear **520** thereof to the output gear **501**. A second bevel gear **534** couples the high-torque gear **530** to the output gear **501**.

[0130] The input shaft **504** drives rotation of the transition nut **506** about an input axis AI. The transition nut **506** transmits its rotation to the output gear **501** by one of the high-speed gear **520** or the high-torque gear **530**. For example, the transition nut **506** includes a first portion **550** and a second portion **560** flexibly or non-rigidly spaced apart from the first portion **550** along the input axis AI by a spring **570**. The spring **570** provides flexibility and bounce as the transition nut slides in/out of engagement with the gear teeth **512**, for example. The first portion **550** includes a first end **552** adjacent to the high-torque gear **530**. The second portion **560** includes a second end **562** adjacent to the gear train **521** and the grasping gear **510** thereof.

[0131] In the first portion **550**, the transition nut **506** includes an array of sloping teeth **554** around its perimeter. The sloping teeth **554** extend to the first end **552**. The sloping teeth **554** are helical ridges or external threads. For example, the sloping teeth **554** are defined by pairs of ramped or angled surfaces, which are angled relative to the axis of rotation of the transition nut **506**, the input axis AI. For example, each sloping tooth **554** includes a bottom ramp, a top ramp substantially parallel to or equidistant from the bottom ramp along its length, and a top surface between the bottom ramp and the top ramp.

[0132] The sloping teeth **554** engage sloping receptacles **536** in the high-torque gear **530** when the transition nut **506** is in the high-torque operating state. The sloping receptacles **536** define a complementary geometry to the sloping teeth **554**, such that each sloping receptacle **536** closely receives one of the sloping teeth **554**. Moreover, the complementary sloping geometry functions as a screw—the sloping teeth **554** being external threads and the sloping receptacles **536** being internal threads—such that a “screwing” rotation of the sloping teeth **554** into the sloping receptacles **536** draws the transition nut **506** along the input axis AI and further into engagement with the high-torque gear **530**. More specifically, upon engagement of the angled features **554**, **536**, the complementary geometry is configured to drive the transition nut **506** farther along the input shaft **504** and input axis AI toward the high-torque gear **530** such that the sloping teeth **554** are fully received in the sloping receptacles **536** and drawn into driving engagement with the high-

torque gear **530**. Moreover, when the rotary direction of the transition nut **506** is reversed, the complementary sloping geometry can again function as a screw such that an “unscrewing” rotation of the sloping teeth **554** relative to the sloping receptacles **536** pulls the transition nut **506** along the input axis AI away from the high-torque gear **530** and toward the high-speed gear **520**.

[0133] In other instances, the high-torque gear **530** can include sloping teeth or external threads, and the first portion **550** of the transition nut **506** can including sloping receptacles or internal threads, for example.

[0134] The transition nut **506** includes an array of teeth **564** around the perimeter of the second portion **560**. The teeth **564** extend to the second end **562**. The teeth **564** define a substantially saw-toothed geometry and the top of each tooth **564** is narrower than the bottom. For example, each sloping tooth **564** includes a first ramped surface, a second ramped surface extending toward the first ramped surface, and a top surface between the first and second ramped surfaces. In such instances, the teeth are truncated triangular prisms, for example. Alternative teeth geometry are contemplated.

[0135] The teeth **564** engage corresponding teeth **512** in the grasping gear **510** when the transition nut **506** is in the high-speed operating state. For example, a ramped surface on each tooth **512** is configured to slide along a complementary ramped surface on a tooth **512** to move the teeth **564**, **512** between an engaged and disengaged position. The biasing spring **528** is configured to bias the teeth **564** into engagement with the teeth **512**. For example, in instances in which the teeth **564** and **512** are not precisely aligned when moving into engagement, the spring **570** can ease the transition between the different operating states. In various instances, the spring **528** may also ease the transition between operating states, such as when the angular direction is reversed by a motor to reverse the rotary direction of the drive screw and retract the firing member, for example, and the torque-based transition nut **506** disengages the high-torque gear **530** and moves into engagement with the high-speed gear **520**, for example.

[0136] The transitioning operation of the rotary drive system **500** is depicted in FIGS. **9-11**. FIG. **9** depicts a high-speed operating state of the rotary drive system **500**. Though this operating state is referred to as a high-speed operating state, the reader will appreciate that the maximum speed depends on a number of factors, such as properties of the motor, for example. The high-speed operating state, however, can be designed and optimized to output a higher maximum speed to the output gear **501** than the high-torque operating state. In other words, the maximum speed can be a “high-speed” relative to the maximum speed in the high-torque operating state.

[0137] FIG. **11** depicts a high-torque operating state of the rotary drive system **500**. The torque output to the output gear **501** during the high-torque operating state also depends on a number of factors including properties of the motor, for example. The high-torque operating state, however, can be designed and optimized to output a higher maximum torque to the output gear **501** than the high-speed operating state. In other words, the maximum torque can be a “high-torque” relative to the maximum torque in the high-speed operating state.

[0138] FIG. **10** depicts a transition between the high-speed operating state and the high-torque operating state.

[0139] Referring again to FIG. **9**, the spring **528** has biased the transition nut **506** into engagement with the high-speed gear train **520**. Specifically, the biasing spring **528** exerts a force upon the transition nut **506** along the input axis AI and in the direction of the high-speed gearing, i.e., toward the grasping gear **510** of the gear train **521**. The array of teeth **564** on the second portion **560** meshingly engage the array of teeth **512** on the grasping gear **510**.

[0140] In this arrangement, rotary motion of the input shaft **504** (provided by a motor in the tool driver, for example) is transmitted to the transition nut **506**, which rotates the grasping gear **510** to effect rotation of the gear train **521**. The gear train **521** is configured to increase the maximum speed such that the maximum speed delivered to the output gear **501** via the first bevel gear **532** is optimized for high-speed applications. For example, the high-speed output can be utilized for the



closing of the jaws to grasp and manipulate tissue. Arrows showing exemplary rotary directions for the transition nut **506**, the grasping gear **510**, the gear train **521** gears, and the output gear **501** are included in FIG. **9**.

[0141] Referring now to FIG. **10**, when the torque applied to the transition nut **506** exceeds a threshold value, the torque at least partially overcomes the spring force of the spring arrangement. The array of teeth **564** on the second portion **560** of the transition nut **506** are configured to ride or slide along the complementary ramped surfaces of the array of teeth **512** on the grasping gear **510** as the transition nut **506** rotates and moves along the input axis AI toward the high-torque gearing, i.e. the high-torque gear **530**. Compression of the biasing spring **528** when the torque reaches the threshold value shifts the transition nut **506** out of engagement with the grasping gear **510**.

Moreover, as the grasping gear **510** releases the transition nut **506** from meshing or driving engagement, the array of sloped teeth **554** on the first portion **550** of the transition nut **506** engage the sloped receptacles **536** in the high-torque gear **530**. Upon engagement, the sloped receptacles **536** can “grip” or “grab” the transition nut **506** to draw the teeth **554** farther into the receptacles **536** into the arrangement shown in FIG. **11**, in which the transition nut **506** is completely disengaged from the grasping gear **510** and fully engaged with the high-torque gearing.

[0142] In the high-torque operating state of FIG. **11**, rotary motion of the input shaft **504** (provided by a motor in the tool driver, for example) is transmitted to the transition nut **506**, which rotates the high-torque gear **530**. The high-torque gear **530** is configured to optimize the torque delivered to the output gear **501** via the second bevel gear **534**. Specifically, the torque is optimized for high-torque applications, such as clamping of tissue by an end effector. Arrows showing exemplary rotary directions for the transition nut **506**, the high-torque gear **530**, and the output gear **501** are included in FIG. **11**.

[0143] At the end of the firing stroke, the drive arrangement is configured to reverse the firing member. For example, the drive arrangement can reverse the angular direction of the transition nut **506** to retract the firing member. The reversal of the transition nut **506** can correspond to an “unscrewing” rotation of the transition nut **506**, such that the transition nut **506** is displaced along the input axis AI away from the high-torque gear **530**. In such an arrangement, a return stroke of the firing member and associated reversal of the transition nut **506** and output gear **501** can automatically transition the drive arrangement to the high-speed operating state.

[0144] Owing to the geometry of the high-torque gear **530** and the second bevel gear **534**, the high-torque operating state can increase the torque supplied to the output gear **501** by eight times the torque of the high-speed operating state. In other instances, the torque output can be doubled, or quadrupled, for example. Variations to the number, size, and arrangement of gears between the high-torque gear **530** and the output gear **501** can further increase the torque output.

[0145] Owing to the geometry of the gear train **521** and the first bevel gear **532**, the high-speed operating state can increase the speed supplied to the output gear **501** by four times the speed in the high-torque operating state. In other instances, the torque output can be doubled or increased by eightfold, for example. For example, additional speed gears in the gear train **521** can further increase the speed output. Variations to the number, size, and arrangement of gears between the high-speed gear **520** and the output gear **501** can further increase the speed output.

[0146] In various instances, robotic tools rely on software incorporated into the operating system and the processor of the robotic surgical system to mitigate risks and avoid failures. Redundant systems and/or crosschecks may control certain robotic tools that perform high-severity tasks to mitigate the risks associated with those tasks. For example, clamping can be a high-severity task because insufficient clamping can result in an increased likelihood and/or greater incidences of staple malformation and, thus, insufficient tissue sealing, in certain instances. For example, robotic stapling tools that clamp and/or cut tissue can rely on redundant systems (e.g. mechanical and electrical lockouts) and various crosschecks to ensure the closure motions, clamping forces, and firing strokes meet predefined standards and/or thresholds. Various crosschecks may increase the

costs and/or the complexity of the system, and may require additional maintenance and user-support over time. In certain instances, crosschecks for surgical tools and/or surgical functions that do not add unnecessary cost and complexity to the system may be beneficial.

[0147] Certain robotic tools utilize multiple motors for certain surgical functions. For example, a robotic stapling tool can utilize dual motors for advancing a closure member, performing the closure stroke, and/or clamping tissue. A crosscheck that relies on a dual-motor closure system to create crosscheck algorithms can mitigate risks and avoid failures related to high-severity clamping errors, for example.

[0148] For example, a robotic surgical system can include a closure system including a first pinion drivingly coupled to a first motor, a second pinion drivingly coupled to a second motor, and a closure gear selectively driven by the first pinion and the second pinion. The robotic surgical system can further include a control circuit configured to implement a motor crosscheck operation in which the control circuit is configured to receive a first parameter indicative of a first torque generated by the first motor, receive a second parameter indicative of a second torque generated by the second motor, compare the first parameter to the second parameter, and transmit a signal to a communication device, wherein the signal is based on the comparison and indicative of a status of the closure system.

[0149] In various instances, the control circuit of such a robotic surgical system can also be configured to determine when the closure system has achieved a steady state in the motor crosscheck operation, and to compare the first parameter to the second parameter after the closure system has achieved the steady state.

[0150] The motor crosscheck operation can proceed after a homing operation and/or after a clamping event.

[0151] Such a robotic surgical system may mitigate certain risks and avoid failures related to high-severity clamping errors. Moreover, such crosschecks can improve the operation of the surgical tool without necessitating redundant motor controls and/or requiring dedicated safety processing units, for example.

[0152] FIG. 12 shows an example drive arrangement **800**. The drive arrangement **800** is used to clamp the jaws of an end effector, such as the jaws **480** and **482** of the end effector **456** (FIG. 6), for example. In other instances, a robotic surgical system can utilize the drive arrangement for additional and alternative surgical functions, such as firing fasteners into tissue and/or severing tissue, for example. The drive arrangement **800** includes a first pinion **802** and a second pinion **804**. A motor and corresponding rotary drive are configured to drive the pinions **802**, **804**. For example, each of the driving pinions **802** and **804** can be driven by one of the motors and one of the corresponding rotary drivers **260**, **262**, **264**, **266**, **268**, and **270** in the tool driver **220** (FIG. 4) in certain aspect of the present disclosure.

[0153] The pinions **802** and **804** drive the closure gear **806**, which effects the closure motion of the end effector. The torques on the pinions **802** and **804** and, in certain instances, the torque applied to the closure gear **806** can be monitored and compared during a crosscheck procedure to determine if the drive arrangement **800** is operating properly or is in a fault state, for example. The robotic surgical system can implement the crosscheck procedure at various times during the lifecycle and/or usage cycles of the robotic tool. For example, each time the robotic tool is mounted to the tool drive on the robotic arm, one or more crosscheck procedures can be implemented. Additionally or alternatively, in certain instances, the robotic surgical system can implement a crosscheck at the completion of a homing operating and/or each closure event (e.g. closure stroke). For example, when a robotic tool is mounted to a tool driver, the robotic system can undergo a homing operation, in which positions of the various components are determined and recorded to ascertain various limits of the system. Homing operations are further described in U.S. patent application Ser. No. 16/553,725, titled ARTICULATING INCLUDING ANTAGONISTIC CONTROLS FOR ARTICULATION AND CALIBRATION, filed Aug. 28, 2019, for example. In certain instances, a

clinician can selectively implement a crosscheck and/or override a suggested crosscheck operation. [0154] In one example, to conduct a crosscheck procedure for the robotic tool, the first driving pinion **802** is rotated in a first direction indicated by the arrow **808** (clockwise in the view in FIG. **12**) and the second driving pinion **804** is rotated in a second direction indicated by the arrow **810** (counter-clockwise in the view of FIG. **12**). The first direction is opposite the second direction. Owing to the arrangement of the driving pinions **802** and **804** relative to the closure gear **806**, when the driving pinions **802**, **804** rotate in opposite or opposing directions, the closure gear **806** may rock, sway, or otherwise move within the backlash defined by the gear teeth. For example, the closure gear **806** may rattle when touched owing to the backlash permitted by the gear teeth.

[0155] A graphical representation **820** of torque and angular displacement over time for the drive arrangement **800** is shown in FIG. **13**. From time **t0** to **t1**, the closure gear **806** can shift or rattle within the backlash defined by the gear teeth. When the driving pinions **802**, **804** run out of backlash, they import torque on each other at time **t1** and continue to exert counter-exerted torques upon each other through a dynamic region **822** during which the absolute torque values fluctuate/vacillate. After the dynamic region **822**, the drive arrangement **800** enters a steady-state region **824** at time **t2** during which the torques measured by the driving pinions **802**, **804** may substantially level out and define fewer fluctuations over time. One or more metrics can be utilized to determine and/or compute when the driving pinions **802** and **804** achieve steady-state status and enter the steady-state region.

[0156] The torque for each driving pinion **802** and **804** can be monitored during the crosscheck procedure. For example, a control circuit can monitor and compare the torques throughout the steady-state region **824**. If the magnitudes of the opposing torques are close to each other—i.e. within some predefined threshold value—the control circuit can conclude that the torque values can be trusted. However, if the magnitudes of the opposing torques are not significantly close to each other—i.e. outside a predefined threshold difference—the robotic surgical system can enter an error or fault state. For example, the robotic surgical system can determine the robotic tool is in a fault state. The robotic surgical system can alert the user to the error/fault state and/or can implement one or more lockouts (absolute and/or discretionary) upon entering the error/fault state. In certain instances, the error/fault state may require a recalibration and/or re-inspection of the robotic tool.

[0157] A control circuit **828** for a dual driving pinion arrangement, such as the drive arrangement **800** (FIG. **12**), for example, is shown in FIG. **14**. The control circuit **828** includes a processor **840** in signal communication with a memory **842** and with a communication device **844**. A first drive system **850** and a second drive system **852** are in signal communication with the processor **840**. The first drive system **850** includes a motor **854**, an input drive **856** coupled to the motor **854**, a torque sensor **830**, and a rotary encoder/position sensor **834**. The input drive **856** can correspond to the first pinion gear **802** (FIG. **12**) in the drive arrangement **800**, for example. The second drive system **852** includes a motor **858**, an input drive **860** coupled to the motor **858**, a torque sensor **832**, and a rotary encoder/position sensor **836**. The input drive **860** can correspond to the second pinion gear **804** (FIG. **12**) in the drive arrangement **800**, for example. In such instances, the torque sensors **830** and **832** determine the torque on the first driving pinion **802** and the second driving pinion **804**, respectively. Moreover, the position sensors **834** and **836** determine the angular position of the first driving pinion **802** and the second driving pinion **804**, respectively.

[0158] The control circuit **828** also includes an output drive **862**, a torque sensor **864** and a rotary encoder/position sensor **866** therefor. The output drive **862** can correspond to the closure gear **806** (FIG. **12**) in the drive arrangement **800**, for example. In such instances, the torque sensor **864** determines the output torque applied to the closure gear **806**, and the position sensor **866** determines the angular position of the closure gear **806**.

[0159] During the crosscheck procedure, the torque sensors **830**, **832** and the position sensors **834**, **836** are configured to transmit signals to the processor **840** indicative of the torque and angular position of the input drives **856**, **860**. The torque sensor **864** and the position sensor **866** can also be

in signal communication with the processor **840** and configured to transmit signals thereto indicative of the torque and the angular position of the output drive **862**. The torques detected by the torque sensors **830**, **832**, and **864** and transmitted to the processor **840** are monitored over time and can be recorded in the memory **842**.

[0160] In various instances, the processor **840** is configured to determine when the dual driving pinion system has achieved steady-state and, in the steady-state operating state, to compare the input torques detected by torque sensors **832** and **834**. If the comparison between the absolute torques determined by the torque sensors **832** and **834** exceeds a threshold value, the control circuit **828** is configured to enter a fault state. Operations for the fault state are stored in the memory **842** and implemented by the processor **840** and include, for example, providing an output signal to the clinician or to another surgical system with a communication device **844** and/or implementing one or more lockouts to protect the integrity of the robotic tool and safety of the patient.

[0161] Another crosscheck operation for a robotic tool is shown in FIGS. **15-17**. In various instances, the crosscheck operation of FIGS. **15-17** can be employed with the drive arrangement **800** and the control circuit **828**. To conduct this crosscheck operation, the first driving pinion **802** is rotated in a first direction indicated by the arrow **908** (counterclockwise in the view in FIG. **15**) and the second driving pinion **804** is also rotated in the first direction indicated by the arrow **910** (counterclockwise in the view of FIG. **15**). Owing to the arrangement of the driving pinions **802** and **804** relative to the closure gear **806**, the rotation of the driving pinions **802**, **804** in the first direction is also configured to rotate the closure gear **806** in the first direction (counterclockwise in the view of FIG. **15**) as well, as indicated by the arrow **912**, for example. In such instances, the driving pinions **802** and **804** work together to rotate the closure gear until the closure gear completes the full closure stroke. The full closure stroke is typically completed when clamping tissue or during a “homing” operation, for example.

[0162] Referring primarily now to FIG. **16**, the torque on the driving pinions **802** and **804** is then relieved upon reaching a bottomed-out state. Thereafter, one driving pinion can be configured to hold its position during a crosscheck operation, while the other pinion drives against it through the output gear **806**. For example, the first pinion gear **802** can seek to rotate in a second direction indicated by the arrow **908'** (clockwise in the view of FIG. **16**), which is opposite to the first direction of the arrow **908** in FIG. **15**, while the second pinion gear **804** resists rotation. In such instances, the first pinion gear **802** moves through the backlash region defined between the meshed gear teeth and, then, the pinion gears **802** and **804** have opposing torques, which can be monitored and compared during the crosscheck operation.

[0163] A graphical representation **920** of torque and angular displacement over time for the drive arrangement **800** and the crosscheck sequence depicted in FIGS. **15** and **16** is shown in FIG. **17**. At time **t1**, the closure stroke is initiated during which the driving pinions **802** and **804** cooperatively drive the closure gear **806** through the closure region **926**. In the closure region **926**, the torque and the angular displacement of the pinions **802**, **804** and the closure gear **806** increases. At time **t2**, the closure stroke is completed and the torque on the closure gear **806** is relieved.

[0164] The driving torques are relieved and at time **t2** the first pinion **802** reverses direction (FIG. **16**) and then moves through the backlash defined by the meshing gear teeth during the region **928**. For the crosscheck operation, a dynamic region **922** is followed by a steady-state region **924**, similar to the dynamic region **822** and the steady-state region **824** (FIG. **13**), respectively, for example. In the crosscheck operation of FIG. **17**, the torque on the first pinion gear **802** continues to a non-zero absolute torque. As the first pinion gear **802** generates a non-zero absolute torque, the second pinion **804** generates an opposing torque at time **t3**, which marks the beginning of the dynamic region **922**. In the dynamic region **922**, the absolute torque values of the first pinion **802** and the second pinion **804**, which are in opposing directions, increase. Upon reaching the steady-state region **924** at time **t4**, the absolute torques on the driving pinions **802** and **804** maintain substantially constant values opposing each other. At time **t5**, the steady-state region **924** ends and

the crosscheck procedure has been completed.

[0165] The opposing torques for each driving pinion **802** and **804** can be monitored during the crosscheck procedure of FIGS. **15-17**. For example, the torques can be monitored and compared during the steady-state region **924**. If the magnitudes of the opposing torques are close to each other—i.e., within some predefined threshold value—the control circuit can conclude that the torque values can be trusted. However, if the magnitudes of the opposing torques are not significantly close to each other, the robotic surgical system can enter an error or fault state. For example, the robotic surgical system can determine the robotic tool is in a fault state. The robotic surgical system can alert the user to the error/fault state and/or can implement one or more lockouts (absolute and/or discretionary). In certain instances, the fault state may require a recalibration and/or re-inspection of the robotic tool.

[0166] Additionally or alternatively, the crosscheck procedure can monitor the angular travel of the pinion gears **802**, **804** from the end of the closure stroke at time  $t_2$  to the beginning of the steady-state region **924** at time  $t_4$ . The angular travel is the difference between the first plateau indicating angular displacement for the first driving pinion **802** and the second plateau indicating angular displacement for the first driving pinion **802**. In other words, the first driving pinion **802** rotates from a first position at the end of the closure stroke **926** to a second position at the beginning of the steady-state region **924**, and the difference in angular position can be compared to the stored backlash value. The backlash value can be measured during manufacturing and stored in the memory of the robotic tool and/or robotic surgical system, for example. If the angular travel of the first driving pinion **802** does not match the stored backlash value, within some threshold, the processor can signal an error or fault state. Conversely, if the angular travel is sufficiently close to the stored backlash value, the processor can transmit a signal indicating the robotic tool has passed the check.

[0167] In various instances, the foregoing sequence can be repeated with the second pinion gear **804** switching rotary direction while the first pinion gear **802** seeks to maintain a constant angular position. The opposing torque values and the angular travel of the second driving pinion **804** during the “homing” operating can be monitored and compared, as further described herein with respect to the first driving pinion **802**, for example.

[0168] Another crosscheck operation for a surgical tool is shown in FIGS. **18-20**. In various instances, the crosscheck operation of FIGS. **18-20** can be employed with the drive arrangement **800** and the control circuit **828**. In FIG. **20**, a stiffness of one of the driving pinions **802**, **804** can be compared to a stored stiffness value to determine if the driving pinion **802**, **804** passes the crosscheck. A stiffness **1006** plotted in a graphical representation in FIG. **20** reflects the angular position and torque measurements in FIGS. **18** and **19**, respectively.

[0169] More specifically, the angular position of the driving pinions **802**, **804** and the closure gear **806** (FIG. **15**) over time is shown in the graphical representation **1000** in FIG. **18**. The torque on the driving pinions **802**, **804** over time is shown in the graphical representation **1002** in FIG. **19**. Initially, as described herein with respect to FIG. **15**, the driving pinions **802** and **804** work together to collectively rotate the closure gear **806** until the closure gear completes the full closure stroke at time  $t_1$ . Thereafter, the closure gear **806** can be bottomed-out such that further rotation of the closure gear **806** is prevented after time  $t_1$ . To conduct the crosscheck operation, one of the driving pinions **802**, **804** can apply further torque to the bottomed-out closure gear **806** while the other driving pinion floats or hovers within the backlash regions of the gear teeth. In the example of FIGS. **18** and **19**, the first pinion gear **802** continues to apply torque to the closure gear **806** at time  $t_2$ , while the second pinion gear **804** is allowed to move or shift through the backlash.

[0170] In such an arrangement, the closure gear **806** cannot rotate any further; however, the stiffness **1006** (FIG. **20**) of the first driving pinion **802** in applying torque to the closure gear **806** can be calculated based on the torque and position measurements after time  $t_2$ , when the first driving pinion **802** continues to apply torque to the closure gear **806**. A plot of the stiffness **1006**

relative to a two-dimensional stiffness threshold **1008** in the graphical representation **1004** conveys the comparison conducted in the crosscheck operation. For example, if the stiffness **1006** falls outside the stiffness threshold **1008**, the system can indicate an error or fault state.

[0171] In various instances, the stiffness threshold **1008** can be defined by a slope of the stiffness for torque over angular displacement plus and minus a value corresponding to a threshold amount, percentage, and/or standard deviation, for example.

[0172] In various instances, the foregoing sequence can be repeated with the second pinion gear **804** continuing to apply torque to the closure gear **806** while the first pinion gear **802** freewheels. The stiffness of the second pinion gear **804** can be compared to a threshold stiffness to determine an error or fault state of the second pinion gear **804**.

[0173] In various instances, one or more of the various crosscheck procedures can be implemented after a homing operation and/or clamping event for a dual motor closure system. The crosscheck procedures can check the integrity of the system and motors thereof without requiring redundant motor controllers or dedicated safety processing units, for example. In such instances, the dual motor closure system can be crosschecked without adding additional cost and/or complexity. The reader will further appreciate that such a crosscheck procedure can be performed with respect to other dual motors systems for a robotic surgical tool in certain instances.

[0174] In certain instances, a robotic surgical tool having an articulation joint may define an articulation range of motion with hard stops or mechanical limits at the ends of the articulation range of motion. For example, an interference at the mechanical limit can prevent further motion beyond the mechanical limit and outside the articulation range of motion. Upon reaching the end of the articulation range of motion, the articulation joint can bump into the mechanical limit. Driving articulation of the robotic surgical tool against the mechanical limit(s) at the end of the articulation range of motion may damage the robotic surgical tool and/or the articulation system thereof over time in certain instances. Damage to the robotic surgical tool can be a function of the impact force, velocity and/or torque of the rotary drive inputs, for example.

[0175] In certain instances, to avoid bumping the mechanical limit, a control circuit can control the articulation system such that the articulation joint is limited to move within a narrower range of motion than the full articulation range of motion. For example, the mechanical limits of the articulation range of motion can be stored in the memory and/or obtained during a homing operation. The articulation system may effectively reduce the operating range of the articulation joint to less than the full articulation range of motion to maintain a safety zone or range of motion away from the mechanical limit(s). The safety zone can be configured to account for measurement error in the articulation joint during the homing operation and/or variations to the joint over time, for example. A safety zone reduces the available range of motion of the articulation joint and, thus, may unduly limit the articulation range of motion of the robotic surgical tool in certain instances.

[0176] Alternatively, it can be advantageous in certain instances to maximize the articulation range of motion and move the articulation joint within the full articulation range of motion and up to the mechanical limits while minimizing damage to the robotic surgical tool or articulation mechanism thereof. Such an articulation drive mechanism can be sufficiently robust to drive the articulation joint through its full range of motion up to the mechanical limit(s). For example, the articulation drive system may be configured to detect regions in the articulation range where the device is close to the mechanical limit and regions that are farther from the mechanical limit. Additionally, the articulation drive mechanism may operate the articulation joint differently in the regions closer to the mechanical limit to avoid damaging the articulation mechanism while still functioning fully and efficiently. For example, when the articulation joint angle is in a range of motion farther from the mechanical limit, the articulation joint may operate at a full speed and/or torque. When the articulation joint angle is in a range of motion closer to the mechanical limit, the articulation joint may operate at a limited speed and/or a limited torque. The limited speed and/or torque can allow the articulation joint to approach the mechanical limit and bump the limit softly or gently to avoid

damaging the articulation mechanism. Stated differently, the articulation joint can softly bump the mechanical limit of the articulation joint and, thus, minimize wear and/or damage to the drive mechanism and/or to the articulation joint from the contact, for example.

[0177] In one aspect the present disclosure, a control circuit for use with a robotic surgical system can be configured to receive a parameter indicative of a rotary position of an articulation motor that is configured to drive an articulation joint of a robotic surgical tool. The articulation motor can be configured to move through a first range of positions and a second range of positions. The first range of positions and the second range of positions can be non-overlapping ranges. The control circuit can also be configured to implement a first operating state, and implement a second operating state when the parameter corresponds to a transition of the articulation motor from the first range of positions to the second range of positions. The second operating state can be different than the first operating state. The control circuit can be further configured to re-implement the first operating state when the parameter corresponds to a return of the articulation motor from the second range of positions into the first range of positions by a threshold anti-dither angle.

[0178] In certain instances, the foregoing articulation drive mechanism can provided a greater range of motion than articulation systems in which the articulation motion is confined to outside the safety zones defined in regions adjacent to the mechanical limits. Such an articulation drive mechanism can reduce incidences of crashing into the mechanical limit at significant speeds and/or torques, which avoids producing high impact loads that may damage the articulation system and/or robotic surgical tool, for example.

[0179] Referring to FIG. 21, a robotic surgical tool **3100** is shown. The robotic surgical tool **3100** can be controlled by the control circuit **3020** (FIG. 22) and can be used in conjunction with a robotic surgical system, such as the robotic surgical system **100** (FIG. 1) and with the robotic arm **200** (FIG. 2) and the tool drive **220** (FIGS. 2 and 3). The robotic surgical tool **3100** includes a tool base, or proximal housing, **3102** that is similar in many aspects to the tool base **352** (FIG. 5) and includes six rotary drives **3160**, **3162**, **3164**, **3166**, **3168**, and **3170** similar to the rotary drives **360**, **362**, **364**, **366**, **368**, and **370** of tool base **352** (FIG. 5), for example. As with the rotary drives of the tool base **352**, the rotary drives of the tool base **3102** are configured to mate with six motor-driven rotary inputs or drivers on a tool carriage, such as the rotary drivers **260**, **262**, **264**, **266**, **268**, and **270** on the tool carriage **224** (FIG. 4), for example. In various instances, each rotary drive **3160**, **3162**, **3164**, **3166**, **3168**, and **3170** can be associated with a degree of freedom of the robotic surgical tool **3100**.

[0180] A control circuit, for example the control circuit **3020** (FIG. 22), may be in communication with one or more torque sensors and/or one or more rotary encoders, such as torque sensors **3030**, **3032** and position sensors **3034**, **3036**. The torque sensor(s) and/or rotary encoder(s) can be monitoring devices, which are configured to monitor operational parameters of the robotic surgical tool **3100**. The torque sensors, for instance, may be configured to monitor torque, and the rotary encoders may be configured to monitor motion (rotational or linear). The torque sensors and the rotary encoders can be incorporated into the motors of some or all of the drivers **260**, **262**, **264**, **266**, **268**, and **270** (FIG. 5). Additionally or alternatively, the torque sensors and/or the rotary encoders can be operatively coupled to one or more of the rotary input drives **3160**, **3162**, **3164**, **3166**, **3168**, and **3170** on the tool base **3102**. The torque sensors may be configured to measure the real-time torque loading on the motors, which corresponds to the torque loading by the drivers **260**, **262**, **264**, **266**, **268**, and **270**, and/or the drive inputs **3160**, **3162**, **3164**, **3166**, **3168**, and **3170**, in various instances. The rotary encoders may measure the rotational motion or output of the motors, which corresponds to the rotational motion of the drivers **260**, **262**, **264**, **266**, **268**, and **270** and/or the drive inputs **3160**, **3162**, **3164**, **3166**, **3168**, and **3170**. Monitoring torque loading and rotational motion of the motors may help determine if the robotic surgical tool **3100** is operating in accordance with the commands provided by the control circuit.

[0181] Referring to FIG. 22, a control circuit **3020** for controlling two motors that drive an

articulation joint, such as the drivers **264** and **266** (FIG. 5), for example, is shown in FIG. 22. The control circuit **3020** includes a processor **3040** in signal communication with a memory **3042** and with a communication device **3044**. A first drive system **3050** and a second drive system **3052** are in signal communication with the processor **3040**. The first drive system **3050** includes a motor **3054**, an input drive **3056** coupled to the motor **3054**, a torque sensor **3030**, and a rotary encoder/position sensor **3034**. The input drive **3056** can correspond to the drive input **3164** and the motor **3054** can correspond to the driver **264**, for example. In other aspects of the present disclosure, different drivers and drive inputs can correspond to the motor **3054** and input drive **3056**.

[0182] The second drive system **3052** includes a motor **3058**, an input drive **3060** coupled to the motor **3058**, a torque sensor **3032**, and a rotary encoder/position sensor **3036**. The input drive **3060** can correspond to the drive input **3166** and the motor **3058** can correspond to the driver **266**, for example. In other aspects, different drivers and drive inputs can correspond to the motor **3058** and input drive **3060**. In such instances, the torque sensors **3030** and **3032** determine the torque on the motor **3054** and the motor **3058**, respectively. The torque sensors **3030** and **3032** can determine the torque on the drivers **264** and **266**, for example. Moreover, the position sensors **3034** and **3036** determine the angular position of the motor **3054** and the motor **3058**, respectively. The position sensors **3034** and **3036** can determine the angular position on the drivers **264** and **266**, for example.

[0183] The control circuit **3020** also includes an output drive **3062**, a torque sensor **3064**, and a rotary encoder/position sensor **3066**. The output drive **3062** can correspond to an articulation joint **3108** (FIG. 21), for example. In such instances, the torque sensor **3064** determines the output torque applied to the articulation joint **3108**, and the position sensor **3066** determines the angular position of the articulation joint **3108**.

[0184] Referring primarily to FIG. 21, an elongate shaft **3104** extends distally from the tool base **3102**; the elongate shaft **3104** includes a proximal end **3110** a distal end **3112**. A distal end effector **3106** is coupled to the distal end **3112** of the elongate shaft **3104** at an articulation joint, or wrist joint, **3108**. The articulation joint **3108** is similar to the articulation joint **458** (FIG. 6) in certain aspects of the present disclosure.

[0185] The articulation joint **3108** enables the end effector **3106** to articulate or pivot relative to the shaft **3104** and thereby position the end effector **3106** at desired orientations and locations relative to a surgical site. For example, rotation of the rotary drive **3164** and the rotary drive **3166** may cause the articulation joint **3108** to rotate. Specifically, rotation of the rotary drive **3164** in a direction **3122** and of the rotary drive **3166** in a direction **3124** may cause the articulation joint **3108** to rotate in a direction **3120**. In other aspects of the present disclosure, different rotational directions and/or rotary drives can effect articulation of the articulation joint **3108**.

[0186] Referring to FIG. 23, a soft bump articulation control process **3000** for a robotic surgical tool is shown. The soft bump articulation control process **3000** is configured to control the articulation motors coupled to the rotary drivers that drive the articulation system in the robotic surgical tool. For example, the soft bump articulation control process **3000** is configured to control the articulation of the articulation joint **3108** of the robotic surgical tool **3100** in various instances. The soft bump articulation control process **3000** is configured to allow the articulation mechanism to move through the full articulation range of motion. The full articulation range of motion reaches the mechanical joint limits with a soft bump at the mechanical joint limit, which is when the mechanical limit of the joint is reached. In such instances, the joint can slowly and softly hit the mechanical limit without damaging the robotic surgical tool **3100**. This soft bump articulation control process **3000** allows the articulation joint **3108** to be driven to any location in its full articulation range of motion.

[0187] Prior to starting a teleoperation with a surgical robot and the robotic surgical tool **3100**, the robotic surgical tool **3100** can be attached to the surgical robot and a homing operation for the robotic surgical tool can be performed. For example, when the robotic surgical tool is mounted to



the tool driver, the robotic system can undergo a homing operation, in which positions of the various components are determined and recorded to ascertain various limits of the surgical system. For example, a start location of the rotary inputs attached to the rotary drivers of the robotic surgical tool may be determined by the homing process. The mechanical limits of a joint in a robotic surgical tool, such as the articulation joint **3108**, for example, may also be determined during the homing process.

[0188] In other instances, a robotic surgical system may not perform a homing process and the mechanical limits and/or current joint locations may be stored in a memory and recalled from the memory upon attachment of the robotic surgical tool to the surgical robot.

[0189] If a mechanical limit is reached at a high speed and/or torque, the high impact load may damage the robotic surgical tool or its articulation drive system. A reduction in the range of articulation motion for the tool may be around 1%, 2%, 5%, 10%, or higher to ensure that measurement error of the joint's location does not result in contacting the mechanical limit of the joint at a high speed and/or torque.

[0190] FIG. **23** describes the soft bump articulation control process **3000** for two motors that drive an articulation joint and do not have a reduction from the maximum operating range. In certain instances, the soft bump articulation control process **3000** can be adapted to have only one motor and, in other instances, more than two motors driving an articulation motion.

[0191] Referring still to FIG. **23**, at a step **3002** in the soft bump articulation control process **3000**, the teleoperation begins and the control circuit **3020** starts a normal articulation control mode **3006** (or first operating state). During the normal articulation control mode **3006**, the motors that control the articulation joint, such as the motors driving the rotary drivers **264**, **266** (FIG. **4**) which are mated to the rotary drives **3164**, **3166**, for example, are operated under normal or standard speeds and torques. Additionally, under the normal articulation control mode **3006**, the motors that drive the articulation joint are driven at the desired input inverse kinematics and operated under normal speeds and torques. The two input motor angles can be monitored. Stated differently, parameters indicative of a rotary position of each articulation motors can be monitored during the first operating state. Additionally, a parameter indicative of the position of the articulation joint can be monitored during the first operating state.

[0192] If either motor angle exceeds a threshold rotation angle, then the control circuit **3020** transitions from the normal articulation control mode **3006** to an upper articulation bump control mode **3004** (or second operating state) or a lower articulation bump control mode **3008** (or third operating state), as further described herein. Stated differently, the control circuit **3020** operates the articulation motors in a first operating state, e.g. normal articulation control mode **3006**, in a range of positions and transitions to a second operating state, e.g. the upper articulation bump control mode **3004** or the lower articulation bump control mode **3008**, in a different range of positions.

[0193] The control circuit **3020** transitions from the normal articulation control mode **3006** to the upper articulation bump control mode **3004** following a path **3010** when the angle of a first articulation motor exceeds an upper articulation bump threshold angle. Stated differently, the control circuit **3020** operates a first articulation motor and a second articulation motor in a first operating state, e.g. normal articulation control mode **3006**, when the rotary position of the first articulation motor is in a first range of positions. The control circuit **3020** operates the first and the second articulation motors in a second operating state, e.g. upper articulation bump control mode **3004**, when the rotary position of the first articulation motor is in a second range of positions. In certain instances, the first range of positions and the second range of positions are non-overlapping. In certain instances, the first range of positions and the second range of positions are contiguous. The control circuit **3020** transitions the first and second articulation motors from the first operating state to the second operating state when the rotary position of the first articulation motor moves from the first range of positions to the second range of positions. In certain instances, the first and second articulation motors could be the motors driving the rotary drives **3164** and **3166** or vice

versa.

[0194] In certain instances, an upper articulation bump threshold angle may be a motor rotation angle that corresponds to 1%, 2%, 5%, 10%, or any articulation angle within 15% of the upper mechanical limit of the articulation joint. Additionally, or alternatively, the upper articulation bump threshold could be any motor rotation angle that ensures that the upper mechanical limit is not reached in the normal articulation control mode **3006**.

[0195] During the upper articulation bump control mode **3004**, the two input motor angles and the articulation joint angle can be monitored. Stated differently, parameters indicative of the positions of the input motors and articulation joint can be monitored during the second operating state. If the articulation joint angle is increasing in the upper articulation bump control mode **3004** (i.e. moving toward the mechanical upper limit), then the articulation motors can be driven at the desired inverse kinematics and operated under limited speeds and/or limited torques. The motor torques and/or motor speeds can be limited to less than the standard torque and/or speed permitted during the normal articulation control mode **3006**, which can allow the articulation joint **3108** to reach its mechanical upper limit without causing a high impact load on the articulation system or robotic surgical tool **3100**. Stated differently, when the first articulation motor and the second articulation motors are in the second operating state and the rotary position of the first articulation motor is moving away from the first range of positions, then the maximum allowable speed and maximum allowable torque for the first and second articulation motors are lower than in first operating state.

[0196] In various instances, if the articulation joint angle is decreasing in the upper articulation bump control mode **3004** (i.e. moving away from the mechanical upper limit), then the two articulation motors are driven at the desired inverse kinematics and may be operated under normal speeds and torques. Stated differently, when the first and second articulation motors are in the second operating state and the rotary position of the first articulation motor is moving toward the first range of positions, then the maximum allowable speed and maximum allowable torque for the first and second articulation motors may be the same as in the first operating state, for example. Once the first articulation motor angle decreases past the upper articulation bump threshold angle and an additional anti-dither angle, the control circuit **3020** transitions from the upper articulation bump control mode **3004** back to the normal articulation control mode **3006** following a path **3012**. Stated differently, the control circuit **3020** re-implements the first operating state from the second operating state for the first and second articulation motors when the rotary position of the first articulation motor returns to the first range of positions from the second range of positions by a threshold anti-dither angle. The additional anti-dither angle is a small angle that allows for a smooth transition between the upper articulation bump control mode **3004** and the normal articulation control mode **3006**. In certain instances, the anti-dither angle is an angle that is less than ten degrees and may be one or two degrees, for example. In certain instances, the anti-dither angle is zero.

[0197] The control circuit **3020** transitions from the normal articulation control mode **3006** to the lower articulation bump control mode **3008** following a path **3014** when the angle of the second articulation motor exceeds a lower articulation bump threshold angle. Stated differently, the control circuit **3020** operates the first and second articulation motors in a first operating state, e.g. normal articulation control mode **3006**, when the rotary position of the second articulation motor is in a third range of positions. The control circuit **3020** operates the first and second articulation motors in a third operating state, e.g. lower articulation bump control mode **3008**, when the rotary position of the second articulation motor is in a fourth range of positions. In certain instances, the third range of positions and the fourth range of positions are non-overlapping. In certain instances, the third range of positions and the fourth range of positions are contiguous. The control circuit **3020** transitions the first and second articulation motors from the first operating state to the third operating state when the rotary position of the second articulation motor moves from the third range of positions to the fourth range of positions. In certain instances, the first and second

articulation motors could be the motors driving the rotary drives **3164** and **3166** or vice versa. [0198] In certain instances, the lower articulation bump threshold angle may be a motor rotation angle that corresponds to 1%, 2%, 5%, 10%, or any articulation angle within 15% of the lower mechanical limit of the articulation joint. Additionally, or alternatively, the lower articulation bump threshold could be any motor rotation angle that ensures that the lower mechanical limit in the normal articulation operating mode **3006**.

[0199] During the lower articulation bump control mode **3008**, the two input motor angles and articulation joint angle can be monitored. Stated differently, parameters indicative of the positions of the input motors and the articulation joint can be monitored during the third operating state. If the articulation joint angle is decreasing in the lower articulation bump control mode **3008** (i.e. moving toward the mechanical lower limit), then the articulation motors are driven at the desired inverse kinematics and operated under limited speeds and/or limited torques. The articulation input motor torques and speeds are limited to allow the articulation joint to reach the mechanical lower limit of the articulation joint without causing high impact loads. Stated differently, when the first and second articulation motors are in the third operating state and the rotary position of the second articulation motor is moving away from the third range of positions, then the maximum allowable speed and maximum allowable torque for the first and second articulation motors are lower than in first operating state.

[0200] In various instances, if the articulation joint angle is increasing in the lower articulation bump control mode **3008** (i.e. moving away from the mechanical lower limit), then the two articulation motors are driven at the desired inverse kinematics and operated under normal speeds and torques. Stated differently, when the first and second articulation motors are in the third operating state and the rotary position of the second articulation motor is moving toward the third range of positions, then the maximum allowable speed and maximum allowable torque for the first and second articulation motors may be the same as in the first operating state, for example. Once the second articulation motor angle increases past the lower articulation bump threshold angle and an additional anti-dither angle, the control circuit **3020** transitions from lower articulation bump control mode **3008** back to normal articulation control mode **3006** following path **3016**. Stated differently, the control circuit **3020** re-implements the first operating state from the third operating state for the first and second articulation motors when the rotary position of the second articulation motor returns to the third range of positions from the fourth range of positions by a threshold anti-dither angle.

[0201] The additional anti-dither angle is a small angle that allows for a smooth transition between the lower articulation bump control mode **3008** and the normal articulation control mode **3006**. In certain instances, the anti-dither angle is an angle that is less than ten degrees and may be one or two degrees, for example. In certain instances, the anti-dither angle can be zero.

[0202] The control circuit **3020** can be implemented as a non-transitory computer readable medium storing computer readable instructions. Accordingly, the non-transitory computer-readable medium includes any type of tangible machine-readable medium suitable for storing or transmitting electronic instructions or information in a form readable by a machine (e.g., a computer), which can implement the transitions between operating states and/or modes **3004**, **3006**, and/or **3008**.

[0203] In various instances, the soft bump articulation control process **3000** can be used to control other joints on a robotic surgical tool in which the joint is configured to bumps a mechanical joint limit during its range of motion.

[0204] Referring now to FIG. **24**, a portion of a robotic surgical tool **3200** is shown. The robotic surgical tool **3200** is similar in many aspects to the robotic surgical tool **3100**. The robotic surgical tool **3200** includes a tool base, or proximal housing, **3202**, which is similar in many aspects to the tool base **3102** and includes six rotary drives **3260**, **3262**, **3264**, **3266**, **3268**, and **3270**. Certain portions of the proximal housing **3202** are removed from the robotic surgical tool **3200** in FIG. **24** to expose an interior portion of the proximal housing **3202** including the six rotary drives **3260**,

**3262, 3264, 3266, 3268, and 3270** and components of the articulation system housed therein. [0205] An elongate shaft **3204** extends distally from the tool base **3202**; the elongate shaft **3204** includes a proximal end **3210** and a distal end **3212**. A distal end effector **3206** is coupled to the distal end **3212** of the elongate shaft **3204** at an articulation joint, or wrist joint, **3208**. The articulation joint **3208** is similar to the articulation joint **3108** in many aspects of the present disclosure. The articulation joint **3208** enables the end effector **3206** to articulate or pivot relative to the elongate shaft **3204** and thereby position the end effector **3206** at desired orientations and locations relative to a surgical site.

[0206] Referring still to FIG. **24**, the rotary drive **3264** drives a first drive rack **3240**. Rotational movement of the rotary drive **3264** corresponds to linear movement of the first drive rack **3240** in either a direction **3222** or a direction **3232** depending on the rotational direction of the rotary drive **3264**. The first drive rack **3240** includes a first fork **3242** matable with a first articulation yoke **3244**. More specifically, the first fork **3242** is configured to be received within an annular slot **3246** defined in the first articulation yoke **3244**. Engagement between the first fork **3242** and the annular slot **3246** allows the first drive rack **3240** to drive the first articulation yoke **3244** linearly along an internal shaft **3280** in either the direction **3222** or the direction **3232**. The internal shaft **3280** extends from within the tool base **3202** at a location **3218** through the elongated shaft **3204** to the articulation joint **3208**.

[0207] The first articulation yoke **3244** is coupled to a first articulation band **3248**, which extends distally to the articulation joint **3208**. As illustrated, the first articulation band **3248** is arranged within a corresponding slot defined in the internal shaft **3280**, such that the internal shaft **3280** guides the first articulation band **3248** as it extends distally to the articulation joint **3208**. Axial movement of the first articulation yoke **3244** along a longitudinal axis parallel to the internal shaft **3280** correspondingly moves the first articulation band **3248**, which corresponds to articulation of the articulation joint **3208**. In certain instances, movement of the first articulation yoke **3244** in the direction **3232** may cause the articulation joint **3208** to articulate and move the end effector **3206** in a direction **3230**, for example. In certain instances, movement of the first articulation yoke **3244** in the direction **3222** may cause the articulation joint **3208** to articulate and move the end effector **3206** in a direction **3220**, for example.

[0208] Referring still to FIG. **24**, the rotary drive **3266** drives a second drive rack **3250**. Rotational movement of the rotary drive **3266** corresponds to linear movement of the second drive rack **3250** in either a direction **3224** or a direction **3234** depending on the rotational direction of the rotary drive **3266**. The second drive rack **3250** includes a second fork **3252** matable with a second articulation yoke **3254**. More specifically, the second fork **3252** is configured to be received within an annular slot **3256** defined in the second articulation yoke **3254**. Moreover, engagement between the second fork **3252** and the annular slot **3246** allows the second drive rack **3250** to drive the second articulation yoke **3254** linearly along the internal shaft **3280** in either the direction **3224** or the direction **3234**.

[0209] The second articulation yoke **3254** may be coupled to a second articulation band **3258**, which extends distally to the articulation joint **3208**. As illustrated, the second articulation band **3258** is arranged within a corresponding slot defined in the internal shaft **3280**, such that the internal shaft **3280** guides the second articulation band **3258** as it extends distally to the articulation joint **3208**. Axial movement of the second articulation yoke **3254** along a longitudinal axis parallel to the internal shaft **3280** correspondingly moves the second articulation band **3258**, which causes the articulation joint **3208** to articulate. In certain instances, movement of the second articulation yoke **3254** in the direction **3234** may cause the articulation joint **3208** to articulate and move the end effector **3206** in the direction **3230**, for example. In certain instances, movement of the second articulation yoke **3254** in the direction **3224** may cause the articulation joint **3208** to articulate and move the end effector **3206** in the direction **3220**, for example.

[0210] Axial movement of the first and second articulation yokes **3244, 3254** can cooperatively

actuate the first and second articulation bands **3248**, **3258** and, thereby, articulate the end effector **3206** as further described herein. Movement of the first articulation yoke **3244** in the direction **3232** and movement of the second articulation yoke **3254** in the direction **3234** corresponds to articulation of the end effector **3206** in the direction **3230**. Said another way, movement of the first articulation yoke **3244** and the second articulation yoke **3254** away from each other corresponds to articulation of the end effector **3206** in the direction **3230**. Additionally, movement of the first articulation yoke **3244** in the direction **3222** and movement of the second articulation yoke **3254** in the direction **3224** corresponds to articulation of the end effector **3206** in the direction **3220**. Stated differently, movement of the first articulation yoke **3244** and the second articulation yoke **3254** toward each other corresponds to articulation of the end effector **3206** in the direction **3220**. In at least one aspect of the present disclosure, the first and second articulation yokes **3244**, **3254** antagonistically operate such that one of the articulation yokes **3244**, **3254** pulls one of the articulation bands **3248**, **3258** proximally while the other articulation yokes **3244**, **3254** pushes the other articulation band **3248**, **3258** distally.

[0211] In other aspects, the first and second articulation yokes **3244**, **3254** may be operated independently without the other being operated (affected). In certain instances, the first and second articulation yokes **3244**, **3254** may operate antagonistically where one reduces the force effect of another. In an antagonistic operation, one of the articulation yokes **3244**, **3254** pulls (or pushes) the articulation bands **3248**, **3258** associated therewith proximally (or distally) with a first force while the other one of the articulation yokes **3244**, **3254** pulls (or pushes) the articulation bands **3248**, **3258** associated therewith proximally (or distally) with a second force. When the first force is larger than the second force, the first force can overcome the second force, as well as the internal losses of the device (i.e., friction) and loads imparted on the end effector **3206** via the external environment, such that the articulation yoke **3244**, **3254** providing the first force moves proximally (or distally) while the articulation yoke **3244**, **3254** providing the second force moves distally (or proximally).

[0212] Still referring primarily to FIG. **24**, the internal shaft **3280** extends distally within the elongated shaft **3204** and is connected to the articulation joint **3208**. The articulation bands **3248**, **3258** extend distally towards the articulation joint **3208** within corresponding slots defined within the internal shaft **3280**. The corresponding slots may be provided on opposite sides of the internal shaft **3280**, or may be defined elsewhere about the internal shaft **3280** in other instances.

[0213] FIG. **25** is a cross-sectional view of the proximal housing **3202** taken across the plane indicated in FIG. **24**. The articulation bands **3248**, **3258** sit inside slots on either side of the internal shaft **3280**. The internal shaft **3280** extends through the second articulation yoke **3254**. The second articulation band **3258** attaches to the second articulation yoke **3254**. The first articulation band **3248** extends along the slot in the internal shaft **3280** and through the second articulation yoke **3254**. The second drive rack **3250** attaches to the second articulation yoke **3254** at the second fork **3252**.

[0214] In various instances, the sliding of the articulation yokes **3244**, **3254** along the internal shaft **3280** can generate friction and corresponding internal losses. To effect the articulation motion, the articulation yokes **3244**, **3254** must overcome the frictional losses and move along the internal shaft **3280**. Articulation systems including articulation yokes configured to slide along an internal support chassis, like those shown in FIGS. **24** and **25** are further described in U.S. patent application Ser. No. 16/553,725, titled ARTICULATING INCLUDING ANTAGONISTIC CONTROLS FOR ARTICULATION AND CALIBRATION, filed Aug. 28, 2019, which is incorporated by reference herein in its entirety.

[0215] Internal moving parts that translate along each other to articulate an end effector generate friction. For example, the articulation yokes **3244**, **3254** that move along the internal shaft **3280** of the robotic surgical tool **3200** shown in FIG. **24** generate friction during an articulation motion. In certain instances, the articulation of the end effector can cause significant frictional forces between

the internal translating parts during normal loading conditions. Such frictional forces require the drive mechanism to supply more input torque to overcome the friction. In various instances, the high friction can cause a brake-like effect, which requires additional input torque for various subsystems that interact with the translating parts in order to overcome the friction. In various instances, it can be advantages to reduce the friction on the moving parts of a robotic surgical tool during an articulation motion.

[0216] An articulation drive system that mechanically reduces the friction between certain translating parts may be advantageous in certain instances. Such an articulation drive system can be sufficiently robust to articulate the end effector without requiring additional torque input due to frictional losses along the translating surfaces. For example, the incorporation of rolling elements (e.g. roto-linear ball bearings) between certain translating parts can reduce the frictional forces and losses therebetween.

[0217] In one aspect the present disclosure, a robotic surgical tool can comprise a housing, an end effector, and an elongate shaft extending distally from the housing to the end effector. The robotic surgical tool can further comprise an articulation joint configured to articulate the end effector relative to the elongate shaft during an articulation motion, an internal shaft extending distally from the housing through the elongate shaft, and an articulation drive system. The articulation drive system can comprise an articulation yoke coupled to the internal shaft, an articulation band coupled to the articulation yoke and extending distally along the internal shaft to the articulation joint, and rolling elements intermediate the internal shaft and the articulation yoke. The articulation yoke can be configured to roll along the rolling elements during the articulation motion.

[0218] In certain instances, the foregoing arrangement can reduce frictional losses between certain translating parts of the articulation drive system. Moreover, the reduced friction can improve load handling and requires less input torque. There may also be less induced friction on adjacent subsystems in certain instances.

[0219] Referring to FIGS. **26** and **27**, portions of a robotic surgical tool **3300** are shown. The robotic surgical tool **3300** is similar in many aspects to the robotic surgical tool **3200**. For example, the robotic surgical tool **3300** includes an internal shaft **3380**, an articulation joint **3308**, a surgical end effector **3306**, and an articulation system including articulation yokes **3344**, **3354**. The articulation yokes **3344**, **3354** are similar in many aspects to the articulation yokes **3244**, **3254** (FIG. **24**). Unlike the robotic surgical tool **3200**, the robotic surgical tool **3300** also includes rolling element pads **3382** around the internal shaft **3380** between the articulation yokes **3344**, **3354** and the internal shaft **3380**. The rolling element pads **3382** include roto-linear elements (e.g. balls within a continuous looped track), which can reduce the friction caused from movement of the articulation yokes **3344**, **3354** along the internal shaft **3380**.

[0220] The internal shaft **3380** extends distally and is coupled to an articulation joint, or wrist joint, **3308** at the distal end of the internal shaft **3380**. In various instances, a tool shaft can surround the internal shaft **3380** and also surround the components of the articulation system extending between the proximal housing to the end effector **3306**. The internal shaft **3380** can be a chassis or support for the tool shaft and other components extending between the proximal housing and the end effector. For example, the internal shaft **3380** can support a firing member.

[0221] The articulation joint **3308** is similar in many aspects to the articulation joint **3208**. The articulation joint **3308** enables the end effector **3306** to articulate or pivot relative to the internal shaft **3380** and thereby position the end effector **3306** at desired orientations and locations relative to a surgical site.

[0222] Referring still to FIGS. **26** and **27**, a first drive rack **3340** attaches to the first articulation yoke **3344** with a first fork **3242** matable to the first articulation yoke **3344**. More specifically, the first fork **3342** is configured to be received within an annular slot **3346** defined in the first articulation yoke **3344**. Moreover, engagement between the first fork **3342** and the annular slot **3346** allows the first drive rack **3340** to drive the first articulation yoke **3344** linearly along the

internal shaft **3380** in a direction **3322** or a direction **3332**. Movement of the first articulation yoke **3344** in the direction **3322** or the direction **3332** along the internal shaft **3380** corresponds to articulation of the end effector **3306** in the direction **3320** or the direction **3330**. The articulation yoke stop **3374** prevents the first articulation yoke **3344** from moving too far proximally, i.e. too far in the direction **3332**, on the internal shaft **3380**.

[0223] A second drive rack **3350** attaches to the second articulation yoke **3354** with a second fork **3352** matable to the second articulation yoke **3354**. More specifically, the second fork **3352** is configured to be received within an annular slot **3356** defined in the second articulation yoke **3354**. Moreover, engagement between the second fork **3352** and the annular slot **3356** allows the second drive rack **3350** to drive the second articulation yoke **3354** linearly along the internal shaft **3380** in a direction **3324** or a direction **3334**. Movement of the second articulation yoke **3354** in the direction **3324** or the direction **3334** along the internal shaft **3380** corresponds to articulation of the end effector **3306** in the direction **3320** or the direction **3330**.

[0224] Accordingly, axial movement of the first and second articulation yokes **3344**, **3354**, cooperatively actuate the first and second articulation bands **3348**, **3358** and, thereby, articulate the end effector **3306**, as further described herein. Movement of the first articulation yoke **3344** in the direction **3332** and movement of the second articulation yoke **3354** in the direction **3334** corresponds to articulation of the end effector **3306** in the direction **3330**. Said another way, movement of the first articulation yoke **3344** and the second articulation yoke **3354** away from each other corresponds to articulation of the end effector **3306** in the direction **3330**. Additionally, movement of the first articulation yoke **3244** in the direction **3222** and movement of the second articulation yoke **3254** in the direction **3224** corresponds to articulation of the end effector **3206** in the direction **3220**. Said another way, movement of the first articulation yoke **3244** and the second articulation yoke **3254** toward each other corresponds to articulation of the end effector **3206** in the direction **3220**.

[0225] The articulation yokes **3344**, **3354** are configured to slide along multiple rolling element pads **3382** that are set into the internal shaft **3380**. In certain instances, the rolling element pads **3382** may be press-fit into recesses or cavities in the internal shaft **3380**. In various instances, there may be two, four, or eight rolling element pads **3382** set around the circumference of the internal shaft **3380**. The internal shaft **3380** includes four rolling element pads **3382** around the circumference thereof. The reader will appreciate that there may be other suitable numbers of rolling element pads **3382** around the circumference of the internal shaft **3380**, and the rolling element pads **3382** can be positioned to cover the region along which the articulation yokes **3344**, **3354** move along the internal shaft **3380**.

[0226] Referring now to FIG. **28**, an exploded view of a rolling element pad **3382** is shown. Each rolling element pad **3382** includes a rolling element retainer **3384**, rolling elements, or balls, **3386**, and a rolling element base **3390**. The rolling elements **3386** in each rolling element pad **3382** are divided into two sets of rolling elements **3386** that sit in separate and independent continuous loop tracks **3392**. The continuous loop tracks **3392** are defined between the rolling element retainer **3384** and the rolling element base **3390**. The rolling elements **3386** can roll around their continuous loop track **3392**, which allows the rolling elements **3386** to move and roll as the articulation yokes **3344**, **3354** move relative to the internal shaft **3380**. In such instances, the rolling element pads **3382** comprise roto-linear bearings for the articulation yokes **3344**, **3354**. The slits or windows **3388** in the rolling element retainer **3384** allow the rolling elements **3386** to interact with objects outside of the rolling element retainer **3384**, such as the articulation yokes **3344**, **3354**, for example. The rolling elements **3386** stick out past the slits **3388** so that the articulation yokes **3344**, **3354** are supported by and sit on the rolling elements **3386** and do not slide directly on the rolling element retainer **3384**.

[0227] Referring primarily to FIG. **28**, the rolling elements **3386** of each rolling element pad **3382** are held in the continuous loop track **3392** (FIG. **28**) by the rolling element retainer **3384**. The

articulation yokes **3344**, **3354** (FIGS. **26** and **27**) slide on the rolling elements **3386** during the linear movement of the articulation yokes **3344**, **3354** along the internal shaft **3380**. The articulation yokes **3344**, **3354** do not slide directly on the rolling element retainer **3384**, but slide on the rolling elements **3386** that radially protrude beyond the retainer **3384**. The rolling elements **3386** roll along the continuous loop track **3392** during the movement of the articulation yokes **3344**, **3354**.

[0228] In FIG. **28**, there are two continuous loop tracks **3392** per rolling element pad **3382** and each articulation yoke **3344**, **3354** sits on rolling elements **3386** of a different continuous loop track **3392**. In such instances, the rolling elements **3386** associated with each articulation yoke **3344**, **3354** (FIGS. **26** and **27**) can travel in the same direction as the corresponding articulation yoke **3344**, **3354**. As described herein, the articulation yokes **3344**, **3354** can move axially relative to each other (toward each other/together and away from each other/apart) and, thus, the rolling elements **3386** in the continuous loop tracks **3392** of the same rolling element pad **3382** can simultaneously or concurrently roll in different directions.

[0229] The rolling of the rolling elements **3386** is configured to reduce the friction caused by the movement of the articulation yokes **3344**, **3354**. Such a reduction in friction can allow for better handling of the articulation joint **3308** and require less input torque to articulate the end effector **3306** relative to the elongate shaft of the robotic surgical tool **3300**. Moreover, there can be less induced friction on adjacent subsystems, such as the closure and shaft rolling subsystems of the robotic surgical tool, for example.

[0230] In various instances, it may be difficult for a clinician to visualize the orientation of a robotic surgical tool during a surgical procedure. For example, it may be difficult to visualize the orientation of the tool with respect to a constrained anatomy in which only an end effector, or portion thereof, is visible in the camera view.

[0231] In certain instances, an augmented rendering of the robotic surgical tool can be shown to the user to demonstrate the tool's orientation. The augmented rendering may show joints of the robotic surgical tool that are out of view/off camera. It is desirable to convey such information to the clinician without being overly distracting to the clinician. For example, the orientation may be depicted on the display at a transitional state between completion of a homing operation and the beginning of the teleoperation. The augmented rendering of the robotic surgical tool can then be minimized or otherwise moved to a remote and/or unobtrusive location on the display screen so as to not distract the clinician.

[0232] In certain instances, an end effector overlay feature for a surgical imaging system can inform the clinician of the function and orientation of the robotic surgical tool without distracting the clinician from the surgical operation. The position of the robotic surgical tool in relation to the camera is already calculated by the robotic surgical system for tool mapping purposes in various instances.

[0233] Surgical camera views of a robotic surgical tool **3530** during a surgical procedure are shown in a series of views in FIGS. **30A-D**, in which the orientation of the robotic surgical tool **3530** is conveyed to a clinician in the camera view **3500** with an end effector overlay feature. In various instances, such a feature can take advantage of the state between completion of the homing operation and the beginning of teleoperation of the robotic surgical tool **3530** to overlay, demonstrate, and minimize the augmented rendering of the distal end effector for the clinician's benefit and convenience.

[0234] In various instances, the control system, such as the control tower **130** (FIG. **1**) for example, can complete a homing operation and then wait for a clinician to manually extend the robotic surgical tool **3530** into the surgical field. The control system can track the orientation and position of the robotic surgical tool **3530** relative to the camera and monitor the camera view **3500**. The control system can wait for a minimum amount of the end effector of the robotic surgical tool **3530** to appear within view, as shown in FIG. **30A**, in various instances. The control system can then



overlay an augmented rendering 3520 of the end effector on top of the actual end effector image on the display screen. Though the augmented rendering 3520 may be over the end effector on the display screen, the augmented rendering can be transparent and/or a skeleton/phantom depiction such that the end effector can also be seen by the clinician.

[0235] FIG. 29 is a flowchart 3400 showing the process of displaying the augmented rendering 3520 on the camera view 3500. In step 3410, the camera view has the abstract augmentation 3510 of the surgical tool 3530 in an unobtrusive location of the camera view 3500 and the surgical tool 3530 is not yet in the camera view 3500. At step 3420, the surgical tool 3530 enters the camera view 3500. Step 3430 commences when enough of the surgical tool enters the camera view 3500. At step 3430, an augmented rendering 3520 is overlaid on the camera view 3500. Next, at step 3440, the surgical tool 3530 joint orientations are shown to the clinician. At step 3450, the augmented rendering 3520 is removed by panning and scaling the augmented rendering 3520 toward the abstract augmentation 3510. At step 3460, the augmented rendering 3430 has reached the abstract augmentation 3510 and disappeared from the primary and/or central portion of the display screen.

[0236] The augmented rendering 3520 is a conical schematic reflecting the conical orientation of the jaws of the robotic surgical tool 3530. In other instances, the augmented rendering can be a different three-dimensional shape, such as a sphere or a prism. The shape of the augmented rendering 3520 can correspond to a general shape of the robotic surgical tool 3530 in various instances. The reader will appreciate that alternative robotic surgical tools, e.g. electrosurgery devices, scalpels, clip appliers, clamps, and/or ultrasonic tools, can employ the end effector overlay feature described herein.

[0237] In various instances, the augmented rendering 3520 can show the surgical tool 3530 joint orientations (Step 3440 of FIG. 29). In one example the joint orientations are shown by leaving the augmented rendering 3520 over the surgical tool 3530 for a period of time. Once the period of time has expired, the augmented rendering 3520 can be reduced in scale and moved off the actual robotic surgical tool 3530 to a less clinically-obtrusive location. For example, the augmented rendering 3520 can be moved to a side bar or a corner of the camera view 3500. When the robotic surgical tool 3530 moves during teleoperation, the augmented rendering 3520 can then moves accordingly, which can aid in visualization of the robotic surgical tool.

[0238] The augmented rendering 3520 can show the orientation and functionality of the robotic surgical tool 3530 by rotating the joints of the robotic surgical tool 3530 on the augmented rendering 3520. For example, the augmented rendering 3520 includes marks 3522, 3524 at the distal end thereof. The marks 3522, 3524 can be configured to rotate about the longitudinal axis, i.e. a roll axis, to shown the roll functionality of the robotic surgical tool 3530. In certain instances, the marks 3522, 3524 can be conveyed to a clinician as a variation in the line type of the augmented rendering 3520, as shown in FIG. 30A, and/or as a different color, for example. The marks 3522, 3524 can also be implemented by other signals, which allow the function (e.g. rotation about the longitudinal axis) to be conveyed to the clinician in a simplified and easy-to-identify manner. The marks 3522, 3524 can also be conveyed with a break in the line depicting the augmented rendering 3520.

[0239] An abstract augmentation 3510 of the robotic surgical tool 3530 is shown in an unobtrusive location of the camera view 3500. In FIGS. 30A-D, the unobtrusive location is the top left corner of the camera view 3500. Alternative locations are also possible, such as on a side bar or at any of the corners of the camera view 3500, for example. The abstract augmentation 3510 shows a rendering of the robotic surgical tool 3530 that shows the orientation of the entire robotic surgical tool 3530 including joints that are not in the camera view 3500. These orientations may be challenging for a clinician to appreciate in a typical view, in which most of the elongated shaft of the robotic surgical tool 3530 are not shown in the camera view. For example, the articulation joint place markers 3512 and roll place markers 3514 are shown in the abstract augmentation 3510 of

FIGS. 30A-30D. The rendering on the abstract augmentation **3510** can move as the robotic surgical tool **3530** moves, which provides the clinician with feedback and information about the overall orientation of the joints of the robotic surgical tool **3530**.

[0240] FIGS. 30A-30D show four stages of animation of the augmented rendering **3520** going from full overlay in FIG. 30A to the abstract augmentation **3510** in FIG. 30D. FIG. 30A shows the augmented rendering **3520** in a fully overlaid state. FIGS. 30B and 30C are transitional frames of the augmented rendering **3520** panning and scaling toward the abstract augmentation **3510**. FIG. 30D shows a post-overlay scene with just the abstract augmentation **3510** in the top-left corner. The transition between the full overlay stage (FIG. 30A) and pure abstract augmentation **3510** stage (FIG. 30D) can be smooth in implementation. The augmented rendering **3520** pans and scales to become part of the abstract augmentation **3510**.

[0241] In various instances, the rotation about a longitudinal axis is shown by roll place markers **3514** and the rotation about the articulation joint is shown by articulation place markers **3512**, for example. The roll place markers **3514** and/or the articulation place markers **3512** can include marks, which can correspond to the marks on the augmented rendering **3520**. For example, the marks can include the same signal and/or color to convey the correspondence to the clinician.

[0242] The augmented rendering **3520** can be configured to show the orientation of the surgical tool **3530** (Step **3440** of FIG. 29) by remaining on the robotic surgical tool **3530** for a period of time. Once the period of time is over, the augmented rendering **3520** can move off the robotic surgical tool **3530** to the abstract augmentation **3510**, in certain aspects of the present disclosure. For example, the augmented rendering **3520** can pan and scale to the abstract augmentation **3510** located in the unobtrusive location.

[0243] In certain instances, the augmented rendering **3520** can show the orientation of the surgical tool **3530** (Step **3440** of FIG. 29) by remaining overlaid on the robotic surgical tool **3530** until the robotic surgical tool **3530** enters a teleoperation mode and a minimum amount of roll and/or articulation is implemented. In such instances, the augmented rendering **3520** moves with the robotic surgical tool **3530**, which allows the clinician to observe the motion of the augmented rendering **3520**. Once a minimum amount of travel or movement has been observed, the augmented rendering **3520** can pan and scale to the abstract augmentation **3510** located in the unobtrusive location.

[0244] In still other instances, the augmented rendering **3520** can be configured to show the orientation of the surgical tool **3530** (Step **3440** of FIG. 29) by having the augmented rendering **3520** automatically oscillate the joints of the robotic surgical tool **3530**. This process could be used to catch the clinician's attention. For example, the roll joint and/or the articulation joints can initially be slightly oscillated to alert the clinician to their locations. After such an oscillation, the augmented rendering **3520** can return to matching the orientation of the robotic surgical tool, and then pan and scale to the abstract augmentation **3510** located in the unobtrusive location.

[0245] It is noted that there could be other methods to perform step **3440** of FIG. 29 with the augmented rendering **3520** and abstract augmentation **3510**. Any method that uses the augmented rendering **3520** and abstract augmentation **3510** to show the surgical tool **3530** joint orientations could be used.

[0246] A robotic surgical system **2100** is shown in FIG. 31. Various aspects of the robotic surgical system **2100** are further described in U.S. Pat. No. 10,470,830, titled SYSTEM AND METHODS FOR INSTRUMENT BASED INSERTION ARCHITECTURES, issued Nov. 12, 2019, for example. U.S. Pat. No. 10,470,830, titled SYSTEM AND METHODS FOR INSTRUMENT BASED INSERTION ARCHITECTURES, issued Nov. 12, 2019, is incorporated by reference herein in its entirety.

[0247] The robotic surgical system **2100** includes a base **2101** coupled to one or more robotic arms, e.g., the robotic arms **2102** in FIG. 31. The base **2101** is communicatively coupled to a command console or user console, which is further described in U.S. Pat. No. 10,470,830, titled SYSTEM

[0248] In various instances, the command console for the robotic surgical system **2100** is similar in many aspects to the user console **110** (FIG. 1). The base **2101** can be positioned such that the robotic arm **2102** has access to perform a surgical procedure on a patient, while a user, such as a clinician or surgeon, for example, can control the robotic surgical system **2100** from the comfort of the command console. In some instances, the base **2101** can be coupled to a surgical operating table or a bed for supporting the patient. In other instances, the robotic arms can be supported by a free-standing robot having a base and/or column, for example, as further described in U.S. patent application Ser. No. 16/553,725, titled ARTICULATING INCLUDING ANTAGONISTIC CONTROLS FOR ARTICULATION AND CALIBRATION, filed Aug. 28, 2019, for example.

[0249] In some instances, the base **2101** may include subsystems such as control electronics, pneumatics, power sources, optical sources, and the like. The robotic arm **2102** includes multiple arm segments **2110** coupled at joints **2111**, which provides multiple degrees of freedom, e.g., seven degrees of freedom corresponding to seven arm segments, for the robotic arm **2102**. The base **2101** may contain a source of power **2112**, pneumatic pressure **2113**, and control and sensor electronics **2114**—including components such as a central processing unit, data bus, control circuitry, and memory—and related actuators such as motors to move the robotic arm **2102**. The electronics **2114** in the base **2101** may also process and transmit control signals communicated from the command console. The base **2101** also includes wheels **2115** to transport the robotic surgical system **100**.

[0250] In some aspects of the present disclosure, the robotic arm **2102** includes set up joints that use a combination of brakes and counter-balances to maintain a position of the robotic arm **2102**. The counter-balances may include gas springs or coil springs. The brakes, which are fail-safe brakes in certain instances, may include mechanical and/or electrical components. Further, the robotic arms **2102** can be gravity-assisted passive support type robotic arms.

[0251] Each robotic arm **2102** may be coupled to a tool driver **2117**, which is also referred to herein as an instrument device manipulator (IDM), using a changer interface **2116**. The tool driver **2117** can serve as a tool holder. In some instances, the tool driver **2117** can be removable, such that the tool driver **2117** can be replaced with a different type of tool driver. For example, the tool drivers **220** (FIG. 2-4) for the robotic surgical system **100** (FIG. 1) can be interchangeable with the tool driver **2117** (FIG. 31) in certain instances. For example, a first type of tool driver that manipulates an endoscope can be replaced with a second type of tool driver that manipulates a laparoscope. The changer interface **2116** includes connectors to transfer pneumatic pressure, electrical power, electrical signals, and optical signals from the robotic arm **2102** to the tool driver **2117**. The changer interface **2116** can be a set screw or base plate connector. The tool driver **2117** manipulates surgical tools, such as the surgical tool **2118**, for example, using techniques including direct drive, harmonic drive, geared drives, belts and pulleys, magnetic drives, and the like. The changer interface **2116** is interchangeable based on the type of tool driver **2117** and can be customized for a certain type of surgical procedure. The robotic arm **2102** can include joint level torque sensing and a wrist at a distal end, in various instances.

[0252] The surgical tool **2118** can be a laparoscopic, endoscopic and/or endoluminal tool, for example, that is capable of performing a procedure on a patient at a surgical site. In some aspects of the present disclosure, the surgical tool **2118** includes a laparoscopic tool, which can be inserted into an incision of a patient. The laparoscopic tool can comprise a rigid, semi-rigid, or flexible shaft. When designed for laparoscopy, the distal end of the shaft can be connected to an end effector that may comprise, for example, a wrist, a grasper, a scissors, a stapler, or other surgical device. Exemplary end effectors for cutting and fastening tissue are further described herein.

[0253] In certain aspects of the present disclosure, the surgical tool **2118** comprises an endoscopic surgical tool that is inserted into the anatomy of a patient to capture images of the anatomy (e.g., body tissue). The endoscopic tool, or endoscope, can include a tubular and flexible shaft. The

endoscope includes one or more imaging devices (e.g., cameras or sensors) that capture images at the surgical site. The imaging devices may include one or more optical components such as an optical fiber, fiber array, or lens. The optical components move along with the tip of the surgical tool **2118** such that movement of the tip of the surgical tool **2118** results in changes to the images captured by the imaging devices. Exemplary imaging devices and visualization systems are further described herein.

[0254] In other instances, the surgical tool **2118** comprises an endoluminal tool, which can be inserted through a natural orifice of a patient, such as a bronchoscope or urethroscope. The endoluminal tool can also include a tubular and flexible shaft. When designed for endoluminal surgery, the distal end of the shaft can be connected to an end effector that may comprise, for example, a wrist, a grasper, scissors, or other surgical device.

[0255] The robotic arms **2102** of the robotic surgical system **2100** can manipulate the surgical tool **2118** using elongate movement members. The elongate movement members may include pull-wires, also referred to as pull or push wires, cables, fibers, or flexible shafts. For example, the robotic arms **2102** are configured to actuate multiple pull-wires coupled to the instrument **2118** to deflect, articulate, and/or rotate the tip of the surgical tool **2118**. The pull-wires may include both metallic and non-metallic materials such as stainless steel, Kevlar, tungsten, carbon fiber, and the like. In some aspects of the present disclosure, the surgical tool **2118** may exhibit nonlinear behavior in response to forces applied by the elongate movement members. The nonlinear behavior may be based on stiffness and compressibility of the tool **2118**, as well as variability in slack or stiffness between different elongate movement members.

[0256] Referring still to FIG. **31**, the robotic surgical system **2100** also includes a controller **2120**, which can be a computer processor, for example. The controller **2120** includes a calibration module **2125**, image registration module **2130**, and a calibration store **2135**. The calibration module **2125** can characterize the nonlinear behavior of the tool using a model with piecewise linear responses along with parameters such as slopes, hysteresis, and dead zone values. The robotic surgical system **2100** can more accurately control the surgical tool **2118** by determining accurate values of the parameters. In some instances, some or all functionality of the controller **2120** is performed outside the robotic surgical system **2100**. For example, certain functionalities can be performed on another computer system or server communicatively coupled to the robotic surgical system **2100**.

[0257] Another surgical robot **2200** is shown in FIG. **32**. Various aspects of the surgical robot **2200** are further described in U.S. Pat. No. 10,470,830, titled SYSTEM AND METHODS FOR INSTRUMENT BASED INSERTION ARCHITECTURES, issued Nov. 12, 2019, for example.

[0258] The surgical robot **2200** can be incorporated into the robotic surgical system **2100** of FIG. **31** in certain aspects of the present disclosure. The surgical robot **2200** includes one or more robotic arms **2202** each having a tool driver **2217** and a surgical tool **2218** attached thereto. In FIG. **32**, the robotic arms **2202** are attached to adjustable rails **2250** coupled to a patient platform **2260** in the form of a bed. In the surgical robot **2200**, three robotic arms **2202** are attached to the adjustable rail **2250** on a first side of the patient platform **2260**, while two robotic arms **2202** are attached to the adjustable rail **2250** on a second side of the patient platform **2260**, thereby providing a system with bilateral arms. The surgical robot **2200** can also include a controller like the controller **2120** (FIG. **31**), for example, and can be communicatively coupled to a command console, such that a surgeon's inputs at the command console can be implemented by the surgical robot **2200** via the controller.

[0259] FIG. **33** illustrates a perspective view of a tool driver **2300**, which is also referred to herein as an IDM. Various aspects of the tool driver **2300** are further described in U.S. Pat. No. 10,470,830, titled SYSTEM AND METHODS FOR INSTRUMENT BASED INSERTION ARCHITECTURES, issued Nov. 12, 2019, for example.

[0260] The tool driver **2300** can be used with the robotic surgical system **2100** and with the surgical robot **2200**, for example. The tool driver **2300** is configured to attach a surgical tool to a robotic

arm in a manner that allows the surgical tool to be continuously rotated, or “rolled”, about a longitudinal axis of the surgical tool. The tool driver **2300** includes a base **2302** and a surgical tool holder assembly **2304** coupled to the base **2302**. The surgical tool holder assembly **2304** service as tool holder for holding a surgical tool, such as the surgical tool **2118** (FIG. **31**) or the surgical tool **2218** (FIG. **32**).

[0261] The surgical tool holder assembly **2304** further includes an outer housing **2306**, a surgical tool holder **2308**, an attachment interface **2310**, a passage **2312**, and a plurality of torque couplers **2314** that have splines **2318**. The passage **2312** comprises a through-bore that extends from one face of the tool driver **2300** to an opposing face of the tool driver **2300** along the axis **2316**. The tool driver **2300** can be used with a variety of surgical tools, which may include a handle, or housing, and an elongated body, or shaft, and which may be for a laparoscope, an endoscope, or other types of surgical tools. An exemplary surgical tool **2400** is shown in FIG. **34**, for example.

[0262] The base **2302** removably or fixedly mounts the tool driver **2300** to a robotic surgical arm of a robotic surgical system. In FIG. **33**, the base **2302** is fixedly attached to the outer housing **2306** of the surgical tool holder assembly **2304**. In alternative instances, the base **2302** is structured to include a platform, which is adapted to rotatably receive the surgical tool holder **2308** on the face opposite from the attachment interface **2310**. The platform may include a passage aligned with the passage **2312** to receive the elongated body of the surgical tool and, in some instances, an additional elongated body of a second surgical tool mounted coaxially with the first surgical tool. One or more motors can be housed in the base **2302**. For example, the surgical tool holder **2308** can include multiple motors, which are configured to drive, i.e. rotate torque drivers **2314** with a torque and rotary velocity, which can be controlled by the controller, for example.

[0263] The surgical tool holder assembly **2304** is configured to secure a surgical tool to the tool driver **2300** and rotate the surgical tool relative to the base **2302**. Mechanical and electrical connections are provided from the surgical arm to the base **2302** and then to the surgical tool holder assembly **2304** to rotate the surgical tool holder **2308** relative to the outer housing **2306** and to manipulate and/or deliver power and/or signals from the surgical arm to the surgical tool holder **2308** and ultimately to the surgical tool. Signals may include signals for pneumatic pressure, electrical power, electrical signals, and/or optical signals.

[0264] The attachment interface **2310** is a face of the surgical tool holder **2308** that attaches to the surgical tool. The attachment interface **2310** includes a first portion of an attachment mechanism that reciprocally mates with a second portion of the attachment mechanism located on the surgical tool. The attachment interface **2310** is further described in U.S. Pat. No. 10,470,830, titled SYSTEM AND METHODS FOR INSTRUMENT BASED INSERTION ARCHITECTURES, issued Nov. 12, 2019, for example.

[0265] Various tools can attach to the tool driver **2300**, including tools used for laparoscopic, endoscopic and endoluminal surgery. Tools can include tool-based insertion architectures that reduce the reliance on robotic arms for insertion. In other words, insertion of a surgical tool (e.g., towards a surgical site) can be facilitated by the design and architecture of the surgical tool. For example, in some instances, wherein a tool comprises an elongated shaft and a handle, the architecture of the tool enables the elongated shaft to translate longitudinally relative to the handle along an axis of insertion. Various advantages of tool-based insertion architectures are further described in U.S. Pat. No. 10,470,830, titled SYSTEM AND METHODS FOR INSTRUMENT BASED INSERTION ARCHITECTURES, issued Nov. 12, 2019, which is incorporated by reference herein its entirety.

[0266] A surgical tool **2400** having a tool-based insertion architecture is shown in FIG. **34**. Various aspects of the surgical tool **2400** are further described in U.S. Pat. No. 10,470,830, titled SYSTEM AND METHODS FOR INSTRUMENT BASED INSERTION ARCHITECTURES, issued Nov. 12, 2019, for example.

[0267] The surgical tool **2400** enables a translation of the surgical tool **2400** (e.g., translation of its

shaft **2402** and end effector **2412** relative to a tool driver and/or distal end of the robotic arm) along an insertion axis. In such instances, the surgical tool **2400** can be moved along the insertion axis without reliance—or with less reliance—on movement of a robotic arm. The surgical tool **2400** includes an elongated shaft **2402**, an end effector **2412** connected to the shaft **2402**, and a handle **2420**, which may also be referred to as an instrument housing or base, coupled to the shaft **2402**. The elongated shaft **2402** comprises a tubular member having a proximal portion **2404** and a distal portion **2406**. The elongated shaft **2402** includes one or more channels or grooves along its outer surface. The grooves are configured to receive one or more wires or cables **2430** therethrough. The cables **2430** run along an outer surface of the elongated shaft **2402**. In other aspects of the present disclosure, certain cables **2430** can run through the shaft **2402** and may not be exposed. Manipulation of the cables **2430** (e.g., via the tool driver **2300**) results in actuation of the end effector **2412**, for example.

[0268] The end effector **2412** comprises laparoscopic, endoscopic, or endoluminal components, for example, and can be designed to provide an effect to a surgical site. For example, the end effector **2412** can comprise a wrist, grasper, tines, forceps, scissors, clamp, knife, and/or fasteners. Exemplary surgical end effectors are further described herein. The cables **2430** that extend along the grooves on the outer surface of the shaft **2402** can actuate the end effector **2412**. The cables **2430** extend from a proximal portion **2404** of the shaft **2402**, through the handle **2420**, and toward a distal portion **2406** of the shaft **2402**, where they actuate the end effector **2412**.

[0269] The instrument handle **2420** includes an attachment interface **2422** having one or more mechanical inputs **2424**, e.g., receptacles, pulleys or spools, that are designed to be reciprocally mated with one or more torque couplers **2314** (FIG. 33) on the attachment interface **2310** of the tool driver **2300**. The attachment interface **2422** is capable of attaching to the tool driver **2300** via a front-mount, back-mount and/or top mount. When physically connected, latched, and/or coupled together, the mated mechanical inputs **2424** of the instrument handle **2420** may share axes of rotation with the torque couplers **2314** of the tool driver **2300**, thereby allowing the transfer of torque from the motors in the tool driver **2300** to the instrument handle **2420**. In some instances, the torque couplers **2314** may comprise splines that are designed to mate with receptacles on the mechanical inputs. Cables **2430** that actuate the end effector **2412** engage the receptacles, pulleys, or spools of the handle **2420**, such that the transfer of torque from the tool driver **2300** to the instrument handle **2420** results in actuation of the end effector **2412**.

[0270] The surgical tool **2400** can include a first actuation mechanism **2450** (FIG. 35) that controls actuation of the end effector **2412**. The tool **2400** can also include a second actuation mechanism that enables the shaft **2402** to translate relative to the handle **2420** along an axis of insertion A. In various instances, the first actuation mechanism **2450** can be decoupled from the second actuation mechanism, such that actuation of the end effector **2412** is not affected by the translation of the shaft **2402**, and vice versa.

[0271] In various instances, an actuation mechanism can include one or more pulleys mounted on a rotary axis to change relative cable length and, in other instances, mounting a pulley on a lever, gear or track-based system to adjust its location. Additionally or alternatively, ball spline rotary shafts that travel down a length of a tool can also be used to transmit forces in a mechanically-remote way. Various actuation mechanisms are further described in U.S. Pat. No. 10,470,830, titled SYSTEM AND METHODS FOR INSTRUMENT BASED INSERTION ARCHITECTURES, issued Nov. 12, 2019, for example.

[0272] Referring to FIG. 35, the first actuation mechanism **2450** can provide N+1 wrist motion, wherein N is the number of degrees of freedom provided by N+1 cables. The first actuation mechanism **2450** for actuating the end effector **2412** comprises at least one cable segment **2430** that extends through at least one set of pulleys. In the actuation mechanism of FIG. 35, a first cable, or first cable segment, extends through pulley members **2450a**, **2450b**, **2450c**, while a second cable, or second cable segment, extends through pulley members **2450d**, **2450e**, **2450f**. The cables **2430**

are grounded at or near the proximal end **2404** (FIG. **34**) of the shaft **2402**, then extends through the set of pulleys **2450a**, **2450b**, **2450c**, **2450d**, **2450e**, **2450f** located within the housing **2420**, before terminating at or near the end effector **2412**. Cable total path length is kept constant by grounding each cable **2430** at or near the proximal end **2404** of the shaft **2402**, and relative length changes are made by moving one or more pulleys (e.g., pulley members **2450b** and **2450e**) relative to each other as indicated by the arrows in FIG. **35**, thereby enabling actuation of the end effector **2412**. In some instances, the pulleys can be moved via linear or rotary motion of corresponding mechanical inputs **2424**. The first actuation mechanism **2450** can permit free movement of the instrument shaft **2402** relative to the actuation pulleys **2450a**, **2450b**, **2450c**, **2450d**, **2450e**, **2450f** thereby allowing an additional cable to be included to permit insertion and retraction of the instrument shaft **1202** at the same time as end effector **1212** actuation.

[0273] Robotic surgical tools having tool-based insertion architecture, such as the surgical tool **2400** shown in FIG. **34**, for example, may be subjected to high loads during certain surgical actuations or surgical functions. For example, a surgical tool that is used to clamp, cut, staple and/or fasten tissue may be subjected to high clamping and firing loads when clamping certain types of tissue and/or when firing fasteners. In certain instances, the clamping and firing loads on a surgical tool can exceed 300 lbf, for example. The tool-based insertion architecture in the housing of such a surgical tool should be configured to withstand such loads. In certain instances, a lead screw may be used to translate the tool housing along the elongate shaft, which may withstand the high clamping and firing loads. However, a lead screw arrangement may be bulky and/or costly in certain instances.

[0274] Alternatively, a translation mechanism that is lightweight, nimble, and/or less expensive than a lead screw may be advantageous in certain instances. Such a translation mechanism can be sufficiently robust to withstand significant forces during use, such as the high forces transmitted during clamping and/or firing, for example. For example, a pulley and cable arrangement can be used in combination with one or more pivoting locks, which are configured to resist the high clamping and/or firing forces.

[0275] In one aspect of the present disclosure, a surgical tool can include a surgical end effector comprising opposing jaws, an elongate shaft extending distally to the surgical end effector, and a housing defining a passage therethrough, wherein the elongate shaft extends through the passage. The surgical tool can also include an actuation mechanism configured to selectively move the housing along the elongate shaft relative to the surgical end effector, wherein the actuation mechanism comprises a pulley, a cable engaged with the pulley and a lock arrangement configured to releasably lock the housing relative to the elongate shaft. The lock arrangement can include a washer positioned around the elongate shaft, wherein the cable is engaged with the washer, and wherein the washer is configured to pivot relative to the elongate shaft between a locked orientation and an unlocked orientation. Moreover, an actuation of the pulley can apply a tension to the cable to pivot the washer to the unlocked orientation.

[0276] In various instances, such a lock arrangement can also include a second washer positioned around the elongate shaft, wherein an opposite end of the cable is engaged with the second washer, and wherein the second washer is configured to pivot relative to the elongate shaft between a locked orientation and an unlocked orientation.

[0277] In certain instances, the foregoing arrangement can securely ground translation of the surgical tool housing along the elongate shaft of the surgical tool without requiring a high mechanical advantage linear motion, such as the linear motion achieved with a lead screw, for example. Moreover, the actuation mechanism for effecting the tool-based translation can be nimble and lightweight, for example.

[0278] Referring now to FIG. **36**, a surgical tool **2500** is shown. The surgical tool **2500** includes a housing **2520**, which is also referred to herein as a handle or tool base, an elongate shaft **2530** slidably positioned through a portion of the housing **2520**, and a distal end effector **2512**. The

housing **2520** can be similar to the housing **2420** (FIG. **34**) in many aspects. For example, the housing **2520** can include an attachment interface having one or more mechanical inputs, such as receptacles, pulleys, and/or spools, that are designed to reciprocally mate with one or more torque couplers **2314** (FIG. **33**) on the attachment interface **2310** of the tool driver **2300** and to receive actuation motion(s) from a robotic system. One or more actuation mechanisms, such as the actuation mechanism **2550**, for example, can be positioned in the housing **2520** and configured to effect one or more surgical actuations, such as articulation, clamping, and/or firing of the end effector **2512**.

[0279] Translation of the end effector **2512** can be achieved with the actuation mechanism **2570**, which includes a pulley arrangement **2572** and a lock arrangement **2584**. The pulley arrangement **2572** includes a pulley wheel **2574**, a capstan **2576**, and a cable **2578** extending from a first end **2580** to a second end **2582**. The cable **2578** terminates at the first end **2580** and at the second end **2582**. The first end **2580** and the second end **2582** are mounted to features in the housing **2520**, which are further described herein. The cable **2578** in FIG. **36** is not a continuous loop. Rather, the cable **2578** comprises a piece of cable with ends **2580**, **2582** that are configured to move relative to each other in certain instances to change the length of the cable loop. An actuation of the pulley arrangement **2572** is configured to apply tension to the cable **2578** to exert a pulling force on the housing **2520** along the length of the elongate shaft **2530**. For example, rotation of the capstan **2576**, applies tension to the cable **2578**. When the actuation mechanism **2570** is unlocked, as further described herein, the pulling force on the cable **2578** is configured to pull the housing **2520** along the length of the elongate shaft **2530**, such that the end effector **2512** is displaced along the longitudinal axis A of the surgical tool **2500**.

[0280] The elongate shaft **2530** is grounded at its proximal end **2532** to a component **2502** of the surgical robot, such as a distal end of a robotic arm, which is similar in many aspects to the robotic arm **2102** (FIG. **31**) and the robotic arm **2202** (FIG. **32**), for example. Similarly, the distal end **2534** of the elongate shaft **2530** is grounded to a distal portion of the surgical tool **2500**. More specifically, the distal end **2534** is fixed to a bracket **2514** mounted to the end effector **2512**. The housing **2520** is configured to move along the elongate shaft **2530** between the component **2502** and the bracket **2514**.

[0281] The actuation mechanism **2570** also includes the lock arrangement **2584** in combination with the pulley arrangement **2572**. The lock arrangement **2584** is depicted schematically in FIG. **36**. The lock arrangement **2584** is configured to releasably lock the housing **2520** to the elongate shaft **2530** such that forces applied to the elongate shaft **2530** during certain surgical actuations and/or functions (e.g. clamping and/or firing) do not effect longitudinal displacement of the housing **2520** relative to the elongate shaft **2530** and do not move the end effector **2512** along the insertion axis A.

[0282] Generally, the end effector **2512** would not be advanced or retracted along the insertion axis, or longitudinal axis of the elongate shaft **2530**, during a clamping and/or firing actuation. More specifically, while tissue is being clamped, cut, and/or stapled, for example, the longitudinal position of the end effector **2512** is often fixed, which may avoid damaging and/or traumatizing the tissue in certain instances. To this end, the lock arrangement **2584** can be configured to lock the longitudinal position of the housing **2520** on the elongate shaft **2530** during a clamping and/or firing actuation. When in the locked configuration, any forces transmitted between the housing **2520** and the shaft **2530** can be resisted by the lock arrangement **2584** in order to hold the end effector **2512** stationary relative to the tissue being clamped, transected, and/or stapled, for example.

[0283] Referring now to FIG. **37**, a surgical tool **2600** is shown. Portions of the surgical tool **2600** are removed from FIG. **37** for clarity. For example, portions of a housing **2620** are removed from FIG. **37**. The surgical tool **2600** can be similar in many aspects to the surgical tool **2500**. For example, the surgical tool **2600** includes a housing **2620**, which is also referred to herein as a



handle or tool base, an elongate shaft **2630** slidably positioned through the housing **2620**, and a distal end effector **2612**. The housing **2620** can be similar to the housing **2420** (FIG. **34**) in many aspects. For example, the housing **2620** can include an attachment interface having one or more mechanical inputs, such as receptacles, pulleys, and/or spools, that are designed to reciprocally mate with one or more torque couplers **2314** (FIG. **33**) on the attachment interface **2310** of the tool driver **2300**, which are configured to receive actuation motion from the robotic system. One or more actuation mechanisms in the housing **2620** can be configured to effect one or more surgical actuations, such as articulation, clamping, and/or firing of the end effector **2612**, for example. The housing **2620** can be built around the elongate shaft **2630**, for example.

[0284] The elongate shaft **2630** extends from the surgical robot to the end effector **2612**. For example, a proximal end **2632** of the elongate shaft **2630** is mounted to a robotic arm **2602** of a robotic surgical system, and a distal end **2634** of the elongate shaft **2630** is mounted to a distal flange **2614** of the end effector **2612**. The housing **2620** is slidably positioned around the elongate shaft **2630** between the proximal end **2632** and the distal end **2634**.

[0285] The surgical tool **2600** includes an actuation mechanism **2670** including a pulley arrangement **2672** and a lock arrangement **2684**. The pulley arrangement **2672** is similar in many aspects to the pulley arrangement **2572** (FIG. **36**) and includes a pulley **2674** mounted to the robotic arm **2602**, a capstan **2676** mounted to the flange **2614**, and a cable **2678** engaged with the pulley **2674** and the capstan **2676** and extending therebetween. The cable **2678** is mounted to the housing **2620** via the lock arrangement **2684**. Moreover, the pulley arrangement **2672** and, more specifically, the cable **2678** thereof, is configured to move the lock arrangement **2684** between the unlocked configuration and the locked configuration.

[0286] The lock arrangement **2684** is configured to releasably lock the housing **2620** relative to the elongate shaft **2630**. The lock arrangement **2684** includes a first lock **2686** and a second lock **2688**. The locks **2686**, **2688** are washer-shaped and have a central bore or through-hole, which is configured to receive the elongate shaft **2630** therethrough. In other words, the first lock **2686** and the second lock **2688** are positioned around the elongate shaft **2630** within the housing **2620**. A first end **2636** of the cable **2678** is engaged with the first lock **2686** and a second end **2638** of the cable **2678** is engaged with the second lock **2688**. The locks **2686**, **2688** are configured to pivot relative to the elongate shaft **2630** as they move between a locked orientation and an unlocked orientation. More specifically, an actuation of the pulley arrangement **2672**, e.g. rotation of the capstan **2676**, is configured to apply a tension to the cable **2678** to pull the ends **2636**, **2638** and pivot the locks **2686**, **2688** to the unlocked configuration.

[0287] In the locked configuration, the first lock **2686** and the second lock **2688** are oriented at an oblique angle relative to a longitudinal axis defined by the elongate shaft **2630**. More specifically, an axis extending through the central bore in each lock **2686**, **2688** is obliquely-oriented relative to the longitudinal axis of the elongate shaft **2630**. In the unlocked configuration, the first lock **2686** and the second lock **2688** are configured to pivot toward a parallel orientation, in which the locks **2686**, **2688** are parallel, or nearly parallel with each other. As the locks **2686**, **2688** pivot toward the unlocked configuration, the axes extending through the central bore in each lock **2686**, **2688** are configured to move into axial alignment with the longitudinal axis of the elongate shaft **2630**. The first lock **2686** and the second lock **2688** can be referred to as screen door locks or, collectively, as opposing screen door locks, in certain instances.

[0288] The lock arrangement **2684** includes a spring **2690** positioned between the first lock **2686** and the second lock **2688**. The spring **2690** biases a portion of the first lock **2686** away from a portion of the second lock **2688**, such that the locks **2686**, **2688** pivot into an angled orientation relative to the elongate shaft **2630**. In various instances, the tension applied by the actuation of the pulley arrangement **2672** is configured to overcome the biasing force of the spring **2690** to move the first lock **2686** and the second lock **2688** from their locked configurations to their unlocked configurations and, thus, to unlock the actuation mechanism **2670** and the lock arrangement **2684**.

thereof. In such an arrangement, the tension in the cable **2678** first overcomes the lock arrangement **2684** and then pulls on the elongate shaft **2630** to achieve a displacement along the insertion axis A.

[0289] Referring still to FIG. **37**, the housing **2620** includes a body portion **2622** having an internal cavity **2626**, which receives at least a portion of the locks **2686**, **2688** and a portion of the elongate shaft **2630**. The body portion **2622** includes an internal wall **2624** that defines a portion of the internal cavity. The actuation of the pulley arrangement **2672** is configured to push a portion of the first lock **2686** against the internal wall **2624** to draw or pull the housing **2620** along the elongate shaft **2630**. In various instances, when the tension in the cable **2678** is relieved, the spring **2690** is configured to return the locks **2686**, **2688** to their locked configurations, in which clamping and firing loads directed to the elongate shaft **2630** are resisted by the lock arrangement **2684**.

[0290] In various instances, the lock arrangement **2684** can be incorporated into the surgical tool **2500** (FIG. **36**). For example, the lock arrangement **2584** (FIG. **36**) can include the lock arrangement **2684** or components thereof.

[0291] Referring now to a flow chart in FIG. **38**, a transection operation **2800** is depicted. Various surgical tools comprising end effectors for transecting tissue are described herein and these various surgical tools and/or robotic surgical systems therefor can utilize the transection operation **2800** to cut tissue and/or fire fasteners. The reader will understand that various control circuits can be utilized to implement the transection operation **2800**, including a control circuit, controller, computer processor located in the controller **2120** (FIG. **31**) and/or in the control tower **130** (FIG. **1**), for example.

[0292] An example control circuit **2728** for implementing the transection operation **2800** (FIG. **38**) is shown in FIG. **39**, for example. The control circuit **2728** includes a processor **2740** in signal communication with a memory **2742**, a communication device **2744**, a drive system **2752**, and inputs **2780**, **2782**. The processor **2740** includes a clock, or timer, **2741**, which is configured to time various stages or sub-stages in the transection operation **2800** (FIG. **38**), as further described herein.

[0293] The memory **2742** stores program instructions, which are configured to implement various surgical operations, including a clamping operation **2840** and the transection operation **2800** (FIG. **38**) or various stages thereof. The memory **2742** also stores various threshold parameters related to transitioning between the stages in the transection operation **2800**, such as bailout threshold parameters, for example. Additional parameters stored in the memory **2742** are further described herein.

[0294] The communication device **2744** is configured to convey information from the processor **2740** to external devices, such as a graphical user interface (GUI) **2790**, for example. Various outputs to the GUI **2790** are further described herein.

[0295] The drive system **2752** includes a motor **2758**, an input drive **2760** coupled to the motor **2758**, a torque sensor **2732**, a rotary encoder/position sensor **2736**, and a velocity sensor **2738**. The drive system **2752** corresponds to a rotary drive in a tool holder or tool drive, as further described herein. The drive system **2752** is configured to provide rotary input to the surgical tool to effect a surgical function. More specifically, the drive system **2752** corresponds to a firing drive system, which is configured to effect a firing motion of the surgical tool. In various instances, the input drive **2760** can correspond to one of the torque couplers **2314** in FIG. **33**. For example, output from the motor **2758** can be transferred to a torque coupler **2314** and, ultimately, to a surgical tool to effect the surgical function. More specifically, one of the torque couplers **2314** is configured to transfer output motions from the firing motor **2758** to the surgical tool to effect a firing stroke. The torque sensor **2732** can detect the torque from the firing motor **2758** and/or input drive **2760** coupled thereto, for example, the position sensor **2736** can detect the rotary position of the input drive **2760**, for example, and the velocity sensor **2738** can detect the rotary velocity of the input drive **2760**, for example.

[0296] The control circuit **2728** also includes inputs **2780**, **2782**, which are configured to convey signals to the processor **2740** indicative of inputs from the surgeon and/or clinician positioned at the command console. In various instances, the input **2780** can correspond to the active/inactive status of a transection input, such as a transection pedal at the command console, for example, and the input **2782** can correspond to the active/inactive status of a clamping input, such as a clamping pedal at the command console, for example.

[0297] Referring again to FIG. **38**, the transection operation **2800** includes bailout detection, graphical user interface (GUI) prompts and/or alerts, stall detection, and various safety faults, as further described herein. The transection operation **2800** can utilize velocity, torque, and/or position sensors to transition between states and progress through the transition operation **2800**. Various sensors in the robot and/or surgical tool can be configured to detect the velocity, torque, and/or position of the input components (e.g. input actuators and/or pedals), rotary drive members (e.g. motors and/or rotary drives in the tool drive and/or the tool base), and of output components (e.g. the firing member and/or cutting edge).

[0298] In various instances, the transection operation **2800** may follow a clamping step or clamping operation **2840**. During a normal, uninterrupted transection, the transection operation **2800** can proceed from the clamping operation **2840**, to an Outset State **2802**, to a Pre-Lockout Region State **2804**, to a Lockout Region State **2808**, to a Transection State **2816**, to a Transection-Completed State **2818**, to a Retraction State **2830**, and finally to a Transection-Ended state **2834**. However, the control circuit is configured to monitor various parameters during the transection operation **2800** and certain parameters at certain stages may trigger a variation from the normal, uninterrupted transection operation **2800**. For example, torque and/or velocity of the firing member can cause the operation **2800** to detour from the above-summarized flow between the Outset State **2802** and the Transection-Ended state **2834**. Additional states in the operation **2800** can include a Pre-Lockout Pause State **2806**, a Lockout Pause State **2810**, a Lockout-Detected State **2812**, a Lockout-Damaged State **2814**, a Transection-Canceled State **2820**, a Transection Pause State **2822**, a Damaged State **2824**, a Transection-Stalled State **2826**, a Stall Limit State **2828**, a Retraction-Stalled State **2832**, a Bailout-Attempt State **2836**, and/or a Non-Recoverable State **2838**, for example.

[0299] In various instances, the transection operation **2800** relates to a clinician's activation of the transection input (e.g. a pedal) to transection or cut the tissue clamped between the end effector jaws. Cutting the tissue generally relies on extending a knife or cutting edge distally through clamped tissue. In various aspects of the present disclosure, the transection of tissue is accompanied with nearly simultaneous stapling of tissue. For example, the cutting edge can sever tissue directly following the stapling of the tissue.

[0300] In various instances, when a surgical tool is mounted to a robotic arm, the surgical robot can initially implement a homing operation, in which the angular position of the torque couplers and/or rotary inputs are measured and recorded in the memory of the control circuit (e.g. memory **2742**) at the various limits or “bumps” in the range of motion of the surgical tool. Homing operations are further described herein and in U.S. patent application Ser. No. 16/553,725, titled ARTICULATING INCLUDING ANTAGONISTIC CONTROLS FOR ARTICULATION AND CALIBRATION, filed Aug. 28, 2019, for example.

[0301] After homing and clamping, the transection operation **2800** can commence with entry into the Outset State **2802**. Upon entering the Outset State **2802**, the control circuit (e.g. the control circuit **2728**) can check Condition A, which corresponds to the disablement value (DV) of future firings by the surgical system and/or surgical tool. Condition A is satisfied when the DV stored in the memory (e.g. the memory **2742**) is false/negative, which indicates that future firings of the surgical system and/or surgical tool have not been disabled. If Condition A is satisfied, the transection operation **2800** proceeds from the Outset State **2802** to the Pre-Lockout Region State **2804**. Alternatively, if the DV is true/positive such that Condition A is not satisfied, future firings

have been disabled and the operation **2800** does not proceed from the Outset State **2802**. In various instances, if the DV is true/positive, the control circuit can convey the disablement state to a user via the GUI (e.g. the GUI **2790**), for example. In various instances, the GUI may be updated throughout the operation **2800**. For example, a firing member and/or cutting edge extension function can send updated signals to the GUI throughout the operation **2800** regarding the position and/or status of the cutting edge (e.g. before a lockout region, in the lockout region, in a transection region, at a terminal transection position, and so on).

[0302] Upon entry to the Pre-Lockout Region State **2804**, a firing motor angle (FMA) from a position sensor (e.g. the position sensor **2736**), a firing motor velocity (FMV) from a velocity sensor (e.g. the velocity sensor **2738**), and a firing motor torque (FMT) from a torque sensor (e.g. the torque sensor **2732**) are set or targeted by the control circuit (e.g. the control circuit **2728**). The target FMA corresponds to a terminal transection angle (TTA) at which the firing member has reached a terminal or distal-most position within the end effector. The target FMV corresponds to a pre-lockout region velocity stored in the memory (e.g. the memory **2742**). The motor associated with the firing actuation (e.g. the firing motor **2758**) is configured to deliver the target FMT. In the Pre-Lockout Region State **2804**, the target FMT corresponds to a pre-lockout region operating torque stored in the memory (e.g. the memory **2742**). In the Pre-Lockout Region State **2804**, if the FMA from the position sensor (e.g. the position sensor **2736**) exceeds a threshold non-opening angle associated with a firing member position that prevents unclamping or opening of the jaws, then a non-opening code (NOC) is set to positive/true. The threshold non-opening angle can be recorded during the homing operation, for example, and stored in the memory (e.g. the memory **2742**). The NOC corresponds to an inability to open the jaws. In various instances, the NOC can remain positive/true until the operation **2800** proceeds to the Transection-Ended State **2834**.

[0303] In the Pre-Lockout Region State **2804**, the control circuit (e.g. the control circuit **2728**) can check for Conditions B and C. Condition B corresponds to the FMA from the position sensor (e.g. the position sensor **2736**) being equal to or greater than a minimum cartridge lockout angle, which is stored in the memory (e.g. memory **2742**). In such instances, the FMA can indicate that the firing member has been extended into the lockout region. If Condition B is satisfied during the Pre-Lockout Region State **2804**, then the operation **2800** proceeds to the Lockout Region State **2808**, which is further described herein.

[0304] Condition C corresponds to the inactive status of a transection pedal (e.g. the input **2780**). If Condition C is satisfied during the Pre-Lockout Region State **2804**, i.e. the transection pedal becomes inactive, then the operation **2800** proceeds to a Pre-Lockout Pause State **2806**, which is further described herein.

[0305] During the normal, uninterrupted transection, the firing member can be advanced from the pre-lockout region into the lockout region (e.g. satisfying Condition B) without incidence. As a result, the operation **2800** proceeds to Lockout Region State **2808** during which the firing member can traverse the cartridge lockout, for example. The lockout region can correspond to the region in the staple cartridge in which an empty, spent, and/or missing cartridge lockout is positioned. In various instances, the cartridge lockout comprises a mechanical feature in a proximal portion of the end effector and/or cartridge which prevents the cutting edge on the firing member from being advanced distally into tissue when the cartridge (or absence thereof) would not adequately fasten the to-be-transected tissue.

[0306] Upon entry to the Lockout Region State **2808**, the FMA, FMV, and FMT are set or targeted by the control circuit (e.g. the control circuit **2728**). The target FMA can again correspond to the terminal transection angle (TTA). The target FMV corresponds to a lockout region velocity stored in the memory (e.g. memory **2742**), which may be different from the pre-lockout region velocity. Moreover, the target FMT corresponds to a lockout region operating torque also stored in the memory (e.g. memory **2742**). In the Lockout Region State **2808**, if the FMA from a position sensor (e.g. the position sensor **2736**) exceeds the threshold non-opening angle associated with a position

that prevents unclamping or opening of the jaws, then the NOC (associated with an inability to open the jaws) is set to positive/true.

[0307] In the Lockout Region State **2808**, the control circuit (e.g. the control circuit **2728**) can check for Conditions G, H, I, and J. Condition G corresponds to the FMA from the position sensor (e.g. the position sensor **2736**) being equal to or greater than a maximum cartridge lockout angle, which can be determined during a homing operation, for example, and stored in the memory (e.g. memory **2742**). In such instances, the firing motor angle can indicate that the firing member has been extended past the lockout region. If Condition G is satisfied during the Lockout Region State **2808**, then the operation **2800** proceeds to the Transection State **2816**, which is further described herein.

[0308] Condition H corresponds to (A) the FMT from the torque sensor (e.g. the torque sensor **2732**) being equal to or greater than the lockout region operating torque and (B) the FMV from a velocity sensor (e.g. the velocity sensor **2738**) being equal to or less than the lockout region velocity for a period of time exceeding a lockout threshold time stored in the memory (e.g. memory **2742**). For example, a high torque from the motor and applied to the firing member may result in minimal or no displacement of the firing member when the lockout is obstructing the firing path in order to prevent transection of unstapled tissue, for example. Condition H indicates that a cartridge lockout has occurred. If Condition H is satisfied during the Lockout Region State **2808**, then the operation **2800** proceeds to the Lockout-Detected State **2812**, which is further described herein.

[0309] Condition I corresponds to the FMT from the torque sensor (e.g. the torque sensor **2732**) being equal to or greater than a damaged-lockout threshold torque, which is stored in the memory (e.g. the memory **2742**) and can indicate that the cartridge lockout has been damaged. In various instances, the damaged-lockout threshold torque can be greater than the lockout region operating torque. If Condition I is satisfied during the Lockout Region State **2808**, then the operation **2800** proceeds to the Lockout-Damaged State **2814**.

[0310] Condition J corresponds to the inactive status of the transection pedal (e.g. the input **2780**). If Condition J is satisfied during the Lockout Region State **2808**, i.e. the transection pedal becomes inactive, then the transection operation **2800** proceeds to the Lockout Pause State **2810**, which is further described herein.

[0311] During the normal, uninterrupted transection, the firing member can be advanced from the lockout region into a transection region (satisfying condition G) without incidence. As a result, the operation **2800** proceeds to the Transection State **2816**. Upon entry to the Transection State **2816**, a transection count stored in the memory of the control circuit (e.g. the memory **2742** of the control circuit **2728**) is incremented up by one. Moreover, the FMA, FMV, and FMT for the Transection State **2816** are set or targeted. The target FMA can again correspond to the terminal transection angle (TTA) and the target FMV can correspond to a transection region velocity stored in the memory (e.g. the memory **2742**). In various instances, the transection region velocity can be different than the pre-lockout region velocity and/or the lockout region velocity. The target FMT corresponds to a transection operating torque stored in the memory (e.g. the memory **2742**).

[0312] In the Transection State **2816**, the control circuit (e.g. the control circuit **2728**) can check for Conditions N, O, P, Q and R. Condition N corresponds to the inactive status of the transection pedal (e.g. the input **2780**). If Condition N is satisfied during the Transection State **2816**, i.e. the transection pedal becomes inactive, then the operation **2800** proceeds to a Transection Pause State **2822**, which is further described herein.

[0313] Condition O corresponds to the FMT from the torque sensor (e.g. the torque sensor **2732**) being equal to or greater than a maximum transection torque, which is stored in the memory (e.g. the memory **2742**) and indicates that the firing member (e.g. knife/cutting edge) has been subjected to high torques during the Transection State **2816** and may be damaged. If Condition O is satisfied during the Transection State **2816**, the operation **2800** proceeds to the Damaged State **2824**, which is further described herein.

[0314] Condition P corresponds to both (A) the FMT from the torque sensor (e.g. the torque sensor **2732**) being equal to or greater than the transection operating torque and (B) the FMV from a velocity sensor (e.g. the velocity sensor **2738**) being equal to or below a stall threshold velocity with both (A) and (B) being true for a time period exceeding a stall threshold time (STT) stored in the memory (e.g. the memory **2742**). Condition P can indicate that the firing member, or knife, has stalled during the Transection State **2816**. Condition Q corresponds to the number of firing member stalls being equal to or less than a maximum number of firing member stalls, which is stored in the memory (e.g. the memory **2742**). If Conditions P and Q are satisfied, the operation **2800** proceeds to the Transection-Stalled State **2826**, which is further described herein. If Condition P is satisfied, but Condition Q is not satisfied, the operation **2800** proceeds to a Stall Limit State **2828**, which is further described herein and indicates that the surgical device has exceeded the stall limit.

[0315] Condition R corresponds to the FMA from the position sensor (e.g. the position sensor **2736**) achieving the terminal transection angle (TTA), which indicates the firing member has traveled to the end of the transection or cutline, for example. If Condition R is satisfied, the operation **2800** proceeds to the Transection-Completed State **2818**.

[0316] During the normal, uninterrupted transection, the firing member can be advanced to the end of the transection region (satisfying condition R) without incidence. As a result, the operation **2800** proceeds to the Transection-Completed State **2818**. Upon entry to the Transection-Completed State **2818**, the control circuit (e.g. the control circuit **2728**) is configured to issue GUI feedback to the GUI (e.g. the GUI **2790**) indicating the transection or firing stroke is complete, thus, ready to transition to the Retraction State **2830**.

[0317] During the normal, uninterrupted transection, the firing member proceeds from the Transection-Completed State **2818** to the Retraction State **2830** without incidence. Upon entry to the Retraction State **2830**, a FMA, FMV, FMT are set or targeted by the control circuit (e.g. the control circuit **2728**). The target FMA can correspond to an after-homing firing angle, which is stored in the memory (e.g. the memory **2742**), and the target FMV can correspond to a retraction velocity, which is also stored in the memory (e.g. the memory **2742**). The target FMT can correspond to a retraction operating torque stored in the memory (e.g. the memory **2742**). In the retraction state **2830**, the control circuit (e.g. the control circuit **2728**) can check for Conditions Y and Z.

[0318] Condition Y corresponds to both (A) the FMT from the torque sensor (e.g. the torque sensor **2732**) being equal to or greater than the retraction operating torque and (B) the FMV from a velocity sensor (e.g. the velocity sensor **2738**) being equal to or less than the retraction velocity with both (A) and (B) being true for a time period equal to or greater than the stall threshold time (STT) stored in the memory (e.g. the memory **2742**). Condition Y indicates that the firing member has stalled during retraction. If Condition Y is satisfied during the retraction state **2830**, the operation **2800** proceeds to the Retraction-Stalled State **2832**.

[0319] Condition Z corresponds to the FMA from the position sensor (e.g. the position sensor **2736**) achieving the after-homing firing angle. Condition Z can indicate that the firing member has returned to its after-homing, pre-firing-stroke angle. If Condition Z is satisfied during the Retraction State **2830**, the operation **2800** proceeds to the Transection-Ended State **2834**.

[0320] Upon entry to the Transection-Ended State **2834**, the NOC (associated with the inability to open the jaws) stored in the memory (e.g. the memory **2742**) is set to negative/false, which indicates that the firing member has been sufficiently retracted to permit opening or unclamping of the jaws. The operation **2800** then proceeds to the Clamping Operation **2840**.

[0321] In various instances, the operation **2800** can detour from the Pre-Lockout Region State **2804** to the Pre-Lockout Pause State **2806**. From the Pre-Lockout Pause State **2806**, the operation **2800** may return to the Pre-Lockout Pause State **2806**, or may proceed to the Transection-Cancelled State **2020**, or the Bailout Attempt State **2036**. Upon entry to the Pre-Lockout Pause State **2806**, the control circuit (e.g. the control circuit **2728**) is configured to store the FMA from the position

sensor (e.g. the position sensor **2736**), which corresponds to the pre-lockout pause angle. The control circuit is configured to target the pre-lockout pause angle during the Pre-Lockout Pause State **2806**. For example, the pre-lockout pause angle can be held or maintained during the Pre-Lockout Pause State **2806**.

[0322] In the Pre-Lockout Pause State **2806**, the control circuit (e.g. the control circuit **2728**) can check for Conditions D, E, and F. Condition D corresponds to the active status of the transection pedal (e.g. the input **2780**). If Condition D is satisfied during the Pre-Lockout Pause State **2806**, i.e. the transection pedal becomes active, then the operation **2800** returns to the Pre-Lockout Region State **2804**, which is further described herein.

[0323] Condition E corresponds to the active status of the clamping pedal (e.g. the input **2782**). If Condition E is satisfied during the Pre-Lockout Pause State **2806**, i.e. the clamping pedal becomes active, then the operation **2800** proceeds to the Transection-Canceled State **2820**, which is further described herein.

[0324] Condition F corresponds to both (A) the FMT from a torque sensor (e.g. the torque sensor **2732**) being equal to or greater than a bailout detection torque and (B) the FMV from a velocity sensor (e.g. the velocity sensor **2738**) being equal to or less than a bailout detection velocity with both (A) and (B) being true for a time period equal to or greater than a bailout detection time stored in the memory (e.g. the memory **2742**). Condition F can indicate a surgeon or clinician is attempting and/or effecting a bailout step while the firing member moves through the pre-lockout region. For example, during a surgical procedure, the surgeon or clinician can manually manipulate the firing member via a bailout lever or actuator on the housing of the surgical tool, which may involve decoupling the firing member from the firing motor and retracting the firing member manually, for example. If Condition F is satisfied during the Pre-Lockout Pause State **2806**, then the transection operation **2800** proceeds to the Bailout-Attempt State **2836**, which is further described herein.

[0325] In various instances, the operation **2800** can detour from the Lockout Region State **2808** to the Lockout Pause State **2810**. From the Lockout Pause State **2810**, the operation **2800** may return to the Lockout Region State **2808**, or may proceed to the Transection-Canceled State **2020** or the Bailout Attempt State **2036**. Upon entry to the Lockout Pause State **2810**, the control circuit (e.g. the control circuit **2728**) is configured to store the FMA, which corresponds to the lockout pause angle. The control circuit is configured to target the lockout pause angle during the Lockout Pause State **2810**. For example, the FMA can be held or maintained during the Lockout Pause State **2810**.

[0326] In the Lockout Pause State **2810**, the control circuit (e.g. the control circuit **2728**) can check for Conditions K, L, and M. Condition K corresponds to the active status of the transection pedal (e.g. the input **2780**). If Condition K is satisfied during the Lockout Pause State **2810**, i.e. the transection pedal becomes active, then the operation **2800** returns to the Lockout Region State **2808**, which is further described herein.

[0327] Condition L corresponds to the active status of the clamping pedal (e.g. the input **2782**). If Condition L is satisfied during the Lockout Pause State **2810**, i.e. the clamping pedal becomes active, then the operation **2800** proceeds to the Transection-Canceled State **2820**, which is further described herein.

[0328] Condition M corresponds to both (A) the FMT from the torque sensor (e.g. the torque sensor **2732**) being equal to or greater than the bailout detection torque and (B) the FMV from a velocity sensor (e.g. the velocity sensor **2738**) being equal to or less than the bailout detection velocity with both (A) and (B) being true for a time period equal to or greater than the bailout detection time. The bailout detection torque, bailout detection velocity, and bailout detection time are the same threshold values in the Pre-Lockout Pause State **2806**. For example, Condition M can be the same as Condition F. In other instances, different bailout threshold values can apply during the Pre-Lockout Pause State **2806** and the Lockout Pause State **2810**. Condition M can indicate a surgeon or clinician is attempting and/or effecting a bailout step while the firing member moves

through the lockout region. For example, during a surgical procedure, the surgeon or clinician can manually manipulate the firing member, which may involve decoupling the firing member from the firing motor and retracting the firing member manually, for example. If Condition M is satisfied during the Lockout Pause State **2810**, then the transection operation **2800** proceeds to the Bailout-Attempt State **2836**, which is further described herein.

[0329] In various instances, the operation **2800** can detour from the Lockout Region State **2808** to the Lockout-Detected State **2812** and, then, to the Retraction State **2830**. Upon entry to the Lockout-Detected State **2812**, the control circuit (e.g. the control circuit **2728**) is configured to convey determination of the lockout and the locked-out state to a clinician via the GUI (e.g. the GUI **2790**), for example. For example, the control circuit can issue an error message informing the clinician that a cartridge is missing and/or that the installed cartridge is empty/spent. From the Lockout-Detected State **2812**, the operation **2800** can proceed to the Retraction State **2830**, which is further described herein.

[0330] In various instances, the operation **2800** can detour from the Lockout Region State **2808** to the Lockout-Damaged State **2814** and, then, to the Retraction State **2830**. Upon entry to the Lockout-Damaged State **2814**, the control circuit (e.g. the control circuit **2728**) is configured to convey a message to the clinician indicating that damage has been detected and the surgical tool is likely damaged or otherwise inoperable. For example, the control circuit can issue an error message via the GUI (e.g. the GUI **2790**). Moreover, the control circuit can update the DV to true/positive, which indicates that future firings of the surgical system and/or surgical tool have been disabled. As further described herein, when the DV is true/positive, Condition A is not satisfied and a subsequent operation **2800** would not proceed from the Outset State **2802**. From the Lockout-Damaged State **2814**, the operation **2800** can proceed to the Retraction State **2830**, with is further described herein.

[0331] In various instances, the operation **2800** can detour from various states to the Transection-Canceled State **2820** and, then, to the Retraction State **2830**. For example, the transection operation **2800** can be canceled and, thus, detour to the Transection-Canceled State **2820** directly from the Pre-Lockout Pause State **2806** (Condition E), the Lockout Pause State **2810** (Condition L), the Transection Pause State **2822** (Condition T), or the Transection-Stalled State **2826** (Condition V). For example, actuation of the clamping operation (e.g. activation of the clamping pedal or other input) can cancel the operation **2800** and the operation can proceed directly to the Transection-Canceled State **2820**. Upon entry to the Transection-Canceled State **2820**, the control circuit (e.g. the control circuit **2728**) is configured to convey a message to the clinician indicating that the transection operation **2800** has been canceled. For example, the control circuit can issue an error message via the GUI (e.g. the GUI **2790**). From the Transection-Canceled State **2820**, the operation **2800** can proceed to the Retraction State **2830**, with is further described herein.

[0332] In various instances, the operation **2800** can detour from the Transection State **2816** to the Transection Pause State **2822**. For example, deactivation of the clamping pedal or other input during the Transection State **2816** can pause the transection operation **2800**. Upon entry to the Transection Pause State **2822**, the control circuit (e.g. the control circuit **2728**) is configured to store the FMA, which corresponds to the transection pause angle. The control circuit is configured to target the transection pause angle during the Transection Pause State **2822**. For example, the transection pause angle can be held or maintained during the Transection Pause State **2822**.

[0333] In the Transection Pause State **2822**, the control circuit (e.g. the control circuit **2728**) can check for Conditions S, T, and U. Condition S corresponds to the active status of the transection pedal (e.g. the input **2780**). If Condition S is satisfied during the Transection Pause State **2822**, i.e. the transection pedal becomes active, then the operation **2800** returns to the Transection State **2816**, which is further described herein.

[0334] Condition T corresponds to the active status of the clamping pedal (e.g. the input **2782**). If Condition T is satisfied during the Transection Pause State **2822**, i.e. the clamping pedal becomes



active, then the operation **2800** proceeds to the Transection-Canceled State **2820**, which is further described herein.

[0335] Condition U corresponds to both (A) the FMT from the torque sensor (e.g. the torque sensor **2732**) being equal to or greater than the bailout detection torque and (B) the FMV from a velocity sensor (e.g. the velocity sensor **2738**) being equal to or less than the bailout detection velocity with both (A) and (B) being true for a time period equal to or greater than the bailout detection time. The bailout detection torque, bailout detection velocity, and bailout detection time are the same threshold values in the Pre-Lockout Pause State **2806** and Lockout Pause State **2810**. In other instances, different bailout threshold values can apply during the Pre-Lockout Pause State **2806**, the Lockout Pause State **2810**, and/or the Transection Pause State **2822**. For example, Condition U can be the same as Condition F and/or Condition M. In other instances, different bailout threshold values can apply during the Transection Pause State **2822**. Condition U can indicate a surgeon or clinician is attempting and/or effecting a bailout step during a tissue transection step. For example, during a surgical procedure, the surgeon or clinician can manually manipulate the firing member, which may involve decoupling the firing member from the firing motor and retracting the firing member manually, for example. If Condition U is satisfied during the Transection Pause State **2822**, then the transection operation **2800** proceeds to the Bailout-Attempt State **2836**, which is further described herein.

[0336] In various instances, the operation **2800** can detour from the Transection State **2816** to the Damaged State **2824** and, then, to the Retraction State **2830**. Detection of a high torque on the firing motor and/or firing member during the Transection State (e.g. Condition O), which is associated with damage to the surgical device, can trigger the detour to the Damaged State **2824**. Upon entry to the Damaged State **2824**, the control circuit (e.g. the control circuit **2728**) is configured to convey a message to the clinician indicating that damage has been suspected and the surgical tool is likely damaged or otherwise inoperable. For example, the control circuit can issue an error message via the GUI (e.g. the GUI **2790**). Moreover, the control circuit can update the DV stored in the memory (e.g. the memory **2742**) to true/positive, which indicates that future firings of the surgical system and/or surgical tool have been disabled. As further described herein, when the DV is true/positive, Condition A is not satisfied and a subsequent operation **2800** would not proceed from the Outset State **2802**. From the Damaged State **2824**, the operation **2800** can proceed to the Retraction State **2830**, which is further described herein.

[0337] In various instances, the operation **2800** can detour from the Transection State **2816** to the Transection-Stalled State **2826**. For example, if certain monitored parameters (e.g. FMV and FMT) indicate that the firing member has stalled during the Transection State and the total number of firing member stalls is less than a maximum threshold, the operation **2800** can enter the Transection-Stalled State **2826**.

[0338] Upon entry to the Transection-Stalled State **2826**, a transection-stall count stored in the memory of the control circuit (e.g. the memory **2742** of the control circuit **2728**) is incremented up by one. As further described herein, the transection-stall count is compared to a threshold maximum number of firing member stalls stored in the memory for Condition Q in the Transection State **2816**. Moreover, the control circuit is configured to convey or communicate the stall and, in certain instances, the transection-stall count, to the clinician. For example, the control circuit can issue GUI feedback via the GUI (e.g. the GUI **2790**) indicating the operation **2800** has stalled and, thus, entered the Transection-Stalled State **2826**.

[0339] Upon entry to the Transection-Stalled State **2826**, the control circuit (e.g. the control circuit **2728**) is also configured to store the FMA from the position sensor (e.g. the position sensor **2736**), which corresponds to the stall angle, and set a timer and/or set a time parameter of an internal clock (e.g. the clock **2741**) to the current time, i.e. the time the Transection-Stalled State **2826** was initiated. Moreover, the FMA, MFV and FMT are set or targeted by the control circuit. The target FMA angle can correspond to a back-off angle, and the target FMV can again correspond to the

transection region velocity, which is the same target FMV as during the Transection State **2816**, in various instances. The target FMT corresponds to the transection operating torque, which is the same target FMT as during the Transection State **2816**, in various instances.

[0340] In the Transection-Stalled State **2826**, the control circuit (e.g. the control circuit **2728**) can check for Conditions V, W, and X. Condition V corresponds to the active status of the clamp pedal (e.g. the input **2782**). If Condition V is satisfied during the Transection-Stalled State **2826**, i.e. the clamp pedal becomes active, then the operation **2800** proceeds to the Transection-Canceled State **2820**, which is further described herein.

[0341] Condition W corresponds to both (A) the current time minus the recorded time parameter being equal to or greater than a transection back-off time and (B) the transection pedal status (e.g. status of the input **2780**) changing from inactive to active. Condition W corresponds to the duration of the stall being less than a threshold time period stored in the memory (e.g. the memory **2742**) and the transection pedal returning to an active status. In such instances, Condition W is satisfied, and the operation returns to the Transection State **2816**.

[0342] Condition X corresponds to both (A) the FMT from the torque sensor (e.g. the torque sensor **2732**) begin equal to or greater than the bailout detection torque and (B) the FMV from a velocity sensor (e.g. the velocity sensor **2738**) being equal to or less than the bailout detection velocity with both (A) and (B) being true for a time period equal to or greater than the bailout detection time. The bailout detection torque, bailout detection velocity, and bailout detection time are the same threshold values in the Pre-Lockout Pause State **2806**, Lockout Pause State **2810**, Transection Pause State **2822**, and/or the Transection-Stalled State **2826**. For example, Condition X can be the same as Condition F, Condition M, and/or Condition U. In other instances, different bailout threshold values can apply during the Transection-Stalled State **2826**.

[0343] Condition X can indicate a surgeon or clinician is attempting and/or effecting a bailout step while the firing member moves through the lockout region. For example, during a surgical procedure, the surgeon or clinician can manually manipulate the firing member, which may involve decoupling the firing member from the firing motor and retracting the firing member manually, for example. If Condition X is satisfied during the Transection Stalled State **2826**, then the transection operation **2800** proceeds to the Bailout-Attempt State **2836**, which is further described herein.

[0344] In various instances, the operation **2800** can detour from the Transection State **2816** to the Stall Limit State **2828** and then to the Transection-Canceled State **2820**. For example, the operation **2800** can proceed to the Stall Limit State **2828** if the various parameters for entering the Transection-Stalled State **2826** are satisfied; however, the surgical tool has exceeded the threshold maximum number of firing member stalls. In other words, the surgical tool has already stalled more times than is reasonable and/or expected. Upon entry to the Stall Limit State **2828**, the control circuit (e.g. the control circuit **2728**) is configured to convey the determination regarding the stall limit to a clinician via the GUI (e.g. the GUI **2790**), for example. In various instances, the control circuit can issue an error message to the GUI informing the clinician that the stall limit has been reached and/or the Stall Limit State **2828** has commenced. From the Stall Limit State **2828**, the operation **2800** can proceed to the Retraction State **2830**, which is further described herein.

[0345] In various instances, the operation can detour from the Retraction State **2830** to the Retraction-Stalled State **2832**. For example, the firing member may become stuck or otherwise inoperable by the motor (e.g. the firing motor **2758**) during the Retraction State **2830**. Upon entry to the Retraction-Stalled State **2832**, the control circuit (e.g. the control circuit **2728**) can issue a message and/or convey the state of the surgical tool to a clinician or user. For example, the control circuit can convey signals to the GUI (e.g. the GUI **2790**), which indicate one or more troubleshooting steps for the clinician. The troubleshooting steps can be configured to remedy a mechanically bound-up surgical tool and/or firing system thereof. The control circuit can also update the DV stored in the memory (e.g. the memory **2742**) to true/positive, which indicates that future firings of the surgical system and/or surgical tool have been disabled. As further described

herein, when the DV is true/positive, Condition A is not satisfied and a subsequent operation **2800** would not proceed from the Outset State **2802**. From the Retraction-Stalled State **2832**, the operation **2800** can proceed to the Non-Recoverable State **2838**, with is further described herein. [0346] In various instances, the operation **2800** can enter the Bailout-Attempt State **2836** from the Pre-Lockout Pause State **2806**, the Lockout Pause State **2810**, the Transection Pause State **2822**, and/or the Transection-Stalled State **2826**. The Bailout-Attempt State **2836** can corresponds to a higher FMT from the torque sensor (e.g. the torque sensor **2732**) and lower FMV from a velocity sensor (e.g. the velocity sensor **2738**) than during typical advancement and retraction of the firing member, as further described herein. Upon entry to the Bailout-Attempt State **2836**, the control circuit (e.g. the control circuit **2728**) provides feedback to the clinician regarding how to bailout the surgical device. For example, the control circuit can issue signals to the GUI (e.g. the GUI **2790**) indicative of instructions (verbal and/or visual) regarding how to manually extract the surgical device (e.g. manually retract the firing member such that the jaws can release any tissue clamped therebetween). From the Bailout-Attempt State **2836**, the operation can proceed to the Non-Recoverable State **2838**.

[0347] The operation **2800** can enter the Non-Recoverable State **2838** from the Bailout-Attempt State **2836** and/or the Retraction-Stalled State **2832**, for example. The surgical device can be non-recoverable upon entering the Non-Recoverable State **2838**. In various instances, the control circuit (e.g. the control circuit **2728**) can provide signals to the GUI (e.g. the GUI **2790**) regarding the non-recoverable condition of the surgical tool. In such instances, a new clamping operation **2840** and/or a new transection operation **2800** can be prevented. The surgical tool can be retired and/or returned to the manufacturer for inspection and/or repair, in certain instances.

#### EXAMPLES

[0348] Various aspects of the subject matter described herein are set out in the following numbered examples.

[0349] Example 1—A surgical tool configured to receive rotary inputs from a robotic surgical system. The surgical tool comprises a distal end effector comprising jaws for clamping tissue therebetween, an intermediate shaft portion coupled to the distal end effector, and a proximal housing coupled to the intermediate shaft portion. The proximal housing comprises an arrangement of rotary drives comprising a first rotary drive. The first rotary drive comprises an input shaft configured to receive a rotary input from the robotic surgical system, a transition nut slidably positioned on the input shaft, and an output gear. The first rotary drive further comprises a high-speed gear configured to selectively drive the output gear, a high-torque gear configured to selectively drive the output gear, and a spring arrangement configured to bias the transition nut along the input shaft from a high-speed operating state, in which the transition nut is in driving engagement with the high-speed gear, to a high-torque operating state, in which the transition nut is in driving engagement with the high-torque gear upon obtaining a threshold torque.

[0350] Example 2—The surgical tool of Example 1, wherein the transition nut comprises a perimeter, a first end, and an array of sloping teeth around the perimeter extending to the first end.

[0351] Example 3—The surgical tool of Example 2, wherein the high-torque gear comprises an array of complementary sloping receptacles configured to receive the array of sloping teeth when the transition nut is in the high-torque operating state.

[0352] Example 4—The surgical tool of Examples 1, 2, or 3, wherein the transition nut further comprises a second end, and a first array of teeth around the perimeter extending to the second end.

[0353] Example 5—The surgical tool of Example 4, further comprising a grasping gear drivingly engaged with the high-speed gear, wherein the grasping gear comprises a second array of teeth configured to receive the first array of teeth when the transition nut is in the high-speed operating state.

[0354] Example 6—The surgical tool of Example 5, wherein the spring arrangement comprises a first spring configured to bias the first array of teeth toward the second array of teeth.

[0355] Example 7—The surgical tool of Examples 1, 2, 3, 4, 5, or 6, wherein the spring arrangement further comprises a second spring configured to bias the first end of the transition nut away from the second end of the transition nut.

[0356] Example 8—The surgical tool of Examples 1, 2, 3, 4, 5, 6, or 7, further comprising an output shaft drivingly coupled to the output gear, wherein the output shaft is configured to drive a rotary drive screw to effect a closure of the jaws.

[0357] Example 9—The surgical tool of Examples 1, 2, 3, 4, 5, 6, 7, or 8, wherein the first rotary drive further comprises a gear train comprising the high-speed gear, and wherein the gear train comprises a speed ratio greater than one.

[0358] Example 10—A surgical tool for a robotic surgical system. The surgical tool comprises a distal end effector comprising jaws for clamping tissue therebetween, an intermediate shaft portion coupled to the distal end effector, and a proximal housing coupled to the intermediate shaft portion. The proximal housing comprises an input shaft configured to receive a rotary input from the robotic surgical system, a transition nut slidably positioned on the input shaft, and an output gear. The proximal housing further comprises a first rotary drive configured to selectively drive the output gear, a second rotary drive configured to selectively drive the output gear, and a spring arrangement configured to bias the transition nut along the input shaft to couple the input shaft with either the first rotary drive or the second rotary drive based on a threshold torque applied to the transition nut.

[0359] Example 11—The surgical tool of Example 10, wherein the transition nut rotates with the input shaft.

[0360] Example 12—The surgical tool of Examples 10 or 11, wherein the spring arrangement comprises a first spring configured to bias the transition nut out of engagement with the second rotary drive and into engagement with the first rotary drive when the threshold torque is exceeded.

[0361] Example 13—The surgical tool of Examples 10, 11, or 12, wherein the transition nut comprises a perimeter, a first end, and an array of sloping teeth around the perimeter extending to the first end. The transition nut further comprises a second end, a first array of teeth around the perimeter extending to the second end, and a second spring configured to bias the first end away from the second end.

[0362] Example 14—The surgical tool of Example 13, wherein the first rotary drive comprises a high-torque gear comprising complementary sloping receptacles configured to receive the array of sloping teeth when the input shaft is engaged with the first rotary drive, and wherein the surgical tool is in a high-torque operating state when the first rotary drive is engaged with the input shaft.

[0363] Example 15—The surgical tool of Examples 13 or 14, wherein the second rotary drive comprises a high-speed gear and a grasping gear drivingly engaged with the high-speed gear, wherein the grasping gear comprises a second array of teeth configured to receive the first array of teeth when the input shaft is engaged with the second rotary drive, and wherein the surgical tool is in a high-speed operating state when the second rotary drive is engaged with the input shaft.

[0364] Example 16—The surgical tool of Examples 10, 11, 12, 13, 14, or 15, wherein the second rotary drive further comprises a gear train comprising the high-speed gear, and wherein the gear train comprises a speed ratio greater than one.

[0365] Example 17—The surgical tool of Examples 10, 11, 12, 13, 14, 15, or 16, further comprising an output shaft drivingly coupled to the output gear, wherein the output shaft is configured to drive a rotary drive screw to effect a closure of the jaws.

[0366] Example 18—A rotary drive system for rotating a drive screw in a robotic surgical tool. The rotary drive system comprises an input shaft configured to receive a rotary input from a robotic surgical system, a transition nut slidably positioned on the input shaft, and an output gear drivingly coupled to an output shaft. The rotary drive system further comprises a first rotary drive configured to selectively drive the output gear, a second rotary drive configured to selectively drive the output gear, and a spring arrangement configured to bias the transition nut along the input shaft into

engagement with either the first rotary drive or the second rotary drive based on a threshold torque applied to the transition nut.

[0367] Example 19—The rotary drive system of Example 18, wherein the first rotary drive comprises a high-torque gear that comprises complementary sloping receptacles configured to receive an array of sloping teeth on the transition nut when the input shaft is engaged with the first rotary drive.

[0368] Example 20—The rotary drive system of Examples 18 or 19, wherein the second rotary drive comprises a high-speed gear and a grasping gear drivingly engaged with the high-speed gear, wherein the grasping gear comprises an array of teeth configured to engage the transition nut when the input shaft is engaged with the second rotary drive.

[0369] Example 21—A robotic surgical system that comprises a closure system. The closure system comprises a first pinion drivingly coupled to a first motor, a second pinion drivingly coupled to a second motor, and a closure gear selectively driven by the first pinion and the second pinion. The robotic surgical system further comprises a control circuit configured to implement a motor crosscheck operation. The control circuit is configured to receive a first parameter indicative of a first torque generated by the first motor, receive a second parameter indicative of a second torque generated by the second motor, compare the first parameter to the second parameter, and transmit a signal to a communication device, wherein the signal is based on the comparison and indicative of a status of the closure system.

[0370] Example 22—The robotic surgical system of Example 21, wherein the control circuit is further configured to determine when the closure system has achieved a steady state in the motor crosscheck operation, and compare the first parameter to the second parameter after the closure system has achieved the steady state.

[0371] Example 23—The robotic surgical system of Examples 21 or 22, wherein the first pinion and the second pinion simultaneously drive the closure gear to effect a closure stroke.

[0372] Example 24—The robotic surgical system of Examples 21, 22, or 23, wherein the status transmitted by the control circuit corresponds to a fault state when the comparison of the first parameter to the second parameter exceeds a threshold value.

[0373] Example 25—The robotic surgical system of Example 24, wherein the robotic surgical system is configured to implement a lockout when the status corresponds to the fault state.

[0374] Example 26—The robotic surgical system of Examples 21, 22, 23, 24, or 25, wherein, to implement the motor crosscheck operation, the first motor is configured to drive the closure gear in a first direction, and wherein the second motor is configured to drive the closure gear in a second direction opposite to the first direction.

[0375] Example 27—The robotic surgical system of Examples 21, 22, 23, 24, 25, or 26, wherein the first motor is configured to transfer torque to the second pinion.

[0376] Example 28—The robotic surgical system of Examples 21, 22, 23, 24, 25, 26, or 27, wherein the second motor is configured to transfer torque to the first pinion.

[0377] Example 29—The robotic surgical system of Examples 21, 22, 23, 24, 25, 26, 27, or 28, wherein the second pinion is configured to move through a backlash region prior to the closure system achieving a steady state.

[0378] Example 30—The robotic surgical system of Example 29, wherein the control circuit is further configured to record a duration of the backlash region and obtain the duration to a stored value.

[0379] Example 31—A non-transitory computer readable medium storing computer readable instructions which, when executed, cause a machine to receive a first parameter indicative of a first torque generated by a first motor of a closure system, receive a second parameter indicative of a second torque generated by a second motor of the closure system, and implement a motor crosscheck. The first motor and the second motor are configured to concurrently drive a closure gear. The motor crosscheck comprises compare the first parameter to the second parameter, and

transmit a signal to a communication device, wherein the signal is based on the comparison and indicative of a status of the closure system.

[0380] Example 32—The non-transitory computer readable medium storing computer readable instructions of Example 31, which, when executed, further cause the machine to determine when the closure system has achieved a steady state, and compare the first parameter to the second parameter after the closure system has achieved the steady state.

[0381] Example 33—The non-transitory computer readable medium storing computer readable instructions of Examples 31 or 32, which, when executed, further cause the machine to enter a fault state when the comparison of the first parameter to the second parameter exceeds a threshold value.

[0382] Example 34—The non-transitory computer readable medium storing computer readable instructions of Example 33, which, when executed, further cause the machine to implement a lockout state when the status corresponds to the fault state.

[0383] Example 35—A robotic surgical system that comprises a closure system. The closure system comprises a first pinion drivingly coupled to a first motor, a second pinion drivingly coupled to a second motor, and a closure gear selectively driven by the first pinion and the second pinion. The closure system further comprises a processor and a memory coupled to the processor. The memory storing instructions executable by the processor to receive a first parameter indicative of a first torque from the first motor, receive a second parameter indicative of a second torque from the second motor, and receive a third parameter indicative of a first angular displacement of the first motor. The memory further stores instructions executable by the processor to receive a fourth parameter indicative of a second angular displacement of the second motor, and determine a status of the closure system based on the first parameter, the second parameter, the third parameter, and the fourth parameter. The memory further stores instructions executable by the processor to transmit a signal to a communication device indicative of the status of the closure system.

[0384] Example 36—The robotic surgical system of Example 35, wherein the memory further stores instructions executable by the processor to implement a motor crosscheck in which the first pinion and the second pinion are rotated in opposite directions.

[0385] Example 37—The robotic surgical system of Example 35, wherein the memory further stores instructions executable by the processor to implement a motor crosscheck in which the first pinion is driven by the first motor and the second pinion is not driven by the second motor.

[0386] Example 38—The robotic surgical system of Examples 35, 36 or 37, wherein the memory further stores instructions executable by the processor to measure a backlash angle during the motor crosscheck, and compare the backlash angle to a backlash value stored in the memory.

[0387] Example 39—The robotic surgical system of Examples 35, 36, 37, or 38, wherein the memory further stores instructions executable by the processor to implement a motor crosscheck in which a stiffness of the first pinion is computed from the first torque and the first angular displacement, and the stiffness is compared to a threshold.

[0388] Example 40—The robotic surgical system of Examples 35, 36, 37, 38, or 39, wherein the memory stores instructions executable by the processor to implement a motor crosscheck after at least one of a homing operation or clamping event by the closure system.

[0389] Example 41—A control circuit for use with a robotic surgical system. The control circuit is configured to receive a parameter indicative of a rotary position of an articulation motor. The articulation motor is configured to drive an articulation joint of a robotic surgical tool, wherein the articulation motor is configured to move through a first range of positions and a second range of positions. The first range of positions and the second range of positions are non-overlapping. The control circuit is further configured to implement a first operating state, and implement a second operating state when the parameter corresponds to a transition of the articulation motor from the first range of positions to the second range of positions. The second operating state is different than the first operating state. The control circuit is further configured to re-implement the first operating state when the parameter corresponds to a return of the articulation motor from the second range of

positions into the first range of positions by a threshold anti-dither angle.

[0390] Example 42—The control circuit of Example 41, wherein the first range of positions and the second range of positions are contiguous.

[0391] Example 43—The control circuit of Examples 41 or 42, wherein the second range of positions comprises an upper mechanical limit of the articulation joint.

[0392] Example 44—The control circuit of Examples 41, 42, or 43, wherein a maximum allowable speed of the articulation motor is less in the second operating state than in the first operating state when the parameter is moving away from the first range of positions.

[0393] Example 45—The control circuit of Examples 41, 42, 43, or 44, wherein a maximum allowable torque of the articulation motor is less in the second operating state than in the first operating state when the parameter is moving away from the first range of positions.

[0394] Example 46—The control circuit of Examples 41, 42, or 43, wherein a maximum allowable speed and a maximum allowable torque of the articulation motor is less in the second operating state than in the first operating state when the parameter is moving away from the first range of positions.

[0395] Example 47—The control circuit of Examples 41, 42, 43, 44, 45, or 46, wherein the parameter comprises a first parameter indicative of a rotary position of a first articulation motor, and wherein the control circuit is further configured to receive a second parameter indicative of a second rotary position of a second articulation motor, wherein the second articulation motor is configured to drive the articulation joint of the robotic surgical tool, wherein the second articulation motor is configured to move through a third range of positions and a fourth range of positions, and wherein the third range of positions and the fourth range of positions are non-overlapping.

[0396] Example 48—The control circuit of Example 47, wherein the control circuit is further configured to implement a third operating state when the second parameter corresponds to a transition of the second articulation motor from the third range of positions to the fourth range of positions, wherein the third operating state is different than the first operating state. The control circuit is further configured to re-implement the first operating state when the second parameter corresponds to a return of the second articulation motor from the fourth range of positions into the third range of positions by a threshold anti-dither angle.

[0397] Example 49—The control circuit of Examples 47 or 48, wherein the fourth range of positions comprises a lower mechanical limit of the articulation joint.

[0398] Example 50—A non-transitory computer readable medium storing computer readable instructions which, when executed, cause a machine to receive a first parameter indicative of a rotary position of a first articulation motor, receive a second parameter indicative of a rotary position of a second articulation motor, and implement a first operating state. The non-transitory computer readable medium storing computer readable instructions which, when executed, further cause a machine to transition from the first operating state to a second operating state when the first parameter corresponds to a transition of the first articulation motor from a first range of positions to an upper range of positions, wherein the second operating state is different than the first operating state. The non-transitory computer readable medium storing computer readable instructions which, when executed, further cause a machine to return to the first operating state from the second operating state when the first parameter corresponds to a return of the first articulation motor from the upper range of positions into the first range of positions by a first anti-dither angle. The non-transitory computer readable medium storing computer readable instructions which, when executed, further cause a machine to implement a third operating state when the second parameter corresponds to a transition of the second articulation motor from a second range of positions to a lower range of positions, wherein the third operating state is different than the first operating state. The non-transitory computer readable medium storing computer readable instructions which, when executed, further cause a machine to return to the first operating state from the third operating state when the second parameter corresponds to a return of the second articulation motor from the lower

range of positions into the second range of positions by a second anti-dither angle.

[0399] Example 51—A robotic surgical tool that comprises a housing, an end effector, and an elongate shaft extending distally from the housing to the end effector. The robotic surgical tool further comprises an articulation joint configured to articulate the end effector relative to the elongate shaft during an articulation motion, an internal shaft extending distally from the housing through the elongate shaft, and an articulation drive system. The articulation drive system comprises an articulation yoke coupled to the internal shaft, an articulation band coupled to the articulation yoke and extending distally along the internal shaft to the articulation joint, and rolling elements intermediate the internal shaft and the articulation yoke, wherein the articulation yoke is configured to roll along the rolling elements during the articulation motion.

[0400] Example 52—The robotic surgical tool of Example 51, wherein the rolling elements are positioned around the circumference of the internal shaft.

[0401] Example 53—The robotic surgical tool of Examples 51 or 52, further comprises a rolling element pad. The rolling element pad comprises a base secured to the internal shaft, a retainer secured to the base, wherein the base and the retainer form a continuous loop track therebetween. The rolling element pad further comprises the rolling elements, wherein the rolling elements comprise spheres positioned in the continuous loop track.

[0402] Example 54—The robotic surgical tool of Example 53, wherein the retainer comprises a window, and wherein a set of the rolling elements protrude through the window and contact the articulation yoke.

[0403] Example 55—The robotic surgical tool of Examples 53 or 54, wherein the rolling element pad is press-fit into a recess in the internal shaft.

[0404] Example 56—The robotic surgical tool of Examples 53, 54, or 55, wherein the continuous loop track comprises a first continuous loop track, and wherein the base and the retainer form a second continuous loop track configured to receive a plurality of the rolling elements therein.

[0405] Example 57—The robotic surgical tool of Example 56, wherein the articulation yoke comprises a first articulation yoke configured to slidably engage the rolling elements positioned in the first continuous loop track during the articulation motion, wherein the articulation drive system further comprises a second articulation yoke coupled to the internal shaft at a location distal to the first articulation yoke, and wherein the second articulation yoke is configured to slidably engage the rolling elements positioned in the second continuous loop track during the articulation motion.

[0406] Example 58—The robotic surgical tool of Example 57, wherein the articulation band comprises a first articulation band attached to the first articulation yoke and extending along the internal shaft to the articulation joint, and wherein the articulation drive system further comprises a second articulation band attached to the second articulation yoke and extending along the internal shaft to the articulation joint.

[0407] Example 59—The robotic surgical tool of Examples 57 or 58, wherein the articulation drive system is configured to move the first articulation yoke and second articulation yoke relative to each other and along the internal shaft to effect the articulation motion.

[0408] Example 60—A surgical tool that comprises a surgical end effector comprising opposing jaws, an elongate shaft extending distally to the surgical end effector, and a housing defining a passage therethrough, wherein the elongate shaft extends through the passage. The surgical tool further comprises an actuation mechanism configured to selectively move the housing along the elongate shaft relative to the surgical end effector. The actuation mechanism comprises a pulley, a cable engaged with the pulley, and a lock arrangement configured to releasably lock the housing relative to the elongate shaft. The lock arrangement comprises a washer positioned around the elongate shaft. The cable is engaged with the washer. An actuation of the pulley is configured to apply a tension to the cable to pivot the washer relative to the elongate shaft from a locked orientation to an unlocked orientation.

[0409] Example 61—The surgical tool of Example 60, wherein the washer comprises a first



washer, wherein the lock arrangement further comprises a second washer positioned around the elongate shaft, wherein the cable is engaged with the second washer, and wherein the second washer is configured to pivot relative to the elongate shaft between a locked orientation and an unlocked orientation.

[0410] Example 62—The surgical tool of Example 61, wherein, in their locked orientations, the first washer and the second washer are obliquely-oriented relative to a longitudinal axis of the elongate shaft, and wherein the first washer and the second washer are configured to pivot toward a parallel orientation when they move to their unlocked orientations.

[0411] Example 63—The surgical tool of Examples 61 or 62, wherein the lock arrangement further comprises a spring between the first washer and the second washer, and wherein the spring biases a portion of the first washer away from a portion of the second washer.

[0412] Example 64—The surgical tool of Example 63, wherein the tension applied by the actuation of the pulley is configured to overcome a biasing force of the spring to move the first washer and the second washer from their locked orientations to their unlocked orientations.

[0413] Example 65—The surgical tool of Examples 61, 62, 63, or 64, wherein the tension in the cable applied by the actuation of the pulley is configured to pivot the first washer and second washer to the unlocked orientation and then pull on the elongate shaft to move the housing along the elongate shaft.

[0414] Example 66—The surgical tool of Examples 60, 61, 62, 63, 64, or 65, wherein the housing comprises a body comprising an internal wall, wherein the internal wall defines a portion of an internal cavity in the body, and wherein the washer extends at least partially into the internal cavity.

[0415] Example 67—The surgical tool of Example 68, wherein the actuation of the pulley is configured to push the washer against the internal wall to draw the housing along the elongate shaft.

[0416] Example 68—The surgical tool of Examples 60, 61, 62, 63, 64, 65, 66, or 67, wherein the surgical end effector further comprises a firing member configured to cut tissue positioned between the opposing jaws.

[0417] Example 69—The surgical tool of Examples 60, 61, 62, 63, 64, 65, 66, 67, or 68, wherein the surgical end effector further comprises a staple cartridge comprising staples.

[0418] Example 70—A surgical tool that comprises a surgical end effector, an elongate shaft extending distally to the surgical end effector, and a housing defining a passage therethrough, wherein the elongate shaft extends through the passage. The surgical tool further comprises an actuation mechanism configured to selectively move the housing along the elongate shaft relative to the surgical end effector. The actuation mechanism comprises a pulley, a capstan, and a cable engaged with the pulley and the capstan. The actuation mechanism further comprises a lock arrangement configured to releasably lock the housing relative to the elongate shaft. The lock arrangement comprising a first washer positioned around the elongate shaft. A first end of the cable is engaged with the first washer. The first washer is configured to pivot relative to the elongate shaft between a locked orientation and an unlocked orientation. The lock arrangement further comprising a second washer positioned around the elongate shaft. A second end of the cable is engaged with the second washer. The second washer is configured to pivot relative to the elongate shaft between a locked orientation and an unlocked orientation. The lock arrangement further comprising a spring between the first washer and the second washer, wherein the spring is configured to bias a portion of the first washer away from a portion of the second washer to pivot the first washer and second washer into the locked orientations. A rotation of the capstan is configured to apply a tension to the cable to pivot the first washer and second washer to their unlocked orientations.

[0419] Example 71—The surgical tool of Example 70, wherein, in the locked orientations, the first washer and the second washer are obliquely-oriented relative to a longitudinal axis of the elongate shaft, and wherein the first washer and the second washer are configured to pivot toward parallel

from their locked orientations to their unlocked orientations.

[0420] Example 72—The surgical tool of Examples 70 or 71, wherein the tension applied by the rotation of the capstan is configured to overcome the biasing force of the spring to move the first washer and the second washer from their locked orientations to their unlocked orientations.

[0421] Example 73—The surgical tool of Examples 70, 71, or 72, wherein the housing comprises a body comprising an internal wall, wherein the internal wall defines a portion of an internal cavity in the body, and wherein the first washer extends at least partially into the internal cavity.

[0422] Example 74—The surgical tool of Example 73, wherein the rotation of the capstan is configured to push the first washer against the internal wall to draw the housing along the elongate shaft.

[0423] Example 75—The surgical tool of Examples 70, 71, 72, 73, or 74, wherein the tension in the cable applied by the rotation of the capstan is configured to pivot the first washer and second washer to their unlocked orientations and pull the housing along the elongate shaft.

[0424] Example 76—A surgical tool that comprises an elongate shaft, and a housing defining a passage therethrough, wherein the elongate shaft extends through the passage. The surgical tool further comprises an actuation mechanism configured to selectively move the housing along the elongate shaft. The actuation mechanism comprises a pulley arrangement, and a lock arrangement configured to releasably lock the housing relative to the elongate shaft. The lock arrangement comprises a lock positioned around the elongate shaft. An actuation of the pulley arrangement is configured to move the lock from a locked orientation to an unlocked orientation.

[0425] Example 77—The surgical tool of Example 76, wherein the lock is configured to pivot from the locked orientation to the unlocked orientation.

[0426] Example 78—The surgical tool of Examples 76 or 77, wherein, in the locked orientation, the lock is obliquely-oriented relative to a longitudinal axis of the elongate shaft.

[0427] Example 79—The surgical tool of Examples 76, 77, or 78, wherein the lock arrangement further comprises a spring configured to bias the lock toward the locked orientation.

[0428] While several forms have been illustrated and described, it is not the intention of Applicant to restrict or limit the scope of the appended claims to such detail. Numerous modifications, variations, changes, substitutions, combinations, and equivalents to those forms may be implemented and will occur to those skilled in the art without departing from the scope of the present disclosure. Moreover, the structure of each element associated with the described forms can be alternatively described as a means for providing the function performed by the element. Also, where materials are disclosed for certain components, other materials may be used. It is therefore to be understood that the foregoing description and the appended claims are intended to cover all such modifications, combinations, and variations as falling within the scope of the disclosed forms. The appended claims are intended to cover all such modifications, variations, changes, substitutions, modifications, and equivalents.

[0429] The foregoing detailed description has set forth various forms of the devices and/or processes via the use of block diagrams, flowcharts, and/or examples. Insofar as such block diagrams, flowcharts, and/or examples contain one or more functions and/or operations, it will be understood by those within the art that each function and/or operation within such block diagrams, flowcharts, and/or examples can be implemented, individually and/or collectively, by a wide range of hardware, software, firmware, or virtually any combination thereof. Those skilled in the art will recognize that some aspects of the forms disclosed herein, in whole or in part, can be equivalently implemented in integrated circuits, as one or more computer programs running on one or more computers (e.g., as one or more programs running on one or more computer systems), as one or more programs running on one or more processors (e.g., as one or more programs running on one or more microprocessors), as firmware, or as virtually any combination thereof, and that designing the circuitry and/or writing the code for the software and or firmware would be well within the skill of one of skill in the art in light of this disclosure. In addition, those skilled in the art will

appreciate that the mechanisms of the subject matter described herein are capable of being distributed as one or more program products in a variety of forms, and that an illustrative form of the subject matter described herein applies regardless of the particular type of signal bearing medium used to actually carry out the distribution.

[0430] Instructions used to program logic to perform various disclosed aspects can be stored within a memory in the system, such as dynamic random access memory (DRAM), cache, flash memory, or other storage. Furthermore, the instructions can be distributed via a network or by way of other computer readable media. Thus a machine-readable medium may include any mechanism for storing or transmitting information in a form readable by a machine (e.g., a computer), but is not limited to, floppy diskettes, optical disks, compact disc, read-only memory (CD-ROMs), and magneto-optical disks, read-only memory (ROMs), random access memory (RAM), erasable programmable read-only memory (EPROM), electrically erasable programmable read-only memory (EEPROM), magnetic or optical cards, flash memory, or a tangible, machine-readable storage used in the transmission of information over the Internet via electrical, optical, acoustical or other forms of propagated signals (e.g., carrier waves, infrared signals, digital signals, etc.). Accordingly, the non-transitory computer-readable medium includes any type of tangible machine-readable medium suitable for storing or transmitting electronic instructions or information in a form readable by a machine (e.g., a computer).

[0431] As used in any aspect herein, the term “control circuit” may refer to, for example, hardwired circuitry, programmable circuitry (e.g., a computer processor including one or more individual instruction processing cores, processing unit, processor, microcontroller, microcontroller unit, controller, digital signal processor (DSP), programmable logic device (PLD), programmable logic array (PLA), or field programmable gate array (FPGA)), state machine circuitry, firmware that stores instructions executed by programmable circuitry, and any combination thereof. The control circuit may, collectively or individually, be embodied as circuitry that forms part of a larger system, for example, an integrated circuit (IC), an application-specific integrated circuit (ASIC), a system on-chip (SoC), desktop computers, laptop computers, tablet computers, servers, smart phones, etc. Accordingly, as used herein “control circuit” includes, but is not limited to, electrical circuitry having at least one discrete electrical circuit, electrical circuitry having at least one integrated circuit, electrical circuitry having at least one application specific integrated circuit, electrical circuitry forming a general purpose computing device configured by a computer program (e.g., a general purpose computer configured by a computer program which at least partially carries out processes and/or devices described herein, or a microprocessor configured by a computer program which at least partially carries out processes and/or devices described herein), electrical circuitry forming a memory device (e.g., forms of random access memory), and/or electrical circuitry forming a communications device (e.g., a modem, communications switch, or optical-electrical equipment). Those having skill in the art will recognize that the subject matter described herein may be implemented in an analog or digital fashion or some combination thereof.

[0432] As used in any aspect herein, the term “logic” may refer to an app, software, firmware and/or circuitry configured to perform any of the aforementioned operations. Software may be embodied as a software package, code, instructions, instruction sets and/or data recorded on non-transitory computer readable storage medium. Firmware may be embodied as code, instructions or instruction sets and/or data that are hard-coded (e.g., nonvolatile) in memory devices.

[0433] As used in any aspect herein, the terms “component,” “system,” “module” and the like can refer to a computer-related entity, either hardware, a combination of hardware and software, software, or software in execution.

[0434] As used in any aspect herein, an “algorithm” refers to a self-consistent sequence of steps leading to a desired result, where a “step” refers to a manipulation of physical quantities and/or logic states which may, though need not necessarily, take the form of electrical or magnetic signals capable of being stored, transferred, combined, compared, and otherwise manipulated. It is

common usage to refer to these signals as bits, values, elements, symbols, characters, terms, numbers, or the like. These and similar terms may be associated with the appropriate physical quantities and are merely convenient labels applied to these quantities and/or states.

[0435] A network may include a packet switched network. The communication devices may be capable of communicating with each other using a selected packet switched network communications protocol. One example communications protocol may include an Ethernet communications protocol which may be capable permitting communication using a Transmission Control Protocol/Internet Protocol (TCP/IP). The Ethernet protocol may comply or be compatible with the Ethernet standard published by the Institute of Electrical and Electronics Engineers (IEEE) titled “IEEE 802.3 Standard”, published in December 2008 and/or later versions of this standard. Alternatively or additionally, the communication devices may be capable of communicating with each other using an X.25 communications protocol. The X.25 communications protocol may comply or be compatible with a standard promulgated by the International Telecommunication Union-Telecommunication Standardization Sector (ITU-T). Alternatively or additionally, the communication devices may be capable of communicating with each other using a frame relay communications protocol. The frame relay communications protocol may comply or be compatible with a standard promulgated by Consultative Committee for International Telegraph and Telephone (CCITT) and/or the American National Standards Institute (ANSI). Alternatively or additionally, the transceivers may be capable of communicating with each other using an Asynchronous Transfer Mode (ATM) communications protocol. The ATM communications protocol may comply or be compatible with an ATM standard published by the ATM Forum titled “ATM-MPLS Network Interworking 2.0” published August 2001, and/or later versions of this standard. Of course, different and/or after-developed connection-oriented network communication protocols are equally contemplated herein.

[0436] Unless specifically stated otherwise as apparent from the foregoing disclosure, it is appreciated that, throughout the foregoing disclosure, discussions using terms such as “processing,” “computing,” “calculating,” “determining,” “displaying,” or the like, refer to the action and processes of a computer system, or similar electronic computing device, that manipulates and transforms data represented as physical (electronic) quantities within the computer system's registers and memories into other data similarly represented as physical quantities within the computer system memories or registers or other such information storage, transmission or display devices.

[0437] One or more components may be referred to herein as “configured to,” “configurable to,” “operable/operative to,” “adapted/adaptable,” “able to,” “conformable/conformed to,” etc. Those skilled in the art will recognize that “configured to” can generally encompass active-state components and/or inactive-state components and/or standby-state components, unless context requires otherwise.

[0438] The terms “proximal” and “distal” are used herein with reference to a clinician manipulating the handle portion of the surgical instrument. The term “proximal” refers to the portion closest to the clinician and the term “distal” refers to the portion located away from the clinician. It will be further appreciated that, for convenience and clarity, spatial terms such as “vertical”, “horizontal”, “up”, and “down” may be used herein with respect to the drawings. However, surgical instruments are used in many orientations and positions, and these terms are not intended to be limiting and/or absolute.

[0439] Those skilled in the art will recognize that, in general, terms used herein, and especially in the appended claims (e.g., bodies of the appended claims) are generally intended as “open” terms (e.g., the term “including” should be interpreted as “including but not limited to,” the term “having” should be interpreted as “having at least,” the term “includes” should be interpreted as “includes but is not limited to,” etc.). It will be further understood by those within the art that if a specific number of an introduced claim recitation is intended, such an intent will be explicitly

recited in the claim, and in the absence of such recitation no such intent is present. For example, as an aid to understanding, the following appended claims may contain usage of the introductory phrases “at least one” and “one or more” to introduce claim recitations. However, the use of such phrases should not be construed to imply that the introduction of a claim recitation by the indefinite articles “a” or “an” limits any particular claim containing such introduced claim recitation to claims containing only one such recitation, even when the same claim includes the introductory phrases “one or more” or “at least one” and indefinite articles such as “a” or “an” (e.g., “a” and/or “an” should typically be interpreted to mean “at least one” or “one or more”); the same holds true for the use of definite articles used to introduce claim recitations.

[0440] In addition, even if a specific number of an introduced claim recitation is explicitly recited, those skilled in the art will recognize that such recitation should typically be interpreted to mean at least the recited number (e.g., the bare recitation of “two recitations,” without other modifiers, typically means at least two recitations, or two or more recitations). Furthermore, in those instances where a convention analogous to “at least one of A, B, and C, etc.” is used, in general such a construction is intended in the sense one having skill in the art would understand the convention (e.g., “a system having at least one of A, B, and C” would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). In those instances where a convention analogous to “at least one of A, B, or C, etc.” is used, in general such a construction is intended in the sense one having skill in the art would understand the convention (e.g., “a system having at least one of A, B, or C” would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). It will be further understood by those within the art that typically a disjunctive word and/or phrase presenting two or more alternative terms, whether in the description, claims, or drawings, should be understood to contemplate the possibilities of including one of the terms, either of the terms, or both terms unless context dictates otherwise. For example, the phrase “A or B” will be typically understood to include the possibilities of “A” or “B” or “A and B.”

[0441] With respect to the appended claims, those skilled in the art will appreciate that recited operations therein may generally be performed in any order. Also, although various operational flow diagrams are presented in a sequence(s), it should be understood that the various operations may be performed in other orders than those which are illustrated, or may be performed concurrently. Examples of such alternate orderings may include overlapping, interleaved, interrupted, reordered, incremental, preparatory, supplemental, simultaneous, reverse, or other variant orderings, unless context dictates otherwise. Furthermore, terms like “responsive to,” “related to,” or other past-tense adjectives are generally not intended to exclude such variants, unless context dictates otherwise.

[0442] It is worthy to note that any reference to “one aspect,” “an aspect,” “an exemplification,” “one exemplification,” and the like means that a particular feature, structure, or characteristic described in connection with the aspect is included in at least one aspect. Thus, appearances of the phrases “in one aspect,” “in an aspect,” “in an exemplification,” and “in one exemplification” in various places throughout the specification are not necessarily all referring to the same aspect. Furthermore, the particular features, structures or characteristics may be combined in any suitable manner in one or more aspects.

[0443] Any patent application, patent, non-patent publication, or other disclosure material referred to in this specification and/or listed in any Application Data Sheet is incorporated by reference herein, to the extent that the incorporated materials is not inconsistent herewith. As such, and to the extent necessary, the disclosure as explicitly set forth herein supersedes any conflicting material incorporated herein by reference. Any material, or portion thereof, that is said to be incorporated by reference herein, but which conflicts with existing definitions, statements, or other disclosure material set forth herein will only be incorporated to the extent that no conflict arises between that

incorporated material and the existing disclosure material.

[0444] In summary, numerous benefits have been described which result from employing the concepts described herein. The foregoing description of the one or more forms has been presented for purposes of illustration and description. It is not intended to be exhaustive or limiting to the precise form disclosed. Modifications or variations are possible in light of the above teachings. The one or more forms were chosen and described in order to illustrate principles and practical application to thereby enable one of ordinary skill in the art to utilize the various forms and with various modifications as are suited to the particular use contemplated. It is intended that the claims submitted herewith define the overall scope.

## Claims

**1-20.** (canceled)

**21.** A rotary drive system for use with a robotic surgical tool, the rotary drive system comprising: an input shaft configured to receive an input torque to effect rotation of the input shaft about a rotation axis; an output gear; a first rotary drive configured to selectively drive the output gear; a second rotary drive configured to selectively drive the output gear; and a transition nut movable along the input shaft between a first position and a second position based on the input torque exceeding a threshold torque, wherein, in the first position, the transition nut engages the first rotary drive to selectively drive the output gear, and wherein, in the second position, the transition nut engages the second rotary drive to selectively drive the output gear.

**22.** The rotary drive system of claim 21, wherein the transition nut comprises a flexible transition nut.

**23.** The rotary drive system of claim 22, wherein the flexible transition nut comprises: a first end positionable to engage the first rotary drive; a second end positionable to engage the second rotary drive; and a spring positioned between the first end and the second end.

**24.** The rotary drive system of claim 23, wherein the first end comprises a first plurality of teeth, wherein the first rotary drive comprises a second plurality of teeth, and wherein, in the first position, the first plurality of teeth is positioned and structured to engage the second plurality of teeth.

**25.** The rotary drive system of claim 23, wherein the second end comprises a plurality of teeth, wherein the second rotary drive comprises a plurality of receptacles, and wherein, in the second position, the plurality of teeth is positioned and structured to be received by the plurality of receptacles.

**26.** The rotary drive system of claim 25, wherein the plurality of teeth comprises external threads, wherein the plurality of receptacles comprises internal threads, and wherein the internal threads are structured to threadably receive the external threads.

**27.** The rotary drive system of claim 21, wherein the first rotary drive selectively drives the output gear in a first operating state, and wherein the second rotary drive selectively drives the output gear in a second operating state.

**28.** A rotary drive system for use with a robotic surgical tool, the rotary drive system comprising: an input shaft to receive an input torque to effect rotation of the input shaft about a rotation axis; an output gear; a first rotary drive; a second rotary drive; and a transition nut movable along the input shaft between a first position and a second position based on the input torque exceeding a threshold torque, wherein, in the first position, the transition nut engages the first rotary drive to selectively drive the output gear, and wherein, in the second position, the transition nut engages the second rotary drive to selectively drive the output gear.

**29.** The rotary drive system of claim 28, wherein the transition nut comprises an axially-flexible transition nut.

**30.** The rotary drive system of claim 29, wherein the axially-flexible transition nut comprises: a

first end oriented to engage the first rotary drive; a second end oriented to engage the second rotary drive; and a spring positioned between the first end and the second end.

**31.** The rotary drive system of claim 30, wherein the first end comprises a first plurality of teeth, wherein the first rotary drive comprises a second plurality of teeth, and wherein, in the first position, the first plurality of teeth is positioned and structured to engage the second plurality of teeth.

**32.** The rotary drive system of claim 30, wherein the second end comprises a plurality of teeth, wherein the second rotary drive comprises a plurality of receptacles, and wherein, in the second position, the plurality of teeth is positioned and structured to be received by the plurality of receptacles.

**33.** The rotary drive system of claim 32, wherein the plurality of teeth comprises external threads, wherein the plurality of receptacles comprises internal threads, and wherein the internal threads are structured to threadably receive the external threads.

**34.** The rotary drive system of claim 28, wherein the first rotary drive is to selectively drives the output gear in a first operating state, and wherein the second rotary drive is to selectively drives the output gear in a second operating state.

**35.** A rotary drive system for use with a robotic surgical tool, the rotary drive system comprising: an input shaft rotatable about a rotation axis by an input torque; an output gear to effect a surgical function; a first rotary drive to selectively drive the output gear in a first operating state; a second rotary drive to selectively drive the output gear in a second operating state; and a transition nut movable along the input shaft between a first position and a second position based on the input torque exceeding a threshold torque, wherein, in the first position, the transition nut engages the first rotary drive to effect the surgical function in the first operating state, and wherein, in the second position, the transition nut engages the second rotary drive to effect the surgical function in the second operating state.

**36.** The rotary drive system of claim 35, wherein the transition nut comprises an axially-deformable transition nut.

**37.** The rotary drive system of claim 36, wherein the axially-deformable transition nut comprises: a first end structured and positioned to engage the first rotary drive; a second end structured and positioned to engage the second rotary drive; and a spring positioned between the first end and the second end.

**38.** The rotary drive system of claim 37, wherein the first end comprises a first plurality of teeth, wherein the first rotary drive comprises a second plurality of teeth, and wherein, in the first position, the first plurality of teeth is positioned and structured to engage the second plurality of teeth.

**39.** The rotary drive system of claim 37, wherein the second end comprises a plurality of teeth, wherein the second rotary drive comprises a plurality of receptacles, and wherein, in the second position, the plurality of teeth is positioned and structured to be received by the plurality of receptacles.

**40.** The rotary drive system of claim 35, wherein the first operating state is a high-speed firing state, and wherein the second operating state is a high-torque firing state.

---