

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12395456
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Smetanin; Sergey et al.

Generating media content items during user interaction

Abstract

A method includes determining participation in an interaction function by a first user of an interaction system with a second user of the interaction system. The method also includes accessing profile data of the first user, and determining, based on the profile data, whether the first user has captured or designated a first-user self-image for use in the interaction function. In response to determining that the first user has not captured or designated the first-user self-image, the method includes accessing a media content item that includes a character, identifying a head portion of the character in the media content item, replacing the head portion with a placeholder space, and displaying the media content item with the placeholder space in a user interface corresponding to the interaction function.

Inventors: Smetanin; Sergey (London, GB), Golobokov; Roman (London, GB), Claudet; Emily Ann (Brooklyn, NY), Ayalon; Dor (Glasgow, GB), Gordienko; Vladimir (London, GB), Houston; Erin (Saratoga Springs, UT), Babanin; Ivan (London, GB), Zakirov; Timur (London, GB), Demidov; Nikita (London, GB), Larionov; Aleksandr (London, GB), Kovalenko; Anna (London, GB), Belosludtcev; Nikita (London, GB)

Applicant: Snap Inc. (Santa Monica, CA)

Family ID: 1000008766950

Assignee: SNAP INC. (Santa Monica, CA)

Appl. No.: 18/742913

Filed: June 13, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250016127 A1	Jan. 09, 2025

Related U.S. Application Data

continuation parent-doc US 18346667 20230703 US 12047337 child-doc US 18742913

Publication Classification

Int. Cl.: G06F15/16 (20060101); G06F3/0482 (20130101); G06T13/40 (20110101); H04L51/046 (20220101); H04L51/10 (20220101); H04L51/52 (20220101); H04N5/265 (20060101)

U.S. Cl.:

CPC H04L51/10 (20130101); G06F3/0482 (20130101); G06T13/40 (20130101); H04L51/046 (20130101); H04L51/52 (20220501); H04N5/265 (20130101);

Field of Classification Search

CPC: H04L (51/10); H04L (51/52); H04L (51/046); G06F (3/0482); G06T (13/40); H04N (5/265)

USPC: 709/206; 709/204; 709/217

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5604843	12/1996	Shaw et al.	N/A	N/A
5689559	12/1996	Park	N/A	N/A
5880731	12/1998	Liles et al.	N/A	N/A
6023270	12/1999	Brush, II et al.	N/A	N/A
RE36919	12/1999	Park	N/A	N/A
RE37052	12/2000	Park	N/A	N/A
6223165	12/2000	Lauffer	N/A	N/A
6650793	12/2002	Lund et al.	N/A	N/A
6772195	12/2003	Hatlelid et al.	N/A	N/A
6804417	12/2003	Lund et al.	N/A	N/A
6842779	12/2004	Nishizawa	N/A	N/A
7342587	12/2007	Danzig et al.	N/A	N/A
7468729	12/2007	Levinson	N/A	N/A
7636755	12/2008	Blattner et al.	N/A	N/A
7639251	12/2008	Gu et al.	N/A	N/A
7775885	12/2009	Van et al.	N/A	N/A
7859551	12/2009	Bulman et al.	N/A	N/A
7885931	12/2010	Seo et al.	N/A	N/A
7925703	12/2010	Dinan et al.	N/A	N/A
8088044	12/2011	Tchao et al.	N/A	N/A
8095878	12/2011	Bates et al.	N/A	N/A
8108774	12/2011	Finn et al.	N/A	N/A
8117281	12/2011	Robinson et al.	N/A	N/A

8130219	12/2011	Fleury et al.	N/A	N/A
8146005	12/2011	Jones et al.	N/A	N/A
8151191	12/2011	Nicol	N/A	N/A
RE43993	12/2012	Park	N/A	N/A
8384719	12/2012	Reville et al.	N/A	N/A
RE44054	12/2012	Kim	N/A	N/A
RE44068	12/2012	Park	N/A	N/A
RE44106	12/2012	Park	N/A	N/A
8396708	12/2012	Park et al.	N/A	N/A
RE44121	12/2012	Park	N/A	N/A
8425322	12/2012	Gillo et al.	N/A	N/A
8458601	12/2012	Castelli et al.	N/A	N/A
8462198	12/2012	Lin et al.	N/A	N/A
8484158	12/2012	Deluca et al.	N/A	N/A
8495503	12/2012	Brown et al.	N/A	N/A
8495505	12/2012	Smith et al.	N/A	N/A
8504926	12/2012	Wolf	N/A	N/A
8559980	12/2012	Pujol	N/A	N/A
8564621	12/2012	Branson et al.	N/A	N/A
8564710	12/2012	Nonaka et al.	N/A	N/A
8581911	12/2012	Becker et al.	N/A	N/A
8597121	12/2012	del Valle	N/A	N/A
8601051	12/2012	Wang	N/A	N/A
8601379	12/2012	Marks et al.	N/A	N/A
8632408	12/2013	Gillo et al.	N/A	N/A
8648865	12/2013	Dawson et al.	N/A	N/A
8659548	12/2013	Hildreth	N/A	N/A
8683354	12/2013	Khandelwal et al.	N/A	N/A
8692830	12/2013	Nelson et al.	N/A	N/A
8810513	12/2013	Ptucha et al.	N/A	N/A
8812171	12/2013	Filev et al.	N/A	N/A
8832201	12/2013	Wall	N/A	N/A
8832552	12/2013	Arrasvuori et al.	N/A	N/A
8839327	12/2013	Amento et al.	N/A	N/A
8890926	12/2013	Tandon et al.	N/A	N/A
8892999	12/2013	Nims et al.	N/A	N/A
8924250	12/2013	Bates et al.	N/A	N/A
8963926	12/2014	Brown et al.	N/A	N/A
8989786	12/2014	Feghali	N/A	N/A
9086776	12/2014	Ye et al.	N/A	N/A
9105014	12/2014	Collet et al.	N/A	N/A
9241184	12/2015	Weerasinghe	N/A	N/A
9256860	12/2015	Herger et al.	N/A	N/A
9298257	12/2015	Hwang et al.	N/A	N/A
9314692	12/2015	Konoplev et al.	N/A	N/A
9330483	12/2015	Du et al.	N/A	N/A
9357174	12/2015	Li et al.	N/A	N/A
9361510	12/2015	Yao et al.	N/A	N/A
9378576	12/2015	Bouaziz et al.	N/A	N/A
9402057	12/2015	Kaytaz et al.	N/A	N/A

9412192	12/2015	Mandel et al.	N/A	N/A
9460541	12/2015	Li et al.	N/A	N/A
9489760	12/2015	Li et al.	N/A	N/A
9503845	12/2015	Vincent	N/A	N/A
9508197	12/2015	Quinn et al.	N/A	N/A
9532364	12/2015	Fujito	N/A	N/A
9544257	12/2016	Ogundokun et al.	N/A	N/A
9576400	12/2016	Van Os et al.	N/A	N/A
9589357	12/2016	Li et al.	N/A	N/A
9592449	12/2016	Barbalet et al.	N/A	N/A
9648376	12/2016	Chang et al.	N/A	N/A
9697635	12/2016	Quinn et al.	N/A	N/A
9706040	12/2016	Kadirvel et al.	N/A	N/A
9744466	12/2016	Fujioka	N/A	N/A
9746990	12/2016	Anderson et al.	N/A	N/A
9749270	12/2016	Collet et al.	N/A	N/A
9792714	12/2016	Li et al.	N/A	N/A
9839844	12/2016	Dunstan et al.	N/A	N/A
9883838	12/2017	Kaleal, III et al.	N/A	N/A
9898849	12/2017	Du et al.	N/A	N/A
9911073	12/2017	Spiegel et al.	N/A	N/A
9936165	12/2017	Li et al.	N/A	N/A
9959037	12/2017	Chaudhri et al.	N/A	N/A
9980100	12/2017	Charlton et al.	N/A	N/A
9990373	12/2017	Fortkort	N/A	N/A
10039988	12/2017	Lobb et al.	N/A	N/A
10097492	12/2017	Tsuda et al.	N/A	N/A
10116598	12/2017	Tucker et al.	N/A	N/A
10155168	12/2017	Blackstock et al.	N/A	N/A
10158589	12/2017	Collet et al.	N/A	N/A
10242477	12/2018	Charlton et al.	N/A	N/A
10242503	12/2018	McPhee et al.	N/A	N/A
10262250	12/2018	Spiegel et al.	N/A	N/A
10348662	12/2018	Baldwin et al.	N/A	N/A
10362219	12/2018	Wilson et al.	N/A	N/A
10432559	12/2018	Baldwin et al.	N/A	N/A
10454857	12/2018	Blackstock et al.	N/A	N/A
10475225	12/2018	Park et al.	N/A	N/A
10504266	12/2018	Blattner et al.	N/A	N/A
10552977	12/2019	Theis	N/A	G06T 7/70
10573048	12/2019	Ni et al.	N/A	N/A
10656797	12/2019	Alvi et al.	N/A	N/A
10657695	12/2019	Chand et al.	N/A	N/A
10657701	12/2019	Osman et al.	N/A	N/A
10762174	12/2019	Denton et al.	N/A	N/A
10805248	12/2019	Luo et al.	N/A	N/A
10872451	12/2019	Sheth et al.	N/A	N/A
10880246	12/2019	Baldwin et al.	N/A	N/A
10895964	12/2020	Grantham et al.	N/A	N/A
10896534	12/2020	Smith et al.	N/A	N/A

10933311	12/2020	Brody et al.	N/A	N/A
10938758	12/2020	Allen et al.	N/A	N/A
10964082	12/2020	Amitay et al.	N/A	N/A
10979752	12/2020	Brody et al.	N/A	N/A
10984575	12/2020	Assouline et al.	N/A	N/A
10992619	12/2020	Antmen et al.	N/A	N/A
11010022	12/2020	Alvi et al.	N/A	N/A
11030789	12/2020	Chand et al.	N/A	N/A
11036781	12/2020	Baril et al.	N/A	N/A
11063891	12/2020	Voss	N/A	N/A
11069103	12/2020	Blackstock et al.	N/A	N/A
11080917	12/2020	Monroy-Hernandez et al.	N/A	N/A
11128586	12/2020	Al Majid et al.	N/A	N/A
11188190	12/2020	Blackstock et al.	N/A	N/A
11189070	12/2020	Jahangiri et al.	N/A	N/A
11199957	12/2020	Alvi et al.	N/A	N/A
11218433	12/2021	Baldwin et al.	N/A	N/A
11229849	12/2021	Blackstock et al.	N/A	N/A
11245658	12/2021	Grantham et al.	N/A	N/A
11249614	12/2021	Brody	N/A	N/A
11263254	12/2021	Baril et al.	N/A	N/A
11270491	12/2021	Monroy-Hernández et al.	N/A	N/A
11284144	12/2021	Kotsopoulos et al.	N/A	N/A
12047337	12/2023	Smetanin et al.	N/A	N/A
2002/0067362	12/2001	Agostino Nocera et al.	N/A	N/A
2002/0169644	12/2001	Greene	N/A	N/A
2004/0177116	12/2003	Mcconn et al.	N/A	N/A
2005/0162419	12/2004	Kim et al.	N/A	N/A
2005/0206610	12/2004	Cordelli	N/A	N/A
2006/0294465	12/2005	Ronen et al.	N/A	N/A
2007/0113181	12/2006	Blattner et al.	N/A	N/A
2007/0168863	12/2006	Blattner et al.	N/A	N/A
2007/0176921	12/2006	Iwasaki et al.	N/A	N/A
2008/0158222	12/2007	Li et al.	N/A	N/A
2008/0162649	12/2007	Lee et al.	N/A	N/A
2009/0016617	12/2008	Bregman-amitai et al.	N/A	N/A
2009/0055484	12/2008	Vuong et al.	N/A	N/A
2009/0063645	12/2008	Casey et al.	N/A	N/A
2009/0070688	12/2008	Gyorfi et al.	N/A	N/A
2009/0099925	12/2008	Mehta et al.	N/A	N/A
2009/0106672	12/2008	Burstrom	N/A	N/A
2009/0158170	12/2008	Narayanan et al.	N/A	N/A
2009/0177976	12/2008	Bokor et al.	N/A	N/A
2009/0202114	12/2008	Morin et al.	N/A	N/A
2009/0265604	12/2008	Howard et al.	N/A	N/A
2009/0300525	12/2008	Jolliff et al.	N/A	N/A

2009/0303984	12/2008	Clark et al.	N/A	N/A
2010/0011422	12/2009	Mason et al.	N/A	N/A
2010/0023885	12/2009	Reville et al.	N/A	N/A
2010/0115426	12/2009	Liu et al.	N/A	N/A
2010/0162149	12/2009	Sheleheda et al.	N/A	N/A
2010/0203968	12/2009	Gill et al.	N/A	N/A
2010/0227682	12/2009	Reville et al.	N/A	N/A
2011/0093780	12/2010	Dunn	N/A	N/A
2011/0115798	12/2010	Nayar et al.	N/A	N/A
2011/0148864	12/2010	Lee et al.	N/A	N/A
2011/0239136	12/2010	Goldman et al.	N/A	N/A
2011/0320531	12/2010	Cheah	709/203	H04L 67/10
2012/0113106	12/2011	Choi et al.	N/A	N/A
2012/0124458	12/2011	Cruzada	N/A	N/A
2012/0130717	12/2011	Xu et al.	N/A	N/A
2012/0166532	12/2011	Juan et al.	N/A	N/A
2013/0103760	12/2012	Golding et al.	N/A	N/A
2013/0201187	12/2012	Tong et al.	N/A	N/A
2013/0249948	12/2012	Reitan	N/A	N/A
2013/0257877	12/2012	Davis	N/A	N/A
2014/0043329	12/2013	Wang et al.	N/A	N/A
2014/0055554	12/2013	Du et al.	N/A	N/A
2014/0125678	12/2013	Wang et al.	N/A	N/A
2014/0129343	12/2013	Finster et al.	N/A	N/A
2014/0245183	12/2013	Lewis	715/753	H04N 21/25891
2015/0206349	12/2014	Rosenthal et al.	N/A	N/A
2016/0134840	12/2015	Mcculloch	N/A	N/A
2016/0150009	12/2015	Leroy et al.	N/A	N/A
2016/0234149	12/2015	Tsuda et al.	N/A	N/A
2016/0364106	12/2015	Koum et al.	N/A	N/A
2017/0080346	12/2016	Abbas	N/A	N/A
2017/0087473	12/2016	Siegel et al.	N/A	N/A
2017/0113140	12/2016	Blackstock et al.	N/A	N/A
2017/0118145	12/2016	Aittoniemi et al.	N/A	N/A
2017/0199855	12/2016	Fishbeck	N/A	N/A
2017/0235848	12/2016	Van Deusen et al.	N/A	N/A
2017/0310934	12/2016	Du et al.	N/A	N/A
2017/0312634	12/2016	Ledoux et al.	N/A	N/A
2018/0047200	12/2017	O'hara et al.	N/A	N/A
2018/0113587	12/2017	Allen et al.	N/A	N/A
2018/0115503	12/2017	Baldwin et al.	N/A	N/A
2018/0198743	12/2017	Blackstock et al.	N/A	N/A
2018/0205681	12/2017	Gong et al.	N/A	N/A
2018/0225703	12/2017	State	N/A	G06Q 30/0242
2018/0315076	12/2017	Andreou	N/A	N/A
2018/0315133	12/2017	Brody et al.	N/A	N/A
2018/0315134	12/2017	Amitay et al.	N/A	N/A
2019/0001223	12/2018	Blackstock et al.	N/A	N/A

2019/0052934	12/2018	Groves	N/A	H04N 21/632
2019/0057616	12/2018	Cohen et al.	N/A	N/A
2019/0097958	12/2018	Collet et al.	N/A	N/A
2019/0188920	12/2018	Mcphee et al.	N/A	N/A
2019/0280997	12/2018	Baldwin et al.	N/A	N/A
2020/0306637	12/2019	Baldwin et al.	N/A	N/A
2020/0372127	12/2019	Denton et al.	N/A	N/A
2020/0410575	12/2019	Grantham et al.	N/A	N/A
2021/0074047	12/2020	Sheth et al.	N/A	N/A
2021/0089179	12/2020	Grantham et al.	N/A	N/A
2021/0104087	12/2020	Smith et al.	N/A	N/A
2021/0168108	12/2020	Antmen et al.	N/A	N/A
2021/0170270	12/2020	Brody et al.	N/A	N/A
2021/0192823	12/2020	Amitay et al.	N/A	N/A
2021/0209825	12/2020	Assouline et al.	N/A	N/A
2021/0225058	12/2020	Chand et al.	N/A	N/A
2021/0240315	12/2020	Alvi et al.	N/A	N/A
2021/0243482	12/2020	Baril et al.	N/A	N/A
2021/0243503	12/2020	Kotsopoulos et al.	N/A	N/A
2021/0266277	12/2020	Allen et al.	N/A	N/A
2021/0281897	12/2020	Brody et al.	N/A	N/A
2021/0285774	12/2020	Collins et al.	N/A	N/A
2021/0306290	12/2020	Voss	N/A	N/A
2021/0306451	12/2020	Heikkinen et al.	N/A	N/A
2021/0337277	12/2020	Scott-green	N/A	N/A
2021/0375016	12/2020	Voss et al.	N/A	N/A
2021/0385179	12/2020	Heikkinen	N/A	H04L 51/52
2021/0385180	12/2020	Al Majid et al.	N/A	N/A
2021/0397645	12/2020	Wang et al.	N/A	N/A
2021/0405831	12/2020	Mourkogiannis et al.	N/A	N/A
2021/0409535	12/2020	Mourkogiannis et al.	N/A	N/A
2022/0012929	12/2021	Blackstock et al.	N/A	N/A
2022/0148276	12/2021	Golobokov	N/A	G06T 11/60

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
109863532	12/2018	CN	N/A
110168478	12/2018	CN	N/A
2184092	12/2009	EP	N/A
2001230801	12/2000	JP	N/A
5497931	12/2013	JP	N/A
101445263	12/2013	KR	N/A
WO-2003094072	12/2002	WO	N/A
WO-2004095308	12/2003	WO	N/A
WO-2006107182	12/2005	WO	N/A
WO-2007134402	12/2006	WO	N/A
WO-2012139276	12/2011	WO	N/A

WO-2013027893	12/2012	WO	N/A
WO-2013152454	12/2012	WO	N/A
WO-2013166588	12/2012	WO	N/A
WO-2014031899	12/2013	WO	N/A
WO-2014194439	12/2013	WO	N/A
WO-2016090605	12/2015	WO	N/A
WO-2018081013	12/2017	WO	N/A
WO-2018102562	12/2017	WO	N/A
WO-2018129531	12/2017	WO	N/A
WO-2019089613	12/2018	WO	N/A
2022103862	12/2021	WO	N/A
WO-2025010208	12/2024	WO	N/A

OTHER PUBLICATIONS

“U.S. Appl. No. 18/346,667, Examiner Interview Summary mailed Feb. 14, 2024”, 2 pgs. cited by applicant

“U.S. Appl. No. 18/346,667, Non Final Office Action mailed Nov. 21, 2023”, 21 pgs. cited by applicant

“U.S. Appl. No. 18/346,667, Notice of Allowance mailed Mar. 15, 2024”, 13 pgs. cited by applicant

“U.S. Appl. No. 18/346,667, Response filed Feb. 14, 2024 to Non Final Office Action mailed Nov. 21, 2023”, 11 pgs. cited by applicant

“Bitmoji”, Snapchat Support, [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20190503063620/https://support.snapchat.com/en-US/a/bitmoji>>, (captured May 3, 2019), 2 pgs. cited by applicant

“Bitmoji Chrome Extension”, [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20200919024925/https://support.bimoji.com/hc/en-us/articles/360001494066>>, (Sep. 19, 2020), 5 pgs. cited by applicant

“Bitmoji Customize text”, [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20210225200456/https://support.bitmoji.com/hc/en-us/articles/360034632291-Customize-Text-on-Bitmoji-Stickers>>, (captured Feb. 25, 2021), 3 pgs. cited by applicant

“Bitmoji Family”, Snapchat Support, [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20190503063620/https://support.snapchat.com/en-US/article/bitmoji-family>>, (captured May 3, 2019), 4 pgs. cited by applicant

“Instant Comics Starring You & Your Friends”, Bitstrips Inc, [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20150206000940/http://company.bitstrips.com/bitstrips-app.html>>, (captured Feb. 6, 2015), 3 pgs. cited by applicant

“Manage Your Bitmoji”, Snapchat Support, [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20190503063620/https://support.snapchat.com/en-US/a/manage-bitmoji>>, (captured May 3, 2019), 3 pgs. cited by applicant

“Your Own Personal Emoji”, Bitstrips Inc, [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20150205232004/http://bitmoji.com/>>, (captured Feb. 5, 2015), 3 pgs. cited by applicant

Carnahan, Daniel, “Snap is Offering Personalized Video Content Through Bitmoji TV”, Business Insider, [Online] Retrieved from the Internet: <URL: <https://www.businessinsider.com/snap-offers-personalized-video-content-through-bitmoji-tv-2019-12>>, (2019), 10 pgs. cited by applicant

Constine, Josh, “Snapchat launches Bitmoji merch and comic strips starring your avatar”, TechCrunch, [Online] Retrieved from the Internet: <URL: <https://techcrunch.com/2018/11/13/bitmoji-store/>>, (Nov. 13, 2018), 16 pgs. cited by applicant

Constine, Josh, "Snapchat Launches Bitmoji TV: Zany 4-min Cartoons of Your Avatar", TechCrunch, [Online] Retrieved from the Internet: <URL: <https://techcrunch.com/2020/01/30/bitmoji-tv/>>, (Jan. 30, 2020), 13 pgs. cited by applicant

MacMillan, Douglas, "Snapchat Buys Bitmoji App for More Than \$100 Million", The Wallstreet Journal, [Online] Retrieved from the Internet: <URL: <https://www.wsj.com/articles/snapchat-buys-bitmoji-app-for-more-than-100-million-1458876017>>, (Mar. 25, 2016), 5 pgs. cited by applicant

Newton, Casey, "Your Snapchat friendships now have their own profiles—and merchandise", The Verge, [Online] Retrieved from the Internet: <URL: <https://www.theverge.com/2018/11/13/18088772/snapchat-friendship-profiles-bitmoji-merchandise-comics>>, (Nov. 13, 2018), 5 pgs. cited by applicant

Ong, Thuy, "Snapchat takes Bitmoji deluxe with hundreds of new customization options", The Verge, [Online] Retrieved from the Internet on Nov. 2, 2018: <URL: <https://www.theverge.com/2018/1/30/16949402/bitmoji-deluxe-snapchat-customization>>, (Jan. 30, 2018), 2 pgs. cited by applicant

Reign, Ashley, "How To Add My Friend's Bitmoji To My Snapchat", Women.com, [Online] Retrieved from the Internet: <URL: <https://www.women.com/ashleyreign/lists/how-to-add-my-friends-bitmoji-to-my-snapchat>>, (Jun. 30, 2017), 7 pgs. cited by applicant

Tumbokon, Karen, "Snapchat Update: How To Add Bitmoji To Customizable Geofilters", International Business Times, [Online] Retrieved from the Internet : <URL: <https://www.ibtimes.com/snapchat-update-how-add-bitmoji-customizable-geofilters-2448152>>, (Nov. 18, 2016), 6 pgs. cited by applicant

"International Application Serial No. PCT/US2024/036244, International Search Report mailed Oct. 22, 2024", 4 pgs. cited by applicant

"International Application Serial No. PCT/US2024/036244, Written Opinion mailed Oct. 22, 2024", 8 pgs. cited by applicant

Primary Examiner: Huang; Kaylee J

Attorney, Agent or Firm: SCHWEGMAN LUNDBERG & WOESSNER, P.A.

Background/Summary

CLAIM OF PRIORITY (1) This application is a continuation of U.S. patent application Ser. No. 18/346,667, filed Jul. 3, 2023, which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

(1) The present disclosure relates generally to generating media content, and more specifically to generate media content during user interaction with other users.

BACKGROUND

(2) The popularity of electronic messaging, particularly instant messaging, continues to grow. Users increasingly share media content items such as electronic images and videos with each other. Users are communicate with each other using interaction applications on their mobile phones. Users also utilize mobile devices to communicate with each other using various systems that include messaging functionality (also referred to as chat functionality) suitable for sharing such messages.

(3) Multiple computer-implemented applications exist that permit users to share content with other users through messaging clients running on user systems. Some of such computer-implemented applications can be designed to run on a mobile device such as a phone, a tablet, or a wearable device. The backend service provided on a server can perform operations that may require resources greater than is reasonable to perform at a user system (e g., storing large amounts of data

or performing computationally expensive processing).

(4) A messaging application running on a user system provides a user interface that allows a user to send and receive messages. The user interface enables the user to include various types of message content, such as text or image content, in a message. The user interface provides a message composition area where the user can add and edit message content before a message is transmitted to another user. For example, the user can type text to the message composition area, and then select a user-selectable element in the form of a send button to cause transmission of a message (that includes the desired text) to another user.

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

- (1) In the drawings, which are not necessarily drawn to scale, like numerals may describe similar components in different views. To identify the discussion of any particular element or act more easily, the most significant digit or digits in a reference number refer to the figure number in which that element is first introduced. Some non-limiting examples are illustrated in the figures of the accompanying drawings in which:
- (2) FIG. 1 is a diagrammatic representation of a networked environment in which the present disclosure may be deployed, according to some examples.
- (3) FIG. 2 is a diagrammatic representation of an interaction system that has both client-side and server-side functionality, according to some examples.
- (4) FIG. 3 is a diagrammatic representation of a data structure as maintained in a database, according to some examples.
- (5) FIG. 4 illustrates a flowchart for determining a media content item to display for an interaction function, according to some examples.
- (6) FIG. 5 illustrates a flowchart for applying a placeholder head in a media content item, according to some examples.
- (7) FIG. 6 illustrates a flowchart for replacing the placeholder head with a user's head in a media content item, according to some examples.
- (8) FIG. 7 is a user interface diagram displaying a chat window between a first user and a second user, according to some examples.
- (9) FIG. 8 is a user interface diagram displaying an apportioned section of the user interface for displaying a set of media content items, according to some examples.
- (10) FIG. 9 is a user interface diagram displaying a selected media content item in a chat window, according to some examples.
- (11) FIG. 10 is a user interface diagram illustrating updated media content items after a user successfully takes a self-image, according to some examples.
- (12) FIG. 11 illustrates a set of user interfaces that show user interfaces displayed for a user from when the user has not yet taken a self-image to when the placeholder space in a media content item is updated with the user's or another user's head, according to some examples.
- (13) FIG. 12 is a diagrammatic representation of a message, according to some examples.
- (14) FIG. 13 illustrates a system including a head-wearable apparatus, according to some examples.
- (15) FIG. 14 is a diagrammatic representation of a machine in the form of a computer system within which a set of instructions may be executed to cause the machine to perform any one or more of the methodologies discussed herein, according to some examples.
- (16) FIG. 15 is a block diagram showing a software architecture within which examples may be implemented.

DETAILED DESCRIPTION

- (17) In some cases, users have not taken a self-image of their own head, nor has another user's head

to apply to a media content item. Traditional systems are not able to replace a head of a media content item (such as a still image, video, or animation of an individual or character) with a self-image of a person's head. For example, the user can be exchanging conversation messages with another user (such as a friend) in a chat window. However, the user may not have taken a self-image nor is able to use the head of the friend to apply to media content items. In such circumstances, the system does not have the ability to provide a personalized media content item to send to the friend in the chat window where the head of the media content item could be replaced with the user's head or friend's head.

(18) Example interaction systems described herein enable users to send such media content items even if the user does not have a user's head to apply (such as if the user has not completed the onboarding process of taking a self-image to personalize such media content items or has an image of the friend's head available for the media content item). The system determines that a user is interacting with another user (such as exchanging messages in a chat window with a friend). The system then accesses a user's profile. After determining that the user has not completed the onboarding process of capturing or designating a self-image for the user's profile, the system also checks whether the friend in the chat completed the onboarding process of capturing or designating a self-image. The system also checks the friend's profile to determine whether the friend has allowed other users to use the friend's self-image in media content items.

(19) If a self-image of the user or friend is unavailable, the system then accesses sets of media content items and replaces the head portion of the individual or character that is shown in the media content items with a placeholder space, such as a blank oval. The set of media content items with the blank oval are displayed in the user interface and can be sent to the friend.

(20) If the user chooses to send a media content item with a blank head, the system displays the media content item in the chat window for both the user and the friend. The chat window displays a user selectable element (such as a banner or embedded within the media content item so that the user can select the media content item itself) that, when selected, initiates opening of the camera to begin the onboarding process of taking a self-image. Upon user completion of the onboarding process, the system automatically updates the media content item sent to the chat and other media content items that have not yet been sent to the chat by replacing the blank space with the user's head.

(21) Advantageously, the systems and methods described herein enable users to use these media content items without having completed the onboarding process of taking a self-image. Moreover, the systems encourage users to complete the onboarding process by providing an easily accessible user interface icon that automatically opens the camera of a user's mobile device so the user can take a self-image.

(22) When the effects in this disclosure are considered in aggregate, one or more of the methodologies described herein may improve known systems, providing additional functionality (such as, but not limited to, the functionality mentioned above), making them easier, faster, or more intuitive to operate, and/or obviating a need for certain efforts or resources that otherwise would be involved in an electronic interaction process. Computing resources used by one or more machines, databases, or networks may thus be more efficiently utilized or even reduced.

(23) Networked Computing Environment

(24) FIG. 1 is a block diagram showing an example interaction system **100** for facilitating interactions (e.g., exchanging text messages, conducting text audio and video calls, sending or receiving content items, or playing games) over a network. The interaction system **100** includes multiple user systems **102**, each of which hosts multiple applications, including an interaction client **104** and other applications **106**. Each interaction client **104** is communicatively coupled, via one or more communication networks including a network **108** (e.g., the Internet), to other instances of the interaction client **104** (e.g., hosted on respective other user systems **102**), an interaction server system **110** and third-party servers **112**). An interaction client **104** can also

communicate with locally hosted applications **106** using Applications Program Interfaces (APIs).
(25) Each user system **102** may include multiple user devices, such as a mobile device **114**, head-wearable apparatus **116**, and a computer client device **118** that are communicatively connected to exchange data and messages.

(26) An interaction client **104** interacts with other interaction clients **104** and with the interaction server system **110** via the network **108**. The data exchanged between the interaction clients **104** (e.g., interactions **120**) and between other interaction clients **104** and the interaction server system **110** includes functions (e.g., commands to invoke functions) and payload data (e.g., text, audio, video, or other multimedia data).

(27) The interaction server system **110** provides server-side functionality via the network **108** to the interaction clients **104**. While certain functions of the interaction system **100** are described herein as being performed by either an interaction client **104** or by the interaction server system **110**, the location of certain functionality either within the interaction client **104** or the interaction server system **110** may be a design choice. For example, it may be technically preferable to initially deploy particular technology and functionality within the interaction server system **110** but to later migrate this technology and functionality to the interaction client **104** where a user system **102** has sufficient processing capacity.

(28) The interaction server system **110** supports various services and operations that are provided to the interaction clients **104**. Such operations include transmitting data to, receiving data from, and processing data generated by the interaction clients **104**. This data may include message content, client device information, geolocation information, media augmentation and overlays, message content persistence conditions, entity relationship information, and live event information. Data exchanges within the interaction system **100** are invoked and controlled through functions available via user interfaces (UIs) of the interaction clients **104**.

(29) Turning now specifically to the interaction server system **110**, an API server **122** is coupled to and provides programmatic interfaces to interaction servers **124**, making the functions of the interaction servers **124** accessible to interaction clients **104**, other applications **106** and third-party server **112**. The interaction servers **124** are communicatively coupled to a database server **126**, facilitating access to a database **128** that stores data associated with interactions processed by the interaction servers **124**. Similarly, a web server **130** is coupled to the interaction servers **124** and provides web-based interfaces to the interaction servers **124**. To this end, the web server **130** processes incoming network requests over the Hypertext Transfer Protocol (HTTP) and several other related protocols.

(30) The API server **122** receives and transmits interaction data (e.g., commands and message payloads) between the interaction servers **124** and the user systems **102** (and, for example, interaction clients **104** and other application **106**) and the third-party server **112**. Specifically, the API server **122** provides a set of interfaces (e.g., routines and protocols) that can be called or queried by the interaction client **104** and other applications **106** to invoke functionality of the interaction servers **124**. The API server **122** exposes various functions supported by the interaction servers **124**, including account registration; login functionality; the sending of interaction data, via the interaction servers **124**, from a particular interaction client **104** to another interaction client **104**; the communication of media files (e.g., images or video) from an interaction client **104** to the interaction servers **124**; the settings of a collection of media data (e.g., a story); the retrieval of a list of friends of a user of a user system **102**; the retrieval of messages and content; the addition and deletion of entities (e.g., friends) to an entity relationship graph (e.g., the entity graph **310**); the location of friends within an entity relationship graph; and opening an application event (e.g., relating to the interaction client **104**).

(31) The interaction servers **124** host multiple systems and subsystems, described below with reference to FIG. 2.

(32) Linked Applications

(33) Returning to the interaction client **104**, features and functions of an external resource (e.g., a linked application **106** or applet) are made available to a user via an interface of the interaction client **104**. In this context, “external” refers to the fact that the application **106** or applet is external to the interaction client **104**. The external resource is often provided by a third party but may also be provided by the creator or provider of the interaction client **104**. The interaction client **104** receives a user selection of an option to launch or access features of such an external resource. The external resource may be the application **106** installed on the user system **102** (e.g., a “native app”), or a small-scale version of the application (e.g., an “applet”) that is hosted on the user system **102** or remote of the user system **102** (e.g., on third-party servers **112**). The small-scale version of the application includes a subset of features and functions of the application (e.g., the full-scale, native version of the application) and is implemented using a markup-language document. In some examples, the small-scale version of the application (e.g., an “applet”) is a web-based, markup-language version of the application and is embedded in the interaction client **104**. In addition to using markup-language documents (e.g., a *.ml file), an applet may incorporate a scripting language (e.g., a *.js file or a .json file) and a style sheet (e.g., a *.ss file).

(34) In response to receiving a user selection of the option to launch or access features of the external resource, the interaction client **104** determines whether the selected external resource is a web-based external resource or a locally installed application **106**. In some cases, applications **106** that are locally installed on the user system **102** can be launched independently of and separately from the interaction client **104**, such as by selecting an icon corresponding to the application **106** on a home screen of the user system **102**. Small-scale versions of such applications can be launched or accessed via the interaction client **104** and, in some examples, no or limited portions of the small-scale application can be accessed outside of the interaction client **104**. The small-scale application can be launched by the interaction client **104** receiving, from third-party servers **112** for example, a markup-language document associated with the small-scale application and processing such a document.

(35) In response to determining that the external resource is a locally installed application **106**, the interaction client **104** instructs the user system **102** to launch the external resource by executing locally stored code corresponding to the external resource. In response to determining that the external resource is a web-based resource, the interaction client **104** communicates with the third-party servers **112** (for example) to obtain a markup-language document corresponding to the selected external resource. The interaction client **104** then processes the obtained markup-language document to present the web-based external resource within a user interface of the interaction client **104**.

(36) The interaction client **104** can notify a user of the user system **102**, or other users related to such a user (e.g., “friends”), of activity taking place in one or more external resources. For example, the interaction client **104** can provide participants in a conversation (e.g., a chat session) in the interaction client **104** with notifications relating to the current or recent use of an external resource by one or more members of a group of users. One or more users can be invited to join in an active external resource or to launch a recently used but currently inactive (in the group of friends) external resource. The external resource can provide participants in a conversation, each using respective interaction clients **104**, with the ability to share an item, status, state, or location in an external resource in a chat session with one or more members of a group of users. The shared item may be an interactive chat card with which members of the chat can interact, for example, to launch the corresponding external resource, view specific information within the external resource, or take the member of the chat to a specific location or state within the external resource. Within a given external resource, response messages can be sent to users on the interaction client **104**. The external resource can selectively include different media items in the responses, based on a current context of the external resource.

(37) The interaction client **104** can present a list of the available external resources (e.g.,

applications **106** or applets) to a user to launch or access a given external resource. This list can be presented in a context-sensitive menu. For example, the icons representing different applications **106** (or applets) can vary based on how the menu is launched by the user (e.g., from a conversation interface or from a non-conversation interface).

(38) System Architecture

(39) FIG. 2 is a block diagram illustrating further details regarding the interaction system **100**, according to some examples. Specifically, the interaction system **100** is shown to comprise the interaction client **104** and the interaction servers **124**. The interaction system **100** embodies multiple subsystems, which are supported on the client-side by the interaction client **104** and on the server-side by the interaction servers **124**. In some examples, these subsystems are implemented as microservices. A microservice subsystem (e.g., a microservice application) may have components that enable it to operate independently and communicate with other services. Example components of microservice subsystem may include: Function logic: The function logic implements the functionality of the microservice subsystem, representing a specific capability or function that the microservice provides. API interface: Microservices may communicate with each other component through well-defined APIs or interfaces, using lightweight protocols such as REST or messaging. The API interface defines the inputs and outputs of the microservice subsystem and how it interacts with other microservice subsystems of the interaction system **100**. Data storage: A microservice subsystem may be responsible for its own data storage, which may be in the form of a database, cache, or other storage mechanism (e.g., using the database server **126** and database **128**). This enables a microservice subsystem to operate independently of other microservices of the interaction system **100**. Service discovery: Microservice subsystems may find and communicate with other microservice subsystems of the interaction system **100**. Service discovery mechanisms enable microservice subsystems to locate and communicate with other microservice subsystems in a scalable and efficient way. Monitoring and logging: Microservice subsystems may need to be monitored and logged in order to ensure availability and performance. Monitoring and logging mechanisms enable the tracking of health and performance of a microservice subsystem.

(40) In some examples, the interaction system **100** may employ a monolithic architecture, a service-oriented architecture (SOA), a function-as-a-service (FaaS) architecture, or a modular architecture:

(41) Example subsystems are discussed below.

(42) An image processing system **202** provides various functions that enable a user to capture and augment (e.g., annotate or otherwise modify or edit) media content associated with a message.

(43) A camera system **204** includes control software (e.g., in a camera application) that interacts with and controls camera hardware (e.g., directly or via operating system controls) of the user system **102** to modify and augment real-time images captured and displayed via the interaction client **104**.

(44) The augmentation system **206** provides functions related to the generation and publishing of augmentations (e.g., media overlays) for images captured in real-time by cameras of the user system **102** or retrieved from memory of the user system **102**. For example, the augmentation system **206** operatively selects, presents, and displays media overlays (e.g., an image filter or an image lens) to the interaction client **104** for the augmentation of real-time images received via the camera system **204** or stored images retrieved from memory **1302** of a user system **102**. These augmentations are selected by the augmentation system **206** and presented to a user of an interaction client **104**, based on a number of inputs and data, such as for example: Geolocation of the user system **102**; and Entity relationship information of the user of the user system **102**.

(45) An augmentation may include audio and visual content and visual effects. Examples of audio and visual content include pictures, texts, logos, animations, and sound effects. An example of a visual effect includes color overlaying. The audio and visual content or the visual effects can be applied to a media content item (e.g., a photo or video) at user system **102** for communication in a

message, or applied to video content, such as a video content stream or feed transmitted from an interaction client **104**. As such, the image processing system **202** may interact with, and support, the various subsystems of the communication system **208**, such as the messaging system **210** and the video communication system **212**.

(46) A media overlay may include text or image data that can be overlaid on top of a photograph taken by the user system **102** or a video stream produced by the user system **102**. In some examples, the media overlay may be a location overlay (e.g., Venice beach), a name of a live event, or a name of a merchant overlay (e.g., Beach Coffee House). In further examples, the image processing system **202** uses the geolocation of the user system **102** to identify a media overlay that includes the name of a merchant at the geolocation of the user system **102**. The media overlay may include other indicia associated with the merchant. The media overlays may be stored in the databases **128** and accessed through the database server **126**.

(47) The image processing system **202** provides a user-based publication platform that enables users to select a geolocation on a map and upload content associated with the selected geolocation. The user may also specify circumstances under which a particular media overlay should be offered to other users. The image processing system **202** generates a media overlay that includes the uploaded content and associates the uploaded content with the selected geolocation.

(48) The augmentation creation system **214** supports augmented reality developer platforms and includes an application for content creators (e.g., artists and developers) to create and publish augmentations (e.g., augmented reality experiences) of the interaction client **104**. The augmentation creation system **214** provides a library of built-in features and tools to content creators including, for example custom shaders, tracking technology, and templates.

(49) In some examples, the augmentation creation system **214** provides a merchant-based publication platform that enables merchants to select a particular augmentation associated with a geolocation via a bidding process. For example, the augmentation creation system **214** associates a media overlay of the highest bidding merchant with a corresponding geolocation for a predefined amount of time.

(50) A communication system **208** is responsible for enabling and processing multiple forms of communication and interaction within the interaction system **100** and includes a messaging system **210**, an audio communication system **216**, and a video communication system **212**. The messaging system **210** is responsible for enforcing the temporary or time-limited access to content by the interaction clients **104**. The messaging system **210** incorporates multiple timers (e.g., within an ephemeral timer system) that, based on duration and display parameters associated with a message or collection of messages (e.g., a story), selectively enable access (e.g., for presentation and display) to messages and associated content via the interaction client **104**. The audio communication system **216** enables and supports audio communications (e.g., real-time audio chat) between multiple interaction clients **104**. Similarly, the video communication system **212** enables and supports video communications (e.g., real-time video chat) between multiple interaction clients **104**.

(51) A user management system **218** is operationally responsible for the management of user data and profiles, and maintains entity information (e.g., stored in entity tables **308**, entity graphs **310** and profile data **302**) regarding users and relationships between users of the interaction system **100**. The user management system **218** initiates the onboarding process of capturing or designating a self-image of the user via a camera system of an interaction system, accesses user profile data to determine whether users have completed the onboarding process and enabled other friends to use their self-image, identifies and replaces head portions of media content items, provides user interface features for users to send content items with blank faces and/or initiate the onboarding process, and updated media content items with the captured or designated self-image.

(52) The user management system **218** stores user profile data. User profile databases can store self-images of users, such as a self-image to use on a head portion of a media content item. The

user management system **218** accesses user profile data to determine whether users have taken a self-image for the purposes of generating a personalized media content item with a replaced head portion. The user management system **218** accesses user profile data to determine whether users have enabled other users (such as friends) to use their self-image in media content items, such as enabling a friend to send a media content item with a head image of the user.

(53) The user management system **218** accesses sets of media content items, identifies head portions, and replaces the original head of a character in the media content item with something else, such as a placeholder space or a head of an actual user. The user management system **218** places selectable user interface elements, such as a banner or an embedded element within the media content item, to a user interface that when selected causes initiation of a camera system for taking a self-image. The user management system **218** causes changes to the user interface such as apportioning a portion of the user interface for the media content items and displaying the set of media content items.

(54) The user management system **218** determines how the set of media content items are to be displayed. If users have not taken a self-image and does not have the ability to apply a friend's self-image, then the user management system **218** uses a placeholder space for the head portion in media content items. Upon a user or friend taking the self-image, the user management system **218** updates media content items with the taken self-image.

(55) A collection management system **220** is operationally responsible for managing sets or collections of media (e.g., collections of text, image video, and audio data). A collection of content (e.g., messages, including images, video, text, and audio) may be organized into an “event gallery” or an “event story.” Such a collection may be made available for a specified time period, such as the duration of an event to which the content relates. For example, content relating to a music concert may be made available as a “story” for the duration of that music concert. The collection management system **220** may also be responsible for publishing an icon that provides notification of a particular collection to the user interface of the interaction client **104**. The collection management system **220** includes a curation function that allows a collection manager to manage and curate a particular collection of content. For example, the curation interface enables an event organizer to curate a collection of content relating to a specific event (e.g., delete inappropriate content or redundant messages). Additionally, the collection management system **220** employs machine vision (or image recognition technology) and content rules to curate a content collection automatically. In certain examples, compensation may be paid to a user to include user-generated content into a collection. In such cases, the collection management system **220** operates to automatically make payments to such users to use their content.

(56) A map system **222** provides various geographic location (e.g., geolocation) functions and supports the presentation of map-based media content and messages by the interaction client **104**. For example, the map system **222** enables the display of user icons or avatars (e.g., stored in profile data **302**) on a map to indicate a current or past location of “friends” of a user, as well as media content (e.g., collections of messages including photographs and videos) generated by such friends, within the context of a map. For example, a message posted by a user to the interaction system **100** from a specific geographic location may be displayed within the context of a map at that particular location to “friends” of a specific user on a map interface of the interaction client **104**. A user can furthermore share his or her location and status information (e.g., using an appropriate status avatar) with other users of the interaction system **100** via the interaction client **104**, with this location and status information being similarly displayed within the context of a map interface of the interaction client **104** to selected users.

(57) A game system **224** provides various gaming functions within the context of the interaction client **104**. The interaction client **104** provides a game interface providing a list of available games that can be launched by a user within the context of the interaction client **104** and played with other users of the interaction system **100**. The interaction system **100** further enables a particular user to

invite other users to participate in the play of a specific game by issuing invitations to such other users from the interaction client **104**. The interaction client **104** also supports audio, video, and text messaging (e.g., chats) within the context of gameplay, provides a leaderboard for the games, and also supports the provision of in-game rewards (e.g., coins and items).

(58) An external resource system **226** provides an interface for the interaction client **104** to communicate with remote servers (e.g., third-party servers **112**) to launch or access external resources, i.e., applications or applets. Each third-party server **112** hosts, for example, a markup language (e.g., HTML5) based application or a small-scale version of an application (e.g., game, utility, payment, or ride-sharing application). The interaction client **104** may launch a web-based resource (e.g., application) by accessing the HTML5 file from the third-party servers **112** associated with the web-based resource. Applications hosted by third-party servers **112** are programmed in JavaScript leveraging a Software Development Kit (SDK) provided by the interaction servers **124**. The SDK includes APIs with functions that can be called or invoked by the web-based application. The interaction servers **124** host a JavaScript library that provides a given external resource access to specific user data of the interaction client **104**. HTML5 is an example of technology for programming games, but applications and resources programmed based on other technologies can be used.

(59) To integrate the functions of the SDK into the web-based resource, the SDK is downloaded by the third-party server **112** from the interaction servers **124** or is otherwise received by the third-party server **112**. Once downloaded or received, the SDK is included as part of the application code of a web-based external resource. The code of the web-based resource can then call or invoke certain functions of the SDK to integrate features of the interaction client **104** into the web-based resource.

(60) The SDK stored on the interaction server system **110** effectively provides the bridge between an external resource (e.g., applications **106** or applets) and the interaction client **104**. This gives the user a seamless experience of communicating with other users on the interaction client **104** while also preserving the look and feel of the interaction client **104**. To bridge communications between an external resource and an interaction client **104**, the SDK facilitates communication between third-party servers **112** and the interaction client **104**. A bridge script running on a user system **102** establishes two one-way communication channels between an external resource and the interaction client **104**. Messages are sent between the external resource and the interaction client **104** via these communication channels asynchronously. Each SDK function invocation is sent as a message and callback. Each SDK function is implemented by constructing a unique callback identifier and sending a message with that callback identifier.

(61) By using the SDK, not all information from the interaction client **104** is shared with third-party servers **112**. The SDK limits which information is shared based on the needs of the external resource. Each third-party server **112** provides an HTML5 file corresponding to the web-based external resource to interaction servers **124**. The interaction servers **124** can add a visual representation (such as a box art or other graphic) of the web-based external resource in the interaction client **104**. Once the user selects the visual representation or instructs the interaction client **104** through a GUI of the interaction client **104** to access features of the web-based external resource, the interaction client **104** obtains the HTML5 file and instantiates the resources to access the features of the web-based external resource.

(62) The interaction client **104** presents a graphical user interface (e.g., a landing page or title screen) for an external resource. During, before, or after presenting the landing page or title screen, the interaction client **104** determines whether the launched external resource has been previously authorized to access user data of the interaction client **104**. In response to determining that the launched external resource has been previously authorized to access user data of the interaction client **104**, the interaction client **104** presents another graphical user interface of the external resource that includes functions and features of the external resource. In response to determining

that the launched external resource has not been previously authorized to access user data of the interaction client **104**, after a threshold period of time (e.g., 3 seconds) of displaying the landing page or title screen of the external resource, the interaction client **104** slides up (e.g., animates a menu as surfacing from a bottom of the screen to a middle or other portion of the screen) a menu for authorizing the external resource to access the user data. The menu identifies the type of user data that the external resource will be authorized to use. In response to receiving a user selection of an accept option, the interaction client **104** adds the external resource to a list of authorized external resources and allows the external resource to access user data from the interaction client **104**. The external resource is authorized by the interaction client **104** to access the user data under an OAuth 2 framework.

(63) The interaction client **104** controls the type of user data that is shared with external resources based on the type of external resource being authorized. For example, external resources that include full-scale applications (e.g., an application **106**) are provided with access to a first type of user data (e.g., two-dimensional avatars of users with or without different avatar characteristics). As another example, external resources that include small-scale versions of applications (e.g., web-based versions of applications) are provided with access to a second type of user data (e.g., payment information, two-dimensional avatars of users, three-dimensional avatars of users, and avatars with various avatar characteristics). Avatar characteristics include different ways to customize a look and feel of an avatar, such as different poses, facial features, clothing, and so forth.

(64) An advertisement system **228** operationally enables the purchasing of advertisements by third parties for presentation to end-users via the interaction clients **104** and also handles the delivery and presentation of these advertisements.

(65) Data Architecture

(66) FIG. **3** is a schematic diagram illustrating data structures **300**, which may be stored in the database **304** of the interaction server system **110**, according to certain examples. While the content of the database **304** is shown to comprise multiple tables, it will be appreciated that the data could be stored in other types of data structures (e.g., as an object-oriented database).

(67) The database **304** includes message data stored within a message table **306**. This message data includes, for any particular message, at least message sender data, message recipient (or receiver) data, and a payload. Further details regarding information that may be included in a message and included within the message data stored in the message table **306**, are described below with reference to FIG. **3**.

(68) An entity table **308** stores entity data, and is linked (e.g., referentially) to an entity graph **310** and profile data **302**. Entities for which records are maintained within the entity table **308** may include individuals, corporate entities, organizations, objects, places, events, and so forth. Regardless of entity type, any entity regarding which the interaction server system **110** stores data may be a recognized entity. Each entity is provided with a unique identifier, as well as an entity type identifier (not shown).

(69) The entity graph **310** stores information regarding relationships and associations between entities. Such relationships may be social, professional (e.g., work at a common corporation or organization), interest-based, or activity-based, merely for example. Certain relationships between entities may be unidirectional, such as a subscription by an individual user to digital content of a commercial or publishing user (e.g., a newspaper or other digital media outlet, or a brand). Other relationships may be bidirectional, such as a “friend” relationship between individual users of the interaction system **100**. A friend relationship can be established by mutual agreement between two entities. This mutual agreement may be established by an offer from a first entity to a second entity to establish a friend relationship, and acceptance by the second entity of the offer for establishment of the friend relationship.

(70) Where the entity is a group, the profile data **302** for the group may similarly include one or

more avatar representations associated with the group, in addition to the group name, members, and various settings (e.g., notifications) for the relevant group.

(71) The database **304** also stores augmentation data, such as overlays or filters, in an augmentation table **312**. The augmentation data is associated with and applied to videos (for which data is stored in a video table **314**) and images (for which data is stored in an image table **316**).

(72) Filters, in some examples, are overlays that are displayed as overlaid on an image or video during presentation to a recipient user. Filters may be of various types, including user-selected filters from a set of filters presented to a sending user by the interaction client **104** when the sending user is composing a message. Other types of filters include geolocation filters (also known as geo-filters), which may be presented to a sending user based on geographic location. For example, geolocation filters specific to a neighborhood or special location may be presented within a user interface by the interaction client **104**, based on geolocation information determined by a Global Positioning System (GPS) unit of the user system **102**.

(73) Another type of filter is a data filter, which may be selectively presented to a sending user by the interaction client **104** based on other inputs or information gathered by the user system **102** during the message creation process. Examples of data filters include current temperature at a specific location, a current speed at which a sending user is traveling, battery life for a user system **102**, or the current time.

(74) Other augmentation data that may be stored within the image table **316** includes augmented reality content items (e.g., corresponding to applying “lenses” or augmented reality experiences). An augmented reality content item may be a real-time special effect and sound that may be added to an image or a video.

(75) A collections table **318** stores data regarding collections of messages and associated image, video, or audio data, which are compiled into a collection (e.g., a story or a gallery). The creation of a particular collection may be initiated by a particular user (e.g., each user for which a record is maintained in the entity table **308**). A user may create a “personal story” in the form of a collection of content that has been created and sent/broadcast by that user. To this end, the user interface of the interaction client **104** may include an icon that is user-selectable to enable a sending user to add specific content to his or her personal story.

(76) A collection may also constitute a “live story,” which is a collection of content from multiple users that is created manually, automatically, or using a combination of manual and automatic techniques. For example, a “live story” may constitute a curated stream of user-submitted content from various locations and events. Users whose client devices have location services enabled and are at a common location event at a particular time may, for example, be presented with an option, via a user interface of the interaction client **104**, to contribute content to a particular live story. The live story may be identified to the user by the interaction client **104**, based on his or her location. The end result is a “live story” told from a community perspective.

(77) A further type of content collection is known as a “location story,” which enables a user whose user system **102** is located within a specific geographic location (e.g., on a college or university campus) to contribute to a particular collection. In some examples, a contribution to a location story may employ a second degree of authentication to verify that the end-user belongs to a specific organization or other entity (e.g., is a student on the university campus).

(78) As mentioned above, the video table **314** stores video data that, in some examples, is associated with messages for which records are maintained within the message table **306**. Similarly, the image table **316** stores image data associated with messages for which message data is stored in the entity table **308**. The entity table **308** may associate various augmentations from the augmentation table **312** with various images and videos stored in the image table **316** and the video table **314**.

(79) Determining Media Content Items for Display

(80) FIG. 4 illustrates a flowchart **400** for determining the media content item to display for the

interaction function, according to some examples. Although the example flowchart **400** depicts a particular sequence of operations, the sequence may be altered without departing from the scope of the present disclosure. For example, some of the operations depicted may be performed in parallel or in a different sequence that does not materially affect the function of the flowchart **400**. In other examples, different components of an example device or system that implements the flowchart **400** may perform functions at substantially the same time or in a specific sequence.

(81) At operation **402**, the system, such as the interaction client **104** or the user management system **218**, determines that a first user is participating in an interaction function with a second user.

Interaction functions include a chat window where messages, stickers, emojis, and other media content items are shared between users. Interaction functions include users sending photos or videos to friends, either individually or in groups, which can be edited with text, stickers, filters, and drawings before being sent. Interaction functions include videos, audio, text, or other communications that disappear after certain conditions are met, such as being viewed once or setting a time limit, creating a more ephemeral and casual sharing experience.

(82) Interaction functions include a collection of videos, messages, stickers, or other media content items that are visible to friends for a certain period of hours (e.g., 24 hours). Interaction functions include displaying media content items from other users, such as publishers, creators, and influencers, where users can explore and subscribe to different channels to receive updates on their favorite content. Interaction functions include map and location functions, such as users sharing their location with friends and viewing their friends' locations on a map, or exploring a map with points of interest by other users categorized by location and events.

(83) Interaction functions include various filters and content augmentations to enhance images, videos, or other media content items to share with others, such as by adjusting the color or appearance or adding interactive elements such as animations and facial transformations, in real-time. Interaction functions include saving favorite media content items with other users in a private archive, where users can access these saved media content items later, edit them, or share them with friends. Interaction functions include personalized avatars which can be used as a profile picture to be viewed by others and in stickers, chat, and image/video decorations. Interaction functions include multiplayer games that users can play with their friends directly within the user interface of the system to share messages and media content items.

(84) At operation **404**, the system accesses profile data of the first user. Profile data of users includes personal information, such as a name, email address, phone number, date of birth, gender, education, occupation, interests, and/or the like. Profile data of users includes profile pictures, cover photos, biographies, and any other customizations made by the user to their online profiles. Profile data of users includes connections and relationships with other users, such as a user's friends, followers, and connections, as well as the groups and pages they follow or like. Profile data of users includes content users share, such as text, direct messages, photos, videos, and links, and direct messages, comments, and any other interactions users have within the platform. Profile data of users includes location data, such as the user's city or precise GPS coordinates, such as when using location-based features or when sharing content with location tags. Profile data of users includes how users interact with the platform's services, such as the content they view, like, share, or engage with, as well as the features they use and the duration of their sessions. Profile data of users includes data about the devices used to access their services, including device model, operating system, browser type, IP address, and unique identifiers like device IDs or cookies.

(85) In some examples, other users that are associated with the user (such as within an interaction function of the interactive system) include followers or friends, where users can follow or be followed by others, or form some form of relationship such that other users can see certain information, such as each other's posts on their feeds. In some examples, the other users can include "close" or "best" friends that can create a relationship to share additional information not available to others, such as private posts, targeted sharing of content, and/or the like. In some

examples, other users are users mentioned or tagged in the user's posts, comments, chat messages, or other communication that draws the attention of the tagged user and/or can initiate conversations or discussions. In some examples, other users are users that are involved in a message chat with the user, such as a private messaging feature that allows users to send messages directly to one another or within group chats among many users. In some examples, other users are users that joined a group based on shared interests or common goals. Within these groups, users can interact and form relationships based on the group's focus and/or share information among group members. In some examples, other users are users who express support for users, such as through likes, comments, or shares, or vice versa. In some examples, other users are influencers or brand ambassadors that have established large followings and are seen as authorities or trendsetters in their niches. In some examples, other users are collaborators working together on projects or create content together.

(86) The system determines, based on the profile data, whether the first user has captured or designated a self-image for use in the interaction function and/or media content item. In some examples, the system determines that the user has not captured or designated a self-image by looking for a self-image in the profile data. In some examples, the system looks in a particular storage location in the database that is designated for user self-images to be used in media content items.

(87) A self-image includes an image in which the face of the user appears. A self-image can include a self-taken image (such as a “selfie”), a headshot, a profile photo, a video still frame, and/or the like.

(88) At operation **406**, the system determines whether the first user captured the self-image. In response to determining that the first user has captured the self-image for the purposes of applying to media content items, at operation **408**, the system applies the media content to the interaction function with the first user's self-image. In some examples, the first user's self-image replaces the head of a character displayed in the media content item and is sent to a friend who is also in the chat window.

(89) At operation **406**, in response to determining that the first user has not captured or designated the self-image for the purposes of applying to media content items, at operation **410**, the system accesses profile data of the second user. Then at operation **412**, the system determines whether the second user captured or designated a self-image to use for media content items. In some examples, the system accesses profile data for a group of other users that the user is participating in an interaction function with to make such determinations described herein.

(90) In response to determining that the second user has not captured or designated the self-image for the purposes of applying to media content items, at operation **416**, the system generates and applies the media content item to the interaction function with a placeholder space. In some examples, the system replaces the head of a character displayed in the media content item with a placeholder space, such as a blank oval.

(91) At operation **412**, in response to determining that the second user has captured or designated the self-image for the purposes of applying to media content items, at operation **414**, the system determines whether the second user enabled others to use the other user's self-image in media content items. At operation **414**, in response to determining that the second user has not enabled others to use the other user's self-image, at operation **416**, the system generates and applies the media content item to the interaction function with a placeholder space. At operation **414**, in response to determining that the second user has enabled others to use the other user's self-image, at operation **418**, the system applies the self-image of the second user to the media content item.

(92) Applying a Placeholder Head for Media Content Items

(93) FIG. 5 illustrates a flowchart **500** for applying a placeholder head in a media content item, according to some examples. Although the example flowchart **500** depicts a particular sequence of operations, the sequence may be altered without departing from the scope of the present disclosure. For example, some of the operations depicted may be performed in parallel or in a different

sequence that does not materially affect the function of the flowchart **500**. In other examples, different components of an example device or system that implements the flowchart **500** may perform functions at substantially the same time or in a specific sequence.

(94) At operation **502**, the system, such as the interaction client **104** or the user management system **218**, accesses a media content item that includes at least one character, such as a person or individual. At operation **504**, the system identifies a head portion of the character in the media content item. The system can apply an object detection method that is trained to recognize specific objects, such as faces or heads. Certain object detection methods can scan the image at different scales and positions to identify the object of interest.

(95) In some examples, the system applies techniques that extract features from the image, which capture the distribution of gradient directions in localized regions, which are then fed into a classifier to detect objects like heads or faces. In some examples, the system applies Convolutional Neural Networks (CNN), which include multiple layers that learn to recognize features in the input image. Pre-trained CNN models can be fine-tuned for head or face detection tasks by training on labeled datasets. In some examples, the system applies a real-time object detection technique that uses a single CNN to both propose object regions and classify them simultaneously, which can be trained for head detection tasks using labeled datasets. In some examples, the system can apply another real-time object detection method that processes the entire image in a single pass by dividing the input image into a grid and assigning bounding boxes and class probabilities to each grid cell.

(96) In some examples, the system identifies and/or applies the appropriate algorithm depending on factors such as the complexity of the task, available computational resources, and the desired level of accuracy and speed.

(97) At operation **506**, the system replaces the head portion with a placeholder space. The system can replace the head of a character, such as an individual or animation, with other content, such as a placeholder space or another individual's head. The system can employ advanced image processing techniques and/or machine learning techniques to swap the head of a character in a media content item. In some examples, the system swaps the head/placeholder space by detecting facial landmarks in the target image and then aligning the image with landmarks on the other image or the placeholder space by applying an affine transformation or thin-plate spline warping. Then, the new head or placeholder space is seamlessly blended into the target image using seamless cloning and/or the like. In some examples, the system detects facial landmarks on a target image and aligns the facial landmarks with landmarks for the placeholder space.

(98) In some examples, the system swaps the head/placeholder space by applying Generative Adversarial Networks (GANs). The models are trained to learn a mapping from one image domain to another. By training a GAN on paired images with swapped heads or on an image with a head and an image with a placeholder space, the model can learn to replace the head of a person in an image with another person's head or placeholder space while maintaining the original image's appearance.

(99) In some examples, the system swaps the head by using autoencoder-based architectures, where separate encoder-decoder networks are trained for the source and target subjects. The encoders learn to extract facial features, while the decoders learn to reconstruct the faces or placeholder spaces. To perform head swapping, the source person's head is encoded and then decoded using the target person's decoder placeholder space, generating a new image with the target person's head or placeholder space.

(100) In some examples, the system swaps the head by segmenting the faces into semantic regions (e.g., eyes, nose, mouth) using techniques like fully convolutional networks. The segmented facial regions from the source and target images can then be aligned and combined, followed by blending to create a seamless result.

(101) The placeholder space includes a portion of the media content item that is saved to be

replaced by the head of a user. In some examples, the placeholder space includes an empty portion, such as an empty oval shape, empty square or circle, dotted lines, colored boxes or shapes (such as a gray box), transparent portions, a checkerboard pattern, placeholder icons, generic symbols, and/or the like.

(102) At operation **508**, the system displays the media content item with the replaced head portion in a user interface corresponding to the interaction function. In some examples, the system displays the media content item in a chat window where messages are exchanged between users. The system displays the media content item in the chat window at a first interaction client of the user and a second interaction client of the other user in the chat window. In some examples, the media content item is displayed with other media content items from other users, where the media content items are from publishers, creators, and influencers and where users can explore and subscribe to different channels to receive updates on their favorite content.

(103) At operation **510**, the system displays a selectable user interface element, such as with the media content item. In some examples, the system embeds the selectable user interface element within the media content item. The selectable user interface element is embedded within the media content item such that the selectable user interface element initiates an action (such as opening a camera system to capture a self-image) in response to a user selection of at least a portion of the media content item. In some examples, the system displays a selectable banner or icon.

(104) Replacing Placeholder Heads with a User's Head in Media Content Items

(105) FIG. **6** illustrates a flowchart **600** for replacing the placeholder head with a user's head in a media content item, according to some examples. Although the example flowchart **600** depicts a particular sequence of operations, the sequence may be altered without departing from the scope of the present disclosure. For example, some of the operations depicted may be performed in parallel or in a different sequence that does not materially affect the function of the flowchart **600**. In other examples, different components of an example device or system that implements the flowchart **600** may perform functions at substantially the same time or in a specific sequence.

(106) At operation **602**, the system displays a media content item with the placeholder space. The system also displays a selectable user interface element, such as a banner or embedded with the media content item.

(107) At operation **604**, the system determines if the user selects the selectable user interface element. At operation **604**, in response to the user selecting the selectable user interface element, at operation **606**, the system opens a camera system to initiate a camera feed. The system displays the camera feed from the camera system on the interaction client of the first user start a camera feed. At operation **608**, the system captures a self-image of the first user, such as in response to the user aligning the user's head on the camera feed and selecting a button to capture an image.

(108) At operation **610**, the system replaces the head portion that was currently being displayed as a placeholder space with the self-image of the first user. In some examples, the media content item with the placeholder space was posted, sent to a chat window, or otherwise selected for the interaction function. At operation **610**, the system replaces the media content item that was used in the interaction function and that includes the placeholder space with a media content item that includes the first user's self-image.

(109) At operation **604**, if the system has not received a user selection of the selectable user interface element, at operation **612**, the system determines whether a self-image was captured by a second user, the second user being associated with the interaction function. At operation **604**, in response to determining that a self-image was captured by the second user, at operation **614**, the system replaces the head portion with the self-image of the second user. At operation **604**, in response to determining that a self-image was not captured by the second user, the system returns to operation **604** to check whether the user selected the selectable user interface element.

(110) In some examples, the user has captured a self-image and the system checks whether the other user connected with the interaction function (friend also in the chat window) has captured a

self-image. In response to determining that the other user has also captured the self-image, the system identifies media content items with two head portions. For each of the identified media content items with two head portions, the system replaces a first head portion in the media content item with a head portion of the first user, and a second head portion in the media content item with a head portion of the second user. The system displays the media content items with the replaced two head portions in the chat window.

(111) Example User Interface Diagrams

(112) FIG. 7 is a user interface diagram **700** displaying a user interface for a second user **702** in a chat window **704** with a first user, according to some examples. The first user and the second user **702** exchanges messages within this chat window **704**. In some examples, the second user asks if the first user would like to “go grab some pizza.”

(113) The user interface includes a selectable user interface element **708** that enables users to add a media content item to the chat window. In some examples, the media content item includes a character (such as an animation or an individual) where a head of the character shown in the media content item is replaced with a head of the user or a placeholder space. In the example of FIG. 7, the first user and second user **702** has not completed taking a self-image to use for the media content item. Thus, the selectable user interface element **708** includes an image indicating that the media content items will have placeholder spaces.

(114) Upon user selection of the selectable user interface element **708**, the system initiates displays of the media content items that the user can select to add to the chat window **706**. The media content items can include an image or video of the user's head or placeholder space replacing the original head of the character in the media content item.

(115) The user interface includes a plurality of different media content items to select from. The media content items include: Emojis that are small images or icons that represent emotions, reactions, or objects. Stickers are larger images or animations that can be sent in a chat window. Images or photographs can be sent to other users to share visual information or document a particular event. Video clips can be used to share recorded content or document a particular event. Audio messages can be shared to communicate audible communication. Graphics Interchange Formats (GIFs) are short animations that can be used to add humor or express emotions.

(116) In response to determining that the user has not captured a self-image for use in media content items, the system accesses a set of media content items that include a character, identify a head portion of the character in the media content item, and replace the head portion with a placeholder space.

(117) FIG. 8 is a user interface diagram **800** displaying an apportioned section of the user interface for the set of media content items, according to some examples. Portion **802** of the user interface is part of the chat window, which originally took a larger portion of the user interface (for example FIG. 7). The system apports a section of the user interface, such as portion **804**, to make space for the set of media content items.

(118) The set of media content items are assessed to identify a head portion of the character **806** displayed within the media content item. The head portion is replaced with a placeholder space **808**, given that the user has not taken a self-image. In some cases, the media content items are originally generated with a placeholder face section. Each media content item is selectable by the user to include in the chat. The user interface includes a selectable banner **810** that when selected by the user, initiates opening of a camera system to begin onboarding of the user of taking a self-image.

(119) The system generates a graphical user interface and/or graphical user interface data that optimizes valuable user interface real estate. For example, the system provides a user interface where upon a selection of the user to display a set of media content items with placeholder spaces on the head of the character, the system reduces the size of a portion of the user interface, such as the chat window, and apports the unused space for the display of the set of media content items.

Moreover, the system displays a selectable banner **810** in between the chat window and the set of media content items, whereby in response to a user selection of the selectable banner, the system directly initiates the opening of the camera system for the user to take a self-image. Furthermore, the system displays a selectable user interface element near, adjacent to, or embedded within a selected media content item that is already in the chat window that, in response to a user selection, initiates opening of the camera system for the user to take a self-image. Moreover, the selectable user interface element follows the media content item in the chat window as the user scrolls through the chat window and/or as new messages are added to the chat.

(120) Such an improved display interface allows a user to more quickly access desired data stored or features available in the mobile application and/or an external database, such as displaying the set of media content items on a mobile phone while also viewing a chat window between users, or a single user selectable interface element that initiates the start of the camera system for the user to take a self-image, which upon such action, the system updates the placeholder spaces for the media content items to the head of the user (both or either the selected media content items already in the chat window and for the set of media content items available for the user to continue to add to the chat). As such, the selectable user interface element launches one or more applications or systems, such as a camera system, to provide further functionality than is typically available in a chat window.

(121) Advantageously, the specific and practical manner of displaying the limited set of information to the user via the apportioning of the chat window improves the technical problem for the user interface in electronic devices over conventional systems by enabling the user to be able to view both the chat window and the set of media content items on a single user interface, and/or more quickly sign up to use the user's self-image as the head of characters in the media content items. Accordingly, such features improve the speed of the user's navigation through various views and windows. The user is saved from navigating in between chat windows and displays of media content items, let alone having to save a copy of a potential media content item from another window or another website/application locally to then attach back to the chat window. Moreover, the user is saved from having to exit from the chat window, click through icons to identify a camera system option to take a self-image, capture only the head of the self-image, and to replace the head of characters in media content items to send to the chat window. Moreover, traditional systems do not have an option to update media content items that have already been sent to the chat after a user has taken the self-image.

(122) The system determines a number of recommended media content items to display based on a characteristic of the interaction client that the user is using. The interaction system can limit a number of media content items to display based on screen size. In some examples, the interaction system varies the number based on whether the interaction client is a mobile device or a laptop screen, or other user computing system type.

(123) In some examples, the system filters out media content items that include a plurality of head portions and/or media content items that are specific to a particular gender or age group to identify the initial set of media content items.

(124) FIG. **9** is a user interface diagram **900** displaying a selected media content item in a chat window, according to some examples. From FIG. **8**, the user selects the media content item **902**, and in FIG. **9**, the media content item **904** is displayed in the chat window with the placeholder space **906**. The media content item **904** includes a selectable user interface element **908**, such as an embedded interface element within the media content item. The user selectable user interface element moves with the media content item within the chat window. In some examples, if follow-on messages are sent after the media content item **904** is added to the chat, the media content item **904** moves in the direction of older messages (such as upward) and the selectable user interface element moves along with the media content item.

(125) In response to a user selection of the selectable user interface element, the system initiates a

camera system that begins display of a camera feed to the user. The user takes a self-image and opts-in to applying his or her face onto the media content items.

(126) In some examples, the system disables the option to save the media content item with the placeholder space onto a local memory, which is typically enabled for other media content items. In some examples, the system displays a search bar to search for other media content items that enable a placeholder space.

(127) FIG. **10** is a user interface diagram **1000** illustrating media content items after a user successfully takes a self-image, according to some examples. After a user selects the selectable user interface element and captures a self-image, the media content item **1002** that was sent to the chat window is updated to include the head of the user. The system replaces the placeholder space with the head of the user **1004**. The set of media content items **1006** on the apportioned section of the user interface also displays the head of the user **1008** instead of the placeholder space. The banner and the embedded user selectable user interface elements are removed from the user interface.

(128) FIG. **11** illustrates a set of user interfaces **1100** from when the user has not yet taken a self-image to when the placeholder spaces are updated with the user's or friend's head, according to some examples. The user interface **1102** illustrates an initial set of media content items where the heads of the original characters are shown.

(129) The system identifies the head portion for each character in the media content items and replaces the head portion with a blank or placeholder space, as shown in user interface **1104**. The user selects one of the media content items **1106** to be included in the interaction feature, such as a chat window where messages can be exchanged between a user and a friend. The media content item **1106** is displayed with a user selectable option **1108** that initiates the process of capturing a self-image of the user to use in media content items.

(130) The system determines that the user either has taken a self-image for the purposes of use in media content items and/or has the option to use the friend's self-image. The system applies the friend's face **1112** instead of the placeholder space on the media content item **1110** that is showing on the chat window. The user selectable option **1114** for the user to take the self-image is still available for the user, since the user has not yet taken the self-image to be used in media content items.

(131) The user selects the user selectable option **1108** or **1114** embedded within either media content items **1106** and **1110**. At user interface **1116**, the interaction client opens the camera system such that a user can take a self-image to be used on media content items. The interaction client blocks off certain parts of the camera feed in the shape of a user's face, such that the user would have to position the interaction client to fit within the user face. Once the user has taken a self-image, the media content item is updated to include the face of the user **1120** at user interface **1118**. The user selectable options that were previously shown (e.g., **1108**, **1114**) are now disabled.

(132) In some examples, the system replaces a different portion of a user's body, such as a user's eyes, ears, nose, mouth, neck, torso, chest, abdomen, pelvis, arms, shoulders, wrist, hand, forearm, leg, foot, ankle, skin, and/or the like.

(133) Data Communications Architecture

(134) FIG. **12** is a schematic diagram illustrating a structure of a message **1200**, according to some examples, generated by an interaction client **104** for communication to a further interaction client **104** via the interaction servers **124**. The content of a particular message **1200** is used to populate the message table **306** stored within the database **304**, accessible by the interaction servers **124**. Similarly, the content of a message **1200** is stored in memory as “in-transit” or “in-flight” data of the user system **102** or the interaction servers **124**. A message **1200** is shown to include the following example components: Message identifier **1202**: a unique identifier that identifies the message **1200**. Message text payload **1204**: text, to be generated by a user via a user interface of the user system **102**, and that is included in the message **1200**. Message image payload **1206**: image data, captured by a camera component of a user system **102** or retrieved from a memory component

of a user system **102**, and that is included in the message **1200**. Image data for a sent or received message **1200** may be stored in the image table **316**. Message video payload **1208**: video data, captured by a camera component or retrieved from a memory component of the user system **102**, and that is included in the message **1200**. Video data for a sent or received message **1200** may be stored in the image table **316**. Message audio payload **1210**: audio data, captured by a microphone or retrieved from a memory component of the user system **102**, and that is included in the message **1200**. Message augmentation data **1212**: augmentation data (e.g., filters, stickers, or other annotations or enhancements) that represents augmentations to be applied to message image payload **1206**, message video payload **1208**, or message audio payload **1210** of the message **1200**. Augmentation data for a sent or received message **1200** may be stored in the augmentation table **312**. Message duration parameter **1214**: parameter value indicating, in seconds, the amount of time for which content of the message (e.g., the message image payload **1206**, message video payload **1208**, message audio payload **1210**) is to be presented or made accessible to a user via the interaction client **104**. Message geolocation parameter **1216**: geolocation data (e.g., latitudinal and longitudinal coordinates) associated with the content payload of the message. Multiple message geolocation parameter **1216** values may be included in the payload, each of these parameter values being associated with respect to content items included in the content (e.g., a specific image within the message image payload **1206**, or a specific video in the message video payload **1208**). Message story identifier **1218**: identifier values identifying one or more content collections (e.g., “stories” identified in the collections table **318**) with which a particular content item in the message image payload **1206** of the message **1200** is associated. For example, multiple images within the message image payload **1206** may each be associated with multiple content collections using identifier values. Message tag **1220**: each message **1200** may be tagged with multiple tags, each of which is indicative of the subject matter of content included in the message payload. For example, where a particular image included in the message image payload **1206** depicts an animal (e.g., a lion), a tag value may be included within the message tag **1220** that is indicative of the relevant animal. Tag values may be generated manually, based on user input, or may be automatically generated using, for example, image recognition. Message sender identifier **1222**: an identifier (e.g., a messaging system identifier, email address, or device identifier) indicative of a user of the user system **102** on which the message **1200** was generated and from which the message **1200** was sent. Message receiver identifier **1224**: an identifier (e.g., a messaging system identifier, email address, or device identifier) indicative of a user of the user system **102** to which the message **1200** is addressed. (135) The contents (e.g., values) of the various components of message **1200** may be pointers to locations in tables within which content data values are stored. For example, an image value in the message image payload **1206** may be a pointer to (or address of) a location within an image table **316**. Similarly, values within the message video payload **1208** may point to data stored within an image or video table **316**, values stored within the message augmentation data **1212** may point to data stored in an augmentation table **312**, values stored within the message story identifier **1218** may point to data stored in a collections table **318**, and values stored within the message sender identifier **1222** and the message receiver identifier **1224** may point to user records stored within an entity table **308**.

(136) System with Head-Wearable Apparatus

(137) FIG. **13** illustrates a system **1300** including a head-wearable apparatus **116** with a selector input device, according to some examples. FIG. **13** is a high-level functional block diagram of an example head-wearable apparatus **116** communicatively coupled to a mobile device **114** and various server systems **1304** (e.g., the interaction server system **110**) via various networks **108**. The networks **108** may include any combination of wired and wireless connections.

(138) The head-wearable apparatus **116** includes one or more cameras, each of which may be, for example, a visible light camera **1306**, an infrared emitter **1308**, and an infrared camera **1310**.

(139) An interaction client, such as a mobile device **114** connects with head-wearable apparatus **116**

using both a low-power wireless connection **1312** and a high-speed wireless connection **1314**. The mobile device **114** is also connected to the server system **1304** and the network **1316**.

(140) The head-wearable apparatus **116** further includes two image displays of the image display of optical assembly **1318**. The two image displays of optical assembly **1318** include one associated with the left lateral side and one associated with the right lateral side of the head-wearable apparatus **116**. The head-wearable apparatus **116** also includes an image display driver **1320**, an image processor **1322**, low-power circuitry **1324**, and high-speed circuitry **1326**. The image display of optical assembly **1318** is for presenting images and videos, including an image that can include a graphical user interface to a user of the head-wearable apparatus **116**.

(141) The image display driver **1320** commands and controls the image display of optical assembly **1318**. The image display driver **1320** may deliver image data directly to the image display of optical assembly **1318** for presentation or may convert the image data into a signal or data format suitable for delivery to the image display device. For example, the image data may be video data formatted according to compression formats, such as H.264 (MPEG-4 Part **10**), HEVC, Theora, Dirac, RealVideo RV40, VP8, VP9, or the like, and still image data may be formatted according to compression formats such as Portable Network Group (PNG), Joint Photographic Experts Group (JPEG), Tagged Image File Format (TIFF) or exchangeable image file format (EXIF) or the like.

(142) The head-wearable apparatus **116** includes a frame and stems (or temples) extending from a lateral side of the frame. The head-wearable apparatus **116** further includes a user input device **1328** (e.g., touch sensor or push button), including an input surface on the head-wearable apparatus **116**. The user input device **1328** (e.g., touch sensor or push button) is to receive from the user an input selection to manipulate the graphical user interface of the presented image.

(143) The components shown in FIG. **13** for the head-wearable apparatus **116** are located on one or more circuit boards, for example a PCB or flexible PCB, in the rims or temples. Alternatively, or additionally, the depicted components can be located in the chunks, frames, hinges, or bridge of the head-wearable apparatus **116**. Left and right visible light cameras **1306** can include digital camera elements such as a complementary metal oxide-semiconductor (CMOS) image sensor, charge-coupled device, camera lenses, or any other respective visible or light-capturing elements that may be used to capture data, including images of scenes with unknown objects.

(144) The head-wearable apparatus **116** includes a memory **1302**, which stores instructions to perform a subset or all of the functions described herein. The memory **1302** can also include storage device.

(145) As shown in FIG. **13**, the high-speed circuitry **1326** includes a high-speed processor **1330**, a memory **1302**, and high-speed wireless circuitry **1332**. In some examples, the image display driver **1320** is coupled to the high-speed circuitry **1326** and operated by the high-speed processor **1330** in order to drive the left and right image displays of the image display of optical assembly **1318**. The high-speed processor **1330** may be any processor capable of managing high-speed communications and operation of any general computing system needed for the head-wearable apparatus **116**. The high-speed processor **1330** includes processing resources needed for managing high-speed data transfers on a high-speed wireless connection **1314** to a wireless local area network (WLAN) using the high-speed wireless circuitry **1332**. In certain examples, the high-speed processor **1330** executes an operating system such as a LINUX operating system or other such operating system of the head-wearable apparatus **116**, and the operating system is stored in the memory **1302** for execution. In addition to any other responsibilities, the high-speed processor **1330** executing a software architecture for the head-wearable apparatus **116** is used to manage data transfers with high-speed wireless circuitry **1332**. In certain examples, the high-speed wireless circuitry **1332** is configured to implement Institute of Electrical and Electronic Engineers (IEEE) 802.11 communication standards, also referred to herein as WI-FI®. In some examples, other high-speed communications standards may be implemented by the high-speed wireless circuitry **1332**.

(146) The low-power wireless circuitry **1334** and the high-speed wireless circuitry **1332** of the

head-wearable apparatus **116** can include short-range transceivers (Bluetooth™) and wireless wide, local, or wide area network transceivers (e.g., cellular or WI-FI®). Mobile device **114**, including the transceivers communicating via the low-power wireless connection **1312** and the high-speed wireless connection **1314**, may be implemented using details of the architecture of the head-wearable apparatus **116**, as can other elements of the network **1316**.

(147) The memory **1302** includes any storage device capable of storing various data and applications, including, among other things, camera data generated by the left and right visible light cameras **1306**, the infrared camera **1310**, and the image processor **1322**, as well as images generated for display by the image display driver **1320** on the image displays of the image display of optical assembly **1318**. While the memory **1302** is shown as integrated with high-speed circuitry **1326**, in some examples, the memory **1302** may be an independent standalone element of the head-wearable apparatus **116**. In certain such examples, electrical routing lines may provide a connection through a chip that includes the high-speed processor **1330** from the image processor **1322** or the low-power processor **1336** to the memory **1302**. In some examples, the high-speed processor **1330** may manage addressing of the memory **1302** such that the low-power processor **1336** will boot the high-speed processor **1330** any time that a read or write operation involving memory **1302** is needed.

(148) As shown in FIG. **13**, the low-power processor **1336** or high-speed processor **1330** of the head-wearable apparatus **116** can be coupled to the camera (visible light camera **1306**, infrared emitter **1308**, or infrared camera **1310**), the image display driver **1320**, the user input device **1328** (e.g., touch sensor or push button), and the memory **1302**.

(149) The head-wearable apparatus **116** is connected to a host computer. For example, the head-wearable apparatus **116** is paired with the mobile device **114** via the high-speed wireless connection **1314** or connected to the server system **1304** via the network **1316**. The server system **1304** may be one or more computing devices as part of a service or network computing system, for example, that includes a processor, a memory, and network communication interface to communicate over the network **1316** with the mobile device **114** and the head-wearable apparatus **116**.

(150) The mobile device **114** includes a processor and a network communication interface coupled to the processor. The network communication interface allows for communication over the network **1316**, low-power wireless connection **1312**, or high-speed wireless connection **1314**. Mobile device **114** can further store at least portions of the instructions for generating binaural audio content in the mobile device **114**'s memory to implement the functionality described herein.

(151) Output components of the head-wearable apparatus **116** include visual components, such as a display such as a liquid crystal display (LCD), a plasma display panel (PDP), a light-emitting diode (LED) display, a projector, or a waveguide. The image displays of the optical assembly are driven by the image display driver **1320**. The output components of the head-wearable apparatus **116** further include acoustic components (e.g., speakers), haptic components (e.g., a vibratory motor), other signal generators, and so forth. The input components of the head-wearable apparatus **116**, the mobile device **114**, and server system **1304**, such as the user input device **1328**, may include alphanumeric input components (e.g., a keyboard, a touch screen configured to receive alphanumeric input, a photo-optical keyboard, or other alphanumeric input components), point-based input components (e.g., a mouse, a touchpad, a trackball, a joystick, a motion sensor, or other pointing instruments), tactile input components (e.g., a physical button, a touch screen that provides location and force of touches or touch gestures, or other tactile input components), audio input components (e.g., a microphone), and the like.

(152) The head-wearable apparatus **116** may also include additional peripheral device elements. Such peripheral device elements may include biometric sensors, additional sensors, or display elements integrated with the head-wearable apparatus **116**. For example, peripheral device elements may include any I/O components including output components, motion components, position components, or any other such elements described herein.

(153) For example, the biometric components include components to detect expressions (e.g., hand expressions, facial expressions, vocal expressions, body gestures, or eye-tracking), measure biosignals (e.g., blood pressure, heart rate, body temperature, perspiration, or brain waves), identify a person (e.g., voice identification, retinal identification, facial identification, fingerprint identification, or electroencephalogram based identification), and the like.

(154) The motion components include acceleration sensor components (e.g., accelerometer), gravitation sensor components, rotation sensor components (e.g., gyroscope), and so forth. The position components include location sensor components to generate location coordinates (e.g., a Global Positioning System (GPS) receiver component), Wi-Fi or Bluetooth™ transceivers to generate positioning system coordinates, altitude sensor components (e.g., altimeters or barometers that detect air pressure from which altitude may be derived), orientation sensor components (e.g., magnetometers), and the like. Such positioning system coordinates can also be received over low-power wireless connections **1312** and high-speed wireless connection **1314** from the mobile device **114** via the low-power wireless circuitry **1334** or high-speed wireless circuitry **1332**.

(155) Machine Architecture

(156) FIG. **14** is a diagrammatic representation of the machine **1400** within which instructions **1402** (e.g., software, a program, an application, an applet, an app, or other executable code) for causing the machine **1400** to perform any one or more of the methodologies discussed herein may be executed. For example, the instructions **1402** may cause the machine **1400** to execute any one or more of the methods described herein. The instructions **1402** transform the general, non-programmed machine **1400** into a particular machine **1400** programmed to carry out the described and illustrated functions in the manner described. The machine **1400** may operate as a standalone device or may be coupled (e.g., networked) to other machines. In a networked deployment, the machine **1400** may operate in the capacity of a server machine or a client machine in a server-client network environment, or as a peer machine in a peer-to-peer (or distributed) network environment. The machine **1400** may comprise, but not be limited to, a server computer, a client computer, a personal computer (PC), a tablet computer, a laptop computer, a netbook, a set-top box (STB), a personal digital assistant (PDA), an entertainment media system, a cellular telephone, a smartphone, a mobile device, a wearable device (e.g., a smartwatch), a smart home device (e.g., a smart appliance), other smart devices, a web appliance, a network router, a network switch, a network bridge, or any machine capable of executing the instructions **1402**, sequentially or otherwise, that specify actions to be taken by the machine **1400**. Further, while a single machine **1400** is illustrated, the term “machine” shall also be taken to include a collection of machines that individually or jointly execute the instructions **1402** to perform any one or more of the methodologies discussed herein. The machine **1400**, for example, may comprise the user system **102** or any one of multiple server devices forming part of the interaction server system **110**. In some examples, the machine **1400** may also comprise both client and server systems, with certain operations of a particular method or algorithm being performed on the server-side and with certain operations of the particular method or algorithm being performed on the client-side.

(157) The machine **1400** may include processors **1404**, memory **1406**, and input/output I/O components **1408**, which may be configured to communicate with each other via a bus **1410**. In an example, the processors **1404** (e.g., a Central Processing Unit (CPU), a Reduced Instruction Set Computing (RISC) Processor, a Complex Instruction Set Computing (CISC) Processor, a Graphics Processing Unit (GPU), a Digital Signal Processor (DSP), an Application Specific Integrated Circuit (ASIC), a Radio-Frequency Integrated Circuit (RFIC), another processor, or any suitable combination thereof) may include, for example, a processor **1412** and a processor **1414** that execute the instructions **1402**. The term “processor” is intended to include multi-core processors that may comprise two or more independent processors (sometimes referred to as “cores”) that may execute instructions contemporaneously. Although FIG. **14** shows multiple processors **1404**, the machine **1400** may include a single processor with a single-core, a single processor with multiple cores (e.g.,

a multi-core processor), multiple processors with a single core, multiple processors with multiples cores, or any combination thereof.

(158) The memory **1406** includes a main memory **1416**, a static memory **1418**, and a storage unit **1420**, both accessible to the processors **1404** via the bus **1410**. The main memory **1406**, the static memory **1418**, and storage unit **1420** store the instructions **1402** embodying any one or more of the methodologies or functions described herein. The instructions **1402** may also reside, completely or partially, within the main memory **1416**, within the static memory **1418**, within machine-readable medium **1422** within the storage unit **1420**, within at least one of the processors **1404** (e.g., within the processor's cache memory), or any suitable combination thereof, during execution thereof by the machine **1400**.

(159) The I/O components **1408** may include a wide variety of components to receive input, provide output, produce output, transmit information, exchange information, capture measurements, and so on. The specific I/O components **1408** that are included in a particular machine will depend on the type of machine. For example, portable machines such as mobile phones may include a touch input device or other such input mechanisms, while a headless server machine will likely not include such a touch input device. It will be appreciated that the I/O components **1408** may include many other components that are not shown in FIG. **14**. In various examples, the I/O components **1408** may include user output components **1424** and user input components **1426**. The user output components **1424** may include visual components (e.g., a display such as a plasma display panel (PDP), a light-emitting diode (LED) display, a liquid crystal display (LCD), a projector, or a cathode ray tube (CRT)), acoustic components (e.g., speakers), haptic components (e.g., a vibratory motor, resistance mechanisms), other signal generators, and so forth. The user input components **1426** may include alphanumeric input components (e.g., a keyboard, a touch screen configured to receive alphanumeric input, a photo-optical keyboard, or other alphanumeric input components), point-based input components (e.g., a mouse, a touchpad, a trackball, a joystick, a motion sensor, or another pointing instrument), tactile input components (e.g., a physical button, a touch screen that provides location and force of touches or touch gestures, or other tactile input components), audio input components (e.g., a microphone), and the like.

(160) In further examples, the I/O components **1408** may include biometric components **1428**, motion components **1430**, environmental components **1432**, or position components **1434**, among a wide array of other components. For example, the biometric components **1428** include components to detect expressions (e.g., hand expressions, facial expressions, vocal expressions, body gestures, or eye-tracking), measure biosignals (e.g., blood pressure, heart rate, body temperature, perspiration, or brain waves), identify a person (e.g., voice identification, retinal identification, facial identification, fingerprint identification, or electroencephalogram-based identification), and the like.

(161) The motion components **1430** include acceleration sensor components (e.g., accelerometer), gravitation sensor components, and rotation sensor components (e.g., gyroscope).

(162) The environmental components **1432** include, for example, one or cameras (with still image/photograph and video capabilities), illumination sensor components (e.g., photometer), temperature sensor components (e.g., one or more thermometers that detect ambient temperature), humidity sensor components, pressure sensor components (e.g., barometer), acoustic sensor components (e.g., one or more microphones that detect background noise), proximity sensor components (e.g., infrared sensors that detect nearby objects), gas sensors (e.g., gas detection sensors to detection concentrations of hazardous gases for safety or to measure pollutants in the atmosphere), or other components that may provide indications, measurements, or signals corresponding to a surrounding physical environment.

(163) With respect to cameras, the user system **102** may have a camera system comprising, for example, front cameras on a front surface of the user system **102** and rear cameras on a rear surface

of the user system **102**. The front cameras may, for example, be used to capture still images and video of a user of the user system **102** (e.g., “selfies”), which may then be augmented with augmentation data (e.g., filters) described above. The rear cameras may, for example, be used to capture still images and videos in a more traditional camera mode, with these images similarly being augmented with augmentation data. In addition to front and rear cameras, the user system **102** may also include a 360° camera for capturing 360° photographs and videos.

(164) Further, the camera system of the user system **102** may include dual rear cameras (e.g., a primary camera as well as a depth-sensing camera), or even triple, quad or penta rear camera configurations on the front and rear sides of the user system **102**. These multiple cameras systems may include a wide camera, an ultra-wide camera, a telephoto camera, a macro camera, and a depth sensor, for example.

(165) The position components **1434** include location sensor components (e.g., a GPS receiver component), altitude sensor components (e.g., altimeters or barometers that detect air pressure from which altitude may be derived), orientation sensor components (e.g., magnetometers), and the like.

(166) Communication may be implemented using a wide variety of technologies. The I/O components **1408** further include communication components **1436** operable to couple the machine **1400** to a network **1438** or devices **1440** via respective coupling or connections. For example, the communication components **1436** may include a network interface component or another suitable device to interface with the network **1438**. In further examples, the communication components **1436** may include wired communication components, wireless communication components, cellular communication components, Near Field Communication (NFC) components, Bluetooth® components (e.g., Bluetooth® Low Energy), Wi-Fi® components, and other communication components to provide communication via other modalities. The devices **1440** may be another machine or any of a wide variety of peripheral devices (e.g., a peripheral device coupled via a USB).

(167) Moreover, the communication components **1436** may detect identifiers or include components operable to detect identifiers. For example, the communication components **1436** may include Radio Frequency Identification (RFID) tag reader components, NFC smart tag detection components, optical reader components (e.g., an optical sensor to detect one-dimensional bar codes such as Universal Product Code (UPC) bar code, multi-dimensional bar codes such as Quick Response (QR) code, Aztec code, Data Matrix, Dataglyph™, MaxiCode, PDF417, Ultra Code, UCC RSS-2D bar code, and other optical codes), or acoustic detection components (e.g., microphones to identify tagged audio signals). In addition, a variety of information may be derived via the communication components **1436**, such as location via Internet Protocol (IP) geolocation, location via Wi-Fi® signal triangulation, location via detecting an NFC beacon signal that may indicate a particular location, and so forth.

(168) The various memories (e.g., main memory **1416**, static memory **1418**, and memory of the processors **1404**) and storage unit **1420** may store one or more sets of instructions and data structures (e.g., software) embodying or used by any one or more of the methodologies or functions described herein. These instructions (e.g., the instructions **1402**), when executed by processors **1404**, cause various operations to implement the disclosed examples.

(169) The instructions **1402** may be transmitted or received over the network **1438**, using a transmission medium, via a network interface device (e.g., a network interface component included in the communication components **1436**) and using any one of several well-known transfer protocols (e.g., hypertext transfer protocol (HTTP)). Similarly, the instructions **1402** may be transmitted or received using a transmission medium via a coupling (e.g., a peer-to-peer coupling) to the devices **1440**.

(170) Software Architecture

(171) FIG. **15** is a block diagram **1500** illustrating a software architecture **1502**, which can be installed on any one or more of the devices described herein. The software architecture **1502** is

supported by hardware such as a machine **1504** that includes processors **1506**, memory **1508**, and I/O components **1510**. In this example, the software architecture **1502** can be conceptualized as a stack of layers, where each layer provides a particular functionality. The software architecture **1502** includes layers such as an operating system **1512**, libraries **1514**, frameworks **1516**, and applications **1518**. Operationally, the applications **1518** invoke API calls **1520** through the software stack and receive messages **1522** in response to the API calls **1520**.

(172) The operating system **1512** manages hardware resources and provides common services. The operating system **1512** includes, for example, a kernel **1524**, services **1526**, and drivers **1528**. The kernel **1524** acts as an abstraction layer between the hardware and the other software layers. For example, the kernel **1524** provides memory management, processor management (e.g., scheduling), component management, networking, and security settings, among other functionalities. The services **1526** can provide other common services for the other software layers. The drivers **1528** are responsible for controlling or interfacing with the underlying hardware. For instance, the drivers **1528** can include display drivers, camera drivers, BLUETOOTH® or BLUETOOTH® Low Energy drivers, flash memory drivers, serial communication drivers (e.g., USB drivers), WI-FI® drivers, audio drivers, power management drivers, and so forth.

(173) The libraries **1514** provide a common low-level infrastructure used by the applications **1518**. The libraries **1514** can include system libraries **1530** (e.g., C standard library) that provide functions such as memory allocation functions, string manipulation functions, mathematic functions, and the like. In addition, the libraries **1514** can include API libraries **1532** such as media libraries (e.g., libraries to support presentation and manipulation of various media formats such as Moving Picture Experts Group-4 (MPEG4), Advanced Video Coding (H.264 or AVC), Moving Picture Experts Group Layer-3 (MP3), Advanced Audio Coding (AAC), Adaptive Multi-Rate (AMR) audio codec, Joint Photographic Experts Group (JPEG or JPG), or Portable Network Graphics (PNG)), graphics libraries (e.g., an OpenGL framework used to render in two dimensions (2D) and three dimensions (3D) in a graphic content on a display), database libraries (e.g., SQLite to provide various relational database functions), web libraries (e.g., WebKit to provide web browsing functionality), and the like. The libraries **1514** can also include a wide variety of other libraries **1534** to provide many other APIs to the applications **1518**.

(174) The frameworks **1516** provide a common high-level infrastructure that is used by the applications **1518**. For example, the frameworks **1516** provide various graphical user interface (GUI) functions, high-level resource management, and high-level location services. The frameworks **1516** can provide a broad spectrum of other APIs that can be used by the applications **1518**, some of which may be specific to a particular operating system or platform.

(175) In an example, the applications **1518** may include a home application **1536**, a contacts application **1538**, a browser application **1540**, a book reader application **1542**, a location application **1544**, a media application **1546**, a messaging application **1548**, a game application **1550**, and a broad assortment of other applications such as a third-party application **1552**. The applications **1518** are programs that execute functions defined in the programs. Various programming languages can be employed to create one or more of the applications **1518**, structured in a variety of manners, such as object-oriented programming languages (e.g., Objective-C, Java, or C++) or procedural programming languages (e.g., C or assembly language). In a specific example, the third-party application **1552** (e.g., an application developed using the ANDROID™ or IOS™ software development kit (SDK) by an entity other than the vendor of the particular platform) may be mobile software running on a mobile operating system such as IOS™, ANDROID™, WINDOWS® Phone, or another mobile operating system. In this example, the third-party application **1552** can invoke the API calls **1520** provided by the operating system **1512** to facilitate functionalities described herein.

EXAMPLES

(176) In view of the above-described implementations of subject matter this application discloses

the following list of examples, wherein one feature of an example in isolation or more than one feature of an example, taken in combination and, optionally, in combination with one or more features of one or more further examples are further examples also falling within the disclosure of this application.

(177) Example 1 is a system comprising: at least one processor; and at least one memory component storing instructions that, when executed by the at least one processor, cause the at least one processor to perform operations comprising: determining participation in an interaction function by a first user of an interaction system with a second user of the interaction system; accessing profile data of the first user; determining, based on the profile data, whether the first user has captured or designated a first-user self-image for use in the interaction function; and in response to determining that the first user has not captured or designated the first-user self-image: accessing a media content item that includes, a character; identifying a head portion of the character in the media content item; replacing the head portion with a placeholder space; and displaying the media content item with the placeholder space in a user interface corresponding to the interaction function.

(178) In Example 2, the subject matter of Example 1 includes, wherein the operations further comprise, subsequent to displaying the media content item with the placeholder space: determining that the first user has captured or designated the first-user self-image; and in response to determining that the first user has captured or designated the first-user self-image, replacing the placeholder space with a head image of the first user in the user interface corresponding to the interaction function.

(179) In Example 3, the subject matter of Examples 1-2 includes, wherein the operations further comprise determining that a second user has not captured or designated a second-user self-image, wherein replacing the head portion with the placeholder space is further in response to determining that the second user has not captured or designated the second-user self-image.

(180) In Example 4, the subject matter of Examples 1-3 includes, wherein the operations further comprise determining, from profile data of a second user, that the second user has captured or designated a second-user self-image but has not enabled other users to use the second-user self-image, wherein replacing the head portion with the placeholder space is further in response to determining, from profile data of the second user, that the second user has not enabled other users to use the second-user self-image.

(181) In Example 5, the subject matter of Examples 1~4 includes, wherein the operations further comprise, subsequent to displaying the media content item with the placeholder space: determining that a second user captured or designated a second-user self-image; and in response to determining that the second user captured or designated the second-user self-image, replacing the placeholder space with the second-user self-image.

(182) In Example 6, the subject matter of Examples 1-5 includes, wherein the interaction function includes a chat window configured to display exchanged messages between the first and second users.

(183) In Example 7, the subject matter of Example 6 includes, wherein displaying the media content item includes: reducing a size of the chat window in the user interface; and apportioning unused user interface space for display of the media content item.

(184) In Example 8, the subject matter of Examples 6-7 includes, wherein the operations further include, subsequent to displaying the media content item with the placeholder space: identifying a user selection of the media content item from a set of media content items being displayed in the user interface; and in response to the user selection, causing presentation of the selected media content item in the chat window at a first interaction client of the first user and a second interaction client of the second user.

(185) In Example 9, the subject matter of Example 8 includes, wherein the operations further include, subsequent to displaying the selected media content item in the chat window: determining

that the second user captured or designated a second-user self-image; and in response determining that the second user captured or designated the second-user self-image, replacing the placeholder space in the media content item that is displayed in the chat window with a head portion of the captured or designated second-user self-image.

(186) In Example 10, the subject matter of Examples 1-9 includes, wherein the operations further include: displaying a selectable user interface element that initiates a camera feed from a camera system of a first interaction client of the first user to capture the first-user self-image, wherein the selectable user interface element is disposed adjacent to or embedded at least partially within the displayed media content item.

(187) In Example 11, the subject matter of Example 10 includes, wherein the operations further include: displaying a message between the first and second users subsequent to displaying the media content item with the placeholder space, wherein the message is displayed below the displayed media content item, wherein the selectable user interface element moves along the user interface with the displayed media content item.

(188) In Example 12, the subject matter of Examples 1-11 includes, wherein the operations further include disabling an option to save the media content item onto the at least one memory component.

(189) In Example 13, the subject matter of Examples 1-12 includes, wherein the operations further comprise, subsequent to displaying the media content item with the placeholder space: determining that the first user captured or designated the first-user self-image using a first interaction client of the first user; determining the second user captured or designated a second-user self-image of the second user using a second interaction client of the second user; and in response to determining that the first user and second user captured or designated the first-user self-image and second-user self-image, respectively: identifying a media content item with two characters; replacing a head portion for a first character identified in the media content item with a head portion of the first user; replacing a head portion for a second character identified in the media content item with a head portion of the second user; and displaying the media content item with the replaced head portion of the first user and the replaced head portion of the second user for the interaction function.

(190) In Example 14, the subject matter of Examples 1-13 includes, wherein the operations further comprise displaying a search bar configured to initiate a search for other media content items that include a placeholder space for the head portion.

(191) In Example 15, the subject matter of Examples 1-14 includes, wherein the operations further comprise filtering out media content items that include a plurality of head portions or media content items that are specific to a particular gender or age group for said accessing of the media content item.

(192) In Example 16, the subject matter of Examples 1-15 includes, wherein the interaction function comprises a user selectable user interface element configured to enable the first user to subscribe to a channel of the second user.

(193) In Example 17, the subject matter of Examples 1-16 includes, wherein the interaction function comprises an online post, wherein the operations further comprise displaying one or more online posts from the second user, wherein the one or more online posts include the media content item with the placeholder space.

(194) In Example 18, the subject matter of Examples 1-17 includes, wherein the media content item includes a static image or an animation.

(195) Example 19 is a method comprising: determining participation in an interaction function by a first user of an interaction system with a second user of the interaction system; accessing profile data of the first user; determining, based on the profile data, whether the first user has captured or designated a first-user self-image for use in the interaction function; and in response to determining that the first user has not captured or designated the first-user self-image: accessing a media content item that includes, a character; identifying a head portion of the character in the media content

item; replacing the head portion with a placeholder space; and displaying the media content item with the placeholder space in a user interface corresponding to the interaction function.

(196) Example 20 is a non-transitory computer-readable storage medium storing instructions that, when executed by at least one processor, cause the at least one processor to perform operations comprising: determining participation in an interaction function by a first user of an interaction system with a second user of the interaction system; accessing profile data of the first user; determining, based on the profile data, whether the first user has captured or designated a first-user self-image for use in the interaction function; and in response to determining that the first user has not captured or designated the first-user self-image: accessing a media content item that includes, a character; identifying a head portion of the character in the media content item; replacing the head portion with a placeholder space; and displaying the media content item with the placeholder space in a user interface corresponding to the interaction function.

(197) Example 21 is at least one machine-readable medium including instructions that, when executed by processing circuitry, cause the processing circuitry to perform operations to implement any of Examples 1-20.

(198) Example 22 is an apparatus comprising means to implement any of Examples 1-20.

(199) Example 23 is a system to implement any of Examples 1-20.

(200) Example 24 is a method to implement any of Examples 1-20.

Glossary

(201) “Client device” refers, for example, to any machine that interfaces to a communications network to obtain resources from one or more server systems or other client devices. A client device may be, but is not limited to, a mobile phone, desktop computer, laptop, portable digital assistants (PDAs), smartphones, tablets, ultrabooks, netbooks, laptops, multi-processor systems, microprocessor-based or programmable consumer electronics, game consoles, set-top boxes, or any other communication device that a user may use to access a network.

(202) “Communication network” refers, for example, to one or more portions of a network that may be an ad hoc network, an intranet, an extranet, a virtual private network (VPN), a local area network (LAN), a wireless LAN (WLAN), a wide area network (WAN), a wireless WAN (WWAN), a metropolitan area network (MAN), the Internet, a portion of the Internet, a portion of the Public Switched Telephone Network (PSTN), a plain old telephone service (POTS) network, a cellular telephone network, a wireless network, a Wi-Fi® network, another type of network, or a combination of two or more such networks. For example, a network or a portion of a network may include a wireless or cellular network, and the coupling may be a Code Division Multiple Access (CDMA) connection, a Global System for Mobile communications (GSM) connection, or other types of cellular or wireless coupling. In this example, the coupling may implement any of a variety of types of data transfer technology, such as Single Carrier Radio Transmission Technology (1×RTT), Evolution-Data Optimized (EVDO) technology, General Packet Radio Service (GPRS) technology, Enhanced Data rates for GSM Evolution (EDGE) technology, third Generation Partnership Project (3GPP) including 3G, fourth-generation wireless (4G) networks, Universal Mobile Telecommunications System (UMTS), High Speed Packet Access (HSPA), Worldwide Interoperability for Microwave Access (WiMAX), Long Term Evolution (LTE) standard, others defined by various standard-setting organizations, other long-range protocols, or other data transfer technology.

(203) “Component” refers, for example, to a device, physical entity, or logic having boundaries defined by function or subroutine calls, branch points, APIs, or other technologies that provide for the partitioning or modularization of particular processing or control functions. Components may be combined via their interfaces with other components to carry out a machine process. A component may be a packaged functional hardware unit designed for use with other components and a part of a program that usually performs a particular function of related functions.

Components may constitute either software components (e.g., code embodied on a machine-

readable medium) or hardware components. A “hardware component” is a tangible unit capable of performing certain operations and may be configured or arranged in a certain physical manner. In various examples, one or more computer systems (e.g., a standalone computer system, a client computer system, or a server computer system) or one or more hardware components of a computer system (e.g., a processor or a group of processors) may be configured by software (e.g., an application or application portion) as a hardware component that operates to perform certain operations as described herein. A hardware component may also be implemented mechanically, electronically, or any suitable combination thereof. For example, a hardware component may include dedicated circuitry or logic that is permanently configured to perform certain operations. A hardware component may be a special-purpose processor, such as a field-programmable gate array (FPGA) or an application-specific integrated circuit (ASIC). A hardware component may also include programmable logic or circuitry that is temporarily configured by software to perform certain operations. For example, a hardware component may include software executed by a general-purpose processor or other programmable processors. Once configured by such software, hardware components become specific machines (or specific components of a machine) uniquely tailored to perform the configured functions and are no longer general-purpose processors. It will be appreciated that the decision to implement a hardware component mechanically, in dedicated and permanently configured circuitry, or in temporarily configured circuitry (e.g., configured by software), may be driven by cost and time considerations. Accordingly, the phrase “hardware component” (or “hardware-implemented component”) should be understood to encompass a tangible entity, be that an entity that is physically constructed, permanently configured (e.g., hardwired), or temporarily configured (e.g., programmed) to operate in a certain manner or to perform certain operations described herein. Considering examples in which hardware components are temporarily configured (e.g., programmed), each of the hardware components need not be configured or instantiated at any one instance in time. For example, where a hardware component comprises a general-purpose processor configured by software to become a special-purpose processor, the general-purpose processor may be configured as respectively different special-purpose processors (e.g., comprising different hardware components) at different times. Software accordingly configures a particular processor or processors, for example, to constitute a particular hardware component at one instance of time and to constitute a different hardware component at a different instance of time. Hardware components can provide information to, and receive information from, other hardware components. Accordingly, the described hardware components may be regarded as being communicatively coupled. Where multiple hardware components exist contemporaneously, communications may be achieved through signal transmission (e.g., over appropriate circuits and buses) between or among two or more of the hardware components. In examples in which multiple hardware components are configured or instantiated at different times, communications between such hardware components may be achieved, for example, through the storage and retrieval of information in memory structures to which the multiple hardware components have access. For example, one hardware component may perform an operation and store the output of that operation in a memory device to which it is communicatively coupled. A further hardware component may then, at a later time, access the memory device to retrieve and process the stored output. Hardware components may also initiate communications with input or output devices, and can operate on a resource (e.g., a collection of information). The various operations of example methods described herein may be performed, at least partially, by one or more processors that are temporarily configured (e.g., by software) or permanently configured to perform the relevant operations. Whether temporarily or permanently configured, such processors may constitute processor-implemented components that operate to perform one or more operations or functions described herein. As used herein, “processor-implemented component” refers to a hardware component implemented using one or more processors. Similarly, the methods described herein may be at least partially processor-implemented, with a particular processor or processors

being an example of hardware. For example, at least some of the operations of a method may be performed by one or more processors or processor-implemented components. Moreover, the one or more processors may also operate to support performance of the relevant operations in a “cloud computing” environment or as a “software as a service” (SaaS). For example, at least some of the operations may be performed by a group of computers (as examples of machines including processors), with these operations being accessible via a network (e.g., the Internet) and via one or more appropriate interfaces (e.g., an API). The performance of certain of the operations may be distributed among the processors, not only residing within a single machine, but deployed across a number of machines. In some examples, the processors or processor-implemented components may be located in a single geographic location (e.g., within a home environment, an office environment, or a server farm). In other examples, the processors or processor-implemented components may be distributed across a number of geographic locations.

(204) “Computer-readable storage medium” refers, for example, to both machine-storage media and transmission media. Thus, the terms include both storage devices/media and carrier waves/modulated data signals. The terms “machine-readable medium,” “computer-readable medium” and “device-readable medium” mean the same thing and may be used interchangeably in this disclosure.

(205) “Machine storage medium” refers, for example, to a single or multiple storage devices and media (e.g., a centralized or distributed database, and associated caches and servers) that store executable instructions, routines and data. The term shall accordingly be taken to include, but not be limited to, solid-state memories, and optical and magnetic media, including memory internal or external to processors. Specific examples of machine-storage media, computer-storage media and device-storage media include non-volatile memory, including by way of example semiconductor memory devices, e.g., erasable programmable read-only memory (EPROM), electrically erasable programmable read-only memory (EEPROM), FPGA, and flash memory devices; magnetic disks such as internal hard disks and removable disks; magneto-optical disks; and CD-ROM and DVD-ROM disks. The terms “machine-storage medium,” “device-storage medium,” “computer-storage medium” mean the same thing and may be used interchangeably in this disclosure. The terms “machine-storage media,” “computer-storage media,” and “device-storage media” specifically exclude carrier waves, modulated data signals, and other such media, at least some of which are covered under the term “signal medium.”

(206) “Non-transitory computer-readable storage medium” refers, for example, to a tangible medium that is capable of storing, encoding, or carrying the instructions for execution by a machine.

(207) “Signal medium” refers, for example, to any intangible medium that is capable of storing, encoding, or carrying the instructions for execution by a machine and includes digital or analog communications signals or other intangible media to facilitate communication of software or data. The term “signal medium” shall be taken to include any form of a modulated data signal, carrier wave, and so forth. The term “modulated data signal” means a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal. The terms “transmission medium” and “signal medium” mean the same thing and may be used interchangeably in this disclosure.

(208) “User device” refers, for example, to a device accessed, controlled or owned by a user and with which the user interacts to perform an action or interaction on the user device, including an interaction with other users or computer systems.

CONCLUSION

(209) As used in this disclosure, phrases of the form “at least one of an A, a B, or a C,” “at least one of A, B, or C,” “at least one of A, B, and C,” and the like, should be interpreted to select at least one from the group that comprises “A, B, and C.” Unless explicitly stated otherwise in connection with a particular instance in this disclosure, this manner of phrasing does not mean “at least one of A, at

least one of B, and at least one of C.” As used in this disclosure, the example “at least one of an A, a B, or a C,” would cover any of the following selections: {A}, {B}, {C}, {A, B}, {A, C}, {B, C}, and {A, B, C}.

(210) Unless the context clearly requires otherwise, throughout the description and the claims, the words “comprise,” “comprising,” and the like are to be construed in an inclusive sense, as opposed to an exclusive or exhaustive sense, i.e., in the sense of “including, but not limited to.” As used herein, the terms “connected,” “coupled,” or any variant thereof means any connection or coupling, either direct or indirect, between two or more elements; the coupling or connection between the elements can be physical, logical, or a combination thereof. Additionally, the words “herein,” “above,” “below,” and words of similar import, when used in this application, refer to this application as a whole and not to any particular portions of this application. Where the context permits, words using the singular or plural number may also include the plural or singular number respectively. The word “or” in reference to a list of two or more items, covers all of the following interpretations of the word: any one of the items in the list, all of the items in the list, and any combination of the items in the list. Likewise, the term “and/or” in reference to a list of two or more items, covers all of the following interpretations of the word: any one of the items in the list, all of the items in the list, and any combination of the items in the list.

(211) Although some examples, e.g., those depicted in the drawings, include a particular sequence of operations, the sequence may be altered without departing from the scope of the present disclosure. For example, some of the operations depicted may be performed in parallel or in a different sequence that does not materially affect the functions as described in the examples. In other examples, different components of an example device or system that implements an example method may perform functions at substantially the same time or in a specific sequence.

(212) The various features, steps, and processes described herein may be used independently of one another, or may be combined in various ways. All possible combinations and subcombinations are intended to fall within the scope of this disclosure. In addition, certain method or process blocks may be omitted in some implementations.

Claims

1. A system comprising: memory; and one or more processors coupled to the memory and configured to perform operations comprising: determining participation in an interaction function by a first user of an interaction system with a second user of the interaction system; accessing profile data of the first user; determining, based on the profile data of the first user, that the first user has not captured or designated a first-user self-image for use in the interaction function; determining, from profile data of the second user, that the second user has not enabled other users to use a second-user self-image in response to determining that the first user has not captured or designated the first-user self-image; in response to determining, from the profile data of the second user, that the second user has not enabled other users to use the second-user self-image: replacing a portion of a character within a media content item with a placeholder space; and displaying the media content item with the placeholder space in a user interface corresponding to the interaction function.
2. The system of claim 1, wherein the portion is a head portion.
3. The system of claim 1, wherein determining that the second user has not enabled other users includes determining that the second user has captured or designated a second user self-image.
4. The system of claim 1, wherein the operations further comprise, subsequent to displaying the media content item with the placeholder space: determining that the first user has captured or designated the first-user self-image; and in response to determining that the first user has captured or designated the first-user self-image, replacing the placeholder space with a portion of the first-user self-image in the user interface corresponding to the interaction function.

5. The system of claim 1, wherein the operations further comprise determining that the second user has not captured or designated the second-user self-image, wherein replacing the portion with the placeholder space is further in response to determining that the second user has not captured or designated the second-user self-image.
6. The system of claim 1, wherein the operations further comprise, subsequent to displaying the media content item with the placeholder space: determining that a third user captured or designated a third-user self-image; and in response to determining that the third user captured or designated the third-user self-image, replacing the placeholder space with the third-user self-image, wherein the third user is also participating in the interaction function.
7. The system of claim 1, wherein the interaction function includes a chat window configured to display exchanged messages between the first user and the second user.
8. The system of claim 7, wherein displaying the media content item includes: reducing a size of the chat window in the user interface; and apportioning unused user interface space for display of the media content item.
9. The system of claim 7, wherein the operations further include, subsequent to displaying the media content item with the placeholder space: identifying a user selection of the media content item from a set of media content items being displayed in the user interface; and in response to the user selection, causing presentation of the selected media content item in the chat window at a first interaction client of the first user and a second interaction client of the second user.
10. The system of claim 9, wherein the operations further include, subsequent to displaying the selected media content item in the chat window: determining that the second user has enabled other users to use the second-user self-image; and in response determining that the second user has enabled other users to use the second-user self-image, replacing the placeholder space in the media content item that is displayed in the chat window with a portion of the second-user self-image.
11. The system of claim 1, wherein the operations further include: displaying a selectable user interface element that initiates a camera feed from a camera system of a first interaction client of the first user to capture the first-user self-image, wherein the selectable user interface element is disposed adjacent to or embedded at least partially within the displayed media content item.
12. The system of claim 11, wherein the operations further include: displaying a message between the first user and the second user subsequent to displaying the media content item with the placeholder space, wherein the message is displayed below the displayed media content item, wherein the selectable user interface element moves along the user interface with the displayed media content item.
13. The system of claim 1, wherein the operations further include disabling an option to save the media content item onto at least one memory component.
14. The system of claim 1, wherein the operations further comprise displaying a search bar configured to initiate a search for other media content items that include a placeholder space for the portion.
15. The system of claim 1, wherein the operations further comprise filtering out media content items that include a plurality of portions or media content items that are specific to a particular gender or age group for said media content item.
16. The system of claim 1, wherein the interaction function comprises a user selectable user interface element configured to enable the first user to subscribe to a channel of the second user.
17. The system of claim 1, wherein the interaction function comprises an online post, wherein the operations further comprise displaying one or more online posts from the second user, wherein the one or more online posts include the media content item with the placeholder space.
18. The system of claim 1, wherein the media content item includes a static image or an animation.
19. A method comprising: determining participation in an interaction function by a first user of an interaction system with a second user of the interaction system; accessing profile data of the first user; determining, based on the profile data of the first user, that the first user has not captured or

designated a first-user self-image for use in the interaction function; determining, from profile data of the second user, that the second user has not enabled other users to use a second-user self-image in response to determining that the first user has not captured or designated the first-user self-image; in response to determining, from the profile data of the second user, that the second user has not enabled other users to use the second-user self-image: replacing a portion of a character within a media content item with a placeholder space; and displaying the media content item with the placeholder space in a user interface corresponding to the interaction function.

20. A non-transitory computer-readable storage medium storing instructions that, when executed by at least one processor, cause the at least one processor to perform operations comprising: determining participation in an interaction function by a first user of an interaction system with a second user of the interaction system; accessing profile data of the first user; determining, based on the profile data of the first user, that the first user has not captured or designated a first-user self-image for use in the interaction function; determining, from profile data of the second user, that the second user has not enabled other users to use a second-user self-image in response to determining that the first user has not captured or designated the first-user self-image; in response to determining, from the profile data of the second user, that the second user has not enabled other users to use the second-user self-image: replacing a portion of a character within a media content item with a placeholder space; and displaying the media content item with the placeholder space in a user interface corresponding to the interaction function.
