

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250260317

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

CHENG; Yongjie et al.

DRIVER CIRCUITRY AND OPERATION

Abstract

This application relates to methods and apparatus for driving a transducer. A transducer driver has a switch network that is operable to selectively connect a driver output to any of a first set of at least three different switching voltages which are, in use, maintained throughout a switching cycle of the driver apparatus. The switch network is also operable to selectively connect the driver output to flying capacitor driver. A controller is configured to control the switch network and flying capacitor driver to generate a drive signal at the driver output based on an input signal, wherein in one mode of operation the driver output is switched between two of the first set of switching voltages with a controlled duty cycle and in another mode of operation the driver output is connected to the flying capacitor driver which is switched between first and second states with a controlled duty cycle.

Inventors: CHENG; Yongjie (Austin, TX), ZHANG; Lingli (Austin, TX), MELANSON; John L. (Austin, TX), HOFF; Thomas H. (Austin, TX), KING; Eric J. (Austin, TX), HE; Zhaohui (Austin, TX)

Applicant: Cirrus Logic International Semiconductor Ltd. (Edinburgh, GB)

Family ID: 81851503

Assignee: Cirrus Logic International Semiconductor Ltd. (Edinburgh, GB)

Appl. No.: 19/194708

Filed: April 30, 2025

Related U.S. Application Data

parent US continuation 17678527 20220223 parent-grant-document US 12323055 child US 19194708

us-provisional-application US 63278606 20211112

us-provisional-application US 63220469 20210710

us-provisional-application US 63190582 20210519

Publication Classification

Int. Cl.: H02M3/07 (20060101); H02M1/00 (20070101); H03F3/217 (20060101); H04R3/00 (20060101)

U.S. Cl.:

CPC H02M3/07 (20130101); H02M1/0095 (20210501); H03F3/2173 (20130101); H04R3/00 (20130101); H03F2200/03 (20130101)

Background/Summary

FIELD OF DISCLOSURE

[0001] The field of representative embodiments of this disclosure relates to methods, apparatus and/or implementations concerning or relating to driver circuits, and in particular to switching driver circuits as may be used to drive a transducer.

BACKGROUND

[0002] Many electronic devices include transducer driver circuitry for driving a transducer with a suitable driving signal, for instance for driving an audio output transducer of the host device or a connected accessory, with an audio driving signal.

[0003] In some applications the driver circuitry may include a switching amplifier stage, e.g. a class-D amplifier output stage or the like, for generating the drive signal. Switching amplifier stages can be relatively power efficient and thus can be advantageously used in some applications. A switching amplifier stage generally operates to switch an output node between defined high-side and low-side switching voltages, with a duty cycle that provides a desired average output voltage over the course of the duty cycle for the drive signal.

[0004] At least one of the high-side and low-side voltages for the output driver may be generated from a suitable input voltage, e.g. a battery voltage, by a DC-DC converter. In some cases, the DC-DC converter may be a variable voltage converter operable to selectively vary the switching voltage in use.

[0005] FIG. 1 illustrates generally the principles of one example of a switching driver circuit **100** for driving a load transducer **101**, where a switching voltage may be selectively varied. The driver circuit **100** comprises a class-D switching output stage **102**, which could be implemented as a single-ended driver with a half-bridge switching stage or as a differential driver with a full bridge switching stage, as would be understood by one skilled in the art. The class-D switching output stage **102** is thus configured to switch an output node on at least one side of the load between high-side and low-side switching voltages V_H and V_L , with a duty cycle based on an input signal (not shown).

[0006] In the driver circuit of FIG. 1, the high-side switching voltage V_H is generated from an input voltage, e.g. a battery voltage V_{Batt} , by a DC-DC converter, which in this example comprises a charge pump **103**. The charge pump **103** comprises a switch network and, in this example, two flying capacitors $CF1$ and $CF2$ and at least one reservoir capacitor CR . In this example, the charge pump **103** is operable to provide a variable boost level and is operable in different modes to provide an output voltage V_{CP} with a magnitude which can be selected to be substantially equal to the input voltage, to twice the input voltage or to three times the input voltage.

[0007] In the example of FIG. 1, the variable voltage charge pump **103** is used to provide the high-side switching voltage V_H , whilst the low-side voltage V_L is a defined voltage, in this case ground.

[0008] Using a variable voltage charge pump to provide a selectively variable high-side switching

voltage allows a high voltage to be used when required to provide a relatively high voltage drive signal. For example, with a differential output stage **102**, an output drive voltage of a magnitude up to near $3 \times V_{Batt}$ may be generated by operating the charge pump **103** in the three times mode and driving one output node of the class-D output stage with a duty cycle (in terms of proportion of time spent connected to the high-side switch voltage compared to the low-side switching voltage) at or near 100% and the other output node with a duty cycle at or near 0%. However, for lower signal levels, e.g. with a magnitude below $2 \times V_{Batt}$ or below V_{Batt} , the charge pump **103** may be operated in the two times mode or one times mode respectively. Varying the output voltage of the charge pump **103** in this way can improve power efficiency.

[0009] Whilst a driver circuit such as illustrated in FIG. **1** can be satisfactorily used in a number of applications, in general there is a desire for driver circuitry that may offer improvements with regard to the trade-off between circuit area and system efficiency, whilst meeting power output and performance requirements such as total harmonic distortion.

SUMMARY

[0010] Embodiments of the present disclosure relate to improved switching driver circuits and to methods of operation.

[0011] According to an aspect of the disclosure there is provided a driver apparatus for driving a transducer based on an input signal comprising: [0012] a first driver output node for outputting a first drive signal; [0013] a switch network; [0014] a flying capacitor driver having an output voltage node for connection, in use, to a first terminal of a flying capacitor, the flying capacitor driver being selectively operable in a first state with a second terminal of the flying capacitor connected to a first input voltage and the first terminal of the flying capacitor connected to a second input voltage to charge the flying capacitor and driver the output voltage node to the second input voltage and a second state with a second terminal of the flying capacitor connected to a third input voltage, different to the first voltage, and first terminal of the flying capacitor disconnected from the second input voltage to drive the output voltage node to a boosted voltage; and [0015] a controller; [0016] wherein the switch network is operable to selectively connect the first driver output node to the output voltage node of the flying capacitor driver or to any of a first set of at least three different switching voltages, wherein the switching voltages of the first set are, in use, maintained at a respective voltage node throughout a switching cycle of the driver apparatus; and [0017] wherein the controller is configured to control the switch network and flying capacitor driver to generate the first drive signal at the first driver output node based on the input signal, wherein in at least one mode of operation the first driver output node is switched between two of the first set of switching voltages with a controlled duty cycle based on the input signal and in at least one mode of operation the first driver output node is connected to the output voltage node of the flying capacitor driver and the flying capacitor is switched between the first and second states with a controlled duty cycle based on the input signal.

[0018] In some examples, the first set of switching voltages may comprise first and second supply voltages received by the driver apparatus. In some examples, the driver apparatus comprises a DC-DC converter configured to generate at least a third supply voltage from at least one of the first and second supply voltages. The DC-DC converter may comprise a charge-pump or inductive boost converter. In some examples, the first supply voltage may be less positive or more negative than the second supply voltage and the DC-DC converter may be configured to generate the third supply voltage as $V_3 = V_2 + (V_2 - V_1)$, where V_1 is the first supply voltage and V_2 is the second supply voltage.

[0019] In some examples, at least one of the first, second and third input voltages may be the same as a voltage of the first set of switching voltages. In some examples, the first set of switching voltages may comprise first and second supply voltages received by the driver apparatus and the first input voltage may be the same as the second supply voltage and each of the second and third input voltages may be the same the first supply voltage.

[0020] The driver apparatus may further comprise a second driver output node. The switch network may be further configured to selectively connect the second driver output node to the output voltage node of the flying capacitor driver or to any of the first set of at least three different switching voltages. The controller may be further configured to control the switch network and flying capacitor driver to generate a first drive signal at the second driver output node based on the input signal so as to drive a transducer connected between the first and second driver output nodes with a differential drive signal. The switch network may comprise: switches for selectively connecting the first and second output nodes respectively to a first voltage rail and switches for selectively connecting the first and second driver output nodes respectively to a second voltage rail; and switches for selectively connecting either of at least two of the first set of switching voltages to the first voltage rail, wherein the output voltage node of the flying capacitor driver may, in use, coupled to one of the first and second output nodes via the second voltage rail. In some implementations, the switch network may further comprise switches for selectively connecting the first and second driver output nodes respectively to one of the first set of switching voltages which is different to the voltages that can be selectively connected to the first voltage rail.

[0021] The controller may be operable: in a first mode in which each of the first and second driver output nodes is switched between first and second supply voltages of the first set of switching voltages; in a second mode in which one of the first and second driver output nodes is switched between said first and second supply voltages and the other one of the first and second driver output nodes is connected to the output voltage node of the flying capacitor driver which operates to switch the voltage output node between the first supply voltage and the boosted voltage; and in a third mode in which one of the first and second driver output nodes is switched between the second supply voltage and a third supply voltage of the first set of switching voltages. The driver apparatus may comprise a DC-DC converter configured to generate said third supply voltage from said first and second supply voltages.

[0022] In some examples, the driver apparatus may further comprise a second flying capacitor driver. The controller may be operable to control the first and second flying capacitor drivers together to modulate the first output node between the boosted voltage generated by the first flying capacitor driver and an additional boosted voltage generated by the second flying capacitor driver.

[0023] In some examples, the first set of switching voltages, and the boosted voltage generated by the flying capacitor driver, may together form a set of equally spaced voltage levels. In some examples, the first set of switching voltage levels may comprise a received ground voltage, a received positive supply voltage and a boosted voltage equal to twice the received positive supply voltage.

[0024] The driver apparatus may be an audio driver apparatus for driving an audio output transducer based on an audio input signal. Embodiments also relate to an integrated circuit comprising the driver apparatus and to an electronic device comprising the driver apparatus.

[0025] In another aspect, there is provided a driver apparatus for driving a transducer based on an input signal comprising: [0026] a first driver output node for outputting a first drive signal; [0027] a switch network; [0028] a flying capacitor driver having an output voltage node for connection, in use, to a first terminal of a flying capacitor, the flying capacitor driver being operable in use to selectively switch a second terminal of the flying capacitor between two different voltages to modulate the voltage at the output voltage node; and [0029] a controller; [0030] wherein the switch network is operable to selectively connect the first driver output node to the output voltage node of the flying capacitor driver or to any of a first set of at least three different switching voltages, wherein the switching voltages of the first set are, in use, maintained at a respective voltage node throughout a switching cycle of the driver apparatus; and [0031] wherein the controller is configured to control the switch network and flying capacitor driver to generate the first drive signal at the first driver output node based on the input signal.

[0032] In another aspect, there is provided a driver apparatus for driving a transducer based on an

input signal comprising: a first driver output node for outputting a first drive signal; a switch network operable in a direct mode to selectively connect the first driver output node to any of a first set of at least three different continuous voltages; wherein the switch network is further operable in an indirect mode to connect the output node to a flying capacitor so as to drive the output node to a voltage boosted by the flying capacitor.

[0033] In another aspect, there is provided a transducer driver configured to receive an input signal and first and second supply voltages and to generate an output signal for driving the transducer driver comprising: a combined charge pump and driver operable, in use, with at least one primary capacitor to selectively provide at least a first generated voltage based on the first and second supply voltages; a flying-capacitor driver operable, in use, with at least one secondary capacitor to provide at least a second generated voltage based on the first and second supply voltages; and an output bridge configured to selectively receive the first and second supply voltages, the first generated voltage and the second generated voltage to generate the output signal based on the input signal.

[0034] The combined charge pump and driver may be operable, in use, with first and second primary capacitors. The flying-capacitor driver is operable, in use, with first and second secondary capacitors.

[0035] It should be noted that, unless expressly indicated to the contrary herein or otherwise clearly incompatible, then any feature described herein may be implemented in combination with any one or more other described features.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0036] For a better understanding of examples of the present disclosure, and to show more clearly how the examples may be carried into effect, reference will now be made, by way of example only, to the following drawings in which:

[0037] FIG. 1 illustrates one example of a known driving circuit for driving a load;

[0038] FIG. 2 illustrates the principles of a switching driver according to an embodiment;

[0039] FIG. 3 illustrates switching an output node between multiple different voltage levels;

[0040] FIG. 4 illustrates one example of a driver apparatus according to an embodiment;

[0041] FIGS. 5a to 5d illustrate example switching waveforms for the driver apparatus of FIG. 4 in different operating modes;

[0042] FIG. 6 illustrates example switching waveforms for the driver apparatus of FIG. 4 as the required output signal varies;

[0043] FIG. 7 illustrates generally an embodiment of a driver apparatus;

[0044] FIG. 8 illustrates one example of a driver apparatus according to another embodiment;

[0045] FIGS. 9a to 9d illustrate example switching waveforms for the driver apparatus of FIG. 8 in different operating modes;

[0046] FIG. 10 illustrates example switching waveforms for the driver apparatus of FIG. 9 as the required output signal varies; and

[0047] FIG. 11 illustrates generally the embodiment of a driver apparatus of FIG. 9.

DETAILED DESCRIPTION

[0048] The description below sets forth example embodiments according to this disclosure. Further example embodiments and implementations will be apparent to those having ordinary skill in the art. Further, those having ordinary skill in the art will recognize that various equivalent techniques may be applied in lieu of, or in conjunction with, the embodiments discussed below, and all such equivalents should be deemed as being encompassed by the present disclosure.

[0049] Embodiments of the disclosure relate to driver circuitry for driving a transducer and, in

particular, to switching driver circuitry in which an output node can be switched between different switching voltages with a controlled duty cycle. Embodiments of the disclosure also relate to methods of operation of driver circuitry.

[0050] In embodiments of the disclosure, a driver apparatus may comprise a switch network configured to selectively switch an output node between any of first set of a plurality of switching voltages, where the first set of voltages are different to one another and, in use, the relevant switching voltage is maintained at a corresponding switching voltage node substantially continuously throughout the whole of the switching cycle of the driver. In use, the output node may be switched between different switching voltages of the first set with a controlled duty cycle so as to generate an output drive signal.

[0051] At least one of the first set of switching voltages may comprise a system voltage, i.e. a defined DC voltage that is provided to the driver apparatus, such as an input supply or reference voltage. For example, the first set of switching voltages may comprise a positive input supply voltage, such as a battery voltage, received by the driver apparatus and/or a defined ground reference. At least one of first set of switching voltages may also include at least one supply voltage generated by a DC-DC converter of the driver apparatus, e.g. from a charge pump or inductive boost converter or the like, which may be powered by the input power supply voltages. In some embodiments, the first set of switching voltages may comprise at least three switching voltages.

[0052] The voltages of the first set of switching voltages may, in use, be maintained at respective switching voltage nodes and the output node may be switched between selected ones of the first set of switching voltage nodes to provide the desired voltage modulation at the output node.

[0053] In addition, the output node can be selectively connected to an output voltage node of a flying capacitor driver. The flying capacitor driver is configured for use with a first terminal of the flying capacitor connected to the output voltage node and is operable to switch a second terminal of the flying capacitor between two different voltages, which may comprise one or more of the system voltages, to modulate the voltage at the output voltage node. The flying capacitor driver may be configured such that at least one of the voltages generated at the output voltage node, in use, is an additional voltage which is different to any of the switching voltages of the first set. It will be understood that this additional voltage is generated in a discontinuous manner, i.e. the additional voltage may be generated for only part of the switching cycle of the driver apparatus. Conveniently the other voltage to which the output voltage node of the flying capacitor driver is modulated is the same as one of the voltages of the first set of voltage. When the output node is connected to the output voltage node of the flying capacitor driver, the flying capacitor driver may be switched with a controlled duty cycle based on the input signal so as to modulate the voltage driver output node.

[0054] FIG. 2 illustrates the principles of a driver apparatus **200** for driving a load **201** according to an embodiment. FIG. 2 illustrates that an output node **202a** can be selectively connected, via switching paths **S1a**, **S2a** and **S3a**, to any of three supply voltages **V1**, **V2** or **V3**, at respective switching voltage nodes.

[0055] FIG. 2 illustrates that the voltages **V1** and **V2** may be system voltages, which as used herein shall refer to any generally continuous voltage maintained or generated by other components, and which is received by/available to the driver apparatus. For example **V1** and **V2** could be ground and a received input supply voltage +**VDD** (or -**VDD**). The input supply voltage **V2** may be derived from a system battery voltage, possibly with some voltage regulation and/or boosting applied by some other upstream circuitry and/or the input supply voltage could be provided from a system power supply, such as a switched mode-power supply. Switching path **S1a** selectively connects the output node **202a** to the received voltage **V1** and switching path **S2a** selectively connects the output node **202a** to the received voltage **V2**.

[0056] A third, different, supply voltage **V3** is generated by a DC-DC converter **203**, which may comprise a charge pump or an inductive converter or the like. In this example the DC-DC converter may generate the voltage **V3** using the received system voltages **V1** and **V2**. The output node **202a**

can be selectively connected to the supply voltage **V3** output by the charge pump by switching path **S3a**.

[0057] Each of the voltages **V1**, **V2** and **V3** is, in use, maintained in a substantially continuous manner, that is, the relevant voltage is maintained at a substantially constant level and the voltage at the relevant switching node thus does not substantially vary over the course of a full switching cycle of the driver apparatus **200**. Where the DC-DC converter is a switched mode converter, such as a charge pump, the DC-DC converter is operable to maintain the supply voltage throughout a full switching cycle of the DC-DC converter. The voltages at the relevant switching node is thus substantially independent of the input signal for the driver apparatus. It will, of course, be understood that the output voltage of a DC-DC converter such as a charge pump or inductive boost converter or the like may exhibit some voltage ripple due to the operation of the DC-DC converter, but the extent of such ripple is relatively small and a switched DC-DC converter such as a charge pump generally comprises an energy storage element such as a reservoir capacitor to maintain the output voltage throughout the whole of switching cycle of the DC-DC converter.

[0058] It should be noted that the voltage **V3**, generated by the DC-DC converter is generated in a substantially continuous manner when the DC-DC converter is active. This does not, however, mean that the DC-DC converter need be continuously active. If, for instance, the supply voltage generated by the DC-DC converter is only used for switching for relatively high magnitude output signals, in some cases the DC-DC converter may be controlled to be inactive if the signal magnitude is relatively low. However, when active, the DC-DC converter operates to maintain its output supply voltage **V3** in a continuous manner.

[0059] The voltages **V1**, **V2** and **V3** provide a first set of switching voltages and, in use, the output node **202a** may be switched between a selected pair of these switching voltages with a controlled duty cycle so as to provide the desired output signal. The output node **202a** is switched between these voltages by controlling the relevant switching paths **S1a**, **S2a** and **S3a** to connect the output node to the relevant supply voltages with a controlled duty-cycle. Such operation can be seen as direct-coupled switching, or a direct charge transfer mode of operation, as the output node **202a** is switched to be directly coupled to the relevant DC voltage supplies. As noted above, the DC supply voltages may, for example, be derived from a battery, an inductive switched mode power supply, or a switched capacitor power supply and maintain the voltage in substantially continuous fashion, i.e. are generally able to supply current for an extended period of time, for example greater than the period of the output drive signal at the lowest needed frequency. The terms “direct-coupled” and “DC-coupled” shall be used herein to refer to such switching of the output node between such supply voltages.

[0060] In addition, the output node **202a** may be selectively coupled, via switching path **S0a**, to an output voltage node **204** of a flying capacitor driver **206**. The output voltage node **204** is coupled to a first terminal of a capacitor **205**. The second terminal of capacitor **205** is configured to be selectively switched between two different voltages **Vac1** and **Vac2** by switches **Sac1** and **Sac2**. The first terminal of the capacitor **205** may also be selectively connected to a voltage **Vac3**, by switch **Sac3**. In use, the capacitor **205** may be cyclically charged and then connected to provide voltage boosting (positive or negative) of one of the voltages **Vac1** and **Vac2** to generate a boosted voltage at the switching voltage node and thus the capacitor **205** is used as a flying capacitor. The voltages **Vac1**, **Vac2** and **Vac3** may, in some implementations, be selected such that the boosted voltage generated at the output voltage node **204** is different to any of the voltages **V1**, **V2** and **V3**. The voltage **Vac1** is different to the voltage **Vac2** and, if the switches **Sac1** and **Sac3** are operated in phase with one another, then **Vac1** and **Vac3** are also different from one another so that the capacitor **205** is charged by the voltage difference between **Vac1** and **Vac3** when both these switches are closed. **Vac2** and **Vac3** may be the same as one another or different. It will be understood that **Vac1** may be more or less positive than **Vac2** and/or **Vac3**. Conveniently at least one, and possibly all, of the voltages **Vac1**, **Vac2** and **Vac3** is provided by the supply voltage **V1**,

V2 and V3, but any other system voltage could be used to provide one or more of these voltages. [0061] For example, consider that the supply voltage V2 is used for Vac1 and that the supply voltage V1 is used for both Vac2 and Vac3, with the supply voltage V2 being more positive than V1. In use, in one state with the second terminal of the capacitor 205 connected to Vac1=V2 and the first terminal of the capacitor 205 connected to Vac3=V1, the capacitor is charged to a voltage + (V2-V1) with the positive plate at the second terminal. In this state the output voltage node 204 is at the voltage Vac3=V1. In a second state, the second terminal of the capacitor 205 is instead connected to Vac2=V1 and the first terminal of the capacitor 205 is disconnected from Vac3. In this state the capacitor 205 provides negative boosting of the supply voltage Vac2, which thus generates a negatively boosted voltage V0 at the output voltage node, where $V0 = -(V2 - V1)$. In this example, the output voltage node 204 can thus be switched between the voltages V1 and V0, with the duty cycle being controlled by the switching of switches Sac1, Sac2 and Sac3. The capacitor 205, together with the switches Sac1, Sac2 and Sac3 can thus be seen as a flying capacitor based auxiliary driver or charge pump 206 for driving the output node.

[0062] The capacitor 205 can thus be selectively switched to provide selective boosting to provide a voltage V0, which may be different to the voltages V1, V2 and V3. Such operation can be seen as an indirect-coupled switching, or an indirect charge transfer mode of operation, as, in operation when the voltage V0 is generated, the output node is indirectly coupled to the supply Vac2 via the capacitor. The voltage V0 is not maintained continuously throughout the whole switching cycle of the driver apparatus. As used herein, the terms “indirect-coupled” or “indirect switching” will be used to refer to such operation and the term “AC-coupled” will also be used to refer to such operation.

[0063] The driver apparatus 200 is thus operable in a direct-coupled mode of operation and can switch the output between selected ones of the supply voltages V1, V2, V3 and also operable in an indirect-coupled mode of operation, to generate at least one additional voltage V0. The driver apparatus 200 is thus a mixed direct-coupled and indirect-coupled switching driver. Energy can be transferred to the load 201 via a mix of “DC-coupled” and “AC-coupled” paths according to the required output signal.

[0064] The DC supply voltages V1, V2 and V3 and the at least one additional boosted voltage V0 are chosen to provide a desired output voltage range for the single ended drive signal at the output node 202a. The difference between the highest voltage level (i.e. most positive/least negative) and the lowest voltage level (i.e. least positive or most negative) from the voltages V1, V2, V3 and V0 is selected to provide a desired output range for the output drive signal. The other voltages are selected to provide intermediate voltages levels. In use, the driver apparatus 200 may be controlled so as to only switch the output node between adjacent voltage levels.

[0065] For instance, if $V3 > V2 > V1 > V0$ (in terms being more positive), then the output node may be switched between the voltages V2 and V3 with a controlled duty cycle to provide an (average) output voltage at the output node 202a in the range between V2 and V3. To provide a lower (average) output voltage, the output node may be switched between V1 and V2 to provide an (average) output voltage in the range between V1 and V2 or switched between V0 and V1 to provide an average voltage in this range.

[0066] FIG. 3 illustrates this principle and illustrates the switching waveforms at the output node 202a according to one example and the resulting output voltage 301 (averaged over a duty cycle), i.e. the desired voltage of the drive signal output from the driver apparatus. It should be noted that FIG. 3 illustrates the switching waveforms for a single ended driver signal generated at just one output node, i.e. as would be applied to just one side of the load.

[0067] The output voltage 301 at the output node can thus vary within substantially all of a full voltage range defined between V3 and V0. However, across the whole of this output voltage range, the output node is switched between two switching voltages that differ by less than the full voltage range, i.e. the magnitude of the voltage modulation applied to the output node over each switching

cycle is less than the full voltage output range.

[0068] By contrast, for the switching driver discussed with reference to FIG. 1, generating a drive signal across the full output range would require switching the output node between voltages that differ by the full output range. In embodiments of the present disclosure, a similar output voltage range could be achieved but with a smaller magnitude of voltage modulation at the output node during the switching cycle. This is advantageous in terms of reducing possible electromagnetic interference (EMI), as a lower magnitude of voltage modulation at the output node during the switching cycle can result in lower EMI. In addition, the maximum voltage stress across components of the driver apparatus may depend on the difference between the switching voltages during the switching cycle and using a lower voltage difference may thus ease requirement for voltage stresses across the components, such as switches, of the driver apparatus, which may allow the use of fewer and/or smaller components.

[0069] In some cases the voltages levels **V1**, **V2**, **V3** and **V0** may be arranged so that voltage difference between successive voltages levels may be substantially the same as one another. Where **V1** and **V2** are received system voltages, the voltage **V3** may be generated to differ from **V1** by an amount equal in magnitude to $(V2 - V1)$ and likewise **V0** may be generated so as to differ from one of **V1**, **V2** and **V3** by the same magnitude. For example, if **V1** is ground and **V2** is an input voltage **VP**, then one of **V3** and **V0** may be generated as $2VP$ and the other generated as $-VP$, although other combinations would be possible.

[0070] As noted, FIG. 3 illustrates the switching waveforms at one output node only. In some implementations the driver apparatus may be implemented as a single ended driver configured to drive one side of the load only, with the other side of the load being held at a constant defined voltage, e.g. ground or a non-zero quiescent voltage level. However, in some implementations the driver apparatus may be implemented as a differential driver configured to drive both sides of the load.

[0071] Referring back to FIG. 2, the driver apparatus may thus also comprise switching paths **S1b**, **S2b** and **S3b** for selectively connecting an output node **202b** on the other side of the load to the supply voltages **V1**, **V2** and **V3** respectively. There is also a switching path **S0b** for selectively connecting the output node **202b** to a switching voltage node for indirect-coupled switching. In some cases, the switching path **S0b** may connect the output node **202b** to the output voltage node **204**, but in some cases, there may be an additional charge pump, similar to charge pump **206**, for providing indirectly-coupled switching for the output node **202b**. Each of the output nodes **202a** and **202b** can be selectively switched between appropriate switching voltages to provide a desired differential voltage across the load.

[0072] Thus, considering the example of the different voltage levels of FIG. 3, where **V3** is the highest (most positive/least negative) voltage and **V0** is the lowest (most negative/least positive) voltage, and **V2** is higher (more positive/less negative) than **V1**, a differential voltage in the output range of $+(V3 - V0)$ to $-(V3 - V0)$ can be generated. For a relatively high magnitude output voltage within this range, the driver apparatus **200** may operate in a mode in which the output node on one side of the load is switched between **V2** and **V3**, whilst the output node on the other side of the load is switched between **V0** and **V1**. For a relatively low magnitude signal within this range, the driver apparatus **200** may operate in a different mode in which each side of the load may be switched between the voltages **V1** and **V2**, with appropriate duty cycles on each side of the load. In some implementations, the driver apparatus **200** may operate in either of these two modes of operation and switch between them when an appropriate signal threshold is reached. However, in some implementations the driver apparatus may also be operable in another mode for intermediate magnitude signals. In the intermediate magnitude mode, the output node on one side of the load may be switched between the voltages **V1** and **V2** whilst the output node on the other side of the load is switched between **V0** and **V1**. Alternatively (or as an additional intermediate-magnitude mode) the output node on one side of the load may be switched between the voltages **V2** and **V3**,

whilst the output node on the other side of the load is switched between V1 and V2. The use of an intermediate-magnitude mode can reduce the need to achieve duty-cycles at or near 100% in the high-magnitude and low-magnitude modes, which may be practically difficult, but the common-mode component of the differential output signal may be different in the intermediate-magnitude mode compared to the high-magnitude or low-magnitude modes.

[0073] In the example of FIG. 2, the switching driver **200** thus receives input system voltages V1 and V2, e.g. ground and an input supply voltage VP, and generates an additional supply voltage V3. The switching driver also, when required, generates an additional boosted voltage V0 using the flying capacitor **205**.

[0074] Driving the load with the boosted voltage V0 generated by the flying capacitor can be relatively power efficient, as charge transferred from the supply to the capacitor is then transferred to the load without significant wastage. However, the duty cycle of switching of the capacitor **205** is dependent on the required output signal voltage and thus is input signal dependent. This results in a duty-cycle dependent impedance variation. A significant signal dependent impedance variation can generally be undesirable.

[0075] By using a mix of direct-coupled and indirect-coupled switching, embodiments of the present disclosure provide an advantageous balance between power efficiency and impedance variation. This may also allow use of a reduced number of capacitors compared to the driver illustrated in FIG. 1.

[0076] FIG. 4 illustrates one embodiment of a switching driver **400** according to an embodiment in more detail, in which similar components to those discussed with reference to FIG. 2 are identified with the same reference numerals.

[0077] The embodiment of FIG. 4 comprises a differential driver for driving output nodes **202a** and **202b**. The embodiment of FIG. 4 receives system voltages V1 and V2, which in this example are ground and a supply voltage VP. The driver apparatus comprises a 2× (times two) charge pump **203**, which receives the system voltages VP and ground, and which generates a further supply voltage V3, which in this example is equal to 2VP.

[0078] The charge pump **203** comprises a capacitor C1 arranged as a flying capacitor with switches S1, S2, S3 and S4. Switches S1 and S2 selectively connect a first terminal of the capacitor C1 to the system voltages VP and ground respectively, whilst switch S3 selectively connects the second terminal to system voltage VP and switch S4 selectively couples the second terminal of capacitor C1 to the charge pump output for the voltage 2VP.

[0079] In use, switches S2 and S3 are switched together and in antiphase with switches S1 and S4. The charge pump **203** thus cycles between a first state, with switches S2 and S3 closed (and switches S1 and S4 open), to charge the flying capacitor C1 to the voltage VP with the second terminal being positive, and a second state with switches S1 and S4 closed (and switches S2 and S3 open), such that the system voltage VP is connected to the first terminal of capacitor C1 and the second terminal of capacitor C1 is boosted to 2VP. This state charges the reservoir capacitor C2, connected between the system voltage VP and the charge pump output, and thus provides an output voltage of 2VP, which is maintained by the capacitor C2.

[0080] The switches S1 to S4 of the charge pump **203** are switched at a charge pump frequency which is independent of the output signal being output by the driver apparatus, and which is thus independent of the duty cycles at the output nodes **202a** and **202b**.

[0081] The driver apparatus **400** also comprises a differential output bridge **401** for the output nodes **202a** and **202b**. In the example of FIG. 4, the 2VP output voltage from the charge pump **203** or the system voltage VP may be respectively coupled to a common-rail, which may be referred to as a high-side rail by switches S5 and S6 respectively. Each of the output nodes **202a** and **202b** may be selectively connected to the high-side rail by respective switches S7 and S8. The output nodes **202a** and **202b** can also be selectively connected to a low-side rail by respective switches S9 and S10, or to the system ground voltage by respective switches S11 and S12. The output bridge

401 may thus be referred to as a T-bridge.

[0082] The driver apparatus also comprises a flying capacitor auxiliary driver **206** as discussed with reference to FIG. 2. In this example, switches **S13** and **S14** (equivalent to switches **Sac1** and **Sac2** of FIG. 2) selectively connect the first terminal of capacitor **205** to the system voltage **VP** or ground respectively, and switch **S15** (equivalent to **Sac3**) selectively connects the second terminal of capacitor **205** to ground.

[0083] Switch **S11** thus provides the switching path **S1a** discussed with reference to FIG. 2. Switches **S7** and **S5** collectively provide the switching path **S2a** and switches **S7** and **S6** thus collectively provide the switching path **S3a**. Switching path **S0a** is provided by switches **S9** and **S16**.

[0084] The embodiment of FIG. 4 also includes a second flying capacitor auxiliary driver **402**, which comprises switches **S17** and **S18** and capacitor **C4**, which is also connected to the low-side rail. The second flying capacitor auxiliary driver **402** can be implemented so as to operate, together with the first flying capacitor auxiliary driver **206**, to generate a further different boosted voltage, as will be described in more detail below, so as to extend to the output voltage range of the driver apparatus **400**. In some implementation, however, this further different boosted voltage may not be required and the second flying capacitor auxiliary driver **402** may be omitted.

[0085] In use, the various switches **S5** to **S18** of the driver apparatus are controlled by a controller **403** based on an input signal **Sin**, for example an input audio signal, to generate a corresponding differential output signal. The controller **403** may be configured to operate the driver apparatus selectively in different modes of operation to provide a differential output voltage in the range of $+4VP$ to $-4VP$ based on the input signal **Sin**. The controller **403** thus receives the input signal **Sin** and generates a series of switch control signals **Scon** for controlling the switches. The controller **403** may also control the switches **S1-S4** of the charge pump **203** but the control of these switches may be independent of the input signal **Sin**.

[0086] For a relatively low-magnitude output signal, i.e. for a differential output magnitude below a first threshold, where the first threshold is a magnitude of **VP** or lower, the driver apparatus **400** can be operated in a first mode in which each of the output nodes **202a** and **202b** is switched between voltages ground and **VP**.

[0087] In this first mode of operation, switch **S6** is closed to connect the input supply voltage **VP** to the high-side rail and switch **S5** is open to disconnect the output of the charge pump **203** from this rail. Switches **S9** and **S10** are also open to disconnect the output nodes from the low-side rail.

[0088] The switches **S7** and **S11** are switched in antiphase with a controlled duty-cycle to switch the output node between the voltage **VP** (at the high-side rail) and ground. Likewise the switches **S8** and **S12** are also switched with a controlled duty cycle for the output node **202b**.

[0089] Each of the output node **202a** and **202b** is thus switched between the voltages ground and **VP** with respective controlled duty cycles to provide the desired output voltage based on the input signal. FIG. 5a illustrates one example of switching waveforms **Vouta** and **Voutb** for the output nodes **202a** and **202b** and the resulting differential voltage **Vdiff** over one switching cycle period **Tpwm**.

[0090] In this first mode of operation, the switches **S1** to **S4** of the charge pump may be switched at the charge pump frequency as discussed above to maintain the voltage on capacitor **C2**. In addition, switches **S13** and **S15** of the first flying capacitor auxiliary driver **206** may be kept closed so that the capacitor **205** is charged to the voltage **VP**. Switches **S16**, **S17** and **S18** may be kept open, or in some cases switches **S16** and **S18** could be closed so as to provide some pre-charging of capacitor **C4** (which is used in a fourth mode as discussed below).

[0091] For a higher intermediate magnitude output signal, i.e. for a differential output magnitude between the first threshold and a second higher threshold, where the second threshold is a magnitude of **2VP** or lower, the driver apparatus **400** can be operated in a second mode in which one of the output nodes **202a** and **202b** (depending on the required polarity) is switched between

voltages ground and VP and the other output node is switched between voltages $-VP$ and ground.

[0092] If the polarity of the differential output is defined as being positive when the voltage at the output node **202a** is more positive than the voltage at the output node **202b**, then for a positive output signal in the second mode of operation the output node **202a** would be switched between VP and ground, whilst the output node **202b** is switched between $-VP$ and ground.

[0093] In this case, switch **S6** is again closed to connect the input voltage VP to the high-side rail, with switch **S5** open, and switches **S7** and **S11** are again switched with a controlled duty-cycle, whilst switch **S9** is open.

[0094] In this case switch **S10** is closed to connect the output node **202b** to the low-side rail, with switches **S8** and **S12** open. Switch **S16** is closed to connect the low-side rail to the first flying capacitor auxiliary driver **206**. Switches **S13** and **S15** are switched together in antiphase with switch **S14** with a controlled duty cycle based on the input signal S_{in} . As described with reference to FIG. 2, with switches **S13** and **S15** closed (and **S14** open) the voltage at node **204**, and hence the low-side rail, is ground and the capacitor **205** is charged to VP. With switch **S14** closed (and **S13** and **S15** open) the capacitor **205** is connected between ground and the switching voltage node **104**, with its positive plate connected to ground to drive the voltage at the output voltage node **204**, and hence the low-side rail to $-VP$. In this mode the second flying capacitor auxiliary driver **402** is not used and switches **S18** and **S17** may be held open so that capacitor **C4** is left floating, or alternatively the switches could be controlled to maintain some pre-charge on capacitor **C4**.

[0095] The output node **202a** is thus switched between the voltages ground and VP, whilst the output node **202b** is switched between the voltage $-VP$ and ground, with respective controlled duty cycles to provide the desired output voltage based on the input signal. FIG. 5b illustrates one example of switching waveforms V_{outa} and V_{outb} for the output nodes **202a** and **202b** and the resulting differential voltage V_{diff} over one switching cycle period T_{pwm} in this second mode of operation for a positive differential output. For a negative differential output, the output node **202a** would instead be connected to the low-side rail and output node **202b** switched between ground and the high-side rail.

[0096] For a still higher intermediate magnitude output signal, i.e. for a differential output magnitude between the second threshold and a third higher threshold, where the third threshold is a magnitude of $3VP$ or lower, the driver apparatus **400** can be operated in a third mode in which one of the output nodes **202a** and **202b** (depending on the required polarity) is switched between voltages VP and $2VP$ and the other output node is switched between voltage $-VP$ and ground.

[0097] For a positive differential output, the output node **202a** may be switched between the voltages VP and $2VP$. In this case, switch **S7** is closed throughout the switching cycle to connect the output node to the high-side rail (with switches **S9** and **S11** open) and the switches **S5** and **S6** are switched with a controlled duty cycle to switch the voltage at the high-side rail between VP and $2VP$. The output node **202b** is connected to the low-side rail by switch **S10** and the flying capacitor auxiliary driver **206** operates in the same manner as in the second mode.

[0098] The output node **202a** is thus switched between the voltages VP and $2VP$, whilst the output node **202b** is switched between the voltage $-VP$ and ground, with respective controlled duty cycles to provide the desired output voltage based on the input signal. FIG. 5c illustrates one example of switching waveforms V_{outa} and V_{outb} for the output nodes **202a** and **202b** and the resulting differential voltage V_{diff} over one switching cycle period T_{pwm} in this third mode of operation for a positive differential output. For a negative differential output, the output node **202a** would instead be connected to the low-side rail and output node **202b** connected to the high-side rail.

[0099] For a still higher magnitude output signal, i.e. for a differential output magnitude above the third threshold, the driver apparatus **400** can be operated in a fourth mode in which one of the output nodes **202a** and **202b** (depending on the required polarity) is switched between voltages VP and $2VP$ and the other output node is switched between voltage $-2VP$ and $-VP$.

[0100] For a positive differential output, the output node **202a** may be switched between the

voltages VP and 2VP. In this case, switch S7 is closed throughout the switching cycle to connect the output node to the high-side rail (with switches S9 and S11 open) and the switches S5 and S6 are switched with a controlled duty cycle to switch the voltage at the high-side rail between VP and 2VP in a similar fashion as in the third mode.

[0101] The output node **202b** is connected to the low-side rail with switch S10 closed (and switches S8 and S12 open). In this case, the first flying capacitor auxiliary driver **206** cooperates with the second flying capacitor auxiliary driver **402** to switch the voltage at the low-side rail between -VP and -2VP. These auxiliary drivers are controlled between two states with a controlled duty cycle based on the input signal Sin.

[0102] In the first state, switches S14 and S16 are closed (with switches S13 and S15 open). The capacitor **205**, charged to VP, is thus connected between ground and the low-side rail, with the positive plate connected to ground. This drives the low-voltage rail, and hence the output node **202b** to a voltage -VP. In this first state switch S18 is also closed, with switch S17 open, so that capacitor C4 is charged to a voltage of 2VP.

[0103] In the second state, switch S16 is open to isolate the first flying capacitor auxiliary driver **206** from the low-side rail, and switch S17 is closed (with switch S18 open) to connect capacitor C4 between ground and the low-side rail, with its positive plate connected to ground. This drives the low-side rail to -2VP. In this first state, switches S13 and S15 may also be closed, with switch S14 open, to recharge the capacitor **205**.

[0104] Thus, in the fourth mode, the first flying capacitor auxiliary driver acts as a helper charge pump for the second flying capacitor auxiliary driver.

[0105] The output node **202a** is thus switched between the voltages VP and 2VP, whilst the output node **202b** is switched between the voltages -2VP and -VP, with respective controlled duty cycles to provide the desired output voltage based on the input signal. FIG. 5d illustrates one example of switching waveforms Vouta and Voutb for the output nodes **202a** and **202b** and the resulting differential voltage Vdiff over one switching cycle period Tpw in this fourth mode of operation for a positive differential output. For a negative differential output, the output node **202a** would instead be connected to the low-side rail and output node **202b** connected to the high-side rail.

[0106] It will be seen from FIGS. 5a to 5d that in each of these first to fourth modes of operation, the voltage modulation at each of the output nodes over the course of the switching period has a magnitude equal to the input voltage VP (i.e. equal to V2-V1). In addition, the magnitude of the modulation of the differential voltage is, in each of these modes, limited to this voltage VP.

[0107] The controller **403** therefore receives the input signal Sin and generates appropriate control signals Scon for the switches of the driver apparatus **400** to provide a corresponding output signal. Depending on the signal magnitude, the controller operates in the appropriate mode and controls the duty cycles on both sides of the load. As the input signal varies, the controller controllably adjusts the duty cycles accordingly within a given mode of operation, until a threshold for changing mode is reached, at which point the controller **403** transitions to the new mode of operation, with appropriate changes in duty cycle to account for the change in switching voltages and maintain the correct differential voltage.

[0108] FIG. 6 illustrates examples waveforms for a switching driver apparatus such as illustrated in FIG. 4 as the output signal varies. The waveforms **601** and **602** illustrate the voltages Vouta and Voutb at the output nodes **202a** and **202b** respectively. Waveform **603** illustrates the unfiltered differential voltage across the load and waveform **604** illustrates the resulting average differential output, i.e. the differential output signal as experienced by the load after filtering.

[0109] The driver apparatus **400** may be implemented using FET devices for the switches.

[0110] In general, as illustrated in FIG. 7 the driver apparatus **400** according to this embodiment can be seen receiving system (or supply) voltages V1 and V2, where V1 may be ground or some other defined reference and V2 may be an input supply. An output bridge **701**, such as the output bridge **401** discussed with reference to FIG. 2, is configured for outputting a signal to a load **201**,

e.g. a transducer. A combined charge pump and driver **702** is operable, to selectively provide at least a first generated voltage **V3**. In this example, the combined charge pump and driver **702** is operable, to selectively provide the received supply voltage **V2** and at least one generated boosted voltage **V3** to the output stage **701** for DC-coupled switching. The combined charge pump and driver **702** may thus comprise charge pump functionality to generate a boosted voltage from the received supply voltages and driver capability so as to drive the output bridge between different switching voltages with a controlled duty cycle so as to generate the output signal. The combined charge pump and driver **702** is operable, in use, with at least one capacitor, which may be referred to as a primary capacitor. In the example of FIG. 7, there may be first and second primary capacitors **C1** and **C2**, which in some cases could be integrated capacitors, but in some cases may be off-chip components.

[0111] The first and second primary capacitors may be configured as flying and reservoir capacitors respectively. The combined charge pump and driver may comprise the charge pump **203** discussed with reference to FIG. 4, along with the switches **S5** and **S6** for providing a selected output to the high-side rail.

[0112] A flying capacitor auxiliary driver is also operable to provide at least a second generated voltage. The flying capacitor auxiliary driver **703** may be configured to provide a voltage **V0** by indirect-coupled or AC coupled switching, e.g. through use of a flying capacitor. The combined charge pump and driver **703** may thus comprise driver capability so as to drive the output bridge between different switching voltages with a controlled duty cycle by switching of a flying capacitor. The flying capacitor driver **703** is operable, in use, with at least one capacitor, which may be referred to as a secondary capacitor. In the example of FIG. 7, there may be first and second secondary capacitors **C3** and **C4**, which again could be integrated or off-chip components. Both of the first and second secondary capacitors **C3** and **C4** may be configured as flying capacitors. The flying capacitor auxiliary driver **703** may comprise the first and second flying capacitor auxiliary drivers **206** and **403** discussed with reference to FIG. 4. The output bridge is configured to selectively receive the first and second supply voltages, **V1** and **V2**, the first generated voltage **V3** and the second generated voltage **V0** to generate the output signal based on the input signal. A controller **704** controls the switching operation of the output stage **701**, combined charge pump and driver **702** and flying capacitor auxiliary driver **703** based on an input signal (not separately illustrated).

[0113] FIG. 8 illustrates an example of a driver apparatus **800** according to another embodiment.

[0114] The embodiment of FIG. 8 comprises a differential driver for driving output nodes **202a** and **202b**. The embodiment of FIG. 4 receives systems voltages **V1** and **V2**, which in this example are ground and a supply voltage **VP**.

[0115] The switching apparatus **800** comprises an output stage **801** for driving the output nodes **202a** and **202b**. The output stage **801** in this embodiment comprises switches **SW5a** and **SW5b** for selectively connecting the output node **202a** to respective high-side and low side-rails for the output node **202a**. Likewise switches **SW4b** and **SW5b** selectively connect the output node to high-side and low-side rails for output node **202b**. The output stage **801** in this example may thus be seen as an H-bridge.

[0116] A driver **802a** is operable to provide voltages for the high-side and low-side rails for output node **202a**. The driver **802a** comprises a capacitor **CP1a** coupled between the high-side and low-side voltage rails. A switch **SW6a** selectively couples the high-side voltage rail to a voltage select node which can be selectively connected to either of the system voltages **V1** or **V2**, i.e. ground and **VP** in this example, by switches **SW7a** and **SW8a**. Likewise, **SW3a** selectively couples the low-side voltage rail to a voltage select node which can be selectively connected to either of the system voltages **V1** or **V2** by switches **SW1a** and **SW2a**.

[0117] In use, the driver **802a** can supply the system voltages **V2** and **V1** as voltages to the high-side and low-side rails for DC-coupled switching. In addition, the driver **802a** can selectively

connect the capacitor **CP1a** in series with one of these supply voltages to provide positive or negative boosting of the relevant supply voltage to provide an indirect (or AC coupled) switching voltage, as will be described in more detail below.

[0118] A driver **802b** is coupled to the high-side and low-side rails for the output node **202b**. The driver **802b** has generally the same structure as the driver **802a** and thus has components corresponding those of the driver **802a** (identified by the same reference but with the suffix b in FIG. 8).

[0119] The driver apparatus **800** also comprises a charge pump **803**. The charge pump **803** is configured to be operable to provide a supply voltage to, in this example, the low-side rail for either of the output nodes **202a** or **202b**. The charge pump driver **803** comprises a capacitor **CP2** and switches **S9** and **S10** for selectively connecting a first terminal of capacitor **CP2** to either of the system voltages **V2** or **V1**, and switch **SW11** for selectively connecting a first terminal of capacitor **CP2** to **V1**, i.e. ground in this example. Switches **SW12** and **SW13** selectively connect the charge pump driver to the low-sides rails for output nodes **202a** and **202b** respectively. In use, when the charge pump **803** is active to supply a voltage to one of the low side rails, the respective capacitor **CP1a** or **CP2b** connected to that voltage rail may be used as a reservoir capacitor, as will be discussed in more detail below.

[0120] In use, the various switches of the driver apparatus are controlled by a controller **804** based on an input signal S_{in} , for example an input audio signal, to generate a corresponding differential output signal. The controller **804** may be configured to operate the driver apparatus selectively in different modes of operation to provide a differential output voltage in the range of $+3V_P$ to $-3V_P$ based on the input signal S_{in} . The controller **804** thus receives the input signal S_{in} and generates a series of switch control signals S_{con} for controlling the switches.

[0121] For a relatively low-magnitude output signal, i.e. for a differential output magnitude below a first threshold, where the first threshold is a magnitude of V_P or lower, the driver apparatus **800** can be operated in a first mode in which each of the output nodes **202a** and **202b** is switched between voltages which are ground and V_P .

[0122] In the first mode, for driver apparatus **800**, switches **SW1a**, **SW3a**, **SW8a** and **S6a** are also closed (with switches **SW2a** and **SW7a** open) to connect the high-side and low-side voltage rails of driver **802a** to the voltage V_P and ground respectively, and the corresponding switches of driver **802b** are switched in the same way. The switches **SW4a** and **SW5a** are switched in antiphase with a controlled duty-cycle to switch the output node **202a** between the voltage V_P at the high-side rail and ground at the low-side rail. Likewise the switches **SW4b** and **SW5b** are also switched with a controlled duty cycle for the output node **202b**.

[0123] Each of the output nodes **202a** and **202b** is thus switched between the voltages ground and V_P with respective controlled duty cycles to provide the desired output voltage based on the input signal. FIG. 9a illustrates one example of switching waveforms V_{outa} and V_{outb} for the output nodes **202a** and **202b** and the resulting differential voltage V_{diff} over one switching cycle period T_{pwm} .

[0124] In addition, as the capacitors **CP1a** and **CP1b** are connected between the respective high-side and low-side rails of the relevant driver, each of these capacitors is charged to the voltage V_P .

[0125] In this first mode of operation, switches **SW12** and **SW13** are open to disconnect the charge pump **803** from the low-side rails. Switches **SW9** and **SW11** may be closed, with switch **SW10** open, to charge the capacitor **CP2** to a voltage V_P .

[0126] For a higher intermediate magnitude output signal, i.e. for a differential output magnitude between the first threshold and a second higher threshold, where the second threshold is a magnitude of $2V_P$ or lower, the driver apparatus **800** can be operated in a second mode in which one of the output nodes **202a** and **202b** (depending on the required polarity) is switched between voltages ground and V_P and the other output node is switched between $-V_P$ and ground.

[0127] If the polarity of the differential output is defined as being positive when the voltage at the

output node **202a** is more positive than the voltage at the output node **202b**, then for a positive output signal in the second mode of operation the output node **202a** would be switched between ground and VP, whilst the output node **202b** is switched between $-VP$ and ground.

[0128] In this case, driver **802a** may be operated in the same way as in the first mode. For driver **802b**, switch SW**4b** may be closed, with switch SW**5b** open, to connect the output node **202b** to the low-side rail. In this mode, the driver **802a** may cycle between two states with a controlled duty-cycle to vary the voltages at the low-side voltage rail. In one state, switches SW**1b**, SW**3b**, SW**6b** and SW**8b** may be closed (with switches SW**2b** and SW**7b** open) so that the low-side rail is driven to ground and the capacitor CP**1b** is charged to a voltage of VP. In the other state, switches SW**6b** and SW**7b** are closed (with switches SW**1b**, SW**2b**, SW**3b** and SW**8b** open) so that the capacitor CP**1b** is connected between V**1**, ground in this example, and the low-side rail with its positive plate connected to V**1**. This provides negative boosting of the voltage V**1** and, in this example, drives the low-side rail to the voltage $-P$.

[0129] The driver **802b** in this mode thus provides an indirect-coupled switching voltage, with the advantages of power efficiency discussed above.

[0130] The output node **202a** is thus switched between the voltages ground and VP, whilst the output node **202b** is switched between the voltage $-VP$ and ground, with respective controlled duty cycles to provide the desired output voltage based on the input signal. FIG. **9b** illustrates one example of switching waveforms Vouta and Voutb for the output nodes **202a** and **202b** and the resulting differential voltage Vdiff over one switching cycle period Tpw in this second mode of operation for a positive differential output. For a negative differential output, the operation of the drivers **802a** and **802b** would be swapped.

[0131] Again, in this second mode of operation for the driver apparatus, switches SW**12** and SW**13** are open to disconnect the charge pump **803** from the low-side rails and switches SW**9** and SW**11** may be closed, with switch SW**10** open, to charge the capacitor CP**2** to a voltage VP.

[0132] For a still higher intermediate magnitude output signal, i.e. for a differential output magnitude between the second threshold and a third higher threshold, where the third threshold is a magnitude of 3VP or lower, the driver apparatus **800** can be operated in a third mode in which one of the output nodes **202a** and **202b** (depending on the required polarity) is switched between voltages VP and 2VP and the other output node is switched between voltage $-VP$ and ground.

[0133] For a positive differential output, the output node **202a** may be switched between the voltages VP and 2VP. In this case, switch SW**5a** may be closed throughout the switching cycle to connect the output node **202a** to the high-side rail (with switch SW**4a** open). The driver **802a** then cycles between two states with a controlled duty cycle so as to modulate the voltage at the high-side rail between VP and 2VP.

[0134] In one state, switches SW**1a**, SW**3a**, SW**6a** and SW**8a** are closed (with switches SW**2a** and SW**7a** open) to connect the high-side rail to the voltage VP and to charge the capacitor CP**1a** to the voltage VP. In the other state, switches SW**2a** and SW**3a** are closed (with switches SW**1a**, SW**6a**, SW**7a** and SW**8a** open) to connect the capacitor CP**1a** between the voltage V**2**, i.e. VP in this example, and the high-side rail, so as to provide a boosted voltage at the high-side rail, equal to +2VP in this example.

[0135] In this mode of operation, the driver **802a** thus operates to provide an indirect-coupled positive boosted voltage of 2VP.

[0136] The driver **802b** may operate in the same way as the second mode.

[0137] The output node **202a** is thus switched between the voltages VP and 2VP, whilst the output node **202b** is switched between the voltage $-VP$ and ground, with respective controlled duty cycles to provide the desired output voltage based on the input signal. FIG. **9c** illustrates one example of switching waveforms Vouta and Voutb for the output nodes **202a** and **202b** and the resulting differential voltage Vdiff over one switching cycle period Tpw in this third mode of operation for a positive differential output. For a negative differential output, the output node **202a** would instead

be switched between $-VP$ and ground and output node **202b** switched between $+VP$ and $+2VP$.

[0138] Again, in this third mode of operation for the driver apparatus **800**, switches SW**12** and SW**13** are open to disconnect the charge pump **803** from the low-side rails and switches SW**9** and SW**11** may be closed, with switch SW**10** open, to charge the capacitor CP**2** to a voltage VP .

[0139] In this third mode of operation for the driver apparatus **800**, the drivers **802a** and **802b** on both sides of the load are operating in an indirect-coupled mode to generate an indirect-coupled boosted voltage.

[0140] As discussed above, whilst such indirect-coupled switching can be power efficient, it can result in an undesirable duty-cycle dependent impedance variation. This impedance variation is dependent on duty-cycle, and the extent of the variation depends on the proportion of time the relevant AC-coupled boosted voltage is connected to the output node.

[0141] To reduce this variation, the driver apparatus **800** is also operable in a fourth mode when the differential output magnitude between the second threshold and third thresholds. In the fourth mode, one of the output nodes **202a** and **202b** (depending on the required polarity) is switched between voltages VP and $2VP$ but the other output node is held constant throughout the switching cycle at the voltage $-VP$. The voltage $-VP$ is generated by the charge pump **803** at the low-side rail for the relevant output node.

[0142] The controller may operate in the fourth mode when the differential output magnitude is between the second threshold and third thresholds, and where, for the relevant output node that would otherwise be switching between $-VP$ and ground, the proportion of the switching cycle that would be spent at the indirect-coupled boosted voltage $-VP$ would be above a threshold. For example, the threshold could be 50%. Thus, if the relevant output node would spend 50% or more of the switching cycle connected to $-VP$ if operating in the third mode (which corresponds, in this case, to a duty cycle for that output node of less than 0.5), the controller **804** can control the driver apparatus to operate in the fourth mode instead.

[0143] For a positive differential output, the output node **202a** may be switched between the voltages VP and $2VP$ and the output node **202b** may be held static at the voltage $-VP$. The driver **802a** may thus be operated in the same way as in the third mode.

[0144] To generate the static voltage $-VP$, switch SW**4b** is closed, with switch SW**5b** open, to connect the output node **202b** to the low-side rail. Switches SW**6b** and SW**7b** of the driver **802b** are closed (with the other switches of the driver **802b** open) so as to connect capacitor CP**1b** between the low-side rail and ground so that the capacitor CP**1b** can act as a reservoir capacitor for the charge pump **803**.

[0145] The charge pump **803** then controls switches SW**9** and SW**11** together and in antiphase with switches SW**10** and SW**13** to repeatedly charge capacitor CP**2** to VP , and then connect the capacitor CP**2** between ground and the low-side rail, with its positive plate connected to ground, so as to drive the low-voltage rail to $-VP$. This charges the capacitor CP**1b** to maintain the voltage at the low-side rail. The switches SW**9**, SW**10**, SW**11** and, in this case, SW**13**, are cycled at a defined charge pump switching frequency which is independent of the duty cycle of the switching node **202a**.

[0146] In this mode of operation, the charge pump **803** thus operates, together with the capacitor CP**1b** of the driver **802b**, to provide a continuous supply voltage at the low-side rail, and the output node is directly coupled to this supply voltage.

[0147] The output node **202a** is thus switched between the voltages VP and $2VP$ with a controlled duty cycle, whilst the output node **202b** is held static, through the switching cycle at the voltage $-VP$ and ground, to provide the desired output voltage based on the input signal. FIG. **9d** illustrates one example of switching waveforms V_{outa} and V_{outb} for the output nodes **202a** and **202b** and the resulting differential voltage V_{diff} over one switching cycle period T_{pwm} in this fourth mode of operation for a positive differential output. For a negative differential output, the output node **202a** would instead be held static at $-VP$ and the output node **202b** switched between $+VP$ and $+2VP$.

[0148] FIG. 10 illustrates examples waveforms for a switching driver apparatus **800** such as illustrated in FIG. 8 as the output signal varies. The waveforms **1001** and **1002** illustrate the voltages V_{outa} and V_{outb} at the output nodes **202a** and **202b** respectively. Waveform **1003** illustrates the unfiltered differential voltage across the load and waveform **1004** illustrates the resulting average differential output, i.e. the differential output signal as experienced by the load after filtering. It can be seen that the driver apparatus operates in the first mode for low signal magnitude and then switches to the second mode of operation as the required signal magnitude rises. As the magnitude rises higher, the driver switches to the third mode of operation. If the signal magnitude rises higher, such that the duty cycle for the output node switching between $-VP$ and ground falls below a threshold, the driver apparatus switches to the fourth mode of operation so that one output node is held static and direct-coupled to a supply voltage of $-VP$ to limit the impedance variation. When the signal magnitude then drops such that the duty cycle would be greater than the threshold, the driver apparatus transition back to the third mode of operation and then the second and first modes of operation as the signal magnitude reduces further.

[0149] FIG. 8 illustrates an embodiment where the charge pump **803** is configured to be operable, when required, to generate a negative boosted voltage at the low-side rails for the output nodes, in this case a voltage of $-VP$. In this case, the driver apparatus **800** operates with three supply voltages, which are the received system voltages ground and $+VP$ and the voltage $-VP$ which is generated by the charge pump **803**. These three supply voltages can be seen as the three voltages V_1 , V_2 and V_3 discussed with reference to FIG. 2, although the supply voltage V_3 is only generated by charge pump **803** when required (but, when it is generated it is generated so as to be a continuously maintained voltage throughout the switching cycle). In this example, the charge pumps of the drivers **802a** and **802b** provide the functionality of the flying capacitor driver and are operable to generate boosted voltages in an indirect-coupled mode. The charge pump of drivers **802a** and **802b** are operable to generate a boosted voltage $+2VP$, which is different to any of the supply voltages. The voltage $+2VP$ generated by a charge pump of drivers **802a** and **802b** can thus be seen as the voltage V_0 discussed above. The charge pump of drivers **802a** and **802b** are also operable to generate an additional boosted voltage $-VP$ in an indirect-coupled mode, which in this case is the same as the supply voltage $-VP$ which can be generated by the charge pump **803**.

[0150] It will be understood, however, that the charge pump **803** could alternatively be arranged to provide a positive boosted supply voltage to the high side rail, i.e. to provide a supply voltage of $+2VP$. In this case, the fourth mode may correspond to one output node being held static with the supply voltage $2VP$ and the other output node being switched with a controlled duty cycle between $-VP$ and ground. In some implementations there could be two charge pumps, coupled to the high-side and low-side rails respectively.

[0151] Note that the second mode of operation of the driver apparatus is described as a mode where one of the output nodes switches between $-VP$ and ground, and the other node switches between ground and VP . It would be possible to implement an alternative second mode, that provides the same range of differential output voltage, by switching one output node between ground and VP , whilst the other output node is switched between $+VP$ and $+2VP$.

[0152] It will also be understood that the voltages VP and ground are given as an example only.

[0153] In general, as illustrated in FIG. 11 the driver apparatus **800** according to this embodiment can be seen receiving system voltages V_1 and V_2 , where V_1 may be ground or some other defined reference and V_2 may be an input supply. First and second drivers **801a** and **801b**, which are combined charge pumps and drivers, receive the system voltages V_1 and V_2 are arranged to drive the output nodes **202a** and **202b** respectively. An additional charge pump **803** is shared between the drivers to provide a supply voltage generated from the system voltages V_1 and V_2 . A controller **804** controls the switching operation of the output stage **801**, combined charge pump and drivers **802** and flying capacitor auxiliary driver **803** based on an input signal (not separately illustrated).

[0154] Embodiments of the disclosure thus relate to driver apparatus that operates with a multi-

level switching voltages and which operates with a mixed direct-coupled and indirect-coupled energy transfer.

[0155] In some embodiments, there is provided a system and method for providing a multi-level output voltage, comprising: a plurality of voltage nodes to receive supply voltages, the supply voltages at separate voltage levels; at least one flying capacitor arranged to provide stored charge, the charge derived from the local voltage sources; and a switch network arranged to selectively couple one of the supply voltages or the flying capacitor to a voltage output node. The system may be configured to operate in at least two modes: a direct charge transfer mode, known as a DC-coupled mode, where at least one of the supply voltages is coupled to the voltage output node to provide an output voltage; and an indirect charge transfer mode, known as an AC-coupled mode, where the at least one flying capacitor is coupled to the voltage output node to provide an output voltage.

[0156] The supply voltages may comprise a system supply voltage or reference voltage (e.g. V_{dd} , $-V_{dd}$, Gnd), and at least one voltage source generated from a system supply voltage or reference voltage using a charge pump (e.g. $2V_{dd}$). Preferably, the system comprises at least three voltage nodes to receive supply voltages.

[0157] The direct mode is understood as a configuration where a power supply is coupled to the output node to provide an output voltage. The direct mode may be a DC-coupled mode, where the output node is coupled to a semi-stable power supply. When in the direct charge transfer mode, the output impedance of the semi-stable power supply is signal independent. The indirect mode is understood as a configuration where stored charge on a capacitor is coupled to the output node to provide an output voltage. The capacitor is further coupled to a voltage source or power supply via switches, where adjustment of the switch connection can result in movement of the output voltage. The indirect mode may be an AC-coupled mode, where a capacitor is provided with switches to connect to the voltage sources and the output node, and where the transition of switched drives the output voltage. When in the indirect charge transfer mode, the output impedance of the indirect charge transfer network is signal dependent.

[0158] The combination of the two operational modes enables a higher peak power deliverable to be supported without too much duty-cycle dependent impedance constraints.

[0159] Some embodiments relate to a system and method for providing a multi-level output voltage, comprising first, second and third voltage supplies at different voltage levels; a fourth voltage supply, wherein the fourth voltage supply is provided by a flying capacitor transitioning between two of the first, second and third voltage supplies; and switch network configured to selectively couple the first, second, third and fourth voltage supplies to an output node, to provide a multi-level output voltage. The third voltage supply may be derived from the first and second voltage supplies using a charge pump. The system may be operable in a direct mode (or DC-coupled mode) and in an indirect mode (or AC-coupled mode), as described above.

[0160] In some embodiments there is also provided a multi-level converter or driver apparatus (such as an amplifier) having a supply voltage (V_P) comprising: an output bridge arranged to receive an input signal (e.g. an audio input signal) and to output an output voltage for driving a load; at least one charge pump arranged to output a multiple of a supply voltage (e.g. $2V_P$); a first negative flying capacitor-based driver; and a switch network. The switch network is controlled to selectively couple the output bridge with the supply voltage, ground, the charge pump, and the first negative flying capacitor-based driver, where the switching of the switch network is controlled based on the input signal.

[0161] Preferably, the switch network is configured to switch the negative flying capacitor-based driver such that one end of the flying capacitor is coupled to the output voltage node, where the voltage at the other end of the flying capacitor can be switched to adjust the output voltage level. The converter may be operable in a direct mode and an indirect mode, as described above.

[0162] In some examples, the converter may further comprise a second negative flying capacitor-

based driver, the second flying capacitor-based driver adapted to store twice the charge of the first negative flying capacitor-based driver; and wherein the switch network is controlled to selectively couple the output bridge with the second negative flying capacitor-based driver.

[0163] Some embodiments relate to a multi-level converter or driver apparatus (such as an amplifier, e.g. a loudspeaker amplifier) comprising: a first combined charge pump driver, e.g. a speaker driver, to receive an input signal and provide an output signal to a first load terminal; a second combined charge pump driver, e.g. a speaker driver, to receive an input signal and provide an output signal to a second load terminal; at least one auxiliary charge pump; and a switch network, wherein the at least one auxiliary charge pump is configured to be selectively coupled with the first and/or second combined charge pump drivers, to provide additional charge levels to the first and/or second combined charge pump drivers.

[0164] The connection of the auxiliary charge pump to the drivers may be based on an input signal received by the multi-level converter, e.g. an audio input signal. It will be understood that the converter may comprise a low-side auxiliary charge pump, a high-side auxiliary charge pump, or both.

[0165] Some embodiments relate to a multi-level converter (such as an amplifier) arranged to receive a supply voltage and provide an output voltage at an output terminal, the converter comprising: at least one driver, e.g. a speaker driver, having an integrated direct charge pump; at least one auxiliary supply, preferably provided as an auxiliary helper charge pump; and a switch network coupling the driver and negative supply. The converter may be operable in at least two modes: a direct mode, where the driver with integrated charge pump generates an output voltage based on the supply voltage, and a hybrid mode, where the auxiliary supply is coupled with the driver to provide an increased output voltage level.

[0166] Preferably, the integrated direct charge pump comprises a switch to drive an output voltage based on the supply voltage, the integrated direct charge pump further comprising a capacitor operable to drive an output voltage based on a multiple of the supply voltage.

[0167] As used herein, the term DC-coupled may be understood as switching between two voltage levels, preferably using resistive switches. This can be extended to three or more voltages, with more switches. By way of example, DC voltages may be derived from a battery, an inductive switched mode power supply, or a switched cap power supply. Such power sources are assumed to be able to supply current for an extended period of time, for example greater than the period of the class D output signals at the lowest needed frequency.

[0168] As used herein, the term AC-coupled may be understood as an output driven to a voltage level by switching terminal T1 of a capacitor between two voltages while terminal T2 of the capacitor is coupled to the output. This can result in the load terminal driven outside of the range of the DC coupled power supplies. The capacitor and the load have a time constant, inherently limiting the duration of the pulse. If the load has an impedance of R, the capacitor a value of C, then RC would normally be chosen to be 1-100× the class D switching frequency.

[0169] For a system having a nominal 5V supply, 0V and 5V terminals, AC coupling alone could be used to achieve {0,5,10} V output or {-5,0,5} V. Alternative DC coupling alone with voltages, {0,5,10} V from three different rails could be used. However, an advantage of the above-described system comes with combining the AC-and DC-coupling systems for at least four levels of output. Two of the states are available directly from the power supply, i.e. DC coupled. Another DC state is made possible by a switched capacitor DC-DC converter. A fourth state is AC coupled. Using S to notate supply, and D and A for DC/AC coupled respectively, an example configuration of output voltages can be as follows: [0170] {0S, 5S, 10D, -5A} [0171] {0S, 5S, 10D, 15A} [0172] {0S, 5S, -5D, 10A} [0173] {0S, 5S, -5D, -10A} [0174] {0S, 5S, 10D, 20A} [0175] {0S, 5S, 10D, -10A}

[0176] The last two output voltage configurations are possible by using the DC supply for the source of the T1 capacitor terminal drive. If multiple supplies are available, the AC drive boost does not have to be the same supply as the main supply. For example, if 0V 2V 5V are the available

rails, output choices of {0,5,7} would be possible.

[0177] The driver apparatus of embodiments of the disclosure may be suitable for driving an output transducer. The output transducer may be, in some implementations, be an audio output transducer such as a loudspeaker or the like. The output transducer may be a haptic output transducer. In some implementation the output transducer may be driven in series with an inductor, i.e. there may be an inductor in an output path between an output node of the switching driver and the load. In some implementations the transducer may be a piezoelectric or ceramic transducer.

[0178] Embodiments may be implemented as an integrated circuit. Embodiments may be implemented in a host device, especially a portable and/or battery powered host device such as a mobile computing device for example a laptop, notebook or tablet computer, or a mobile communication device such as a mobile telephone, for example a smartphone. The device could be a wearable device such as a smartwatch. The host device could be a games console, a remote-control device, a home automation controller or a domestic appliance, a toy, a machine such as a robot, an audio player, a video player. It will be understood that embodiments may be implemented as part of a system provided in a home appliance or in a vehicle or interactive display. There is further provided a host device incorporating the above-described embodiments.

[0179] The skilled person will recognise that some aspects of the above-described apparatus and methods, for instance aspects of controlling the switching control signals to implement the different modes, may be embodied as processor control code, for example on a non-volatile carrier medium such as a disk, CD- or DVD-ROM, programmed memory such as read only memory (Firmware), or on a data carrier such as an optical or electrical signal carrier. For some applications, embodiments may be implemented on a DSP (Digital Signal Processor), ASIC (Application Specific Integrated Circuit) or FPGA (Field Programmable Gate Array). Thus, the code may comprise conventional program code or microcode or, for example code for setting up or controlling an ASIC or FPGA. The code may also comprise code for dynamically configuring re-configurable apparatus such as re-programmable logic gate arrays. Similarly, the code may comprise code for a hardware description language such as Verilog™ or VHDL (Very high-speed integrated circuit Hardware Description Language). As the skilled person will appreciate, the code may be distributed between a plurality of coupled components in communication with one another. Where appropriate, the embodiments may also be implemented using code running on a field-(re) programmable analogue array or similar device in order to configure analogue hardware.

[0180] It should be noted that the above-mentioned embodiments illustrate rather than limit the invention, and that those skilled in the art will be able to design many alternative embodiments without departing from the scope of the appended claims. The word “comprising” does not exclude the presence of elements or steps other than those listed in a claim, “a” or “an” does not exclude a plurality, and a single feature or other unit may fulfil the functions of several units recited in the claims. Any reference numerals or labels in the claims shall not be construed so as to limit their scope.

[0181] As used herein, when two or more elements are referred to as “coupled” to one another, such term indicates that such two or more elements are in electronic communication or mechanical communication, as applicable, whether connected indirectly or directly, with or without intervening elements.

[0182] This disclosure encompasses all changes, substitutions, variations, alterations, and modifications to the example embodiments herein that a person having ordinary skill in the art would comprehend. Similarly, where appropriate, the appended claims encompass all changes, substitutions, variations, alterations, and modifications to the example embodiments herein that a person having ordinary skill in the art would comprehend. Moreover, reference in the appended claims to an apparatus or system or a component of an apparatus or system being adapted to, arranged to, capable of, configured to, enabled to, operable to, or operative to perform a particular function encompasses that apparatus, system, or component, whether or not it or that particular

function is activated, turned on, or unlocked, as long as that apparatus, system, or component is so adapted, arranged, capable, configured, enabled, operable, or operative. Accordingly, modifications, additions, or omissions may be made to the systems, apparatuses, and methods described herein without departing from the scope of the disclosure. For example, the components of the systems and apparatuses may be integrated or separated. Moreover, the operations of the systems and apparatuses disclosed herein may be performed by more, fewer, or other components and the methods described may include more, fewer, or other steps. Additionally, steps may be performed in any suitable order. As used in this document, “each” refers to each member of a set or each member of a subset of a set.

[0183] Although exemplary embodiments are illustrated in the figures and described below, the principles of the present disclosure may be implemented using any number of techniques, whether currently known or not. The present disclosure should in no way be limited to the exemplary implementations and techniques illustrated in the drawings and described above.

[0184] Unless otherwise specifically noted, articles depicted in the drawings are not necessarily drawn to scale.

[0185] All examples and conditional language recited herein are intended for pedagogical objects to aid the reader in understanding the disclosure and the concepts contributed by the inventor to furthering the art, and are construed as being without limitation to such specifically recited examples and conditions. Although embodiments of the present disclosure have been described in detail, it should be understood that various changes, substitutions, and alterations could be made hereto without departing from the spirit and scope of the disclosure.

[0186] Although specific advantages have been enumerated above, various embodiments may include some, none, or all of the enumerated advantages. Additionally, other technical advantages may become readily apparent to one of ordinary skill in the art after review of the foregoing figures and description.

[0187] To aid the Patent Office and any readers of any patent issued on this application in interpreting the claims appended hereto, applicants wish to note that they do not intend any of the appended claims or claim elements to invoke 35 U.S.C. § 112(f) unless the words “means for” or “step for” are explicitly used in the particular claim.

Claims

1.-23. (canceled)

24. A driver apparatus for driving a transducer based on an input signal comprising: a first driver output node for outputting a first drive signal for driving said transducer; a switch network; a flying capacitor driver having an output voltage node for connection, in use, to a first terminal of a flying capacitor, the flying capacitor driver being operable in use to selectively switch a second terminal of the flying capacitor between two different voltages in a switching cycle of the driver apparatus such a voltage at the output voltage node is modulated between first and second driver voltages over the switching cycle of the driver apparatus; and a controller; wherein the switch network is operable to selectively connect the first driver output node to the output voltage node of the flying capacitor driver or to any of a first set of at least three different switching voltages, that are, in use, maintained at a respective voltage node throughout the switching cycle of the driver apparatus; and wherein the controller is configured to control the switch network and flying capacitor driver to generate the first drive signal at the first driver output node based on the input signal.

25. The driver apparatus of claim 24 wherein the first set of switching voltages comprises first and second supply voltages received by the driver apparatus.

26. The driver apparatus of claim 25 wherein the first set of switching voltages further comprises a first generated voltage generated by a DC-DC converter from at least one of the first and second supply voltages.

- 27.** The driver apparatus of claim 26 wherein the DC-DC converter comprises a charge-pump which is configured to operate with a reservoir capacitor at an output of the charge pump to maintain the first boosted voltage throughout a switching cycle of the charge-pump.
- 28.** The driver apparatus of claim 24 further comprising a second driver output node for outputting a second drive signal for driving said transducer differentially together with said first drive signal, wherein the switch network is further operable to selectively connect the second driver output node to the output voltage node of the flying capacitor driver or to any of the first set of at least three different switching voltages, and the controller is further configured to control the switch network and flying capacitor driver to generate the second drive signal at the second driver output node based on the input signal.
- 29.** The driver apparatus of claim 28 wherein the switch network comprises: switches for selectively connecting the first and second output nodes respectively to a first voltage rail and switches for selectively connecting the first and second driver output nodes respectively to a second voltage rail; and switches for selectively connecting either of at least two of the first set of switching voltages to the first voltage rail; wherein the output voltage node of the flying capacitor driver is, in use, coupled to one of the first and second output nodes via the second voltage rail.
- 30.** The driver apparatus of claim 29 wherein the switch network further comprises switches for selectively connecting the first and second driver output nodes respectively to one of the first set of switching voltages which is different to the voltages than can selectively connected to the first voltage rail.
- 31.** The driver apparatus of claim 28 wherein the controller is operable: in a first mode in which each of the first and second driver output nodes is switched between first and second supply voltages of the first set of switching voltages with a controlled duty-cycle; in a second mode in which one of the first and second driver output nodes is switched between said first and second supply voltages with a controlled duty-cycle and the other one of the first and second driver output nodes is connected to the output voltage node of the flying capacitor driver which operates to modulate the voltage at the output voltage node between the first and second driver voltages with a controlled duty cycle; and in a third mode in which one of the first and second driver output nodes is switched between said second supply voltage and a first boosted voltage of the first set of switching voltages.
- 32.** The driver apparatus of claim 31 where the driver apparatus comprises a DC-DC converter configured to generate said first boosted voltage from at least one of said first and second supply voltages.
- 33.** The driver apparatus of claim 24 wherein the flying capacitor driver is configured such that the first driver voltage is equal to one of the first set of at least three different switching voltages and the second driver voltage is different to each of the first set of at least three different switching voltages.
- 34.** The driver apparatus of claim 33 wherein the first set of switching voltages and the second driver voltage form a set of equally spaced voltage levels.
- 35.** The driver apparatus of claim 24 wherein the first set of switching voltage levels comprises a received ground voltage, a received positive supply voltage and a boosted voltage equal to twice the received positive supply voltage.
- 36.** The driver apparatus of claim 24 wherein the driver apparatus is an audio driver apparatus for driving an audio output transducer based on an audio input signal.
- 37.** An integrated circuit comprising the driver apparatus of claim 24.
- 38.** An electronic device comprising the driver apparatus of claim 24.
- 39.** A driver apparatus for driving a transducer based on an input signal comprising: a first driver output node for outputting a first drive signal for driving said transducer; a switch network operable in a direct mode to selectively connect the first driver output node to any of a first set of at least three different continuous voltages which are maintained throughout a switching cycle of the driver

apparatus; wherein the switch network is further operable in an indirect mode to connect the output node to a flying capacitor so as to drive the output node to a first drive voltage boosted by the flying capacitor, where the first drive voltage is only generated for part of the switching cycle of the driver apparatus.

40. A transducer driver configured to receive an input signal and first and second supply voltages and to generate an output signal for driving a transducer, the transducer driver comprising: a charge pump operable, in use, with at least one primary capacitor to selectively provide at least a first generated voltage based on the first and second supply voltages; a flying-capacitor driver operable, in use, with at least one secondary capacitor to provide at least a second generated voltage based on the first and second supply voltages,; and an output bridge configured to selectively modulate at least one output node between selected ones of the first and second supply voltages, the first generated voltage and the second generated voltage in a switching cycle to generate the output signal based on the input signal; wherein the first generated voltage is maintained throughout the switching cycle and the second generated voltage is only maintained for part of the switching cycle.

41. A switching amplifier apparatus for driving a transducer with a drive signal based on an input signal comprising: an output bridge configured to selectively modulate at least one output node between selected switching voltages with a controlled duty-cycle to generate said drive signal, wherein the switching voltages can be selected from any of: a first supply voltage received by the switching amplifier apparatus; a second supply voltage generated from the first voltage supply by a DC-DC converter; a first capacitor voltage generated by connecting a charged a flying capacitor to the at least one output node.

42. The switching amplifier apparatus of claim 41 wherein the DC-DC converter comprises a charge-pump or an inductive DC-DC converter.
