

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250264959

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Peng; Chih et al.

ELECTRONIC DEVICE AND METHOD FOR DRIVING TOUCH DISPLAY PANEL

Abstract

An electronic device configured to detect a touch event of a stylus and a hand is provided. The electronic device includes a touch display panel and a driver circuit. The touch display panel is configured to detect the touch event of the stylus and the hand. The touch display panel includes a plurality of driving lines. The driver circuit is coupled to the touch display panel. The driver circuit is configured to determine a first area and a second area. The stylus touches the first area, and the hand touches the second area. The driver circuit is configured to make the driving lines corresponding to the second area to be in a high impedance state when the touch display panel detects the touch event of the stylus and the hand.

Inventors: Peng; Chih (Hsinchu City, TW), Chan; Hsin-Ting (Taichung City, TW), Shih; Ding-Teng (Hsinchu City, TW), Kuo; Fan-Wei (Hsinchu County, TW)

Applicant: Novatek Microelectronics Corp. (Hsinchu, TW)

Family ID: 1000007695846

Assignee: Novatek Microelectronics Corp. (Hsinchu, TW)

Appl. No.: 18/581323

Filed: February 19, 2024

Publication Classification

Int. Cl.: G06F3/041 (20060101); G06F3/044 (20060101)

U.S. Cl.:

CPC G06F3/0418 (20130101); G06F3/04166 (20190501); G06F3/044 (20130101); G06F2203/04104 (20130101)

Background/Summary

BACKGROUND

Technical Field

[0001] The invention relates to an electronic device and a method for driving a touch display panel.

Description of Related Art

[0002] In recent years, the use of smartphones and tablets with styluses has become more and more common. Styluses offer more precise clicks, smoother swipes, and more sophisticated drawings, expanding business opportunities. Users often rest their hands on the mobile device when using a stylus, rather than holding it, for comfort and stability. However, if the mobile device is placed on a desk, it will lead to a lower signal-to-noise ratio (SNR) of styluses having relatively small capacitive values, and thus styluses may fail to click or slide. This can make it challenging to distinguish styluses' touch from hands or other interference, resulting in poor user experience.

SUMMARY

[0003] The invention is directed to an electronic device and a method for driving a touch display panel, capable of effectively distinguishing styluses' touch from hands or other interference, so as to provide good user experience.

[0004] An embodiment of the invention provides an electronic device configured to detect a touch event of a stylus and a hand. The electronic device includes a touch display panel and a driver circuit. The touch display panel is configured to detect the touch event of the stylus and the hand. The touch display panel includes a plurality of driving lines. The driver circuit is coupled to the touch display panel. The driver circuit is configured to determine a first area and a second area. The stylus touches the first area, and the hand touches the second area. The driver circuit is configured to make the driving lines corresponding to the second area to be in a high impedance state when the touch display panel detects the touch event of the stylus and the hand.

[0005] An embodiment of the invention provides a method for driving a touch display panel having a plurality of driving lines. The method includes detecting a touch event of a stylus and a hand; determining a first area and a second area, wherein the stylus touches the first area, and the hand touches the second area; and driving the driving lines corresponding to the second area to be in a high impedance state when the touch display panel detects the touch event of the stylus and the hand.

[0006] To make the aforementioned more comprehensible, several embodiments accompanied with drawings are described in detail as follows.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] The accompanying drawings are included to provide a further understanding of the disclosure, and are incorporated in and constitute a part of this specification. The drawings illustrate exemplary embodiments of the disclosure and, together with the description, serve to explain the principles of the disclosure.

[0008] FIG. 1 is a schematic diagram illustrating an electronic device according to an embodiment of the invention.

[0009] FIG. 2 is a block diagram illustrating the electronic device of FIG. 1 according to an embodiment of the invention.

[0010] FIG. 3 is a schematic diagram illustrating an application scenario of the electronic device of FIG. 1 according to an embodiment of the invention.

[0011] FIG. 4A and FIG. 4B are schematic diagrams illustrating sensing units of the touch display

panel and signal values thereof according to different embodiments of the invention.

[0012] FIG. 5 is a structure diagram illustrating a touch display panel according to an embodiment of the invention.

[0013] FIG. 6 is a schematic diagram illustrating the touch display panel of FIG. 5 including sensing units.

[0014] FIG. 7 is a flowchart illustrating steps in a method for driving a touch display panel according to an embodiment of the invention.

[0015] FIG. 8 is a flowchart illustrating steps in a method for driving a touch display panel according to another embodiment of the invention.

[0016] FIG. 9 is a waveform diagram illustrating a touch sensing signal, a common signal and a sensing data according to an embodiment of the invention.

DESCRIPTION OF THE EMBODIMENTS

[0017] Embodiments are provided below to describe the disclosure in detail, though the disclosure is not limited to the provided embodiments, and the provided embodiments can be suitably combined. The term “coupling/coupled” or “connecting/connected” used in this specification (including claims) of the application may refer to any direct or indirect connection means. For example, “a first device is coupled to a second device” should be interpreted as “the first device is directly connected to the second device” or “the first device is indirectly connected to the second device through other devices or connection means.” In addition, the term “signal” can refer to a current, a voltage, a charge, a temperature, data, electromagnetic wave or any one or multiple signals.

[0018] FIG. 1 is a schematic diagram illustrating an electronic device according to an embodiment of the invention. FIG. 2 is a block diagram illustrating the electronic device of FIG. 1 according to an embodiment of the invention. Referring to FIG. 1 and FIG. 2, the electronic device **100** includes a driver circuit **110** and a touch display panel **120**. The driver circuit **110** is configurable to be coupled to the touch display panel **120**. The electronic circuit **110** is adapted to drive the touch display panel **120**.

[0019] In the present embodiment, the electronic device **100** may be an electronic device having a display function, a touch sensing function and/or a fingerprint sensing function. In an embodiment, the electronic device **100** may be, but not limited to, a smartphone, a non-smart phone, a wearable electronic device, a tablet computer, a personal digital assistant, a notebook and other portable electronic devices that can operate independently and have the display function, the touch sensing function and/or the fingerprint sensing function. In an embodiment, the electronic device **100** may be, but not limited to, a portable or un-portable electronic device in a vehicle intelligent system. In an embodiment, the electronic device **100** may be, but not limited to, intelligent home appliances such as, a television, a computer, a refrigerator, a washing machine, a telephone, an induction cooker, a table lamp and so on.

[0020] In an embodiment, when the electronic circuit **110** is implemented as a single chip integrated circuit that can drive and control the touch display panel **120** to perform the display operation, the touch sensing operation and/or the fingerprint sensing operation, the electronic circuit **110** may include a control circuit, and the control circuit may be a micro-controller based core to perform all of control activities of the display operation, the touch sensing operation and/or the fingerprint sensing operation.

[0021] Regarding hardware structures of the components in the embodiment of FIG. 2, the driver circuit **110** may includes a processor having computational capability. Alternatively, the driver circuit **110** may be designed through hardware description languages (HDL) or any other design methods for digital circuits familiar to people skilled in the art and may be hardware circuits implemented through a field programmable gate array (FPGA), a complex programmable logic device (CPLD), or an application-specific integrated circuit (ASIC). In addition, enough teaching, suggestion, and implementation illustration for hardware structures of the driver circuit **110** and the

touch display panel **120** can be obtained with reference to common knowledge in the related art. [0022] FIG. **3** is a schematic diagram illustrating an application scenario of the electronic device of FIG. **1** according to an embodiment of the invention. Referring to FIG. **1** to FIG. **3**, taking a portable electronic device for example, the electronic device **100** is configured to detect a touch event of a stylus **310** and a hand **320** of a user. The driver circuit **110** is configured to drive the touch display panel **120** to detect the touch event of the stylus **310** and the hand **320**. The touch display panel **120** may include an active area and a peripheral area, and the active area is configured to be a detection area for detecting the touch event. The application scenario of FIG. **3** is taking for example, and does not intend to limit the invention.

[0023] In the present embodiment, objects such as passive capacitive styluses or gloves may have relatively small signal values compared to hands. To be specific, FIG. **4A** and FIG. **4B** are schematic diagrams illustrating sensing units of the touch display panel and signal values thereof according to different embodiments of the invention. Referring to FIG. **3** to FIG. **4B**, the touch display panel **120** includes a plurality of touch sensing units **122**. The touch sensing units **122** are arranged in an array, which includes a plurality of columns **X1** to **X10** and a plurality of rows **Y1** to **Y30**. The signal values in figures are capacitive values of the touch sensing units **122**.

[0024] In the present embodiment, the driver circuit **110** may drive the touch display panel **120** to perform a scan operation to detect touch events. For example, the touch display panel **120** may perform the scan operation in a horizontal direction, and the columns **X1** to **X10** of the touch sensing units **122** are scanned from two sides to a center, as illustrated in scan directions **D1** and **D2**. The scan directions **D1** and **D2** are taking for example, and do not intend to limit the invention. In addition, the signal values and the number of the touch sensing units **122**, the number of the columns **X1** to **X10**, and the number of the rows **Y1** to **Y30** are taking for example, and do not intend to limit the invention.

[0025] FIG. **4A** illustrates a case that only the stylus **310** touches the touch display panel **120**. In FIG. **4A**, the stylus **310** touches a detection area **410**, and the detection area **410** has relatively large signal values compared to other detection area. FIG. **4B** illustrates a case that only the hand **320** touches the touch display panel **120**. In FIG. **4B**, the hand **320** touches a detection area **420**, and the detection area **420** has relatively large signal values compared to other detection area.

[0026] From FIG. **4A** and FIG. **4B**, the detection area **410** of the stylus **310** has relatively small signal values compared to the detection area **420** of the hand **320**. Therefore, the signal values of the hand **320** may affect the signal values of the stylus **310** when the touch display panel **120** detects the touch event of the stylus **310** and the hand **320**.

[0027] To reduce the impact of hands or other interference, in the embodiments of the invention, the driver circuit **110** is configured to make driving lines of other detection area other than the detection area **410** to be in a high impedance state when the touch display panel **120** detects the touch event of the stylus **310** and the hand **320**.

[0028] FIG. **5** is a structure diagram illustrating a touch display panel according to an embodiment of the invention. Referring to FIG. **5**, the touch display panel **520** includes a plurality of touch sensors **522** and a plurality of display pixels **524**. One sensing unit includes multiple touch sensors **522**. In an embodiment, each touch sensor may be formed by connecting a plurality of common electrodes which are provided with a display common voltage in a display phase. In another aspect, the touch sensors **522** may serve as common electrodes in the display phase.

[0029] To be specific, the driver circuit **110** drives the display pixels **524** to display images via display scan lines GDL and display data lines SDL. Each display pixel **524** represents a pixel which is not a subpixel but a basic unit of a display resolution, such as a full-color pixel including R, G, B subpixels. Each display data line SDL represents a data line group including a plurality of data lines with respect to a display pixel.

[0030] The driver circuit **110** also drives and controls the touch sensors **522** to sense touch events via driving lines TSL. For self-capacitance touch sensing, touch driving signals and touch sensing

signals may be both transmitted on the driving lines TSL. For mutual-capacitance touch sensing, the touch display panel **520** may further include sensing lines for transmitting the touch sensing signals. In an embodiment, the touch display panel **520** may be an in-cell touch and display panel that the touch sensors are embedded, but the invention is not limited thereto.

[0031] In the present embodiment, the driving lines TSL may be connected to corresponding switches (not shown). The driver circuit **110** can turn off the corresponding switches to make the driving lines of the second area to be in the high impedance state.

[0032] For example, FIG. **6** is a schematic diagram illustrating the touch display panel of FIG. **5** including sensing units. Referring to FIG. **5** to FIG. **6**, the touch display panel **520** includes a plurality of sensing units **622**, and one sensing unit **622** includes multiple touch sensors **522**. At least one of the touch sensing units **622** forms a detection area. The touch display panel **520** includes a plurality of driving lines. The stylus **310** touches the first area **610**, and the hand **320** touches the second area **620**. The second area **620** is all detection area on the touch display panel **520** other than the first area **610**. The second area **620** is larger than the first area **610**. The driver circuit **110** can determine the first area **610** and the second area **620**, and turn off the switches connected to the driving lines corresponding to the second area, so that the driving lines corresponding to the second area are in the high impedance state when the touch display panel **520** detects the touch event of the stylus **310** and the hand **320**. The driving lines corresponding to the second area may be selected from corresponding part of the driving lines TSL of FIG. **5**. Therefore, the driver circuit **110** can make the driving lines corresponding to the second area to be in a high impedance state, and only scan the first area **610** of the touch display panel **520** during a touch term.

[0033] In addition, the second area **620** includes a first subarea **620_1** and a second subarea **620_2**. The hand **320** touches the first subarea **620_1**, and the second subarea **620_2** is all detection area on the touch display panel **520** other than the first area **610** and the first subarea **620_1**. The first subarea **620_1** is smaller than the second subarea **620_2**. The driver circuit **110** makes the driving lines corresponding to the first subarea **620_1** and the second subarea **620_2** to be in the high impedance state when the touch display panel **120** detects the touch event of the stylus **310** and the hand **320**.

[0034] FIG. **7** is a flowchart illustrating steps in a method for driving a touch display panel according to an embodiment of the invention. Referring to FIG. **1** to FIG. **3**, FIG. **6** and FIG. **7**, in the present embodiment, the method for sensing the at least one fingerprint image is at least adapted to the electronic device **100** depicted in FIG. **1**, but the disclosure is not limited thereto.

[0035] Taking the electronic device **100** for example, in step **S100**, the driver circuit **110** drives the touch display panel **520** to detect a touch event of a stylus **310** and a hand **320**. In step **S120**, the driver circuit **110** determines a first area **610** and a second area **620**, wherein the stylus **310** touches the first area **610**, and the hand **320** touches the second area **620**, and the second area **620** is all detection area on the touch display panel **520** other than the first area **610**. In an embodiment, the driver circuit **110** determines whether the detection area is the first area **610** or the second area **620** according to at least one of a unit signal value, a total signal value, a signal peak value, and an area size of the least one touch sensing unit **622**.

[0036] In step **S120**, the driver circuit **110** makes the driving lines corresponding to the second area **620** to be in a high impedance state when the touch display panel **520** detects the touch event of the stylus **310** and the hand **320**. Therefore, the driver circuit **110** can only scan the first area **610** of the touch display panel **520** during a touch term to reduce the impact of hands or other interference.

[0037] The method for driving the touch display panel described in the embodiment of the invention is sufficiently taught, suggested, and embodied in the embodiments illustrated in FIG. **1** to FIG. **6**, and therefore no further description is provided herein.

[0038] FIG. **8** is a flowchart illustrating steps in a method for driving a touch display panel according to another embodiment of the invention. Referring to FIG. **1** to FIG. **3**, FIG. **6** and FIG.

8, in the present embodiment, the method for detecting styluses is at least adapted to the electronic device **100** depicted in FIG. 1, but the disclosure is not limited thereto.

[0039] In step **S200**, the driver circuit **110** determines whether the touch display panel **520** will operate in a mode for detecting styluses. If the touch display panel **520** will operate in the mode for detecting styluses, the driver circuit **110** performs step **S210**. In step **S210**, the driver circuit **110** expects to find the pen area (the first area) **610** from the smallest area.

[0040] Next, in step **S220**, the driver circuit **110** determines the size of the pen area **610**

[0041] according to unit signal values of touch sensing units, and whether the determined size of the pen area **610** is smaller than a reference pitch value. The unit signal value indicates the capacitive value of the touch sensing unit to be determined. If the determined size of the pen area **610** is smaller than the reference pitch value, e.g. three pitches, but is not a limitation of the invention, the driver circuit **110** determines the area to be determined is the pen area **610** and performs step **S230**. If the determined size of the pen area **610** is larger than or equal to the reference pitch value, the driver circuit **110** determines the area to be determined is not the pen area **610** and performs step **S250**. In step **S250**, the driver circuit **110** drives the touch display panel **520** to operate in a mode for detecting hands. In the mode for detecting hands, the driver circuit **110** scan all detection area of the touch display panel **520**.

[0042] In step **S230**, the driver circuit **110** determines whether a signal peak value, i.e. a maximum signal value, of the touch sensing units of the pen area **610** is smaller than a first reference capacitive value. If the signal peak value of the touch sensing units of the pen area **610** is smaller than the first reference capacitive value, e.g. 180 pF, but is not a limitation of the invention, the driver circuit **110** determines the area to be determined is the pen area **610** and performs step **S240**. If the signal peak value of the touch sensing units of the pen area **610** is larger than or equal to the first reference capacitive value, the driver circuit **110** determines the area to be determined is not the pen area **610** and performs step **S250**.

[0043] In step **S240**, the driver circuit **110** determines whether a total signal value, i.e. a summation of the signal values, of the touch sensing units of the pen area **610** is smaller than a second reference capacitive value. If the total signal value of the touch sensing units of the pen area **610** is smaller than the second reference capacitive value, e.g. 300 pF, but is not a limitation of the invention, the driver circuit **110** determines the area to be determined is the pen area **610** and performs step **S260**. In step **S260**, the driver circuit **110** drives the touch display panel **520** to operate in the mode for detecting styluses. In the mode for detecting styluses, the driver circuit **110** only scans the pen area **610**, and makes the driving lines corresponding to the area **620** other than the pen area **610** to be in the high impedance state. If the total signal value of the touch sensing units of the pen area **610** is larger than or equal to the second reference capacitive value, the driver circuit **110** determines the area to be determined is not the pen area **610** and performs step **S250**.

[0044] In steps **S220**, **S230** and **S240**, the driver circuit **110** determines whether the detection area is the pen area **610** according to the unit signal value, the total signal value, the signal peak value, and the area size of the touch sensing units, but the invention is not limited thereto. In an embodiment, the driver circuit can determine whether the detection area is the pen area according to at least one of the unit signal value, the total signal value, the signal peak value, and the area size of the least one touch sensing unit.

[0045] After steps **S220**, **S230** and **S240**, the driver circuit **110** can locate the pen area **610**. In an embodiment, the driver circuit **110** can repeat steps **S220**, **S230** and **S240** many times to ensure the location of the pen area **610** is correct.

[0046] On the other hand, if the touch display panel **520** will not operate in the mode for detecting styluses, the driver circuit **110** performs step **S270**. In step **S270**, the driver circuit **110** expects to find the hand area (the second area) from the largest area.

[0047] In step **S280**, the driver circuit **110** determines whether a total signal value, i.e. a summation of the signal values, of the touch sensing units of the hand area **620_1** is larger than a third

reference capacitive value. If the total signal value of the touch sensing units of the hand area **620_1** is larger than the third reference capacitive value, e.g. 2000 pF, but is not a limitation of the invention, the driver circuit **110** determines the area to be determined is the hand area **620_1** and locates the hand area **620_1** in step **S290**. If the total signal value of the touch sensing units of the hand area **620_1** is smaller than or equal to the third reference capacitive value, the driver circuit **110** determines the area to be determined is not the hand area **620_1** and performs step **S250**.

[0048] In step **S300**, the driver circuit **110** makes the driving lines corresponding to the hand area **620_1** (the first subarea) to be in the high impedance state for locating the pen area **610** easily. After step **S300**, the driver circuit **110** may return to step **S210** to further locate the pen area **610**.

[0049] In steps **S280**, the driver circuit **110** determines whether the detection area is the hand area **620_1** according to the total signal value of the touch sensing units, but the invention is not limited thereto. In an embodiment, the driver circuit can determine whether the detection area is the hand area according to at least one of the unit signal value, the total signal value, the signal peak value, and the area size of the least one touch sensing unit.

[0050] The method for driving the touch display panel described in the embodiment of the invention is sufficiently taught, suggested, and embodied in the embodiments illustrated in FIG. 1 to FIG. 7, and therefore no further description is provided herein.

[0051] FIG. 9 is a waveform diagram illustrating a touch sensing signal, a common signal and a sensing data according to an embodiment of the invention. Referring to FIG. 9, the high level period of the touch sensing signal TSHD indicates a touch term. The common signal VCOM indicates the sensing data of the stylus **310** accumulated many times. A dashed box **900** indicates the sensing data of the stylus **310** accumulated once. That is, the driver circuit **110** can increase signal accumulation times of the stylus **310** during the touch term since the driver circuit **110** only scans the pen area **610** of the touch display panel **520** during the touch term.

[0052] In summary, in the embodiments of the invention, the driver circuit can locate the stylus according to the unit signal value, the total signal value, the signal peak value, and/or the area size of the touch sensing units. For the pen area, the driver circuit enhances the signal-to-noise ratio of the stylus by increasing signal accumulation times during the touch term to minimize the effect of noise. For the area other than the pen area, the driver circuit makes driving lines of the area other than the pen area to be in a high impedance state when the touch display panel detects the touch event of the stylus and the hand to reduce the impact of hands or other interference. Therefore, the electronic device and the method for driving the touch display panel are capable of effectively distinguishing styluses' touch from hands or other interference, so as to provide good user experience.

[0053] It will be apparent to those skilled in the art that various modifications and variations can be made to the disclosed embodiments without departing from the scope or spirit of the disclosure. In view of the foregoing, it is intended that the disclosure covers modifications and variations provided that they fall within the scope of the following claims and their equivalents.

Claims

1. An electronic device, configured to detect a touch event of a stylus and a hand, the electronic device comprising: a touch display panel, configured to detect the touch event of the stylus and the hand, wherein the touch display panel comprises a plurality of driving lines; and a driver circuit, coupled to the touch display panel, and configured to determine a first area and a second area, wherein the stylus touches the first area, and the hand touches the second area, and the driver circuit is configured to make the driving lines corresponding to the second area to be in a high impedance state when the touch display panel detects the touch event of the stylus and the hand, wherein the touch display panel comprises a plurality of touch sensing units, at least one of the touch sensing units forms a detection area, and the driver circuit determines whether the detection

area is the first area according to at least one of a unit signal value, a total signal value, a signal peak value, or an area size of the least one touch sensing unit.

2. The electronic device of claim 1, wherein the second area is all detection area on the touch display panel other than the first area.

3. The electronic device of claim 1, wherein the second area is larger than the first area.

4. (canceled)

5. The electronic device of claim 1, wherein the driver circuit only scans the first area of the touch display panel during a touch term.

6. The electronic device of claim 5, wherein the driver circuit increases signal accumulation times of the stylus during the touch term.

7. The electronic device of claim 1, wherein the second area comprises a first subarea and a second subarea, the hand touches the first subarea, and the driver circuit makes the driving lines corresponding to the first subarea to be in the high impedance state when the touch display panel detects the touch event of the stylus and the hand.

8. The electronic device of claim 7, wherein the driver circuit further makes the driving lines corresponding to the second subarea to be in the high impedance state when the touch display panel detects the touch event of the stylus and the hand.

9. The electronic device of claim 7, wherein the first subarea is smaller than the second subarea.

10. The electronic device of claim 7, wherein the driver circuit further determines whether the detection area is the first subarea according to at least one of the unit signal value, the total signal value, the signal peak value, or the area size of the least one touch sensing unit.

11. A method for driving a touch display panel having a plurality of driving lines, comprising: detecting a touch event of a stylus and a hand; determining a first area and a second area, wherein the stylus touches the first area, and the hand touches the second area; and making the driving lines corresponding to the second area to be in a high impedance state when the touch display panel detects the touch event of the stylus and the hand, wherein the touch display panel comprises a plurality of touch sensing units, at least one of the touch sensing units forms a detection area, and the step of determining the first area and the second area comprises: determining whether the detection area is the first area according to at least one of a unit signal value, a total signal value, a signal peak value, or an area size of the least one touch sensing unit.

12. The method of claim 11, wherein the second area is all detection area on the touch display panel other than the first area.

13. The method of claim 11, wherein the second area is larger than the first area.

14. (canceled)

15. The method of claim 11, further comprising: only scanning the first area of the touch display panel during a touch term.

16. The method of claim 15, further comprising: increasing signal accumulation times of the stylus during the touch term.

17. The method of claim 11, wherein the second area comprises a first subarea and a second subarea, the hand touches the first subarea, and the step of making the driving lines corresponding to the second area to be in the high impedance state when the touch display panel detects the touch event of the stylus and the hand comprises: making the driving lines corresponding to the first subarea to be in the high impedance state when the touch display panel detects the touch event of the stylus and the hand.

18. The method of claim 17, wherein the step of making the driving lines corresponding to the second area to be in the high impedance state when the touch display panel detects the touch event of the stylus and the hand further comprises: making the driving lines corresponding to the second subarea to be in the high impedance state when the touch display panel detects the touch event of the stylus and the hand.

19. The method of claim 17, wherein the first subarea is smaller than the second subarea.

20. The method of claim 17, wherein the step of determining the first area and the second area further comprises: determining whether the detection area is the first subarea according to at least one of the unit signal value, the total signal value, the signal peak value, or the area size of the least one touch sensing unit.
