

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250262780

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Dryfhout; Matthew James

SAFETY RAZOR WITH COMB AND BLADE

Abstract

A safety razor removes hair from skin using the cutting blade comprising a sharp edge along an elongated side of a planar surface. An outer comb has a row of outer teeth running along the planar surface on an outside of the cutting blade, each outer tooth is substantially perpendicular to the sharp edge and spaced with a gap between the row of the outer teeth and the planar surface of the cutting blade. Ends of the row of outer teeth comprise outer teeth tips. An inner guard runs along the planar surface on an inside of the cutting blade.

Inventors: Dryfhout; Matthew James (Homer Glen, IL)

Applicant: Personal Grooming Co Limited (London, GB)

Family ID: 1000008589467

Appl. No.: 19/185227

Filed: April 21, 2025

Related U.S. Application Data

parent US continuation 17444281 20210802 parent-grant-document US 12280512 child US 19185227

parent US continuation 15156816 20160517 parent-grant-document US 10315322 child US 14170269

parent US continuation-in-part 14170269 20140131 parent-grant-document US 9718200 child US 15156868

parent US continuation-in-part 14170269 20140131 parent-grant-document US 9718200 child US 15162606 20160523

parent US division 16248760 20190115 parent-grant-document US 11077570 child US 17444281

parent US division 15156868 20160517 parent-grant-document US 10500744 child US 16248760

Publication Classification

Int. Cl.: B26B21/12 (20060101); **B26B21/40** (20060101); **B26B21/52** (20060101)

U.S. Cl.:

CPC B26B21/12 (20130101); **B26B21/125** (20130101); **B26B21/4031** (20130101);
B26B21/4081 (20130101); **B26B21/523** (20130101);

Background/Summary

PRIORITY CLAIMS [0001] This application is a Continuation of U.S. patent application Ser. No. 17/444,28, filed Aug. 2, 2021, which is a Divisional (DIV) from U.S. Pat. No. 11,077,570 granted Aug. 8, 2021 from U.S. patent application Ser. No. 16/248,760 filed on Jan. 15, 2019 by the same inventor which was a Divisional (DIV) from U.S. Pat. No. 10,500,744 granted Dec. 16, 2019 from U.S. patent application Ser. No. 15/156,868 filed on May 17, 2016 by the same inventor which was a Continuation-in-part (CIP) of U.S. Pat. No. 9,718,200 granted Aug. 1, 2017 from U.S. patent application Ser. No. 14/170,269 filed on Jan. 31, 2014 by the same inventor. [0002] U.S. Pat. No. 11,077,570 granted Aug. 8, 2021 from U.S. patent application Ser. No. 16/248,760 was also a Divisional (DIV) from U.S. patent application Ser. No. 15/162,606 filed on May 23, 2016 by the same inventor, and Ser. No. 15/162,606 was a Continuation-in-part (CIP) of U.S. Pat. No. 9,718,200 granted Aug. 1, 2017 from U.S. patent application Ser. No. 14/170,269 filed on Jan. 31, 2014 by the same inventor, and Ser. No. 15/162,606 was also a Continuation (CON) from U.S. Pat. No. 10,315,322 granted Jun. 11, 2019 from U.S. patent application Ser. No. 15/156,816 filed on May 17, 2016 by the same inventor.

BACKGROUND OF THE INVENTIONS

1. Technical Field

[0003] The present inventions relate to body shavers and, more particularly, relate to handle couplings for body shavers.

DESCRIPTION OF THE RELATED ART

[0004] Safety razor blades have had assemblies where a cutting blade is surrounded by flexible portions or guards within a construction assembly used to house the cutting blade and are generally flexible for the purposes of temporarily allowing a greater cutting blade exposure when force is manually applied and when force is withdrawn the cutting blade exhibits less exposure. The cutting blades within these prior safety razor blades are typically fastened rigidly in order to disallow the cutting blade to move in relation to the housing cartridge of the safety razor blade. We often see the housing or cartridge of the prior safety razors adjusting in order to contour to challenging surfaces while the blade is anchored in place for the purpose of remaining rigid. These characteristics prove beneficial in creating and allowing for a clean close shave cutting hairs as close as possible.

Therefore, getting the cleanest and closest shave is often a primary competitive factor between shaving companies. In fact, in today's market we even see multiple rows of cutting blades rigidly in place in order to continue this trend. Because of the closeness these safety razors offer and because of the level of cutting blade exposure to one's skin we find that shaving cream is a necessary promoted lubricant in the shaving method in order to prevent cutting or bleeding. These safety razors were typically created for men who seek to shave their face as well as women who seek to shave their legs. Most prior art configurations illustrate flexible guards or a safety razor cartridge housing in order to safely contour a straight edge razor along the many curves that typically exist on a face of a man or legs of a woman while cutting hair as close as possible in order to promote

the smoothest shave attainable.

[0005] Examples of safety blade prior art are exhibited herein. One example is illustrated in U.S. Pat. No. 3,500,539 by Muros.

[0006] Another example of a prior art is U.S. Pat. No. 4,409,735 by Cartwright, wherein we see a shaving geometry that promotes a flexible cutting blade cartridge that offers more controlled flexibility when protruding a skin surface along the elongated side.

[0007] Yet another prior art is EP U.S. Pat. No. 1,537,964 by Pennella et al., wherein we see a wet shaving geometry that incorporates guard elements. The guard elements are staggered alongside the sharp edge of the razor while perpendicular and bisecting each razor row.

[0008] Yet another prior art is U.S. Pat. No. 5,031,316 by Oldroyd wherein we see another illustration wherein a supporting member or guard surrounds the flexible cutting blade allowing a level of protection while the sharp edge of the cutting blade protrudes the skin surface.

[0009] Yet another prior art is U.S. Pat. No. 2,670,533 by Kearney, wherein we see another illustration that similar to the U.S. Pat. No. 3,500,539 by Muros wherein the cutting blade protrudes into a skin surface which in turn allows an overexposure of a rigid cutting blade.

[0010] Yet another prior art is U.S. Pat. No. 2,725,886 by Gagliano, wherein there is illustrated a comb or like structure used for cutting or trimming hair on one's head but the prior art does not have a supporting inner guard, pre-determined base, nor a void used to assist in creating the shaving geometry illustrated in embodiments of the present inventions.

[0011] Yet another prior art is U.S. Pat. No. 6,094,820 by Adachi, wherein there is illustrated a razor comb blade unit intended for cutting or trimming hair on one'. However, the cutting blade in this example is slidably held in the blade holder leaving no base, void or gap to allow a desired cutting blade flexibility as described in the embodiments of the present inventions.

[0012] Yet another prior art is U.S. Pat. No. 8,413,334 by Walker, wherein there is illustrated a more recent art form where we are presented again a purposely rigid cutting blade that is rigidly anchored into place in order to allow the safety blade housing or cartridge to alone provide a level of safety through the depth margin of slots or grooves between each tooth in the comb guard.

[0013] When shaving the body skin it is also difficult to understand whether or not the safety razor is positioned at a correct shaving angle. It is commonly known that there are many hills and valleys that can be found over one's body or backside. Muscular and skeletal obstacles that protrude often are protruding at alternate shapes and sizes provide an even greater challenge when attempting to shave the backside. Those who are muscularly fit commonly have deeper cracks and crevices between muscles that can be even more of a challenge. For these reasons many men decide to settle for more expensive and painful alternatives such as waxing or laser treatments. Not only has displaying unshaven back hair been deemed as "gross" or disgusting by society but it's also seen as non-hygienic.

SUMMARY OF THE INVENTIONS

[0014] Thus, it is an object of the present inventions to provide a safety shaving razor blade that allows wet and dry shaving capabilities and the like.

[0015] It is still another object of the present inventions to minimize accidental cutting, nicking or razor burn from the sharp edge of the cutting blade which can often be negative results of shaving without applying shaving cream.

[0016] It is another object of the present inventions to provide such a razor blade that will eliminate the need to use a hair trimmer prior to shaving with a straight edge razor blade.

[0017] It is yet another object of the present inventions to provide such a razor blade that will cut hair at or slightly below a skin surface but not to the depth at which other safety razors provide. Thus, the shaving geometry eliminates the need of shaving cream in order to protect the skin surface from cutting or nicking.

[0018] It is still another object of the present inventions to provide such a razor blade that will allow an individual the choice to choose whether to dry shave without the application of water

and/or shaving cream or to choose to apply shaving cream or shaving lubricant and/or water to one's back side during the shaving process such as in the shower.

[0019] It is still another object of the present inventions to allow certain individuals who may have extremely sensitive skin or even viruses such as MERSA the ability to shave certain areas without irritation the infected skin surface which when using an overly exposure cutting blade tends to irritate, flare up and spread a virus.

[0020] It is still another object of the present inventions to offer a quick and easy shave during situations where a medical emergency may occur. An example of this could be using embodiments of the present inventions in the effect that a medical team may need to shave an individual chest in order to apply defibrillator in order to control heart fibrillation when applying an electric current to the chest wall.

[0021] It is still another object of the present inventions to eliminate the user of batteries and moving parts which are all too often found when using electronic devices.

[0022] It is still another object of the present inventions to eliminate the use of a device that possess moving parts which tends to break down and cause returns when selling through distributors, wholesalers and retailers.

[0023] It is still another object of the present inventions to offer a device that maintains a handle of which can accept its replacement shaving blades as well as accepts a device used to lubricate one's back with a shaving cream or gel type of lubricant prior to shaving.

[0024] It is still another object of the present inventions to offer a device that can be folded into a smaller more compact size that would be easily stored in a convenient space such as on the wall of one's shower and such. Folding the device would also prove efficient when selling in retail stores in that it would save space which is very important to retailers.

[0025] It is still another object of the present inventions to offer a shaving device that would allow handicapped individuals access easily and effectively shave "hard-to-reach" areas such as their legs without the effort that is normally required when using a traditional straight edge shaver handle and razor blade.

[0026] It is still another object of the present inventions to create a razor blade that could act as a handle itself or adhere to a handle that could be used for any part of the body.

[0027] It is still another object of the present inventions to create a razor that could prove beneficial for prepping during medical surgery or in an emergency matter time is crucial and shaving must be performed rapidly.

[0028] It is still another object of the present inventions to create a razor that could prove beneficial for use in rehabilitation centers such as prisons or detention centers where safety is important.

[0029] There is a need for a safety razor blade with outer teeth, outer teeth edge, deep void, inner guard, inner guard edge and an integrated cutting blade whereby deep void is intermediate of cutting blade and outer teeth.

[0030] The present inventions are illustrated by way of example and are not limited by the accompanying figures, in which like references indicate similar elements. Elements in the figures are illustrated for simplicity and clarity and have not necessarily been drawn to scale.

[0031] The details of the preferred embodiments and these and other objects and features of the inventions will be more readily understood from the following detailed description when read in conjunction with the accompanying drawings wherein:

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0032] FIG. 1 is a schematic cross-sectional view of a razor blade shaving geometry wherein a cutting blade engages alongside skin surface in a first position according to a first embodiment of

the present inventions;

[0033] FIG. 2 is a schematic cross-sectional view of a razor blade shaving geometry wherein a cutting blade engages an opposing force of a convex skin surface contour in a second position according to the first embodiment of the present inventions;

[0034] FIG. 3 is a schematic cross-sectional view of razor blade shaving geometry illustrating whereby said cutting blade is positioned inside of a skin surface contour A at inverted skin surface contour B according to a second embodiment of the present inventions;

[0035] FIG. 4 is a schematic cross-sectional view of a razor blade shaving geometry whereby the base is positioned in a closer distance in comparison to FIG. 1 and FIG. 2 and said cutting blade engages a convex skin surface contour according to the second embodiment of the present inventions;

[0036] FIG. 5 is a schematic cross-sectional view of a razor blade shaving geometry whereby said cutting blade is fastened in a fixed position inside of the skin surface contour according to a third embodiment of the present inventions;

[0037] FIG. 6 is a schematic cross-sectional view of a razor blade shaving geometry whereby said sharp edge of a cutting blade is at the skin surface contour A in a first position and a spring is embodied in order to prepare for a cutting blade to engage skin surface contour in a second position according to a fourth embodiment of the present inventions;

[0038] FIG. 7 is a schematic cross-sectional view of a razor blade shaving geometry whereby said cutting blade is engaged in a second position inside of the skin surface contour by a spring according to the fourth embodiment of the present inventions;

[0039] FIG. 8 is an angled elevated view of the razor blade whereby the comb portion is end up according to embodiments of the present inventions;

[0040] FIG. 9 is an elevated cut-away view of the apparatus as seen in FIG. 8 illustrating the comb, cutting blade and inner guard assembly according to embodiments of the present inventions;

[0041] FIG. 10 is an eye-level view of the apparatus of the present inventions illustrating the comb, cutting blade and inner guard according to the first through fourth embodiments of the present inventions;

[0042] FIG. 11 is an elevated angled view of the present inventions whereby the inner guard is end up and apparatus is up-side down according to the first through fourth embodiments of the present inventions;

[0043] FIG. 12 is an elevated angled up-side down view of the present inventions that illustrates a plurality of razor blades assembled together as one apparatus according to the first through fourth embodiments of the present inventions;

[0044] FIG. 13 is a side view the elongated handle by which the razor blade attaches on the upper end to in order to reach and shave areas of the body according to first through fourth embodiments of the present inventions;

[0045] FIG. 14 is an side close up view of the end of the that handle whereby the razor blade attaches according to embodiments of the present inventions;

[0046] FIG. 15 is an elevated angled view illustrated a handle shaped to conform to the shape of an individuals' hand or palm according to first through fourth embodiments of the present inventions;

[0047] FIG. 16 is an elevated angled view of the present inventions whereby the safety razor is attached a handle according to first through fourth embodiments of the present inventions;

[0048] FIG. 17 is and front elevated view of the razor blade illustrating the web coverings existing between each tooth in order to conceal shorn hair from view according to the first through fourth embodiments of the present inventions.

[0049] FIG. 18 is a view of an individual utilizing the safety razor by method of an elongated handle according to first embodiment of the present inventions;

[0050] FIG. 19 is a close up view of the razor blade cutting hair along the back side of an individual according to first embodiment of the present inventions;

[0051] FIG. **20** illustrates a side view of a wet shave sponge with a handle according to embodiments of the present inventions;

[0052] FIG. **21** illustrates a side view of a safety razor and an elongated handle for tactile feedback along a skin surface plane having a blade group and a support according to an embodiment of the present inventions;

[0053] FIG. **22** illustrates a front view of a safety razor and an elongated handle according to embodiments of the present inventions;

[0054] FIG. **23** illustrates a view on the inner side of an elongated handle and a safety razor according to embodiments of the present inventions;

[0055] FIG. **24** illustrates a rear view of a safety razor and an elongated handle according to embodiments of the present inventions;

[0056] FIG. **25** illustrates a close up side view of a safety razor of the circled area of prior FIG. **1** according to embodiments of the present inventions;

[0057] FIG. **26** illustrates a close up cross-sectional view of a blade group of the circled area of prior FIG. **5** according to embodiments of the present inventions;

[0058] FIGS. **27-28** illustrate aerial views of a two-sided back shaver handle gripped by a user extended under the armpit towards the backside according to embodiments of the present inventions;

[0059] FIG. **29** illustrates a side view of a safety razor of the circled area of prior FIG. **7** according to embodiments of the present inventions;

[0060] FIG. **30** illustrates a close up side view of a safety razor of the circled area of prior FIG. **8** according to embodiments of the present inventions;

[0061] FIG. **31** illustrates a close up cross-sectional view of a blade group of the circled area of prior FIG. **10** according to embodiments of the present inventions;

[0062] FIGS. **32-33** illustrate aerial views of handles gripped by a user extended under the armpit towards the backside with two safety blades indenting into the skin surface and triggering a sensory system according to embodiments of the present inventions;

[0063] FIGS. **34-36** illustrate side views of handles gripped by a user extended under the armpit towards the backside according to embodiments of the present inventions;

[0064] FIG. **37** illustrates a side view of a blade group for removably attaching to a substrate structure of a safety razor according to embodiments of the present inventions;

[0065] FIG. **38** illustrates a diagram of the different muscles that are found on the backside of the human body;

[0066] FIGS. **39-41** illustrate a close up side views of a muscle divide as was illustrated in the previous FIG. **18** and showing a safety razor and elongated handle for two-point discrimination according to embodiments of the present inventions;

[0067] FIG. **42** illustrates a close up side view of a circled portion of a blade group in prior FIG. **39** according to embodiments of the present inventions;

[0068] FIG. **43** illustrates a close up side view of a circled portion of a blade group in prior FIG. **40** according to embodiments of the present inventions;

[0069] FIG. **44** illustrates a close up side view of a circled portion of a blade group in prior FIG. **40**;

[0070] FIGS. **45-46** illustrate close up side views of a safety razor and elongated handle for tactile feedback according to embodiments of the present inventions;

[0071] FIG. **47** illustrates a close up side view of a safety razor and elongated handle for tactile feedback having an electric trimmer for a support according to embodiments of the present inventions;

[0072] FIG. **48** illustrate a close up side view of a safety razor and elongated handle for tactile feedback having a lubrication strip for a support according to embodiments of the present inventions;

[0073] FIGS. **49-50** illustrate front views of a safety razor with a channel inside of a blade group and a support according to embodiments of the present inventions;

[0074] FIGS. **51-52** illustrate close up side views of a safety razor and elongated handle for tactile feedback according to embodiments of the present inventions;

[0075] FIGS. **53-55** illustrate close up cross-sectional views of a blade group for tactile feedback according to embodiments of the present inventions;

[0076] FIGS. **56-57** illustrate close up views of a blade group rear surface of a blade group for tactile feedback according to embodiments of the present inventions;

[0077] FIGS. **58-59** illustrate an eye-level view of a safety razor for tactile feedback according to embodiments of the present inventions;

[0078] FIG. **60** illustrates a front view of an alternate embodiment of a safety razor with a skeletal structure according to embodiments of the present inventions; and

[0079] FIG. **61** illustrates the many level of distances to create two-point discrimination on the human male body locations in which these distances are performed in order for effective two-point discrimination communication; and

[0080] FIGS. **62-63** illustrate close up side views of an elongated back shaver handle and a safety razor removably attaching to the elongated handle with a pivot mechanism according to embodiments of the present inventions

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0081] FIG. **1** is a schematic cross-sectional view of a razor blade shaving geometry illustrating a skin surface contour A, an outer comb **140**, an outer teeth tip **150**, an outer teeth inside edge **190**, an inner guard **130**, an inner guard edge **180**, a base **200**, a deep void **160**, a cutting blade **110** and a sharp edge **120** of cutting blade **110** wherein sharp edge **120** engages alongside skin surface contour A in a first position; and alongside inverted skin surface contour C in a second position while the opposite side view of this embodiment being identical according to a first embodiment of the present inventions. As illustrated in FIG. **1** a safety razor **100** with an outer comb **140** and cutting blade **110** and a shaving geometry coinciding with present inventions. A cutting blade **110**; a sharp edge **120** at the end of a cutting blade **110**; an inner guard **130**; an outer comb **140**; an outer teeth tip **150**; a deep void **160**; an inner guard edge **180**; an inside edge **190** of outer teeth tips **150**; a base **200**; an elongated side **210**; and a cutting blade end **220** whereby in one embodiment illustrated in FIG. **1** the members engaging in a first position or in other words making initial contact with skin surface contour A includes the inside edge **190** of the outer teeth tip **150**, the sharp edge **120**, and the inner guard edge **180** wherein a skin surface contour A is defined by the inside edge **190** of outer teeth tips **150** and the inner guard edge **180** of the inner guard **130**. In the first embodiment the sharp edge **120** of the cutting blade **110** does not protrude the skin planar surface A. As will be seen in each of the first through the fourth embodiments, the sharp edge **120** of the cutting blade **110** does not protrude the skin planar surface A. A cutting blade **110** made of stainless steel extends along a path intermediate of a deep void **160** and inner guard **130**. It should be known the preferred cutting blade **110** exposure is less than about 0.030 inches (about 0.0762 centimeter). A strong opposing force of at least 10 pounds (4.536 kilograms (10 pounds)) may be applied while protecting and minimizing cutting or nicking on a skin surface when the apparatus engages.

[0082] A sharp edge **120** opposite of cutting blade end **220** is dependent on shaving blade geometry in order to produce greater or lesser friction. One characteristic in creating a lesser friction between sharp edge **120** of cutting blade **110** and a skin surface contour A is presented in this invention wherein a sharp edge **120** of a cutting blade **110** is prohibited from protruding said skin surface contour A. In the efforts to promote less friction, the level of distance between the base **200** and the sharp edge **120** of the cutting blade **110** will be substantial. Flexibility of cutting blade **110** is dependent upon the distance exhibited between a base **200** and sharp edge **120** wherein the greater the margin of distance the more flexibility is exhibited which results in less friction between sharp

edge **120** and skin surface when opposing force is applied. An extremely decreased level of friction by an extremely flexible cutting blade **110** wherein said sharp edge **120** of cutting blade **110** does not protrude flat plane of a skin surface contour A and allows for a shave where lubricant is not a recommended application. The less the level of distance between base **200** and sharp edge **120** the more rigid and less flexible the cutting blade **110**. Thus, a more rigid cutting blade **110** would be the result of an increased level of friction between sharp edge **120** of a cutting blade **110** and a skin surface.

[0083] An inner guard **130** is a supporting member mounted adjacent of said cutting blade **110** where, within said shaving geometry, inner guard **130** embodies an inner guard edge **180** which with an inside edge **190** of outer teeth tips **150** together create skin surface contour A. Inner guard edge **180** may have teeth wherein teeth possess a web covering in order to hide shorn hairs as will later be further disused and illustrated in FIG. **17**. Overall preferred distance from inner guard edge **180** to outer teeth inside edge **190** of outer teeth tips **150** is about 0.068 inches (about 0.1727 centimeter).

[0084] An outer comb **140** having elongated side **210** a row of outer teeth tips **150** and allowing shorn hair to exit the safety razor rearward of outer teeth inside edge **190** as illustrated in FIG. **19**. Outer teeth tips **150**, in a preferred embodiment as illustrated in FIG. **1-7** are no more than 0.032 inches (0.08128 centimeter) outside of sharp edge **120** of cutting blade **110**. The outer comb **140** is preferably made from injected molded plastic or flexible plastic material used in many of the prior art shaving assemblies and typically well acceptable by customers seeking shaving products as they are durable and productive. The outer comb **140** may also be manufactured of stainless steel or chrome in order to cater to an audience seeking a higher quality product which is common in the wet shaving industry market. An inside portion of the outer comb **140** removed in order to create a deep void **160**.

[0085] A deep void **160** is spaced intermediately of outer teeth tips **150** and cutting blade **110**. Deep void **160** in a preferred embodiment having a preferred thickness “K” of 0.014 inches (0.03556 centimeter) or less in order to control overexposure and over flexibility of said cutting blade **110**. The thickness K as described is can be measured between inner side of comb and inner side of the cutting blade **110**. The deep void **160** level of thickness limits the level of flexibility of the cutting blade **110** and plays an important role in the preferred level of friction displayed between the sharp edge **120** of a cutting blade **110** and a the skin surface contours in FIGS. **1-4**. Although said deep void **160** may run thicker than 0.014 inches (0.03556 centimeter) a dangerous level of friction is presented wherein greater exposure of sharp edge **120** of cutting blade **110** is presented. Deep void **160** also maintains a length which is referenced as “L” in FIGS. **1-7**. However, the length of L plays a vital role in FIG. **1-4** in that the L represents the distance from base **200** to sharp edge **120** of cutting blade **110**. It is important to remember that in seeking to prevent a dangerous level of sharp edge **120** exposure the opening between the sharp edge **120** of the cutting blade **110** and an inside edge **190** of the outer teeth tips **150** of the outer comb **140** has a dimension less than or equal to a dimension of an opening between the sharp edge **120** of the cutting blade **110** and an inner guard edge **180** of the inner guard **130**. Dimension of said deep void **160** is chosen to control the level of flexibility of a cutting blade **110** in order to shave hairs effectively while maintaining a level of friction that reduces the risk of cutting or bleeding. When beginning the shaving process an individual embracing the safety razor **100** makes initial contact to their skin surface on the skin surface contour A which is referred to as “first position”. The distance from the inside edge **190** of the outer teeth tips **150** to the inner guard edge **180** define the skin surface contour A or the first position. In certain embodiments as illustrated by FIG. **1** and FIG. **6** the sharp edge **120** of cutting blade **110** is also engaged in first position along a skin surface contour A. When said sharp edge **120** of cutting blade **110** is engaging in a first position said sharp edge **120** will not protrude the skin surface contour A. As can be seen and will be further described cutting blade **110** in FIG. **3** engages in the second position.

[0086] The skin surface contour A is flat when not pressed by the safety razor **100**. When the safety razor **100** is pressed against the skin surface contour A during shaving, the skin surface contours B or C result as illustrated in FIG. 1, depending on how hard it is pressed. The outer comb **140** and the inner guard **130** press against the skin surface creating two impressions and a convex skin surface contour B or C therebetween. This convex surface of the skin raises the skin closer to the sharp edge **120** for a closer cut of the hair. In some instances the convex skin surface may be considered protuberant.

[0087] The skin surface contours B or C have a convex skin surface contour between a pair of skin indents respectively created between both the outer comb **140** and the inner guard **130**. When both the inside edge **190** of the outer comb **140** and the inner guard edge **180** of the inner guard **130** press into the skin, the recessed sharp edge **120** moves relatively closer towards the skin surface contour B or C of the skin when cutting the hair.

[0088] The outer comb **140** and the inner guard **130** simultaneously touch the skin surface during shaving and can also firmly press respective indents into the skin surface during shaving. Thus the convex contour between a pair of skin indents is respectively created between both the outer comb **140** and the inner guard **130** pressing into the skin surface. Because the present inventions are suitable for dry shaving, without a shaving cream or surface lubricant, the inner guard **130** can firmly press against the skin surface and there is no concern about shaving cream or skin lubricant removal by scraping from the skin surface before the skin surface and hair hit the sharp edge **120** of the cutting blade **110**.

[0089] Letter designations in the drawings depict certain planes, gap distances and contours, defined throughout, and for convenience are summarily defined wherein: [0090] "L" references the deep void **160** running lengthwise from the outer teeth tips **150** to the base **200** which allows ample space for the flexibility of said cutting blade **110** to perform [0091] "K" references the thickness of the said deep void **160** between the outer comb **140** and the cutting blade **110** which is a contributing factor in the level of flexibility the cutting blade **110** illustrates when shaving; [0092] "A" references the skin surface contour A which is formed between the inside edge **190** of the outer teeth tips **150** and the inner guard edge **180**. Skin surface contour A is also referenced as being the "first position" when safety razor **100** initially engages a skin surface contour A; [0093] "B" references a convex skin surface contour A engaged in a convex surface contour in a second position as indicated in FIG. 3 wherein the sharp edge **120** of cutting blade **110** is engaged initially at a second position inside the original first position or skin surface contour A; [0094] "C" references a convex skin surface contour A engaged in a convex contour whereby in FIG. 1 and FIG. 2 convex skin surface contour C is formed by cutting blade **110** flexed against an opposing skin surface force in a second position is inside the original first position and in FIG. 3 and FIG. 4 convex skin surface contour C is formed in a third position inside of the original first position A and the second position B when opposing force is applied during the shaving operation; [0095] "D" references the margin difference between when sharp edge **120** of cutting blade **110** is flexed against opposing force versus its original position or "uninterrupted" position. In FIG. 1 and FIG. 2 reference D is the margin of difference between skin surface contours A versus C. In FIG. 3 we see reference D is the difference between convex skin surface contour B and skin surface contour C. [0096] "E" referencing the distance of skin surface contour A or the distance between the inside edge **190** of outer teeth tips **150** and the inner guard edge **180**. Reference J is always greater than or equal to G. Although a number alternative distances may exist to create an effective shaving assembly a preferred embodiment the margin of distance is about 0.068"; [0097] "J" references the margin of distance between the sharp edge **120** of a cutting blade **110** and the inner guard edge **180**. Although a number alternative distances may exist to create an effective shaving assembly a preferred embodiment the margin of distance is about 0.024"; [0098] "G" references the margin of distance between the sharp edge **120** of a cutting blade **110** and the inside edge **190** of the outer teeth tips **150**. Although a number alternative distances may exist to create an effective shaving

assembly a preferred embodiment the margin of distance is about 0.018"; and [0099] "H" references to the midpoint section of a cutting blade **110**.

[0100] The safety razor **100** removes hair from skin using the cutting blade **110** comprising a sharp edge **120** along an elongated side **210** of a planar surface. An outer comb **140** has a row of outer teeth **140** running along the planar surface on an outside of the cutting blade **110**, each of the outer teeth of the outer comb **140** is substantially perpendicular to the sharp edge **120** and spaced with a deep void **160** between the row of the outer comb **140** and the planar surface of the cutting blade **110**, wherein ends of the outer comb **140** comprise outer teeth tips **150**. An inner guard **130** runs along the planar surface on an inside of the cutting blade **110**. The sharp edge **120** of cutting blade **110** is recessed up to a skin surface contour A. The skin surface contour defined from the inside edges **190** of outer teeth tips **150** to the inner guard edge **180**. When cutting blade **110** is flexing said cutting blade **110** longitudinally bends in a curved-like arc while sharp edge **120** of cutting blade **110** causing further recess D relative to the skin surface contour A. The sharp edge of the cutting blade can longitudinally bend to cause further recess relative to the skin surface contour. The sharp edge of the cutting blade can longitudinally bend to cause further recess relative to the skin surface contour. The cutting blade **110** is fixedly anchored on the cutting blade end **220** opposite the sharp edge **120**.

[0101] The inner guard **130** may comprise an inner comb comprising a row of inner teeth running along the elongated side of an inside of the cutting blade **110**, each of the inner teeth substantially perpendicular to the sharp edge **120**.

[0102] A user for hair removal moves the safety razor **100** across skin such that the outer comb **140** extends over the cutting blade **110** to contact the hair before the hair comes in contact with the sharp edge **120**. Prior to the shaving operation or flexing of the cutting blade **110** the inner guard **130** can have substantially no void between the cutting blade **110** and inner guard **130**. When the safety razor **100** moves across the skin, the hair first passes through the outer comb **140** and then second the sharp edge **120** of the cutting blade **110** bends in a direction towards the outer comb **140** against a skin surface contour shortening the width of the gap G between the sharp edge **120** of the cutting blade **110** and the row of outer teeth of the outer comb **140** in FIG. 1-4 and the hair is cut by the sharp edge **120**. The base **200** is positioned to create a level of distance between said base **200** and sharp edge **120** of cutting blade **110** in order to enable a controlled level of flexibility with said cutting blade **110**. Outer comb **140** acts as a barrier to physically limit over bending of the sharp edge **120** of the cutting blade **110**.

[0103] The safety razor **100** is moved across skin such that an outer comb **140** extends over the cutting blade **110** to contact hair before the hair comes in contact with a sharp edge **120**. When moving the safety razor **100** across skin, the hair first passes through the outer teeth of the outer comb **140** and second then the sharp edge **120** of the cutting blade **110** bends in a direction to shorten the width of the gap G between the sharp edge **120** of the cutting blade **110** and the row of outer teeth of the outer comb **140** and the hair is cut by the sharp edge **120**.

[0104] A deep void **160** exists between the planar surface of the cutting blade **110** and the outer comb **140** in the first and second and third and fourth embodiments of respective FIGS. 1-5. The deep void **160** extending from the outer teeth tips **150** to a base **200** of the outer comb **140**. In order to create a desired "light friction" shave a preferred length of the deep void **160** reaching from outer teeth tips **150** to the base **200** is 0.180 inches (0.4572 centimeter). The closer a base **200** in distance to the sharp edge **120** of a cutting blade **110** the more rigid and less flexible the cutting blade **110** becomes and thus the level of friction increases between sharp edge **120** of a cutting blade **110** and a skin surface contour. Just the opposite, the further in distance a base **200** is to the sharp edge **120** of a cutting blade **110** the less rigid or more flexible the cutting blade **110** becomes and thus the level of friction decreases between a sharp edge **120** of a cutting blade **110** and a skin surface contour. It is important to note that aside from the position of said base **200**, the degree of thickness of the deep void **160** which is represented as K plays a factor in determining the level of

flexibility by which said cutting blade **110** is granted.

[0105] An opening G between the sharp edge **120** of cutting blade **110** and inside edges **190** of the outer teeth tips **150** of the outer comb **140** has a dimension G the same or less than a dimension J of an opening J between the sharp edge **120** of cutting blade **110** and an inner guard edge **180** of the inner guard **130**. A dimension of the deep void **160** has a depth extending from the outer teeth tips **150** to a base **200** of the outer comb **140** substantially greater than a dimension G of the gap G. A dimension of the gap G is chosen in connection with the preferred distance of a base **200** from the sharp edge **120** of a cutting blade **110**. It should be noted that the closer the base **200** is in distance to the sharp edge **120** of a cutting blade **110** the smaller the gap G becomes. The further away the base **200** is in distance to the sharp edge **120** of the cutting blade **110**, the larger the gap G may become.

[0106] A problem with prior safety razors is that while they do offer a level of protection when contouring within the shaving process, it is widely known that in order to attain such a close shave that they still do require and create a cutting blade flexibility and exposure that is far too rigid to create a controlled atmosphere that would allow one to dry shave a hard-to-reach area such as one's back without application of shaving cream. More often in order to create a safety razor that navigates angles and bumps we see the safety razor **100** housing or "cartridge" being altered while the cutting blade **110** remains rigid. The strong friction is often illustrated in today's market between the sharp edge **120** of the cutting blade **110** and a skin surface which is why the application of shaving cream or shaving gel prior to shaving is recommended in order to minimize the cutting or nicking of the skin surface. The prior safety razors do not allow a controlled shaving geometry that minimizes cutting blade **110** exposure while offering a level of flexibility take place without the use of shaving cream or gel in order to greatly minimize cutting or bleeding. One common factor amongst the majority of safety razors is that the cutting blade, although engaging by guards that may assist in deflection when engaging a skin surface, often embody a cutting blade that is capable of protruding a skin surface contour A that is formed between an inner guard edge **180** and the inside edge **190** of the outer teeth tips **150**. Another important missing characteristic of the prior art is that there does not exist an opening G between the sharp edge **120** of cutting blade **110** and an inside edge **190** that remains the same level of distance or less than an opening represented by J which exists between the sharp edge **120** of cutting blade **110** and an inner guard edge **180** of the inner guard **130**. A final important notation is that a cutting blade **110** that is most commonly found within razors today do not embody a preferred level of distance between a sharp edge **120** and a base **200** that would allow for a proper amount of cutting blade **110** flexibility which creates an extremely light or soft level of friction between sharp edge **120** of a cutting blade **110** and a skin surface.

[0107] Furthermore, in embodiments of the present inventions there is a deep void **160** that is specified in FIG. 1 wherein said deep void **160** is embodied between the base **200** and outer teeth tips **150** and enables multiple contributing factors one of which would be the thickness of the deep void **160** represented by K which the level of thickness controls the level flexibility of cutting blade **110**. This ultimately controls the level of friction allowed between sharp edge **120** of cutting blade **110** and a skin surface contour which in FIG. 1 is represented as A in the first position. These are important factors of the present inventions since creating a light traction is necessary when dry shaving and cutting at a lesser depth than a traditional over exposed and over rigid safety razor cutting blade **110**. In summary, this prior art is generally designed to perform or cut hair at an aggressive level while creating a housing surrounding a cutting blade **110** or blades that create or allow a level of safety during the shaving operation. My invention, however, does not attempt to perform or cut hair at an aggressive level but instead performs or cuts at a less aggressive level. Furthermore, my invention takes advantage of the flexibility of a skin surface. The human skin is flexible and is able to bend at many contour angles. Being that in my invention a skin surface is granted ability to bend in a convex contour between a pair of skin indents respectively created

between the comb and guard with an aggressively flexible cutting blade we notice a preferred level of friction throughout the shaving operation. Most prior art embodiments we see the guards or housing cartridges bending or flexing around the cutting blade wherein my invention I illustrate the cutting blade bending and flexing in relation to skin surface contour created by the fixed housing. The priority in my invention is that it cuts at a less aggressive level wherein an individual is not required to apply shaving cream or shaving lubricant to their back or back side prior to shaving in order to prevent several razor burn or cutting. It is very difficult for an individual to access their own back or back side with shaving cream without asking for assistance from another individual or without using a handle that may extend in length to access their back or back side. Thus, it proves beneficial to have a safety razor designed to allow an effective shave that does not rely on shaving cream or a shaving lubricant to be applied to dry skin prior to the shaving operation in order to protect oneself from cutting or bleeding. In addition, the cost associated with purchasing shaving cream is saved since shaving cream is not a requirement. Also, it is very scary for an individual to access their back or back side with a safety razor that does not cut at a level aggressive level of shaving friction. Not being able to accurately view your own back or back side while attempting to use a sharp safety razor is very dangerous and scary. The less aggressive level of shaving operation in my invention offers a level of protection and light friction that does not require shaving cream or a shaving lubricant to be applied to dry skin prior to the shaving operation in order to protect a skin surface from cutting or bleeding from the cutting blade. It is widely known that cutting or bleeding is a common side effect when shaving one's face with a safety razor design for one's face. Also, an area such as one's back or back side offers a surface where the larger area of skin offers more flexibility of a skin surface area which proves beneficial to my invention. The majority allows a redundant amount of rigid cutting blade exposure when attempting to dry shave without the use of shaving cream which can lead to severe cutting or what is commonly referred to as "razor burn" to take place which is described as a skin condition featuring a red rash, bumps, or even infected blisters.

[0108] FIG. 2 is a schematic cross-sectional view of a razor blade shaving geometry wherein a cutting blade **110** engages an opposing force of a convex skin surface contour C in a second position according to the first embodiment of the present inventions. FIG. 2 illustrates a skin surface contour A or C, a comb, an outer teeth tip **150**, outer teeth inside edge **190**, an inner guard **130**, an inner guard edge **180**, a base **200** and a cutting blade **110** wherein the cutting blade **110** engages a convex skin surface in a second position; the opposite side view of this embodiment being identical according to a second embodiment of the present inventions. As illustrated in FIG. 2, while a first position is still active, a "second position" is created when an individual exercises a shaving stroke wherein an opposing force is applied allowing a determined degree of friction between sharp edge **120** of cutting blade **110** and skin surface whereby the degree of friction is determined by the sharp edge **120** of a cutting blade **110** being recessed up to a skin surface as well determined by the degree of distance a base **200** is positioned from the sharp edge **120** of a cutting blade **110**. The further the distance a base **200** is positioned away from a sharp edge **120** of a cutting blade **110** the more flexibility is allowed by a cutting blade **110** which creates a lower level of friction and a softer shave. The closer the distance a base **200** is positioned from a sharp edge **120** of a cutting blade **110** the cutting blade **110** is more rigid and less flexible which creates a higher level of friction and a stronger shave. Although various measurements will create a light friction between the sharp edge **120** and a skin surface, the preferred length of the deep void **160** in creating a light friction is 0.180 inches (0.4572 centimeter) from the base **200** to the outer teeth tips **150**. Furthermore, the thickness of the deep void **160** participates in controlling the level of friction between the sharp edge **120** of a cutting blade **110** and a skin surface as it limits the flexibility level of a cutting blade **110**. Said sharp edge **120** of cutting blade **110** may engage in a first and second position but always along with at least one outer teeth inside edge **190** and at least one inner guard edge **180** on each opposite side of cutting blade **110**. An outer teeth inside edge **190** running along

the elongated side **210** of an outside of said cutting blade **110** and inner guard edge **180** running along the elongated side **210** of an inside of said cutting blade **110**. As illustrated in FIG. 2 a safety razor **100** with comb and integrated blade in accordance with FIG. 1 wherein the cutting blade **110** is engaged in a second position with an opposing force wherein sharp edge **120** is flexed against a convex skin surface contour C. FIG. 2 illustrates a gentle friction between cutting blade **110** and skin surface contour which allows for an effective shave while cutting the hair a beneficial level versus the majority of straight edge razors assemblies on the market which aim to cut the hair as close as possible or even beneath the skin surface which is the reason shaving cream or shaving gel is often sold with straight razors. Skin surface contour A, in a preferred embodiment, is positioned between 20 to 50 degrees. Due to the fact that my invention cuts a hair at a less aggressive length the presence of shaving cream or gel prior to shaving is not necessary to minimize cutting or nicking of the skin surface. Furthermore, embodiments of the present inventions work better in areas of the body that have hair follicles less coarse. For example embodiments of the present inventions work better on back or arm hair which often possesses hair less coarse or thick in comparison to facial hair which is known to be thicker in nature.

[0109] FIG. 3 is a schematic cross-sectional view of razor blade shaving geometry illustrating whereby the base **200** is positioned closer in distance to the sharp edge **120** in comparison to the first embodiment in FIG. 1 and FIG. 2. When creating a less flexible cutting blade **110** in comparison to the first embodiment, it is necessary, in the spirit of maintaining a lighter friction between skin surface contour A and sharp edge **120**, for said cutting blade **110** to be positioned inside of a skin surface contour A creating less cutting blade **110** blade exposure which in turn creates a lighter friction. As illustrated in FIG. 3 is a safety razor **100** with comb and integrated blade in accordance with FIG. 1 wherein the cutting blade **110** is positioned at convex skin surface contour B in a second position inside a skin surface contour A. The cutting blade **110** is fixedly anchored at a cutting blade end **220**. This FIG. 3 demonstrates how when a cutting blade **110** maintains a base **200** closer in margin distance to the sharp edge **120** it is necessary to decrease the exposure of a cutting blade **110** in relation to the skin surface in order to maintain a less aggressive shaving friction.

[0110] FIG. 4 is a schematic cross-sectional view of a razor blade shaving geometry whereby the base **200** is positioned in a closer distance in comparison to FIG. 1 and FIG. 2 and said cutting blade **110** is engaged in the second position an opposing force at a convex skin surface contour C according to the second embodiment of the present inventions. The inverted skin surface contour C is a sharper arc shaped bend than the inverted skin surface contour B or the flat plane of the skin surface contour A. As illustrated in FIG. 4 is a safety razor **100** in accordance with FIG. 3 wherein the cutting blade **110** is engaged in a third position with an opposing force and sharp edge **120** is flexed against a convex skin surface contour C. The cutting blade **110** is fixedly anchored at a cutting blade end **230**. When said cutting blade **110** is engaged in a third position with an opposing force the void margin indicated by K is minimized between the cutting blade **110** and the outer comb **140**. FIG. 4 clearly illustrates since the distance margin between the base **200** and the sharp edge **120** is increased when compared to FIG. 1 and FIG. 2 the exposure of the cutting blade **110** is decreased. This adjustment allows a light friction to be maintained in order to create an effective shave that ultimately does not require shaving cream or lubricant in order to prevent severe cutting or nicking of a skin surface.

[0111] FIG. 5 is a schematic cross-sectional view of a razor blade shaving geometry whereby the cutting blade **110** is fastened in a fixed position inside of the skin surface contour A according to a third embodiment of the present inventions. A fixedly anchored cutting blade **110** of a rigid material is substantially recessed inside the skin surface contour A of FIG. 5. As illustrated in FIG. 5 is a safety razor **100** wherein a cutting blade **110** is made from a non-flexible razor or perhaps ceramic. The cutting blade **110** is fixedly anchored between cutting blade end **240** and a base **200** wherein the sharp edge **120** remaining inside of a skin surface contour A at the same position in

both the first position A and second position B for the purpose of allowing cutting accessibility while protecting the skin surface due to non-flexing attributes of cutting blade **110**. Being that the cutting blade **110** in this example is made from a non-flexible razor such as ceramic the position of the base **200** to the sharp edge **120** of the cutting blade **110** is not relevant in this example.

[0112] FIG. **6** is a schematic cross-sectional view of a razor blade shaving geometry whereby said sharp edge **120** of a cutting blade **110** is at the skin surface contour A in a first position and a flexible spring **170** is embodied in order to prepare for the cutting blade **110** to engage an opposing force of a skin surface contour in a second position according to a fourth embodiment of the present inventions. As illustrated in FIG. **6** is a safety razor **100** wherein a cutting blade **110** is in an engaging first position alongside a skin surface contour A and not protruding the skin surface contour A. Illustrated in FIG. **6** is a flexible spring **170** which is implemented in order to cutting blade **110** flexibility in a different manner when compared to FIG. **2** and FIG. **4**. The cutting blade **110** is fixedly anchored at a flexible spring **170**. The flexible spring **170**, of the fourth embodiment of FIG. **6**, is operatively coupled to the cutting blade **110** on a cutting blade end **250** of the planar surface opposite the sharp edge **120**, causes further recess relative to the skin surface contour A. Being that the cutting blade **110** in this example is allowed flexibility in a different manner when compared to FIG. **2** and FIG. **4** the position of the base **200** is not relevant in terms of determining a level of friction between sharp edge **120** of the cutting blade **110** and a skin surface.

[0113] FIG. **7** is a schematic cross-sectional view of a razor blade shaving geometry whereby said cutting blade **110** is flexed and engaged in a second position C inside of the skin surface contour A by a spring according to the fourth embodiment of the present inventions. As illustrated in FIG. **7** and in accordance with FIG. **6** the cutting blade **110** is flexing due to a flexible spring **170** allowing the cutting blade **110** to retract horizontally and away from skin surface contour A. The flexible spring **170**, of the fourth embodiment of FIG. **7**, is operatively coupled to the cutting blade **110** on a cutting blade end **250** of the planar surface opposite the sharp edge **120**, causes further recess relative to the skin surface contour A. The cutting blade **110** is fixedly anchored at a flexible spring **170**. Due to the manner in which the cutting blade **110** is flexing in FIG. **7** the need for a deep void **160** is irrelevant as the cutting blade **110** is not flexing or bending towards the outer comb **140**. It can be seen in FIG. **7** that the margin indicated by L is greatly reduced when engaging in a second position with an opposing force. Being that the cutting blade **110** in this example is allowed flexibility in a different manner when compared to FIG. **2** and FIG. **4** the position of the base **200** is not relevant in terms of determining a level of friction between sharp edge **120** of the cutting blade **110** and a skin surface contour. Furthermore, as illustrated in FIG. **1-6** a margin or gap represented by G in FIG. **7** is the equal to or less than the margin represented by J.

[0114] A FIG. **8** is an angled elevated view of the razor blade whereby the comb portion is end up. As illustrated in FIG. **8** the safety razor **100** is in an upright position.

[0115] FIG. **9** is an elevated cut-away view of the apparatus as seen in FIG. **8** illustrating the comb, cutting blade and inner guard assembly.

[0116] FIG. **10** is an eye-level view of the apparatus of the present inventions illustrating the comb, cutting blade and inner guard with like reference numerals according to any of the first through fourth embodiments of FIGS. **1-7**.

[0117] FIG. **11** is an elevated angled view of the present inventions whereby the inner guard **130** is end up and apparatus is up-side down with like reference numerals according to any of the first through fourth embodiments of FIGS. **1-7**. As illustrated in FIG. **11** the safety razor **100** is in an upside-down position wherein the inner guard **130** is upright.

[0118] FIG. **12** is an elevated angled up-side down view of the present inventions that illustrates a plurality of safety razors **100** assembled together as one apparatus with like reference numerals according to any of the first through seventh embodiments. As illustrated in FIG. **12** are redundant safety razors **100** creating a dual-blade structure.

[0119] FIG. **13** is a side view the elongated handle **260** by which the safety razor **100** attaches on

the upper end **290** in order to reach and shave areas of the body. As illustrated in FIG. **13** a safety razor **100** may attach to an elongated handle **260** which has an upper end **290** as well as a lower end **300** and a receiving end **320**. Using the elongated handle **260** with attached safety razor **100** allows for access to desired shaving areas that may be hard-to-reach or prove difficult access.

[0120] FIG. **14** is a side close up view of the upper end **290** of the handle whereby the safety razor **100** attaches. As seen from FIG. **14** upper end **290** or a portion thereof of receiving end **320** may be made from a material such as rubber or another flexible material that would allow the cutting blade **110** to pivot which would prove beneficial during the shaving process. A handle at the upper end **290** comprises a flexible coupling **350** coupled to the safety razor **100**. Furthermore, a flexible coupling **350** proves beneficial when a user to have flexibility in their shaving stroke in order to navigate bumps or contour angles that can otherwise prove difficult.

[0121] FIG. **15** is an elevated angled view illustrated a palm-fitted handle **270** shaped to conform to the shape of an individuals' hand or palm. As illustrated in FIG. **15** is a palm-fitted handle **270** used to accommodate desired shaving areas that would benefit from the safety razor **100** but would not necessarily require an elongated handle **260** in order to access the desired shaving area. One example of this embodiment would be for individuals who wish to shave hair on their arms or legs in order to better display their tattoos. Because a safety razor **100** that is wider would prove more beneficial to shaving quickly a palm-fitted handle **270** would be much more accommodating versus a traditional shaving handle found in most markets.

[0122] FIG. **16** is an elevated angled view of the present inventions whereby the safety razor **100** is attached to handle **280** most commonly used in with traditional shaving razor blades that are used to shave one's face. As illustrated in FIG. **16** is a safety razor **100** is attached to a traditional shaving handle **280** to allow access to areas whereby such handle **280** may prove useful such as one's neckline. The present invention illustrated in FIG. **1** creates such a soft friction between sharp edge **120** of cutting blade **110** and a skin surface which would not be the most desirable for accomplishing a clean close shave on one's face. FIG. **1** is most beneficial for areas of the body wherein hair may exist to be less dense in population as it strives to reduce the level at which hair is cut while still disallowing stubble. However, the closer the base **200** is positioned to the sharp edge **120** the more rigid the cutting blade **110** becomes and the easier the shaving operation becomes when attempting to shave areas consisting of more dense population of hair such as one's face.

[0123] FIG. **17** is and front elevated view of the razor blade illustrating the web covering **340** existing between each tooth in order to conceal shorn hair from view. The illustration of FIG. **17** can apply to any of the first through fourth embodiments of FIGS. **1-7**. As previously mentioned and illustrated in FIG. **17** the inner guard **130** in a separate embodiment may embody a comb or teeth near the side wherein the inner guard edge **180** is positioned. That being said, the web covering **340** embodied in-between each tooth can be implemented between the teeth embodied within the elongated side H of the inner guard **130** as well as the elongated side of the outer comb **140**. The web covering **340** acts much like an umbrella overhang covering between each tooth in order to conceal any shorn hairs from the public viewing. Being that the current invention embodies a deep void **160** there poses a risk of shorn hairs getting clogged over time. Though most shorn hairs will past through the safety razor **100** there is a small percentage that may still get stuck or clogged within the deep void **160**. Too often users of safety razors dispose far too quickly disposable razors that are esthetically unappealing due to a build-up of shorn hairs. The web covering **340** acts to conceal any unappealing shorn hairs that cannot get brushed out or unclogged.

[0124] FIG. **18** is a view of an individual utilizing the safety razor **100** by method of an elongated handle **260**. As illustrated in FIG. **18** is an individual gripping the lower end **300** of the elongated handle **260** and utilizing the elongated handle **260** attached to a safety razor **100** and shaving the back side which often proves difficult in gaining appropriate access. Although the illustration of FIG. **18** illustrates the first embodiment of FIGS. **1-2**, FIG. **18** can apply to any of the first through fourth embodiments of FIGS. **1-7**.

[0125] FIG. 19 is a close up view of the safety razor 100 cutting hair along the back side of an individual. As illustrated in FIG. 19 is a close-up view of the safety razor 100 illustration of FIG. 18. Illustrated is the safety razor 100 shaving hair and cutting blade 110 flexing in a second position C according to the cutting action illustrated by FIG. 2 for the first embodiment. Furthermore, shorn hairs may pass through the outer teeth tips 150 and exit the safety razor 100 versus getting clogged or caught in the deep void 160. Though some hairs may get clogged or caught the web covering 340 covers visible exposure.

[0126] As previously indicated, FIG. 19 is a close-up view of the safety razor 100 as seen in FIG. 18 and illustrates the first embodiment illustrated in FIGS. 1-2. The skin surface contour has a convex skin surface contour between a pair of skin indents respectively created between both the outer comb 140 and the inner guard 130. When both the inside edge 190 of the outer comb 140 and the inner guard edge 180 of the inner guard 130 press into the skin, the recessed sharp edge 120 moves relatively closer towards the skin surface contour of the skin when cutting the hair.

[0127] The cutting blade 110 is at an angle nearly parallel to both the outer comb 140 and the inner guard 130 in embodiments. The cutting blade 110 of embodiments longitudinally bends in a direction of uncut hairs when the safety razor 100 is moved across the skin surface. The sharp edge of the cutting blade can longitudinally bend to cause further recess relative to the skin surface contour. The sharp edge of the cutting blade can longitudinally bend to cause further recess relative to the skin surface contour. This bend is in a direction less perpendicular to the skin surface. In embodiments of the present inventions, the cutting blade 110 in the safety razor 100 performs less rigidly against the skin surface and hair than in most prior razors. The deeper the void, the more the blade is cantilevered and the less rigid is its flexibility. Alternately, with a springier cutting blade 110 material or an inner spring, the blade has more flexibility. Such contributes to enhanced performance on dry conditions knowing that the closest shave is not a highest priority on certain skin such as self-shaving the skin surface of ones back with a long handle 280 and no mirror.

[0128] A user of the safety razor 100 of embodiments can adjust how far the sharp edge 120 digs into the user's skin by varying the pressure of the safety razor 100 thereby adjusting how far the cutting blade 110 longitudinally bends. This may in some embodiments adjust the relative blade recess depth from the skin. These embodiments can be one mechanism for a user who feels adverse cutting feedback to adjust the blade recess by altering the pressure during the movement stroke. In other embodiments the cutting blade may be configured so altering speed or intensity of the movement stroke adjusts the blade recess.

[0129] FIG. 20 illustrates a side view of a safety razor 100 with an elongated handle 260 which embodies an upper end 290 and a lower end 300. As illustrated in FIG. 20 an elongated handle 260 can accept a shaving soap sponge 330 at a receiving end 320 near an upper end 290 opposite a lower end 300 and can easily be attached and removed in the same way the safety razor 100 can be easily attached and removed if an individual should decide to use the safety razor 100 in the shower which is commonly referred to as "wet shaving".

[0130] The term "flexible", as described previously in the first and second embodiment, is intended to describe the amount of bending or curved margin D the cutting blade 110 is granted in response to normal human opposing shaving forces. The "flexibility" of the cutting blade 110 in the first embodiment of FIGS. 1 and 2 is greater than the flexibility exhibited in the second embodiment or FIGS. 3 and 4. The term "flexible" takes on a different interpretation in the fourth embodiment wherein the flexible spring 170 is "flexed" allowing the cutting blade 110 to retract or flex horizontally and away from skin surface contour A.

[0131] A low friction between sharp edge 120 and a skin surface is illustrated in the first through the fourth embodiments illustrated in FIGS. 1-7 of the present inventions wherein a cutting blade 110 capable of less coarse hair found on an individual's back or arms at a depth allowing a smooth surface and all while minimizing cutting, razor burn as well as minimizing pulling or tugging hair while absent of an application of shaving cream or a shaving gel. Though a stronger friction may be

allowed through the methods previously described, the preferred light or low friction is best practice when shaving one's back, buttock, arms or other areas that contain less dense areas of hair or areas that may be very sensitive to close shaving.

[0132] It is important to note in embodiments of the present inventions preferred cutting axis is a cutting axis between 20-50 degrees. An axis outside of 20-50 degrees, though may be accomplished, proves difficult when accessing petite skin surface areas whereby the risk of cutting or razor burn is greatly increased.

[0133] In further contrast to prior art the current invention does not require the razor blades to be exposed to water or shaving cream in order to offer a clean and close shave or to protect from cutting, nicking or skin irritation. This is a very important factor of the present inventions since application of shaving cream or lubricant can be extremely time consuming especially when applying to one's back side. Thus, not requiring the shaving cream lubricant is very time efficient. Furthermore, because the cutting blade **110** may be made from stainless steel the invention allows the safety razor **100** to last longer without any rusting since water and shaving cream, which will cause erosion or rust, is not necessary.

[0134] The preferred distance of separation between the inner guard edge **180** and the sharp edge **120** is a preferable margin of about 0.030 inches (about 0.0762 centimeter). The preferred distance of separation between the sharp edge **120** and the outer comb **140** inside edge **190** is about 0.032 inches (about 0.08128 centimeter). The preferred thickness of inner guard **130** is about 0.024 inches (about 0.06096 centimeter) or less. The preferred thickness of outer teeth tips **150** is about 0.026 inches (about 0.06604 centimeter) or less. The preferred cutting blade **110** exposure is about 0.030 inches (about 0.0762 centimeter) or less. Although the shaving geometry can be accomplished outside of these measurements these are preferred.

[0135] The present inventions relate to a safety razors themselves or safety razors with elongated handles of the type that allow a user to, with force applied, creates, in some embodiments forces along the handle with the skin and, in other embodiments, creates indentations into the skin and more particularly, in some further embodiments, may relate to a safety razor and elongated handle granting a user a source of communication known as "two-point discrimination" with regards to the location and angle of safety razor while simultaneously granting effective navigation over challenging muscular and skeletal terrain on the backside and body.

[0136] FIG. **21** illustrates a side view of an elongated back shaver handle **315** and a safety razor **105** removably attaching to the elongated handle **315** according to embodiments of the present inventions. The elongated handle **315** is generally an s-shaped elongated member **315** having a surface along a length of the elongated handle **315** defining an inner side **485**, an outer side **475**, a blade end **325** and a grip end **355** and the blade end **325** opposite the grip end **355** and the said outer side **475** opposite the inner side **485** and having a finger surface grip **395** located on the inner side **485** of the elongated handle **315**. The inner side **485**, the outer side **475**, the blade end **325**, and the grip end **355** join one another to create an outside surface of the elongated member **315** that is substantially smooth and a cross-sectional shape of the elongated member **315** near the midway is substantially smooth having a shape that is substantially round or oval and a handle attachment **295** at the blade end **325** of the elongated member **315** opposite the grip end **355** and the handle attachment **295** located on the inner side **485** of the elongated handle member **315** and the blade end **325** comprises a handle clip **365** used to lock and release the safety razor **105** in the handle attachment **295**.

[0137] The handle attachment **295** removably attaches the safety razor **105** for tactile feedback to a blade attachment of the elongated handle **315**. The safety razor **105** has at least a blade group **265** protruding away from a substrate structure **215** of the safety razor **105** located on the inner side **485** of the elongated handle **315** facing against the torso backside of the user or in FIG. **21** facing against a flat skin surface plane referenced as plane A. It should be noted that when discussing the torso the breast tissue is not considered part of the torso. FIG. **21** illustrates the blade group **265**

and a support **275** which, in FIG. **21**, the support **275** takes the form of a secondary blade group. The blade group **265** and support **275** are protruding at an angle away from a front surface **375** of the safety razor **105**. In order to illustrate the difference in angle between the front surface of the substrate structure **215** in relation to the top side **595** of the blade group **265** or support **275** the front surface, in FIG. **21**, is with a dashed line. A substrate structure **215** adapts the tip or top side **595** of the blade group **265** or the top side **595** of the support **275** at an angle of about 75 degrees or less in relation to the front surface **375** of the substrate structure **215**. A preferred angle between the top side **595** of the blade group **265** and the front surface **375** of the substrate structure **215** is about 20 degrees. Another way to measure this angle is by comparing the angle of a midpoint of a portion of a non-flexing sharp blade **115** which is referenced as midpoint H, to the front surface **375** of a substrate structure **215** of the safety razor **105**. The midpoint H of a non-flexing portion of a sharp blade **115** is referenced as midpoint H which is illustrated in FIG. **21** with a dashed line. For the purpose of illustrating angle the front surface **375** of the substrate structure **215** is illustrated with a dashed line. The angle between the front surface **375** of the substrate structure **215** or the safety razor **105** in relation to the midpoint H is referenced as angle Y. Angle Y is 75 degrees or less. A preferred angle of angle Y is about 20 degrees. A similar angle that may be used is the angle between the midpoint H in relation to a flat skin plane A which is referenced as angle M. If the skin plane A is flat then angle M will be similar to angle Y.

[0138] The support **275** may take the form of a blade group or an alternative embodiment but having at least one blunt protrusion or bump sufficient for safely poking into the skin surface A. The support **275** may comprise more than one blunt protrusion wherein each blunt protrusion may be at staggered locations. In fact, in another alternate embodiment there may be three blunt protrusions **276** at staggered locations. As will be illustrated in the upcoming FIGS. **47** and **48** a support **275** may comprise a bump or blunt tip or blunt protrusion **276** as illustrated. The support **275** in further alternate embodiments, rather than another blade group or blunt protrusion **276**, the support **275** may take the form of a lubrication strip, soap, or an electric trimmer, wherein each may have a blunt protrusion **276** for safely poking. There may also be other items that may be removably attached to the substrate structure **215** which would prove a benefit to a user for the sake of other methods of pre or post shaving efforts.

[0139] The blade group **265** and the support **275** spaced a distance sufficient to achieve discrimination such as two-point discrimination on the flat skin plane A of a user and a tactile discrimination distance **285** between the blade group **265** and support **275**. A tactile discrimination distance **285** is any distance gap spaced inside of at least the blade group **265** and the support **275** and the tactile discrimination distance **285** may have a deep or shallow elevation which is referenced as elevation gap EE. The tactile discrimination distance **285** may be a tactile distance for two-point discrimination. The distance of the tactile discrimination distance **285** between the blade group **265** and the support **275** may vary on the area of the body that is going to be shaved. For instance, when shaving on the back area a preferred tactile discrimination distance for the human torso between the two points between the blade group **265** blunt tip and the support **275** blunt tip is about 35 millimeters or more. It should be noted that when discussing the torso the breast tissue is not considered part of the torso. The back side human skin surface is among the least sensitive portions of the human body and needs a longer tactile discrimination distance of about 39 millimeters. These 35 millimeter and 39 millimeter tactile discrimination distances are derived from the data cited in Myles and Binseel, 2007 referencing Weinstein, 1968. The tactile discrimination distance **285** allows balance and stability of the safety razor **105** for two-point discrimination when stroking against the skin surface A. Two-point discrimination, which will be further illustrated and discussed in FIG. **30** and FIGS. **32-33**, describes the distance between the tip of the blade group **265** and the support **275** are about 35 millimeters on the human torso in order for the tactile two-point discrimination to be effective. It is for this reason that about 35 millimeters has been chosen as the preferred distance inside the blade group **265** tip and the support **275** tip.

Tactile discrimination distance **285** also grants space for a tightened skin to convex to enter inside of the tactile discrimination distance **285** and inside of the elevation **EE** without rubbing against the front surface **375** of substrate structure **215** while tip of the blade group **265** and support **275** allowing a user to maintain an effective angle between the blade group **265** and support **275** and the skin surface **A** without difficulty. The tactile discrimination distance **285** also creates an effective amount of distance between the blade group **265** and the support **275** in order to allow two-point discrimination to occur which will be further illustrated and described in the upcoming FIG. **30** and FIGS. **32-33**.

[0140] A body leverage surface **495** is located on the outer side **475** of the elongated member **315** near a midway between the blade end **325** and the grip **395** and the blade end **325** configured to press the body leverage surface **495** against a user's forearm when the grip **395** is respectively gripped by fingers and hand by a same arm of the user located on the inner side **485** of the elongated handle member **315** and a thumb of the hand facing away from the blade end **325** of the elongated member **315** while the long handle **315** is reaching the blade end **325** under an armpit of the same arm of the user to leverage the handle attachment **295** located on the inner side **485** of the elongated handle **315** against a torso backside of the user. This will be further illustrated in the upcoming FIGS. **27-37**. It should be noted that when discussing the torso the breast tissue is not considered part of the torso.

[0141] The safety razor **105** for point discrimination is highly dependent on creating safe pokes or gouges into the skin surface **A** in order to create indentations that allow a skin convex to form inside of inner guard and outer comb belonging to the blade group **265** or the support **275** which may also take the form of a blade group as seen here in FIG. **21**. In FIG. **21** the blade group **265** and support **275** are only making initial contact with the skin surface **A** and are simply touching the skin surface **A** and are not safely poking into the skin surface **A** to establish point discrimination. It can be seen in FIG. **21** the midpoint **H** of a non-flexed portion of the sharp blade **115** is in a straight line. It will be seen in the upcoming FIGS. **29-31**, FIGS. **42-44** that when the blade group **265** is pressing into the skin surface **A**, a midpoint of a flexing sharp blade **115** will be directed at an alternative angle in relation to the front surface **375** of the substrate structure **215** when compared to the midpoint **H**. A safety razor **105** removably connecting to the elongated handle **315** is circled in FIG. **21** in order to illustrate the area that will have a close up view in the upcoming fifth illustration in FIG. **25**.

[0142] Letter designations in the drawings depict certain planes, gap distances and contours, defined throughout, and for convenience are summarily defined wherein: [0143] “**A**” references a flat skin plane surface; [0144] “**H**” references the midpoint section of a non-flexing sharp blade **115**; [0145] “**Y**” references the angle between the front surface **375** of a substrate structure **215** or safety razor **105** in relation to the midpoint **H** is referenced as angle **Y**; [0146] “**M**” references the angle between midpoint **H** in relation to a flat skin plane **A** which is referenced as angle **M**; and [0147] “**EE**” is an elevation gap inside a blade group **265** and a support **275**.

[0148] FIG. **22** illustrates a front view of a back shaver handle **315** having a surface along a length of the elongated handle member **315** having a handle clip **365** and the elongated handle **315** defining a left handle side **525**, a right handle side **535**, an inner side **485**, an outer side **475**, and a blade end **325** wherein the left handle side **525** is opposite the right handle side **535** and the inner side **485** is opposite the outer side **475** and the blade end **325** between the left handle side **525** and right handle side **535**. Although the safety razor **105** is illustrated in FIG. **22** as removably attaching to the elongated handle **315**, the safety razor **105** is not included when referencing the left handle side **525** and the right handle side **535** of the elongated handle **315**. The safety razor **105** having a left side of safety razor **505** and a safety razor right side **515** and a top side **335** wherein the left side of safety razor **505** is opposite the safety razor right side **515**. The elongated handle **315** having an opening **565** allowing a user access the safety razor **105** in order to clean the safety razor **105** without having to remove the safety razor **105** from elongated handle **315** after performing shaving

strokes. Often times hair will get caught or stuck inside of safety razors. Safety razors such as the one presented within require a cleaning brush to stroke the outer comb or even inner guard in order to thoroughly and effectively clean most of the shorn hairs out of the safety razor **105**. Thus, an opening in the elongated handle **315** near the blade end **325** would prove beneficial in allowing a user to save time and effort and keep the safety razor **105** for tactile feedback removably attaching to the elongated handle **315** when performing a cleaning.

[0149] FIG. **23** illustrates a front view of an inner side **485** of an elongated back shaver handle **315** near the blade end **325** wherein said handle **315** is removably attaching to a safety razor **105** for tactile feedback wherein the elongated handle **315** having a left handle side **525** and a right handle side **535** and a blade end **325** and wherein the left handle side **525** is opposite the right handle side **535**. The elongated handle **315** having an opening **565** allowing a user access to clean the safety razor **105** after performing shaving strokes. The elongated handle **315** having a handle clip **365** which is inside the opening **565** allowing the user to press the handle clip **365** in order to allow the safety razor **105** to remove itself from the elongated handle **315**.

[0150] The safety razor **105** for two point discrimination having a top side **335** a bottom side **345** and a safety razor left side **505** and a safety razor right side **515** wherein the top side **335** is opposite the bottom side **345** and the safety razor left side **505** is opposite the safety razor right side **515**. A front surface **375** of a substrate structure **215** of the safety razor **105** is illustrated wherein the substrate structure **215** is removably attaching with a blade group **265** and a support **275** and the support **275**, in FIG. **23**, is taking the form of a secondary blade group. In FIG. **23** the blade group **265** and the support **275** both have an outer comb **145** and an inner guard **135** and a sharp blade **115** inside of the outer comb **145** and the inner guard **135**. In another embodiment there may be multiple inner guards **135** and the sharp blade **115** inside of said multiple inner guards **135**. It can be seen that a tactile discrimination distance **285**, which was earlier explained as a gap for two point discrimination, is illustrated inside of a tip of both the blade group **265** and the support **275**. Furthermore, even though in FIG. **23** the support **275** is closer to the top side **335** of the safety razor **105** it should be known that in an alternative embodiment the support **275** and the blade group **265** may switch positions wherein the blade group **265** is closer to the top side **335** of the safety razor **105** and inside the top side **335** and the support **275**.

[0151] FIG. **24** illustrates a rear view of a back shaver handle **315** having a surface along a length of the elongated member **315** defining a left handle side **5** and a right handle side **535** a blade end **325** and a grip end **355** and the left handle side **525** opposite the right handle side **535** and the grip end **355** opposite the blade end **325** and between the left handle side **525** and right handle side **535**. A safety razor **105** is not included when referencing the left handle side **525** and the right handle side **535** of the elongated handle **315**. The elongated member **315** having a surface along a length of the elongated handle **315** defining an inner side **485** and an outer side **475** wherein the inner side **485** is opposite the outer side **475** and a having a finger surface grip **395** located on the inner side **485** of the elongated handle **315** and wherein the inner side **485**, the outer side **475**, the blade end **325**, and the grip end **355** join one another to create an outside surface of the elongated back shaver handle **315**. The elongated back shaver handle **315** removably attaching to a safety razor **105** for tactile feedback and the safety razor **105** having a front surface **375**, a rear surface **385**, a safety razor left side **505**, a safety razor right side **515** wherein the front surface **375** is opposite the rear surface **385** and the safety razor left side **505** is opposite the safety razor right side **515**. A blade group **265** is extending from the front surface **375** of the safety razor **105**. The elongated handle **315** having an opening **565** allowing a user access to clean the safety razor **105** after performing shaving strokes. Finally, a body leverage surface **495** is illustrated midway the grip **395** and the blade end **325** on the outer side **475** of the elongated handle **315**.

[0152] FIG. **25** illustrates an up-close side view of a portion of the previously illustrated and circled elongated handle **315** removably attaching to the safety razor **105** for tactile feedback along the skin surface plane A in the prior FIG. **21**. The safety razor **105** has a blade group **265** and a support

275 according to embodiments of the present inventions. The elongated handle 315 having a blade end 325. In FIG. 25 a substrate structure 215 adapted to hold both the blade group 265 and the support 275 the on a front surface 375 of the substrate structure 215 with the blade group 265 and the support 275 spaced a tactile discrimination distance sufficiently wide enough to achieve tactile feedback felt through a torso region of the skin of the user perceived between the blade group 265 and the support 275 and wherein the substrate structure 215 is adapted such that no elements within the tactile distance produce a tactile sensation on the skin surface A. It should be noted that when discussing the torso the breast tissue is not considered part of the torso. Two-point discrimination, which will be further illustrated and discussed in FIG. 30 and FIGS. 32-33, describes the distance between the tip of the blade group 265 and the support 275 are about 35 millimeters on the torso in order for the tactile two-point discrimination to be effective. It is for this reason that about 35 millimeters has been chosen as the preferred distance inside the blade group 265 tip and the support 275 tip. The substrate structure 215 is adapted to hold both the blade group 265 and the support 275 a distance measured from a leading edge of the blade group 265 to a trailing edge of the support 275 of a minimum of at least 1.59 millimeters.

[0153] The substrate structure 215 is further adapted to additionally provide a tactile discrimination distance between the blade group 265 and the support 275 spaced sufficiently wide enough to achieve point discrimination tactile feedback felt on the skin of the user between the blade group 265 and the support 275. The blade group 265 and the support 275 each extend from the front surface 375 of the substrate structure 215 at a height X or elevation EE sufficient to avoid loose skin of the user touching the front surface 375 of the substrate structure 215 within the tactile discrimination distance spaced between the blade group 265 and the support 275 and loss of point discrimination. In FIG. 25 a support 275 comprises another blade group comprising another sharp blade 115 and another guard 135 parallel to the another sharp blade 115. The substrate structure 215 is adapted with the blade group 265 and the support 275 are also spaced a tactile discrimination distance sufficiently wide enough to achieve point discrimination tactile feedback felt through on a backside torso region of the skin of the user perceived between the blade group 265 and the support 275. It should be noted that when discussing the torso the breast tissue is not considered part of the torso. Each of the different blade groups may have different angles in relation to the substrate structure 215. In another embodiment a plurality of blade groups 265 arranged in parallel rows on a front surface 375 of the substrate structure 215, each of the blade groups 265 spaced a distance there between, each of the blade groups 265. The blade group 265 and the support 275 are spaced a tactile leverage feedback distance sufficiently wide enough to provide leverage feedback felt through the elongated back shaver handle 315 for the user to maintain a consistent angle of the sharp blade 115 relative to the skin surface when an arm of the user reaches the elongated back shaver handle 315 to the user's backside during shaving movement over a shoulder blade peak or a spine depression.

[0154] The safety razor 105 in FIG. 25 is removably attached by a handle attachment 295 and a handle clip 365 configured to allow a user to press in order to grant the handle attachment 295 to remove itself from the elongated handle 315. The handle attachment 295 may remove itself by sliding out of the elongated handle 315. In another embodiment the handle attachment 295 may be embodied on the elongated handle 315 wherein the safety razor 105 accepts the handle attachment 295 of the elongated handle 315. The safety razor 105 having a rear surface 385, a front surface, a top side 335 and a bottom side 345 wherein the rear surface 385 is opposite the front surface 375 and the top side 335 is opposite the bottom side 345.

[0155] The support 275 in FIG. 25 takes the form a blade group and the blade group 265 and the support 275 both comprising a sharp blade 115 with a sharp edge 125 and an inner guard 135 parallel to the sharp blade 115 on a trailing side of the sharp blade 115 opposite an outer comb 145 wherein the outer comb 145 parallel to the sharp blade 115 on a leading side of the sharp blade 115 and a substrate structure 215 adapted to hold a blade group 265 and the support 275 on the front

surface **375** opposite the rear surface **385** of the substrate structure **215** with the blade group **265** and support **275** spaced a distance sufficient to achieve point discrimination on the skin of a user between the blade group **265** and support **275**. The inner guard **135** having an outer edge **185** and a trailing opening **J** wherein the trailing opening **J** is inside of the outer edge **185** and the sharp edge **125** of the sharp blade **115**. The outer comb **145** having an inside edge **195** and a leading opening **G** wherein the leading opening **G** is inside of the inside edge **195** and the sharp edge **125** of the sharp blade **115**. A suppleness distance is measured between the inside edge **195** of the outer comb **145** and the outer edge **185** of the inner guard **135** of the blade group **265**. The suppleness distance is narrower than tactile discrimination distance **285** spaced between the blade group **265** and support **275**, which said support **275** is a blade group in FIG. 25.

[0156] The substrate structure **215** adapted to hold the blade group **265** and a support **275** on the front surface **375** of the substrate structure **215** with the blade group **265** and the support **275** spaced a distance sufficient to achieve two-point discrimination on the skin **A** of a user between the blade group **265** and the support **275** and the support **275** and the blade group **265** extend from the front surface **375** of the substrate structure **215** of the safety razor **105** at a height **X** or elevation **EE** sufficient to avoid loose skin of the user touching and rubbing the front surface **375** of the substrate structure **215** which would interfere with a shaving stroke. This loose skin is more clearly illustrated in upcoming FIG. 30 as a skin convex **CC** inside blade group **265** and support **275**. In FIG. 25 the front surface **375** of the substrate structure **215** comprising one or more grooves parallel from each other and adapted to removably hold at least one blade group **265** and support **275**. The front surface **375** of the substrate structure **215** further comprises a second groove **675** adapted to removably hold the support **275** inserted therein and configured parallel to the first groove **305** spaced the tactile leverage distance sufficiently wide enough to provide the tactile leverage feedback felt through the elongated back shaver handle **315** for the user to maintain the consistent angle of the sharp blade **115** relative to the skin surface **A** when an arm of the user reaches the elongated back shaver handle **315** to a backside of the user during shaving movement over a shoulder blade peak or a spine depression on the backside.

[0157] In FIG. 25 there is a first groove **305** and a secondary groove **675**. Both groove **305** and the secondary groove **675** will be more clearly illustrated in the upcoming FIGS. 47-48. The grooves allow a user an option to choose a preferred distance for two point discrimination between the blade group **265** and the support **275** which will be further illustrated in the upcoming FIGS. 45-46. The blade group **265** and the support **275** may attach to a groove by method of a clip **175** with a spring or a snap-lock by inserting the blade group **265** or support **275** into a groove from the front surface **375** of the substrate structure **215** until the clip **175** snaps into place. It is commonly known there are many alternative methods in which holding and securing the blade group **265** and the support **275** which would also suffice. In another embodiment the handle attachment **295** designed to removably attach and temporarily hold the safety razor **105** may be embodied on or near the top side **335** or bottom side **345** of a safety razor **105**. In one embodiment the blade group **265** or support **275** may slide into a groove **305** or a secondary groove **675** from the left attachment side **545** or the right attachment side **555** of the safety razor **105** as will be illustrated in the upcoming FIG. 58. In FIG. 25 the first groove **305** and secondary groove **675** are illustrated. First groove **305** is removably holding the blade group **265** while secondary groove **675** is removably holding the support **275**. Grooves allow a user an option to choose a distance between the blade group **265** and the support **275**.

[0158] The substrate structure **215** adapts the tip or a top side **595** of the blade group **265** or support **275** at an angle of about 75 degrees or less in relation to the front surface **375** of the substrate structure **215**. A preferred angle between the top side **595** of the blade group **265** in relation to the front surface **375** of the substrate structure **215** is 20 degrees.

[0159] The support **275** may take the form of a blade group or an alternative embodiment having a least one blunt protrusion **276** sufficient for safely poking into the skin surface **A**. The support **275**

may comprise more than one blunt protrusion **276** wherein each blunt protrusion may be at staggered locations. As will be illustrated in the upcoming FIGS. **47-48** a support **275** may comprise a bunt tip or bump or blunt protrusion being a soap strip, a lubrication strip, or an electric trimmer each having a blunt protrusion.

[0160] A tactile discrimination distance **285** is a gap spaced inside of at least the blade group **265** and the support **275** and sufficiently spaced for two-point discrimination. The tactile discrimination distance **285** may have an elevation gap EE which may be a deep or shallow gap. The elevational gap EE is inside the blade group **265** and support **275** as well as inside of the tactile discrimination distance **285** and the front surface **375** of the safety razor **105**. When shaving the back the substrate structure **215** holds the blade group **265** and the support **275** spaced the tactile discrimination distance greater than about 35 millimeters. However, other more sensitive areas of the body may require less distance. The tactile discrimination distance **285** allows balance and stability of the substrate structure **215** when stroking against the skin surface A. The tactile discrimination distance **285** also grants space for a tightened skin to convex to enter inside of the tactile discrimination distance **285** without rubbing against the front surface **375** of the substrate structure **215** while allowing a user to maintain an effective angle between the blade group **265** and the support **275** and the skin surface A without difficulty. The tactile discrimination distance **285** also creates an effective amount of distance between the blade group **265** and support **275** in order to allow point discrimination to occur. The elevation gap EE, which in FIG. **25** is illustration with dashed lines, allows a skin convex to enter when the safety razor **105** for point discrimination is pressing into the skin surface A.

[0161] The height from tips of each of the blade group **265** and the support **275** to the front surface **375** of the substrate structure **215** is referenced as height X and is 3.81 mm or more in order to avoid the loose skin of the user touching the front surface **375** of the substrate structure **215**. In a preferred embodiment height X is about 3.81 mm and wherein the substrate structure **215** holds the blade group **265** and the support **275** spaced a tactile discrimination distance about 35 millimeters or greater. However, other more sensitive areas of the body may require less distance. Both the blade group **265** and the support **275** have the top side **595** and bottom side **605** which is opposite the top side **595**. A midpoint of a non-flexing portion of a sharp blade **115** referenced as midpoint H may be between about 0-75 degrees in relation to the front surface **375** of the substrate structure **215**. A preferred angle from the tip or the top side **595** of the blade group **265** in relation to the front surface **375** of the substrate structure **215** is about 20 degrees. In FIG. **25** the safety razor **105** for two-point discrimination is shown prior to gouging and indenting into the skin surface A while the opposite side view of this embodiment being identical according to a first embodiment of the present inventions. In FIG. **25** the support **275** comprises another blade group **265** comprising another sharp blade **115** having another leading side and another trailing side for shaving the hair and another outer comb **145** next to and parallel to the another leading side of the another sharp blade **115** and another inner guard **135** next to and parallel to the another trailing side of the another sharp blade **115**.

[0162] The front surface **375** of the substrate structure **215** is represented by a dashed line in order to clearly illustrate angle Y. Y represents the angle between the front surface **375** in relation to the midpoint H of a portion of a non-flexing sharp blade **115**. The angle between the midpoint H in relation to the flat skin plane A is angle M. Angle M may also be between about 0-75 degrees in order for a safety razor **105** for two-point discrimination to shave a stroke properly and effectively. A preferred angle of the tip or the top side **595** of the blade group **265** in relation to the front surface **375** of the substrate structure **215** is about 20 degrees. Finally, a circle is illustrated around the cutting area of a blade group **265**. The circled area will be illustrated in a close-up schematic cross-sectional view in the upcoming FIG. **26**.

[0163] The safety razor **105** for tactile feedback is highly dependent on creating safe pokes or gouges into the skin surface A in order to create indentations that allow a first skin convex to form

inside of the inner guard **135** and outer comb **145** and a second skin convex inside the tactile discrimination distance **285**. In FIG. **25** the outer edge **185** and the outer teeth inside edge **195** make initial contact with the skin surface A. At this point the inner guard **135** and outer comb **145** are simply touching the skin surface A and are not gouging into skin surface A. Finally, the support **275** and blade group **265** extend from the front surface **375** of the substrate structure **215** and creating a height X or EE which is the height inside of the tips of both the blade group **265** and the support **275** to the front surface **375** of the substrate structure **215**. Height X is about 3.81 millimeters or more. Height X or EE is sufficient to avoid loose skin of the user touching and rubbing the front surface **375** of the substrate structure **215** which would interfere with a shaving stroke. In alternative embodiments the handle attachment **295** may located on the elongated handle **315** or the safety razor **105** or both the elongated handle **315** and safety razor **105**. In FIG. **25** it can be seen that the safety razor **105** is removably attaching with the elongated handle **315** on the rear surface **385** of the safety razor **105**. In alternative embodiments the safety razor may removably attach with the elongated handle **315** at the top side **335**, the bottom side **345** or even the front surface **375** or a combination of them. Finally, the handle attachment **295** may have a spring allowing flexibility in the angle between the safety razor **105** and the elongated handle **315**. There is a relationship between the tactile discrimination distance **285** and the distance of height X as presented herein. It is desired to prevent the front surface **375** of the substrate structure **215** from rubbing against the skin surface A during a shaving stroke. That being said, the greater the tactile discrimination distance **285** the greater the dimension of height X. Just the same, when the lesser the tactile discrimination distance **285** the lesser the dimension of height X.

[0164] Letter designations in the drawings depict certain planes, gap distances and contours, defined throughout, and for convenience are summarily defined wherein: [0165] “X” references a height from tips of a blade group **265** and a support **275** to a front surface **375** of a substrate structure **215**; [0166] “J” references a trailing opening inside a sharp blade **115** and an outer edge **185** of inner guard **135**; [0167] “G” references a leading opening inside a sharp edge **125** of a sharp blade **115** and an inside edge **195** of an outer comb **145**; and [0168] “Y” represents an angle between front surface **375** in relation to a midpoint H portion of a non-flexing sharp blade **115**.

[0169] FIG. **26** illustrates a close up cross-sectional view of a blade group **265** which was circled in the prior FIG. **25** according to embodiments of the present inventions. The blade group **265** comprising at least one sharp blade **115** comprising a sharp edge **125** facing towards a skin surface A comprising an outer comb **145** comprising an inside edge **195**, a comb inside wall **645** inside of the sharp edge **125** and inside edge **195** and an inner guard **135** comprising an inner guard outer edge **185**, an inner guard inside end **235** and an inner guard inside wall **665** inside the outer edge **185** and the inner guard inside end **235**. The comb inside wall **645** is adjacent to the sharp blade **115** and is inside the inside edge **195** and the sharp edge **125** of the sharp blade **115**. Inner guard inside end **235** is embodied where the inner guard **135** and the sharp blade **115** meet. An inside portion of the outer comb **145** removed in order to create a deep void **165**. The sharp blade **115** is fixedly anchored on a sharp blade end **225** opposite the sharp edge **125** of sharp blade **115**. A suppleness distance is measured between the inside edge **195** of the outer comb **145** and the outer edge **185** of the inner guard **135** of the blade group **265**. Also the suppleness distance is narrower than tactile discrimination distance **285** spaced between the blade group **265** and support **275**, which said support **275** is a blade group in FIG. **26**. A base **205** is positioned to create a level of distance between the base **205** and the sharp edge **125** of the sharp blade **115** in order to enable a controlled level of flexibility with the sharp blade **115**. The deep void **165** is spaced intermediately of the outer comb **145** and sharp blade **115**. Deep void **165** thickness allowing a level of control over the flexibility of the sharp blade **115** as well as over-exposure of the sharp blade **115**. The thickness of the deep void **165** is represented as K. Thickness K is 1.016 millimeters or less. In a preferred embodiment distance thickness K is about 0.381 millimeters. Thickness K of deep void **165** may run thicker but the danger of enabling the sharp blade **115** to become like a dagger in

relation to the skin surface becomes increasingly probable. The level of distance of the deep void **165** between the base **205** and the sharp edge **125** of the sharp blade **115** is referenced as L. The distance L is about 4.572 millimeters or less. A preferred distance of distance L is about 2.032 or less. Distance L may be less or greater than the preferred distance. However, if the distance of distance L becomes much greater than 4.572 millimeters then the sharp blade **115** will start to bend too much and the sharp edge **125** of the sharp blade **115** will run the danger of not cutting effectively. It should be understood that comb inside wall **645** inside the sharp edge **125** and the inside edge creates a barrier for a skin surface convex to enter inside of inside edge **195** and outer edge **185** which will be illustrated in the upcoming FIG. **31**. The outer comb **145** having an outer wall **155** which in another embodiment may also be rounded with an arc instead of a straight wall. The midpoint of a portion of a non-flexing sharp blade **115** is referred to as midpoint H which is illustrated with a straight or flat dashed line. In FIG. **26** the inner guard **135** and outer comb **145** are not indenting into the skin surface A and thus the sharp blade **115** is not pressing against the skin surface A and the sharp blade **115** is not flexing.

[0170] As seen in FIG. **26** when viewing a close up cross-sectional view of the blade group **265** a portion of the inner guard **135** inside of the outer edge **185** and the sharp edge **125** is removed in order to create a trailing opening J inside of outer edge **185** and sharp edge **125** of the sharp blade. In FIG. **26** the trailing opening J is illustrated as with dashed triangle inside of the outer edge **185** of the inner guard **135** and the sharp edge **125** of the sharp blade **115**. In other alternate embodiments the dashed triangle may be a right triangle or an isosceles triangle or an isosceles right triangle. The trailing opening J cross sectional has three triangular corners or vertices which have three walls but it is not a perfect triangle being that the three walls or sides are not always flat. This is especially true of the sharp blade **115** and the skin surface A which both flex under pressure. The inner guard inside wall **665** of inner guard **135** creates a second wall or side. The inner guard inside wall **665** of the inner guard **135** does not need to be a straight wall but in another embodiment may be rounded with an arc. The skin surface A is the third and final wall or side which also deforms and will convex. The skin needs to deform inside the trailing opening J in order for the sharp blade **115** to access the base of a hair **415** which results in a shave that leaves a smooth skin surface after a shaving stroke. In FIG. **26** the first of the vertices is where the inner guard inside end **235** and the sharp blade **115** meet. The second of the vertices is where the sharp blade **115** and skin surface plane A intersect. The second vertex may also be where the sharp edge **125** of the sharp blade **115** and the skin surface plane A meet. The third of the vertices is where the skin surface A and the outer edge **185** of the inner guard **135** meet. The vertices work together to form the planes that create trailing opening J or void in order for the trailing opening J to allow for a sufficient opening or void for tightening skin to enter and convex inside of the blade group **265** which is illustrated in the upcoming FIGS. **29-31**. It should also be known that the inner guard inside wall **665** and the comb inside wall **645** controls the amount of skin convex allowed inside the blade group **265**. As will be illustrated in the upcoming FIGS. **29-31** a skin convex is referenced as T and the inner guard **135** outer edge **185** and the outer comb **145** inside edge **195** simultaneously dig into the skin surface A in order to tighten the skin so that when the hair is presented to the sharp blade **115** the root or base of the hair **415** is being greatly exposed. In FIG. **26**, a leading opening G is inside of inside edge **195** and the sharp edge **125** of the sharp blade **115**. The leading opening G allowing a sufficient opening in order for a skin convex to safely press against the sharp edge **125** of the sharp blade **115** when pressing the blade group **265** against the skin surface A. It can be seen in FIG. **26** the outer wall **155** of the outer comb **145** and the skin plane A create a vertex of a leading side imaginary triangle referenced as vertex O. Vertex O is created in order to allow the outer comb **145** to better indent into the skin surface A allowing the blade group **265** to shave properly and for better tactile feedback.

[0171] It can be seen that the sensors that require pressure in order to trigger such as the Pacinian Corpuscle **425** and the Ruffini's Corpuscle **435** are not yet being triggered since there is only light

touch between the blade group **265** and the skin surface A. Only the hairs **415** may detect the light touch. It can be seen in the illustration the tissue sub layers and the sensors within each layer which include the Epidermis **445**, the Dermis **455** and the Hypodermis **465**.

[0172] Letter designations in the drawings depict certain planes, gap distances and contours, defined throughout, and for convenience are summarily defined wherein: [0173] “L” references a deep void **165** running lengthwise from inside edge **195** of outer teeth **145** to a base **205** which allows ample space for the preferred flexibility of a sharp blade **115** to the inside of a outer comb **145**; [0174] “K” references a thickness of a deep void **165** between an outer comb **145** and a sharp blade **115** which is a contributing factor in the amount of allowed inverted skin convex T as well as the level of flexibility a sharp blade **115** illustrates against inverted skin convex T when shaving; and [0175] “O” references a void inside an outer wall **155** of an outer comb **145** and a flat skin surface plane A.

[0176] FIGS. **27-28** illustrate aerial views of a two-sided back shaver handle gripped by a user extended under the armpit towards the backside according to embodiments of the present inventions. The elongated handle **315** removably attaching to a safety razor **105** for tactile feedback and, in some embodiments, using leverage feedback, when gripped by a user extended under the armpit towards the backside according to embodiments of the present inventions. A handle attachment **295** on the safety razor **105** is coupled with the long handle **315** gripped by a user extended under the armpit towards the backside. The user feeling within the hand of the user on the grip **395** of the elongated handle **315** a leverage feedback from both the blade group **265** and the support **275** against the backside skin.

[0177] A substrate structure **215** is adapted to removably hold at least the blade group **265** and a support **275**. In FIGS. **27-28** a substrate structure **215** operatively coupled to the blade end **325** of the elongated back shaver handle **315**, wherein the substrate structure **215** is adapted to hold both the blade group **265** and the support **275** on a front surface **375** of the substrate structure **215** with the blade group **265** and the support **275** spaced a tactile leverage feedback distance sufficiently wide enough to provide leverage feedback felt through the elongated back shaver handle **315** for the user to maintain a consistent angle of the sharp blade relative to the skin surface when an arm of the user reaches the elongated back shaver handle **315** to a backside of the user during shaving movement over a shoulder blade peak or a spine depression on the backside. The blade group **265** and the support **275** each extend from the front surface **375** of the substrate structure **215** at least 0.381 centimeters to avoid loose skin of the user touching the front surface **375** of the substrate structure **215** within the distance spaced between the blade group **265** and the substrate structure **215**. In FIGS. **27-28** the support **275** comprises another blade group comprising another sharp blade **115** and another guard **135** parallel to another sharp blade **115**.

[0178] The front surface **375** of the substrate structure **215** further comprises a second groove **675** adapted to removably hold the support **275** inserted therein and configured parallel to the first groove **305** spaced the tactile leverage feedback distance sufficiently wide enough to provide the tactile leverage feedback felt through the elongated back shaver handle **315** for the user to maintain the consistent angle of the sharp blade **115** relative to the skin surface A when an arm of the user reaches the elongated back shaver handle **315** to a backside of the user during shaving movement over a shoulder blade peak or a spine depression on the backside. The substrate structure **215** is adapted with the blade group **265** and the support **275** are also spaced a tactile discrimination distance sufficiently wide enough to achieve tactile feedback tactile feedback felt through on a backside torso region of the skin of the user perceived between the blade group **265** and the support **275**. The support **275** comprises at least one blunt protrusion. The blade group **265** and the support **275** are spaced a tactile leverage feedback distance sufficiently wide enough to provide leverage feedback felt through the elongated back shaver handle **315** for the user to maintain a consistent angle of the sharp blade **115** relative to the skin surface when an arm of the user reaches the elongated back shaver handle **315** to the user's backside during shaving movement over a shoulder

blade peak or a spine depression.

[0179] The safety razor **105** in FIGS. **27-28** having a blade group **265** and a support **275** which in FIGS. **27-28** the support **275** takes the form of an additional blade group. In FIG. **25** the support **275** comprises another blade group **265** comprising another sharp blade **115** having another leading side and another trailing side for shaving the hair and another outer comb **145** next to and parallel to the another leading side of the another sharp blade **115** and another inner guard **135** next to and parallel to the another trailing side of the another sharp blade **115**. In FIGS. **27-28** the safety razor **105** attaches to the elongated handle **315**. The handle attachment **295** also attaches to the elongated handle **315**. The safety razor **105** has the blade group **265** and the support **275** attached on an inner side **485** of the back shaver handle **315** facing against the torso backside of the user. It should be noted that when discussing the torso the breast tissue is not considered part of the torso. The elongated handle **315** has a surface along a length of the elongated handle **315** defining the inner side **485** and an outer side **475** and a blade end **325** and a grip end **355** wherein the outer side **475** opposite the said inner side **485** and the blade end **325** opposite the grip end **355** and the elongated handle **315** having a finger surface grip **395** located on the inner side **485** of the elongated handle **315**. The handle attachment **295** is at the blade end **325** of the elongated handle **315**. The blade end **325** is located at an end of the elongated handle **315** opposite the grip end **355**. The handle attachment **295** is located on the inner side **485** of the elongated handle **315**. The handle attachment **295** comprises a handle clip **365** used to lock and release the safety razor **105** for tactile feedback in the elongated handle **315**. The handle attachment **295** attaches to the safety razor **105** with at least one blade group **265** and a support **275** protruding away from the safety razor **105** on the inner side **485** of the back shaver handle **315** facing against the torso backside of the user.

[0180] A body leverage surface **495** is located on the outer side **475** of the two-sided back shaver handle **315** near a midway between the grip **395** and the blade end **325** and the blade end **325** configured to press the body leverage surface **495** against a user's forearm when the grip **395** is respectively gripped by fingers and hand by a same arm of the user located on the inner side **485** of the back shaver handle **315** a thumb of the hand facing away from the blade end **325** of the s-shaped back shaver handle **315** and the elongated handle **315** is reaching the blade end **325** under an armpit of the same arm of the user to leverage the handle attachment **295** located on the inner side **485** of the elongated handle **315** against a torso backside of the user. It should be noted that when discussing the torso the breast tissue is not considered part of the torso. As seen in FIGS. **27-28** when the grip **395** is respectively gripped by fingers and hand by a same arm of the user the user is illustrated pressing the body leverage surface **495** located on the outer side **475** of the back shaver handle **315** near a midway between the grip **395** and the handle attachment **295** and configured to press the body leverage surface **495** against a user's forearm, in which the fulcrum is referenced as F, in order to leverage the handle attachment **295** located on the inner side **485** of the back shaver handle **315** against a torso backside of the user and leveraging the back shaver handle **315** using the body leverage surface **495** as a fulcrum F relative to the grip **395** to press the blade end **325** towards the torso backside of the user and stroking the blade end **325** against the torso backside of the user.

[0181] A portion of the safety razor **105** inside of the blade group **265** and support **275** is removed in order to create tactile discrimination distance **285**. A tactile discrimination distance **285** is inside of two supports at about 35 millimeters. The tactile discrimination distance **285** having an elevational gap EE that may be shallow or deep and the distance of the tactile discrimination distance **285** between the blade group **265** and support **275** may vary. The tactile discrimination distance **285** serves multiple purposes. The first purpose of the tactile discrimination distance **285** is chosen to allow a user to find an effective cutting angle between the blade group **265** and skin surface with ease. Also the tactile discrimination distance **285** separates the blade group **265** and the support **275** allowing them to stabilize one another when stroking against the skin surface. The tactile discrimination distance **285** can also create an effective amount of distance between the

blade group **265** and the support **275** in order to allow two-point discrimination which will be further discussed and illustrated in the upcoming FIG. **30** and FIGS. **32-33**. The tactile discrimination distance **285** also grants space for a skin convex to enter inside of the blade group **265** and the support **275** which is illustrated as skin convex CC in FIG. **8**. It can be seen in FIG. **8** that the tactile discrimination distance **285** is allowing skin convex CC to enter and preventing the skin convex CC from pressing against the front surface **375** of the safety razor **105** and interrupting the shaving process.

[0182] It can be seen in FIG. **27** a portion of the elongated handle **315** and the safety razor **105** is circled. The upcoming FIG. **29** will offer a close up illustration of the portion circled here in FIG. **27**. Furthermore, it can be seen in FIG. **28** a portion of the elongated handle **315** and the safety razor **105** is circled. The upcoming FIG. **30** will offer a close up illustration of the portion circled here in FIG. **28**. In FIGS. **27-28** the blade group **265** is pressing into the skin and is creating an indentation into the skin creating skin convex T inside the blade group **265**.

[0183] It can be seen in FIGS. **27-28** the grip **395** is respectively gripped by fingers and hand by a same arm of the user the user is illustrated pressing the body leverage surface **495** against a user's forearm, in which the fulcrum is referenced as F, in order to leverage the handle attachment **295** located on the inner side **485** of the back shaver handle **315** against a torso backside of the user and leveraging the back shaver handle **315** using the body leverage surface **495** as the fulcrum F relative to the grip **395** to press the blade end **325** which is opposite the grip end **355**, towards the torso backside of the user and stroking the blade end **325** against the torso backside of the user. It should be noted that when discussing the torso the breast tissue is not considered part of the torso. One difference when comparing FIG. **28** to FIG. **27** is that in FIG. **28** the support **275**, which takes the form of a secondary blade group, is now pressing into the skin and with force is creating a skin convex referred to as U along with the blade group **265** which is creating skin convex T. Since the blade group **265** and support **275** are pressing into the skin a skin convex CC is illustrated inside the blade group **265** and support **275**. In FIG. **28** both the blade group **265** and the support **275** are in position and through leverage feedback the user tactically feels leverage feedback through the handle and can feel that the safety razor **105** is at the correct angle according to one leverage feedback embodiment.

[0184] FIGS. **27-28** provide one embodiment for illustration of a tactile leverage feedback distance. When the tactile leverage feedback distance is sufficiently wide, leverage feedback felt by the user through the elongated back shaver handle for the user to maintain a consistent angle of the sharp blade relative to the skin surface when an arm of the user reaches the elongated back shaver handle to a backside of the user during shaving movement over a shoulder blade peak or a spine depression on the backside. As seen in FIG. **27** a user presses the blade group **265** into the user's own back. In order for the user to gain effective leverage feedback felt by the user through the elongated back shaver handle, the user must grasp and move the grip end **355** away from the front side of the user. As seen in FIG. **28**, in comparison with FIG. **27**, the user has moved the grip end **355** further away from the front side of the user and the user has pressed the support **275** into their back side. When the support **275** is pressed into the back side, the user feels this resistance in the handle **315**. The resistance is felt in the palm of the user's hand gripping the handle as well between the forearm of the user and the inner side **485** of the handle **315**. These feelings of resistance permit leverage feedback to communicate to the user that the safety razor **105** is positioned at a correct cutting angle. It is important to have the safety razor **105** at the correct cutting angle since the blade group **265** and support **275** are positioned at a distance and an angle from the front surface **375** of the substrate structure **215**.

[0185] To achieve the above-described leverage feedback felt through the elongated back shaver handle, the blade group and the support need to be spaced a tactile leverage feedback distance sufficiently wide. (Note as discussed elsewhere, the support can be a one or more blunt protrusions or bump shapes or the support can be one or more another blade groups.) This tactile leverage

feedback distance is between the blade group and the support is the distance measured from the forward most leading edge and the reward most trailing edge of the blade group and the support. An example illustration of the tactile leverage feedback distance **286** between the leading edge **195** of a leading blade group **265** and the trailing edge **185** of an adjacent trailing blade group **275** as a support will be illustrated in the upcoming FIGS. **29** and **30**. In one embodiment, the tactile leverage feedback distance measured as above described is at least about 1 inch or 25.4 mm separation. Thus the substrate structure in this one embodiment with the elongated handle would be adapted to hold one or more of blade groups and one or more of supports spaced the tactile leverage feedback distance of at least about 25.4 millimeters (or 1 inch equivalent) measured between outermost edges of a pair of outermost blade groups and supports of the substrate structure.

[0186] Note that the tactile discrimination distance sufficiently wide enough to achieve two-point discrimination is felt through by a user through the skin of the user, not through the handle to the hand of the user. Because the tactile discrimination distance is felt on the back skin, the tactile discrimination distance should be measured from different ends than the tactile leverage feedback distance. While the tactile leverage feedback distance is measured between the outermost edges of a plurality of blade groups or supports, the tactile discrimination distance is measured between the widest space between the inside edges of a pair of an adjacent blade group and support. This tactile discrimination distance is between an adjacent blade group and support is the distance measured from the trailing edge and the leading edge of the adjacent blade group and support. An example illustration of the tactile discrimination distance **285** between the trailing edge **185** of a leading blade group **265** and the leading edge **195** of an adjacent trailing blade group **275** as a support will be illustrated in the upcoming FIGS. **29** and **30**.

[0187] The straight line length of the elongated handle **315**, the height of the blade group **265** and support **275**, and the tactile leverage feedback distance work in relationship with one another. The elongated handle **315** has a straight line length measured directly from the blade end **325** to the grip end **355** of about 330 mm to about 457.2 mm. A preferred straight line length of the back shaver handle **315** is about 355.6 mm. This straight line length is measured across in a straight line from end to end, not following the curve of the elongated handle **315**. In order to create a leveled back shaver handle **315** with safety razor **105** in an alternate embodiment when the straight line length of the handle **315** is greater than 355.6 mm then the tactile leverage feedback distance **285** becomes greater. In this instance when the straight line length of the handle **315** is greater than 355.6 mm and a user is gripping the handle near the grip end **355**, the user will begin to lose leverage feedback which desires the tactile leverage feedback distance **285** to increase in order to maintain effective tactile feedback. Conversely, when the straight line length of the handle **315** is less than 355.6 mm then the tactile discrimination distance **285** may be less and still maintain tactile feedback for the user. Thus when a length of the elongated handle changes, the tactile discrimination distance **285** or tactile leverage feedback distance **286** needs to proportionately change.

[0188] To prevent skin from rubbing against or touching the front surface **375** of the substrate structure **215**, the height EE of the blade group **265** and support **275** relative to the substrate needs to be considered. The blade group and the support each extend from the front surface of the substrate structure at a height sufficient to avoid loose skin of the user touching the front surface of the substrate structure within the distance spaced between the blade group and the substrate structure. The tactile discrimination distance **285** or tactile leverage feedback distance **286** also comes into play here. When the tactile discrimination distance **285** or tactile leverage feedback distance **286** changes, the height the blade group and the support each extend from the front surface of the substrate structure needs to proportionately change. When the tactile discrimination distance **285** or tactile leverage feedback distance **286** increases, the height also needs to increase. Conversely, when the tactile discrimination distance **285** or tactile leverage feedback distance **286**

is less, the height EE may also be less. In one embodiment, for a flat substrate structure, the height X or elevation EE from tips of each of the blade group and the support to the front surface of the substrate structure is at least 0.381 centimeters.

[0189] In other embodiments, as described in the upcoming FIGS. 32-33, the substrate structure 215 is adapted with the blade group 265 and the support 275 also spaced a tactile discrimination distance 285 sufficiently wide enough to achieve two-point discrimination tactile feedback felt through on a backside torso region of the skin of the user perceived between the blade group 265 and the support 275.

[0190] The two-point discrimination study offers an understanding on how the components found within the sensory system may be utilized to establish effective communication through the sensory system without having to actually view the location where the senses are being activated, or in my invention, when the blade group 265 and support 275 are safely poking or gouging the skin on the backside or body. The two-point discrimination illustrates the ability to discern that two or more nearby objects gouging or poking the skin are truly multiple distinct points set apart from each other and allowing a user to understand the location of each point. It is often tested with points creating sufficient indents into the skin, as illustrated in my invention, in order to assure the communication is effective.

[0191] In research and clinical studies, two-point discrimination is a technique for determining tactile agnosia. According to Sir Sidney Weintin, who tested Weber's observations published in year 1834, he agreed with the theory that there is a lack of uniformity of tactile sensitivity found throughout different parts of the body skin. In 1965 Sidney Weinstein decided to test the two-point discrimination theory to determine what areas of the body were more sensitive than others. In fact, he concluded the areas of the body such as the face, lips or fingers require less distance between the two points or indents in order to distinguish the two points. During the testing, he found the skin surface located on the back required much more distance between each point in order for the participant to differentiate the two points. However, the exact distance can be influenced based on whether or not the individual has hair on their back. In hairy skin, Merkel nerve endings are clustered into specialized epithelial structures called "touch domes" or "hair disks". An individual with hair grown in on their backside have additive sensitivity to pressure or skin indentations with the presence of Merkel nerve endings. Merkel nerve endings are found in the basal layer of glabrous and hairy skin and in hair follicles as well. They provide information on pressure and deep touch which in my invention are provided by a blunt tip of the blade group 265 and a blunt tip of the support 275.

[0192] Seven non-patent literature publications have been located that explain tactile discrimination including that between two points at different distances and locations on human skin surfaces. These were: [0193] Gemperle, F.; Hirsch, T.; Goode, A.; Pearce, J.; Siewiorek, D.; Smailigic, A. Wearable Vibro-Tactile Display. Carnegie Mellon Wearable Group, Carnegie Mellon University, 2003. [0194] Sherrick, C. E.; Cholewiak, R. W.; Collins, A. A. The Localization of Low- and High-Frequency Vibrotactile Stimuli. Journal of the Acoustical Society of America 1990, 88 (1), 169-179. [0195] Verrillo, R. T. Vibrotactile Thresholds for Hairy Skin. Journal of Experimental Psychology 1966, 72 (1), 47-50. [0196] Zhu, B; Skin-Inspired Haptic Memory Arrays with an Electrically Reconfigurable Architecture; 2015. [0197] Shih; Dubrowski; Carnahan; Evidence for Haptic Memory; 2009. [0198] van Erp, J. B. F. Tactile displays for navigation and orientation: perception and behavior (pp. 26-27), Soesterberg, The Netherlands: TNO Human Factors, 2007. [0199] Myles; Binseel; The Tactile Modality: A Review of Tactile Sensitivity and Human Tactile Interfaces; ARL-TR-4115 report; 2007.

[0200] An eighth publication by Weinstein was unable to be located, yet much of its contents were cited within this publication by Miles and Binseel. Also additional publications were not obtained, yet mentioned and cited within this publication by Myles and Binseel. The citations for Weinstein and the additional other publications in the References listed by Miles and Binseel were: [0201]

Weinstein, S. Intensive and Extensive Aspects of Tactile Sensitivity as a Function of Body Part, Sex, and Laterality. In D. R. Kenshalo (Ed.), *The Skin Senses* (pp. 195-222). Springfield, IL: Charles C. Thomas, 1968. [0202] Weber, E. H. *The Sense of Touch* (De Tactu. H. E. Ross and Der Tastsinn, D. J. Murray, Trans.): New York: Academic Press, 1978 (original works published in 1834). [0203] Sherrick, C. E.; Cholewiak, R. W. Cutaneous Sensitivity. In K. Boff, L. Kaufman, & J. L. Thomas (Eds.), *Handbook of Perception and Human Performance*, pp. Dec. 1, 2012-58. New York: Wiley, 1986. [0204] Kandel, E. R.; Jessell, T. M. Touch. In E. R. Kandel, J. H. Schwartz, T. M. Jessell (Eds.), *Principles of Neural Science*, 3rd ed. (pp. 349-414). New York: Oxford University Press, 1991. van Erp, J. B. F.; van den Dobbelaars, J. J. On the Design of Tactile Displays; TNO-report TM-98-B012; Soesterberg, The Netherlands: TNO Human Factors Research Institute, 1998.

[0205] The below data reproduced in Table 1 is read from the 2007 publication by Kimberly Myles and Mary S. Binseel of the Army Research Laboratory entitled "The Tactile Modality: A Review of Tactile Sensitivity and Human Tactile Interfaces" which cited Weinstein. The graph associated in the upcoming FIG. 61 of the instant patent disclosure is also taken from this same publication. The below numbers are approximations read from the graph associated since the graph did not have hard numbers associated with each measurement. The tactile distance between pressure points for two-point discrimination is summarized in Table 1:

TABLE-US-00001 TABLE 1 Skin Tactile Distance Body Part in millimeters (mm) toe 10 foot 21 leg 47 thigh 44 belly 35 back 39 breast 32 upper lip 5 cheek 7 nose 8 forehead 15 forearm 38 shoulder 38 upper arm 46 palm 11 finger 1

[0206] A graphical representation of the data represented in Table 1 will be provided in FIG. 61.

[0207] Letter designations in the drawings depict certain planes, gap distances and contours, defined throughout, and for convenience are summarily defined wherein: [0208] "F" references a fulcrum when the inside of a user's forearm presses against a body leverage surface 495 relative to a grip 395 of an elongated handle 315 and pressing the blade end 325 of an elongated handle 315 towards the torso backside of the user; [0209] "T" references a skin convex inside a blade group 265; [0210] "U" references a skin convex inside a support 275 taking form of a blade group; and [0211] "CC" references a skin convex inside a blade group 265 and a support 275.

[0212] FIG. 29 illustrates a close up side view of the elongated handle and the safety razor 105 for two-point discrimination previously circled in the prior illustration in FIG. 27 and the safety razor 105 removably attaching to the elongated handle 315. The elongated handle 315 having the handle clip 365 allowing a user to press in order to allow the safety razor 105 to removably attach or detach from the elongated handle 315. The safety razor 105 having the blade group 265 and support 275 according to embodiments of the present inventions. A substrate structure 215 adapted to hold both the blade group 265 and the support 275 the on a front surface 375 of the substrate structure 215 with the blade group 265 and the support 275 spaced a tactile discrimination distance 285 sufficiently wide enough to achieve two-point discrimination tactile feedback felt through a torso region of the skin of the user perceived between the blade group 265 and the support 275 and wherein the substrate structure 215 is adapted such that no elements within the tactile distance produce a tactile sensation on the skin surface A. The support 275 comprises another blade group comprising another sharp blade 115 and another guard 135 parallel to the another sharp blade 115. In FIG. 29 the support 275 takes the form a blade group and each blade group comprising a sharp blade 115 with a sharp edge 125 and an inner guard 135 parallel to the sharp blade 115 on a trailing side of the sharp blade 115 opposite an outer comb 145 having an inside edge 195 wherein the outer comb 145 parallel to the sharp blade 115 on a leading side of the sharp blade 115 and a substrate structure 215 adapted to hold the blade group 265 and the support 275 on a front surface 375 of the substrate structure 215 with the blade group 265 and support 275 spaced a distance sufficient to achieve two-point discrimination on the skin of a user between the blade group 265 and support 275. The front surface 375 of the substrate structure 215 opposite a rear surface 385.

Inner guard **135** having an outer edge **185** and a trailing opening **J** inside of the outer edge **185** and the sharp edge **125** of the sharp blade **115**. Though the blade group **265**, in FIG. **29**, is pressing into the skin surface **A** the support **275** is not pressing into the skin surface **A** and thus, the leading opening **G** inside of the inside edge **195** and the sharp edge **125** is still present. Depending on how flexible the sharp blade **115** is allowed the leading opening **G** is able to remain present or may no longer be present when the sharp blade **115** moves closer to the inside of the outer comb **145**. Blade group **265** is safely poking the skin surface **A** and creating a skin convex inside of an outer edge **185** and an inside edge **195** which is referenced as skin convex **T**. Skin convex **T** will be even more clearly illustrated in the close up view in the upcoming illustration in FIG. **31**.

[0213] The safety razor **105** for two point discrimination having the front surface **375**, the rear surface **385**, a top side **335**, a bottom side **345** wherein the top side **335** is opposite the bottom side **345** and the top side **335** is close to the blade end **325** of the elongated handle **315**. The substrate structure **215** adapted to hold the blade group **265** and the support **275** on the front surface **375** of the substrate structure **215** with the blade group **265** and the support **275** spaced a distance sufficient to achieve two-point discrimination on the skin of a user between the blade group **265** and support **275** and said support **275** and blade group **265** extend from the front surface **375** of the substrate structure **215** and having a height **X** which is the height inside of the tips of both the blade group **265** and the support **275** to the front surface **375** of the substrate structure **215**. Height **X** is about 3.81 millimeters or more. Height **X** is sufficient to avoid loose skin of the user touching and rubbing the front surface **375** of the substrate structure **215** which would interfere with a shaving stroke. Both the blade group **265** and the support **275** having a bottom side **605** and a top side **595** wherein the bottom side **605** is opposite the top side **595**. In a preferred embodiment height **X** is about 3.81 millimeters or more and wherein the substrate structure **215** holds the blade group **265** and the support **275** spaced a distance between about 35 millimeters. A midpoint **H** may be between about 0-75 degrees in relation to the front surface **375** of the substrate structure **215**. A preferred angle of the tip of the blade group **265** or the top side **595** of a blade group **265** in relation to the front surface **375** of the substrate structure **215** is about 20 degrees. In FIG. **29** the safety razor **105** for two-point discrimination is shown prior to gouging and indenting into the skin surface **A** while the opposite side view of this embodiment being identical according to a first embodiment of the present inventions.

[0214] The front surface **375** of the substrate structure **215** comprising one or more grooves parallel from each other and adapted to removably hold the blade group **265** and support **275**. In FIG. **29** a first groove **305** and secondary groove **675** are illustrated. First groove **305** is removably holding blade group **265** while the secondary groove **675** is removably holding the support **275**. The first groove **305** and secondary groove **675** allow a user an option to choose a distance between the blade group **265** and the support **275**. The safety razor **105** also having a rear surface **385** comprising a handle attachment **295** which is removably attaching to the elongated handle **315**. It is preferred that the substrate structure **215** removably adapts at least one blade group **265** at an angle of about 0-75 degrees in relation to the front surface **375** of said substrate structure **215**. The blade group **265** in my invention is capable of successfully stroking skin and shaving hair when the midpoint **H** of a non-flexing portion of the sharp blade **115** is at about 75 degrees or less in relation to the front surface **375** of said substrate structure **215**.

[0215] The support **275** may take the form of a blade group or an alternative embodiment having a least one blunt protrusion sufficient for safely poking into the skin surface **A**. The support **275** may comprises more than one blunt protrusion wherein each blunt protrusion may be at staggered locations.

[0216] A tactile discrimination distance **285** is a gap spaced inside of the blade group **265** and the support **275** and is about 35 millimeters or larger for the torso. The back side human skin surface is among the least sensitive portions of the human body and needs a longer tactile discrimination distance **285** of about 39 millimeters. These 35 millimeter and 39 millimeter tactile discrimination

distances are derived from the data cited in Myles and Binseel, 2007 referencing Weinstein, 1968. The tactile discrimination distance **285** may have an elevational gap EE which may be a deep or shallow gap inside of the tips of the blade group **265** and the support **275** and the front surface **375**. The tactile discrimination distance **285** between a least the blade group **265** and the support **275** may vary. The tactile discrimination distance **285** allows balance and stability of the substrate structure **215** and safety razor **105** when stroking against the skin surface A. Tactile discrimination distance **285** also grants space for a tightened skin to convex and enter inside of the tactile discrimination distance **285** without rubbing against the front surface of substrate structure while allowing a user to maintain an effective angle between the blade group **265** and a skin surface without difficulty. In order for the safety razor **105** to hover over hills and valleys which may be found on the torso or back side of a user it is useful to have an elevational gap EE. In FIG. **29** the elevational gap EE is allowing room for the skin to move inside and begin to convex without touching or rubbing against the front surface of substrate structure. It will be illustrated in the upcoming FIG. **10** the skin convex taking full shape inside the elevational gap EE. The elevational gap EE allows the skin to tighten inside of the blade group **265** and support **275** creating a stabilized substrate structure **215**. The tactile discrimination distance **285** also creates an effective amount of distance between the blade group **265** and the support **275** in order to allow two-point discrimination to occur which will be further described in the upcoming FIGS. **32-33**. The tactile discrimination distance **285** is inside of the blade group **265** and support **275** and the elevational gap EE is illustrated with dashed lines inside the support **275** and blade group **265**.

[0217] In FIG. **29** the safety razor **105** for two-point discrimination is illustrated attaching the blade group **265** and a support **275**, which in FIG. **29** takes the shape of a blade group. In FIG. **29** the blade group **265** is poking and indenting into a skin surface A while the opposite side view of this embodiment being identical according to a first embodiment of the present inventions. This illustration in FIG. **29** shows the blade group **265** creating the first point of the two points in two-point discrimination represented by an initial sensory point signal **245**. Initial sensory point signal **245** is a sensory in the human sensory system that is being triggered by the blunt tip of the blade group **265** poking the skin surface A and letting a user understand the location of the blade group **265**. The blade group **265** in my invention functions properly and is highly dependent on safely poking into the skin surface A in order to create indentations that allow a skin convex to form inside of the inner guard **135** and outer comb **145**. It can be seen in FIG. **29** the sharp blade **115** belonging to the blade group **265** is now flexing. The sharp blade **115** may flex very little or may be very flexible depending on the location of the base in relation to the sharp edge **125** of the sharp blade **115**. The base was previously illustrated as base **205** in the prior FIG. **26**. The angle of a top side **595** of the blade group **265** or the midpoint H in relation to the front surface **375** of a substrate structure **215** area is about between 0-75 degrees. A preferred angle of a tip or the top side **595** of the blade group **265** in relation to the front surface **375** of the substrate structure **215** is 20 degrees. The midpoint S references the flexing midpoint of the sharp blade **115** belonging to the blade group **265** or the support **275** when support **275** takes the form of a blade group. Midpoint H and midpoint S are both illustrated to show the difference between when a portion of the sharp blade **115** is flexing and what it is not flexing. A cutting surface inside of the inner guard **135** and the outer comb **145** is referenced as a convex surface Z. The angle between a midpoint S in relation to the angle of the convex surface Z is referenced as angle R. Convex surface Z is illustrated with a dashed line extending out from the skin convex T in order to illustrate the angle representation. Angle R is about 35 degrees or less. A suppleness distance is measured between the inside edge **195** of the outer comb **145** and the outer edge **185** of the inner guard **135** of the blade group **265**. The suppleness distance is narrower than tactile discrimination distance **285** spaced between the blade group **265** and support **275**, which said support **275** is a blade group in FIG. **29**. There is a relationship between the tactile discrimination distance **285** and the distance of height X as presented herein. It is helpful to prevent the front surface **375** of the substrate structure **215** from

rubbing against the skin surface A during a shaving stroke. That being said, the greater the tactile discrimination distance **285** the greater the dimension of height X. Just the same, when the lesser the tactile discrimination distance **285** the lesser the dimension of height X.

[0218] Letter designations in the drawings depict certain planes, gap distances and contours, defined throughout, and for convenience are summarily defined wherein: [0219] “S” references a midpoint portion of a flexing sharp blade; [0220] “Z” references a convex cutting surface; and [0221] “R” references an angle between midpoint S and cutting surface Z.

[0222] FIG. **30** illustrates a close up side view of the elongated handle **315** and the safety razor **105** for two-point discrimination previously circled in the prior illustration in FIG. **28** and removably attaching to an elongated handle **315**. The elongated handle **315** having a handle clip **365** allowing a user to press in order to allow the safety razor **105** to removably attach or detach from the elongated handle **315**. The safety razor **105** having a blade group **265** and a support **275** according to embodiments of the present inventions. A substrate structure **215** adapted to hold both the blade group **265** and the support **275** on a front surface **375** of the substrate structure **215** with the blade group **265** and the support **275** spaced a tactile discrimination distance **285** sufficiently wide enough to achieve two-point discrimination tactile feedback felt through a torso region of the skin of the user perceived between the blade group **265** and the support **275** and wherein the substrate structure **215** is adapted such that no elements within the tactile distance produce a tactile sensation on the skin surface A. Another reason why the skin convex CC should not touch or rub the front surface **375** of the substrate structure **215**, as illustrated in the one embodiment of FIG. **30**, is to avoid creating a tactile sensation on the skin and disrupting tactile discrimination, either or both two-point discrimination and tactile leverage feedback. It should be noted that when discussing the torso the breast tissue is not considered part of the torso. The support **275** in FIG. **30** takes the form a blade group and both support **275** and the blade group **265** comprising a sharp blade **115** with a sharp edge **125** and an inner guard **135** parallel to the sharp blade **115** on a trailing side of the sharp blade **115** opposite the outer comb **145** wherein the outer comb **145** parallel to the sharp blade **115** on a leading side of the sharp blade **115**. A suppleness distance is measured between the inside edge **195** of the outer comb **145** and the outer edge **185** of the inner guard **135** of the blade group **265**. The suppleness distance is narrower than tactile discrimination distance **285** spaced between the blade group **265** and support **275**, which said support **275** is a blade group in FIG. **30**.

[0223] A substrate structure **215** adapted to hold the blade group **265** and the support **275** on the front surface **375** of the substrate structure **215** opposite the rear surface **385** with the blade group **265** and support **275** spaced with a tactile discrimination distance **285** distance sufficient to achieve two-point discrimination on the skin of a user between the blade group **265** and support **275**. Inner guard **135** having an outer edge **185** and a trailing opening J inside of the outer edge **185** and the sharp edge **125** of the sharp blade **115**. Outer comb **145** having an inside edge **195**. In FIG. **30** a support **275** comprises another blade group comprising another sharp blade **115** and another guard **135** parallel to the another sharp blade **115**.

[0224] In FIG. **30** the blade group **265** and support **275** are both safely poking a skin surface A and the blade group **265** is creating a skin convex T inside of the outer edge **185** and the inside edge **195**. The skin convex inside a blade group **265** is referenced as skin convex T while the skin convex inside the support **275**, which in FIG. **30** takes the form of a blade group, is referenced as skin convex U. The safety razor **105** having a top side **335** and a bottom side **345** wherein the top side **335** is opposite the bottom side **345**. The top side **335** of the safety razor **105** is on the blade end **325** of the elongated handle **315**. The blade group **265** and the support **275** also having a top side **595** and a bottom side **605** wherein the top side **595** is opposite the bottom side **605**.

[0225] The front surface **375** of the substrate structure **215** comprising one or more grooves parallel from each other and adapted to removably hold at least one or more blade group **265** and support **275**. In FIG. **30** a first groove **305** and a secondary groove **675** are illustrated. The first groove **305** is removably holding blade group **265** while the secondary groove **675** is removably holding the

support **275**. It is preferred that a substrate structure **215** adapts the blade group **265** at an angle of about 75 degrees or less in relation to the front surface **375** of said substrate structure **215**.

[0226] Grooves allow a user an option to choose a distance between the blade group **265** and support **275**. The substrate structure **215** also having a rear surface **385** comprising a handle attachment **295** for removably attaching to the elongated handle **315**. Handle attachment **295** may also take the form of an alternative method of attaching the safety razor **105** for tactile feedback. For example, instead of the handle attachment **295** being a protrusion that protrudes from the rear surface **385** in another embodiment a handle attachment **295** may be embodied as a female slot that interlocks with the long handle **315**. Other alternative embodiments may exist as well in order to attach the safety razor **105** with the elongated handle **315**.

[0227] The support **275**, as seen here in FIG. **30** may take the form of a blade group or in an alternative embodiment having a least one blunt protrusion sufficient for safely poking into a skin surface. The support **275** may comprises more than one blunt protrusion but instead may have multiple blunt protrusions that are at staggered locations. A clip **175** attaching a blade group **265** and attaching a support **275** to a substrate structure **215**.

[0228] A tactile leverage feedback distance **286** is between the blade group and the support is the distance measured from the forward most leading edge and the reward most trailing edge of the blade group and the support. An example illustration of the tactile leverage feedback distance **286** between the leading edge **195** of a leading blade group **265** and the trailing edge **185** of an adjacent trailing blade group **275** as a support will be illustrated in the upcoming FIGS. **29** and **30**.

[0229] A tactile discrimination distance **285** is between an adjacent blade group and support is the distance measured from the trailing edge and the leading edge of the adjacent blade group and support. An example illustration of the tactile discrimination distance **285** between the trailing edge **185** of a leading blade group **265** and the leading edge **195** of an adjacent trailing blade group **275** as a support will be illustrated in the upcoming FIGS. **29** and **30**. The tactile discrimination distance **285** is a gap spaced inside of two supports and is about 35 millimeters. The tactile discrimination distance **285** may be a two-point discrimination distance as in FIG. **30**. The tactile discrimination distance **285** may have an elevational gap EE which may be a deep or shallow gap inside of the tips of the blade group **265** and the support **275** and the front surface **375**. The tactile discrimination distance **285** between a least the blade group **265** and the support **275** may vary. The tactile discrimination distance **285** allows balance and stability of the substrate structure **215** and safety razor **105** when stroking against the skin surface A. Tactile discrimination distance **285** also grants space for a tightened skin to convex and enter inside of the tactile discrimination distance **285** without rubbing against the front surface **375** of substrate structure **215** while allowing a user to maintain an effective angle between the blade group **265** and a skin surface without difficulty. The tactile discrimination distance **285** also creates an effective amount of distance between the blade group **265** and the support **275** in order to allow tactile feedback to occur which will be further described in the upcoming FIGS. **32-33**. The tactile discrimination distance **285** is inside of blade group **265** and support **275** and the elevational gap EE is illustrated with dashed lines inside the support **275** and blade group **265**.

[0230] In order for the safety razor **105** to hover over hills and valleys which may be found on the torso or back side of a user it is useful to have a height or elevational gap EE. The blade group and the support each extend from the front surface of the substrate structure at a height sufficient to avoid loose skin of the user touching the front surface of the substrate structure within the distance spaced between the blade group and the substrate structure. An adequate height or elevational gap EE prevents skin from rubbing against or touching the front surface **375** of the substrate structure **215**. In FIG. **30** the elevational gap EE allows room for the skin convex CC to completely enter inside the elevational gap EE. In FIG. **30** the skin convex CC is taking full shape inside the elevational gap EE and the skin convex CC is not touching the front surface **375** of the substrate structure **215**. If the skin convex CC was rubbing against the front surface **375** of the substrate

structure **215** then the skin convex CC would not tighten and would not allow the substrate structure **215** to stabilize itself. Furthermore, if the skin surface is rubbing against the front surface **375** of the substrate structure **215** the skin would interfere with the shaving stroke when shaving over hills or valleys.

[0231] The height from tips of each of the blade group **265** and the support **275** to the front surface **375** of a substrate structure **215** is referenced as height X and is about 3.81 millimeters or more to avoid the loose skin of the user touching the front surface **375** of the substrate structure **215**.

[0232] In FIG. **30** the blade group **265** and the support **275** are both poking and indenting into the skin surface A while the opposite side view of this embodiment being identical according to a first embodiment of the present inventions. This illustration in FIG. **30** shows both of the two points being made to carry out two-point discrimination and the user may now understand the location of both the blade group **265** and the support **275**. The blade group **265** in my invention functions properly and is highly dependent on safely poking into the skin surface A in order to create indentations that allow a skin convex to form inside of inner guard **135** and outer comb **145**. It can be seen in FIG. **30** the sharp blade **115** belonging to the support **275** is now flexing along with the sharp blade **115** belonging to the blade group **265**. The preferred angle of the top side **595** of the blade group **265** in relation to the front surface **375** of the substrate structure **215** area is about between 0-75 degrees. A preferred angle of a tip or the top side **595** of the blade group **265** in relation to the front surface **375** of the substrate structure **215** is 20 degrees. The midpoint S references the flexing midpoint of sharp blade **115** belonging to blade group **265** or a support **275** taking the form of a blade group. Midpoint H and midpoint S are both illustrated to show the difference between when the sharp blade **115** is not flexing and when it is flexing with midpoint S. A cutting surface inside of the inner guard **135** and the outer comb **145** belonging to the support **275** and the blade group **265** is referenced as a convex surface Z. The angle between a midpoint S and the convex surface Z is referenced as angle R. Convex surface Z is illustrated with a dashed line extending out from the skin convex T in order to illustrate the angle representation. Angle R is about 35 degrees or less. Midpoint H may be at about 0-75 degrees in relation to the front surface **375**. It is easy for a user to accomplish a shave with such a wide range of angles when stroking the safety razor **105** to shave. Since shaving your backside or other areas of the body that are hard to see can be difficult to get a good shaving angle this is a very helpful feature.

[0233] In FIG. **30** the tactile discrimination distance **285** is inside of sensory point signal **245** and a secondary sensory point signal **255**. Sensory point signal **245** represents the initial sensory point signal **245** and secondary sensory point signal **255** represents the secondary sensory point signal **255** being triggered through the sensory system and communicating to a user's brain the location of the sensory point signal **245** and the location of the secondary sensory point signal **255** with regards to the 2-point discrimination. It is illustrated with a stream of star shapes representing the triggered signal. Furthermore, it can be seen in FIG. **30** that the skin surface plane A is now forming inside of the tactile discrimination distance **285** and there is now a skin convex CC that has formed inside the tactile discrimination distance **285**. The tactile discrimination distance **285** is the tactile distance or the distance. It can be seen that the blade group **265** extending from the front surface **375** of the substrate structure **215** at a height X sufficient to avoid the loose skin of skin convex CC from touching and rubbing the front surface **375** which would interfere with a shaving stroke. It should be noted that a portion of the blade group **265** is circled. The area circled will be illustrated as a close up view in the upcoming FIG. **31**. There is a relationship between the tactile discrimination distance **285** and the distance of height X as presented herein. It is helpful to prevent the front surface **375** of the substrate structure **215** from rubbing against the skin surface A during a shaving stroke. That being said, the greater the tactile discrimination distance **285** the greater the dimension of height X. Just the same, when the lesser the tactile discrimination distance **285** the lesser the dimension of height X.

[0234] Letter designations in the drawings depict certain planes, gap distances and contours,

defined throughout, and for convenience are summarily defined wherein: "CC" references a convex skin surface contour A engaged in a convex contour inside a blade group **265** and a support **275**. [0235] FIG. **31** illustrates a close up cross-sectional view of a portion of a blade group **265** circled in the prior FIG. **30** according to embodiments of the present inventions. The blade group **265** comprising at least a sharp blade **115** comprising a sharp edge **125** facing towards a skin surface A and an outer comb **145** having an inside edge **195**, an outer wall **155** of outer comb **145**, an outer comb inside wall **645** and an inner guard **135** comprising an inner guard outer edge **185** and an inner guard inside end **235**. Inner guard inside end **235** is embodied where the inner guard **135** and the sharp blade **115** meet. An inside portion of the outer comb **145** removed in order to create a deep void **165**. The sharp blade **115** is fixedly anchored on a sharp blade end **225** opposite the sharp edge **125**. A deep void **165** having a thickness which is represented as K allowing a level of control over the flexibility of the sharp blade **115** as well as over-exposure of the sharp blade **115** in relation to the skin surface A. Thickness K of deep void **165** is about 0.381 millimeters or less. In a preferred embodiment distance K is about 0.381 millimeters. Thickness K may run thicker but the danger of cutting becomes increasingly probable. It should be understood that the outer comb inside wall **645** is measured inside of the inside edge **195** and the sharp edge **125** of the sharp blade **115** and said outer comb inside wall **645** creates a barrier for the skin surface convex T. The deep void **165** is spaced intermediately of the outer comb **145** and the sharp blade **115**. The level of distance of the deep void **165** between a base **205** and the sharp edge **125** of the sharp blade **115** is referenced as L. The distance of L is about 4.572 millimeters or less. A preferred distance of L is about 2.032. Although L may be less or greater than the preferred distance if the distance becomes much less than 2.032 then the sharp blade **115** may run the risk of becoming too rigid and less able to bend and the sharp blade **115** may become more of a dagger which can be dangerous. If the distance of L becomes much greater than 4.572 millimeters then the sharp blade **115** will start to bend too much and the sharp edge **125** of the sharp blade **115** may move too far inside the outer edge **185** and inside edge **195** and will run the danger of not cutting effectively. It can be seen in FIG. **31** the midpoint S references the midpoint of the flexing sharp blade **115**. A skin convex T inside of the outer comb **145** and the inner guard **135** has a cutting referenced as a convex surface Z. The angle between the midpoint S and the convex surface Z is referenced as angle R. Convex surface Z is illustrated with a dashed line extending out from the skin convex T in order to illustrate the angle representation. Angle R is about 35 degrees or less.

[0236] In FIG. **31** the cross-section of the blade group **265** is illustrated pressing into skin according to embodiments of the present inventions. The blade group **265** is safely poking or indenting into the skin surface A in order for the blade group **265** to dry shave hairs properly as well as to create tactile feedback within the practice of two-point discrimination. The sharp edge **125** of the sharp blade **115** longitudinally bends relatively more parallel to a skin surface A when the inside edge **195** and the inner guard outer edge **185** safely poke into the skin surface A during shaving of hair. It can be seen from FIG. **31** that the hair **415**, the Pacinian Corpuscle **425** and the Ruffini's Corpuscle **435** are now all actively being triggered due to the skin stretching and pressure from the inner guard **135** and the outer comb **145** into the skin surface A and forming the tightening skin convex T in order to exposure the base of a hair **415**. Pacinian corpuscles **425**, also known as the Lamellar corpuscles, are one of the four major types of mechanoreceptor. They are nerve endings in the skin found in the subcutaneous layer of skin and are responsible for sensitivity to vibration and pressure. They respond only to sudden disturbances and are especially sensitive to vibration. Feelings of deep pressure from a poke, for instance are generated from Pacinian corpuscles **425** which are located deeper in the dermis **455**. In my invention the outer comb **145** and inner guard **135** serve to poke the skin surface A creating skin surface indentations and since the Pacinian corpuscles **425** are located deep in the dermis **455** it would be difficult for a safety razor that did not create a significant poke or indentation to stimulate the Pacinian corpuscles **425**. By taking full advantage of communicating with the Pacinian corpuscles my invention is utilizing

this communication in the same way this communication is used in two-point discrimination. Most safety razors found in most markets are designed to glide across the skin surface and are not designed to poke into the skin surface in order to trigger these nerves. The Ruffini Corpuscle **435**, also known as the Ruffini's ending, is a slowly mechanoreceptors found in the subcutaneous tissue layer and are another receptor responsible for mechanoreception. This spindle-shaped receptor is sensitive to skin stretch, responds to sustained pressure, and is located in the deep layers of the skin. As seen in FIG. **31** the skin indentations being created from the inner guard **135** and the outer comb **145** are stretching and poking the skin. Thus, communication through the sensory system to a user's brain is taking place in relation to the location of blade group **265**.

[0237] It can be seen now in FIG. **31** a trailing opening J allows for a sufficient opening or void for creating a tightening skin convex T and the skin convex T entering between inner guard outer edge **185** and comb inside edge **195**.

[0238] A trailing opening J is illustrated as a dashed imaginary triangle inside of the outer edge **185** of the inner guard **135** and the sharp edge **125** of the sharp blade **115**. In other alternate embodiments the dashed triangle may be a right triangle or an isosceles triangle or an isosceles right triangle. In FIG. **31** an inner guard inside wall **665** is inside of the inner guard inside end **235** and the inner guard inside wall **665** is one of three sides or walls of the imaginary dashed triangle illustrating the trailing opening J in FIG. **31**. The second side of the imaginary triangle for trailing opening J starts from the inner guard inside end **235** and runs along the sharp blade **115** up to the sharp edge **125** of the sharp blade **115**. The third and final side starts from the sharp edge **125** of the sharp blade **115** and runs along the skin surface plane A when adjacent to the skin surface plane A area and up to the outer edge **185**. These three sides work together to form the trailing opening J. The trailing opening J allows for a sufficient opening or space for tightening skin to enter and convex and exposure the base or root of a hair **415** in order to for the sharp blade **115** to cut a hair **415** at the base of the hair very effectively which is illustrated here in FIG. **31**. The trailing hairs illustrated in FIG. **31** are not shorn because the blade group **265** is merely pressing into the skin surface A and not performing a shaving stroke. If the blade group **265** were moving forward making a shaving stroke the hairs will become shorn. As seen in FIG. **31** each of the outer teeth **145** are substantially perpendicular to the sharp edge **125** and it can be seen that the leading opening G, which was illustrated in the second illustration in the prior FIG. **26**, is no longer illustrated since the sharp blade **115** has flexed enough to remove the opening G. However, in the case where the base **205** is closer to the sharp edge **125** of the sharp blade **115** the flexibility of the sharp blade **115** may be greatly limited and the opening G may still exist. It can be seen in FIG. **31** the outer wall **155** of the outer comb **145** and the skin plane A create a one imaginary triangle with a vertex referenced as vertex O. Vertex O angle is created in order to allow the outer comb **145** to better indent into the skin surface A allowing the blade group **265** to shave properly and for better two-point discrimination. In FIG. **31** it can be seen that the vertex O vertices is allowing the inside edge **195** of the outer comb **145** to safety indent into the skin in order to create a better skin convex T.

[0239] It can be seen in the illustration the tissue sub layers and the sensors within each layer which include the Epidermis **445**, the Dermis **455** and the Hypodermis **465**. For the sake of clarity the sensors located in the deep tissue sub layers are illustrated as being activated from the poke. The star shapes embodied on the strand of the sensor indicates the communication taking place. The illustrated sensors include the Ruffini's Corpuscle **435**, which are found in the Dermis **455** layer and the Pacinian Corpuscle **425**, which are found in the "subcutaneous" or hypodermis **465** layer. In FIG. **31** the star shapes represent sensors being triggered in the sensory system.

[0240] FIGS. **32-33** illustrate aerial views of a handles gripped by a user extended under the armpit towards the backside with two safety blades indenting into the skin surface and triggering a sensory system according to embodiments of the present inventions. In FIGS. **32-33** a user holds the elongated handle **315** removably attaching to a safety razor **105** wherein a grip **395** of the elongated handle **315** is respectively gripped by fingers and hand by a same arm of the user the user is

illustrated pressing a body leverage surface **495** located on an outer side **475** of the elongated handle **315** near a midway between the grip **395** and a blade end **325**, which is opposite a grip end **355**, and configured to press the body leverage surface **495** against a user's forearm in order to leverage a handle attachment **295** located on an inner side **485** of the shaver handle **315** against a torso backside of the user and leveraging the shaver handle **315** using the body leverage surface **495** to create a fulcrum F relative to the grip **395** in order to press the blade end **325** towards the torso backside of the user and stroking the blade end **325** against the torso backside of the user. It should be noted that when discussing the torso the breast tissue is not considered part of the torso. A substrate structure **215** operatively coupled to the blade end **325** of the elongated back shaver handle **315**, wherein the substrate structure **215** is adapted to hold both the blade group **265** and the support **275** on a front surface **375** of the substrate structure **215** with the blade group **265** and the support **275** spaced a tactile leverage feedback distance sufficiently wide enough to provide leverage feedback felt through the elongated back shaver handle **315** for the user to maintain a consistent angle of the sharp blade relative to the skin surface when an arm of the user reaches the elongated back shaver handle **315** to a backside of the user during shaving movement over a shoulder blade peak or a spine depression on the backside. The user feeling within the hand of the user on the grip **395** of the elongated handle **315** a leverage feedback from both the blade group **265** and the support **275** against the backside skin.

[0241] The elongated handle **315** may have a generally s-shape and having a surface along a length of the elongated member **315**. The elongated handle **315** inner side **485** is opposite the outer side **475** and the elongated handle **315** also having a handle clip **365**. A skin convex CC is illustrated inside of the blade group **265** and the support **275** and has moved inside of the elevational gap EE. Each of the different blade groups may have different angles in relation to the substrate structure **215**. A suppleness distance is measured between the inside edge **195** of the outer comb **145** and the outer edge **185** of the inner guard **135** of the blade group **265**. The suppleness distance is narrower than tactile discrimination distance **285** spaced between the blade group **265** and support **275**, which said support **275** is a blade group in FIGS. 32-33.

[0242] FIGS. 32-33 further illustrates star shaped figures dispatching from a skin convex U created from a support **275** and a skin convex T created from a blade group **265**. These stars represent the sensors of which are being communicated through the sensory system as a result of initial sensory point signal **245** and secondary sensory point **255** being created by the blade group **265** and the support **275** indenting into the skin surface and signaling the sensors. The user feeling within nerves of the user's skin a first tactile feedback at a first location where the blade group **265** presses against the user's skin and the user separately feeling within nerves of the user's skin a second tactile feedback at a second location where the support **275** presses against the user's skin. A user may adjust a relative pressure of the pressing to seek equal pressure on the skin of the blade group **265** and the support **275** based on the first tactile feedback and the second tactile feedback. In FIGS. 23-33 the skin convex T is created by the blade group **265**, while the skin convex U is created by the support **275**. The sensory signals are communicating through the sensory system to the user's brain allowing the user to understand that both the initial sensory point signal **245** created by the blade group **265** as well as the secondary sensory point signal **255** created by the support **275** while both blade group **265** and support **275** indenting into the skin and allowing the user to understand the location of blade group **265** and support **275**. It can be seen that when comparing FIG. 32 to FIG. 33 the safety razor **105** has made a shaving stroke across the back side. During this stroke it can be seen that the sensors represented by the stars and referenced as initial sensory point signal **245** and secondary sensory point signal **255** have moved from one location to another and during this transition the user is gaining the understanding of the old and new location of the safety razor **105** because of two-point discrimination. Also, although in FIG. 33 the safety razor **105** has traveled across the skin surface in comparison to FIG. 32, the sensory memory allows a user to temporarily still feel previously made impressions or indentations for a short period of time

allowing a user to understand where they have already just shaved or where they still may need to shave. This allows a user to refrain from shaving in areas on the back that have already been shorn cuts down on time and makes the process much more timely efficient. The elongated handle **315** has a straight distance measured directly from the blade end **325** to the grip end **355** that is measured not following the curve of the elongated handle **315** which is about 330 mm to about 457.2 mm. A preferred straight distance of the back shaver handle **315** is about 355.6 mm.

[0243] The ability to discriminate stimuli on the skin also varies with where the skin is located on the body. Two-point discrimination is a measure that represents how far apart two pressure points must be before they are perceived as two distinct points on the skin (Gemperle et al., 2003). Weber's research focused on obtaining two-point discrimination thresholds for various areas of the body (Myles and Binseel, 2007 references Weber 1834/1978). Using a metal compass, touched various areas of the skin with the two points of the compass some distance apart and recorded judgments of the distance between the two points. (Myles and Binseel, 2007 references Weber, 1834/1978). From his work, promulgated five general propositions, of which the first two stated that (a) various parts of the touch organ are not equally sensitive to the spatial separation of two simultaneous points of contact, (b) if two objects touch us simultaneously, we perceive their spatial separation more distinctly if they are oriented along the transverse rather than the longitudinal axis of the body. (Myles and Binseel, 2007 references Weber, 1834/1978). This measurement will help the user to choose how dense his or her tactile array can be depending on what part of the body the tactile display is applied. (Myles and Binseel, 2007 references Weinstein, 1968) reported differences in two point discrimination thresholds for different areas of the body. Since each tip or factor is responsible for presenting a unique signal, if the blunt tips or tractors are placed too close together the user will perceive it as one signal and will miss the sensory message being generated with the use of two signals. Weinstein's chart that better illustrates the thresholds of two-point discrimination in the upcoming FIG. **61**.

[0244] From F his work, (Myles and Binseel, 2007 references Weber, 1834/1978) promulgated five general propositions, of which the first two stated that (a) various parts of the touch organ are not equally sensitive to the spatial separation of two simultaneous points of contact, (b) if two objects touch us simultaneously, we perceive their spatial separation more distinctly if they are oriented along the transverse rather than the longitudinal axis of the body. In order of decreasing sensitivity for two-point discrimination, the tongue was found to be most sensitive, followed by the lips, fingers/palm, toes, and forehead. If tactors are placed too close together and each factor is responsible for presenting a unique signal in the scheme of some complex, tactile pattern, the observer will perceive it as one signal and will miss the underlying message generated with the use of two signals. Two-point discrimination acuity is less than 1 millimeters for the fingers, 15 millimeters for the forehead, 35 millimeters for the forearm, 39 millimeters for the back, and 45 millimeters for the calf (Gemperle et al., 2003). Some areas of the body require are more sensitive that other areas of the body and thus, require less distance between a pair of distinct points.

[0245] In general, sensitivity decreases as one moves from distal to proximal extremities (Sherrick, Cholewiak, & Collins, 1990) and skin impedance of the stimuli is different for different areas of the body (Myles and Binseel, 2007 references Sherrick & Cholewiak, 1986). All skin on the body will probably follow some of the basic characteristics mentioned, but skin on different areas of the body will not be equally acute because of differences in skin "thickness, vascularity, density, electrical conductivity, and more derived properties, such as moduli of shear and elasticity" (Myles and Binseel, 2007 references Sherrick & Cholewiak, 1986, p. 12-3; Weber, 1834/1978).

[0246] Similar to the relationship found for the visual and auditory modalities, absolute threshold is inversely proportional to the amount of energy applied to the skin (Verrillo, 1966). Vibration is detected best on hairy, bony skin. (Gemperle et al., 2003). Since the four fibers overlap in their absolute sensitivities, a vibration stimulus will seldom stimulate one fiber in the skin but several fibers because the energy applied to the skin will move throughout nearby skin tissues (Myles and

Binseel, 2007 references Sherrick & Cholewiak, 1986.) Within the vibrotactile literature, the fibers are grouped to describe two systems: the Pacinian system and the non-Pacinian system. The Pacinian system has a large receptive field excited by higher frequencies and the non-Pacinian system consists of a small receptive field thought to be excited by lower frequencies (Sherrick, Cholewiak, & Collins, 1990). (Sherrick et al., 1990) report perceptual sensations of the non-Pacinian system as a superficial skin flutter while sensations for the Pacinian system are described as deep and diffuse. For this reason, my safety razor **105** creates for a user effective communication in having multiple blunt tips that create multiple points of indentations at a distance apart from each other which create deep impression or indentations into a skin surface on a trunk or back side of a user.

[0247] Sensory memory is the process by which the human body retains the sensations of interaction with human body after the external stimuli ceased, thus helping humans describe the physical quantities in their environment and manipulate objects in daily activities. Skin, the largest organ in the human body, has a variety of sensory receptors and provides significant sensation information such as force, pain, shape, and texture. Skin perceives external stimuli and conveys the sensory information to the brain through afferent neurons to form haptic memory, allowing humans to remember the impressions of the stimuli applied on the skin (Zhu et al., 2015).

[0248] The term haptic memory can be defined as the ability to retain impressions of haptically acquired information after the original stimulus is absent (Shih, Dubrowski & Carnahan, 2009). After a series of tests were conducted it was concluded that haptic memory may last for up to 2 seconds. (Shih, Dubrowski & Carnahan, 2009). In embodiments of the present inventions the poking that my safety razor **105** creates against a user's torso stimulates the sensory memory of a user allows the information regarding the location of the safety razor **105** to be processed and retained if only for a short period of time. This allows a user to have a temporary understanding as to where the safety razor **105** has already been stroking and still where the safety razor **105** needs to still stroke.

[0249] As seen in FIGS. **32-33** after stroking the blade group **265** and a support **275** against the skin surface a user may now have a temporary understanding as to the location of where the blade group **265** and support **275** were traveling from and where the blade group **265** and support **275** are now presently location. This allows a user to, for a brief period of time, understand where both the blade group **265** and support **275** has just been and where the safety razor **105** is no longer present. This means that a user would be able to understand that they have been shaving in one area and may dictate where they need to stop and start based on a communication set forth with sensory memory.

[0250] According to (Myles and Binseel, 2007 references Kandel and Jessell, 1991), Meissner's corpuscles and Merkel's cells respond to touch, Pacinian corpuscles respond to vibration, and Ruffini's corpuscles respond to rapid indentation of the skin. Thus, a vibration stimulus delivered to non-Pacinian fibers but designed to evoke responses typical of Pacinian fibers (i.e., response to vibration) would produce lower threshold values than if the stimulus were directly delivered to Pacinian fibers. Likewise, stimuli for glabrous and hairy skin must be created to obtain the maximum sensitivity possible for each type of skin. Compatibility between the stimulus and the skin structure to be stimulated will yield sensitivity values closer to true threshold values. In the study conducted by Van Erp & Van den Dobbeltsteen (Myles and Binseel, 2007 references an Erp & van den Dobbeltsteen, 1998) they concluded that the Pacinian corpuscle and Ruffini's ending both have large receptive fields and respond to high levels of pressure vibration and indenting into the skin. Van Erp & van den and Dobbeltsteen concluded that while the range of the Pacinian Corpuscle was 40 to 800 Hz, the range of the Ruffini's ending was 15 to 400 Hz. (Myles and Binseel, 2007 references an van Erp & van den Dobbeltsteen, 1998).

[0251] In embodiments there may be staggered supports **274** with blunt tips for indenting to cause tactile discrimination distance. A study was previously conducted and discussed by (van Erp, 2007)

wherein 14 tactors were placed in a horizontal array on the back with a spacing of 4 millimeters, resulting in a center to center distance of 2 cm. The results show a uniform acuity across the torso of 3-4 cm, except for locations on the body midline (i.e., the spine and the navel) for horizontally oriented arrays (but not for the vertical arrays) where the resolution is much higher, about 1-2 cm. With a torso circumference between 80-100 cm and a horizontal acuity of 3-4 cm, a horizontal display resolution of 24 tactors should be obtainable. A similar calculation would result in a vertical display resolution of 8 tactors. In addition to skin location, parameters of the vibrotactile signal can also influence sensitivity to and the perception of tactile stimuli. For example, the tactile threshold for the trunk is 4 microns or lower but this threshold may very well increase or decrease, depending on the inter-stimulus interval, amplitude, frequency, or location on the trunk. (van Erp, 2007)

[0252] One of the earliest and most well-known form of sensory substitution devices was Paul Bach-y-Rita's TV SS that converted the image from a video camera into a tactile image and coupled it to the tactile receptors on the back of his blind subject. In summary, the receptors would create a tactile image on the back of the subject and the blind subject could determine the image. Recently, several new systems have been developed that interface the tactile image to tactile receptors on different areas of the body.

[0253] FIGS. 34-36 illustrate side views of a user utilizing an elongated handle 315 according to embodiments of the present inventions. The elongated handle 315 removably attaching to a safety razor 105 for two point discrimination and said handle 315 having a blade end 325 and a grip end 355 and the blade end 325 opposite the grip 395 and the outer side 475 opposite the inner side 485, and between the outer side 475 and the inner side 485. A handle clip 365 used to lock and release the safety razor 105.

[0254] A body leverage surface 495 is located on the outer side 475 of the elongated handle 315 near a midway between the grip 395 and the blade end 325 and the blade end 325 configured to press the body leverage surface 495 against a user's forearm creating a fulcrum F when the grip 395 is respectively gripped by fingers and hand by a same arm of the user located on the inner side 485 of the elongated handle 315 and a thumb of the hand facing away from the blade end 325 of the elongated handle 315 and the elongated handle 315 is reaching the blade end 325 under an armpit of the same arm of the user to leverage the safety razor 105 and handle attachment located on the inner side 485 of the elongated handle 315 against a torso backside of the user. It should be noted that when discussing the torso the breast tissue is not considered part of the torso.

[0255] FIG. 37 illustrates a side view of a right attachment side 555 of a blade group 265 and blade group 265 comprising a sharp blade 115 with a sharp edge 125 and an inner guard 135 parallel to the sharp blade 115 on a trailing side of the sharp blade 115 opposite the outer comb 145 wherein an outer comb 145 parallel to the sharp blade 115 on a leading side of the sharp blade 115 and an outer comb 145 comprising an inside edge 195 and an inner guard 135 comprising an inner guard outer edge 185. A portion of the inner guard 135 inside of the outer edge 185 and the sharp edge 125 of the sharp blade 115 is removed in order to create a trailing opening J. Trailing opening J allows for a sufficient opening or void for tightening skin to enter and convex in order for the sharp blade 115 to gain access to a base of a hair. Each of the outer teeth 145 substantially perpendicular to the sharp edge 125 of the sharp blade 115 and spaced with a leading opening G between the inside edge 195 of the outer teeth 145 and the sharp edge 125 of the sharp blade 115. The right attachment side 555 having a clip 175 which is used to snap into a groove attachment of a substrate structure first or second groove. The clip 175 may be on the right attachment side 555 or a left attachment side which is opposite a right attachment side 555 of the blade group 265 or support as will be further illustrated in the upcoming FIG. 58. In an alternative embodiment the clip 175 may be inside the left attachment side and right attachment side 555 and near a bottom side 605 which is opposite a top side 595 or may also be near a blade group front surface 615 which is opposite a blade group rear surface 625 of the blade group 265 or support.

[0256] In FIG. 37 the blade group 265 has an inner rearward distance BB from the sharp edge 125

of the flexible sharp blade **115** to the inner guard edge of the inner guard **135** in relation to an outer rearward distance **N** from the inside edge **195** of the outer comb **145** to the sharp edge **125** of the sharp blade **115** has a ratio of about 1. In other words, in this embodiment, the inner rearward distance **BB** and the outer rearward distance **N** are substantially the same. The inner rearward distance **BB** from the sharp edge **125** of the sharp blade **115** to the inner guard edge of the inner guard **135** is about 0.508 mm to about 1.016 mm. A preferred inner rearward distance **BB** from the sharp edge **125** of the sharp blade **115** to the inner guard **135** is about 0.762 mm. Also, the outer rearward distance **N** from the inside edge **195** of the outer comb **145** to the sharp edge **125** of the sharp blade **115** is about 0.508 mm to about 1.016 mm. A preferred outer rearward distance **N** from the inside edge **195** to the sharp edge **125** is about 0.762 mm.

[0257] A thickness of the inner guard **135** from the outer edge **185** of the inner guard **135** to the nearest portion of the sharp blade **115** is referenced as distance **DD**. Distance **DD** is about 0.381 mm to about 0.889 mm. A preferred distance **DD** is about 0.61 mm.

[0258] A deep void **165** running from a base **205** to the sharp edge **125**. A thickness of the deep void **165** is referenced as thickness **K**. Thickness **K** of the deep void **165** is about 0.7262 millimeters or less. In a preferred embodiment distance **K** is 0.0381 millimeters. The inner edge of the inner guard **135** and the inside edge **195** of the outer comb **145** in practice are blunt or curved edges because no corner is perfectly sharp or square. If the inner edge of the inner guard **135** and the inside edge **195** of the outer comb **145** were perfectly sharp or square, they would risk cutting into the skin or feel uncomfortable. That being said, there may be a slightly square edge sufficient to indent and grip the skin in order for the skin inside of the inside edge **195** and the inner guard **135** to stretch. These ends are the outermost horizontal dimension to the end or tip of the inner guard **135** or the outer comb **145**. Therefore the inner rearward distance **BB** and outer rearward distance **N** are stated measured from respective ends of the inner guard **135** and the outer comb **145**.

[0259] The deep void **165** between the row of the outer comb **145** and the planar surface of the sharp blade **115**. The top side **595** is opposite the bottom side **605** and the right attachment side **555** of the blade group **265** close to the bottom side **605**. The blade group front surface **615** is opposite the blade group rear surface **625** and the blade group front surface **615** is facing against a skin surface during a shaving stroke. A height from a blunt tip of the blade group **265** to the lowest portion of the blade group rear surface **625** of the blade group **265** is referenced as height **V** and is about 5.08 millimeters or more.

[0260] Letter designations in the drawings depict certain planes, gap distances and contours, defined throughout, and for convenience are summarily defined wherein: [0261] “**BB**” references a distance rearward from the sharp edge **125** of the sharp blade **115** to the outer edge **185** of the inner guard **135** is referenced as distance **BB**; [0262] “**N**” references a distance rearward from the inside edge **195** of the outer comb **145** to the sharp edge **125** of the sharp blade **115** is referenced as distance **N**; [0263] “**DD**” references a thickness of the inner guard **135** from the outer edge **185** of the inner guard **135** to the nearest portion of the sharp blade **115** is referenced as distance **DD**; and [0264] “**V**” references a height from a blunt tip of the blade group **265** to the lowest portion of the blade group rear surface **625** of the blade group **265** is referenced as height **V**.

[0265] FIG. **38** illustrates a diagram of the different muscles that are found on the backside of the human body. It is important to take notice as to just how many different muscles that are found on the backside and the divides, which are illustrated as divide **P** are seen in FIG. **38** between the muscles. The more defined the muscles on one's backside means the more muscles divides **P** are present which means the more of a challenge the shaving terrain may pose for most traditional safety razors found in most markets. In the body building world an individual who has a high level of muscle definition is known as being “cut”. When an individual has a high level of muscle definition it is common to see a defined divide or a “cut” which looks like a valley between each muscle group which can be seen in FIG. **38**. In the upcoming FIGS. **39-44** it will be more clearly

illustrated as to how a safety razor **105** for two-point discrimination performs a shaving stroke over challenging terrain with hills and valleys which can be found on the body and especially the back side of a user. It is because these areas are difficult to reach and shave properly that many individuals with muscles as such are forced to maintain their back hair with other non-preferable and painful means such as waxing and laser hair removal. It should be understood that the strength and flexibility of skin comes from two structures found in the dermal layer of skin which are collagen and elastin. Together, collagen and elastin make up about 70% of the dermal layer. Collagen is a fibrous protein that gives the skin form and strength. It holds together all the various structures of the skin and gives it plumpness and firmness. Elastin is a protein base interwoven with the collagen fibers to form elastic tissue. This gives the skin its flexibility and elasticity which my invention takes much advantage in using during the shaving process. Elastin helps the skin resume its shape after expanding or stretching. Muscle tissue is arranged in bundles of parallel fibers and is stretchy. Being that skin and muscle have these characteristics is very relevant in that while most traditional shavers are used to glide on the skin surface my invention is purposely designed to indent into the skin and when moving across the skin.

[0266] Letter designations in the drawings depict certain planes, gap distances and contours, defined throughout, and for convenience are summarily defined wherein: [0267] “P” illustrates a muscle divide inside of a pair of muscles found on the human back side.

[0268] FIGS. **39-41** illustrate close up side views of a muscle divide P as was illustrated in the previous FIG. **38** and showing a safety razor **105** removably attaching to an elongated handle **315** according to embodiments of the present inventions. The safety razor **105** having a front surface **375**, a rear surface **385**, a top side **335**, and a bottom side **345** wherein the front surface **375** is opposite the rear surface **385** and the top side **335** is opposite the bottom side **345** and a blade group **265** comprising a sharp blade **115** with a sharp edge **125** and an inner guard **135** parallel to the sharp blade **115** on a trailing side of the sharp blade **115** opposite an outer comb **145** wherein the outer comb **145** parallel to the sharp blade **115** on a leading side of the sharp blade **115** and the outer comb **145** comprising an inside edge **195** and an outer wall **155** of outer comb **145** and the inner guard **135** comprising an inner guard outer edge **185**. It can be seen that the top side **335** is close to a blade end **325** of the elongated handle **315**. A handle clip **365** is on the inner side **485** of the elongated handle **315**. The elongated handle **315** having an inner side **485** and an outer side **475** wherein the inner side **485** is opposite the outer side **475**. In another embodiment the handle clip **365** may also be on the outer side **475** of the elongated handle **315**. A portion of the inner guard **135** inside of the outer edge **185** and sharp blade **115** is removed in order to create a trailing opening J which a skin convex T enters as seen in FIGS. **39-41**. Trailing opening J allows for a sufficient opening or space for tightening skin to enter and allow convex T to form and in order for the sharp blade **115** to gain access to a base of a hair **415**. Each of the outer teeth **145** substantially perpendicular to the sharp edge **125** of the sharp blade **115**. A deep void **165** between the row of the outer comb **145** and the planar surface of the sharp blade **115**. When the sharp blade **115** is flexed a void is inside the inner guard inside end **235** and the sharp blade **115**. In FIGS. **39-41** the safety razor **105** is pressing into a skin surface A having a muscular skin surface hill and how when safely poking and gouging into the skin and moving forward to perform a shaving stroke it can also be seen that the while the inner guard **135** outer edge **185** and the outer comb **145** inside edge **195** are gouging the skin surface A they are creating a skin convex T while inside of the blade group **265** and a support **275** a skin convex contour CC is inside of an elevational gap EE and a tactile discrimination distance **285**. The tactile discrimination distance **285** inside the blade group **265** and support **275** and the elevational gap EE creating sufficient space and allowing the blade group **265** and the support **275** to navigate the terrain without having the skin convex CC rubbing against the front surface **375** of the safety razor **105** which would cause a disruption in the shaving stroke process. A tactile discrimination distance **285** inside a blade group **265** and support **275** allowing said blade group **265** and support **275** to navigate the terrain without having a skin convex CC or a

secondary skin convex CC from rubbing against the front surface 375 of a safety razor 105 which would cause a disruption in the shaving stroke process. A tactile discrimination distance 285 inside a blade group 265 and support 275 allowing said blade group 265 and support 275 to navigate the terrain without having skin convex CC rubbing against the front surface 375 of a safety razor 105 which would cause a disruption in the shaving stroke process. It is illustrated that as the safety razor 105 for two-point discrimination moves closer to the muscle divide P the hairs 415 are being shorn. Initial sensory point signal 245 and secondary sensory point signal 255 are illustrated and are communicating through a user's sensory system and letting the user know the location of each of the two points.

[0269] It is illustrated that as the safety razor 105 for two-point discrimination moves closer to the muscle divide P the hairs 415 are being shorn. Initial sensory point signal 245 representing the sensory communication taking place from the blade group 265 poking the skin while the secondary sensory point signal 255 representing the sensory communication taking place from the support 275 poking the skin. Both initial sensory point signal 245 and secondary sensory point signal 255 are communicating through a user's sensory system and letting the user know the location of each of the two points. It can be seen in FIGS. 39-41 that a midpoint of a non-flexing portion of the sharp blade 115 is referenced as midpoint H. The degree of angle between mid-point H in relation to the skin surface A is referenced as angle M. Angle M may range from about 0-75 degrees. Since angle M may be at 0-75 degrees to work properly it can be seen this is very beneficial in making it easier for a user to get an accurate shaving angle. It is preferred that M be at about a 20 degree angle. The angle between the front surface 375 the safety razor 105 in relation to the midpoint H is referenced as angle Y. Angle Y is 0-75 degrees or less. A preferred angle of angle Y is about 20 degrees. A handle attachment 295 is on the rear surface 385 of the safety razor 105.

[0270] In FIGS. 39-41 a portion of the blade group 265 in each illustration is circled referencing a close view of this circled area which will be illustrated in a close up view in the upcoming FIGS. 42-44. In FIG. 39 angle M is at about 45 degrees. In FIG. 40 angle M is 50 degrees. In FIG. 41 angle M is 35 degrees which is illustrating how angle M is able to perform at such a wide range of angle. Furthermore, the circled portion of the blade group 265 in FIG. 39 is illustrated in a close up view illustration in the upcoming FIG. 42. The circled portion of the blade group 265 in FIG. 40 is illustrated in a close up view illustration in the upcoming FIG. 43. Finally, the circled portion of the blade group 265 in FIG. 41 is illustrated in a close up view illustration in the upcoming FIG. 44.

[0271] It can be seen in FIG. 41 that when the muscles divide P is inside of the tactile discrimination distance 285 that the skin convex CC may sometimes exist between the muscles divide P and the support 275 or blade group 265. The tactile discrimination distance 285 inside the blade group 265 and support 275 allowing said blade group 265 and support 275 to navigate the terrain without having a skin convex CC or a secondary skin convex CC from rubbing against the front surface 375 of the safety razor 105 which would cause a disruption in the shaving stroke process.

[0272] In FIGS. 42-44 a blade group 265 has a blade group front surface 615 opposite a blade group rear surface 625 along a skin plane A comprising a sharp blade 115 and an inner guard 135 parallel to the sharp blade 115 with a sharp edge 125 on a trailing side of the sharp blade 115 opposite an outer comb 145 wherein the outer comb 145 parallel to the sharp blade 115 on a leading side of the sharp blade 115 and the outer comb 145 comprising an inside edge 195 and an outer wall 155 of outer comb 145 and the inner guard 135 comprising an inner guard outer edge 185 and an inner guard inside wall 665 which is a wall inside the outer edge 185 and the inner guard inside end 235. A portion of the inner guard 135 inside of the outer edge 185 and the sharp edge 125 of the sharp blade 115 is removed in order to create a trailing opening J which a skin convex T entering opening J as seen in FIGS. 42-44. The inner guard 135 comprising the inner guard outer edge 185, an inner guard inside end 235 and an inner guard inside wall 665 inside the outer edge 185 and the inner guard inside end 235. The trailing opening J allows for a sufficient

opening or space for the tightening skin convex T to enter and convex in order for the sharp blade **115** to gain access to a base of a hair **415**. Each of the outer teeth **145** substantially perpendicular to the sharp edge **125** of the sharp blade **115**. A deep void **165** between the row of the outer comb **145** and the planar surface of the sharp blade **115**. When the sharp blade **115** is flexed a void is inside of the inner guard inside end **235** and the sharp blade **115** as see in FIG. **42-44**.

[0273] FIGS. **42-44** illustrate close up side views of the circled portion of the blade group **265** previously illustrated and described in the prior FIGS. **39-44**, each at different angles M. In FIGS. **42-44** a degree of angle between a midpoint of a flexing portion of the sharp blade **115** is referenced as flexing midpoint S and the angle of midpoint S and is illustrated with a dashed line. A cutting surface of skin convex T is referenced as surface Z and illustrated with a dashed lined to illustrate the surface angle of surface Z. The preferred angle of midpoint S in relation to the surface Z is referenced as angle R. Angle R is preferred to have an angle of about 35 degrees or less. In the previous FIGS. **39-41** we learned that angle M may range from about 20-75 degrees. It can be seen in FIGS. **42-44** that despite the wider ranges of angle M, angle R remains at an angle between 20-35 degrees. The embodiments of FIGS. **39-44**, when at 20 degrees for both M and R, assume the non-flexing sharp blade **115** is not flexed. As the handle angle M increases, the sharp blade **115** flexes keeping its change of angle R smaller than the change of handle angle M. Meanwhile, in the embodiments of FIGS. **42-44** the support **275** helps keeps the handle angle M within its own range of 20-70 degrees. In summary, when the safety razor **105** is stroking over hills and valleys at various angles the quality of the preferred angle R is not altered nor disturbed. This allows a user more flexibility when shaving their back side, for example, and it is very difficult for a user to not shave effectively. In FIGS. **42-44** it can be seen there are shorn hairs being cut near the leading side of the blade group **265**.

[0274] FIGS. **45-46** illustrate side views of a safety razor **105** for two-point discrimination removably attaching with an elongated handle **315** having a handle clip **365** and along a skin plane A with a blade group **265** and a support **275** and the elongated handle **315** having an inner side **485** and an outer side **475**. The inner guard **135** can be shaped as a plate running next to and continuously alongside on a trailing side of the sharp blade **115**. The outer comb **145** can be shaped as a plate running next to and continuously alongside on a leading side of the sharp blade **115**. In FIG. **45-46** the support **275** takes the form a blade group and both support **275** and blade group **265** comprising a sharp blade **115** with a sharp edge **125** and an inner guard **135** parallel to the sharp blade **115** opposite an outer comb **145** wherein the outer comb **145** parallel to the sharp blade **115** on a leading side of the sharp blade **115** and a substrate structure **215** adapted to hold the blade group **265** and the support **275** on a front surface **375** of the substrate structure **215** opposite a rear surface **385** and the blade group **265** and support **275** spaced with a tactile discrimination distance **285** allowing a distance sufficient to achieve two-point discrimination on the skin of a user between the blade group **265** and support **275**. The safety razor **105** for two point discrimination having a top side **335** and a bottom side **345** wherein the top side **335** is opposite the bottom side **345**. Inner guard **135** having an outer edge **185** and a trailing opening J inside of the outer edge **185** and the sharp edge **125** of the sharp blade **115**. Outer comb **145** having an inside edge **195** and a leading opening G inside of the inside edge **195** and the sharp edge **125** of the sharp blade **115**. The trailing opening J is referred to a trailing opening since when the safety razor **105** is performing a shaving stroke the trailing opening J is always trailing the leading opening G. However, in FIG. **45** it can be seen that a top side **595** of the blade group **265** and the top side **595** of the support **275** are directed in opposite directions of one another. The top side **595** of the support **275** is directed towards the top side **335** while the top side **595** of the blade group **265** is directed towards the bottom side **345** of the safety razor **105**. This means that when a user is holding the elongated handle **315** and pulling the safety razor **105** across their backside the blade group **265** is shaving while the support **275** is not shaving. Just the opposite, the when user is holding the elongated handle **315** and is pushing the safety razor **105** across their backside the support is shaving while the blade group **265**

is not shaving. This particular method is beneficial as the user may save much time between shaving strokes.

[0275] In FIGS. **45-46** the substrate structure **215** adapted to hold the blade group **265** and the support **275** on the front surface **375** of the substrate structure **215** with the blade group **265** and the support **275** spaced a distance sufficient to achieve two-point discrimination on the skin of a user between the blade group **265** and the support **275**. The support **275** and blade group **265** extend from the front surface **375** of the substrate structure **215** at a height X sufficient to avoid loose skin of the user touching and rubbing the front surface **375** of the substrate structure **215** which would interfere with a shaving stroke. The height from tips of each of the blade group **265** and the support **275** to the front surface **375** of the substrate structure **215** is referenced as height X and is about 3.81 millimeters or more to avoid the loose skin of the user touching the front surface **375** of the substrate structure **215** and wherein the substrate structure **215** holds the blade group **265** and the support **275** spaced a distance about 35 millimeters or more. The front surface **375** of the substrate structure **215** comprising one or more grooves parallel from each other and adapted to removably hold at least one blade group **265** and support **275**. Groove **305** and secondary groove **675** allow a user an option to choose a distance between the blade group **265** and support **275**. The rear surface **385** of the substrate structure **215** comprising a handle attachment **295**. It is preferred that the substrate structure **215** adapts the blade group **265** at an angle of about 0-75 degrees in relation to the front surface **375** of substrate structure **215**.

[0276] The support **275** may take the form of a blade group or an alternative embodiment having a least one blunt protrusion sufficient for safely poking into the skin surface A.

[0277] Tactile discrimination distance **285** is a gap spaced inside of at least one blade group **265** and support **275**. The tactile discrimination distance **285** may have an elevation gap EE which may be deep or shallow and the distance of the tactile discrimination distance **285** between a pair of supports may vary. The tactile discrimination distance **285** allows balance and stability of the substrate structure **215** when stroking against the skin surface A. Tactile discrimination distance **285** also grants space for a tightened skin to convex and enter inside of the tactile discrimination distance **285** without rubbing against the front side of substrate structure **215** while allowing a user to maintain an effective angle between the blade group **265** the skin surface A without difficulty. The tactile discrimination distance **285** also creates an effective amount of distance between the blade group **265** and the support **275** in order to allow two-point discrimination to occur. The tactile discrimination distance **285** is inside of the blade group **265** and support **275** and the elevational gap EE is illustrated with dashed lines. Elevational gap EE allows a skin convex to enter when the safety razor **105** is pressing into the skin surface A.

[0278] In the embodiment here in FIG. **45** the top side **595** of a blade group **265** is directed towards the bottom side **345** of the substrate structure **215** while the top side **595** of the support **275** is directed towards the top side **335** of the substrate structure **215** or safety razor **105**. These arrangements may be altered in order to create alternate two point discrimination distances for shaving alternate areas of the body which will be further illustrated in the upcoming FIGS. **46-47**.

[0279] In FIG. **45** the blade group **265** and support represented as another blade group **275** each having a clip **175** for removably attaching to the substrate structure **215**. The safety razor has a substrate structure **215** according to the embodiment illustrated in FIG. **45** capable of selectively adapting different blade groups **265** and **275**, each of the different blade groups **265** and **275** having different angles in relation to the substrate structure **215**. The angles of the different blade groups **265** can be opposite angles relative to the substrate structure **215**, as illustrated. The angles can also be different from one another for at least two blade groups **265** and **275** when three or more blade groups. The opposite angle can be accommodated by a user merely inserting or sliding in one of the blade groups in an opposite direction from the other. Having a first and second blade group as illustrated in FIG. **45** allows for the safety razor **105** to shave hair when a user is both pulling and pushing the safety razor across the skin.

[0280] As seen in FIG. 46 the support 275, which is taking form of a secondary blade group, has been turned a 185 degrees wherein the top side 595 of the support 275 is now facing the bottom side 345 of the safety razor 105. In FIG. 46 it can be easily seen the tactile discrimination distance 285 distance is much less in comparison to the prior FIG. 45 between the blade group 265 and support 275 for two-point discrimination. A user may now use the two point discrimination on an area that requires less of a tactile discrimination distance 285 distance in comparison to FIG. 45. Alternate embodiments or arrangements of the blade group 265 and support 275 may exist to create alternate tactile discrimination distance 285 distances. Allowing a user the option to create alternate tactile discrimination distance 285 distances allows a user to apply two-point discrimination on alternate areas of the body since different areas on the body require different distances between two points.

[0281] FIGS. 47-48 illustrate side views of an elongated handle 315 having a handle clip 365 and said handle 315 is removably attaching to a safety razor 105 for two-point discrimination according to an embodiment having a substrate structure 215 with a front surface 375, a rear surface 385, a top side 335, a bottom side 345, wherein the front surface 375 is opposite the rear surface 385 and the top side 335 is opposite the bottom side 345 and the rear surface 385 having a handle attachment 295 and a first groove 305, and a secondary groove 675 and a third groove 685 inside of said first groove 305 and said secondary groove 675 wherein a third groove 685 allows the option to choose multiple tactile discrimination distance 285 distances between at least one blade group 265 and support 275 when carrying out two-point discrimination. In FIG. 47 a support 275 taking form of an electrical trimmer 277. In cases where a user is extremely hairy it would prove beneficial to have the support 275 be an electrical trimmer 277 ran by a battery 655 or an electrical power cord that would allow a user to trim back hair and body hair to a lesser level prior to applying the blade group 265. In the same way it is common for a man to trim his beard prior to shaving with razor designed to shave one's face it would also prove beneficial for those who wish to trim their back or body hair prior to applying the blade group 265. The blade group 265 and support 275 having a clip 175 for attaching to the substrate structure 215. A tactile discrimination distance 285 is also illustrated inside the tip of the blade group 265 and the support 275. Although a user may replace the blade group 265 a support 275 in FIG. 47 takes the form of an electric trimmer 277. It is more beneficial to have both the support 275 taking form of an electrical trimmer 277 may lead when stroking the safety razor 105 against a skin surface in order to first trim the hair down with the blade group 265 trailing the support 275 embodied as electric trimmer 277 in order to then closely shave the trimmed hair that was trimmed by the support 275 taking the form of an electric trimmer 277.

[0282] In FIG. 48 a support 275 takes the form of an interchangeable lubricating strip 278 according to an embodiment. In cases where a user wishes to wet shave or shave with the presence of water with a shaving lubrication it would be beneficial for a user to removably hold the support 275 taking form of an interchangeable lubricating strip. An interchangeable lubricating strip 278 is commonly used with safety razors designed for a user's face, however, it is not common to have an interchangeable lubricating strip 278 functioning as the support 275 as seen in FIG. 48. Most safety razors found in most markets have a lubricating strip 278 attached with a safety razor and both safety razor and lubricating strip 278 are disposable. The interchangeable lubricating strip 278 may also contain a solid or liquid soap substance for lubrication. In my invention a user may choose to not dispose of the substrate structure 215 but rather dispose of the support 275 taking the form of an interchangeable lubricating strip 278.

[0283] FIGS. 49-50 illustrate front views of a safety razor 105 for two-point discrimination having a top side 335, a bottom side 345, a safety razor left side 505, a safety razor right side 515, wherein the top side 335 is opposite the bottom side 345 and the safety razor left side 505 is opposite the safety razor right side 515. The safety razor 105 having a front surface 375 with a blade group 265 and a support 275 wherein the blade group 265 and support 275 are separated with a tactile

discrimination distance **285** at a distance sufficient for two-point discrimination. A channel **975** is inside the blade group **265** and the support **275** allowing alternate distances between the blade group **265** and the support **275**. In FIGS. **49-50** the support **275** having a lock and release **965**. However, in an alternate embodiment the blade group **265** may move through the channel **975** as well. The blade group **265** having an inner guard **135**, an outer comb **145** and a sharp blade **115**. In FIGS. **49-50** the support may comprise at least one blunt protrusion **276** for safely poking into the skin surface A. Furthermore, the tip of the blade group **265** may also have a blunt protrusion. The support **275** may comprises more than one blunt protrusion **276** wherein each blunt protrusion **276** may be at staggered locations. In fact, there may be three blunt protrusions **276** at staggered locations.

[0284] Finger depressions **405** are illustrated in FIGS. **49-50** along the bottom side **345** of the safety razor **105**. The safety razor **105** may be removably detached from the elongated handle in order for a user to grasp the safety razor **105** and shave with said safety razor **105** against easy-to-reach areas such as the chest or shoulder area. The finger depressions **405** allow a user to more easily grasp the safety razor **105**. The finger depressions **405** may, in an alternate embodiment, be on the top side **335**, the safety razor left side **505** or the safety razor right side **515**. In FIG. **50** a user's hand is illustrated with dashed lines in order to illustrate how a user may press the support **275** or the lock and release **965** of the support **275** and may move the support **275** through the channel **975** and closer to the blade group **265**. Furthermore, it can be seen that the tactile discrimination distance **285** in FIG. **50** has become a lesser distance in comparison to FIG. **49**. In FIGS. **49-50** the channel **975** stretches vertically from the top side **335** to the bottom side **345** of the safety razor **105** substrate structure **215**. It can be seen that in FIGS. **49-50** an alternate embodiment is presented wherein the inner guard **135** may be embodied as a comb inside of the outer comb **145**. An inner guard **135** with a comb may allow a user to have multiple edges on the inner guard **135** tip which may help indenting into the skin during shaving. Furthermore, when the inner guard **135** has a comb, the inner guard **135** may better exfoliate and removing dead skin during the shaving process since the inner guard **135** with a comb has multiple points on the inner guard **135** tip for dragging against the dead skin surface.

[0285] Having a channel **975** that is parallel with the front surface allows the height X of both the blade group **265** and the support **275** to remain somewhat equal. In another embodiment the channel **975** may be at an angle in relation to the front surface of the safety razor **105**. This allows the height X of the blade group **265** to become different than the height X of the support **275** which will be further illustrated in the upcoming FIGS. **51-52**.

[0286] FIGS. **31-32** illustrate close up side views of a safety razor and elongated handle according to embodiments of the present inventions. The elongated handle **315** has a handle clip **365** removably attaching to a safety razor **105** for two-point discrimination along a skin surface plane A and the safety razor **105** having a blade group **265** and a support **275** according to an embodiment of the present inventions. The safety razor **105** having a top side **335**, a bottom side **345**, a front surface **375**, and a rear surface **385**, wherein the top side **335** is opposite the bottom side **345** and the front surface **375** is opposite the rear surface **385**. The rear surface **385** having a handle attachment **295** for removably attaching to a blade attachment of the elongated handle **315**. The safety razor **105** having a substrate structure **215** for removably attaching the blade group **265** and the support **275** wherein the blade group **265** and support **275** are separated with a tactile discrimination distance **285** at a distance sufficient for two-point discrimination. The tactile discrimination distance **285** having an elevational gap EE inside the tactile discrimination distance **285** which may be deep or shallow. A height X measured from the front surface **375** to the tips of the blade group **265** or support **275**. A channel **975** is inside the top side **335** and the bottom side **345** of the safety razor **105** and inside the front surface **375** and the rear surface **385** and said channel **975** allowing alternate distances for two-point discrimination between the blade group **265** and the support **275**. In FIG. **51** the channel **975** is at an alternate angle in relation to the front

surface **375** of the substrate structure **215** or safety razor **105**. This allows multiple alternate angles between the midpoint H of the blade group **265** and support **275** in relation to the skin plane A. For example, in FIG. **51** the midpoint H in relation to the skin surface A is 30 degrees while in FIG. **52** the midpoint H in relation to the skin surface A is 40 degrees. Not only has the angle of the midpoint H in relation to the skin surface A changed, when comparing FIG. **51** to FIG. **52**, but also in FIG. **52** the tactile discrimination distance **285** has become lesser in distance when comparing to FIG. **51**. Furthermore, it can be seen that the height X between the front surface **375** and the tip of the support **275** is greater than the height X between the front surface **375** and the tip of the blade group **265**. In another alternate embodiment the channel **975** may not be at an angle in relation to the front surface **375** of the safety razor **105** but may be parallel with the front surface **375**. This allows the support **275** and blade group **265** to be allowed multiple distances from each other without altering the angle between the midpoint H and the skin surface A.

[0287] In FIGS. **51-52** the blade group **265** and support **275** embodied as a blade group comprising at least one sharp blade **115** comprising a sharp edge **125** facing towards a skin surface A comprising an outer comb **145** comprising an inside edge **195**, an inner guard **135** comprising an inner guard outer edge **185**. Both the blade group **265** and the support **275** having bottom side **605** and a top side **595** where a midpoint H is embodied. A trailing opening J wherein the trailing opening J is inside of the outer edge **185** and the sharp edge **125** of the sharp blade **115**. A leading opening G wherein the leading opening G is inside of the inside edge **195** and the sharp edge **125** of the sharp blade **115**. A portion of the inner guard **135** inside of the outer edge **185** and sharp edge **125** is removed in order to create a trailing opening J inside of outer edge **185** and a sharp edge **125** of a sharp blade.

[0288] FIGS. **53-55** illustrate a close up cross-sectional view of a blade group **265** according to embodiments of the present inventions. A blade group **265** comprising at least one sharp blade **115** comprising a sharp edge **125** facing towards a skin surface A comprising an outer comb **145** comprising an inside edge **195**, an outer comb outer wall **155**, and an outer comb inside wall **645** on the inside of the outer comb **145** and inside of the sharp edge **125** and inside edge **195** and an inner guard **135** comprising an inner guard outer edge **185**, an inner guard inside end **235** and an inner guard inside wall **665** of the inner guard **135** inside an outer edge **185** and an inner guard inside end **235**. The comb inside wall **645** is adjacent to the sharp blade **115** and inside the inside edge **195** and sharp edge **125** of the sharp blade **115** in order to be a barrier for a skin convex during a shaving stroke. Inner guard inside end **235** is embodied where the inner guard **135** and the sharp blade **115** meet. An inside portion of the outer comb **145** removed in order to create a deep void **165**. The sharp blade **115** is fixedly anchored on a sharp blade end **225** opposite the sharp edge **125** of the sharp blade **115**. A base **205** is positioned to create a level of distance between said base **205** and the sharp edge **125** of the sharp blade **115** in order to enable a controlled level of flexibility with the sharp blade **115**. The deep void **165** is spaced intermediately of the outer comb **145** and sharp blade **115**. Deep void **165** thickness allowing a level of control over the flexibility of the sharp blade **115** as well as over-exposure of the sharp blade **115**. Deep void **165** having a thickness which is represented as K. Thickness K of deep void **165** is about 0.7262 millimeters or less. In a preferred embodiment distance K is 0.381 millimeters. Thickness K of deep void **165** may run thicker but the danger of enabling the sharp blade **115** to become like a dagger in relation to the skin surface becomes increasingly probable. The level of distance of the deep void **165** between the base **205** and the sharp edge **125** of the sharp blade **115** is referenced as L. The distance L is about 4.57 millimeters or less. A preferred distance of distance L is about 2.03 millimeters. Distance L may be less or greater than the preferred distance.

[0289] An inner rearward distance B from the sharp edge **125** of the sharp blade **115** to the inner guard edge of the inner guard **135** in relation to an outer rearward distance N from the inside edge **195** of the outer comb **145** to the sharp edge **125** of the sharp blade **115** has a ratio of about 1. In other words, in this embodiment, the inner rearward distance B and the outer rearward distance N

are substantially the same. The inner rearward distance B from the sharp edge **125** of the sharp blade **115** to the inner guard edge of the inner guard **135** is about 0.508 mm to about 1.016 mm. A preferred inner rearward distance B from the sharp edge **125** of the sharp blade **115** to the inner guard **135** is about 0.762 mm. Also, the outer rearward distance N from the inside edge **195** of the outer comb **145** to the sharp edge **125** of the sharp blade **115** is about 0.508 mm to about 1.016 mm. A preferred outer rearward distance N from the inside edge **195** to the sharp edge **125** is about 0.762 mm. In this discussion of an additional embodiment the diagonal distance **985**, diagonal distance J, and diagonal distance G are also affected and have alternate dimensions as well. Diagonal distance **985** may be about 1.54 mm to about 2.54 mm. A preferred diagonal distance **985** is about 2.3622 mm. Diagonal distance J may be about 0.762 mm to 1.6 mm. A preferred distance J is about 1.4986 mm. Diagonal distance G may be about 0.254 mm to about 0.889 mm. A preferred diagonal distance G is about 0.8636 mm. Furthermore, the inner guard **135** has an inside end **235** and an outer edge **185** wherein the distance between the inner guard **135** inside end **235** and the outer edge **185** is considered the inner guard **135** inside wall **665**. The inside wall **665** distance is referenced as distance DD. Distance DD is about 0.381 mm to about 0.889 mm. A preferred distance DD is about 0.61 mm. The distance DD is the same or greater than a thickness “K” of a deep void **165**. Note that diagonal distance J is substantially equal or greater than distance G. Note that the skin convex enters and stretches inside of the outer edge **185** and inside edge **195** it is preferable to have a greater diagonal distance J in comparison to diagonal distance G. Having a greater diagonal distance J allows the stretching skin convex to press against the sharp blade **115** and bending the sharp blade **115** towards the inside of the outer comb **145**. If diagonal distance J was less than diagonal distance G the skin convex will have a harder time pressing the sharp blade **115** towards the inside of the outer comb **145** and the sharp blade **115** becomes more likely to poke into the skin as a dagger instead of at an cutting angle between the sharp edge **125** of the sharp blade **115** and the skin surface.

[0290] The inner edge of the inner guard **135** and the inside edge **195** of the outer comb **145** in practice are blunt or curved edges because no corner is perfectly sharp or square. If the inner edge of the inner guard **135** and the inside edge **195** of the outer comb **145** were perfectly sharp or square, they would risk cutting into the skin or feel uncomfortable. That being said, there may be at a slightly square edge sufficient to indent and grip the skin in order for the skin inside of the inside edge **195** and the inner guard **135** to stretch. These ends are the outermost horizontal dimension to the end or tip of the inner guard **135** or the outer comb **145**. Therefore the inner rearward distance B and outer rearward distance N are stated measured from respective ends of the inner guard **135** and the outer comb **145**.

[0291] It should be understood that outer comb inside wall **645** creates a barrier for a skin surface convex to enter inside of the inside edge **195** and outer edge **185**. The outer comb **145** having an outer wall **155** which in another embodiment may also be rounded with an arc instead of a straight wall. The midpoint of a portion of the non-flexing sharp blade **115** is referred to as midpoint H which is illustrated with a straight or flat dashed line. In FIGS. 53-55 the inner guard **135** and outer comb **145** are not indenting into the skin surface A and thus the sharp blade **115** is not pressing against the skin surface A and the sharp blade **115** is not flexing.

[0292] As seen in FIGS. 53-55 a portion of the inner guard **135** inside of the outer edge **185** and sharp edge **125** is removed in order to create a trailing opening J inside of outer edge **185** and a sharp edge **125** of a sharp blade. In FIGS. 53-55 the trailing opening J is illustrated as a dashed triangle inside of the outer edge **185** of the inner guard **135** and the sharp edge **125** of the sharp blade **115**. The trailing opening J cross sectional has three triangular corners or vertices which have three walls but it is not a perfect triangle being that the three walls or sides of the vertices are not always flat. This is especially true of the sharp blade **115** and the skin surface A which both flex under pressure. The sharp blade **115**, which forms one of the walls or sides, will flex and bend which is key in situations where a less rigid blade is necessary to create a softer shaver against a

skin surface A. The inner guard inside wall **665** of inner guard **135** which starts from the outer edge **185** and ends at the inner guard inside end **235** of the inner guard **135** creates a second wall or side. The inner guard inside wall **665** of inner guard **135** does not need to be a straight wall but in another embodiment may be rounded with an arc. The skin surface A is the third and final wall or side which also deforms and will be convex. The skin surface A starts from the sharp edge **125** and ends at the outer edge **185**. The trailing opening J allows the skin to deform and tighten itself in order for the sharp blade **115** to access the base of a hair which results in a shave that leaves a smooth skin surface after a shaving stroke. In FIGS. **53-55** the first of the vertices is where the inner guard inside end **235** and the sharp blade **115** meet. The second of the vertices is where the sharp blade **115** and the skin surface plane A intersect. The second vertices may also be where the sharp edge **125** of the sharp blade **115** and the skin surface plane A meet. The third of the vertices is where the skin surface A and the outer edge **185** of the inner guard **135** meet. The vertices work together to form the planes that create trailing opening J or void allowing for a sufficient opening or void for tightening skin to enter and be convex. It should also be known that the inner guard inside wall **665** controls the amount of skin convex allowed inside as does the outer comb inside wall **645**. In FIGS. **53-55** the trailing opening J allows for a sufficient void or space for tightening skin to enter and be convex in order for the sharp blade **115** to gain access to a base of a hair. A leading opening G is inside of the inside edge **195** and the sharp edge **125** of the sharp blade **115**. Leading opening G allows a sufficient opening in order for a skin convex to safely press against the sharp edge **125** of the sharp blade **115** when pressing the blade group **265** against the skin surface A. In FIGS. **53-55** the blade group **265** is not yet pressing into the skin surface A and thus the sharp blade **115** is illustrated in a stationary position.

[0293] The first dimension of opening G across the gap thickness K measured diagonally between the sharp edge **125** of the sharp blade **115** and the inside edge **195** of the outer comb **145** is less than or equal to a second dimension of the opening J inside the inner guard **135** measured diagonally between the sharp edge **125** of the sharp blade **115** and the outer edge **185** of the inner guard **135**. The leading opening G is inside the inside edge **195** of the outer comb **145** and the sharp edge **125** of the sharp blade **115**. The distance of G is the diagonal distance between the inside edge **195** of the outer teeth **145** and the outer edge **185** of inner guard **135** and is about 1.524 millimeters or less. A preferred distance of G or the diagonal distance between the inside edge **195** of the outer teeth **145** and the outer edge **185** of the inner guard **135** is about 0.889 millimeters.

[0294] The trailing opening J inside the outer edge **185** of the inner guard **135** and the sharp edge **125** of the sharp blade **115**. The distance of J is the diagonal distance between the outer edge **185** of inner guard **135** and the sharp edge **125** of the sharp blade **115** and is about 1.905 millimeters. A preferred distance of J or a diagonal distance between the outer edge **185** of the inner guard **135** and the sharp edge **125** of the sharp blade **115** is about 1.4224 millimeters.

[0295] A diagonal distance inside the inside edge **195** of the outer comb **145** and the outer edge **185** of the inner guard **135** is referenced as distance **985**. Distance **985** is 2.286 or less. A preferred distance of **985** or the diagonal distance between the inside edge **195** of the outer teeth **145** and the outer edge **185** of inner guard **135** is about 1.7272 millimeters.

[0296] Note that in FIGS. **53-55** the angle of the outer edge **185** and the inside edge **195** in relation to the midpoint H is referred to as angle **995**. Angle **995** may be 40 degrees or less. A preferred angle of angle **995** is about 20 degrees. FIGS. **53-55** illustrates a range of alternate angle that angle **995** may take form. For instance, in FIG. **53** angle **995** is 20 degrees, in FIG. **54** angle **995** is 30 degrees while in FIG. **55** angle **995** is 40 degrees.

[0297] An angle between the skin plane A and the outer wall **155** of outer comb **145** is referenced as vertex O. Vertex O is an angle created in order to allow the outer comb **145** to better indent into the skin surface A allowing the blade group **265** to shave properly.

[0298] FIGS. **56-57** illustrates close up views of a blade group rear surface **625** of a blade group **265** having a top side **595**, a bottom side, **605** wherein the top side **595** is facing a skin plane A

opposite the bottom side **605**. The blade group **265** having an outer comb **145** with an inside edge **195** and a sharp blade **115** with a sharp edge **125** and the sharp blade **115** is opposite the blade group rear surface **625**. As can be seen in FIGS. **56-57** the outer comb **145** having a tooth end **775**, a tooth length **785** and a tooth width **795** wherein the tooth length **785** illustrates the length of the outer teeth **145** or outer comb **145** stretching from the tooth end **775** to the inside edge **195** of the outer comb **145**. The tooth width **795** illustrates the width of the opening gap inside of at least two teeth **145**. In FIG. **56** it can be seen that hair **415** is illustrated inside of the tooth end **775** and the sharp edge **125** of the inside edge **195**. Although in FIG. **56** the blade group **265** is not pressing into the skin plane A it can be seen that the hair **415** may move inside of the tooth end **775** and the inside edge **195** when approaching the skin surface A which often times may cause hair **415** to clog and get stuck inside of the blade group **265** after being shorn as in FIG. **57**. In order for a user to easily clean the blade group **265** with a cleaning brush it is preferred that the tooth end **775** be inside of the sharp edge **125** of the sharp blade **115** as illustrated in FIGS. **56-57**. As it can be seen in FIG. **57** after the user has performed a shaving stroke the hairs **415** have collected inside of the tooth end **775** and inside edge **195**. However, since the tooth length **785** stretching from the inside edge **195** to the tooth end **775** inside the sharp edge **125** the user is able to access all of the shorn hairs collected inside the sharp blade **115** and outer comb **145**.

[0299] FIGS. **58-59** illustrate an eye-level view of the bottom side **345** of a safety razor **105** for two-point discrimination according to an embodiment where a blade group **265** has a sharp blade **115** and an inner guard **135** parallel to the sharp blade **115** on a trailing side of the sharp blade **115** opposite the outer comb **145** wherein an outer comb **145** parallel to the sharp blade **115** on a leading side of the sharp blade **115** and a substrate structure **215** having a groove **305** and adapted to hold the blade group **265** and a support on the front surface **375** of the substrate structure **215** opposite a rear surface **385**. In FIGS. **58-39** the blade group **265** having a left attachment side **545** and a right attachment side **555** wherein the left attachment side **545** is opposite the right attachment side **555** and a user's hand, which is illustrated with a dashed line, is removably holding the right attachment side **555** and sliding said blade group **265** along a substrate structure **215** and towards a safety razor left side **505** of the blade group **265** and is sliding the blade group **265** into the groove **305**. In the illustration in FIGS. **58-39** the groove **305** of substrate structure **215** having a track **705** while a blade group **265** having a track attachment slot **715** close to the bottom side **605** of the blade group **265** which may have an opening in order for the track **705** to insert into the track attachment slot **715** while a bottom side **605** opposite a top side **595** of the blade group **265** is entering the groove **305** from the safety razor right side **515** opposite a safety razor left side **505**. Track attachment slot **715** may have a track attachment secondary slot **725** as illustrated in FIGS. **58-59**. The blade group **265** top side **595** is opposite the bottom side **605** and the top side **595** is a portion of the blade group **265** touching a skin surface of a user during a shaving stroke during two-point discrimination. The length of the blade group **265** or a support **275** referenced as support length **575** is the length of the blade group **265** or support **275** inside of the left attachment side **545** and the right attachment side **555**. The length of the support length **575** is about 36.322 millimeters or greater. A preferred support length **575** is about 72.644 millimeters.

[0300] A substrate structure **215** having an anchor **695** and a lock and release lever **755** with a spring **765** that when said lock and release lever **755** is pushed in a container **745** by a user the anchor **695** may move towards the rear surface **385** of the safety razor **105** and when a user releases the lock and lock and release lever **755** the spring **765** will move the anchor **695** may move towards the front surface **375** of a safety razor **105**. In another embodiment the anchor **695** may move towards the safety razor left side **505** or the safety razor right side **515**. As seen in FIG. **59** this functionality allows the anchor **695** to move inside the track attachment secondary slot **725** when the anchor **695** moves into the track attachment secondary slot **725** the blade group **265** or support are removably interlocking with substrate structure **215** forming the safety razor **105** for two-point discrimination. As seen in FIG. **59** the anchor **695** is removably interlocking with the track

attachment secondary slot **725** which small arrows are illustrating the spring **765** has allowed the anchor **695** to snap into the track attachment secondary slot **725**. It should be stated that in another alternate embodiment, the left attachment side **545** and right attachment side **555** of a safety razor **105** may simultaneously removably attach into place with the safety razor left side **505** and the safety razor right side **515** when entering from the front surface **375** of the safety razor **105**. In yet another embodiment the lock and release lever **755**, spring **765** and anchor **695** may interlock with a blade group **265** and support **275** which are one piece and not separate. In another embodiment a lock and release lever **755**, spring **765** and anchor **695** may be embodied on the safety razor right side **515** opposite a safety razor left side **505** or on the front surface **375** or rear surface **385** of the safety razor **105**. In yet another embodiment, the handle attachment **295** on the rear surface **385** of a substrate structure **215** having a handle clip insert **635** for when attaching a safety razor **105** to an elongated handle for shaving. In FIG. **59** is an illustration wherein a user has completely attached the blade group **265** to the substrate structure **215**. As seen in FIG. **59** a secondary anchor **735** may be embodied near the right attachment side **555** of the substrate structure **215** interlocking the blade group **265** or in another embodiment a support **275** into place. In another embodiment the secondary anchor **735** may be on the left attachment side **545**. Also, in alternate embodiments the other parts found in FIGS. **58-59** be may located on opposite side of ends of the substrate structure **215** and will still perform effectively.

[0301] FIG. **60** illustrates a front view of an alternate embodiment of a safety razor **105** with a skeletal structure. The safety razor **105** has a top side **335**, a bottom side **345**, a safety razor left side **505**, a safety razor right side **515**, wherein the top side **335** is opposite the bottom side **345** and the safety razor left side **505** is opposite the safety razor right side **515**. The safety razor **105** having a front surface **375** with a blade group **265** and a support **275** wherein the blade group **265** and support **275** are separated with a tactile discrimination distance **285** at a distance sufficient for two-point discrimination. In FIG. **60** the support **275** is embodied as a blade group and both blade group **265** and support **275** having a sharp blade **115** inside an inner guard **135** and outer comb **145**. In FIG. **60** the safety razor **105** is has a skeletal structure which multiple safety razor skeletal openings **996**. Having a skeletal structure offers a light weight safety razor **105** which may be more efficient for shaving as well as saves cost in manufacturing due to the absent amount of material that is saved. The safety razor **105** having a handle attachment **295** that can be seen through at least one safety razor skeletal opening **996** on the rear surface of the safety razor **105** opposite the front surface **375**. Furthermore, illustrated are finger depressions **405** near the bottom side **345** of the safety razor **105**.

[0302] In FIG. **61** illustrates a chart depicting the many level of distances to create two-point discrimination on the human male body locations in which these distances are performed in order for effective two-point discrimination communication. FIG. **61** is a graphical representation of the data represented in Table 1 discussed above with respect to FIGS. **27** and **28**. The different parts of the body illustrated in FIG. **61** are the a hallux **805**, a sole **815**, a calf **825**, a thigh **835**, a belly **845**, a back **855**, a breast **865**, a upper lip **875**, a shoulder **885**, a nose **935**, a forehead **905**, a forearm **915**, a upper arm **925**, a cheek **895**, a palm **945** and fingers **955**.

[0303] FIGS. **62-63** illustrate close up side views of an elongated back shaver handle **315** and a safety razor **105** removably attaching to the elongated back shaver handle **315** with a pivot mechanism **296** according to embodiments of the present inventions. The elongated handle **315** is generally an s-shaped elongated member **315** having a surface along a length of the elongated handle **315** defining a blade end **325**. The safety razor **105** having a front surface **375** and a rear surface **385** wherein the front surface **375** is opposite the rear surface **385** and in FIGS. **42-43** the rear surface **385** if facing the elongated back shaver handle **325**. A handle attachment **295** is on the rear surface **385** of the substrate structure **215** and removably attaching the safety razor **105** with the handle **315**. A pivot mechanism **296** is located near the blade end **325** and allowing the safety razor **105** to move and pivot at alternate angles when pressed against a skin surface A. In an

alternate embodiment the pivot mechanism **296** can also be embodied closer or further from the rear surface **385** of the substrate. Also, in another alternate embodiment the pivot mechanism **296** may also be located entirely on the safety razor **105** or the handle **315** or may be located on both in order to have the pivot work properly in allowing the safety razor **105** to pivot at alternate angles when pressed against the skin. The handle **315** having a handle clip **365** to lock and release the safety razor **105** for tactile feedback in the handle attachment **295**. The safety razor having a top side **335** and a bottom side **345** wherein the top side **335** is opposite the bottom side **345**.

[0304] The safety razor **105** has a blade group **265** and the support **275** spaced a distance sufficient to achieve tactile feedback on the flat skin plane A of a user and a tactile discrimination distance **285** between the blade group **265** and support **275**. A tactile discrimination distance **285** is any distance gap spaced inside of at least the blade group **265** and the support **275** and the tactile discrimination distance **285** may have a deep or shallow elevation which is referenced as elevation gap EE. The tactile discrimination distance **285** may be a tactile distance for two-point discrimination. In FIGS. **42-43** the support **275** takes the form a blade group and each blade group comprising a sharp blade **115** with a sharp edge **125** and an inner guard **135** parallel to the sharp blade **115** with an outer edge **185** on a trailing side of the sharp blade **115** opposite an outer comb **145** having an inside edge **195** wherein the outer comb **145** parallel to the sharp blade **115** on a leading side of the sharp blade **115** and a substrate structure **215** adapted to hold the blade group **265** and the support **275** on a front surface **375** of the substrate structure **215** with the blade group **265** and support **275** spaced a distance sufficient to achieve two-point discrimination on the skin of a user between the blade group **265** and support **275**. A trailing opening J is inside the sharp blade **115** and the inner guard **135** while the leading opening G is inside the inside edge **195** and the sharp edge **125**.

[0305] Although the invention is described herein with reference to specific embodiments, various modifications and changes can be made without departing from the scope of the present inventions as set forth in the claims below. Accordingly, the specification and figures are to be regarded in an illustrative rather than a restrictive sense, and all such modifications are intended to be included within the scope of the present inventions. They can have different configurations than the examples illustrated in the drawings. Any benefits, advantages, or solutions to problems that are described herein with regard to specific embodiments are not intended to be construed as a critical, required, or essential feature or element of any or all the claims.

[0306] Any letter designations such as (a) or (b) etc. used to label steps of any of the method claims herein are step headers applied for reading convenience and are not to be used in interpreting an order or process sequence of claimed method steps. Any method claims that recite a particular order or process sequence will do so using the words of their text, not the letter designations.

[0307] Unless stated otherwise, terms such as “first” and “second” are used to arbitrarily distinguish between the elements such terms describe. Thus, these terms are not necessarily intended to indicate temporal or other prioritization of such elements.

Claims

1. A back shaver, comprising: a substrate structure having a front surface, a rear surface opposite the front surface, a top side, and a bottom side opposite the top side; an elongated channel formed in at least a portion of the front surface of the substrate structure; one or more blade groups slidably mounted in the elongated channel and configured to be secured at multiple positions along the elongated channel, each of the blade groups comprising a sharp blade, an outer comb, and an inner guard; a handle attachment on the rear surface of the substrate structure; and an elongated handle removably coupled to the handle attachment, the elongated handle having a length sufficient to reach a user's back.

2. The back shaver of claim 1, wherein the elongated channel extends from the top side of the

- substrate structure to the bottom side of the substrate structure parallel to, or at an angle relative to, the front surface of the substrate structure.
3. The back shaver of claim 1, further comprising a support slidably mounted in the elongated channel and configured to be secured at multiple positions along the elongated channel, the support comprising at least one blunt protrusion.
 4. The back shaver of claim 3, wherein the one or more blade groups and the support are configured such that a user may vary the distance between any one of the one or more blade groups and the support by moving the one or more blade groups relative to the support along the elongated channel.
 5. The back shaver of claim 1, wherein the handle attachment comprises a flexible coupling for coupling the elongated handle to the substrate structure.
 6. The back shaver of claim 5, wherein the handle attachment further comprises a mechanical pivot mechanism adapted to movably couple the elongated handle to the substrate structure.
 7. The back shaver of claim 6, wherein the mechanical pivot mechanism comprises a ball joint with a socket recessed in the elongated handle.
 8. The back shaver of claim 5, wherein the flexible coupling comprises a material configured to allow the substrate structure to pivot with respect to the elongated handle.
 9. The back shaver of claim 1, further comprising a first blade group and a second blade group, wherein the first blade group and the second blade group are configured such that a user may vary the distance between the first blade group and the second blade group by moving the first blade group relative to the second blade group along the elongated channel.
-