

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250261225

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Abdelmonem; Amr et al.

METHOD AND APPARATUS FOR COLLECTING AND PROCESSING INTERFERENCE INFORMATION

Abstract

A system that incorporates the subject disclosure may perform, for example, a method for receiving interference information from each of the plurality of communication devices detecting interference information in a plurality of segments of a radio frequency spectrum, correlating the interference information of the plurality of communication devices to generate correlated information, and identifying a plurality of interferers according to the correlated information. Other embodiments are disclosed.

Inventors: Abdelmonem; Amr (Northbrook, IL), Cordone; Sean S. (Chicago, IL), Seskiewicz; Dariusz (Mundelein, IL), Myers; Bill (Buffalo Grove, IL), Komoravolu; Krishna (Aurora, IL)

Applicant: ISCO International, LLC (Schaumburg, IL)

Family ID: 51526668

Assignee: ISCO International, LLC (Schaumburg, IL)

Appl. No.: 19/192776

Filed: April 29, 2025

Related U.S. Application Data

parent US continuation 18590279 20240228 parent-grant-document US 12317304 child US 19192776

parent US continuation 17488017 20210928 parent-grant-document US 11950270 child US 18590279

parent US continuation 16572852 20190917 parent-grant-document US 11166288 child US 17488017

parent US continuation 16212836 20181207 parent-grant-document US 10798718 child US 16572852

parent US continuation 14927650 20151030 parent-grant-document US 10187190 child US 16212836
parent US continuation 14623254 20150216 parent-grant-document US 9214983 child US 14927650
parent US continuation 13957897 20130802 parent-grant-document US 8989235 child US 14623254
us-provisional-application US 61792184 20130315

Publication Classification

Int. Cl.: **H04W72/541** (20230101); **H04B1/10** (20060101); **H04B1/709** (20110101); **H04B1/71** (20110101); **H04B1/7103** (20110101); **H04B7/26** (20060101); **H04B15/00** (20060101); **H04B17/00** (20150101); **H04B17/21** (20150101); **H04B17/26** (20150101); **H04B17/327** (20150101); **H04B17/345** (20150101); **H04B17/373** (20150101); **H04J11/00** (20060101); **H04L5/00** (20060101); **H04L41/069** (20220101); **H04W4/02** (20180101); **H04W4/029** (20180101); **H04W16/28** (20090101); **H04W24/02** (20090101); **H04W24/08** (20090101); **H04W24/10** (20090101); **H04W28/02** (20090101); **H04W28/04** (20090101); **H04W40/16** (20090101); **H04W52/04** (20090101); **H04W52/14** (20090101); **H04W52/24** (20090101); **H04W64/00** (20090101); **H04W72/0446** (20230101); **H04W72/0453** (20230101); **H04W72/52** (20230101); **H04W72/54** (20230101); **H04W72/542** (20230101)

U.S. Cl.:

CPC **H04W72/541** (20230101); **H04B1/1036** (20130101); **H04B1/709** (20130101); **H04B1/71** (20130101); **H04B1/7103** (20130101); **H04B15/00** (20130101); **H04B17/00** (20130101); **H04B17/21** (20150115); **H04B17/26** (20150115); **H04B17/327** (20150115); **H04B17/345** (20150115); **H04B17/373** (20150115); **H04L5/0007** (20130101); **H04L5/0026** (20130101); **H04L5/0032** (20130101); **H04L5/0073** (20130101); **H04L41/069** (20130101); **H04W4/02** (20130101); **H04W4/023** (20130101); **H04W4/029** (20180201); **H04W16/28** (20130101); **H04W24/02** (20130101); **H04W24/08** (20130101); **H04W24/10** (20130101); **H04W28/0236** (20130101); **H04W28/04** (20130101); **H04W40/16** (20130101); **H04W52/04** (20130101); **H04W52/14** (20130101); **H04W52/243** (20130101); **H04W64/00** (20130101); **H04W64/006** (20130101); **H04W72/0446** (20130101); **H04W72/0453** (20130101); **H04W72/52** (20230101); **H04W72/54** (20230101); **H04W72/542** (20230101); **H04B7/2634** (20130101); **H04B2201/709709** (20130101); **H04B2201/709745** (20130101); **H04J11/0066** (20130101); **H04L5/006** (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/590,279, filed Feb. 28, 2024, which is a continuation of U.S. patent application Ser. No. 17/488,017, filed Sep. 28, 2021 (now U.S. Pat. No. 11,950,270), which is a continuation of U.S. patent application Ser. No. 16/572,852, filed Sep. 17, 2019 (now U.S. Pat. No. 11,166,288), which is a continuation of U.S. patent application Ser. No. 16/212,836, filed Dec. 7, 2018 (now U.S. Pat. No. 10,798,718), which is a continuation of U.S. patent application Ser. No. 14/927,650 filed Oct. 30, 2015 (now U.S. Pat. No. 10,187,190), which is a continuation of U.S. patent application Ser. No. 14/623,254 filed Feb. 16, 2015 (now U.S. Pat. No. 9,214,983), which is

a continuation of U.S. patent application Ser. No. 13/957,897 filed Aug. 2, 2013 (now U.S. Pat. No. 8,989,235), which claims the benefit of priority to U.S. Provisional Application No. 61/792,184 filed on Mar. 15, 2013. All sections of the aforementioned application(s) and patent(s) are incorporated by reference herein in their entirety.

FIELD OF THE DISCLOSURE

[0002] The subject disclosure is related to a method and apparatus for collecting and processing interference information.

BACKGROUND

[0003] In most communication environments involving short range or long-range wireless communications, interference from unexpected wireless sources can impact the performance of a communication system leading to lower throughput, dropped calls, reduced bandwidth which can cause traffic congestion, or other adverse effects, which are undesirable.

[0004] Some service providers of wireless communication systems have addressed interference issues by adding more communication nodes, policing interferers, or utilizing antenna steering techniques to avoid interferers.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] Reference will now be made to the accompanying drawings, which are not necessarily drawn to scale, and wherein:

[0006] FIG. 1 depicts an illustrative embodiment of a communication system;

[0007] FIG. 2 depicts an illustrative embodiment of a frequency spectrum of a four carrier CDMA signal;

[0008] FIG. 3 depicts an illustrative embodiment of a frequency spectrum of a four carrier CDMA signal showing unequal power balancing between the four CDMA carriers and including a narrowband interferer;

[0009] FIG. 4 depicts an illustrative embodiment of a base station of FIG. 1;

[0010] FIG. 5 depicts an illustrative embodiment of a frequency spectrum of a four carrier CDMA signal having four CDMA carriers with suppression of a narrowband interferer that results in falsing;

[0011] FIG. 6 depicts an illustrative embodiment of an interference detection and mitigation system;

[0012] FIG. 7 depicts an illustrative embodiment of an interference detection and mitigation system;

[0013] FIG. 8 depicts an illustrative embodiment of signal processing module of FIG. 7;

[0014] FIG. 9 depicts an illustrative embodiment of plots of a spread spectrum signal;

[0015] FIG. 10 depicts an illustrative embodiment of a method for interference detection;

[0016] FIG. 11 depicts illustrative embodiments of the method of FIG. 10;

[0017] FIG. 12 depicts illustrative embodiments of a series of spread spectrum signals intermixed with an interference signal;

[0018] FIG. 13 depicts an illustrative embodiment of a graph depicting interference detection efficiency of a system of the subject disclosure;

[0019] FIG. 14 depicts illustrative embodiments of Long-Term Evolution (LTE) time and frequency signal plots;

[0020] FIG. 15 depicts illustrative embodiments of LTE time and frequency signal plots intermixed with interference signals;

[0021] FIG. 16 depicts an illustrative embodiment of a method for detecting and mitigating interference signals shown in FIG. 15;

[0022] FIG. 17 depicts an illustrative embodiment of adaptive thresholds used for detecting and mitigating interference signals shown in FIG. 15;

[0023] FIG. 18 depicts an illustrative embodiment of resulting LTE signals after mitigating interference according to the method of FIG. 16;

[0024] FIG. 19A depicts an illustrative embodiment of a method for mitigating interference;

[0025] FIG. 19B depicts an illustrative embodiment of a communication system utilizing the method of FIG. 19A;

[0026] FIG. 20 depicts an illustrative embodiment of a communication device that can utilize in whole or in part embodiments of the subject disclosure for detecting and mitigating interference; and

[0027] FIG. 21 is a diagrammatic representation of a machine in the form of a computer system within which a set of instructions, when executed, may cause the machine to perform any one or more of the methods described herein.

DETAILED DESCRIPTION

[0028] The subject disclosure describes, among other things, illustrative embodiments for detecting and mitigating interference signals. Other embodiments are included in the subject disclosure.

[0029] One embodiment of the subject disclosure includes a method for receiving, by a system comprising a processor, interference information from each of a plurality of communication devices detecting the interference information according to at least one adaptive threshold for detecting signal interference in a plurality of resource blocks in a radio frequency spectrum of a wireless communication system, correlating, by the system, the interference information of the plurality of communication devices to generate correlated information, detecting, by the system, a plurality of interferers according to the correlated information, identifying, by the system, a profile for each of the plurality of interferers that describes characteristics of each of the plurality of interferers, and determining, by the system, a first temporal recurrence of a first interferer of the plurality of interferers according to the interference information associated with the first interferer.

[0030] One embodiment of the subject disclosure includes a machine-readable storage medium, comprising instructions, which when executed by a processor, cause the processor to perform operations comprising receiving interference information from each of a plurality of communication devices detecting interference information in a plurality of segments in a radio frequency spectrum of a wireless communication system, correlating the interference information of the plurality of communication devices to generate correlated information, identifying a plurality of interferers according to the correlated information, and approximating a location of the plurality of interferers according to information provided by the plurality of communication devices.

[0031] One embodiment of the subject disclosure includes a communication device, comprising a memory to store instructions, and a processor coupled to the memory, wherein execution of the instructions by the processor causes the processor to perform operations comprising receiving interference information from each of the plurality of communication devices detecting interference information in a plurality of segments of a radio frequency spectrum; correlating the interference information of the plurality of communication devices to generate correlated information; identifying a plurality of interferers according to the correlated information; and presenting an interference map of the plurality of interferers according to location information provided by the plurality of communication devices.

[0032] Interference signals can be generated from various sources including bidirectional amplifiers, unintended radiation from communication equipment (e.g., faulty transmitters of the carrier or other carriers), wireless microphones, garage door openers and similar production equipment, cross-border cellular (reduced buffer zones), federal and military installations, television transmissions, intermodulation from other transmitters, intermodulation from own faulty components and connectors, and so forth.

[0033] The embodiments of the subject disclosure can be performed singly or in combination by a

mobile communication device, a stationary communication device, base stations, a wireless hub used by a satellite communication system, and/or a system or systems in communication with the base stations, the wireless hub, and/or mobile communication devices.

[0034] As shown in FIG. 1, an exemplary telecommunication system **10** may include mobile units **12**, **13A**, **13B**, **13C**, and **13D**, a number of base stations, two of which are shown in FIG. 1 at reference numerals **14** and **16**, and a switching station **18** to which each of the base stations **14**, **16** may be interfaced. The base stations **14**, **16** and the switching station **18** may be collectively referred to as network infrastructure.

[0035] During operation, the mobile units **12**, **13A**, **13B**, **13C**, and **13D** exchange voice, data or other information with one of the base stations **14**, **16**, each of which is connected to a conventional land line communication network. For example, information, such as voice information, transferred from the mobile unit **12** to one of the base stations **14**, **16** is coupled from the base station to the communication network to thereby connect the mobile unit **12** with, for example, a land line telephone so that the land line telephone may receive the voice information. Conversely, information, such as voice information may be transferred from a land line communication network to one of the base stations **14**, **16**, which in turn transfers the information to the mobile unit **12**.

[0036] The mobile units **12**, **13A**, **13B**, **13C**, and **13D** and the base stations **14**, **16** may exchange information in either narrow band or wide band format. For the purposes of this description, it is assumed that the mobile unit **12** is a narrowband unit and that the mobile units **13A**, **13B**, **13C**, and **13D** are wideband units. Additionally, it is assumed that the base station **14** is a narrowband base station that communicates with the mobile unit **12** and that the base station **16** is a wideband digital base station that communicates with the mobile units **13A**, **13B**, **13C**, and **13D**.

[0037] Narrow band format communication takes place using, for example, narrowband 200 kilohertz (KHz) channels. The Global system for mobile phone systems (GSM) is one example of a narrow band communication system in which the mobile unit **12** communicates with the base station **14** using narrowband channels. Alternatively, the mobile units **13A**, **13B**, **13C**, and **13D** communicate with the base stations **16** using a form of digital communications such as, for example, code-division multiple access (CDMA), Universal Mobile Telecommunications System (UMTS), 3GPP Long Term Evolution (LTE), or other next generation wireless access technologies. CDMA digital communication, for instance, takes place using spread spectrum techniques that broadcast signals having wide bandwidths, such as, for example, 1.2288 megahertz (MHz) bandwidths.

[0038] The switching station **18** is generally responsible for coordinating the activities of the base stations **14**, **16** to ensure that the mobile units **12**, **13A**, **13B**, **13C**, and **13D** are constantly in communication with the base station **14**, **16** or with some other base stations that are geographically dispersed. For example, the switching station **18** may coordinate communication handoffs of the mobile unit **12** between the base stations **14** and another base station as the mobile unit **12** roams between geographical areas that are covered by the two base stations.

[0039] One particular problem that may arise in the telecommunication system **10** is when the mobile unit **12** or the base station **14**, each of which communicates using narrowband channels, interferes with the ability of the base station **16** to receive and process wideband digital signals from the digital mobile units **13A**, **13B**, **13C**, and **13D**. In such a situation, the narrowband signal transmitted from the mobile unit **12** or the base station **14** may interfere with the ability of the base station **16** to properly receive wideband communication signals.

[0040] As will be readily appreciated, the base station **16** may receive and process wideband digital signals from more than one of the digital mobile units **13A**, **13B**, **13C**, and **13D**. For example, the base station **16** may be adapted to receive and process four CDMA carriers **40A-40D** that fall within a multi-carrier CDMA signal **40**, as shown in FIG. 2. In such a situation, narrowband signals transmitted from more than one mobile units, such as, the mobile unit **12**, may interfere with the ability of the base station **16** to properly receive wideband communication signals on any of the

four CDMA carriers **40A-40D**. For example, FIG. 3 shows a multi-carrier CDMA signal **42** containing four CDMA carriers **42A, 42B, 42C** and **42D** adjacent to each other wherein one of the CDMA carriers **42C** has a narrowband interferer **46** therein. As shown in FIG. 3, it is quite often the case that the signal strengths of the CDMA carrier signals **42A-42D** are not equal.

[0041] As disclosed in detail hereinafter, a system and/or a method for multiple channel adaptive filtering or interference suppression may be used in a communication system. In particular, such a system or method may be employed in a wideband communication system to protect against, or to report the presence of, narrowband interference, which has deleterious effects on the performance of the wideband communication system. Additionally, such a system and method may be operated to eliminate interference in CDMA carriers having other CDMA carriers adjacent thereto.

[0042] As shown in FIG. 4, the signal reception path of the base station **16**, which was described as receiving narrowband interference from the mobile unit **12** in conjunction with FIG. 1, includes an antenna **50** that provides signals to a low noise amplifier (LNA) **52**. The output of the LNA **52** is coupled to a splitter **54** that splits the signal from the LNA **52** into a number of different paths, one of which may be coupled to an adaptive front end **56** and another of which may be coupled to a narrowband receiver **58**. The output of the adaptive front end **56** is coupled to a wideband receiver **60**, which may, for example, be embodied in a CDMA receiver or any other suitable wideband receiver. The narrowband receiver **58** may be embodied in a 15 KHz bandwidth receiver or in any other suitable narrowband receiver. Although only one signal path is shown in FIG. 4, it will be readily understood to those having ordinary skill in the art that such a signal path is merely exemplary and that, in reality, a base station may include two or more such signal paths that may be used to process main and diversity signals received by the base station **16**.

[0043] It will be readily understood that the illustrations of FIG. 4 can also be used to describe the components and functions of other forms of communication devices such as a small base station, a femto cell, a Wi-Fi router or access point, a cellular phone, a smart phone, a laptop computer, a tablet, or other forms of wireless communication devices suitable for applying the principles of the subject disclosure. Accordingly, such communication devices can include variants of the components shown in FIG. 4 and perform the functions that will be described below. For illustration purposes only, the descriptions below will address the base station **16** with an understanding that these embodiments are exemplary and non-limiting to the subject disclosure.

[0044] Referring back to FIG. 4, the outputs of the narrowband receiver **58** and the wideband receiver **60** can be coupled to other systems within the base station **16**. Such systems may perform voice and/or data processing, call processing or any other desired function. Additionally, the adaptive front-end module **56** may also be communicatively coupled, via the Internet, telephone lines, cellular network, or any other suitable communication systems, to a reporting and control facility that is remote from the base station **16**. In some networks, the reporting and control facility may be integrated with the switching station **18**. The narrowband receiver **58** may be communicatively coupled to the switching station **18** and may respond to commands that the switching station **18** issues.

[0045] Each of the components **50-60** of the base station **16** shown in FIG. 4, except for the adaptive front-end module **56**, may be found in a conventional wideband cellular base station **16**, the details of which are well known to those having ordinary skill in the art. It will also be appreciated by those having ordinary skill in the art that FIG. 4 does not disclose every system or subsystem of the base station **16** and, rather, focuses on the relevant systems and subsystems to the subject disclosure. In particular, it will be readily appreciated that, while not shown in FIG. 4, the base station **16** can include a transmission system or other subsystems. It is further appreciated that the adaptive front-end module **56** can be an integral subsystem of a wideband cellular base station **16** or can be a modular subsystem that can be physically placed in different locations of a receiver chain of the base station **16**, such as at or near the antenna **50**, at or near the LNA **52**, or at or near the wideband receiver **60**.

[0046] During operation of the base station **16**, the antenna **50** receives CDMA carrier signals that are broadcast from the mobile unit **13A**, **13B**, **13C** and **13D** and couples such signals to the LNA **52**, which amplifies the received signals and couples the amplified signals to the splitter **54**. The splitter **54** splits the amplified signal from the LNA **52** and essentially places copies of the amplified signal on each of its output lines. The adaptive front-end module **56** receives the signal from the splitter **54** and, if necessary, filters the CDMA carrier signal to remove any undesired narrowband interference and couples the filtered CDMA carrier signal to the wideband receiver **60**.

[0047] As noted previously, FIG. **2** illustrates an ideal frequency spectrum **40** of a CDMA carrier signal that may be received at the antenna **50**, amplified and split by the LNA **52** and the splitter **54** and coupled to the adaptive front-end module **56**. If the CDMA carrier signal received at the antenna **50** has a frequency spectrum **40** as shown in FIG. **2** without any narrowband interference, the adaptive front end will not filter the CDMA carrier signal and will simply couple the wideband signal directly through the adaptive front-end module **56** to the wideband receiver **60**.

[0048] However, as noted previously, it is possible that the CDMA carrier signal transmitted by the mobile units **13A-13D** and received by the antenna **50** has a frequency spectrum as shown in FIG. **3** which contains a multi-carrier CDMA signal **42** that includes not only the four CDMA carriers **42A**, **42B**, **42C** and **42D** from the mobile units **13A**, **13B**, **13C** and **13D** having unequal CDMA carrier strengths, but also includes narrowband interferer **46**, as shown in FIG. **3**, which in this illustration is caused by mobile unit **12**. If a multi-carrier CDMA signal having a multi-carrier CDMA signal **42** including narrowband interferer **46** is received by the antenna **50** and amplified, split and presented to the adaptive front-end module **56**, it will filter the multi-carrier CDMA signal **42** to produce a filtered frequency spectrum **43** as shown in FIG. **5**.

[0049] The filtered multi-carrier CDMA signal **43** has the narrowband interferer **46** removed, as shown by the notch **46A**. The filtered multi-carrier CDMA signal **43** is then coupled from the adaptive front-end module **56** to the wideband receiver **60**, so that the filtered multi-carrier CDMA signal **43** may be demodulated. Although some of the multi-carrier CDMA signal **42** was removed during filtering by the adaptive front-end module **56**, sufficient multi-carrier CDMA signal **43** remains to enable the wideband receiver **60** to recover the information that was broadcast by mobile unit(s). Accordingly, in general terms, the adaptive front-end module **56** selectively filters multi-carrier CDMA signals to remove narrowband interference therefrom. Further details regarding the adaptive front-end module **56** and its operation are provided below in conjunction with FIGS. **6-20**.

[0050] FIG. **3** depicts another example embodiment of the adaptive front-end module **56**. As noted earlier, the adaptive front-end module **56** can be utilized by any communication device including cellular phones, smartphones, tablets, small base stations, femto cells, Wi-Fi access points, and so on. In the illustration of FIG. **3**, the adaptive front-end module **56** can include a radio **60** comprising two stages, a receiver stage **62** and a transmitter stage **64**, each coupled to an antenna assembly **66**, **66'**, which may comprise one of more antennas for the radio **60**. The radio **60** has a first receiver stage coupled to the antenna assembly **66** and includes an adaptive front-end controller **68** that receives the input RF signal from the antenna and performs adaptive signal processing on that RF signal before providing the modified RF signal to an analog-to-digital converter **70**, which then passes the adapted RF signal to a digital RF tuner **72**.

[0051] As shown in FIG. **6**, the adaptive front-end controller **68** of the receiver stage **62** includes two RF signal samplers **74**, **76** connected between an RF adaptive filter stage **78** that is controlled by controller **80**. The adaptive filter stage **78** may have a plurality of tunable digital filters that can sample an incoming signal and selectively provide bandpass or bandstop signal shaping of an incoming RF signal, whether it is an entire wideband communication signal or a narrowband signal or various combinations of both. A controller **80** is coupled to the samplers **74**, **76** and filter stage **78** and serves as an RF link adapter that along with the sampler **74** monitors the input RF signal from the antenna **66** and determines various RF signal characteristics such as the interferences and

noise within the RF signal. The controller **80** is configured to execute any number of a variety of signal processing algorithms to analyze the received RF signal and determine a filter state for the filter stage **78**.

[0052] By providing tuning coefficient data to the filter stage **78**, the adaptive front-end controller **68** acts to pre-filter the received RF signal before the signal is sent to the RF tuner **72**, which analyzes the filtered RF signal for integrity and/or for other applications such as cognitive radio applications. After filtering, the radio tuner **72** may then perform channel demodulation, data analysis, and local broadcasting functions. The RF tuner **72** may be considered the receiver side of an overall radio tuner, while RF tuner **72'** may be considered the transmitter side of the same radio tuner. Prior to sending the filtered RF signal, the sampler **76** may provide an indication of the filtered RF signal to the controller **80** in a feedback manner for further adjusting of the adaptive filter stage **78**.

[0053] In some examples, the adaptive front-end controller **68** is synchronized with the RF tuner **72** by sharing a master clock signal communicated between the two. For example, cognitive radios operating on a 100 μ s response time can be synchronized such that for every clock cycle the adaptive front end analyzes the input RF signal, determines an optimal configuration for the adaptive filter stage **78**, filters that RF signal into the filtered RF signal and communicates the same to the radio tuner **72** for cognitive analysis at the radio. By way of example, cellular phones may be implemented with a 200 μ s response time on filtering. By implementing the adaptive front-end controller **68** using a field programmable gate array configuration for the filter stage, wireless devices may identify not only stationary interference, but also non-stationary interference, of arbitrary bandwidths on that moving interferer.

[0054] In some implementations, the adaptive front-end controller **68** may filter interference or noise from the received incoming RF signal and pass that filtered RF signal to the tuner **72**. In other examples, such as cascaded configurations in which there are multiple adaptive filter stages, the adaptive front-end controller **68** may be configured to apply the filtered signal to an adaptive bandpass filter stage to create a passband portion of the filtered RF signal. For example, the radio tuner **72** may communicate information to the controller **68** to instruct the controller that the radio is only looking at a portion of an overall RF spectrum and thus cause the adaptive front-end controller **68** not to filter certain portions of the RF spectrum and thereby bandpass only those portions. The integration between the radio tuner **72** and the adaptive front-end controller **68** may be particularly useful in dual-band and tri-band applications in which the radio tuner **72** is able to communicate over different wireless standards, such as GSM or UMTS standards.

[0055] The algorithms that may be executed by the controller **80** are not limited to interference detection and filtering of interference signals. In some configurations the controller **80** may execute a spectral blind source separation algorithm that looks to isolate two sources from their convolved mixtures. The controller **80** may execute a signal to interference noise ratio (SINR) output estimator for all or portions of the RF signal. The controller **80** may perform bidirectional transceiver data link operations for collaborative retuning of the adaptive filter stage **78** in response to instructions from the radio tuner **72** or from data the transmitter stage **64**. The controller **80** can determine filter tuning coefficient data for configuring the various adaptive filters of stage **78** to properly filter the RF signal. The controller **80** may also include a data interface communicating the tuning coefficient data to the radio tuner **72** to enable the radio tuner **72** to determine filtering characteristics of the adaptive filter **78**.

[0056] In one embodiment the filtered RF signal may be converted from a digital signal to an analog signal within the adaptive front-end controller **68**. This allows the controller **68** to integrate in a comparable manner to conventional RF filters. In other examples, a digital interface may be used to connect the adaptive front-end controller **68** with the radio tuner **72**, in which case the ADC **70** would not be necessary.

[0057] The above discussion is in the context of the receiver stage **62**. Similar elements are shown

in the transmitter stage **64** but bearing a prime. The elements in the transmitter stage **64** may be similar to those of the receiver **62**, with the exception of the digital to analog converter (DAC) **70'** and other adaptations to the other components shown with a prime in the reference numbers. Furthermore, some or all of these components may in fact be executed by the same corresponding structure in the receiver stage **62**. For example, the RF receiver tuner **72** and the transmitter tuner **72'** may be performed by a single tuner device. The same may be true for the other elements, such as the adaptive filter stages **78** and **78'**, which may both be implemented in a single FPGA, with different filter elements in parallel for full duplex (simultaneous) receive and transmit operation.

[0058] FIG. 7 illustrates another example implementation of an adaptive front-end controller **100**. Input RF signals are received at an antenna (not shown) and coupled to an initial analog filter **104**, such as low noise amplifier (LNA) block, then digitally converted via an analog to digital converter (ADC) **106**, prior to the digitized input RF signal being coupled to a field programmable gate array (FPGA) **108**. The adaptive filter stage described above may be implemented within the FPGA **108**, which has been programmed to contain a plurality of adaptive filter elements tunable to different operating frequencies and frequency bands, and at least some being adaptive from a bandpass to a bandstop configuration or vice versa, as desired. Although an FPGA is illustrated, it will be readily understood that other architectures such as an application specific integrated circuit (ASIC) or a digital signal processor (DSP) may also be used to implement a digital filter architecture described in greater detail below.

[0059] A DSP **110** is coupled to the FPGA **108** and executes signal processing algorithms that may include a spectral blind source separation algorithm, a signal to interference noise ratio (SINR) output estimator, bidirectional transceiver data line operation for collaborative retuning of the adaptive filter stage in response to instructions from the tuner, and/or an optimal filter tuning coefficients algorithm.

[0060] FPGA **108** is also coupled to a PCI target **112** that interfaces the FPGA **108** and a PCI bus **114** for communicating data externally. A system clock **118** provides a clock input to the FPGA **108** and DSP **110**, thereby synchronizing the components. The system clock **118** may be locally set on the adaptive front-end controller, while in other examples the system clock **118** may reflect an external master clock, such as that of a radio tuner. The FPGA **108**, DSP **110**, and PCI target **112**, designated collectively as signal processing module **116**, will be described in greater detail below. In the illustrated example, the adaptive front-end controller **100** includes a microcontroller **120** coupled to the PCI bus **114** and an operations, alarms and metrics (OA&M) processor **122**.

Although they are shown and described herein as separate devices that execute separate software instructions, those having ordinary skill in the art will readily appreciate that the functionality of the microcontroller **120** and the OA&M processor **122** may be merged into a single processing device. The microcontroller **120** and the OA&M processor **122** are coupled to external memories **124** and **126**, respectively. The microcontroller **120** may include the ability to communicate with peripheral devices, and, as such, the microcontroller **120** may be coupled to a USB port, an Ethernet port, or an RS232 port, among others (though none shown). In operation, the microcontroller **120** may locally store lists of channels having interferers or a list of known typically available frequency spectrum bands, as well as various other parameters. Such a list may be transferred to a reporting and control facility or a base station, via the OA&M processor **122**, and may be used for system diagnostic purposes.

[0061] The aforementioned diagnostic purposes may include, but are not limited to, controlling the adaptive front-end controller **100** to obtain particular information relating to an interferer and retasking the interferer. For example, the reporting and control facility may use the adaptive front-end controller **100** to determine the identity of an interferer, such as a mobile unit, by intercepting the electronic serial number (ESN) of the mobile unit, which is sent when the mobile unit transmits information on the narrowband channel. Knowing the identity of the interferer, the reporting and control facility may contact infrastructure that is communicating with the mobile unit (e.g., the base

station) and may request the infrastructure to change the transmit frequency for the mobile unit (i.e., the frequency of the narrowband channel on which the mobile unit is transmitting) or may request the infrastructure to drop communications with the interfering mobile unit altogether. [0062] Additionally, in a cellular configuration (e.g., a system based on a configuration like that of FIG. 1) diagnostic purposes may include using the adaptive front-end controller **100** to determine a telephone number that the mobile unit is attempting to contact and optionally handling the call. For example, the reporting and control facility may use the adaptive front-end controller **100** to determine that the user of the mobile unit was dialing 911, or any other emergency number, and may, therefore, decide that the adaptive front-end controller **100** should be used to handle the emergency call by routing the output of the adaptive front-end controller **100** to a telephone network.

[0063] The FPGA **108** can provide a digital output coupled to a digital to analog converter (DAC) **128** that converts the digital signal to an analog signal which may be provided to a filter **130** to generate a filtered RF output to be broadcast from the base station or mobile station. The digital output at the FPGA **108**, as described, may be one of many possible outputs. For example, the FPGA **108** may be configured to output signals based on a predefined protocol such as a Gigabit Ethernet output, an open base station architecture initiative (OBSAI) protocol, or a common public radio interface (CPRI) protocol, among others.

[0064] It is further noted that the aforementioned diagnostic purposes may also include creating a database of known interferers, the time of occurrence of the interferers, the frequency of occurrence of the interferers, spectral information relating to the interferers, a severity analysis of the interferers, and so on. The identity of the interferers may be based solely on spectral profiles of each interferer that can be used for identification purposes. Although the aforementioned illustrations describe a mobile unit **12** as an interferer, other sources of interference are possible. Any electronic appliance that generates electromagnetic waves such as, for example, a computer, a set-top box, a child monitor, a wireless access point (e.g., Wi-Fi, ZigBee, Bluetooth, etc.) can be a source of interference. In one embodiment, a database of electronic appliances can be analyzed in a laboratory setting or other suitable testing environment to determine an interference profile for each appliance. The interference profiles can be stored in a database according to an appliance type, manufacturer, model number, and other parameters that may be useful in identifying an interferer. Spectral profiles provided by, for example, the OA&M processor **108** to a diagnostic system can be compared to a database of previously characterized interferers to determine the identity of the interference when a match is detected.

[0065] A diagnostic system, whether operating locally at the adaptive front end controller, or remotely at a base station, switching station, or server system, can determine the location of the interferer near the base station (or mobile unit) making the detection, or if a more precise location is required, the diagnostic system can instruct several base stations (or mobile units) to perform triangulation analysis to more precisely locate the source of the interference if the interference is frequent and measurable from several vantage points. With location data, interference identity, timing and frequency of occurrence, the diagnostic system can generate temporal and geographic reports showing interferers providing field personnel a means to assess the volume of interference, its impact on network performance, and it may provide sufficient information to mitigate interference by means other than filtering, such as, for example, interference avoidance by way of antenna steering at the base station, beam steering, retasking an interferer when possible, and so on.

[0066] FIG. 8 illustrates further details of an example implementation of a signal processing module **116** that may serve as another embodiment of an adaptive front-end controller, it being understood that other architectures may be used to implement a signal detection algorithm. A decoder **150** receives an input from the ADC **106** and decodes the incoming data into a format suitable to be processed by the signal processing module **116**. A digital down converter **152**, such as a polyphase decimator, down converts the decoded signal from the decoder **150**. The decoded

signal is separated during the digital down conversion stage into a complex representation of the input signal, that is, into In-Phase (I) and Quadrature-Phase (Q) components which are then fed into a tunable infinite impulse response (IIR)/finite impulse response (FIR) filter **154**. The IIR/FIR filter **154** may be implemented as multiple cascaded or parallel IIR and FIR filters. For example, the IIR/FIR filter **154** may be used with multiple filters in series, such as initial adaptive bandpass filter followed by adaptive bandstop filter. For example, the bandpass filters may be implemented as FIR filters, while the bandstop filters may be implemented as IIR filters. In an embodiment, fifteen cascaded tunable IIR/FIR filters are used to optimize the bit width of each filter. Of course, other digital down converters and filters such as cascaded integrator-comb (CIC) filters may be used to name a few. By using complex filtering techniques, such as the technique described herein, the sampling rate is lowered thereby increasing (e.g., doubling) the bandwidth that the filter **154** can handle. In addition, using complex arithmetic also provides the signal processing module **116** with the ability to perform higher orders of filtering with greater accuracy.

[0067] The I and Q components from the digital down converter **152** are provided to the DSP **110** which implements a detection algorithm and in response provides the tunable IIR/FIR filter **154** with tuning coefficient data that tunes the IIR and/or FIR filters **154** to specific notch (or bandstop) and/or bandpass frequencies, respectively, and specific bandwidths. The tuning coefficient data, for example, may include a frequency and a bandwidth coefficient pair for each of the adaptive filters, which enables the filter to tune to a frequency for bandpass or bandstop operation and the bandwidth to be applied for that operation. The tuning coefficient data corresponding to a bandpass center frequency and bandwidth may be generated by the detection algorithm and passed to a tunable FIR filter within the IIR/FIR filter **154**. The filter **154** may then pass all signals located within a passband of the given transmission frequency. Tuning coefficient data corresponding to a notch (or bandstop) filter may be generated by the detection algorithm and then applied to an IIR filter within the IIR/FIR filter **154** to remove any narrowband interference located within the passband of the bandpass filter. The tuning coefficient data generated by the detection algorithm are implemented by the tunable IIR/FIR filters **154** using mathematical techniques known in the art. In the case of a cognitive radio, upon implementation of the detection algorithm, the DSP **110** may determine and return coefficients corresponding to a specific frequency and bandwidth to be implemented by the tunable IIR/FIR filter **154** through a DSP/PCI interface **158**. Similarly, the transfer function of a notch (or bandstop) filter may also be implemented by the tunable IIR/FIR filter **154**. Of course, other mathematical equations may be used to tune the IIR/FIR filters **154** to specific notch, bandstop, or bandpass frequencies and to a specific bandwidth.

[0068] After the I and Q components are filtered to the appropriate notch (or bandstop) or bandpass frequency at a given bandwidth, a digital upconverter **156**, such as a polyphase interpolator, converts the signal back to the original data rate, and the output of the digital upconverter is provided to the DAC **128**.

[0069] A wireless communication device capable of being operated as a dual- or tri-band device communicating over multiple standards, such as over GSM and UMTS may use the adaptive digital filter architecture embodiments as described above. For example, a dual-band device (using both UMTS and GSM) may be preprogrammed within the DSP **110** to transmit first on UMTS, if available, and on GSM only when outside of a UMTS network. In such a case, the IIR/FIR filter **154** may receive tuning coefficient data from the DSP **110** to pass all signals within a UMTS range. That is, the tuning coefficient data may correspond to a bandpass center frequency and bandwidth adapted to pass only signals within the UMTS range. The signals corresponding to a GSM signal may be filtered, and any interference caused by the GSM signal may be filtered using tuning coefficients, received from the DSP **110**, corresponding to a notch (or bandstop) frequency and bandwidth associated with the GSM interference signal.

[0070] Alternatively, in some cases it may be desirable to keep the GSM signal in case the UMTS signal fades quickly and the wireless communication device may need to switch communication

standards rapidly. In such a case, the GSM signal may be separated from the UMTS signal, and both passed by the adaptive front-end controller. Using the adaptive digital filter, two outputs may be realized, one output corresponding to the UMTS signal and one output corresponding to a GSM signal. The DSP **110** may be programmed to again recognize the multiple standard service and may generate tuning coefficients corresponding to realize a filter, such as a notch (or bandstop) filter, to separate the UMTS signal from the GSM signal. In such examples, an FPGA may be programmed to have parallel adaptive filter stages, one for each communication band.

[0071] To implement the adaptive filter stages, in some examples, the signal processing module **116** is pre-programmed with general filter architecture code at the time of production, for example, with parameters defining various filter types and operation. The adaptive filter stages may then be programmed, through a user interface or other means, by the service providers, device manufactures, etc., to form the actual filter architecture (parallel filter stages, cascaded filter stages, etc.) for the particular device and for the particular network(s) under which the device is to be used. Dynamic flexibility can be achieved during runtime, where the filters may be programmed to different frequencies and bandwidths, each cycle, as discussed herein.

[0072] One method of detecting a wideband signal having narrowband interference is by exploiting the noise like characteristics of a signal. Due to such noise like characteristics of the signal, a particular measurement of a narrowband channel power gives no predictive power as to what the next measurement of the same measurement channel may be. In other words, consecutive observations of power in a given narrowband channel are un-correlated. As a result, if a given measurement of power in a narrowband channel provides predictive power over subsequent measurements of power in that particular channel, thus indicating a departure from statistics expected of a narrowband channel without interference, such a narrowband channel may be determined to contain interference.

[0073] FIG. **9** illustrates an IS-95 CDMA signal **202**, which is a generic Direct Sequence Spread Spectrum (DSSS) signal. The CDMA signal **202** may have a bandwidth of 1.2288 MHz and it may be used to carry up to 41 narrowband channels, each of which has a bandwidth of 30 kHz. One way to identify interference affecting the CDMA signal **202** may be to identify any of such 41 narrowband channels having excess power above an expected power of the CDMA signal **202**. FIG. **9** also illustrates the probability distribution functions (PDFs) **204** of a typical DSSS signal and a complementary cumulative distribution functions (CCDFs) **206** of a typical DSSS signal, which may be used to establish a criteria used to determine narrowband channels disposed within a wideband signal and having excess power.

[0074] Specifically, the PDFs **204** include probability distribution of power in a given channel, which is the likelihood $p(x)$ of measuring a power x in a given channel, for a DSSS signal carrying one mobile unit (**212**), for a DSSS signal carrying ten mobile units (**214**), and for a DSSS signal carrying twenty mobile units (**210**). For example, for the PDF **212**, representing a DSSS signal carrying one mobile unit, the distribution $p(x)$ is observed to be asymmetric, with an abbreviated high-power tail. In this case, any channel having power higher than the high-power tail of the PDF **212** may be considered to have an interference signal.

[0075] The CCDFs **206** denote the likelihood that a power measurement in a channel will exceed a given mean power α , by some value α/σ , wherein σ is standard deviation of the power distribution. Specifically, the CCDFs **206** include an instance of CCDF for a DSSS signal carrying one mobile unit (**220**), an instance of CCDF for a DSSS signal carrying ten mobile units (**222**), and an instance of CCDF for a DSSS signal carrying twenty mobile units (**224**). Thus, for example, for a DSSS signal carrying one mobile unit, the likelihood of any narrowband channel having the ratio α/σ of 10 dB or more is 0.01%. Therefore, an optimal filter can be tuned to such a narrowband channel having excess power.

[0076] One method of detecting such a narrowband channel having interference is by exploiting the noise like characteristic of a DSSS signal. Due to such noise like characteristic of DSSS signal, a

particular measurement of a narrowband channel power gives no predictive power as to what the next measurement of the same measurement channel may be. In other words, consecutive observations of power in a given narrowband channels are un-correlated. As a result, if a given measurement of power in a narrowband channel provides predictive power over subsequent measurements of power in that particular channel, thus indicating a departure from statistics expected of a narrowband channel without interference, such a narrowband channel may be determined to contain interference.

[0077] FIG. **10** illustrates a flowchart of an interference detection program **300** that may be used to determine location of interference in a DSSS signal. At block **302** a series of DSSS signals can be scanned by the adaptive front-end controller described above and the observed values of the signal strengths can be stored for each of various narrowband channels located in the DSSS signal. For example, at block **302** the adaptive front-end controller may continuously scan the 1.2288 MHz DSSS signal **60** for each of the 41 narrowband channels dispersed within it. The adaptive front-end controller may be implemented by any well-known analog scanner or digital signal processor (DSP) used to scan and store signal strengths in a DSSS signal. The scanned values of narrowband signal strengths may be stored in a memory of such DSP or in any other computer readable memory. The adaptive front-end controller may store the signal strength of a particular narrowband channel along with any information, such as a numeric identifier, identifying the location of that particular narrowband channel within the DSSS signal.

[0078] At block **304** the adaptive front-end controller can determine the number of sequences m of a DSSS signal that may be required to be analyzed to determine narrowband channels having interference. A user may provide such a number m based on any pre-determined criteria. For example, a user may provide m to be equal to four, meaning that four consecutive DSSS signals need to be analyzed to determine if any of the narrowband channels within that DSSS signal spectrum includes an interference signal. As one of ordinary skill in the art would appreciate, the higher is the selected value of m , the more accurate will be the interference detection. However, the higher the number m is, the higher is the delay in determining whether a particular DSSS signal had an interference present in it, subsequently, resulting in a longer delay before a filter is applied to the DSSS signal to remove the interference signal.

[0079] Generally, detection of an interference signal may be performed on a rolling basis. That is, at any point in time, m previous DSSS signals may be used to analyze the presence of an interference signal. The earliest of such m interference signals may be removed from the set of DSSS signals used to determine the presence of an interference signal on a first-in-first-out basis. However, in an alternate embodiment, an alternate sampling method for the set of DSSS signals may also be used.

[0080] At block **306** the adaptive front-end controller can select x narrowband channels having the highest signal strength from each of the m most recent DSSS signals scanned at the block **302**. A user may determine the number x . For example, if x is selected to be equal to three, the block **306** may select the three highest channels from each of the m most recent DSSS signals. The methodology for selecting x narrowband channels having highest signal strength from a DSSS signal is described in further detail in FIG. **11** below. For example, the adaptive front-end controller at block **306** may determine that the first of the m DSSS signals has narrowband channels **10**, **15** and **27** having the highest signal strengths, the second of the m DSSS channels has narrowband channels **15** and **27** and **35** having the highest signal strengths, and the third of the m DSSS channels has the narrowband channels **15**, **27** and **35** having the highest narrowband signal strength.

[0081] After having determined the x narrowband channels having the highest signal strengths in each of the m DSSS signals, at block **308** the adaptive front-end controller can compare these x narrowband channels to determine if any of these highest strength narrowband channels appear more than once in the m DSSS signals. In case of the example above, the adaptive front-end

controller at block **308** may determine that the narrowband channels **15** and **27** are present among the highest strength narrowband channels for each of the last three DSSS signals, while channel **35** is present among the highest strength narrowband channels for at least two of the last three DSSS signals.

[0082] Such consistent appearance of narrowband channels having highest signal strength over subsequent DSSS signals indicate that narrowband channels **15** and **27**, and probably the narrowband channel **35**, may have an interference signal super-imposed on them. At block **310** the adaptive front-end controller may use such information to determine which narrowband channels may have interference. For example, based on the number of times a given narrowband channel appears in the selected highest signal strength channels, the adaptive front-end controller at block **310** may determine the confidence level that may be assigned to a conclusion that a given narrowband channel contains an interference signal.

[0083] Alternatively, at block **310** the adaptive front-end controller may determine a correlation factor for each of the various narrowband channels appearing in the x selected highest signal strength channels and compare the calculated correlation factors with a threshold correlation factor to determine whether any of the x selected channels has correlated signal strengths. Calculating a correlation factor based on a series of observations is well known to those of ordinary skill in the art and therefore is not illustrated in further detail herein. The threshold correlation factor may be given by the user of the interference detection program **300**.

[0084] Note that while in the above illustrated embodiment, the correlation factors of only the selected highest signal strength channels are calculated, in an alternate embodiment, correlation factors of all the narrowband channels within the DSSS signals may be calculated and compared to the threshold correlation factor.

[0085] Empirically, it may be shown that when m is selected to be equal to three, for a clean DSSS signal, the likelihood of having at least one match among the higher signal strength narrowband channels is 0.198, the likelihood of having at least two matches among the higher signal strength narrowband channels is 0.0106, and the likelihood of having at least three matches among the higher signal strength narrowband channels is 9.38×10^{-5} . Thus, the higher the number of matches, the lesser is the likelihood of having a determination that one of the x channels contains an interference signal (i.e., a false positive interference detection). It may be shown that if the number of scans m is increased to, say four DSSS scans, the likelihood of having such matches in m consecutive scans is even smaller, thus providing higher confidence that if such matches are found to be present, they indicate presence of interference signal in those narrowband channels.

[0086] To identify the presence of interference signals with even higher level of confidence, at block **312** the adaptive front-end controller may decide whether to compare the signal strengths of the narrowband channels determined to have an interference signal with a threshold. If at block **312** the adaptive front-end controller decides to perform such a comparison, at block **314** the adaptive front-end controller may compare the signal strength of each of the narrowband channels determined to have an interference with a threshold level. Such comparing of the narrowband channel signal strengths with a threshold may provide added confidence regarding the narrowband channel having an interference signal so that when a filter is configured according to the narrowband channel, the probability of removing a non-interfering signal is reduced. However, a user may determine that such added confidence level is not necessary and thus no such comparison to a threshold needs to be performed. In which case, at block **316** the adaptive front-end controller stores the interference signals in a memory.

[0087] After storing the information about the narrowband channels having interference signals, at block **318** the adaptive front-end controller selects the next DSSS signal from the signals scanned and stored at block **302**. At block **318** the adaptive front-end controller may cause the first of the m DSSS signals to be dropped and the newly added DSSS signal is added to the set of m DSSS signals that will be used to determine presence of an interference signal (first-in-first-out).

Subsequently, at block **306** the process of determining narrowband channels having interference signals is repeated by the adaptive front-end controller. Finally, at block **320** the adaptive front-end controller may select and activate one or more filters that are located in the path of the DSSS signal to filter out any narrowband channel identified as having narrowband interference in it.

[0088] Now referring to FIG. **11**, a flowchart illustrates a high strength channels detection program **350** that may be used to identify various channels within a given scan of the DSSS signal that may contain an interference signal. The high strength channels detection program **350** may be used to implement the functions performed at block **306** of the interference detection program **300**. In a manner similar to the interference detection program **300**, the high strength channels detection program **350** may also be implemented using software, hardware, firmware or any combination thereof.

[0089] At block **352** the adaptive front-end controller may sort signal strengths of each of the n channels within a given DSSS signal. For example, if a DSSS signal has 41 narrowband channels, at block **352** the adaptive front-end controller may sort each of the 41 narrowband channels according to its signal strengths. Subsequently, at block **354** the adaptive front-end controller may select the x highest strength channels from the sorted narrowband channels and store information identifying the selected x highest strength channels for further processing. An embodiment of the high strength channels detection program **350** may simply use the selected x highest strength channels from each scan of the DSSS signals to determine any presence of interference in the DSSS signals. However, in an alternate embodiment, additional selected criteria may be used.

[0090] Subsequently, at block **356** the adaptive front-end controller can determine if it is necessary to compare the signal strengths of the x highest strength narrowband channels to any other signal strength value, such as a threshold signal strength, etc., where such a threshold may be determined using the average signal strength across the DSSS signal. For example, at block **356** the adaptive front-end controller may use a criterion such as, for example: “when x is selected to be four, if at least three out of four of the selected narrowband channels have also appeared in previous DSSS signals, no further comparison is necessary.” Another criterion may be, for example: “if any of the selected narrowband channels is located at the fringe of the DSSS signal, the signal strengths of such narrowband channels should be compared to a threshold signal strength.” Other alternate criteria may also be provided.

[0091] If at block **356** the adaptive front-end controller determines that no further comparison of the signal strengths of the selected x narrowband channels is necessary, at block **358** the adaptive front end controller stores information about the selected x narrowband channels in a memory for further processing. If at block **356** the adaptive front-end controller determines that it is necessary to apply further selection criteria to the selected x narrowband channels, the adaptive front-end controller returns to block **360**. At block **360** the adaptive front-end controller may determine a threshold value against which the signal strengths of each of the x narrowband channels are compared based on a predetermined methodology.

[0092] For example, in an embodiment, at block **360** the adaptive front-end controller may determine the threshold based on the average signal strength of the DSSS signal. The threshold signal strength may be the average signal strength of the DSSS signal, or a predetermined value may be added to such average DSSS signal to derive the threshold signal strength.

[0093] Subsequently, at block **362** the adaptive front-end controller may compare the signal strengths of the selected x narrowband channels to the threshold value determined at block **360**. Only the narrowband channels having signal strengths higher than the selected threshold are used in determining presence of interference in the DSSS signal. Finally, at block **364** the adaptive front-end controller may store information about the selected x narrowband channels having signal strengths higher than the selected threshold in a memory. As discussed above, the interference detection program **300** may use such information about the selected narrowband channels to determine the presence of interference signal in the DSSS signal.

[0094] The interference detection program **300** and the high strength channel detection program **350** may be implemented by using software, hardware, firmware or any combination thereof. For example, such programs may be stored on a memory of a computer that is used to control activation and deactivation of one or more notch filters. Alternatively, such programs may be implemented using a digital signal processor (DSP) which determines the presence and location of interference channels in a dynamic fashion and activates/de-activates one or more filters.

[0095] FIG. **12** illustrates a three-dimensional graph **370** depicting several DSSS signals **372-374** over a time period. A first axis of the graph **370** illustrates the number of narrowband channels of the DSSS signals **372-374**, a second axis illustrates time over which a number of DSSS signals **372-374** are scanned, and a third axis illustrates the power of each of the narrowband channels. The DSSS signals **372-374** are shown to be affected by an interference signal **378**.

[0096] The interference detection program **370** may start scanning various DSSS signals **372-374** starting from the first DSSS signal **372**. As discussed above at block **304** the adaptive front-end controller determines the number m of the DSSS signals **372-374** that are to be scanned. Because the interference signal **378** causes the signal strength of a particular narrowband channel to be consistently higher than the other channels for a number of consecutive scans of the DSSS signals **372-374** at block **210** the adaptive front-end controller identifies a particular channel having an interference signal present. Subsequently, at block **320** the adaptive front-end controller will select and activate a filter that applies the filter function as described above, to the narrowband channel having interference.

[0097] The graph **370** also illustrates the average signal strengths of each of the DSSS signals **372-374** by a line **376**. As discussed above, at block **362** the adaptive front-end controller may compare the signal strengths of each of the x selected narrowband channels from the DSSS signals **372-374** with the average signal strength, as denoted by line **376**, in that particular DSSS signal.

[0098] Now referring to FIG. **13**, a graph **380** illustrates interference detection success rate of using the interference detection program **370**, as a function of strength of an interference signal affecting a DSSS signal. The x-axis of the graph **380** depicts the strength of interference signal relative to the strength of the DSSS signal, while the y-axis depicts the detection success rate in percentages. As illustrated, when an interference signal has a strength of at least 2 dB higher than the strength of the DSSS signal, such an interference signal is detected with at least ninety five percent success rate.

[0099] The foregoing interference detection and mitigation embodiments can further be adapted for detecting and mitigating interference in long-term evolution (LTE) communication systems.

[0100] LTE transmission consists of a combination of Resource Blocks (RBs) which have variable characteristics in frequency and time. A single RB can be assigned to a user equipment, specifically, a 180 KHz continuous spectrum utilized for 0.5-1 millisecond. An LTE band can be partitioned into a number of RBs which could be allocated to individual communication devices for specified periods of time for LTE transmission. Consequently, an LTE spectrum has an RF environment dynamically variable in frequency utilization over time. FIG. **14** depicts an illustrative LTE transmission.

[0101] LTE utilizes different media access methods for downlink (orthogonal frequency-division multiple access; generally, referred to as OFDMA) and uplink (single carrier frequency-division multiple access; generally, referred to as SC-FDMA). For downlink communications, each RB contains 12 sub-carriers with 15 KHz spacing. Each sub-carrier can be used to transmit individual bit information according to the OFDMA protocol. For uplink communications, LTE utilizes a similar RB structure with 12 sub-carriers, but in contrast to downlink, uplink data is pre-coded for spreading across 12 sub-carriers and is transmitted concurrently on all 12 sub-carriers.

[0102] The effect of data spreading across multiple sub-carriers yields a transmission with spectral characteristics similar to a CDMA/UMTS signal. Hence, similar principles of narrow band interference detection can be applied within an instance of SC-FDMA transmission from an individual communication device—described herein as user equipment (UE). However, since each

transmission consists of unknown RB allocations with unknown durations, such a detection principle can only be applied separately for each individual RB within a frequency and specific time domain. If a particular RB is not used for LTE transmission at the time of detection, the RF spectrum will present a thermal noise which adheres to the characteristics of a spread spectrum signal, similar to a CDMA/UMTS signal.

[0103] Co-channel, as well as other forms of interference, can cause performance degradation to SC-FDMA and OFDMA signals when present. FIG. 15 depicts an illustration of an LTE transmission affected by interferers 402, 404, 406 and 408 occurring at different points in time. Since such LTE transmissions do not typically have flat power spectral densities (see FIG. 14), identification of interference as shown in FIG. 15 can be a difficult technical problem. The subject disclosure presents a method to improve the detection of narrowband interference in SC-FDMA/OFDM channels through a time-averaging algorithm that isolates interference components in the channel and ignores the underlying signal.

[0104] Time averaging system (TAS) can be achieved with a boxcar (rolling) average, in which the TAS is obtained as a linear average of a Q of previous spectrum samples, with Q being a user-settable parameter. The Q value determines the “strength” of the averaging, with higher Q value resulting in a TAS that is more strongly smoothed in time and less dependent on short duration transient signals. Due to the frequency-hopped characteristic of SC-FDMA/OFDMA signals, which are composed of short duration transients, the TAS of such signals is approximately flat. It will be appreciated that TAS can also be accomplished by other methods such as a forgetting factor filter.

[0105] In one embodiment, an adaptive threshold can be determined by a method 500 as depicted in FIG. 16. Q defines how many cycles of t.sub.i to use (e.g., 100 cycles can be represented by t.sub.1 through t.sub.100). The adaptive front-end module 56 of FIG. 6 can be configured to measure power in 30 KHz increments starting from a particular RB and over multiple time cycles. For illustration purposes, the adaptive front-end module 56 is assumed to measure power across a 5 MHz spectrum. It will be appreciated that the adaptive front-end module 56 can be configured for other increments (e.g., 15 KHz or 60 KHz), and a different RF spectrum bandwidth. With this in mind, the adaptive front-end module 56 can be configured at frequency increment f1 to measure power at t1, t2, through tq (q representing the number of time cycles, i.e., Q). At f1+30 kHz, the adaptive front-end module 56 measures power at t1, t2, through tn. The frequency increment can be defined by $f_0 + (z-1) \cdot 30 \text{ KHz} = f_z$, where f0 is a starting frequency, where $z=1 \dots x$, and z defines increments of 30 KHz increment, e.g., f1=f(z=1) first 30 KHz increment, f2=f(z=2) second 30 KHz increment, etc.

[0106] The adaptive front-end module 56 repeats these steps until the spectrum of interest has been fully scanned for Q cycles, thereby producing the following power level sample sets: [0107]

S.sub.f1 (t1 thru tq): s.sub.1,t1,f1, s.sub.2,t2,f1, . . . , s.sub.q,tq,f1 [0108] S.sub.f2 (t1 thru tq):

s.sub.1,t1,f2, s.sub.2,t2,f2, . . . , s.sub.q,tq,f2 [0109] S.sub.fx (t1 thru tq): s.sub.1,t1,fz, s.sub.2,t2,fx, . . . , s.sub.q,tq,fx

[0110] The adaptive front-end module 56 in step 504, calculates averages for each of the power level sample sets as provided below:

$$[00001] a1(f1) = (s_{1,t1,f1} + s_{2,t2,f1}, \dots, s_{q,tq,f1}) / q$$

$$a2(f2) = (s_{1,t1,f2} + s_{2,t2,f2}, \dots, s_{q,tq,f2}) / q$$

$$ax(fx) = (s_{1,t1,fx} + s_{2,t2,fx}, \dots, s_{q,tq,fx}) / q$$

[0111] In one embodiment, the adaptive front-end module 56 can be configured to determine at step 506 the top “m” averages (e.g., the top 3 averages) and dismiss these averages from the calculations. The variable “m” can be user-supplied or can be empirically determined from field measurements collected by one or more base stations utilizing an adaptive front-end module 56. This step can be used to avoid skewing a baseline average across all frequency increments from being too high, resulting in a threshold calculation that may be too conservative. If step 506 is

invoked, a baseline average can be determined in step **508** according to the equation: Baseline Avg=(a1+a2+ . . . +az-averages that have been dismissed)/(x-m). If step **506** is skipped, the baseline average can be determined from the equation: Baseline Avg=(a1+a2+ . . . +az)/x. Once the baseline average is determined in step **508**, the adaptive front-end module **56** can proceed to step **510** where it calculates a threshold according to the equation: Threshold=y dB offset+Baseline Avg. The y dB offset can be user defined or empirically determined from field measurements collected by one or more base stations utilizing an adaptive front-end module **56**.

[0112] Once a cycle of steps **502** through **510** have been completed, the adaptive front-end module **56** can monitor at step **512** interference per frequency increment of the spectrum being scanned based on any power levels measured above the threshold **602** calculated in step **510** as shown in FIG. **17**. Not all interferers illustrated in FIG. **17** exceed the threshold, such as the interferer with reference **610**. Although this interferer has a high-power signature, it was not detected because it occurred during a resource block (R4) that was not in use. As such, the interferer **510** fell below the threshold **602**. In another illustration, interferer **s 612** also fell below the threshold **602**. This interferer was missed because of its low power signature even though the RB from which it occurred (R3) was active.

[0113] Method **500** can utilize any of the embodiments in the illustrated flowcharts described above to further enhance the interference determination process. For example, method **500** of FIG. **16** can be adapted to apply weights to the power levels, and/or perform correlation analysis to achieve a desired confidence level that the proper interferers are addressed. For example, with correlation analysis, the adaptive front-end module **56** can be configured to ignore interferers **614** and **616** of FIG. **17** because their frequency of occurrence is low. Method **500** can also be adapted to prioritize interference mitigation. Prioritization can be based on frequency of occurrence of the interferers, time of day of the interference, the effect the interference has on network traffic, and/or other suitable factors for prioritizing interference to reduce its impact on the network. Prioritization schemes can be especially useful when the filtering resources of the adaptive front-end module **56** can only support a limited number of filtering events.

[0114] When one or more interferers are detected in step **512**, the adaptive front-end module **56** can mitigate the interference at step **514** by configuring one or more filters to suppress the one or more interferers as described above. When there are limited resources to suppress all interferers, the adaptive front-end module **56** can use a prioritization scheme to address the most harmful interference as discussed above. FIG. **18** provides an illustration of how the adaptive front-end module **56** can suppress interferers based on the aforementioned algorithms of the subject disclosure. For example, interferers **612**, **614** and **616** can be ignored by the adaptive front-end module **56** because their correlation may be low, while interference suppression is applied for all other interferers as shown by reference **650**.

[0115] In one embodiment, the adaptive front-end module **56** can submit a report to a diagnostic system that includes information relating to the interferers detected. The report can include among other things, a frequency of occurrence of the interferer, spectral data relating to the interferer, an identification of the base station from which the interferer was detected, a severity analysis of the interferer (e.g., bit error rate, packet loss rate, or other traffic information detected during the interferer), and so on. The diagnostic system can communicate with other base stations with other operable adaptive front-end module **56** to perform macro analysis of interferers such as triangulation to locate interferers, identity analysis of interferers based on a comparison of spectral data and spectral profiles of known interferers, and so on.

[0116] In one embodiment, the reports provided by the adaptive front-end module **56** can be used by the diagnostic system to in some instances perform avoidance mitigation. For example, if the interferer is known to be a communication device in the network, the diagnostic system can direct a base station in communication with the communication device to direct the communication device to another channel so as to remove the interference experienced by a neighboring base station.

Alternatively, the diagnostic system can direct an affected base station to utilize beam steering and/or mechanical steering of antennas to avoid an interferer. When avoidance is performed, the mitigation step **514** can be skipped or may be invoked less as a result of the avoidance steps taken by the diagnostic system.

[0117] Once mitigation and/or an interference report has been processed in steps **514** and **516**, respectively, the adaptive front-end module **56** can proceed to step **518**. In this step, the adaptive front-end module **56** can repeat steps **502** through **510** to calculate a new baseline average and corresponding threshold based on Q cycles of the resource blocks. Each cycle creates a new adaptive threshold that is used for interference detection. It should be noted that when Q is high, changes to the baseline average are smaller, and consequently the adaptive threshold varies less over Q cycles. In contrast, when Q is low, changes to the baseline average are higher, which results in a more rapidly changing adaptive threshold.

[0118] Generally speaking, one can expect that there will be more noise-free resource blocks than resource blocks with substantive noise. Accordingly, if an interferer is present (constant or ad hoc), one can expect the aforementioned algorithm described by method **500** will produce an adaptive threshold (i.e., baseline average+offset) that will be lower than interferer's power level due to mostly noise-free resource blocks driving down baseline average. Although certain communication devices will have a high initial power level when initiating communications with a base station, it can be further assumed that over time the power levels will be lowered to a nominal operating condition. A reasonably high Q would likely also dampen disparities between RBs based on the above-described embodiments.

[0119] It is further noted that the aforementioned algorithms can be modified while maintaining the objective of mitigating detected interference. For instance, instead of calculating a baseline average from a combination of averages $a_1(f_1)$ through $a_x(f_x)$ or subsets thereof, the adaptive front end controller **56** can be configured to calculate a base line average for each resource block according to a known average of adjacent resource blocks, an average calculated for the resource block itself, or other information that may be provided by, for example, to a resource block scheduler (e.g., a software application and/or hardware component of the base station) that may be helpful in calculating a desired baseline average for each resource block or groups of resource blocks. For instance, the resource block schedule can inform the adaptive front-end module **56** as to which resource blocks are active and at what time periods. This information can be used by the adaptive front-end module **56** determine individualized baseline averages for each of the resource blocks or groups thereof. Since baseline averages can be individualized, each resource block can also have its own threshold applied to the baseline average of the resource block. Accordingly, thresholds can vary between resource blocks for detecting interferers.

[0120] It is further noted that the aforementioned mitigation and detection algorithms can be implemented by any communication device including cellular phones, smartphones, tablets, small base stations, macro base stations, femto cells, Wi-Fi access points, and so on. Small base stations (commonly referred to as small cells) can represent low-powered radio access nodes that can operate in licensed and/or unlicensed spectrum that have a range of 10 meters to 1 or 2 kilometers, compared to a macrocell (or macro base station) which might have a range of a few tens of kilometers. Small base stations can be used for mobile data offloading as a more efficient use of radio spectrum.

[0121] FIG. **19A** depicts an illustrative embodiment of a method **700** for mitigating interference such as shown in FIG. **15**. Method **700** can be performed singly or in combination by a mobile communication device, a stationary communication device, base stations, and/or a system or systems in communication with the base stations and/or mobile communication devices. FIG. **19B** depicts an illustrative embodiment of a communication system operating according to method **700**. In this illustration, a central system **750** can collect interference information from adaptive filter modules **56** across a network of base stations interconnected by a data transport system.

[0122] With this in mind, method **700** can begin with step **702**, where a number of base stations utilizing one or more adaptive filter modules **56** detect interference in segments of spectrum, such as for example resource blocks, and send interference information to the central system **750** for processing at step **704**. At step **706**, the central system **750** can correlate the interference information and determine from the correlated data the existence of interferers at step **708**. Recurring interferers can be detected from the correlated data by utilizing a correlation algorithm such as regression analysis. In addition to correlation analysis, the central system **750** can generate a profile for each interferer at step **710**. The profile can describe unique characteristics of the interferer such as its spectral shape, its amplitude, its phase, its time of occurrence, its frequency of occurrence, a geographic location of the base stations and/or the adaptive filter modules **56** detecting the interferer, network traffic levels at a time of detection of the interferer, identities of the base stations performing the detection, and so on.

[0123] At step **708**, the central system **750** can compare the profiles generated for each interferer with profiles of known interferers. The profiles of known interferers can be stored in a database created by a service provider that tracks the identity of interferers. The database can be created from interferers characterized in a lab setting, and/or can be developed from data collected from adaptive filter modules **56** which is analyzed for accuracy and utility to identify interferers. Interferers can be characterized by spectral shape, time of occurrence, frequency of occurrence, phase, geographic location of occurrence, and so on. At step **714**, the central system **750** can determine if any matches exist. A match need not be a perfect match. For example, a user-defined setting can be established where 70% or more similarity between characteristics of the profile of a detected interferer and a known profile would be sufficient to establish a match. Other user-defined settings may be established according to performance and/or business objectives of a service provider. The database can also characterize interferers by identity (e.g., a certain product type associated with the interferer), a source party in control of the interferer, a behavioral pattern of recurrence of interference from the source party and so on.

[0124] If a match exists at step **714**, the central system **750** can associate at step **718** the identified interferer with base stations detecting the identified interferer. Such an association can be stored in the database for future reference at step **714** when new interference information is processed by the central system **750**. In addition to identifying interferers, the central system **750** can predict recurrences of interferers at step **720**. The central system **750** can perform this task by processing present and past interference information received from the base stations at step **704** and by utilizing predictive algorithms such as regression. The predictions can include a prediction of which of the detected interferers will have a recurrence, and in some instances, an expected time and date of recurrence of the interferer.

[0125] At step **722**, the central system **750** can determine if a user-defined event has been triggered by the predictions of step **720**. A user-defined event can be, for example, a trigger that is activated when the predicted recurrences exceed a threshold of recurrences, when a particular known interferer resurfaces, when predicting that network traffic will be adversely impacted at one or more base stations affected by the recurrence of interferers at the predicted time of recurrence, or any other suitable trigger important to a service provider. User-defined events such as the service provider can establish these to achieve quality of service, reduced dropped calls, or other business objectives.

[0126] When a user-defined event is detected, the central system **750** can notify a field agent or other suitable personnel at step **724** of the predicted recurrence of the interferer and can provide other vital information associated with the interferer such as its identity, base stations detecting the interferer and so on. The field agent at step **726** can request spectral data associated with the interferer from one or more base stations that detected the interferer. At step **728** the central system **750** can receive a stream of spectral data collected in real-time by the base stations or spectral data collected over a period of time in accordance with the request generated by the field agent. The

streamed spectral data can be presented to the field agent by the central system **750** at step **728** by way of frequency plots or other suitable presentation methods to enable the field agent to analyze the interferer. The presentation can take place at a computer terminal remote from the affected base stations without requiring the field agent to travel to their respective locations. To further assist the field agent, the agent can request at step **730** that the central system **750** present an interference map at step **732**.

[0127] The interference map can be a geographic map that shows all interferers in the region where the affected base stations are located, or at a macro view, the interference map can cover geographic regions from various vantage points such as villages, towns, cities, states or a nation. The field agent can direct the central station **750** to zoom in and out of desired views of any geographic region defined by the field agent utilizing graphical tools suitable for such tasks. The interference map can present the interference map according to time intervals so that the field agent can visualize the behavior of interferers at various times of the day. The interference map can also depict characteristics of the interferers by selecting an interferer with a mouse pointer or simply placing the mouse pointer over the interferer thereby causing a pop screen with relevant information associated with the interferer such as amplitude, phase, time of occurrence, frequency of occurrence, number of dropped packets when the interferer was detected, number of dropped communication sessions (voice or data) when the interferer was detected, and so on.

[0128] Referring back to step **722**, when the user-defined event is not detected, the central system **750** can identify at step **734** correlated interferers detected by multiple base stations. That is, in step **734**, the central system **750** can detect from correlation data it has gathered from the base stations when multiple base stations are sensing the same interferer. Once the central system **750** has detected like interferers from the correlation data, it can determine at step **736** which base stations have sensed the same interferers and their respective geographic locations. With the geographic location of the base stations, the central system **750** can determine utilizing triangulation techniques an approximate (or precise) location of an interference source associated with each interferer and at step **724** notify the field agent of the locations of interference sources. The field agent can if desirable analyze the spectral information provided by the base stations as described in steps **726-732**, and/or can generate field tickets directed to field personnel to investigate, and if possible, mitigate the interference by removal of the source, shielding of the source, or perform other suitable mitigation techniques.

[0129] It is contemplated that the steps of method **700** can be rearranged and/or individually modified without departing from the scope of the claims of the subject disclosure. Consequently, the steps of method **700** can be performed by a mobile communication device, a base station, a central system, or any combination thereof. For example, method **700** can be adapted so that it is performed by mobile communication devices. Mobile communication devices can be instructed by base stations to detect interference and provide interference information to the base stations or central system **750**. Alternatively, or in combination, the mobile devices can be adapted to perform such tasks autonomously, and at random intervals. The interference information can include spectral, temporal, and location information provided by mobile communication devices utilizing a GPS receiver to assist in triangulating a location of source interferers. Interference information such as this can be collected by the central system **750** and processed according to method **700** as depicted in FIG. **19A**.

[0130] An illustrative embodiment of a communication device **800** is shown in FIG. **20**.

Communication device **800** can serve in whole or in part as an illustrative embodiment of the devices depicted in FIGS. **1**, **4**, and **6-8**. In one embodiment, the communication device **800** can be configured, for example, to perform operations such as measuring a power level in at least a portion of a plurality of resource blocks occurring in a radio frequency spectrum, where the measuring occurs for a plurality of time cycles to generate a plurality of power level measurements, calculating a baseline power level according to at least a portion of the plurality of power levels,

determining a threshold from the baseline power level, and monitoring at least a portion of the plurality of resource blocks for signal interference according to the threshold. Other embodiments described in the subject disclosure can be used by the communication device **800**.

[0131] To enable these features, communication device **800** can comprise a wireline and/or wireless transceiver **802** (herein transceiver **802**), a user interface (UI) **804**, a power supply **814**, a location receiver **816**, a motion sensor **818**, an orientation sensor **820**, and a controller **806** for managing operations thereof. The transceiver **802** can support short-range or long-range wireless access technologies such as Bluetooth, ZigBee, Wi-Fi, DECT, or cellular communication technologies, just to mention a few. Cellular technologies can include, for example, CDMA-1×, UMTS/HSDPA, GSM/GPRS, TDMA/EDGE, EV/DO, WiMAX, SDR, LTE, as well as other next generation wireless communication technologies as they arise. The transceiver **802** can also be adapted to support circuit-switched wireline access technologies (such as PSTN), packet-switched wireline access technologies (such as TCP/IP, VoIP, etc.), and combinations thereof.

[0132] The UI **804** can include a depressible or touch-sensitive keypad **808** with a navigation mechanism such as a roller ball, a joystick, a mouse, or a navigation disk for manipulating operations of the communication device **800**. The keypad **808** can be an integral part of a housing assembly of the communication device **800** or an independent device operably coupled thereto by a tethered wireline interface (such as a USB cable) or a wireless interface supporting for example Bluetooth. The keypad **808** can represent a numeric keypad commonly used by phones, and/or a QWERTY keypad with alphanumeric keys. The UI **804** can further include a display **810** such as monochrome or color LCD (Liquid Crystal Display), OLED (Organic Light Emitting Diode) or other suitable display technology for conveying images to an end user of the communication device **800**. In an embodiment where the display **810** is touch-sensitive, a portion or all of the keypad **808** can be presented by way of the display **810** with navigation features.

[0133] The display **810** can use touch screen technology to also serve as a user interface for detecting user input. As a touch screen display, the communication device **800** can be adapted to present a user interface with graphical user interface (GUI) elements that can be selected by a user with a touch of a finger. The touch screen display **810** can be equipped with capacitive, resistive or other forms of sensing technology to detect how much surface area of a user's finger has been placed on a portion of the touch screen display. This sensing information can be used to control the manipulation of the GUI elements or other functions of the user interface. The display **810** can be an integral part of the housing assembly of the communication device **800** or an independent device communicatively coupled thereto by a tethered wireline interface (such as a cable) or a wireless interface.

[0134] The UI **804** can also include an audio system **812** that utilizes audio technology for conveying low volume audio (such as audio heard in proximity of a human ear) and high-volume audio (such as speakerphone for hands free operation). The audio system **812** can further include a microphone for receiving audible signals of an end user. The audio system **812** can also be used for voice recognition applications. The UI **804** can further include an image sensor **813** such as a charged coupled device (CCD) camera for capturing still or moving images.

[0135] The power supply **814** can utilize common power management technologies such as replaceable and rechargeable batteries, supply regulation technologies, and/or charging system technologies for supplying energy to the components of the communication device **800** to facilitate long-range or short-range portable applications. Alternatively, or in combination, the charging system can utilize external power sources such as DC power supplied over a physical interface such as a USB port or other suitable tethering technologies.

[0136] The location receiver **816** can utilize location technology such as a global positioning system (GPS) receiver capable of assisted GPS for identifying a location of the communication device **800** based on signals generated by a constellation of GPS satellites, which can be used for facilitating location services such as navigation. The motion sensor **818** can utilize motion sensing

technology such as an accelerometer, a gyroscope, or other suitable motion sensing technology to detect motion of the communication device **800** in three-dimensional space. The orientation sensor **820** can utilize orientation sensing technology such as a magnetometer to detect the orientation of the communication device **800** (north, south, west, and east, as well as combined orientations in degrees, minutes, or other suitable orientation metrics).

[0137] The communication device **800** can use the transceiver **802** to also determine a proximity to a cellular, Wi-Fi, Bluetooth, or other wireless access points by sensing techniques such as utilizing a received signal strength indicator (RSSI) and/or signal time of arrival (TOA) or time of flight (TOF) measurements. The controller **806** can utilize computing technologies such as a microprocessor, a digital signal processor (DSP), programmable gate arrays, application specific integrated circuits, and/or a video processor with associated storage memory such as Flash, ROM, RAM, SRAM, DRAM or other storage technologies for executing computer instructions, controlling, and processing data supplied by the aforementioned components of the communication device **400**.

[0138] Other components not shown in FIG. **20** can be used in one or more embodiments of the subject disclosure. For instance, the communication device **800** can include a reset button (not shown). The reset button can be used to reset the controller **806** of the communication device **800**. In yet another embodiment, the communication device **800** can also include a factory default setting button positioned, for example, below a small hole in a housing assembly of the communication device **800** to force the communication device **800** to re-establish factory settings. In this embodiment, a user can use a protruding object such as a pen or paper clip tip to reach into the hole and depress the default setting button. The communication device **400** can also include a slot for adding or removing an identity module such as a Subscriber Identity Module (SIM) card. SIM cards can be used for identifying subscriber services, executing programs, storing subscriber data, and so forth.

[0139] The communication device **800** as described herein can operate with more or less of the circuit components shown in FIG. **20**. These variant embodiments can be used in one or more embodiments of the subject disclosure.

[0140] It should be understood that devices described in the exemplary embodiments can be in communication with each other via various wireless and/or wired methodologies. The methodologies can be links that are described as coupled, connected and so forth, which can include unidirectional and/or bidirectional communication over wireless paths and/or wired paths that utilize one or more of various protocols or methodologies, where the coupling and/or connection can be direct (e.g., no intervening processing device) and/or indirect (e.g., an intermediary processing device such as a router).

[0141] FIG. **21** depicts an exemplary diagrammatic representation of a machine in the form of a computer system **900** within which a set of instructions, when executed, may cause the machine to perform any one or more of the methods described above. One or more instances of the machine can operate, for example, as the devices of FIGS. **1**, **4**, and **6-8**. In some embodiments, the machine may be connected (e.g., using a network **926**) to other machines. In a networked deployment, the machine may operate in the capacity of a server or a client user machine in server-client user network environment, or as a peer machine in a peer-to-peer (or distributed) network environment.

[0142] The machine may comprise a server computer, a client user computer, a personal computer (PC), a tablet PC, a smart phone, a laptop computer, a desktop computer, a control system, a network router, switch or bridge, or any machine capable of executing a set of instructions (sequential or otherwise) that specify actions to be taken by that machine. It will be understood that a communication device of the subject disclosure includes broadly any electronic device that provides voice, video or data communication. Further, while a single machine is illustrated, the term “machine” shall also be taken to include any collection of machines that individually or jointly execute a set (or multiple sets) of instructions to perform any one or more of the methods

discussed herein.

[0143] The computer system **900** may include a processor (or controller) **902** (e.g., a central processing unit (CPU), a graphics processing unit (GPU, or both), a main memory **904** and a static memory **906**, which communicate with each other via a bus **908**. The computer system **900** may further include a display unit **910** (e.g., a liquid crystal display (LCD), a flat panel, or a solid-state display. The computer system **900** may include an input device **912** (e.g., a keyboard), a cursor control device **914** (e.g., a mouse), a disk drive unit **916**, a signal generation device **918** (e.g., a speaker or remote control) and a network interface device **920**. In distributed environments, the embodiments described in the subject disclosure can be adapted to utilize multiple display units **910** controlled by two or more computer systems **900**. In this configuration, presentations described by the subject disclosure may in part be shown in the first of the display units **910**, while the remaining portion is presented in a second of the display units **910**.

[0144] The disk drive unit **916** may include a tangible computer-readable storage medium **922** on which is stored one or more sets of instructions (e.g., software **924**) embodying any one or more of the methods or functions described herein, including those methods illustrated above. The instructions **924** may also reside, completely or at least partially, within the main memory **904**, the static memory **906**, and/or within the processor **902** during execution thereof by the computer system **900**. The main memory **904** and the processor **902** also may constitute tangible computer-readable storage media.

[0145] Dedicated hardware implementations including, but not limited to, application specific integrated circuits, programmable logic arrays and other hardware devices that can likewise be constructed to implement the methods described herein. Application specific integrated circuits and programmable logic array can use downloadable instructions for executing state machines and/or circuit configurations to implement embodiments of the subject disclosure. Applications that may include the apparatus and systems of various embodiments broadly include a variety of electronic and computer systems. Some embodiments implement functions in two or more specific interconnected hardware modules or devices with related control and data signals communicated between and through the modules, or as portions of an application-specific integrated circuit. Thus, the example system is applicable to software, firmware, and hardware implementations.

[0146] In accordance with various embodiments of the subject disclosure, the operations or methods described herein are intended for operation as software programs or instructions running on or executed by a computer processor or other computing device, and which may include other forms of instructions manifested as a state machine implemented with logic components in an application specific integrated circuit or field programmable gate array. Furthermore, software implementations (e.g., software programs, instructions, etc.) including, but not limited to, distributed processing or component/object distributed processing, parallel processing, or virtual machine processing can also be constructed to implement the methods described herein. It is further noted that a computing device such as a processor, a controller, a state machine or other suitable device for executing instructions to perform operations or methods may perform such operations directly or indirectly by way of one or more intermediate devices directed by the computing device.

[0147] While the tangible computer-readable storage medium **622** is shown in an example embodiment to be a single medium, the term “tangible computer-readable storage medium” should be taken to include a single medium or multiple media (e.g., a centralized or distributed database, and/or associated caches and servers) that store the one or more sets of instructions. The term “tangible computer-readable storage medium” shall also be taken to include any non-transitory medium that is capable of storing or encoding a set of instructions for execution by the machine and that cause the machine to perform any one or more of the methods of the subject disclosure.

[0148] The term “tangible computer-readable storage medium” shall accordingly be taken to include, but not be limited to solid-state memories such as a memory card or other package that

houses one or more read-only (non-volatile) memories, random access memories, or other re-writable (volatile) memories, a magneto-optical or optical medium such as a disk or tape, or other tangible media which can be used to store information. Accordingly, the disclosure is considered to include any one or more of a tangible computer-readable storage medium, as listed herein and including art-recognized equivalents and successor media, in which the software implementations herein are stored.

[0149] Although the present specification describes components and functions implemented in the embodiments with reference to particular standards and protocols, the disclosure is not limited to such standards and protocols. Each of the standards for Internet and other packet switched network transmission (e.g., TCP/IP, UDP/IP, HTML, and HTTP) represents examples of the state of the art. Such standards are superseded from time-to-time by faster or more efficient equivalents having essentially the same functions. Wireless standards for device detection (e.g., RFID), short-range communications (e.g., Bluetooth, Wi-Fi, ZigBee), and long-range communications (e.g., WiMAX, GSM, CDMA, LTE) can be used by computer system **900**.

[0150] The illustrations of embodiments described herein are intended to provide a general understanding of the structure of various embodiments, and they are not intended to serve as a complete description of all the elements and features of apparatus and systems that might make use of the structures described herein. Many other embodiments will be apparent to those of skill in the art upon reviewing the above description. The exemplary embodiments can include combinations of features and/or steps from multiple embodiments. Other embodiments may be utilized and derived therefrom, such that structural and logical substitutions and changes may be made without departing from the scope of this disclosure. Figures are also merely representational and may not be drawn to scale. Certain proportions thereof may be exaggerated, while others may be minimized. Accordingly, the specification and drawings are to be regarded in an illustrative rather than a restrictive sense.

[0151] Although specific embodiments have been illustrated and described herein, it should be appreciated that any arrangement calculated to achieve the same purpose may be substituted for the specific embodiments shown. This disclosure is intended to cover any and all adaptations or variations of various embodiments. Combinations of the above embodiments, and other embodiments not specifically described herein, can be used in the subject disclosure.

[0152] The Abstract of the Disclosure is provided with the understanding that it will not be used to interpret or limit the scope or meaning of the claims. In addition, in the foregoing Detailed Description, it can be seen that various features are grouped together in a single embodiment for the purpose of streamlining the disclosure. This method of disclosure is not to be interpreted as reflecting an intention that the claimed embodiments require more features than are expressly recited in each claim. Rather, as the following claims reflect, inventive subject matter lies in less than all features of a single disclosed embodiment. Thus, the following claims are hereby incorporated into the Detailed Description, with each claim standing on its own as a separately claimed subject matter.

Claims

1. A method, comprising: receiving, by a processing system comprising a processor, signals via a common public radio interface (CPRI) from a base station, wherein the base station receives the signals via a plurality of wireless uplink channels; detecting, by the processing system, a recurring intermodulation interference of one of the signals based on a correlation analysis using an adaptive threshold, wherein the adaptive threshold is calculated from a baseline average signal strength across the plurality of wireless uplink channels without a predetermined number of wireless uplink channels having a highest average signal strength of the plurality of wireless uplink channels, wherein the correlation analysis is based in part on a threshold number of interference recurrences;

- and identifying, by the processing system, a source of the recurring intermodulation interference from the correlation analysis, wherein the source comprises one or more other transmitters, one or more faulty components, or both.
2. The method of claim 1, wherein information obtained from the correlation analysis comprises comparing the recurring intermodulation interference to a source interference profile to identify the source.
 3. The method of claim 2, wherein the source interference profile is stored in a database of profiles of interferers.
 4. The method of claim 3, wherein characteristics of the recurring intermodulation interference and the source interference profile relate to at least one of spectral data and frequency of occurrence data.
 5. The method of claim 3, wherein characteristics of the recurring intermodulation interference and the source interference profile relate to time of occurrence data.
 6. The method of claim 3, wherein the source interference profile comprises spectral data, time of occurrence data, frequency of occurrence data, geographic location of occurrence data, network traffic data, or any combinations thereof.
 7. The method of claim 1, wherein the source is identified as a communication device.
 8. The method of claim 7, further comprising: instructing, by the processing system, the base station to direct the communication device to communicate via another wireless uplink channel of the plurality of wireless uplink channels, wherein using the another wireless uplink channel mitigates interference.
 9. The method of claim 7, further comprising: instructing, by the processing system, the base station to utilize beam steering to avoid the source.
 10. A non-transitory, machine-readable storage device comprising instructions, which when executed by a processing system including a processor, facilitate performance of operations, comprising: receiving signals from a base station associated with the processing system, wherein the base station receives the signals via a plurality of wireless uplink channels; detecting a recurring intermodulation interference of one of the signals based on a correlation analysis using an adaptive threshold, wherein the adaptive threshold is calculated from a baseline average signal strength across the plurality of wireless uplink channels without a predetermined number of wireless uplink channels having a highest average signal strength of the plurality of wireless uplink channels, wherein the correlation analysis is based in part on a threshold number of interference recurrences; and identifying a source of the recurring intermodulation interference from the correlation analysis, wherein the source comprises one or more other transmitters, one or more faulty components, or both.
 11. The non-transitory, machine-readable storage device of claim 10, wherein the signals are received via a common public radio interface (CPRI).
 12. The non-transitory, machine-readable storage device of claim 11, wherein the correlation analysis comprises comparing one or more of the signals received via the CPRI to a spectral profile.
 13. The non-transitory, machine-readable storage device of claim 12, wherein the spectral profile further comprises spectral data, time of occurrence data, frequency of occurrence data, geographic location of occurrence data, network traffic data, or any combinations thereof.
 14. The non-transitory, machine-readable storage device of claim 10, wherein the operations further comprise determining that the source is detected from more than one of the plurality of wireless uplink channels.
 15. The non-transitory, machine-readable storage device of claim 14, wherein the operations further comprise determining an approximate location of the source according to location information obtained from the more than one of the plurality of wireless uplink channels.
 16. A base station, comprising: a processing system including a processor; and a memory that

stores executable instructions that, when executed by the processing system, facilitate performance of operations, comprising: receiving signals via a plurality of wireless uplink channels; detecting a recurring intermodulation interference based on a correlation analysis using an adaptive threshold, wherein the adaptive threshold is calculated from a baseline average signal strength across the plurality of wireless uplink channels without a predetermined number of wireless uplink channels having a highest average signal strength of the plurality of wireless uplink channels, wherein the correlation analysis is based in part on a threshold number of interference recurrences; and identifying a source for the recurring intermodulation interference from the correlation analysis, wherein the source comprises one or more other transmitters, one or more faulty components of the base station, or both.

17. The base station of claim 16, wherein the signals are received via a cable conforming to a common public radio interface (CPRI) protocol, and wherein the executable instructions facilitate performance of additional operations comprising: filtering the signals to remove the recurring intermodulation interference therefrom, thereby creating filtered signals; and providing the filtered signals to the cable conforming to the CPRI protocol.

18. The base station of claim 16, wherein a spectral profile used in the correlation analysis comprises time of occurrence data.

19. The base station of claim 18, wherein the spectral profile further comprises frequency of occurrence data.

20. The base station of claim 19, wherein the spectral profile further comprises geographic location of occurrence data, network traffic data, or any combinations thereof.
