

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250260899

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

SAKURABU; Hitoshi et al.

IMAGING ELEMENT, IMAGING APPARATUS, IMAGE DATA PROCESSING METHOD, AND PROGRAM THAT PERFORMS IMAGING IN A FIRST FRAME RATE AND OUTPUTS DATA IN A SECOND FRAME RATE

Abstract

An imaging element includes: a memory that stores captured image data obtained by imaging a subject at a first frame rate; an image processing circuit that performs processing on the captured image data; and an output circuit that outputs output image data obtained by performing the processing on the captured image data to an exterior of the imaging element at a second frame rate, wherein the image processing circuit performs cut-out processing with respect to one frame of the captured image data, the cut-out processing including cutting out partial image data indicating an image of a part of the subject in the captured image data from a designated address in the memory, the output image data includes image data based on the partial image data that is cut out from the captured image data, and the first frame rate is a frame rate higher than the second frame rate.

Inventors: SAKURABU; Hitoshi (Saitama, JP), HASEGAWA; Ryo (Saitama, JP), KAWAI; Tomoyuki (Saitama, JP)

Applicant: FUJIFILM CORPORATION (Tokyo, JP)

Family ID: 69642916

Appl. No.: 19/192279

Filed: April 28, 2025

Foreign Application Priority Data

JP	2018-163996	Aug. 31, 2018
----	-------------	---------------

Related U.S. Application Data

parent US continuation 18465139 20230911 parent-grant-document US 12323708 child US 19192279
parent US continuation 18054533 20221110 parent-grant-document US 11792519 child US 18465139
parent US continuation 17180888 20210222 parent-grant-document US 11533437 child US 18054533
parent WO continuation PCT/JP2019/025646 20190627 PENDING child US 17180888

Publication Classification

Int. Cl.: **H04N23/69** (20230101); **H04N5/262** (20060101); **H04N23/65** (20230101); **H04N23/67** (20230101); **H04N23/80** (20230101); **H04N23/951** (20230101); **H04N25/443** (20230101); **H04N25/78** (20230101); **H04N25/79** (20230101)

U.S. Cl.:

CPC **H04N23/69** (20230101); **H04N5/2628** (20130101); **H04N23/651** (20230101); **H04N23/675** (20230101); **H04N23/80** (20230101); **H04N23/951** (20230101); **H04N25/443** (20230101); **H04N25/78** (20230101); **H04N25/79** (20230101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation application of, and claims the benefit of, U.S. application Ser. No. 18/465,139, filed on Sep. 11, 2023, which is a continuation application of U.S. application Ser. No. 18/054,533, filed on Nov. 10, 2022, which is a continuation application of U.S. application Ser. No. 17/180,888, filed on Feb. 22, 2021, which is a continuation application of International Application No. PCT/JP2019/025646, filed on Jun. 27, 2019. Further, this application claims priority from Japanese Patent Application No. 2018-163996, filed on Aug. 31, 2018. The entire disclosure of each of the above applications is incorporated by reference herein.

BACKGROUND

Technical Field

[0002] The technology of the present disclosure relates to an imaging element, an imaging apparatus, an image data processing method, and a non-transitory program storage medium.

Related Art

[0003] JP2016-225970A discloses an imaging apparatus including an imaging element, a signal processing portion that performs predetermined signal processing on image data output from the imaging element, a display portion that displays an image, and a control portion that controls each of the imaging element, the signal processing portion, and the display portion.

[0004] The imaging element disclosed in JP2016-225970A comprises a first semiconductor substrate and a second semiconductor substrate that are laminated with each other and are electrically directly connected. An imaging unit that receives and photoelectrically converts an incidence ray, and an AD conversion unit that converts an analog image signal output from the imaging unit into digital image data are disposed in the first semiconductor substrate. A storage unit that stores the digital image data of one frame converted by the AD conversion unit, and a processing unit that performs resizing processing on the digital image data stored in the storage unit are disposed in the second semiconductor substrate. In the imaging element disclosed in JP2016-225970A, the processing unit cuts out image data of a predetermined region from the digital image

data of one frame before being stored in the storage unit and stores the cut-out image data in the storage unit.

[0005] JP2018-007210A discloses an imaging apparatus including an imaging unit and a control unit. The imaging unit included in the imaging apparatus disclosed in JP2018-007210A comprises a plurality of pixels and outputs a first image signal acquired by a first pixel group of the plurality of pixels and a second image signal acquired by a second image group of the plurality of pixels. The control unit included in the imaging apparatus disclosed in JP2018-007210A performs a first control and a second control. The first control is performing processing based on the second image signal and displaying a first image corresponding to the first image signal on a display screen. The second control is displaying a second image obtained by combining the first image signal with the second image signal on a display screen.

SUMMARY

[0006] One embodiment of the present invention provides an imaging element, an imaging apparatus, an image data processing method, and a non-transitory storage medium storing a program capable of reducing power consumption, compared to a case of cutting out partial image data from image data that is output to the outside of an imaging element without passing through a storage portion (i.e., memory), and outputting the partial image data.

[0007] A first aspect according to the technology of the present disclosure is an imaging element comprising a memory that stores captured image data obtained by imaging a subject at a first frame rate, the memory being incorporated in the imaging element; an image processing circuit that performs processing on the captured image data, the image processing circuit being incorporated in the imaging element; and an output circuit that outputs output image data obtained by performing the processing on the captured image data to an exterior of the imaging element at a second frame rate, the output circuit being incorporated in the imaging element, wherein the image processing circuit performs cut-out processing with respect to one frame of the captured image data, the cut-out processing including cutting out partial image data indicating an image of a part of the subject in the captured image data from a designated address in the memory, the output image data includes image data based on the partial image data that is cut out from the captured image data as a result of performing the cut-out processing by the image processing circuit, and the first frame rate is a frame rate higher than the second frame rate.

[0008] Accordingly, the imaging element of the first aspect according to the technology of the present disclosure can reduce power consumption compared to a case of cutting out the partial image data from image data output to the outside of the imaging element without passing through the storage portion, and outputting the partial image data.

[0009] A second aspect according to the technology of the present disclosure is the imaging element according to the first aspect, in which the cut-out processing is processing of cutting out the partial image data from the captured image data stored in the memory by random access to the memory.

[0010] Accordingly, the imaging element of the second aspect according to the technology of the present disclosure can quickly cut out the partial image data from the designated address compared to a case where random access to the memory is not available.

[0011] A third aspect according to the technology of the present disclosure is the imaging element according to the first aspect or the second aspect, wherein the memory is capable of storing the captured image data of a plurality of frames, the cut-out processing includes processing of cutting out the partial image data of the plurality of frames from the captured image data stored in the memory, and the output portion outputs, as the output image data, image data that is obtained by combining the partial image data of the plurality of frames cut out as a result of performing the cut-out processing by the image processing circuit.

[0012] Accordingly, the imaging element of the third aspect according to the technology of the present disclosure can reduce power consumption compared to a case of outputting the captured

image data to the outside of the imaging element, cutting out the partial image data of the plurality of frames from the captured image data outside the imaging element, and combining the partial image data of the plurality of frames.

[0013] A fourth aspect according to the technology of the present disclosure is the imaging element according to the third aspect, in which the partial image data is at least one of a plurality of pieces of divided region image data corresponding to a plurality of divided regions obtained by dividing the part.

[0014] Accordingly, the imaging element of the fourth aspect according to the technology of the present disclosure can reduce power consumption compared to a case of cutting out the partial image data from the captured image data of each of the plurality of frames and combining the cut-out partial image data of the plurality of frames.

[0015] A fifth aspect according to the technology of the present disclosure is the imaging element according to the fourth aspect, in which the plurality of pieces of divided region image data have a relationship in which mutually different pixels are thinned out in units of lines.

[0016] Accordingly, the imaging element of the fifth aspect according to the technology of the present disclosure can obtain a subject image of high reproducibility compared to a case of thinning out pixels at the same position in units of lines.

[0017] A sixth aspect according to the technology of the present disclosure is the imaging element according to the fourth aspect or the fifth aspect, in which the output image data includes combined data obtained by combining the plurality of pieces of divided region image data.

[0018] Accordingly, the imaging element of the sixth aspect according to the technology of the present disclosure can provide an image of high image quality compared to a case of outputting the partial image data of a single frame.

[0019] A seventh aspect according to the technology of the present disclosure is the imaging element according to the sixth aspect, in which the output circuit selectively outputs, as the partial image data, divided region image data of a part of the plurality of pieces of divided region image data or the combined data in accordance with a provided condition.

[0020] Accordingly, the imaging element of the seventh aspect according to the technology of the present disclosure can reduce power consumption compared to a case of outputting the combined data to the outside of the imaging element from the imaging element at all times.

[0021] An eighth aspect according to the technology of the present disclosure is the imaging element according to any one of the first aspect to the seventh aspect, wherein the subject is imaged by a photoelectric conversion element, in a case in which an area of the photoelectric conversion element corresponding to the part is designated by designating the part of the subject, the image processing circuit causes the area of the photoelectric conversion element to perform imaging, and the image processing circuit acquires partial image correspondence data corresponding to the partial image data at the first frame rate by performing imaging by the area of the photoelectric conversion element, and outputs image data based on the acquired partial image correspondence data to the exterior of the imaging element at the second frame rate.

[0022] Accordingly, the imaging element of the eighth aspect according to the technology of the present disclosure can reduce power consumption compared to a case of imaging the subject using all regions (i.e., the entire area) of the photoelectric conversion element at all times.

[0023] A ninth aspect according to the technology of the present disclosure is the imaging element according to any one of the first aspect to the eighth aspect, in which the part includes a plurality of regions in the subject, and the partial image data is a plurality of pieces of region image data indicating the plurality of regions in the captured image data.

[0024] Accordingly, the imaging element of the ninth aspect according to the technology of the present disclosure can reduce power consumption even in a case where a cut-out target is present across a plurality of regions of the subject.

[0025] A tenth aspect according to the technology of the present disclosure is the imaging element

according to any one of the first aspect to the ninth aspect, in which the output image data further includes wide range image data that indicates an image of a range of the subject wider than the part of the subject, and resolution of the wide range image data is lower than resolution of the partial image data.

[0026] Accordingly, the imaging element of the tenth aspect according to the technology of the present disclosure can reduce power consumption compared to a case where the resolution of the wide range image data is the same as the resolution of the partial image data.

[0027] An eleventh aspect according to the technology of the present disclosure is the imaging element according to the tenth aspect, in which the wide range image data is image data indicating an image of an entirety of the subject.

[0028] Accordingly, the imaging element of the eleventh aspect according to the technology of the present disclosure can reduce power consumption compared to a case where resolution of the image data indicating the image of the entirety of the subject is the same as the resolution of the partial image data.

[0029] A twelfth aspect according to the technology of the present disclosure is the imaging element according to any one of the first aspect to the eleventh aspect, in which the output image data further includes focusing control image data indicating an image of a range that is a range of the subject wider than the part of the subject and that is a predetermined range as a range required for a focusing control of an imaging apparatus including the imaging element.

[0030] Accordingly, even in a case where the focusing control is performed using the focusing control image data, the imaging element of the twelfth aspect according to the technology of the present disclosure can reduce power consumption even compared to a case of generating the focusing control image data outside the imaging element.

[0031] A thirteenth aspect according to the technology of the present disclosure is the imaging element according to any one of the first aspect to the twelfth aspect, in which the imaging element is a stacked imaging element that includes a photoelectric conversion element, and in which the photoelectric conversion element is stacked on the memory.

[0032] Accordingly, the imaging element of the thirteenth aspect according to the technology of the present disclosure can output image data subjected to image processing in the imaging element to the outside of the imaging element.

[0033] A fourteenth aspect according to the technology of the present disclosure is an imaging apparatus comprising the imaging element according to any one of the first aspect to the thirteenth aspect of the technology of the present disclosure, and a display processor that is configured to perform a control for displaying an image based on the output image data output by the image processing circuit on a display in an enlarged manner.

[0034] Accordingly, the imaging apparatus of the fourteenth aspect according to the technology of the present disclosure can reduce power consumption compared to a case of cutting out the partial image data from image data output to the outside of the imaging element without passing through the storage portion, and outputting the partial image data.

[0035] A fifteenth aspect according to the technology of the present disclosure is an image data processing method of an imaging element in which a memory, an image processing circuit, and an output circuit are incorporated, the image data processing method comprising: storing, by the memory, captured image data obtained by imaging a subject at a first frame rate; performing, by the image processing circuit, processing on the captured image data; outputting, by the output circuit, output image data obtained by performing the processing on the captured image data to an exterior of the imaging element at a second frame rate; and performing, by the image processing circuit, cut-out processing with respect to one frame of the captured image data, the cut-out processing including cutting out partial image data indicating an image of a part of the subject in the captured image data from a designated address in the memory, wherein the output image data includes image data based on the partial image data that is cut out from the captured image data as a result of

performing the cut-out processing by the image processing circuit, and the first frame rate is a frame rate higher than the second frame rate.

[0036] Accordingly, the image data processing method of the fifteenth aspect according to the technology of the present disclosure can reduce power consumption compared to a case of cutting out the partial image data from image data output to the outside of the imaging element without passing through the storage portion, and outputting the partial image data.

[0037] A sixteenth aspect according to the technology of the present disclosure is a non-transitory storage medium storing a program that causes a computer to function as an image processing circuit and an output portion included in an imaging element, and to perform an image data processing, the imaging element incorporating a memory, the image processing circuit, and the output circuit, the image data processing comprising: storing, by the memory, captured image data obtained by imaging a subject at a first frame rate; performing, by the image processing circuit, processing on the captured image data; outputting, by the output circuit, output image data obtained by performing the processing on the captured image data to an exterior of the imaging element at a second frame rate; and performing, by the image processing circuit, cut-out processing with respect to one frame of the captured image data, the cut-out processing including cutting out partial image data indicating an image of a part of the subject in the captured image data from a designated address in the memory, wherein the output image data includes image data based on the partial image data that is cut out from the captured image data as a result of performing the cut-out processing by the image processing circuit, and the first frame rate is a frame rate higher than the second frame rate.

[0038] Accordingly, the program of the sixteenth aspect according to the technology of the present disclosure can reduce power consumption compared to a case of cutting out the partial image data from image data output to the outside of the imaging element without passing through the storage portion, and outputting the partial image data.

[0039] A seventeenth aspect according to the technology of the present disclosure is an imaging element comprising a memory that stores captured image data obtained by imaging a subject at a first frame rate and is incorporated in the imaging element, a processor that performs processing on the captured image data, outputs output image data obtained by performing the processing on the captured image data to an outside of the imaging element at a second frame rate, and is incorporated in the imaging element, in which the processor performs cut-out processing of cutting out partial image data indicating an image of a part of the subject in the captured image data from a designated address in the memory, the output image data includes image data based on the partial image data that is cut out from the captured image data by performing the cut-out processing by the processor, and the first frame rate is a frame rate higher than the second frame rate.

[0040] According to one embodiment of the present invention, an effect of being able to reduce power consumption compared to a case of cutting out the partial image data from the image data output to the outside of the imaging element without passing through the storage portion, and outputting the partial image data is achieved.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0041] FIG. 1 is a perspective view illustrating one example of an exterior of an imaging apparatus that is an interchangeable lens camera according to first to fourth embodiments.

[0042] FIG. 2 is a rear view illustrating a rear surface side of the imaging apparatus according to the first to fourth embodiments.

[0043] FIG. 3 is a block diagram illustrating one example of a hardware configuration of the imaging apparatus according to the first to fourth embodiments.

[0044] FIG. 4 is a schematic configuration diagram illustrating one example of a configuration of a hybrid finder included in the imaging apparatus according to the first to fourth embodiments.

[0045] FIG. 5 is a schematic configuration diagram illustrating one example of a schematic configuration of an imaging element included in the imaging apparatus according to the first to fourth embodiments.

[0046] FIG. 6 is a block diagram illustrating one example of a main configuration of the imaging element included in the imaging apparatus according to the first to fourth embodiments.

[0047] FIG. 7 is a flowchart illustrating one example of a flow of image data generation processing according to the first embodiment.

[0048] FIG. 8 is a flowchart illustrating one example of a flow of image data output processing according to the first to fourth embodiments.

[0049] FIG. 9 is a flowchart illustrating one example of a flow of display control processing according to the first to third embodiments.

[0050] FIG. 10 is a conceptual diagram illustrating one example of a schematic configuration of captured image data and combined data of a first frame to a third frame.

[0051] FIGS. 11A and 11B are state transition diagrams illustrating one example of a flow of data of the imaging apparatus. FIG. 11A is a state transition diagram illustrating one example of a flow of data of an imaging apparatus according to a technology in the related art. FIG. 11B is a state transition diagram illustrating one example of a flow of data of an imaging apparatus according to an embodiment of the technology of the present disclosure.

[0052] FIG. 12 is a state transition diagram illustrating one example of a flow of data of the imaging apparatus according to the embodiment of the technology of the present disclosure.

[0053] FIGS. 13A and 13B are state transition diagrams illustrating one example of a flow of processing of the imaging apparatus. FIG. 13A is a state transition diagram illustrating one example of a flow of processing of the imaging apparatus according to the technology in the related art. FIG. 13B is a state transition diagram illustrating one example of a flow of processing of the imaging apparatus according to the embodiment of the technology of the present disclosure.

[0054] FIG. 14 is a conceptual diagram illustrating a state example in which an image showing a face region of a person who is a subject is displayed in an enlarged manner after the face region is detected.

[0055] FIG. 15 is a conceptual diagram illustrating a first modification example of the schematic configuration of the captured image data and the combined data of the first frame to the third frame.

[0056] FIG. 16 is a conceptual diagram illustrating a second modification example of the schematic configuration of the captured image data and the combined data of the first frame to the third frame.

[0057] FIG. 17 is a descriptive diagram for describing a difference between thinned output image data and non-thinned output image data.

[0058] FIGS. 18A and 18B are descriptive diagrams for describing an exposure method of the imaging apparatus according to the first to fourth embodiments. FIG. 18A is a descriptive diagram for describing a first exposure method of the imaging apparatus according to the first to fourth embodiments. FIG. 18B is a descriptive diagram for describing a second exposure method of the imaging apparatus according to the first to fourth embodiments.

[0059] FIG. 19 is a state transition diagram illustrating one example of a flow of data of the imaging apparatus according to the embodiment of the technology of the present disclosure.

[0060] FIG. 20 is a state transition diagram illustrating one example of a flow of data of the imaging apparatus according to the embodiment of the technology of the present disclosure.

[0061] FIG. 21 is a flowchart illustrating one example of a flow of image data generation processing according to the second embodiment.

[0062] FIG. 22 is a flowchart illustrating one example of a flow of single region cut-out processing

according to the second embodiment.

[0063] FIG. **23** is a flowchart illustrating one example of a flow of plural region cut-out processing according to the second embodiment.

[0064] FIG. **24** is a state transition diagram illustrating one example of a flow of data of the imaging apparatus according to the embodiment of the technology of the present disclosure.

[0065] FIG. **25** is a state transition diagram illustrating one example of a flow of data of the imaging apparatus according to the embodiment of the technology of the present disclosure.

[0066] FIG. **26** is a flowchart illustrating one example of a flow of image data generation processing according to the third embodiment.

[0067] FIG. **27** is a state transition diagram illustrating one example of a flow of data of the imaging apparatus according to the embodiment of the technology of the present disclosure.

[0068] FIG. **28** is a flowchart illustrating one example of a flow of output image data processing according to the third embodiment.

[0069] FIG. **29** is a flowchart illustrating one example of a flow of imaging control processing according to the fourth embodiment.

[0070] FIG. **30** is a flowchart illustrating one example of a flow of image data generation processing according to the fourth embodiment.

[0071] FIG. **31** is a conceptual diagram illustrating one example of a state where a program according to the embodiment is installed on the imaging element from a storage medium storing the program according to the embodiment.

[0072] FIG. **32** is a block diagram illustrating one example of a schematic configuration of a smart device in which the imaging element according to the first to fourth embodiments is incorporated.

DETAILED DESCRIPTION

[0073] Hereinafter, one example of an embodiment of an imaging apparatus according to the embodiment of the technology of the present disclosure will be described in accordance with the appended drawings.

First Embodiment

[0074] For example, as illustrated in FIG. **1**, an imaging apparatus **10** is an interchangeable lens camera. The imaging apparatus **10** is a digital camera that includes an imaging apparatus main body **12** and an interchangeable lens **14** interchangeably mounted on the imaging apparatus main body **12**, and does not include a reflex mirror. The interchangeable lens **14** includes an imaging lens **18** including a focus lens **16** that is movable in an optical axis direction by a manual operation.

[0075] A hybrid finder (registered trademark) **21** is disposed in the imaging apparatus main body **12**. For example, the hybrid finder **21** here refers to a finder in which an optical view finder (hereinafter, referred to as the OVF) and an electronic view finder (hereinafter, referred to as the EVF) are selectively used. The abbreviation OVF stands for “Optical View Finder”. The abbreviation EVF stands for “Electronic View Finder”.

[0076] The interchangeable lens **14** is interchangeably mounted on the imaging apparatus main body **12**. A focus ring **22** that is used at a time of a manual focus mode is disposed in a lens barrel of the interchangeable lens **14**. The focus lens **16** moves in the optical axis direction in accordance with a manual rotation operation of the focus ring **22**, and an image of subject light is formed on an imaging element **20** (refer to FIG. **3**), described later, at a focal position corresponding to a subject distance.

[0077] A finder window **24** of the OVF included in the hybrid finder **21** is disposed on a front surface of the imaging apparatus main body **12**. In addition, a finder switching lever (finder switching portion) **23** is disposed on the front surface of the imaging apparatus main body **12**. In a case where the finder switching lever **23** is rotationally moved in a direction of an arrow SW, switching is performed between an optical image that is visually recognizable by the OVF, and an electronic image (live view image) that is visually recognizable by the EVF.

[0078] An optical axis L2 of the OVF is an optical axis different from an optical axis L1 of the

interchangeable lens **14**. A release button **25** and a dial **28** for setting such as a mode of an imaging system and a mode of a playback system are disposed on an upper surface of the imaging apparatus main body **12**.

[0079] The release button **25** functions as an imaging preparation instruction portion and an imaging instruction portion, and a push operation of two stages of an imaging preparation instruction state and an imaging instruction state can be detected. For example, the imaging preparation instruction state refers to a state where a push is performed to an intermediate position (half push position) from a standby position, and the imaging instruction state refers to a state where a push is performed to a final push position (full push position) beyond the intermediate position. Hereinafter, the “state where a push is performed to the half push position from the standby position” will be referred to as a “half push state”, and the “state where a push is performed to the full push position from the standby position” will be referred to as a “full push state”.

[0080] In the imaging apparatus **10** according to a first embodiment, an imaging mode and a playback mode are selectively set as an operation mode in accordance with an instruction from a user. In the imaging mode, the manual focus mode and an auto focus mode are selectively set in accordance with an instruction from the user. In the auto focus mode, an imaging condition is adjusted by causing the release button **25** to enter the half push state, and then, exposure is performed in a case where the full push state is subsequently set. That is, after an exposure state is set by an automatic exposure (AE) function by causing the release button **25** to enter the half push state, a focusing control is performed by an auto-focus (AF) function, and imaging is performed in a case where the release button **25** is caused to enter the full push state.

[0081] For example, as illustrated in FIG. **2**, a touch panel display **30**, a cross key **32**, a menu key **34**, an instruction button **36**, and a finder eyepiece portion **38** are disposed on a rear surface of the imaging apparatus main body **12**.

[0082] The touch panel display **30** comprises a liquid crystal display (hereinafter, referred to as a “first display”) **40** and a touch panel **42** (refer to FIG. **3**).

[0083] The first display **40** displays an image, a text information, and the like. The first display **40** is used for displaying a live view image (live preview image) that is one example of a consecutive frame image obtained by imaging in consecutive frames at a time of the imaging mode. The first display **40** is also used for displaying a still picture that is one example of a single frame image obtained by imaging in a single frame in a case where an instruction to image a still picture is provided. Furthermore, the first display **40** is used for displaying a playback image at a time of the playback mode and/or displaying a menu screen or the like.

[0084] The touch panel **42** is a transmissive touch panel and is overlaid on a surface of a display region of the first display **40**. The touch panel **42** detects a contact of an instruction object such as a finger or a stylus pen. The touch panel **42** outputs detection result information indicating a detection result (presence or absence of the contact of the instruction object with the touch panel **42**) to a predetermined output destination (for example, a CPU **52** (refer to FIG. **3**) described later) in a predetermined cycle (for example, 100 milliseconds). In a case where the touch panel **42** detects the contact of the instruction object, the detection result information includes two-dimensional coordinates (hereinafter, referred to as the “coordinates”) for specifying a contact position of the instruction object on the touch panel **42**. In a case where the touch panel **42** does not detect the contact of the instruction object, the detection result information does not include the coordinates.

[0085] The cross key **32** has a function as a multifunction key that outputs various instruction signals for selecting one or a plurality of menus, zooming, and/or frame advance or the like. The menu key **34** is an operation key that has both of a function as a menu button for providing an instruction to display one or a plurality of menus on a screen of the first display **40** and a function as an instruction button for providing an instruction for confirmation, execution, and the like of a

selected content. The instruction button **36** is operated in a case of deleting a desired target such as a selected item, canceling a designated content, and returning to an immediately previous operation state.

[0086] The imaging apparatus **10** has a still picture imaging mode and a motion picture imaging mode as an operation mode of the imaging system. The still picture imaging mode is an operation mode in which a still picture obtained by imaging a subject by the imaging apparatus **10** is recorded, and the motion picture imaging mode is an operation mode in which a motion picture obtained by imaging the subject by the imaging apparatus **10** is recorded.

[0087] For example, as illustrated in FIG. **3**, the imaging apparatus **10** includes a mount **46** (refer to FIG. **1**) comprised in the imaging apparatus main body **12**, and a mount **44** on an interchangeable lens **14** side corresponding to the mount **46**. The interchangeable lens **14** is interchangeably mounted on the imaging apparatus main body **12** by joining the mount **44** to the mount **46**.

[0088] The imaging lens **18** includes a sliding mechanism **48** and a motor **50**. The sliding mechanism **48** moves the focus lens **16** along the optical axis **L1** by operating the focus ring **22**. The focus lens **16** is slidably attached to the sliding mechanism **48** along the optical axis **L1**. The motor **50** is connected to the sliding mechanism **48**, and the sliding mechanism **48** slides the focus lens **16** along the optical axis **L1** by receiving motive power of the motor **50**.

[0089] The motor **50** is connected to the imaging apparatus main body **12** through the mounts **44** and **46**, and driving thereof is controlled in accordance with a command from the imaging apparatus main body **12**. In the first embodiment, a stepping motor is applied as one example of the motor **50**. Accordingly, the motor **50** operates in synchronization with pulse power in accordance with a command from the imaging apparatus main body **12**. While an example in which the motor **50** is disposed in the imaging lens **18** is illustrated in the example illustrated in FIG. **3**, the technology of the present disclosure is not limited thereto, and the motor **50** may be disposed in the imaging apparatus main body **12**.

[0090] The imaging apparatus **10** is a digital camera that records the still picture and the motion picture obtained by imaging the subject. The imaging apparatus main body **12** comprises an operation portion **54**, an external interface (I/F) **63**, and a rear stage circuit **90**. The rear stage circuit **90** is a circuit on a side of receiving data transmitted from the imaging element **20**. In the first embodiment, an integrated circuit (IC) is employed as the rear stage circuit **90**. Large-scale integration (LSI) is illustrated as one example of the IC.

[0091] The rear stage circuit **90** includes the central processing unit (CPU) **52**, an I/F **56**, a primary storage portion **58**, a secondary storage portion **60**, an image processing portion **62**, a first display control portion **64**, a second display control portion **66**, a position detection portion **70**, and a device control portion **74**. A single CPU is illustrated as the CPU **52** in the first embodiment. However, the technology of the present disclosure is not limited thereto, and a plurality of CPUs may be employed instead of the CPU **52**. That is, various types of processing executed by the CPU **52** may be executed by one processor or a plurality of physically separated processors.

[0092] In the first embodiment, each of the image processing portion **62**, the first display control portion **64**, the second display control portion **66**, the position detection portion **70**, and the device control portion **74** is implemented by an application specific integrated circuit (ASIC). However, the technology of the present disclosure is not limited thereto. For example, instead of the ASIC, at least one of a programmable logic device (PLD) or a field-programmable gate array (FPGA) may be employed. Alternatively, at least one of the ASIC, the PLD, or the FPGA may be employed. Alternatively, a computer including a CPU, a read only memory (ROM), and a random access memory (RAM) may be employed. The CPU may be a single CPU or a plurality of CPUs. In addition, at least one of the image processing portion **62**, the first display control portion **64**, the second display control portion **66**, the position detection portion **70**, or the device control portion **74** may be implemented by a combination of a hardware configuration and a software configuration.

[0093] The CPU 52, the I/F 56, the primary storage portion 58, the secondary storage portion 60, the image processing portion 62, the first display control portion 64, the second display control portion 66, the operation portion 54, the external I/F 63, and the touch panel 42 are connected to each other through a bus 68.

[0094] The CPU 52 controls the entire imaging apparatus 10. In the imaging apparatus 10 according to the first embodiment, at a time of the auto focus mode, the CPU 52 performs the focusing control by controlling driving of the motor 50 such that a contrast value of the image obtained by imaging is maximized. In addition, at the time of the auto focus mode, the CPU 52 calculates AE information that is a physical quantity indicating brightness of the image obtained by imaging. In a case where the release button 25 is caused to enter the half push state, the CPU 52 derives a shutter speed and an F number corresponding to the brightness of the image indicated by the AE information. The exposure state is set by controlling each related portion to achieve the derived shutter speed and the F number.

[0095] The primary storage portion 58 means a volatile memory and refers to, for example, a RAM. The secondary storage portion 60 means a non-volatile memory and refers to, for example, a flash memory or a hard disk drive (HDD).

[0096] The operation portion 54 is a user interface that is operated by the user in a case of providing various instructions to the rear stage circuit 90. The operation portion 54 includes the release button 25, the dial 28, the finder switching lever 23, the cross key 32, the menu key 34, and the instruction button 36. Various instructions received by the operation portion 54 are output to the CPU 52 as an operation signal, and the CPU 52 executes processing corresponding to the operation signal input from the operation portion 54.

[0097] The position detection portion 70 is connected to the CPU 52. The position detection portion 70 is connected to the focus ring 22 through the mounts 44 and 46, detects a rotation angle of the focus ring 22, and outputs rotation angle information indicating the rotation angle that is a detection result to the CPU 52. The CPU 52 executes processing corresponding to the rotation angle information input from the position detection portion 70.

[0098] In a case where the imaging mode is set, image light showing the subject is formed on a light receiving surface of the color imaging element 20 through the imaging lens 18 including the focus lens 16 which is movable by a manual operation, and a mechanical shutter 72.

[0099] The device control portion 74 is connected to the CPU 52. In addition, the device control portion 74 is connected to the imaging element 20 and the mechanical shutter 72. Furthermore, the device control portion 74 is connected to the motor 50 of the imaging lens 18 through the mounts 44 and 46.

[0100] The device control portion 74 controls the imaging element 20, the mechanical shutter 72, and the motor 50 under control of the CPU 52.

[0101] For example, as illustrated in FIG. 4, the hybrid finder 21 includes an OVF 76 and an EVF 78. The OVF 76 is a reverse Galilean finder including an objective lens 81 and an eyepiece lens 86, and the EVF 78 includes a second display 80, a prism 84, and the eyepiece lens 86.

[0102] A liquid crystal shutter 88 is arranged in front of the objective lens 81. The liquid crystal shutter 88 blocks light such that the optical image is not incident on the objective lens 81 in a case of using the EVF 78.

[0103] The prism 84 guides the electronic image or various information to be displayed on the second display 80 to the eyepiece lens 86 by reflecting the electronic image or various information, and combines the optical image with the electronic image and/or various information to be displayed on the second display 80.

[0104] In a case where the finder switching lever 23 is rotationally moved in the direction of the arrow SW illustrated in FIG. 1, an OVF mode in which the optical image is visually recognizable by the OVF 76 and an EVF mode in which the electronic image is visually recognizable by the EVF 78 are alternately switched each time the finder switching lever 23 is rotationally moved.

[0105] In a case of the OVF mode, the second display control portion **66** enables the optical image to be visually recognized from the eyepiece portion by controlling the liquid crystal shutter **88** to enter a non-light blocking state. In a case of the EVF mode, the second display control portion **66** enables only the electronic image displayed on the second display **80** to be visually recognized from the eyepiece portion by controlling the liquid crystal shutter **88** to enter a light blocking state. [0106] The imaging element **20** is one example of a “laminated imaging element” according to the embodiment of the technology of the present disclosure. For example, the imaging element **20** is a complementary metal oxide semiconductor (CMOS) image sensor. For example, as illustrated in FIG. 5, a photoelectric conversion element **92**, a processing circuit **94**, and a memory **96** are incorporated in the imaging element **20**. In the imaging element **20**, the photoelectric conversion element **92** is laminated with the processing circuit **94** and the memory **96**. The memory **96** is one example of a storage portion according to the embodiment of the technology of the present disclosure.

[0107] The processing circuit **94** is, for example, LSI, and the memory **96** is, for example, a RAM. A dynamic random access memory (DRAM) is employed as one example of the memory **96** in the first embodiment. However, the technology of the present disclosure is not limited thereto, and a static random access memory (SRAM) may be used.

[0108] The processing circuit **94** is implemented by an ASIC in the first embodiment. However, the technology of the present disclosure is not limited thereto. For example, at least one of a PLD or an FPGA may be employed instead of the ASIC. Alternatively, at least one of the ASIC, the PLD, or the FPGA may be employed. The CPU may be a single CPU or a plurality of CPUs. Alternatively, a computer including a CPU, a ROM, and a RAM may be employed. Alternatively, the processing circuit **94** may be implemented by a combination of a hardware configuration and a software configuration.

[0109] The photoelectric conversion element **92** includes a plurality of photosensors arranged in a matrix form. In the first embodiment, photodiodes are employed as one example of the photosensors. Photodiodes of “4896×3265” pixels are illustrated as one example of the plurality of photosensors.

[0110] The photoelectric conversion element **92** comprises color filters, and the color filters include a G filter corresponding to green (G) that most contributes to obtaining a brightness signal, an R filter corresponding to red (R), and a B filter corresponding to blue (B). In the first embodiment, the G filter, the R filter, and the B filter are arranged with a predetermined periodicity in each of a row direction (horizontal direction) and a column direction (vertical direction) for the plurality of photodiodes of the photoelectric conversion element **92**. Thus, the imaging apparatus **10** can perform processing in accordance with a repeating pattern in a case of performing demosaicing and the like on R, G, and B signals. The demosaicing refers to processing of calculating all color information for each pixel from a mosaic image corresponding to color filter arrangement of a single plate color imaging element. For example, in a case of an imaging element consisting of color filters of three colors of R, G, and B, the demosaicing means processing of calculating color information about all of R, G, and B for each pixel from a mosaic image consisting of R, G, and B.

[0111] While the CMOS image sensor is illustrated as the imaging element **20**, the technology of the present disclosure is not limited thereto. For example, the technology of the present disclosure is also established in a case where the photoelectric conversion elements **92** is a charge coupled device (CCD) image sensor.

[0112] The imaging element **20** has a so-called electronic shutter function and controls an electric charge accumulation time period of each photodiode in the photoelectric conversion element **92** by performing the electronic shutter function under control of the device control portion **74**. The electric charge accumulation time period refers to a so-called shutter speed.

[0113] The processing circuit **94** is controlled by the device control portion **74**. The processing circuit **94** reads out captured image data that is obtained by imaging the subject by the photoelectric

conversion element **92**. The “captured image data” here refers to image data indicating the subject. The captured image data is signal electric charges accumulated in the photoelectric conversion element **92**. The processing circuit **94** performs analog/digital (A/D) conversion on the captured image data read out from the photoelectric conversion element **92**. The processing circuit **94** stores, in the memory **96**, the captured image data obtained by performing the A/D conversion on the captured image data. The processing circuit **94** acquires the captured image data from the memory **96** and outputs, to the I/F **56** of the rear stage circuit **90**, output image data that is image data based on the acquired captured image data. Hereinafter, for convenience of description, the “output image data that is image data based on the captured image data” will be simply referred to as the “output image data”.

[0114] The processing circuit **94** performs first processing and second processing on the captured image data. The first processing refers to processing of reading out the captured image data from the photoelectric conversion element **92** and storing the read-out captured image data in the memory **96**. The second processing refers to processing of outputting the output image data to the outside of the imaging element **20**. For example, the “outside of the imaging element **20**” here refers to the I/F **56** of the rear stage circuit **90**.

[0115] The first processing includes cut-out processing. The cut-out processing refers to processing of cutting out partial image data indicating an image of a part of the subject in the captured image data from a designated address in the memory **96** in a state where the captured image data is stored in the memory **96**. The partial image data is at least one of a plurality of pieces of divided region image data corresponding to a plurality of divided regions obtained by dividing a part of the subject.

[0116] The “plurality of pieces of divided region image data” here have a relationship in which pixels different from each other are thinned out in units of lines. In the first embodiment, horizontal lines are thinned out in the vertical direction by skipping two lines at a time. However, the technology of the present disclosure is not limited thereto. For example, the horizontal lines may be thinned out in the vertical direction by skipping one line at a time, or the horizontal lines may be thinned out in the vertical direction three or more lines at a time. Vertical lines may be thinned out in the horizontal direction a predetermined number of lines more than or equal to one line at a time. Thinning out may be performed in accordance with a predetermined rule for each pixel or in units of pixel groups of a few pixels.

[0117] As described in detail later, for example, as the “plurality of pieces of divided region image data” here, partial image data **200** (refer to FIGS. **11A** and **11B** and FIG. **12**) obtained from the captured image data of each of a first frame to a third frame illustrated in FIG. **10**, FIG. **15**, or FIG. **16** is illustrated.

[0118] The output image data output from the processing circuit **94** is broadly classified into the partial image data, wide range image data, and focusing control image data. The wide range image data refers to image data indicating an image of a range of the subject wider than the part of the subject related to the partial image data. For example, the wide range image data refers to entirety image data that indicates an image of the entirety of the subject in a range falling within an angle of view imageable by all photodiodes in a partial region **92A** (refer to FIGS. **11A** and **11B**) of the photoelectric conversion element **92**. The focusing control image data refers to image data indicating an image of a range that is a range of the subject wider than the part of the subject related to the partial image data and is a predetermined range as a range required for the focusing control of the imaging apparatus **10**. For example, the “predetermined range” here refers to a range that is obtained in advance by the CPU **52** by test using an actual apparatus and/or computer simulation or the like as a range which can be used for specifying a focusing state using so-called contrast AF or phase difference AF. In the first embodiment, “all photodiodes” refer to usable photodiodes that do not have defects.

[0119] In the imaging element **20**, the subject is imaged at a first frame rate. The processing circuit

94 performs the first processing at the first frame rate and performs the second processing at a second frame rate. The first frame rate is a frame rate higher than the second frame rate. In the first embodiment, the second frame rate is 60 frames per second (fps), and the first frame rate is 240 fps. However, the technology of the present disclosure is not limited thereto, and a relationship “second frame rate<first frame rate” may be satisfied. In addition, the first frame rate is a frame rate that is variable in a range of not less than or equal to the second frame rate.

[0120] For example, as illustrated in FIG. 6, the processing circuit **94** includes a photoelectric conversion element drive circuit **94A**, an analog-to-digital (AD) conversion circuit **94B**, an image processing circuit **94C**, and an output circuit **94D** and operates under control of the CPU **52**. The photoelectric conversion element drive circuit **94A** is connected to the photoelectric conversion element **92** and the AD conversion circuit **94B**. The memory **96** is connected to the AD conversion circuit **94B** and the image processing circuit **94C**. The image processing circuit **94C** is connected to the output circuit **94D**. The output circuit **94D** is connected to the I/F **56** of the rear stage circuit **90**.

[0121] The photoelectric conversion element drive circuit **94A** controls the photoelectric conversion element **92** and reads out analog captured image data from the photoelectric conversion element **92** under control of the device control portion **74**. The AD conversion circuit **94B** digitizes the captured image data read out by the photoelectric conversion element drive circuit **94A** and stores the digitized captured image data in the memory **96**.

[0122] The memory **96** is a memory that can store the captured image data of a plurality of frames. The image processing circuit **94C** is one example of a processing portion according to the embodiment of the technology of the present disclosure and performs processing on the captured image data. That is, the image processing circuit **94C** cuts out the output image data from the captured image data stored in the memory **96** by random access to the memory **96**. The image processing circuit **94C** performs necessary signal processing on the cut-out output image data. The “random access” here refers to an access method capable of directly accessing a location in which target data is stored in the memory **96**.

[0123] The first processing is performed by the photoelectric conversion element drive circuit **94A**, the AD conversion circuit **94B**, the memory **96**, and the image processing circuit **94C**. That is, processing in the photoelectric conversion element drive circuit **94A**, the AD conversion circuit **94B**, the memory **96**, and the image processing circuit **94C** is performed at the first frame rate.

[0124] While an example of a form in which processing in the photoelectric conversion element drive circuit **94A**, the AD conversion circuit **94B**, the memory **96**, and the image processing circuit **94C** is performed at the first frame rate is illustratively described here, the technology of the present disclosure is not limited thereto. For example, among reading out by the photoelectric conversion element drive circuit **94A**, storage of the captured image data in the memory **96** by the AD conversion circuit **94B**, and processing by the image processing circuit **94C**, at least storage of the captured image data in the memory **96** by the AD conversion circuit **94B** may be performed at the first frame rate.

[0125] The output circuit **94D** performs the second processing. That is, the output circuit **94D** outputs the output image data subjected to the signal processing by the image processing circuit **94C** to the I/F **56** of the rear stage circuit **90** at the second frame rate. The output circuit **94D** is one example of an “output portion” according to the embodiment of the technology of the present disclosure.

[0126] Next, actions of parts of the imaging apparatus **10** according to the embodiment of the technology of the present disclosure will be described.

[0127] Hereinafter, for convenience of description, the first display **40** and the second display **80** will be referred to as a “display apparatus” without a reference sign unless otherwise necessary to distinguish therebetween for description. The display apparatus is one example of a “display portion” according to the embodiment of the technology of the present disclosure. In addition, hereinafter, for convenience of description, the first display control portion **64** and the second

display control portion **66** will be referred to as a “display control portion” without a reference sign unless otherwise necessary to distinguish therebetween for description. The display control portion is one example of a “control portion” according to the embodiment of the technology of the present disclosure. In addition, hereinafter, for convenience of description, a case of displaying the live view image on the display apparatus will be described.

[0128] First, image data generation processing executed by the processing circuit **94** will be described with reference to FIG. 7. The image data generation processing illustrated in FIG. 7 is performed at the first frame rate by the processing circuit **94**. Hereinafter, for convenience of description, the memory **96** will be assumed to be a memory capable of storing the captured image data of three frames using a FIFO method.

[0129] In the image data generation processing illustrated in FIG. 7, first, in step **S100**, for example, the photoelectric conversion element drive circuit **94A** reads out the captured image data from the partial region **92A** of the photoelectric conversion element **92** illustrated in FIGS. **11A** and **11B**, and then, the image data generation processing transitions to step **S102**.

[0130] For example, the captured image data obtained from the partial region **92A** of the photoelectric conversion element **92** by executing processing of step **S100** is captured image data obtained by imaging the subject by the partial region **92A** of the photoelectric conversion element **92** as illustrated in FIGS. **11A** and **11B**. While the captured image data obtained by imaging by the partial region **92A** is illustrated here for convenience of description, the technology of the present disclosure is not limited thereto. For example, captured image data obtained by imaging the subject by all photodiodes of the photoelectric conversion element **92** may be used, or a captured image obtained by imaging the subject by each of a plurality of locations in the photoelectric conversion element **92** may be used.

[0131] For example, the captured image data of one frame read out from the partial region **92A** of the photoelectric conversion element **92** by executing processing of step **S100** is image data in which the horizontal lines are thinned out in the vertical direction by skipping two lines at a time as illustrated in FIG. **10**. In addition, for example, as illustrated in FIG. **10**, in a case where a cycle for reading out the captured image data of three frames is one cycle, the captured image data read out from the partial region **92A** of the photoelectric conversion element **92** is thinned out by shifting the horizontal lines one line at a time in the vertical direction for each frame in one cycle.

[0132] While a state example of the captured image data of the first frame to the third frame is schematically illustrated in the example illustrated in FIG. **10**, pixels from a fourth frame are thinned out using the same method as the first frame to the third frame. In addition, while an example of thinning out in a case where one cycle is three frames is illustrated in the example illustrated in FIG. **10** for convenience of description, the technology of the present disclosure is not limited thereto, and thinning out may be performed using the same method even in a case where one cycle is four frames or more.

[0133] A method of thinning out for the captured image data is not limited to a method of thinning out the horizontal lines in the vertical direction by shifting one line at a time. For example, a method of thinning out the vertical lines in the horizontal direction by shifting one line at a time may be used, or a method of thinning out in accordance with a predetermined rule in units of a predetermined number of pixels more than or equal to one pixel may be used.

[0134] In step **S102**, the AD conversion circuit **94B** digitizes and stores the captured image data read out by the photoelectric conversion element drive circuit **94A** in the memory **96**, and then, the image data generation processing transitions to step **S104**.

[0135] In step **S104**, the image processing circuit **94C** determines whether or not a cut-out instruction is received by the touch panel **42** and/or the operation portion **54**. The cut-out instruction refers to an instruction to cut out the partial image data from the captured image data. The cut-out instruction includes a designation address that is an address in the memory **96** storing the captured image data and can be used for designating a target to be cut out in the captured image

data.

[0136] In a case where the entirety image in a live view format based on the captured image data is displayed on the display apparatus, an instruction for any location in the entirety image is provided through the touch panel **42** and/or the operation portion **54** by the user, and coordinates of the location of the instruction are converted into an address of the memory **96**. The address obtained by conversion is the designation address. In the example illustrated in FIGS. **11A** and **11B**, a state where the partial image data **200** is specified from the captured image data stored in the memory **96** is illustrated. The partial image data **200** is specified by the designation address included in the cut-out instruction.

[0137] A face detection instruction is illustrated as one example of the cut-out instruction. The face detection instruction refers to an instruction to perform a face detection function. The face detection function is a function of detecting a face of a person who is the subject from the captured image data, and is implemented by the image processing circuit **94C**. For example, as illustrated in FIG. **12**, an address of a rectangular region including a face **202F** of a person **202** who is the subject in the captured image data is specified as an address of the target to be cut out, and the partial image data **200** is specified in accordance with the specified address.

[0138] While face detection is illustrated here, a pupil detection function of detecting a pupil of the person who is the subject may be performed. By performing the face detection function and/or the pupil detection function, a region of a size designated as the target to be cut out from a center of the face of the person who is the subject is decided based on a face detection result and/or a pupil detection result. Thus, even in a case where the person who is the subject moves, the CPU **52** can perform AF by following a motion of the person. In addition, by performing the face detection on the memory **96** and calculating center coordinates of the face of the person, the display apparatus can perform displaying in display control processing described later with a smaller time lag in adjustment of an angle of view than in a case of not performing the face detection and/or the pupil detection. Furthermore, an enlargement ratio of the partial image data **200** may be changed based on the face detection result and/or the pupil detection result.

[0139] In step **S104**, in a case where the cut-out instruction is received by the touch panel **42** and/or the operation portion **54**, a positive determination is made, and the image data generation processing transitions to step **S110**. In step **S104**, in a case where the cut-out instruction is not received by the touch panel **42** and/or the operation portion **54**, a negative determination is made, and the image data generation processing transitions to step **S106**.

[0140] In step **S106**, the image processing circuit **94C** acquires the captured image data from the memory **96**, and then, the image data generation processing transitions to step **S108**.

[0141] In step **S108**, the image processing circuit **94C** generates the entirety image data based on the captured image data acquired in step **S106** and outputs the generated entirety image data to the output circuit **94D**, and then, the image data generation processing transitions to step **S130**. The entirety image data generated by executing processing of step **S108** is one type of image data included in the output image data.

[0142] The cut-out instruction received by the touch panel **42** and/or the operation portion **54** in step **S104** is broadly classified into a low image quality cut-out instruction and a high image quality cut-out instruction. The low image quality cut-out instruction refers to an instruction to cut out a low image quality cut-out image, and the high image quality cut-out instruction refers to an instruction to cut out a high image quality cut-out image. The high image quality cut-out image has higher image quality than the low image quality cut-out image. For example, the low image quality cut-out image refers to image data in which the horizontal lines are thinned out in the vertical direction by skipping two lines at a time as illustrated in FIG. **10**. Meanwhile, for example, the high image quality cut-out image refers to combined data obtained by combining the captured image data of three frames, that is, non-thinned image data, as illustrated in FIG. **10**.

[0143] In step **S110**, the image processing circuit **94C** determines whether or not the cut-out

instruction received by the touch panel **42** and/or the operation portion **54** in step **S104** is the high image quality cut-out instruction. In step **S110**, in a case where the cut-out instruction received by the touch panel **42** and/or the operation portion **54** in step **S104** is not the high image quality cut-out instruction, that is, in a case where the cut-out instruction is the low image quality cut-out instruction, a negative determination is made, and a transition is made to step **S112**. In step **S110**, in a case where the cut-out instruction received by the touch panel **42** and/or the operation portion **54** in step **S104** is the high image quality cut-out instruction, a positive determination is made, and a transition is made to step **S118**.

[0144] In step **S112**, the image processing circuit **94C** acquires the designation address from the cut-out instruction received in step **S104**, and then, the image data generation processing transitions to step **S114**.

[0145] In step **S114**, the image processing circuit **94C** cuts out the partial image data from the captured image data of a single frame of the captured image data in the memory **96** in accordance with the designation address acquired in step **S112**, and then, the image data generation processing transitions to step **S116**. For example, the captured image data of the single frame as a cut-out target for the partial image data is the captured image data least recently stored in the memory **96**. However, the technology of the present disclosure is not limited thereto. For example, in a case where the captured image data of a plurality of frames is stored in the memory **96**, the captured image data of the single frame as the cut-out target for the partial image data may be any captured image data in the captured image data of the plurality of frames stored in the memory **96**.

[0146] While the captured image data of the single frame is used as the captured image data of the cut-out target, for example, combined data obtained by combining the captured image data of two frames in the captured image data of the first to third frames illustrated in FIG. **10** may be used as the cut-out target. That is, in a case where the combined data obtained by combining the captured image data of three frames is defined as high image quality cut-out image data, the captured image data of one frame may be used as the captured image data of the cut-out target, or the combined data obtained by combining the captured image data of two frames may be used as the cut-out target.

[0147] In step **S116**, the image processing circuit **94C** generates and outputs low image quality cut-out image data to the output circuit **94D**, and then, the image data generation processing transitions to step **S130**. The partial image data cut out in step **S114** is employed as the low image quality cut-out image data. However, the technology of the present disclosure is not limited thereto. For example, the low image quality cut-out image data may be image data obtained by performing various types of image processing on the partial image data cut out in step **S114**. The low image quality cut-out image data generated by executing processing of step **S116** is one type of image data included in the output image data.

[0148] In step **S118**, the image processing circuit **94C** determines whether or not the captured image data of a plurality of frames is stored in the memory **96**. In step **S118**, three frames are employed as one example of the plurality of frames. In step **S118**, in a case where the captured image data of the plurality of frames is not stored in the memory **96**, a negative determination is made, and a transition is made to step **S120**. In step **S118**, in a case where the captured image data of the plurality of frames is stored in the memory **96**, a positive determination is made, and a transition is made to step **S124**.

[0149] In step **S120**, the image processing circuit **94C** acquires the captured image data from the memory **96**, and then, the image data generation processing transitions to step **S122**.

[0150] In step **S122**, the image processing circuit **94C** generates the entirety image data based on the captured image data acquired in step **S120** and outputs the generated entirety image data to the output circuit **94D**, and then, the image data generation processing transitions to step **S118**. The entirety image data generated by executing processing of step **S122** is one type of image data included in the output image data.

[0151] In step S124, the image processing circuit 94C acquires the designation address from the cut-out instruction received in step S104, and then, the image data generation processing transitions to step S126.

[0152] In step S126, the image processing circuit 94C cuts out the partial image data from the captured image data of each of the plurality of frames of the captured image data in the memory 96 in accordance with the designation address acquired in step S124, and then, the image data generation processing transitions to step S128.

[0153] For example, the captured image data of the plurality of frames as the cut-out target for the partial image data is the captured image data of all frames currently stored in the memory 96, that is, the captured image data of three frames. However, the technology of the present disclosure is not limited thereto. In a case where the captured image data of one frame is defined as the low image quality cut-out image data, the combined data obtained by combining the captured image data of two frames may be used as the cut-out target.

[0154] In step S128, the image processing circuit 94C generates and outputs the high image quality cut-out image data to the output circuit 94D, and then, the image data generation processing transitions to step S130. For example, the combined data obtained by combining the partial image data of three frames cut out in step S126 as illustrated in FIG. 10 is employed as the high image quality cut-out image data. However, the technology of the present disclosure is not limited thereto. For example, the high image quality cut-out image data may be image data obtained by performing various types of image processing on the combined data obtained by combining the partial image data of three frames cut out in step S126. The high image quality cut-out image data generated by executing processing of step S128 is one type of image data included in the output image data.

[0155] In step S130, the image processing circuit 94C determines whether or not an image data generation processing finish condition that is a condition for finishing the image data generation processing is satisfied. For example, a condition that an instruction to finish the image data generation processing is received by the touch panel 42 and/or the operation portion 54 is illustrated as the image data generation processing finish condition. In addition, for example, a condition that a time period in which a positive determination is not made in step S104 from a start of the image data generation processing exceeds a predetermined time period is illustrated as the image data generation processing finish condition. For example, the “predetermined time period” here is five minutes. The predetermined time period may be a fixed value or a variable value that can be changed in accordance with an instruction provided from the user.

[0156] In step S130, in a case where the image data generation processing finish condition is not satisfied, a negative determination is made, and the image data generation processing transitions to step S100. In step S130, in a case where the image data generation processing finish condition is satisfied, a positive determination is made, and the processing circuit 94 finishes the image data generation processing.

[0157] Next, image data output processing executed by the output circuit 94D of the processing circuit 94 will be described with reference to FIG. 8. The image data output processing illustrated in FIG. 8 is performed at the second frame rate by the output circuit 94D.

[0158] In the image data output processing illustrated in FIG. 8, first, in step S150, the output circuit 94D determines whether or not the output image data is input from the image processing circuit 94C. Image data that includes at least one of the entirety image data, the high image quality cut-out image data, or the low image quality cut-out image data output by the image data generation processing illustrated in FIG. 7 is illustrated as one example of the output image data input into the output circuit 94D from the image processing circuit 94C.

[0159] In step S150, in a case where the output image data is not input from the image processing circuit 94C, a negative determination is made, and a transition is made to step S154.

[0160] In step S150, in a case where the output image data is input from the image processing circuit 94C, a positive determination is made, and a transition is made to step S152.

[0161] In step **S152**, the output circuit **94D** outputs the output image data to the I/F **56** of the rear stage circuit **90** and then, transitions to step **S154**. For example, the I/F **56** outputs the output image data input from the output circuit **94D** to the CPU **52** and the image processing portion **62** through the bus **68**.

[0162] In step **S154**, the output circuit **94D** determines whether or not an image data output processing finish condition that is a condition for finishing the image data output processing is satisfied. For example, the image data output processing finish condition is the same condition as the image data generation processing finish condition.

[0163] In step **S154**, in a case where the image data output processing finish condition is not satisfied, a negative determination is made, and the image data output processing transitions to step **S150**. In step **S154**, in a case where the image data output processing finish condition is satisfied, a positive determination is made, and the output circuit **94D** finishes the image data output processing.

[0164] Next, the display control processing executed by the display control portion of the rear stage circuit **90** will be described with reference to FIG. **9**. For convenience of description, it is assumed that the output image data is output to the rear stage circuit **90** from the output circuit **94D** by executing the image data output processing illustrated in FIG. **8**, and that the output image data is input into the CPU **52** and the image processing portion **62**. In addition, hereinafter, for convenience of description, the high image quality cut-out image data and the low image quality cut-out image data will be referred to as “cut-out image data” unless otherwise necessary to distinguish therebetween for description. In addition, the high image quality cut-out image indicated by the high image quality cut-out image data and the low image quality cut-out image indicated by the low image quality cut-out image data will be referred to as a “cut-out image” unless otherwise necessary to distinguish therebetween for description.

[0165] In the display control processing illustrated in FIG. **9**, in step **S160**, the display control portion determines whether or not the output image data is input from the image processing portion **62**. In step **S160**, in a case where the output image data is not input from the image processing portion **62**, a negative determination is made, and the display control processing transitions to step **S164**. In step **S160**, in a case where the output image data is input from the image processing portion **62**, a positive determination is made, and the display control processing transitions to step **S162**.

[0166] In step **S162**, the display control portion outputs the output image data to the display apparatus as graphics data, and then, the display control processing transitions to step **S164**. In a case where the output image data is output to the display apparatus by executing processing of step **S162**, the display apparatus displays an image indicated by the output image data. For example, in a case where the entirety image data is included in the output image data, the display apparatus displays the entirety image indicated by the entirety image data. The “entirety image” here refers to an image showing the entirety of the subject in the range falling within the angle of view imageable by all photodiodes in the partial region **92A** of the photoelectric conversion element **92**.

[0167] For example, in a case where the cut-out image data is included in the output image data, the display apparatus displays the cut-out image indicated by the cut-out image data as illustrated in FIGS. **11A** and **11B** and FIG. **12**.

[0168] For example, in a case where an enlarged display instruction is received by the touch panel **42** and/or the operation portion **54**, the display apparatus displays the cut-out image in an enlarged manner as illustrated in FIG. **14**.

[0169] The cut-out image is any of the high image quality cut-out image and the low image quality cut-out image. For example, the high image quality cut-out image is an image based on the combined data obtained by combining the captured image data of three frames as illustrated in FIG. **10**. Meanwhile, the low image quality cut-out image is a thinned image based on the captured image data of one frame. The entirety image is also a thinned image based on the captured image

data of one frame. Thus, image quality of the image displayed on the display apparatus is such that the high image quality cut-out image has higher image quality than the low image quality cut-out image and the entirety image.

[0170] It is not necessary to display the same image on both of the first display **40** and the second display **80**. For example, the entirety image may be displayed on one of the first display **40** and the second display **80**, and the cut-out image may be displayed on the other together with the entirety image. Alternatively, the cut-out image may be displayed without displaying the entirety image. In a case of displaying the cut-out image on the display apparatus together with the entirety image, first to third display methods are considered. The first display method refers to a display method of arranging and displaying the entirety image and the cut-out image. The second display method refers to a display method of displaying by superimposing one of the entirety image and the cut-out image on the other. The third display method refers to a display method of displaying by embedding one of the entirety image and the cut-out image in a display region of the other.

[0171] In step **S164**, the display control portion determines whether or not a display control processing finish condition that is a condition for finishing the display control processing is satisfied. For example, the display control processing finish condition is the same condition as the image data generation processing finish condition.

[0172] In step **S164**, in a case where the display control processing finish condition is not satisfied, a negative determination is made, and the display control processing transitions to step **S160**. In step **S164**, in a case where the display control processing finish condition is satisfied, a positive determination is made, and the display control portion finishes the display control processing.

[0173] For example, by executing the image data generation processing illustrated in FIG. **7**, the image data output processing illustrated in FIG. **8**, and the display control processing illustrated in FIG. **9**, the live view image is displayed on the display apparatus under control of the display control portion. The “live view image” here refers to an image in a live view format, that is, a live preview image, based on the output image data including at least one of the cut-out image data or the entirety image data. In the imaging apparatus **10** according to the first embodiment, the live view image is displayed at the second frame rate.

[0174] The imaging apparatus **10** according to the first embodiment is different from an imaging apparatus according to a technology in the related art in that a laminated CMOS image sensor is employed as the imaging element **20**. That is, in an imaging element according to the technology in the related art, the laminated CMOS image sensor is not employed. Thus, in the imaging apparatus according to the technology in the related art, for example, as illustrated in FIG. **11A**, the captured image data obtained by imaging the subject by the imaging element is output to the rear stage circuit **90**, and the partial image data **200** is cut out from the captured image data by the rear stage circuit **90**. An image based on the cut-out partial image data **200** is displayed on the display apparatus.

[0175] Meanwhile, in the imaging apparatus **10** according to the first embodiment, the laminated CMOS image sensor is employed as the imaging element **20**. Thus, for example, as illustrated in FIG. **11B**, the captured image data is temporarily stored in the memory **96** incorporated in the imaging element **20**, and the partial image data **200** is cut out by random access to the memory **96**. Image data based on the cut-out partial image data **200** is output to the rear stage circuit **90**. That is, a data amount output to the rear stage circuit **90** from the imaging element **20** according to the first embodiment is smaller than a data amount output to the rear stage circuit **90** from the imaging element of the imaging apparatus according to the technology in the related art. Thus, the imaging apparatus **10** according to the first embodiment can reduce power consumption accompanied by output of the image data compared to the imaging apparatus according to the technology in the related art.

[0176] Since the partial image data **200** is cut out in the rear stage circuit **90**, for example, it is necessary to move the captured image data of the first frame to the rear stage circuit **90** after first

exposure for obtaining the captured image data of the first frame is finished as illustrated in FIG. 13A. The captured image data is moved to the rear stage circuit 90 from the imaging element at the second frame rate.

[0177] Meanwhile, for example, as illustrated in FIG. 13B, in the imaging apparatus 10, image processing such as read-out of the captured image data, storage of the captured image data in the memory 96, and cut-out of the partial image data 200 is performed at the first frame rate in the imaging element 20. Even in the imaging apparatus 10, the captured image data is moved to the rear stage circuit 90 from the imaging element 20 at the second frame rate.

[0178] However, in the imaging apparatus 10, at least imaging processing from read-out of the captured image data to cut-out or the like is performed at the first frame rate. Thus, for example, as illustrated in FIG. 13B, the imaging apparatus 10 can perform more processing in the imaging element 20 than the imaging apparatus according to the technology in the related art even during movement of the output image data to the rear stage circuit 90. In the example illustrated in FIG. 13B, second exposure and image processing from read-out of the captured image data of the second frame obtained by the second exposure to cut-out or the like are performed during movement of the output image data of the first frame to the rear stage circuit 90 from the imaging element 20.

[0179] In addition, in the imaging apparatus 10, for example, as illustrated in FIG. 10, the captured image data of the plurality of frames is stored in the memory 96 in the imaging element 20. Thus, the processing circuit 94 can output combined data obtained by combining the captured image data of the plurality of frames to the rear stage circuit 90.

[0180] In the example illustrated in FIG. 10, the captured image data of each of three consecutive frames is image data obtained by thinning out the horizontal lines in the vertical direction by shifting one line at a time. However, the technology of the present disclosure is not limited thereto. For example, as illustrated in FIG. 15, image data obtained by not thinning out the captured image data of each of three consecutive frames may be used. In this case, for example, the amount of electric charges per line of the horizontal lines used for exposure in the photoelectric conversion element 92 is $\frac{1}{3}$ of the amount of electric charges per line of the horizontal lines used for exposure for obtaining the captured image data of each frame illustrated in FIG. 10. Accordingly, even in a case of the example illustrated in FIG. 15, the output image data that can implement the same image quality as in a case of the example illustrated in FIG. 10 is obtained by combining the captured image data of the first frame to the third frame.

[0181] Here, “ $\frac{1}{3}$ of the amount of electric charges per line of the horizontal lines used for exposure for obtaining the captured image data of each frame” corresponds to a ratio of the amount of electric charges obtained by exposure using a second exposure method described later, to the amount of electric charges obtained by exposure using a first exposure method described later.

[0182] In the imaging apparatus 10 according to the first embodiment, for example, as illustrated in FIG. 18A and FIG. 18B, the first exposure method and the second exposure method are selectively used in accordance with an instruction received by the touch panel 42 and/or the operation portion 54. Hereinafter, for convenience of description, a time period required for exposure performed using the first exposure method will be referred to as a first exposure time period, and a time period required for exposure performed using the second exposure method will be referred to as a second exposure time period.

[0183] For example, in the first exposure method illustrated in FIG. 18A, the subject is imaged in the first exposure time period by all photodiodes in the partial region 92A of the photoelectric conversion element 92 illustrated in FIG. 11B. Accordingly, for example, image data having brightness corresponding to brightness of the output image data obtained by combining the first frame to the third frame illustrated in FIG. 15 is obtained.

[0184] Meanwhile, for example, in the second exposure method illustrated in FIG. 18B, while the subject is imaged in the second exposure time period by all photodiodes in the partial region 92A of the photoelectric conversion element 92, the second exposure time period is $\frac{1}{3}$ of the first exposure

time period. Thus, for example, as illustrated in FIG. 15, the amount of electric charges of the captured image data of one frame is $\frac{1}{3}$ of the amount of electric charges of the captured image data of one frame based on the first exposure method.

[0185] In the first exposure method, the number of times that a series of processing of image processing such as read-out of the captured image data from the photoelectric conversion element **92**, storage of the captured image data in the memory **96**, and cut-out of the partial image data is performed is three. That is, the number of times that the first processing is performed is larger in the second exposure method than in the first exposure method by two. The number of times that the first processing is performed in the second exposure method is a number of times that can be implemented at the first frame rate. Thus, output image data having brightness corresponding to brightness of the output image data of one frame obtained in the first exposure time period can be generated without changing the second exposure time period to the first exposure time period by extending the exposure time period by decreasing the first frame rate. That is, even in the second exposure method, the output image data having brightness corresponding to the brightness of the output image data of one frame obtained using the first exposure method can be generated by obtaining the cut-out image from the captured image data of each of three consecutive frames and combining the cut-out images.

[0186] In addition, for example, captured image data in which the horizontal lines are thinned out in the vertical direction by skipping two lines at a time in the captured image data of each of the first frame to the third frame illustrated in FIG. 16 may be employed. In the example illustrated in FIG. 16, the captured image data in which the horizontal lines are thinned out in the vertical direction by skipping two lines at a time in the captured image data of each of the first frame to the third frame is illustrated. In the example illustrated in FIG. 16, output image data in which the horizontal lines are thinned out in the vertical direction by skipping two lines at a time is obtained by combining the captured image data of the first frame to the third frame.

[0187] In addition, in the imaging apparatus **10** according to the first embodiment, since the laminated CMOS sensor is employed as the imaging element **20**, the image quality can be changed even in a case where the total data amount is the same, by changing a method of reading out the output image data from the captured image data of the memory **96**.

[0188] For example, as illustrated in FIG. 17, a data amount of the output image data acquired from the memory **96** by the image processing circuit **94C** can be the same between a case of thinning out and a case of not thinning out. For example, as illustrated in FIG. 17, non-thinned captured image data does not need to be thinned out as much as a read-out target is narrower than thinned captured image data. Thus, the non-thinned captured image data can implement higher image quality than the thinned captured image. In the imaging apparatus **10**, for example, as illustrated in FIG. 17, regardless of whether or not thinning is performed, a data amount output from the processing circuit **94** is smaller than in a case of outputting the captured image data of all pixels to the rear stage circuit **90**. Thus, in the imaging apparatus **10**, power consumption required for output to the rear stage circuit **90** from the output circuit **94D** can be reduced compared to a case of performing thinning processing or cut-out processing in the rear stage circuit **90** as in the imaging apparatus according to the technology in the related art.

[0189] As described above, in the imaging apparatus **10**, the memory **96** and the processing circuit **94** are incorporated in the imaging element **20**. In addition, the processing circuit **94** executes the first processing at the first frame rate and executes the second processing at the second frame rate. The first processing includes the cut-out processing. In addition, for example, the partial image data is cut out from the captured image data by performing the cut-out processing as in steps **S114** and **S116** illustrated in FIG. 7 by the processing circuit **94**. The output image data includes image data based on the cut-out partial image data.

[0190] Accordingly, the imaging apparatus **10** can reduce power consumption compared to a case of cutting out the partial image data from image data output to the outside of the imaging element

without passing through the storage portion, and outputting the partial image data.

[0191] In addition, in the imaging apparatus **10**, the image processing circuit **94C** cuts out the partial image data from the captured image data stored in the memory **96** by random access to the memory **96**.

[0192] Accordingly, the imaging apparatus **10** can quickly cut out the partial image data from the designated address compared to a case where random access to the memory **96** is not available.

[0193] In addition, in the imaging apparatus **10**, the memory **96** can store the captured image data in a plurality of frames, and the cut-out processing includes processing of cutting out the partial image data of the plurality of frames from the captured image data stored in the memory **96**. In addition, for example, as in processing of steps **S126** and **S128** illustrated in FIG. 7, the second processing includes processing of combining the partial image data of the plurality of frames cut out by performing the cut-out processing by the image processing circuit **94C**. Combined data obtained by combining the partial image data of the plurality of frames is output to the rear stage circuit **90** by the output circuit **94D** as the output image data.

[0194] Accordingly, the imaging apparatus **10** can reduce power consumption compared to a case of outputting the captured image data to the rear stage circuit **90**, cutting out the partial image data of the plurality of frames from the captured image data in the rear stage circuit **90**, and combining the partial image data of the plurality of frames.

[0195] In addition, in the imaging apparatus **10**, for example, the partial image data is cut out from the captured image data of the single frame, and the cut-out partial image data is employed as the low image quality cut-out image data illustrated in step **S116** in FIG. 7.

[0196] Accordingly, in the imaging apparatus **10**, power consumption can be reduced compared to a case of cutting out the partial image data from the captured image data of each of the plurality of frames and combining the cut-out partial image data of the plurality of frames.

[0197] In addition, in the imaging apparatus **10**, the partial image data of the plurality of frames has a relationship in which pixels different from each other are thinned out in units of lines.

[0198] Accordingly, the imaging apparatus **10** can obtain a subject image of high reproducibility compared to a case of thinning out pixels at the same position in units of lines.

[0199] A degree of thinning may be decided in accordance with a degree of enlargement of the cut-out image. For example, as the degree of enlargement is increased, the degree of thinning may be decreased. In a case of performing a special type of processing on the output image data, the degree of thinning may be decided in accordance with the type of processing.

[0200] In addition, in the imaging apparatus **10**, the output image data output from the output circuit **94D** is the combined data obtained by combining the partial image data of the plurality of frames thinned out at different locations.

[0201] Accordingly, the imaging apparatus **10** can display an image of high image quality compared to a case of outputting the partial image data of the single frame.

[0202] In addition, in the imaging apparatus **10**, for example, the display control portion performs a control for displaying, on the display apparatus, an image based on the output image data output by the output circuit **94D** in an enlarged manner as illustrated in FIGS. **11A** and **11B**, FIG. **12**, and FIG. **14**.

[0203] Accordingly, the imaging apparatus **10** can cause the user to visually recognize the image based on the output image data output by the output circuit **94D**.

[0204] In addition, in the imaging apparatus **10**, the laminated CMOS image sensor is employed as the imaging element **20**. Accordingly, the imaging apparatus **10** can output image data subjected to image processing in the imaging element **20** to the rear stage circuit **90**.

[0205] While an example of a form in which the captured image data obtained by imaging the subject by the partial region **92A** of the photoelectric conversion element **92** is stored in the memory **96** is illustratively described in the first embodiment, the technology of the present disclosure is not limited thereto. For example, as illustrated in FIG. **19**, the entirety image data that

is the captured image data obtained by imaging the subject by all photodiodes in the photoelectric conversion element **92** may be stored in the memory **96**. Even in this case, the image processing circuit **94C** generates the cut-out image data by cutting out the partial image data **200** from the entirety image data by random access to the memory **96** in the same manner as the first embodiment. An image based on the cut-out image data is displayed on the display apparatus. [0206] For example, as illustrated in FIG. **20**, the entirety image data that is one example of the “wide range image data” according to the embodiment of the technology of the present disclosure, and the cut-out image data based on the partial image data **200** may be output to the rear stage circuit **90** from the output circuit **94D** of the imaging element **20**. In this case, resolution of the entirety image data is preferably lower than resolution of the partial image data. Accordingly, power consumption is reduced.

[0207] For example, as illustrated in FIG. **20**, the display apparatus may display the cut-out image indicated by the cut-out image data in an enlarged manner and display the entirety image indicated by the entirety image data using a display method based on the first display method under control of the display control portion.

[0208] The display apparatus may display the cut-out image and the entirety image using a display method based on the second or third display method under control of the display control portion. The display apparatus may display the cut-out image or the entirety image under control of the display control portion. For example, any of the cut-out image and the entirety image that is to be displayed on the display apparatus may be decided in accordance with an instruction received by the touch panel **42** and/or the operation portion **54**.

[0209] The processing circuit **94** may selectively output a partial image of a part of the partial image data of three frames and the combined data obtained by combining the partial image data of three frames to the rear stage circuit **90** in accordance with a provided condition as the partial image data. Accordingly, power consumption is reduced compared to a case of outputting the combined data to the rear stage circuit **90** at all times. For example, the “partial image of the part of the partial image data of three frames” refers to a number of partial images less than three frames. In addition, for example, the “provided condition” is illustrated by a condition that a specific instruction is received by the touch panel **42** and/or the operation portion **54**, or a condition that remaining power of the imaging apparatus **10** is below a threshold value. For example, the “condition that the specific instruction is received” here is illustrated by a condition that an instruction for a power saving mode is received, or a condition that an instruction for image processing that requires a special type of processing is received by the touch panel **42** and/or the operation portion **54**.

Second Embodiment

[0210] While a case of cutting out the partial image data indicating the image of the part of the subject is described in the first embodiment, a case where a part of the subject is present across a plurality of regions will be described in a second embodiment. In the second embodiment, the same constituents as the first embodiment will be designated by the same reference signs and will not be described.

[0211] For example, the imaging apparatus **10** according to the second embodiment is different from the imaging apparatus **10** according to the first embodiment in that a partial region **92B** is included instead of the partial region **92A** of the photoelectric conversion element **92** as illustrated in FIG. **24**. The partial region **92B** is a region that has a larger width than the partial region **92A** in the vertical direction of the photoelectric conversion element **92**.

[0212] Next, the image data generation processing executed by the processing circuit **94** according to the second embodiment will be described with reference to FIG. **21**.

[0213] In the image data generation processing illustrated in FIG. **21**, first, in step **S250**, the photoelectric conversion element drive circuit **94A** reads out the captured image data from the partial region **92B** of the photoelectric conversion element **92**, and then, the image data generation

processing transitions to step S252.

[0214] For example, the captured image data of one frame read out from the partial region **92B** of the photoelectric conversion element **92** by executing processing of step S250 is image data in which the horizontal lines are thinned out in the vertical direction by skipping two lines at a time as illustrated in FIG. **10**.

[0215] For example, the captured image data obtained from the partial region **92B** of the photoelectric conversion element **92** by executing processing of step S250 is captured image data obtained by imaging the subject by the partial region **92B** of the photoelectric conversion element **92** in the same manner as the example illustrated in FIGS. **11A** and **11B**.

[0216] In step S252, the AD conversion circuit **94B** digitizes and stores the captured image data read out by the partial region **92B** of the photoelectric conversion element drive circuit **94A** in the memory **96**, and then, the image data generation processing transitions to step S254.

[0217] In step S254, the image processing circuit **94C** determines whether or not the cut-out instruction is received by the touch panel **42** and/or the operation portion **54**. In step S254, the “cut-out instruction” is broadly classified into a single region cut-out instruction and a plural region cut-out instruction. The single region cut-out instruction refers to an instruction to cause the image processing circuit **94C** to cut out a single region from an image indicated by the captured image data. The plural region cut-out instruction refers to an instruction to cause the image processing circuit **94C** to cut out a plurality of regions from the image indicated by the captured image data.

[0218] The single region cut-out instruction is broadly classified into a single low image quality image cut-out instruction and a single high image quality image cut-out instruction. The single low image quality image cut-out instruction refers to an instruction to cut out a single low image quality image from the image indicated by the captured image data as an image of a cut-out region. The single high image quality image cut-out instruction refers to an instruction to cut out a single high image quality image from the image indicated by the captured image data as an image of a cut-out region. The single high image quality image has higher image quality than the single row image quality image. The single low image quality image refers to image data in which the horizontal lines are thinned out in the vertical direction by skipping two lines at a time in the same manner as the example illustrated in FIG. **10**. Meanwhile, the single high image quality image refers to the combined data obtained by combining the captured image data of three frames, that is, non-thinned image data, in the same manner as the example illustrated in FIG. **10**.

[0219] The plural region cut-out instruction is broadly classified into a plural low image quality cut-out instruction and a plural high image quality image cut-out instruction. The plural low image quality cut-out instruction refers to an instruction to cut out a low image quality image from each of the plurality of regions cut out from the image indicated by the captured image data. Hereinafter, for convenience of description, the low image quality image cut out from each of the plurality of regions will be referred to as the “low image quality cut-out image”.

[0220] The plural high image quality image cut-out instruction refers to an instruction to cut out a high image quality image from each of the plurality of regions cut out from the image indicated by the captured image data. Hereinafter, for convenience of description, the high image quality image cut out from each of the plurality of regions will be referred to as the “high image quality cut-out image”.

[0221] The high image quality cut-out image has higher image quality than the low image quality cut-out image. The low image quality cut-out image refers to a plurality of pieces of image data in each of which the horizontal lines are thinned out in the vertical direction by skipping two lines at a time in the same manner as the example illustrated in FIG. **10**. Meanwhile, a plurality of high image quality cut-out images refer to a plurality of pieces of combined data each of which is obtained by combining the captured image data of three frames, that is, a plurality of pieces of non-thinned image data, in the same manner as the example illustrated in FIG. **10**.

[0222] In step S254, in a case where the cut-out instruction is received by the touch panel **42** and/or

the operation portion **54**, a positive determination is made, and the image data generation processing transitions to step **S260**. In step **S254**, in a case where the cut-out instruction is not received by the touch panel **42** and/or the operation portion **54**, a negative determination is made, and the image data generation processing transitions to step **S256**.

[0223] In step **S256**, the image processing circuit **94C** acquires the captured image data from the memory **96**, and then, the image data generation processing transitions to step **S258**.

[0224] In step **S258**, the image processing circuit **94C** generates main subject image data based on the captured image data acquired in step **S256** and outputs the generated main subject image data to the output circuit **94D**, and then, the image data generation processing transitions to step **S266**. For example, the main subject image data generated by executing processing of step **S258** refers to the subject included in a rectangular region including faces of a plurality of persons. The faces of the persons are specified by performing the face detection function provided in the imaging apparatus **10**. The main subject image data is one type of image data that is a part of the captured image data and is included in the output image data.

[0225] In step **S260**, the image processing circuit **94C** determines whether or not the cut-out instruction received in step **S254** is the plural region cut-out instruction. In step **S260**, in a case where the cut-out instruction received in step **S254** is not the plural region cut-out instruction, that is, in a case where the cut-out instruction received in step **S254** is the single region cut-out instruction, a negative determination is made, and the image data generation processing transitions to step **S262**. In step **S260**, in a case where the cut-out instruction received in step **S254** is the plural region cut-out instruction, a positive determination is made, and the image data generation processing transitions to step **S264**.

[0226] In step **S262**, for example, the image processing circuit **94C** executes single region cut-out processing illustrated in FIG. **22**, and then, the image data generation processing transitions to step **S266**.

[0227] In step **S264**, for example, the image processing circuit **94C** executes plural region cut-out processing illustrated in FIG. **23**, and then, the image data generation processing transitions to step **S266**.

[0228] In the single region cut-out processing illustrated in FIG. **22**, in step **S262A**, a determination as to whether or not the single region cut-out instruction received in step **S254** is the single high image quality image cut-out instruction is performed. In step **S262A**, in a case where the single region cut-out instruction received in step **S254** is the single low image quality image cut-out instruction, a negative determination is made, and the single region cut-out processing transitions to step **S262B**. In step **S262A**, in a case where the single region cut-out instruction received in step **S254** is the single high image quality image cut-out instruction, a positive determination is made, and the single region cut-out processing transitions to step **S262E**.

[0229] In step **S262B**, the image processing circuit **94C** acquires the designation address from the cut-out instruction received in step **S254**, and then, the single region cut-out processing transitions to step **S262C**.

[0230] In step **S262C**, the image processing circuit **94C** cuts out region image data from the captured image data of one frame of the captured image data in the memory **96** in accordance with the designation address acquired in step **S262B**, and then, the single region cut-out processing transitions to step **S262D**. The region image data refers to image data of the captured image data that indicates a region specified in accordance with the designation address in the image indicated by the captured image data. For example, the captured image data of the single frame as a cut-out target for the region image data is the captured image data least recently stored in the memory **96**. However, the technology of the present disclosure is not limited thereto. For example, the captured image data of the single frame as the cut-out target for the region image data may be any captured image data in a case where the captured image data of the plurality of frames is stored in the memory **96**.

[0231] In step S262D, the image processing circuit 94C generates and outputs single low image quality cut-out image data to the output circuit 94D, and then, the image processing circuit 94C finishes the single region cut-out processing. The region image data cut out in step S262C is employed as the single low image quality cut-out image data. However, the technology of the present disclosure is not limited thereto. For example, the single low image quality cut-out image data may be image data obtained by performing various types of image processing on the region image data cut out in step S262C. The single low image quality cut-out image data generated by executing processing of step S262D is one type of image data included in the output image data and is one example of “image data based on partial image data” according to the embodiment of the technology of the present disclosure.

[0232] In step S262E, the image processing circuit 94C determines whether or not the captured image data of a plurality of frames is stored in the memory 96. In step S262E, three frames are employed as one example of the plurality of frames. In step S262E, in a case where the captured image data of the plurality of frames is not stored in the memory 96, a negative determination is made, and a transition is made to step S262F. In step S262E, in a case where the captured image data of the plurality of frames is stored in the memory 96, a positive determination is made, and a transition is made to step S262H.

[0233] In steps S262F and S262G, the image processing circuit 94C executes processing corresponding to processing of steps S256 and S258 illustrated in FIG. 21, and the single region cut-out processing transitions to step S262E.

[0234] In step S262H, the image processing circuit 94C acquires the designation address from the cut-out instruction received in step S254, and then, the single region cut-out processing transitions to step S262I.

[0235] In step S262I, the image processing circuit 94C cuts out the region image data from the captured image data of each of the plurality of frames of the captured image data in the memory 96 in accordance with the designation address acquired in step S262H, and then, the single region cut-out processing transitions to step S262J.

[0236] For example, the captured image data of the plurality of frames as the cut-out target for the region image data is the captured image data of all frames currently stored in the memory 96, that is, the captured image data of three frames. However, the technology of the present disclosure is not limited thereto. In a case where the captured image data of one frame is defined as the single low image quality cut-out image data, the combined data obtained by combining the captured image data of two frames may be used as the cut-out target.

[0237] The region image data cut out in each of steps S262C and S262I is one example of “partial image data” according to the embodiment of the technology of the present disclosure.

[0238] In step S262J, the image processing circuit 94C generates and outputs single high image quality cut-out image data to the output circuit 94D, and then, the image processing circuit 94C finishes the single region cut-out processing. For example, the combined data obtained by combining the region image data of three frames cut out in step S262I is employed as the single high image quality cut-out image data in the same manner as the example illustrated in FIG. 10. However, the technology of the present disclosure is not limited thereto. For example, the single high image quality cut-out image data may be image data obtained by performing various types of image processing on the combined data obtained by combining the region image data of three frames cut out in step S262I. The single high image quality cut-out image data generated by executing processing of step S262J is one type of image data included in the output image data and is one example of the “image data based on the partial image data” according to the embodiment of the technology of the present disclosure.

[0239] In the plural region cut-out processing illustrated in FIG. 23, in step S264A, the image processing circuit 94C determines whether or not the plural region cut-out instruction received in step S254 is the plural high image quality image cut-out instruction. In step S264A, in a case where

the plural region cut-out instruction received in step S254 is the plural low image quality image cut-out instruction, a negative determination is made, and the plural region cut-out processing transitions to step S264B. In step S264A, in a case where the plural region cut-out instruction received in step S254 is the plural high image quality image cut-out instruction, a positive determination is made, and the plural region cut-out processing transitions to step S264F.

[0240] In step S264B, the image processing circuit 94C acquires a non-processed designation address from the cut-out instruction received in step S254, and then, the plural region cut-out processing transitions to step S264C. In step S264B, the “non-processed designation address” refers to a designation address that is not used yet in processing of step S264C described later.

[0241] In step S264C, the image processing circuit 94C cuts out the region image data from the captured image data of one frame of the captured image data in the memory 96 in accordance with the designation address acquired in step S264B, and then, the plural region cut-out processing transitions to step S264D. For example, the captured image data of the single frame as a cut-out target for the region image data is the captured image data least recently stored in the memory 96. However, the technology of the present disclosure is not limited thereto. For example, the captured image data of the single frame as the cut-out target for the region image data may be any captured image data in a case where the captured image data of the plurality of frames is stored in the memory 96.

[0242] In step S264D, the image processing circuit 94C determines whether or not all designation addresses are processed. In step S264D, in a case where the non-processed designation address is present, a negative determination is made, and the plural region cut-out processing transitions to step S264B. In step S264D, in a case where the non-processed designation address is not present, a positive determination is made, and the plural region cut-out processing transitions to step S264E.

[0243] A plurality of pieces of region image data cut out by executing processing of step S264B to step S264D are one example of a “plurality of pieces of region image data indicating a plurality of regions in captured image data” according to the embodiment of the technology of the present disclosure.

[0244] In step S264E, the image processing circuit 94C generates and outputs plural low image quality cut-out image data to the output circuit 94D, and then, the image processing circuit 94C finishes the plural region cut-out processing. The plurality of pieces of region image data cut out in step S264C are employed as the plural low image quality cut-out image data. However, the technology of the present disclosure is not limited thereto. For example, the plural low image quality cut-out image data may be image data obtained by performing various types of image processing on the plurality of pieces of region image data cut out in step S264C. The plural low image quality cut-out image data generated by executing processing of step S264E is one type of image data included in the output image data and is one example of the “image data based on the partial image data” according to the embodiment of the technology of the present disclosure.

[0245] In step S264F, the image processing circuit 94C determines whether or not the captured image data of a plurality of frames is stored in the memory 96. In step S264F, three frames are employed as one example of the plurality of frames. In step S264F, in a case where the captured image data of the plurality of frames is not stored in the memory 96, a negative determination is made, and a transition is made to step S264G. In step S264F, in a case where the captured image data of the plurality of frames is stored in the memory 96, a positive determination is made, and a transition is made to step 264I.

[0246] In steps S264G and S264H, the image processing circuit 94C executes processing corresponding to processing of steps S256 and S258 illustrated in FIG. 21, and the plural region cut-out processing transitions to step S264F.

[0247] In step S264I, the image processing circuit 94C acquires the non-processed designation address from the cut-out instruction received in step S254, and then, the plural region cut-out processing transitions to step S264J. In step S264I, the “non-processed designation address” refers

to a designation address that is not used yet in processing of step S264J described later.

[0248] In step S264J, the image processing circuit 94C cuts out the region image data from the captured image data of each of the plurality of frames of the captured image data in the memory 96 in accordance with the designation address acquired in step S264I, and then, the plural region cut-out processing transitions to step S264K.

[0249] For example, the captured image data of the plurality of frames as the cut-out target for the region image data is the captured image data of all frames currently stored in the memory 96, that is, the captured image data of three frames. However, the technology of the present disclosure is not limited thereto. In a case where the captured image data of one frame is defined as the plural low image quality cut-out image data, the combined data obtained by combining the captured image data of two frames may be used as the cut-out target.

[0250] In step S264K, the image processing circuit 94C determines whether or not all designation addresses are processed. In step S264K, in a case where the non-processed designation address is present, a negative determination is made, and the plural region cut-out processing transitions to step S264I. In step S264K, in a case where the non-processed designation address is not present, a positive determination is made, and the plural region cut-out processing transitions to step S264L.

[0251] A plurality of pieces of region image data cut out by executing processing of step S264I to step S264K are one example of the “plurality of pieces of region image data indicating the plurality of regions in the captured image data” according to the embodiment of the technology of the present disclosure.

[0252] A plurality of pieces of region image data cut out by executing processing of step S264J are one example of the “plurality of pieces of region image data indicating the plurality of regions in the captured image data” according to the embodiment of the technology of the present disclosure.

[0253] In step S264L, the image processing circuit 94C generates and outputs plural high image quality cut-out image data to the output circuit 94D, and then, the image processing circuit 94C finishes the plural region cut-out processing. For example, the combined data obtained by combining the region image data of three frames cut out in step S264J for each of a plurality of locations as the cut-out target is employed as the plural high image quality cut-out image data in the same manner as the example illustrated in FIG. 10. However, the technology of the present disclosure is not limited thereto.

[0254] For example, the plural high image quality cut-out image data may be image data obtained by performing various types of image processing on the combined data obtained by combining the region image data of three frames cut out in step S264J for each of the plurality of regions as the cut-out target. The plural high image quality cut-out image data generated by executing processing of step S264L is one type of image data included in the output image data and is one example of the “image data based on the partial image data” according to the embodiment of the technology of the present disclosure.

[0255] In the image data generation processing illustrated in FIG. 21, in step S266, a determination as to whether or not the image data generation processing finish condition described in the first embodiment is satisfied is performed. In step S266, in a case where the image data generation processing finish condition is not satisfied, a negative determination is made, and the image data generation processing transitions to step S250. In step S266, in a case where the image data generation processing finish condition is satisfied, a positive determination is made, and the image processing circuit 94C finishes the image data generation processing.

[0256] Next, the image data output processing executed by the output circuit 94D of the processing circuit 94 according to the second embodiment will be described with reference to FIG. 8. The image data output processing illustrated in FIG. 8 is performed at the second frame rate by the output circuit 94D.

[0257] In the image data output processing illustrated in FIG. 8, first, in step S280, the output circuit 94D determines whether or not the output image data is input from the image processing

circuit **94C**. Image data that includes at least one of the main subject image data, the single low image quality cut-out image data, the single high image quality cut-out image data, the plural low image quality cut-out image data, or the plural high image quality cut-out image data output by the image data generation processing illustrated in FIG. **21** is illustrated as one example of the output image data input into the output circuit **94D** from the image processing circuit **94C**.

[0258] In step **S280**, in a case where the output image data is not input from the image processing circuit **94C**, a negative determination is made, and a transition is made to step **S284**.

[0259] In step **S280**, in a case where the output image data is input from the image processing circuit **94C**, a positive determination is made, and a transition is made to step **S282**.

[0260] In step **S282**, the output circuit **94D** outputs the output image data to the I/F **56** of the rear stage circuit **90** and then, transitions to step **S284**. For example, the I/F **56** outputs the output image data input from the output circuit **94D** to the CPU **52** and the image processing portion **62** through the bus **68**.

[0261] In step **S284**, the output circuit **94D** determines whether or not the image data output processing finish condition described in the first embodiment is satisfied. In step **S284**, in a case where the image data output processing finish condition is not satisfied, a negative determination is made, and the image data output processing transitions to step **S280**. In step **S284**, in a case where the image data output processing finish condition is satisfied, a positive determination is made, and the output circuit **94D** finishes the image data output processing.

[0262] Next, the display control processing executed by the display control portion of the rear stage circuit **90** will be described with reference to FIG. **9**. For convenience of description, it is assumed that the output image data is output to the rear stage circuit **90** from the output circuit **94D** by executing the image data output processing illustrated in FIG. **8**, and that the output image data is input into the CPU **52** and the image processing portion **62**.

[0263] In the display control processing illustrated in FIG. **9**, in step **S290**, the display control portion determines whether or not the output image data is input from the image processing portion **62**. In step **S290**, in a case where the output image data is not input from the image processing portion **62**, a negative determination is made, and the display control processing transitions to step **S294**. In step **S290**, in a case where the output image data is input from the image processing portion **62**, a positive determination is made, and the display control processing transitions to step **S292**.

[0264] In step **S292**, the display control portion outputs the output image data to the display apparatus as graphics data, and then, the display control processing transitions to step **S294**. In a case where the output image data is output to the display apparatus by executing processing of step **S292**, the display apparatus displays the image indicated by the output image data. For example, in a case where the main subject image data is included in the output image data, the display apparatus displays a main subject image indicated by the main subject image data.

[0265] While the main subject image is illustrated here, the entirety image may be displayed in the same manner as the first embodiment, or both of the main subject image and the entirety image may be arranged and displayed. For example, the “entirety image” according to the second embodiment refers to an image showing the entirety of the subject in a range falling within an angle of view imageable by all photodiodes in the partial region **92B** of the photoelectric conversion element **92** illustrated in FIG. **24**.

[0266] For example, in a case where the single high image quality cut-out image data is included in the output image data, the display apparatus arranges and displays the single high image quality cut-out image indicated by the single high image quality cut-out image data and the main subject image as illustrated in FIG. **24**.

[0267] For example, in a case where the enlarged display instruction is received by the touch panel **42** and/or the operation portion **54**, the display apparatus displays the single high image quality cut-out image in an enlarged manner as illustrated in FIG. **24**.

[0268] While a display example of the single high image quality cut-out image is illustrated in the example illustrated in FIG. 24, the display apparatus displays the single low image quality cut-out image instead of the single high image quality cut-out image in a case where the single low image quality cut-out image data is included in the output image data.

[0269] The image quality of the image displayed on the display apparatus is such that the single high image quality cut-out image has higher image quality than the single low image quality cut-out image and the main subject image.

[0270] It is not necessary to display the same image on both of the first display 40 and the second display 80. For example, the main subject image may be displayed on one of the first display 40 and the second display 80, and the single high image quality cut-out image or the single low image quality cut-out image may be displayed on the other together with the main subject image.

Alternatively, the single high image quality cut-out image or the single low image quality cut-out image may be displayed without displaying the main subject image.

[0271] Meanwhile, for example, in a case where the plural high image quality cut-out image data is included in the output image data, the display apparatus arranges and displays the plurality of high image quality cut-out images indicated by the plural high image quality cut-out image data and the main subject image as illustrated in FIG. 25. In the example illustrated in FIG. 25, a state where two high image quality cut-out images and the main subject image are arranged and displayed on the display apparatus is illustrated.

[0272] In a case where the enlarged display instruction is received by the touch panel 42 and/or the operation portion 54, the display apparatus displays at least one of the plurality of high image quality cut-out images in an enlarged manner.

[0273] The image quality of the image displayed on the display apparatus is such that the plurality of high image quality cut-out images have higher image quality than a plurality of low image quality cut-out images and the main subject image.

[0274] It is not necessary to display the same image on both of the first display 40 and the second display 80. For example, the main subject image may be displayed on one of the first display 40 and the second display 80, and the plurality of high image quality cut-out images or the plurality of low image quality cut-out images may be displayed on the other together with the main subject image. Alternatively, the plurality of high image quality cut-out images or the plurality of low image quality cut-out images may be displayed without displaying the main subject image.

[0275] In step S294, the display control portion determines whether or not the display control processing finish condition described in the first embodiment is satisfied. In step S294, in a case where the display control processing finish condition is not satisfied, a negative determination is made, and the display control processing transitions to step S290. In step S294, in a case where the display control processing finish condition is satisfied, a positive determination is made, and the display control portion finishes the display control processing.

[0276] As described above, in the imaging apparatus 10 according to the second embodiment, a part of the subject corresponding to the cut-out target is present across a plurality of regions, and a plurality of pieces of region image data are cut out from the captured image data. The plural low image quality image data and the plural high image quality cut-out image data are generated based on the plurality of pieces of cut-out region image data.

[0277] Accordingly, the imaging apparatus 10 according to the second embodiment can reduce power consumption even in a case where the cut-out target is present across a plurality of regions of the subject.

[0278] In the example illustrated in FIG. 25, a range specified by the designation address related to the main subject image data overlaps with a range specified by the designation address related to the plural high image quality cut-out image data.

[0279] However, even in a state where the ranges specified by the designation addresses overlap, the image processing circuit 94C can individually acquire the main subject image data and the

plural high image quality cut-out image data since the captured image data is held in the memory **96**.

[0280] The image processing circuit **94C** can individually acquire not only the plural high image quality cut-out image data but also the main subject image data and the plural low image quality cut-out image data. In addition, not only the plural high image quality cut-out image data and the plural low image quality cut-out image data but also the main subject image data and the single high image quality cut-out image data or the single low image quality cut-out image data may be individually acquired. In addition, the entirety image data can be applied instead of the main subject image data.

[0281] While an example of a form in which two pieces of partial image data are cut out from the captured image data is illustratively described in the second embodiment, the technology of the present disclosure is not limited thereto. For example, three or more pieces of partial image data may be cut out from the captured image data. In this case, the display control portion may arrange and display the entirety image and three or more images based on three or more pieces of partial image data. Among three or more images based on three or more pieces of partial image data, only a designated image may be displayed in an enlarged manner or displayed in a reduced manner.

Third Embodiment

[0282] While a method of using the partial image data out of the partial image data and the focusing control image data is illustrated in the first embodiment, a method of using both of the partial image data and the focusing control image data will be described in the third embodiment. In the third embodiment, the same constituents as constituents described in the first embodiment will be designated by the same reference signs and will not be described.

[0283] The imaging apparatus **10** according to the third embodiment is different from the imaging apparatus **10** according to the first embodiment in that the processing circuit **94** executes the image data generation processing illustrated in FIG. **26** instead of the image data generation processing illustrated in FIG. **8**.

[0284] In the image data generation processing illustrated in FIG. **26**, first, in step **S300**, the photoelectric conversion element drive circuit **94A** reads out the captured image data from the partial region **92A** of the photoelectric conversion element **92**, and then, the image data generation processing transitions to step **S302**.

[0285] For example, the captured image data of one frame read out from the partial region **92A** of the photoelectric conversion element **92** by executing processing of step **S300** is image data in which the horizontal lines are thinned out in the vertical direction by skipping two lines at a time as illustrated in FIG. **10**.

[0286] In step **S302**, the AD conversion circuit **94B** digitizes and stores the captured image data read out by the partial region **92A** of the photoelectric conversion element drive circuit **94A** in the memory **96**, and then, the image data generation processing transitions to step **S304**.

[0287] In step **S304**, the image processing circuit **94C** determines whether or not the enlarged display instruction is received by the touch panel **42** and/or the operation portion **54**. The enlarged display instruction includes the designation address described in the first embodiment.

[0288] In step **S304**, in a case where the enlarged display instruction is not received by the touch panel **42** and/or the operation portion **54**, a negative determination is made, and the image data generation processing transitions to step **S306**. In step **S304**, in a case where the enlarged display instruction is received by the touch panel **42** and/or the operation portion **54**, a positive determination is made, and the image data generation processing transitions to step **S310**.

[0289] In steps **S306** and **S308**, the image processing circuit **94C** executes processing corresponding to processing of steps **S106** and **S108** illustrated in FIG. **7** and then, transitions to step **S334**.

[0290] In step **S310**, the image processing circuit **94C** determines whether or not the enlarged display instruction received in step **S304** is a focusing control enlarged display instruction. The

focusing control enlarged display instruction refers to an instruction to cause the display apparatus to display an image of a location designated in accordance with the designation address in an enlarged manner and cause the processing circuit **94** to generate and output the focusing control image data.

[0291] In step **S310**, in a case where the enlarged display instruction received in step **S304** is not the focusing control enlarged display instruction, a negative determination is made, and the image data generation processing transitions to step **S312**. In step **S310**, in a case where the enlarged display instruction received in step **S304** is the focusing control enlarged display instruction, a positive determination is made, and the image data generation processing transitions to step **S318**.

[0292] In steps **S312** and **S314**, the image processing circuit **94C** executes processing corresponding to processing of steps **S112** and **S114** illustrated in FIG. 7, and then, the image data generation processing transitions to step **S316**.

[0293] In step **S316**, the image processing circuit **94C** generates and outputs enlarged display image data to the output circuit **94D**, and then, the image processing circuit **94C** transitions to step **S334**. The partial image data cut out in step **S314** is employed as the enlarged display image data. However, the technology of the present disclosure is not limited thereto. For example, the enlarged display image data may be image data obtained by performing various types of image processing on the partial image data cut out in step **S314**. The enlarged display image data generated by executing processing of step **S316** is one type of image data included in the output image data.

[0294] In steps **S318**, **S320**, **S322**, **S324**, and **S326**, the image processing circuit **94C** executes processing corresponding to processing of steps **S118**, **S120**, **S122**, **S124**, and **S126** illustrated in FIG. 7. After processing of step **S326** is executed, the image data generation processing transitions to step **S328**.

[0295] In step **S328**, the image processing circuit **94C** derives a focusing control address based on the designation address acquired in step **S324**, and then, the image data generation processing transitions to step **S330**. The focusing control address is an address that can be used for specifying a part of the captured image data required for the focusing control performed by the CPU **52** from the memory **96** storing the captured image data. In step **S328**, the focusing control address is derived from the designation address in accordance with a predetermined derivation table.

However, the technology of the present disclosure is not limited thereto. For example, the focusing control address may be derived using a calculation expression that can be used for deriving the same result as the derivation table.

[0296] In step **S330**, the image processing circuit **94C** cuts out the partial image data from the captured image data of each of the plurality of frames of the captured image data in the memory **96** in accordance with the focusing control address acquired in step **S328**, and then, the image data generation processing transitions to step **S332**. Hereinafter, the partial image data cut out in step **S326** will be referred to as “enlarged display partial image data”, and the partial image data cut out in step **S330** will be referred to as “focusing control partial image data”.

[0297] For example, the captured image data of the plurality of frames as the cut-out target for the focusing control partial image data is the captured image data of all frames currently stored in the memory **96**, that is, the captured image data of three frames. However, the technology of the present disclosure is not limited thereto. Combined data obtained by combining the captured image data of one frame or two frames may be used as the cut-out target.

[0298] In step **S332**, the image processing circuit **94C** generates image data corresponding to the high image quality cut-out image data in step **S128** illustrated in FIG. 7 as the enlarged display image data, and generates the focusing control partial image data based on the enlarged display image data. The image processing circuit **94C** outputs the generated enlarged display image data and the focusing control partial image data to the output circuit **94D**, and then, the image data generation processing transitions to step **S334**.

[0299] For example, combined data obtained by combining the focusing control partial image data

of three frames cut out in step S330 is employed as the focusing control image data in the same manner as the example illustrated in FIG. 10. However, the technology of the present disclosure is not limited thereto. For example, the focusing control image data may be image data obtained by performing various types of image processing on the combined data obtained by combining the focusing control partial image data of three frames cut out in step S330. The focusing control image data generated by executing processing of step S332 is one type of image data included in the output image data.

[0300] In the example illustrated in FIG. 27, a width relationship between images of enlarged display image data 200A and focusing control image data 352 is shown. For example, as illustrated in FIG. 27, the image indicated by the focusing control image data 352 is an image of a range wider than the image indicated by the enlarged display image data 200A. The “wider range” here means the “predetermined range” described in the first embodiment.

[0301] For example, in a case where the CPU 52 performs the so-called contrast AF or the phase difference AF in a state where the live view image is displayed on the display apparatus in the imaging apparatus 10, a region of the image indicated by the focusing control image data 352 may be enlarged or reduced in accordance with a blurriness amount. For example, under control of the CPU 52, the image processing circuit 94C adjusts the focusing control image data 352 such that the region of the image indicated by the focusing control image data 352 is narrowed as the blurriness amount is decreased. Accordingly, the imaging apparatus 10 can reduce power consumption compared to a case where the focusing control image data 352 is constant regardless of the blurriness amount.

[0302] In step S334, the image processing circuit 94C determines whether or not the image data generation processing finish condition described in the first embodiment is satisfied. In step S334, in a case where the image data generation processing finish condition described in the first embodiment is not satisfied, a negative determination is made, and the image data generation processing transitions to step S300. In step S334, in a case where the image data generation processing finish condition described in the first embodiment is satisfied, a positive determination is made, and the image processing circuit 94C finishes the image data generation processing.

[0303] Next, the image data output processing executed by the output circuit 94D of the processing circuit 94 according to the third embodiment will be described with reference to FIG. 8. The image data output processing illustrated in FIG. 8 is performed at the second frame rate by the output circuit 94D.

[0304] In the image data output processing illustrated in FIG. 8, first, in step S350, the output circuit 94D determines whether or not the output image data is input from the image processing circuit 94C. Image data that includes at least one of the entirety image data, the enlarged display image data, or the focusing control image data is illustrated as one example of the output image data input into the output circuit 94D from the image processing circuit 94C.

[0305] In step S350, in a case where the output image data is not input from the image processing circuit 94C, a negative determination is made, and a transition is made to step S354. In step S350, in a case where the output image data is input from the image processing circuit 94C, a positive determination is made, and a transition is made to step S351.

[0306] In step S351, the output circuit 94D outputs the output image data to the I/F 56 of the rear stage circuit 90 and then, transitions to step S354. For example, the I/F 56 outputs the output image data input from the output circuit 94D to the CPU 52 and the image processing portion 62 through the bus 68.

[0307] In step S354, the output circuit 94D determines whether or not the image data output processing finish condition described in the first embodiment is satisfied. In step S354, in a case where the image data output processing finish condition is not satisfied, a negative determination is made, and the image data output processing transitions to step S350. In step S354, in a case where the image data output processing finish condition is satisfied, a positive determination is made, and

the output circuit **94D** finishes the image data output processing.

[0308] Next, output image data processing executed by the CPU **52** will be described with reference to FIG. **28**.

[0309] In the imaging apparatus **10** according to the third embodiment, an output image data processing program is stored in the secondary storage portion **60**, and the CPU **52** reads out the output image data processing program from the secondary storage portion **60** and loads the output image data processing program into the primary storage portion **58**. The CPU **52** executes the output image data processing in accordance with the output image data processing program loaded in the primary storage portion **58**.

[0310] In the output image data processing illustrated in FIG. **28**, in step **S360**, the CPU **52** determines whether or not the output image data is input into the I/F **56** from the processing circuit **94**. In step **S360**, in a case where the output image data is not input into the I/F **56** from the processing circuit **94**, a negative determination is made, and the output image data processing transitions to step **S370**. In step **S360**, in a case where the output image data is input into the I/F **56** from the processing circuit **94**, a positive determination is made, and the output image data processing transitions to step **S362**.

[0311] In step **S362**, a determination as to whether or not only the enlarged display image data is included in the output image data is performed. In step **S362**, in a case where only the enlarged display image data is included in the output image data, a positive determination is made, and the output image data processing transitions to step **S364**. In step **S362**, in a case where the enlarged display image data and the focusing control image data are included in the output image data, a negative determination is made, and the output image data processing transitions to step **S366**.

[0312] In step **S364**, the CPU **52** outputs enlarged display image data to the display control portion, and then, the output image data processing transitions to step **S370**. For example, in a case where the enlarged display image data is output to the display control portion, the display control portion displays an image based on the enlarged display image data on the display apparatus as illustrated in FIG. **27**. The image based on the enlarged display image data is displayed at the second frame rate on the display apparatus.

[0313] In step **S366**, the CPU **52** executes processing corresponding to processing of step **S364**, and then, the output image data processing transitions to step **S368**.

[0314] In step **S368**, the CPU **52** performs the focusing control based on the focusing control image data, and then, the output image data processing transitions to step **S370**.

[0315] In step **S370**, the CPU **52** determines whether or not an output image data processing finish condition that is a condition for finishing the output image data processing is satisfied. The same condition as the display control processing finish condition described in the first embodiment is illustrated as one example of the output image data processing finish condition.

[0316] In step **S370**, in a case where the output image data processing finish condition is not satisfied, a negative determination is made, and the output image data processing transitions to step **S360**. In step **S370**, in a case where the output image data processing finish condition is satisfied, a positive determination is made, and the CPU **52** finishes the output image data processing.

[0317] As described above, in the imaging apparatus **10** according to the third embodiment, the focusing control image data is generated, and the generated focusing control image data is included in the output image data. Accordingly, even in a case where the focusing control is performed using the focusing control image data, the imaging apparatus **10** according to the third embodiment can reduce power consumption compared to a case of generating the focusing control image data in the rear stage circuit **90**.

Fourth Embodiment

[0318] The image data generation processing and the image data output processing are illustrated in the first embodiment. In a fourth embodiment, an example of a form in which the processing circuit **94** further executes imaging control processing will be described. In the fourth embodiment, the

same constituents as constituents described in the first embodiment will be designated by the same reference signs and will not be described.

[0319] The imaging apparatus **10** according to the fourth embodiment is different from the imaging apparatus **10** according to the first embodiment in that the processing circuit **94** can further execute the imaging control processing illustrated in FIG. **29**. In addition, the imaging apparatus **10** according to the fourth embodiment is different from the imaging apparatus **10** according to the first embodiment in that the image data generation processing illustrated in FIG. **30** can be further executed. The imaging control processing illustrated in FIG. **29** and the image data generation processing illustrated in FIG. **30** are executed at the first frame rate by the processing circuit **94**.

[0320] In the imaging control processing illustrated in FIG. **29**, first, in step **S400**, the processing circuit **94** determines whether or not imaging location designation information is received by the touch panel **42** and/or the operation portion **54**. The imaging location designation information refers to information for designating a photodiode to be used for obtaining the partial image data among all photodiodes in the photoelectric conversion element **92**. The imaging location designation information includes an imaging location designation address that can be used for specifying a designated position in the photoelectric conversion element **92**.

[0321] In step **S400**, in a case where the imaging location designation information is not received by the touch panel **42** and/or the operation portion **54**, a negative determination is made, and the imaging control processing transitions to step **S402**. In step **S400**, in a case where the imaging location designation information is received by the touch panel **42** and/or the operation portion **54**, a positive determination is made, and the imaging control processing transitions to step **S404**. A case where a positive determination is made in step **S400** is one example of a “case where a location corresponding to a part of a subject in a photoelectric conversion element is designated by designating the part of the subject” according to the embodiment of the technology of the present disclosure.

[0322] In step **S402**, the photoelectric conversion element drive circuit **94A** acquires the captured image data by imaging the subject using all photodiodes in the photoelectric conversion element **92**, and then, the imaging control processing transitions to step **S414**.

[0323] In step **S404**, the photoelectric conversion element drive circuit **94A** acquires the imaging location designation address from the imaging location designation information, and then, the imaging control processing transitions to step **S406**.

[0324] In step **S406**, the photoelectric conversion element drive circuit **94A** causes the photoelectric conversion element **92** to start imaging at an imaging location designated in accordance with the imaging location designation address, and then, the imaging control processing transitions to step **S408**. The captured image data obtained by imaging by executing processing of step **S406** is partial image correspondence data. The partial image correspondence data refers to image data corresponding to the partial image data described in the first embodiment. The partial image correspondence data is stored in the memory **96** in the same manner as the partial image data.

[0325] In step **S408**, the processing circuit **94** acquires the partial image correspondence data from the memory **96**, and then, the imaging control processing transitions to step **S410**.

[0326] In step **S410**, the processing circuit **94** determines whether or not a release condition for releasing a designation state of the imaging location for the photoelectric conversion element **92** is satisfied. In step **S410**, in a case where the release condition is not satisfied, a negative determination is made, and the imaging control processing transitions to step **S400**. In step **S410**, in a case where the release condition is satisfied, a positive determination is made, and the imaging control processing transitions to step **S412**.

[0327] In step **S412**, the photoelectric conversion element drive circuit **94A** releases the designation state of the imaging location for the photoelectric conversion element **92**, and then, the imaging control processing transitions to step **S414**.

[0328] In step **S414**, the processing circuit **94** determines whether or not an imaging control processing finish condition that is a condition for finishing the imaging control processing is satisfied. For example, a condition that an instruction to finish the imaging control processing is received by the touch panel **42** and/or the operation portion **54** is illustrated as the imaging control processing finish condition.

[0329] In step **S414**, in a case where the imaging control processing finish condition is not satisfied, a negative determination is made, and the imaging control processing transitions to step **S400**. In step **S414**, in a case where the imaging control processing finish condition is satisfied, a positive determination is made, and the processing circuit **94** finishes the imaging control processing.

[0330] Next, a case where the image data generation processing according to the fourth embodiment is executed by the processing circuit **94** will be described with reference to FIG. **30**.

[0331] In the image data generation processing illustrated in FIG. **30**, in step **S450**, the processing circuit **94** determines whether or not image data is acquired from the photoelectric conversion element **92** by the photoelectric conversion element drive circuit **94A**. For convenience of description, the image data acquired from the photoelectric conversion element **92** is the partial image correspondence data acquired in step **S408** of the imaging control processing or the captured image data acquired in step **S402** of the imaging control processing.

[0332] In step **S450**, in a case where the image data is not acquired from the photoelectric conversion element **92** by the photoelectric conversion element drive circuit **94A**, a negative determination is made, and the image data generation processing transitions to step **S468**. In step **S450**, in a case where the image data is acquired from the photoelectric conversion element **92** by the photoelectric conversion element drive circuit **94A**, a positive determination is made, and the image data generation processing transitions to step **S452**.

[0333] In step **S452**, the processing circuit **94** determines whether or not the image data acquired from the photoelectric conversion element **92** is the partial image correspondence data. In step **S452**, in a case where the image data acquired from the photoelectric conversion element **92** is not the partial image correspondence data, that is, in a case where the image data acquired from the photoelectric conversion element **92** is the captured image data, a negative determination is made, and a transition is made to step **S454**. In step **S452**, in a case where the image data acquired from the photoelectric conversion element **92** is the partial image correspondence data, a positive determination is made, and the image data generation processing transitions to step **S456**. In a case where the image data acquired from the photoelectric conversion element **92** is the captured image data, the captured image data is stored in the memory **96**.

[0334] In step **S454**, the image processing circuit **94C** acquires the captured image data from the memory **96** and generates and outputs the entirety image data described in the first embodiment to the output circuit **94D** based on the acquired captured image data, and then, the image data generation processing transitions to step **S468**.

[0335] In step **S456**, the AD conversion circuit **94B** stores the partial image correspondence data in the memory **96**, and then, the image data generation processing transitions to step **S458**.

[0336] In step **S458**, the image processing circuit **94C** determines whether or not the high image quality cut-out instruction described in the first embodiment is received by the touch panel **42** and/or the operation portion **54**. In step **S458**, in a case where the high image quality cut-out instruction is not received by the touch panel **42** and/or the operation portion **54**, a negative determination is made, and the image data generation processing transitions to step **S460**. In step **S458**, in a case where the high image quality cut-out instruction is received by the touch panel **42** and/or the operation portion **54**, a positive determination is made, and the image data generation processing transitions to step **S462**.

[0337] In step **S460**, the image processing circuit **94C** acquires the partial image correspondence data of a single frame from the memory **96**. The image processing circuit **94C** generates and

outputs low image quality cut-out image correspondence data to the output circuit **94D** based on the acquired partial image correspondence data of the single frame, and then, the image data generation processing transitions to step **S468**.

[0338] For example, the partial image correspondence data of the single frame refers to the partial image correspondence data least recently stored in the memory **96**. However, the technology of the present disclosure is not limited thereto. For example, the partial image correspondence data of the single frame may be any partial image correspondence data in a case where the partial image correspondence data of a plurality of frames is stored in the memory **96**.

[0339] The low image quality cut-out image correspondence data refers to image data corresponding to the low image quality cut-out image data described in the first embodiment.

[0340] In step **S462**, the image processing circuit **94C** determines whether or not the captured image data of a plurality of frames is stored in the memory **96**. In step **S462**, three frames are employed as one example of the plurality of frames. In step **S462**, in a case where the captured image data of the plurality of frames is not stored in the memory **96**, a negative determination is made, and the image data generation processing transitions to step **S464**. In step **S462**, in a case where the captured image data of the plurality of frames is stored in the memory **96**, a positive determination is made, and the image data generation processing transitions to step **S466**.

[0341] In step **S464**, the image processing circuit **94C** executes processing corresponding to processing of step **S454**, and then, the image data generation processing transitions to step **S462**.

[0342] In step **S466**, the image processing circuit **94C** acquires the partial image correspondence data of the plurality of frames from the memory **96**. The image processing circuit **94C** generates and outputs high image quality cut-out image correspondence data to the output circuit **94D** based on the acquired partial image correspondence data of the plurality of frames, and then, the image data generation processing transitions to step **S468**.

[0343] The high image quality cut-out image correspondence data refers to image data corresponding to the high image quality cut-out image data described in the first embodiment. For example, combined data obtained by combining the partial image correspondence data of three frames is employed as the high image quality cut-out image correspondence data in the same manner as the example illustrated in FIG. **10**. However, the technology of the present disclosure is not limited thereto. For example, the high image quality cut-out image correspondence data may be image data obtained by performing various types of image processing on the combined data obtained by combining the partial image data of three frames.

[0344] The low image quality cut-out image data generated by executing processing of step **S460** and the high image quality cut-out image data generated by executing processing of step **S466** are one example of “image data based on partial image correspondence data” according to the embodiment of the technology of the present disclosure.

[0345] In step **S468**, the image processing circuit **94C** determines whether or not the image data generation processing finish condition described in the first embodiment is satisfied. In step **S468**, in a case where the image data generation processing finish condition is not satisfied, a negative determination is made, and the image data generation processing transitions to step **S450**. In step **S468**, in a case where the image data generation processing finish condition is satisfied, a positive determination is made, and the image processing circuit **94C** finishes the image data generation processing.

[0346] Hereinafter, for convenience of description, the low image quality cut-out image correspondence data and the high image quality cut-out image correspondence data will be referred to as “cut-out image correspondence data” unless otherwise necessary to distinguish therebetween for description.

[0347] Next, the image data output processing executed by the output circuit **94D** of the processing circuit **94** according to the fourth embodiment will be described with reference to FIG. **8**. The image data output processing illustrated in FIG. **8** according to the fourth embodiment is performed

at the second frame rate by the output circuit **94D**.

[0348] In the image data output processing illustrated in FIG. **8** according to the fourth embodiment, first, in step **S490**, the output circuit **94D** determines whether or not the cut-out image correspondence data is input from the image processing circuit **94C**. In step **S490**, in a case where the cut-out image correspondence data is not input from the image processing circuit **94C**, a negative determination is made, and a transition is made to step **S494**. In step **S490**, in a case where the cut-out image correspondence data is input from the image processing circuit **94C**, a positive determination is made, and a transition is made to step **S492**.

[0349] In step **S492**, the output circuit **94D** outputs the cut-out image correspondence data to the I/F **56** of the rear stage circuit **90** and then, transitions to step **S494**. For example, the I/F **56** outputs the cut-out image correspondence data input from the output circuit **94D** to the CPU **52** and the image processing portion **62** through the bus **68**.

[0350] In step **S494**, the output circuit **94D** determines whether or not the image data output processing finish condition is satisfied. In step **S494**, in a case where the image data output processing finish condition is not satisfied, a negative determination is made, and the image data output processing transitions to step **S490**. In step **S494**, in a case where the image data output processing finish condition is satisfied, a positive determination is made, and the output circuit **94D** finishes the image data output processing.

[0351] Next, the display control processing executed by the display control portion of the rear stage circuit **90** according to the fourth embodiment will be described with reference to FIG. **9**. For convenience of description, it is assumed that the cut-out image correspondence data is output to the rear stage circuit **90** from the output circuit **94D** by executing the image data output processing illustrated in FIG. **8**, and that the cut-out image correspondence data is input into the CPU **52** and the image processing portion **62**. In addition, an image indicated by the high image quality cut-out image correspondence data and an image indicated by the low image quality cut-out image correspondence data will be referred to as a “cut-out correspondence image” unless otherwise necessary to distinguish therebetween for description.

[0352] In the display control processing illustrated in FIG. **9**, in step **S500**, the display control portion determines whether or not the cut-out image correspondence data is input from the image processing portion **62**. In step **S500**, in a case where the cut-out image correspondence data is not input from the image processing portion **62**, a negative determination is made, and the display control processing transitions to step **S504**. In step **S500**, in a case where the cut-out image correspondence data is input from the image processing portion **62**, a positive determination is made, and the display control processing transitions to step **S502**.

[0353] In step **S502**, the display control portion outputs the cut-out image correspondence data to the display apparatus as graphics data, and then, the display control processing transitions to step **S504**. In a case where the cut-out image correspondence data is output to the display apparatus by executing processing of step **S502**, the display apparatus displays the cut-out correspondence image indicated by the cut-out image correspondence data.

[0354] The cut-out correspondence image is any of a high image quality cut-out correspondence image and a low image quality cut-out correspondence image. For example, the high image quality cut-out correspondence image is an image corresponding to the image based on the combined data obtained by combining the captured image data of three frames in the same manner as the example illustrated in FIG. **10**. Meanwhile, the low image quality cut-out correspondence image is a thinned image based on the captured image data of one frame. Thus, the image quality of the image displayed on the display apparatus is such that the high image quality cut-out correspondence image has higher image quality than the low image quality cut-out correspondence image.

[0355] In step **S504**, the display control portion determines whether or not the display control processing finish condition is satisfied. In step **S504**, in a case where the display control processing finish condition is not satisfied, a negative determination is made, and the display control

processing transitions to step S500. In step S504, in a case where the display control processing finish condition is satisfied, a positive determination is made, and the display control portion finishes the display control processing.

[0356] For example, by executing the imaging control processing illustrated in FIG. 29, the image data generation processing illustrated in FIG. 30, the image data output processing illustrated in FIG. 8, and the display control processing illustrated in FIG. 9, the live view image is displayed on the display apparatus under control of the display control portion. In this case, the “live view image” refers to an image in a live view format based on the cut-out image correspondence data. In the imaging apparatus 10 according to the fourth embodiment, the live view image is displayed at the second frame rate.

[0357] As described above, in the imaging apparatus 10 according to the fourth embodiment, the processing circuit 94 generates the partial image correspondence data by causing the photoelectric conversion element 92 to perform imaging at the imaging location designated in accordance with the imaging location designation address, and stores the partial image correspondence data in the memory 96. The processing circuit 94 acquires the partial image correspondence data from the memory 96. The output circuit 94D outputs the cut-out image correspondence data to the rear stage circuit 90.

[0358] Accordingly, the imaging apparatus 10 according to the fourth embodiment can reduce power consumption compared to a case of imaging the subject using all regions of the photoelectric conversion element 92 at all times.

[0359] While a case where compressed image data is used for displaying the live view image is described in each embodiment above, the technology of the present disclosure is not limited thereto. For example, by the CPU 52, the compressed image data may be stored in the secondary storage portion 60 in the rear stage circuit 90 or may be output to the outside of the imaging apparatus 10 through the external I/F 63.

[0360] While the processing circuit 94 implemented by the ASIC is illustrated in each embodiment above, the image data generation processing, the image data output processing, and the imaging control processing may be implemented by a computer using a software configuration.

[0361] In this case, for example, as illustrated in FIG. 31, a program 600 for causing a computer 20A incorporated in the imaging element 20 to execute the image data generation processing, the image data output processing, and the imaging control processing is stored in a storage medium 700. The computer 20A comprises a CPU 20A1, a ROM 20A2, and a RAM 20A3. The program 600 of the storage medium 700 is installed on the computer 20A, and the CPU 20A1 of the computer 20A executes the image data generation processing, the image data output processing, and the imaging control processing in accordance with the program 600. A single CPU is illustrated as the CPU 20A1. However, the technology of the present disclosure is not limited thereto, and a plurality of CPUs may be employed instead of the CPU 20A1. That is, the image data generation processing, the image data output processing, and/or the imaging control processing may be executed by one processor or a plurality of physically separated processors.

[0362] Any portable storage medium such as a solid state drive (SSD) or a universal serial bus (USB) is illustrated as one example of the storage medium 700.

[0363] Alternatively, the program 600 may be stored in a storage portion of another computer, a server apparatus, or the like connected to the computer 20A through a communication network (not illustrated), and the program 600 may be downloaded in accordance with a request from the imaging apparatus 10 or the like. In this case, the downloaded program 600 is executed by the computer 20A.

[0364] The computer 20A may be disposed outside the imaging element 20. In this case, the computer 20A may control the processing circuit 94 in accordance with the program 600.

[0365] Various processors illustrated below can be used as a hardware resource for executing various types of processing described in each embodiment above. As various types of processing

described in each embodiment above, the image data generation processing, the image data output processing, the display control processing, the single region cut-out processing, the plural region cut-out processing, the output image data processing, and the imaging control processing are illustrated. For example, as described above, a CPU that is a general-purpose processor functioning as a hardware resource for executing various types of processing according to the embodiment of the technology of the present disclosure by executing software, that is, the program, is illustrated as a processor. In addition, a dedicated electric circuit such as an FPGA, a PLD, or an ASIC that is a processor having a circuit configuration dedicatedly designed to execute a specific type of processing is illustrated as a processor. A memory is incorporated in or connected to any of the processors, and any of the processors executes various types of processing using the memory.

[0366] The hardware resource for executing various types of processing according to the embodiment of the technology of the present disclosure may be configured with one of those various processors or may be configured with a combination of two or more processors of the same type or different types (for example, a combination of a plurality of FPGAs or a combination of a CPU and an FPGA). Alternatively, the hardware resource for executing various types of processing according to the embodiment of the technology of the present disclosure may be one processor.

[0367] As an example of a configuration with one processor, first, as represented by a computer such as a client and a server, a form in which one processor is configured with a combination of one or more CPUs and software and this processor functions as the hardware resource for executing various types of processing according to the embodiment of the technology of the present disclosure is available. Second, as represented by a system-on-a-chip (SoC) or the like, a form of using a processor that implements, by one IC chip, a function of the entire system including a plurality of hardware resources for executing various types of processing according to the embodiment of the technology of the present disclosure is available. Accordingly, various types of processing according to the embodiment of the technology of the present disclosure are implemented using one or more of above various processors as a hardware resource.

[0368] Furthermore, as a hardware structure of those various processors, more specifically, an electric circuit in which circuit elements such as semiconductor elements are combined can be used.

[0369] While an interchangeable lens camera is illustrated as the imaging apparatus **10** in each embodiment above, the technology of the present disclosure is not limited thereto. For example, the technology of the present disclosure may be applied to a smart device **900** illustrated in FIG. **32**.

For example, the smart device **900** illustrated in FIG. **32** is one example of the imaging apparatus according to the embodiment of the technology of the present disclosure. The imaging element **20** described in the embodiments is mounted on the smart device **900**. Even with the smart device **900** configured in such a manner, the same action and effect as the imaging apparatus **10** described in each embodiment above are achieved. The technology of the present disclosure can be applied to not only the smart device **900** but also a personal computer or a wearable terminal apparatus.

[0370] While the first display **40** and the second display **80** are illustrated as the display apparatus in each embodiment above, the technology of the present disclosure is not limited thereto. For example, a separate display that is retrofit into the imaging apparatus main body **12** may be used as the “display portion” according to the embodiment of the technology of the present disclosure.

[0371] The image data generation processing, the image data output processing, the display control processing, the output image data processing, and the imaging control processing described in each embodiment above are merely one example. Accordingly, unnecessary steps may be removed, new steps may be added, or a processing order may be changed without departing from a gist of the technology of the present disclosure.

[0372] Above described contents and illustrated contents are detailed description for parts according to the embodiment of the technology of the present disclosure and are merely one example of the technology of the present disclosure. For example, description related to the above

configurations, functions, actions, and effects is description related to one example of configurations, functions, actions, and effects of the parts according to the embodiment of the technology of the present disclosure. Thus, unnecessary parts may be removed, new elements may be added, or parts may be replaced in the above described contents and the illustrated contents without departing from the gist of the technology of the present disclosure. In addition, particularly, description related to common technical knowledge or the like that does not need to be described in terms of embodying the technology of the present disclosure is omitted in the above described contents and the illustrated contents in order to avoid complication and facilitate understanding of the parts according to the embodiment of the technology of the present disclosure.

[0373] In the present specification, “A and/or B” has the same meaning as “at least one of A or B”. This means that “A and/or B” may be only A, may be only B, or may be a combination of A and B. In addition, in the present specification, the same approach as “A and/or B” is applied to a case where three or more matters are represented by connecting the matters with “and/or”.

[0374] All documents, patent applications, and technical standards disclosed in the present specification are incorporated in the present specification by reference to the same extent as in a case where each of the documents, patent applications, technical standards is specifically and individually indicated to be incorporated by reference.

Claims

1. An imaging element comprising: a memory that stores captured image data obtained by imaging a subject at a first frame rate; an image processing circuit that performs processing on the captured image data that is stored in the memory to generate output image data, the image processing circuit being incorporated in the imaging element; and an output circuit that outputs output image data obtained by performing the processing on the captured image data to an exterior of the imaging element at a second frame rate, wherein the processing performed by the image processing circuit comprises cut-out processing with respect to one frame of the captured image data, the cut-out processing including cutting out partial image data indicating an image of a part of the subject in the captured image data from a designated address in the memory, the image processing circuit performing the cut-out processing at the first frame rate within one frame period thereof, the output image data includes image data based on the partial image data that is cut out from the captured image data as a result of performing the cut-out processing by the image processing circuit, and the first frame rate is a frame rate higher than the second frame rate.
2. The imaging element according to claim 1, wherein the cut-out processing is processing of cutting out the partial image data from the captured image data stored in the memory by random access to the memory.
3. The imaging element according to claim 1, wherein the memory is capable of storing the captured image data of a plurality of frames, the cut-out processing includes processing of cutting out the partial image data of the plurality of frames from the captured image data stored in the memory, and the output portion outputs, as the output image data, image data that is obtained by combining the partial image data of the plurality of frames cut out as a result of performing the cut-out processing by the image processing circuit.
4. The imaging element according to claim 3, wherein the partial image data is at least one of a plurality of pieces of divided region image data corresponding to a plurality of divided regions obtained by dividing the part.
5. The imaging element according to claim 4, wherein the plurality of pieces of divided region image data have a relationship in which mutually different pixels are thinned out in units of lines.
6. The imaging element according to claim 4, wherein the output image data includes combined data obtained by combining the plurality of pieces of divided region image data.
7. The imaging element according to claim 6, wherein the output circuit selectively outputs, as the

partial image data, divided region image data of a part of the plurality of pieces of divided region image data or the combined data in accordance with a provided condition.

8. The imaging element according to claim 1, wherein the subject is imaged by a photoelectric conversion element, in a case in which an area of the photoelectric conversion element corresponding to the part is designated by designating the part of the subject, the image processing circuit causes the area of the photoelectric conversion element to perform imaging, and the image processing circuit acquires partial image correspondence data corresponding to the partial image data at the first frame rate by performing imaging by the area of the photoelectric conversion element, and outputs image data based on the acquired partial image correspondence data to the exterior of the imaging element at the second frame rate.

9. The imaging element according to claim 1, wherein the part includes a plurality of regions in the subject, and the partial image data is a plurality of pieces of region image data indicating the plurality of regions in the captured image data.

10. The imaging element according to claim 1, wherein the output image data further includes wide range image data that indicates an image of a range of the subject wider than the part of the subject, and resolution of the wide range image data is lower than resolution of the partial image data.

11. The imaging element according to claim 10, wherein the wide range image data is image data indicating an image of an entirety of the subject.

12. The imaging element according to claim 1, wherein the output image data further includes focusing control image data indicating an image of a range that is a range of the subject wider than the part of the subject and that is a predetermined range as a range required for a focusing control of an imaging apparatus including the imaging element.

13. An imaging apparatus comprising: the imaging element according to claim 1; and a display processor that is configured to perform a control for displaying an image based on the output image data output by the image processing circuit on a display in an enlarged manner.

14. An image data processing method of an imaging element including a memory, an image processing circuit, and an output circuit, the image data processing method comprising: storing, by the memory, captured image data obtained by imaging a subject at a first frame rate; performing, by the image processing circuit, processing on the captured image data that is stored in the memory to generate output image data; and outputting, by the output circuit, output image data obtained by performing the processing on the captured image data to an exterior of the imaging element at a second frame rate, wherein the processing performed by the image processing circuit comprises cut-out processing with respect to one frame of the captured image data, the cut-out processing including cutting out partial image data indicating an image of a part of the subject in the captured image data from a designated address in the memory, the image processing circuit performing the cut-out processing at the first frame rate within one frame period thereof, wherein the output image data includes image data based on the partial image data that is cut out from the captured image data as a result of performing the cut-out processing by the image processing circuit, the first frame rate is a frame rate higher than the second frame rate.

15. A non-transitory storage medium storing a program that causes a computer to function as an image processing circuit and an output portion included in an imaging element, and to perform an image data processing, the imaging element including a memory, the image processing circuit, and the output circuit, the image data processing comprising: storing, by the memory, captured image data obtained by imaging a subject at a first frame rate; performing, by the image processing circuit, processing on the captured image data that is stored in the memory to generate output image data; and outputting, by the output circuit, output image data obtained by performing the processing on the captured image data to an exterior of the imaging element at a second frame rate, wherein the processing performed by the image processing circuit comprises cut-out processing with respect to one frame of the captured image data, the cut-out processing including cutting out partial image data indicating an image of a part of the subject in the captured image data from a

designated address in the memory, the image processing circuit performing the cut-out processing at the first frame rate within one frame period thereof, wherein the output image data includes image data based on the partial image data that is cut out from the captured image data as a result of performing the cut-out processing by the image processing circuit, and the first frame rate is a frame rate higher than the second frame rate.

16. The imaging element according to claim 1, wherein all of the captured image data obtained by the imaging is once stored in the memory and then output from the output circuit via the image processing circuit.

17. The imaging element according to claim 1, further comprising a photoelectric conversion element that generates the captured image data by imaging the subject, wherein an output terminal of the photoelectric conversion element is connected to the memory, an output terminal of the memory is connected to the image processing circuit, and an output terminal of the image processing circuit is connected to the output circuit.
