

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250263096

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Brick; Michael James et al.

---

### AUTOMATED TIE MARKING

---

#### Abstract

A system and method for automating railroad maintenance for a tie gang using electronic tie marking (ETM) configured to optimize railroad asset maintenance. The system enables the automating of an adaptive maintenance process for the asset that is being maintained. The system can identify a railroad asset scheduled for maintenance using various forms of inspection including real-time kinematic (RTK)-corrected GPS data, radar signal processing data, and real-time imaging. The system also provides for the acquisition and upload of asset pictures for verification and analysis of a railroad asset. The system can identify a next location to perform maintenance and can calculate an optimum path based on sensor input incorporating machine-specific and environmental characteristics. The system further can provide a customizable user interface to identify, track, and process information related to maintenance of the railroad asset.

---

**Inventors:** Brick; Michael James (Fort Worth, TX), Kelly; Lisa Marie (Weatherford, TX), Minton; Samuel (Brandon, SD), Keller; Richard William (Spokane Valley, WA)

**Applicant:** BNSF Railway Company (Fort Worth, TX)

**Family ID:** 1000008576591

**Assignee:** BNSF Railway Company (Fort Worth, TX)

**Appl. No.:** 19/198912

**Filed:** May 05, 2025

#### Related U.S. Application Data

parent US continuation 18055015 20221114 parent-grant-document US 12291248 child US 19198912

parent US continuation 17687025 20220304 parent-grant-document US 11565730 child US 18055015

---

## Publication Classification

**Int. Cl.:** **B61K9/08** (20060101); **B61L23/04** (20060101); **B61L25/02** (20060101); **E01B29/02** (20060101); **E01B29/10** (20060101); **E01B29/26** (20060101); **E01B29/32** (20060101); **E01B35/00** (20060101)

**U.S. Cl.:**

**CPC** **B61K9/08** (20130101); **E01B29/02** (20130101); **E01B29/10** (20130101); **E01B29/26** (20130101); **E01B29/32** (20130101); **E01B35/00** (20130101); B61L23/042 (20130101); B61L23/047 (20130101); B61L25/025 (20130101)

---

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] The present application is a Continuation Application of U.S. patent application Ser. No. 18/055,015, filed Nov. 14, 2022, and U.S. patent application Ser. No. 17/687,025, filed Mar. 4, 2022, the contents of which are incorporated herein in its entirety for all purposes.

### TECHNICAL FIELD

[0002] The present disclosure relates generally to the management of railroad asset maintenance, and more particularly to systems and methods for automated railroad asset maintenance for railroad system infrastructure.

### BACKGROUND

[0003] Railroad assets such as railroad ties, spikes, ballast, and other assets degrade over time. If the railroad assets are subjected to extreme elements, the assets can degrade at a much higher rate. Accordingly, significant resources have been dedicated to inspecting and repairing such railroad infrastructure. Traditional approaches to identifying and repairing/replacing degraded railroad assets suffer from many shortcomings. For example, identifying a railroad spike to replace can be difficult. Generally, the railroad spike can have asset location data, such as the latitude and longitude of the railroad asset. However, the method to arrive at the latitude and longitude provides difficulty in locations without sufficient global positioning system (GPS) signal strength.

[0004] Conventional approaches can use a number of methods, including counting railroad ties to identify their location. Such an approach can provide wide variability and inaccuracies. For example, these approaches can be as far off of the target railroad asset by tens of railroad ties. Naturally, being so far off of the target can cause significant efficiency errors in maintaining a railroad. Additionally, railroad personnel are still required to use the improper GPS data and travel to the improper location to perform maintenance on the railroad asset. Inefficient maintenance procedures can lead to near impossible railroad asset maintenance when based on inaccurate location information. And the determination of whether an asset is to receive maintenance can be subjective without any uniformity based on a visual determination of asset integrity.

[0005] Finding the correct railroad asset is another problem. In the rare case that the maintenance crew reaches the correct location, identifying the correct railroad asset prior to repair/replacement requires manual intervention for the maintenance crew to visually inspect the asset to determine if it indeed requires maintenance. Visually inspecting an asset can be confusing to the maintenance crew because the asset might be damaged, dirty, and obfuscated. Moreover, the maintenance crew requires various machines to complete maintenance, each machine working on the railroad asset one at a time. In this manner, a first group of the maintenance crew can reach the railroad asset minutes, or even hours, before a second group of the maintenance crew. By approaching the

railroad asset at different times, the difficulty to identify the same railroad asset increases because there might be no efficient way to communicate which railroad asset was worked on by the first group. Although there is an antiquated approach to railroad asset maintenance, it is near impossible to consistently maintain an entire railroad in a comparable manner. The costs associated with the aforementioned traditional operations can be staggering. For example, given tens of thousands of miles of railroad track, the cost of paint alone can be in the hundreds of thousands. With only two tie painters per tie gang, the employee cost for providing the tie painters can be in the millions per year.

## SUMMARY

[0006] The present disclosure achieves technical advantages as a system and method for automating railroad maintenance by a tie gang using Electronic Tie Marking (ETM) configured to optimize railroad asset maintenance. The present system enables the automating of an adaptive maintenance process for the asset that is being maintained (e.g., Rails, Ties, Ballasts, Turnouts, Crossings, etc.). The system can identify a railroad asset scheduled for maintenance using various forms of inspection including real-time kinematic (RTK)-corrected GPS data, radar signal processing data, and real-time imaging, among others. The system can utilize RTK-corrected GPS coordinates from ground stations in communication with a tie gang. The system also provides for the acquisition and upload of asset pictures for verification and analysis of a railroad asset. The system can identify a next location to perform maintenance and can calculate an optimum path based on sensor input incorporating machine-specific and environmental characteristics. The system can provide a customizable user interface to identify, track, and process information related to maintenance of the railroad asset.

[0007] The present disclosure solves the technological problem of navigating a tie gang to railroad assets needing maintenance and providing the tie gang with a system configured to capture an image of a railroad asset to verify the railroad asset and analyze a health of the railroad asset. The system can be disposed in a lead machine of the tie gang (or have a distributed architecture) and enable the tie gang to efficiently perform maintenance on the railroad asset. The present disclosure goes beyond mere manual inspection and maintenance of a railroad asset, incorporating at least image analysis functionality and machine learning modules that can identify whether the railroad asset is to be maintained, GPS receivers (including RTK-corrected GPS) to provide greater location granularity, location calibration, receipt of predetermined maintenance information, and location information for a maintenance operation. Advantageously, the system can perform an analysis of the railroad asset based on physical characteristics of the railroad asset determined from the image, and by providing calibration techniques for the tie gang to locate the railroad asset within centimeters. This also provides the benefit of simplifying the maintenance process for the tie gang by providing them with only relevant information needed for a particular railroad asset, so the tie gang can conduct their maintenance more quickly, more clearly, and more concisely, without inefficient duplicative work.

[0008] The present disclosure provides a technical solution to the technical problem by acquiring maintenance data for one or more railroad assets, providing location calibration for the tie gang, analyzing an image of the railroad asset, and automating the maintenance procedures of the railroad asset. In contrast, traditional systems simply rely on manual processes and often-inaccurate location information, resulting in inefficient maintenance procedures inundated with errors, redundant work, and add to the strain on an already overspent system. The present disclosure can not only determine exactly where the railroad asset that needs to be replaced or maintenance is located, but can also enable an automated maintenance process as disclosed in more detail below.

[0009] In one embodiment, the system can include an ability to determine a movement path of the tie gang, avoid collisions between machines in the tie gang, generate machine production identifiers to queue a workflow of railroad asset maintenance, and display a user interface in the machines. By way of overview, the process flow can begin at the machine production identifier,

which can be displayed on a user interface (UI) operable by a crew member in the tie gang performing maintenance on a section of track or another railroad asset. Using track maintenance as an example, the tie gang can generate trackside inspections with or without connectivity using a local file distribution system. The precise location (e.g., latitude and longitude coordinates) of a user/client can be determined using RTK-corrected GPS data from a GPS disposed within the tie gang, comparing the location information for the railroad asset with visual techniques to determine a precise location, or comparing the location information of the railroad asset with a combination of RTK-corrected GPS data, visual techniques, and radar signal processing. The system can transmit the production identifiers to the machines of the tie gang for ease of railroad asset identification. In current applications, the maintenance of railroad assets is based on a time to complete the maintenance, rather than organized using a workflow production system and production identifiers. For example, some tie gangs can complete railroad maintenance in half the time as another tie gang, which leads to inconsistencies in maintenance management. The use of production identifiers can free up the systemic inefficiency of railroad maintenance.

[0010] The system also can display information about the production identifier using the UI. The UI can include direction, location, railroad asset information, among other characteristics important to the tie gang. The UI can include a map having the railroad line segment milepost to the client to generate a workflow schedule. The location data can be captured at the trackside, along with the asset data for the track type (e.g., mainline, main one, main two, main three, turnout, switch, bridge, crossover, etc.), as well as any defect data. In one exemplary embodiment, users can store maintenance instructions for one or more sections of track on a client locally without connectivity, and once connectivity is acquired, all the stored inspections can be uploaded to a central server and further processed by the backend system.

[0011] The system also can determine a movement path of the tie gang. The movement path can be based on various factors impacting an ability of the tie gang to travel along the tracks of the railroad. For example, the various factors can include both vehicle characteristics and external environmental characteristics. Particularly, the movement of the tie gang can be heavily reliant on the weight of the machines, the length of the machines, and environmental conditions. For example, the weight of the machines in the tie gang might increase if collecting discarded railroad assets or decrease if depositing new railroad assets. Additionally, the system can optimize a movement path of the tie gang based on a braking algorithm to determine the appropriate braking maneuvers to apply to reach a next railroad asset to perform maintenance.

[0012] The system also can perform collision avoidance for the machines in the tie gang. The tie gang can include a plurality of machines and the track can include curves that block the line of sight for the engineers in the tie gang. Accordingly, the poor visual ability of the machines of the tie gang can result in hazardous conditions. The system can determine when an obstacle is ahead of the machines of the tie gang and can apply brakes of the machines in the tie gang accordingly. For example, when the obstacle is another machine, the machines of the tie gang can include forward-looking radar systems to identify whether the obstacle machine is ahead of the respective machine in the tie gang. Alternatively, the machines of the tie gang can perform machine-to-machine (M2M) communications to establish distances between the machines for enhanced safety.

[0013] It is an object of the invention to provide a system for generating a strategic track and maintenance planning inspection record for a railroad asset. It is a further object of the invention to provide a method for generating a strategic track and maintenance planning inspection record for a railroad asset. These and other objects are provided by at least the following embodiments.

[0014] In one embodiment, a method for performing maintenance using electronic tie marking (ETM), comprising: receiving a maintenance operation request for a maintenance item, the request having a calibration location, predetermined maintenance information, and location information for a maintenance operation; positioning a first vehicle having a GPS receiver identifying the first vehicle location at the calibration location by correlating the first vehicle location with the

calibration location; calculating a travel distance from the calibration location to a maintenance location based on the maintenance information; traveling the travel distance from the calibration location to the maintenance location to perform the maintenance operation for a maintenance item at the maintenance location; capturing an image of the maintenance item; generating an analysis of the maintenance item based on the image; and automatically performing a maintenance operation based on the analysis. Wherein the method further comprises: verifying a calibration location of a machine based on the maintenance information and the location information; and traveling to the calibration location to calibrate the machine. Wherein the file is via a Universal Serial Bus (USB). Wherein the calibration location is verified based on a comparison between the location information with real-time kinematic (RTK) corrected global position system (GPS) data, radar signal processing, and a real-time image. The method further comprising transmitting the image to a central server to generate the analysis, wherein the central server includes a server on a machine in a tie gang or the central server includes a server in a cloud-based environment. Wherein the maintenance item is to receive maintenance when the analysis meets a condition. Wherein the maintenance item is to receive maintenance based on a maintenance indicator, wherein the maintenance indicator is based on whether the maintenance item already received maintenance. Wherein the maintenance item is to receive maintenance based on a comparison between the maintenance information and information from the image including railway plate hole characteristics, railway spike patterns, and a distance corresponding to the plate hole characteristics. Wherein the maintenance information includes tie marking information and tie grading information. Wherein the maintenance action is based on at least one workhead actions such as spike pulling, anchor spreading, and tie kicking, wherein the maintenance item includes a railway tie. Wherein the analysis is based on image analysis techniques, wherein the image analysis techniques include a machine learning model.

[0015] In another embodiment, a method for guiding a tie gang to perform maintenance, comprising: receiving a location signal; comparing the location signal with location information from a file to calibrate a location of a machine; calculating a distance of a path from the location of the machine to a maintenance location; traveling to the maintenance location. Wherein the method further comprises identifying an edge of a track along the path based on sensor information. Wherein the sensor information includes at least one of a real-time image or radar signal processing data. Wherein the location signal includes at least one of radar signal processing data, global positioning system (GPS) data, or real-time kinematic (RTK)-corrected GPS data.

[0016] In another embodiment, a system for electronic tie marking (ETM), comprising: a memory including railway markings for ETM; and a networked computer processor operably coupled to the memory and capable of executing machine-readable instructions to perform program steps, the program steps comprising: receiving a maintenance operation request for a maintenance item, the request having a calibration location, predetermined maintenance information, and location information for a maintenance operation; positioning a first vehicle having a GPS receiver identifying the first vehicle location at the calibration location by correlating the first vehicle location with the calibration location; calculating a travel distance from the calibration location to a maintenance location based on the maintenance information; traveling the travel distance from the calibration location to the maintenance location to perform the maintenance operation for a maintenance item at the maintenance location; capturing an image of the maintenance item; generating an analysis of the maintenance item based on the image; and automatically performing a maintenance operation based on the analysis. Wherein the file is via a Universal Serial Bus (USB). Wherein the calibration location is verified based on a comparison between the location information with real-time kinematic (RTK) corrected global position system (GPS) data, radar signal processing, and a real-time image. Wherein the program steps further comprising transmitting the image to a central server to generate the analysis, wherein the central server includes a server on a machine part of a tie gang or a server in a cloud-based environment. Wherein

the maintenance item is to receive maintenance when a paint marker is present. Wherein the maintenance item is to receive maintenance based on a maintenance indicator, wherein the maintenance indicator is based on whether the maintenance item already received maintenance. Wherein the maintenance item is to receive maintenance based on a comparison between the maintenance information and information from the image including railway plate hole characteristics, railway spike patterns, and a distance corresponding to the plate hole characteristics. Wherein the location information includes latitude and longitude information. Wherein the maintenance information includes tie marking information and tie grading information. Wherein the maintenance action is based on at least one of spike pulling, an anchor spreading, or tie kicking, wherein the maintenance item includes a railway tie. Wherein the analysis is based on image analysis techniques, wherein the image analysis techniques include a machine learning model.

[0017] In another embodiment, a system for guiding a tie gang to perform maintenance, comprising: a memory including railway markings for electronic tie marking (ETM); and a networked computer processor operably coupled to the memory and capable of executing machine-readable instructions to perform program steps, the program steps comprising: receiving a location signal; comparing the location signal with location information from a file to calibrate a location of a machine; identifying a maintenance location based on sensor information; calculating a distance from the location of the machine to the maintenance location; identifying an edge of a track based on sensor information; and traveling to the maintenance location. Wherein the location signal includes a global positioning system (GPS) signal, a real-time kinematic corrected global positioning system (GPS) data, or radar signal processing data. Wherein the sensor information includes a real-time image or radar signal processing data. Wherein the sensor information includes a real-time image and radar signal processing data.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0018] The present disclosure will be readily understood by the following detailed description, taken in conjunction with the accompanying drawings that illustrate, by way of example, the principles of the present disclosure. The drawings illustrate the design and utility of one or more exemplary embodiments of the present disclosure, in which like elements are referred to by like reference numbers or symbols. The objects and elements in the drawings are not necessarily drawn to scale, proportion, or precise positional relationship. Instead, emphasis is focused on illustrating the principles of the present disclosure.

[0019] FIG. 1 illustrates a railroad asset maintenance system schematic, in accordance with one or more exemplary embodiments of the present disclosure;

[0020] FIG. 2 illustrates a block diagram of an automated workflow system, in accordance with one or more exemplary embodiments of the present disclosure;

[0021] FIG. 3 illustrates a block diagram of a machine in a tie gang, in accordance with one or more exemplary embodiments of the present disclosure;

[0022] FIG. 4 illustrates a block diagram of a railroad maintenance system, in accordance with one or more exemplary embodiments of the present disclosure;

[0023] FIG. 5A illustrates a flowchart exemplifying railroad asset maintenance control logic, in accordance with one or more exemplary embodiments of the present disclosure;

[0024] FIG. 5B illustrates a flowchart exemplifying railroad asset maintenance control logic, in accordance with one or more exemplary embodiments of the present disclosure;

[0025] FIG. 6 illustrates a flowchart exemplifying tie gang guidance control logic, in accordance with one or more exemplary embodiments of the present disclosure; and

[0026] FIG. 7 illustrates a perspective view of a plurality of machines disposed on railroad tracks, in accordance with one or more exemplary embodiments of the present disclosure.

#### DETAILED DESCRIPTION

[0027] The disclosure presented in the following written description and the various features and advantageous details thereof, are explained more fully with reference to the non-limiting examples included in the accompanying drawings and as detailed in the description, which follow.

Descriptions of well-known components have been omitted to not unnecessarily obscure the principal features described herein. The examples used in the following description are intended to facilitate an understanding of the ways in which the disclosure can be implemented and practiced. A person of ordinary skill in the art would read this disclosure to mean that any suitable combination of the functionality or exemplary embodiments below could be combined to achieve the subject matter claimed. The disclosure includes either a representative number of species falling within the scope of the genus or structural features common to the members of the genus so that one of ordinary skill in the art can visualize or recognize the members of the genus. Accordingly, these examples should not be construed as limiting the scope of the claims.

[0028] FIG. 1 illustrates a schematic view of a railroad asset maintenance system **100**, in accordance with one or more exemplary embodiments of the present disclosure. The system **100** can include one or more servers **102** having one or more processor(s) **104**, a memory **130**, machine-readable instructions **106**, including a connectivity module **108**, identification module **110**, status module **112**, authentication module **114**, initialization module **116**, data link module **118**, and geolocation module **120**, among other relevant modules. The server **102** can be operably coupled to one or more clients via a network **140**. The client can be a machine **150** including a railroad maintenance assembly **152** as part of a tie gang along a railway **154**. In another exemplary embodiment, the machine **150** can include an application configured to communicate with the server **102** over the network **140**.

[0029] The aforementioned system components (e.g., server(s) **102** and machine **150**) can be communicably coupled to each other via the network **140**, such that data can be transmitted. The network **140** can be the Internet, intranet, or other suitable network. The data transmission can be encrypted, unencrypted, over a VPN tunnel, or other suitable communication means. The network **140** can be a WAN, LAN, PAN, or other suitable network type. The network communication between the clients, server **102**, or any other system component can be encrypted using PGP, Blowfish, Twofish, AES, 3DES, HTTPS, or other suitable encryption. The system **100** can be configured to provide communication via the various systems, components, and modules disclosed herein via an application programming interface (API), PCI, PCI-Express, ANSI-X12, Ethernet, Wi-Fi, Bluetooth, or other suitable communication protocol or medium. Additionally, third party systems and databases can be operably coupled to the system components via the network **140**.

[0030] The data transmitted to and from the components of system **100** (e.g., the server **102** and machine **150**), can include any format, including JavaScript Object Notation (JSON), TCP/IP, XML, HTML, ASCII, SMS, CSV, representational state transfer (REST), or other suitable format. The data transmission can include a message, flag, header, header properties, metadata, and/or a body, or be encapsulated and packetized by any suitable format having same.

[0031] The server(s) **102** can be implemented in hardware, software, or a suitable combination of hardware and software therefor, and may comprise one or more software systems operating on one or more servers, having one or more processor(s) **104**, with access to memory **130**. Server(s) **102** can include electronic storage, one or more processors, and/or other components. Server(s) **102** can include communication lines, connections, and/or ports to enable the exchange of information via a network (e.g., the network **140**) and/or other computing platforms. Server(s) **102** can also include a plurality of hardware, software, and/or firmware components operating together to provide the functionality attributed herein to server(s) **102**. For example, server(s) **102** can be implemented by a cloud of computing platforms operating together as server(s) **102**, including Software-as-a-

Service (SaaS) and Platform-as-a-Service (PaaS) functionality. Additionally, the server(s) **102** can include memory **130**.

[0032] Memory **130** can comprise electronic storage that can include non-transitory storage media that electronically stores information. The electronic storage media of electronic storage can include one or both of system storage that can be provided integrally (e.g., substantially non-removable) with server(s) **102** and/or removable storage that can be removably connectable to server(s) **102** via, for example, a port (e.g., a USB port, a firewire port, etc.) or a drive (e.g., a disk drive, etc.). Electronic storage may include one or more of optically readable storage media (e.g., optical disks, etc.), magnetically readable storage media (e.g., magnetic tape, magnetic hard drive, floppy drive, etc.), electrical charge-based storage media (e.g., EEPROM, RAM, etc.), solid-state storage media (e.g., flash drive, etc.), and/or other electronically readable storage media. Electronic storage may include one or more virtual storage resources (e.g., cloud storage, a virtual private network, and/or other virtual storage resources). The electronic storage can include a database, or public or private distributed ledger (e.g., blockchain). Electronic storage can store machine-readable instructions **106**, software algorithms, control logic, data generated by processor(s), data received from server(s), data received from computing platform(s), and/or other data that can enable server(s) to function as described herein. The electronic storage can also include third-party databases accessible via the network **140**.

[0033] Processor(s) **104** can be configured to provide data processing capabilities in server(s) **102**. As such, processor(s) **104** can include one or more of a digital processor, an analog processor, a digital circuit designed to process information, an analog circuit designed to process information, a state machine, and/or other mechanisms for electronically processing information, such as FPGAs or ASICs. The processor(s) **104** can be a single entity or include a plurality of processing units. These processing units can be physically located within the same device, or processor(s) **104** can represent processing functionality of a plurality of devices or software functionality operating alone, or in concert.

[0034] The processor(s) **104** can be configured to execute machine-readable instructions **106** or machine learning modules via software, hardware, firmware, some combination of software, hardware, and/or firmware, and/or other mechanisms for configuring processing capabilities on processor(s) **104**. As used herein, the term “machine-readable instructions” can refer to any component or set of components that perform the functionality attributed to the machine-readable instructions component **106**. This can include one or more physical processor(s) **104** during execution of processor-readable instructions, the processor-readable instructions, circuitry, hardware, storage media, or any other components.

[0035] The server(s) **102** can be configured with machine-readable instructions having one or more functional modules. The machine-readable instructions **106** can be implemented on one or more servers **102**, having one or more processor(s) **104**, with access to memory **130**. The machine-readable instructions **106** can be a single networked node, or a machine cluster, which can include a distributed architecture of a plurality of networked nodes. The machine-readable instructions **106** can include control logic for implementing various functionality, as described in more detail below. The machine-readable instructions **106** can include certain functionality associated with the system **100**. Additionally, the machine-readable instructions **106** can include a smart contract or multi-signature contract that can process, read, and write data to the database, distributed ledger, or blockchain.

[0036] The maintenance assembly **152** can include various maintenance assemblies to perform maintenance. For example, the maintenance assembly **152** can include assemblies such as a computer, GPS, control and display units, workhead assemblies, among other relevant assemblies for performing maintenance.

[0037] FIG. 2 illustrates a schematic view of an automated workflow system **200**, in accordance with one or more exemplary embodiments of the present disclosure. The system **200** can include a



network management system **202**, an asset management system **204**, and a production management system **206**. Although certain exemplary embodiments may be directed to rail assets, the system **200** can be used to plan maintenance for a type of railroad asset, including rails, ballasts, panels, ties, turnouts, facilities, or any suitable asset.

[0038] In one exemplary embodiment, the network management system **202** can include a connectivity module **108**, identification module **110**, status module **112**, and authentication module **114**. The connectivity module **108**, identification module **110**, status module **112**, and authentication module **114** can implement one or more algorithms to connectivity to a network to communicate with a machine in a tie gang, ultimately to facilitate maintenance of a railroad asset and communicate data related to the maintenance performed. The algorithms and their associated thresholds and/or signatures can be programmable to suit a particular railroad asset, application, function, facility, or other requirement. The network management system **202** can be configured to send and receive messages related to an inspection or other suitable activity, to and from the client or server. In another exemplary embodiment, the network management system **202** can generate one or more elements for display on the user device. The elements can provide additional information to the user related to an inspection. For example, alerts can be generated by the network management system **202** and displayed on the client to indicate inspection count, inspection completion, inspection submission, inspection request, or other suitable information. Additionally, system symbols can be displayed on the client to indicate inspection status.

[0039] The connectivity module **108** can establish a network connection between the vehicle and the one or more servers **102**. For example, the connectivity module **108** can execute either hardware or software to wirelessly, or in a wired manner, connect to the network **140**. The connectivity module **108** compares a strength of a network connectivity of the server **102** with a known value to determine the network is accessible. In an example, the connectivity module **108** can ping a known address of the vehicle to determine whether the vehicle is accessible. For example, the connectivity module **108** can store the Internet Protocol (IP) addresses of a plurality of vehicles to perform maintenance and transmit electrical signals through the network **140** to the IP addresses. If the vehicle is accessible based on a response from one or more of the vehicles (e.g., based on responses from the particular IP addresses), the connectivity module **108** can execute the identification module to further determine whether the vehicle is an identified vehicle for performing maintenance on the railway.

[0040] The identification module **110** can identify whether the responses from the vehicles correspond with an identified vehicle for performing maintenance on the railway. For example, the identification module **110** can correlate information from the connectivity module **108** with a workflow queue including a schedule of all the maintenance to be performed on the particular railway. The identification module **110** can compare the information from the responses with the workflow queue to verify the vehicle is the identified vehicle to perform the maintenance.

[0041] The status module **112** can list data stored on the server **102** for a particular user. In another example, the status module **112** can indicate the status of one or entries stored on the client or server for a particular user. For example, an inspection stored on the server **102** can be displayed on a client and labeled with its status (e.g., “in progress,” “completed,” or “to be completed”) on a dashboard page of the client. In another example, the status module **112** can display a notification on the client of a status change or a new requirement (e.g., new or re-inspection, capital plan generation, approval request, change request, etc.).

[0042] The authentication module **114** authenticate a user on a client, such as a mobile phone, laptop, tablet, wearable device, or other suitable device. For example, the authentication module **114** can authenticate a user or the vehicle using a username, password, authentication token, biometric, or other suitable attribute received from the vehicle or user. In an example embodiment, the authentication module **114** can generate an authentication token for a particular user, session, or request. In another example, the authentication module **114** can generate an authentication token

using user data stored in the client. For example, a user can access a client by providing valid credentials via a login page or screen, including a username and password, biometrics, multi-factor authentication, or other suitable credential, such credentials, along with a user's information such as name, username, employee number, etc, can be stored in the client or server. In another example, the authentication module **114** can process at least a portion of the credentials and/or user information to generate an authentication token. For example, the authentication token can be generated as a JSON Web Token (JWT), via dongles or key fobs that can periodically generate a new authentication token in accordance with a known algorithm, using an authenticator app on the client or sent on demand via SMS, by hashing at least a portion of the login credentials, or other suitable methodology. In an example, the authentication token can allow for single sign-on authentication to the server and/or memory from the client.

[0043] In one exemplary embodiment, the asset management system **204** can include an initialization module **116**, data link module **118**, and a geolocation module **120**. The initialization module **116**, data link module **118**, and a geolocation module **120** can implement one or more algorithms to connectivity to a network to communicate with a machine in a tie gang, ultimately to facilitate maintenance of a railroad asset and communicate data related to the maintenance performed. The algorithms and their associated thresholds and/or signatures can be programmable to suit a particular railroad asset, application, function, facility, or other requirement. The asset management system **204** can be configured to send and receive messages related to an inspection or other suitable activity, to and from the client or server. In another exemplary embodiment, the asset management system **204** can generate one or more elements for display on the user device. The elements can provide additional information to the user related to an inspection. For example, alerts can be generated by the asset management system **204** and displayed on the client to indicate inspection count, inspection completion, inspection submission, inspection request, or other suitable information. Additionally, system symbols can be displayed on the client to indicate inspection status.

[0044] In an embodiment, the initialization module **116** can initiate an action. For example, the actions can include asset type selection, create inspection, download plans, search inspections, change settings, or other suitable action. In an example, the initialization module **116** can upload inspections to or download inspections from the server. In an example, the initialization module **116** can initiate an action by calling or instantiating one or more modules on the server, WebUI, or client. In another example, one or more inspections may be transferred to or received from the client via the initialization module **116** over an encrypted network (e.g., the network **140**).

[0045] In one exemplary embodiment, data link module **118** can establish a data link to the vehicle. For example, the data link module **118** can establish the data link using a virtual environment over the network. In another example, the data link module **118** can establish the data link using satellite communications when the vehicle is in remote locations. In an example, the data link module **118** can include a custom protocol arrangement for optimum communication between the vehicle and the server. In an example, the data link module **118** can establish data links with a plurality of vehicles to transmit data to all available vehicles performing maintenance.

[0046] The data link module **118** can identify whether the data link is established based on a value of a signal threshold. For example, the signal threshold can correspond to wireless communication signal strength and be reliant on the vehicle location. When the vehicle is in a remote area of geography, without any cellular reception, or any satellite availability, the signal threshold can be at a minimum. Alternatively, when the vehicle is within an area able to reach cellular signal or satellite availability, the signal threshold can be at a maximum.

[0047] In one exemplary embodiment, the geolocation module **120** can transmit and receive location coordinates of the vehicle. For example, the geolocation module **120** can locate the vehicle based on radio frequency triangulation, trilateration, electromagnetic sensor detection, or from latitude and longitude values, or another suitable geolocation method. In another example, the

geolocation module **120** can locate a plurality of vehicles performing maintenance on a railway. For example, the geolocation module **120** can locate the vehicle based on real-time imaging. In an example, the vehicle can transmit the real-time images and the geolocation module **120** can process the images to compare the images to a known location to identify the location of the vehicle.

[0048] For example, during railway maintenance, a user can begin inspecting a rail segment by beginning at a start point on a first end of the rail segment and capture a series of data points related to the segment. In order to begin logging the data related to an inspection, the user's location must first be determined. In one exemplary embodiment, the user's location can be identified by receiving one or more characteristics of the user's location (e.g., line segment, milepost location, etc.) or by utilizing the GPS functionality of the client. In another exemplary embodiment, once the GPS location (latitude and longitude coordinates) are determined, the geolocation module **120** can determine one or more characteristics of the user's location (e.g., line segment, milepost location, curve-high rail or low rail, etc.). In another exemplary embodiment, the GPS coordinates can determine the line segment and the mileposts by correlating the GPS coordinates with those stored in a geographic information system (GIS) database. For example, a GIS database can include one or more rail segment characteristics associated with a particular latitude and longitude coordinate.

[0049] In one exemplary embodiment, the production management system **206** can include a maintenance tracking module **122** and maintenance analysis module **124**. The maintenance tracking module **122** and maintenance analysis module **124** can implement one or more algorithms to connectivity to a network to communicate with a machine in a tie gang, ultimately to facilitate maintenance of a railroad asset and communicate data related to the maintenance performed. The algorithms and their associated thresholds and/or signatures can be programmable to suit a particular railroad asset, application, function, facility, or other requirement. The network management system **202** can be configured to send and receive messages related to an inspection or other suitable activity, to and from the client or server. In another exemplary embodiment, the network management system **202** can generate one or more elements for display on the user device. The elements can provide additional information to the user related to an inspection. For example, alerts can be generated by the network management system **202** and displayed on the client to indicate inspection count, inspection completion, inspection submission, inspection request, or other suitable information. Additionally, system symbols can be displayed on the client to indicate inspection status.

[0050] The maintenance tracking module **122** can monitor the workflow queue for the maintenance of the railway. For example, the maintenance tracking module **122** can push or pop elements of the workflow queue to either add maintenance requirements or remove maintenance requirements. For example, as the tie gang moves across the railway, the maintenance tracking module **122** can remove the maintenance requirements the tie gang performed. In another example, the maintenance tracking module **122** can assign identifiers to each element of the workflow queue. For example, each of the elements of the workflow queue can include unique tasks directing the tie gang to perform particular tasks to resolve the maintenance for the railway. The maintenance tracking module **122** can generate unique identifiers for each of the tasks to optimize the maintenance process for the tie gang.

[0051] The maintenance analysis module **124** can inspect the tie gang efficiency for performing maintenance on the railway. For example, the maintenance analysis module **124** can compare the efficiency to a known value to determine whether the tie gang is performing within a suitable time frame. In another example, the maintenance analysis module **124** can compare the efficiency with an organizational average to determine whether the tie gang is efficient.

[0052] FIG. 3 illustrates block diagram of a machine in a tie gang **300**, in accordance with one or more exemplary embodiments of the present disclosure. In an embodiment, the machine **300** can be the same as the machine **150** in FIG. 1. The machine **300** can include the maintenance assembly **152**, which includes a computer **302**, positioning assembly **304**, a main control and display

assembly **306**, a workhead assembly **308**, and image capture and analysis assembly **310**. The aforementioned components are operably coupled to transfer information.

[0053] The computer **302** can process instructions and processes to the individual components of the machine **300**. For example, the computer **302** can instruct the positioning assembly **304**, a main control and display assembly **306**, a workhead assembly **308**, and image capture and analysis assembly **310** to execute the respective programs. In another example, the programs being executed can include software executable instructions, firmware that controls hardware, or any combination thereof. In another example, the computer **302** can receive a maintenance operation request for a maintenance item. For example, the computer **302** can receive files including the maintenance operation via Universal Serial Bus (USB). The computer **302** can locate files associated with a maintenance operation request based on an identifier for the files.

[0054] In another example, the computer **302** can receive data for the maintenance operation and organize the data in response to known fields. For example, the computer **302** can organize the data based on maintenance item type, maintenance operation request type, a type of vehicle, or another type of identifier to organize the data. In another example, the computer **302** can append data to existing data sets to add a new maintenance operation while the machine **300** is in the field. In another example, the computer **302** can remove data from the existing data to remove an old maintenance operation.

[0055] The positioning assembly **304** can execute instructions to receive location signals and identify a location of the machine **300**. For example, the positioning assembly **304** can receive electromagnetic signal from a GPS satellite including latitude and longitude data for the positioning assembly **304** to identify the location of the machine **300**. In another example, the positioning assembly **304** can verify a calibration location. For example, the positioning assembly **304** can verify the calibration location based on a comparison between values of the location information with GPS data. The values of the location information can include latitude and longitude values associated with a location of the vehicle. In another example, the positioning assembly **304** can verify the calibration location using RTK-corrected GPS data, radar signal processing, and/or a real-time image. In an example, the positioning assembly **304** can compare the values of the location information with the GPS data including calculating a difference between the values with the GPS data. The difference can indicate whether the vehicle is located at the calibration location and whether the vehicle is calibrated.

[0056] In another example, the positioning assembly **304** can identify the location of the machine **300** using localized means for location detection. For example, the machine **300** can identify the location of the machine **300** based on radar positioning. In an example, the machine **300** can transmit radio frequency energy and receive a response signal. From the response signal, the first locomotive can identify a location. Alternatively, the positioning assembly **304** can identify the location using real-time imaging. For example, the machine **300** can identify the location based on matching a physical location from the real-time images.

[0057] In another example, the positioning assembly **304** can transmit and receive electromagnetic energy. For example, the first locomotive can include a radar to transmit and receive the electromagnetic energy. The radar can receive a response from the electromagnetic energy reflecting off the local environment. From the response, the machine **300** can generate an image of the surrounding environment of the machine **300**. In another example, the positioning assembly **304** can calculate a travel distance from the calibration location to a maintenance location based on the maintenance information. In another example, the positioning assembly **304** can verify a calibration location of a machine based on the maintenance information and the location information

[0058] The main control and display assembly **306** can execute instructions to move the machine **300**. For example, the main control and display assembly **306** can execute instructions to transfer power to an electromechanical locomotive assembly resulting in the machine **300** to move. The

main control and display assembly **306** can operate workheads of the machine **300**. For example, the main control and display assembly **306** can execute any of the modules in the main control system **420** and/or the workhead system **436**. In an example, the main control and display assembly **306** can activate the spike puller module **438** to perform maintenance on the railway. For example, the main control and display assembly **306** can control the workhead modules manually or automatically. For example, the main control and display assembly **306** can be used by an operator to control one of the workhead modules to perform the maintenance on the railway. Alternatively, the main control and display assembly **306** can automatically control the workhead modules to operate.

[0059] In another example, the main control and display assembly **306** can display information regarding the operations for maintenance. For example, the display can include a mobile phone, laptop, tablet, virtual reality system, augmented reality system, heads up display, or another type of display. In an example, the main control and display assembly **306** can show icons that correspond to the various operations and maintenance the machine **300** can perform. For example, the main control and display assembly **306** can illuminate the display as part of a windshield of the machine **300** in an augmented reality manner.

[0060] In another example, the main control and display assembly **306** can position a machine **300** having a GPS receiver identifying the machine **300** location at the calibration location by correlating the machine **300** location with the calibration location. In another example, the main control and display assembly **306** can travel the travel distance from the calibration location to the maintenance location to perform the maintenance operation for a maintenance item at the maintenance location. In another example, the main control and display assembly **306** can travel to the calibration location to calibrate the machine.

[0061] In another example, the main control and display assembly **306** can control movement of the machine **300**. For example, the main control and display assembly **306** can cause the machine **300** to accelerate, decelerate, or stop completely. In another example, the main control and display assembly **306** can be controlled manually or automatically. For example, an operator can control the main control and display assembly **306** to move the machine **300**. Alternatively, the main control and display assembly **306** can be controlled automatically based on various sensor inputs.

[0062] The workhead assembly **308** can execute instructions to perform any of the workhead modules in the workhead system **436**. Just as one example, the workhead assembly **308** can execute a spike puller associated to the spike puller module **438**.

[0063] The image capture and analysis assembly **310** can execute instructions to execute an image capture module. For example, the image capture and analysis assembly **310** can capture an image of the maintenance item. In an example, the image capture and analysis assembly **310** can control a camera of the machine **300**. The image can include an environment of the machine **300**. Alternatively, the image can include the maintenance item.

[0064] In another example, the image capture and analysis assembly **310** can generate an analysis of the maintenance item based on the image. For example, the analysis is based on image analysis techniques. In an example, wherein the image analysis techniques can include a machine learning model. In another example, the image capture and analysis assembly **310** can transmit the image to a central server to generate the analysis. For example, the central server includes a server on a machine in a tie gang. In another example, the central server includes a server in a cloud-based environment.

[0065] In another example, the image capture and analysis assembly **310** can identify the location of the machine **300** based on the image of the environment. The image capture and analysis assembly **310** can correlate the image of the environment with the location information to match the image of the environment to the location of the machine **300**.

[0066] FIG. 4 illustrates a schematic view of a railroad maintenance system **400**, in accordance with one or more exemplary embodiments of the present disclosure. The system **400** can include a

file management system **402**, positioning system **410**, main control system **420**, workhead system **436**, and image capture and analysis system **444**. Although certain exemplary embodiments may be directed to rail assets, the system **400** can be used to plan maintenance for a type of railroad asset, including rails, ballasts, panels, ties, turnouts, facilities, or any suitable asset. In another example, the railroad maintenance system **400** can be executed by any or all of the components of the machine **300** of FIG. 3.

[0067] In one exemplary embodiment, the file management system **402** can include a file retrieval module **404**, data parsing module **406**, and network communication module **408**. The file retrieval module **404**, data parsing module **406**, and network communication module **408** can implement one or more algorithms to connectivity to a network to communicate with a machine in a tie gang, ultimately to facilitate maintenance of a railroad asset and communicate data related to the maintenance performed. The algorithms and their associated thresholds and/or signatures can be programmable to suit a particular railroad asset, application, function, facility, or other requirement. The file management system **402** can be configured to send and receive messages related to an inspection or other suitable activity, to and from the client or server. In another exemplary embodiment, the file management system **402** can generate one or more elements for display on the user device. The elements can provide additional information to the user related to an inspection. For example, alerts can be generated by the file management system **402** and displayed on the client to indicate inspection count, inspection completion, inspection submission, inspection request, or other suitable information. Additionally, system symbols can be displayed on the client to indicate inspection status.

[0068] The file retrieval module **404** can receive a maintenance operation request for a maintenance item. For example, the file retrieval module **404** can receive files including the maintenance operation via Universal Serial Bus (USB). In an example, the maintenance operation request can include a calibration location, a predetermined maintenance information, and location information for a maintenance operation. For example, the calibration location can identify to the first vehicle a location for the first vehicle to calibrate geolocation sensors. In another example, the predetermined maintenance information can include information about what type of maintenance will occur. For example, the predetermined maintenance information can correspond to performing maintenance on a particular railway tie. In an example, the location information for the maintenance operation can identify to the first vehicle a location of where the maintenance operation can occur. The file retrieval module **404** can locate files associated with a maintenance operation request based on an identifier for the files.

[0069] The data parsing module **406** can receive data for the maintenance operation and organize the data in response to known fields. For example, the data parsing module **406** can organize the data based on maintenance item type, maintenance operation request type, a type of vehicle, or another type of identifier to organize the data. In another example, the data parsing module **406** can append data to existing data sets to add a new maintenance operation while the first vehicle is in the field. In another example, the data parsing module **406** can remove data from the existing data to remove an old maintenance operation.

[0070] The network communication module **408** can establish a network connection between the first vehicle and one or more servers. For example, the network communication module **408** can execute either hardware or software to wirelessly, or in a wired manner, connect to the network **140**. The network communication module **408** compares a strength of a network connectivity of the server with a known value to determine the network is accessible. In an example, the network communication module **408** can ping a known address of the vehicle to determine whether the vehicle is accessible. For example, the network communication module **408** can store the IP addresses of a plurality of vehicles to perform maintenance and transmit electrical signals through a network to the IP addresses. If the network is accessible based on a response from (e.g., based on responses from the particular IP addresses), the network communication module **408** can execute

the identification module to further determine whether the vehicle is an identified vehicle for performing maintenance on the railway.

[0071] In one exemplary embodiment, the positioning system **410** can include a global position module **412**, local position module **414**, radar module **416**, and a position verification module **418**. global position module **412**, local position module **414**, radar module **416**, and a position verification module **418** can implement one or more algorithms to connectivity to a network to communicate with a machine in a tie gang, ultimately to facilitate maintenance of a railroad asset and communicate data related to the maintenance performed. The algorithms and their associated thresholds and/or signatures can be programmable to suit a particular railroad asset, application, function, facility, or other requirement. The positioning system **410** can be configured to send and receive messages related to an inspection or other suitable activity, to and from the client or server. In another exemplary embodiment, the positioning system **410** can generate one or more elements for display on the user device. The elements can provide additional information to the user related to an inspection. For example, alerts can be generated by the positioning system **410** and displayed on the client to indicate inspection count, inspection completion, inspection submission, inspection request, or other suitable information. Additionally, system symbols can be displayed on the client to indicate inspection status.

[0072] The global position module **412** can verify the calibration location. For example, the global position module **412** can verify the calibration location based on a comparison between values of the location information with GPS data. The values of the location information can include latitude and longitude values associated with a location of the vehicle. In another example, the global position module **412** can verify the calibration location using real-time kinematic (RTK) corrected GPS data, radar signal processing, and/or a real-time image. In an example, the global position module **412** can compare the values of the location information with the GPS data including calculating a difference between the values with the GPS data. The difference can indicate whether the vehicle is located at the calibration location and whether the vehicle is calibrated.

[0073] The local position module **414** can identify the location of the first vehicle using localized means for location detection. For example, the first vehicle can identify the location of the first vehicle based on radar positioning. In an example, the first vehicle can transmit radio frequency energy and receive a response signal. From the response signal, the first locomotive can identify a location. Alternatively, the local position module **414** can identify the location using real-time imaging. For example, the first vehicle can identify the location based on matching a physical location from the real-time images.

[0074] The radar module **416** can transmit and receive electromagnetic energy. For example, the first locomotive can include a radar to transmit and receive the electromagnetic energy. The radar can receive a response from the electromagnetic energy reflecting off the local environment. From the response, the first vehicle can generate an image of the surrounding.

[0075] The radar module **416** can correspond with an energy threshold to avoid any received spurious signals. For example, the radar module **416** can receive electromagnetic energy from various sources, such as reflections of the transmitted signals off structures in the surrounding environment of the vehicle. For example, the energy threshold can be at a minimum when no electromagnetic energy reflects off any structures around the vehicle. Alternatively, the energy threshold can be at a maximum when all transmitted energy is reflected and returned to the radar module **416**, for example, when an object is directly blocking hardware executed by the radar module **416**.

[0076] The position verification module **418** can calculate a travel distance from the calibration location to a maintenance location based on the maintenance information. In another example, the position verification module **418** can verify a calibration location of a machine based on the maintenance information and the location information.

[0077] In one exemplary embodiment, the main control system **420** can include a hand controller

module **422**, stop module **424**, electric interlock module **426**, display module **428**, movement module **430**, engine control module **432**, and machine identification module **434**. The hand controller module **422**, stop module **424**, electric interlock module **426**, display module **428**, movement module **430**, engine control module **432**, and machine identification module **434** can implement one or more algorithms to connectivity to a network to communicate with a machine in a tie gang, ultimately to facilitate maintenance of a railroad asset and communicate data related to the maintenance performed. The algorithms and their associated thresholds and/or signatures can be programmable to suit a particular railroad asset, application, function, facility, or other requirement. The main control system **420** can be configured to send and receive messages related to an inspection or other suitable activity, to and from the client or server. In another exemplary embodiment, the main control system **420** can generate one or more elements for display on the user device. The elements can provide additional information to the user related to an inspection. For example, alerts can be generated by the main control system **420** and displayed on the client to indicate inspection count, inspection completion, inspection submission, inspection request, or other suitable information. Additionally, system symbols can be displayed on the client to indicate inspection status.

[0078] The hand controller module **422** can operate workheads of the first vehicle. For example, the hand controller module **422** can execute any of the modules in the workhead system **436**. In an example, the hand controller module **422** can activate the spike puller module **438** to perform maintenance on the railway. For example, the hand controller module **422** can control the workhead modules manually or automatically. For example, the hand controller module **422** can be used by an operator to control one of the workhead modules to perform the maintenance on the railway. Alternatively, the hand controller module **422** can automatically control the workhead modules to operate.

[0079] The stop module **424** can cause the first vehicle to cease operation. For example, the stop module **424** can be an emergency switch to cut power from the first vehicle in an emergency. Alternatively, the stop module **424** can be manually executed or automatically executed. In an example, the stop module **424** can manually be executed by an operator in the first vehicle. Alternatively, the stop module **424** can automatically cease the power to the first vehicle when an emergency situation triggers the automatic response.

[0080] The electric interlock module **426** can connect power to various components of the first vehicle. For example, the components can include controllers, manifolds, sensors, and brakes of the first vehicle. In another example, the electric interlock module **426** can include protections from spurious power to the components and control the power to each of the components the electric interlock module **426** is connected.

[0081] The display module **428** can display information regarding the operations for maintenance. For example, the display can include a mobile phone, laptop, tablet, virtual reality system, augmented reality system, heads up display, or another type of display. In an example, the display module **428** can show icons that correspond to the various operations and maintenance the first vehicle can perform. For example, the display module **428** can illuminate the display as part of a windshield of the first vehicle in an augmented reality manner.

[0082] The movement module **430** can position a first vehicle having a GPS receiver identifying the first vehicle location at the calibration location by correlating the first vehicle location with the calibration location. In another example, the movement module **430** can travel the travel distance from the calibration location to the maintenance location to perform the maintenance operation for a maintenance item at the maintenance location. In another example, the movement module **430** can travel to the calibration location to calibrate the machine.

[0083] The movement module **430** can rely upon a movement threshold to follow safety protocols. For example, the movement threshold can allow slack in an accelerator to avoid unwanted movement of the vehicle. The movement threshold can be dependent on the type of machine. For



example, when the machine is a member of the tie gang, the movement threshold can be at a minimum to allow for slight movements of the machine for alignment purposes to perform maintenance. Alternatively, when the machine is a freight locomotive, the movement threshold can be a maximum to incentivize purposeful movement to cause the freight locomotive to begin to travel.

[0084] The engine control module **432** can control movement of the first vehicle. For example, the engine control module **432** can cause the first vehicle to accelerate, decelerate, or stop completely. In another example, the engine control module **432** can be controlled manually or automatically. For example, an operator can control the engine control module **432** to move the first vehicle. Alternatively, the engine control module **432** can be controlled automatically based on various sensor inputs.

[0085] The machine identification module **434** can display engine control and diagnostic information. For example, the machine identification module **434** can show the mechanical characteristics of the engine for maintenance of the first vehicle. The machine identification module **434** can identify diagnostic information regarding the first vehicle.

[0086] In one exemplary embodiment, the workhead system **436** can include a spike puller module **438**, anchor spreader module **440**, and tie kicker module **442**. The spike puller module **438**, anchor spreader module **440**, and tie kicker module **442** can implement one or more algorithms to connectivity to a network to communicate with a machine in a tie gang, ultimately to facilitate maintenance of a railroad asset and communicate data related to the maintenance performed. The algorithms and their associated thresholds and/or signatures can be programmable to suit a particular railroad asset, application, function, facility, or other requirement. The workhead system **436** can be configured to send and receive messages related to an inspection or other suitable activity, to and from the client or server. In another exemplary embodiment, the workhead system **436** can generate one or more elements for display on the user device. The elements can provide additional information to the user related to an inspection. For example, alerts can be generated by the workhead system **436** and displayed on the client to indicate inspection count, inspection completion, inspection submission, inspection request, or other suitable information. Additionally, system symbols can be displayed on the client to indicate inspection status.

[0087] The spike puller module **438** can perform a maintenance operation based on an analysis indicating a spike pulling operation is required. For example, the spike puller module **438** can control a spike puller. The spike puller is a railroad maintenance of way machine designed to remove rail spikes from ties. In another example, the spike puller module **438** can automatically perform the maintenance operation, without operator intervention. In another example, the maintenance item is to receive maintenance when the analysis meets a condition. For example, the condition can include a maintenance score of above or below a maintenance threshold. In an example, the maintenance item is to receive maintenance based on a maintenance indicator, where the maintenance indicator is based on whether the maintenance item already received maintenance. The maintenance item can indicate whether it already received maintenance based on a quality status of the maintenance item. For example, a maintenance item already receiving maintenance can correspond to a high-quality status indicating the maintenance item already received maintenance. When the maintenance item requires maintenance, the maintenance item can have a low-quality status. In another example, the maintenance item is to receive maintenance based on a comparison between the maintenance information and information from the image including railway plate hole characteristics, railway spike patterns, and a distance corresponding to the plate hole characteristics. For example, the maintenance information can include tie marking information and tie grading information. The tie marking information can correspond to indicating whether a particular railroad tie requires maintenance. In an example, the tie grading information can correspond to a grade of the maintenance item, where the grade is a spectrum indicating a relative quality of the maintenance item. In another example, the maintenance item includes a railway tie.

[0088] The anchor spreader module **440** can perform a maintenance operation based on an analysis indicating an anchor spreading operation is required. For example, the anchor spreader module **440** can control an anchor spreader. The anchor spreader is a type of maintenance equipment designed to spread or shape ballast profiles. In another example, the anchor spreader module **440** can automatically perform the maintenance operation, without operator intervention. In another example, the maintenance item is to receive maintenance when the analysis meets a condition. For example, the condition can include a maintenance score of above or below a maintenance threshold. In an example, the maintenance item is to receive maintenance based on a maintenance indicator, where the maintenance indicator is based on whether the maintenance item already received maintenance. The maintenance item can indicate whether it already received maintenance based on a quality status of the maintenance item. For example, a maintenance item already receiving maintenance can correspond to a high-quality status indicating the maintenance item already received maintenance. When the maintenance item requires maintenance, the maintenance item can have a low-quality status. In another example, the maintenance item is to receive maintenance based on a comparison between the maintenance information and information from the image including railway plate hole characteristics, railway spike patterns, and a distance corresponding to the plate hole characteristics. For example, the maintenance information can include tie marking information and tie grading information. The tie marking information can correspond to indicating whether a particular railroad tie requires maintenance. In an example, the tie grading information can correspond to a grade of the maintenance item, where the grade is a spectrum indicating a relative quality of the maintenance item. In another example, the maintenance item includes a railway tie.

[0089] The tie kicker module **442** can perform a maintenance operation based on an analysis indicating a tie kicking operation is required. For example, the tie kicker module **442** can control a tie kicker. The tie kicker is a mechanical system for removing and installing track and switch ties having a clamp for gripping the ties for removal and insertion. In another example, the tie kicker module **442** can automatically perform the maintenance operation, without operator intervention. In another example, the maintenance item is to receive maintenance when the analysis meets a condition. For example, the condition can include a maintenance score of above or below a maintenance threshold. In an example, the maintenance item is to receive maintenance based on a maintenance indicator, where the maintenance indicator is based on whether the maintenance item already received maintenance. The maintenance item can indicate whether it already received maintenance based on a quality status of the maintenance item. For example, a maintenance item already receiving maintenance can correspond to a high-quality status indicating the maintenance item already received maintenance. When the maintenance item requires maintenance, the maintenance item can have a low-quality status. In another example, the maintenance item is to receive maintenance based on a comparison between the maintenance information and information from the image including railway plate hole characteristics, railway spike patterns, and a distance corresponding to the plate hole characteristics. For example, the maintenance information can include tie marking information and tie grading information. The tie marking information can correspond to indicating whether a particular railroad tie requires maintenance. In an example, the tie grading information can correspond to a grade of the maintenance item, where the grade is a spectrum indicating a relative quality of the maintenance item. In another example, the maintenance item includes a railway tie.

[0090] In one exemplary embodiment, the image capture and analysis system **444** can include an image capture module **446**, image analysis module **448**, and visual position module **450**. The image capture module **446**, image analysis module **448**, and visual position module **450** can implement one or more algorithms to connectivity to a network to communicate with a machine in a tie gang, ultimately to facilitate maintenance of a railroad asset and communicate data related to the maintenance performed. The algorithms and their associated thresholds and/or signatures can be

programmable to suit a particular railroad asset, application, function, facility, or other requirement. The image capture and analysis system **444** can be configured to send and receive messages related to an inspection or other suitable activity, to and from the client or server. In another exemplary embodiment, the image capture and analysis system **444** can generate one or more elements for display on the user device. The elements can provide additional information to the user related to an inspection. For example, alerts can be generated by the image capture and analysis system **444** and displayed on the client to indicate inspection count, inspection completion, inspection submission, inspection request, or other suitable information. Additionally, system symbols can be displayed on the client to indicate inspection status.

[0091] The image capture module **446** can capture an image of the maintenance item. For example, the image capture module **446** can control a camera of the first vehicle. The image can include an environment of the first vehicle. Alternatively, the image can include the maintenance item.

[0092] The image analysis module **448** can generate an analysis of the maintenance item based on the image. For example, the analysis is based on image analysis techniques. In an example, wherein the image analysis techniques can include a machine learning model. In another example, the image analysis module **448** can transmit the image to a central server to generate the analysis. For example, the central server includes a server on a machine in a tie gang. In another example, the central server includes a server in a cloud-based environment.

[0093] The visual position module **450** can identify the location of the first vehicle based on the image of the environment. The visual position module **450** can correlate the image of the environment with the location information to match the image of the environment to the location of the first vehicle.

[0094] FIGS. 5A-5B illustrates a flowchart exemplifying railroad asset maintenance control logic **500**, in accordance with one or more exemplary embodiments of the present disclosure. The railroad asset maintenance control logic **500** can be implemented as an algorithm on a server **102**, a machine learning module, a machine **150**, a database, or other suitable system. Additionally, the railroad asset maintenance control logic **500** can implement or incorporate one or more features of the railroad maintenance system **400**, including the file management system **402**, positioning system **410**, main control system **420**, workhead system **436**, and image capture and analysis system **444**. The railroad asset maintenance control logic **500** can be achieved with software, hardware, firmware, an API, a network connection, a network transfer protocol, HTML, DHTML, JavaScript, Dojo, Ruby, Rails, other suitable applications, or a suitable combinations thereof.

[0095] The railroad asset maintenance control logic **500** can leverage the ability of a computer platform to spawn multiple processes and threads by processing data simultaneously. The speed and efficiency of the railroad asset maintenance control logic **500** can be greatly improved by instantiating more than one process to implement a curve-flow rail inspection. However, one skilled in the art of programming will appreciate that use of a single processing thread may also be utilized and is within the scope of the present disclosure.

[0096] In one exemplary embodiment, commands or data can be received via user input generated on a client or server, such as a screen tap, swipe, mouse click, key press, voice command, or other suitable mechanism. In another exemplary embodiment, the inspection commands or data can include inspection data having one or more fields, parameters, characteristics, or metadata, related to an inspection. The control logic **500** then proceeds to step **502**.

[0097] At step **502**, in an embodiment, the control logic **500** can receive a maintenance operation request for a maintenance item, the request having a calibration location, predetermined maintenance information, and location information for a maintenance operation. For example, the maintenance operation request for the maintenance item can include a unique production identifier to track scheduling of a maintenance workflow for a tie gang. The calibration location can include latitude and longitude values for locating the maintenance item. In an example, the calibration location can correspond to RTK-corrected GPS data for precise location determination. In another

example, the calibration location can include image data visualizing an environment around the tie gang for image recognition of the location of the tie gang. In an example, the tie gang can use the latitude and longitude value for travel purposes, either manually or autonomously. The predetermined maintenance information can include a type of the maintenance item, a queue of production identifiers for the tie gang to perform maintenance, among other relevant maintenance information. The control logic **500** proceeds to step **504**.

[0098] At step **504**, in an embodiment, the control logic **500** can position a first vehicle having a GPS receiver identifying the first vehicle location at the calibration location by correlating the first vehicle location with the calibration location. For example, the first vehicle can correspond with any of the machines of the tie gang. The first vehicle can compare the first vehicle location with the calibration location to determine a distance to travel to reach the calibration location. The control logic **500** proceeds to step **506**.

[0099] At step **506**, in an embodiment, the control logic **500** can determine whether the first vehicle location is the same as the calibration location. For example, the control logic **500** can determine whether the first vehicle is located at the calibration location. The first vehicle can compare latitude and longitude values of the first vehicle location with latitude and longitude values of the calibration location. If the calibration locations are the same, the control logic **500** proceeds with step **508**. If the maintenance locations are not the same, the control logic **500** proceeds with step **504**.

[0100] At step **508**, in an embodiment, the control logic **500** can execute motion control for the first vehicle to travel to the calibration location. For example, the control logic **500** can control relevant systems in the railroad maintenance system to cause the first vehicle to travel. In an example, the systems can include the positioning system **410** and the main control system **420**, among other relevant modules. The control logic **500** then proceeds to step **510**.

[0101] At step **510**, in an embodiment, the control logic **500** can determine whether the first vehicle is calibrated. For example, the control logic **500** can calculate whether the first vehicle is located at the calibration location. The control logic **500** can compare latitude and longitude values of the first vehicle location after traveling to the calibration location and determine whether the two locations are the same. When the two locations are the same, the control logic **500** classifies the first vehicle as calibrated. If the first vehicle is calibrated, the control logic **500** proceeds to step **512**. If the first vehicle is not calibrated, the control logic **500** then proceeds to step **504**.

[0102] At step **512**, in an embodiment, the control logic **500** can calculate a travel distance from the calibration location to a maintenance location based on the maintenance information. For example, the control logic **500** can determine a distance the first vehicle is to travel to reach the maintenance location. The first vehicle can compare latitude and longitude values of the calibration location with latitude and longitude values of the maintenance location. The control logic **500** can assign the difference between the calibration location and the maintenance location as the travel distance. The control logic **500** then proceeds to step **514**.

[0103] At step **514**, in an embodiment, the control logic **500** can travel the travel distance from the calibration location to the maintenance location to perform the maintenance operation for a maintenance item at the maintenance location. For example, the control logic **500** can control relevant systems in the railroad maintenance system to cause the first vehicle to travel. In an example, the systems can include the positioning system **410** and the main control system **420**, among other relevant modules. The control logic **500** then proceeds to step **516**.

[0104] At step **516**, in an embodiment, the control logic **500** can identify a maintenance item. For example, the control logic **500** can identify the maintenance item by comparing a current first vehicle location with the maintenance location. When the current first vehicle location is the same as the maintenance location, the control logic **500** can confirm the first vehicle reached the maintenance item. The control logic **500** then proceeds to step **518**.

[0105] At step **518**, in an embodiment, the control logic **500** can determine whether the

maintenance item is to receive maintenance. For example, when the first vehicle arrives at the maintenance location, the control logic **500** can determine whether the maintenance item is to receive maintenance based on matching the maintenance item with information from a production identifier. For example, the control logic **500** can match the production identifier to the maintenance item identifying what type of maintenance is to be performed by the first vehicle. In another example, the maintenance can include various workhead activities, such as spike pulling, anchor spreading, tie kicking, or any other maintenance activity of the tie gang. The control logic **500** then proceeds to step **520**.

[0106] At step **520**, in an embodiment, capture an image of the maintenance item. For example, when the first vehicle reaches the maintenance location, the control logic **500** can capture an image of the maintenance item using an image capture module (e.g., the image capture and analysis system **444** of FIG. **4**). The control logic **500** then proceeds to step **522**.

[0107] At step **522**, in an embodiment, the control logic **500** can generate the analysis of the maintenance item based on the image. The control logic **500** can analyze the image of the maintenance item using an image analysis framework. For example, the image analysis framework can include a machine learning model, trained on data of railroad assets, to classify whether the railroad asset is the maintenance item. The image analysis framework can include an image comparison ability to compare a known railroad asset to the image to determine whether the image includes the maintenance item. In another example, the control logic **500** can transmit the image to a central server to generate an analysis. The control logic **500** then proceeds to step **524**.

[0108] At step **524**, in an embodiment, the control logic **500** can perform a maintenance operation based on the analysis. For example, the maintenance operation can include various workhead activities, such as spike pulling, anchor spreading, tie kicking, or any other maintenance activity of the tie gang. In an example, the control logic **500** can perform the maintenance operation automatically. The control logic **500** then terminates or awaits a new inspection creation request and can repeat the aforementioned steps.

[0109] FIG. **6** illustrates a flowchart exemplifying rail inspection control logic **600**, in accordance with one or more exemplary embodiments of the present disclosure. The rail inspection control logic **600** can be implemented as an algorithm on a server **102**, a machine learning module, a machine **150**, a database, or other suitable system. Additionally, the rail inspection control logic **600** can implement or incorporate one or more features of the railroad maintenance system **400**, including the file management system **402**, positioning system **410**, main control system **420**, workhead system **436**, and image capture and analysis system **444**. The rail inspection control logic **600** can be achieved with software, hardware, firmware, an API, a network connection, a network transfer protocol, HTML, DHTML, JavaScript, Dojo, Ruby, Rails, other suitable applications, or a suitable combinations thereof.

[0110] The rail inspection control logic **600** can leverage the ability of a computer platform to spawn multiple processes and threads by processing data simultaneously. The speed and efficiency of the rail inspection control logic **600** can be greatly improved by instantiating more than one process to implement a tangent-flow rail inspection. However, one skilled in the art of programming will appreciate that use of a single processing thread may also be utilized and is within the scope of the present disclosure.

[0111] The rail inspection control logic **600** of the present embodiment begins at step **602**, where, in an embodiment, the control logic **600** can receive a location signal. For example, the location signal can correspond to received electromagnetic energy (e.g., from satellite communications, radar signal processing, real-time image processing, etc.). The control logic **600** can include latitude and longitude values for locating the maintenance item. In an example, the location signal can correspond to RTK-corrected GPS data for precise location determination. In another example, the location data can include image data visualizing an environment around the tie gang for image recognition of the location of the tie gang. In an example, the tie gang can use the latitude and

longitude value for travel purposes, either manually or autonomously. The predetermined maintenance information can include a type of the maintenance item, a queue of production identifiers for the tie gang to perform maintenance, among other relevant maintenance information. The control logic **600** then proceeds to step **604**.

[0112] At step **604**, in an embodiment, the control logic **600** can compare the location signal with location information from a file to calibrate a location of a machine. For example, the control logic **600** can calculate the value difference between the location signal with the location information to determine an offset for calibration purposes. In an example, the control logic **600** can compensate the location information based on the location signal. For example, the control logic **600** can update the location information based on the location signal. The control logic **600** then proceeds to step **606**.

[0113] At step **606**, in an embodiment, the control logic **600** can determine whether the location signal and the location information are the same. For example, the control logic **600** can calculate the value difference between the location signal with the location information to determine whether the locations are the same. If the locations are the same, the control logic **600** then proceeds to step **610**. If the locations are different, the control logic **600** then proceeds to step **608**.

[0114] At step **608**, in an embodiment, the control logic **600** can calibrate a location of the machine. In an example, the control logic **600** can compensate the location information based on the location signal. For example, the control logic **600** can update the location information based on the location signal. In an example, the control logic **600** can either substitute the location information for values from the location signal or can calculate an offset between the location information and the values from the location signal and calibrate the location information accordingly. The control logic **600** then proceeds to step **604**.

[0115] At step **610**, in an embodiment, the control logic **600** can calculate a distance of a path from the location of the machine to a maintenance location. When the control logic **600** calibrates the location information, the control logic **600** can compare the location information with the maintenance location to determine the distance for the machine to travel. In an example, the control logic **600** can include preset railway information of the railway between the location information and the maintenance location. For example, the preset railway information can include curves lengthening the distance as compared to a direct route between the location information and the maintenance location. The control logic **600** proceeds to step **612**.

[0116] At step **612**, in an embodiment, the control logic **600** can identifying an edge of a track along the path based on sensor information. For example, the control logic **600** can capture an image of the railway as the sensor information and identify edges of tracks of the railway. In another example, the control logic **600** can transmit and receive electromagnetic energy to determine the edges of the track (e.g., using a forward-looking radar, short wave radar, among other electromagnetic components). In an example, the sensor information corresponds to physical characteristics resulting from the electromagnetic energy. When identifying the edges of the track, the control logic **600** can identify any obstacles ahead of the machine on the railway. The control logic **600** then proceeds to step **614**.

[0117] At step **614**, in an embodiment, the control logic can travel to the maintenance location. For example, the control logic **600** can control relevant systems in the railroad maintenance system to cause the first vehicle to travel. In an example, the systems can include the positioning system **410** and the main control system **420**, among other relevant modules. The control logic **600** then terminates or awaits a new inspection creation request and can repeat the aforementioned steps.

[0118] FIG. 7 illustrates a perspective view of a plurality of machines disposed on railroad tracks, generally referenced as **700**, in accordance with one or more exemplary embodiments of the present disclosure. For example, a machine can be a spike puller **702**, anchor spreader **706**, tie kicker **710**, locomotive, or any machine related to railway maintenance or operations. In another embodiment, a tie gang can include one or more of each type of machine, or none of some types of

machines, based upon the type of maintenance to be performed. For example, the tie gang can include a first spike puller **702**, a second spike puller **704**, a first anchor spreader **706**, a second anchor spreader **708**, a tie kicker **710**, a locomotive, or any machine related to railway maintenance or operations. In another embodiment, the machines can be spaced a predetermined distance for safety. For example, the machines can maintain a minimum fifty-foot safety distance. In another embodiment, the safety distance can vary based up-on the machine type. In another embodiment, the lead vehicle (e.g., spike puller **702**) can include a digital line scan and gauge camera. The embodiments disclosed herein can be operable in a tie gang similar to that shown in FIG. 7, as well as with more machines, fewer machines, and/or different machines.

[0119] The present disclosure achieves at least the following advantages: [0120] 1. improves organization and accessibility of asset inspections and maintenance, among other technological improvements; [0121] 2. increases the efficiency of asset inspections and inspectors via improved systems that can add and modify prompts based on responses; [0122] 3. eliminates the need to paint ties; [0123] 4. reduces the hazard exposure of personnel walking track; [0124] 5. provides costs savings for paint and personnel; [0125] 6. provides a unified platform for facilitating railroad asset inspections; and [0126] 7. provides centralized and accessible data models and criteria for assets throughout the railroad infrastructure, enabling faster and more-informed decision making. [0127] Persons skilled in the art will readily understand that advantages and objectives described above would not be possible without the particular combination of computer hardware and other structural components and mechanisms assembled in this inventive system and described herein. Additionally, the algorithms, methods, and processes disclosed herein improve and transform any general-purpose computer or processor disclosed in this specification and drawings into a special purpose computer programmed to perform the disclosed algorithms, methods, and processes to achieve the aforementioned functionality, advantages, and objectives. It will be further understood that a variety of programming tools, known to persons skilled in the art, are available for generating and implementing the features and operations described in the foregoing. Moreover, the particular choice of programming tool(s) may be governed by the specific objectives and constraints placed on the implementation selected for realizing the concepts set forth herein and in the appended claims.

[0128] The description in this patent document should not be read as implying that any particular element, step, or function can be an essential or critical element that must be included in the claim scope. Also, none of the claims can be intended to invoke 35 U.S.C. § 112 (f) with respect to any of the appended claims or claim elements unless the exact words “means for” or “step for” are explicitly used in the particular claim, followed by a participle phrase identifying a function. Use of terms such as (but not limited to) “mechanism,” “module,” “device,” “unit,” “component,” “element,” “member,” “apparatus,” “machine,” “system,” “processor,” “processing device,” or “controller” within a claim can be understood and intended to refer to structures known to those skilled in the relevant art, as further modified or enhanced by the features of the claims themselves, and can be not intended to invoke 35 U.S.C. § 112 (f). Particularly, the term machine is not intended to invoke 35 U.S.C. § 112 (f), as disclosed herein. Even under the broadest reasonable interpretation, in light of this paragraph of this specification, the claims are not intended to invoke 35 U.S.C. § 112 (f) absent the specific language described above.

[0129] The disclosure may be embodied in other specific forms without departing from the spirit or essential characteristics thereof. For example, each of the new structures described herein, may be modified to suit particular local variations or requirements while retaining their basic configurations or structural relationships with each other or while performing the same or similar functions described herein. The present embodiments are therefore to be considered in all respects as illustrative and not restrictive. Accordingly, the scope of the inventions can be established by the appended claims rather than by the foregoing description. All changes which come within the meaning and range of equivalency of the claims are therefore intended to be embraced therein.

Further, the individual elements of the claims are not well-understood, routine, or conventional. Instead, the claims are directed to the unconventional inventive concept described in the specification.

## Claims

- 1.** A system for electronic tie marking (ETM), comprising: a memory including railway information for ETM; and a processor operably coupled to the memory and capable of executing machine-readable instructions to perform program steps, the program steps comprising: receiving a maintenance operation request for a maintenance item, the request having a calibration location, predetermined maintenance information, and location information for a maintenance operation; positioning a first vehicle having a GPS receiver identifying the first vehicle location at the calibration location by correlating the first vehicle location with the calibration location; calculating a travel distance from the calibration location to a maintenance location based on the maintenance information; and traveling the travel distance from the calibration location to the maintenance location to perform the maintenance operation for a maintenance item at the maintenance location.
- 2.** The system of claim 1, wherein the program steps further comprise: verifying a calibration location of a machine based on the maintenance information and the location information; and traveling to the calibration location to calibrate the machine.
- 3.** The system of claim 1, wherein the file is via a Universal Serial Bus (USB).
- 4.** The system of claim 1, wherein the calibration location is verified based on a comparison between the location information with real-time kinematic (RTK) corrected global position system (GPS) data, radar signal processing, and a real-time image.
- 5.** The system of claim 1, wherein the maintenance item is to receive maintenance when a condition is satisfied.
- 6.** The system of claim 1, wherein the maintenance item is to receive maintenance based on a maintenance indicator, wherein the maintenance indicator is based on whether the maintenance item already received maintenance.
- 7.** The system of claim 1, wherein the maintenance item is to receive maintenance based on a comparison between the maintenance information and information from an image including railway plate hole characteristics, railway spike patterns, and a distance corresponding to the plate hole characteristics.
- 8.** The system of claim 1, wherein the maintenance information includes tie marking information and tie grading information.
- 9.** The system of claim 1, wherein a maintenance action is based on at least one workhead actions such as spike pulling, anchor spreading, and tie kicking, wherein the maintenance item includes a railway tie.
- 10.** The system of claim 1, the program steps further comprising an analysis based on image analysis techniques, wherein the image analysis techniques include a machine learning model.
- 11.** A method for performing maintenance using electronic tie marking (ETM), comprising: receiving a maintenance operation request for a maintenance item, the request having a calibration location, predetermined maintenance information, and location information for a maintenance operation; positioning a first vehicle having a GPS receiver identifying the first vehicle location at the calibration location by correlating the first vehicle location with the calibration location; calculating a travel distance from the calibration location to a maintenance location based on the maintenance information; and traveling the travel distance from the calibration location to the maintenance location to perform the maintenance operation for a maintenance item at the maintenance location.
- 12.** The method of claim 11, wherein the method further comprises: verifying a calibration location of a machine based on the maintenance information and the location information; and traveling to



the calibration location to calibrate the machine.

**13.** The method of claim 11, wherein the file is via a Universal Serial Bus (USB).

**14.** The method of claim 11, wherein the calibration location is verified based on a comparison between the location information with real-time kinematic (RTK) corrected global position system (GPS) data, radar signal processing, and a real-time image.

**15.** The method of claim 11, wherein the maintenance item is to receive maintenance when a condition is satisfied.

**16.** The method of claim 11, wherein the maintenance item is to receive maintenance based on a maintenance indicator, wherein the maintenance indicator is based on whether the maintenance item already received maintenance.

**17.** The method of claim 11, wherein the maintenance item is to receive maintenance based on a comparison between the maintenance information and information from an image including railway plate hole characteristics, railway spike patterns, and a distance corresponding to the plate hole characteristics.

**18.** The method of claim 11, wherein the maintenance information includes tie marking information and tie grading information.

**19.** The method of claim 11, wherein a maintenance action is based on at least one workhead actions such as spike pulling, anchor spreading, and tie kicking, wherein the maintenance item includes a railway tie.

**20.** The method of claim 11, further comprising an analysis based on image analysis techniques, wherein the image analysis techniques include a machine learning model.

---