

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12392515
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Blanton; Norman J.

Refrigerant leak management systems

Abstract

A refrigerant leak management system includes a controller is configured to receive a signal indicative of a refrigerant pressure within a refrigerant circuit and determine whether the refrigerant pressure is indicative of a refrigerant leak in the refrigerant circuit. In response to determining that the refrigerant pressure is indicative of the refrigerant leak, the controller is configured to activate a fan configured to motivate air proximate the refrigerant circuit.

Inventors: Blanton; Norman J. (Norman, OK)

Applicant: Johnson Controls Technology Company (Auburn Hills, MI)

Family ID: 1000008764924

Assignee: JOHNSON CONTROLS TECHNOLOGY COMPANY (Auburn Hills, MI)

Appl. No.: 18/124409

Filed: March 21, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230221026 A1	Jul. 13, 2023

Related U.S. Application Data

continuation parent-doc US 17195025 20210308 US 11609009 child-doc US 18124409
continuation parent-doc US 16912295 20200625 US 11365897 20220621 child-doc US 17195025
continuation parent-doc US 16182287 20181106 US 10731884 20200804 child-doc US 16912295
us-provisional-application US 62752181 20181029

Publication Classification

Int. Cl.: G05D15/00 (20060101); F24F11/36 (20180101); F24F11/77 (20180101); F24F140/12 (20180101)

U.S. Cl.:

CPC F24F11/36 (20180101); F24F11/77 (20180101); F24F2140/12 (20180101)

Field of Classification Search

CPC: F24F (11/36); F24F (11/77); F24F (2140/12)

USPC: 165/285

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8844301	12/2013	Yamashita et al.	N/A	N/A
9302565	12/2015	Johnston et al.	N/A	N/A
9857113	12/2017	Morimoto et al.	N/A	N/A
9933205	12/2017	Hatomura et al.	N/A	N/A
10731884	12/2019	Blanton	N/A	F24F 11/36
11365897	12/2021	Blanton	N/A	F24F 11/77
2008/0264086	12/2007	Liu	N/A	N/A
2015/0282643	12/2014	Lee et al.	N/A	N/A
2017/0284718	12/2016	Suzuki et al.	N/A	N/A
2019/0242632	12/2018	Sakae et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3315880	12/2017	EP	N/A
5730238	12/2014	JP	N/A
20030085763	12/2002	KR	N/A

Primary Examiner: Hwu; Davis D

Attorney, Agent or Firm: Fletcher Yoder, PC

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/195,025, entitled “REFRIGERANT LEAK MANAGEMENT SYSTEMS,” filed Mar. 8, 2021, which is a continuation of U.S. patent application Ser. No. 16/912,295, entitled “REFRIGERANT LEAK MANAGEMENT SYSTEMS,” filed Jun. 25, 2020, which is a continuation of U.S. patent application Ser. No. 16/182,287, entitled “REFRIGERANT LEAK MANAGEMENT SYSTEMS,” filed Nov. 6, 2018, which claims priority to and the benefit of U.S. Provisional Application No. 62/752,181, entitled “REFRIGERANT LEAK MANAGEMENT SYSTEMS,” filed Oct. 29, 2018, each of which is hereby incorporated by reference in its entirety for all purposes.

BACKGROUND

(1) The present disclosure relates generally to heating, ventilation, and/or air conditioning (HVAC) systems, and more particularly to refrigerant leak detection and management for HVAC systems.

(2) Residential, light commercial, commercial, and industrial HVAC systems are used to control temperatures and air quality in residences and buildings. Generally, the HVAC systems may circulate a refrigerant through a closed refrigerant circuit between an evaporator, where the refrigerant absorbs heat, and a condenser, where the refrigerant releases heat. The refrigerant flowing within the refrigerant circuit is generally formulated to undergo phase changes within the normal operating temperatures and pressures of the system so that quantities of heat can be exchanged by virtue of the latent heat of vaporization of the refrigerant. As such, the refrigerant flowing within an HVAC system travels through multiple conduits and components of the refrigerant circuit. Inasmuch as refrigerant leaks compromise system performance or result in increased costs, it is accordingly desirable to provide detection and response systems and methods for the HVAC system to reliably detect and respond to any refrigerant leaks of the HVAC system.

SUMMARY

(3) In one embodiment of the present disclosure, a refrigerant leak management system includes a controller is configured to receive a signal indicative of a refrigerant pressure within a refrigerant circuit and determine whether the refrigerant pressure is indicative of a refrigerant leak in the refrigerant circuit. In response to determining that the refrigerant pressure is indicative of the refrigerant leak, the controller is configured to activate a fan configured to motivate air proximate the refrigerant circuit.

(4) In another embodiment of the present disclosure, a heating, ventilation, and/or air conditioning (HVAC) system includes a leak detection device configured to be operably coupled to a refrigerant circuit of the HVAC system and configured to provide management signals in response to a change in a pressure of a refrigerant within the refrigerant circuit. The HVAC system also includes a fan configured to be operably coupled to the leak detection device and configured to motivate air proximate the refrigerant circuit. The leak detection device is configured to provide the management signals to control the fan to operate continuously in response to the change in the pressure.

(5) In a further embodiment of the present disclosure, a heating, ventilation, and/or air conditioning (HVAC) system includes a refrigerant circuit configured to circulate a refrigerant therein and a controller. The HVAC system also includes a leak detection device communicatively coupled to the controller and fluidly coupled to the refrigerant circuit to sense a pressure of the refrigerant therein. Independent of compressor operation, the leak detection device or the controller is configured to activate a fan configured to provide air to an interior space configured to be climate managed by the HVAC system in response to the pressure being below a predefined threshold pressure.

(6) Other features and advantages of the present application will be apparent from the following, more detailed description of the embodiments, taken in conjunction with the accompanying drawings which illustrate, by way of example, the principles of the application.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a perspective view of an embodiment of a commercial or industrial HVAC system, in accordance with an aspect of the present disclosure;

(2) FIG. 2 is a perspective cutaway view of an embodiment of a packaged unit of an HVAC system, in accordance with an aspect of the present disclosure;

(3) FIG. 3 is a perspective cutaway view of an embodiment of a split system of an HVAC system, in accordance with an aspect of the present disclosure;

- (4) FIG. 4 is a schematic diagram of an embodiment of a vapor compression system of an HVAC system, in accordance with an aspect of the present disclosure;
- (5) FIG. 5 is a schematic diagram of an embodiment of a leak management system of an HVAC system, in accordance with an aspect of the present disclosure;
- (6) FIG. 6 is a schematic diagram of another embodiment of the leak management system, in accordance with an aspect of the present disclosure;
- (7) FIG. 7 is a schematic diagram of an embodiment of a pressure switch of a leak detection and management (LDM) device, in accordance with an aspect of the present disclosure;
- (8) FIG. 8 is a flow diagram representing an embodiment of a process of operating the leak management system of FIG. 5, in accordance with an aspect of the present disclosure; and
- (9) FIG. 9 is a flow diagram representing an embodiment of a process of operating the LDM device of FIG. 7, in accordance with an aspect of the present disclosure.

DETAILED DESCRIPTION

(10) The present disclosure is directed to refrigerant leak detection and management for HVAC systems. As discussed above, to condition the interior space of a building, an HVAC system generally includes refrigerant flowing within a refrigerant circuit. However, the refrigerant may inadvertently leak from a flow path of the refrigerant circuit due to wear or degradation of components or imperfect joints or connections within the refrigerant circuit at some point after installation. Under certain conditions, leaking refrigerant vaporizes and distributes outward from a source of the leak, which can result in refrigerant-containing air accumulating, for example, within a casing of an HVAC unit, within the ductwork of the building, and/or within the conditioned interior space of the building. Additionally, traditional sensors that detect leaked refrigerant vapor within the conditioned interior space may be complicated or consumable devices, such as those that lose sensitivity over time, and which are only able to sense leaked refrigerant that is within a threshold distance of the traditional sensors. As such, multiple, strategically-placed sensors may be employed to monitor the conditioned interior space. Accordingly, the present techniques enable the HVAC system to reliably detect whether refrigerant is leaking from a refrigerant circuit, as well as manage any leaked refrigerant.

(11) With the foregoing in mind, present embodiments are directed to a leak management system of an HVAC system. The leak management system includes a leak detection (LD) device or leak detection and management (LDM) device that is fluidly coupled to the refrigerant circuit to monitor an operating parameter of the refrigerant therein, and to activate in response to the operating parameter being indicative of a refrigerant leak. For example, the LDM device may include any suitable quantities of pressure switches and pressure transducers that monitor a refrigerant pressure of the refrigerant and activate in response to detecting a drop in the refrigerant pressure below a predefined threshold pressure. In response to the operating parameter being indicative of a refrigerant leak, the LDM device may send signals to operate a supply fan that provides air to interior space. As such, the leak management system causes circulation of the air within the conditioned interior space to dilute any leaked or pooled refrigerant and/or prevent pooling of refrigerant.

(12) Moreover, the leak management system of certain embodiments activates auxiliary fans of an HVAC system, further improving circulation and dilution of any leaked refrigerant within the conditioned interior space. In some embodiments having a low pressure switch as part of the LDM device, the low pressure switch is able to directly activate the supply fan in response to a low pressure. In some embodiments having a pressure transducer as part of the LDM device, the pressure transducer is communicatively coupled to a suitable controller, such as an HVAC controller, to provide signals to the controller indicative of the refrigerant leak. Then, the controller can modify operation of the HVAC system in response to these signals. It should be noted that, in other embodiments, the LDM device may monitor a temperature, a flow rate, a fill level, or other parameter of the refrigerant circuit in addition or in alternative to monitoring pressure. Moreover,

multiple pressure transducers and/or pressure switches are included in the LDM device of some embodiments to enable more granular detection of changes in refrigerant pressure and corresponding escalated control actions. In this manner, the disclosed techniques enable detection of refrigerant leaks within the HVAC system, and enable response via any combination of suitable control actions to address and manage the leaked refrigerant.

(13) Turning now to the drawings, FIG. 1 illustrates an embodiment of a heating, ventilation, and/or air conditioning (HVAC) system for environmental management that may employ one or more HVAC units. As used herein, an HVAC system includes any number of components configured to enable regulation of parameters related to climate characteristics, such as temperature, humidity, air flow, pressure, air quality, and so forth. For example, an “HVAC system” as used herein is defined as conventionally understood and as further described herein. Components or parts of an “HVAC system” may include, but are not limited to, all, some of, or individual parts such as a heat exchanger, a heater, an air flow control device, such as a fan, a sensor configured to detect a climate characteristic or operating parameter, a filter, a control device configured to regulate operation of an HVAC system component, a component configured to enable regulation of climate characteristics, or a combination thereof. An “HVAC system” is a system configured to provide such functions as heating, cooling, ventilation, dehumidification, pressurization, refrigeration, filtration, or any combination thereof. The embodiments described herein may be utilized in a variety of applications to control climate characteristics, such as residential, commercial, industrial, transportation, or other applications where climate control is desired.

(14) In the illustrated embodiment, a building 10 is air conditioned by a system that includes an HVAC unit 12. The building 10 may be a commercial structure or a residential structure. As shown, the HVAC unit 12 is disposed on the roof of the building 10; however, the HVAC unit 12 may be located in other equipment rooms or areas adjacent the building 10. The HVAC unit 12 may be a single package unit containing other equipment, such as a blower, integrated air handler, and/or auxiliary heating unit. In other embodiments, the HVAC unit 12 may be part of a split HVAC system, such as the system shown in FIG. 3, which includes an outdoor HVAC unit 58 and an indoor HVAC unit 56.

(15) The HVAC unit 12 is an air cooled device that implements a refrigeration cycle to provide conditioned air to the building 10. Specifically, the HVAC unit 12 may include one or more heat exchangers across which an air flow is passed to condition the air flow before the air flow is supplied to the building. In the illustrated embodiment, the HVAC unit 12 is a rooftop unit (RTU) that conditions a supply air stream, such as environmental air and/or a return air flow from the building 10. After the HVAC unit 12 conditions the air, the air is supplied to the building 10 via ductwork 14 extending throughout the building 10 from the HVAC unit 12. For example, the ductwork 14 may extend to various individual floors or other sections of the building 10. In certain embodiments, the HVAC unit 12 may be a heat pump that provides both heating and cooling to the building with one refrigeration circuit configured to operate in different modes. In other embodiments, the HVAC unit 12 may include one or more refrigeration circuits for cooling an air stream and a furnace for heating the air stream.

(16) A control device 16, one type of which may be a thermostat, may be used to designate the temperature of the conditioned air. The control device 16 also may be used to control the flow of air through the ductwork 14. For example, the control device 16 may be used to regulate operation of one or more components of the HVAC unit 12 or other components, such as dampers and fans, within the building 10 that may control flow of air through and/or from the ductwork 14. In some embodiments, other devices may be included in the system, such as pressure and/or temperature transducers or switches that sense the temperatures and pressures of the supply air, return air, and so forth. Moreover, the control device 16 may include computer systems that are integrated with or separate from other building control or monitoring systems, and even systems that are remote from the building 10.

(17) FIG. 2 is a perspective view of an embodiment of the HVAC unit 12. In the illustrated embodiment, the HVAC unit 12 is a single package unit that may include one or more independent refrigeration circuits and components that are tested, charged, wired, piped, and ready for installation. The HVAC unit 12 may provide a variety of heating and/or cooling functions, such as cooling only, heating only, cooling with electric heat, cooling with dehumidification, cooling with gas heat, or cooling with a heat pump. As described above, the HVAC unit 12 may directly cool and/or heat an air stream provided to the building 10 to condition a space in the building 10.

(18) As shown in the illustrated embodiment of FIG. 2, a cabinet 24 encloses the HVAC unit 12 and provides structural support and protection to the internal components from environmental and other contaminants. In some embodiments, the cabinet 24 may be constructed of galvanized steel and insulated with aluminum foil faced insulation. Rails 26 may be joined to the bottom perimeter of the cabinet 24 and provide a foundation for the HVAC unit 12. In certain embodiments, the rails 26 may provide access for a forklift and/or overhead rigging to facilitate installation and/or removal of the HVAC unit 12. In some embodiments, the rails 26 may fit into “curbs” on the roof to enable the HVAC unit 12 to provide air to the ductwork 14 from the bottom of the HVAC unit 12 while blocking elements such as rain from leaking into the building 10.

(19) The HVAC unit 12 includes heat exchangers 28 and 30 in fluid communication with one or more refrigeration circuits. Tubes within the heat exchangers 28 and 30 may circulate refrigerant, such as R-410A, through the heat exchangers 28 and 30. The tubes may be of various types, such as multichannel tubes, conventional copper or aluminum tubing, and so forth. Together, the heat exchangers 28 and 30 may implement a thermal cycle in which the refrigerant undergoes phase changes and/or temperature changes as it flows through the heat exchangers 28 and 30 to produce heated and/or cooled air. For example, the heat exchanger 28 may function as a condenser where heat is released from the refrigerant to ambient air, and the heat exchanger 30 may function as an evaporator where the refrigerant absorbs heat to cool an air stream. In other embodiments, the HVAC unit 12 may operate in a heat pump mode where the roles of the heat exchangers 28 and 30 may be reversed. That is, the heat exchanger 28 may function as an evaporator and the heat exchanger 30 may function as a condenser. In further embodiments, the HVAC unit 12 may include a furnace for heating the air stream that is supplied to the building 10. While the illustrated embodiment of FIG. 2 shows the HVAC unit 12 having two of the heat exchangers 28 and 30, in other embodiments, the HVAC unit 12 may include one heat exchanger or more than two heat exchangers.

(20) The heat exchanger 30 is located within a compartment 31 that separates the heat exchanger 30 from the heat exchanger 28. Fans 32 draw air from the environment through the heat exchanger 28. Air may be heated and/or cooled as the air flows through the heat exchanger 28 before being released back to the environment surrounding the rooftop unit 12. A blower assembly 34, powered by a motor 36, draws air through the heat exchanger 30 to heat or cool the air. The heated or cooled air may be directed to the building 10 by the ductwork 14, which may be connected to the HVAC unit 12. Before flowing through the heat exchanger 30, the conditioned air flows through one or more filters 38 that may remove particulates and contaminants from the air. In certain embodiments, the filters 38 may be disposed on the air intake side of the heat exchanger 30 to prevent contaminants from contacting the heat exchanger 30.

(21) The HVAC unit 12 also may include other equipment for implementing the thermal cycle. Compressors 42 increase the pressure and temperature of the refrigerant before the refrigerant enters the heat exchanger 28. The compressors 42 may be any suitable type of compressors, such as scroll compressors, rotary compressors, screw compressors, or reciprocating compressors. In some embodiments, the compressors 42 may include a pair of hermetic direct drive compressors arranged in a dual stage configuration 44. However, in other embodiments, any number of the compressors 42 may be provided to achieve various stages of heating and/or cooling. As may be appreciated, additional equipment and devices may be included in the HVAC unit 12, such as a solid-core filter

drier, a drain pan, a disconnect switch, an economizer, pressure switches, phase monitors, and humidity sensors, among other things.

(22) The HVAC unit **12** may receive power through a terminal block **46**. For example, a high voltage power source may be connected to the terminal block **46** to power the equipment. The operation of the HVAC unit **12** may be governed or regulated by a control board **48**. The control board **48** may include control circuitry connected to a thermostat, sensors, and alarms. One or more of these components may be referred to herein separately or collectively as the control device **16**. The control circuitry may be configured to control operation of the equipment, provide alarms, and monitor safety switches. Wiring **49** may connect the control board **48** and the terminal block **46** to the equipment of the HVAC unit **12**.

(23) FIG. **3** illustrates a residential heating and cooling system **50**, also in accordance with present techniques. The residential heating and cooling system **50** may provide heated and cooled air to a residential structure, as well as provide outside air for ventilation and provide improved indoor air quality (IAQ) through devices such as ultraviolet lights and air filters. In the illustrated embodiment, the residential heating and cooling system **50** is a split HVAC system. In general, a residence **52** conditioned by a split HVAC system may include refrigerant conduits **54** that operatively couple the indoor unit **56** to the outdoor unit **58**. The indoor unit **56** may be positioned in a utility room, an attic, a basement, and so forth. The outdoor unit **58** is typically situated adjacent to a side of residence **52** and is covered by a shroud to protect the system components and to prevent leaves and other debris or contaminants from entering the unit. The refrigerant conduits **54** transfer refrigerant between the indoor unit **56** and the outdoor unit **58**, typically transferring primarily liquid refrigerant in one direction and primarily vaporized refrigerant in an opposite direction.

(24) When the system shown in FIG. **3** is operating as an air conditioner, a heat exchanger **60** in the outdoor unit **58** serves as a condenser for re-condensing vaporized refrigerant flowing from the indoor unit **56** to the outdoor unit **58** via one of the refrigerant conduits **54**. In these applications, a heat exchanger **62** of the indoor unit functions as an evaporator. Specifically, the heat exchanger **62** receives liquid refrigerant, which may be expanded by an expansion device, and evaporates the refrigerant before returning it to the outdoor unit **58**.

(25) The outdoor unit **58** draws environmental air through the heat exchanger **60** using a fan **64** and expels the air above the outdoor unit **58**. When operating as an air conditioner, the air is heated by the heat exchanger **60** within the outdoor unit **58** and exits the unit at a temperature higher than it entered. The indoor unit **56** includes a blower or fan **66** that directs air through or across the indoor heat exchanger **62**, where the air is cooled when the system is operating in air conditioning mode. Thereafter, the air is passed through ductwork **68** that directs the air to the residence **52**. The overall system operates to maintain a desired temperature as set by a system controller. When the temperature sensed inside the residence **52** is higher than the set point on the thermostat, or a set point plus a small amount, the residential heating and cooling system **50** may become operative to refrigerate additional air for circulation through the residence **52**. When the temperature reaches the set point, or a set point minus a small amount, the residential heating and cooling system **50** may stop the refrigeration cycle temporarily.

(26) The residential heating and cooling system **50** may also operate as a heat pump. When operating as a heat pump, the roles of heat exchangers **60** and **62** are reversed. That is, the heat exchanger **60** of the outdoor unit **58** will serve as an evaporator to evaporate refrigerant and thereby cool air entering the outdoor unit **58** as the air passes over outdoor the heat exchanger **60**. The indoor heat exchanger **62** will receive a stream of air blown over it and will heat the air by condensing the refrigerant.

(27) In some embodiments, the indoor unit **56** may include a furnace system **70**. For example, the indoor unit **56** may include the furnace system **70** when the residential heating and cooling system **50** is not configured to operate as a heat pump. The furnace system **70** may include a burner

assembly and heat exchanger, among other components, inside the indoor unit **56**. Fuel is provided to the burner assembly of the furnace **70** where it is mixed with air and combusted to form combustion products. The combustion products may pass through tubes or piping in a heat exchanger, separate from heat exchanger **62**, such that air directed by the blower **66** passes over the tubes or pipes and extracts heat from the combustion products. The heated air may then be routed from the furnace system **70** to the ductwork **68** for heating the residence **52**.

(28) FIG. **4** is an embodiment of a vapor compression system **72** that can be used in any of the systems described above. The vapor compression system **72** may circulate a refrigerant through a circuit starting with a compressor **74**. The circuit may also include a condenser **76**, an expansion valve(s) or device(s) **78**, and an evaporator **80**. The vapor compression system **72** may further include a control panel **82** that has an analog to digital (A/D) converter **84**, a microprocessor **86**, a non-volatile memory **88**, and/or an interface board **90**. The control panel **82** and its components may function to regulate operation of the vapor compression system **72** based on feedback from an operator, from sensors of the vapor compression system **72** that detect operating conditions, and so forth.

(29) In some embodiments, the vapor compression system **72** may use one or more of a variable speed drive (VSDs) **92**, a motor **94**, the compressor **74**, the condenser **76**, the expansion valve or device **78**, and/or the evaporator **80**. The motor **94** may drive the compressor **74** and may be powered by the variable speed drive (VSD) **92**. The VSD **92** receives alternating current (AC) power having a particular fixed line voltage and fixed line frequency from an AC power source, and provides power having a variable voltage and frequency to the motor **94**. In other embodiments, the motor **94** may be powered directly from an AC or direct current (DC) power source. The motor **94** may include any type of electric motor that can be powered by a VSD or directly from an AC or DC power source, such as a switched reluctance motor, an induction motor, an electronically commutated permanent magnet motor, or another suitable motor.

(30) The compressor **74** compresses a refrigerant vapor and delivers the vapor to the condenser **76** through a discharge passage. In some embodiments, the compressor **74** may be a centrifugal compressor. The refrigerant vapor delivered by the compressor **74** to the condenser **76** may transfer heat to a fluid passing across the condenser **76**, such as ambient or environmental air **96**. The refrigerant vapor may condense to a refrigerant liquid in the condenser **76** as a result of thermal heat transfer with the environmental air **96**. The liquid refrigerant from the condenser **76** may flow through the expansion device **78** to the evaporator **80**.

(31) The liquid refrigerant delivered to the evaporator **80** may absorb heat from another air stream, such as a supply air stream **98** provided to the building **10** or the residence **52**. For example, the supply air stream **98** may include ambient or environmental air, return air from a building, or a combination of the two. The liquid refrigerant in the evaporator **80** may undergo a phase change from the liquid refrigerant to a refrigerant vapor. In this manner, the evaporator **80** may reduce the temperature of the supply air stream **98** via thermal heat transfer with the refrigerant. Thereafter, the vapor refrigerant exits the evaporator **80** and returns to the compressor **74** by a suction line to complete the cycle.

(32) In some embodiments, the vapor compression system **72** may further include a reheat coil in addition to the evaporator **80**. For example, the reheat coil may be positioned downstream of the evaporator relative to the supply air stream **98** and may reheat the supply air stream **98** when the supply air stream **98** is overcooled to remove humidity from the supply air stream **98** before the supply air stream **98** is directed to the building **10** or the residence **52**.

(33) It should be appreciated that any of the features described herein may be incorporated with the HVAC unit **12**, the residential heating and cooling system **50**, or other HVAC systems.

Additionally, while the features disclosed herein are described in the context of embodiments that directly heat and cool a supply air stream provided to a building or other load, embodiments of the present disclosure may be applicable to other HVAC systems as well. For example, the features

described herein may be applied to mechanical cooling systems, free cooling systems, chiller systems, or other heat pump or refrigeration applications.

(34) FIG. 5 is a schematic diagram of an HVAC system **100** having a leak management system **102** for detecting and controlling leaked refrigerant within the HVAC system **100** and/or a building, such as the building **10** discussed above. As shown, the HVAC system **100** includes a refrigerant circuit **104** having conduits **106** that fluidly couple the evaporator **80**, the compressor **74**, the condenser **76**, and the expansion device **78**. A refrigerant **110** flows between HVAC components of the refrigerant circuit **104**, undergoing phase changes that enable the HVAC system **100** to condition or climate manage an interior space **114** of the building **10**. The refrigerant **110** may be any suitable refrigerant, such as R32, R1234ze, R1234yf, R-454A, R-454C, R-455A, R-447A, R-452B, R-454B, and the like. Each of the evaporator **80**, the compressor **74**, the condenser **76**, and the expansion device **78** may correspond with any suitable HVAC devices discussed above with reference to FIGS. 1-4. Moreover, the evaporator **80**, the compressor **74**, the condenser **76**, and the expansion device **78** may be part of any suitable residential refrigeration system, commercial refrigeration system, split refrigeration system, and/or single unit refrigeration system. As will be discussed in more detail below, the leak management system **102** is configured to detect a leak of the refrigerant **110** from the refrigerant circuit **104**. In response to detection of a leak, the leak management system **102** is further enabled to provide suitable control signals or take suitable corrective actions to dilute or mitigate the leak of the refrigerant **110**.

(35) Looking first to the components of the HVAC system **100** that operate to condition an interior space **114** of the building **10**, for the illustrated embodiment, the compressor **74** and the condenser **76** are disposed within an outdoor unit **120** or outdoor HVAC unit of the HVAC system **100**, and the expansion device **78** and the evaporator **80** are disposed within an indoor unit **122** or indoor HVAC unit of the HVAC system **100**. As discussed above, the compressor **74** may be driven by the motor **94**, which is driven by the VSD **92**. The VSD **92** regulates a magnitude of voltage and/or current supplied to the motor **94** from a power source **126**, such as an AC or DC power source, to modify an operational speed of the compressor **74**. During operation, the compressor **74** pressurizes a low pressure gas flow of the refrigerant **110** to yield a high pressure gas flow. The compressor **74** therefore provides energy to drive the refrigerant **110** along a refrigerant flow direction **130** through the refrigerant circuit **104** between the compressor **74**, the condenser **76**, the expansion device **78**, and the evaporator **80**. Moreover, an outdoor fan **134** of the HVAC system **100** is disposed adjacent to the condenser **76** to direct a flow of outside air **136** across the condenser **76**, thereby enabling the high pressure gas flow of the refrigerant **110** traveling therethrough to release thermal energy to the outside air **136** and condense into a high pressure liquid refrigerant flow.

(36) From the condenser **76**, the high pressure liquid refrigerant **110** travels further along the conduits **106** to the indoor unit **122**, where it passes through the expansion device **78** to expand the refrigerant **110** into a low pressure liquid flow. The refrigerant **110** then travels through the evaporator **80** to absorb thermal energy and vaporize into a low pressure gas flow, thereby completing the cycle. In the present embodiment, an economizer fan **140** is fluidly coupled to a damper opening **142** formed in a wall of the indoor unit **122**. The economizer fan **140** may be activated to draw another flow of outside air from an external environment **144**, through the damper opening **142**, and into the indoor unit **122** as a source of fresh or ventilation air. In some embodiments, the damper opening **142** may include actuatable slats that may be adjusted to modify an amount of fresh, outside air drawn into the indoor unit **122**. The indoor unit **122** further includes a supply fan **150** or indoor fan disposed adjacent to the evaporator **80** to direct a flow of indoor supply air **152** across the evaporator **80**. As used herein, the supply fan **150** is therefore configured to move air proximate, or within inches or feet from, the refrigerant circuit **104**. The indoor supply air **152** may include the outside air **136** drawn through the damper opening **142**, as well as return air drawn through a return air duct **154** from the interior space **114**, in some embodiments. When the compressor **74** is activated, active coils of the evaporator **80** cool and/or remove dissolved

moisture, such as humidity, from the flow of indoor supply air **152** by enabling heat transfer between the refrigerant **110** and the flow of indoor supply air **152**. When the compressor **74** is not activated and the supply fan **150** is operating, the supply fan **150** draws the unconditioned flow of indoor supply air **152** across inactive coils of the evaporator **80**.

(37) Whether the indoor supply air **152** is conditioned or unconditioned, the supply fan **150** directs the indoor supply air **152** along one or multiple ducts **156**, such as the ductwork **14** illustrated in FIG. **1**, to provide the supply air **152** to the interior space **114** of the building **10**. In the present embodiment, a duct fan **160** is disposed within the duct **156** to further facilitate movement of the indoor supply air **152** into the interior space **114**. The duct fan **160** may be any suitable fan capable of pushing or drawing the indoor supply air **152** into the interior space **114**, such as a register boost fan, an inline duct fan, and so forth. In other embodiments, any suitable quantity of duct fans **160** may be provided in any suitable locations, such as within the ducts **156**, within a threshold distance of the ducts **156**, within a wall, ceiling, or floor of the interior space **114**, and so forth. The indoor supply air **152** provided by the supply fan **150** generally circulates within the interior space **114**, stirring room air **162** therein as well as moving a portion of the room air **162** out of the interior space **114** through imperfect seals between windows and doors, through the return air duct **154**, and so forth. Moreover, a ceiling fan **166** is disposed within the interior space **114** of the present embodiment to provide further recirculation and movement of the room air **162** within the interior space **114**. As noted herein, the ceiling fan **166**, the duct fan **160**, and the economizer fan **140** are each auxiliary fans that complement operation of the supply fan **150** to provide air dilution and mixing to the room air **162** within the interior space **114**. In certain embodiments, the supply fan **150**, the ceiling fan **166**, the duct fan **160**, and/or the economizer fan **140** are free of activation sources and/or are driven by motors that are free of activation sources, such as sparks. Moreover, the ceiling fan **166**, the duct fan **160**, and/or the economizer fan **140** may also be considered proximate the refrigerant circuit **104** in certain embodiments.

(38) With the above understanding of the HVAC components, as noted herein and during normal operation, the HVAC system **100** of the present embodiment operates in one of an on-cycle, a vent-cycle, or an off-cycle. The on-cycle of the HVAC system **100** actively conditions the interior space **114** by conditioning the indoor supply air **152** via heat transfer with the refrigerant **110** within the refrigerant circuit **104** and providing the indoor supply air **152** to the interior space **114**. That is, during the on-cycle, the compressor **74** is operating and the refrigerant **110** is flowing within the refrigerant circuit **104**. During the vent-cycle, the supply fan **150** is activated, while the compressor **74** is deactivated. Operation in the vent-cycle thus directs the indoor supply air **152** along the ducts **156** and into the interior space **114** to provide ventilation and recirculation of air within the interior space **114**, without providing active conditioning to the indoor supply air **152**. Moreover, in the off-cycle, both the compressor **74** and the supply fan **150** are deactivated, and the interior space **114** is not actively conditioned.

(39) Under normal operating conditions, a target amount of the refrigerant **110** is present within the refrigerant circuit **104** to enable proper operation of the HVAC system **100**. Because the refrigerant circuit **104** is generally a pressurized, closed system in which the refrigerant **110** is desirably retained, the target amount of the refrigerant **110** includes a refrigerant pressure that is within a threshold range from a target refrigerant pressure. Under certain conditions, the refrigerant circuit **104** may develop an opening through which the refrigerant **110** may inadvertently flow or leak from the refrigerant circuit **104**, causing the refrigerant pressure to fall beneath or deviate from the target refrigerant pressure. As presently recognized herein, monitoring a source of the refrigerant **110** via the leak management system **102** to monitor the refrigerant pressure, instead of or in addition to monitoring the interior space **114**, enables more rapid detection of refrigerant leaks with a reduced dependence on complicated, insensitive, unreliable, and/or expendable refrigerant concentration sensors within the interior space **114**.

(40) Accordingly, to enable detection of a leak of the refrigerant **110** from the refrigerant circuit

104, the embodiment of the leak management system **102** illustrated in FIG. **5** includes a leak detection and management (LDM) device **178**, which includes a pressure switch **180** or pressure multi-switch, in the illustrated embodiment. As noted herein, the LDM device **178** may be one of multiple suitable embodiments of a leak detection (LD) device, such as one having one or multiple signal-sending or management components. In some embodiments, a LD device that sends signals indicative of refrigerant pressure, which are subsequently utilized for management via other components of the leak management system **102**, may be considered a LDM device. The pressure switch **180** of the LDM device **178** illustrated in FIG. **5** is fluidly coupled to the refrigerant circuit **104**, such as a portion of the conduits **106** at a suction side **182** of the compressor **74**. As used herein, the suction side **182** of the compressor **74** is downstream of the evaporator **80** relative to the refrigerant flow direction **130** of the refrigerant **110** and upstream of the compressor **74** relative to the refrigerant flow direction **130**. In certain embodiments, the LDM device **178** of the leak management system **102** may include multiple pressure switches **180** fluidly coupled to other portions of the refrigerant circuit **104**. For example, in an embodiment, the LDM device **178** may include a second pressure switch communicatively coupled to the evaporator **80** and a third pressure switch communicatively coupled to the condenser **76**, which each may operate similarly to or different from the pressure switch **180**. However, to illustrate the effective and straightforward operation thereof, the present discussion of the LDM device **178** will focus on operation of the embodiment having the single pressure switch **180**. Further embodiments of the LDM device **178** with additional pressure-activated devices will be introduced below, with reference to FIG. **6**.

(41) In other embodiments, the pressure switch **180** of the LDM device **178** may be replaced or accompanied by any other pressure-activated device or hydraulic pressure sensing instrument. Indeed, as discussed below with reference to FIG. **6**, any suitable number of pressure transducers may be used in place of or in addition to the pressure switch. In other embodiments, the LDM device **178** of the leak management system **102** may, additionally or alternatively, include other sensors suitable for detecting or enabling detecting of an amount, such as a mass or a volume, of the refrigerant **110** within the refrigerant circuit **104**, or any other suitable operating parameter indicative of the amount of the refrigerant **110**. For example, other embodiments of the LDM device **178** may include pressure sensors, temperature sensors, level sensors, acoustic sensors, flowrate sensors, and so forth. Moreover, as used herein, the term “sensor” may include any suitable instrument capable of acquiring feedback through direct or indirect observation indicators, such as feedback acquired from monitoring other features or components of the HVAC system **100**.

(42) Indeed, the LDM device **178** of the present embodiment is capable of monitoring a refrigerant pressure of the refrigerant **110** within the refrigerant circuit **104** to detect whether a refrigerant leak has occurred. For example and as discussed herein, the pressure switch **180** of the LDM device **178** actuates in response to a refrigerant pressure dropping below a predefined threshold pressure, which is indicative of a refrigerant leak. In some embodiments, the predefined threshold pressure may be set as or slightly above an ambient pressure outside the refrigerant circuit **104**, such that a refrigerant pressure below the predefined threshold pressure indicates the refrigerant circuit **104** has equalized with an ambient environment in which the refrigerant circuit **104** is disposed. In some embodiments, the predefined threshold pressure is set as a pressure that corresponds to 80%, 70%, 60%, 50%, 40%, 30%, 20%, 10%, or less of the target refrigerant pressure of the refrigerant circuit **104**. The leak management system **102** may be operated in various modes, including an active response mode to monitor for refrigerant leaks. The leak management system **102** may operate in active response mode during all operations of the HVAC system **100**, such as while the HVAC system **100** is operating in the on-cycle, the vent-cycle, and the off-cycle.

(43) In response to detecting a refrigerant leak of sufficient volume or magnitude, the leak management system **102** switches to a leak management mode or a controller-override mode to mitigate the refrigerant leak. In the present embodiment, the LDM device **178** operating in leak management mode activates the supply fan **150** to mitigate pooling of leaked refrigerant **110** within

the interior space **114**. That is, the pressure switch **180** selectively activates the supply fan **150** to direct the indoor supply air **152** into the interior space **114** when the refrigerant pressure within the conduit **106** falls beneath the predefined threshold pressure, thereby providing the indoor supply air **152** to the interior space **114**. More particularly, when the refrigerant pressure falls beneath the predefined threshold pressure, the pressure switch **180** of the present embodiment provides a supply fan signal or management signal, such as an electrical current flowing between a controller **190** and the supply fan **150**, and thus, activates the supply fan **150**. As such, by activating the supply fan **150** that is proximate the refrigerant circuit **104**, or any other suitable proximate auxiliary fans, it is recognized herein that refrigerant leaks from portions of the refrigerant circuit **104** to which the supply fan **150** is proximate may be more effectively diluted.

(44) In the present embodiment, the pressure switch **180** of the LDM device **178** is also able to simultaneously block, interrupt, or override a compressor signal, such as an electrical current flowing between the controller **190** and the VSD **92** discussed above, to deactivate or prevent activation of the compressor **74**. That is, upon detection of a refrigerant pressure indicative of a potential leak, the LDM device **178** of certain embodiments sends management signals that override normal operation of the compressor **74** to deactivate the compressor **74**. It may be appreciated that, in certain embodiments, the supply fan signal and/or the compressor signal are electrical signals or management signals that respectively directly power the supply fan **150**, the VSD **92**, the motor **94**, and/or the compressor **74**. In other embodiments, the supply fan **150**, the VSD **92**, the motor **94**, and/or the compressor **74** receive a separate supply of electrical power, and the supply fan signals and the compressor signals are data or instruction signals that trigger respective activation and operation of these components.

(45) Further details regarding an example embodiment of the pressure switch **180** are discussed with reference to FIG. 7 below. For example, the illustrated pressure switch **180** of FIG. 5 includes a sensing portion **206** having a piston **208** disposed within a chamber that is fluidly coupled to a portion of the conduits **106**. The piston **208** is configured to move longitudinally within the chamber to move one or multiple switching elements based on the refrigerant pressure. The sensing portion **206** may be calibrated, for example, using a spring element disposed above the piston **208**, such that a magnitude of the predefined threshold pressure may be adjusted. In other embodiments, the pressure switch **180** may include any other suitable hydraulic pressure sensing instrument or pressure switch component that may be configured to move when the refrigerant pressure within the conduit **106** falls below the predefined threshold pressure.

(46) As such, the leak management system **102** having the LDM device **178** with the pressure switch **180** is configured to detect and mitigate leaks, without reliance on control decisions from the controller **190** or sensors to monitor the interior space **114**. Specifically, in response to a detected leak of the refrigerant **110**, the pressure switch **180** may initiate or provide any suitable instructions or management signals that control the supply fan **150** to dilute or dissipate the leaked refrigerant within the interior space **114**. In some embodiments, the controller **190** is omitted or not a component of the leak management system **102**. In these embodiments, the pressure switch **180** may also be directly coupled to other components of the HVAC system **100** to perform additional control actions. The additional control actions of certain embodiments include activation of one or multiple additional response devices, such as an alarm, the economizer fan **140**, the duct fan **160**, the ceiling fan **166**, the outdoor fan **134**, and so forth. The pressure switch **180** may activate the supply fan **150** and/or perform the additional control actions for a predefined threshold time, until reset or deactivated by a technician, and so forth.

(47) In some embodiments, the controller **190** is communicatively coupled to the pressure switch **180** and performs the control actions introduced above in response to detection of a refrigerant leak. In these embodiments, signals provided to the controller **190** by the LDM device **178** may be considered indications. Such embodiments may be advantageous to enable the leak management system **102** to monitor the refrigerant pressure over time, to reduce adjustments for retrofitting the

leak management system **102** into existing HVAC systems, to coordinate timing of operations of the leak management system **102**, and so forth. For example, as illustrated, the pressure switch **180** is communicatively coupled to the controller **190**, which is the HVAC controller that governs operation of the entire HVAC system **100** in addition to, or in lieu of, the control panel **82**. For example, the controller **190** is operatively coupled to the VSD **92**, the outdoor fan **134**, the economizer fan **140**, the supply fan **150**, the duct fan **160**, and the ceiling fan **166** in the present embodiment by any suitable control transfer devices, such as wires, cables, wireless communication devices, and the like. Moreover, the controller **190** can be any device employing a general purpose or an application-specific processor **220**, both of which may generally include memory **222** or suitable memory circuitry for storing instructions and/or data. However, in certain embodiments, the controller **190** may be a separate controller for controlling the leak management system **102** that is communicatively coupled to exchange data and/or instructions with an HVAC controller or another suitable master controller.

(48) The processor **220** of the controller **190** illustrated in FIG. 5 may include one or more processing devices, and the memory **222** may include one or more tangible, non-transitory, machine-readable media collectively storing instructions executable by the processor **220** to control the leak management system **102** and/or the HVAC system **100**. The processor **220** provides control signals to operate the leak management system **102** and the HVAC system **100** to perform the control actions disclosed herein. More specifically, as discussed below, the controller **190** receives input signals from various components of the HVAC system **100** and outputs control signals to control and communicate with various components in the HVAC system **100**. The controller **190** may provide suitable control signals to control the flowrates, motor speeds, and valve positions, among other parameters, of the HVAC system **100**.

(49) Although the controller **190** is described as having the processor **220** and the memory **222**, it should be noted that the controller **190** may include or be communicatively coupled to a number of other computer system components to enable the controller **190** to control the operations of the HVAC system **100** and the related components. For example, the controller **190** may include a communication component **224** that enables the controller **190** to communicate with other computing systems and electronic devices, such as alarm systems. The controller **190** may also include an input/output component that enables the controller **190** to interface with users via a graphical user interface or the like. In addition, the communication between the controller **190** and other components of the HVAC system **100** may be via a wireless connection, such as a connection through BLUETOOTH® Low Energy, ZIGBEE®, WIFI®, or may be a wired connection, such as a connection through Ethernet. In some embodiments, the controller **190** may include a distributed control system (DCS), a computer-based workstation, a laptop, a smartphone, a tablet, a personal computer, a human-machine interface, or the like. Additionally, the embodiments disclosed herein may be at least partially embodied using hardware implementations. For example, logic elements of the controller **190** may include a field-programmable gate array (FPGA) or other specific circuitry.

(50) In some embodiments in which the controller **190** is part of the leak management system **102**, and in contrast to embodiments in which the LDM device **178** operates by sending instructions without interacting with the controller **190**, the controller **190** operates in an active response mode to receive input signals from the pressure switch **180** indicative of the refrigerant pressure within the refrigerant circuit **104**. For example, the illustrated controller **190** may receive data indicating whether the pressure switch **180** is in a first position, in which the pressure switch **180** enables normal operation of the VSD **92** and the supply fan **150**, or a second position, in which the pressure switch **180** blocks operation of the VSD **92** and activates the supply fan **150**. In response to determining that the pressure switch **180** is in the second position, the controller **190** may determine that a refrigerant leak is present or is likely to be present, and may thus switch the leak management system **102** to leak management mode to perform any desired additional control

actions. Moreover, in some embodiments, the controller **190** may determine that a refrigerant leak has occurred from a non-communicating embodiment of the pressure switch **180**. For example, the controller **190** may determine that the pressure switch **180** is opened or actuated in response to instructing the VSD **92** to operate, while also sensing that power to the VSD **92** has been interrupted by the pressure switch **180**.

(51) In other embodiments in which the controller **190** is part of the leak management system **102**, the controller **190** performs the aforementioned comparison of the refrigerant pressure to the predefined threshold pressure. That is, the controller **190** receives data indicative of the refrigerant pressure and compares the refrigerant pressure to the predefined threshold pressure discussed above. However, in contrast to being set by positioning physical components of the pressure switch **180**, such as a spring, the threshold used by the controller **190** may be any suitable user-set, technician-set, or distributor-set value that is stored within the memory **222** of controller **190**, either before or after the controller **190** is placed into operation within the HVAC system **100**.

(52) In certain embodiments, the controller **190** adjusts the predefined threshold pressure to which the refrigerant pressure is compared based on an operating parameter of the HVAC system **100**. For example, the controller **190** may use a lower predefined threshold pressure during on-cycle operation of the HVAC system **100** in which the compressor **74** is activated. In some of these embodiments, the predefined threshold pressure may be adjusted based on the current operating speed of the compressor **74** or a velocity or flowrate of the refrigerant **110** measured by a flowrate sensor. Indeed, it is presently recognized that, because flowing, pressurized refrigerant generally has a lower pressure than a similar pressured refrigerant that is not flowing, adaption or adjustment of the predefined threshold pressure based on an operating condition of the refrigerant **110** may provide more rapid or accurate detection of refrigerant leaks. In some embodiments, the controller **190** may instead wait until on-cycle operation of the HVAC system **100** is concluded and thereafter determine the refrigerant pressure based on signals from the pressure switch **180** during the off-cycle of the HVAC system **100**.

(53) FIG. **6** is a schematic diagram of an embodiment of the leak management system **102** in which the LDM device **178** includes multiple pressure-activated devices **250** to monitor the refrigerant circuit **104** for refrigerant leaks therefrom. In addition to the pressure switch **180** discussed above, the LDM device **178** includes pressure transducers **252** fluidly coupled to the refrigerant circuit **104**. For example, the pressure-activated devices **250** of the illustrated embodiment include a first pressure transducer **252A** fluidly coupled to an interior of the conduit **106** at the suction side **182** of the compressor **74** and a second pressure transducer **252B** fluidly coupled to an interior of the evaporator **80**. The pressure transducers **252** include a sensing portion **256** fluidly coupled to the refrigerant circuit **104** to sense the refrigerant pressure therein, as well as a communication component **258** that is wirelessly communicatively coupled to the controller **190**. In other embodiments, the pressure transducers **252** may be physically coupled to the controller **190** by any other control transfer devices. The pressure transducers **252** may therefore provide signals indicative of the refrigerant pressure to the controller **190** at any suitable rate, such as at a regular interval, upon sensing a change in the refrigerant pressure, and so forth. In other embodiments, the LDM device **178** may include one or multiple pressure transducers **252** while lacking pressure switches **180**.

(54) As recognized herein, use of the pressure transducers **252** within the LDM device **178** enables the controller **190** to receive additional information and perform more complex control actions than embodiments of the leak management system **102** having the one pressure switch **180** and lacking pressure transducers **252**. As discussed in more detail with reference to FIG. **5**, during normal operation of the HVAC system **100** when a refrigerant leak is not present, the refrigerant **110** has a refrigerant pressure that is within or above the predefined threshold pressure. During the normal operation, the pressure transducers **252** therefore provide signals indicative of the refrigerant pressure to the controller **190**, which determines that a refrigerant leak is not present and continues

normal operation of the HVAC system **100** to condition the interior space **114** to desired conditions. In some embodiments, the pressure transducers **252** only provide signals in response to a leak condition. Under conditions in which the pressure transducers **252** transmit signals indicative of a refrigerant leak, such as a refrigerant pressure below the predefined threshold pressure, the controller **190** determines that a refrigerant leak is occurring or has occurred, and the leak management system **102** changes its operation from active response mode to leak management mode. Indeed, as discussed above, the controller **190** activates the supply fan **150** to direct the indoor supply air **152** into the interior space **114**.

(55) In certain embodiments, the controller **190** performs additional or escalated control actions in response to determining that the refrigerant pressure is beneath a secondary predefined threshold pressure, lower than the predefined threshold pressure. The predefined threshold pressure discussed above may be referred to as a primary predefined threshold pressure in these embodiments. In some of these embodiments, the secondary predefined threshold pressure may be selected to correspond to a refrigerant pressure indicative of a majority or a significant portion of the refrigerant **110** having leaked from the refrigerant circuit **104**. As such, to address the additional amount of the refrigerant **110** that has leaked from the refrigerant circuit **104**, the escalated control actions of certain embodiments include activating one or multiple of the economizer fan **140**, the duct fan **160**, the ceiling fan **166**, and so forth. Further, the escalated control actions of certain embodiments includes deactivating the compressor **74**, such that the HVAC system **100** is either moved to or confined to off-cycle operations that do not actively condition the indoor supply air **152** provided to the interior space **114**. Accordingly, the refrigerant **110** is not further distributed from the refrigerant circuit **104** by operation of the compressor **74**, and the HVAC components are protected from wear that may otherwise occur during operation with insufficient levels of refrigerant **110**. In this manner, additional refrigerant leakage from the refrigerant circuit **104** is also mitigated. It is to be understood that the controller **190** may perform each of these escalated control actions as regular control actions in some embodiments, such that the actions are performed in response to determining that the refrigerant pressure is below the primary predefined refrigerant threshold.

(56) Moreover, the controller **190** of certain embodiments coordinates operation of the pressure transducers **252** with the pressure switch **180**, which is operatively coupled to the controller **190**. As such, the leak management system **102** may distribute or duplicate any suitable operations between the pressure switch **180**, the pressure transducers **252**, and the controller **190**. For example, the pressure switch **180** of the present embodiment may be responsible for deactivating the compressor **74** and activating the supply fan **150** and the duct fan **160**, while the controller **190** may be responsible for activating the economizer fan **140**, activating the ceiling fan **166**, transmitting alerts to a user interface or computing device, and so forth.

(57) FIG. 7 is a schematic diagram of an embodiment of the pressure switch **180** of the LDM device **178** having multiple switch portions **280**. For example, in the illustrated embodiment, the pressure switch **180** includes a supply fan switch portion **280A**, one or more than one auxiliary fan switch portions **280B**, and a compressor switch portion **280C**. Generally, the switch portions **280** control whether certain components of the HVAC system **100**, such as the supply fan **150**, ceiling fans **166**, the duct fan **160**, the economizer fan **140**, and/or the compressor **74**, are able to continue receiving control signals from the controller **190**, or whether these components instead receive an override control signal via the pressure switch **180** in response to a low refrigerant pressure condition within the HVAC system **100**. As such, in certain embodiments, the pressure switch **180** is responsive to a refrigerant leak condition to operate as a physical override or interrupt device that is configured to operate or override control of certain components of the HVAC system **100**. It may be appreciated that, in other embodiments, the LDM device **178** may instead be implemented as multiple, independent switching devices that collectively operate to provide the disclosed physical override or interrupt device functionality.

(58) For the embodiment illustrated in FIG. 7, to manage these control signals, the switch portions

280 include switching elements **282** or management components, such as switching elements **282A**, **282B**, **282C**, that are operatively coupled to corresponding output contacts **284**, such as output contacts **284A**, **284B**, **284C**, and are moveable between one or multiple corresponding input contacts **286**, such as input contacts **286A**, **286B**, **286C**, **286D**, **286E**. It is to be understood that components are operatively coupled in any suitable manner to provide any suitable control signals including communication and/or power signals that enable the corresponding components to perform their intended operations. For example, the switching elements **282** may be moveable by the piston **208** of the sensing portion **206** or multiple pistons in response to pressure fluctuations of the refrigerant **110** within the refrigerant circuit **104**, as illustrated in FIGS. **5** and **6**. For example, the piston **208** of certain embodiments is disposed within a chamber that is fluidly coupled to a portion of the conduits **106**. The piston **208** is then able to move longitudinally along direction **290** within the chamber in response to dropping refrigerant pressure. As such, the switching elements **282** move relative to the input contacts **286** based on the drop in refrigerant pressure, as indicated in FIG. **7**. Thus, should the refrigerant pressure within a portion of the HVAC system **100** fall beneath a respective predefined threshold pressure, the piston **208** moves the switching elements **282** to respective leak response orientations or positions. Indeed, the illustrated embodiments of the switching elements **282** move with the piston **208** in the direction **290** as the refrigerant pressure drops. In other embodiments, any suitable number of any suitable actuating and/or switching components may be employed.

(59) For example, in the illustrated embodiment, the supply fan switch portion **280A** includes output contact **284A** that is coupled to controller input contact **286A** by switching element **282A** at normal refrigerant pressures. When in the illustrated closed configuration, the controller **190** is capable of providing control signals to the supply fan **150** through the supply fan switch portion **280A**. The supply fan switch portion **280A** also includes override input contact **286B** that, when coupled to the output contact **284A**, interrupts control of the supply fan **150** by the controller **190** and instead instructs the supply fan **150** to operate at high or maximum speed, regardless of any control signals provided by the controller **190**. In response to the refrigerant pressure falling beneath a specified predefined pressure threshold, which results in the switching element **282A** being shifted in the direction **290**, the switching element **282A** is moved to a leak management configuration, wherein the output contact **284A** and the override input contact **286B** are electrically and operatively coupled. Thus, the pressure switch **180** can override the controller **190** and reflexively activate the supply fan **150** or provide management signals to instruct the supply fan **150** to continuously operate at a maximum capacity to mitigate the accumulation of refrigerant vapor as a result of the sensed refrigerant leak.

(60) Similarly, the auxiliary fan switch portion **280B** includes output contact **284B** that is selectively coupled to controller input contact **286C** or override input contact **286D** by switching element **282B** based on the refrigerant pressure. As indicated by the exponential N, the pressure switch **180** of certain embodiments includes multiple auxiliary fan switch portions **280B**, such as one for each of the auxiliary fans discussed above. In other embodiments, more than one of the aforementioned fans may be collectively controlled by one auxiliary fan switch portion **280B**. Moreover, for the illustrated embodiment, a distance **294** between the controller input contact **286C** and the override input contact **286D**, which may represent a first switching element travel distance, is longer than a distance **296** between the controller input contact **286A** and the override input contact **286B** of the supply fan switch portion **280A**, which may represent a second switching element travel distance. As such, the auxiliary fans coupled to the output contact **284B** are activated by the pressure switch **180** at a lower predefined refrigerant pressure threshold than the predefined refrigerant pressure threshold of the supply fan switch portion **280A**. As such, it is presently recognized that the disclosed pressure switch **180** enables targeted, staged, or escalated control actions in response to detected leaks of greater magnitudes, though in other embodiments, any suitable predefined refrigerant pressure threshold may be selected.

(61) Further, the illustrated embodiment of the compressor switch portion **280C** includes output contact **284C** that is coupled to power input contact **286E** by switching element **282C** to provide operational power to the compressor **74** which sufficiently high refrigerant pressures exist within the HVAC system **100**. As such, during operation of the HVAC system **100**, the compressor **74** is driven by the VSD **92** and the motor **94** discussed above. However, in response to a refrigerant pressure that is below a respective predefined refrigerant pressure threshold, the switching element **282C** disconnects from the power input contact **286E**, which interrupts control signals, such as communication signals and/or power signals, to the compressor **74**. In some embodiments, the switching element **282C** actuates upon the refrigerant pressure reaching the predefined refrigerant pressure thresholds of the other switching portions **280A**, **280B**, or alternatively, a different, higher, and/or lower predefined threshold pressure based on a travel distance of the switching element **282C** to disconnect from the power input contact **286E**.

(62) With the foregoing in mind, FIG. **8** is an embodiment of a process **320** of operating the leak management system **102** of FIG. **6**. It is to be understood that the steps discussed herein are merely exemplary, and certain steps may be omitted or performed in a different order than the order discussed herein. In some embodiments, the process **320** may be performed by the processor **220** of the controller **190**, which may be an HVAC controller or a separate controller that is communicatively coupled to the HVAC controller. Additionally, although the process **320** is discussed with reference to the LDM device **178** having the pressure switch **180** and the pressure transducers **252**, it is to be understood that the present techniques may be extended to operate based on operation of any suitable LDM device **178** of any suitable leak management system **102**, including the LDM device **178** of FIG. **5** having the one pressure switch **180**.

(63) To begin the illustrated process **320**, the controller **190** monitors, at step **322**, the refrigerant pressure within the refrigerant circuit **104**. As discussed above, the pressure switch **180** and the pressure transducers **252** include respective sensing portions **206**, **256** that are fluidly coupled to the interior of the refrigerant circuit **104** to measure and provide signals or indications indicative of the refrigerant pressure therein. Thus, based on the signals from the LDM device **178**, the controller **190** is able to determine, at step **324**, whether the refrigerant pressure is below the predefined threshold pressure. Indeed, as discussed above, the predefined threshold pressure is set as any suitable pressure threshold for the refrigerant below which a leak from the refrigerant circuit **104** is likely to have occurred. Moreover, in some embodiments, the controller **190** is configured to determine whether a refrigerant leak has occurred based on input from additional components of the HVAC system **100**, such as the VSD **92**. For example, in embodiments in which the controller **190** is instructing the VSD **92** to operate and the pressure switch **180** has interrupted power supplied to the VSD **92**, the controller **190** may determine that the pressure switch **180** has likely actuated in response to a low refrigerant pressure condition, indicating that a refrigerant leak is present.

(64) In response to determining that the refrigerant pressure is at or above the predefined threshold pressure value, the controller **190** enables, at step **326**, continued, normal operation of the HVAC system **100**. That is, the controller **190** determines a leak has not occurred and continues to operate the compressor **74**, the supply fan **150**, and any other suitable components of the HVAC system **100** to provide desired conditioning to the interior space **114**. Thus, the leak management system **102** continues to operate in active response mode to monitor the refrigerant pressure based on input from the pressure switch **180**. The controller **190** following the process **320** therefore returns to step **322** to continue monitoring the refrigerant pressure. In some embodiments, the controller **190** may also wait a predefined time threshold before determining the pressure of the refrigerant **110** again, thus reducing usage of computing power of the controller **190**. In certain embodiments, the predefined time threshold is set as 1 minute, 5 minutes, 10 minutes, 60 minutes, or more.

(65) In response to determining that the refrigerant pressure is below the predefined threshold pressure, the controller **190** provides, at step **328**, a first control signal to activate the supply fan

150. That is, the controller **190** determines that a refrigerant leak from the refrigerant circuit **104** has occurred. Thus, to perform suitable control actions or corrective actions for managing the detected leak of the refrigerant **110**, the leak management system **102** enters leak management mode, in which the supply fan **150** is activated to promote dilution of any refrigerant **110** within the indoor supply air **152** of the interior space **114**. For example, the controller **190** may provide the supply fan signal to the supply fan **150** to cause the supply fan **150** to motivate the flow of the indoor supply air **152** into the interior space **114**. As such, pooling of the refrigerant within the interior space **114** may be mitigated or prevented by circulation and dilution via the indoor supply air **152**.

(66) The controller **190** following the present embodiment of the process **320** additionally provides, at step **330**, a second control signal to deactivate the compressor **74**. That is, the controller **190** may turn the compressor **74** off if the compressor **74** was operating during the determination of step **324** and may prevent subsequent operation of the compressor **74**. In these embodiments, the indoor supply air **152** motivated into the interior space **114** by the supply fan **150** is unconditioned. In some embodiments, the controller **190** provides the second control signal in response to the LDM device **178** detecting a refrigerant pressure equal to a second predefined refrigerant pressure, lower than the predefined refrigerant pressure. It is to be understood that step **328** and step **330** may be performed simultaneously, in some embodiments, or step **330** may be omitted in some embodiments. In some embodiments, the controller **190** monitors a change of the refrigerant pressure over time to monitor a rate or speed at which the refrigerant pressure is changing. For example, based on signals from the pressure transducers **252**, the controller **190** of certain embodiments determines whether the refrigerant pressure is dropping or has a rate of change that is greater than a predefined threshold rate of change. The predefined threshold rate of change may be any suitable pressure change over time, such as 1 pound per square inch (psi) per minute, 1 psi per hour, 1 psi per day, and so forth. As such, the controller **190** is capable of preemptively identifying refrigerant leaks and performing control actions before the refrigerant pressure falls below the predefined threshold pressure, in some embodiments. In response to determining that the refrigerant pressure has a rate of change that is greater than the predefined threshold rate of change, the controller **190** performs any of the control actions discussed herein.

(67) Moreover, the controller **190** may proceed to perform any other suitable control actions to mitigate pooled or leaked refrigerant, such as activating other components of the HVAC system **100**. In some embodiments, the controller **190** additionally activates the economizer fan **140** or adjusts a position of actuatable slats of the damper opening **142** to provide a greater amount of fresh air into the indoor supply air **152** supplied to the indoor unit **122** and the interior space **114**. The controller **190** may also activate the duct fan **160** and/or the ceiling fan **166** to provide additional mixing of the indoor supply air **152**. As such, any collections or pools of the refrigerant **110** within the interior space **114** are mitigated and/or removed from the interior space **114**. Accordingly, the controller **190** in communication with the LDM device **178** of the leak management system **102** may detect refrigerant leaks and mitigate pooling of the refrigerant within the interior space **114** by dilution, circulation, and/or removal.

(68) FIG. **9** is an embodiment of a process **350** of operating the leak management system **102** of FIG. **5**. It is to be understood that the steps discussed herein are merely exemplary, and certain steps may be omitted or performed in a different order than the order discussed herein. In the present embodiment, the process **350** is performed via the LDM device **178** having the one pressure switch **180** that operates as an interrupt or override device. In other embodiments, the present techniques may be extended to operate based on any suitable LDM device **178** of any suitable leak management system **102**, including the LDM device **178** of FIG. **6** having the pressure transducers **252** as well.

(69) To begin the illustrated process **350**, the pressure switch **180** of the LDM device **178** monitors, at step **352**, the refrigerant pressure within the refrigerant circuit **104**. As discussed above, the

sensing portion **206** of the pressure switch **180** is fluidly coupled to the conduits **106** at the suction side **182** of the compressor **74** to hydraulically sense the refrigerant pressure therein. The pressure switch **180** enables control or power signals to traverse the pressure switch **180** throughout normal operating conditions of the HVAC system **100**, such as those without leak conditions. Indeed, when the pressure switch **180** is not actuated, the HVAC system **100** operates normally to provide control signals to the supply fan **150**, the compressor **74**, and so forth.

(70) In response to the refrigerant pressure dropping to a first threshold pressure, the pressure switch **180** overrides, at step **354**, the controller **190** to provide a first control signal to activate the supply fan **150** by transmitting instructions thereto. As discussed above with reference to FIG. 7, the switching element **282A** or any suitable management component of the supply fan switch portion **280A** is moved from the controller input contact **286A** to the override input contact **286B**, thus instructing or signaling the supply fan **150** to operate continuously in leak management mode to promote dilution of any refrigerant leaks within the interior space **114**.

(71) In response to the refrigerant pressure dropping to a second threshold pressure, which may be below the first threshold pressure, the pressure switch **180** provides, at step **356**, a second control signal to control signal to activate additional or auxiliary fans. Indeed, as discussed with respect to FIG. 7, the switching element **282B** of the auxiliary fan switch portion **280B** similarly moves from the controller input contact **286C** to the override input contact **286D** in response to the continued refrigerant pressure decrease. As such, the additional or auxiliary fans coupled to the output contact **284B** are instructed to operate in leak management mode, such as in an always on and/or maximum speed setting, to further facilitate dilution of any refrigerant leaks.

(72) In response to the refrigerant pressure dropping to a third threshold pressure, which may be below the first and/or second threshold pressure, the pressure switch **180** modifies, at step **358**, a third control signal to deactivate the compressor **74**. The switching element **282C** of the compressor switch portion **280C** may therefore disconnect from the power input contact **286E** to interrupt power flow between the power source **126** and the compressor **74**. In such embodiments, the indoor supply air **152** provided to the interior space **114** by the supply fan **150** is unconditioned. It is to be understood that each of the first, second, and third threshold pressures may be individually selected to enable the pressure switch **180** of the LDM device **178** to implement control actions to mitigate refrigerant leaks in any suitable order. Accordingly, the LDM device **178** having the pressure switch **180** provides efficient monitoring and management of refrigerant leaks from the refrigerant circuit **104** based on the refrigerant pressure within the refrigerant circuit **104**.

(73) Accordingly, embodiments discussed herein are directed to a refrigerant leak management system having a LD device or LDM device that includes one or multiple pressure-activated devices fluidly coupled to a refrigerant circuit. The pressure-activated devices include pressure switches, pressure transducers, or a combination thereof in some embodiments. By monitoring a source of the refrigerant, the LDM device reduces a demand for complicated, insensitive, unreliable, and/or expendable refrigerant concentration sensors disposed within an interior space. In response to detecting or determining that the refrigerant pressure is indicative of a refrigerant leak, the LDM device or the controller activates a supply fan that is configured to provide conditioned air to the interior space. Additionally, the LDM device and/or the controller deactivates the compressor, in some embodiments, so that additional refrigerant is not driven through the refrigerant circuit and potentially leaked out of the refrigerant circuit. Thus, the unconditioned, ventilation air provided to the interior space dilutes and circulates the air within the interior space to stop or prevent undesired pooling of the refrigerant within the interior space. In some embodiments, the LDM device or the controller activates additional fans within or fluidly coupled to the interior space to provide further mixing and dilution of the refrigerant therein. By these and any other suitable manners, the refrigerant leak management system may improve operation of the HVAC system, while enabling the detection and mitigation of refrigerant leaks.

(74) While only certain features and embodiments of the present disclosure have been illustrated

and described, many modifications and changes may occur to those skilled in the art, such as variations in sizes, dimensions, structures, shapes and proportions of the various elements, values of parameters, mounting arrangements, use of materials, colors, orientations, and so forth, without materially departing from the novel teachings and advantages of the subject matter recited in the claims. The order or sequence of any process or method steps may be varied or re-sequenced according to alternative embodiments. It is, therefore, to be understood that the appended claims are intended to cover all such modifications and changes as fall within the true spirit of the present disclosure. Furthermore, in an effort to provide a concise description of the exemplary embodiments, all features of an actual implementation may not have been described, such as those unrelated to the presently contemplated best mode of carrying out the present disclosure, or those unrelated to enabling the claimed disclosure. It should be appreciated that in the development of any such actual implementation, as in any engineering or design project, numerous implementation specific decisions may be made. Such a development effort might be complex and time consuming, but would nevertheless be a routine undertaking of design, fabrication, and manufacture for those of ordinary skill having the benefit of this disclosure, without undue experimentation.

Claims

1. A heating, ventilation, and/or air conditioning (HVAC) system, comprising: a refrigerant circuit; a compressor configured to circulate a refrigerant through the refrigerant circuit; a first leak detection and management (LDM) device disposed in a first location of the refrigerant circuit and configured to detect a pressure of the refrigerant at the first location; a second LDM device disposed in a second location of the refrigerant circuit and configured to detect a pressure of the refrigerant at the second location; and a controller configured to disable the compressor in response to: a first signal from the first LDM device, the first signal indicating a first refrigerant leak at the first location; or a second signal from the second LDM device, the second signal indicating a second refrigerant leak at the second location.
2. The HVAC system of claim 1, wherein the controller is configured to control a valve position in response to the first signal or the second signal.
3. The HVAC system of claim 2, wherein the controller is configured to control the valve position of an expansion valve in response to the first signal or the second signal.
4. The HVAC system of claim 1, wherein the controller is configured to activate or maintain operation of a fan in response to the first signal.
5. The HVAC system of claim 1, wherein the controller is configured to activate or maintain operation of a first fan in response to the first signal and a second fan in response to the second signal.
6. The HVAC system of claim 1, wherein the controllers is configured to actuate a damper to open the damper and expose a damper opening in response to the first signal or the second signal.
7. The HVAC system of claim 1, wherein the first LDM device is disposed at an evaporator corresponding to the first location.
8. The HVAC system of claim 1, wherein: the first LDM device comprises a first pressure switch; and the second LDM device comprises a second pressure switch.
9. The HVAC system of claim 1, wherein: the first LDM device comprises a first pressure transducer; and the second LDM device comprises a second pressure transducer.
10. A refrigerant leak detection and management assembly, comprising: a leak detection and management (LDM) device configured to detect a pressure of a refrigerant in a refrigerant circuit of a heating, ventilation, and/or air conditioning (HVAC) system; a controller configured to: receive, from the LDM device, a signal indicative of a refrigerant leak in the refrigerant circuit; and control a compressor, a valve, a fan, or any combination thereof based on the signal.
11. The refrigerant leak detection and management assembly of claim 10, comprising an additional

LDM device configured to detect an additional pressure of the refrigerant at a location of the refrigerant circuit different than that of the LDM device, wherein the controller is configured to: receive, from the additional LDM device, an additional signal indicative of an additional refrigerant leak in the refrigerant circuit; and control the compressor, the valve, the fan, an additional valve, an additional fan, or any combination thereof based on the additional signal.

12. The refrigerant leak detection and management assembly of claim 10, wherein the LDM device comprises a pressure switch.

13. The refrigerant leak detection and management assembly of claim 10, wherein the LDM device comprises a pressure transducer.

14. The refrigerant leak detection and management assembly of claim 10, wherein the controllers is configured to actuate a damper to open the damper and expose a damper opening in response to the signal.

15. The refrigerant leak detection and management assembly of claim 10, wherein the LDM device is disposed at or adjacent to an evaporator of the HVAC system.

16. A control assembly of a heating, ventilation, and/or air conditioning (HVAC) system, the control assembly comprising: a sensing portion configured to sense a pressure of a refrigerant in a refrigerant circuit of the HVAC system; and at least one actuation portion configured to cause, in response to the pressure falling below a threshold pressure, actuation of a compressor to disable the compressor, activation of a fan, operation of a valve to control a positioning of the valve, or any combination thereof.

17. The control assembly of claim 16, comprising: an additional sensing portion configured to sense an additional pressure of the refrigerant in the refrigerant circuit of the HVAC system, wherein: the sensing portion is disposed at a location of the refrigerant circuit; the additional sensing portion is disposed at an additional location of the refrigerant circuit; and the at least one actuation portion is configured to cause, in response to the additional pressure falling below the threshold pressure, actuation of the compressor to disable the compressor, activation of the fan, operation of the valve to control the positioning of the valve, activation of an additional fan, operation of an additional valve to change an additional position of the additional valve, or any combination thereof.

18. The control assembly of claim 16, wherein the sensing portion comprises a pressure switch or a pressure transducer.

19. The control assembly of claim 16, wherein the at least one actuation portion is configured to actuate a damper to open a damper opening in response to the pressure falling below the threshold pressure.

20. The control assembly of claim 16, wherein the actuation portion comprises a controller.
