

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12392492
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Weilert; Jeffrey R. et al.

System for burning combustible fuel above a placement surface

Abstract

A stand is provided for elevating a portable stove above a surface. The stand includes a plurality of legs extending radially outward.

Inventors: Weilert; Jeffrey R. (Southlake, TX), Maghsadi; Alexander K. (Lewisville, TX)

Applicant: Solo Brands, LLC (Grapevine, TX)

Family ID: 1000008763694

Assignee: SOLO BRANDS, LLC (Grapevine, TX)

Appl. No.: 18/942947

Filed: November 11, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250067440 A1	Feb. 27, 2025

Related U.S. Application Data

continuation parent-doc US 18408011 20240109 US 12140313 child-doc US 18942947
continuation parent-doc US 18100790 20230124 US 11994298 20240528 child-doc US 18408011
continuation parent-doc US 17886239 20220811 PENDING child-doc US 18100790

Publication Classification

Int. Cl.: F24B1/18 (20060101); F24B1/181 (20060101); F24C1/16 (20210101)

U.S. Cl.:

Field of Classification Search

CPC: F24B (1/181); F24C (3/14); F24C (1/16)

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
685194	12/1900	Young	N/A	N/A
904188	12/1907	Engle	N/A	N/A
1298762	12/1918	Milligan	N/A	N/A
1694175	12/1927	Hauser	N/A	N/A
D100012	12/1935	Ford	N/A	N/A
2614553	12/1951	Cox	N/A	N/A
2722883	12/1954	Rignell	N/A	N/A
2738225	12/1955	Meek	N/A	N/A
D196018	12/1962	Palmer et al.	N/A	N/A
3756218	12/1972	Simpson	N/A	N/A
D229013	12/1972	Storandt	N/A	N/A
D229277	12/1972	Chan	N/A	N/A
3790081	12/1973	Thornton	N/A	N/A
3937138	12/1975	Tidwell	N/A	N/A
3951082	12/1975	Leggett	N/A	N/A
D258259	12/1980	Lindholm	N/A	N/A
D258712	12/1980	Jacobson	N/A	N/A
D273264	12/1983	Elliston	N/A	N/A
4735135	12/1987	Walker	N/A	N/A
4903683	12/1989	Larsen	N/A	N/A
5024208	12/1990	Hottenroth	N/A	N/A
5117558	12/1991	Hull	N/A	N/A
D355809	12/1994	Kothrade	N/A	N/A
D358204	12/1994	Ferrier	N/A	N/A
5490452	12/1995	Schlosser	N/A	N/A
D379900	12/1996	Gillam et al.	N/A	N/A
5638808	12/1996	Home	N/A	N/A
5651356	12/1996	Kaines	N/A	N/A
5797386	12/1997	Orr	N/A	N/A
5809988	12/1997	Wagner	N/A	N/A
6024081	12/1999	Libertini, Jr.	N/A	N/A
D422452	12/1999	Persson	N/A	N/A
D435191	12/1999	Cooper	N/A	N/A
6196121	12/2000	Crowl	N/A	N/A
6196215	12/2000	Chandaria	N/A	N/A
D442422	12/2000	Dabney	N/A	N/A
D444991	12/2000	Measom	N/A	N/A
6314955	12/2000	Boetcker	N/A	N/A
6393717	12/2001	Santos	N/A	N/A

6488023	12/2001	Pecoskie	N/A	N/A
6609514	12/2002	Bertolas	N/A	N/A
D488023	12/2003	Siegel et al.	N/A	N/A
D491409	12/2003	Siegel	N/A	N/A
D495552	12/2003	Siegel	N/A	N/A
D531849	12/2005	Turner	N/A	N/A
D534756	12/2006	Jensen	N/A	N/A
D549300	12/2006	Harrell	N/A	N/A
D607265	12/2009	Gaunaurd, III	N/A	N/A
D612191	12/2009	Taber	N/A	N/A
D612662	12/2009	Lorenz	N/A	N/A
D618038	12/2009	Davies	N/A	N/A
7810484	12/2009	Schlosser	N/A	N/A
D644474	12/2010	Wilgus	N/A	N/A
8087410	12/2011	Gregory	N/A	N/A
D658426	12/2011	Saunders	N/A	N/A
8272601	12/2011	Kocher	N/A	N/A
D683999	12/2012	Karlsson	N/A	N/A
8668949	12/2013	Wilson	N/A	N/A
D701721	12/2013	Jan	N/A	N/A
8991382	12/2014	Mau	N/A	N/A
D749960	12/2015	Bhattacharyya et al.	N/A	N/A
9328928	12/2015	Wehr	N/A	N/A
9844300	12/2016	Cedar	N/A	N/A
10098502	12/2017	Ohler	N/A	N/A
10125995	12/2017	Kohli	N/A	N/A
10222092	12/2018	Traeger	N/A	N/A
D858729	12/2018	Scott	N/A	N/A
10557635	12/2019	Wanderscheid et al.	N/A	N/A
10743712	12/2019	Skillman	N/A	N/A
D923163	12/2020	Jan	N/A	N/A
11092342	12/2020	Harrington	N/A	N/A
2006/0219233	12/2005	Sorenson	N/A	N/A
2007/0137634	12/2006	Traeger	N/A	N/A
2009/0165772	12/2008	Hunt	N/A	N/A
2010/0043775	12/2009	Phillips	N/A	N/A
2010/0083946	12/2009	Cedar	126/25B	F24B 1/00
2011/0073723	12/2010	Ashpole	N/A	N/A
2011/0180527	12/2010	Abbott	N/A	N/A
2012/0017884	12/2011	Van Den Hoff	N/A	N/A
2012/0145139	12/2011	Deeds	N/A	N/A
2012/0222668	12/2011	Unger	N/A	N/A
2014/0007778	12/2013	Marks	N/A	N/A
2014/0026765	12/2013	Fou	N/A	N/A
2014/0165993	12/2013	Ahmed	N/A	N/A
2014/0238378	12/2013	Scott	N/A	N/A
2015/0068512	12/2014	Mehler	N/A	N/A
2015/0110939	12/2014	Benson	N/A	N/A
2015/0211743	12/2014	Defoort	N/A	N/A
2017/0059178	12/2016	Lando et al.	N/A	N/A

2017/0363325	12/2016	Diurlin	N/A	N/A
2019/0313851	12/2018	Shemp	N/A	N/A
2020/0049344	12/2019	Masterson	N/A	N/A
2020/0208842	12/2019	Jan et al.	N/A	N/A
2020/0309369	12/2019	Jan	N/A	N/A
2021/0018180	12/2020	Jan	N/A	N/A
2021/0048188	12/2020	Harrington	N/A	N/A
2021/0199301	12/2020	Poggi	N/A	N/A
2021/0274970	12/2020	Stoltzfus	N/A	N/A
2021/0282592	12/2020	Jan	N/A	N/A
2022/0186931	12/2021	Jan	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2035756	12/1988	CN	N/A
201715561	12/2010	CN	N/A
103528100	12/2013	CN	N/A
204388128	12/2014	CN	N/A
202013002524	12/2012	DE	N/A
10236945	12/2023	DE	N/A
2000342462	12/1999	JP	N/A
2001161169	12/2000	JP	N/A
10323289	12/2002	JP	N/A
2003190011	12/2002	JP	N/A
200295935	12/2001	KR	N/A
100898493	12/2008	KR	N/A
1020200122766	12/2019	KR	N/A
2017078762	12/2016	WO	N/A
2018160767	12/2017	WO	N/A
2021111262	12/2020	WO	N/A

OTHER PUBLICATIONS

International Search Authority, International Search Report and Written Opinion, ISA/KR, PCT/US2019/063180, Mar. 26, 2020, 10 pages. cited by applicant

International Search Authority, International Search Report and Written Opinion, for PCT/US2021/020687, mailed Aug. 5, 2021, 11 pages. cited by applicant

Solo Stove, webpage capture: <https://www.solostove.com/solo-stove-bonfire>, 2017, 8 pages. cited by applicant

Screen captures from YouTube video clip entitled “Solo Stove Bonfire: Best Gear of 2017,” 4 pages, uploaded on May 14, 2017 by user “Canadian Prepper”. Retrieved from Internet: https://www.youtube.com/watch?v=Vo_J_fIWq5g. cited by applicant

Camping stove, <https://www.kickstarter.com/projects/340672218/solo-stove-campfire-backpack-camp-survive/description>, 21 pages (2014). cited by applicant

Korean Intellectual Property Office, International Search Report and Written Opinion, PCT/US2022/011365, May 3, 2022, 12 pages. cited by applicant

International Search Report and Written Opinion for related International Application No. PCT/US2023/071938, mailed Nov. 28, 2023; 9 pages. cited by applicant

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 18/408,011, filed Jan. 9, 2024, entitled SYSTEM FOR BURNING COMBUSTIBLE FUEL ABOVE A PLACEMENT SURFACE, which is a continuation of U.S. patent application Ser. No. 18/100,790, filed Jan. 24, 2023, now U.S. Pat. No. 11,994,298, entitled PORTABLE STOVE WITH FOLDING STAND, which is a continuation of U.S. patent application Ser. No. 17/886,239, filed Aug. 11, 2022, entitled PORTABLE STOVE WITH FOLDING STAND, all of which are hereby incorporated by reference in their entirety as though fully set forth herein. (2) This application is also related to U.S. Design patent application Ser. No. 29/865,767, filed Aug. 11, 2022, now U.S. Pat. No. D1,018,812, entitled FIRE PIT STAND, and to U.S. Design patent application Ser. No. 29/865,766, filed Aug. 11, 2022, now U.S. Pat. No. D1,043,934, entitled FIRE PIT AND STAND, both of which are hereby incorporated by reference in their entirety as though fully set forth herein.

FIELD

(1) The subject matter described herein relates to stand for a portable stove and to a portable stove. The stand may offset the portable stove from a surface, such as a non-heatproof surface.

BACKGROUND

(2) Camp stoves and other portable stoves are often used in backpacking, picnics, backyard cookouts, and at other times. The components of a portable stove may become hot during use. This may present a risk of heat damage when, for example, a hot metal stove is placed on a non-heatproof surface such as a vehicle hood, picnic table, forest floor, etc.

(3) The information included in this Background section of the specification, including any references cited herein and any description or discussion thereof, is included for technical reference purposes only and is not to be regarded as subject matter by which the scope of the disclosure is to be bound.

SUMMARY

(4) Disclosed is a portable stand for a portable cooking stove usable in environments where a heatproof surface is not available for placement of the stove. Together, the stove and stand may create a system that can be used in conjunction with pots and pans to, for example, boil water, cook eggs, heat rehydrated foods, etc. In some aspects, the stand is a removable, foldable stand that can be disposed inside the stove body during transportation or storage of the stove. In its unfolded state, the stand includes legs and feet that are sized and shaped to hold the stove bottom a sufficient distance away from a tabletop or other surface.

(5) The stand disclosed herein has particular, but not exclusive, utility for camping, backpacking, and picnics. One general aspect of the stove and stand system includes a stand for elevating a portable stove above a surface. The stand includes a central intersection and a plurality of legs, where each leg includes: an inner link extending radially outward from the central intersection; an outer link connected to the inner link by a hinge, the outer link movable to a position extending radially outward from the inner link; and a foot coupled to and extending transverse to the outer link, the foot including: a standoff extending transverse from the outer link in a first direction; and an interference arm extending transverse from the outer link in a second direction opposite the first direction.

(6) Implementations may include one or more of the following features. In some embodiments, the hinges, the inner link, and the outer link are structurally configured such that the outer link can rotate downward but not upward. In some embodiments, when the stand is configured such that

when the stove is rested on the stand, the bottom portion of the stove rests on at least one of the central region or the plurality of legs. In some embodiments, a surface of each standoff portion includes a pad fixedly attached to the standoff portion. In some embodiments, the pads include at least one of a thermal insulation property, an anti-slip property, or a vibration suppression property. In some embodiments, the pads include a rubbery material. In some embodiments, the outer link of each leg is movable to a folded position. In some embodiments, when at least some of the outer links are in the folded position, the stand is positionable inside the stove. In some embodiments, the height of the standoffs is selected to minimize heat transfer between the stove and the surface. In some embodiments, when all of the outer links are in the position extending radially outward, a width of the stand is such that the stove fits between all of the interference arms, and such that the stove is arrested from motion in any radially outward direction.

(7) One general aspect includes a stove and stand system. The stove and stand system includes a stove body including an outer width, a cavity having an inner width, and a bottom portion. The stove and stand system also includes a stand including: a central region; and a plurality of legs extending radially outward from the central region, each leg including: an inner link extending radially outward from the central region; an outer link pivotably attached to the inner link and pivotable from a first position parallel with the inner link to a second position angled relative to the inner link, the stand having a first width when the outer links are in the first position and having a second width smaller than the first width when the outer links are in the second position, the first width being greater than the outer width of the stove body and the second width being smaller than the inner width of the cavity of the stove body.

(8) Implementations may include one or more of the following features. In some embodiments, the stand includes a foot at an end of the outer link, the foot including: a standoff extending transverse from the outer link in a first direction; and an interference arm extending transverse from the outer link in a second direction opposite the first direction. In some embodiments, the stove and stand are configured such that when the stove is on the stand: the bottom portion of the stove rests on at least one of the central region and the plurality of legs, and the standoff of each leg arrests the stove from moving laterally beyond a radial position. In some embodiments, the height of the standoffs is selected to minimize heat transfer between the stove and the surface. In some embodiments, the stove and stand are configured such that when at least some the outer links are in the second position, the stand can be stored within the cavity. In some embodiments, the hinges, the inner link, and the outer link are structurally configured such that the outer link can rotate downward but not upward. In some embodiments, a surface of each standoff portion includes a pad fixedly attached to the standoff portion. In some embodiments, the pads include a rubbery material providing at least one of a thermal insulation property, an anti-slip property, or a vibration suppression property.

(9) One general aspect includes a stove and stand system. The stove and stand system includes a stove body including an outer width, a cavity having an inner width, and a bottom portion. The stove and stand system also includes a stand including: a central region; and a plurality of legs extending radially outward from the central region, each leg including: an inner link extending radially outward from the central region; an outer link pivotably attached to the inner link and pivotable from a first position parallel with the inner link to a second position angled relative to the inner link, the stand having a first width when the outer links are in the first position and having a second width smaller than the first width when the outer links are in the second position, the stand being sized so that the central region is introducible into the cavity when in the second position. In some embodiments, the stand includes a foot at an end of the outer link, the foot including: a standoff extending transverse from the outer link in a first direction; and an interference arm extending transverse from the outer link in a second direction opposite the first direction.

(10) In some implementations, the present disclosure is directed to a camp stove that includes a stove body comprising an outer width, a cavity having an inner width, and a bottom portion. An outer surface may define the outer width and may have a plurality of rows of ventilation holes

extending about a circumference of the stove body. The rows may be disposed along a lower portion of the outer surface. An inner surface may define the inner width and may form a combustion chamber. The inner surface may have a row of ventilation holes extending about the inner circumference of the stove body in an upper portion of the inner surface. The ventilation holes in the outer surface may be in fluid communication with a) the ventilation holes in the inner surface through a vertical passage between the inner surface and the outer surface, and b) with the combustion chamber through a horizontal passage extending above the bottom portion.

(11) In some aspects, the camp stove may include three rows of holes extending about the circumference of the stove body. In some aspects, the ventilation holes in the inner surface may have a width greater than a width of the ventilation holes in the outer surface. In some aspects, the ventilation holes in the inner surface are formed in a different number of rows (such as one) than the number of rows of the ventilation holes in the outer surface and the ventilation holes in the inner surface have a width greater than a width of the ventilation holes in the outer surface.

(12) This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to limit the scope of the claimed subject matter. A more extensive presentation of features, details, utilities, and advantages of the stove and stand system, as defined in the claims, is provided in the following written description of various embodiments of the disclosure and illustrated in the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Illustrative embodiments of the present disclosure will be described with reference to the accompanying drawings, of which:

(2) FIG. 1 is a front perspective view of an example stove and stand system, in accordance with aspects of the present disclosure.

(3) FIG. 2 is perspective bottom view of an example stove and stand system in accordance with aspects of the present disclosure.

(4) FIG. 3 is a perspective top view of an example stove and stand system, in accordance with aspects of the present disclosure.

(5) FIG. 4 is a front cross-sectional view of an example stove and stand system, in accordance with aspects of the present disclosure.

(6) FIG. 5 is a front perspective view of the stove body of an example stove and stand system, with the outer wall and stand removed for clarity, in accordance with aspects of the present disclosure.

(7) FIG. 6 is a front perspective view of the stove body of an example stove and stand system, with the outer wall, stand, top bezel, and inner wall removed for clarity, in accordance with aspects of the present disclosure.

(8) FIG. 7 is a top perspective view of the stand of an example stove and stand system, in an unfolded configuration, in accordance with aspects of the present disclosure.

(9) FIG. 8 is a top perspective view of the stand of an example stove and stand system, in a folded configuration, in accordance with aspects of the present disclosure.

(10) FIG. 9 is a front cross-sectional view of an example stove and stand system, with the stand stored inside the stove body, in accordance with aspects of the present disclosure.

DETAILED DESCRIPTION

(11) Disclosed herein is a stand for a portable stove for use in environments where a heatproof surface is not available on which to place the stove. The stand may be used with a portable stove that can burn solid fuel such as sticks, branches, paper, cardboard, etc. The stove can be used in

conjunction with pots and pans to, for example, boil water, cook eggs, heat rehydrated foods, etc. Alternatively, or in addition, the stove may be used for roasting, browning, or toasting foods, or as a heat source. In some aspects, the stand is foldable. In its folded state, the stove stand can be disposed inside the stove body for transportation or storage. In its unfolded state, the stove stand includes legs and feet that are sized and shaped to restrain movement of the stove, and to offset the bottom surface of the stove a safe distance away from the tabletop or other placement surface during cooking or other use of the stove.

(12) For the purposes of promoting an understanding of the principles of the present disclosure, reference will now be made to the embodiments illustrated in the drawings, and specific language will be used to describe the same. It is nevertheless understood that no limitation to the scope of the disclosure is intended. Any alterations and further modifications to the described devices, systems, and methods, and any further application of the principles of the present disclosure are fully contemplated and included within the present disclosure as would normally occur to one skilled in the art to which the disclosure relates. In particular, it is fully contemplated that the features, components, and/or steps described with respect to one embodiment may be combined with the features, components, and/or steps described with respect to other embodiments of the present disclosure. For the sake of brevity, however, the numerous iterations of these combinations will not be described separately.

(13) These descriptions are provided for exemplary purposes only and should not be considered to limit the scope of the stove and stand system. Certain features may be added, removed, or modified without departing from the spirit of the claimed subject matter.

(14) FIG. 1 is a front perspective view of an example stove and stand system **100**, in accordance with aspects of the present disclosure. The stove and stand system **100** includes a stove **105** and a stand **120**. The stove **105** includes stove body **110** with a width or outer diameter OD. In some embodiments, the outer diameter OD is between 6" and 12". In some embodiments, the outer diameter OD is between 5" and 15", although other diameters, both larger and smaller, may be used instead or in addition.

(15) In the example shown in FIG. 1, the stove body includes a plurality of ventilation holes **170** in a lower portion **160** of the stove body **110**. In this particular implementation, there are three horizontal rows of holes, equally spaced and extending entirely about the circumference of the stove body. In order to provide sufficient airflow, but also balancing a desire to keep the hole size small, the ventilation holes **170** are provided in multiple rows of small holes instead of a single row of larger holes. Since the stove **105** is sized to be used on a table-top, it may be advantageous to provide smaller holes instead of larger holes to reduce the chance of users inserting debris, fingers, or other items into the ventilation holes **170**, as the stove rests on a table about which people are sitting or standing. Accordingly, in some implementations, the holes are arranged in three rows as shown in FIG. 1 with each hole having a diameter sized less than a diameter of an average finger. For example, in some implementations, each hole has a diameter in a range of about 0.3 to about 0.75 inches. In some implementations, each hole has a diameter in a range of about 0.4 to 1 inch. Even still, multiple rows, such as three rows of holes larger than 1 inch are also contemplated. In some examples, the holes have a diameter in a range of about 0.5 to 1.5 inches. By summing the area of the smaller holes, placed in horizontal rows, sufficient airflow can still be provided to provide ventilation to the upper ventilation holes and to the bottom of the burn chamber. Although described as having diameters, each ventilation hole **170** may have a perimeter shape that is not round, and therefore the holes may have a width instead of a diameter.

(16) In some examples, the stove body **110** has a generally cylindrical shape with a circular cross section, although in other examples it may have shapes with other cross-sections, including but not limited to oval, square, rectangular, triangular, or polygonal. The stove **105** may be used to provide heat, provide ambience, for cooking, or for other desirable purposes. In this example, the stove **105** includes a top bezel or pot support **130** that rests on an upper portion **150** of the stove body **110**.

The top bezel or pot support **130** is configured to support the weight of, for example, a frying pan of a water-filled pot, although the stove can be used with its top open for roasting marshmallows, hot dogs, or other foods.

(17) The example stove and stand system **100** also includes the stand **120**. In the example shown in FIG. **1**, the stove body **110** rests removably on the stand **120**. The stand is configured to support the weight of the stove body **110**, including any fuel that may be inside the stove body, and including the loaded cooking weight of pans, water-filled pots, etc. The stand **120** is also sized and shaped to arrest lateral motion of the stove body **110**, and to prevent the stove body **110** from directly contacting a placement surface **180** on which the stand rests. Thus, for example, if the placement surface **180** is a non-heatproof surface (e.g., a non-heatproof picnic table, non-heatproof countertop, plastic table, forest floor covered in pine needles or leaf litter, etc.), then the stand **120** may protect the placement surface **180** by minimizing the amount of heat from the bottom portion **160** of the stove body **110** that is transferred directly to the placement surface **180** via conduction. This may limit or prevent heat damage to the placement surface **180** from heat generated by the combustion of fuel within the stove body **110**.

(18) This configuration advantageously permits the stove and stand system **100** to serve as an aesthetic source of firelight ambience, a heat source, and/or a cooking stove, whether simultaneously or at different times. The size and structure permit the stove and stand system to be used on a tabletop or other surface, about which people may socially gather to build relationships, share time, and create memories. For example, the stove and stand system **100** may be placed on the placement surface **180** as a tabletop centerpiece that allows users seated around the table to see, read, warm their hands, and/or roast food such as marshmallows or hot dogs, or heat foods in a cooking pot, pan, or grill that is rested on the top bezel **130**. The simple proximity of a stove sized to fit on a tabletop to people gathered about the table may create certain interactions not achievable by a firepit or stove intended to rest on the ground. Such multi-functionality, in a small device that fits on a tabletop or other surface, and is easily portable and storable, provides clear advantages over existing firepits, camp stoves, tiki torches, and other combustion devices.

(19) Before continuing, it should be noted that the examples described herein are provided for purposes of illustration and are not intended to be limiting. Other devices and/or device configurations may be utilized to carry out the operations described herein.

(20) FIG. **2** is perspective bottom view of an example stove and stand system **100**, in accordance with aspects of the present disclosure. The stove and stand system **100** includes the stove body **110**, which includes an outer wall **210** and a bottom surface **215**. In some examples, when the stove body **110** contains burning fuel, the amount of heat generated by the combustion may be such that the outer wall **210** and bottom surface **215** may become hot enough to damage materials or surfaces with which they are in contact.

(21) FIG. **2** also shows the bottom of the stand **120**. When the stove body **110** is placed on the stand **120**, the stand **120** prevents the placement surface **180** (FIG. **1**) from coming in direct contact with the bottom surface **215** of the stove body **110**. The stand **120** includes a central region **220**, and a plurality of legs **230** projecting radially outward from the central region. In an example, the legs **230** project horizontally, although in other examples the legs **230** may be angled upward or downward. In some examples, a minimum of three legs **230** may be needed to support the stove body **110** in a stable manner. However, depending on the implementation, the stand **120** may include only two legs **230**, or may include four or more legs **230**, without departing from the spirit of the present disclosure.

(22) Each leg **230** includes an inner link **240** that projects radially from the central region **220**. In some examples, the inner links **240** and the central region **220** form a single piece that may, for example, be stamped from a sheet metal blank. In other examples, the inner links **240** may be attached to the central region **220** by welds, solder, brazing, bolts, screws, rivets, pins, or otherwise. Each leg also includes an outer link **260** that is rotatably attached to the inner link **240** by a hinge

250 located at a radially outermost portion of the inner link **240** and a radially innermost portion of the outer link **260**. The hinge **250** is configured to transition the outer link **260** from a first, unfolded configuration (shown here in FIG. 2) to a second, folded configuration (shown below in FIGS. 8 and 9). In this example, the hinge **250** pivots around a hinge pin. However, other implementations use alternative hinge types. Yet other implementations utilize an outer link that telescopes between a first configuration and a smaller second configuration.

(23) Each leg also includes a foot **270**, located at a radially outermost portion of the outer link **260** such that, when the stove body **110** is placed on the stand **120**, the bottom surface **215** of the stove body **110** is stood off from the placement surface by a sufficient distance to limit or prevent heat damage to the placement surface **180** from heat generated by the combustion of fuel within the stove body **110**, and such that the stove body **110** is arrested from lateral movement in a radial or horizontal direction.

(24) FIG. 3 is a perspective top view of an example stove and stand system **100**, in accordance with aspects of the present disclosure. Visible are the stove body **110** and stand **120**. In addition to an outer wall **102**, the stove body includes an inner wall **310** spaced from the outer wall **102** and defining a combustion cavity **330**. Within the combustion cavity **330** is a fire grate **320**, which may for example support a load of combustible solid fuel such as sticks, branches, paper, cardboard, etc.

(25) FIG. 4 is a front cross-sectional view of an example stove and stand system **100**, in accordance with aspects of the present disclosure. The stove body **110** includes the outer wall **102** along with an inner wall **310** that is spaced from the outer wall **102** and defines an inner width or inner diameter ID of the combustion chamber **330**. The inner wall **310** includes a top lip **440** that enables the inner wall **310** to hang removably from a top edge **450** of the outer wall **210**. An upper portion of the inner wall **310**, below the top lip **440**, includes a plurality of ventilation holes **350**.

(26) The top bezel or pot support **130** may for example rest removably on the top lip **440**. The inner wall **310** rests removably on a choke pan **410**. Within the combustion chamber **330** is a quantity of combustible solid fuel **470**, supported by the fuel or fire grate **320**. The fire grate **320** is supported by the choke pan **410**. Within the choke pan **410**, below the fire grate **320**, is an ash pan **420**, which receives ashes and other combustion remnants that fall through the fire grate **320** as the fuel **470** is combusted. The ash pan **420** is positioned centrally within the choke pan **410** by a plurality of ash pan spacers **430** (e.g., three, four, or more ash pan spacers **410**), which project inward from the wall of the choke pan. Below the ash pan **420** is an air-damper **480** with a central air passage **482**.

(27) The bottom surface **215** of the stove body **110** is attached adjacent to a bottom edge of the outer wall **102**. The bottom surface **215** of the stove body **110** may rest on the stand **120**, such that the bottom surface **215** is spaced from the placement surface **180** (e.g., a tabletop) by a height H, which limits heat transfer between the bottom surface **215** and the placement surface **180**. This may help to prevent heat damage to the placement surface **180**, in cases where the placement surface **180** is a non-heat-resistant surface.

(28) Air may flow through the three rows of ventilation holes **170**, and then divide to flow upward to the ventilation holes **350** and to flow toward the combustion chamber **330** by flowing between the air-damper **480** and the bottom surface **215**, through the central air passage **482**, and around the bottom of the ash pan **420**, upward toward the fire grate **320**, and above the ash pan **420** into the combustion chamber **330**. In addition, the configuration shown in FIG. 4 can enable secondary combustion of unburnt volatile organic compounds (VOCs) emitted by the fuel **470** during combustion. When a fire is lit, rising hot air and the absence of oxygen created by the combustion process creates a vacuum at the bottom of the burn chamber. This vacuum draws oxygen in through the three rows of ventilation holes **170** at the bottom portion of the outer wall **102**, horizontally between the air-damper **480** and the bottom surface **215**, upward through the central air passage **482**, and around the bottom of the ash pan **420**, upward toward the fire grate **320**, and above the ash pan **420** into the combustion chamber **330** to fuel the fire on the fuel or fire grate. At the same time, additional oxygen travels from the three rows of ventilation holes **170** vertically upward in a gap

between the outer wall **102** and the inner wall **310**, where the oxygen is preheated by the temperature of the inner wall **310**. The oxygen continues to then flow back into the combustion chamber **330** through the upper ventilation holes **350**, for additional combustion of VOCs within the column of heat and flame rising in the combustion chamber **330**. Such secondary combustion can not only increase heat and light output of the stove and stand system **100**, but also decrease the production of smoke by ensuring a more complete combustion of the fuel **470**.

(29) FIG. 5 is a front perspective view of the stove body **110** of an example stove and stand system **100**, with the outer wall **102** and stand **120** removed for clarity, in accordance with aspects of the present disclosure. Visible are the top bezel or pot support **130**, top lip **440**, inner wall **310**, and choke pan **410**. In the example shown in FIG. 5, a lower edge **510** of the inner wall **310** rests on an upper edge **520** of the choke pan **410**. In some embodiments, the shape of the inner wall **310**, choke pan **410**, the lower edge **510**, and upper edge **520** are selected such that the lower edge **520** and upper edge **510** interlock. This may, for example, arrest the inner wall **310** from rotating relative to the choke pan **410**, or arrest the choke pan **410** from rotating relative to the inner wall **310**. The inner wall **310** includes a plurality of ventilation holes **350** that in this implementation are different than the ventilation holes **170**. The ventilation holes **350** may have a larger diameter and may be formed in a single row instead of multiple rows.

(30) FIG. 6 is a front perspective view of the stove body **110** of an example stove and stand system **100**, with the outer wall **102**, stand **120**, top bezel **130**, and inner wall **310** removed for clarity, in accordance with aspects of the present disclosure. Visible are the fire grate **320**, choke pan **410**, ash pan **420**, and ash pan spacers **430**.

(31) FIG. 7 is a top perspective view of the stand **120** of an example stove and stand system, in an unfolded configuration, in accordance with aspects of the present disclosure. Visible are the central region **220**, legs **230**, inner links **240**, hinges **250**, outer links **260**, and feet **270**. As shown in FIG. 7, in the unfolded configuration, the stand **120** has a width W_1 that is greater than the outer diameter of the stove body, such that the stove body can rest removably on the stand.

(32) In the example in FIG. 7, each foot **270** extends laterally from an end of one of the outer links **260**. Each foot is rigidly connected to the outer link **260**. Accordingly, the foot **270** may be welded or otherwise fixed or formed at the end of the outer links **260**. In other implementations, the foot **270** may be attached via a hinge or other connection. Each foot **270** includes an interference arm **710** and a standoff **720**. The interference arm **710** extends transverse from its respective outer link **260** (e.g., in an upward direction as shown). The interference arms **710** are positioned such that they can arrest motion of the stove body in a lateral or radial direction (e.g., away from the central region **220**). Each foot **270** also includes a standoff **720** that extends transverse from its respective outer link **260** (e.g., in a downward direction as shown). In the example shown, the interference arm **710** and standoff **720** are formed together as a single structure (e.g., by stamping a piece of sheet metal), extending both above and below the outer link **260**. In an example, the foot **270** is attached to the outer link **260** with welds, solder, brazing, bolts, screws, rivets, pins, or otherwise. In some examples, each foot may also include a pad **730**. The pad **730** may for example be or include a rubbery material (e.g., silicone rubber) that provides heat resistance, thermal insulation, slip resistance, vibration resistance, cushioning, or combinations thereof.

(33) The standoff **720** and pad **730** are sized and shaped such that a top surface **740** of the stand **120**, on which the stove body will rest, is a height H above the placement surface (e.g., a wooden picnic table). Depending on the implementation, the bottom surface of the stove body may rest on at least a portion of the central region **220**, at least a portion of the inner links **240**, at least a portion of the outer links **260**, at least a portion of the interference arms **710**, or any combination thereof. In the implementation shown, the central region **220** is also an intersection of the inner links **240**. The inner links **240** cooperate with and overlap the outer links **260** in a manner that allows the inner link to fold from a position parallel to the inner link in only one direction. Accordingly, when loading applied to the stand **220**, the overlapping nature of the inner links **240** and the outer links

260 prevent the inner link from pivoting beyond parallel so that the central region **220** is maintained at the height **H**. That is, the overlapping nature of the inner links **240** and the outer links **260** may prevent the central region from collapsing. In the example shown, the central region and inner links **240** are all formed as a single monolithic component.

(34) FIG. **8** is a top perspective view of the stand **120** in a folded configuration. Visible are the central region **220**, legs **230**, inner links **240**, hinges **250**, outer links **260**, feet **270**, interference arms **710**, and standoffs **720**. In the example shown in FIG. **6**, the outer links **260** have been rotated downward around the hinges **250** to the limit of their travel (e.g., until the feet **270** come in contact with the inner links **240**). In the example shown in FIG. **6** each outer link **260** is separately rotatable, such that any number of legs (e.g., one leg, two legs, three legs, etc.) may be folded at any given time. When all of the legs are folded (e.g., in the example of FIG. **6**, when all four outer links are rotated downward to the limit of their travel), the stand **120** has a folded width **W2** that is smaller than the unfolded width **W1** shown in FIG. **7**.

(35) In some embodiments, the legs **230** telescope rather than fold. In such embodiments, the hinges **250** may be absent, and the inner links **240** may be wider than the outer links **260**, such that the outer links **260** can slide at least partially into the inner links **240**, thus shortening the legs **230** such that the stand **120** has a telescoped width **W2**.

(36) In the example shown in FIG. **8**, the outer links **260** fold in only a single direction from parallel, e.g., downward. It is noted that if the exemplary stand of FIG. **6** included outer links **360** that were capable of folding upward, the stand might collapse under its own weight or under the weight of the stove body. However, it should be understood that in other embodiments, the outer links may rotate upward, leftward, rightward, clockwise, counterclockwise, or otherwise, without departing from the spirit of the present disclosure, so long as the stand **120** in its unfolded state is capable of supporting the stove body, and in its folded state is capable of having a smaller profile. In some examples, as described herein, the stand **120** may be folded to a size that permits placement within the stove body.

(37) FIG. **9** is a front cross-sectional view of an example stove and stand system **100**, with the stand **120** placed inside the stove body **110**, in accordance with aspects of the present disclosure. Visible are the stove body **110**, top bezel or pot support **130**, outer wall **210**, top edge **450** of the outer wall **210**, bottom surface **215**, inner wall **310**, top lip **440** of inner wall **310**, fire grate **320**, choke pan **410**, ash pan **420**, and an ash pan spacer **430**.

(38) In the example shown in FIG. **9**, the stand **120** has been folded such that it has a folded width **W2** that is less than the inner diameter **ID** of the inner wall. Similarly, the stand has a folded height **F** that is smaller than a height **C** of the inner wall **310** above the fire grate **320**. Thus, the stand **120** in its folded state can be stored within the combustion chamber **330** of the stove body **110**.

Although shown with the width **W2** being less than an inner width **ID** of the stove body **110**, some implementations of the stand are greater than the width **ID** of the stove body **110**, but the width **W2** still fits within the volume of the combustion chamber **330**. That is, in some implementations, the stand may be sized to be introduced into the combustion chamber by introducing the stand on its side.

(39) Because the stand **120** is storable inside the stove body **110**, the stove and stand system **100** advantageously takes up less storage space than if the stand **120** were permanently attached to the stove body **110**, or non-foldable, or otherwise not storable within the stove body **110**. This storage configuration also makes the stove and stand system **100** more easily transportable (e.g., in a backpack, duffel bag, suitcase, or picnic basket).

(40) Depending on the implementation, the outer diameter **OD** of the stove body may fall in a range of between 6 inches and 16 inches, which the inner diameter **ID** is between 0.25" and 1.5" less than the outer diameter **OD**. The unfolded width **W1** of the stand may be between one-eighth inch and seven-eighths inch less than the outer diameter **OD** of the stove body, while the folded width **W2** may be between one half inch and six inches less than the inner diameter **ID**. However, in other

examples, different dimensions, whether larger or smaller, may be used instead or in addition.

(41) In an example, the top bezel or pot support **130**, outer wall **210**, bottom surface **215**, top lip **440**, choke pan **410**, ash pan **420**, and ash pan spacers are all formed from a metal such as stainless steel, and may for example be formed by stamping or rolling of sheet metal, or combinations thereof, with components or edges of components welded together as needed. In an example, the fire grate **320** is made from metal (e.g., stainless steel) bar or wire stock that is cut, bent, and welded to form the fire grate structure shown, or a different structure capable or serving the same function. In other embodiments, the fire grate **320** may also be made from stamped sheet metal such as stainless steel.

(42) As will be readily appreciated by those having ordinary skill in the art after becoming familiar with the teachings herein, the disclosed stove and stand system advantageously provides a means to operate a solid-fuel-burning (e.g., wood-burning) stove on a non-heatproof surface, by providing a stand to offset the bottom surface of the stove from the non-heatproof surface by a safe height. The stand is also foldable, such that it can be stored inside the stove, thus providing a storage or transportation volume for the stove and stand system that is comparable to that of the stove by itself.

(43) A number of variations are possible on the examples and embodiments described above. For example, the stove, stand, or portions thereof may be made from a variety of different materials, including but not limited to metals, ceramics, polymers, composites, or combinations thereof. Dimensions, both relative and absolute, may be different than those shown herein, without departing from the spirit of the present disclosure. The folding mechanism of the stand may be different than shown or described herein, so long as the width W1 of the unfolded configuration is sufficient to support the stove body as described, and the width W2 of the folded configuration is small enough that the stand can fit entirely inside the stove body in at least some orientations. The technology described herein may be applied to portable stoves, camp stoves, tabletop stoves, backyard firepits, or other types of stoves, and may further be applied to gas-burning or liquid-burning stoves.

(44) Accordingly, the logical operations making up the embodiments of the technology described herein may be referred to variously as operations, steps, objects, elements, components, or modules. Furthermore, it should be understood that these may occur or be performed or arranged in any order, unless explicitly claimed otherwise or a specific order is inherently necessitated by the claim language.

(45) All directional references e.g., upper, lower, inner, outer, upward, downward, left, right, lateral, front, back, top, bottom, above, below, vertical, horizontal, clockwise, counterclockwise, proximal, and distal are only used for identification purposes to aid the reader's understanding of the claimed subject matter, and do not create limitations, particularly as to the position, orientation, or use of the stove and stand system. Connection references, e.g., attached, coupled, connected, joined, or "in communication with" are to be construed broadly and may include intermediate members between a collection of elements and relative movement between elements unless otherwise indicated. As such, connection references do not necessarily imply that two elements are directly connected and in fixed relation to each other. The term "or" shall be interpreted to mean "and/or" rather than "exclusive or." The word "comprising" does not exclude other elements or steps, and the indefinite article "a" or "an" does not exclude a plurality. Unless otherwise noted in the claims, stated values shall be interpreted as illustrative only and shall not be taken to be limiting.

(46) The above specification, examples and data provide a complete description of the structure and use of exemplary embodiments of the stove and stand system as defined in the claims. Although various embodiments of the claimed subject matter have been described above with a certain degree of particularity, or with reference to one or more individual embodiments, those skilled in the art could make numerous alterations to the disclosed embodiments without departing from the spirit or scope of the claimed subject matter.

(47) Still other embodiments are contemplated. It is intended that all matter contained in the above description and shown in the accompanying drawings shall be interpreted as illustrative only of particular embodiments and not limiting. Changes in detail or structure may be made without departing from the basic elements of the subject matter as defined in the following claims.

Claims

1. A system for burning a combustible fuel above a placement surface, the system comprising: a body, comprising: an upper portion; a lower portion; an outer wall extending between the upper portion and the lower portion; an inner wall that is tubular in shape so as to at least partially define a fuel combustion chamber, the inner wall being spaced from the outer wall to: form a gap between the inner wall and the outer wall, and permit an upward flow of air in the gap between the inner wall and the outer wall; and one or more inner ventilation holes proximate the upper portion of the body, the one or more inner ventilation holes being configured to permit airflow from the gap between the inner wall and the outer wall in a manner that facilitates secondary combustion of compounds emitted by fuel combustion in the fuel combustion chamber; and a plurality of legs configured to support the body in a position spaced above the placement surface, wherein each leg of the plurality of legs extends outwardly from beneath the body, and radially beyond the outer wall of the body, at least when the body is supported by the plurality of legs in the position spaced above the placement surface, wherein the plurality of legs at least partially forms a stand, and wherein the stand comprises the plurality of legs and a central intersection from which each leg of the plurality of legs radially extends.
2. The system of claim 1, wherein, in a first configuration of the system, the body is adapted to sit on the stand so that the stand supports the body in the position spaced above the placement surface.
3. The system of claim 2, wherein, in a second configuration of the system, the body is removable from the stand.
4. The system of claim 1, wherein the body further comprises one or more outer ventilation holes proximate the lower portion of the body, the one or more outer ventilation holes being configured to permit airflow into the gap between the inner wall and the outer wall.
5. The system of claim 4, wherein the one or more outer ventilation holes are formed in a plurality of rows proximate the lower portion of the body.
6. The system of claim 1, wherein each leg of the plurality of legs comprises: a hinge; and an outer link pivotable about the hinge between a first state and a second state.
7. The system of claim 6, wherein, in a first configuration of the system, the outer link of each leg of the plurality of legs is pivoted about the corresponding hinge to the second state to support the body in the position spaced above the placement surface; and wherein, in a second configuration of the system, the outer link of each leg of the plurality of legs is pivoted about the corresponding hinge to the first state.
8. The system of claim 6, wherein each leg of the plurality of legs further comprises: an inner link to which the corresponding outer link is pivotably connected via the corresponding hinge.
9. The system of claim 6, wherein each leg of the plurality of legs further comprises: a foot connected to the corresponding outer link, opposite the corresponding hinge, and configured to contact the placement surface when the corresponding outer link is in the second state.
10. The system of claim 9, wherein at least a portion of the foot of each leg of the plurality of legs extends at an angle from the corresponding outer link.
11. The system of claim 1, wherein the body further comprises a bottom surface disposed below the fuel combustion chamber.
12. The system of claim 11, wherein each leg of the plurality of legs is configured to contact the bottom surface at least when the body is supported by the plurality of legs in the position spaced above the placement surface.

13. A system for burning a combustible fuel above a placement surface, the system comprising: a body, comprising: an upper portion; a lower portion; an outer wall extending between the upper portion and the lower portion; an inner wall that is tubular in shape so as to at least partially define a fuel combustion chamber, the inner wall being spaced from the outer wall to: form a gap between the inner wall and the outer wall, and permit an upward flow of air in the gap between the inner wall and the outer wall; and one or more inner ventilation holes proximate the upper portion of the body, the one or more inner ventilation holes being configured to permit airflow from the gap between the inner wall and the outer wall in a manner that facilitates secondary combustion of compounds emitted by fuel combustion in the fuel combustion chamber; and a plurality of legs configured to support the body in a position spaced above the placement surface, wherein each leg of the plurality of legs extends outwardly from beneath the body, and radially beyond the outer wall of the body, at least when the body is supported by the plurality of legs in the position spaced above the placement surface, wherein the plurality of legs at least partially forms a stand, wherein, in a first configuration of the system, the body is adapted to sit on the stand so that the stand supports the body in the position spaced above the placement surface, wherein, in a second configuration of the system, the body is removable from the stand, and wherein, in the second configuration of the system, the stand is adapted to fit within the fuel combustion chamber of the body.

14. The system of claim 13, wherein the body further comprises one or more outer ventilation holes proximate the lower portion of the body, the one or more outer ventilation holes being configured to permit airflow into the gap between the inner wall and the outer wall.

15. The system of claim 14, wherein the one or more outer ventilation holes are formed in a plurality of rows proximate the lower portion of the body.

16. The system of claim 13, wherein each leg of the plurality of legs comprises: a hinge; and an outer link pivotable about the hinge between a first state and a second state.

17. The system of claim 16, wherein, in the first configuration of the system, the outer link of each leg of the plurality of legs is pivoted about the corresponding hinge to the second state to support the body in the position spaced above the placement surface; and wherein, in the second configuration of the system, the outer link of each leg of the plurality of legs is pivoted about the corresponding hinge to the first state.

18. The system of claim 16, wherein each leg of the plurality of legs further comprises: an inner link to which the corresponding outer link is pivotably connected via the corresponding hinge.

19. The system of claim 16, wherein each leg of the plurality of legs further comprises: a foot connected to the corresponding outer link, opposite the corresponding hinge, and configured to contact the placement surface when the corresponding outer link is in the second state.

20. The system of claim 19, wherein at least a portion of the foot of each leg of the plurality of legs extends at an angle from the corresponding outer link.

21. The system of claim 13, wherein the body further comprises a bottom surface disposed below the fuel combustion chamber.

22. The system of claim 21, wherein each leg of the plurality of legs is configured to contact the bottom surface at least when the body is supported by the plurality of legs in the position spaced above the placement surface.

23. A system for burning a combustible fuel above a placement surface, the system comprising: a body, comprising: an upper portion; a lower portion; an outer wall extending between the upper portion and the lower portion; an inner wall that is tubular in shape so as to at least partially define a fuel combustion chamber, the inner wall being spaced from the outer wall to: form a gap between the inner wall and the outer wall, and permit an upward flow of air in the gap between the inner wall and the outer wall; and one or more inner ventilation holes proximate the upper portion of the body, the one or more inner ventilation holes being configured to permit airflow from the gap between the inner wall and the outer wall in a manner that facilitates secondary combustion of compounds emitted by fuel combustion in the fuel combustion chamber; and a plurality of legs

configured to support the body in a position spaced above the placement surface, wherein each leg of the plurality of legs extends outwardly from beneath the body, and radially beyond the outer wall of the body, at least when the body is supported by the plurality of legs in the position spaced above the placement surface, wherein the body further comprises one or more outer ventilation holes proximate the lower portion of the body, the one or more outer ventilation holes being configured to permit airflow into the gap between the inner wall and the outer wall, and wherein each ventilation hole of the one or more outer ventilation holes is sized smaller than each ventilation hole of the one or more inner ventilation holes.

24. The system of claim 23, wherein each leg of the plurality of legs comprises: a hinge; and an outer link pivotable about the hinge between a first state and a second state.

25. The system of claim 24, wherein, in a first configuration of the system, the outer link of each leg of the plurality of legs is pivoted about the corresponding hinge to the second state to support the body in the position spaced above the placement surface; and wherein, in a second configuration of the system, the outer link of each leg of the plurality of legs is pivoted about the corresponding hinge to the first state.

26. The system of claim 24, wherein each leg of the plurality of legs further comprises: an inner link to which the corresponding outer link is pivotably connected via the corresponding hinge.

27. The system of claim 24, wherein each leg of the plurality of legs further comprises: a foot connected to the corresponding outer link, opposite the corresponding hinge, and configured to contact the placement surface when the corresponding outer link is in the second state.

28. The system of claim 27, wherein at least a portion of the foot of each leg of the plurality of legs extends at an angle from the corresponding outer link.

29. The system of claim 23, wherein the plurality of legs at least partially forms a stand.

30. The system of claim 29, wherein, in a first configuration of the system, the body is adapted to sit on the stand so that the stand supports the body in the position spaced above the placement surface.

31. The system of claim 30, wherein, in a second configuration of the system, the body is removable from the stand.

32. The system of claim 23, wherein the body further comprises a bottom surface disposed below the fuel combustion chamber.

33. The system of claim 32, wherein each leg of the plurality of legs is configured to contact the bottom surface at least when the body is supported by the plurality of legs in the position spaced above the placement surface.

34. A system for burning a combustible fuel above a placement surface, the system comprising: a body, comprising: an upper portion; a lower portion; an outer wall extending between the upper portion and the lower portion; an inner wall that is tubular in shape so as to at least partially define a fuel combustion chamber, the inner wall being spaced from the outer wall to: form a gap between the inner wall and the outer wall, and permit an upward flow of air in the gap between the inner wall and the outer wall; and one or more inner ventilation holes proximate the upper portion of the body, the one or more inner ventilation holes being configured to permit airflow from the gap between the inner wall and the outer wall in a manner that facilitates secondary combustion of compounds emitted by fuel combustion in the fuel combustion chamber; and a plurality of legs configured to support the body in a position spaced above the placement surface, wherein each leg of the plurality of legs extends outwardly from beneath the body, and radially beyond the outer wall of the body, at least when the body is supported by the plurality of legs in the position spaced above the placement surface, wherein each leg of the plurality of legs comprises: a hinge; and an outer link pivotable about the hinge between a first state and a second state, wherein, in a first configuration of the system, the outer link of each leg of the plurality of legs is pivoted about the corresponding hinge to the second state to support the body in the position spaced above the placement surface, wherein, in a second configuration of the system, the outer link of each leg of

the plurality of legs is pivoted about the corresponding hinge to the first state, and wherein, in the second configuration of the system, each leg of the plurality of legs is adapted to extend entirely within a boundary defined by the outer wall of the body.

35. The system of claim 34, wherein, in the second configuration of the system, each leg of the plurality of legs is further adapted to extend entirely within another boundary defined by the inner wall of the body.

36. The system of claim 34, wherein each leg of the plurality of legs further comprises: an inner link to which the corresponding outer link is pivotably connected via the corresponding hinge.

37. The system of claim 36, wherein the plurality of legs at least partially forms a stand.

38. The system of claim 34, wherein the plurality of legs at least partially forms a stand.

39. The system of claim 38, wherein, in the first configuration of the system, the body is adapted to sit on the stand so that the stand supports the body in the position spaced above the placement surface.

40. The system of claim 39, wherein, in the second configuration of the system, the body is removable from the stand.

41. The system of claim 34, wherein the body further comprises one or more outer ventilation holes proximate the lower portion of the body, the one or more outer ventilation holes being configured to permit airflow into the gap between the inner wall and the outer wall.

42. The system of claim 41, wherein the one or more outer ventilation holes are formed in a plurality of rows proximate the lower portion of the body.

43. The system of claim 34, wherein each leg of the plurality of legs further comprises: a foot connected to the corresponding outer link, opposite the corresponding hinge, and configured to contact the placement surface when the corresponding outer link is in the second state.

44. The system of claim 43, wherein at least a portion of the foot of each leg of the plurality of legs extends at an angle from the corresponding outer link.

45. The system of claim 34, wherein the body further comprises a bottom surface disposed below the fuel combustion chamber.

46. The system of claim 45, wherein each leg of the plurality of legs is configured to contact the bottom surface at least when the body is supported by the plurality of legs in the position spaced above the placement surface.

47. A system for burning a combustible fuel above a placement surface, the system comprising: a body, comprising: an upper portion; a lower portion; an outer wall extending between the upper portion and the lower portion; an inner wall that is tubular in shape so as to at least partially define a fuel combustion chamber, the inner wall being spaced from the outer wall to: form a gap between the inner wall and the outer wall, and permit an upward flow of air in the gap between the inner wall and the outer wall; and one or more inner ventilation holes proximate the upper portion of the body, the one or more inner ventilation holes being configured to permit airflow from the gap between the inner wall and the outer wall in a manner that facilitates secondary combustion of compounds emitted by fuel combustion in the fuel combustion chamber; and a plurality of legs configured to support the body in a position spaced above the placement surface, wherein each leg of the plurality of legs extends outwardly from beneath the body, and radially beyond the outer wall of the body, at least when the body is supported by the plurality of legs in the position spaced above the placement surface, wherein each leg of the plurality of legs comprises: a hinge; an outer link pivotable about the hinge between a first state and a second state; and an inner link to which the corresponding outer link is pivotably connected via the corresponding hinge, wherein the plurality of legs at least partially forms a stand, and wherein the stand comprises the plurality of legs and a central intersection from which the inner link of each leg of the plurality of legs radially extends.

48. The system of claim 47, wherein each leg of the plurality of legs further comprises: a foot connected to the corresponding outer link, opposite the corresponding hinge, and configured to contact the placement surface when the corresponding outer link is in the second state.

49. The system of claim 48, wherein at least a portion of the foot of each leg of the plurality of legs extends at an angle from the corresponding outer link.
50. The system of claim 47, wherein the body further comprises a bottom surface disposed below the fuel combustion chamber.
51. The system of claim 50, wherein each leg of the plurality of legs is configured to contact the bottom surface at least when the body is supported by the plurality of legs in the position spaced above the placement surface.
52. The system of claim 47, wherein, in a first configuration of the system, the body is adapted to sit on the stand so that the stand supports the body in the position spaced above the placement surface.
53. The system of claim 52, wherein, in a second configuration of the system, the body is removable from the stand.
54. The system of claim 47, wherein the body further comprises one or more outer ventilation holes proximate the lower portion of the body, the one or more outer ventilation holes being configured to permit airflow into the gap between the inner wall and the outer wall.
55. The system of claim 54, wherein the one or more outer ventilation holes are formed in a plurality of rows proximate the lower portion of the body.
56. The system of claim 47, wherein, in a first configuration of the system, the outer link of each leg of the plurality of legs is pivoted about the corresponding hinge to the second state to support the body in the position spaced above the placement surface; and wherein, in a second configuration of the system, the outer link of each leg of the plurality of legs is pivoted about the corresponding hinge to the first state.
-