

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12390849
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Davies; Peter J. et al.

---

### Expansion tool

---

#### Abstract

An expansion tool includes a housing, a collar rotatably coupled to the housing, the collar including a plurality of slots, a plurality of jaws, each jaw having a projection received in a corresponding one of the plurality of slots such that the jaws are coupled for co-rotation with the collar, a mandrel moveable relative to the housing between a retracted position and an extended position, the mandrel engageable with the jaws to expand the jaws in response to movement of the mandrel to the extended position, and a cone received within the plurality of jaws and engageable with inner surfaces of the plurality of jaws. The mandrel is configured to engage the cone to move the cone with the mandrel to expand the jaws as the mandrel moves toward the extended position, and a rotation mechanism is configured to incrementally rotate the collar.

---

<b>Inventors:</b>	<b>Davies; Peter J. (Milwaukee, WI), Kuhls; Alex R. (Brookfield, WI)</b>
<b>Applicant:</b>	<b>MILWAUKEE ELECTRIC TOOL CORPORATION (Brookfield, WI)</b>
<b>Family ID:</b>	<b>1000008762733</b>
<b>Assignee:</b>	<b>MILWAUKEE ELECTRIC TOOL CORPORATION (Brookfield, WI)</b>
<b>Appl. No.:</b>	<b>18/482992</b>
<b>Filed:</b>	<b>October 09, 2023</b>

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20240033805 A1	Feb. 01, 2024

#### Related U.S. Application Data

continuation parent-doc US 17716773 20220408 US 11779990 child-doc US 18482992  
us-provisional-application US 63303732 20220127  
us-provisional-application US 63172874 20210409

---

## Publication Classification

**Int. Cl.:** B21D39/20 (20060101); B21D37/04 (20060101); B21D37/18 (20060101); B25F5/00 (20060101)

**U.S. Cl.:**

**CPC** B21D39/20 (20130101); B21D37/04 (20130101); B21D37/18 (20130101); B25F5/001 (20130101);

## Field of Classification Search

**CPC:** B21D (37/04); B21D (41/021); B21D (41/028); B21D (41/025); B21D (39/08); B25F (5/001); B29C (57/06); B29C (57/04); B29C (57/00)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1404819	12/1921	Wiedeke	N/A	N/A
1752408	12/1929	Zein	N/A	N/A
2085447	12/1936	Plaine	N/A	N/A
2725918	12/1954	Deshler	N/A	N/A
2737996	12/1955	Toth	N/A	N/A
2835307	12/1957	Jorgensen	N/A	N/A
2999529	12/1960	Wlodzimierz	N/A	N/A
3550424	12/1969	Rast	N/A	N/A
3677684	12/1971	Platz	N/A	N/A
3753635	12/1972	Barnett	N/A	N/A
3857666	12/1973	Barnett	N/A	N/A
3861847	12/1974	Barnett	N/A	N/A
3888102	12/1974	Nigido	N/A	N/A
3940227	12/1975	Strasser	N/A	N/A
3947950	12/1975	Adams	N/A	N/A
4034591	12/1976	Rothenberger	N/A	N/A
4107249	12/1977	Murai et al.	N/A	N/A
4144735	12/1978	Rothenberger	N/A	N/A
4154083	12/1978	Rothenberger	N/A	N/A
4397173	12/1982	Eftefield et al.	N/A	N/A
4425783	12/1983	Rast	N/A	N/A
4603890	12/1985	Huppee	N/A	N/A
4733551	12/1987	Bryant et al.	N/A	N/A
4735078	12/1987	Wesebaum	N/A	N/A
4890472	12/1989	Rothenberger	N/A	N/A
5046349	12/1990	Velte	N/A	N/A
5090226	12/1991	Takeoka et al.	N/A	N/A
5090230	12/1991	Koskinen	N/A	N/A
5135268	12/1991	McNaughton et al.	N/A	N/A
5243845	12/1992	Velte	N/A	N/A

5261709	12/1992	McNaughton et al.	N/A	N/A
5704244	12/1997	Halasz et al.	N/A	N/A
5727414	12/1997	Halasz et al.	N/A	N/A
5744085	12/1997	Soberg	N/A	N/A
5879033	12/1998	Hansel et al.	N/A	N/A
5943891	12/1998	Takagi et al.	N/A	N/A
6199915	12/2000	Becker	N/A	N/A
6783160	12/2003	Rowley	N/A	N/A
6862766	12/2004	Geurts	N/A	N/A
7014214	12/2005	Kaneko	N/A	N/A
7065995	12/2005	Frenken	N/A	N/A
7128560	12/2005	Tandart	N/A	N/A
7325436	12/2007	Cheng	N/A	N/A
7490499	12/2008	Suzuki et al.	N/A	N/A
7516990	12/2008	Jamison et al.	N/A	N/A
7681636	12/2009	Roggeband et al.	N/A	N/A
7735877	12/2009	Ito et al.	N/A	N/A
7806213	12/2009	Inoue et al.	N/A	N/A
7922475	12/2010	Gueit	N/A	N/A
8302448	12/2011	Woelcken et al.	N/A	N/A
8303295	12/2011	Gueit	N/A	N/A
8371409	12/2012	Inoue et al.	N/A	N/A
8511133	12/2012	Chen	N/A	N/A
8517715	12/2012	Thorson	425/467	B29D 23/001
8534711	12/2012	Inoue et al.	N/A	N/A
8562331	12/2012	Schramm et al.	N/A	N/A
8763439	12/2013	Thorson et al.	N/A	N/A
9027966	12/2014	Altmann et al.	N/A	N/A
9089889	12/2014	Kohnen	N/A	N/A
9248617	12/2015	Lundequist et al.	N/A	N/A
9808852	12/2016	Frenken	N/A	N/A
9862137	12/2017	Dickert et al.	N/A	N/A
9914260	12/2017	Ellice	N/A	N/A
9975289	12/2017	Li et al.	N/A	N/A
9993961	12/2017	Dickert et al.	N/A	N/A
10000007	12/2017	Dickert et al.	N/A	N/A
10195783	12/2018	Dickert et al.	N/A	N/A
10406586	12/2018	Frenken	N/A	N/A
2005/0093298	12/2004	Takayanagi	N/A	N/A
2006/0201228	12/2005	Rothenberger	N/A	N/A
2007/0057393	12/2006	Hartmann et al.	N/A	N/A
2008/0122222	12/2007	Sheppard	N/A	N/A
2008/0160130	12/2007	Gueit	N/A	N/A
2010/0308503	12/2009	Schramm	264/312	B29C 57/045
2011/0239674	12/2010	Defilippi	N/A	N/A
2013/0341831	12/2012	Thorson et al.	N/A	N/A
2018/0029286	12/2017	Li	N/A	B21D 41/028
2018/0128323	12/2017	Carlson	N/A	N/A
2019/0351605	12/2018	Trickle	N/A	N/A
2020/0094465	12/2019	Lindsey	N/A	B29C 57/04

2020/0261958	12/2019	Davies	N/A	N/A
2020/0261959	12/2019	Wekwert et al.	N/A	N/A
2021/0023767	12/2020	Brochman	N/A	N/A
2021/0254773	12/2020	Adelman	N/A	B29C 57/04
2022/0168793	12/2021	Davies et al.	N/A	N/A

## FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
201346602	12/2008	CN	N/A
204018564	12/2013	CN	N/A
107838304	12/2017	CN	N/A
207308769	12/2017	CN	N/A
497609	12/1929	DE	N/A
2800079	12/1977	DE	N/A
3439522	12/1984	DE	N/A
4003994	12/1990	DE	N/A
4005474	12/1990	DE	N/A
19730054	12/1998	DE	N/A
19924695	12/1999	DE	N/A
19963885	12/2000	DE	N/A
10063517	12/2001	DE	N/A
20301139	12/2003	DE	N/A
102005033482	12/2006	DE	N/A
102006015368	12/2006	DE	N/A
202008002265	12/2007	DE	N/A
202008002266	12/2007	DE	N/A
102007053518	12/2008	DE	N/A
102008061441	12/2008	DE	N/A
102008064320	12/2009	DE	N/A
102013208330	12/2013	DE	N/A
0234283	12/1986	EP	N/A
0397570	12/1989	EP	N/A
0462719	12/1990	EP	N/A
0567742	12/1992	EP	N/A
0718057	12/1995	EP	N/A
0878287	12/1997	EP	N/A
0967427	12/1998	EP	N/A
1118401	12/2000	EP	N/A
1278001	12/2002	EP	N/A
1930640	12/2007	EP	N/A
2090384	12/2008	EP	N/A
3520923	12/2018	EP	N/A
2451235	12/1979	FR	N/A
2645052	12/1989	FR	N/A
1485098	12/1976	GB	N/A
1524149	12/1977	GB	N/A
8800503	12/1987	WO	N/A
96020798	12/1995	WO	N/A
96040457	12/1995	WO	N/A
0189736	12/2000	WO	N/A

## OTHER PUBLICATIONS

International Search Report and Written Opinion for Application No. PCT/US2022/024077 dated Jul. 27, 2022 (8 pages). cited by applicant

Partial Supplementary European Search Report for Application No. 22785554.1 dated Feb. 28, 2025 (15 pages). cited by applicant

Extended European Search Report for Application No. 22785554.1 dated May 19, 2025 (12 pages). cited by applicant

---

*Primary Examiner:* Kim; Bobby Yeonjin

*Attorney, Agent or Firm:* Michael Best & Friedrich LLP

---

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/716,773, filed Apr. 8, 2022, now U.S. Pat. No. 11,779,990, which claims priority to U.S. Provisional Patent Application No. 63/172,874, filed Apr. 9, 2021, and to U.S. Provisional Patent Application No. 63/303,732, filed Jan. 27, 2022, the entire contents of each of which are incorporated by reference herein.

### FIELD

(1) The present disclosure relates to pipe and tubing expansion tools. More particularly, the present disclosure relates to PEX (cross-linked polyethylene) expansion tools.

### BACKGROUND

(2) PEX tubing is commonly used in plumbing applications as a substitute for copper pipe. PEX tubing can be coupled to fittings in various ways. Crimp rings or clamp rings can be compressed onto the outside of PEX tubing over a fitting to couple the PEX tubing to the fitting. Alternatively, the PEX tube can be expanded, and the fitting inserted into the expanded end of the PEX tube. The PEX tube elastically recovers around the fitting to form a tight connection. Tools used to expand PEX tube for this purpose are referred to as PEX expansion tools.

### SUMMARY

(3) The present invention provides, in a first aspect, an expansion tool including a housing, a collar rotatably coupled to the housing, the collar including a plurality of slots, a plurality of jaws, each jaw having a projection received in a corresponding one of the plurality of slots such that the jaws are coupled for co-rotation with the collar, a mandrel moveable relative to the housing between a retracted position and an extended position, the mandrel engageable with the jaws to expand the jaws in response to movement of the mandrel to the extended position, and a cone received within the plurality of jaws and engageable with inner surfaces of the plurality of jaws. The mandrel is configured to engage the cone to move the cone with the mandrel to expand the jaws as the mandrel moves toward the extended position, and a rotation mechanism is configured to incrementally rotate the collar.

(4) The present invention provides, in another aspect, an expansion tool including a housing, a motor supported in the housing, a plurality of jaws, a mandrel moveable relative to the housing between a retracted position and an extended position, the mandrel engageable with the jaws to expand the jaws in response to movement of the mandrel to the extended position, and a drive mechanism configured to convert rotational input from the motor into translational movement of the mandrel between the retracted position and the extended position. The drive mechanism is operable in a high speed configuration and a low speed configuration.

(5) The present invention provides, in another aspect, an expansion tool including a housing, a collar rotatably coupled to the housing, a plurality of jaws coupled for co-rotation with the collar, a mandrel moveable relative to the housing between a retracted position and an extended position, the mandrel engageable with the jaws to expand the jaws in response to movement of the mandrel to the extended position, and a cone received within the plurality of jaws and engageable with inner surfaces of the plurality of jaws. The mandrel is configured to engage the cone to move the cone with the mandrel to expand the jaws as the mandrel moves toward the extended position, and the cone includes means for containing grease to lubricate the inner surfaces of the plurality of jaws.

(6) Other features and aspects of the invention will become apparent by consideration of the detailed description and accompanying drawings. Any feature(s) described herein in relation to one aspect or embodiment may be combined with any other feature(s) described herein in relation to any other aspect or embodiment as appropriate and applicable.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a perspective view of an expansion tool according to an embodiment of the present disclosure.
- (2) FIG. 2 is a cross-sectional view illustrating a drive assembly of the expansion tool of FIG. 1.
- (3) FIG. 3 is a perspective view of the expansion tool of FIG. 1, illustrating a shift actuator of the expansion tool.
- (4) FIG. 4 is a perspective view of the expansion tool of FIG. 1 with portions removed, illustrating the shift actuator.
- (5) FIG. 5 is a perspective view of a portion of the expansion tool of FIG. 1, illustrating a rotation collar.
- (6) FIG. 6A is a perspective view illustrating a first embodiment of a head for use with the expansion tool of FIG. 1.
- (7) FIG. 6B is a perspective view illustrating a second embodiment of a head for use with the expansion tool of FIG. 1.
- (8) FIG. 7 is an exploded view illustrating a portion of the expansion tool of FIG. 1 including the rotation collar and the head.
- (9) FIG. 8 is a cross-sectional view illustrating the head of FIG. 6B in a partially installed position on the expansion tool of FIG. 1.
- (10) FIG. 9 is a cross-sectional view illustrating the head of FIG. 6B in a fully installed position on the expansion tool of FIG. 1.
- (11) FIG. 10A is a cross-sectional view illustrating a third embodiment of a head for use with the expansion tool of FIG. 1.
- (12) FIG. 10B is a perspective view of an inner cone of the head of FIG. 10A.
- (13) FIG. 11A is a cross-sectional view illustrating a fourth embodiment of a head for use with the expansion tool of FIG. 1.
- (14) FIG. 11B is a perspective view of an inner cone of the head of FIG. 11A.

### DETAILED DESCRIPTION

(15) Before any embodiments of the invention are explained in detail, it is to be understood that the invention is not limited in its application to the details of construction and the arrangement of components set forth in the following description or illustrated in the following drawings. The invention is capable of other embodiments and of being practiced or of being carried out in various ways.

(16) FIG. 1 illustrates an expansion tool 10 usable to expand PEX tubing prior to inserting a fitting. The expansion tool 10 includes a housing 12 with a handle portion 14 configured to be gripped by

a user during operation of the expansion tool **10**. The illustrated housing **12** also includes a motor housing portion **18** positioned in front of the handle portion **14**, and a drive housing portion **22** positioned above the motor housing portion **18** and the handle portion **14**. An actuator **26** (e.g., a trigger) for operating the expansion tool **10** is positioned on the handle portion **14**. A motor **30** (e.g., a brushless DC electric motor) is supported within the motor housing portion **18**, and a drive mechanism **34** is supported within the drive housing portion **22** (FIG. 2).

(17) The illustrated expansion tool **10** includes a battery **46** (FIG. 1) configured to provide electrical power to the motor **30** (e.g., in response to depressing the actuator **26**). The battery **46** is preferably a rechargeable battery pack with a plurality of lithium-based cells and is removably coupled to a battery receptacle **48** located at a base of the handle **14** (FIG. 1). In some embodiments, the battery **46** has a nominal output voltage of about 18 volts. In other embodiments, the battery **46** has a nominal output voltage of about 12 volts. In other embodiments, the battery **46** may have other nominal output voltages (e.g., 24 volts, 36 volts, 40 volts, etc.).

(18) Referring to FIG. 2, the motor **30** includes a rotor or motor shaft **38** that rotates about a first axis or motor axis **42** to provide a rotational input to the drive mechanism **34**. In the illustrated embodiment, the motor shaft **38** is rotationally supported by three bearings **43** spaced along the motor axis **42**. The drive mechanism **34** converts the rotational input from the motor shaft **38** into a translational movement of a mandrel **50** along a second axis or mandrel axis **54**. In the illustrated embodiment, the mandrel axis **54** is perpendicular to the motor axis **42**, which contributes to a compact overall length of the expansion tool **10**.

(19) The illustrated drive mechanism **34** includes a first gear **58** coupled for co-rotation with the motor shaft **38** about the motor axis **42**, a second gear **62** meshed with the first gear **58**, and a third gear **66** meshed with the second gear **62**. The drive mechanism **34** provides a speed reduction and torque increase from the motor shaft **38** to the third gear **66**. For example, in the illustrated embodiment, the second gear **62** is larger in diameter and includes a greater number of teeth than the first gear **58**, and the third gear **66** is larger in diameter and includes a greater number of teeth than the second gear **62**.

(20) With continued reference to FIG. 2, the third gear **66** is coupled for co-rotation with a shaft **70**, such that the third gear **66** and the shaft **70** co-rotate together about a third axis or drive axis **74** that is parallel to the motor axis **42** and perpendicular to the mandrel axis **54**. The shaft **70** provides a rotational input to a transmission **76**, which in the illustrated embodiment is a multi-stage planetary transmission (e.g., a four-stage planetary transmission). In other embodiments, other types of transmissions **76** may be used. In the illustrated embodiment, the transmission **76** is shiftable to provide the expansion tool **10** with two different operating speeds.

(21) More specifically, with reference to FIGS. 3-4, the expansion tool **10** includes a shifting assembly **1000** which may alternate between a high speed configuration or a low speed configuration. The illustrated shifting assembly **1000** includes an actuator **1002** positioned on the housing **12** of the expansion tool **10** and a shifting arm **1004** connected to the actuator **1002**. The actuator **1002** is located on a rear side of the housing **12**, above the handle portion **14** in the illustrated embodiment; however, the actuator **1002** may be located in other positions on the housing **12** in other embodiments.

(22) The shifting arm **1004** is coupled to a movable ring gear **1008** (FIG. 2), which is part of an intermediate stage of the multi-stage planetary transmission **76**. The shifting arm **1004** is pivotable to translate movement of the actuator **1002** into axial movement of the movable ring gear **1008**. When the shifting assembly **1000** is in the low speed configuration, the movable ring gear **1008** engages a locking ring **1010**, which prevents the ring gear **1008** from rotating. When the shifting assembly **1000** is in the high speed configuration, the movable ring gear **1008** disengages from the locking ring **1010**, permitting free rotation of the ring gear **1008**.

(23) Referring to FIG. 4, the shifting assembly **1000** includes a shifting detector **1006** configured to detect when the shifting assembly **1000** is actuated between the high speed configuration and the

low speed configuration. In the illustrated embodiment, the shifting detector **1006** includes a micro switch **1007** with a spring lever **1009** that extends into the path of the shifting arm **1004**. The shifting arm **1004** engages the spring lever **1009** to close the micro switch **1007** when the shifting assembly **1000** is in the high speed configuration. When the shifting assembly **1000** is moved to the low speed configuration, the spring lever **1009** moves with the shifting arm **1004** to open the micro switch **1007**. In other embodiments, the position of the micro switch **1007** may be varied such that the micro switch **1007** is closed when the shifting assembly **1000** is in the low speed configuration and opens when the shifting assembly **1000** is moved to the high speed configuration.

(24) The shifting detector **1006** is electrically coupled to a controller **1010** (FIG. 1) of the expansion tool **10**. The controller **1010** includes a plurality of electrical and electronic components that provide power, operational control, and protection to the components and modules within the controller **1010**. In particular, the controller **1010** may include, among other things, an electronic processor (e.g., a programmable microprocessor, microcontroller, or similar device), non-transitory, machine-readable memory, an input/output interface, and the like. The components and modules of the controller **1010** may be mounted on a PCB supported within the housing **12**. The electronic processor is communicatively coupled to the memory and configured to retrieve from memory and execute, among other things, instructions related to the control processes and methods described herein.

(25) The shifting detector **1006** provides a signal to the controller **1010** of the expansion tool **10** to indicate if a shift is taking place. For example, the controller **1010** may determine that a shift from the low speed configuration to the high speed configuration is taking place if the micro switch **1007** changes state from its open position to its closed position. The controller **1010** may similarly determine that a shift from the high speed configuration to the low speed configuration is taking place if the micro switch **1007** changes state from its closed position to its open position. In other embodiments, the shifting detector **1006** may include other sensors capable of determining whether a shift is taking place. For example, in other embodiments, the shifting detector **1006** may include one or more optical sensors, magnetic sensors, position sensors, or the like capable of determining whether a shift is taking place by monitoring movement of the actuator **1002**, ring gear **1008**, and/or the shifting arm **1004**.

(26) In the illustrated embodiment, the expansion tool **10** includes a light source **1012** positioned on a front side of the housing **12** (FIG. 1). The light source **1012** may be configured to illuminate a workpiece during operation of the expansion tool **10**. The light source **1012** may also be controlled by the controller **1010** to provide an operator with visual feedback associated with operation of the shifting assembly **1000**.

(27) In operation, the shifting assembly **1000** may be in either the high speed configuration or the low speed configuration. When the operator depresses the actuator **26** and energizes the motor **30**, the controller **1010** monitors the shifting detector **1006**. If the operator attempts to shift the shifting assembly **1000** between the high speed position and the low speed position by actuating the actuator **1002** while the motor **30** is energized, the shifting detector **1006** provides a signal to the controller **1010** indicating that a shift is occurring. In response to this signal, the controller **1010** automatically deenergizes the motor **30**. By deenergizing the motor **30**, the gears of the transmission **76** slow, and adverse impacts on the gears that may occur by shifting during operation are lessened. In some embodiments, the controller **1010** may also control the light source **1012** to produce a predetermined blinking pattern in order to communicate to the operator that the shut off was intentional. In other embodiments, other indicators, including but not limited to audible indicators, colored LEDs, LED/LCD displays, or the like may be used to alert the user to the intentional shut-off of the motor **30**. The operator can then resume operation by depressing the actuator **26** once more, thereby energizing the motor **30**.

(28) With reference to FIG. 2, the illustrated transmission **76** includes an output member **78** (i.e., a carrier of the final stage of the planetary transmission **76**) coupled to a drive shaft **82** such that the



drive shaft **82** co-rotates with the output member **78** about the drive axis **74**. A cam **86** is coupled for co-rotation with the drive shaft **82**. The cam **86** includes a contact surface **90** at its outer periphery. The contact surface **90** engages a follower or roller **94**, which in turn is coupled to the mandrel **50** via a pin **98** extending vertically through the mandrel **50**. The follower **94** is biased into engagement with the contact surface **90** of the cam **86** by a spring **102** acting on the mandrel **50**. (29) The contact surface **90** of the cam **86** has a variable radius such that rotation of the cam **86** moves the follower **94** to reciprocate the mandrel **50** along the mandrel axis **54**. The cam **86**, follower **94**, spring **102**, and mandrel **50** are supported within a frame **104**, which may be similar to the frame **627** described and illustrated in U.S. Patent Application Publication No. 2020/0261959, filed as application Ser. No. 16/795,742 on Feb. 20, 2020, in the name of Milwaukee Electric Tool Corporation, the entire content of which is incorporated herein by reference.

(30) The mandrel **50** includes a conical outer surface **106** engageable with a head or working element **110** of the expansion tool **10** (FIG. 1). In the illustrated embodiment, the working element **110** includes a plurality of jaws **114**. The conical outer surface **106** of the mandrel **50** (FIG. 2) is engageable with interior sides of the jaws **114** as the mandrel **50** moves from a retracted position to an extended position along the mandrel axis **54**. This expands the jaws **114** radially outward from a closed position (illustrated in FIG. 1) to an expanded position. The jaws **114** may be biased toward the closed position (e.g., by an O-ring or toroidal spring surrounding the jaws **114**, by tension springs interconnecting adjacent jaws **114**, or by any other suitable arrangement), such that the jaws **114** return to the closed position when the mandrel **50** retracts along the mandrel axis **54**.

(31) Referring to FIG. 1, each of the jaws **114** has an exterior side with a tapered portion **118** and a sizing portion **122**. When the working element **110** is in the closed position, adjacent jaws **114** abut one another such that the tapered portions **118** define a generally frustoconical shape. The sizing portions **122** collectively define a constant diameter or maximum cross-sectional dimension when the jaws **114** are in the closed position, with the diameter being sized for proper expansion of PEX tubing of a desired nominal size. In other embodiments, the jaws **114** may be formed with other linear and/or non-linear profiles along the length of each jaw **114**. In some embodiments, the working element **110** may be removably coupled to the expansion tool **10** such that the jaws **114** may be interchanged with jaws having other sizes/geometries. For example, the working element **110** may be part of an expansion tool system including a plurality of interchangeable working elements, such as the expansion tool system **905** described and illustrated in U.S. Patent Application Publication No. 2020/0261959, which, as discussed above, is incorporated by reference.

(32) The expansion tool **10** may include an automatic jaw rotation mechanism **200**, such as the automatic jaw rotation mechanism **200** described and illustrated in U.S. patent application Ser. No. 17/187,265, filed Feb. 26, 2021, in the name of Milwaukee Electric Tool Corporation, the entire content of which is incorporated herein by reference. The automatic jaw rotation mechanism **200** is configured to automatically rotate the jaws **114** of the working element **110** about the mandrel axis **54** during operation of the expansion tool **10**.

(33) Referring to FIG. 5, in the illustrated embodiment, the automatic jaw rotation mechanism **200** includes a rotation collar **220** rotatably supported by the frame **104** adjacent a connection end **2000** of the frame **104**. The connection end **2000** includes a set of external threads **2002**. The rotation collar **220** includes a central bore **2004** which allows the mandrel **50** to pass through the rotation collar **220** and engage the jaws **114**. The rotation collar **220** includes an end face **2006** having a plurality of slots **2008** extending from the end face **2006** in an axial direction (i.e. a rearward direction). A plurality of teeth **2010** extends forwardly from the end face **2006**. The teeth **2010** are arranged such that each tooth **2010** is disposed between an adjacent pair of slots **2008**. The illustrated teeth **2010** are formed as truncated pyramids. In other embodiments, the teeth **2010** may be formed in other suitable shapes.

(34) With reference to FIGS. 6A and 7, the working element **110** is removably coupled to the frame

104 by a retaining sleeve 2012. The retaining sleeve 2012 includes an internal groove 2013 and a set of internal threads 2014. Each of the jaws 114 includes a flange 2015 that is received within the internal groove 2013 of the retaining sleeve 2012. The jaws 114 are rotatable relative to the retaining sleeve 2012, as the flanges 2015 are slidable within the internal groove 2013. The internal threads 2014 of the retaining sleeve 2012 cooperate with the external threads 2002 of the connection end 2000 to removably couple the retaining sleeve 2012 to the frame 104

(35) Referring to FIG. 6A, each of the jaws 114 of the working element 110 includes a base surface 2016, which faces rearward when the working element 110 is coupled to the expansion tool 10. The base surface 2016 includes a projection or tab 2018 and two grooves 2022 located on either side of the tab 2018, along the edges of the base surface 2016. When the tabs 2018 are tapered outward in the rearward direction to match the profile of the conical outer surface 106 mandrel 50.

(36) As illustrated in FIGS. 8 and 9, when attaching the working element 110 to the expansion tool 10, an operator positions the retaining sleeve 2012 adjacent the connection end 2000 of the frame. In order to couple the jaws 114 to the rotation collar 220, the tabs 2018 of the jaws 114 must align with the slots 2008 formed in the end face 2006 of the rotation collar 220. As shown in FIG. 8, the jaws 114 can then be rotated relative to the retaining sleeve 2012 and the frame 104 until the tabs 2018 are aligned with the slots 2008, at which point the retaining sleeve 2012 can be rotated relative to the frame 104 to begin threading the retaining sleeve 2012 on to the external threads 2002 of the connection end 2000.

(37) Continued rotation of the retaining sleeve 2012 in a tightening direction causes the tabs 2018 to travel further into the slots 2008, thereby rotatably coupling the rotation collar 220 and the jaws 114. Once the retaining sleeve 2012 is fully installed on the connection end 2000, the teeth 2010 (FIG. 5) engage the grooves 2022 (FIG. 6A) to provide an additional torque-transmitting connection between the rotation collar 220 and the jaws 114.

(38) In operation, the jaws 114 (FIG. 1) of the expansion tool 10 are inserted into an end of a segment of PEX tubing to be expanded such that the tapered portions 118 abut an interior wall of the PEX tubing. The operator depresses the actuator 26, which energizes the motor 30.

(39) Once energized, the motor 30 rotates the cam 86 via the drive mechanism 34 to perform cycles of axially extending and retracting the mandrel 50 along the mandrel axis 54 (FIG. 2), thereby expanding and contracting the jaws 114. As the jaws 114 expand, the tapered portions 118 engage with the interior wall of the PEX tubing to gradually expand the PEX tubing. The expansion tool 10 continues the cycles of axially extending and retracting the mandrel 50. The operator pushes the jaws 114 deeper into the PEX tubing with each successive expansion until the sizing portions 122 of the jaws 114 are fully inserted into the PEX tubing. This indicates to the operator that expansion is complete. The jaws 114 are withdrawn from the PEX tubing, and the operator inserts a fitting into the end of the PEX tubing. The interior of the PEX tubing then elastically recovers and secures the fitting in place.

(40) The automatic rotation mechanism 200 operates to incrementally rotate the jaws 114 during each cycle of axially extending and retracting the mandrel 50. The automatic rotation mechanism 200 incrementally rotates the rotation collar 220. As the rotation collar 220 rotates, the slots 2008 engage the tabs 2018 and transfer the rotation to the jaws 114. The engagement between the tabs 2018 and the slots 2008 ensure that rotation is transferred without any slippage. Additionally, the teeth 2010 engage the grooves 2022 to provide an additional torque-transmitting connection between the rotation collar 220 and the jaws 114. The retaining sleeve 2012 remains stationary and retains the jaws 114 adjacent the connection end 2000 of the frame 104.

(41) The jaws 114 are preferably incrementally rotated during each retraction cycle by an angular displacement that is less than the angular spacing of the jaws 114. For example, when the working element 110 includes six jaws, the jaws are spaced by sixty degrees, and the automatic rotation mechanism 200 is operable to rotate the jaws 114 by an angular displacement less than sixty degrees during each retraction cycle. In some embodiments, the jaws 114 are rotated by an angular

displacement less than 45 degrees, and in some embodiments, the jaws **114** are rotated by an angular displacement less than 20 degrees.

(42) By rotating the jaws **114** by an angular displacement that is less than the angular spacing of the jaws **114**, the jaws **114** smooth out any indentations that may be formed on the interior wall of the PEX tubing during expansion. This promotes a quality seal with the subsequently inserted fitting. Furthermore, by rotating the jaws **114** while the jaws **114** are retracting, friction between the jaws **114** and the PEX tubing is reduced. In addition, rotating the jaws **114** simultaneously while the jaws **114** are retracting advantageously reduces the cycle time of the expansion tool **10**.

(43) FIG. **6B** illustrates a conventional working element **110a**, which may alternatively be coupled to the expansion tool **10**. The working element **110a** does not include the tabs **2018** and instead only includes the grooves **2020a** formed on the base surfaces **2016a** of the jaws **114a**. Because the rotation collar **220** includes the teeth **2010**, the teeth **2010** are received within the grooves **2020a** when the working element **110a** is coupled to the frame **104** to couple the jaws **114a** for co-rotation with the rotation collar **220**. Thus, the rotation collar **220** of the expansion tool **10** is advantageously backwards-compatible with conventional working elements, such as the working element **110a**.

(44) FIGS. **10A** and **11A** illustrate additional embodiments of working elements **110b** and **110c** which may be coupled to the expansion tool **10** (e.g., by the retaining sleeve **2012**). In each case, the interior sides of jaws **114** define an interior cavity **126** in which an inner cone **130a** (FIG. **10A**), **130b** (FIG. **10B**) is disposed. The inner cone **130a**, **130b** defines an outer conical surface **134** that abuts and engages the interior sides of the jaws **114** and an inner bore **138** that extends at least partially along the length of the inner cone **130** along a conical axis **142**.

(45) The inner cone **130a**, **130b** is engageable with the mandrel **50** and slidable along the mandrel axis **54** therewith. More specifically, the mandrel **50** engages the inner cone **130a**, **130b** with the mandrel **50** at least partially disposed in the inner bore **138** of the inner cone **130a**, **130b**. As the mandrel **50** engages the inner cone **130a**, **130b** and proceeds in a linear direction along the mandrel axis **54**, the inner cone **130a**, **130b** engages the interior sides of jaws **114** thereby transitioning the jaws from the closed position (e.g., shown in FIG. **9**) to the expanded position (as shown in FIGS. **10A** and **11A**).

(46) As shown in FIGS. **10B** and **11B**, the inner cone **130a**, **130b** may include features for distributing and/or retaining lubricant (such as grease, oil, or other appropriate material for reducing friction between surfaces moving relative to one another) at the interface of the outer conical surface **134** of the inner cone **130a**, **130b** and the interior sides of jaws **114**.

(47) For example, as shown in FIG. **10B**, the inner cone **130a** includes a plurality of bores **146** extending from the outer conical surface **134** to the inner bore **138** and fluidly communicating with the inner bore **138**, such that lubricant is allowed to move through the inner bore **138** at the engagement with the mandrel **50** to the outer conical surface **134** via bores **146**. Lubricant is thereby applied at the interface of the outer conical surface **134** and the interior sides of jaws **114**.

(48) In another example, as shown in FIG. **11B**, the inner cone **130b** includes a plurality of grooves **150** disposed on the outer conical surface **134** spaced along the conical axis **142** and extending circumferentially about the outer conical surface **134** and radially inward toward the inner bore **138**. Lubricant may be disposed in the grooves **150** whereby the interface of the outer conical surface **134** and the interior sides of jaws **114** is maintained in a lubricated state.

(49) Various features and aspects of the present invention are set forth in the following claims.

## Claims

1. An expansion tool, comprising: a housing; a collar rotatably coupled to the housing, the collar including a plurality of slots; a plurality of jaws, each jaw having a projection received in a corresponding one of the plurality of slots such that the jaws are coupled for co-rotation with the

collar; a mandrel moveable relative to the housing between a retracted position and an extended position, the mandrel engageable with the jaws to expand the jaws in response to movement of the mandrel to the extended position; a cone received within the plurality of jaws and engageable with inner surfaces of the plurality of jaws, wherein the mandrel is configured to engage the cone to move the cone with the mandrel to expand the jaws as the mandrel moves toward the extended position; and a rotation mechanism configured to incrementally rotate the collar.

2. The expansion tool of claim 1, wherein the collar includes a front surface facing the jaws, and wherein the slots extend in a rearward direction from the front surface.

3. The expansion tool of claim 2, wherein the collar includes a plurality of teeth extending in a forward direction from the front surface.

4. The expansion tool of claim 3, wherein the plurality of jaws is removably coupled to the housing.

5. The expansion tool of claim 4, wherein the housing at least partially encloses a frame having a connection end, wherein the expansion tool further comprises a retaining sleeve surrounding the plurality of jaws, and wherein the plurality of jaws is configured to be coupled to the housing by coupling the retaining sleeve to the connection end of the frame.

6. The expansion tool of claim 4, wherein the plurality of jaws is a first plurality of jaws, and the first plurality of jaws is interchangeable with a second plurality of jaws.

7. The expansion tool of claim 6, wherein each jaw of the second plurality of jaws includes a recess formed in a rear surface of the jaw, and each recess is configured to receive a corresponding one of the plurality of teeth to couple the second plurality of jaws for co-rotation with the collar.

8. The expansion tool of claim 1, further comprising a drive mechanism including a motor and a rotatable cam, wherein rotation of the cam moves the mandrel between the retracted position and the extended position.

9. The expansion tool of claim 8, wherein the drive mechanism is operable in a high speed configuration and a low speed configuration, and wherein the expansion tool further comprises: a shifting assembly including an actuator operable to shift the drive mechanism between the high speed configuration and the low speed configuration; and a shifting detector configured to detect a shift between the high speed configuration and the low speed configuration.

10. The expansion tool of claim 1, wherein the cone includes a plurality of grooves containing grease to lubricate the inner surfaces of the plurality of jaws.

11. The expansion tool of claim 1, wherein the cone includes a plurality of bores extending from an outer conical surface to an inner bore, the plurality of bores defining fluid pathways to convey lubricant between the inner bore and an outer surface of the cone.

12. An expansion tool comprising: a housing; a motor supported in the housing; a plurality of jaws; a mandrel moveable relative to the housing between a retracted position and an extended position, the mandrel engageable with the jaws to expand the jaws in response to movement of the mandrel to the extended position; a drive mechanism configured to convert rotational input from the motor into translational movement of the mandrel between the retracted position and the extended position, the drive mechanism including a rotatable cam, wherein rotation of the cam moves the mandrel between the retracted position and the extended position, and wherein the drive mechanism is operable in a high speed configuration and a low speed configuration; a shifting assembly including an actuator operable to shift the drive mechanism between the high speed configuration and the low speed configuration; and a shifting detector configured to detect a shift between the high speed configuration and the low speed configuration.

13. The expansion tool of claim 12, wherein the shifting detector includes a micro switch.

14. The expansion tool of claim 13, wherein the shifting assembly includes a shifting arm engageable with the micro switch.

15. The expansion tool of claim 12, wherein the motor rotates the rotatable cam via the drive mechanism and a controller in communication with the shifting detector, wherein the controller is

configured to deenergize the motor in response to the shifting detector detecting the shift.

16. The expansion tool of claim 15, further comprising an indicator, wherein the controller is configured to illuminate the indicator in response to the shifting detector detecting the shift.

17. The expansion tool of claim 12, wherein the drive mechanism includes a multi-stage planetary transmission, wherein the multi-stage planetary transmission includes a movable ring gear and a locking ring, wherein the movable ring gear is engaged with the locking ring in the low speed configuration, and wherein the movable ring gear is disengaged from the locking ring in the high speed configuration.

18. An expansion tool, comprising: a housing; a collar rotatably coupled to the housing; a plurality of jaws coupled for co-rotation with the collar; a mandrel moveable relative to the housing between a retracted position and an extended position, the mandrel engageable with the jaws to expand the jaws in response to movement of the mandrel to the extended position; and a cone received within the plurality of jaws and engageable with inner surfaces of the plurality of jaws, wherein the mandrel is configured to engage the cone to move the cone with the mandrel to expand the jaws as the mandrel moves toward the extended position, and wherein the cone includes means for containing grease to lubricate the inner surfaces of the plurality of jaws.

---